



US011178741B1

(12) **United States Patent**  
**Jacobs et al.**

(10) **Patent No.:** **US 11,178,741 B1**  
(45) **Date of Patent:** **Nov. 16, 2021**

(54) **LIGHTING SYSTEM CONFIGURED TO  
EMIT VISIBLE AND INFRARED LIGHT**

(71) Applicant: **Hughey & Phillips, LLC**, Urbana, OH  
(US)

(72) Inventors: **Jeffrey A Jacobs**, Galloway, OH (US);  
**Steven M. Schneider**, Urbana, OH  
(US); **Brian J. Hockensmith**,  
Columbus, OH (US)

(73) Assignee: **Hughey & Phillips, LLC**, Urbana, OH  
(US)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 550 days.

(21) Appl. No.: **15/386,587**

(22) Filed: **Dec. 21, 2016**

**Related U.S. Application Data**

(60) Provisional application No. 62/270,836, filed on Dec.  
22, 2015.

(51) **Int. Cl.**  
**H05B 45/37** (2020.01)  
**H05B 45/50** (2020.01)  
**F21V 3/02** (2006.01)  
**F21Y 115/10** (2016.01)  
**F21Y 113/00** (2016.01)  
**F21V 7/00** (2006.01)  
**G08G 5/04** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **H05B 45/50** (2020.01); **H05B 45/37**  
(2020.01); **F21V 3/02** (2013.01); **F21V 7/00**  
(2013.01); **F21Y 2113/00** (2013.01); **F21Y**  
**2115/10** (2016.08); **G08G 5/04** (2013.01)

(58) **Field of Classification Search**  
CPC combination set(s) only.  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,610,912 A 10/1971 Schwartz  
4,498,004 A 2/1985 Adolfsson et al.  
4,609,306 A 9/1986 Loire  
5,155,666 A 10/1992 Radford et al.

(Continued)

FOREIGN PATENT DOCUMENTS

CN 201636748 U 11/2010  
EP 1231109 A1 8/2002

(Continued)

OTHER PUBLICATIONS

“LP-8862-Q1 Low-EMI Automotive LED Driver With Two 160-  
mA Channels,” product data sheet, Aug. 2016, 10 pages, published  
by Texas Instruments, Dallas, Texas.

(Continued)

*Primary Examiner* — Amy Cohen Johnson


*Assistant Examiner* — Jianzi Chen

(74) *Attorney, Agent, or Firm* — Kegler Brown Hill +  
Ritter LPA Co.; Lorraine Hernandez

(57) **ABSTRACT**

A lighting system includes a first light emitter configured to  
emit light outside a visible-light spectrum. A second light  
emitter is configured to emit light in a visible-light spectrum.  
The first and second light emitters are co-located, such as in  
a stacked arrangement with one light emitted atop the other.  
The amount of visible illumination of the second light  
emitter may correspond to a correlated radiant intensity of  
infrared light emitted by the first light emitter.

**20 Claims, 3 Drawing Sheets**



(56)

References Cited

U.S. PATENT DOCUMENTS

5,608,290 A 3/1997 Hutchisson et al.  
 5,642,933 A 7/1997 Hitora  
 5,838,247 A 11/1998 Bladowski  
 5,929,788 A 7/1999 Vukosic  
 6,022,124 A 2/2000 Bourn et al.  
 6,070,994 A 6/2000 Sebek et al.  
 6,183,100 B1 2/2001 Suckow et al.  
 6,364,506 B1 4/2002 Gallo  
 6,379,026 B1 4/2002 Petrick  
 6,425,678 B1 7/2002 Verdes et al.  
 6,464,373 B1 10/2002 Petrick  
 6,525,668 B1 2/2003 Petrick  
 6,561,689 B1 5/2003 Kidd et al.  
 6,601,970 B2 8/2003 Ueda et al.  
 6,637,921 B2 10/2003 Coushaine  
 6,679,618 B1 1/2004 Suckow et al.  
 6,705,745 B1 3/2004 Pederson  
 6,793,372 B2 9/2004 Wehner et al.  
 6,932,496 B2 8/2005 Rizkin et al.  
 6,948,830 B1 9/2005 Petrick  
 6,962,423 B2 11/2005 Hamilton et al.  
 6,991,351 B1 1/2006 Petrick  
 7,040,782 B2 5/2006 Mayer  
 7,079,041 B2 7/2006 Fredericks et al.  
 7,160,004 B2 1/2007 Peck  
 7,163,322 B2 1/2007 Tatewaki et al.  
 7,236,105 B2 6/2007 Brenner et al.  
 7,237,929 B2 7/2007 Stahl  
 7,378,983 B2\* 5/2008 Wang ..... H05B 45/22  
 340/815.45  
 7,497,593 B2 3/2009 Wang  
 7,568,821 B2 8/2009 Peck et al.  
 7,578,600 B2 8/2009 Czajkowski  
 7,604,384 B2 10/2009 Peck  
 7,658,513 B2 2/2010 Peck  
 7,758,210 B2 7/2010 Peck  
 7,791,497 B2 9/2010 Clerk  
 7,832,908 B2 11/2010 Peck et al.  
 8,033,683 B2 10/2011 Fields  
 8,096,677 B2 1/2012 Fields et al.  
 8,525,425 B1 9/2013 Roudeski  
 9,010,969 B2 4/2015 Roudeski et al.  
 9,013,331 B2 4/2015 Wise  
 9,016,896 B1 4/2015 Roudeski  
 9,206,961 B1 12/2015 Bastiani et al.  
 9,297,514 B2 3/2016 Roudeski  
 9,423,086 B2 8/2016 Peck  
 9,572,223 B1 2/2017 Mula et al.  
 9,694,914 B2 7/2017 Wise  
 9,702,525 B1 7/2017 Roudeski  
 10,106,276 B2 10/2018 Ricca et al.  
 10,124,910 B2 11/2018 Wise  
 2001/0015899 A1 8/2001 Kondo et al.  
 2004/0004836 A1 1/2004 Dubuc  
 2004/0057234 A1 3/2004 Mohacsi  
 2004/0057244 A1 3/2004 Amano  
 2004/0145910 A1 7/2004 Lisowski  
 2004/0196646 A1 10/2004 Machi et al.  
 2005/0094393 A1 5/2005 Czajkowski  
 2005/0157490 A1 7/2005 Klose  
 2006/0007012 A1 1/2006 Machi et al.  
 2006/0012990 A1 1/2006 Walser et al.  
 2006/0083017 A1 4/2006 Wang  
 2006/0291209 A1 12/2006 Booth et al.  
 2008/0192480 A1 8/2008 Rizkin et al.  
 2009/0207605 A1 8/2009 Fields  
 2009/0219715 A1 9/2009 Peck et al.  
 2010/0027281 A1 2/2010 Waters et al.

2010/0049454 A1\* 2/2010 Irissou ..... H05B 45/58  
 702/58  
 2010/0084979 A1 4/2010 Burton et al.  
 2010/0194603 A1 8/2010 Wobben  
 2010/0244748 A1 9/2010 Haab et al.  
 2010/0259929 A1 10/2010 Henri et al.  
 2011/0018439 A1 1/2011 Fabbri et al.  
 2011/0051421 A1 3/2011 Chew  
 2011/0058370 A1 3/2011 Datz et al.  
 2011/0090681 A1 4/2011 Hobson  
 2011/0121734 A1 5/2011 Pape  
 2011/0194283 A1 8/2011 Roer  
 2011/0235322 A1 9/2011 Fields et al.  
 2011/0241926 A1 10/2011 Laufer  
 2011/0301567 A1\* 12/2011 Boulanger ..... A61M 5/14232  
 604/500  
 2011/0305014 A1 12/2011 Peck  
 2012/0300449 A1 11/2012 Fields  
 2014/0036168 A1\* 2/2014 Ludwig ..... H01L 27/323  
 349/12  
 2014/0062302 A1 3/2014 Tischler et al.  
 2015/0036222 A1\* 2/2015 Mihara ..... G02B 27/14  
 359/630  
 2016/0201888 A1\* 7/2016 Ackley ..... G03B 21/14  
 362/276  
 2016/0304215 A1 10/2016 Ricca et al.  
 2019/0055034 A1 2/2019 Ricca et al.  
 2019/0168890 A1 6/2019 Wise


FOREIGN PATENT DOCUMENTS

EP 1698823 A2 9/2006  
 EP 1698823 B1 4/2010  
 EP 2199206 A1 6/2010  
 EP 2648174 A3 10/2013  
 JP 2001243821 A 9/2001  
 WO 2009084049 A1 7/2009  
 WO 2009090185 A2 7/2009  
 WO 2009133326 A2 11/2009

OTHER PUBLICATIONS


Dialight, PLC, Brochure, "Vigilent(R) LED Based Obstruction Lights," PDF Creation Date Feb. 29, 2016, 12 pages, Document No. Obstruction\_Brochure\_M, retrieved from company website www.dialight.com May 10, 2016.  
 SPX Corporation, Brochure, "FTS 361X-5 Medium Intensity Red LED Aviation Obstruction Lighting System," PDF Creation Date Feb. 11, 2016, 2 pages, Document No. FTS361X-120115, retrieved from company website www.spx.com May 10, 2016.  
 Flash Technology, Reference Manual, "Vanguard(R) FTS 370d, 370w, 370r LED Medium Intensity Obstruction Lighting System," Revision 18, Sep. 21, 2017, 104 pages, Part No. F7913702, retrieved from company website www.flashtechology.com Dec. 7, 2017.  
 Data Sheet, Orga Model AOL 1000SA High Intensity Aeronautical Obstruction Light, 1 page, created 2007.  
 Promotional Sheet, Excelitas Technologies "Lighting Solutions for Safety and Security". 4 pages. Copyright 2011.  
 European Search Report, Application EP12160211, dated Aug. 7, 2013.  
 Dialight Corp., Product datasheet for D164 Series LED Red Beacon, 1 page, printed Jan. 21, 2011, Newmarket, England.  
 Installation and Operation Guide, "Horizon(TM) Medium Intensity Dual LED Lighting System," Manual No. EPM-00000043-001, Revision E, copyright 2014, 17 pages, Hughey & Phillips, LLC, Urbana Ohio, retrieved from company website www.hugheyandphillips.com Apr. 23, 2018.

\* cited by examiner




***Fig. 1***





**Fig. 2**



**Fig. 3**



**1****LIGHTING SYSTEM CONFIGURED TO  
EMIT VISIBLE AND INFRARED LIGHT****CROSS-REFERENCE TO RELATED  
APPLICATIONS**

This application claims priority to U.S. provisional patent application No. 62/270,836, filed Dec. 22, 2015, the entire contents of which is expressly incorporated by reference herein.

**FIELD**

The present invention relates generally to lighting systems, such as obstruction lighting systems.

**BACKGROUND**

Obstructions to aircraft navigation, such as towers, cables and tall buildings are typically fitted with visibly perceivable elements to render these structures highly visible to approaching aircraft. These obstruction lights are placed in accordance with a set plan at levels on all obstructions that are potential hazards to air navigation. Standards for obstruction lighting have been established by the U.S. Federal Aviation Administration (FAA), International Civil Aviation Organization (ICAO), and Australia Civil Aviation Safety Authority (CASA) among others.

While visible-light obstruction lighting performance standards are well established, there are no standards for compatibility of obstruction lights with night vision imaging systems (“NVIS”) commonly used by military and emergency/rescue air operators. NVIS systems are typically configured to receive and amplify low-level infrared radiation to form a “night vision” image, which improves air operators’ ability to navigate at night and under poor visibility conditions. The lack of performance standards for compatibility with NVIS equipment is particularly problematic for obstruction lights that utilize light emitting diodes (LEDs), since LEDs generate considerably less heat (and thus less infrared radiation) than conventional incandescent and xenon strobe light sources, making them difficult to see with NVIS. Providers of obstruction lighting systems have attempted to solve this problem by co-mingling some infrared light emitting diodes or other infrared emitters (hereafter generally “IRLEDs”) with their visible-light emitters. However, since the optical systems of these obstruction lighting systems are designed to emit visible light, the lighting pattern, intensity and other characteristics of the infrared light emitted by the co-mingled IRLEDs are often compromised. There remains a need for an obstruction lighting system that provides satisfactory light emissions for both visible light and infrared light.

**SUMMARY**

A lighting system configured to emit both visible and infrared light is disclosed according to an embodiment of the present invention. The system comprises a first light emitter that is configured to emit light outside a visible-light spectrum. A second light emitter is configured to emit visible light. The lighting characteristics of the second light emitter are altered when a fault condition is present in the first light emitter, thereby providing a visually perceivable indication of the fault.

In one embodiment a lighting system includes a first light emitter configured to emit light outside a visible-light spec-

**2**

trum. A second light emitter is configured to emit light in a visible-light spectrum. The first and second light emitters are co-located, such as in a stacked arrangement with one light emitted atop the other. The amount of visible illumination of the second light emitter may correspond to a correlated radiant intensity of infrared light emitted by the first light emitter.

In another embodiment of the present lighting system a first light emitter is configured to emit light in an infrared light spectrum. A second light emitter is arranged to emit light in a visible-light spectrum. A controller is configured to control the operation of the first and second light emitters. A monitor is arranged to detect a fault condition of the first light emitter and communicate the fault condition to the controller. The controller alters lighting characteristics of the second light emitter by turning off the second light emitter while the fault condition of the first light emitter is present. The light emissions of the first and second light emitters may be correlated. In addition, the first and second light emitters may be co-located such that the second light emitter is atop the first light emitter in a stacked arrangement. The first and second light emitters preferably have separate optical systems.

**BRIEF DESCRIPTION OF THE DRAWINGS**

Further features of the inventive embodiments will become apparent to those skilled in the art to which the embodiments relate from reading the specification and claims with reference to the accompanying drawings, in which:

FIG. 1 is a block diagram showing the general arrangement of a lighting system configured to emit both visible and infrared light according to an embodiment of the present invention;

FIG. 2 shows an example lighting system according to an embodiment of the present invention; and

FIG. 3 shows an example lighting system according to another embodiment of the present invention.

**DETAILED DESCRIPTION**

The general arrangement of a lighting system **10** configured to emit both visible and infrared light is shown in FIG. **1** according to an embodiment of the present invention. System **10** comprises a first light emitter **12** that is configured to emit light outside a visible-light spectrum such as, without limitation, in the infrared light spectrum. A second light emitter **14** is configured to emit light in a visible-light spectrum that is perceivable to the unaided eye.

A controller **16** controls the operation of first and second light emitters **12**, **14** respectively. Controller **16** may, for example, establish and control the amount of voltage and/or current that is supplied to first and second light emitters **12**, **14** respectively. Controller **16** may also control the on-and-off operation of first and second light emitters **12**, **14** such as, for example, turning either or both of the light emitters ON at a first desired time or at dusk, and turning either or both of the light emitters OFF at a second desired time or at dawn. Controller **16** may optionally utilize a local or remote photocell or a global positioning satellite (GPS) receiver to determine when the light emitters **12**, **14** are to be turned on and turned off. Controller **16** may further “flash” either or both of light emitters **12**, **14** with a desired ON-OFF duty cycle or pattern, or turn either or both light emitters ON or OFF in a predetermined manner or in response to predetermined conditions.



Monitor **18** is coupled to and monitors the status of either or both of first and second light emitters **12**, **14** respectively. Status information may include, without limitation, the amount of voltage and/or current present in first and second light emitters **12**, **14** respectively, or elements thereof (such as, for example, one or more individual visible or infrared light emitting diodes), whether the light emitters or any elements thereof have failed with an electrical open-circuit fault condition, whether the light emitters or any elements thereof have failed with an electrical short-circuit fault condition, the amount of light being emitted by the light emitters or elements thereof, and the wavelength of light being emitted by the light emitters or elements thereof. As a non-limiting example, measurement of the voltage across a light emitting diode will provide an indication of whether the light emitting diode is functioning or whether it has experienced an electrical open- or short-circuit voltage fault condition. Likewise, measurement of the current through a light emitting diode will provide an indication of whether the light emitting diode is functioning, or whether it has experienced an open- or short-circuit electrical current fault condition.

If monitor **18** detects a predetermined fault condition in either or both of first and second light emitters **12**, **14** (or the elements that comprise them) a fault signal is provided to controller **16** by the monitor. Controller **16** receives the fault signal from monitor **18** and activates a local and/or remote alarm **20** which may be, without limitation, an electronic, aural, visually perceivable, non-visually perceivable (e.g., infrared, ultraviolet) or tactile alarm signal.

In an embodiment of the present invention first and second light emitters **12**, **14** respectively are steady-burning and are co-located as generally shown in FIG. **2**. Monitor **18** monitors the status of first light emitter **12** configured as an infrared light emitter and, upon detection of a predetermined fault condition, provides a fault signal to controller **16**. Controller **16** responds to the fault signal and provides a local alarm signal by “flashing” second light emitter **14**, which is configured as a visible-light emitter, at a predetermined duty cycle until the fault is corrected. Second light emitter **14** may thus be operated to provide a local alarm signal with an ON-OFF duty cycle whereby the second light emitter is turned OFF for about one second and then turned ON for about fourteen seconds.

Alternatively, second light emitter **14** may be turned OFF by controller **16** and be kept in an OFF state to visually indicate a fault in first light emitter **12** until the fault is corrected, then be restored to its normal ON state while the first light emitter is again operational. This provides maintenance personnel with an indication that is visually perceivable to the unaided eye that first light emitter **12**, which cannot be observed without the use of special NVIS equipment, has a fault condition.

First and second light emitters **12**, **14** respectively may be configured such that the light emitted by the first and second light emitters has a predetermined corresponding relationship. In one embodiment the amount of visible illumination in foot-candles of second light emitter **14** corresponds to a correlated radiant intensity of infrared light emitted by first light emitter **12** in watts per steradian. This correlation between first and second light emitters **12**, **14** respectively may result in a lighting system **10** that emits both visible and infrared light with a generally equivalent perceived intensity when second light emitter **14** is viewed with the unaided eye and when first light emitter **12** is viewed with NVIS equipment. In this arrangement lighting system **10** appears to an observer to be the same general distance away from the

observer both when the lighting system is viewed by the observer with the unaided eye and when the lighting system is viewed by the observer with NVIS equipment. Prior lighting systems lack this correlation between the visible and infrared light emitters, resulting in a perceived appearance of the light being closer or farther away from the observer, depending upon whether the prior lighting system is viewed by the observer with the unaided eye or if the lighting system viewed by the observer with NVIS equipment. This lack of correlation between the visible and infrared light emitted by prior lighting systems results in a greater hazard to air navigation when the lighting system is an obstruction light, since the obstruction light will appear to be closer or farther from an observer in a nearby aircraft, depending upon whether the observer is using NVIS equipment or the unaided eye. The present invention overcomes this short-coming.

Details of a non-limiting example lighting system **10** are shown in FIG. **2**. First light emitter **12** is configured to emit light outside a visible-light spectrum such as, without limitation, infrared light. For example, the infrared light may be in the 850 nanometer (nm) region of the infrared spectrum. The infrared light may be generated by one or more IRLEDs **22**. IRLEDs **22** are arranged and oriented such that infrared light emitted by the IRLEDs is directed generally outwardly and away from lighting system **10**. In some embodiments a plurality of IRLEDs **22** may be arranged such that lighting system **10** emits infrared light outwardly about a 360 degree radius (or a portion thereof) of lighting system **10**. In some embodiments IRLEDs **22** may be infrared emitters (e.g., infrared light emitting diodes) or any other suitable source of infrared emissions.

Second light emitter **14** is configured to emit light in a visible-light spectrum. The visible light may be generated by one or more visible-light light emitting diodes (LEDs) **24** and reflected outwardly by a reflector **26**. In some embodiments a plurality of visible-light LEDs **24** may be arranged about reflector **26** such that lighting system **10** emits visible light outwardly about a 360 degree radius (or a portion thereof) of lighting system **10**.

As further shown in FIG. **2**, first and second light emitters **12**, **14** respectively are co-located in a stacked arrangement. Second light emitter **14** is stacked atop first light emitter **12** in this embodiment, although a reverse arrangement with the first light emitter stacked atop the second light emitter is envisioned within the scope of the invention. Similarly, first and second light emitters **12**, **14** may be laterally co-located in a generally side-by-side arrangement.

In the example embodiment shown in FIG. **2**, IRLEDs **22** are arranged and oriented such that light generated by the IRLEDs is directed outwardly and away from lighting system **10**. However, this arrangement is merely shown as one example optical arrangement and is not intended to be limiting in any way. For example, IRLEDs **22** may be arranged with a reflector similar to reflector **26** of second light emitter **14**. Likewise, visible-light LEDs **24** may be arranged and oriented in a manner similar to first light emitter **12** such that reflector **26** is omitted and light generated by visible-light LEDs is directed generally outwardly and away from lighting system **10**.

Lighting system **10** may further include a housing **28**. Housing **28** can be configured with features that are sized and shaped to mount or attach lighting system **10** to structures and other equipment. Housing **28** may further enclose some portions or the entirety of controller **16**, monitor **18** and alarm **20**.



## 5

A cover globe **30** may enclose first and second light emitters **12**, **14** respectively. Globe **30** may be generally transparent (i.e., “clear”) or may be tinted or dyed to one or more desired colors, such as red.

With reference now to FIG. **3**, in some embodiments of the present invention a plurality of lighting systems **10** may be utilized, and may be mounted to a common fixture **32** if desired. In addition, any suitable portions of lighting system **10** may be made common to plural lighting systems. For example, portions or all of controller **16**, monitor **18** and alarm **20** may be made a common assembly **34** for plural lighting systems **10**, and may be disposed within fixture **32**, distributed among the plural lighting systems, or located remotely.

First light emitter **12** may utilize any type of emitter now known or later invented to emit light outside a visible-light spectrum. The IRLEDs **22** described herein are for illustration only and are not intended to be limiting in any way. Likewise, second light emitter **14** may utilize any type of visible-light emitter now known or later invented. The visible light emitting diodes **24** described herein are for illustration only and are not intended to be limiting in any way.

Optical systems that do not include a reflector **26** are envisioned within the scope of the invention. For example, either or both of light emitting diodes **22**, **24** may be directed or aimed outwardly from lighting system **10**, and may optionally include optical elements such as, but not limited to, baffles and lenses to shape and direct the light emitted from the light emitting diodes.

Referring again to FIG. **2**, preferably first light emitter **12** and second light emitter **14** utilize separate optical systems comprising optical elements such as, without limitation, light emitter aiming, reflectors, baffles, and lenses, each optical system being tailored to the spectrum of light emitted. The use of a first optical system tailored to first light emitter **12** and a separate, second optical system tailored to the second light emitter **14** allows for optimization of the efficiency (e.g., light intensity, distribution and pattern) of the particular spectrum of light emitted. This provides a lighting system **10** with an optimized first light emitter **12** and an optimized second light emitter **14** that work together to provide predetermined lighting characteristics without compromising the optical characteristics of either of light emitters **12**, **14**. This separate optical arrangement overcomes the drawbacks of prior lighting systems utilizing a common optical system for both visible and infrared emitters, which would necessarily compromise the efficiency of the visible light emitter, the infrared light emitter, or even both light emitters. An optimized optical system for each of first light emitter **12** and second light emitter **14** may comprise one or more light emitters oriented generally away from lighting system **10**, a reflector or reflectors, baffles, lenses, light tubes, or any combination thereof along with any other light-shaping and modifying elements now known or later conceived.

Controller **16**, monitor **18** and alarm **20** may be separate elements comprising any suitable combinations of discrete electronic components and integrated circuits. Alternatively, some portions or all of controller **16**, monitor **18** and alarm **20** may be integrated together. Furthermore, the functions of some or all of controller **16**, monitor **18** and alarm **20** may be managed by a device capable of storing and executing predetermined instructions such as, without limitation, a computer, a microprocessor or a microcontroller.

While this invention has been shown and described with respect to a detailed embodiment thereof, it will be under-

## 6

stood by those skilled in the art that changes in form and detail thereof may be made without departing from the scope of the claims of the invention. For example, although the present disclosure has been presented in the context of obstruction lighting, this is merely for the purpose of illustration. Those skilled in the art will appreciate that the present invention may be used to advantage in connection with any type of lighting equipment and/or any suitable lighting application.

What is claimed is:

1. A lighting system, comprising:

a first light emitter configured to emit light outside a visible-light spectrum; and

a second light emitter configured to emit light in a visible-light spectrum,

an amount of light emitted in the visible light spectrum by the second light emitter having a predetermined corresponding relationship to a radiant intensity of light emitted outside the visible light spectrum by the first light emitter,

such that the lighting system appears to an observer to be the same intensity both when the lighting system is viewed by the observer with an unaided eye and when the lighting system is viewed by the observer with an imaging device.

2. The lighting system of claim 1, further including a controller arranged to control the operation of the first and second light emitters.

3. The lighting system of claim 2, further comprising a monitor arranged to detect a fault condition of the first light emitter and communicate the fault condition to the controller.

4. The lighting system of claim 3 wherein the monitor is configured to detect an electrical current fault condition of the first light emitter.

5. The lighting system of claim 3 wherein the monitor is configured to detect a voltage fault condition of the first light emitter.

6. The lighting system of claim 3 wherein the monitor is configured to detect a fault condition of the amount of light emitted by the first light emitter.

7. The lighting system of claim 3 wherein the controller alters lighting characteristics of the second light emitter while the fault condition of the first light emitter is present.

8. The lighting system of claim 7 wherein the controller alters lighting characteristics of the second light emitter by turning off the second light emitter while the fault condition of the first light emitter is present.

9. The lighting system of claim 7 wherein the controller alters lighting characteristics of the second light emitter by periodically turning the second light emitter on and off at a predetermined duty cycle while the fault condition of the first light emitter is present.

10. The lighting system of claim 3, further including a housing, the controller and monitor being disposed within the housing.

11. The lighting system of claim 3, further including an alarm coupled to the controller, the alarm being configured to issue an alert signal relating to the fault condition when commanded by the controller.

12. The lighting system of claim 1 wherein the first light emitter is an infrared light emitter.

13. The lighting system of claim 1 wherein the second light emitter is a visible-light light emitting diode.

14. The lighting system of claim 1 wherein the first emitter and the second emitter have separate optical systems.



7

15. The lighting system of claim 1 wherein the first and second light emitters are co-located such that the second light emitter is arranged atop the first light emitter in a stacked arrangement.

16. The lighting system of claim 1 wherein the first light emitter and the second light emitter emit light about a 360 degree radius.

17. A lighting system, comprising:

a first light emitter configured to emit light in an infrared light spectrum;

a second light emitter arranged to emit light in a visible-light spectrum;

a controller configured to control the operation of the first and second light emitters; and

a monitor arranged to detect a fault condition of the first light emitter and communicate the fault condition to the controller,

an amount of light emitted in the visible light spectrum by the second light emitter having a predetermined corresponding relationship to a radiant intensity of light emitted in the infrared light spectrum by the first light emitter,

such that the lighting system appears to an observer to be the same intensity both when the lighting system is viewed by the observer with an unaided eye and when the lighting system is viewed by the observer with an imaging device,

the first and second light emitters being co-located such that the second light emitter is atop the first light emitter in a stacked arrangement,

8

the first and second light emitters having separate optical systems, and

the controller altering lighting characteristics of the second light emitter by turning off the second light emitter while the fault condition of the first light emitter is present.

18. The lighting system of claim 17 wherein the first light emitter and the second light emitter emit light about a 360 degree radius.

19. A method for producing a lighting system, comprising the steps of:

selecting a first light emitter configured to emit light outside a visible-light spectrum;

selecting a second light emitter configured to emit light in a visible-light spectrum; and

establishing an amount of light emitted in the visible light spectrum by the second light emitter to correspond to a radiant intensity of light emitted outside the visible light spectrum by the first light emitter,

such that the lighting system appears to an observer to be the same intensity both when the lighting system is viewed by the observer with an unaided eye and when the lighting system is viewed by the observer with an imaging device.

20. The method of claim 19, further comprising the step of arranging the first emitter and the second emitter with separate optical systems.

\* \* \* \* \*