

US011180292B2

(12) **United States Patent**
Benoit-Gonin et al.

(10) **Patent No.:** **US 11,180,292 B2**
(45) **Date of Patent:** **Nov. 23, 2021**

(54) **METHOD OF MANUFACTURING A TAMPER-EVIDENT CLOSURE**

USPC 215/48, 250, 253, 254, 256
See application file for complete search history.

(71) Applicant: **Obrist Closures Switzerland GmbH**,
Reinach (CH)

(56) **References Cited**

(72) Inventors: **Claude Benoit-Gonin**, Odenas (FR);
Jean-Yves Rognard, Marcy-sur-Anse (FR)

U.S. PATENT DOCUMENTS

5,427,260 A 6/1995 Mueller et al.
5,772,076 A 6/1998 Juk et al.

(73) Assignee: **Obrist Closures Switzerland GmbH**,
Reinach (CH)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

EP 1582475 A1 10/2005
EP 1892194 A1 2/2008
EP 2213584 A1 8/2010
JP 2006232359 A 9/2006
JP 2012046209 A 3/2012
WO 0041943 A1 7/2000
WO 2008089785 A1 7/2008
WO 2009022892 A1 2/2009

(21) Appl. No.: **16/254,090**

(22) Filed: **Jan. 22, 2019**

OTHER PUBLICATIONS

(65) **Prior Publication Data**
US 2019/0152658 A1 May 23, 2019

Great Britain Intellectual Property Office, Search Report Issued in
Application GB1317407.3, dated Feb. 13, 2014, 4 pages.

Related U.S. Application Data

ISA European Patent Office, International Search Report Issued and
Written Opinion Issued in Application No. PCT/EP2014/052564,
dated Sep. 15, 2014, WIPO, 10 pages.

(63) Continuation of application No. 15/026,484, filed as
application No. PCT/EP2014/052564 on Feb. 10,
2014, now Pat. No. 10,287,067.

State Intellectual Property Office of the People's Republic of China,
Office Action and Search Report Issued in Application No.
202010326381.8, dated May 25, 2021, 23 pages (Submitted with
Partial Translation).

(30) **Foreign Application Priority Data**

Oct. 1, 2013 (GB) 1317407

Primary Examiner — Anthony D Stashick

Assistant Examiner — Raven Collins

(51) **Int. Cl.**
B65D 47/08 (2006.01)
B65D 55/02 (2006.01)

(74) *Attorney, Agent, or Firm* — McCoy Russell LLP


(52) **U.S. Cl.**
CPC **B65D 47/0804** (2013.01); **B65D 55/024**
(2013.01); **B65D 2401/30** (2020.05)

(57) **ABSTRACT**

A method of manufacturing a tamper-evident closure, comprising the steps of: forming a body having a base and a lid; and inserting a dispensing member and a tamper-evident member into the body.

(58) **Field of Classification Search**
CPC B65D 47/0804; B65D 55/024; B65D
2401/30; B65D 2401/50; B65D 47/103

18 Claims, 14 Drawing Sheets






FIG. 1

FIG. 2




FIG. 4




FIG. 3




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16






FIG. 17

211




FIG. 18





FIG. 19




FIG. 20




FIG. 21







FIG. 22A

FIG. 22B

FIG. 23A

FIG. 23B




FIG. 24A




FIG. 24B




FIG. 25A




FIG. 25B




FIG. 25G




FIG. 25C




FIG. 25D




FIG. 25E




FIG. 25H




FIG. 25F




FIG. 25I

METHOD OF MANUFACTURING A TAMPER-EVIDENT CLOSURE

CROSS REFERENCE TO RELATED APPLICATIONS

The present application is a continuation of U.S. patent application Ser. No. 15/026,484, entitled "A METHOD OF MANUFACTURING A TAMPER-EVIDENT CLOSURE" filed on Mar. 31, 2016. U.S. patent application Ser. No. 15/026,484 is a U.S. National Phase of International Application No. PCT/EP2014/052564, entitled "A METHOD OF MANUFACTURING A TAMPER-EVIDENT CLOSURE," filed on Feb. 10, 2014. International Application No. PCT/EP2014/052564 claims priority to Great Britain Application No. 1317407.3 filed on Oct. 1, 2013. The entire contents of the above-identified applications are hereby incorporated by reference in their entirety for all purposes.

The present disclosure relates generally to the manufacture of closures and particularly to the manufacture of tamper-evident closures.

Tamper-evident closures are widely used and include some means of indicating that a closure has been opened at least once. Such closures can be fabricated in a variety of different ways.

The present disclosure seeks to provide improvements in or relating to the method by which a tamper-evident closure is fabricated.

According to a first aspect of the present disclosure there is provided a method of manufacturing a tamper-evident closure, comprising the steps of: forming a body having a base and a lid; and inserting a dispensing member and a tamper-evident member into the body

The base and lid may be formed integrally, for example with an integral hinge connecting them together.

The lid may be movable between an open position and a closed position. The body may be formed with the lid in an open or partially open position.

The tamper-evident member and/or the dispensing member may be introduced into the body with the lid in an open position.

In some embodiments, prior to inserting the tamper-evident member and/or the dispensing member into the body the lid may be closed onto the base for example the tamper-evident member and/or the dispensing member are introduced after the lid has been closed.

The body may be formed with the lid in a closed position. The tamper-evident member and/or the dispensing member may be inserted into the body with the lid in the closed position. Alternatively the lid may be opened before introduction.

In some embodiments, the tamper-evident member engages the lid when introduced into the body. For example the member may secure the lid in the closed position. For this purpose the lid and member may be provided with co-operating features (such as a hook and a ledge) so that they engage upon insertion of the member. The engagement may then be used to cause the tamper evidence to operate, for example by causing the member to be broken or separated upon opening of the lid.

In some embodiments the member is a double ring structure, with two rings frangibly connected. Upon assembly, one of the rings engages in the lid and one engages in the base so that upon first opening the rings are pulled apart.

In some embodiment the tamper-evident member is inserted before the dispensing member and the dispensing

member may be used to secure the tamper-evident member in position. In other embodiments the dispensing member is inserted first.

The dispensing member may comprise or include a spout or the like.

The method may further comprise a slitting step, for example to form one or more frangible lines on the body, tamper-evident member or dispensing member. For example a frangible line may be formed towards the free end of a base sidewall to form a tamper-evident band that will activate if an attempt is made to remove the closure from an associated container.

In some embodiments the tamper-evident member and/or the dispensing member are introduced through the base, for example from its end opposite the lid and through a sidewall.

The present disclosure also provides a method of manufacturing a tamper-evident closure, comprising the steps of: a) forming a body having a base and a lid; b) inserting a tamper-evident member into the body, and c) inserting a dispensing member into the body, in which the tamper-evident member secures or holds the lid in a closed position prior to step c).

In this method the tamper-evident member secures the lid in a closed position with respect to the base before the dispensing member is inserted. In other words, the lid and base are held in a closed position during assembly of the dispensing member.

The present disclosure also provides a tamper-evident dispensing closure manufactured using a method as described herein.

The present disclosure also provides a closure as described herein in combination with a container.

Different aspects and embodiments of the disclosure may be used separately or together.

Particular aspects of the present disclosure are set out in the accompanying independent and dependent claims. Features of the dependent claims may be combined with the features of the independent claims as appropriate, and in combination other than those explicitly set out in the claims.

The present disclosure will now be more particularly described, by way of example, with reference to the accompanying drawings.

BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 is a side elevation of a tamper-evident closure suitable for manufacture using the method of the present disclosure.

FIG. 2 is a section of the closure of FIG. 1.

FIG. 3 is a side perspective view of a dispensing spout forming part of the closure of FIGS. 1 and 2.

FIG. 4 is a section of the spout of FIG. 3.

FIG. 5 is a section of a tamper-evident member forming part of the closure of FIGS. 1 and 2.

FIG. 6 is a perspective view of the closure of FIGS. 1 and 2 shown in an opened position.

FIG. 7 is a perspective view of an alternative closure suitable for the present disclosure and shown in a fully assembled, closed position.

FIG. 8 is a front view of the closure of FIG. 7.

FIG. 9 is a section of the closure of FIGS. 7 and 8.

FIG. 10 is a perspective view of the closure of FIGS. 7 to 9 shown in an open position.

FIG. 11 is a side view of the closure of FIG. 10 after it has been re-closed.

FIG. 12 is a section of the closure of FIG. 11.

FIG. 13 is a perspective view of a tamper-evident member forming part of the closure of FIGS. 7 to 12 and shown in an unbroken condition.

FIG. 14 is a section of a closure body in an as-moulded condition.

FIG. 15 shows the closure body of FIG. 14 following a pre-closing step.

FIG. 16 shows the closure body of FIG. 15 in a fully closed position.

FIG. 17 shows a tamper-evident member offered up to the body of FIG. 16.

FIG. 18 shows the member of FIG. 17 inserted into the body.

FIG. 19 shows a dispensing spout offered up to the body/member of FIG. 18.

FIG. 20 shows the spout of FIG. 18 inserted into the body/member to form a fully assembled closure.

FIG. 21 shows the fully assembled closure of FIG. 20 ready for further processing or use.

FIG. 22A is a section of a closure body formed according to an alternative embodiment and shown with a tamper-evident member being presented.

FIG. 22B is a front view of the closure body and member of FIG. 22A.

FIG. 23A is a section of the closure of FIG. 22A shown with a tamper-evident member inserted and with a spout being presented.

FIG. 23B is a front view of the closure of FIG. 23A.

FIG. 24A is a section of the closure of FIG. 23A shown following insertion of the spout.

FIG. 24B is a front view of the closure of FIG. 24A.

FIGS. 25A to 25F show front perspective, rear perspective, rear, side, front and top views of the fully assembled closure in a closed position.

FIGS. 25G to 25I show front perspective, side and top views of the closure in an open position.

DETAILED DESCRIPTION

FIGS. 1, 2 and 6 show a closure 10 being an embodiment of which the method of the present disclosure is suitable.

The closure 10 comprises a body having a base 20 and a lid 25. The lid has a top surface 25a and a projection 25c on one side to aid gripping and opening of the lid 25.

Referring also to FIGS. 3 and 4, within the closure 10 is a spout or dispensing member 40 which is a separate member fitted inside the base 20 and lid 25.

The base 20 and lid 25 are pivoted together by a hinge 26.

The lid 25 has an outer skirt 25b and an annular inner skirt 25d which depend from the top surface 25a and presses against part of the spout 40 so as to provide a seal. Further, the lid 25 includes an annular projection 25f depending from the underside of top surface 25a and which takes the form of a bore seal to seal against the inner surface of the spout 40 to prevent leakage of the contents of the container when the lid is in the closed position.

The spout 40 includes a flange 41 which projects radially outward from the side of the spout 40 at approximately the same axial level, when assembled with the base and/or lid, as the parting plane between the underside of the lid 25 and the upper surface of the base 20. Furthermore, the skirt 25d of the lid 25 has a projection 25e. This projection 25e projects radially outwards at the lower end of the skirt 25d. A gap 27 is left between the lower end of the side skirt 25b in a region approximately opposite the hinge 26 and the upper surface of the base 20. A void or pocket 31 is provided between the spout 40 and the base 20.

The spout 40 also includes a bore seal 44 which depends from the flange 41 and seals against the radially inner surface of an associated container (see FIG. 2).

Referring also to FIG. 5, a tamper-evident member 30 which takes the form of a separate element having an upper ring 30a and a lower ring 30b connected together by frangible connections 32 is assembled with the closure 10. Upon assembly, the tamper-evident member 30 fits between the base and the lid and radially outward of the spout 40. The tamper-evident member 30 includes an upper projection 34 which projects radially inwards and a lower flange 33 which projects radially outwards.

When the tamper-evident member 30 is assembled with the closure 10 the upper projection 34 engages with the projection 25e provided on the radially inner surface of the side skirt 25b of the lid 25. Further, the lower projection 33 engages under a terminal sidewall portion 21. In this manner, the lid cannot be opened without breaking the frangible connections 32. The components are all shaped to allow initial installation; for example the upper ring 30a has an angled surface 30c so that the ring 30a can pass over the projection 25e during assembly. The upper projection 34 includes an undercut, on the side opposite to the side having the angled surface, which engage with the projection 25e to prevent the projections from passing over one another following installation.

Furthermore, the closure 10 includes a tamper-evident band 23 at the lower end of the base 20 which operates in a similar manner to well-known tamper-evident drop members.

Referring now to FIGS. 7 to 13 there is shown a further embodiment of a closure 110 which is suitable for fabrication using a method according to the present disclosure.

The closure 110 is connectable to a container neck.

The closure 110 comprises a body 111, a spout insert 120 and a tamper-evident member insert 101.

The body 111 comprises a base 112 and a lid 114.

The base 112 comprises a generally cylindrical side wall 116 having at one end a tamper-evident annular band 117 connected thereto by a plurality of frangible bridges 118.

The side wall 116 terminates at its end opposite the band 117 with an annular shoulder 116c which extends radially inwards.

The turret-like lid 114 is connected to the free end of the shoulder 116c via a hinge arrangement generally indicated 132.

The interior of the base side wall 116 comprises internal screw thread formations 116a for engaging corresponding external screw thread formations on a container neck. The interior of the side wall 116 further comprises an annular retention bead 116b positioned below a second shoulder 116d in the sidewall 116.

The interior of the band 117 comprises a segmented retention bead 117a for engagement under a locking bead on a container neck so that if the closure is unscrewed the band 117 will remain on a container neck.

The lid 114 comprises a top plate 134 from which depends a curved outer sidewall 135; an inner skirt 125b depends from the underside of the top plate, radially inwards of the outer wall 135 and a spigot 136 depends from the underside of the centre of the plate 134, radially inwards of the inner skirt 125b. The free end of the lid sidewall 135 includes a window 108 (which could be, for example, a material thinning or an opening).

Opposite the hinge 132 the lid 114 includes a small peak 138 used to lift the lid and flip it open with respect to the base 112.

5

The spout **120** comprises a generally cylindrical lower portion **150**, a generally cylindrical central portion **151** and a generally frusto conical upper portion **152**.

The lower portion **150** comprises an annular external sealing bead **156**. In use, the portion **150** enters the bore of the container neck such that the sealing bead **156** seals against its inner surface.

The central retention portion **151** comprises a plurality of radially outwardly extending retention spokes **160**.

The upper portion **152** comprises a curved, generally frusto conical outer surface defining a spout. At the end of the spout side wall opposite the central portion **151** is a cylindrical terminal portion **170**. An inclined annular orifice wall **172** extends inwards from the free end of the portion **170** and from it an annular wall **173** depends; the wall **173** defines an orifice **174**.

The separate spout **120** is received into the body **111** as part of method described in more detail below with reference to FIGS. **14** to **21**. The spokes **160** abut against the shoulder **116d** and engage under the projection **116b** to retain the spout in the base. The spigot **136** enters through the wall **173** to close the orifice **174**.

A tamper-evident member **101** is provided for the closure and is shown in more detail in FIG. **13**.

The member **101** takes the form of a separate element having an upper ring **102** and a lower ring **103** connected together by frangible connections **104** and is assembled with the closure **110** as part of a method described in more detail below with reference to FIGS. **14** to **21**. Upon assembly, the tamper-evident member **101** fits between the base and the lid and radially outward of the spout **120**. The tamper-evident member **101** includes an upper projection **105** on the upper ring **102** which projects radially inwardly and a lower flange **106** on the lower ring which projects radially outwardly.

When the tamper-evident member **101** is assembled with the closure **110** the upper projection **105** engages with a projection **125e** provided on the radially inner surface of the inner skirt **125b** of the lid. Further, the flange **106** engages with the underside of the shoulder **116c**. In this manner, the lid cannot be opened without breaking the frangible connections **104**. The member **101** splits into the two rings **102**, **103** as shown in FIGS. **10** to **12** and the lower ring **103** is no longer visible through the lid window **108**, having dropped into a void **107** above the spout ledge **121**.

In FIGS. **7** to **9** the closure **110** is shown in the closed position. When a user desires to drink from the spout they grasp the lid and flip it open to the position shown in FIG. **11** using the peak **138**.

The user can now access the spout freely and unencumbered by the lid. With the lid in the open position the ring **103** is retained in the lid by the projection **125e** and is clearly visible in the lid. The separated rings **102**, **103** show that the closure has been opened at least once.

Referring now to FIGS. **14** to **21** there is described a method of manufacturing a tamper-evident dispensing closure.

In FIG. **14** a closure body **211** is shown and is generally the same as that of the closures **10**, **110**, comprising a base **212** and a lid **214** hinged together by an integral hinge **232**. In this embodiment the body is formed with the lid **214** in an open position.

FIG. **15** shows a pre-closing step, in which the lid **214** is moved to a partially closed position with respect to the base **212**.

In FIG. **16** the lid **214** has been fully closed on to the base **212**.

6

In FIG. **17** a tamper-evident member **201** is presented to the closed body **211**.

The member **201** takes the form of a separate annular element having an upper ring **202** and a lower ring **203** connected together by frangible connections **204**.

The member **201** includes an upper projection **205** on the upper ring **202** which projects radially inwardly to form a hook; and a lower flange **206** is provided on the lower ring **203** and projects radially outwardly.

In FIG. **18** the member **201** is pushed through the open end of the base sidewall **216**. The member flange **206** abuts against the underside of the shoulder **216c** and the upper ring projection **205** snaps over the lid inner skirt bead **225e** to connect it to the lid and to hold the lid in the closed position.

In FIG. **19** a dispensing spout **220** is presented to the closed body (with the member **201** in position).

In FIG. **20** the spout **220** is pushed into the open end of the base sidewall **216**.

The spokes **260** (which in other embodiments may be a continuous flange) abut against the shoulder **216d** and engage over the projection **216b** to retain the spout in the base. The lid spigot **236** enters through the spout wall **273** to close the orifice **274**.

The assembled closure **210** is now shown in FIG. **21**. Further processing steps may now be performed, such a slitting to form a tamper-evident band at the free end of the base sidewall.

The closure **210** functions in a similar way to the closures **10**, **110**. Upon first opening the tamper member rings **202**, **203** are torn apart because the upper ring **202** is clipped over the skirt bead **225e** and the lower ring flange abuts against the shoulder **216c**. The upper ring **202** is retained by the lid, and the lower ring **203** drops into the base void **207** so it can no longer be seen through the window **208**.

Referring now to FIGS. **22** to **24** there is described a method of manufacturing a tamper-evident dispensing closure **310** formed according to an alternative embodiment.

In FIGS. **22A** and **22B** a closure body **311** is shown and is generally the same as that of the closures **10**, **110**, comprising a base **312** and a lid **314** hinged together by an integral hinge **332**. In this embodiment the body is formed with the lid **214** in a closed position. In other embodiments the lid is formed in an at least partially open position.

A tamper-evident member **301** is presented to the closed body **311**. The member **301** takes the form of a separate annular element having an upper ring **302** and a lower ring **303** connected together by frangible connections **304**.

The member **301** includes an upper projection **305** on the upper ring **202** which projects radially inwardly to form a hook; and a lower flange **306** is provided on the lower ring **303** and projects radially outwardly.

In FIGS. **23A** and **23B** the member **301** has been pushed through the open end of the base sidewall **316**. The member flange **306** abuts against the underside of the shoulder **316c** and the upper ring projection **305** snaps over the lid inner skirt bead **325e** to connect it to the lid and to hold the lid in the closed position.

A dispensing spout **320** is presented to the closed body (with the member **301** in position).

In FIGS. **24A** and **24B** the spout **320** has been pushed into the open end of the base sidewall **316**.

The spokes **360** (which in other embodiments may be a continuous flange) abut against the shoulder **316d** and engage over the projection **316b** to retain the spout in the base. The lid spigot **336** enters through the spout wall **373** to close the orifice **374**.

7

The assembled closure **310** is now shown in FIGS. **25A** to **25F**. Further processing steps may now be performed, such a slitting to form a tamper-evident band at the free end of the base sidewall.

The closure **310** functions in a similar way to the closures **10**, **110**, **210**. Upon first opening the tamper member rings **302**, **303** are torn apart because the upper ring **302** is clipped over the skirt bead **325e** and the lower ring flange abuts against the shoulder **316c**. The upper ring **302** is retained by the lid and the lower ring **303** drops into the base void **307** so it can no longer be seen through the window **308** (see FIGS. **25G** to **25I**).

Although illustrative embodiments of the disclosure have been disclosed in detail herein, with reference to the accompanying drawings, it is understood that the disclosure is not limited to the precise embodiments shown and that various changes and modifications can be effected therein by one skilled in the art without departing from the scope of the disclosure as defined by the appended claims and their equivalents.

The invention claimed is:

1. A tamper-evident closure assembly, comprising:
a body having a base and a lid connected by an integral hinge;
a tamper-evident member which is a separate element to the body, the tamper-evident member comprising an upper projection which projects radially inwards and a lower flange which projects radially outwards, the upper projection engaging the lid and the lower flange engaging the base; and
a dispensing spout in the body.
2. The tamper-evident closure assembly of claim 1, wherein the tamper-evident member comprises two rings frangibly connected together.
3. The tamper-evident closure assembly of claim 2, wherein one of the two rings engages in the lid and one of the two rings engages in the base.
4. The tamper-evident closure assembly of claim 1, wherein the lid includes an inner skirt, and the upper projection engages with a projection provided on the inner skirt of the lid.
5. The tamper-evident closure assembly of claim 1, wherein the base has a sidewall and the sidewall has a terminal sidewall portion, wherein the lower flange is part of a lower ring, and wherein the lower flange of the lower ring engages under the terminal sidewall portion.
6. The tamper-evident closure assembly of claim 1, wherein the upper projection includes an undercut.

8

7. The tamper-evident closure assembly of claim 1, wherein the tamper-evident member fits between the base and the lid and radially outward of the spout.

8. The tamper-evident closure assembly of claim 1, wherein the lid has a top surface and the lid has an outer skirt and an inner skirt which depend from the top surface, the inner skirt presses against part of the dispensing spout to provide a seal.

9. The tamper-evident closure assembly of claim 1, wherein the lid includes a top surface, an annular projection depending from an underside of the top surface which takes the form of a bore seal to seal against an inner surface of the dispensing spout to prevent leakage of contents of the container when the lid is in a closed position.

10. The tamper-evident closure assembly of claim 1, wherein the lid has a top surface and a projection on one side to aid gripping and opening of the lid.

11. The tamper-evident closure assembly of claim 1, wherein a void or pocket is provided between the dispensing spout and the base.

12. The tamper-evident closure assembly of claim 1, wherein the lid includes a small peak opposite the integral hinge, the small peak used to lift the lid and flip it open with respect to the base.

13. The tamper-evident closure assembly of claim 1, wherein the lid comprises a top plate from which depends a curved outer sidewall, an inner skirt depends from an underside of the top plate, radially inwards of the outer sidewall, and a spigot depends from the underside of the center of the plate, radially inwards of the inner skirt.

14. The tamper-evident closure assembly of claim 1, wherein the lid includes a sidewall and the free end of the lid sidewall includes a window.

15. The tamper-evident closure assembly of claim 14, wherein the window is a material thinning or an opening.

16. The tamper-evident closure assembly of claim 1, wherein upon first opening of the lid the tamper-evident member splits into two rings, an upper ring and a lower ring, where the upper ring is retained in the lid and the lower ring is retained in the base.

17. The tamper-evident closure assembly of claim 1, wherein the lid has a window and the base has a void, in an unopened position the tamper-evident member is visible through the window, and upon first opening a lower ring drops into the void, and the lower ring is no longer visible through the window.

18. The tamper-evident closure assembly of claim 1, wherein the upper projection and the lower flange extend completely around a circumference of the spout.

* * * * *