



US011188891B2

(12) **United States Patent**
Vick et al.

(10) **Patent No.:** US 11,188,891 B2
(45) **Date of Patent:** Nov. 30, 2021

(54) **MODULAR DUAL BAND MOBILE
POINT-OF-SALE TERMINAL**

FOREIGN PATENT DOCUMENTS

WO WO-2015030675 A1 * 3/2015 G06Q 50/12

(71) Applicant: **TOAST, INC.**, Boston, MA (US)

OTHER PUBLICATIONS

(72) Inventors: **Ronald Vick**, Morton Grove, IL (US);
Steven P. Papa, Windham, NH (US)

<https://www.marketsandmarkets.com/Market-Reports/tv-white-space-spectrum-market-71081100.html> (Year: 2016).*

(73) Assignee: **Toast, Inc.**, Boston, MA (US)

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 139 days.

Primary Examiner — Ariel J Yu

Assistant Examiner — Dana Amsdell

(21) Appl. No.: **16/197,755**

(74) *Attorney, Agent, or Firm* — Richard K. Huffman;
Huffman Patent Group, LLC

(22) Filed: **Nov. 21, 2018**

(65) **Prior Publication Data**

US 2020/0160313 A1 May 21, 2020

(57) **ABSTRACT**

(51) **Int. Cl.**
G06Q 20/20 (2012.01)
H04W 16/14 (2009.01)
H04W 88/06 (2009.01)
H04W 84/18 (2009.01)
H04W 84/12 (2009.01)
H04L 29/08 (2006.01)

A modular mobile point-of-sale POS terminal is provided that includes a state processor, an order processor, a conventional wireless communications element, and a detachable television whitespace (TVWS)/payment processing module. The state processor queues state changes for orders in a restaurant. The order processor is coupled to the state processor and generates, accesses, and transmits to a back-end server when operably connected to a network. The conventional wireless communications element enables the mobile POS terminal to communicate over a Wi-Fi network within the restaurant. The detachable television whitespace (TVWS)/payment processing module enables the mobile POS terminal to communicate over a White-Fi network within the restaurant. When programmed in a Wi-Fi mode, the mobile POS terminal communicates only over the Wi-Fi network as a selected wireless network, and when programmed in a White-Fi mode, the mobile POS terminal communicates only over the White-Fi network as the selected wireless network.

(52) **U.S. Cl.**
CPC **G06Q 20/208** (2013.01); **G06Q 20/202** (2013.01); **H04W 16/14** (2013.01); **H04W 88/06** (2013.01); **H04L 67/10** (2013.01); **H04W 84/12** (2013.01); **H04W 84/18** (2013.01)

(58) **Field of Classification Search**
CPC ... G06Q 20/202; G06Q 20/208; H04W 84/18; H04W 16/14; H04W 84/12; H04L 67/10
See application file for complete search history.


(56) **References Cited**

U.S. PATENT DOCUMENTS

6,694,362 B1 2/2004 Secor et al.
7,120,677 B1 10/2006 Berger et al.

(Continued)

20 Claims, 8 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

7,568,614 B2 8/2009 Pang et al.
 8,320,304 B2 11/2012 Deb et al.
 9,204,311 B1* 12/2015 Banerjea H04W 16/14
 9,282,464 B2 3/2016 Deb et al.
 9,301,299 B2 3/2016 Garnett et al.
 9,526,011 B2 12/2016 Lee et al.
 9,582,797 B1* 2/2017 Holmes G06Q 20/3224
 9,762,389 B2 9/2017 Smedman et al.
 10,567,971 B2 2/2020 Eng et al.
 2007/0077883 A1* 4/2007 Childers H04H 20/61
 455/3.05
 2009/0252318 A1* 10/2009 Smith H04M 3/5238
 379/265.1
 2010/0142446 A1 6/2010 Schlicht et al.
 2011/0218867 A1* 9/2011 Cerrato G06Q 50/12
 705/15
 2011/0280227 A1 11/2011 McCann et al.
 2012/0238226 A1 9/2012 Vermani et al.
 2013/0195089 A1* 8/2013 Tandra H04W 16/14
 370/338
 2013/0325526 A1* 12/2013 Tyler G06Q 10/02
 705/5
 2014/0156359 A1* 6/2014 Morgan G06Q 20/322
 705/13

2014/0156431 A1* 6/2014 Morgan G06Q 20/20
 705/21
 2015/0206116 A1 7/2015 Bess et al.
 2015/0237550 A1 8/2015 Krisnaswamy
 2016/0125449 A1* 5/2016 Beatty G06Q 20/202
 705/14.38
 2016/0155108 A1 6/2016 McLaughlin et al.
 2017/0046800 A1* 2/2017 Zomet G06Q 50/12
 2017/0134255 A1 5/2017 Amini et al.
 2017/0161851 A1* 6/2017 Li H04W 4/14
 2017/0169413 A1* 6/2017 Holmes G06Q 20/20
 2020/0067594 A1 2/2020 Tsuchida et al.
 2021/0168856 A1* 6/2021 Cariou H04W 88/06

OTHER PUBLICATIONS

“FIFO (computing and electronics)”. Wikipedia. Retrieved from [https://en.wikipedia.org/w/index.php?title=FIFO_\(computing_and_electronics\)&oldid=773338255](https://en.wikipedia.org/w/index.php?title=FIFO_(computing_and_electronics)&oldid=773338255). Original publication date Apr. 1, 2017. pp. 1-5.
 Radunovic, Bozidar et al. “Rethinking Indoor Wireless Mesh Design: Low Power, Low Frequency, Full-duplex” Wireless Mesh Networks (WIMESH 2010), 2010 Fifth IEEE Workshop on IEE, Piscataway, NJ. Jun. 21, 2010. pp. 1-6. XP031707502.

* cited by examiner

FIG. 1 (Prior Art)

PRESENT DAY ORDERING SYSTEM




FIG. 2

DUAL BAND RESTAURANT ORDERING SYSTEM




FIG. 3




FIG. 4




FIG. 5




FIG. 6

EXEMPLARY TERMINAL BAND ASSIGNMENT MAP




FIG. 7

TVWS ROUTING TABLE DETAILS




FIG. 8

TVWS COMMS MODULE DETAILS




FIG. 9

EXEMPLARY UPDATE/STATUS MESSAGES





FIG. 10



1

MODULAR DUAL BAND MOBILE POINT-OF-SALE TERMINAL

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is related to the following co-pending U.S. patent applications, each of which has a common assignee and common inventors.

Ser. No.	FILING DATE	TITLE
16/197,615	Nov. 21, 2018	DUAL BAND RESTAURANT ORDERING SYSTEM
16/197,636	Nov. 21, 2018	DUAL BAND FIXED POINT-OF-SALE TERMINAL
16/197,657	Nov. 21, 2018	DUAL BAND MOBILE POINT-OF-SALE TERMINAL
16/197,682	Nov. 21, 2018	ADAPTIVE DUAL BAND MOBILE RESTAURANT TERMINAL
16/197,700	Nov. 21, 2018	COMBINED BAND RESTAURANT ORDERING SYSTEM
16/197,718	Nov. 21, 2018	RESTAURANT ORDERING SYSTEM EMPLOYING DUAL BAND MESH NETWORK
16/197,735	Nov. 21, 2018	RESTAURANT ORDERING SYSTEM EMPLOYING TELEVISION WHITESPACE COMMUNICATION CHANNELS

BACKGROUND OF THE INVENTION

Field of the Invention

This invention relates in general to the field of point-of-sale (POS) systems, and more particularly to a dual band restaurant ordering system.

Description of the Related Art

It is rare these days to walk into a retail store or restaurant that has a manually operated cash register along with manual (i.e., pencil and paper) order entry. Rather, it is more common to find one or more electronic point-of-sale (POS) terminals through which a patron may order goods and/or services. And the POS terminals do not merely record orders, but rather account for available inventory, modify items available for order based upon recent orders, and optionally provide for payment for the orders. In many scenarios, most notably restaurants, though wait staff may employ manual techniques to enter and modify orders, such orders are entered by the wait staff themselves into electronic POS terminals at selected positions within the restaurants.

Many establishments use a type of POS terminal may be configured as a mobile device, such as a smartphone or tablet, that is additionally equipped with a card or chip reader (typically plugged into an audio jack). The mobile device may run an application program that provides for order entry and fulfillment, and which further may synchronize with a server in the cloud for purposes of order payment processing and inventory management. Food trucks, mobile kiosks, and pop-ups generally use these mobile devices for order entry, fulfillment, and payment. In a present-day establishment, conventional Wi-Fi networks are ubiquitous, for they provide for access to the cloud (and server) not only for the mobile POS terminals, but also for the myriad numbers of smartphones and tablets that patrons bring into the establishment.

2

As one skilled in the art will appreciate, Wi-Fi coverage in any establishment can be spotty due to dead spots, degraded due to decreased signal strengths from access points, or absent altogether. All of these problems arise from the number, placement, and type of Wi-Fi access points that are disposed therein. And the number, placement, and types of Wi-Fi access points that a proprietor chooses to deploy are determined by the cost and complexity of the deployment. For example, the proprietor may determine to forego deployment of a Wi-Fi access point on, say, a porch area of the establishment because it is not as heavily trafficked as other areas of the establishment. The proprietor may choose to hide a Wi-Fi access point behind a door or in a ceiling because of aesthetic reasons, while at the same time degrading the effectiveness of the overall Wi-Fi network as a result of the placement. Consequently, employment of these mobile POS terminals, whether used by patrons or staff, becomes complicated, burdensome, or altogether impossible.

The present inventors have observed the above noted problems and disadvantages associated with present-day Wi-Fi networks, and they have further noted stop gap fallback solutions, such as the use of cellular or Bluetooth ad hoc networks when reliable Wi-Fi coverage is unavailable. As one skilled in the art will appreciate, both cellular and Bluetooth coverage are subject to the same problems as Wi-Fi networks. Accordingly, the present inventors have sensed a need in the art for an effective and reliable fallback communication technique for mobile terminals within a retail establishment, for employment when Wi-Fi access is unavailable. The present inventors have also recognized a need in the art for communication techniques within an establishment having a number of mobile POS terminals that do not suffer from the problems noted above.

Therefore, what is needed is a multi-band ordering and fulfillment system for communication with mobile POS terminals.

What is also needed is a dual band fixed POS terminal that provides for fallback communication with one or more mobile terminals within an establishment.

What is additionally needed is a dual band mobile POS terminal that is capable of communicating to a server via Wi-Fi or via a fallback television whitespace (TVWS) communication band.

What is furthermore needed is an adaptive dual band mobile restaurant POS terminal that communicates via Wi-Fi or TVWS channels as a function of coverage and network availability.

What is moreover needed is a combined band ordering system that increases coverage and throughput of orders within an establishment by simultaneously employing both Wi-Fi and TVWS channels for transmission/reception of data to/from mobile terminals.

What is yet additionally needed is an ordering system that employs a dual band mesh network.

What is further needed is a restaurant ordering system that employs both Wi-Fi and TVWS communication channels.

What is likewise needed is a modular dual band mobile POS terminal.

SUMMARY OF THE INVENTION

The present invention, among other applications, is directed to solving the above-noted problems and addresses other problems, disadvantages, and limitations of the prior art. In one aspect, a modular dual band mobile point-of-sale (POS) terminal is provided that includes a state processor, an

3

order processor, a conventional wireless communications element, and a detachable television whitespace (TVWS)/payment processing module. The state processor is configured to queue state changes in one or more order queues that correspond to one or more orders in a restaurant. The order processor is coupled to the state processor and is configured to generate the state changes, and is configured to access and transmit the state changes in each one of the one or more order queues to a backend server, from oldest to youngest, when operably connected to a network, where the order processor comprises current order state fields corresponding to all of the orders. The conventional wireless communications element enables the mobile POS terminal to communicate over a Wi-Fi network within the restaurant. The detachable television whitespace (TVWS)/payment processing module enables the mobile POS terminal to communicate over a White-Fi network within the restaurant. When programmed in a Wi-Fi mode, the mobile POS terminal communicates only over the Wi-Fi network as a selected wireless network, and when programmed in a White-Fi mode, the mobile POS terminal communicates only over the White-Fi network as the selected wireless network.

Another aspect of the present invention contemplates a modular dual band mobile point-of-sale (POS) terminal that includes a state processor, a touchpad display/camera circuit, an order processor, a conventional wireless communications element, and a detachable television whitespace (TVWS)/payment processing module. The state processor is configured to queue state changes in one or more order queues that correspond to one or more orders in a restaurant. The touchpad display/camera circuit is configured to input menu selections and/or payment options. The order processor is coupled to the state processor and is configured to generate the state changes, and is configured to access and transmit the state changes in each one of the one or more order queues to a backend server, from oldest to youngest, when operably connected to a network, where the order processor comprises current order state fields corresponding to all of the orders. The conventional wireless communications element enables the mobile POS terminal to communicate over a Wi-Fi network within the restaurant. The detachable television whitespace (TVWS)/payment processing module enables the mobile POS terminal to communicate over a White-Fi network within the restaurant. When programmed in a Wi-Fi mode, the mobile POS terminal communicates only over the Wi-Fi network as a selected wireless network, and when programmed in a White-Fi mode, the mobile POS terminal communicates only over the White-Fi network as the selected wireless network.

A further aspect of the present invention comprehends an order fulfillment method using a dual band mobile point-of-sale (POS) terminal, the method comprising: queuing state changes in one or more order queues that correspond to one or more orders in a restaurant; generating the state changes, and accessing and transmitting the state changes in each one of the one or more order queues to a backend server, from oldest to youngest, when operably connected to a network and maintaining current order state fields corresponding to all of the orders; and employing conventional wireless communications elements that enable the mobile POS terminal to communicate over a Wi-Fi network; attaching a detachable television whitespace (TVWS)/payment processing module, enabling the mobile POS terminal to communicate over a White-Fi network within the restaurant; where, when programmed in a Wi-Fi mode, the mobile POS terminal communicates only over the Wi-Fi network as a selected wireless network, and when programmed in a

4

White-Fi mode, the mobile POS terminal communicates only over the White-Fi network as the selected wireless network.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other objects, features, and advantages of the present invention will become better understood with regard to the following description, and accompanying drawings where:

FIG. 1 is a block diagram illustrating a present-day system for fulfilling product orders to one or more patrons.

FIG. 2 is a block diagram depicting a dual band restaurant ordering system according to the present invention;

FIG. 3 is a block diagram featuring a backend server according to the present invention;

FIG. 4 is a block diagram showing dual band fixed terminal according to the present invention;

FIG. 5 is a block diagram illustrating a dual band mobile terminal according to the present invention;

FIG. 6 is a block diagram detailing an exemplary band assignment map for fixed and mobile terminals, such as may be employed in the backend server of FIG. 3;

FIG. 7 is a block diagram illustrating details of a TVWS routing table according to the present invention, such as may be employed in the fixed terminals of FIGURE;

FIG. 8 is a block diagram depicting a television whitespace (TVWS) communication module, such as may be employed in the dual band mobile terminal of FIGS. 5 and 10;

FIG. 9 is a block diagram detailing exemplary update/status messages according to the present invention that flow between a backend server and dual band fixed and mobile terminals; and

FIG. 10 is a block diagram illustrating a combined band mobile terminal according to the present invention.

DETAILED DESCRIPTION

Exemplary and illustrative embodiments of the invention are described below. In the interest of clarity, not all features of an actual implementation are described in this specification, for those skilled in the art will appreciate that in the development of any such actual embodiment, numerous implementation specific decisions are made to achieve specific goals, such as compliance with system-related and business-related constraints, which vary from one implementation to another. Furthermore, it will be appreciated that such a development effort might be complex and time-consuming, but would nevertheless be a routine undertaking for those of ordinary skill in the art having the benefit of this disclosure. Various modifications to the preferred embodiment will be apparent to those skilled in the art, and the general principles defined herein may be applied to other embodiments. Therefore, the present invention is not intended to be limited to the particular embodiments shown and described herein, but is to be accorded the widest scope consistent with the principles and novel features herein disclosed.

The present invention will now be described with reference to the attached figures. Various structures, systems, and devices are schematically depicted in the drawings for purposes of explanation only and so as to not obscure the present invention with details that are well known to those skilled in the art. Nevertheless, the attached drawings are included to describe and explain illustrative examples of the present invention. The words and phrases used herein should

be understood and interpreted to have a meaning consistent with the understanding of those words and phrases by those skilled in the relevant art. No special definition of a term or phrase (i.e., a definition that is different from the ordinary and customary meaning as understood by those skilled in the art) is intended to be implied by consistent usage of the term or phrase herein. To the extent that a term or phrase is intended to have a special meaning (i.e., a meaning other than that understood by skilled artisans) such a special definition will be expressly set forth in the specification in a definitional manner that directly and unequivocally provides the special definition for the term or phrase.

In view of the above background discussion on present-day ordering systems and associated techniques employed therein for dealing with intermittent, poor quality, or absent Wi-Fi connections, a discussion of the disadvantages and limitations of those systems will now be presented with reference to FIG. 1. Following this, a discussion of the present invention is presented with reference to FIGS. 2-10. The present invention provides superior mechanisms and techniques that enable robust POS terminal interconnectivity within a retail establishment by employing an additional or replacement wireless network that operates using television whitespace (TVWS) channel frequencies.

Referring to FIG. 1, a block diagram is presented illustrating a present-day system for fulfilling product orders to one or more patrons, such as may be present in any of a number of different retail establishments. The system 100 may include one or more wireless access points 101 that operate over conventional wireless links 103. The conventional wireless links 103 comprise Wi-Fi links that comport with commonly employed IEEE 802.11 Wi-Fi standards that include both 2.4 GHz and 5 GHz frequencies, namely IEEE 802.11a/b/g/n. The system may include a number of ordering positions 104 that are serviced for purposes of ordering and order fulfillment by one or more mobile terminals 121 that communicate over the conventional wireless links 103. Patrons or staff within the retail establishment may also have smartphones 106 (or tablets) that connect to the internet via the wireless access points 101.

The wireless access points 101 each provide for access within a given area of coverage 131. As shown, the mobile terminals 121 within the upper area of coverage 131 may be employed to place and fulfill orders OD1 and OD2 providing that the upper access point 101 is not oversubscribed by terminals 121 and smartphones/tablets 106. Similarly, mobile terminals 121 within the lower area of coverage 131 may be employed to place and fulfill orders OD1, OD2, ODA, and ODB providing that the lower access point 101 is not oversubscribed by terminals 121 and smartphones/tablets 106. As one skilled in the art will appreciate, a mobile terminal 121 (typically a modified tablet computer) connects to the access point 101 having the highest signal strength. However, it is noted that orders OD3 and OD4 cannot be serviced by a mobile terminal 121 that is connected to the wireless network 103 because the mobile terminal 121 is outside of the coverage areas 131 and is thus unable to connect to any of the wireless access points 101. As one skilled in the art will also appreciate, the coverage areas 131 are determined not only by physical distance, but also by obstructions, as the conventional Wi-Fi links, because of frequency band, degrade when transmitting through doors, walls, windows, ceilings, and the like. Accordingly, orders OD3 and ODC must be taken and fulfilled via mechanisms other than a mobile terminal 121, namely pencil and paper.

The present inventors have observed that the scenario depicted with reference to FIG. 1 applies to virtually all

present-day retail establishments, whether they are a big box store or a restaurant, for several factors affect both the number and placement of wireless access points 101. These factors may include the costs, time, or complexities associated with deploying an establishment-wide Wi-Fi network 103, the number of non-establishment devices 106 connected to an existing Wi-Fi network 103, or simply sheer aesthetics. For example, a proprietor may opt to provide Wi-Fi coverage for heavily trafficked areas, resulting in remaining areas of the establishment that have poor or no Wi-Fi coverage. Likewise, the proprietor may opt to hide Wi-Fi access points 101 in the ceiling or behind walls, simply because they detract from the aesthetics of the establishment, and thus Wi-Fi coverage is degraded because of attenuation. Similarly, because of time, cost, or complexities, the proprietor may install Wi-Fi access points 101 that are incapable of handling the establishments mobile terminals 121 in conjunction with a significant number of patron devices 106.

The system 101 of FIG. 1 exemplifies a present-day retail establishment that employs a wireless network 103 to provide for ordering and fulfillment, and the present inventors have noted that degraded, poor quality, or absent wireless coverage are substantial problems that limit an establishment's ability to effectively process orders. Disadvantages of present-day systems 100 include delay in order processing, errors in order processing, and overall annoyance of patrons. Accordingly, the present inventors have sensed a need in the art for better wireless connectivity within establishments that provides greater and more robust coverage.

The present invention overcomes the above noted limitations and disadvantages, by providing a dual band restaurant order system that employs both conventional Wi-Fi frequencies and TVWS frequencies. The present invention will now be discussed with reference to FIGS. 2-10.

Turning to FIG. 2, a block diagram is presented depicting a dual band restaurant ordering system 200 according to the present invention. The system 200 may include one or more service areas 202, such as a front service area 202, service area 1-service area N 202, and service area kitchen 202. Going forward, the present inventors note that though the present invention is applicable to any type of retail establishment as is described above, a restaurant establishment will be henceforth employed in order to teach relevant aspects of the present invention. The present inventors further note that though restaurant terms such as host, wait staff, cook, kitchen, food item, etc. may be employed, such terms are used to more clearly teach the present invention in a given context, however, broader and different retail establishment types are contemplated.

The service areas 202 may comprise one or more wireless access points 201. The service areas 202 may also comprise dual band mobile point-of-sale (POS) terminals 221 coupled to the access points 201 via conventional wireless links 203. The service areas 202 may further comprise a gateway 213 to which are coupled one or more fixed POS terminals 211-212, 231 via a wired network 207 and which provide for coupling of the fixed terminals 211-212, 231 and access points 201 an internet cloud 260 via conventional wired links. Wired links 205, 207 may include, but are not limited to, Ethernet, cable, fiber optic, and digital subscriber line (DSL). As part of the network path to and through the cloud 260, providers of internet connectivity (e.g., ISPs) may employ wireless technologies from tower to tower, etc., but for purposes of this application, such links 205, 207 will be referred to as conventional wired links 205 to distinguish them from conventional wireless links 203, as discussed

above, along with cellular links **209** (e.g., 3G, 4G, LTE). The POS terminals **211-212**, **221**, **231** may be configured differently to comport with intended function (i.e., host seating, order and payment entry, order processing and fulfillment, etc.), or they may be configured similarly. In one embodiment, the mobile terminals **221** may comprise a touch screen display and integral payment processor (e.g., card/chip/tap reader) that provides for both order entry, display of order status, and payment processing. As such, the host terminal **211**, fixed POS terminals **212**, and order processing terminals **231** may comprise larger touch screens to allow for easier viewing by restaurant staff, or they may comprise displays with keyboard entry. In one embodiment, terminals **211-212**, **231** may comprise desktop computers, laptop computers, smartphones, or tablets that are running application programs or web-enabled application programs that provide for communication with a backend server **270** for purposes of order entry, status updates, payment processing, and wireless communications channel assignment.

The backend server **270** is coupled to the internet cloud **260**, and an administrative console **271** that is operably coupled to the backend server **270** via a conventional wired link **205** and/or a wireless link **203**. The backend server **270** is not on-premise. The administrative console **271** may be disposed within the restaurant premises and coupled to the backend server **260** via the links **203**, **205**, or the console **271** may be disposed in another location, say, at an operations headquarters for multiple restaurants within a given region. In addition, the system **200** may comprise one or more browser-based terminals **281** that are coupled to the backend server **270** via links **205**. In one embodiment, the browser-based terminals **281** may comprise desktop computers, laptop, computers, smartphones, or tablets that are running stand-alone applications or web-enabled applications that provide for communication with the backend server **270** for purposes of order entry, status updates, and optionally, payment processing.

The system **200** may further comprise one or more third-party-based terminals **241** that are coupled to the backend server **270** via the conventional links **205** though the cloud **260**. The third party-based terminals **241** may comprise desktop computers, laptop, computers, smartphones, or tablets that are running stand-alone third-party applications or web-enabled third-party applications that provide for communication with the backend server **270** for purposes of order entry, status updates, and optionally, payment processing via a proprietary application programming interface (API) **242**. An example of such a terminal **241** may include the well-known GrubHub third-party application that is configured to communicate with the backend server **270** via the API **241**.

The system **200** may further comprise one or more delivery terminals **251** that are coupled to one or more cellular access points **208** via conventional cellular wireless links **209**, and the cellular access points **208** are coupled to the backend server **270** via the cloud **260**. The mobile terminals **221** and delivery terminals **251** are configured to provide services for order entry, order fulfillment (i.e., delivery), and payment processing. In one embodiment, the delivery terminals **251** are identical to the mobile terminals **221** and are disposed as smartphone or tablets with a detachable payment processor (e.g., card/chip reader). In a further embodiment, the mobile terminals **221** and delivery terminals **251** are disposed as smartphone or tablets with a payment processor integrated within a single housing, where the payment processor comprises a module that is coupled to the smartphone/tablet via a connector. In yet another

embodiment, the mobile terminals **221** and delivery terminals **251** are disposed as smartphone or tablets with a TVWS/payment processor integrated within a single housing, where the TVWS/payment processor comprises a module that is coupled to the smartphone/tablet via a connector. Other embodiments are contemplated.

Service areas **202** corresponding to the mobile terminals **221** may have one or more tables **204** corresponding to one or more orders. For clarity, service area **1 202** depicts two tables **204**, one of which corresponds to order **1 OD1**, and the other of which corresponds to order **2 OD2**. The mobile terminals **221** within service area **1 202** may process portions of both order **1 OD1** and order **2 OD2**.

Service area **N 202** depicts two tables **204**, both of which correspond to order **A ODA**. The mobile terminals **221** within service area **N 202** may both process portions order **A ODA**.

Though disposed within separate service areas (service area **1 202**—service area **N 202**), the mobile terminals **221** therein may be further configured to process portions of any and all orders within the restaurant and may roam from service area **202** to service area to support work load of the restaurant.

The order processing terminals **231** may process all orders in the restaurant, or they may be configured to each process a portion of all of the orders in the restaurant according to preparation station or inventory station.

The host terminal **211** and fixed terminals **212** may be configured to process all orders in the restaurant to provide for on-premise seating assignment, order initiation, order selection, and payment processing, including closeout of orders.

One or more patrons or staff members within service area **1 202**—service area **N 202** may have a personal device (e.g., smartphone, tablet, laptop) **206** that can provide an ad hoc network (i.e., hotspot) to which one or more of the mobile terminals **221** may tether for purposes of communicating with the backend server **270** in the absence of Wi-Fi connectivity to the access points **201**.

As one skilled in the art will appreciate, several years ago the Federal Communications Commission (FCC) abandoned use of older analog television (TV) channels corresponding to analog channels 2-69 operating at frequencies of 54-72 MHz, 76-88 MHz, 174-216 MHz, 470-680 MHz, and 614-806 MHz, and that in 2009 these frequencies were opened up for consumer use. These specific channels are commonly referred to as television whitespace (TVWS) or White-Fi channels. As one skilled will also appreciate, these frequency channels previously allowed for analog TV transmission paths upwards to 100 miles using very high power broadcast transmitters (e.g., 10,000 Watts). As one skilled will further appreciate, these channels are being employed to provide for internet infrastructure in many undeveloped parts of the world. One skilled will moreover appreciate that the FCC has provided these frequencies for both fixed and personal/portable devices to operate in the TV white spaces on an unlicensed basis; however, the devices must include a geolocation capability and capability to access a database of protected radio services. The devices provide their location to their database, which returns a list of TVWS channels on which they may operate (channel lists are specific to the location of the device). There are numerous databases and these databases are established and administered by third parties (e.g., Google, Microsoft, etc.). The devices must register their locations in the database and provide identifying information. Devices are precluded from transmitting

without checking the database and devices must recheck periodically, on the order of every 48 hours.

It is not within the scope of the present application to provide an in-depth discussion of TVWS technology and related implementations. What is relevant to the present application is that TVWS frequency channels exist for public use, provided that the foregoing requirements are met prior to and during use of the channels for communications.

The present inventors have noted that even using a low transmit power—approximately 40 milliwatts—enables TVWS wireless coverage areas within a restaurant to increase in size by a factor of 5 to 10, while simultaneously decreasing signal degradation when travelling through obstructions such as ceilings, doors, and windows.

Accordingly, the present inventors have provided the dual band system 200 of FIG. 2 that employs, in one embodiment, TVWS frequencies as a fallback communication method for scenarios as described above where conventional Wi-Fi performance is degraded, poor quality, or even absent.

Thus, the dual band system 200 according to the present invention may employ dual band mobile terminals 221 that are selectively configurable to exclusively operate using either conventional Wi-Fi 203 via the Wi-Fi access points 201 or using White-Fi. In such and embodiment, staff may configure the mobile terminals 221, via a maintenance interface, prior to deployment within the restaurant. That is, the mobile terminals 221 may be configured to use conventional Wi-Fi 203 via the Wi-Fi access points 201 in a restaurant that has excellent Wi-Fi coverage. Alternatively, the mobile terminals 221 may be configured to exclusively used White-Fi for communications, as will be described in further detail below. An exclusive White-Fi restaurant ordering system may be advantageous in scenarios where Wi-Fi coverage is not required and/or where greater coverage areas are required.

The dual band system 200 according to the present invention may employ dual band mobile terminals 221 that are dynamically configurable to operate using conventional Wi-Fi 203 via the Wi-Fi access points 201 or using White-Fi. When configured as such, in one embodiment, the mobile terminals 221 may operate in a default mode, say Wi-Fi, and switch to a fallback mode, say White-Fi, when default mode coverage is insufficient. In such an embodiment, the mobile terminals 221 themselves measure network parameters (e.g. signal strength, number of hops, etc.) and are programmed to switch from one operating mode to the next if measurements exceed programmed thresholds.

In a further embodiment, the dual band mobile terminals 221 are configurable to operate using both conventional Wi-Fi 203 and White-Fi simultaneously to allow for greater data throughput and reliability.

All of the previously described embodiments may be configured via the maintenance interface.

In an single White-Fi access point configuration, one of the fixed terminals 211-212, 231 is additionally configured as a White-Fi access point that provides for communications with designated mobile terminals 221 within the restaurant over a White-Fi link 281. In a multiple White-Fi access point configuration, a plurality of the fixed terminals 211-212, 231 are additionally configured as a White-Fi access points that provide for communications with designated mobile terminals 221 within the restaurant over plurality of White-Fi links 281. In a mesh network embodiment, a plurality of the fixed terminals 211-212, 231 are additionally configured as a White-Fi access points that provide for communications with designated mobile terminals 221 within the restaurant over a plurality of White-Fi links 281, and that additionally

are configured together in a mesh network for purposes of data synchronization, including those communications designated for the designated mobile terminals 221. As such, synchronization between the fixed terminals 211-212, 231 and mobile terminals 221 may employ any of the conventional wireless links 203, wired links 207, or cellular links 209, as described above, to forward data to its destination in the mesh network. As one skilled in the art will appreciate, selection of one or more of the links 203, 207, 209 for forwarding is determined as a function of proximity and network throughput.

The system 200 of FIG. 2 shows the host terminal 211, one of the fixed terminals 212, and one of the order processing terminals 231 configured as White-Fi access points in addition to providing for their intended functions.

In one embodiment, operations are initiated when the one or more patrons enter the restaurant. Generally, a host (not shown) will create an order (along with corresponding order identifier (OID) via the host terminal 211 for the one or more patrons and will seat the patrons at one or more tables 204. The created order may include service area designation and assignment of the order to one or more mobile terminals 221. In another embodiment, mobile terminals 221 within a service area 202 are assigned to all orders within that service area 202. Other embodiments are contemplated. The created order and service area assignment are transmitted over the cloud 260 to the backend server 270, which maintains durable terminal queues within which are stored order updates for all orders in the restaurant. The backend server 270 additionally maintains a band assignment mapping, discussed below, that assigns each of the mobile terminals 221 to communicate via conventional Wi-Fi links 203, via White-Fi links 281 (including channel assignment), or both Wi-Fi links 203 and White-Fi links 281 as described above. In one embodiment, the White-Fi links comport with IEEE 802.11af standards, though other embodiments are contemplated.

Each of the plurality of durable queues correspond to each of the POS terminals 211-212, 221, 231, 251 within the system 200. When connection status to a given terminal 211, 212, 221, 231, 251 is down (i.e., the server 270 cannot verify communication with the given terminal 211, 212, 221, 231, 251), then the server maintains the order updates for that terminal 211, 212, 221, 231, 251 until connectivity is reestablished, at which time the server 270 may transmit one or more of the order updates to the terminal, verifying with each transmission that the terminal 211, 212, 221, 231, 251 received the update. Advantageously, each of the terminals 211, 212, 221, 231, 251 is capable of processing portions of any of the orders in the restaurant.

Likewise, each of the terminals 211, 212, 221, 231, 251 maintains durable order queues within which are stored order updates only for each of the orders being processed by the terminal 211, 212, 221, 231, 251. Each of the terminals 211, 212, 221, 231, 251 also maintains a plurality of order states that depict a current state for each of the orders in the restaurant. As a seated patron selects one or more menu items, wait staff enters the menu items as an update in one of the terminals 211, 212, 221, 231, 251, generally a mobile terminal 221 assigned to the given service area 202. The order update is entered into one of the durable order queues that corresponds to the order ID. If connectivity is present, then the terminal 211, 212, 221, 231, 251 transmits the order update to the server 270 and waits for the server 270 to acknowledge the order update. If acknowledged, the terminal 211, 212, 221, 231, 251 removes the order update from the one of the durable order queues. If unacknowledged (i.e.,

in the case of non-persistent network connectivity), the terminal **211, 212, 221, 231, 251** maintains the order update in the one of the durable order queues until such time as connectivity is reestablished, and the terminal **211, 212, 221, 231, 251** completes transmission of the order update with acknowledgement by the server **270**.

Upon reception of a particular update from the server **270**, the terminals **211, 212, 221, 231, 251** may check one of their plurality of order states that correspond to the particular update for conflicts, as will be described in further detail below. If a conflict exists, the terminals **211, 212, 221, 231, 251** may utilize domain specific rules to resolve the conflict in order to establish a valid order state. Each of the terminals **211, 212, 221, 231, 251** is configured with the same domain specific rules to provide for consistent resolution of order states.

Preferably, the mobile terminals **221** monitor signal strengths of the Wi-Fi access points **201** and may request connection to that access point **201** having the highest signal strength. In one embodiment, if Wi-Fi signal strength is insufficient to provide connectivity, a mobile terminal **221** may request attachment to a White-Fi access point **211, 212, 231** within the restaurant to restore communications.

As patrons continue to order items corresponding to the order ID, the one or more of the terminals **211, 212, 221, 231, 251** may enter the order updates and transmit/durably queue the order updates to the server **270** in accordance with connectivity conditions. The server **270** may also queue/transmit order updates for all orders in the restaurant to each of the terminals **211, 212, 221, 231, 251** according each terminal's connectivity. Order fulfillment, payment, and closeout are likewise handled as order updates through the server **270** and are queued/transmitted to all of the terminals **211, 212, 221, 231, 251** in accordance with the connection status of each terminal **211, 212, 221, 231, 251**.

Patrons outside of the restaurant are also handled in similar fashion via the browser-based terminals **281**, and third-party terminals **241**, though without feedback from the server **270** regarding all orders in the restaurant. When accessed through the browser-based terminals **281** and third-party terminals **241**, the server **270** creates an order ID and assigns it to one of the order processing terminals **231** for fulfillment, while sending status updates on the order ID to all of the terminals **211, 212, 221, 231, 251** via the durable terminal queue therein. The server **270** may designate a specific delivery terminal **251** for pickup, delivery, and payment based upon geofenced proximity to the restaurant, or based upon workload corresponding to the delivery terminal. Proximity to the restaurant may be determined by a number of different mechanisms, as will be described in further detail below.

The administrative console **271** may maintain a master record of all order states and order updates according to all of the terminals **211-212, 221, 231, 251** in order to provide for restaurant management, maintenance, analytics, and network traffic analyses. The console **271** may alternatively be disposed in an expediter's area of the restaurant for use by expediters in assignment and allocation of patron seating and terminals **211-212, 221, 231, 251**.

The durable terminal queues and durable order queues may be disposed as battery backed random-access memory, electrically-erasable programmable read-only memory, solid state memory, hard disk memory, or a combination of the above that will provide for maintaining order updates within the queues across network and power interruptions.

Advantageously, the present invention provides for more efficient performance of computational resources within the

server **270** and the POS terminals **211-212, 221, 231, 251** over that which has heretofore been provided because multiple terminals **211-212, 221, 231, 251** may be assigned to process portions of a single order, resulting in more timely processing of the single order. In addition, performance is increased as a result of using White-Fi links **281** exclusively or dynamically as a fallback in the event of degraded Wi-Fi coverage. Moreover, performance is enhanced by simultaneously employing both Wi-Fi links **203** and White-Fi links **281**. Similarly, any of the terminals **211-212, 221, 231, 251** in the restaurant may be immediately reassigned to a particular order to replace a malfunctioning terminal or to increase throughput of the server **270**. Accordingly, computational resources **211-212, 221, 231, 251, 270** within the system **200** are afforded an overall performance improvement as a result of the present invention.

Now referring to FIG. 3, a block diagram is presented featuring a backend server **300** according to the present invention. The backend server **300** may comprise communications circuitry COMMS **302** (e.g., transceivers, modems, message formatter, etc.) that is coupled to one or more wired or conventional wireless communications links **301**, examples of which are described above with reference to FIGS. 1-2. The server **300** may also comprise a terminal status element **305**, a terminal update element **306**, and a payment processor **304**, all of which are coupled to COMMS **302** via a message bus MSG. The terminal status element **305** is coupled to the terminal update element **306** via a status bus STS. The terminal update element **306** may comprise a service area map SA MAP **307** and a terminal band assignment map **308**. The terminal update element **306** is coupled to the payment processor **304** and to an order initiation element ORDER INIT **303** via a terminal bus TBUS. The terminal update element **306** is also coupled to a queue processor **310** via a queue bus QBUS. The server **300** may further comprise a TVWS band update element **309** that is coupled to the COMMS **302**, the terminal status element **305**, the payment processor **304**, and the terminal update element **306** via the MSG bus.

The queue processor **310** may include a durable terminal queue **311** that includes terminal update records **312**, each of which are associated with a corresponding POS terminal (not shown) that is employed within a given restaurant. In the embodiment of FIG. 3, N terminal update records **312** are shown, each associated with a corresponding one of N POS terminals for the given restaurant. In a large restaurant or big box environment, N may be roughly equal to 100 POS terminals, though larger and smaller numbers are contemplated.

Each of the terminal update records **312** may comprise update fields **313**, which are employed to queue order updates for transmission to each of the corresponding POS terminals as connectivity to the corresponding POS terminals permits. Update fields **313** nearest to OUT are the oldest order updates queued for transmission to the corresponding POS terminals. Update fields **313** nearest to IN are youngest (or most recent) order updates queued for transmission to the corresponding POS terminals. Fields **313** between the oldest order updates and the youngest order updates descend in age from oldest to youngest update according to when those updates are received from others of the corresponding POS terminals.

Values of the order update fields **313** may include, but are not limited to, an order ID along with order details taken by the others of the corresponding POS terminals. Accordingly, the terminal update record **312** for POS terminal 1 TERM1 depicts a plurality of order update fields **313** to be transmit-

ted to TERM1 when connectivity is reestablished with TERM1. In decreasing age from oldest to youngest order update, the fields **313** depict updates to order **64 U64**, then order **6 U6**, then order **22 U22**, and so on, culminating with an update to order **17 U17**. As one skilled in the art will appreciate, the terminal update record **312** for TERM1 is indicative that TERM1 has been offline (i.e., no connectivity) longer than any of the other POS terminals in the restaurant. This length of time may correspond to a mobile POS terminal that is serving a party on a restaurant porch that has poor Wi-Fi connectivity, or may correspond to a delivery POS terminal that is traversing an area with poor cellular coverage. The terminal update records **312** corresponding to TERM2, TERM 3, and TERMN depict a number of populated order update fields **313** less than the number of fields for TERM1, which may correspond to mobile POS terminals within the restaurant that have only slightly intermittent Wi-Fi connectivity. And the terminal update record for TERM4 through TERM N-1 contain only empty order update fields **313**, thus indicated that these POS terminals are up to date on all order state changes within the restaurant. As a Wi-Fi connected terminal experiences degraded Wi-Fi connectivity, it may request fallback or supplemental communications using White-Fi over the White-Fi network, as described above with reference to FIG. 2. Assignment of a particular mobile terminal to Wi-Fi only, White-Fi only (including channel assignment), or combined Wi-Fi and White-Fi is maintained within the terminal band assignment map **308**.

Operationally, the terminal status element **305** may periodically transmit a first message to each of the POS terminals using the communication mode and channels indicated by the band assignment map **308**, and accessed via bus STS, and update the connectivity status of the POS terminals based upon whether they acknowledge the first message or not. In one embodiment, the first message may comprise a ping message. In one embodiment, acknowledgment may comprise a simple acknowledge message. In other embodiments, acknowledgment may comprise additional data such as received signal strength indication Wi-Fi/White-Fi RSSI, number of hops, or Global Positioning System (GPS) coordinates, as will be described in further detail below.

The terminal status element **305** may provide connectivity status of each of the POS terminals to the terminal update element **306** via bus STS. The service area map **307** is a table that associates each of the POS terminals to one or more service areas within the restaurant. In one embodiment, the terminal update element **306** may generate order update messages from oldest to youngest update for each of the POS terminals that are connected. Connectivity is maintained when a POS terminal acknowledges receipt of an order update message over its designated communication channel. Once acknowledged, the terminal update element **306** directs the queue processor **310** to delete the oldest order update for that POS terminal and shift pending order updates so that the next oldest order update becomes the oldest order update. In one embodiment, order updates are transmitted to a given POS terminal until its terminal update record **312** is empty, or until connectivity is broken.

In one embodiment, all of the POS terminals associated with the restaurant are updated by the terminal update element **306**. In an alternative embodiment, POS terminals are selectively updated in accordance with their mapping to the one or more service areas. For example, the delivery POS terminals may only require knowledge of orders that are to be delivered outside the restaurant, and thus they may be mapped to a "delivery" service area so that order updates

that correspond to the delivery service area are transmitted to the delivery POS terminals. Similarly, the restaurant or retail establishment may be so large that management dedicates certain POS terminals to designated service areas. Accordingly, all of the POS terminals in a given service area may be employed to update any order placed within the given service area, but they may not be employed to update orders placed outside of the given service area.

Messages received from the communications circuit **302** may also require additional functions to be performed by the backend server **300**. For example, when orders are placed by a browser-based or third-party based terminal, the terminal update element **306** may transmit the order update to the order initiation element **303** via TBUS. The order initiation element **303** may then create an order ID for the order update and may assign the order ID to one or more of the POS terminals within the restaurant. Similarly, when an order update message received over the COMMS **302** requires processing of transactions outside of the POS terminals' capabilities (e.g., financial transactions with credit card providers, loyalty card discounts, etc.), the payment processor **304** may generate messages to complete the transactions and the messages are transmitted via COMMS **302**. The payment processor **304** may further generate order updates (e.g., "order paid," "payment source 1 approved," "discount amount," etc.) to be transmitted to the POS terminals and may provide these updates to the terminal update element **306** via TBUS. The terminal update element **306** may then provide those updates to the durable queue **311** via QBUS, and the updates are transmitted to the POS terminals in due course dependent upon connection status, as is described above.

The present inventor notes that the term "restaurant" is employed to include those fixed and mobile POS terminals within the restaurant along with corresponding delivery POS terminals associated with the restaurant, such as delivery POS terminals **251** depicted in FIG. 2. There are no terminal update records **312** corresponding to browser-based or third-party-based terminals since orders placed on these devices are created and assigned to one of the POS terminals within the restaurant for fulfillment, preferably order processing terminals, such as the order processing terminals **231** in FIG. 2.

As discussed above with reference to FIG. 2, devices such as the dual band mobile and fixed terminals according to the present invention may operate in the TV white spaces on an unlicensed basis but the fixed device must register their locations in the TVWS database, and the TVWS database will provide one or more TVWS channel assignments for each fixed device based on its location. In addition, location information and channel assignments must be periodically updated with the TVWS database. To this end, the TVWS band update element **309** may monitor message traffic on MSG to extract GPS coordinates of all fixed terminals within the restaurant that are configured to additionally function as a White-Fi access point. The band update element **309** may further generate TVWS band update messages via the COMMS **302** that are directed to register the fixed terminals, periodically update the terminal's location information, and receive TVWS available channels for White-Fi. The update element may assign one of the TVWS available channels to all of the fixed terminals and may update the band assignment map **308** with the one of the TVWS available channels for all fixed and mobile terminals in the restaurant, regardless of whether they are enabled to communicate via White-Fi, thus enabling for fallback to White-Fi in the absence of Wi-Fi connectivity.

The backend server **300** according to the present invention is configured to perform the functions and operations as discussed above and may comprise one or more central processing units (CPUs) coupled to both transitory and non-transitory stores via conventional mechanisms. The non-transitory stores may include one or more applications programs that may be executed to perform the functions and operations discussed above. The one or more application programs may be cached within the transitory storage for speed of execution at run time. The server **300** may comprise digital and/or analog logic, circuits, devices, or microcode (i.e., micro instructions or native instructions), or a combination of logic, circuits, devices, or microcode, or equivalent elements that are employed to execute the functions and operations according to the present invention as noted. The elements employed to accomplish these operations and functions within the server **300** may be shared with other circuits, microcode, etc., that are employed to perform other functions and/or operations within the server **300**. According to the scope of the present application, microcode is a term employed to refer to a plurality of micro instructions. A micro instruction (also referred to as a native instruction) is an instruction at the level that a unit executes. For example, micro instructions are directly executed by a reduced instruction set computer (RISC) microprocessor. For a complex instruction set computer (CISC) microprocessor such as an x86-compatible microprocessor, x86 instructions are translated into associated micro instructions, and the associated micro instructions are directly executed by a unit or units within the CISC microprocessor.

Turning now to FIG. 4, a block diagram is presented showing dual band fixed terminal **400** according to the present invention. The terminal **400** may comprise a communications circuit COMMS **402** (e.g., transceivers, modems, message formatter, etc.) that is coupled to one or more wired or conventional wireless communications links **401**, examples of which are described above with reference to FIGS. 2-3. The durable POS terminal **400** may also comprise a connection monitor **404**, an order processor **410**, and a payment processor **406**, all of which are coupled to COMMS **402** via a message bus MSG. The terminal **400** may also comprise a link select element **405** that is coupled to the connection monitor **404** via bus CS and to the COMMS **402** via bus LNK. The order processor **410** is coupled to the connection monitor **404** via bus CBUS and to the payment processor **406**, an order initiation element **407**, and a GPS receiver **408** via bus SBUS. The order processor **410** is coupled to a touchpad display/camera **403** via bus DATA and to terminal ID logic **409** via bus TID. The order processor **410** is also coupled to a state processor **420** via a queue bus QBUS.

The state processor **420** may include an order update queue **421** that includes order update records **422**, each of which is associated with the fixed terminal **400**. The terminal ID element **409** provides a unique identifier (e.g., a number) for the terminal **400**, and which can then be associated with one or more orders. Contents of the terminal ID element **409** are typically entered by staff through the touchpad **403**.

Each of the order update records **422** may comprise order state fields **423**, which are employed to queue order state changes (i.e., order updates) for transmission to a backend server (not shown) as connectivity to the backend server permits. State fields **423** nearest to OUT are the oldest order state changes queued for transmission to the backend server. State fields **423** nearest to IN are youngest (or most recent) order state changes queued for transmission to the backend server. Fields **423** between the oldest state fields **423** and the

youngest state fields **423** descend in age from oldest to youngest according to when those state changes are entered by terminal **400**.

Values of the order state fields **423** may include, but are not limited to, an order ID along with order details taken by the terminal **400**. Accordingly, an order update record **422** for order **27 O27** depicts a plurality of order state fields **423** to be transmitted to the server when connectivity is reestablished. In decreasing age from oldest to youngest order state change, the fields **423** depict order state changes S1 through SN. As one skilled in the art will appreciate, the order update record **422 O27** depicts that many more state changes have been entered while connection status of the POS terminal **400** is down than have been entered for orders **62 O62** through order **3 O3**. Advantageously, the POS terminal **400** according to the present invention may be employed for entry of order updates even in the presence of network interruptions.

In operation, order state changes result from two sources: the touchpad display/camera circuit **403** and messages received over COMMS **402** from the backend server. In the first case, wait staff in possession of the fixed terminal **400** may enter order items as requested by patrons, or in the case of a self-service terminal **400**, the patrons may enter the order items themselves. The present invention contemplates provisions within the fixed terminal **400** to display menu selections and payment options to both wait staff and patrons. Order items received from the touchpad display/camera circuit **403** are provided to the order processor **410** via bus DATA, which generates the state changes. State changes received from the server are provided to the order processor **410** in messages over bus MSG. If the fixed terminal **400** is not additionally configured as a White-Fi access point, then the TVWS communications circuit **431**, antenna **432**, and GPS receiver **408** are not required, however, conventional wireless links **401** may be provided in the event of failure of a hardwired link **401**. In one embodiment, the fixed terminal **400** may comprise a touchpad display/camera **403** on the order of 15 inches, an example of which is a 11-Series 2.0 for Android 15" AiO Touchscreen as produced by Elo Touch Solutions, Inc. A POS terminal **400** functioning as a fixed terminal **400** for use by wait staff may be configured similar to the kiosk, but may exhibit a larger touchpad display/camera circuit **403**, an example of which is a 11-Series 2.0 for Android 22" AiO Touchscreen as produced by Elo Touch Solutions, Inc. A fixed terminal **400** additionally functioning as a TVWS access point must include a wired link **401**, the GPS receiver **408**, and the TVWS communications circuit **431**, and TVWS antenna **432**. Order items received from the touchpad display/camera circuit **403** are provided to the order processor **410** via bus DATA, which generates the state changes. State changes received from the backend server are provided to the order processor **410** in messages over bus MSG.

The order processor **410** may maintain a current state of all orders being fulfilled by the restaurant. The current state of each of the orders are stored in order current state fields **412** therein. The order processor **410** may further include a TVWS routing table **433**. The routing table **433** provides a designated TVWS channel for White-Fi communications, which is received from the backend server. The routing table **433** may further include a list of mobile terminals that are assigned to the fixed terminal for White-Fi communications. The routing table **433** may also include a routing table for all fixed terminals within a mesh network configuration that are additionally configured as White-Fi access points for purposes of forwarding message traffic.

The connection monitor **404** may monitor reception of a first message (e.g., a ping message) from the backend server and direct transmission of an acknowledgement message. The connection monitor **404** may update the connectivity status of the fixed terminal **400** accordingly. In one embodiment, acknowledgment may comprise a simple acknowledge message. In other embodiments, acknowledgment may comprise additional data such as received signal strength indication RSSI associated with one or more access points, number of hops between the backend server and the POS terminal **400**, and Global Positioning System (GPS) coordinates, as will be described in further detail below.

The link select element **405** may be employed to direct the COMMS **402** to change links **401** over which to communicate with the backend server, such as switching from Wi-Fi to LTE, for example, when the fixed terminal **400** is not additionally configured to function as a White-Fi access point. In one embodiment, in the absence of connectivity within the restaurant, the link select element **405** may direct the COMMS **402** to tether to a cellular equipped device corresponding to an order ID, such as devices **206** in FIG. 2, in order to transmit acknowledgements and order state changes to the backend server. When configured to additionally function as a White-Fi access point, the link select element **405** may direct the terminal **400** to employ wired links **401** only for communication with the backend server. When White-Fi is employed as a fallback, the link select element **405** may direct that communication with mobile terminals designated for the fixed terminal occur using White-Fi at a channel assignment that is stored in the TVWS routing table **433**.

As noted above, the fixed terminal **400** may also include the TVWS communication element **431** that is coupled to the analog TV band antenna **432** and that is coupled to both the MSG bus and the LNK bus. When additionally configured as a White-Fi access point, the TVWS communication element **431** may access messages received from the backend server and forward these messages to designated mobile terminals using the specific TVWS channels stored in the TVWS routing table **433**. The TVWS communication element **431** may further receive messages from the designated mobile terminals over the channels stored in the TVWS routing table **433** and forward these messages to the backend server. In a mesh configuration, order processor **410** may direct the COMMS **402** to forward all message traffic to a next fixed terminal as indicated by the TVWS routing table **433**.

The connection monitor **404** may provide connectivity status of the POS terminal **400** to the order processor **410** via bus CBUS. In one embodiment, the order processor **410** may generate order state change messages from oldest to youngest update for each of the orders in the queue **421**. Connectivity is maintained when the POS terminal **400** receives acknowledgement of a previously transmitted order state change message from the server. Once acknowledged, the order processor **410** directs the state processor **420** to delete the oldest state change update for a corresponding order ID and shift pending updates so that the next oldest state change update becomes the oldest order update. In one embodiment, state change updates are transmitted to the server until its order state change record **422** is empty, or until connectivity is lost.

Messages received from the communications circuit **402** may also require additional functions to be performed by the fixed terminal **400**. For example, when orders are placed by a browser-based or third-party based terminal, the backend server may transmit the order state change to the terminal

400 and the order processor **410** may direct the state processor **420** to create a corresponding order status record **422** in the queue **421**. Similarly, when processing of transactions outside of the terminal's capabilities (e.g., financial transactions with credit card providers, loyalty card discounts, etc.) are required, the order processor **410** may direct the payment processor **406** to generate messages to the backend server to provide data (e.g., amounts, payment source type, card swipe/chip information, etc.) to complete the transactions. Such messages are transmitted via COMMS **402** or/and the TVWS COMMS **431**, according to mode of operation of the fixed terminal **400**. The payment processor **406** may further receive state changes (e.g., "order paid," "payment source 1 approved," "discount amount," etc.) from the server and may provide these state changes to the order processor **410** via SBUS. The order processor **410** may then provide those updates to the queue **421** via OBUS. The terminal **400** may further be employed to create an order. Accordingly, from order entry data received over DATA, the order processor **410** may direct the order initiation element **407** to create an order ID and may also direct the state processor **420** to create a corresponding order state record **422** in the queue **421**.

Advantageously, the present invention provides for improvements in performance of computational resources within the fixed terminals **400** over that which has heretofore been provided because the fixed terminal **400** may be employed to process orders in the absence of conventional Wi-Fi network connectivity. In addition, computing performance is increased because the fixed terminal **400** may be employed to process any of the other orders within the restaurant since the current states **412** of all restaurant orders are resident therein. Moreover, order processing throughput is substantially increased by employing White-Fi channels in the absence of reliable conventional Wi-Fi connectivity. And throughput increases yet more when a combined band protocol (Wi-Fi and White-Fi) is employed to communicate with selected mobile terminals.

The fixed terminal **400** according to the present invention is configured to perform the functions and operations as discussed above and may comprise one or more central processing units (CPUs) coupled to both transitory and non-transitory stores via conventional mechanisms. The non-transitory stores may include one or more applications programs that may be executed to perform the functions and operations discussed above. The one or more application programs may be cached within the transitory storage for speed of execution at run time. The terminal **400** may comprise digital and/or analog logic, circuits, devices, or microcode (i.e., micro instructions or native instructions), or a combination of logic, circuits, devices, or microcode, or equivalent elements that are employed to execute the functions and operations according to the present invention as noted. The elements employed to accomplish these operations and functions within the terminal **400** may be shared with other circuits, microcode, etc., that are employed to perform other functions and/or operations within the terminal **400**. According to the scope of the present application, microcode is a term employed to refer to a plurality of micro instructions. A micro instruction (also referred to as a native instruction) is an instruction at the level that a unit executes. For example, micro instructions are directly executed by a reduced instruction set computer (RISC) microprocessor. For a complex instruction set computer (CISC) microprocessor such as an x86-compatible microprocessor, x86 instructions are translated into associated micro instructions,

and the associated micro instructions are directly executed by a unit or units within the CISC microprocessor.

Now referring to FIG. 5, a block diagram is presented illustrating a dual band mobile terminal 500 according to the present invention. The mobile terminal 500 may be adapt-
5 able for handheld use by staff and may comprise a communications circuit COMMS 502 (e.g., transceivers, modems, message formatter, etc.) that is coupled to one or more conventional wireless communications links 501, examples of which are described above. The mobile terminal 400 may also comprise a connection monitor 504, an order processor 510, and a payment processor 506, all of which are coupled to COMMS 502 via a message bus MSG. The mobile terminal 500 may also comprise a link select element 505
10 that is coupled to the connection monitor 504 via bus CS and to the COMMS 502 via bus LNK. The order processor 510 is coupled to the connection monitor 504 via bus CBUS and to the payment processor 506 and an order initiation element 507 via bus SBUS. The order processor 510 is coupled to a touchpad display/camera 503 via bus DATA and to terminal ID logic 509 via bus TID. The order processor 510 is also coupled to a state processor 520 via a queue bus QBUS.

The state processor 520 may include an order update queue 521 that includes order update records 522, each of which is associated with the mobile terminal 500. The terminal ID element 509 provides a unique identifier (e.g., a number) for the mobile terminal 500, and which can then be associated with one or more orders. Contents of the terminal ID element 509 are typically entered by staff through the touchpad 503.
25

Each of the order update records 522 may comprise order state fields 523, which are employed to queue order state changes (i.e., order updates) for transmission to a backend server (not shown) as connectivity to the backend server permits, whether that connectivity is via conventional Wi-Fi or White-Fi. State fields 523 nearest to OUT are the oldest order state changes queued for transmission to the backend server. State fields 523 nearest to IN are youngest (or most recent) order state changes queued for transmission to the backend server. Fields 523 between the oldest state fields 523 and the youngest state fields 523 descend in age from oldest to youngest according to when those state changes are entered by mobile terminal 500.
30

Values of the order state fields 523 may include, but are not limited to, an order ID along with order details taken by the terminal 500. Accordingly, an order update record 522 for order 27 O27 depicts a plurality of order state fields 523 to be transmitted to the server when connectivity is reestablished. In decreasing age from oldest to youngest order state change, the fields 523 depict order state changes S1 through SN. As one skilled in the art will appreciate, the order update record 522 O27 depicts that many more state changes have been entered while connection status of the mobile terminal 500 is down than have been entered for orders 62 O62 through order 3 O3. Advantageously, the mobile terminal 500 according to the present invention may be employed for entry of order updates even in the presence of network interruptions.
35

In operation, order state changes result from two sources: the touchpad display/camera circuit 503 and messages received over COMMS 502 from the backend server. When White-Fi is enabled, messages from the backend server (forwarded by a fixed terminal that is additionally configured as a White-Fi access point) are also received from a TVWS module 531, which will be described in more detail below. When White-Fi is employed as a fallback to Wi-Fi, messages from the backend server are only received over the
40

TVWS module 531. In a dual band (Wi-Fi and White-Fi) implementation, messages from the backend server are received over both COMMS 502 the TVWS module 531, as will be described in more detail below with reference to FIG. 10. Accordingly, wait staff in possession of the mobile terminal 500 may enter order items as requested by patrons, or in the case of a self-service mobile terminal 500, the patrons may enter the order items themselves. The present invention contemplates provisions within the mobile terminal 500 to display menu selections and payment options to both wait staff and patrons. Order items received from the touchpad display/camera circuit 503 are provided to the order processor 510 via bus DATA, which generates the state changes. State changes received from the backend server are provided to the order processor 510 in messages over bus MSG. If the mobile terminal 500 is not additionally configured for White-Fi communications, then the TVWS communications module 531, described in more detail with reference to FIG. 8, is not required, and may be replaced by a module (not shown) that comprises a credit card reader without White-Fi capabilities. In one embodiment, the mobile terminal 500 may comprise a touchpad display/camera 503 on the order of 7-10 inches, dependent upon menu complexity, and may comprise the Android operating system. Order items received from the touchpad display/camera circuit 503 are provided to the order processor 510 via bus DATA, which generates the state changes. State changes received from the backend server are provided to the order processor 510 in messages over bus MSG.
45

The order processor 510 may maintain a current state of all orders being fulfilled by the restaurant. The current state of each of the orders are stored in order current state fields 512 therein. The order processor 510 may further include a TVWS channel assignment table 533. The channel assignment table 533 provides a designated TVWS channel for White-Fi communications, which has been previously received from the backend server and which may be employed when Wi-Fi coverage is absent.
50

The connection monitor 504 may monitor reception of a first message (e.g., a ping message) from the backend server (sent via Wi-Fi) and direct transmission of an acknowledgement message. The connection monitor 504 may update the connectivity status of the mobile terminal 500 accordingly. In one embodiment, acknowledgment may comprise a simple acknowledge message. In other embodiments, acknowledgment may comprise additional data such as received signal strength indication RSSI associated with one or more access points (both Wi-Fi and White-Fi), number of hops between the backend server and the POS terminal 400, and Global Positioning System (GPS) coordinates, as will be described in further detail below. The connection monitor 504 may further determine that connectivity over Wi-Fi is degraded to the extent that the connection monitor may access the TVWS channel assignment table 533 and direct the link select element 505 to connect to the backend server via one or more fixed terminals that are additionally configured to function as TVWS access points. The connection monitor 504 may provide the designated TVWS channel to the link select element 505 which, in turn, will direct that subsequent outgoing messages to the backend server be over White-Fi, and the link select element 505 will provide the designated TVWS channel to the TVWS module via bus LNK.
55

The link select element 505 may be employed to direct the COMMS 502 to change conventional wireless links 501 over which to communicate with the backend server, such as switching from Wi-Fi to LTE. In one embodiment, in the
60

absence of connectivity within the restaurant (both Wi-Fi and White-Fi), the link select element **505** may direct the COMMS **502** to tether to a cellular equipped device corresponding to an order ID, such as devices **206** in FIG. 2, in order to transmit acknowledgements and order state changes to the backend server.

The connection monitor **504** may provide connectivity status of the mobile terminal **500** to the order processor **510** via bus CBUS. In one embodiment, the order processor **510** may generate order state change messages from oldest to youngest update for each of the orders in the queue **521**. Connectivity is maintained when the mobile terminal **500** receives acknowledgement of a previously transmitted order state change message from the backend server. Once acknowledged, the order processor **510** directs the state processor **520** to delete the oldest state change update for a corresponding order ID and shift pending updates so that the next oldest state change update becomes the oldest order update. In one embodiment, state change updates are transmitted to the backend server until its order state change record **522** is empty, or until connectivity is lost.

Messages received from the communications circuit **502** may also require additional functions to be performed by the fixed terminal **500**. For example, when orders are placed by a browser-based or third-party based terminal, the backend server may transmit the order state change to the terminal **500** and the order processor **510** may direct the state processor **520** to create a corresponding order status record **522** in the queue **521**. Similarly, when processing of transactions outside of the terminal's capabilities (e.g., financial transactions with credit card providers, loyalty card discounts, etc.) are required, the order processor **510** may direct the payment processor **506** to generate messages to the server to provide data (e.g., amounts, payment source type, card swipe/chip information, etc.) to complete the transactions. Such messages are transmitted via COMMS **502** or/and the TVWS module **531**. The payment processor **506** may further receive state changes (e.g., "order paid," "payment source 1 approved," "discount amount," etc.) from the backend server and may provide these state changes to the order processor **510** via SBUS. The order processor **510** may then provide those updates to the queue **521** via OBUS. The terminal **500** may further be employed to create an order. Accordingly, from order entry data received over DATA, the order processor **510** may direct the order initiation element **507** to create an order ID and may also direct the state processor **520** to create a corresponding order state record **522** in the queue **521**.

Advantageously, the present invention provides for improvements in performance of computational resources within the mobile terminals **500** over that which has heretofore been provided because the mobile terminal **500** may be employed to process orders in the absence of conventional Wi-Fi network connectivity. In addition, computing performance is increased because the mobile terminal **500** may be employed to process any of the other orders within the restaurant since the current states **512** of all restaurant orders are resident therein. Moreover, order processing throughput is substantially increased by employing White-Fi channels in the absence of reliable conventional Wi-Fi connectivity. And throughput increases yet more when a combined band protocol (Wi-Fi and White-Fi) is employed to communicate with fixed terminals additionally configured as White-Fi access points.

The mobile terminal **500** according to the present invention is configured to perform the functions and operations as discussed above and may comprise one or more central

processing units (CPUs) coupled to both transitory and non-transitory stores via conventional mechanisms. The non-transitory stores may include one or more applications programs that may be executed to perform the functions and operations discussed above. The one or more application programs may be cached within the transitory storage for speed of execution at run time. The terminal **500** may comprise digital and/or analog logic, circuits, devices, or microcode (i.e., micro instructions or native instructions), or a combination of logic, circuits, devices, or microcode, or equivalent elements that are employed to execute the functions and operations according to the present invention as noted. The elements employed to accomplish these operations and functions within the terminal **500** may be shared with other circuits, microcode, etc., that are employed to perform other functions and/or operations within the terminal **500**. According to the scope of the present application, microcode is a term employed to refer to a plurality of micro instructions. A micro instruction (also referred to as a native instruction) is an instruction at the level that a unit executes. For example, micro instructions are directly executed by a reduced instruction set computer (RISC) microprocessor. For a complex instruction set computer (CISC) microprocessor such as an x86-compatible microprocessor, x86 instructions are translated into associated micro instructions, and the associated micro instructions are directly executed by a unit or units within the CISC microprocessor.

Turning now to FIG. 6, a block diagram is presented detailing an exemplary band assignment map **600** for fixed and mobile dual band terminals, such as may be employed in the backend server of FIG. 3. The exemplary band assignment map **600** may comprise a plurality of band assignment records **601**, each associated with a corresponding dual band terminal within the restaurant. Each of the band assignment records **601** may comprise a plurality of fields **602**. In the records **601** shown in FIG. 6, there is a terminal ID field TERMID that identifies a corresponding dual band mobile terminal, a band selection field BAND that, in one embodiment, designates that communication with the corresponding mobile terminal occur over convention Wi-Fi only, White-Fi only, or both Wi-Fi and White-Fi. The records **601** also have a plurality of TVWS access point fields TACCPT that may indicate a corresponding plurality of dual band fixed terminal IDs for employment as TVWS access points. Though three TACCPT fields **602** are depicted for each record **601**, other numbers of TACCPT fields **602** are contemplated, as is a function of restaurant configuration. Finally, the records have a TVWS channel field TVWS CHAN, which the backend server terminal update element stores based upon the most recent query to the TVWS database by the TVWS band update element.

The backend server employs entries **601** in the band assignment map **600** to determine whether to direct messages for a given mobile terminal over the COMMS **302** designating a Wi-Fi access point for routing to the mobile terminal, one or more fixed terminals additionally configured as a White-Fi access point for routing to the mobile terminal, or both Wi-Fi access points and White-Fi access points, when the restaurant ordering system is operating in a combined dual band mode for communication with selected mobile terminals. When operating in a combined dual band mode, terminal update logic within the backend server will also divide message data to the selected mobile terminals between White-Fi and Wi-Fi to optimize data throughput utilizing both networks. The terminal update logic within the backend server will also combine message

data from the selected mobile terminals what is received via the White-Fi and Wi-Fi networks.

Now referring to FIG. 7, a block diagram is presented illustrating details of a TVWS routing table **700** according to the present invention, such as may be employed in the fixed terminal of FIG. 4. The routing table **700** may comprise a plurality of mobile terminal records **701**, each of which is associated with a corresponding dual band mobile terminal within the restaurant. The records **701** may comprise a plurality of fields **702** that include a terminal ID field **TERMID**, a communication mode ID field **COMMID**, a TVWS enable field **TVWSEN**, a TVWS access point field **TACCPT**, and a TVWS channel designation field **TVWS CHAN**. The **TERMID** field **702** uniquely identifies the corresponding dual band mobile terminal. Contents of **COMMID** may direct that communications with the designated dual band mobile terminal occur over Wi-Fi only, White-Fi only, or combined Wi-Fi and White-Fi. Contents of **TACCPT** field **702** identifies one or more fixed terminals within the restaurant that may serve as White-Fi access points for the corresponding mobile terminal. Contents of **TVWS CHAN** designate a White-Fi channel for communication with the corresponding mobile terminal.

In one embodiment, the fixed dual band terminal may access the TVWS routing table records **701** to determine whether to intercept messages received over the wired link in order to forward them on to a dual band mobile terminal over White-Fi. For example, if the terminal ID for the fixed terminal matches the **TACCPT** field contents for any record **701**, the fixed terminal may then intercept message from the backend server for those corresponding mobile terminals (identified by contents of **TERMID** fields **702**), and may forward those messages to the corresponding mobile terminals over White-Fi on the TVWS channel indicated by contents of **TVWS CHAN**. The fixed terminal may also receive messages from the corresponding mobile terminals over the TVWS channel and may forward those messages to the backend server over the wired link.

Now turning to FIG. 8, a block diagram is presented depicting a television whitespace (TVWS) communication module **800**, such as may be employed in the dual band mobile terminals of FIGS. 2, 5, and 10. The communication module **800** may comprise a TVWS transceiver **801** that is coupled to a TVWS antenna **806** and to channel select logic **802**. The communication module **800** may further comprise a GPS transceiver **803** that is coupled to a GPS antenna **807**. A message bus **MSG** interconnects the channel select logic **802**, the GPS transceiver **803** and a credit card reader **804**. A link bus **LNK** is coupled to the channel select logic **802**. Both **LNK** and **MSG** are coupled to a connector **805** or connection device. As noted above, the mobile terminals may be disposed as smartphone or tablets with a payment processor integrated within a single housing, where the payment processor comprises a module that is coupled to the smartphone/tablet via a connector. In this case, the module **800** may be replaced with a payment processor module (not shown) that includes only a credit card reader, as would be the case for a delivery terminal. As additionally noted above, the mobile terminals may be disposed as smartphone or tablets with a TVWS/payment processor **800** integrated within a single housing, where the TVWS/payment processor **800** comprises a module that is coupled to the smartphone/tablet via a connector. Alternatively, the connector **805** may comport with an existing port or connector protocol that is employed on a smartphone or tablet, such as, but not limited to, a USB connector or a PCIe connector. Rather than being integrated into a single housing, the TVWS/payment

processor **800** may merely be connected via a cable to the smartphone/tablet, thus providing, say, a legacy mobile terminal with the payment processing and White-Fi communications capabilities.

Though not explicitly shown in the block diagram of FIG. 4, the TVWS/payment processor **800**, may be employed in place of the TVWS **COMMS** element **431** and the TVWS antenna **432**, as is describe above in modular embodiments of the mobile terminal. Accordingly, a legacy fixed terminal, having only conventional wired and wireless communications capabilities over **COMMS 402**, and having an existing port or connector, can easily be upgraded via connection of the module **800** to the existing port of connector to additionally provide for payment processing and White-Fi communications.

The TVWS communication module **800** is provided according to the present invention to allow for a modular adaptation of the mobile terminals of FIGS. 2 and 5 to provide for White-Fi communications and payment processing, or payment processing only. In operation, credit card information is provided over bus **MSG** to payment processing logic within the mobile terminal when a credit card is swiped, dipped, or tapped. In addition, messages to/from a TVWS access point are transmitted/received via the TVWS antenna **806** and transceiver **801** over a TVWS channel provided via **LNK** and designated via the channel select logic **802**. The GPS receiver **803** and antenna **807** are optional, and if employed may be used to provide location information of the mobile terminal within which the module **800** is disposed. Advantageously, the TVWS communications module **800** according to the present invention allows for selective adaptation of table-based mobile terminals to provide for either payment processing only, or payment processing and White-Fi network communications.

Referring now to FIG. 9, a block diagram **500** is presented illustrating exemplary update/status messages according to the present invention that flow between a backend server and fixed and mobile terminals.

An order assignment message **910** transmitted by the server to one or more terminals may comprise fields **901** having a specific terminal ID **TERMID** assigned for a particular order ID **ORDERID** along with a table number **TABLENUM** having a given number of seats **NUMSEATS**. The message **910** may further comprise a **SPECIAL** field **901** via which special requirements (e.g., high chair, wheel chair access) are communicated to the terminal.

An order state change message **920** transmitted from a fixed or mobile terminal to the server may comprise **TERMID** and **ORDERID** fields **901** as described above, along with one or more groups of **ITEM**, **MOD**, and **SEAT #** fields **901**, where contents of the **ITEM** field **901** indicated a menu item ordered for a given seat number at the table along with any modifications to the item number (e.g., rare, no onions, etc.).

A payment state change message **930** transmitted from a terminal to the server may comprise **TERMID** and **ORDERID** fields along with one or more groups of **PMTREQ**, **AMT**, and **TIP** fields **901**, where contents of the **PMTREQ** field **901** indicate a payment type (e.g., cash, MasterCard, etc.), and contents of **AMT** and **TIP** fields **901** indicate amount of payment for the particular payment type along with a tip amount.

An order closeout message **940** may comprise **TERMID** and **ORDER ID** fields **901** as noted above, along with a **CLOSED** field **901**, the contents of which indicate whether the particular order ID is open or closed.

A dual band message **990** may be transmitted from the server to a fixed terminal that is additionally configured as a White-Fi access point. The message **990** may have a TERMID field, the contents of which identify a specific mobile terminal. The message **990** may further include a combine band field COMBINE, the contents of which indicate the communication mode for the specific mobile terminal, namely, Wi-Fi only, White-Fi only, or combined Wi-Fi and White-Fi.

The messages **910**, **920**, **930**, **940**, **990** are not exhaustive of those what may be employed according to the present disclosure but are provided herein to teach further aspects and advantages according to the present invention.

Finally turning to FIG. **10**, a block diagram is presented illustrating a combined band mobile terminal **1000** according to the present invention. The combined band mobile terminal **1000** is virtually the same as the dual band mobile terminal **500** of FIG. **5**, where elements in the combined band mobile terminal operate in the same manner as those like-named elements of the dual band mobile terminal. In addition, the combined band mobile terminal **1000** may comprise message combine logic **1031** in place of the TVWS channel logic **533** of FIG. **5**. In addition to performing the functions described above to the TVWS channel logic **533**, the combine logic **1031** may further combine message data designated for the terminal **1000** that is received over both Wi-Fi and White-Fi channels, and may further split data that is designated for the backend server for transmission over both Wi-Fi and White-Fi.

Although the above embodiments are presented to clearly teach the present invention, other embodiments are contemplated as well. As is disclosed herein, mobile dual band terminals may comprise conventional wireless communications links such as Wi-Fi, cellular (e.g., 3G, 4G, LTE), Bluetooth, etc., and are additionally configured for White-Fi communications. Likewise, fixed terminals according to the present invention may comprise wired communication links (e.g., Ethernet) and conventional wireless communications links such as Wi-Fi, cellular (e.g., 3G, 4G, LTE), Bluetooth, etc., and are additionally configured for White-Fi communications. One embodiment of the fixed terminal of FIG. **4** contemplates its use as a White-Fi access point for communications with designated mobile terminals. However, another embodiment of the present invention comprehends a system of fixed terminals and mobile terminals that couple to one or more stand-alone White-Fi base stations (not shown), where the White-Fi base station functions as White-Fi access points, substantially similar in function to a conventional Wi-Fi access point.

Portions of the present invention and corresponding detailed description are presented in terms of software, or algorithms and symbolic representations of operations on data bits within a computer memory. These descriptions and representations are the ones by which those of ordinary skill in the art effectively convey the substance of their work to others of ordinary skill in the art. An algorithm, as the term is used here, and as it is used generally, is conceived to be a self-consistent sequence of steps leading to a desired result. The steps are those requiring physical manipulations of physical quantities. Usually, though not necessarily, these quantities take the form of optical, electrical, or magnetic signals capable of being stored, transferred, combined, compared, and otherwise manipulated. It has proven convenient at times, principally for reasons of common usage, to refer to these signals as bits, values, elements, symbols, characters, terms, numbers, or the like.

It should be borne in mind, however, that all of these and similar terms are to be associated with the appropriate physical quantities and are merely convenient labels applied to these quantities. Unless specifically stated otherwise, or as is apparent from the discussion, terms such as “processing” or “computing” or “calculating” or “determining” or “displaying” or the like, refer to the action and processes of a computer system, a microprocessor, a central processing unit, or similar electronic computing device, that manipulates and transforms data represented as physical, electronic quantities within the computer system’s registers and memories into other data similarly represented as physical quantities within the computer system memories or registers or other such information storage, transmission or display devices.

Note also that the software implemented aspects of the invention are typically encoded on some form of program storage medium or implemented over some type of transmission medium. The program storage medium may be electronic (e.g., read only memory, flash read only memory, electrically programmable read only memory), random access memory magnetic (e.g., a floppy disk or a hard drive) or optical (e.g., a compact disk read only memory, or “CD ROM”), and may be read only or random access. Similarly, the transmission medium may be metal traces, twisted wire pairs, coaxial cable, optical fiber, or some other suitable transmission medium known to the art. The storage medium may be non-transitory or transitory. The invention is not limited by these aspects of any given implementation.

The particular embodiments disclosed above are illustrative only, and those skilled in the art will appreciate that they can readily use the disclosed conception and specific embodiments as a basis for designing or modifying other structures for carrying out the same purposes of the present invention, and that various changes, substitutions and alterations can be made herein without departing from the scope of the invention as set forth by the appended claims.

What is claimed is:

1. A modular dual band mobile point-of-sale (POS) terminal, comprising:
 - a state processor, configured to queue state changes in one or more order queues disposed within the mobile POS terminal that correspond to orders in a restaurant;
 - an order processor, coupled to said state processor, configured to generate said state changes, and configured to access and transmit said state changes in each one of said one or more order queues to a backend server, from oldest to youngest, when operably connected to a network, wherein said order processor comprises current order state fields corresponding to all of said orders in said restaurant;
 - a conventional wireless communications element, enabling the mobile POS terminal to communicate over a Wi-Fi network within said restaurant; and
 - a detachable television whitespace (TVWS)/payment processing module, enabling the mobile POS terminal to communicate over a White-Fi network within said restaurant;
 wherein, when programmed in a Wi-Fi mode, the mobile POS terminal communicates only over said Wi-Fi network as a selected wireless network, and when programmed in a White-Fi mode, said mobile POS terminal communicates only over said White-Fi network as said selected wireless network.
2. The mobile POS terminal as recited in claim 1, wherein said network comprises the internet and said selected wireless network.

3. The mobile POS terminal as recited in claim 2, wherein said backend server comprises a cloud-based server.

4. The mobile POS terminal as recited in claim 3, wherein the mobile POS terminal and other POS terminals are configured to generate unique ones of said state changes corresponding to a same one of said one or more orders.

5. The mobile POS terminal as recited in claim 4, wherein, when programmed to operate in said Wi-Fi mode, said mobile POS terminal operably connects to said network via one or more Wi-Fi access points that are disposed within said restaurant.

6. The mobile POS terminal as recited in claim 4, wherein, when programmed to operate in said White-Fi mode, said mobile POS terminal operably connects to said network via a White-Fi access point that is disposed within said restaurant.

7. The mobile POS terminal as recited in claim 6, wherein said order processor comprises:

a television whitespace (TVWS) channel assignment table, that provides a designated TVWS channel, previously received from said backend server, which is employed by said communications elements for communications over said White-Fi network.

8. A dual band mobile point-of-sale (POS) terminal, comprising:

a state processor, configured to queue state changes in one or more order queues disposed within the mobile POS terminal that correspond to orders in a restaurant;

a touchpad display/camera circuit, configured to input menu selections and/or payment options;

an order processor, coupled to said state processor, configured to generate said state changes, and configured to access and transmit said state changes in each one of said one or more order queues to a backend server, from oldest to youngest, when operably connected to a network, wherein said order processor comprises current order state fields corresponding to all of said orders in said restaurant;

a conventional wireless communications element, enabling the mobile POS terminal to communicate over a Wi-Fi network within said restaurant; and

a detachable television whitespace (TVWS)/payment processing module, enabling the mobile POS terminal to communicate over a White-Fi network within said restaurant;

wherein, when programmed in a Wi-Fi mode, the mobile POS terminal communicates only over said Wi-Fi network as a selected wireless network, and when programmed in a White-Fi mode, said mobile POS terminal communicates only over said White-Fi network as said selected wireless network.

9. The mobile POS terminal as recited in claim 8, wherein said network comprises the internet and said selected wireless network.

10. The mobile POS terminal as recited in claim 9, wherein said backend server comprises a cloud-based server.

11. The mobile POS terminal as recited in claim 10, wherein the mobile POS terminal and other POS terminals are configured to generate unique ones of said state changes corresponding to a same one of said one or more orders.

12. The mobile POS terminal as recited in claim 11, wherein, when programmed to operate in said Wi-Fi mode,

said mobile POS terminal operably connects to said network via one or more Wi-Fi access points that are disposed within said restaurant.

13. The mobile POS terminal as recited in claim 11, wherein, when programmed to operate in said White-Fi mode, said mobile POS terminal operably connects to said network via a White-Fi access point that is disposed within said restaurant.

14. The mobile POS terminal as recited in claim 13, wherein said order processor comprises:

a television whitespace (TVWS) channel assignment table, that provides a designated TVWS channel, previously received from said backend server, which is employed by said communications elements for communications over said White-Fi network.

15. An order fulfillment method using a dual band mobile point-of-sale (POS) terminal, the method comprising:

queuing state changes in one or more order queues disposed within the mobile POS terminal that correspond to orders in a restaurant;

generating the state changes, and accessing and transmitting the state changes in each one of the one or more order queues to a backend server, from oldest to youngest, when operably connected to a network and maintaining current order state fields corresponding to all of the orders in the restaurant; and

employing conventional wireless communications elements that enable the mobile POS terminal to communicate over a Wi-Fi network;

attaching a detachable television whitespace (TVWS)/payment processing module, enabling the mobile POS terminal to communicate over a White-Fi network within said restaurant;

wherein, when programmed in a Wi-Fi mode, the mobile POS terminal communicates only over the Wi-Fi network as a selected wireless network, and when programmed in a White-Fi mode, the mobile POS terminal communicates only over the White-Fi network as the selected wireless network.

16. The method as recited in claim 15, wherein the network comprises the internet and the selected wireless network.

17. The method as recited in claim 16 wherein the backend server comprises a cloud-based server.

18. The method as recited in claim 17, wherein the mobile POS terminal and other POS terminals generate unique ones of the state changes corresponding to a same one of the one or more orders.

19. The method as recited in claim 18, wherein, when programmed to operate in the Wi-Fi mode, the mobile POS terminal operably connects to the network via one or more Wi-Fi access points that are disposed within the restaurant.

20. The method as recited in claim 18, wherein, when programmed to operate in the White-Fi mode, the mobile POS terminal operably connects to the network via a White-Fi access point that is disposed within the restaurant, and communicates on a designated television whitespace (TVWS) channel that has been previously received from the backend server.