



US011198966B2

(12) **United States Patent**
Hodgell

(10) **Patent No.:** **US 11,198,966 B2**
(45) **Date of Patent:** ***Dec. 14, 2021**

(54) **LAUNDRY TREATING APPLIANCE WITH AN ADJUSTABLE HEIGHT LIFTER**

(71) Applicant: **WHIRLPOOL CORPORATION**,
Benton Harbor, MI (US)

(72) Inventor: **James Hodgell**, Stevensville, MI (US)

(73) Assignee: **Whirlpool Corporation**, Benton Harbor, MI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 181 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **16/695,812**

(22) Filed: **Nov. 26, 2019**

(65) **Prior Publication Data**

US 2020/0095717 A1 Mar. 26, 2020

Related U.S. Application Data

(62) Division of application No. 15/299,957, filed on Oct. 21, 2016, now Pat. No. 10,508,377.

(51) **Int. Cl.**
D06F 37/06 (2006.01)
D06F 58/04 (2006.01)

(52) **U.S. Cl.**
CPC **D06F 37/06** (2013.01); **D06F 58/04** (2013.01)

(58) **Field of Classification Search**
None
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

9,487,907 B2 11/2016 Hapke et al.
2004/0118168 A1 6/2004 Woo et al.
2005/0022565 A1 2/2005 Jung et al.

FOREIGN PATENT DOCUMENTS

EP 2053152 A1 4/2009
EP 2280108 A1 2/2011
JP S5670793 A 6/1981
JP H0433689 A 2/1992
KR 20050082930 A 8/2005
KR 100701174 B1 3/2007

OTHER PUBLICATIONS


European Search Report for Counterpart EP17197549.3, dated Mar. 2, 2018.

Primary Examiner — Rita P Adhlakha
(74) *Attorney, Agent, or Firm* — McGarry Bair PC

(57) **ABSTRACT**

A lifter for a laundry treating appliance having a rotating treating chamber includes a main lifter body configured to mount in the rotating treating chamber. An adjustable element is rotatably mounted to the main lifter body and rotates between first and second positions. When the adjustable element is in the first position, a first profile provides the lifter with a first effective height. When the adjustable element is in the second position, a second profile provides the lifter with a second effective height.

20 Claims, 5 Drawing Sheets






FIG. 1




FIG. 2A




FIG. 2B




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B

LAUNDRY TREATING APPLIANCE WITH AN ADJUSTABLE HEIGHT LIFTER

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a divisional application of U.S. patent application Ser. No. 15/299,957, filed Oct. 21, 2016, and now U.S. Pat. No. 10,508,377, issued Dec. 17, 2019, which is incorporated herein by reference in its entirety.

BACKGROUND

A horizontal axis washing machine typically has a rotatable drum that rotates about a generally horizontal axis and defines a treating chamber for receiving the laundry. A plurality of lifters can be disposed on an inner surface of the drum to lift the laundry load received in the treating chamber while the drum rotates. The lifter design imparts mechanical energy to the laundry primarily by lifting/dropping the laundry items as the drum is rotated. The mechanical energy is used to clean the laundry items during a wash cycle.

BRIEF SUMMARY

One aspect of the present disclosure relates to a lifter for a laundry treating appliance having a rotating treating chamber, the lifter comprising a main lifter body configured to mount in the rotating treating chamber, and an adjustable element rotatably mounted to the main lifter body and rotating between first and second positions, the adjustable element having first and second profiles and a maximum projection, wherein when the adjustable element is in the first position, the first profile provides the lifter with a first effective height defined by the maximum projection, and when the adjustable element is in the second position, the second profile provides the lifter with a second effective height, which is less than the first effective height, and further wherein the maximum projection is at least one of flush with a sidewall of the main lifter body or received within an interior of the main lifter body when the adjustable element is in the second position.

Another aspect of the present disclosure relates to a lifter for a laundry treating appliance having a rotating treating chamber, the lifter comprising a main lifter body configured to mount in the rotating treating chamber, and an adjustable element rotatably mounted to the main lifter body and rotating between first and second positions, the adjustable element having a main body and a ridge projecting radially outwardly from the main body, wherein when the adjustable element is in the first position, the lifter is provided with a first profile having a first effective height defined by the ridge of the adjustable element, and when the adjustable element is in the second position, the lifter is provided with a second profile having a second effective height defined by the main body of the adjustable element, wherein the second effective height is less than the first effective height, and further wherein the ridge is at least one of flush with a sidewall of the main lifter body or received within an interior of the main lifter body when the adjustable element is in the second position.

Yet another aspect of the present disclosure relates to a lifter for a laundry treating appliance having a rotating treating chamber, the lifter comprising a main lifter body configured to mount in the rotating treating chamber, and an adjustable element rotatably mounted to the main lifter body and rotating about a rotation axis between first and second

positions, the adjustable element comprising an asymmetrical body having first and second profiles and a maximum projection, wherein when the adjustable element is in the first position, the first profile provides the lifter with a first effective height defined by the maximum projection, and when the adjustable element is in the second position, the second profile provides the lifter with a second effective height, which is less than the first effective height, and further wherein the maximum projection is at least one of flush with a sidewall of the main lifter body or received within an interior of the main lifter body when the adjustable element is in the second position.

BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings:

FIG. 1 is a front view of a horizontal axis laundry treating appliance incorporating aspects of the present disclosure, with a door of the laundry treating appliance shown in an open position to better see lifters within a drum.

FIG. 2A is a perspective view of a lifter in a first height position, which happens to be an extended height.

FIG. 2B is a perspective view of the lifter in FIG. 2A in a second position, which happens to be a reduced height.

FIG. 3A is a cross-sectional view of the lifter in FIG. 2A in the first position.

FIG. 3B is a cross-sectional view of the lifter in FIG. 2B in the second position.

FIG. 4A is a perspective view of a second aspect of the present disclosure, in which a lifter is in the first position.

FIG. 4B is a perspective view of the lifter in FIG. 4A in the second position.

FIG. 5A is a cross-sectional view of the lifter in FIG. 4A in the first position.

FIG. 5B is a cross-sectional view of the lifter in FIG. 4B in the second position.

DETAILED DESCRIPTION

FIG. 1 shows a laundry treating appliance in accordance with the present disclosure, which happens to be a horizontal axis automatic clothes washing machine 10. Although much of the remainder of this application will focus on the aspect of the horizontal axis automatic clothes washing machine 10, the present disclosure encompasses other environments, including other horizontal axis laundry treating appliances such as a laundry dryer. Also, while illustrated as a front-loading, horizontal axis laundry treating appliance, other loading configurations, such as top-loading are contemplated.

Further, other axes of rotation are contemplated. A vertical axis laundry treating appliance is contemplated in addition to the illustrated horizontal axis laundry treating appliance. For purposes of this description, the terms horizontal axis and vertical axis are used to represent the general orientation of the axis of rotation and is not meant to be limited to a perfectly horizontal or vertical axis of rotation. More accurately, the terms horizontal axis of rotation or vertical axis of rotation, when used to identify the type of laundry treating appliance, are more accurately used to describe the primary mechanism by which mechanical energy is imparted to the laundry. The horizontal axis washing machine imparts mechanical energy primarily by tumbling the laundry within the drum. That is, rotation of the drum lifts and then drops the laundry. This lifting/dropping imparts mechanical energy to the laundry. The vertical axis washing machine imparts mechanical energy via a clothes mover, such as an

agitator, impeller, pulsator, auger, etc., which is rotated within the basket to effect movement of liquid in the basket or directly impact the laundry. While a laundry container is normally referred to as a drum for a horizontal axis machine and a basket for a vertical axis machine, for this disclosure, unless otherwise stated, drum and basket are interchangeable.

The washing machine **10** shares many features of a conventional automated clothes washer, which will not be described in detail herein except as necessary for a complete understanding of the illustrative aspects in accordance with the present disclosure. Examples of articles include, but are not limited to, a hat, a scarf, a glove, a sweater, a blouse, a shirt, a pair of shorts, a dress, a sock, and a pair of pants, a shoe, an undergarment, and a jacket. One or more articles form a laundry load.

The washing machine comprises a cabinet **18** that defines an interior. The cabinet **18** can be a housing having a chassis and/or a frame, defining the interior, enclosing components typically found in a conventional washing machine, such as motors, pumps, fluid lines, controls, sensors, transducers, and the like. Such components will not be described further herein except as necessary for a complete understanding of the disclosure.

A tub **16** is located within the interior of the cabinet **18** and defines a liquid-holding chamber in which liquid for the treating cycle is held during operation. A drum **12** is located within the tub **16** and can be rotatably mounted to the tub **16** or the cabinet **18**. A suspension system (not shown) suspends at least one of the tub **16** and drum **12** relative to the cabinet **18**.

The drum **12** defines a treating chamber **14** for receiving the laundry and rotates about a generally horizontal axis. The drum **12** can include a plurality of perforations (not shown) such that liquid can flow between the tub **16** and the drum **12** through the perforations.

A door **24** can be movably mounted to the cabinet **18** to selectively close an opening **22** to the treating chamber **14**. The door **24** can have a handle **32** for pivotally opening the door about a hinge **34**.

The washing machine **10** can also be provided with a dispenser **20** for dispensing treating chemistry to the treating chamber **14** for use in treating the laundry according to a cycle of operation. Non-limiting examples of treating chemistries that can be dispensed by the dispenser **20** during a cycle of operation include one or more of the following: water, detergents, softeners, bleach, rinse aids, surfactants, enzymes, fragrances, stiffness/sizing agents, wrinkle releasers/reducers, antistatic or electrostatic agents, stain repellants, water repellants, energy reduction/extraction aids, antibacterial agents, medicinal agents, vitamins, moisturizers, shrinkage inhibitors, and color fidelity agents, and combinations thereof.

At least one or more lifters **50** can be provided within the drum **12**. The lifters **50** can extend from an inner surface of the drum and are typically, but not necessarily, equally spaced about the inner surface of the drum **12**. The lifters **50** can be configured as a separate member to be installed in the drum **12** or integrally made with the drum **12**. The lifter **50** may extend in parallel with a central axis of the drum **12**. The lifter **50** is preferably formed of a material that is resistant against corrosion and abrasion due to water and chemical detergent. The lifter **50** can be coated with antimicrobial coatings with anti-staining properties to protect the surface and laundry articles from microbial contamination after continuous use. The lifter **50** is adjustable to extend at varying heights relative to the drum **12**.

The varying height of one of the lifters **50**, is best seen with respect to FIG. 2A, which shows the lifter **50** at a maximum height and FIG. 2B, which shows the lifter **50** at a minimum height. It is contemplated that the lifter **50** can be fixedly positioned at any location between the maximum and minimum height positions, including the maximum and minimum heights. For purposes of simplicity only two such positions, first and second positions, will be described and correspond to the maximum and minimum heights, with it being understood many more positions/heights are contemplated.

Referring to FIG. 2A, the lifter **50** includes a housing **51** to which is moveably mounted an adjustable element **52**. While any type of movable mounting is contemplated, the adjustable element **52** is illustrated as being rotatably mounted to the housing **51** for rotation about a rotation axis **57**.

The lifter **50** further comprises a lock **53** fixing the position of the adjustable element **52** in at least one of the first and second positions. The lock **53** comprises an actuator **54**, which can be conveniently located on a portion of the lifter **50** facing the access opening **22** of the treating chamber **14**. The lock **53** can be in the form of a conventional detent mechanism to prevent unexpected rotary movement of the adjustable element in the first and second positions. Any other type of known lock can be used.

Referring to FIG. 3A, the adjustable element **52** comprises a main body **56** and a ridge **58** projecting from the main body **56**. The adjustable element **52** has an asymmetrical body **61** wherein the asymmetrical body **61** comprises a maximum projection **55** from the drum **12**, which corresponds to the ridge **58** being rotated to the first position, which defines the first effective height. As shown in FIG. 3B, a lesser projection **59** of the asymmetrical body **61** relative to the drum **12** occurs when the ridge **58** is rotated to the second position, with the projection **59** defining a second height in the second position that is less than the first height in the first position.

Still referring to FIG. 3B, conveniently, the shape of the body **56**, including the ridge **58**, is such that the adjustable element is complementary in shape to the lifter housing **51** in the second position. The complementary shapes provide for a flush receipt of the ridge **58** with the housing **51** in the second position to prevent the ridge **58** from inadvertently catching laundry items in the second position. Thus, the first position for the adjustable element **52** can be thought of as a use position and the second position can be thought of as a stored position.

A second aspect of the lifter **150** is illustrated in FIG. 4A. The second aspect is similar to the first aspect, with it being understood that the description of the like parts of the first aspect applies to the additional aspects, unless otherwise noted. Thus, numerals for elements of the second aspect similar to the first aspect will be increased by 100.

The second aspect of the lifter **150** is similar to the first aspect **50**, in that it comprises an adjustable element **152** rotatable about a rotation axis **157** and a locking mechanism **153** with an actuator **154**. The adjustable element **152** is rotatably mounted to the lifter housing **151** and rotates between the first and second positions having first and second effective height as shown in FIGS. 4A and 4B respectively. The lifter **150** differs in that the ridge **158** projected from the main body **156** of the adjustable element **152** is shown as having a rectangular profile. The lifter **150** also differs in that the ridge **158** can be received within an interior compartment **160** of the lifter **150** when the adjustable element **152** is in the second position.

5

FIGS. 5A and 5B illustrate the movement of the adjustable element 152 from the first to the second positions, respectively, with FIG. 5B illustrating the receipt of the ridge 158 within the interior compartment 160. In FIG. 5A the ridge 158 with a rectangular profile defines the maximum height of the lifter 150 when the adjustable element 152 is rotated to the first position. As shown in FIG. 5B, the ridge 158 of the adjustable element 152 is received within an interior compartment 160 of the lifter 150 when the adjustable element 152 is in the second position. In an alternative aspect, the lifter 150 can be configured to have an interior compartment 160 to accommodate the varying profile of the ridge 158 while still retaining a flush appearance from the exterior when the adjustable element 152 is in the second position.

The ease of adjustability of each lifter height and profile allow the user to adjust the amount of mechanical energy by lifting/dropping, collision and friction imparted to the laundry items as the amount of mechanical energy is related to the height of the lifter. A heavy-duty load can benefit from a lifter 150 setting with a higher protrusion and edged profile to create more friction during a washing cycle. A delicate load can benefit from a lifter 150 setting with a lower protrusion and smoother profile to prevent any damage done to the laundry during a washing cycle. Furthermore, the adjustable element in the second position being one of flush with a sidewall of the lifter or received within an interior of the lifter provide an appearance that is clean and aesthetically pleasing to the consumers.

The lifter 50, while variable in height, can be used alone or in combination with other lifters that are fixed height or variable in height.

To the extent not already described, the different features and structures of the various aspects can be used in combination with each other as desired. That one feature cannot be illustrated in all of the aspects is not meant to be construed that it cannot be, but is done for brevity of description. Thus, the various features of the different aspects can be mixed and matched as desired to form new aspects, whether or not the new aspects are expressly described. Combinations or permutations of features described herein are covered by this disclosure.

Although illustrative aspects of the present disclosure have been shown and described, it would be appreciated by those skilled in the art that changes may be made in these illustrative aspects without departing from the principles and spirit of the present disclosure, the scope of which is defined in the claims and their equivalents.

What is claimed is:

1. A lifter for a laundry treating appliance having a rotating treating chamber, the lifter comprising:
a main lifter body configured to mount in the rotating treating chamber; and
an adjustable element rotatably mounted to the main lifter body and rotating between first and second positions, the adjustable element having first and second profiles and a maximum projection;
wherein when the adjustable element is in the first position, the first profile provides the lifter with a first effective height defined by the maximum projection, and when the adjustable element is in the second position, the second profile provides the lifter with a second effective height, which is less than the first effective height, and further wherein the maximum projection is at least one of flush with a sidewall of the

6

main lifter body or received within an interior of the main lifter body when the adjustable element is in the second position.

2. The lifter of claim 1 wherein the adjustable element comprises a main body and a ridge projecting from the main body.

3. The lifter of claim 2 wherein the maximum projection comprises the ridge.

4. The lifter of claim 2 wherein in the first position, the ridge defines a maximum height of the lifter.

5. The lifter of claim 2 wherein in the second position, the ridge lies below a maximum height of the lifter.

6. The lifter of claim 1 wherein the adjustable element comprises an asymmetrical body rotatable about a rotation axis.

7. The lifter of claim 6 wherein the asymmetrical body defines the maximum projection of the adjustable element radially furthest from the rotation axis.

8. The lifter of claim 7 wherein the asymmetrical body further defines a lesser projection radially closer to the rotation axis than the maximum projection, and in the second position the lesser projection defines the second effective height.

9. The lifter of claim 1 further comprising a lock fixing the adjustable element in at least one of the first and second positions.

10. The lifter of claim 9 wherein the lock comprises an actuator located on an end of the lifter.

11. A lifter for a laundry treating appliance having a rotating treating chamber, the lifter comprising:

a main lifter body configured to mount in the rotating treating chamber; and

an adjustable element rotatably mounted to the main lifter body and rotating between first and second positions, the adjustable element having a main body and a ridge projecting radially outwardly from the main body;

wherein when the adjustable element is in the first position, the lifter is provided with a first profile having a first effective height defined by the ridge of the adjustable element, and when the adjustable element is in the second position, the lifter is provided with a second profile having a second effective height defined by the main body of the adjustable element, wherein the second effective height is less than the first effective height, and further wherein the ridge is at least one of flush with a sidewall of the main lifter body or received within an interior of the main lifter body when the adjustable element is in the second position.

12. The lifter of claim 11 further comprising a lock fixing the adjustable element in at least one of the first and second positions.

13. The lifter of claim 12 wherein the lock comprises an actuator located on an end of the lifter.

14. The lifter of claim 11 wherein the ridge defines a radially outermost maximum projection of the adjustable element.

15. The lifter of claim 11 wherein the adjustable element comprises an asymmetrical body rotatable about a rotation axis.

16. The lifter of claim 15 wherein the asymmetrical body comprises the ridge defining a maximum projection of the adjustable element radially furthest from the rotation axis.

17. The lifter of claim 16 wherein the asymmetrical body comprises the main body defining a lesser projection radially closer to the rotation axis than the maximum projection, and in the second position the lesser projection defines the second effective height.

- 18.** A lifter for a laundry treating appliance having a rotating treating chamber, the lifter comprising:
a main lifter body configured to mount in the rotating treating chamber; and
an adjustable element rotatably mounted to the main lifter 5
body and rotating about a rotation axis between first and second positions, the adjustable element comprising an asymmetrical body having first and second profiles and a maximum projection;
wherein when the adjustable element is in the first posi- 10
tion, the first profile provides the lifter with a first effective height defined by the maximum projection, and when the adjustable element is in the second position, the second profile provides the lifter with a second effective height, which is less than the first 15
effective height, and further wherein the maximum projection is at least one of flush with a sidewall of the main lifter body or received within an interior of the main lifter body when the adjustable element is in the second position. 20
- 19.** The lifter of claim **18** further comprising a lock fixing the adjustable element in at least one of the first and second positions.
- 20.** The lifter of claim **19** wherein the lock comprises an actuator located on an end of the lifter. 25

* * * * *