



US011203421B1

(12) **United States Patent**
Knoll et al.

(10) **Patent No.:** **US 11,203,421 B1**
(45) **Date of Patent:** **Dec. 21, 2021**

(54) **PASSIVE TIP GAP MANAGEMENT SYSTEMS FOR DUCTED AIRCRAFT**

(71) Applicant: **Textron Innovations Inc.**, Providence, RI (US)

(72) Inventors: **Jonathan Andrew Knoll**, Burseson, TX (US); **George Matthew Thompson**, Lewisville, TX (US); **Nicholas Ralph Carlson**, Dallas, TX (US)

(73) Assignee: **Textron Innovations Inc.**, Providence, RI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 50 days.

(21) Appl. No.: **16/907,087**

(22) Filed: **Jun. 19, 2020**

(51) **Int. Cl.**
B64C 11/00 (2006.01)
B64C 27/46 (2006.01)
B64C 27/59 (2006.01)
B64C 29/00 (2006.01)

(52) **U.S. Cl.**
CPC **B64C 27/59** (2013.01); **B64C 11/001** (2013.01); **B64C 11/003** (2013.01); **B64C 27/463** (2013.01); **B64C 29/0033** (2013.01)

(58) **Field of Classification Search**
CPC **B64C 27/59**; **B64C 27/463**; **B64C 27/20**; **B64C 11/001**; **B64C 11/003**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,464 A *	6/1850	Timby	B64C 11/003 416/87
3,814,351 A *	6/1974	Bielawa	B64C 27/10 244/17.19
5,566,907 A *	10/1996	Marze	B64C 27/82 244/1 N
7,004,427 B2 *	2/2006	Gerbino	B64C 27/30 244/17.25
8,636,246 B2	1/2014	Robertson et al.	
8,640,984 B2	2/2014	Kebrle et al.	
9,809,304 B1 *	11/2017	Beckman	B64C 39/064
10,106,253 B2	10/2018	Groninga et al.	
2018/0362160 A1	12/2018	Groninga et al.	
2020/0089227 A1 *	3/2020	LeGrand	B64C 11/46

* cited by examiner


Primary Examiner — Brian M O'Hara

(74) *Attorney, Agent, or Firm* — Lawrence Youst PLLC

(57) **ABSTRACT**

A prop rotor system for a ducted aircraft includes a duct and prop rotor blades surrounded by the duct. Each prop rotor blade is rotatable about a respective pitch change axis. The prop rotor blades are configured to change collective pitch about the pitch change axes. The prop rotor blades are extendable along the pitch change axes into various positions including a retracted position and an extended position. The prop rotor blades change between the retracted position and the extended position based on the collective pitch of the prop rotor blades, thereby controlling a tip gap between the prop rotor blades and the duct.

20 Claims, 23 Drawing Sheets






FIG. 1B




FIG. 1A




FIG. 1D




FIG. 1C




FIG. 1F




FIG. 1E




FIG. 2




FIG. 3




FIG. 4




FIG. 5A




FIG. 5B




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D




FIG. 6E




FIG. 6F




FIG. 6G




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 7D




FIG. 7E




FIG. 7F












FIG. 7G








FIG. 9A




FIG. 9B

FIG. 9C




FIG. 10A




FIG. 10B




FIG. 10C




FIG. 10D




FIG. 10E




FIG. 11D




FIG. 11C




FIG. 11B




FIG. 11A




FIG. 11E




FIG. 11F




FIG. 11G




FIG. 11H




FIG. 12C




FIG. 12D




FIG. 12A




FIG. 12B




FIG. 12E




FIG. 12F




FIG. 13A




FIG. 13B




FIG. 13C




FIG. 13D




FIG. 13E




FIG. 14A




FIG. 14C




FIG. 14B




FIG. 14D




FIG. 14B

1

**PASSIVE TIP GAP MANAGEMENT SYSTEMS
FOR DUCTED AIRCRAFT**

TECHNICAL FIELD OF THE DISCLOSURE

The present disclosure relates, in general, to aircraft having ducted rotor systems and, in particular, to tip gap monitoring and control systems that actively, semi-actively or passively manage the tip gap between the rotor blades and duct of a ducted rotor system.

BACKGROUND

Ducted rotor systems offer several benefits over open rotor systems in which the rotor blades are exposed. For example, ducted rotor systems emit less noise and are therefore preferred when a reduced noise environment is desired, such as during air reconnaissance, clandestine operations or flight in urban airspace. Ducts increase safety for ground personnel and crew by preventing contact with an operating rotor. Openly exposed rotors can lead to blade tip thrust losses during flight. By reducing rotor blade tip losses, a ducted rotor system is more efficient in producing thrust than an open rotor system of similar diameter, especially at low speed and high static thrust levels. Also, the thrust vectoring capabilities of open rotor systems are limited as is the use of pressure differentials to augment thrust.

The performance of a ducted rotor system is sensitive to the tip gap between the blade tips and the duct. Ducted rotor systems are designed to have a minimum tip gap throughout the flight envelope to maximize duct performance. For example, ducted rotor systems are most efficient in hover when the tip gap is as small as possible. Conversely, the tip gap must be large enough to avoid collisions between the rotor blades and the duct during operation. Furthermore, the tip gap of a ducted rotor system changes during flight as the duct, rotor blades or stators deform or deflect under load in response to flight conditions. For example, on tiltrotor aircraft utilizing ducted proprotor systems, the ducted proprotor systems experience high loads in the transition between the vertical takeoff and landing flight mode and the forward flight mode. These high transition loads can deform the duct, proprotor blades, stators or other parts of the ducted proprotor system, which affects the tip gap. Unexpected collisions with ducted rotor systems during flight, such as bird strikes, also affect the tip gap. Current ducted aircraft are unable to monitor, manage and control the changing tip gap of their ducted rotors, which necessitates shortening the rotor blades more than necessary to prevent collisions between the rotor blades and duct, which in turn leads to performance degradation. Accordingly, a need has arisen for tip gap monitoring and control systems that actively, semi-actively or passively enable the rotor blades of a ducted rotor system to be as close as possible to the duct while mitigating the risk of collision between the rotor blades and the duct.

SUMMARY

In a first aspect, the present disclosure is directed to a proprotor system for a ducted aircraft including a duct and proprotor blades surrounded by the duct. Each proprotor blade is rotatable about a respective pitch change axis. The proprotor blades are configured to change collective pitch about the pitch change axes. The proprotor blades are extendable along the pitch change axes into various positions including a retracted position and an extended position. The proprotor blades change between the retracted position

2

and the extended position based on the collective pitch of the proprotor blades, thereby controlling a tip gap between the proprotor blades and the duct.

In some embodiments, the proprotor blades may be rotatable between various collective pitches about the pitch change axes including a higher collective pitch and a lower collective pitch, the proprotor blades in one of the retracted position or the extended position at the higher collective pitch and the other of the retracted position or the extended position at the lower collective pitch. In certain embodiments, the proprotor blades may be in the retracted position at the higher collective pitch and in the extended position at the lower collective pitch. In other embodiments, the proprotor blades may be in the extended position at the higher collective pitch and in the retracted position at the lower collective pitch. In some embodiments, the distal end of each of the proprotor blades may include a blade tip extension movable between the retracted position and the extended position.

In certain embodiments, each of the proprotor blades may include a main body having an open distal end, the blade tip extensions slidably coupled to the open distal ends of the main bodies of the proprotor blades. In such embodiments, the blade tip extensions may be at least partially retracted into the main bodies of the proprotor blades in the retracted position and at least partially extended from the open distal ends of the main bodies of the proprotor blades in the extended position, thereby increasing the tip gap in the retracted position. In certain embodiments, each of the proprotor blades may include a main body having a distal end, the blade tip extensions hingeably coupled to the distal ends of the main bodies of the proprotor blades. In such embodiments, the blade tip extensions may be substantially coplanar with the main bodies of the proprotor blades in the extended position and form an angle of less than 180 degrees with the main bodies of the proprotor blades in the retracted position, thereby increasing the tip gap in the retracted position.

In some embodiments, the proprotor system may include a pitch-span converter configured to convert the collective pitch of the proprotor blades about the pitch change axes into the position of the blade tip extensions. In certain embodiments, the proprotor system may include a pitch control assembly coupled to the proprotor blades to change the collective pitch of the proprotor blades about the pitch change axes, the pitch-span converter coupled to the pitch control assembly and one or more of the blade tip extensions. In some embodiments, the proprotor system may include a proprotor hub interconnecting the proprotor blades, the pitch-span converter disposed at the proprotor hub. In certain embodiments, the pitch-span converter may include a helical threaded screw. In some embodiments, the pitch-span converter may include a plurality of pitch-span converters, each pitch-span converter configured to convert the collective pitch of the proprotor blades about the pitch change axes into the position of a respective blade tip extension. In certain embodiments, each pitch-span converter may be coupled to a respective blade tip extension by a spanwise link disposed inside a respective proprotor blade.

In some embodiments, the proprotor system may include springs, each spring biasing a respective blade tip extension into the extended position. In such embodiments, each spanwise link may include a cable configured to pull a respective blade tip extension into the retracted position against the bias of a respective spring. In certain embodiments, the proprotor system may include a proprotor hub and a plurality of tension-torsion straps, each proprotor

3

blade coupled to the proprotor hub via a respective tension-torsion strap, the tension-torsion straps twistable between a wound position and an unwound position in response to the collective pitch of the proprotor blades. In such embodiments, the proprotor blades may be in the extended position when the tension-torsion straps are in the unwound position and the retracted position when the tension-torsion straps are in the wound position. In some embodiments, the proprotor blades may be rotatable between various collective pitches about the pitch change axes including a higher collective pitch and a lower collective pitch, the tension-torsion straps in one of the wound position or the unwound position at the higher collective pitch and the other of the wound position or the unwound position at the lower collective pitch.

In a second aspect, the present disclosure is directed to a rotorcraft including a fuselage and a proprotor system coupled to the fuselage. The proprotor system includes a duct and proprotor blades surrounded by the duct. Each proprotor blade is rotatable about a respective pitch change axis. The proprotor blades are configured to change collective pitch about the pitch change axes. The proprotor blades are extendable along the pitch change axes into various positions including a retracted position and an extended position. The proprotor blades change between the retracted position and the extended position based on the collective pitch of the proprotor blades, thereby controlling a tip gap between the proprotor blades and the duct.

In some embodiments, the rotorcraft may be convertible between a vertical takeoff and landing flight mode and a forward flight mode, the proprotor blades having a lower collective pitch in the vertical takeoff and landing flight mode and a higher collective pitch in the forward flight mode. In such embodiments, the proprotor blades may be configured to change between the retracted position and the extended position based on the flight mode of the rotorcraft. In certain embodiments, the proprotor blades may change into the extended position in the forward flight mode. In other embodiments, the proprotor blades may change into the retracted position in the forward flight mode. In some embodiments, the proprotor blades may be extendable along the pitch change axes into various intermediate positions between the retracted position and the extended position based on the collective pitch of the proprotor blades.

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the features and advantages of the present disclosure, reference is now made to the detailed description along with the accompanying figures in which corresponding numerals in the different figures refer to corresponding parts and in which:

FIGS. 1A-1F are schematic illustrations of a ducted aircraft having a tip gap monitoring and control system in accordance with embodiments of the present disclosure;

FIG. 2 is a block diagram of a propulsion and control system for a ducted aircraft having a tip gap monitoring and control system in accordance with embodiments of the present disclosure;

FIG. 3 is a block diagram of a control system for a ducted aircraft having a tip gap monitoring and control system in accordance with embodiments of the present disclosure;

FIG. 4 is a schematic illustration of a tip gap monitoring and control system for a ducted aircraft in accordance with embodiments of the present disclosure;

FIGS. 5A-5B are front views of a tip gap monitoring system utilizing distance sensors in accordance with embodiments of the present disclosure;

4

FIGS. 6A-6G are various views of a tip gap control system utilizing active blade tips in accordance with embodiments of the present disclosure;

FIGS. 7A-7G are various views of a tip gap control system utilizing active inner duct surfaces in accordance with embodiments of the present disclosure;

FIGS. 8A-8H are schematic illustrations of a ducted aircraft having a tip gap monitoring and control system in a sequential flight operating scenario in accordance with embodiments of the present disclosure;

FIGS. 9A-9C are flowcharts of various methods for monitoring and controlling the tip gap for a ducted aircraft in accordance with embodiments of the present disclosure;

FIGS. 10A-10E are various views of a passive tip gap control system for a ducted aircraft utilizing blade tip extensions in accordance with embodiments of the present disclosure;

FIGS. 11A-11H are schematic illustrations of a ducted aircraft having a passive tip gap control system in a sequential flight operating scenario in accordance with embodiments of the present disclosure;

FIGS. 12A-12F are various views of a passive tip gap control system for a ducted aircraft utilizing tension-torsion straps in accordance with embodiments of the present disclosure;

FIGS. 13A-13E are various views of a proprotor system having sacrificial blade tips in accordance with embodiments of the present disclosure; and

FIGS. 14A-14D are various views of a proprotor system having sacrificial blade tips including a frangible lattice structure in accordance with embodiments of the present disclosure.

DETAILED DESCRIPTION

While the making and using of various embodiments of the present disclosure are discussed in detail below, it should be appreciated that the present disclosure provides many applicable inventive concepts, which can be embodied in a wide variety of specific contexts. The specific embodiments discussed herein are merely illustrative and do not delimit the scope of the present disclosure. In the interest of clarity, all features of an actual implementation may not be described in this specification. It will of course be appreciated that in the development of any such actual embodiment, numerous implementation-specific decisions must be made to achieve the developer's specific goals, such as compliance with system-related and business-related constraints, which will vary from one implementation to another. Moreover, it will be appreciated that such a development effort might be complex and time-consuming but would nevertheless be a routine undertaking for those of ordinary skill in the art having the benefit of this disclosure.

In the specification, reference may be made to the spatial relationships between various components and to the spatial orientation of various aspects of components as the devices are depicted in the attached drawings. However, as will be recognized by those skilled in the art after a complete reading of the present disclosure, the devices, members, apparatuses, and the like described herein may be positioned in any desired orientation. Thus, the use of terms such as "above," "below," "upper," "lower" or other like terms to describe a spatial relationship between various components or to describe the spatial orientation of aspects of such components should be understood to describe a relative relationship between the components or a spatial orientation of aspects of such components, respectively, as the devices

described herein may be oriented in any desired direction. As used herein, the term “coupled” may include direct or indirect coupling by any means, including by mere contact or by moving and/or non-moving mechanical connections.

Referring to FIGS. 1A-1F in the drawings, various views of a ducted aircraft **10** having a tip gap monitoring and control system are depicted. FIGS. 1A, 1C and 1E depict ducted aircraft **10** in a vertical takeoff and landing (VTOL) orientation wherein the proprotor systems provide thrust-borne lift. FIGS. 1B, 1D and 1F depict ducted aircraft **10** in a forward flight orientation wherein the proprotor systems provide forward thrust with the forward airspeed of ducted aircraft **10** providing wing-borne lift, thereby enabling ducted aircraft **10** to have a high speed and/or high endurance forward flight mode. Ducted aircraft **10** has a longitudinal axis **10a** that may also be referred to as the roll axis, a lateral axis **10b** that may also be referred to as the pitch axis and a vertical axis **10c** that may also be referred to as the yaw axis, as best seen in FIGS. 1A-1B. As illustrated, when longitudinal axis **10a** and lateral axis **10b** are both in a horizontal plane that is normal to the local vertical in the earth's reference frame, ducted aircraft **10** has a level flight attitude.

In the illustrated embodiment, ducted aircraft **10** has an airframe **12** including a fuselage **14**, wings **16a**, **16b** and a tail assembly **18**. Wings **16a**, **16b** have an airfoil cross-section that generates lift responsive to the forward airspeed of ducted aircraft **10**. In the illustrated embodiment, wings **16a**, **16b** are straight wings with a tapered leading edge. It will be appreciated, however, that wings **16a**, **16b** may be of a wide variety of shapes, sizes and configurations, depending upon the performance characteristics desired. In the illustrated embodiment, wings **16a**, **16b** include ailerons to aid in roll and/or pitch control of ducted aircraft **10** during forward flight. Tail assembly **18** is depicted as a vertical fin, or stabilizer, that may include one or more rudders to control the yaw of ducted aircraft **10** during forward flight. In other embodiments, tail assembly **18** may have two or more vertical fins and/or a horizontal stabilizer that may include one or more elevators to control the pitch of ducted aircraft **10** during forward flight. It will be appreciated, however, that tail assembly **18** may be of a wide variety of shapes, sizes and configurations, depending upon the performance characteristics desired.

In the illustrated embodiment, ducted aircraft **10** includes four proprotor systems forming a two-dimensional distributed thrust array that is coupled to airframe **12**. As used herein, the term “two-dimensional thrust array” refers to a plurality of thrust generating elements that occupy a two-dimensional space in the form of a plane. As used herein, the term “distributed thrust array” refers to the use of multiple thrust generating elements, each producing a portion of the total thrust output. The thrust array of ducted aircraft **10** includes a forward-port proprotor system **20a**, a forward-starboard proprotor system **20b**, an aft-port proprotor system **20c** and an aft-starboard proprotor system **20d**, which may be referred to collectively as proprotor systems **20**. Forward-port proprotor system **20a** and forward-starboard proprotor system **20b** are each rotatably mounted to a shoulder portion of fuselage **12** at a forward station thereof. Aft-port proprotor system **20c** is rotatably mounted on the outboard end of wing **16a**. Aft-starboard proprotor system **20d** is rotatably mounted on the outboard end of wing **16b**. Proprotor systems **20** may each include at least one variable speed electric motor and a speed controller configured to provide variable rotor speeds.

When ducted aircraft **10** is operating in the VTOL flight mode and supported by thrust-borne lift, proprotor systems **20** each have a generally horizontal position such that the proprotor assemblies are rotating in generally the same horizontal plane, as best seen in FIGS. 1C and 1E. When ducted aircraft **10** is operating in the forward flight mode and supported by wing-borne lift, proprotor systems **20** each have a generally vertical position with the forward proprotor assemblies rotating generally in a forward vertical plane and the aft proprotor assemblies rotating generally in an aft vertical plane, as best seen in FIG. 1F. Transitions between the VTOL flight mode and the forward flight mode of ducted aircraft **10** are achieved by changing the angular positions of proprotor systems **20** between their generally horizontal positions and their generally vertical positions as discussed herein.

Ducted aircraft **10** may include a liquid fuel powered turbo-generator that includes a gas turbine engine and an electric generator. Preferably, the electric generator charges an array of batteries that provides power to the electric motors of proprotor systems **20** via a power management system. In other embodiments, the turbo-generator may provide power directly to the power management system and/or the electric motors of proprotor systems **20**. In yet other embodiments, proprotor systems **20** may be mechanically driven by the power plant of ducted aircraft **10** via suitable gearing, shafting and clutching systems.

Ducted aircraft **10** has a fly-by-wire control system that includes a flight control computer **22** that is preferably a redundant digital flight control system including multiple independent flight control computers. Flight control computer **22** preferably includes non-transitory computer readable storage media including a set of computer instructions executable by one or more processors for controlling the operation of ducted aircraft **10**. Flight control computer **22** may be implemented on one or more general-purpose computers, special purpose computers or other machines with memory and processing capability. Flight control computer **22** may include one or more memory storage modules including random access memory, non-volatile memory, removable memory or other suitable memory. Flight control computer **22** may be a microprocessor-based system operable to execute program code in the form of machine-executable instructions. Flight control computer **22** may be connected to other computer systems via a suitable communications network that may include both wired and wireless connections.

Flight control computer **22** communicates via a wired communications network within airframe **12** with the electronics nodes of each proprotor system **20**. Flight control computer **22** receives sensor data from and sends flight command information to proprotor systems **20** such that each proprotor system **20** may be individually and independently controlled and operated. For example, flight control computer **22** is operable to individually and independently control the proprotor speed and collective blade pitch of each proprotor system **20** as well as the angular position of each proprotor system **20**. Flight control computer **22** may autonomously control some or all aspects of flight operation for ducted aircraft **10**. Flight control computer **22** is also operable to communicate with remote systems, such as a ground station via a wireless communications protocol. The remote system may be operable to receive flight data from and provide commands to flight control computer **22** to enable remote flight control over some or all aspects of flight operation for ducted aircraft **10**. In addition, ducted aircraft **10** may be pilot operated such that a pilot interacts with a

pilot interface that receives flight data from and provides commands to flight control computer **22** to enable onboard pilot control over some or all aspects of flight operation for ducted aircraft **10**.

Ducted aircraft **10** includes landing gear **24** for ground operations. Landing gear **24** may include passively operated pneumatic landing struts or actively operated landing struts. In the illustrated embodiment, landing gear **24** includes a plurality of wheels that enable ducted aircraft **10** to taxi and perform other ground maneuvers. Landing gear **24** may include a passive brake system, an active brake system such as an electromechanical braking system and/or a manual brake system to facilitate parking as required during ground operations and/or passenger ingress and egress.

In the illustrated embodiment, prop rotor systems **20** are ducted prop rotor systems each having a five bladed prop rotor assembly with variable pitch prop rotor blades **26** operable for collective pitch control. In other embodiments, the number of prop rotor blades could be either greater than or less than five and/or the prop rotor blades could have a fixed pitch. Prop rotor blades **26** of each prop rotor system **20** are surrounded by a duct **28**, which is supported by stators **30**. Duct **28** and stators **30** may be formed from metallic, composite, carbon-based or other sufficiently rigid materials. The inclusion of duct **28** on each prop rotor system **20** offers several benefits over open prop rotor systems having exposed prop rotor blades. For example, prop rotor systems **20** emit less noise and are therefore preferred when a reduced noise environment is desired, such as during air reconnaissance, clandestine operations or flight in urban airspace. Ducts **28** increase safety for ground personnel and crew by preventing inadvertent collisions with a spinning prop rotor. Openly exposed prop rotors can lead to blade tip thrust losses during flight. By reducing prop rotor blade tip losses, ducted prop rotor systems **20** are more efficient in producing thrust than open prop rotor systems of similar diameter, especially at low speed and high static thrust levels. Also, the thrust vectoring capabilities of open rotor systems are limited as is the use of pressure differentials to augment thrust.

The performance of each prop rotor system **20** is sensitive to a tip gap **32** between the tips of prop rotor blades **26** and the inner surfaces of ducts **28**. Prop rotor systems **20** may be designed to have a minimum tip gap **32** throughout the flight envelope to maximize duct performance. For example, prop rotor systems **20** are most efficient while hovering in the VTOL flight mode when tip gap **32** is as small as possible. Conversely, tip gap **32** must be large enough to avoid collisions between prop rotor blades **26** and ducts **28**. Tip gap **32** may vary widely depending on the size of prop rotor systems **20**, desired flight attributes and other factors, but by way of non-limiting example is typically in a range between 0.05 inches and 1 inch, such as between 0.1 inches and 0.25 inches.

Furthermore, tip gap **32** changes as prop rotor blades **26**, ducts **28** and/or stators **30** deform or deflect under load and during unexpected events. For example, prop rotor systems **20** experience higher loads in the conversion mode between the VTOL flight mode and the forward flight mode, caused in part by the dissymmetry of lift and vibration of prop rotor blades **26** at a sideways angle of attack of prop rotor blades **26** during the conversion mode. These increased loads can deform prop rotor blades **26**, ducts **28**, stators **30** and/or other parts of prop rotor systems **20**, thereby affecting tip gap **32**. Unexpected or imminent collisions with prop rotor systems **20** during flight, such as bird strikes, also affect tip gap **32**. Current ducted aircraft are unable to monitor and control the

changing tip gap of their ducted prop rotors, which necessitates shortening their prop rotor blades more than necessary to prevent collisions between the prop rotor blades and duct, which in turn leads to performance degradation.

Ducted aircraft **10** includes tip gap monitoring and control systems **34**, **36** to address these and other tip gap issues of previous aircraft. Tip gap monitoring and control systems **34**, **36** enable ducted aircraft **10** to actively or semi-actively enable prop rotor blades **26** to be as close as possible to ducts **28** while mitigating the risk of collision between prop rotor blades **26** and ducts **28**. Tip gap monitoring system **34** includes sensors **38a**, **38b**, **38c** coupled to prop rotor blades **26**, ducts **28** and stators **30**, respectively, to detect parameters of prop rotor systems **20** such as strain, deflection or tip gap distance. These sensor measurements are transmitted to flight control computer **22** so that tip gap monitoring system **34** can determine tip gap **32** for each prop rotor system **20** based on the sensor measurements. Tip gap control system **36** may then actively or semi-actively adjust tip gap **32** by extending or retracting active blade tips **40** on the distal ends of prop rotor blades **26** and/or active inner duct surfaces **42** circumferentially disposed on the inner surface of ducts **28**. For example, tip gap control system **36** may extend or retract active blade tips **40** and/or active inner duct surfaces **42** by a tip gap adjustment distance determined by tip gap monitoring system **34**. In other embodiments, tip gap control system **36** may control tip gap **32** using active blade tips **40** or active inner duct surfaces **42** based on the flight mode, flight condition or flight maneuver of ducted aircraft **10** or other parameters such as the blade pitch of prop rotor blades **26**. In yet other embodiments, ducted aircraft **10** may include a passive tip gap control system that retracts or extends prop rotor blades **26** of each prop rotor system **20** based on the collective pitch of prop rotor blades **26**. Alternatively, active blade tips **40** may be sacrificial blade tips that deform upon contact with ducts **28** to reduce damage to the main bodies of prop rotor blades **26** as well as ducts **28**.

It should be appreciated that ducted aircraft **10** is merely illustrative of a variety of aircraft that can implement the embodiments disclosed herein. Indeed, tip gap monitoring and control systems **34**, **36**, in both their active and semi-active implementations, as well as the passive tip gap control systems disclosed herein may be implemented on any aircraft that utilizes one or more ducts. Other aircraft implementations can include hybrid aircraft, tiltwing aircraft, unmanned aircraft, gyrocopters, propeller-driven airplanes, quadcopters, compound helicopters, jets, drones and the like. While many of the illustrative embodiments are described herein as being implemented on ducted prop rotors with prop rotor blades, the illustrative embodiments may also be implemented on rotor blades such as those present on helicopters or quadcopters. Tip gap monitoring and control systems **34**, **36** and the passive tip gap control systems disclosed herein may also be implemented on ducted tail rotors or anti-torque systems. As such, those skilled in the art will recognize that tip gap monitoring and control systems **34**, **36** and the passive tip gap control systems disclosed herein can be integrated into a variety of aircraft configurations. It should be appreciated that even though aircraft are particularly well-suited to implement the embodiments of the present disclosure, non-aircraft vehicles and devices can also implement the embodiments.

Referring additionally to FIG. 2 in the drawings, various systems of ducted aircraft **10** including tip gap monitoring and control systems **34**, **36** are depicted. As discussed herein, ducted aircraft **10** includes flight control computer **22** and a two-dimensional distributed thrust array depicted as for-

ward-port proprotor system **20a**, forward-starboard proprotor system **20b**, aft-port proprotor system **20c** and aft-starboard proprotor system **20d**. Each proprotor system **20** includes an electronics node depicted as having one or more controllers such as an electronic speed controller, one or more sensors **38** such as strain or distance sensors and one or more actuators **44** such as an active blade tip actuator, an active inner duct surface actuator, a rotor system position actuator and/or a blade pitch actuator. Each proprotor system **20** also includes at least one variable speed electric motor and a proprotor assembly coupled to the output drive of the electric motor.

Tip gap monitoring system **34** includes sensors **38**, which generate sensor measurements of one or more parameters of proprotor systems **20**. The sensor measurements generated by sensors **38** are transmitted to flight control computer **22**, where tip gap monitoring system **34** determines the current tip gap for each proprotor system **20** based on the sensor measurements. Tip gap monitoring system **34** may then determine tip gap adjustment distances for each proprotor system **20** based on the tip gaps calculated from the sensor measurements. For example, tip gap monitoring system **34** may calculate a tip gap adjustment distance by which to adjust the tip gap of proprotor system **20a** to equal a predetermined tip gap target, which may be larger or smaller than the measured tip gap. Tip gap control system **36** may then send actuator commands to actuators **44** of proprotor systems **20** to extend or retract active blade tips **40** and/or active inner duct surfaces **42** based on the tip gap adjustment distance(s) determined by tip gap monitoring system **34**. More particularly, tip gap control system **36** includes a blade length control module **46** to generate and send blade tip actuator commands to actuators **44**, which move active blade tips **40** of proprotor blades **26**. Tip gap control system **36** also includes inner duct surface control module **48** to generate and send inner duct surface actuator commands to actuators **44** to move active inner duct surfaces **42** of ducts **28**. The measured tip gaps of proprotor systems **20** may be nonuniform due to the unique loads experienced by each proprotor system **20**. Therefore, the blade tip actuator commands and inner duct surface actuator commands generated by tip gap control system **36** may likewise be nonuniform for each proprotor system **20** such that the tip gaps of proprotor systems **20** may be independently adjusted.

Referring additionally to FIG. **3** in the drawings, a block diagram depicts a control system **50** operable for use with ducted aircraft **10** of the present disclosure. In the illustrated embodiment, control system **50** includes three primary computer based subsystems; namely, an airframe system **52**, a remote system **54** and a pilot system **56**. In some implementations, remote system **54** includes a programming application **58** and a remote control application **60**. Programming application **58** enables a user to provide a flight plan and mission information to ducted aircraft **10** such that flight control computer **22** may engage in autonomous control over ducted aircraft **10**. For example, programming application **58** may communicate with flight control computer **22** over a wired or wireless communication channel **62** to provide a flight plan including, for example, a starting point, a trail of waypoints and an ending point such that flight control computer **22** may use waypoint navigation during the mission.

In the illustrated embodiment, flight control computer **22** is a computer based system that includes a command module **64** and a monitoring module **66**. It is to be understood by those skilled in the art that these and other modules executed by flight control computer **22** may be implemented in a

variety of forms including hardware, software, firmware, special purpose processors and combinations thereof. Flight control computer **22** receives input from a variety of sources including internal sources such as sensors **38**, controllers and actuators **44** and proprotor systems **20a-20d** and external sources such as remote system **54** as well as global positioning system satellites or other location positioning systems and the like. During the various operating modes of ducted aircraft **10** including the VTOL flight mode, the forward flight mode and transitions therebetween, command module **64**, which includes tip gap control system **36**, provides commands to controllers and actuators **44**. These commands enable independent operation of each proprotor system **20a-20d** including tip gap adjustment, rotor speed and angular position. Flight control computer **22** receives feedback and sensor measurements from sensors **38**, controllers, actuators **44** and proprotor systems **20a-20d**. This feedback is processed by monitoring module **66**, which includes tip gap monitoring system **34** and can supply correction data and other information to command module **64** and/or controllers and actuators **44**. Sensors **38**, such as strain sensors, distance sensors, accelerometers, vibration sensors, location sensors, attitude sensors, speed sensors, environmental sensors, fuel sensors, temperature sensors and the like also provide information to flight control computer **22** to further enhance autonomous control capabilities.

Some or all of the autonomous control capability of flight control computer **22** can be augmented or supplanted by remote flight control from, for example, remote system **54**. Remote system **54** may include one or more computing systems that may be implemented on general-purpose computers, special purpose computers or other machines with memory and processing capability. Remote system **54** may be a microprocessor-based system operable to execute program code in the form of machine-executable instructions. In addition, remote system **54** may be connected to other computer systems via a proprietary encrypted network, a public encrypted network, the Internet or other suitable communication network that may include both wired and wireless connections. Remote system **54** communicates with flight control computer **22** via communication link **62** that may include both wired and wireless connections.

While operating remote control application **60**, remote system **54** is configured to display information relating to one or more aircraft of the present disclosure on one or more flight data display devices **68**. Remote system **54** may also include audio output and input devices such as a microphone, speakers and/or an audio port allowing an operator to communicate with other operators, a base station and/or a pilot onboard ducted aircraft **10**. Display device **68** may also serve as a remote input device **70** if a touch screen display implementation is used, although other remote input devices such as a keyboard or joystick may alternatively be used to allow an operator to provide control commands to an aircraft being operated responsive to remote control.

Some or all of the autonomous and/or remote flight control of ducted aircraft **10** can be augmented or supplanted by onboard pilot flight control from a pilot interface system **56** that includes one or more computing systems that communicate with flight control computer **22** via one or more wired communication channels **72**. Pilot system **56** preferably includes one or more cockpit display devices **74** configured to display information to the pilot. Cockpit display device **74** may be configured in any suitable form including, for example, a display panel, a dashboard display, an augmented reality display or the like. Pilot system **56** may

11

also include audio output and input devices such as a microphone, speakers and/or an audio port allowing an onboard pilot to communicate with, for example, air traffic control. Pilot system 56 also includes a plurality of user interface devices 76 to allow an onboard pilot to provide control commands to ducted aircraft 10 including, for example, a control panel with switches or other inputs, mechanical control devices such as steering devices or sticks, voice control as well as other control devices.

Referring to FIG. 4 in the drawings, a tip gap monitoring and control system for a ducted aircraft such as ducted aircraft 10 in FIGS. 1A-1F is schematically illustrated and generally designated 100. Tip gap monitoring and control system of ducted aircraft 100 manages tip gap 102 for proprotor system 104. A single proprotor system 104 of ducted aircraft 100 is shown for purposes of describing the functionality of the tip gap monitoring and control system, although it will be appreciated by one of ordinary skill in the art that the tip gap monitoring and control system may manage the tip gaps of any number of proprotor systems for ducted aircraft 100. Proprotor system 104 includes a proprotor hub 106 to which proprotor blades 108 are coupled. Proprotor blades 108 are surrounded by duct 110, which is supported by stators 112. Proprotor system 104 is illustrated as including a horizontal stator and a vertical stator, although proprotor system 104 may include any number of stators in any orientation. Ducted aircraft 100 also includes flight control computer 114, which implements various systems and modules of the tip gap monitoring and control system.

Tip gap monitoring system 116 provides in-flight monitoring of tip gap 102 including the current or projected tip gap 102. Tip gap monitoring system 116 monitors tip gap 102 using sensors 118 coupled to proprotor system 104. Sensors 118 includes sensors 118a coupled to proprotor blades 108. Sensors 118a may be disposed inside or on the outer surface of proprotor blades 108. Sensors 118b are coupled to duct 110 and sensors 118c are coupled to stators 112. A portion of sensors 118 may also be coupled to proprotor hub 106. The number and placement of sensors 118 depends on a variety of factors including the number of proprotor blades 108, the number of stators 112, the design of proprotor system 104, sensor type, anticipated stresses, loads or flight conditions as well as other factors. Sensors 118 detect one or more parameters of proprotor system 104 to generate sensor measurements 120. In some embodiments, sensors 118 may be strain gauges whose sensor measurements 120 are proportional to the deflection, or strain, experienced by the components of proprotor system 104 to which they are attached. Strain gauges on proprotor blades 108, for example, may detect elongation of proprotor blades 108 due to centrifugal forces acting thereon. The strain gauges may also be used to detect loads on proprotor blades 108, duct 110 and/or stators 112 such as axial tension or compression loads on stators 112. Non-limiting examples of strain gauges that may be coupled to proprotor system 104 include foil strain gauges, optical strain gauges or laser strain gauges. Accelerometers may also be used to measure the deflection of the components of proprotor system 104. In some embodiments, sensors 118 may include blade pitch sensors and sensor measurements 120 may indicate the pitch of proprotor blades 108. Sensors 118 may also include optical gauges, laser sensors or accelerometers to measure other parameters of proprotor system 104.

Referring to FIGS. 5A-5B in conjunction with FIG. 4 in the drawings, another implementation of tip gap monitoring system 116 is depicted in which sensors 118 are distance sensors 118e, 118f coupled to proprotor system 104a. Sensor

12

measurements 120 taken by distance sensors 118e, 118f are tip gap distance measurements 102a for each proprotor blade 108a. Non-limiting examples of distance sensors 118e, 118f include Hall Effect sensors, laser sensors or optical sensors. In some embodiments, distance sensors 118f are magnets and distance sensors 118e are Hall Effect sensors that detect the proximity of magnets 118f as proprotor blades 108a rotate to generate tip gap distance measurements 102a. Any combination of the aforementioned strain gauges, distance sensors or other sensor types may be coupled to proprotor system 104 and utilized by tip gap monitoring system 116 to determine tip gap 102.

Referring back to FIG. 4, sensor measurements 120 are transmitted from sensors 118 on proprotor system 104 to flight control computer 114. Tip gap monitoring system 116 includes a tip gap measurement module 122 to determine tip gap 102 between duct 110 and proprotor blades 108 based on sensor measurements 120. Because tip gap 102 may differ for each proprotor blade 108, tip gap measurement module 122 may determine a respective tip gap 102 for each proprotor blade 108 based on sensor measurements 120. Assuming that tip gaps 102 differ for each proprotor blade 108, tip gap measurement module 122 may also determine a minimum, maximum, median or average tip gap 102 between duct 110 and proprotor blades 108. In some embodiments, sensors 118 may have nominal values and tip gap measurement module 122 may determine tip gap 102 by comparing sensor measurements 120 with the nominal values of sensors 118. In one non-limiting implementation, tip gap measurement module 122 may calculate tip gap 102 only if sensor measurements 120 differ from the nominal values for sensors 118 by a predetermined tolerance or noise threshold to reduce the processing requirements of tip gap measurement module 122. For example, in an embodiment in which sensors 118 are strain gauges, the strain measurements of sensor measurements 120 may be used to calculate strain if they exceed a threshold strain level. This threshold strain level may be determined using analysis of the duct structure, stress modeling, mapping and/or other methods. These threshold strain levels may be tested and validated for refinement. In other embodiments, tip gap measurement module 122 may continuously calculate tip gap 102 in real time to constantly monitor tip gap 102 during flight.

In some embodiments, tip gap measurement module 122 determines tip gap 102 based on the deflection or asymmetric loading experienced by proprotor system 104. In some implementations, tip gap measurement module 122 determines a structural deformity, or shape, of proprotor blades 108, duct 110 and/or stators 112 based on sensor measurements 120 from sensors 118 such as strain gauges coupled to proprotor system 104. In particular, strain measurements can be used to calculate loads on proprotor blades 108, duct 110 and/or stators 112 to determine the shape of these components based on the calculated loads. The structural deformity of proprotor blades 108, duct 110 and/or stators 112 may be determined through testing and calibration to flight loads, by computer simulation or by other numerical methods. In one example, the structural deformity or shape of duct 110 is determined using strain gauges on stators 112 to measure axial loads on stators 112 such as tension or compression loads. In another example, strain measurements from strain gauges on proprotor blades 108 may be used to determine any structural deformities of proprotor blades 108 due to centrifugal forces or other loads. Once any structural deformities of proprotor system 104 are determined, tip gap measurement module 122 may then determine tip gap 102 based on any calculated structural defor-

13

mities of proprotor blades **108**, duct **110** and/or stators **112**. For example, the derived shape of proprotor blades **108**, duct **110** and/or stators **112** may be compared to the nominal condition or shape of proprotor blades **108**, duct **110** and/or stators **112**, respectively, to determine tip gap **102** at the tips of each proprotor blade **108**. By determining tip gap **102** based on structural deformities of proprotor system **104**, tip gap measurement module **122** may calculate changes in tip gap **102** due to asymmetric loading of proprotor system **104**, in-flight or imminent collisions with proprotor system **104** such as bird strikes, load changes on proprotor system **104** due to flight conditions such as flight mode or flight maneuvers as well as other events and factors.

In some embodiments, a maneuver selection module **124** may utilize tip gap **102**, as determined by tip gap measurement module **122**, to determine, select or preclude certain flight maneuvers that ducted aircraft **100** may perform. For example, certain maneuvers may cause excessive structural deformity of the components of proprotor system **104**, and maneuver selection module **124** may avoid such maneuvers if tip gap **102** is too small, thereby reducing the likelihood of collision between proprotor blades **108** and duct **110**. Maneuver selection module **124** may also be used to avoid maneuvers causing large increases in tip gap **102** that degrade the performance of ducted aircraft **100**. Tip gap monitoring system **116** may thus allow for safe envelope expansion for flight testing of ducted aircraft **100**. Sensor measurements **120** may also indicate the absolute or relative position of sensors **118**, and therefore the position of underlying component(s) to which they are attached, and these positional sensor measurements **120** may be used to determine tip gap **102**. For example, sensors **118** may be accelerometers that are used to measure movement of the portion(s) of proprotor system **104** to which the accelerometers are coupled. The movement detected by the accelerometer may be used by tip gap measurement module **122** to determine any structural deformities of proprotor system **104**. The blade pitch of proprotor blades **108**, as indicated by sensor measurements **120** and/or flight control computer **114**, may also be used by tip gap measurement module **122** to determine tip gap **102**.

Tip gap monitoring system **116** may also include a tip gap determination engine **126** that compares tip gap **102** calculated by tip gap measurement module **122** with a tip gap target **128** to determine a tip gap adjustment distance **130**. Tip gap target **128** is the desired distance for tip gap **102** and may be determined based on a number of factors such as the flight condition of ducted aircraft **100** including the flight maneuver or flight mode currently being implemented by ducted aircraft **100**. Tip gap adjustment distance **130** is the distance that tip gap **102** is to be adjusted to equal tip gap target **128**. In some examples, tip gap adjustment distance **130** may be determined by calculating the difference between tip gap **102** and tip gap target **128**. Tip gap adjustment distance **130** may then be outputted by tip gap determination engine **126** for use by other systems or modules of flight control computer **114** including for purposes of active or semi-active control of tip gap **102**. In some embodiments, tip gap adjustment distance **130** may be outputted in response to tip gap **102** differing from tip gap target **128** by a tip gap tolerance threshold **132** so that tip gap adjustment distance **130** need only be processed by other systems of flight control computer **114** when tip gap adjustment distance **130** is large enough to merit active or semi-active control of tip gap **102**.

The tip gap monitoring and control system of ducted aircraft **100** includes tip gap control system **134** to actively

14

or semi-actively control tip gap **102** using either or both of active blade tips **136** or active inner duct surfaces **138**. Referring to FIGS. **6A-6B** in conjunction with FIG. **4** in the drawings, each proprotor blade **108** of proprotor system **104** includes a respective active blade tip **136**. Active blade tips **136** are slidably, or telescopically, coupled to open distal ends of main bodies **140** of proprotor blades **108**. Actuators **142** are disposed at proprotor hub **106** and coupled to active blade tips **136** by spanwise links **144**. Each actuator **142** may include a solenoid for electromagnetic control of active blade tips **136**. Each spanwise link **144** may be a cable, rod or other member connecting actuators **142** to active blade tips **136**.

Actuators **142** move active blade tips **136** into a plurality of positions including the extended position shown in FIG. **6A** and the retracted position shown in FIG. **6B**. Actuators **142** may also move active blade tips **136** into an infinite number of intermediate positions between the extended position shown in FIG. **6A** and the retracted position shown in FIG. **6B**. Active blade tips **136** move radially outward or inward along a spanwise axis of each proprotor blade **108**. In the extended position, active blade tips **136** are extended from the open distal ends of main bodies **140** of proprotor blades **108** to form tip gap **102** having a distance d_1 . In the retracted position, active blade tips **136** are retracted into main bodies **140** of proprotor blades **108** to form tip gap **102** having a distance D_1 . Distance D_1 is greater than distance d_1 such that tip gap **102** is larger when active blade tips **136** are in the retracted position shown in FIG. **6B**. Because each active blade tip **136** is associated with a respective actuator **142**, active blade tips **136** may be independently actuated to permit nonuniform positioning of active blade tips **136**. For example, only one or two of active blade tips **136** may be fully or partially retracted while the remaining active blade tips of proprotor system **104** are extended. One scenario in which nonuniform positioning of active blade tips **136** may be useful is when proprotor blades **108** experience nonuniform deflection or deformity loads. In some embodiments, each active blade tip **136** may be coupled to a respective spring **146** that biases the active blade tips **136** into either the extended position or the retracted position. In one non-limiting example, springs **146** may bias active blade tips **136** into the extended position and actuators **142** may be configured to pull active blade tips **136** radially inward against the bias of springs **146** to provide rapid two-way movement of active blade tips **136**. In other example, centrifugal force during operation supplements or replaces the need for spring **146**, in which case spring **146** may be useful to keep the system in tension when proprotor system **104** is not in operation.

FIGS. **6C-6G** illustrate alternative active blade tip configurations. In FIGS. **6C-6D**, actuator **142a** for active blade tip **136a** is located at a distal portion of main body **140a** of proprotor blade **108b**, thereby shortening spanwise link **144a** between actuator **142a** and active blade tip **136a**. Actuator **142a** moves active blade tip **136a** between the extended position shown in FIG. **6C** and the retracted position shown in FIG. **6D**. Distance D_2 is greater than distance d_2 such that tip gap **102** is larger when active blade tip **136a** is in the retracted position shown in FIG. **6D**. In other embodiments, actuator **142a** may be located anywhere within main body **140a** of proprotor blade **108b** including the root or middle portions of main body **140a**. In yet other embodiments, actuator **142a** may abut active blade tip **136a** without the need for spanwise link **144a** or may be located inside of active blade tip **136a**. Actuator **142a** may also be used in conjunction with a spring to bias active blade tip

15

136a in either the extended or retracted position, although centrifugal force may instead be used to bias blade tip **136a** into the extended position.

In FIGS. 6E-6G, active blade tip **136b** is hingeably coupled to the distal end of main body **140b** of proprotor blade **108c** at hinge **148**. Actuator **142b**, which may be located in hinge **148** or elsewhere, moves active blade tip **136b** between the extended position shown in FIG. 6F and the retracted position shown in FIG. 6G. In the extended position, active blade tip **136b** is substantially coplanar with main body **140b**. In the retracted position, active blade tip **136b** forms an angle θ_1 of less than 180 degrees with main body **140b**. In the illustrated embodiment, angle θ_1 is an obtuse angle and active blade tip **136b** is non-coplanar with main body **140b** in the retracted position. When active blade tip **136b** is in the extended position, tip gap **102** has a distance d_3 , which is shorter than distance D_3 of tip gap **102** when active blade tip **136b** is in the retracted position.

Referring back to FIG. 4, tip gap control system **134** includes a blade length control module **150** to actively or semi-actively actuate active blade tips **136** to maintain a desired tip gap **102** for safety and increased performance. Blade length control module **150** generates blade tip actuator commands **152** to control the position of active blade tips **136**. Blade tip actuator commands **152** are transmitted from flight control computer **114** to proprotor system **104** so that actuators **142** extend or retract active blade tips **136** to control tip gap **102** between duct **110** and proprotor blades **108**. In some embodiments, blade tip actuator commands **152** include tip gap adjustment distance **130** determined by tip gap monitoring system **116**. Upon receiving blade tip actuator commands **152**, actuators **142** may then move active blade tips **136** by tip gap adjustment distance **130** so that tip gap **102** is substantially equal to tip gap target **128**. In certain embodiments, blade length control module **150** generates blade tip actuator commands **152** in response to receiving tip gap adjustment distance **130** from tip gap monitoring system **116**. While blade length control module **150** may continuously adjust active blade tips **136** in real time to match tip gap target **128** by sending tip gap adjustment distance **130** to actuators **142** regardless of magnitude, in other embodiments blade length control module **150** may generate blade tip actuator commands **152** in response to tip gap adjustment distance **130** exceeding a tip gap adjustment distance threshold to avoid micro-adjustments below such a threshold. Blade tip actuator commands **152** may extend or retract active blade tips **136** uniformly or may include one or more blade-specific blade tip actuator commands, each corresponding to a respective one of active blade tips **136** for nonuniform positioning. Thus, blade length control module **150** may extend or retract all or a portion of active blade tips **136** at any given time. For example, blade tip actuator commands **152** may include a blade-specific blade tip actuator command that extends only one of active blade tips **136** if such proprotor blade, for example, is shorter than the other proprotor blades due to deflection or other reasons.

While tip gap control system **134** may actively control tip gap **102** using active blade tips **136** during all portions of a flight, tip gap control system **134** may also semi-actively control active blade tips **136**. Semi-active control of active blade tips **136** may be particularly useful in response to events such as bird strikes or severe maneuvers of ducted aircraft **100**. In some semi-active implementations, blade tip actuator commands **152** may include a retract command or an extend command for proprotor blades **108**, and actuators **142** may move active blade tips **136** by a predetermined distance in response to receiving the retract or extend

16

command. For example, blade length control module **150** may send blade tip actuator commands **152** that retract active blade tips **136** by a predetermined distance in response to detecting an imminent or actual collision such as a bird strike with proprotor system **104** during flight. Blade length control module **150** may also generate blade tip actuator commands **152** that retract active blade tips **136** by a predetermined distance in response to tip gap monitoring system **116** detecting a structural deformity of proprotor system **104**. In one non-limiting example, active blade tips **136** may be commanded to retract only if the structural deformity meets or exceeds a structural deformity threshold.

Blade length control module **150** may also generate blade tip actuator commands **152** based on the flight condition of ducted aircraft **100**. For example, blade length control module **150** may generate blade tip actuator commands **152** that retract active blade tips **136** by a predetermined or calculated distance if ducted aircraft **100** executes a flight maneuver **154** that has been predetermined to subject proprotor system **104** to excessive loading. Flight maneuver **154** may be detected by flight control computer **114** using a maneuver detection module **156**. Maneuver detection module **156** may use sensors **118**, pilot inputs, remote inputs or other parameters to determine flight maneuver **154** being executed by ducted aircraft **100**.

Blade length control module **150** may also generate blade tip actuator commands **152** based on the flight mode of ducted aircraft **100**. Examples of such flight modes include the VTOL flight mode, the forward flight mode and the conversion flight mode described in FIGS. 1A-1F. The rotational speed of proprotor system **104** is lower in the forward flight mode than in the VTOL flight mode, which expands tip gap **102** in the forward flight mode. Blade length control module **150** may either supplement or compensate for the naturally higher tip gap **102** in the forward flight mode. Thus, blade length control module **150** may generate blade tip actuator commands **152** that move active blade tips **136** between the retracted and extended positions in response to ducted aircraft **100** converting between the VTOL flight mode and the forward flight mode. For example, blade length control module **150** may generate blade tip actuator commands **152** that move active blade tips **136** by a calculated or predetermined amount from the retracted position to the extended position in response to ducted aircraft **100** converting from the VTOL flight mode to the forward flight mode, thus compensating for the naturally higher tip gap in the forward flight mode. In another example, blade length control module **150** may generate blade tip actuator commands **152** that move active blade tips **136** by a calculated or predetermined amount from the extended position to the retracted position in response to ducted aircraft **100** converting from the VTOL flight mode to the forward flight mode, thus supplementing tip gap **102** to provide additional safety. Because the blade pitch of proprotor blades **108** changes when converting from the VTOL flight mode to the forward flight mode, blade length control module **150** may also generate blade tip actuator commands **152** based on the blade pitch of proprotor blades **108**. Because proprotor system **104** typically experiences higher loading in the conversion flight mode, blade length control module **150** may also generate blade tip actuator commands **152** that retract active blade tips **136** by a calculated or predetermined amount when ducted aircraft **100** is in the conversion flight mode between the VTOL flight mode and the forward flight mode.

Additionally or alternatively, tip gap control system **134** may control tip gap **102** using active inner duct surfaces **138**.

Referring to FIGS. 7A-7C in conjunction with FIG. 4 of the drawings, duct 110 has an inner surface 158 that forms a circumferential cavity, or slot, 160. Active inner duct surfaces 138 are actuated segmented surfaces circumferentially disposed on inner surface 158 of duct 110. The tips of proprotor blades 108 pass adjacent to a blade pass band 162 on inner surface 158 of duct 110. Active inner duct surfaces 138 are disposed along blade pass band 162 and slidably coupled to duct 110 at cavity 160.

Each active inner duct surface 138 is coupled to a respective actuator 164. Actuators 164 move active inner duct surfaces 138 between the extended position shown in FIG. 7B and the retracted position shown in FIG. 7C as well as intermediate positions therebetween. Actuators 164 are disposed inside of duct 110 and may include a solenoid, springs or other actuating components. Active inner duct surfaces 138 are substantially flush with inner surface 158 of duct 110 in the extended position. Active inner duct surfaces 138 slide into cavity 160 in the retracted position to increase tip gap 102 at blade pass band 162. Distance D_4 is greater than distance d_4 such that tip gap 102 is larger when active inner duct surfaces 138 are in the retracted position shown in FIG. 7C. Using active inner duct surfaces 138, duct 110 may be constricted or expanded at blade pass band 162 while maintaining the overall smoothness of inner surface 158. In some embodiments, active inner duct surfaces 138 may be extended beyond the position shown in FIG. 7B so that active inner duct surfaces 138 act as bumpouts to further reduce tip gap 102. Because each active inner duct surface 138 is coupled to a respective actuator 164, active inner duct surfaces 138 may be independently actuated to permit nonuniform positioning of active inner duct surfaces 138.

FIGS. 7D-7G illustrate alternative configurations of the active inner duct surfaces. In FIGS. 7D-7E, active inner duct surface 138a is hingeably coupled to inner surface 158a of duct 110a at cavity 160a via hinge 166. Active inner duct surface 138a may be a flap or thin sheet plate. Actuator 164a rotates active inner duct surface 138a between the extended position shown in FIG. 7D and the retracted position shown in FIG. 7E. In the extended position, active inner duct surface 138a is substantially flush with inner surface 158a of duct 110a. In the retracted position, active inner duct surface 138a is rotated into cavity 160a. Distance D_5 is greater than distance d_5 such that tip gap 102 is larger when active inner duct surface 138a is in the retracted position shown in FIG. 7E. In some embodiments, active inner duct surface 138a may be extended further than the extended position shown in FIG. 7D to further reduce tip gap 102.

In FIGS. 7F-7G, active inner duct surface 138b is fillable with fluid. Fluid-filled active inner duct surface 138b is disposed in cavity 160b. The fluid inside fluid-filled active inner duct surface 138b may be a liquid or a gas. Fluid-filled active inner duct surface 138b may be tubular or have any cross-sectional shape. Actuator 164b is a pump that injects and removes fluid to and from active inner duct surface 138b. Actuator pump 164b fills active inner duct surface 138b with fluid in the extended position such that fluid-filled active inner duct surface 138b is substantially flush with inner surface 158b of duct 110b as shown in FIG. 7F. Actuator pump 164b removes fluid from fluid-filled active inner duct surface 138b in the retracted position as shown in FIG. 7G. Thus, active inner duct surface 138b is inflated in the extended position and deflated in the retracted position. Distance D_6 is greater than distance d_6 such that tip gap 102 is larger when fluid-filled active inner duct surface 138b is in the retracted position shown in FIG. 7G.

Referring back to FIG. 4, tip gap control system 134 includes an inner duct surface control module 168 to actively or semi-actively actuate active inner duct surfaces 138 to maintain a desired tip gap 102 for safety and increased performance. Inner duct surface control module 168 generates inner duct surface actuator commands 170 to control the position of active inner duct surfaces 138. Inner duct surface actuator commands 170 are transmitted from flight control computer 114 to proprotor system 104 so that actuators 164 extend or retract active inner duct surfaces 138 to control tip gap 102 between duct 110 and proprotor blades 108. In some embodiments, inner duct surface actuator commands 170 include tip gap adjustment distance 130 determined by tip gap monitoring system 116. Upon receiving inner duct surface actuator commands 170, actuators 164 may move active inner duct surfaces 138 by tip gap adjustment distance 130 so that tip gap 102 is substantially equal to tip gap target 128. In certain embodiments, inner duct surface control module 168 generates inner duct surface actuator commands 170 in response to receiving tip gap adjustment distance 130 from tip gap monitoring system 116. While inner duct surface control module 168 may continuously adjust active inner duct surfaces 138 in real time to match tip gap target 128 by sending tip gap adjustment distance 130 to actuators 164 regardless of magnitude, in other embodiments inner duct surface control module 168 may generate inner duct surface actuator commands 170 in response to tip gap adjustment distance 130 exceeding a tip gap adjustment distance threshold to avoid micro-adjustments below such a threshold. Inner duct surface actuator commands 170 may extend or retract active inner duct surfaces 138 uniformly or may include one or more active inner duct surface-specific actuator commands each corresponding to a respective one of active inner duct surfaces 138 for nonuniform positioning. Thus, inner duct surface control module 168 may extend or retract all or a portion of active inner duct surfaces 138 at any given time. For example, inner duct surface actuator commands 170 may include an active inner duct surface-specific actuator command that retracts only one of active inner duct surfaces 138 if the portion of duct 110 at which the active inner duct surface is disposed has been deformed.

While tip gap control system 134 may actively control tip gap 102 using active inner duct surfaces 138 during all portions of a flight, tip gap control system 134 may also semi-actively control active inner duct surfaces 138. Semi-active control of active inner duct surfaces 138 may be particularly useful in response to events such as bird strikes or severe maneuvers of ducted aircraft 100. In some semi-active implementations, inner duct surface actuator commands 170 may include a retract command or an extend command for duct 110, and actuators 164 may move active inner duct surfaces 138 by a predetermined distance in response to receiving the retract or extend command. For example, inner duct surface control module 168 may send inner duct surface actuator commands 170 that retract active inner duct surfaces 138 by a predetermined distance in response to detecting an actual or imminent collision such as a bird strike with proprotor system 104 during flight. Inner duct surface control module 168 may also generate inner duct surface actuator commands 170 that retract active inner duct surfaces 138 by a predetermined distance in response to tip gap monitoring system 116 detecting a structural deformity of proprotor system 104. In one non-limiting example, active inner duct surfaces 138 may be commanded to retract only if the structural deformity meets or exceeds a structural deformity threshold.

Inner duct surface control module **168** may also generate inner duct surface actuator commands **170** based on the flight condition of ducted aircraft **100**. For example, inner duct surface control module **168** may generate inner duct surface actuator commands **170** that retract active inner duct surfaces **138** by a predetermined or calculated distance if ducted aircraft **100** executes a flight maneuver **154**, as detected by maneuver detection module **156**, which has been predetermined to subject proprotor system **104** to excessive loading. Inner duct surface control module **168** may also generate inner duct surface actuator commands **170** based on the flight mode of ducted aircraft **100**. The rotational speed of proprotor system **104** is lower in the forward flight mode than in the VTOL flight mode, which expands tip gap **102** in the forward flight mode. Inner duct surface control module **168** may either supplement or compensate for the naturally higher tip gap **102** in the forward flight mode. Thus, inner duct surface control module **168** may generate inner duct surface actuator commands **170** that move active inner duct surfaces **138** between the retracted and extended positions in response to ducted aircraft **100** converting between the VTOL flight mode and the forward flight mode. For example, inner duct surface control module **168** may generate inner duct surface actuator commands **170** that move active inner duct surfaces **138** by a calculated or predetermined amount from the retracted position to the extended position in response to ducted aircraft **100** converting from the VTOL flight mode to the forward flight mode, thus compensating for the naturally higher tip gap in the forward flight mode. In another example, inner duct surface control module **168** may generate inner duct surface actuator commands **170** that move active inner duct surfaces **138** by a calculated or predetermined amount from the extended position to the retracted position in response to ducted aircraft **100** converting from the VTOL flight mode to the forward flight mode, thus supplementing tip gap **102** to provide additional safety.

Because the blade pitch of proprotor blades **108** changes when converting from the VTOL flight mode to the forward flight mode, inner duct surface control module **168** may also generate inner duct surface actuator commands **170** based on the blade pitch of proprotor blades **108**. Because proprotor system **104** typically experiences higher loading in the conversion flight mode, inner duct surface control module **168** may also generate inner duct surface actuator commands **170** that retract active inner duct surfaces **138** by a calculated or predetermined amount when ducted aircraft **100** is in the conversion flight mode between the VTOL flight mode and the forward flight mode. The systems and modules shown as part of flight control computer **114** may be interchangeable with one another. In certain embodiments, flight control computer **114** may include or implement only a portion of the systems and modules shown in FIG. **4** in any combination.

Referring additionally to FIGS. **8A-8H** in the drawings, a sequential flight-operating scenario of ducted aircraft **100** including proprotor systems **104** and flight control computer **114** is depicted. Proprotor systems **104** include forward-port, forward-starboard, aft-port and aft-starboard proprotor systems similar to ducted aircraft **10** in FIGS. **1A-1F**. As best seen in FIG. **8A**, ducted aircraft **100** is positioned on the ground prior to takeoff. When ducted aircraft **100** is ready for a mission, flight control computer **114** commences operations to provide flight control to ducted aircraft **100** which may be onboard pilot flight control, remote flight control, autonomous flight control or a combination thereof. For example, it may be desirable to utilize onboard pilot

flight control during certain maneuvers such as takeoff and landing but rely on autonomous flight control during hover, high speed forward flight and/or transitions between wing-borne flight and thrust-borne flight.

As best seen in FIG. **8B**, ducted aircraft **100** has performed a vertical takeoff and is engaged in thrust-borne lift. As illustrated, the proprotor assemblies of each proprotor system **104** are rotating in the same horizontal plane forming a two-dimensional distributed thrust array of four proprotor systems. As the longitudinal axis and the lateral axis of ducted aircraft **100** are both in the horizontal plane, ducted aircraft **100** has a level flight attitude. During hover, flight control computer **114** utilizes individual variable speed and blade pitch control capability of proprotor systems **104** to control flight dynamics to maintain hover stability and to provide pitch, roll and yaw authority for ducted aircraft **100**. More specifically, as each proprotor system **104** is independently controllable, operational changes to certain proprotor systems **104** enable pitch, roll and yaw control of ducted aircraft **100** during VTOL operations.

For example, by changing the thrust output of the forward proprotor systems relative to the aft proprotor systems, pitch control is achieved. As another example, by changing the thrust output of the port proprotor systems relative to the starboard proprotor systems, roll control is achieved. Changing the relative thrust outputs of the various proprotor systems **104** may be accomplished using differential rotor speed control, that is, increasing the rotor speed of some proprotor systems relative to the rotor speed of other proprotor systems and/or decreasing the rotor speed of some proprotor systems relative to the rotor speed of other proprotor systems. Changing the relative thrust outputs of the various proprotor systems **104** may be accomplished using collective blade pitch. Yaw control or torque balancing of ducted aircraft **100** during VTOL operations may be accomplished by changing the torque output of certain proprotor systems **104**. For example, the forward-port and aft-starboard proprotor systems may have clockwise rotating proprotor assemblies while the forward-starboard and aft-port proprotor systems may have counterclockwise rotating proprotor assemblies. In this example, by changing the torque output of the forward-port and aft-starboard proprotor systems relative to the forward-starboard and aft-port proprotor systems, yaw control is achieved. Changing the relative torque outputs of the various proprotor systems **104** may be accomplished using differential rotor speed control.

During hover, ducted aircraft **100** may experience crosswinds that cause turbulent flow through proprotor systems **104**. This turbulent flow subjects proprotor systems **104** to deforming loads, which affect tip gap **102**. Tip gap monitoring system **116** detects changes to tip gap **102** caused by crosswinds. If tip gap **102** becomes unacceptably small due to the resulting deforming loads, tip gap control system **134** repositions active blade tips **136** and/or active inner duct surfaces **138** to enlarge tip gap **102**.

Returning to the sequential flight-operating scenario of ducted aircraft **100**, after vertical ascent to the desired elevation, ducted aircraft **100** may begin the transition from thrust-borne lift to wing-borne lift. As best seen from the progression of FIGS. **8B-8D**, the angular positions of proprotor systems **104** are changed by a pitch down rotation to transition ducted aircraft **100** from the VTOL flight mode toward the forward flight mode. As seen in FIG. **8C**, proprotor systems **104** have been collectively inclined about 45 degrees pitch down. In the conversion orientations of ducted aircraft **100**, a portion of the thrust generated by proprotor systems **104** provides lift while a portion of the

thrust generated by proprotor systems 104 urges ducted aircraft 100 to accelerate in the forward direction such that the forward airspeed of ducted aircraft 100 increases allowing the wings of ducted aircraft 100 to offload a portion and eventually all of the lift requirement from proprotor systems 104. Proprotor systems 104 may be particularly susceptible to deforming loads in the conversion flight mode shown in FIG. 8C. Tip gap monitoring system 116 detects any structural deformities to proprotor systems 104 during the transition from the VTOL flight mode to the forward flight mode. Tip gap control system 134 repositions active blade tips 136 and/or active inner duct surfaces 138 in response to any structural deformities that unacceptably reduce tip gap 102 during the conversion flight mode to ensure that no collisions occur between proprotor blades 108 and duct 110.

As best seen in FIGS. 8D-8E, proprotor systems 104 have been collectively inclined about 90 degrees pitch down such that the proprotor assemblies are rotating in vertical planes providing forward thrust for ducted aircraft 100 while the wings provide lift. Even though the conversion from the VTOL flight mode to the forward flight mode of ducted aircraft 100 has been described as progressing with collective pitch down rotation of proprotor systems 104, in other implementations, all proprotor systems 104 need not be operated at the same time or at the same rate. As forward flight with wing-borne lift requires significantly less thrust than VTOL flight with thrust-borne lift, the operating speed of some or all of proprotor systems 104 may be reduced particularly in embodiments having collective pitch control. This RPM reduction in the forward flight mode tends to increase tip gap 102. Tip gap control system 134 may decrease tip gap 102 in the forward flight mode by extending active blade tips 136 and/or active inner duct surfaces 138 to compensate for the enlarged tip gap 102. In other embodiments, tip gap control system 134 may further increase tip gap 102 in the forward flight mode by retracting active blade tips 136 and/or active inner duct surfaces 138 since tip gap 102 may be less critical to flight efficiency in the forward flight mode than in the VTOL flight mode. Tip gap control system 134 may increase or decrease tip gap 102 in response to flight control computer 114 signaling a change in flight mode. Because the blade pitch of proprotor blades 108 changes when converting from the VTOL flight mode to the forward flight mode, tip gap control system 134 may also increase or decrease tip gap 102 in response to flight control computer 114 or sensors 118 signaling a change in blade pitch. Proprotor systems 104 are susceptible to collisions such as a collision 174 with a bird 176. Such collisions can cause proprotor systems 104 to structurally deform. Tip gap monitoring system 116 detects any structural deformities to proprotor systems 104 caused by actual or imminent collisions during flight. Tip gap control system 134 repositions active blade tips 136 and/or active inner duct surfaces 138 in response to any structural deformities caused by collision 174 that unacceptably reduce tip gap 102.

In certain embodiments, some of proprotor systems 104 of ducted aircraft 100 could be shut down during forward flight. In the forward flight mode, the independent rotor speed control provided by flight control computer 114 over each proprotor system 104 may provide yaw authority for ducted aircraft 100. For example, by changing the thrust output of either or both port proprotor systems relative to starboard proprotor systems, yaw control is achieved. Changing the relative thrust outputs of the various proprotor systems 104 may be accomplished using differential rotor speed control. Changing the relative thrust outputs of the various proprotor systems 104 may also be accomplished

using collective pitch control. In the forward flight mode, pitch and roll authority is preferably provided by the ailerons and/or elevators on the wings and/or tail assembly of ducted aircraft 100.

As ducted aircraft 100 approaches its destination, ducted aircraft 100 may begin its transition from wing-borne lift to thrust-borne lift. As best seen from the progression of FIGS. 8E-8G, the angular positions of proprotor systems 104 are changed by a pitch up rotation to transition ducted aircraft 100 from the forward flight mode toward the VTOL flight mode. As seen in FIG. 8F, proprotor systems 104 have been collectively inclined about 45 degrees pitch up. In the conversion orientations of ducted aircraft 100, a portion of the thrust generated by proprotor systems 104 begins to provide lift for ducted aircraft 100 as the forward airspeed decreases and the lift producing capability of the wings of ducted aircraft 100 decreases. As best seen in FIG. 8G, proprotor systems 104 have been collectively inclined about 90 degrees pitch up such that the proprotor assemblies are rotating in the horizontal plane providing thrust-borne lift for ducted aircraft 100. Even though the conversion from the forward flight mode to the VTOL flight mode of ducted aircraft 100 has been described as progressing with collective pitch up rotation of proprotor systems 104, in other implementations, all proprotor systems 104 need not be operated at the same time or at the same rate. Once ducted aircraft 100 has completed the transition to the VTOL flight mode, ducted aircraft 100 may commence its vertical descent to a surface. As best seen in FIG. 8H, ducted aircraft 100 has landed at the destination location.

Referring to FIGS. 9A-9C in the drawings, methods for monitoring and controlling a tip gap for a ducted aircraft are illustrated as flowcharts 200, 202, 204. In FIG. 9A, a method for monitoring a tip gap for a ducted aircraft includes detecting one or more parameters of a proprotor system including a duct and a plurality of proprotor blades to form a plurality of sensor measurements (step 206). The method includes transmitting the sensor measurements from a plurality of sensors coupled to the proprotor system to a flight control computer (step 208). The method includes determining a tip gap distance based on the sensor measurements (step 210). The method also includes determining a tip gap adjustment distance based on the tip gap distance and a tip gap target (step 212).

In FIG. 9B, a method for controlling a tip gap for a ducted aircraft includes generating a blade tip actuator command (step 214). The method includes transmitting the blade tip actuator command to a proprotor system including a duct and a plurality of proprotor blades, the proprotor blades including active blade tips (step 216). The method also includes moving at least one of the active blade tips between a retracted position and an extended position in response to the blade tip actuator command, thereby controlling the tip gap between the proprotor blades and the duct (step 218). In FIG. 9C, a method for controlling a tip gap for a ducted aircraft includes generating an inner duct surface actuator command (step 220). The method includes transmitting the inner duct surface actuator command to a proprotor system including a duct and a plurality of proprotor blades, the duct including a plurality of active inner duct surfaces (step 222). The method also includes moving at least one of the active inner duct surfaces between a retracted position and an extended position in response to the inner duct surface actuator command, thereby controlling the tip gap between the proprotor blades and the duct (step 224).

The flowcharts and block diagrams in the different depicted embodiments illustrate the architecture, function-

ality, and operation of some possible implementations of apparatus, methods and computer program products. In this regard, each block in the flowchart or block diagrams may represent a module, segment, or portion of code, which comprises one or more executable instructions for implementing the specified function or functions. In some alternative implementations, the function or functions noted in the block may occur out of the order noted in the figures. For example, in some cases, two blocks shown in succession may be executed substantially concurrently, or the blocks may sometimes be executed in the reverse order, depending upon the functionality involved.

Referring to FIGS. 10A-10E in the drawings, a ducted aircraft implementing a passive tip gap control system is schematically illustrated and generally designated 300. Proprotor system 302 is one of a plurality of proprotor systems of ducted aircraft 300. Similar to ducted aircraft 10 in FIGS. 1A-1F, the proprotor systems of ducted aircraft 300 including proprotor system 302 are rotatable between the vertical orientation of the forward flight mode shown in FIGS. 10A-10C and the horizontal orientation of the VTOL flight mode shown in FIGS. 10D-10E. Proprotor system 302 includes proprotor blades 304 surrounded by duct 306. A pitch control assembly 308 is coupled to proprotor blades 304 to change the collective pitch of proprotor blades 304 about pitch change axis 310. Ducted aircraft 300 relies on thrust-borne lift in the VTOL flight mode and wing-borne lift in the forward flight mode. Proprotor blades 304 have a lower collective pitch in the VTOL flight mode as shown in FIGS. 10D-10E than in the forward flight mode as shown in FIGS. 10B-10C. In addition, proprotor blades 304 operate at two different rotational speeds in the two primary flight modes of ducted aircraft 300. More particularly, proprotor system 302 has a higher rotational speed in the VTOL flight mode than the forward flight mode. Due to a decrease in centrifugal force as well as other factors, the lower rotational speed of proprotor system 302 in the forward flight mode increases tip gap 312 in the forward flight mode relative to tip gap 312 in the VTOL flight mode. The passive tip gap control system of ducted aircraft 300 passively ties the length of proprotor blades 304 to the blade pitch of proprotor blades 304 to accentuate or compensate for increased tip gap 312 in the forward flight mode.

Proprotor blades 304 are extendable along pitch change axis 310 into a plurality of positions including the extended position shown in FIGS. 10B-10C and the retracted position shown in FIGS. 10D-10E as well as an infinite number of intermediate positions therebetween. More particularly, each proprotor blade 304 includes a blade tip extension 314 extendable into the extended position shown in FIGS. 10B-10C and retractable into the retracted position shown in FIGS. 10D-10E. Blade tip extensions 314 are slidably, or telescopically, coupled to the open distal ends of main bodies 316 of proprotor blades 304. Blade tip extensions 314 are retracted into main bodies 316 of proprotor blades 304 in the retracted position and extended from the open distal ends of main bodies 316 of proprotor blades 304 in the extended position, thereby increasing tip gap 312 in the retracted position and decreasing tip gap 312 in the extended position.

Each blade tip extension 314 is associated with a respective pitch-span converter 318. Each pitch-span converter 318 is coupled to and interposed between pitch control assembly 308 and a respective blade tip extension 314. Pitch-span converters 318 are located at proprotor hub 320 of proprotor system 302, although pitch-span converters 318 may be located anywhere on proprotor system 302 including

within main bodies 316 of proprotor blades 304. Each pitch-span converter 318 is coupled to a respective blade tip extension 314 by a spanwise link 322 such as a cable or rod disposed inside a respective proprotor blade 304. Pitch-span converters 318 convert the collective pitch of proprotor blades 304 about pitch change axis 310 into the position of blade tip extensions 314 along pitch change axis 310. In some embodiments, each pitch-span converter 318 may include a screw mechanism such as a helical threaded screw or a pulley to convert the axial motion of pitch control assembly 308 along mast 324 into the spanwise and radially extendable motion of blade tip extensions 314. In embodiments in which each spanwise link 322 is a cable, the cable may pull a respective blade tip extension 314 into the retracted position against the bias of a respective spring 326 and/or centrifugal force during operation. Centrifugal force during operation may supplement or replace the need for spring 326, in which case spring 326 may be useful to keep the system in tension when proprotor system 302 is not in operation. In alternative embodiments, blade tip extensions 314 may instead be hingeably coupled to the distal ends of main bodies 316 of proprotor blades 304 in a similar manner to that described for active blade tips 136b in FIGS. 6E-6G. In such alternative embodiments, blade tip extensions 314 are substantially coplanar with main bodies 316 of proprotor blades 304 in the extended position and form an angle of less than 180 degrees with main bodies 316 of proprotor blades 304 in the retracted position, thereby increasing tip gap 312 in the retracted position and decreasing tip gap 312 in the extended position.

Blade tip extensions 314 change between the extended position of FIGS. 10B-10C and the retracted position of FIGS. 10D-10E based on the collective pitch of proprotor blades 304 to control tip gap 312. As described above, proprotor blades 304 have a lower collective pitch in the VTOL flight mode and a higher collective pitch in the forward flight mode. Thus, blade tip extensions 314 change between the retracted position and the extended position based on the flight mode of ducted aircraft 300. FIGS. 10D-10E show proprotor system 302 in the VTOL flight mode, in which proprotor blades 304 have a lower collective pitch and blade tip extensions 314 are in the retracted position. FIGS. 10B-10C show proprotor system 302 in the forward flight mode, in which proprotor blades 304 have a higher collective pitch and blade tip extensions 314 are in the extended position to compensate for the shortened span of main bodies 316 of proprotor blades 304 in the forward flight mode. Thus, tip gap 312 remains substantially the same in both flight modes. Alternatively, blade tip extensions 314 may extend at the lower collective pitch in the VTOL flight mode and retract at the higher collective pitch of the forward flight mode to increase tip gap 312 in the forward flight mode. Increasing tip gap 312 in this manner may be useful because tip gap 312 is not as critical to performance in the forward flight mode. Increasing tip gap 312 in the forward flight mode may also be used as a safety measure to guard against large deformations of duct 306 due to bird strikes or other collisions, which are more likely to occur and incur more damage in the forward flight mode.

Referring additionally to FIGS. 11A-11H in the drawings, a sequential flight-operating scenario of ducted aircraft 300 including proprotor systems 302 is depicted. Proprotor systems 302 include forward-port, forward-starboard, aft-port and aft-starboard proprotor systems similar to ducted aircraft 10 in FIGS. 1A-1F. As best seen in FIG. 11A, ducted aircraft 300 is positioned on the ground prior to takeoff. When ducted aircraft 300 is ready for a mission, the flight control

computer commences operations to provide flight control to ducted aircraft 300 which may be onboard pilot flight control, remote flight control, autonomous flight control or a combination thereof. For example, it may be desirable to utilize onboard pilot flight control during certain maneuvers such as takeoff and landing but rely on autonomous flight control during hover, high speed forward flight and/or transitions between wing-borne flight and thrust-borne flight.

As best seen in FIG. 11B, ducted aircraft 300 has performed a vertical takeoff and is engaged in thrust-borne lift. As illustrated, the proprotor assemblies of each proprotor system 302 are rotating in the same horizontal plane forming a two-dimensional distributed thrust array of four proprotor systems. As the longitudinal axis and the lateral axis of ducted aircraft 300 are both in the horizontal plane, ducted aircraft 300 has a level flight attitude. During hover, the flight control computer utilizes individual variable speed and blade pitch control capability of proprotor systems 302 to control flight dynamics to maintain hover stability and to provide pitch, roll and yaw authority for ducted aircraft 300. More specifically, as each proprotor system 302 is independently controllable, operational changes to certain proprotor systems 302 enable pitch, roll and yaw control of ducted aircraft 300 during VTOL operations.

Returning to the sequential flight-operating scenario of ducted aircraft 300, after vertical ascent to the desired elevation, ducted aircraft 300 may begin the transition from thrust-borne lift to wing-borne lift. As best seen from the progression of FIGS. 11B-11D, the angular positions of proprotor systems 302 are changed by a pitch down rotation to transition ducted aircraft 300 from the VTOL flight mode toward the forward flight mode. As seen in FIG. 11C, proprotor systems 302 have been collectively inclined about 45 degrees pitch down. In the conversion flight mode of ducted aircraft 300, a portion of the thrust generated by proprotor systems 302 provides lift while a portion of the thrust generated by proprotor systems 302 urges ducted aircraft 300 to accelerate in the forward direction such that the forward airspeed of ducted aircraft 300 increases allowing the wings of ducted aircraft 300 to offload a portion and eventually all of the lift requirement from proprotor systems 302. As best seen in FIGS. 11D-11E, proprotor systems 302 have been collectively inclined about 90 degrees pitch down such that the proprotor assemblies are rotating in vertical planes providing forward thrust for ducted aircraft 300 while the wings provide lift.

Proprotor systems 302 are designed to have a minimum tip gap 312 in the VTOL flight mode to maximize duct performance. As ducted aircraft 300 transitions from the VTOL flight mode in FIG. 11B to the forward flight mode in FIG. 11D, the collective pitch of proprotor blades 304 increases and the RPMs of proprotor systems 302 decrease, thereby enlarging tip gap 312 in the forward flight mode. The passive tip gap control system extends blade tip extensions 314 as the collective pitch of proprotor blades 304 increases into the forward flight mode to compensate for this enlarged tip gap 312. In other embodiments, the passive tip gap control system may retract blade tip extensions 314 as the collective pitch of proprotor blades 304 increases into the forward flight mode to provide additional safety since tip gap 312 is less critical for performance in the forward flight mode.

As ducted aircraft 300 approaches its destination, ducted aircraft 300 may begin its transition from wing-borne lift to thrust-borne lift. As best seen from the progression of FIGS. 11E-11G, the angular positions of proprotor systems 302 are

changed by a pitch up rotation to transition ducted aircraft 300 from the forward flight mode to the VTOL flight mode. As seen in FIG. 11F, proprotor systems 302 have been collectively inclined about 45 degrees pitch up. In the conversion orientations of ducted aircraft 300, a portion of the thrust generated by proprotor systems 302 begins to provide lift for ducted aircraft 300 as the forward airspeed decreases and the lift producing capability of the wings of ducted aircraft 300 decreases. As best seen in FIG. 11G, proprotor systems 302 have been collectively inclined about 90 degrees pitch up such that the proprotor assemblies are rotating in the horizontal plane providing thrust-borne lift for ducted aircraft 300. As ducted aircraft 300 transitions from the forward flight mode in FIG. 11E to the VTOL flight mode in FIG. 11G, the collective pitch of proprotor blades 304 decreases and the RPMs of proprotor systems 302 increase, thereby constricting tip gap 312 in the VTOL flight mode. The passive tip gap control system retracts blade tip extensions 314 as the collective pitch of proprotor blades 304 decreases into the VTOL flight mode to avoid any collisions between proprotor blades 304 and duct 306. In other embodiments, the passive tip gap control system may extend blade tip extensions 314 as the collective pitch of proprotor blades 304 decreases into the VTOL flight mode to improve the performance of duct 306. Even though the conversion from the forward flight mode to the VTOL flight mode of ducted aircraft 300 has been described as progressing with collective pitch up rotation of proprotor systems 302, in other implementations, all proprotor systems 302 need not be operated at the same time or at the same rate. Once ducted aircraft 300 has completed the transition to the VTOL flight mode, ducted aircraft 300 may commence its vertical descent to a surface. As best seen in FIG. 11H, ducted aircraft 300 has landed at the destination location.

Referring to FIGS. 12A-12F in the drawings, a passive tip gap control system for proprotor system 332 including proprotor blades 334 surrounded by duct 336 is schematically illustrated. Proprotor blades 334 change collective pitch about pitch change axis 338. FIGS. 12A-12B show proprotor blades 334 having a higher collective pitch in the forward flight mode while FIGS. 12C-12D show proprotor blades 334 having a lower collective pitch in the VTOL flight mode. Proprotor blades 334 are retained on proprotor hub 340 by tension-torsion straps 342. Tension-torsion straps 342 may be partially or fully disposed inside of proprotor blades 334. Tension-torsion straps 342 may extend from proprotor hub 340 for any spanwise length along proprotor blades 334 such as 10 percent, 20 percent, 30 percent, 40 percent or higher of the spanwise length of proprotor blades 334. In some embodiments, tension-torsion straps 342 may also be used to couple a proprotor blade 334 to other proprotor blades 334. In addition to reacting centrifugal force during the operation of proprotor system 332, tension-torsion straps 342 twist and untwist to extend proprotor blades 334 at the higher collective pitch in the forward flight mode as shown in FIGS. 12A-12B and retract proprotor blades 334 at the lower collective pitch in the VTOL flight mode as shown in FIGS. 12C-12D. Each tension-torsion strap 342 changes between the wound position shown in FIG. 12E and the unwound position shown in FIG. 12F based on the collective pitch of proprotor blades 334. The lengths L_1 of tension-torsion straps 342 are less in the wound position than the lengths L_1 of tension-torsion straps 342 in the unwound position. Thus, proprotor blades 334 are in the retracted position when tension-torsion straps 342 are in the wound position as shown in FIG. 12C and in

the extended position when tension-torsion straps **342** are in the unwound position as shown in FIG. 12A.

Because proprotor system **332** has a slower rotational speed in the forward flight mode shown in FIG. 12A, unwinding tension-torsion straps **342** at the higher collective pitch extends proprotor blades **334** to compensate for shorter proprotor blades **334** at lower RPMs, thereby maintaining an approximately constant tip gap **344** in both flight modes. In other embodiments, tension-torsion straps **342** may be wound at the higher collective pitch in the forward flight mode and unwound at the lower collective pitch in the VTOL flight mode to further retract proprotor blades **334** in the forward flight mode to provide an additional safety buffer between proprotor blades **334** and duct **336**. The spanwise distance that tension-torsion straps **342** extend and retract proprotor blades **334** may depend on various properties of tension-torsion straps **342** such as distance **346** between bands **348**, **350**, the thickness of bands **348**, **350**, the material from which tension-torsion straps **342** are formed and the overall length L_1 of tension-torsion straps **342**. These characteristics of tension-torsion straps **342** may be varied to achieve the desired behavior of tip gap **344** in the various flight modes of the ducted aircraft. In alternative embodiments, tension-torsion straps **342** may instead be helical threaded screws or hydraulic pistons that radially extend and retract proprotor blades **334**. In yet other embodiments, the passive tip gap control system described herein may extend and retract proprotor blades **334** based on the cyclic pitch of proprotor blades **334**.

Referring to FIGS. 13A-13E in the drawings, a ducted aircraft **400** including proprotor system **402** having proprotor blades **404** surrounded by duct **406** is schematically illustrated. Proprotor system **402** may be one of a plurality of proprotor systems of ducted aircraft **400** that moves between vertical and horizontal orientations in forward flight and VTOL flight modes similar to ducted aircraft **10** described in FIGS. 1A-1F. For flight conditions such as flight maneuvers or flight modes in which duct **406** deforms due to flight loads, proprotor blades **404** could potentially come in contact with duct **406** as shown in FIGS. 13B-13C, potentially leading to a critical safety issue such as the failure of proprotor blades **404** or duct **406**. To remedy this issue, proprotor blades **404** include sacrificial blade tips **408** to allow the tips of proprotor blades **404** to act as sacrificial portions of proprotor blades **404** to save duct **406** and/or main bodies **410** of proprotor blades **404** from damage or failure. The root ends of main bodies **410** of proprotor blades **404** are coupled to proprotor hub **412** and sacrificial blade tips **408** are coupled to the distal ends of main bodies **410** of proprotor blades **404**.

Sacrificial blade tips **408** each include a deformable core material **414** and a shell layer **416** covering deformable core material **414**. Shell layer **416** has an airfoil cross-sectional shape and a closed distal end **418**. In other embodiments, distal end **418** of shell layer **416** may be an open distal end to expose deformable core material **414**. Shell layer **416** provides wear resistance during high speed rotation of proprotor blades **404** and general stiffness during flight, but is soft enough to deform or break away in the event of an impact between proprotor blades **404** and duct **406**. Non-limiting examples of materials from which shell layer **416** may be formed include fiberglass, fiberglass with spanwise aligned strands, crumble-prone ceramic material, carbon-based material, sheet metal, composite material, thin material, carbon fiber reinforced plastic or frangible ceramic material. Deformable core material **414** is formed from a softer material than shell layer **416**. For example, deform-

able core material **414** may be formed from foam. Shell layer **416** abuts, overlaps or is adjacent to skin **420** of main body **410** as best seen in FIG. 13C. Sacrificial blade tip **408** is coupled to main body **410** using adhesive **422** such as glue on a backing plate as well as adhesive tape **424** at the outer interface boundary between shell layer **416** and skin **420** of main body **410**. Sacrificial blade tip **408** may be coupled to the backing plate using hooks, fasteners, tabs, adhesive or other coupling techniques.

FIGS. 13B-13C show the moment of contact between proprotor blades **404** and duct **406**. Such contact may occur, for example, upon deformation of proprotor blades **404** and/or duct **406**. The structure and material composition of sacrificial blade tips **408** allow sacrificial blade tips **408** to crumble, compress, crush or otherwise deform upon contact with duct **406**. The aftermath of contact between sacrificial blade tips **408** and duct **406** is shown in FIGS. 13D-13E, in which main bodies **410** of proprotor blades **404** remain undeformed upon contact between sacrificial blade tips **408** and duct **406**. The tip gap between proprotor blades **404** and duct **406** is also increased upon the deformation of sacrificial blade tips **408** to allow the uninterrupted functioning of ducted aircraft **400** for continued operation or an emergency landing. Sacrificial blade tips **408** may be designed to be inexpensive and lightweight, and may be economically replaced when ducted aircraft **400** returns from a mission. Sacrificial blade tips **408** may be designed for one-time use in that they are replaced, as opposed to repaired, when they deform as a result of contact with duct **406**.

Referring to FIGS. 14A-14D in the drawings, a proprotor system **430** having proprotor blades **432** surrounded by duct **434** is schematically illustrated. Proprotor blade **432** includes sacrificial blade tip **436** coupled to the distal end of main body **438**. Sacrificial blade tip **436** includes deformable core material **440** covered by shell layer **442**. Sacrificial blade tip **436** is coupled to main body **438** of proprotor blade **432** at an interface boundary **444**. Interface boundary **444** is illustrated as having a rounded distal end but may be squared off in other embodiments as shown in FIGS. 13C and 13D. In the illustrated embodiment, shell layer **442** is integral with skin **446** of main body **438** to form an integral layer covering interface boundary **444**. Shell layer **442** also has a closed distal end. Deformable core material **440** forms a lattice structure made from polymer or another frangible material. In the illustrated embodiment, the lattice structure formed by deformable core material **440** is a honeycomb structure, although other lattice infill shapes such as triangular, grid or irregular lattices may also be formed by deformable core material **440**. When sacrificial blade tip **436** contacts duct **434** as shown in FIGS. 14A-14B, a fragment **448** of sacrificial blade tip **436** breaks away, leaving a slightly shorter proprotor blade. In other embodiments, sacrificial blade tip **436** may separate from main body **438** at interface boundary **444** upon contact with duct **434**. The breaking away of fragment **448** enlarges the tip gap between proprotor blade **432** and duct **434** to prevent further damage to these components.

The foregoing description of embodiments of the disclosure has been presented for purposes of illustration and description. It is not intended to be exhaustive or to limit the disclosure to the precise form disclosed, and modifications and variations are possible in light of the above teachings or may be acquired from practice of the disclosure. The embodiments were chosen and described in order to explain the principals of the disclosure and its practical application to enable one skilled in the art to utilize the disclosure in various embodiments and with various modifications as are

suited to the particular use contemplated. Other substitutions, modifications, changes and omissions may be made in the design, operating conditions and arrangement of the embodiments without departing from the scope of the present disclosure. Such modifications and combinations of the illustrative embodiments as well as other embodiments will be apparent to persons skilled in the art upon reference to the description. It is, therefore, intended that the appended claims encompass any such modifications or embodiments.

What is claimed is:

1. A proprotor system for a ducted aircraft comprising: a duct; and a plurality of proprotor blades surrounded by the duct, each proprotor blade rotatable about a respective pitch change axis, the proprotor blades configured to change collective pitch about the pitch change axes; wherein, the proprotor blades are extendable along the pitch change axes into a plurality of positions including a retracted position and an extended position; and wherein, the proprotor blades are configured to change between the retracted position and the extended position based on the collective pitch of the proprotor blades, thereby controlling a tip gap between the proprotor blades and the duct.
2. The proprotor system as recited in claim 1 wherein the proprotor blades are rotatable between a plurality of collective pitches about the pitch change axes including a higher collective pitch and a lower collective pitch, the proprotor blades in one of the retracted position or the extended position at the higher collective pitch and the other of the retracted position or the extended position at the lower collective pitch.
3. The proprotor system as recited in claim 2 wherein the proprotor blades are in the retracted position at the higher collective pitch and in the extended position at the lower collective pitch.
4. The proprotor system as recited in claim 2 wherein the proprotor blades are in the extended position at the higher collective pitch and in the retracted position at the lower collective pitch.
5. The proprotor system as recited in claim 1 wherein a distal end of each of the proprotor blades further comprises a blade tip extension movable between the retracted position and the extended position.
6. The proprotor system as recited in claim 5 wherein each of the proprotor blades further comprises a main body having an open distal end, the blade tip extensions slidably coupled to the open distal ends of the main bodies of the proprotor blades; and wherein, the blade tip extensions are at least partially retracted into the main bodies of the proprotor blades in the retracted position and at least partially extended from the open distal ends of the main bodies of the proprotor blades in the extended position, thereby increasing the tip gap in the retracted position.
7. The proprotor system as recited in claim 5 further comprising a pitch-span converter configured to convert the collective pitch of the proprotor blades about the pitch change axes into the position of the blade tip extensions.
8. The proprotor system as recited in claim 7 further comprising a pitch control assembly coupled to the proprotor blades to change the collective pitch of the proprotor blades about the pitch change axes, the pitch-span converter coupled to the pitch control assembly and one or more of the blade tip extensions.

9. The proprotor system as recited in claim 7 further comprising a proprotor hub interconnecting the proprotor blades, the pitch-span converter disposed at the proprotor hub.

10. The proprotor system as recited in claim 7 wherein the pitch-span converter further comprises a helical threaded screw.

11. The proprotor system as recited in claim 7 wherein the pitch-span converter further comprises a plurality of pitch-span converters, each pitch-span converter configured to convert the collective pitch of the proprotor blades about the pitch change axes into the position of a respective blade tip extension.

12. The proprotor system as recited in claim 11 wherein each pitch-span converter is coupled to a respective blade tip extension by a spanwise link disposed inside a respective proprotor blade.

13. The proprotor system as recited in claim 12 further comprising a plurality of springs, each spring biasing a respective blade tip extension into the extended position; wherein, each spanwise link further comprises a cable configured to pull a respective blade tip extension into the retracted position against the bias of a respective spring.

14. The proprotor system as recited in claim 1 further comprising a proprotor hub and a plurality of tension-torsion straps, each proprotor blade coupled to the proprotor hub via a respective tension-torsion strap, the tension-torsion straps twistable between a wound position and an unwound position in response to the collective pitch of the proprotor blades;

wherein, the proprotor blades are in the extended position when the tension-torsion straps are in the unwound position and the retracted position when the tension-torsion straps are in the wound position.

15. The proprotor system as recited in claim 14 wherein the proprotor blades are rotatable between a plurality of collective pitches about the pitch change axes including a higher collective pitch and a lower collective pitch, the tension-torsion straps in one of the wound position or the unwound position at the higher collective pitch and the other of the wound position or the unwound position at the lower collective pitch.

16. A rotorcraft comprising:

a fuselage; and

a proprotor system coupled to the fuselage, the proprotor system comprising:

a duct; and

a plurality of proprotor blades surrounded by the duct, each proprotor blade rotatable about a respective pitch change axis, the proprotor blades configured to change collective pitch about the pitch change axes;

wherein, the proprotor blades are extendable along the pitch change axes into a plurality of positions including a retracted position and an extended position; and wherein, the proprotor blades are configured to change between the retracted position and the extended position based on the collective pitch of the proprotor blades, thereby controlling a tip gap between the proprotor blades and the duct.

17. The rotorcraft as recited in claim 16 wherein the rotorcraft is convertible between a vertical takeoff and landing flight mode and a forward flight mode, the proprotor blades having a lower collective pitch in the vertical takeoff and landing flight mode and a higher collective pitch in the forward flight mode; and

wherein, the proprotor blades are configured to change between the retracted position and the extended position based on the flight mode of the rotorcraft.

18. The rotorcraft as recited in claim **17** wherein the proprotor blades change into the extended position in the forward flight mode. 5

19. The rotorcraft as recited in claim **17** wherein the proprotor blades change into the retracted position in the forward flight mode.

20. The rotorcraft as recited in claim **16** wherein the proprotor blades are extendable along the pitch change axes into a plurality of intermediate positions between the retracted position and the extended position based on the collective pitch of the proprotor blades. 10

* * * * *

15