



US011205058B2

(12) **United States Patent**  
**Volpi et al.**

(10) **Patent No.:** **US 11,205,058 B2**  
(45) **Date of Patent:** **\*Dec. 21, 2021**

(54) **INTERROGATOR AND INTERROGATION  
SYSTEM EMPLOYING THE SAME**

(71) Applicant: **Medical IP Holdings, LP**, Addison, TX  
(US)

(72) Inventors: **John P. Volpi**, Garland, TX (US);  
**Logan Scott**, Fort Collins, CO (US);  
**Eric McMurry**, Richardson, TX (US)

(73) Assignee: **Lone Star SCM Systems, LP**,  
Addison, TX (US)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-  
claimer.

(21) Appl. No.: **16/853,673**

(22) Filed: **Apr. 20, 2020**

(65) **Prior Publication Data**

US 2020/0320257 A1 Oct. 8, 2020

**Related U.S. Application Data**

(63) Continuation of application No. 16/252,652, filed on  
Jan. 20, 2019, now Pat. No. 10,628,645, which is a  
continuation of application No. 15/647,131, filed on  
Jul. 11, 2017, now Pat. No. 10,185,853, which is a  
continuation of application No. 14/611,425, filed on  
Feb. 2, 2015, now Pat. No. 9,710,683, which is a  
(Continued)

(51) **Int. Cl.**  
**G06K 7/10** (2006.01)  
**G06K 7/00** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **G06K 7/10366** (2013.01); **G06K 7/0008**  
(2013.01)

(58) **Field of Classification Search**

CPC ..... G06K 7/10366; G06K 7/0008

USPC ..... 375/260

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

3,367,431 A 2/1968 Baker  
3,564,662 A 2/1971 Dold  
3,675,190 A 7/1972 Auer, Jr. et al.

(Continued)

**FOREIGN PATENT DOCUMENTS**

DE 19923983 A1 12/2000  
EP 0639817 A1 2/1995

(Continued)

**OTHER PUBLICATIONS**

PCT/US2005/007292 PCT International Search Report dated Jul.  
29, 2005, 3 pages.

(Continued)


*Primary Examiner* — Michael R Neff

(74) *Attorney, Agent, or Firm* — Boisbrun Hofman, PLLC

(57) **ABSTRACT**

A control and processing system for use with an interrogator and an interrogation system employing the same. In one embodiment, the control and processing system includes a correlation subsystem having a correlator that correlates a reference code with a reply code from a radio frequency identification (RFID) tag and provides a correlation signal therefrom. The control and processing system also includes a decision subsystem that verifies a presence of the RFID tag as a function of the correlation signal.

**20 Claims, 25 Drawing Sheets**



**Related U.S. Application Data**

continuation of application No. 11/071,652, filed on  
Mar. 3, 2005, now Pat. No. 8,948,279.

(60) Provisional application No. 60/549,853, filed on Mar.  
3, 2004.

(56) **References Cited**

## U.S. PATENT DOCUMENTS

3,802,555 A	4/1974	Grasty et al.	5,781,442 A	7/1998	Engleson et al.
3,941,132 A	3/1976	Lenaghan	5,792,138 A	8/1998	Shipp
3,965,907 A	6/1976	Hardy et al.	5,793,324 A	8/1998	Aslanidis et al.
4,114,601 A	9/1978	Abels	5,801,371 A	9/1998	Kahn et al.
4,151,913 A	5/1979	Freitag	5,827,215 A	10/1998	Yoon
4,164,320 A	8/1979	Irazaqui et al.	5,864,323 A	1/1999	Berthon
4,193,405 A	3/1980	Abels	5,923,001 A	7/1999	Morris et al.
4,213,197 A	7/1980	Mágori	5,931,824 A	8/1999	Stewart et al.
4,249,128 A	2/1981	Karbowski	5,979,941 A	11/1999	Mosher, Jr. et al.
4,289,032 A	9/1981	Tominaga et al.	5,986,550 A	11/1999	Rapaport et al.
4,295,537 A	10/1981	McAvinn et al.	6,026,818 A	2/2000	Blair et al.
4,342,391 A	8/1982	Schainholz	6,037,870 A	3/2000	Alessandro
4,359,015 A	11/1982	Ritchey	6,097,374 A	8/2000	Howard
4,361,231 A	11/1982	Patience	6,150,921 A	11/2000	Werb et al.
4,422,548 A	12/1983	Cheesman et al.	D435,557 S	12/2000	Eisenberg et al.
4,422,584 A	12/1983	Dashnier et al.	6,169,483 B1	1/2001	Ghaffari et al.
4,498,076 A	2/1985	Lichtblau	6,211,672 B1	4/2001	Baumann et al.
4,510,489 A	4/1985	Anderson, III et al.	6,230,888 B1	5/2001	Frieze et al.
4,514,692 A	4/1985	Johnson et al.	6,264,106 B1	7/2001	Bridgelall
4,526,177 A	7/1985	Rudy et al.	6,265,962 B1	7/2001	Black et al.
4,541,992 A	9/1985	Jerge et al.	6,294,997 B1	9/2001	Paratore et al.
4,643,303 A	2/1987	Arp et al.	6,300,872 B1	10/2001	Mathias et al.
4,650,464 A	3/1987	Ruiz et al.	6,305,605 B1	10/2001	Goetz et al.
4,658,818 A	4/1987	Miller, Jr. et al.	6,307,517 B1	10/2001	Lee
4,821,023 A	4/1989	Parks	6,342,187 B1	1/2002	Jacob et al.
4,832,198 A	5/1989	Alikhan	6,366,206 B1	4/2002	Ishikawa et al.
4,855,909 A	8/1989	Vincent et al.	6,377,176 B1	4/2002	Lee
4,857,713 A	8/1989	Brown	6,394,355 B1	5/2002	Schlieffers et al.
4,887,715 A	12/1989	Spahn et al.	D459,246 S	6/2002	Power et al.
4,889,230 A	12/1989	Zachry	6,424,262 B2	7/2002	Garber et al.
4,903,837 A	2/1990	Duello	6,424,263 B1	7/2002	Lee et al.
4,907,000 A	3/1990	Tabourier	6,429,776 B1	8/2002	Alicot et al.
4,922,922 A	5/1990	Pollock et al.	6,446,794 B1	9/2002	Hacikyan
4,943,939 A	7/1990	Hoover	6,448,886 B2 *	9/2002	Garber ..... H01Q 1/2225 340/10.1
5,009,275 A	4/1991	Sheehan	6,483,427 B1	11/2002	Werb
5,031,642 A	7/1991	Nosek	6,484,050 B1	11/2002	Carroll et al.
5,057,095 A	10/1991	Fabian	6,486,783 B1	11/2002	Hausladen et al.
5,103,210 A	4/1992	Rode et al.	6,492,905 B2	12/2002	Mathias et al.
5,105,829 A	4/1992	Fabian et al.	6,492,933 B1	12/2002	McEwan
5,107,862 A	4/1992	Fabian et al.	6,496,112 B1	12/2002	Vega
5,186,322 A	2/1993	Harreld et al.	6,496,113 B2	12/2002	Lee et al.
5,188,126 A	2/1993	Fabian et al.	6,496,806 B1	12/2002	Horwitz et al.
5,190,059 A	3/1993	Fabian et al.	6,509,217 B1	1/2003	Reddy
5,231,273 A	7/1993	Caswell et al.	6,512,478 B1	1/2003	Chien
5,241,568 A	8/1993	Fernandez et al.	6,515,591 B2	2/2003	Lake et al.
5,284,632 A	2/1994	Kudla et al.	6,516,272 B2	2/2003	Lin
5,300,120 A	4/1994	Knapp et al.	6,523,681 B1	2/2003	Hacikyan
5,329,944 A	7/1994	Fabian et al.	6,535,175 B2	3/2003	Brady et al.
5,353,011 A	10/1994	Wheeler et al.	6,600,905 B2	7/2003	Greeff et al.
5,354,975 A	10/1994	Ishibashi et al.	6,609,656 B1	8/2003	Elledge
5,357,240 A	10/1994	Sanford et al.	6,618,024 B1	9/2003	Adair et al.
5,374,261 A	12/1994	Yoon	6,659,344 B2	12/2003	Otto et al.
5,381,137 A	1/1995	Ghaem et al.	6,686,829 B1	2/2004	Hohberger et al.
5,382,784 A	1/1995	Eberhardt	6,696,954 B2	2/2004	Chung
5,414,730 A	5/1995	Lundquist et al.	6,698,285 B1	3/2004	Hacikyan
5,433,929 A	7/1995	Riihimaki et al.	6,708,881 B2	3/2004	Hartmann
5,443,082 A	8/1995	Mewburn	6,720,866 B1	4/2004	Sorrells et al.
5,451,380 A	9/1995	Zinnanti	6,724,309 B2	4/2004	Grose et al.
5,456,718 A	10/1995	Szymaitis	6,753,782 B2	6/2004	Power
5,460,178 A	10/1995	Hudon et al.	6,756,880 B2	6/2004	Hartmann
5,491,468 A	2/1996	Everett et al.	6,757,068 B2	6/2004	Foxlin
5,528,232 A	6/1996	Verma et al.	6,759,789 B2	7/2004	Hartmann
5,594,384 A	1/1997	Carroll et al.	6,759,968 B2	7/2004	Zierolf
5,610,811 A	3/1997	Honda	6,777,623 B2	8/2004	Ballard
5,629,498 A	5/1997	Pollock et al.	6,794,000 B2	9/2004	Adams et al.
5,650,596 A	7/1997	Morris et al.	6,812,707 B2	11/2004	Yonezawa et al.
5,689,239 A	11/1997	Turner et al.	6,812,842 B2	11/2004	Dimmer
			6,822,570 B2	11/2004	Dimmer et al.
			6,838,874 B1	1/2005	Franklin
			6,838,990 B2	1/2005	Dimmer
			6,853,194 B2	2/2005	Nelson et al.
			6,859,190 B2	2/2005	Pillai et al.
			6,861,954 B2	3/2005	Levin
			6,940,408 B2	9/2005	Ferguson et al.
			6,959,031 B2	10/2005	Haynes et al.
			6,967,574 B1	11/2005	Nelson
			6,987,451 B2	1/2006	McKeown et al.
			6,989,750 B2	1/2006	Shanks et al.



(56)

**References Cited****U.S. PATENT DOCUMENTS**

6,992,952 B2 1/2006 Endo et al.  
6,998,541 B2 2/2006 Morris et al.  
7,001,366 B2 2/2006 Ballard  
7,005,968 B1 2/2006 Bridgelall  
7,009,496 B2 3/2006 Arneson et al.  
7,009,519 B2 3/2006 Leonard et al.  
7,014,100 B2 3/2006 Zierolf  
7,019,650 B2 3/2006 Volpi et al.  
7,023,356 B2 4/2006 Burkhardt et al.  
7,079,034 B2 7/2006 Stilp  
7,095,311 B2 8/2006 Coates et al.  
7,100,052 B2 8/2006 Ghazarian  
7,113,125 B2 9/2006 Le Sesne  
7,126,479 B2 10/2006 Claessens et al.  
7,129,840 B2 10/2006 Hull et al.  
7,148,803 B2 12/2006 Bandy et al.  
7,158,034 B2 1/2007 Corbett  
7,159,654 B2 1/2007 Ellison et al.  
7,172,117 B2 2/2007 Moore  
7,176,798 B2 2/2007 Dimmer et al.  
7,193,504 B2 3/2007 Carrender et al.  
7,245,227 B2 7/2007 Winter et al.  
7,301,648 B2 11/2007 Foxlin  
7,307,530 B2 12/2007 Fabian et al.  
7,411,506 B2 8/2008 Volpi et al.  
7,420,468 B2 9/2008 Fabian et al.  
7,501,948 B2 3/2009 Roerman et al.  
7,540,287 B2 6/2009 Chole  
7,541,933 B2 6/2009 Volpi et al.  
7,548,153 B2 6/2009 Gravelle et al.  
7,557,711 B2 7/2009 Volpi et al.  
7,600,613 B2 10/2009 Kang et al.  
7,671,744 B2 \* 3/2010 Volpi ..... G06Q 10/08  
340/572.1  
7,755,491 B2 7/2010 Volpi et al.  
7,760,097 B2 7/2010 Volpi et al.  
7,764,178 B2 7/2010 Roerman et al.  
7,893,840 B2 2/2011 Volpi et al.  
7,948,357 B2 5/2011 Bodin  
8,019,471 B2 9/2011 Bogash et al.  
8,174,366 B2 \* 5/2012 Volpi ..... G06K 17/00  
340/10.3  
8,542,717 B2 \* 9/2013 Volpi ..... G06K 7/0008  
375/150  
8,948,279 B2 \* 2/2015 Volpi ..... G06K 7/10366  
375/260  
9,710,683 B2 \* 7/2017 Volpi ..... G06K 7/10366  
10,185,853 B2 \* 1/2019 Volpi ..... G06K 7/10366  
10,628,645 B2 \* 4/2020 Volpi ..... G06K 7/10366  
2001/0008390 A1 7/2001 Berquist et al.  
2001/0013830 A1 8/2001 Garber et al.  
2001/0034530 A1 10/2001 Malackowski et al.  
2002/0005774 A1 1/2002 Rudolph et al.  
2002/0008623 A1 1/2002 Garber et al.  
2002/0010679 A1 1/2002 Felsher  
2002/0044096 A1 4/2002 Chung  
2002/0048330 A1 4/2002 Schetelig et al.  
2002/0060630 A1 5/2002 Power  
2002/0067263 A1 6/2002 Tafoya et al.  
2002/0070845 A1 6/2002 Reisinger et al.  
2002/0093431 A1 7/2002 Zierolf  
2002/0105424 A1 8/2002 Alicot et al.  
2002/0158120 A1 10/2002 Zierolf  
2002/0017998 A1 11/2002 Price  
2002/0167397 A1 11/2002 Eroglu et al.  
2003/0006762 A1 1/2003 Clements  
2003/0007473 A1 \* 1/2003 Strong ..... G01S 13/78  
370/338  
2003/0025604 A1 2/2003 Freeman  
2003/0076230 A1 4/2003 Runyon et al.  
2003/0083964 A1 5/2003 Horwitz et al.  
2003/0111540 A1 6/2003 Hartmann  
2003/0128100 A1 7/2003 Burkhardt et al.  
2003/0137403 A1 7/2003 Carrender et al.

2003/0141366 A1 7/2003 Hartmann  
2003/0142691 A1 7/2003 Hartmann  
2003/0142741 A1 7/2003 Hartmann  
2003/0142742 A1 7/2003 Hartmann  
2003/0145036 A1 7/2003 Hartmann et al.  
2003/0179072 A1 9/2003 Hartmann  
2003/0179077 A1 9/2003 Hartmann et al.  
2003/0179093 A1 9/2003 Hartmann et al.  
2003/0192722 A1 10/2003 Ballard  
2003/0194859 A1 10/2003 Huang  
2004/0031626 A1 2/2004 Morris et al.  
2004/0046643 A1 3/2004 Becker et al.  
2004/0065733 A1 \* 4/2004 Fukuoka ..... G06K 7/10029  
235/435  
2004/0075361 A1 4/2004 Hartmann  
2004/0075560 A1 4/2004 Hartmann et al.  
2004/0085192 A1 5/2004 Hartmann  
2004/0090868 A1 5/2004 Endo et al.  
2004/0100376 A1 5/2004 Lye et al.  
2004/0128133 A1 7/2004 Sacks et al.  
2004/0129279 A1 7/2004 Fabian et al.  
2004/0142660 A1 7/2004 Churan  
2004/0155651 A1 8/2004 Britton  
2004/0174261 A1 9/2004 Volpi et al.  
2004/0250819 A1 12/2004 Blair et al.  
2004/0257224 A1 \* 12/2004 Sajkowsky ..... G16H 10/65  
340/539.13  
2005/0038574 A1 2/2005 Gila et al.  
2005/0088299 A1 4/2005 Bandy et al.  
2005/0099302 A1 5/2005 Lieffort et al.  
2005/0116033 A1 6/2005 Moore  
2005/0128519 A1 6/2005 Yamauchi  
2005/0159982 A1 7/2005 Showalter et al.  
2005/0201450 A1 9/2005 Volpi et al.  
2005/0207617 A1 9/2005 Sarnoff  
2005/0230110 A1 10/2005 Ellison et al.  
2005/0240305 A1 10/2005 Bogash et al.  
2005/0248456 A1 11/2005 Britton, Jr. et al.  
2005/0263591 A1 \* 12/2005 Smith ..... G06K 19/0723  
235/385  
2005/0282558 A1 12/2005 Choi et al.  
2006/0006986 A1 1/2006 Gravelle et al.  
2006/0017545 A1 1/2006 Volpi et al.  
2006/0044137 A1 3/2006 Morris et al.  
2006/0077036 A1 4/2006 Roerman et al.  
2006/0132351 A1 6/2006 Le Sesne  
2006/0164212 A1 7/2006 Roz  
2006/0241399 A1 10/2006 Fabian  
2006/0265164 A1 11/2006 Clark  
2007/0032224 A1 2/2007 Boyer et al.  
2007/0035383 A1 2/2007 Roerman et al.  
2007/0210921 A1 9/2007 Volpi et al.  
2007/0216526 A1 9/2007 Volpi et al.  
2007/0252697 A1 \* 11/2007 Elledge ..... G08B 13/14  
340/572.1  
2008/0018432 A1 1/2008 Volpi et al.  
2008/0018450 A1 1/2008 Volpi et al.  
2008/0230598 A1 9/2008 Bodin  
2009/0040025 A1 2/2009 Volpi et al.  
2009/0045917 A1 2/2009 Volpi et al.  
2009/0160605 A1 2/2009 Roerman et al.  
2010/0317713 A1 2/2010 Roerman et al.  
2017/0316236 A1 11/2017 Volpi et al.  
2019/0213365 A1 7/2019 Volpi et al.

**FOREIGN PATENT DOCUMENTS**

EP 0 948 940 A1 10/1999  
FR 2 635 259 2/1990  
FR 2635259 2/1990  
WO WO 96/04530 2/1996  
WO WO 99/11086 A1 3/1999

**OTHER PUBLICATIONS**

U.S. Appl. No. 10/841,192, filed May 7, 2004, Roerman, et al.  
U.S. Appl. No. 10/997,617, filed Nov. 24, 2004, Tepera, et al.

(56)

**References Cited**

## OTHER PUBLICATIONS

“Whitepaper: EPCglobal Class 1 Gen 2 RFID Specification,” 2005 (approved Dec. 2004), 7 pages, [http://www.alientechnology.com/docs/AT\\_wp\\_EPCGlobal\\_WEB.pdf](http://www.alientechnology.com/docs/AT_wp_EPCGlobal_WEB.pdf), Alien Technology Corporation, Morgan Hill, CA.

“EPC™ Radio-Frequency Identity Protocols Class-1 Generation-2 UHF RFID Protocol for Communications at 860 MHz-960 MHz,” Version 1.0.9, Jan. 2005, 94 pp., EPCglobal Inc.™, Lawrenceville, NJ.

“Making Health Care Saver: A Critical Analysis of Patient Safety Practices” Evidence Report/Technology Assessment, No. 43, Prepared by University of California at San Francisco (UCSF)—Stanford University, Jul. 20, 2001.


“Technical Report 860 MHz-930 MHz Class I Radio Frequency Identification Tag Radio Frequency & Logical Communication Interface Specification Candidate Recommendation,” Version 1.0.1, Nov. 14, 2002, Auto-ID Center, Massachusetts Institute of Technology, Cambridge, MA.

Codd, E.F., “A Relational Model of Data for Large Shared Data Banks,” Communications of the ACM, Jun. 1970, pp. 377-387, vol. 13, No. 6, Association for Computing Machinery, New York, NY.

“Automatic Identification—Radio Frequency Identification for Item Management,” Part 6: Mode 3—Physical Layer, Anti Collision System and Protocols for Ultra High Frequency (UHF) Systems, Feb. 1, 2002, pp. 48-50, Reference No. of Document: ISO/IEC WD 18000-6 Mode 3, Committee Identification: ISO/IEC SC31/WG 4, Secretariat: ANSI.

\* cited by examiner









FIG. 2







FIG. 4








FIG. 6





FIG. 7








FIG. 9




FIG. 10




FIG. 11





FIG. 12








FIG. 14




FIG. 15




FIG. 16




FIG. 17






FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23






FIG. 24




FIG. 25




FIG. 26




FIG. 29




FIG. 27






FIG. 28





FIG. 30









FIG. 32






FIG. 34



## INTERROGATOR AND INTERROGATION SYSTEM EMPLOYING THE SAME

This is a Continuation of application Ser. No. 16/252,652, entitled "Interrogator and Interrogation System Employing the Same," filed on Jan. 20, 2019, currently allowed which is a continuation of application Ser. No. 15/647,131, entitled "Interrogator and Interrogation System Employing the Same," filed on Jul. 11, 2017, now U.S. Pat. No. 10,185,853, which is a Continuation of application Ser. No. 14/611,425, entitled "Interrogator and Interrogation System Employing the Same," filed on Feb. 2, 2015, now U.S. Pat. No. 9,710,683, which is a Continuation of application Ser. No. 11/071,652, entitled "Interrogator and Interrogation System Employing the Same," filed on Mar. 3, 2005, now U.S. Pat. No. 8,948,279, which claims the benefit of U.S. Provisional Application No. 60/549,853, entitled "An Interrogator and Interrogation System Employing the Same," filed on Mar. 3, 2004, which are incorporated herein by reference.

### TECHNICAL FIELD

The present invention is directed, in general, to communication systems and, more specifically, to an interrogator, method of discerning radio frequency identification (RFID) objects, and an interrogation system employing the same.

### BACKGROUND

Asset tracking for the purposes of inventory control or the like is employed in a multitude of industry sectors such as in the food industry, apparel markets and any number of manufacturing sectors, to name a few. In many instances, a bar coded tag or radio frequency identification (RFID) tag is affixed to the asset and a reader interrogates the item to read the tag and ultimately to account for the asset being tracked. Although not readily adopted, an analogous system may be employed in a medical environment to track equipment such as an Electrocardiogram (EKG) machine or other modular patient monitoring equipment.

Of particular note is a surgical environment in which for preparation for surgery a previously sterilized instrument kit of surgical instruments and disposable items (collectively referred to as surgical items) is brought into a surgical suite. The instrument kit contains an assortment of surgical items including hemostats, clamps, forceps, scissors, sponges, and the like, based on the type of surgery to be performed. Typically, a scrub nurse removes the surgical items from the kit and arranges them on a back table located behind the operating table. The surgical items are organized in rows on rolled toweling for ease of access and handling by a surgeon and supporting team. During the course of a surgical procedure, the surgical items are often positioned on a "Mayo" stand proximate the operating table, while the unused surgical items remain on the back table. During the course of and at the conclusion of the surgery, all of the surgical items must be carefully counted to, among other things, avoid leaving any surgical items in a patient.

In view of the consequences, surgical items are typically counted at least three times during the course of a surgical procedure. The first count is performed prior to the start of the procedure; the second count is performed prior to a closure of the patient; the third count is performed at the conclusion of the procedure. In many instances such as when more than one surgical team is assigned to a procedure, many more counts of the surgical items, often involving different personnel (e.g., a circulating nurse and a scrub

nurse), are performed. As a matter of fact, the Association of Perioperative Registered Nurses (AORN) advocates four counts of the surgical items as part of its recommended practices for surgical procedures. Additionally, to keep track of the counts of the surgical items, rudimentary systems such as visual records scribbled on whiteboards or other more progressive computer tallying systems to designate the count of the surgical items are often employed.

In common practice, access to and from an operating room in the surgical suite is restricted during the counting process thereby resulting in a detention of valuable professional personnel. A discrepancy in the count must be resolved by additional counts, physical examination of the patient or x-ray examination, if necessary. Although it is unusual for a discrepancy in the count to result from a surgical item remaining in the patient, counting and recounting occurs in every surgical procedure and the repercussions associated with the loss of a surgical item is of grave concern to a medical facility and the medical professionals.

Thus, the multiple manual counting of surgical items is time consuming, ties up key professional personnel, contributes to surgical suite down time, distracts personnel from the surgical procedure, lengthens the time the patient is exposed to anesthesia leading to an increase in mortality and morbidity risk, is generally distasteful to all involved, and still results in errors wherein materials are left in the patient. It should be quite understandable that the average cost overruns of such delays associated with the personnel, capital equipment and the surgical suite itself can run into the tens of thousands of dollars per procedure. On an annual basis, the loss of productivity associated with the surgical suite is quite sizeable and should be addressed to bolster the bottom line of a medical facility.

Even with the degree of caution cited above, the problem associated with the loss of surgical items, especially surgical items retained within patients, is a serious one and has a significant influence on the costs of malpractice insurance. As a matter of fact, retained foreign bodies within a patient is one of the most prevalent categories of malpractice claims and the most common retained foreign body is a sponge. In accordance therewith, there is a diagnosis known as "gossypiboma" (wherein *gossypium* is Latin for cotton and boma is Swahili for place of concealment) for the retention of a sponge-like foreign body in a patient. The medical literature is scattered with reports of presentations of retained sponges found days, months, or even years after a surgical procedure.

The sponge is typically made of gauze-like material with dimensions often covering a four-inch square or a two-inch by four-inch rectangle. At one time sponges were commonly made of cotton, but now a number of filament materials are used. Occasionally, a filament of radiopaque material [e.g., barium sulfate (BaSO<sub>4</sub>)] is woven into the surgical sponge, or a tab of that material is attached to the surgical sponge. The filament or tab is provided to produce a distinct signature on an x-ray machine for the purpose of determining if a sponge is present in the patient. While this is generally effective, even these filaments or tabs are not 100% effective in aiding the location of the sponges. Different researchers report that x-ray methods to supplement manual counting are fallible.

Moreover, in cases when a sponge remains in the body for a long time, the radiopaque filament can become difficult to locate and may even conform to internal structures. Some have suggested that a computerized tomography (CT) scan can be more effective than an x-ray examination because the CT scans and ultrasonography may detect the reduced density of a sponge and its characteristic pattern of air or gas



bubbles trapped within the sponge. Many radiologists have published a number of papers over the years on the problem of finding lost sponges and these are generally known in the field of medicine.

As mentioned above, there is a widespread practice in other fields for counting, tracking and accounting for items and two of the more prevalent and lowest cost approaches involve various types of bar coding and RFID techniques. As with bar coding, the RFID techniques are primarily used for automatic data capture and, to date, the technologies are generally not compatible with the counting of surgical items. A reason for the incompatibility in the medical environment for the bar coding and RFID techniques is a prerequisite to identify items covered in fluids or waste, and the exigencies associated with the sterilizing of surgical items including a readable tag.

Even in view of the foregoing limitations for the application of RFID techniques in the medical environment wherein less than ideal conditions are prevalent, RFID tags have been compatible with a number of arduous environments. In the pharmaceutical industry, for instance, RFID tags have survived manufacturing processes that require products to be sterilized for a period of time over 120 degrees Celsius. Products are autoclaved while mounted on steel racks tagged with an RFID tag such that a rack identification (ID) number and time/date stamp can be automatically collected at the beginning and end of the process as the rack travels through the autoclave on a conveyor. The RFID tags can be specified to withstand more than 1000 hours at temperatures above 120 degrees Celsius. This is just one example of how RFID tags can withstand the arduous environment including the high temperatures associated with an autoclave procedure, whereas a bar code label is unlikely to survive such treatment.

While identification tags or labels may be able to survive the difficult conditions associated with medical applications, there is yet another challenge directed to attaching an identification element to a surgical item or any small device. The RFID tags are frequently attached to devices by employing mechanical techniques or may be affixed with sewing techniques. A more common form of attachment of an RFID tag to a device is by bonding techniques including encapsulation or adhesion.

While medical device manufacturers have multiple options for bonding, critical disparities between materials may exist in areas such as biocompatibility, bond strength, curing characteristics, flexibility and gap-filling capabilities. A number of bonding materials are used in the assembly and fabrication of both disposable and reusable medical devices, many of which are certified to United States Pharmacopoeia Class VI requirements. These products include epoxies, silicones, ultraviolet curables, cyanoacrylates, and special acrylic polymer formulations.

In many instances, the toughness and versatile properties of biocompatible epoxies make them an attractive alternative. Epoxies form strong and durable bonds, fill gaps effectively and adhere well to most types of substrates. Common uses for medical epoxies include a number of applications which require sterilization compatibility such as bonding lenses in endoscopes, attaching plastic tips to tubing in disposable catheters, coating implantable prosthetic devices, bonding balloons to catheters for balloon angioplasty, and bonding diamond scalpel blades for coronary bypass surgery, to name a few. A wide range of such materials are available and some provide high strength bonds which are tough, water resistant, low in outgassing, and dimensionally stable over a temperature range of up to

600 degrees Fahrenheit. Some epoxies can withstand repeated sterilization such as autoclaving, radiation, ethylene oxide and cold (e.g., chemical) sterilization methods.

As previously mentioned, familiar applications for RFID techniques include "smart labels" in airline baggage tracking and in many stores for inventory control and for theft deterrence. In some cases, the smart labels may combine both RFID and bar coding techniques. The tags may include batteries and typically only function as read only devices or as read/write devices. Less familiar applications for RFID techniques include the inclusion of RFID tags in automobile key fobs as anti-theft devices, identification badges for employees, and RFID tags incorporated into a wrist band as an accurate and secure method of identifying and tracking prison inmates and patrons at entertainment and recreation facilities. Within the medical field, RFID tags have been proposed for tracking patients and patient files, employee identification badges, identification of blood bags, and process management within the factories of manufacturers making products for medical practice.

Typically, RFID tags without batteries (i.e., passive devices) are smaller, lighter and less expensive than those that are active devices. The passive RFID tags are typically maintenance free and can last for long periods of time. The passive RFID tags are relatively inexpensive, generally as small as an inch in length, and about an eighth of an inch in diameter when encapsulated in hermetic glass cylinders. Recent developments indicate that they will soon be even smaller. The RFID tags can be encoded with 64 or more bits of data that represent a large number of unique ID numbers (e.g., about 18,446,744,073,709,551,616 unique ID numbers). Obviously, this number of encoded data provides more than enough unique codes to identify every item used in a surgical procedure or in other environments that may benefit from asset tracking.

An important attribute of RFID interrogation systems is that a number of RFID tags should be interrogated simultaneously stemming from the signal processing associated with the techniques of impressing the identification information on the carrier signal. A related and desirable attribute is that there is not typically a minimum separation required between the RFID tags. Using an anti-collision algorithm, multiple RFID tags may be readily identifiable and, even at an extreme reading range, only minimal separation (e.g., five centimeters or less) to prevent mutual de-tuning is generally necessary. Most other identification systems, such as systems employing bar codes, usually impose that each device be interrogated separately. The ability to interrogate a plurality of closely spaced RFID tags simultaneously is desirable for applications requiring rapid interrogation of a large number of items.

In general, the sector of radio frequency identification is one of the fastest growing areas within the field of automatic identification and data collection. A reason for the proliferation of RFID systems is that RFID tags may be affixed to a variety of diverse objects (also referred to as "RFID objects") and a presence of the RFID tags may be detected without actually physically viewing or contacting the RFID tag. As a result, multiple applications have been developed for the RFID systems and more are being developed every day.

The parameters for the applications of the RFID systems vary widely, but can generally be divided into three significant categories. First, an ability to read the RFID tags rapidly. Another category revolves around an ability to read a significant number of the RFID tags simultaneously (or nearly simultaneously). A third category stems from an



## 5

ability to read the RFID tags reliably at increased ranges or under conditions wherein the radio frequency signals have been substantially attenuated. While significant progress has been made in the area of reading multiple RFID tags almost simultaneously (see, for instance, U.S. Pat. No. 6,265,962 5 entitled "Method for Resolving Signal Collisions Between Multiple RFID Transponders in a Field," to Black, et al., issued Jul. 24, 2001, which is incorporated herein by reference), there is still room for significant improvement in the area of reading the RFID tags reliably at increased ranges or under conditions when the radio frequency signals have been substantially attenuated. 10

Accordingly, what is needed in the art is an interrogator, interrogation system and related method to identify and account for all types of items regardless of the environment or application that overcomes the deficiencies of the prior art. 15

## SUMMARY OF THE INVENTION

These and other problems are generally solved or circumvented, and technical advantages are generally achieved, by advantageous embodiments of the present invention which includes an interrogator and an interrogation system employing the same. In one embodiment, the interrogator includes a control and processing system having a correlation subsystem that correlates a reference code with a reply code from a radio frequency identification (RFID) tag and provides a correlation signal therefrom. The control and processing system also includes a decision subsystem that verifies a presence of the RFID tag as a function of the correlation signal. 20

In another aspect, the present invention provides an interrogator including an RFID sensing subsystem that provides a reply code associated with an RFID tag and a control and processing subsystem. The control and processing subsystem includes a correlation subsystem that correlates a reference code with the reply code and provides a correlation signal therefrom. The control and processing subsystem also includes a decision subsystem that verifies a presence of the RFID tag as a function of the correlation signal. The interrogator may also include a metal sensing subsystem that provides a signal having a metal signature representing a presence of a metal object. The control and processing subsystem may be configured to discern a presence of the metal object from the signal. 25

In yet another aspect, the present invention provides an interrogation system including a computer system and a transceiver that transmits and receives signals for the computer system. The interrogation system also includes an interrogator having an RFID sensing subsystem that provides a reply code associated with an RFID tag of an RFID object. The interrogator also includes a control and processing subsystem having a correlation subsystem that correlates a reference code with the reply code and provides a correlation signal therefrom. The control and processing subsystem also includes a decision subsystem that verifies a presence of the RFID tag as a function of the correlation signal. The interrogator also includes a communications subsystem that communicates with the transceiver. 30

The foregoing has outlined rather broadly the features and technical advantages of the present invention in order that the detailed description of the invention that follows may be better understood. Additional features and advantages of the invention will be described hereinafter which form the subject of the claims of the invention. It should be appreciated by those skilled in the art that the conception and 35

## 6

specific embodiment disclosed may be readily utilized as a basis for modifying or designing other structures or processes for carrying out the same purposes of the present invention. It should also be realized by those skilled in the art that such equivalent constructions do not depart from the spirit and scope of the invention as set forth in the appended claims.

## BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the present invention, reference is now made to the following descriptions taken in conjunction with the accompanying drawings, in which: 40

FIG. 1 illustrates a diagram of an embodiment of a communication system employable in a medical environment constructed in accordance with the principles of the present invention, 45

FIG. 2 illustrates a pictorial diagram of an embodiment of an interrogation system employable within an operating room of a medical facility and constructed in accordance with the principles of the present invention, 50

FIG. 3 illustrates a pictorial diagram of an embodiment of an interrogation system employable within an operating room of a medical facility and constructed in accordance with the principles of the present invention, 55

FIG. 4 illustrates a pictorial diagram of an embodiment of an interrogator constructed in accordance with the principles of the present invention, 60

FIG. 5 illustrates a system diagram of an embodiment of an interrogator constructed in accordance with the principles of the present invention, 65

FIG. 6 illustrates a block diagram of another embodiment of an interrogator constructed in accordance with the principles of the present invention, 70

FIG. 7 illustrates a system diagram of an alternative embodiment of an interrogator constructed in accordance with the principles of the present invention, 75

FIG. 8 illustrates a block diagram of another embodiment of an interrogator constructed in accordance with the principles of the present invention, 80

FIG. 9 illustrates a block diagram of an embodiment of a control and processing subsystem constructed in accordance with the principles of the present invention, 85

FIG. 10 illustrates a block diagram of an embodiment of an interrogation system demonstrating the capabilities associated with radio frequency identification according to the principles of the present invention, 90

FIG. 11 illustrates a block diagram of an embodiment of a reply code from an RFID tag in response to a query by an interrogator constructed according to the principles of the present invention, 95

FIG. 12 illustrates a waveform diagram of an exemplary one-bit cell of a response from an RFID tag to an interrogator in accordance with the principles of the present invention, 100

FIG. 13 illustrates a waveform diagram of an exemplary response from an RFID tag in accordance with the principles of the present invention, 105

FIG. 14 illustrates a waveform diagram of a spectral response associated with the response from the RFID tag illustrated in FIG. 13, 110

FIG. 15 illustrates a waveform diagram demonstrating a representative signal to noise gain employing an interrogator in accordance with the principles of the present invention, 115



FIG. 16 illustrates a block diagram of an embodiment of an initialization stage of an interrogation system in accordance with the principles of the present invention,

FIG. 17 illustrates a block diagram of an embodiment of a post initialization stage of an interrogation system in accordance with the principles of the present invention,

FIG. 18 illustrates a flow chart of an embodiment of a method of detecting an RFID tag according to the principles of the present invention,

FIG. 19 illustrates a block diagram of portions of a control and processing subsystem of an interrogator constructed according to the principles of the present invention,

FIG. 20 illustrates a block diagram of an embodiment of portions of a correlation subsystem associated with a control and processing subsystem of an interrogator demonstrating an exemplary operation thereof in accordance with the principles of the present invention,

FIG. 21 illustrates a waveform diagram demonstrating exemplary advantages associated with the correlation subsystem described with respect to FIGS. 19 and 20,

FIG. 22 illustrates a block diagram of an embodiment of a decision subsystem associated with a control and processing subsystem of an interrogator constructed according to the principles of the present invention,

FIG. 23 illustrates a block diagram of an embodiment of a correlation subsystem associated with a control and processing subsystem of an interrogator constructed according to the principles of the present invention,

FIG. 24 illustrates a block diagram of an embodiment of portions of a correlation subsystem associated with of a control and processing subsystem of an interrogator constructed according to the principles of the present invention,

FIG. 25 illustrates a block diagram of another embodiment of a correlation subsystem associated with a control and processing subsystem of an interrogator constructed according to the principles of the present invention,

FIG. 26 illustrates a block diagram of yet another embodiment of a correlation subsystem associated with a control and processing subsystem of an interrogator constructed according to the principles of the present invention,

FIGS. 27 and 28 illustrate block diagrams of embodiments of Fast Fourier Transform operations employable with a correlation subsystem associated with the control and processing subsystem of the interrogator constructed according to the principles of the present invention,

FIG. 29 illustrates a waveform diagram demonstrating the sidelobes associated with the correlation subsystem in accordance with the principles of the present invention,

FIG. 30 illustrates a block diagram of an embodiment of a predetecting function operable with a correlation subsystem associated with a control and processing subsystem of an interrogator constructed according to the principles of the present invention, and

FIGS. 31 to 34 illustrate waveform diagrams demonstrating exemplary performances of an interrogator according to the principles of the present invention.

#### DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

The making and using of the presently preferred embodiments are discussed in detail below. It should be appreciated, however, that the present invention provides many applicable inventive concepts that can be embodied in a wide variety of specific contexts. The specific embodiments discussed are merely illustrative of specific ways to make and use the invention, and do not limit the scope of the invention.

The present invention will be described with respect to exemplary embodiments in a specific context, namely, an interrogator, methods of discerning metal objects (i.e., objects that include metal) and RFID objects (i.e., objects that include an RFID tag or radio frequency identification) and an interrogation system employing the same.

In one aspect, an interrogator constructed according to the principles of the present invention reads a reply code from an RFID tag and treats the reply code as a spreading code in the context of spread spectrum communications with the existence of the RFID tag being preferably a single data bit also in the context of spread spectrum communications. The additional gain achieved by this approach substantially expands a potential for a detection process both of an obstructed RFID tag and an RFID tag located at a greater distance from the interrogator.

In another aspect, an interrogator constructed according to the principles of the present invention can read a reply code of the RFID tag with multiple amplitude bits (e.g., at least two) so that unique characteristics of an amplitude of the reply codes are captured and can be used to increase the uniqueness associated with the RFID tag. Thus, in addition to a uniqueness of the reply code including a tag identification (ID) code section thereof, the amplitude information serves as a type of “fingerprint” for the RFID tag.

In another aspect, the interrogation system is operable in a pre-initialization stage, an initialization stage and a post initialization stage. During one of the pre-initialization stage and the initialization stage, reference codes corresponding to the reply codes of the RFID tags are logged into memory (e.g., a database) of an interrogator of the interrogation system. Thereafter and during the post initialization stage, a correlation subsystem of the interrogator correlates between the reference code and a reply code from the RFID tags (when subsequently energized by the interrogator) to enhance a detection sensitivity thereof.

In another aspect, an interrogator constructed according to the principles of the present invention may employ reference codes corresponding to reply codes for the RFID tags that are synthetically derived to attain a higher level of sensitivity therefor. As mentioned herein, amplitude information about an RFID tag can be employed to generate a reference code to correlate against incoming reply codes to detect the presence of an RFID tag. The amplitude, phase and delay (timing of a response to an excitation signal) information of a particular type of RFID tag may be employed by the interrogator to derive the synthetic reference code.

One embodiment of generating a synthetic reference code is to pre-load a logical “0” and a logical “1” for a particular class of RFID tags (see FIG. 12 for an exemplary embodiment of a logical “0” and a logical “1”) wherein the preloaded information contains the unique amplitude, phase and delay information as mentioned above for that particular type of RFID tag. The preloaded information is used as individual building blocks to construct a synthetic code. During initialization, when the RFID object is typically read under docile signal conditions (i.e., high signal to noise ratio), so that it can be read in a conventional manner, the complete RFID tag code or digital signature is obtained. Further, as part of the initialization process, using the complete digital signature and the preloaded logical “0’s” and logical “1’s,” a representation of the RFID object’s response to an RFID query by the interrogator is synthetically constructed one bit at a time, starting with a bit of the digital signature (a “0” or a “1”) and thereby establishing a corresponding bit of the synthetic code (using logical “0s” and logical “1s”).



In a like manner, another bit of the synthetic code is determined and if contiguous to the other bit, is appended to the first bit described above. The process continues on a bit by bit basis, until a synthetic code is generated corresponding to at least a portion of the digital signature. In some instances, it will be desired to construct the entire anticipated response of the RFID object synthetically and this invention comprehends those instances where the entire RFID response as well as only a portion of the RFID response is generated synthetically. The preload of the logical "1's" and "0's" can occur as part of each initialization stage, or they can be contained in non-volatile form within the memory of the control and processing subsystem. They will typically be entered and updated via the communications subsystem of the interrogator. The interrogator may contain one or more such sets of these elements. In addition to creating the reference codes synthetically or partially creating the reference codes synthetically, the interrogator may create the reference code directly by scanning the RFID tag during an initialization stage.

In another aspect, the interrogator constructed according to the principles of the present invention employs non-coherent integration of multiple sequences of reference codes and reply codes from an RFID tag. In accordance therewith, reference bits (of the reference code) and sample bits (corresponding to the reply code) are latched and correlated bit-for-bit within a correlator of a correlation subsystem of the interrogator. A signal from the correlator is processed by a correlation threshold sense, a threshold of which may be altered to refine a threshold of the correlation operation. An output of the correlation threshold sense is then input to a summer, which after multiple transmissions and detections is input to a decision subsystem of the interrogator for an ultimate determination of a presence of an RFID tag.

In another aspect, an interrogator constructed according to the principles of the present invention includes a correlation subsystem that performs a correlation between a reference code and on portions of a reply code from the RFID tag and provide an indication of a presence of the RFID tag. For example, correlating on the preamble of the reply code provides a nine decibel increase in detection sensitivity (e.g., for an eight bit preamble). While employing the preamble alone does not uniquely identify an RFID tag, it does, with a relatively high probability, indicate the presence of an RFID tag. In accordance therewith, the reply codes for multiple RFID tags may have the same preamble and the interrogator correlates a reference code against the preamble of the reply code to indicate the presence of the RFID tag. The apriori knowledge of even the preamble further enhances a correlation operation to increase a sensitivity of the interrogator. Of course, the correlation subsystem may also employ a reference code to correlate against the entire reply code of the RFID tag depending on the particular application. Thus, the interrogator employs a discriminating correlation technique to correlate portions of a reply code from an RFID tag. The discriminating correlation technique may also employ hierarchal detection techniques to exploit portions of the reply code of an RFID tag to iteratively detect a presence thereof.

In another aspect, an interrogator constructed according to the principles of the present invention includes a decision subsystem embodied in a threshold detector. A threshold detector provides at least two logical outputs, namely, a logical "1" and a logical "0." Typically, the output of the threshold detector is a predetermined logical "1" or "0" if a threshold criteria is passed, and an alternate logical "0" or

"1" if the threshold criteria is not passed. In accordance with the selected criteria, the interrogator can provide, via a user interface, an RFID tag detected, RFID tag not detected, and an indeterminate indication (when at least a third state is available). In the latter case, a deeper and more thorough detection mode can be employed to determine the presence of an RFID tag, lack thereof, or an indeterminate condition. As a result, the interrogator can detect readily available RFID tags without employing the additional overhead necessary to detect obscured RFID tags.

In another aspect, an interrogator constructed according to the principles of the present invention includes a correlation subsystem with a single correlator or multiple correlators. In the latter case, the multiple correlators can be used to detect multiple RFID tags simultaneously and, in that instance, the multiple correlators typically operate independently. Alternatively, multiple correlators can be assigned to find a single RFID tag wherein each correlator can be given a slightly different area of time or phase space to search. In other words, the multiple correlators are assigned to an RFID tag offset in code space and can search in multiple locations in code space (i.e., bit or chip space as opposed to time space). For this embodiment, a clocking rate greater than the data rate is preferable. The higher rate is often referred to as a chipping rate so that moving plus or minus a chip can be used to better align the correlators on the data for enhanced signal processing gain. The chipping rate generally refers to a higher rate wherein a chip represents a fraction of a bit and, with "J" contiguous bits occupying the same time as one data bit, the chipping rate is "J" times the data rate.

In another aspect, an interrogator constructed according to the principles of the present invention includes multiple antennas to obtain additional gain from diversity. In accordance therewith, different correlators of a correlation subsystem may be assigned to specific antennas. As a result, the interrogator can benefit from spatial diversity, polarization diversity, angular diversity and time diversity.

In the discussion that follows, the principles of the present invention will be described with respect to a medical environment. Those skilled in the art, however, should recognize that the principles of the present invention are applicable to other fields such as supply chain management systems in the retail industry.

Referring initially to FIG. 1, illustrated is a diagram of an embodiment of a communication system employable in a medical environment constructed in accordance with the principles of the present invention. The communication system is configured to distribute, collect and process information across a communications network **105** that may include a Local Area Network (LAN), a Wide Area Network (WAN), an Intranet, an Extranet, the Internet, the World Wide Web, the Public Switched Telephone Network (PSTN), future extensions of these (e.g., the Internet **2**), or a combination thereof. For purposes of the present invention, the World Wide Web is defined as all the resources and users on the Internet that are generally using the Hypertext Transfer Protocol (HTTP). In one embodiment of the present invention, the communication system communicates to each device connected thereto using Transmission Control Protocol/Internet Protocol (TCP/IP).

TCP/IP is a two-layered protocol. The higher layer, Transmission Control Protocol (TCP), manages the assembling of a message or file into smaller packets that are transmitted over the communications network **105** and received by a TCP layer that reassembles the packets into the original message. The lower layer, Internet Protocol (IP), handles the address part of each packet so that it gets to the right



destination. Each gateway computer on the communication system checks the address to determine where to forward the message. Even though some packets from the same message are routed differently than others, the packets will be reassembled at the destination.

TCP/IP uses the client/server model of communication in which a computer user (a client) requests and is provided a service (such as sending a Web page) by another computer (a server) in the communication system. TCP/IP communication is primarily point-to-point, meaning each communication is from one point (or host computer) in the communication system to another point or host computer. TCP/IP and the higher-level applications that employ TCP/IP are collectively said to be "stateless" because each client's request is considered a new request unrelated to any previous one (unlike ordinary phone conversations that require a dedicated connection for the call duration). Being stateless frees the network paths so that everyone can use the paths continuously. It should be understood that the TCP layer itself is not considered stateless as far as any one message is concerned; the connection remains in place until all packets in a message have been received.

Internet users are familiar with the even higher layer application protocols that use TCP/IP to get to the Internet. The higher level application protocols include the World Wide Web's Hypertext Transfer Protocol (HTTP), the File Transfer Protocol (FTP), Telnet (a command and protocol that allows users to logon to remote computers), and the Simple Mail Transfer Protocol (SMTP). These and other protocols are often packaged together with TCP/IP.

Personal computer users usually access the Internet through the Serial Line Internet Protocol (SLIP) or the Point-to-Point Protocol (PPP). These protocols encapsulate the IP packets such that the packets can be sent over a dial-up phone connection to an access provider's connection device such as a conventional modem.

Protocols related to TCP/IP include the User Datagram Protocol (UDP), the Internet Control Message Protocol (ICMP), the Interior Gateway Protocol (IGP), the Exterior Gateway Protocol (EGP) and the Border Gateway Protocol (BGP). Depending on the circumstance, the UDP may be used instead of TCP for special network communication purposes. The aforementioned protocols, namely, ICMP, IGP, EGP and BGP, are often used by network host computers for exchanging router information.

Besides the Internet, TCP/IP may also be employed as the communication protocol in the private networks called Intranets and Extranets. An Intranet is a private network that is contained within an enterprise (such as an organization's office building). The Intranet may consist of many inter-linked LANs and use leased lines in a WAN. Typically, an Intranet includes connections through one or more gateway computers (not shown) to the outside Internet. The main purpose of an Intranet is to share organizational information and computing resources among employees. An Intranet can also be used to facilitate working in groups and for teleconferences.

An Intranet typically uses TCP/IP, HTTP and other Internet protocols and in general looks like a private version of the Internet. With tunneling, organizations can send private messages through the public network, using the public network with special encryption/decryption and other security safeguards to connect one part of the Intranet to another.

An Extranet is a private network that uses the Internet protocols and may use the public network to securely share part of an organization's information or operations with suppliers, vendors, partners, customers, or other medical

organizations. An Extranet can be viewed as part of an organization's Intranet that is extended to users outside the organization. Just like the Internet, an Extranet also uses HTML, HTTP, SMTP and other Internet protocols.

5 An Extranet also requires security and privacy provided by the use of firewalls. Firewalls are typically servers that have the ability to screen messages in both directions so that security is maintained. Firewall servers use digital certificates or similar means of user authentication, encryption of  
10 messages, and the use of virtual private networks (VPNs) that tunnel through the public network.

A medical organization can use an Extranet to exchange large volumes of data using Electronic Data Interchange (EDI) and share information between facilities associated  
15 therewith. The Extranet can also be employed to allow an organization to collaborate with other organizations on joint development efforts and jointly develop and jointly use training programs. Via the Extranet, an organization can also provide or access services provided by one organization to  
20 a group of other organizations, such as a medical record management application managed by one organization on behalf of the medical organization, and share information of common interest exclusively with partner organizations.

Within the medical environment of the communication system is a server **110** located at a primary medical facility  
25 **120** that includes systems that allow the server **110** to receive requests, perform specific tasks, retrieve and update information in at least one database and respond to requests sent over the communication system to the server **110**. In other  
30 embodiments, the communication system may include multiple servers, each performing specific tasks, performing the same tasks, acting as redundant systems or acting as database sites.

In another embodiment of the present invention, the server **110** may be an application server. An application server is a computer in a distributed network containing specialized programs that provide the business logic for at least one application program located somewhere within the communication system. The application server is frequently  
40 viewed as part of a three-tier application, consisting of a graphical user interface (GUI) server, an application (business logic) server, and a database and a transaction server. The first-tier of the application, also called "front-end," is usually located in a client computer such as a personal  
45 computer (PC) or a workstation and may include a Web browser-based graphical user interface. The second-tier is the business logic application or set of applications and can be located on a LAN or an Intranet server.

The third-tier of the application, also called "back-end," is the database and transaction server and may be located on a mainframe or a large server. Older, legacy databases and transaction management applications are part of the back-end or third-tier. The application server is the middleman between the browser-based front-ends and the back-end  
55 databases and legacy systems.

In many instances, the application server is combined with or works with a Web server and is called a "Web application server." The Web browser supports an easy-to-create HTML-based front-end for the user. The Web server  
60 provides several different ways to forward a request to an application server and to send a modified or new Web page to the user. These approaches include the Common Gateway Interface (CGI), FastCGI, Microsoft's Active Server Page (ASP) and the Java Server Page (JSP). In some cases, the  
65 Web application servers also support request "brokering" interfaces such as CORBA's Internet Inter-ORB Protocol (IIOP).



## 13

The communication system also includes conventional personal computers (PCs) **125**, workstations **130**, office computer systems **140** and laptop computers **150**. In other embodiments, the communication system may include any number of PCs **125**, workstations **130**, office computer systems **140** and laptop computers **150**. In one embodiment of the present invention, the PCs **125**, the workstation **130**, the office computer system **140** and the laptop computers **150** are client computer systems. A client computer system includes a user interface that allows the user to access information, issue requests and perform functions related to the server **110**. In another embodiment, the office computer system **140** may be configured as a second-tier type computer system. For illustrative purposes only, the PCs **125**, the workstation **130**, the office computer system **140** and the laptop computers **150** are located in ones of the primary medical facility **120**, auxiliary medical facility **155** and doctor's office **160** as shown.

In the illustrated embodiment, the communication system also includes a handheld device **170** such as a personal digital assistant (PDA) or a tablet PC. A PDA is a term used for any small mobile hand-held device that provides, in part, computing, information storage and retrieval capabilities. PDAs are often used for keeping schedules, calendars, address book information and medical information (examples of PDAs include Hewlett-Packard's Palmtop™ and 3Com's PalmPilot™). A tablet PC is a compact device similar to a laptop computer but with a handwriting recognition capability (examples of tablet PCs include Compact TC1000 and ViewSonic V1100).

Most PDAs have a small keyboard and some PDAs have an electronically sensitive pad on which handwriting can be received and recognized. Apple's Newton™, which has been withdrawn from the market, was the first widely-sold PDA that accepted handwriting. Many applications have been written for PDAs including network programs and Internet access programs. PDAs are increasingly combined with telephones and paging systems for wireless communications. Some PDAs offer a variation of the Microsoft Windows™ operating system called Windows CE™. Other PDA products use a proprietary operating system, such as PalmOS™ or third party operating systems.

An individually addressable vehicle (IAV) **180** such as an ambulance is also located within the communication system. The IAV **180** can include any type of vehicle capable of having a computer with a wireless network receiver and/or transmitter that is individually addressable. For example, an ambulance containing an Internet terminal is an IAV or a computer with a wireless receiver/transmitter and sensors that transmits patient information falls within the class of IAVs.

In the illustrated embodiment, the IAV **180** can send requests to the server **110** within the communication system to request information or perform specific functions, such as retrieving information related to the location of the vehicle or general patient information. The IAV **180** may include a display (not shown) and an input device (not shown) such as push buttons, a touch screen or a combination of the two to facilitate user interface therewith.

A mobile telephone **190** may also be included in the communication system. The mobile telephone **190** includes a display capable of showing information retrievable from the communication system. The mobile telephone **190** can send and retrieve information from the server **110** and perform specialized tasks associated with the capabilities of a mobile telephone with network capabilities. In one embodiment, the mobile telephone **190** is capable of access-

## 14

ing Web pages, traversing the Internet and displaying information associated with Web pages on its display.

One skilled in the pertinent art should know that the principles of the present invention are not limited for use with the types of devices described above. In other embodiments, the communication system may include individually accessible electronic devices (IAEDs). IAEDs are electronic devices having a network interface that are individually addressable on a network. For example, medical equipment in a medical facility connected to a network having a unique network address is representative of an IAED.

One skilled in the pertinent art should also know that the principles of the present invention may be employed via conventional hardwired or wireless communications networks. For instance, a PDA **170** within the primary medical facility **120** may communicate patient information to the workstation **130** via a wireless link compatible with a Bluetooth communications environment as defined in the Bluetooth Specification, Version 1.1, or an IEEE 802.11 communications environment as defined in the Institute of Electronic and Electrical Engineers Specification, Section 802.11, both of which are herein incorporated by reference in their entirety. Of course, other existing or future wireless specifications including those employing a proprietary system may also be used. The workstation **130** may then download the information to the server **110** via a hardwired connection. Of course, the networks within the medical facilities and the communications network **105** itself may include hardwired and wireless segments. It should also be clear that the principles of the present invention are not limited to a communication system in a medical environment. For example, the principles of the present invention may be employed in conjunction with supply chain applications for the retail industry.

For a better understanding of communication systems and networks in general, see "Wireless Communications, Principles and Practice," by Theodore S. Rappaport, Prentice Hall PTR, 1996, "Microwave Mobile Communications," edited by William C. Jakes, IEEE Communications Society, 1993, and "Digital Communications," 3<sup>rd</sup> Edition, by John C. Proakis, McGraw-Hill, Inc., 1995, all of which are herein incorporated by reference in their entirety. For a better understanding of communication systems including antenna design and communications, etc., see "Antenna Engineering Handbook," by Richard Johnson and Henry Jasik, McGraw-Hill, Inc., 1992, and "Wideband Wireless Digital Communications," by Andreas F. Molisch, Pearson Education, 2000, which are also herein incorporated by reference in their entirety.

Turning now to FIG. 2, illustrated is a pictorial diagram of an embodiment of an interrogation system employable within an operating room of a medical facility and constructed in accordance with the principles of the present invention. In the illustrated embodiment, the interrogation system is employed within the operating room having an operating table **202** with a patient **203** thereon and a back table **204** that accommodates a plurality of surgical instruments **205a** and disposable items **205b** (such as sponges). Other equipment, such as Mayo stands, ring stands, additional back tables and a kick-bucket are also well known to those familiar with the operating room environment and will also likely be present in some quantity and arrangement. The interrogation system includes a computer system **210**, an operating room transceiver **215** that transmits and receives signals associated with the computer system **210** and an interrogator (e.g., a portable interrogator) **225**. It should be understood that the interrogator may be affixed to a table



15

(e.g., the back table **204**), stand, wall or ceiling within a facility and may also be embodied in multiple coordinated systems and subsystems, both hardware and software.

The computer system **210** may operate as a client that is coupled to a server associated with the medical facility or, alternatively, the computer system **210** may be a stand-alone unit solely dedicated to the operating room **201**. The transceiver **215** is coupled between the computer system **210** and the portable interrogator **225** and is employed to transmit signals to and receive signals from the portable interrogator **225**.

In the illustrated embodiment, the transceiver **215** includes transmit and receive sections that are coupled through a wired connection **217** to an antenna array having first, second, third and fourth antenna elements **216a**, **216b**, **216c**, **216d** located proximate the corners of the operating room **201**. The antenna array may be employed by the transceiver **215** to wirelessly communicate with the portable interrogator **225** through an interrogator antenna **226** included in the portable interrogator **225**. The interrogator antenna **226** may be external as shown, or alternatively, it may be integrated into the body of the portable interrogator **225**. Of course, other antenna configurations including additional or fewer antenna elements or alternate placements may be employed as directed by specific parameters or characteristics associated with an operating room environment. Also, a charging stand **230** which charges the portable interrogator **225**, provides a secure place for the portable interrogator **225** to stay when not in use, charges the batteries of the portable interrogator **225**, and can provide an interface between the portable interrogator **225** and the computer system **210**.

The portable interrogator **225** includes a metal sensing subsystem that provides a first signal having a metal signature representing a presence of a metal object and a radio frequency identification (RFID) sensing subsystem that provides a second signal having an RFID signature representing a presence of an RFID object. In the illustrated embodiment, the metal sensing subsystem is configured to employ a metal sensing interface and a metal sensing antenna. Similarly, the RFID sensing subsystem is configured to employ an RFID sensing antenna interface and an RFID sensing antenna. In an alternative embodiment, the metal and RFID sensing subsystems are configured to employ an antenna diplexer and an integrated sensing antenna. Alternatively, the metal and RFID sensing subsystems may be integrated into a sensing subsystem that provides a signal or a plurality of signals having at least one of a metal signature representing a presence of a metal object and an RFID signature representing a presence of an RFID object.

The portable interrogator **225** also includes a control and processing subsystem (also referred to as a control and processing system) that discerns a presence of at least one of the metal and RFID objects from one of the first and second signals. The control and processing subsystem may also coordinate a processing of the signal(s) from the sensing subsystem to discern a presence of at least one of said metal and RFID objects. The control and processing subsystem may also employ an adaptive integrating filter and coordinate a processing of the signal(s) in conjunction with one of an observable and data to discern a presence of at least one of the metal and RFID objects. The portable interrogator **225** also includes a communications subsystem, coupled to the interrogator antenna **226**, that allows communication with the transceiver **215**. The portable interrogator **225** further includes an internal user interface **227** and an external user interface **228** that is coupled to the computer system **210**, in

16

the illustrated embodiment. The portable interrogator **225** still further includes a position sensor that allows a position of the portable interrogator **225** to be determined. The portable interrogator **225** may also have a wired interface, for example, a Universal Serial Bus (USB) port.

Prior to starting a surgical procedure, the portable interrogator **225** may be employed to inventory the plurality of surgical instruments **205a** and disposable items **205b** in the operating room **201**. This may be accomplished by scanning the plurality of surgical instruments **205a** and disposable items **205b** with the portable interrogator **225**, before surgery begins. Alternatively, a separate asset management system may provide this information to the portable interrogator **225**. Verification of the inventory may employ both approaches. In addition, the presence of a particular kind of surgical instrument **205a** may be verified through the scanning action as was requested by a medical professional. The request may have been arranged through the computer system **210** or through a medical professional's PDA. During the surgical procedure, the portable interrogator **225** may be employed to monitor any movement or repositioning of the plurality of surgical instruments **205a** and disposable items **205b** thereby providing location tracking during use of any of the items in the surgical procedure.

Additionally, the portable interrogator **225** may be employed to scan the patient **203** before, during or after closing the surgical procedure. Scanning the patient **203** before the surgical procedure provides location of metal or RFID objects already present in the patient **203**. Scanning the patient **203** during the surgical procedure provides a real-time, operational assurance that the location of the plurality of surgical instruments **205a** and disposable items **205b** are where they are intended to be. Scanning the patient **203** after concluding the surgical procedure provides a verification that any metal or RFID objects remaining are only those intended. In addition, the portable interrogator **225** may make multiple scans about the patient **203** to further assist in ascertaining a location of any metal or RFID objects.

The portable interrogator **225** may be employed in either an autonomous or an integrated mode of operation. In the autonomous mode of operation, the control and processing subsystem autonomously accomplishes the operation of the portable interrogator **225**, provides all analysis algorithms and performs all functions needed to discern the presence of metal and RFID objects that have been scanned by the portable interrogator **225**. Alternatively, the integrated mode of operation employs the computer system **210**, either wirelessly via the transceiver **215**, the antenna array and the interrogator antenna **226** or through the wired interface, to support the control and processing subsystem in discerning the presence of metal and RFID objects. The integrated mode may provide for a greater selection of sensors and sensed items that may be integrated into an enhanced solution. The integrated mode typically allows a more extensive utilization of databases and algorithms to be employed than in the autonomous mode of operation.

The majority of moveable metal objects employed in the operating room **201** are typically surgical instruments or sharps of various sizes and shapes or metal structures intended to be surgically implanted in the patient **203**. Other metal objects may include disposable sponges employing a metal wire that allows their detection by the metal sensing subsystem. Each of the metal objects generates a metal signature that allows its detection by the portable interrogator **225**. Generally, the metal signature may cause its associated first signal to possess a universal characteristic,



such as a shape, an amplitude or a frequency spectrum, that indicates metal is present. More specifically, the metal signature may cause the first signal to possess a particular characteristic that is substantially unique to a particular type of metal object thereby allowing a more unique identification.

RFID signatures differ from metal signatures in that the RFID signature, associated with the second signal, is unique and independent of a shape or a size of the RFID object. The RFID signature is normally provided by an RFID tag (e.g., an RFID information tag including data thereon, of which one is designated **207**) applied to the object. For the purposes of discussion herein, a metal object refers to an object including metal and an RFID object refers to an object with an RFID tag or some other radio frequency identification associated therewith. If an RFID tag were applied to a surgical metal instrument, for example, the portable interrogator **225** would recognize a unique RFID signature as well as the metal signature that may be general or specific to the surgical metal instrument. The metal signature may be used to discern that an object is a metal object, or that it is a type of surgical metal instrument. However, the RFID signature may be used to discern exactly which surgical metal instrument the metal object is. Additionally, RFID tagging of disposable items, such as sponges, may provide a unique RFID signature for each item, whereas disposable items incorporating only a metal wire may typically provide a metal signature specific to all such items.

The internal user interface **227** typically includes an integral display employing alphanumeric or graphical characters and a touchpad for entering data or information. The internal user interface **227** may also employ audible or visual alarms. In the illustrated embodiment, the external user interface **228** includes a monitor **228a** and a keyboard **228b** that are wirelessly coupled to the portable interrogator **225** and the computer system **210**. Alternatively, the wired interface of the portable interrogator **225** may be employed to couple the external user interface **228** to the portable interrogator **225**. The external user interface **228** may provide a more extensive data entry capability while facilitating a broader monitoring capability than may be provided by the internal user interface **227**.

Position monitoring of the portable interrogator **225** is provided by the position sensor, which allows a relative determination of its position with respect to the patient **203**, the back table **204** or another location. RFID position markers may be placed on the patient **203** at predetermined benchmark positions, such as the nose, navel, knee and ankle, to provide substantially unique patient dimensions (or a location of a feature of a patient) and allow other patient attribute positions and metrics to be more accurately determined. Additionally, RFID/metal calibration markers may be positioned at other locations on the patient **203** to allow the portable interrogator **225** to calibrate depths or other appropriate thicknesses associated with the patient **203**. Of course, RFID markers may be placed on items such as the back table, ring stand, the Mayo stand or any other location within the operating room deemed appropriate.

A plurality of the portable interrogators **225** may be coupled together mechanically or electrically, either wirelessly or through their wired interfaces, to form a networked-interrogator mode of operation. The networked-interrogator mode of operation allows two or more interrogators to share and collaborate data. This collaboration may include the coordination of a plurality of interrogators simultaneously employed on the patient **203**. Alternatively, the collaboration may also include coordinating information associated with

the operating room **201**, such as information associated with items on the back table **204**, as well as other pertinent information located within the medical facility environment. This collaborative effort may occur in real time or over a period of time and may employ the interrogators operating in an autonomous mode, an integrated mode or a combination of the modes.

Turning now to FIG. 3, illustrated is a pictorial diagram of an embodiment of an interrogation system employable within an operating room of a medical facility and constructed in accordance with the principles of the present invention. In the illustrated embodiment, the interrogation system is employed within an operating room having an operating table **302** with a patient **303**. Those skilled in the art should understand, however, that the principles of the present invention are equally applicable to other industries and fields of operation.

The interrogation system includes a computer system **310** coupled to a database **311**, a transceiver **315** that transmits and receives signals associated with the computer system **310** employing a transceiver antenna **316** and an interrogator (e.g., a portable interrogator) **325** employing an interrogator antenna **327**. The interrogation system also includes first, second, third and fourth RFID position markers **330**, **331**, **332**, **333**, (collectively referred to as RFID position markers **330-333**), an RFID patient bracelet **340** attached to the patient **303** and first, second, third and fourth RFID/metal calibration markers **341**, **342**, **343**, **344**, (collectively referred to as RFID/metal calibration markers **341-344**).

The RFID position markers **330-333** may be placed at predetermined locations on the patient **303**. Generally, RFID position markers provide "position-unique" mapping of the patient **303** wherein the mapping may employ more or less RFID position markers than those shown therein. When used in conjunction with a sweeping motion of the portable interrogator **325**, it may be possible to specifically identify the presence of a metal or an RFID tagged object as being located between two of the RFID position markers. Thus, a control and processing subsystem of the portable interrogator may employ multiscan, coherent signal processing to coordinate a processing of a plurality of signals (e.g., resulting from multiple scans) from a sensing subsystem to discern a presence of at least one of metal and RFID objects.

Additionally, employing an inertial position sensor in the portable interrogator **325** allows a more precise determination of the presence and location of an RFID or metal object between these two RFID position markers. In this instance, it may be possible to integrate sensor data across multiple sweeps of the portable interrogator **325** thereby increasing its sensitivity and quality of detection. Of course, any number of RFID position markers may be employed and positioned as appropriate to a particular situation.

The RFID/metal calibration markers **341-344** have unique RFID signatures and known amounts and types of metal. They are typically not placed on top of the patient **303**, but are placed beneath or on the side of the patient **303**, such as the underside of a leg or between an arm and the chest. As the portable interrogator **325** is swept over the patient **303**, the RFID/metal calibration markers **341-344** are used to calibrate the type and sensitivity of interrogation needed by the portable interrogator **325** to provide an acceptable level of object identification thereby achieving an increased integrity of operation. Of course, any number of RFID/metal calibration markers may be employed and positioned as appropriate to a particular situation. Alternatively, calibration markers may be employed that use only RFID or only metal as appropriate to a particular application.



The RFID patient bracelet **340** contains specific information pertaining to the patient **303**. The RFID patient bracelet **340** is read, either by the portable interrogator **325** or another appropriate device. The specific information may then be applied by the portable interrogator **325** or the computer system **310** for the purpose of further improving measurement sensitivity and quality. For example, ample interrogation for a seven year old female patient weighing 40 pounds may be quite different from that of a 50 year old male patient weighing 260 pounds. Identifying the patient **303** as well as employing specific databases and general information associated with the patient **303** allows for measurement quality and sensitivity improvements. The computer system **310** employing the database **311** may be employed in an integrated mode of operation or the portable interrogator **325** may operate autonomously.

Additionally, the interrogation system may include and cooperate with a medical facility server and extended databases to provide additional information and algorithms to be used as part of the interrogating process. Not only is patient-specific information available, but statistical information, relevant to patient types may also be available. This information may be employed for extensive signal processing within the medical facility server, or subsets of this information may be used for signal processing within the computer system **310** or the portable interrogator **325** itself.

Turning now to FIG. 4, illustrated is a pictorial diagram of an embodiment of an interrogator (e.g., a portable interrogator) constructed in accordance with the principles of the present invention. The portable interrogator includes an electronics housing **405** having a display **406**, a touch pad **407** employing a collection of touch keys **408** and an audible alarm **409**. The portable interrogator also includes a sensing antenna assembly **410**, a handle **415** and an interrogator antenna **420**.

The sensing antenna assembly **410** contains RFID and metal sensing antennas and antenna interfaces that may be employed to sense RFID and metal objects associated with, for instance, a patient in a medical environment. The electronics housing **405** contains a metal sensing subsystem, an RFID sensing subsystem, a control and processing subsystem and a communications subsystem. The metal sensing subsystem and the RFID sensing subsystem accept RFID and metal antenna signals, respectively, and are coupled to the control and processing subsystem for signal processing that results in the detection of RFID and metal objects, when present. Again, the metal and RFID sensing subsystems may be integrated into a sensing subsystem. The control and processing subsystem is coupled to the communications subsystem, which employs the interrogator antenna **420** to communicate with external computer systems, databases and displays. The display **406**, the touch pad **407** and the audible alarm **409** provide an integral user interface for the portable interrogator. Also, while the interrogators have been described in relation to a medical environment, one skilled in the art should understand that the interrogator may be employed in other environments and still be within the broad scope of the present invention. Also, for further information about applications for the interrogation system especially in the medical environment, see U.S. patent application Ser. No. 10/378,043, entitled "An Interrogator and Interrogation System Employing the Same," filed on Mar. 3, 2003, to Volpi, et al., which is incorporated herein by reference.

Turning now to FIG. 5, illustrated is a system diagram of an embodiment of an interrogator constructed in accordance with the principles of the present invention. The interrogator includes a metal sensing subsystem **505**, a metal sensing

antenna interface **506**, a metal sensing antenna **507**, an RFID sensing subsystem **510**, an RFID sensing antenna interface **511**, an RFID sensing antenna **512**, a control and processing subsystem **515**, a communications subsystem **525**, an internal user interface **530**, a position sensor **535** and a power source **540**. While the illustrated embodiment provides for an integrated metal and RFID detection capability, those skilled in the art should understand that portions of the interrogator may be omitted or rendered inactive to provide a metal or RFID interrogator.

In the illustrated embodiment, the internal user interface **530** includes a touchpad **531**, an integral display **532** and an alarm **533**, which may include both an audible alert **533a** and a visual alert **533b**. Additionally, the interrogator employs an external user interface **534** (e.g., including a charging stand or cradle), coupled through the communications subsystem **525** via a USB connection **526** or a wireless connection **527**, for example, as shown. The external user interface **534** may employ substantially similar elements as the internal user interface **530**. However, the display and touchpad elements may be larger and more extensive in capability.

The metal sensing subsystem **505** is coupled to the metal sensing antenna interface **506** and the metal sensing antenna **507** and is configured to provide a first signal having a signature representing a presence of a metal object. The RFID sensing subsystem **510** is coupled to the RFID sensing antenna interface **511** and the RFID sensing antenna **512** and is configured to provide a second signal having a signature representing a presence of an RFID object. The control and processing subsystem **515** is coupled to the metal sensing subsystem **505** and the RFID sensing subsystem **510** and is configured to discern a presence of at least one of the metal and RFID objects from one of the first and second signals.

The control and processing subsystem **515** coordinates an operation of the metal sensing subsystem **505** and the RFID sensing subsystem **510**. Additionally, the control and processing subsystem **515** analyzes the first signal for a metal object signature and the second signal for an RFID object signature. The metal object signature typically may be created by a change or distortion in a field associated with the metal sensing subsystem **505**. The RFID object signature typically may be created as an identification data sequence associated with an RFID object. Analysis of the first and second signals may employ signature parameters based on factors such as a size, a shape, an orientation, likelihood, a position or a depth associated with the metal object or the RFID object. Additionally, the analysis may employ data associated with metal and RFID objects that is internally or externally stored.

The control and processing subsystem **515** is also coupled to the communications subsystem **525**, the internal user interface **530** and the position sensor **535**. The position sensor **535** may typically be of an inertial type and may provide either two dimensional (2D) or three dimensional (3D) information as to the position of the interrogator for the purpose of aiding metal or RFID tag detection. In the illustrated embodiment, the communications subsystem **525** employs transmit and receive circuitry coupled to an antenna to exchange data with an external transceiver.

For example, the communications subsystem **525** may be employed to send metal and RFID signature information to an external server for a more extensive analysis that may be beyond the capability of the control and processing subsystem **515**. The results of the analysis may be returned through the communications subsystem **525** for final disposition by the control and processing subsystem **515**. Alternatively, the



control and processing subsystem **515** may employ the communications subsystem **525** to sequentially query external databases for signature profiles or analysis algorithms to be applied locally by the control and processing subsystem **515**.

The internal user interface **530** allows a user to interact with the interrogator to provide input and receive output associated with its application. The position sensor **535** cooperates with the control and processing subsystem **515** to allow a position of the interrogator to be determined. The power source **540** employs a rechargeable or replaceable battery and provides necessary operating supply voltages to the interrogator.

The user of the interrogator may employ the touchpad **531** to select a mode of operation or both enter and request information about a specific metal or RFID object. The integral display **532** may be employed to show an RFID number or indicate that the interrogator is detecting the presence of a metal or RFID object. Alternatively, the external display **534** may be employed to indicate the presence of a metal or RFID object. Additionally, the integral display **532** or the external display **534** may be employed in conjunction with the position sensor **535** to determine a profile and a position of the metal or RFID object with respect to a movement or sweeping motion of the interrogator. The audible alert **533a** may include distinctive tones or synthesized voice communications. The visual alert **533b** may be flashing or colored features that include textual or graphical representations. The visual alert **533b** may be associated with the integral display **532**, the external display **534**, or they may be stand-alone.

Turning now to FIG. 6, illustrated is a block diagram of another embodiment of an interrogator constructed in accordance with the principles of the present invention. The interrogator includes a metal sensing subsystem **605**, a metal sensing antenna interface **610**, a metal sensing antenna **615**, an RFID sensing subsystem **620**, an RFID sensing antenna interface **630**, an RFID sensing antenna **635** and a control and processing subsystem **640**. While the illustrated embodiment provides for an integrated metal and RFID detection capability, those skilled in the art should understand that portions of the interrogator may be omitted or rendered inactive to provide a metal or RFID interrogator.

The metal sensing subsystem **605** includes a metal sensing digital-to-analog converter (DAC) **606**, a metal sensing transmit amplifier **607**, a metal sensing receive amplifier **608** and a metal sensing analog-to-digital converter (ADC) **609**. The metal sensing antenna interface **610** includes a metal sensing transmit conditioning filter **611** and a metal sensing receive conditioning filter **612**. The metal sensing antenna **615** includes a metal sensing transmit antenna **616** and a metal sensing receive antenna **617**.

The RFID sensing subsystem **620** includes an RFID sensing DAC **621**, an RFID sensing transmit selector switch **622**, a first RFID sensing transmit amplifier **623**, a second RFID sensing transmit amplifier **624**, a first RFID sensing receive amplifier **625**, a second RFID sensing receive amplifier **626**, an RFID sensing receive selector switch **627** and an RFID sensing ADC **628**. The RFID sensing antenna interface **630** includes first and second RFID sensing transmit conditioning filters **631**, **632** and first and second RFID sensing receive conditioning filters **633**, **634**. The RFID sensing antenna **635** includes first and second RFID sensing transmit antennas **636**, **637** and first and second RFID sensing receive antennas **638**, **639**. "HI band" and "LO

band" capabilities are present to accommodate the wide frequency range necessary to detect the various types of RFID tags.

In an alternative embodiment, a mixing or heterodyning function may be included within the RFID sensing ADC **628** or the RFID sensing DAC **621** functions. These techniques are known to those skilled in the pertinent art and may be employed to translate signal processing to a more desirable frequency range thereby allowing less expensive or more readily available components to be used. Additionally, the specific nature and function of the first and second transmit conditioning filters **631**, **632** and first and second RFID sensing receive conditioning filters **633**, **634** may vary depending on the specific algorithms employed for control and processing and for signal generation and recovery. Also, some embodiments may not require some or all of the filters shown.

In the illustrated embodiment, the control and processing subsystem **640** may be a software defined structure that allows features and functions of the interrogator to be easily modified or tailored by altering software functions. The control and processing subsystem **640** employs a crystal oscillator to provide a precise frequency reference for both the metal and RFID sensing subsystems **605**, **620**.

The control and processing subsystem **640** generates a metal sensing digital excitation signal based on a metal sensing mode of operation selected and provides this signal to the metal sensing DAC **606**. The metal sensing digital excitation signal may be in the form of a continuous tone. Alternatively, the digital excitation signal may vary in amplitude, frequency, or phase and may also be of a pulsed nature wherein the waveform duty cycle is less than 100 percent. The frequency of the metal sensing digital excitation signal may generally be in the range of five to 100 kHz. Different waveforms may be used to optimize a detection of both ferrous and non-ferrous metals. These waveforms may be selected for different sizes and masses of metals and for metals at different locations and depths within a patient. Algorithmic information employed in generating these excitation signals may be part of the control and processing subsystem **640**.

The metal sensing DAC **606** converts the metal sensing digital excitation signal into an analog signal that, except for its amplitude, is the metal sensing transmit signal. The analog signal is provided to the metal sensing transmit amplifier **607**, which amplifies the analog signal to a correct amplitude for transmission. The output of the metal sensing transmit amplifier **607** is provided to the metal sensing transmit conditioning filter **611**, which sufficiently attenuates all out-of-band signals and provides a proper impedance match to the metal sensing transmit antenna **616**. The metal sensing transmit antenna **616** launches the metal sensing transmit signal.

A metal object present in the vicinity of the metal sensing transmit antenna **616** and the metal sensing transmit signal will generate a metal sensing return signal wherein the metal sensing return signal may be based on a change in a field characteristic of the metal sensing transmit signal. The field characteristic may be altered in the vicinity of the metal object such that a distinctive metal sensing receive signal impinges on and excites the metal sensing receive antenna **617**. The output of the metal sensing receive antenna **617** is provided to the metal sensing receive conditioning filter **612**, which sufficiently attenuates all out-of-band energy and provides a proper impedance match between the metal sensing receive antenna **617** and the metal sensing receive amplifier **608**.



The metal sensing receive amplifier **608** amplifies the metal sensing receive signal to a level sufficient for processing and provides it to the metal sensing ADC **609**. The metal sensing ADC **609** provides a metal sensing digital signal, proportional to the metal sensing receive signal, to the control and processing subsystem **640**, which determines if the metal sensing digital signal has a signature representing a presence of a metal object in the vicinity of the metal sensing antenna **615**.

The control and processing subsystem **640** generates an RFID sensing digital excitation signal based on an RFID mode of operation selected and outputs this signal to the RFID sensing DAC **621**. The RFID sensing digital excitation signal may be in the form of a code that excites and energizes an RFID object present including an RFID tag. The carrier frequency associated with this code may be in one of two frequency bands. A first frequency band may be centered around 133-135 kHz and is designated as the "LO band." A second frequency band may be centered around 10-13 MHz and is designated the "HI band." Alternatively, a "HI band" around 902-928 MHz may also be employed. Alternatively, the 133-135 kHz and the 10-13 MHz bands may be combined in the "LO band" and some specific implementations may require only a single band. A frequency band is selected based on the RFID mode of operation selected. Each frequency band corresponds to different types of RFID tags present, which may be based on its size or other factors. Generally, algorithmic information to generate the RFID sensing digital excitation signal is contained in the control and processing subsystem **640**.

The RFID sensing DAC **621** converts the RFID sensing digital excitation signal into an analog signal that, except for amplitude, is the RFID sensing transmit signal. The RFID sensing transmit signal is provided to the RFID sensing transmit selector switch **622**, which is controlled by the control and processing subsystem **640**. The RFID sensing transmit selector switch **622** directs the RFID sensing transmit signal to the first RFID sensing transmit amplifier **623** or the second RFID sensing transmit amplifier **624**, respectively, based on whether the RFID sensing transmit signal is "HI band" or "LO band." The first RFID sensing transmit amplifier **623** and the second RFID sensing transmit amplifier **624** increase the amplitude of the "HI band" and "LO band" signals to a correct amplitude for transmission.

The first RFID sensing transmit amplifier **623** provides the "HI band" signal to the first RFID sensing transmit conditioning filter **631** and the second RFID sensing transmit amplifier **624** provides the "LO band" signal to the second RFID sensing transmit conditioning filter **632**. The first and second RFID sensing transmit conditioning filters **631**, **632** employ differing center frequencies and sufficiently attenuate associated out-of-band signals. Additionally, they provide a proper impedance match to their respective first or second RFID sensing transmit antennas **636**, **637**, which launch their respective RFID sensing transmit signals.

An RFID object, including an RFID tag, in the vicinity of the first or second RFID sensing transmit antenna **636**, **637** generates an RFID sensing return signal. The RFID sensing return signal impinges on and excites the appropriate first or second RFID sensing receive antenna **638**, **639**, respectively, to provide an RFID sensing receive signal. An output of the first or second RFID sensing receive antenna **638**, **639** is provided to the first or second RFID receive conditioning filter **633**, **634**, respectively. The first or second RFID receive conditioning filter **633**, **634** sufficiently attenuates the out-of-band energy and provides a proper impedance

match between the first or second RFID sensing receive antenna **638**, **639** and the first or second RFID sensing receive amplifier **625**, **626**, respectively.

The first or second RFID sensing receive amplifier **625**, **626** amplifies the small RFID sensing receive signal to a level sufficient for processing and provides an amplified RFID sensing receive signal to the RFID sensing receive selector switch **627**, which is controlled by the control and processing subsystem **640**. The control and processing subsystem **640** selects the appropriate reception path through the RFID sensing receive selector switch **627** for input to the RFID sensing ADC **628**, based on the excitation signal transmitted. The RFID sensing ADC **628** provides an RFID sensing digital signal, proportional to the RFID sensing receive signal, to the control and processing subsystem **640**, which determines if the RFID sensing receive signal has a signature representing a presence of an RFID object in the vicinity of the RFID sensing antenna **635**.

Turning now to FIG. 7, illustrated is a system diagram of an alternative embodiment of an interrogator constructed in accordance with the principles of the present invention. The interrogator includes a metal sensing subsystem **705**, an RFID sensing subsystem **710**, a metal and RFID sensing antenna diplexer **712**, a metal and RFID sensing integrated antenna **714**, a control and processing subsystem **715**, a communications subsystem **725**, a user interface **730**, a position sensor **735** and a power source **740**.

The interrogator is similar to the interrogator of FIG. 5 wherein the metal and RFID sensing antenna diplexer **712** has replaced the metal sensing antenna interface **506** and the RFID sensing antenna interface **511**. Additionally, the metal and RFID sensing integrated antenna **714** has replaced the metal sensing antenna **507** and the RFID sensing antenna **512**. General operation of the interrogator is also similar to the operation of the interrogator of FIG. 5.

However, the interrogator employs the metal and RFID sensing antenna diplexer **712** between the transmit and receive paths associated with both the metal sensing and RFID sensing subsystems **705**, **710**. The metal and RFID sensing antenna diplexer **712** accommodates the frequency selecting and impedance matching functions. Similarly, the metal and RFID sensing integrated antenna **714** is also employed in both the transmit and receive paths associated with both the metal sensing and RFID sensing subsystems **705**, **710**. A more detailed discussion of the metal and RFID sensing antenna diplexer **712** and the metal and RFID sensing integrated antenna **714** are presented below with respect to FIG. 8.

Turning now to FIG. 8, illustrated is a block diagram of another embodiment of an interrogator constructed in accordance with the principles of the present invention. The interrogator includes a metal sensing subsystem **805**, an RFID sensing subsystem **810**, a metal and RFID sensing antenna diplexer **815**, a metal and RFID sensing integrated antenna **825** and a control and processing subsystem **830**.

The metal and RFID sensing antenna diplexer **815** includes a metal sensing transmit conditioning filter **816**, a metal sensing receive conditioning filter **817**, a metal sensing diplexer switch **822**, first and second RFID sensing transmit conditioning filters **818**, **819**, first and second RFID sensing receive conditioning filters **820**, **821** and first and second RFID sensing diplexer switches **823**, **824**. The metal and RFID sensing integrated antenna **825** includes a metal sensing transmit/receive antenna **826** and first and second RFID sensing transmit/receive antennas **827**, **828**.

Operation of the metal sensing subsystem **805**, the RFID sensing subsystem **810** and the control and processing



25

subsystem **830** are analogous to the metal sensing subsystem **605**, the RFID sensing subsystem **620** and the control and processing subsystem **640** as was discussed with respect to the interrogator of FIG. 6. While the RFID sensing subsystem **810** includes a single path analog-to-digital converter operating preferably at least twice the Nyquist rate, it is also well within the broad scope of the present invention to configure the analog-to-digital conversion process to operate at the Nyquist rate by separating the signal to be converted into in-phase and quadrature phase signals and performing subsequent processing thereon.

Alternatively, the metal and RFID sensing subsystems **805**, **810** may be integrated into a sensing subsystem that provides a signal or a plurality of signals having at least one of a metal signature representing a presence of a metal object and an RFID signature representing a presence of an RFID object.

However, the interrogator employs the metal and RFID sensing integrated antenna **825**, which shares a common antenna between associated transmit and receive signals. For example, the metal sensing transmit/receive antenna **826** is coupled to both the metal sensing transmit conditioning filter **816** and the metal sensing receive conditioning filter **817** via the metal sensing diplexer switch **822**. Similarly, the first and second RFID sensing transmit/receive antennas **827**, **828** are coupled through the first and second RFID sensing diplexer switches **823**, **824** to their corresponding RFID sensing conditioning filters.

Generally, the diplexer switches are configured as conventional three-port devices so as to provide low loss paths for excitation signals proceeding from the transmit amplifiers to the antennas and correspondingly to provide low loss paths for incoming signals from the antennas to the receiving amplifiers. In time domain configurations, these may be accomplished by simple switching or gating. In continuous mode configurations, this may be accomplished by properly phasing signals so that they are in-phase when traveling to a desired port and out-of-phase when traveling to an undesired port.

The metal and RFID sensing integrated antenna **825** provides a suitable match to both launch a transmit signal and accept a receive signal associated with the metal and RFID sensing functions. The individual antennas may consist of single elements or may themselves be complex in nature with multiple elements. The antennas may be partially shielded so as to inhibit transmitted and received radiation to and from unwanted directions. For example, an antenna being passed over a patient or portion of the operating room such as a back table or MAYO stand, should ideally have maximum sensitivity in the direction and vicinity of the patient and maximum attenuation in all other directions.

Turning now to FIG. 9, illustrated is a block diagram of an embodiment of a control and processing subsystem constructed in accordance with the principles of the present invention. The control and processing subsystem includes a digital signal processor **905** employing a frequency control crystal **910**, a bootstrap memory **915**, a flash memory **920**, a random access memory **925**, and an input/output interface **930**.

The control and processing subsystem provides the digital signal processing functions, the signal generating functions, the control functions and the input and output interface functions associated with an interrogator. The digital signal processor **905** may be embodied as a single integrated circuit, or as a group of integrated circuits performing this role. Additionally, those skilled in the art should understand

26

that the digital signal processor **905** may be embodied in a digital signal processor engine, combinatorial logic and software, or a digital signal processor engine, an application specific integrated circuit, glue logic (including level shifters, translators, drivers, synchronizers, etc.) and software, or a special purpose digital signal processor engine, general purpose engine and software. The transmit signals are generated within the digital signal processor **905** which also includes a signal synthesizing function. The frequency control crystal **910** provides proper timing for the signal synthesizing function.

The bootstrap memory **915** is a non-volatile read-only memory that contains a basic software program to enable the interrogator to power up, accept commands from the keyboard, display diagnostics, and allow data ports to be used. In the case of a software-related system failure, the bootstrap system **915** allows the interrogator to recover (i.e., reboot). It also possesses basic system diagnostics which may be run independently of whatever software has been loaded.

The flash memory **920** is a non-volatile random access memory, where the current operating system and program of the interrogator is loaded. The contents of the flash memory **920** may be changed, updated and checked by diagnostics and programs contained in the bootstrap memory **915**. For example, diagnostics exist within the bootstrap memory **915** to test the random access memory **925**. The input/output interface **930** is a portion of the control and processing subsystem that accesses all other necessary portions as well as external ports of the interrogator, wherein the collection of interface connections **935** may be considered typical.

The data I/O port of the collection of interface connections **935** allows specific software releases or upgrades to be loaded into an interrogator, either wirelessly or using a wireline. In this manner, the characteristics of the interrogator may be easily changed or upgraded as necessary or appropriate. The software defined architecture enables this capability since all signal processing decisions and signal generation initiation occurs within the control and processing subsystem.

Similarly, this architecture permits upgrading of existing algorithms and incorporation of new algorithms for existing RFID tag and metal detection without hardware modifications. Therefore, the interrogator may be employed as substantially a universal interrogator that is capable of adaptation to read multiple versions of RFID tags from various manufacturers, including future-developed RFID tags. Of course, this may also include metal detection improvements and additions, as well.

Although the embodiments of this invention presented have concentrated on the detection and monitoring of disposable and non-disposable medical equipment, alternative embodiments and future applications outside the medical field are envisioned. These applications include integrating the detection of multiple disparate objects within a single system and the integration of disparate observables into a single integrating filter. Also included are the real-time integration of observables with multiple databases, and the real-time offloading of portions of the signal processing from the interrogator.

Alternative embodiments may include added detection range, increased detection sensitivity in hostile environments, increased detection integrity, real-time versatility in dynamically selecting what is to be detected, and simultaneous universal detection of multiple types of RFID tags and metallic objects, often operating at disparate frequencies.



These applications and embodiments may encompass, for example, inventory management, supply chain management, and security.

Having provided exemplary functionality associated with the interrogator and interrogation system according to the principles of the present invention, the radio frequency identification capabilities will hereinafter be described in greater detail. A protocol independent interrogation system (e.g., an RFID interrogation system) is described that includes at least one RFID excitation source, typically embodied in a transmit function, and a corresponding RFID receive function. The transmit and receive functions may be employed in an interrogator that includes control and processing subsystems and sensing subsystems embodied in a software defined architecture wherein a significant portion of signal processing is done in the digital domain after an incoming signal plus any associated noise has been appropriately digitized. The interrogator can accurately and predictably detect and read the signals coming from an RFID object (i.e., an object including an RFID tag or radio frequency identifier) at levels that are substantially below the detection threshold of presently available readers.

The enhanced sensitivity of the interrogation system according to the principles of the present invention can be exploited in several configurations and for several different and disparate applications. The flexibility of the interrogator allows selected RFID tags to remain “quiet” and others to come alive and “talk.” Additionally, an interrogator constructed according to the principles of the present invention may be configured to operate in a conventional reader mode or to employ enhanced sensitivity to perform a “deep” or “focused” detection mode to search for the RFID tags. By a “deep” or “focused” detection mode, the interrogator may be set to increase an energy of an excitation signal, command ones of the RFID tags to be “quiet,” increase an integration period of a correlation subsystem of the interrogator, command a user to scan an area more diligently, or increase aid from external sensors (e.g., position sensor). The aforementioned functions may be manually set by a user or automatically performed by the interrogator.

Further with respect to the RFID sensing functionality of the interrogator, the control and processing subsystem, and RFID sensing subsystem in conjunction with an antenna transmits radio frequency excitation signals and receives a response in the form of a reply code from the RFID tag and, when necessary, down converts the responses to a lower frequency for digitization purposes. A digital-to-analog converter of the RFID sensing subsystem converts the response to a digital signal. The digitization is typically at least one bit quantization. While the amplitude information is typically not preserved for a one bit quantization, the frequency information of the response is typically preserved. As a one bit quantization is subject to squaring loss, quantization employing at least two bits may be preferable depending on the application. Higher level quantization captures amplitude information that reduces squaring loss and also obtains unique amplitude characteristics of specific RFID tags which enhances detection sensitivity.

The digitized signals are input to a digital signal processor of the control and processing subsystem. The digital signal processing may be enhanced by the use of additional external sensors, for example, an inertial position sensor that can aid detection by noting a movement of the interrogator relative to a stationary RFID tag. The control and processing subsystem determines a presence or non-presence of an RFID tag. The systems and subsystems that form the interrogator are controlled by the control and processing subsys-

tem including system modes, detection modes, and all other relevant functions. A user interface and communications subsystem are provided for human and computer system interaction.

Turning now to FIG. 10, illustrated is a block diagram of an embodiment of an interrogation system demonstrating the capabilities associated with radio frequency identification according to the principles of the present invention. The interrogation system includes an interrogator **1015** including an RFID sensing subsystem **1020** and a control and processing subsystem **1030** that energizes an RFID tag **1005** and then receives, detects and decodes the encoded RF energy (reflected or transmitted) from the RFID tag **1005**. The control and processing subsystem **1030** provides overall control of the functions of the interrogator **1015** as well as any reporting functions. The interrogator **1015** may also include a user interface, communications subsystem, a power source and other subsystems as described above.

Additionally, the interrogation system may be employed with multiple RFID objects and with different types of RFID tags. For example, the RFID tags may be passive, passive with active response, and fully active. For a passive RFID tag, the transmitted energy provides a source to charge an energy storage device within the RFID tag. The stored energy is used to power a response from the RFID tag wherein a matching impedance and thereby a reflectivity of the RFID tag is altered in a coded fashion of ones (“1”) and zeros (“0”). At times, the RFID tag will also contain a battery to facilitate a response therefrom. The battery can simply be used to provide power for the impedance matching/mismatching operation described above, or the RFID tag may even possess an active transmitting function and may even respond at a frequency different from a frequency of the interrogator. Any type of tag (e.g., RFID tag) whether presently available or developed in the future may be employed in conjunction with the interrogation system. Additionally, the RFID objects may include more than one RFID tag, each carrying different information (e.g., object specific or sensors reporting on the status of the object) about the RFID object. The RFID tags may also include more than one integrated circuit, each circuit including different coded information for a benefit of the interrogation system.

Turning now to FIG. 11, illustrated is a block diagram of an embodiment of a reply code from an RFID tag in response to a query by an interrogator constructed according to the principles of the present invention. In the present embodiment, the reply code includes three sections, namely, a preamble **1105**, a cyclic redundancy check (CRC) **1110** to check for bit errors, and a tag identification (ID) code **1115** that uniquely specifies an RFID tag. In this example, the preamble **1105** is a fixed length having eight bits, the CRC **1110** is 16 bits and the tag ID code **1115** is either 64 or 96 bits. Of course, the length of the respective sections of the reply code and the sections that form the reply code may be modified including the addition of additional or different sections and still fall within the broad scope of the present invention.

The interrogator may employ the tag ID code **1115** to more definitively detect and identify a specific RFID tag and a digital signature associated with the RFID tag. More specifically, it is possible to detect an RFID tag employing portions of or the entirety of the reply code. As an example, the interrogator may employ the tag ID code **1115** only to detect a presence of an RFID tag or employ the additional bits available from the CRC **1110** as well as the preamble **1105** or other sections of the reply code to create a longer



and more sensitive data stream for processing and identifying an RFID tag. Also, in a conventional reader mode and as noted above, the RFID tags may be detected via incoming RF energy and without apriori knowledge of any information about the RFID tag. In this instance, a relatively strong signal incident on the interrogator is preferable to generate a sufficiently positive signal to noise ratio (SNR) to reliably detect the incoming signal and, ultimately, the presence of the RFID tag.

Turning now to FIG. 12, illustrated is a waveform diagram of an exemplary one-bit cell of a response from an RFID tag to an interrogator in accordance with the principles of the present invention. With a logical "1" response, zero encoding is in a frequency shift keying (FSK) modulation format to distinguish logical "1" from logical "0," but an on/off nature of the backscatter return signal of the RFID tag is also actually an amplitude shift keying (ASK) signal. The shift in amplitude is detected by the interrogator and the frequency of operation determines whether the detection represents a logical "1" or logical "0." For a better understanding of RFID tags, see "Technical Report 860 MHz-930 MHz Class I Radio Frequency Identification Tag Radio Frequency & Logical Communication Interface Specification Candidate Recommendation," Version 1.0.1, November 2002, promulgated by the Auto-ID Center, Massachusetts Institute of Technology, 77 Massachusetts Avenue, Bldg 3-449, Cambridge Mass. 02139-4307, which is incorporated herein by reference.

The backscatter return signal is embodied in the response from an RFID tag. A low backscatter return signal is generated when the RFID tag provides a matched load so that any energy incident on the antenna of the RFID tag is dissipated within the RFID tag and therefore not returned to the interrogator. Alternatively, a high backscatter return signal is generated when the RFID tag provides a mismatched load so that any energy incident on the antenna of the RFID tag is reflected from the RFID tag and therefore returned to the interrogator. For more information, see "RFID Handbook," by Klaus Finkenzeller, published by John Wiley & Sons, Ltd., 2<sup>nd</sup> edition (2003), which is incorporated herein by reference.

Turning now to FIG. 13, illustrated is a waveform diagram of an exemplary response from an RFID tag in accordance with the principles of the present invention. The exemplary response includes recorded transmissions **1315** and backscatter return signals **1320** from the RFID tag under docile conditions. Under docile conditions, the response from the RFID tag is quite strong and substantially above the ambient noise level **1310** and an interrogator can more readily detect the response on an individual bit-by-bit basis.

Turning now to FIG. 14, illustrated is a waveform diagram of a spectral response associated with the response from the RFID tag illustrated in FIG. 13. As illustrated, the spectral response provides a strong signal in accordance with the response from the RFID tag under docile conditions. The signal is essentially in two distinct components. The first component is a strong backscatter return **1410**, which is strongest in amplitude and at the center of the response. The second component is the lower amplitude FSK modulations backscatter return **1415** consisting of a series of peaks. In hostile environments or, more generally, when the response from the RFID tag is not as strong such as when the RFID tag is located at an increased range from the interrogator or the RFID tag is obstructed from the interrogator by absorptive or reflective materials, the backscatter return signals **1415** from the RFID tag to the interrogator are substantially weakened. Consequently, the detec-

tion and identification of the RFID tag is much more difficult and an interrogator architecture that can accommodate an improved signal to noise detection capability under adverse conditions while not increasing the probability of erroneous responses would be advantageous. As will become more apparent, an interrogator and interrogation system constructed according to the principles of the present invention accommodates reliable identification of the RFID tag under docile conditions and in hostile environments.

By way of example, consider a response from an RFID tag and the existence thereof to be a one-bit message, namely, the RFID tag is either present or not. Then, the presence of the RFID tag may be a logical "1" and an absence thereof may be a logical "0," or vice versa. Then, further consider the bits of the reply code (see, for instance, the reply code of FIG. 11) to be a spreading code for the one-bit message. Spreading codes are used in spread spectrum communications to provide additional gain from signal processing for weak signals. For a better understanding of spread spectrum technology, see an "Introduction to Spread Spectrum Communications," by Roger L. Peterson, et al., Prentice Hall Inc. (1995) and "Modern Communications and Spread Spectrum," by George R. Cooper, et al., McGraw-Hill Book Inc. (1986), both of which are incorporated herein by reference.

Further assume that a reference code (representing a reply code or portions thereof such as a tag ID code) is preloaded into an interrogator and the reply code from the RFID tag plus any noise are correlated against the reference code by a correlation subsystem within the interrogator. If a match occurs, an increase in a gain [in decibels (dB)] for the matched signal within the interrogator follows the relationships as set forth below: Gain Increase (dB)=10×Log<sub>10</sub> (N), wherein "N" is the number of bits used in the correlation.

In a numerical example, if an RFID tag with a 64 bit tag ID code is used for the correlation, then the gain would be 18.06 dB. Additionally, if an RFID tag with a 96 bit tag ID code and an eight bit preamble and 16 bit CRC is used for the correlation, then the gain would be 20.79 dB. The gain corresponds to an improvement in the SNR as set forth above.

Turning now to FIG. 15, illustrated is a waveform diagram demonstrating a representative signal to noise gain employing an interrogator in accordance with the principles of the present invention. Typically, a reply code associated with a response from an RFID tag is read on a bit-by-bit basis and each bit is detected on an individual basis. Under less than ideal conditions, the detected bits **1510** are often only slightly above an ambient noise level **1525** as illustrated in FIG. 15. Preferably, an interrogator constructed according to the present invention reads the entire reply code and treats the reply code as a spreading code with the existence of the RFID tag being only a single data bit. Thus, the additional gain **1515** achieved by this approach produces a substantially larger signal **1505** which substantially expands a potential for a reliable detection process both of an obstructed RFID tag and with an RFID tag located at a greater distance from the interrogator.

The detection threshold **1520** is a level that should be sufficiently above noise so that false alarms do not readily occur such that a utility of the interrogator is defeated. Correspondingly, setting the detection threshold **1520** too high will detrimentally affect the sensitivity of the interrogator. Thus, calibrating the threshold of the interrogator provides more latitude in setting a threshold without adversely affecting a detection sensitivity thereof. The additional detection sensitivity may be advantageously used in



several ways. For example, the additional detection sensitivity can be used to increase detection range to detect RFID tags when obscured by attenuating materials, or to substantially improve the statistical quality of a detection (or a non-detection). Thus, by correlating the reference code with incoming reply codes from RFID tags plus ambient noise, the presence of the RFID tags can be reliably detected when the reply codes from the RFID tags are at substantially lower signal levels than is presently possible.

Turning now to FIG. 16, illustrated is a block diagram of an embodiment of an initialization stage of an interrogation system in accordance with the principles of the present invention. During an optional pre-initialization stage, reference codes corresponding to the reply codes of the RFID tags **1605** on the RFID objects **1610** (designated A, B, C, . . . N) are logged into memory (e.g., a database) of an interrogator **1615** of the interrogation system. Then, during an initialization stage, the RFID objects **1610** are scanned by the interrogator **1615** at which time each individual reply code of the RFID tags **1605** is read and checked against the database of reference codes logged during the pre-initialization stage. If a pre-initialization stage is not performed, the reference codes corresponding to the reply codes of the RFID tags **1605** are logged into the database during the initialization stage.

During the initialization stage, the RFID tags **1605** are not typically obstructed so that identifying the reply codes of the RFID tags **1605** can be performed without employing a high level of sensitivity. When read in this manner, the tag ID code and other fields (which may serve as the reference code) corresponding to the reply code of the RFID tag **1605** can be captured using multiple amplitude bits (e.g., at least two) so that unique characteristics of an amplitude of the reply codes are also captured and can be used to increase the uniqueness associated with the RFID tag **1605** and employable during a subsequent correlation operation. While single bit detection is also possible and within the broad scope of the present invention, a single bit detection may be subject to a sensitivity degradation of a squaring loss thereof. The interrogator **1605** may also capture characteristics associated with the environment such as ambient background noise to further increase the sensitivity of the interrogator **1605**.

There are several alternative methods to create the reference code. By directly scanning the RFID tag **1605** during the initialization stage, the most information about the RFID tag **1605** can be obtained to form the reference code. Alternatively, the reference code can be derived synthetically. To derive the reference code synthetically, the amplitude, phase and delay (timing of a response to an excitation signal) information of a particular type of RFID tag **1605** may be employed by the interrogator **1615** to derive the synthetic reference code. Another technique to derive the reference code is also a synthetically derived reference code employing one bit quantization. While the amplitude information may not be preserved for a one bit quantization, the frequency information of the response is typically preserved. As a one bit quantization is subject to squaring loss, quantization employing at least two bits may be preferable depending on the application. Higher level quantization captures amplitude information that reduces squaring loss and also obtains unique amplitude characteristics of specific RFID tags **1605** which enhances detection sensitivity.

In an alternative embodiment, the reference code corresponding to the reply code for the RFID tags **1605** can be input digitally via a keyboard or via a data port and a correlation pattern may be generated in the digital domain

using one bit for each data bit. While amplitude information is not typically captured or used under these circumstances, the ambient noise information can still be collected to augment the sensitivity of the interrogator **1615**. In yet another related embodiment, preloaded amplitude information may be input into the interrogator **1615** that matches amplitude characteristics of a reply code of an RFID tag **1605**. As a result, a sensitivity of the interrogator **1615** is enhanced while, at the same time, taking advantage of digitally inputting the reference code corresponding to the reply code of the RFID tag **1605**. Thereafter and during a post initialization stage, the correlation subsystem of the interrogator **1615** correlates between the reference code and a reply code from the RFID tags **1605** (when subsequently energized by the interrogator **1615**) to enhance a detection sensitivity thereof.

Turning now to FIG. 17, illustrated is a block diagram of an embodiment of a post initialization stage of an interrogation system in accordance with the principles of the present invention. In an exemplary manner, an interrogator **1720** is shown scanning across first, second and third sets of tagged items **1705**, **1710**, **1715** (also referred to as RFID objects). Here, the first set of tagged items **1705** represents unobstructed tags, while the second and third sets of tagged items **1710**, **1715** represent obstructed, obscured, or more distant tags. In general, scanning unobstructed RFID tags can be read by an interrogator **1720** without employing a high level of sensitivity and may be read at substantial ranges (e.g., 15-20 feet). Under such circumstances, the interrogator **1720** may not employ a correlation operation. In contrast, scanning obstructed RFID tags (by an obstructing media or even at greater ranges) is preferably performed by an interrogator **1720** employing a higher level of sensitivity. Under such circumstances, the interrogator **1720** may employ a correlation subsystem to correlate between a reference code (previously logged) and a reply code for an RFID tag.

In such instances, the interrogator **1720** may correlate on small portions of a reply code from the RFID tag and provide an indication of a presence of the RFID tag. For example, correlating on the preamble provides a nine decibel increase in detection sensitivity when the preamble is eight bits long. While employing the preamble alone does not uniquely identify an RFID tag, it does, with high probability, indicate the presence of an RFID tag. Of course, the correlation subsystem may also employ a reference code to correlate against the entire reply code of the RFID tag depending on the particular application. Other detection techniques such as non-coherent averaging may be employed by the interrogator to uniquely identify an RFID tag.

Turning now to FIG. 18, illustrated is a flow chart of an embodiment of a method of detecting an RFID tag according to the principles of the present invention. The system is first powered up performing a system boot and setup **1805**. This is typically followed by a preinitializing and initializing stage **1810**. As mentioned above, during an initialization stage reference codes corresponding to the reply codes of the RFID tag are logged into the interrogator. The reference codes corresponding to the reply codes of the RFID tags are read by or logged into the interrogator, noting specific RFID tag characteristics along with RFID tag's ID code. This is typically done by loading the reference codes into memory and establishing a log within the interrogator during a load memory stage **1815**. Thereafter and during the post initialization stage, the interrogator scans for the RFID tags during a scan stage **1820** (which may be a single scan or non-



coherent integration) and, via the reply code, detects and logs the detection thereof during a detection stage **1825** (which may be located, individually and in groups, correlated with a log).

A correlation operation performed by the interrogator correlates between the reference codes and the reply codes from the RFID tags. Any reference codes previously logged, but not matched during the correlation operation, are flagged during a flagging stage **1830** via a user interface of the interrogator to the user (including audible queues or alarms), communications subsystem to a computer system, or other suitable techniques. Via alerts, the search is repeated during a repeat search stage **1835** with added sensitivity until the reference codes corresponding to the reply codes of previously logged RFID tags match the reply codes from the RFID tags detected during the post initialization stage. Returning to the interrogator in search mode, this is typically a first attempt at locating an RFID tag. When the searches are repeated, other approaches may be employed including multiple scans, highly localized scanning, or coherent integration as discussed later.

Turning now to FIG. **19**, illustrated is a block diagram of portions of a control and processing subsystem of an interrogator constructed according to the principles of the present invention. The control and processing subsystem includes a correlation subsystem **1905** and a decision subsystem **1910**. While in the illustrated embodiment the correlation subsystem and the decision subsystem form a portion of the control and processing subsystem such as within a digital signal processor thereof, those skilled in the art should understand that the subsystems may be discrete subsystems of the control and processing subsystem of the interrogator.

As mentioned above, the interrogator may employ a correlation operation to correlate between reference codes (generally designated **1915**) corresponding to reply codes (generally designated **1925**) from the RFID tags and subsequently received and digitized reply codes from the RFID tags to enhance a sensitivity of the interrogator. The reply codes are typically generated as complex  $I+jQ$  signals where  $I$  signifies the in phase portion of the signal and  $Q$  signifies its quadrature counterpart. The reference codes may be scanned in during the initialization stage or derived synthetically as hereinafter described. To derive the reference code synthetically, the amplitude, phase and delay (timing of a response to an excitation signal) information of a particular type of RFID tag may be employed by the interrogator to derive the synthetic reference code. The correlation occurs in a correlator **1930** wherein the reply code is correlated with the reference code. The correlation is mathematically analogous to a convolution operation. For a better understanding of convolution theory, see "An Introduction to Statistical Communication Theory," by John B. Thomas, published by John Wiley & Sons, Inc. (1969), which is incorporated herein by reference.

A stream of incoming data to the interrogator (corresponding to responses in the form of reply codes from the RFID tags) is correlated against preloaded reference codes loaded into a reference code database in time. Alternatively, samples of the incoming data may be gated in a block by the interrogator and then the data is correlated in block manner against the reference codes. In the latter example, a gating process is employed to gate the incoming data properly. Under such circumstances, it is preferable that apriori knowledge of a timing of the responses from the RFID tag in connection with a query by the interrogator better serves the process of gating the block of incoming data (i.e., the responses) from the RFID tags. Any known delay in the

responses from the RFID tags can be preloaded in the interrogator during the initialization stage. An external sensor such as a position sensor (e.g., inertial sensor) may be employed by the interrogator to aid the correlation subsystem in predicting the timing of a response from the RFID tag. A synchronization pulse (derived from the transmit excitation signal) may also be employed to better define a timing of a response from an RFID tag.

The output of the correlator **1930** representing individual correlations of the reference code with incoming data is summed in a summer **1935** providing a correlation signal to improve the signal to noise ratio of the correlated signal. The correlation signal from the summer **1935** is typically input into a threshold detector **1940** within the decision subsystem **1910** to verify a presence of an RFID tag. The threshold detector **1940** typically compares the correlation signal with at least one threshold criteria or value (also referred to as threshold). The threshold may be fixed or dynamically determined. In one exemplary embodiment, where only a single threshold is present, an RFID tag is declared present if the correlation signal from the summer **1935** exceeds the threshold, and not present if the converse is true. In other embodiments, multiple thresholds may be used to indicate various levels of probabilities as to the likelihood that an RFID tag is present or not. This information may then be used to initiate selected or additional search modes so as to reduce remaining ambiguities.

Regarding the timing of the responses from the RFID tag, a tracking of the reply codes may suggest that the reply code is early, prompt or late. If the tracking suggests that the reply code is prompt (prompt output greater than early and later output), then a gating function is properly aligned to provide a significant correlator output. If the tracking suggests that the reply code is early, then the early correlator output is significant as compared to the late correlator output and the correlation subsystem **1905** is tracking too early and the requisite adjustment may be performed. An opposite adjustment may be performed if the tracking suggests that the reply code is late.

Another approach is to use a tracking loop that uses past successful detection performance to establish a gating process for subsequent correlations. In yet another embodiment relating to the correlation of the reply codes from the RFID tags is to perform Fast Fourier Transforms (FFTs) on both the reference code and a gated sample of the reply codes from the RFID tags. Then, a convolution operation in "Fourier Space" may be performed employing the convolution theorem. The convolution theorem states that the convolution of two functions is the product of the Fourier transforms thereof. An output of the correlation operation is typically envelope detected and several outputs may be averaged in a summing operation that preserves time characteristics of each individual detection.

Turning now to FIG. **20**, illustrated is a block diagram of an embodiment of portions of a correlation subsystem associated with a control and processing subsystem of an interrogator demonstrating an exemplary operation thereof in accordance with the principles of the present invention. In the present embodiment, a technique referred to as a "corner turning memory" is used in accordance with the correlation subsystem allowing a summing and averaging process for multiple correlations. An output of a correlator is read into memory by rows (one of which is designated **2010**) with each row designating a single correlation. Then an output from the summing process (which embodies the memory or a function thereof) is generated by summing across individual columns (generally designated **2015**, hence the name



35

corner turning) applying an appropriate scaling factor. An output from the memory represents an average of “P” outputs of the correlation subsystem wherein “P” is the number of rows in the corner turning memory. Assuming a signal is located in every row of the corner turning memory, the improvement in SNR is increased by the square root of “P.”

Using this approach, several options for enhancing performance of the interrogator are possible. For example, the results of different averaging times can be almost simultaneously compared and the modes of operation of the interrogator adjusted for enhanced performance. Also, this approach allows the sliding average technique (as described above) to be employed so that the output from the memory is an average over a predetermined period of time. Also, other averaging techniques in addition to the use of the corner turning memory are also well within the broad scope of the present invention.

Turning now to FIG. 21, illustrated is a waveform diagram demonstrating exemplary advantages associated with the correlation subsystem described with respect to FIGS. 19 and 20. In the illustrated embodiment, a conventional waveform 2115 represents the probability of detection for a given carrier to noise ratio (C/No) of a conventional reader reading at least one out of 100 possible attempts. A total of 100 trials were averaged in accordance with the correlation subsystem and an improved waveform 2110 represents the increased probability of detection for a given C/No of an interrogator thereby demonstrating an improvement in SNR of 28.06 dB. This represents 18.06 dB due to correlation operation wherein a length 64 electronic product code (EPC) code was used, plus an additional 10 dB due to non-coherent averaging. A purpose of the correlation operation is to determine whether or not the output or averaged output of the interrogator represents a presence of an RFID tag. A threshold detector as herein described then interprets a correlation signal from the correlation subsystem and provides a decision if the output is of sufficient quality to indicate if an RFID tag is present or not and, if indeterminate, to perform a “deeper” or more “focused” search.

Turning now to FIG. 22, illustrated is a block diagram of an embodiment of a decision subsystem associated with a control and processing subsystem of an interrogator constructed according to the principles of the present invention. In the illustrated embodiment, the decision subsystem is referred to as a threshold detector as it indicates a status on a correlation signal input from a correlation subsystem. A threshold detector 2220 provides at least two logical outputs, namely, a logical “1” and a logical “0.” The output of the threshold detector may be a predetermined logical “1” or “0” if a threshold criteria is passed, and an alternate logical “1” or “0” if the threshold criteria is not passed. In short, the output is YES if an RFID tag is detected meaning that the input exceeds a threshold and NO if an RFID tag is not detected meaning that the input does not exceed the threshold.

A decision threshold for the threshold criteria may be embodied in several different ways as set forth below: 1. the threshold criteria may be a predetermined fixed value, 2. the threshold criteria may be a time varying value based on multiple efforts and averaging algorithms used to detect an RFID tag, 3. the threshold criteria may be related to the number of rows used for averaging in the corner turning memory as described above, 4. the threshold criteria may be influenced by ambient conditions (for example, noise) detected in the environment during the initialization stage as described above, 5. the threshold criteria may be determined

36

by a tolerated level of false alarms or missed detections, or 6. the threshold criteria may be determined by whether a cursory or very extensive (“deep” or “focused”) search has been directed by the control and processing subsystem. Other threshold criteria are clearly within the broad scope of the present invention. Also, a noise meter may be employed within the threshold criteria for the threshold detector 2220.

Additionally, more than two outputs may also be present to indicate states of the presence or non-presence of the RFID tag and may exist with lower criteria. For example, an indication may be provided that an RFID tag “may” be present, however the statistical criteria for false alarm may not have been met. This information may be useful and presented in a user interface (e.g., a display or data output), or it may also be used by the control and processing subsystem to change or adjust an operating mode in the interrogator to resolve the ambiguity and direct subsequent actions.

Turning now to FIG. 23, illustrated is a block diagram of an embodiment of a correlation subsystem associated with a control and processing subsystem of an interrogator constructed according to the principles of the present invention. A selected number of reference bits R1 . . . RN associated with reference codes corresponding to reply codes of RFID tags are latched and fed into one input of a correlator 2315 one bit at a time. A stream of derived sample bits T1 . . . TN (corresponding to sample bits S1 . . . SQ of the reply codes from the RFID tags) are input to the correlator 2315 at substantially the same time. A gate pulse from a gating clock synchronizes the inputs to the correlator 2315 at the proper time. Additionally, a Q to N operation 2325 (where “Q” is the length of the shift register 2335 that receives the sample bits S1 . . . SQ and “N” is the size of a latch 2345) is performed wherein the derived sample bits T1 . . . TN from the sampled bits S1 . . . SQ are input into a latch 2345 of the correlation subsystem. Bits reaching the output of the shift register 2335 are typically discarded.

If time synchronization between the reference bits R1 . . . RN and the derived sample bits T1 . . . TN is correct, a signal from the correlator 2315 will be highly correlated resulting in a large output signal to the correlation threshold sense 2350. Also, the output signal will vary in amplitude for the derived sample bits T1 . . . TN corresponding to the bits of the reply code that are before and after a high level of correlation. If time synchronization is not proper or if the reply code is not present, then the correlation function will provide a noisy output. The gating clock is typically shift-able in time and phase to search for a proper alignment between the two signals. To achieve proper alignment, a correlation subsystem employing a single correlator can search across time and phase with respect to the transmission of an excitation signal. Alternatively, a correlation subsystem that employs multiple correlators can be set to slightly different time and phase settings to simultaneously search across a larger phase and frequency space.

The correlation threshold sense 2350 is similar to the threshold detector illustrated and described with respect to FIG. 22. A threshold of the correlation threshold sense 2350 is typically set quite low to allow for a reasonable averaging to occur in subsequent processing. In this context, the correlation threshold sense 2350 may be considered a pre-filter to a decision subsystem. In an alternative embodiment, the correlation threshold sense 2350 may be performed in the decision subsystem. An output of the correlation threshold sense 2350 is then input to a summer 2355, which after



37

multiple transmissions and detections (non-coherent integration) provides a correlation signal to the decision subsystem.

In an exemplary embodiment, the correlation threshold sense **2350** receives an output from an exclusive OR function that performs a bit-by-bit operation on the reference bits **R1** . . . **RN** and the derived sample bits **T1** . . . **TN**. Multiple outputs of the exclusive OR function are accumulated in the correlation threshold sense **2350** and compared to a threshold value. If the outputs of the exclusive OR function exceed the threshold value, a relatively good indication is provided of a location of a peak of a correlation triangle. Otherwise, a relatively good indication is provided that the peak of the correlation triangle either is outside of the sampled bits **S1** . . . **SN** or that the peak of the correlation triangle is not substantially centered within the sampled bits **S1** . . . **SN**. The accumulated outputs of the exclusive OR function are thereafter transmitted to the summer **2355** which may include a corner turning memory (see FIG. **20**) for further processing. In the environment of the corner turning memory, each accumulated output of the exclusive OR function represents a data bit (such as **D(1, P)**) of a row of the corner turning memory.

An exemplary correlation triangle **2365** in reference to a threshold value is illustrated in FIG. **23**. Within the correlation threshold sense **2350**, a threshold detector provides a high signal when the accumulated outputs of the exclusive OR function exceed a threshold value **2370** and, otherwise, provide a low signal. A resulting pulse or signal **2375** as illustrated in FIG. **23** may be employed to ascertain (e.g., estimate) a location of a peak of the correlation triangle **2365**.

Turning now to FIG. **24**, illustrated is a block diagram of an embodiment of portions of a correlation subsystem associated with a control and processing subsystem of an interrogator constructed according to the principles of the present invention. In particular, the present embodiment demonstrates a Q to N operation, wherein "Q" is the length of a shift register **2410** that receives the sample bits **S1** . . . **SQ** of the reply codes from the RFID tags and "N" is the size of a latch. The incoming data including the reply code from the RFID tags is sampled at a rate higher than the signal rate of the reply code to generate the sampled bits **S1** . . . **SQ**. Then the Q to N conversion occurs by summing successive consecutive sequences of J bits, where  $Q=J \times N$  and "J" is the number of sampled bits in a sequence. As a result, derived sample bits **T1** . . . **TN** are derived from the sample bits **S1** . . . **SQ**. Appropriate scaling factors are then applied to the derived sample bits **T1** . . . **TN** and the reference bits to account for the summing operation.

Turning now to FIG. **25**, illustrated is a block diagram of another embodiment of a correlation subsystem associated with a control and processing subsystem of an interrogator constructed according to the principles of the present invention. In contrast to other embodiments of the correlation subsystem wherein a length of the incoming data including the sample bits **S1** . . . **SQ** of the reply codes from the RFID tags is decreased from Q to N (see description with respect to FIG. **24** above), in the present embodiment the number of reference bits **R1** . . . **RN** is increased to provide a set of derived reference bits **U1** . . . **UQ** from a N to Q operation **2510**. The N to Q operation **2510** is substantially opposite to the Q to N operation illustrated and described with respect to FIG. **24**. An output of the N to Q operation is then input to a correlator **2525**. Additionally, the correlation subsystem employs a higher sampling rate with output results (after

38

application of the proper scaling factors) analogous to the correlation subsystem illustrated and described with respect to FIG. **23**.

A gate pulse from a gating clock synchronizes the inputs to the correlator **2525** at the proper time. Additionally, derived sample bits **T1** . . . **TQ** are latched into a Q bit latch **2530** of the correlation subsystem. These bits are a result of sample bits of a reply code clocking through a shift register **2540**. Bits reaching the output of the shift register **2540** are typically discarded.

As in FIG. **23**, if time synchronization between the derived reference bits **U1** . . . **UQ** and the derived sample bits **T1** . . . **TQ** is correct, a signal from the correlator will be highly correlated resulting in a large output signal to the correlation threshold sense **2550**. Also, the output signal will vary in amplitude for the sample bits **T1** . . . **TQ** corresponding to the bits of the reply code that are before and after a high level of correlation. If time synchronization is not proper or if the reply code is not present, then the correlation function will provide a noisy output. The gating clock is typically shiftable in time and phase to search for a proper alignment between the two signals. To achieve proper alignment, a correlation subsystem employing a single correlator can search across time and phase with respect to the transmission of an excitation signal. Alternatively, a correlation subsystem that employs multiple correlators can be set to slightly different time and phase settings to simultaneously search across a larger phase and frequency space.

The correlation threshold sense **2550** is similar to the threshold detector illustrated and described with respect to FIG. **22**. A threshold of the correlation threshold sense **2550** is typically set quite low to allow for a reasonable averaging to occur in subsequent processing. In this context, the correlation threshold sense **2550** may be considered a pre-filter to the decision subsystem. In an alternative embodiment, the correlation threshold sense **2550** may be performed in the decision subsystem. An output of the correlation threshold sense **2550** is then input to a summer **2555**, which after multiple transmissions and detections (non-coherent integration) provides a correlation signal to a decision subsystem.

In an exemplary embodiment, the correlation threshold sense **2550** receives an output from an exclusive OR function that performs a bit-by-bit operation on the derived reference bits **U1** . . . **UQ** and the derived sample bits **T1** . . . **TQ**. Multiple outputs of the exclusive OR function are accumulated in the correlation threshold sense **2550** and compared to a threshold value. If the outputs of the exclusive OR function exceed the threshold value, a relatively good indication is provided of a location of a peak of a correlation triangle. Otherwise, a relatively good indication is provided that the peak of the correlation triangle either is outside of the sampled bits **S1** . . . **SQ** or that the peak of the correlation triangle is not substantially centered within the sampled bits **S1** . . . **SQ**. The accumulated outputs of the exclusive OR function are thereafter transmitted to the summer which may include a corner turning memory (see FIG. **20**) for further processing. In the environment of the corner turning memory, each accumulated output of the exclusive OR function represents a data bit (such as **D(1, P)**) of a row of the corner turning memory.

An exemplary correlation triangle **2565** in reference to a threshold value **2570** is illustrated in FIG. **25**. Within the correlation threshold sense **2550**, a threshold detector provides a high signal when the accumulated outputs of the exclusive OR function exceed the threshold value **2570** and, otherwise, provide a low signal. A resulting pulse **2575** as



illustrated in FIG. 25 may be employed to ascertain (e.g., estimate) a location of a peak of the correlation triangle **2565**.

Turning now to FIG. 26, illustrated is a block diagram of yet another embodiment of a correlation subsystem associated with a control and processing subsystem of an interrogator constructed according to the principles of the present invention. The reference code corresponding to a reply code of an RFID tag is captured during an initialization stage and stored as a higher number of reference bits **R1 . . . RQ**. These bits are then latched into a Q-bit latch **2610** as derived reference bits **U1 . . . UQ** and fed into one input of a correlator **2620** one bit at a time. A stream of derived sample bits **T1 . . . TQ** (corresponding to sample bits **S1 . . . SQ** of the reply codes from the RFID tags) are input to the correlator **2620** at substantially the same time. The correlation operation is then performed without employing the Q to N or N to Q conversion operation as set forth above. Performing the initialization stage with a higher number of bits (at the higher bit rate) captures more of the unique characteristics of the RFID tag and can be used to further aid the correlation subsystem. The aforementioned correlation subsystems perform a non-coherent integration of multiple samples (e.g., 100 samples). A gate pulse from a gating clock synchronizes the inputs to the correlator **2620** at the proper time. Additionally, a Q-bit latch **2625** is used to latch the derived sample bits **T1 . . . TQ** into a latch **2625**. Bits reaching the output of a shift register **2635** are typically discarded.

If time synchronization between the reference bits **R1 . . . RQ** and the sample bits **T1 . . . TQ** is correct, a signal from the correlator **2620** will be highly correlated resulting in a large output signal to a correlation threshold sense **2645**. Also, an output signal will vary in amplitude for the derived sample bits **T1 . . . TQ** corresponding to the bits of the reply code that are before and after a high level of correlation. If time synchronization is not proper or if the reply code is not present, then the correlation function will provide a noisy output. The gating clock is typically shiftable in time and phase to search for a proper alignment between the two signals. To achieve proper alignment, a correlation subsystem employing a single correlator can search across time and phase with respect to the transmission of an excitation signal. Alternatively, a correlation subsystem that employs multiple correlators can be set to slightly different time and phase settings to simultaneously search across a larger phase and frequency space.

The correlation threshold sense **2645** is similar to the threshold detector illustrated and described with respect to FIG. 22. A threshold of the correlation threshold sense **2645** is typically set quite low to allow for a reasonable averaging to occur in subsequent processing. In this context, the correlation threshold sense **2645** may be considered a pre-filter to the decision subsystem. In an alternative embodiment, the correlation threshold sense **2645** may be performed in the decision subsystem. An output of the correlation threshold sense **2645** is then input to a summer **2650**, which after multiple transmissions and detections (non-coherent integration) provides a correlation signal to a decision subsystem.

In an exemplary embodiment, the correlation threshold sense **2645** receives an output from an exclusive OR function that performs a bit-by-bit operation on the derived reference bits **U1 . . . UQ** and the derived sample bits **T1 . . . TQ**. Multiple outputs of the exclusive OR function are accumulated in the correlation threshold sense **2645** and compared to a threshold value. If the outputs of the exclusive

OR function exceed the threshold value, a relatively good indication is provided of a location of a peak of a correlation triangle. Otherwise, a relatively good indication is provided that the peak of the correlation triangle either is outside of the sampled bits **S1 . . . SQ** or that the peak of the correlation triangle is not substantially centered within the sampled bits **S1 . . . SQ**. The accumulated outputs of the exclusive OR function are thereafter transmitted to the summer **2650** which may include a corner turning memory (see FIG. 20) for further processing. In the environment of the corner turning memory, each accumulated output of the exclusive OR function represents a data bit (such as **D(1, P)**) of a row of the corner turning memory.

An exemplary correlation triangle **2660** in reference to a threshold value **2665** is illustrated in FIG. 26. Within the correlation threshold sense **2645**, a threshold detector provides a high signal when the accumulated outputs of the exclusive OR function exceed the threshold value **2665** and, otherwise, provide a low signal. A resulting pulse **2670** as illustrated in FIG. 26 may be employed to ascertain (e.g., estimate) a location of a peak of the correlation triangle **2660**.

Looking at any of the sample(s) and in accordance with the aforementioned discussion regarding FIG. 23, et seq. by performing a bit-for-bit exclusive OR function between the reference bits **R** and derived sample bits **T** from the sample bits **S** and shifting the derived sample bits **T** from the sample bits **S** one bit at a time and performing another bit-for-bit exclusive OR, the correlator derives a correlation triangle when the reply code from the RFID tag is present (which may be sufficient to detect the RFID tag). If the correlation triangle is undistinguishable (maybe weak signal or high ambient noise), the correlation subsystem then repeats the aforementioned function (and maybe many times over) on yet another reply code(s) and the correlator derives yet another correlation triangle, in such circumstances, the results are then integrated (e.g., bit for bit summation) of the correlation triangles to derive a non-coherent integration of multiple reply codes.

As illustrated and described, the previously introduced embodiments of the correlation subsystem employ a gated correlation operation as the signal (reply code) to be correlated is captured in a block and then gated through the correlation subsystem in a serial fashion, at least one bit at a time. For strong signal conditions, a single sampling and correlation will often be sufficient to determine a presence of an RFID tag. For conditions where the signals are not as strong, the number of summed samples increases to be greater than one. An improvement in the SNR may result, in part, from a summing operation and the improvement may increase as the square root of the number of samples averaged before being input to the decision subsystem. The aforementioned summing or integration functionality may be referred to as non-coherent integration.

Turning now to FIGS. 27 and 28, illustrated are block diagrams of embodiments of a Fast Fourier Transform (FFT) operation employable with a correlation subsystem associated with the control and processing subsystem of the interrogator constructed according to the principles of the present invention. As mentioned above, convolution theorem may be performed in conjunction with a FFT operation. A FFT is performed on the reply code and the stored reference code from the initialization stage (see FIG. 27). The reply code and reference code (or selected bits or sample bits thereof) are then complex multiplied and con-



verted back to the time domain by an Inverse Fast Fourier Transform (“IFFT”). Zero padding is employed to substantially prevent aliasing.

With the exception of the FFT operations, the correlation subsystem is analogous to the correlation subsystems described above. The convolution theorem and the use of FFTs provides a computationally efficient technique of implementing a correlation subsystem. Additionally, aliasing in regions of non-interest (i.e., where a correlation triangle is not likely to exist) should not harm the results so that the length of the FFT may be shortened to improve computational efficiency. Also, in those instances where the range of variation is small, it may be preferable to employ dot product correlations for even further computational efficiency.

Referring once again to FIG. 27, incoming data is collected as a block of complex I and Q values 2710 followed by removing the DC terms 2715. These values are correlated 2720 against a reference code 2725 using the convolution theorem. Subsequent to correlation, a square law envelope detection function 2730 obtains amplitude information. This is then input to the corner turning memory function 2735 followed by a summer 2740 and then a threshold and detection function 2745, of which were discussed above.

Referring once again to FIG. 28, the specifics of the correlation operation 2720 is illustrated in detail. The incoming data of length S 2805 is increased to length M by zero padding 2810 to assure the data is of an appropriate length for an FFT operation 2815. In the same manner, the normalized length R of the reference code 2830 is also increased to length M by a zero pad 2835, to which is then performed a length M FFT 2845 and a complex conjugate 2850 of the result performed. A complex term by term multiplication 2820 is performed and a length M IFFT 2825 is performed to complete the function.

In the presence of noise, or during very weak signal conditions, the correlation subsystem may erroneously correlate on noise. The interrogator substantially reduces those effects by comprehending that actual correlations do not have a single correlation peak, but a major peak that is surrounded by smaller correlation peaks. The aforementioned characteristics are referred to as sidelobes or time sidelobes.

Turning now to FIG. 29, illustrated is a waveform diagram demonstrating the sidelobes associated with the correlation subsystem in accordance with the principles of the present invention. Understanding the nature of the sidelobes and using their characteristics within a predetecting function can enhance the correlation subsystem of the interrogator. As illustrated, the correlation includes a major peak 2910 (referred to as “prompt”) and two smaller peaks (generally referred to as “early” 2915 and “late” 2920) about the major peak. By averaging the noise in the early and late regions and comparing those values to noise levels recorded when it was known that no signal was present, additional confirmation is obtained that, in fact, an RFID tag is responding even if the RFID tag is not uniquely identifiable in a single response at the present signal levels. Then, by averaging multiple responses that correspond to RFID tag responses, the SNR will be raised to a level wherein substantially unambiguous detection occurs.

In this instance, the reply code of an RFID tag is not being detected, but the interrogator is detecting a change in ambient noise that substantially increases the probability that an RFID tag is indeed present. For example, sampling in all three regions and having the noise level be the same is a good indication that an RFID tag is not present and therefore

that the sample should be discarded. However, sampling in all three areas and finding that the early and late levels are about equal and the middle level is larger is a good indication that a response from an RFID tag is in fact present and that this sample should be added into the averaging function. Clearly discarding samples that do not pass the early/late noise test will certainly discard data of actual RFID tags. That is a small price to pay, however, for not unduly corrupting the average with samples that do not in fact contain a reply code from an RFID tag. Sampling for slightly longer times compensates for the reduction in samples used. The control and processing subsystem can maintain a running total of how many samples were discarded so that the number of samples averaged will remain valid.

Regarding the timing of the responses from the RFID tag, a tracking of the reply codes may suggest that the reply code is early, prompt or late. If the tracking suggests that the reply code is prompt (prompt output greater than early and late output), then a gating function is properly aligned to provide a significant correlator output. If the tracking suggests that the reply code is early, then the early correlator output is significant as compared to the late correlator output and the correlation subsystem is tracking too early and the requisite adjustment may be performed. An opposite adjustment may be performed if the tracking suggests that the reply code is late.

Another approach is to use a tracking loop that uses past successful detection performance to establish a gating process for subsequent correlations. In yet another embodiment relating to the correlation of the reply codes from the RFID tags is to perform FFTs on both the reference code and a gated sample of the reply codes from the RFID tags. Then, a convolution operation in “Fourier Space” may be performed employing the convolution theorem. The convolution theorem states that the convolution of two functions is the product of the Fourier transforms thereof. An output of the correlation operation is typically envelope detected and several outputs may be averaged in a summing operation that preserves time characteristics of each individual detection.

Turning now to FIG. 30, illustrated is a block diagram of an embodiment of a predetecting function operable with a correlation subsystem associated with a control and processing subsystem of an interrogator constructed according to the principles of the present invention. As mentioned above, multiple correlators in conjunction with the correlation subsystem within an interrogator may be employed to advantage. The multiple correlators can be used to detect multiple RFID tags simultaneously and, in that instance, the multiple correlators typically operate independently. Alternatively, multiple correlators can be assigned to find a single RFID tag wherein each correlator can be given a slightly different area of time or phase space to search. This is especially useful when timing of the response from the RFID tag to a transmit query is not known. Of course, the correlators may be realized in software and/or hardware.

Incoming data is collected as a block of complex I and Q values 3010 followed by removing the DC terms 3015. These values are correlated 3025 against a reference code 3020 using the convolution theorem. Subsequent to correlation, a square law envelope detection function 3030 obtains amplitude information. An alignment and predetection function 3035 follows whose output is then input to the corner turning memory function 3040 followed by the summer 3045 and then a threshold and detection function 3050, of which were discussed above.



It is further within the broad scope of the present invention to employ multiple antennas in accordance with the interrogator and wherein the multiple antennas are employed for diversity and different correlators may be assigned to specific antennas. Under such circumstances, post correlation and/or post averaging results may be combined to provide added detection sensitivity. To perform the aforementioned functions, the interrogator may include multiple RFID sensing subsystems, each with a separate orthogonal input from an antenna(s).

Turning now to FIGS. 31 to 34, illustrated are waveform diagrams demonstrating exemplary performances of an interrogator according to the principles of the present invention. More specifically, FIG. 31 illustrates a correlator response with no averaging for an RFID tag at about 29 feet. It is to be noted that a conventional reader would not typically detect the RFID tag at this distance. These conditions are considered to be docile signal conditions as the SNR is quite large even considering the RFID tag is 29 feet from the interrogator. FIG. 32 illustrates the same conditions as above with the addition of employing a correlation operation with multiple correlations averaged together. Note that the effective noise has been reduced. With respect to FIG. 33, the effect of adding approximately 14 dB of noise to the data and without averaging is demonstrated. The signal is obscured. FIG. 34 shows the results of applying averaging to the previously described conditions for the interrogator. Note that the distinct correlation signature has been restored indicating that even under these extreme conditions, the RFID tag is detected with high reliability.

Exemplary embodiments of the present invention have been illustrated with reference to specific electronic components. Those skilled in the art are aware, however, that components may be substituted (not necessarily with components of the same type) to create desired conditions or accomplish desired results. For instance, multiple components may be substituted for a single component and vice-versa. The principles of the present invention may be applied to a wide variety of applications to identify and detect RFID objects. For instance, in a medical environment, instrument kits including a plurality of RFID objects can be scanned in situ to log the contents thereof into an interrogator and subsequently the instrument kit can be scanned by the interrogator to verify the contents, the integrity of the contents (including expiration dates for time sensitive objects) and the like. The increased sensitivity of the interrogator according to the principles of the present invention opens up many new opportunities (e.g., supply chain management in consumer related retail applications, security applications, etc.) for the interrogation system disclosed herein.

For a better understanding of communication theory and radio frequency identification communication systems, see the following references "RFID Handbook," by Klaus Finkenzeller, published by John Wiley & Sons, Ltd., 2<sup>nd</sup> edition (2003), "Technical Report 860 MHz-930 MHz Class I Radio Frequency Identification Tag Radio Frequency & Logical Communication Interface Specification Candidate Recommendation," Version 1.0.1, November 2002, promulgated by the Auto-ID Center, Massachusetts Institute of Technology, 77 Massachusetts Avenue, Bldg 3-449, Cambridge Mass. 02139-4307, "Introduction to Spread Spectrum Communications," by Roger L. Peterson, et al., Prentice Hall Inc. (1995), "Modern Communications and Spread Spectrum," by George R. Cooper, et al., McGraw-Hill Book Inc. (1986), "An Introduction to Statistical Communication Theory," by John B. Thomas, published by John Wiley &

Sons, Ltd. (1995), "Wireless Communications, Principles and Practice," by Theodore S. Rappaport, published by Prentice Hall Inc. (1996), "The Comprehensive Guide to Wireless Technologies," by Lawrence Harte, et al, published by APDQ Publishing (1998), "Introduction to Wireless Local Loop," by William Webb, published by Artech Home Publishers (1998) and "The Mobile Communications Handbook," by Jerry D. Gibson, published by CRC Press in cooperation with IEEE Press (1996). For a better understanding of conventional readers, see the following readers, namely, a "MP9320 UHF Long-Range Reader" provided by SAMS<sup>™</sup> Technologies, Inc. of Ontario, Canada, a "MR-1824 Sentinel-Prox Medium Range Reader" by Applied Wireless ID of Monsey, N.Y. (see also U.S. Pat. No. 5,594,384 entitled "Enhanced Peak Detector," U.S. Pat. No. 6,377,176 entitled "Metal Compensated Radio Frequency Identification Reader," and U.S. Pat. No. 6,307,517 entitled "Metal Compensated Radio Frequency Identification Reader"), a "2100 UAP Reader," provided by Intermec Technologies Corporation of Everett, Washington and a "ALR-9780 Reader," provided by Alien Technology Corporation of Morgan Hill, Calif. The aforementioned references, and all references herein, are incorporated herein by reference in their entirety.

Also, although the present invention and its advantages have been described in detail, it should be understood that various changes, substitutions and alterations can be made herein without departing from the spirit and scope of the invention as defined by the appended claims. For example, many of the processes discussed above can be implemented in different methodologies and replaced by other processes, or a combination thereof, to form the devices providing reduced on-resistance, gate drive energy, and costs as described herein.

Moreover, the scope of the present application is not intended to be limited to the particular embodiments of the process, machine, manufacture, composition of matter, means, methods and steps described in the specification. As one of ordinary skill in the art will readily appreciate from the disclosure of the present invention, processes, machines, manufacture, compositions of matter, means, methods, or steps, presently existing or later to be developed, that perform substantially the same function or achieve substantially the same result as the corresponding embodiments described herein may be utilized according to the present invention. Accordingly, the appended claims are intended to include within their scope such processes, machines, manufacture, compositions of matter, means, methods, or steps.

What is claimed is:

1. An interrogator loaded with a reference code including a tag identification code from a radio frequency identification (RFID) tag associated with an RFID object and comprising a processor configured to:

- produce an excitation signal for said RFID tag;
- receive a reply code including at least a portion of said tag identification code from said RFID tag in response to said excitation signal;
- compare said reference code to said reply code to verify a presence of said RFID tag;
- produce another excitation signal for said RFID tag if said presence of said RFID cannot initially be verified;
- receive said reply code including said at least a portion of said tag identification code from said RFID tag in response to said another excitation signal;
- compare said reference code to said reply code to verify said presence of said RFID tag; and



45

provide an alert upon verifying said presence of said RFID tag.

2. The interrogator as recited in claim 1 wherein said interrogator is loaded with another reference code including another tag identification code from another radio frequency identification (RFID) tag associated with another RFID object and said processor is configured to:

receive another reply code including at least a portion of said another tag identification code from said another RFID tag in response to said excitation signal; and  
compare said another reference code to said another reply code to verify said presence of said another RFID tag.

3. The interrogator as recited in claim 2 wherein said processor is configured to provide another alert upon verifying said presence of said another RFID tag.

4. The interrogator as recited in claim 1 wherein said processor employs multiscan coherent signal processing to verify said presence of said RFID tag.

5. The interrogator as recited in claim 1 wherein said processor is configured to receive said reference code from a database.

6. The interrogator as recited in claim 1 wherein said tag identification code includes information about said RFID object.

7. The interrogator as recited in claim 1 wherein said reply code further comprises a preamble and cyclic redundancy data.

8. The interrogator as recited in claim 1 wherein said reference code matches said reply code.

9. The interrogator as recited in claim 1 further comprising a keyboard or a data port configured to provide an interface to enter said reference code.

10. The interrogator as recited in claim 1 wherein said processor is configured to control an energy of and/or an interrogation period for said excitation signal for said RFID tag.

11. The interrogator as recited in claim 1 wherein said processor is configured to provide a command to control receiving said reply code from said RFID tag.

12. The interrogator as recited in claim 11 wherein said command is configured to cause said RFID tag to be quiet.

13. The interrogator as recited in claim 1 wherein said interrogator is a portable interrogator.

46

14. A method of operating an interrogator loaded with a reference code including a tag identification code from a radio frequency identification (RFID) tag associated with an RFID object, comprising:

producing an excitation signal for said RFID tag;  
receiving a reply code including at least a portion of said tag identification code from said RFID tag in response to said excitation signal;  
comparing said reference code to said reply code from said RFID tag to verify a presence of said RFID tag;  
producing another excitation signal for said RFID tag if said presence of said RFID cannot initially be verified;  
receiving said reply code including said at least a portion of said tag identification code from said RFID tag in response to said another excitation signal;  
comparing said reference code to said reply code to verify said presence of said RFID tag; and  
providing an alert upon verifying said presence of said RFID tag.

15. The method as recited in claim 14 wherein said interrogator is loaded with another reference code including another tag identification code from another radio frequency identification (RFID) tag associated with another RFID object, further comprising:

receiving another reply code including at least a portion of said another tag identification code from said another RFID tag in response to said excitation signal; and  
comparing said another reference code to said another reply code to verify said presence of said another RFID tag.

16. The method as recited in claim 15 further comprising providing another alert upon verifying said presence of said another RFID tag.

17. The method as recited in claim 14 wherein said interrogator employs multiscan coherent signal processing to verify said presence of said RFID tag.

18. The method as recited in claim 14 further comprising controlling an energy of and/or an interrogation period for said excitation signal for said RFID tag.

19. The method as recited in claim 14 further comprising providing a command to control receiving said reply code from said RFID tag.

20. The method as recited in claim 19 wherein said command causes said RFID tag to be quiet.

\* \* \* \* \*