



US011208047B1

(12) **United States Patent**
Villacrés Mesías et al.

(10) **Patent No.:** **US 11,208,047 B1**
(45) **Date of Patent:** **Dec. 28, 2021**

(54) **STORAGE ASSEMBLY FOR A VEHICLE**

(56) **References Cited**

(71) Applicant: **Ford Global Technologies, LLC**,
Dearborn, MI (US)
(72) Inventors: **Diego Fabricio Villacrés Mesías**,
Cuajimalpa (MX); **Jose Nicolas Juarez**
Espinoza, Cuajimalpa de Morelos
(MX); **Humberto Memetla Martínez**,
Portales Sur (MX)

U.S. PATENT DOCUMENTS

5,590,824 A	1/1997	Weeks	
6,050,202 A *	4/2000	Thompson B60N 3/001 108/144.11
6,733,060 B1	5/2004	Pavkov et al.	
7,401,716 B2 *	7/2008	Svenson B60R 5/045 224/42.32
10,787,128 B2 *	9/2020	Ngo B60R 5/044

(73) Assignee: **Ford Global Technologies, LLC**,
Dearborn, MI (US)

FOREIGN PATENT DOCUMENTS

CN	105818753 A	8/2016
JP	5115694 B2	1/2013

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

* cited by examiner

Primary Examiner — Joseph D. Pape

(74) *Attorney, Agent, or Firm* — David Coppiellie; Price Heneveld LLP

(21) Appl. No.: **17/060,382**

(22) Filed: **Oct. 1, 2020**

(51) **Int. Cl.**
B60R 5/04 (2006.01)


(52) **U.S. Cl.**
CPC **B60R 5/044** (2013.01)

(58) **Field of Classification Search**
CPC B60R 5/044; B60R 5/045
USPC 296/24.4, 37.1, 24.44
See application file for complete search history.

(57) **ABSTRACT**

A damper for a vehicle cargo panel includes an adaptor body that has an attachment surface and an engagement surface. A plurality of flexures outwardly extend from the engagement surface of the adaptor body and has a planar extension that is coupled to the engagement surface and a curved end. The plurality of flexures is operable between an extended condition and a compressed condition. A coupling member is disposed on the adaptor body and is configured to couple the adaptor body to said vehicle cargo panel.

20 Claims, 11 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14

1**STORAGE ASSEMBLY FOR A VEHICLE**

FIELD OF THE DISCLOSURE

The present disclosure generally relates to a storage assembly for a vehicle. More specifically, the present disclosure generally relates to a damper for a storage assembly for a vehicle.

BACKGROUND OF THE DISCLOSURE

Vehicles often have trunk dividers for separating or partitioning a storage area, for example when a panel that lays flat within the trunk. The panel is typically formed from a rigid material that may engage a second rigid material to secure the panel in a selected position.

SUMMARY OF THE DISCLOSURE

According to a first aspect of the present disclosure, a storage assembly for a vehicle includes a rigid retention structure. A cargo panel is operably coupled to and selectively engages the rigid retention structure. The cargo panel has a body that defines at least one aperture on at least one side of the body. At least one damper has an adaptor strip that is disposed within the at least one aperture of the body and a plurality of flexures outwardly extends from the adaptor strip and is operable between a compressed condition and an extended condition. The plurality of flexures are configured to engage the rigid retention structure in the compressed condition.

Embodiments of the first aspect of the disclosure can include any one or a combination of the following features:

each of the plurality of flexures includes a planar extension and a curved end, wherein each of the plurality of flexures is coupled to the adaptor strip via the planar extension;

a return angle is defined between each flexure of the plurality of flexures and the rigid retention structure;

the return angle is approximately 45-degrees;

an approach angle is defined between each flexure of the plurality of flexures and the adaptor strip;

the approach angle is approximately 45-degrees;

the at least one damper has a height of approximately 15-millimeters, wherein each of the plurality of flexures has a thickness of 3.5-millimeters.

According to a second aspect of the present disclosure, a damper for a vehicle cargo panel includes an adaptor body that has an attachment surface and an engagement surface. A plurality of flexures outwardly extend from the engagement surface of the adaptor body and has a planar extension that is coupled to the engagement surface and a curved end. The plurality of flexures is operable between an extended condition and a compressed condition. A coupling member is disposed on the adaptor body and is configured to couple the adaptor body to said vehicle cargo panel.

Embodiments of the second aspect of the disclosure can include any one or a combination of the following features:

each of the plurality of flexures defines a thickness of approximately 2-millimeters;

the adaptor body and the plurality of flexures define a height of said damper of approximately 8.5-millimeters;

each flexure of the plurality of flexures defines an approach angle between the planar extension and the engagement surface of the adaptor body;

2

each flexure of the plurality of flexures has a return angle at least partially defined by the curved end of each flexure;

the return angle is approximately 30-degrees;

each flexure of the plurality of flexures has a thickness of approximately 2-millimeters.

According to a third aspect of the present disclosure, a cargo panel assembly for a vehicle includes a body defining at least one aperture on at least one side of the body. A damper has an adaptor strip that is disposed within the at least one aperture of the body and a plurality of flexures outwardly extend from the adaptor strip and are operable between a compressed condition and an extended condition. The plurality of flexures are configured to engage a rigid surface of said vehicle in the compressed condition.

Embodiments of the third aspect of the disclosure can include any one or a combination of the following features:

each flexure of the plurality of flexures includes a planar extension and a curved end;

each flexure of the plurality of flexures defines an approach angle between the planar extension and the adaptor strip;

the approach angle of the plurality of flexures is smaller in the compressed condition than the approach angle of the plurality of flexures in the extended condition;

each flexure of the plurality of flexures defines a return angle between the curved end of each flexure and the rigid surface of said vehicle;

the return angle is defined between the compressed condition and the extended condition of the plurality of flexures.

These and other aspects, objects, and features of the present invention will be understood and appreciated by those skilled in the art upon studying the following specification, claims, and appended drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings:

FIG. 1 is a rear perspective view of a cargo space of a vehicle of the present disclosure;

FIG. 2 is a partial enlarged side perspective view of a rigid retention structure of the present disclosure;

FIG. 3 is a top perspective view of a storage assembly of the present disclosure with a cargo panel and a storage feature;

FIG. 4 is a bottom plan view of a cargo panel of the present disclosure having a movable portion and a stationary portion;

FIG. 5 is a bottom plan view of a cargo panel of the present disclosure;

FIG. 6 is a bottom perspective view of a damper of the present disclosure;

FIG. 7 is a top perspective view of the damper of FIG. 6;

FIG. 8 is a side elevational view of a first damper, a second damper, and a third damper of the present disclosure;

FIG. 9 is a partial side elevational view of a plurality of flexures of a first damper of the present disclosure;

FIG. 10 is a partial side elevational view of a plurality of flexures of a second damper of the present disclosure;

FIG. 11 is a partial side elevational view of a plurality of flexures of a third damper of the present disclosure;

FIG. 12 is a partial rear perspective view of a cargo space of the present disclosure with a cargo panel in a partially raised position;

FIG. 13 is a partial bottom perspective view of a cargo panel of the present disclosure in a horizontal orientation; and

FIG. 14 is a side elevational view of a damper of the present disclosure in an extended condition and a compressed condition.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Additional features and advantages of the presently disclosed device will be set forth in the detailed description which follows and will be apparent to those skilled in the art from the description, or recognized by practicing the device as described in the following description, together with the claims and appended drawings.

For purposes of description herein, the terms “upper,” “lower,” “right,” “left,” “rear,” “front,” “vertical,” “horizontal,” and derivatives thereof shall relate to the disclosure as oriented in FIG. 1. However, it is to be understood that the disclosure may assume various alternative orientations and step sequences, except where expressly specified to the contrary. It is also to be understood that the specific devices and processes illustrated in the attached drawings, and described in the following specification are simply exemplary embodiments of the inventive concepts defined in the appended claims. Hence, specific dimensions and other physical characteristics relating to the embodiments disclosed herein are not to be considered as limiting, unless the claims expressly state otherwise.

As used herein, the term “and/or,” when used in a list of two or more items, means that any one of the listed items can be employed by itself, or any combination of two or more of the listed items, can be employed. For example, if a composition is described as containing components A, B, and/or C, the composition can contain A alone; B alone; C alone; A and B in combination; A and C in combination; B and C in combination; or A, B, and C in combination.

As used herein, the term “about” means that amounts, sizes, formulations, parameters, and other quantities and characteristics are not and need not be exact, but may be approximate and/or larger or smaller, as desired, reflecting tolerances, conversion factors, rounding off, measurement error and the like, and other factors known to those of skill in the art. When the term “about” is used in describing a value or an end-point of a range, the disclosure should be understood to include the specific value or end-point referred to. Whether or not a numerical value or end-point of a range in the specification recites “about,” the numerical value or end-point of a range is intended to include two embodiments: one modified by “about,” and one not modified by “about.” It will be further understood that the end-points of each of the ranges are significant both in relation to the other end-point, and independently of the other end-point.

The terms “substantial,” “substantially,” and variations thereof as used herein are intended to note that a described feature is equal or approximately equal to a value or description. For example, a “substantially planar” surface is intended to denote a surface that is planar or approximately planar. Moreover, “substantially” is intended to denote that two values are equal or approximately equal. In some embodiments, “substantially” may denote values within about 10% of each other, such as within about 5% of each other, or within about 2% of each other.

As used herein the terms “the,” “a,” or “an,” mean “at least one,” and should not be limited to “only one” unless

explicitly indicated to the contrary. Thus, for example, reference to “a component” includes embodiments having two or more such components unless the context clearly indicates otherwise.

In this document, relational terms, such as first and second, top and bottom, and the like, are used solely to distinguish one entity or action from another entity or action, without necessarily requiring or implying any actual such relationship or order between such entities or actions. The terms “comprises,” “comprising,” or any other variation thereof, are intended to cover a non-exclusive inclusion, such that a process, method, article, or apparatus that comprises a list of elements does not include only those elements but may include other elements not expressly listed or inherent to such process, method, article, or apparatus. An element preceded by “comprises . . . a” does not, without more constraints, preclude the existence of additional identical elements in the process, method, article, or apparatus that comprises the element.

Referring to FIGS. 1-14, reference number 10 generally refers to a storage assembly for a vehicle 12 that includes a rigid retention structure 14 and a cargo panel 16 operably coupled to and selectively engaging the rigid retention structure 14. The cargo panel 16 has a body 18 that defines at least one aperture 20 on at least one surface 22 of the body 18. At least one damper 24 has an adaptor strip 26 disposed within the at least one aperture 20 of the body 18. The at least one damper 24 also has a plurality of flexures 28 outwardly extending from the adaptor strip 26 and operable between a compressed condition 30 and an extended condition 32. The plurality of flexures 28 are configured to engage the rigid retention structure 14 in the compressed condition 30.

Referring to FIGS. 1-3, the vehicle 12 includes a vehicle body 40, which defines an interior 42 of the vehicle 12. A cargo space 44 is further defined within the interior 42 of the vehicle 12, such that the cargo space 44 is defined toward a rear portion 46 of the vehicle 12. Stated differently, the cargo space 44 may be referred to as the trunk space of the vehicle 12. The interior 42 of the vehicle 12 may include a first seating row 48 and a second seating row 50. Fewer or more seating rows may be included in the vehicle 12 without departing from the teachings herein. It is generally contemplated that the cargo space 44 may be at least partially defined by a rear seating row 52, illustrated herein as the second seating row 50, and a rear door 54 of the vehicle 12.

In various examples, the vehicle 12 is a wheeled motor vehicle 12, which may be a sedan, a sport utility vehicle, a truck, a van, a crossover, and/or other styles of vehicle. The vehicle 12 may be a manually operated vehicle (e.g., with a human driver), a fully autonomous vehicle (e.g., no human driver), or a partially autonomous vehicle (e.g., may be operated with or without a human driver). Additionally, the vehicle 12 may be utilized for personal and/or commercial purposes, such as ride-providing services (e.g., chauffeur-ing) and/or ride-sharing services.

With further reference to FIGS. 1-3, the rigid retention structure 14 is defined by sidewalls 60 that also at least partially define the cargo space 44. The rigid retention structure 14 includes ledges 62 outwardly extending from the sidewalls 60 of the vehicle body 40 within the cargo space 44. The ledges 62 may be disposed proximate to a floor surface 64 of the cargo space 44. Additionally or alternatively, the ledges 62 may be disposed proximate to a window 66 or in any location along the sidewalls 60 to provide various height options for the cargo panel 16 within the cargo space 44. The rigid retention structure 14 may also

5

define notches 68 in which the cargo panel 16 may be disposed. It is generally contemplated that the cargo panel 16 is configured to engage the ledges 62 and/or the notches 68 of the rigid retention structure 14 when the cargo panel 16 is in a storage position 70, described in further detail below.

Referring to FIGS. 1-4 and as mentioned above, the body 18 of the cargo panel 16 has at least one surface 22 that defines the at least one aperture 20. It is generally contemplated that the cargo panel 16 of the storage assembly 10 may be referred to as a cargo panel assembly in that the cargo panel 16 includes the at least one damper 24, described further below. The at least one surface 22 of the cargo panel 16 includes a first surface 80 and a second surface 82. The cargo panel 16 also has a first side portion 84 and a second side portion 86 as well as a front portion 88, which may define a handle 90. It is generally contemplated that the first surface 80 may be referred to as a support surface, and the second surface 82 may be referred to as a bracing surface. The support surface 80 is configured to receive items such as boxes, luggage, bags, and other user items. However, the bracing surface 82 may also engage with the user items.

The cargo panel 16 may be positioned horizontally or vertically within the cargo space 44, such that when the cargo panel 16 is in a horizontal orientation 92 the cargo panel 16 is disposed on the ledges 62 of the rigid retention structure 14. Additionally or alternatively, the cargo panel 16 may engage the rigid retention structure 14 within the notches 68 in a vertical orientation 94 of the cargo panel 16. Further, the user items may engage the bracing surface 82 or the support surface 80 of the cargo panel 16 in the vertical orientation 94.

The support surface 80 may include a material that may cushion or otherwise buffer the engagement between the user items and the support surface 80. By way of example, not limitation, the support surface 80 may include a fabric layer, which may be formed from a soft material such as felt. It is also contemplated that the support surface 80 may be formed from a hard plastic or other polymeric material, such that the user may place user items on the support surface 80 that may be wet or otherwise be better suited to be positioned on a surface that may be wiped clean. The bracing surface 82 may be formed from the same material as the support surface 80, however, it is generally contemplated that the bracing surface 82 is formed from a rigid polymeric material, such as plastic. It is generally contemplated that the cargo panel 16 may be reversible, such that the first surface 80 may be the bracing surface and the second surface 82 may be the support surface.

With further reference to FIGS. 3-5, the at least one aperture 20 is generally defined on the bracing surface 82. By way of example, not limitation, the at least one aperture 20 may include a first aperture 96 and a second aperture 98. The first aperture 96 may be defined on the first side portion 84 of the cargo panel 16, and the second aperture 98 may be defined on the second side portion 86 of the cargo panel 16. Additionally or alternatively, each of the first and second side portions 84, 86 may define both a first aperture 96 and a second aperture 98, such that the second aperture 98 may be proximate to the first aperture 96. As will be described in further detail below, the at least one damper 24 may be disposed within at least one of the first and second apertures 96, 98 defined by the body 18 of the cargo panel 16, regardless of orientation or placement of the first and second apertures 96, 98.

The body 18 of the cargo panel 16 may also include retention bars 100 along either of the first or second surfaces

6

80, 82. The retention bars 100 may also be disposed in an opening 102 defined in the body 18 of the cargo panel 16, such that a storage feature 104 may be selectively coupled to the retention bars 100 on either the first surface 80 or the second surface 82. The retention bars 100 are configured to retain the storage feature 104 along the cargo panel 16, such that the storage feature 104 may be operably and selectively coupled to the retention bars 100. By way of example, not limitation, the storage feature 104 may be a net that includes attachment features 106, such as hooks, that may couple to the retention bars 100 to couple the storage feature 104 to the cargo panel 16.

With further reference to FIGS. 3-5, it is generally contemplated that the cargo panel 16 may include hinges 108 that operably couple a movable section 110 of the cargo panel 16 to a stationary section 112 of the cargo panel 16. The movable section 110 is defined by the front portion 88 of the cargo panel 16 and may define the handle 90 that a user can grasp to articulate the movable section 110 about the hinges 108. The user may utilize the handle 90 to articulate the movable section 110, such that the movable section 110 may be raised and lowered when the cargo panel 16 is in the horizontal orientation 92.

It is also contemplated that the cargo panel 16 may be a single panel that conceals the floor surface 64 of the cargo space 44. Additionally or alternatively, the cargo panel 16 may partially conceal the floor surface 64, such that the user may access the floor surface 64 with the cargo panel 16 in the storage position 70. Accordingly, the cargo panel 16 may be positioned horizontally within the cargo space 44, such that the cargo panel 16 engages the ledges 62. As mentioned above, the cargo panel 16 may be positioned in the vertical orientation 94 within the cargo space 44, such that the cargo panel 16 engages the notches 68. The at least one damper 24 coupled to the cargo panel 16 is configured to buffer the engagement of the cargo panel 16 and the ledges 62 or the notches 68 of the rigid retention structure 14, as described in further detail below.

With further reference to FIGS. 4-7, the body 18 of the cargo panel 16 defines at least one aperture 20 on at least one surface 22 of the body 18, which may include the first aperture 96 and the second aperture 98 mentioned above. The at least one aperture 20 may also include a plurality of apertures 116 disposed along either the first surface 80 and/or the second surface 82, such that a plurality of dampers 118 may be disposed in the plurality of apertures 116, as illustrated in FIG. 4. By way of example, not limitation, the first and second apertures 96, 98 will be described herein and will be described as each being disposed on the first and second side portions 84, 86 as well as the front portion 88 of the cargo panel 16. It is generally contemplated that the at least one damper 24 may be disposed in each of the first and second apertures 96, 98.

Referring to FIGS. 6-8, the damper 24 includes the adaptor strip 26 and the plurality of flexures 28. The adaptor strip 26 may also be referred to as an adaptor body, such that the adaptor body 26 has an attachment surface 120 and an engagement surface 122. The attachment surface 120 may include a coupling member 124 formed from a fastening material, such as an adhesive, that couples the damper 24 within the respective aperture 20 to the cargo panel 16. While it is generally contemplated that the coupling member 124 may be an adhesive, it is also contemplated that other fastening or coupling materials, such as hook and loop fasteners, may be used to couple the damper 24 to the cargo panel 16. It is generally contemplated that the plurality of flexures 28 are coupled to the adaptor strip 26. The plurality

of flexures **28** may be integrally formed with the adaptor strip **26** or may be separately coupled to the adaptor strip **26**. A space **126** is defined between each of the flexures **28** and the engagement surface **122** of the adaptor strip **26**, such that the flexures **28** may at least partially extend into the space **126** in the compressed condition **30**, described further below. Each flexure **28** includes a varying height and thickness depending on the level of compression desired for the damper **24** and/or the location and position of the damper **24**.

Additionally, each flexure **28** includes a planar extension **128** and a curved end **130**. The planar extension **128** is coupled to the engagement surface **122** of the adaptor strip **26**, such that the planar extensions **128** of each flexure **28** defines the space **126**, mentioned above. The curved end **130** selectively engages the rigid retention structure **14** on a contact surface **132** of the curved end **130**. The contact surface **132** is the portion of the flexure **28** that contacts the rigid retention structure **14**. The contact surface **132** may be increased or decreased depending on an anticipated load **L** that may be placed on the cargo panel **16**.

The plurality of flexures **28** also have an approach angle α and a return angle β . The approach angle α may be defined as the angle taken between the planar extension **128** of the flexure **28** and the engagement surface **122** of the adaptor strip **26**. As the flexure **28** is compressed toward the engagement surface **122** the approach angle α may get smaller, described further below. Additionally or alternatively, the approach angle α may be defined between the compressed condition **30** and the extended position **32** of the flexures **28**. The return angle β may be defined as the angle taken between the curved end **130** of the flexure **28** and the rigid retention structure **14**. The return angle β defines the longitudinal displacement of the flexures **28** relative to the rigid retention structure **14** between the compressed condition **30** and the extended position **32**.

With further reference to FIGS. **8-11**, the damper **24** may be configured as at least one of a first damper **134**, a second damper **136**, and a third damper **138**. Each of the first, second, and third dampers **134**, **136**, **138** include the adaptor strip **26** and the plurality of flexures **28**. It is generally contemplated that the first damper **134** may be more flexible than the second or third dampers **136**, **138**. However, each of the dampers **134**, **136**, **138** may be adjusted to various flexibilities. Any one or all of the dampers **134**, **136**, **138** may be coupled to the cargo panel **16**, such that the various flexibilities of each may be utilized for different regions of the cargo panel **16**, described further below.

As illustrated in FIG. **9**, each flexure **28** of the first damper **134** has a height H_1 and a thickness T_1 . By way of example, not limitation, the height H_1 of the flexures **28** of the first damper **134** may range between ten (10) millimeters and fifteen (15) millimeters. It is also contemplated that the height H_1 may be less than ten (10) millimeters or greater than fifteen (15) millimeters. As a further example, not limitation, the thickness T_1 of the flexures **28** of the first damper **134** may range between one (1) millimeter and four (4) millimeters. However, it is also contemplated that the thickness T_1 may be less than one (1) millimeter or greater than four (4) millimeters.

The flexures **28** of the first damper **134** may have an approach angle α_1 ranging between 30-degrees and 45-degrees. However, it is also contemplated that the approach angle α_1 may be less than 30-degrees or greater than 45-degrees. Additionally, the flexures **28** of the first damper **134** may have a return angle β_1 ranging between 30-degrees and 60-degrees. For example, the return angle β_1 may be 45-degrees. The return angle β_1 may also be less than

30-degrees or greater than 60-degrees depending on the structure of the flexures **28**. The approach angle α_1 and the return angle β_1 are dependent on the thickness T_1 and the height H_1 of the flexures **28**. For example, the greater the height H_1 of the flexures **28** the more flexible the flexures **28** will be. Additionally, the thinner the thickness T_1 of the flexures **28** translates to the flexures **28** being more flexible overall.

In an alternative configuration illustrated in FIG. **10**, the second damper **136** may include flexures **28** having a height H_2 ranging between seven (7) millimeters and ten (10) millimeters. It is also contemplated that the height H_2 of the flexures **28** may be less than seven (7) millimeters or greater than ten (10) millimeters. By way of example, not limitation, the height H_2 may be eight and a half (8.5) millimeters. The flexures **28** of the second damper **136** may also have a thickness T_2 ranging between one (1) millimeter and three (3) millimeters. For example, the thickness T_2 may be two (2) millimeters. However, it is also contemplated that the thickness T_2 may be less than one (1) millimeter or greater than three (3) millimeters. Additionally, the flexures **28** of the second damper **136** may have an approach angle α_2 that may range between 30-degrees to 45-degrees, and a return angle β_2 of the flexures **28** may range between 30-degrees to 60-degrees. For example, the return angle β_2 may be 30-degrees. The approach angle α_2 may also be less than 30-degrees or greater than 45-degrees, and the return angle β_2 may also be less than 30-degrees or greater than 60-degrees.

In a further alternate configuration illustrated in FIG. **11**, the plurality of flexures **28** of the third damper **138** may have a height H_3 ranging between five (5) millimeters to seven (7) millimeters. It is also contemplated that the height H_3 the flexures **28** may be less than five (5) millimeters or greater than seven (7) millimeters. Further, each flexure may have a thickness T_3 ranging from one (1) millimeter to two (2) millimeters. Additionally, the flexures **28** of the third damper **138** may have an approach angle α_3 that may range between 30-degrees and 45-degrees, and a return angle β_3 that may range between 20-degrees and 45-degrees. However, the approach angle α_3 may be less than 30-degrees or greater than 45-degrees, and the return angle β_3 may be less than 20-degrees or greater than 45-degrees. The approach angle α_3 and the return angle β_3 are dependent on the thickness T_3 and the height H_3 of the flexures **28**. For example, the smaller the height H_3 of the flexures **28** the less flexible the flexures **28** will be. Additionally, the thicker the thickness T_3 of the flexures **28** translates to the flexures **28** being less flexible overall.

Referring to FIGS. **12-14**, the flexures **28** compress towards the engagement surface **122** of the adaptor strip **26** as the load **L** is placed on the support surface **80** of the cargo panel **16** when the cargo panel **16** is in the horizontal orientation **92**. In the horizontal orientation **92**, the cargo panel **16** may rest on the rigid retention structure **14**, such that the flexures **28** are in the extended condition **32**. The flexures **28** may translate into the compressed condition **30** upon placement of the load **L** on the cargo panel **16**, such as luggage, boxes, and other user items. It is also contemplated that the general movement of the vehicle **12** (FIG. **1**) may also result in the compression and extension of the flexures **28** relative to the engagement surface **122** of the adaptor strip **26** and the rigid retention structure **14**. For example, the flexures **28** may translate between the extended condition **32** and the compressed condition **30** when the cargo panel **16** is positioned in the vertical orientation **94** relative to the floor surface **64** of the cargo space **44**. In such configuration, the flexures **28** may engage the rigid retention structure **14** as the

flexures **28** translate between the extended condition **32** and the compressed condition **30**. As mentioned above, the compression and extension of the flexures **28** may be defined by the general movement of the vehicle **12** (FIG. 1), such that the cargo panel **16** may move in a forward direction and a rearward direction relative to the vehicle **12** (FIG. 1) engaging the flexures **28** against the rigid retention structure **14**.

Referring again to FIGS. 1-14, the storage assembly **10** described herein minimizes the overall noise generation of the cargo panel **16** within the cargo space **44**. The damper **24** minimizes potential rattling or other noise that may occur as a result of the engagement between the cargo panel **16** and the rigid retention structure **14**. Specifically, the plurality of flexures **28** minimize such rattling by the respective approach angle α and the respective return angle β in addition to the height and thickness of each of the flexures **28**, described above. The overall flexibility of the flexures **28** results in a smooth movement of the cargo panel **16** relative to the rigid retention structure **14** as the flexures **28** translate between the compressed condition **30** and the extended condition **32**. As mentioned above, the damper **24** may absorb the weight of the load L placed upon or engaging with the cargo panel **16**. Additionally or alternatively, the damper **24** minimizes the noise of the cargo panel **16** engaging the rigid retention structure **14** as the cargo panel **16** may translate relative to the movement of the vehicle **12**.

For purposes of this disclosure, the term “coupled” (in all of its forms, couple, coupling, coupled, etc.) generally means the joining of two components (electrical or mechanical) directly or indirectly to one another. Such joining may be stationary in nature or movable in nature. Such joining may be achieved with the two components (electrical or mechanical) and any additional intermediate members being integrally formed as a single unitary body with one another or with the two components. Such joining may be permanent in nature or may be removable or releasable in nature unless otherwise stated.

Furthermore, any arrangement of components to achieve the same functionality is effectively “associated” such that the desired functionality is achieved. Hence, any two components herein combined to achieve a particular functionality can be seen as “associated with” each other such that the desired functionality is achieved, irrespective of architectures or intermedial components. Likewise, any two components so associated can also be viewed as being “operably connected” or “operably coupled” to each other to achieve the desired functionality, and any two components capable of being so associated can also be viewed as being “operably couplable” to each other to achieve the desired functionality. Some examples of operably couplable include, but are not limited to, physically mateable and/or physically interacting components and/or wirelessly interactable and/or wirelessly interacting components and/or logically interacting and/or logically interactable components. Furthermore, it will be understood that a component preceding the term “of the” may be disposed at any practicable location (e.g., on, within, and/or externally disposed from the vehicle) such that the component may function in any manner described herein.

Modifications of the disclosure will occur to those skilled in the art and to those who make or use the disclosure. Therefore, it is understood that the embodiments shown in the drawings and described above are merely for illustrative purposes and not intended to limit the scope of the disclo-

sure, which is defined by the following claims, as interpreted according to the principles of patent law, including the doctrine of equivalents.

It is to be understood that variations and modifications can be made on the aforementioned structure without departing from the concepts of the present invention, and further it is to be understood that such concepts are intended to be covered by the following claims unless these claims by their language expressly state otherwise.

What is claimed is:

1. A storage assembly for a vehicle, comprising:

a rigid retention structure;

a cargo panel operably coupled to and selectively engaging the rigid retention structure, the cargo panel having a body defining at least one aperture on at least one side of the body; and

at least one damper having an adaptor strip disposed within the at least one aperture of the body and a plurality of flexures outwardly extending from the adaptor strip and operable between a compressed condition and an extended condition, the plurality of flexures being configured to engage the rigid retention structure in the compressed condition.

2. The storage assembly of claim 1, wherein each of the plurality of flexures include a planar extension and a curved end, and wherein each of the plurality of flexures is coupled to the adaptor strip via the planar extension.

3. The storage assembly of claim 1, wherein a return angle is defined between each flexure of the plurality of flexures and the rigid retention structure.

4. The storage assembly of claim 3, wherein the return angle is approximately 45-degrees.

5. The storage assembly of claim 1, wherein an approach angle is defined between each flexure of the plurality of flexures and the adaptor strip.

6. The storage assembly of claim 5, wherein the approach angle is approximately 45-degrees.

7. The storage assembly of claim 1, wherein the at least one damper has a height of approximately 15-millimeters, and wherein each of the plurality of flexures has a thickness of 3.5-millimeters.

8. A damper for a vehicle cargo panel, comprising:

an adaptor body having an attachment surface and an engagement surface;

a plurality of flexures outwardly extending from the engagement surface of the adaptor body and having a planar extension coupled to the engagement surface and a curved end, the plurality of flexures operable between an extended condition and a compressed condition; and

a coupling member disposed on the adaptor body and configured to couple the adaptor body to said vehicle cargo panel.

9. The damper of claim 8, wherein each of the plurality of flexures defines a thickness of approximately 2-millimeters.

10. The damper of claim 8, wherein the adaptor body and the plurality of flexures define a height of said damper of approximately 8.5-millimeters.

11. The damper of claim 8, wherein each flexure of the plurality of flexures defines an approach angle between the planar extension and the engagement surface of the adaptor body.

12. The damper of claim 8, wherein each flexure of the plurality of flexures has a return angle at least partially defined by the curved end of each flexure.

13. The damper of claim 12, wherein the return angle is approximately 30-degrees.

14. The damper of claim **8** wherein each flexure of the plurality of flexures has a thickness of approximately 2-millimeters.

15. A cargo panel assembly for a vehicle, comprising:
 a body defining at least one aperture on at least one side 5
 of the body; and
 a damper having an adaptor strip disposed within the at
 least one aperture of the body and a plurality of flexures
 outwardly extending from the adaptor strip and oper-
 able between a compressed condition and an extended 10
 condition, the plurality of flexures being configured to
 engage a rigid surface of said vehicle in the compressed
 condition.

16. The cargo panel assembly of claim **15**, wherein each flexure of the plurality of flexures includes a planar exten- 15
 sion and a curved end.

17. The cargo panel assembly of claim **16**, wherein each flexure of the plurality of flexures defines an approach angle between the planar extension and the adaptor strip.

18. The cargo panel assembly of claim **17**, wherein the 20
 approach angle of the plurality of flexures is smaller in the compressed condition than the approach angle of the plurality of flexures in the extended condition.

19. The cargo panel assembly of claim **16**, wherein each flexure of the plurality of flexures defines a return angle 25
 between the curved end of each flexure and the rigid surface of said vehicle.

20. The cargo panel assembly of claim **19**, wherein the return angle is defined between the compressed condition and the extended condition of the plurality of flexures. 30

* * * * *