

US011214449B2

(12) **United States Patent**
Chou et al.

(10) **Patent No.:** **US 11,214,449 B2**
(45) **Date of Patent:** **Jan. 4, 2022**

(54) **GLASS PROCESSING APPARATUS AND METHODS**

(58) **Field of Classification Search**
CPC B65G 49/067; B65G 47/91; B65G 49/06;
C03B 35/24; C03B 35/00

(71) Applicant: **CORNING INCORPORATED**,
Corning, NY (US)

(Continued)

(72) Inventors: **Cheng Nan Chou**, Fong-Yuan (TW);
Ming Hua Chuang, Kaohsiung (TW)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(73) Assignee: **Corning Incorporated**, Corning, NY
(US)

3,385,490 A 5/1968 Malmgren et al.
5,002,599 A * 3/1991 McMaster C03B 23/0252
294/64.3

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 97 days.

(Continued)

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **16/630,091**

CN 1513739 A 7/2004
CN 101313168 A 11/2008

(22) PCT Filed: **Jul. 5, 2018**

(Continued)

(86) PCT No.: **PCT/US2018/040850**

OTHER PUBLICATIONS

§ 371 (c)(1),

(2) Date: **Jan. 10, 2020**

Chinese Patent Application No. 201880056958.9, Office Action
dated Apr. 22, 2021, 8 pages (4 pages of English Translation and 4
pages of Original Document), Chinese Patent Office.

(87) PCT Pub. No.: **WO2019/014038**

(Continued)

PCT Pub. Date: **Jan. 17, 2019**

(65) **Prior Publication Data**

US 2020/0216271 A1 Jul. 9, 2020

Primary Examiner — Lynn E Schwenning

(74) *Attorney, Agent, or Firm* — Ryan T. Hardee

Related U.S. Application Data

(60) Provisional application No. 62/531,101, filed on Jul.
11, 2017.


(51) **Int. Cl.**
B65G 49/06 (2006.01)
B65G 47/91 (2006.01)
C03B 35/24 (2006.01)

(52) **U.S. Cl.**
CPC **B65G 49/067** (2013.01); **B65G 47/91**
(2013.01); **C03B 35/24** (2013.01)

(57) **ABSTRACT**

A glass processing apparatus to convey a glass sheet along
a conveyance path can include a plurality of air bars spaced
apart from each other along a first direction extending
perpendicular to a central axis. Each air bar can include a
surface with a plurality of fluid outlet ports. The glass
processing apparatus can include a plurality of plates, and at
least one of the plurality of plates can be positioned between
ones of the plurality of air bars. Each plate can include a
surface with a plurality of fluid inlet ports. The plurality of
air bars and the plurality of plates can be symmetrically
arranged relative to the central axis. Methods of processing

(Continued)



a glass sheet can include emitting fluid from the plurality of fluid outlet ports of each of the plurality of air bars, thereby providing a cushion of fluid.

25 Claims, 3 Drawing Sheets

(58) Field of Classification Search

USPC 414/676
See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

5,016,363	A	5/1991	Krieger	
5,078,775	A	1/1992	Maltby et al.	
6,505,483	B1 *	1/2003	Hoetzl	C03B 35/24 65/25.2
6,736,588	B1	5/2004	Baldwin et al.	
7,077,019	B2	7/2006	Weiss et al.	
7,428,959	B2	9/2008	Jung et al.	
7,607,647	B2	10/2009	Zhao et al.	
8,137,046	B2	3/2012	Kishimoto et al.	
8,142,111	B2	3/2012	Kim et al.	
8,297,077	B2 *	10/2012	Nuttgens	C03B 35/24 65/182.2
8,523,510	B2	9/2013	Snodgrass et al.	
9,038,414	B2	5/2015	Fleming et al.	
9,199,816	B2	12/2015	Blanding et al.	
9,216,924	B2	12/2015	Chang et al.	
10,889,438	B2 *	1/2021	Kusama	H01L 21/67396

2001/0015520	A1 *	8/2001	Gauger	B65H 3/0825 271/18.1
2006/0042314	A1	3/2006	Abbott et al.	
2009/0155024	A1	6/2009	Nuttgens et al.	
2012/0247154	A1	10/2012	Abramov et al.	
2013/0127192	A1 *	5/2013	Regan	B25J 15/0616 294/185
2015/0336751	A1	11/2015	Tsunoda et al.	
2016/0268153	A1	9/2016	Wada	

FOREIGN PATENT DOCUMENTS

CN	101523590	A	9/2009
CN	102167502	A	8/2011
CN	102442768	A	5/2012
CN	103112719	A	5/2013
CN	104211288	A	12/2014
CN	104418497	A	3/2015
JP	2001-010724	A	1/2001
JP	2006-019396	A	1/2006
TW	201529456	A	8/2015

OTHER PUBLICATIONS

International Search Report and Written Opinion of the International Searching Authority; PCT/US2018/040850; dated Sep. 11, 2018; 9 Pages; ISA/US Commissioner for Patents.
Taiwanese Patent Application No. 107123787, Office Action dated Oct. 22, 2021, 1 page (English Translation Only); Taiwanese Patent Office.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4

GLASS PROCESSING APPARATUS AND METHODS

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a national stage entry of International Patent Application Serial No. PCT/US2018/040850, filed on Jul. 5, 2018, which in turn, claims the benefit of priority under 35 U.S.C. § 119 of U.S. Provisional Application Ser. No. 62/531,101 filed on Jul. 11, 2017, the contents of each of which are relied upon and incorporated herein by reference in their entireties.

FIELD

The present disclosure relates generally to methods and apparatus for processing a glass sheet, and more particularly, to methods and apparatus to convey a glass sheet along a conveyance path.

BACKGROUND

It is known to convey a glass sheet. For example, it is known to convey a glass sheet by supporting the glass sheet on a cushion of fluid.

SUMMARY

The following presents a simplified summary of the disclosure in order to provide a basic understanding of some exemplary embodiments described in the detailed description.

In some embodiments, a glass processing apparatus to convey a glass sheet along a conveyance path can include a plurality of air bars spaced apart from each other along a first direction extending perpendicular to a central axis. Each air bar can include a surface with a plurality of fluid outlet ports. The glass processing apparatus can include a plurality of plates, at least one of the plurality of plates can be positioned between ones of the plurality of air bars. Each plate can include a surface with a plurality of fluid inlet ports. The plurality of air bars and the plurality of plates can be symmetrically arranged relative to the central axis.

In some embodiments, the surface of each of the plurality of air bars and the surface of each of the plurality of plates can extend along a common plane.

In some embodiments, the surface of each of the plurality of air bars and the surface of each of the plurality of plates can define a continuous surface.

In some embodiments, the surface of each of the plurality of air bars can span a width extending in the first direction from a first edge of the air bar to a second edge of the air bar, and the width of the surface of each of the plurality of air bars can be equal.

In some embodiments, a widthwise distance extending in the first direction between immediately adjacent outer air bars of the plurality of air bars can be less than a widthwise distance extending in the first direction between immediately adjacent central air bars of the plurality of air bars.

In some embodiments, an effective area of the plurality of fluid outlet ports of each air bar of the plurality of air bars can be equal.

In some embodiments, the surface of each of the plurality of plates can span a width extending in the first direction from a first edge of each plate to a second edge of each plate, and the width of the surface of at least one plate of the

plurality of plates can be different than the width of the surface of one or more other plates of the plurality of plates.

In some embodiments, the width of the surface of a central plate of the plurality of plates can be greater than the width of the surface of an outer plate of the plurality of plates.

In some embodiments, an effective area of the plurality of fluid inlet ports of at least one plate of the plurality of plates can be different than an effective area of the plurality of fluid inlet ports of one or more other plates of the plurality of plates.

In some embodiments, an effective area of the plurality of fluid inlet ports of each of three centermost plates of the plurality of plates can be greater than an effective area of the plurality of fluid inlet ports of each of a first outermost plate of the plurality of plates and a second outermost plate of the plurality of plates.

In some embodiments, an effective area of the plurality of fluid inlet ports of a first intermediate plate of the plurality of plates positioned between the first outermost plate and the three centermost plates can be less than the effective area of the plurality of fluid inlet ports of each of the three centermost plates and greater than the effective area of the plurality of fluid inlet ports of the first outermost plate, and an effective area of the plurality of fluid inlet ports of a second intermediate plate of the plurality of plates positioned between the second outermost plate and the three centermost plates can be less than the effective area of the plurality of fluid inlet ports of each of the three centermost plates and greater than the effective area of the plurality of fluid inlet ports of the second outermost plate.

In some embodiments, an effective area of the plurality of fluid inlet ports of a third intermediate plate of the plurality of plates positioned between the first outermost plate and the first intermediate plate can be equal to the effective area of the plurality of fluid inlet ports of each of the three centermost plates, and an effective area of the plurality of fluid inlet ports of a fourth intermediate plate of the plurality of plates positioned between the second outermost plate and the second intermediate plate can be equal to the effective area of the plurality of fluid inlet ports of each of the three centermost plates.

In some embodiments, the conveyance path can extend along the central axis, and a method of processing a glass sheet can include conveying the glass sheet along the conveyance path.

In some embodiments, the glass processing apparatus can further include a fluid source connected to the plurality of air bars, the fluid source operable to provide fluid to each of the plurality of air bars and to emit fluid from the plurality of fluid outlet ports of each air bar.

In some embodiments, the fluid source can be operable to independently provide fluid to each of the plurality of air bars.

In some embodiments, the fluid source can be operable to emit fluid of differing pressures from the plurality of fluid outlet ports of one or more air bars of the plurality of air bars.

In some embodiments, the fluid source can be operable to emit fluid of a first pressure from the plurality of fluid outlet ports of two centermost air bars of the plurality of air bars and fluid of a second pressure from the plurality of fluid outlet ports of a first outermost air bar of the plurality of air bars and a second outermost air bar of the plurality of air bars, and the first pressure can be greater than the second pressure.

In some embodiments, the fluid source can be operable to emit fluid of a third pressure from the plurality of fluid outlet

3

ports of a first of three air bars of the plurality of air bars positioned between the first outermost air bar and the two centermost air bars and from the plurality of fluid outlet ports of a second of three air bars of the plurality of air bars positioned between the second outermost air bar and the two centermost air bars, and the third pressure can be less than the second pressure.

In some embodiments, the plurality of fluid inlet ports of each plate of the plurality of plates can be provided without a fluid source connected to the plurality of fluid inlet ports.

In some embodiments, a method of processing a glass sheet can include emitting fluid from the plurality of fluid outlet ports of each of the plurality of air bars, thereby providing a cushion of fluid.

In some embodiments, the method can include floating the glass sheet on the cushion of fluid.

In some embodiments, the conveyance path can extend along the central axis, and the method can include conveying the glass sheet along the conveyance path on the cushion of fluid.

In some embodiments, the method can include passing at least a portion of the emitted fluid through the plurality of fluid inlet ports of each of the plurality of plates after providing the cushion of fluid.

The above embodiments are exemplary and can be provided alone or in any combination with any one or more embodiments provided herein without departing from the scope of the disclosure. Moreover, it is to be understood that both the foregoing general description and the following detailed description present embodiments of the present disclosure, and are intended to provide an overview or framework for understanding the nature and character of the embodiments as they are described and claimed. The accompanying drawings are included to provide a further understanding of the embodiments, and are incorporated into and constitute a part of this specification. The drawings illustrate various embodiments of the disclosure, and together with the description, serve to explain the principles and operations thereof.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other features, embodiments, and advantages of the present disclosure can be further understood when read with reference to the accompanying drawings:

FIG. 1 illustrates a schematic side view of an exemplary glass processing apparatus including a plurality of air bars, a plurality of plates, and a glass sheet in accordance with embodiments of the disclosure;

FIG. 2 illustrates a schematic top view of the exemplary glass processing apparatus of FIG. 1 including a conveyance path with the glass sheet removed for clarity in accordance with embodiments of the disclosure;

FIG. 3 shows a view of a central portion of the exemplary conveyance device identified by numeral 3 of FIG. 2 including a plurality of fluid outlet ports of an air bar and a plurality of fluid inlet ports of a plate in accordance with embodiments of the disclosure; and

FIG. 4 shows a view of an outer portion of the exemplary conveyance device identified by numeral 4 of FIG. 2 including a plurality of fluid outlet ports of an air bar and a plurality of fluid inlet ports of a plate in accordance with embodiments of the disclosure.

DETAILED DESCRIPTION

Methods and apparatus will now be described more fully hereinafter with reference to the accompanying drawings in

4

which exemplary embodiments of the disclosure are shown. Whenever possible, the same reference numerals are used throughout the drawings to refer to the same or like parts. However, this disclosure may be embodied in many different forms and should not be construed as limited to the embodiments set forth herein.

Glass sheets are commonly fabricated by flowing molten material to a forming body whereby a glass ribbon can be formed by a variety of ribbon forming processes including, float, slot draw, down-draw (including fusion down-draw), up-draw, press roll or other forming processes. The glass ribbon from any of these processes can then be subsequently divided to provide one or more glass sheets. In some embodiments, processing of the glass sheet can include transporting the glass sheet from one location to another location. Additionally, in some embodiments, the one or more glass sheets can be suitable for further processing into a desired application, including but not limited to, a display application, a lighting application, a photovoltaic application or any other application benefiting from the use of high quality glass sheets. For example, the one or more glass sheets can be used in a variety of display applications, including liquid crystal displays (LCDs), electrophoretic displays (EPD), organic light emitting diode displays (OLEDs), plasma display panels (PDPs), or the like.

FIG. 1 schematically illustrates a side view of an exemplary glass processing apparatus 100 including a glass sheet 101 in accordance with embodiments of the disclosure. In some embodiments, a thickness “t” of the glass sheet 101 defined between a first major surface 102 and an opposing second major surface 103 of the glass sheet 101 can be, for example, from about 25 micrometers (μm) to about 3 millimeters (mm), for example, from about 25 micrometers to about 2 millimeters, for example, from about 25 micrometers to about 1 millimeter, for example, from about 25 micrometers to about 0.5 millimeters, for example, from about 25 micrometers to about 400 micrometers, for example, from about 25 micrometers to about 300 micrometers, for example, from about 25 micrometers to about 200 micrometers, for example, from about 25 micrometers to about 100 micrometers, for example, from about 25 micrometers to about 50 micrometers, although other thicknesses can be provided in further embodiments, without departing from the scope of the disclosure. In addition, in some embodiments, the glass sheet 101 can include a variety of compositions including but not limited to glass, ceramic, glass-ceramic, soda-lime glass, borosilicate glass, aluminoborosilicate glass, an alkali-containing glass, an alkali-free glass, or any combination thereof. In some embodiments, a density of the glass sheet 101 can be about 2.16 grams per cubic centimeter (g/cm^3), an elastic modulus of the glass sheet 101 can be about 73,600 megapascal (MPa), and a Poisson’s ratio of the glass sheet 101 can be about 0.23. Additionally, in some embodiments, the glass sheet 101 can span a dimension (e.g., width) of about 2940 mm along the first direction 201, and a dimension (e.g., length) of about 3370 mm along a direction perpendicular to the first direction 201.

FIG. 2 schematically illustrates a top view of the glass processing apparatus 100 of FIG. 1 with the glass sheet 101 removed for clarity. In some embodiments, the glass processing apparatus 100 can include a plurality of air bars 110 spaced apart from each other along a first direction 201 extending perpendicular to a central axis 200 of the glass processing apparatus 100. Additionally, in some embodiments, the glass processing apparatus 100 can include a plurality of plates 120, at least one of the plurality of plates

positioned between ones of the plurality of air bars **110**. In some embodiments, the plurality of air bars **110** and the plurality of plates **120** can be symmetrically arranged relative to the central axis **200**. In some embodiments, a conveyance path **202** can extend along the central axis **200**, and the glass processing apparatus **100** can be operable to convey the glass sheet **101** along the conveyance path **202**.

Throughout the disclosure, various and specific configurations, quantities, arrangements, dimensions, and other features of the plurality of air bars **110** and the plurality of plates **120** can be provided. In some embodiments, the various and specific configurations, quantities, arrangements, dimensions, and other features of the plurality of air bars **110** and the plurality of plates **120** can be determined based on, for example, computer modeling (e.g., computational fluid dynamics). In some embodiments, the various and specific configurations, quantities, arrangements, dimensions, and other features of the plurality of air bars **110** and the plurality of plates **120** can obtain remarkable advantages relating to processing the glass sheet **101** that cannot be achieved by glass processing apparatus not including the various and specific configurations, quantities, arrangements, dimensions, and other features of the plurality of air bars **110** and the plurality of plates **120**. Moreover, unless otherwise noted, one or more of the features of one or more of the plurality of air bars **110** and one or more of the plurality of plates **120** can be provided, alone or in combination, with features explicitly disclosed in the disclosure as well as with features not explicitly disclosed in the disclosure, without departing from the scope of the disclosure. Therefore, numerous exemplary embodiments are disclosed with the understanding that each embodiment, alone or in combination with other exemplary embodiments, can be considered complete and within the scope of the disclosure.

As shown in FIG. 1 and FIG. 2, in some embodiments, each air bar **110a-j** can include a surface **112a-j** with a plurality of fluid outlet ports **301a-b** (See FIG. 4) and **301e-f** (See FIG. 3). In some embodiments, the plurality of air bars **110** can include an enclosure to contain fluid (e.g., air) with the surface **112a-j** defining at least a portion of the enclosure. In some embodiments, the plurality of fluid outlet ports can be one or more of machined (e.g., drilled), manufactured, and formed in the surface **112a-j** to provide access from inside the enclosure to outside the enclosure such that the fluid can pass from inside the enclosure to outside the enclosure through the plurality of fluid outlet ports of the plurality of air bars **110**.

As shown in FIG. 1 and FIG. 2, in some embodiments, each plate **120a-i** can include a surface **122a-i** with a plurality of fluid inlet ports **302a** (See FIG. 4) and **302e** (See FIG. 3). In some embodiments, the plurality of plates **120** can be a solid material and the plurality of fluid inlet ports can be one or more of machined (e.g., drilled), manufactured, and formed in the surface **122a-i** to extend through the solid material such that fluid (e.g., air) can pass from one side of the plurality of plates **120** through the plurality of fluid inlet ports to another side of the plurality of plates **120**.

Additionally, for simplicity and not limitation, in FIG. 1 and FIG. 2, the plurality of fluid outlet ports of the plurality of air bars **110** and the plurality of fluid inlet ports of the plurality of plates **120** are not illustrated. Rather, FIG. 3 shows a view of a central portion of the glass processing apparatus **100** identified by numeral **3** of FIG. 2, and FIG. 4 shows a view of an outer portion of the glass processing apparatus **100** identified by numeral **4** of FIG. 2. For example, one embodiment of the plurality of fluid outlet ports **301a** of air bar **110a** and the plurality of fluid outlet

ports **301b** of air bar **110b** are shown in FIG. 4. One embodiment of the plurality of fluid outlet ports **301e** of air bar **110e** and the plurality of fluid outlet ports **301f** of air bar **110f** are shown in FIG. 3. Therefore, although not explicitly shown, it is to be understood that one or more of the plurality of air bars (e.g., air bar **110c-d**, **110g-j**) can include same or similar features of the plurality of air bars (e.g., air bar **110a-b**, **110e-f**) shown in FIG. 3 and FIG. 4 without departing from the scope of the disclosure. Similarly, one embodiment of the plurality of fluid inlet ports **302a** of plate **120a** are shown in FIG. 4, and one embodiment of the plurality of fluid inlet ports **302e** of plate **120e** are shown in FIG. 3. Although not explicitly shown, it is to be understood that one or more of the plurality of plates (e.g., plate **120b-d**, **120f-i**) can include same or similar features of the plates (e.g., plate **120a**, **120e**) shown in FIG. 3 and FIG. 4 without departing from the scope of the disclosure.

Turning back to FIG. 1 and FIG. 2, in some embodiments, plate **120a** can be positioned between air bar **110a** and air bar **110b**; plate **120b** can be positioned between air bar **110b** and air bar **110c**; plate **120c** can be positioned between air bar **110c** and air bar **110d**; plate **120d** can be positioned between air bar **110d** and air bar **110e**; plate **120e** can be positioned between air bar **110e** and air bar **110f**; plate **120f** can be positioned between air bar **110f** and air bar **110g**; plate **120g** can be positioned between air bar **110g** and air bar **110h**; plate **120h** can be positioned between air bar **110h** and air bar **110i**; and plate **120i** can be positioned between air bar **110i** and air bar **110j**. In some embodiments, a method of processing the glass sheet **101** can include emitting fluid from the plurality of fluid outlet ports **301a-b**, **301e-f** (See FIG. 3 and FIG. 4) of each of the plurality of air bars **110**, thereby providing the cushion of fluid **105**. For example, in some embodiments, each of the air bars **110a-j** can emit fluid from a respective plurality of fluid outlet ports as respectively shown by arrows **111a-j** in FIG. 1. In some embodiments, providing the plurality of air bars **110** and the plurality of plates **120** with the relative positions described can facilitate creation and maintenance of a cushion of fluid **105** (see FIG. 1) on which the glass sheet **101** can float.

In some embodiments, the method can include floating the glass sheet **101** on the cushion of fluid **105**. As shown in FIG. 1, in some embodiments, the glass sheet **101** can float on the cushion of fluid **105** at a height “h” measured from one or more surfaces **112a-j** of the respective plurality of air bars **110a-j** and/or one or more surfaces **122a-i** of the respective plurality of plates **120a-i** to the second major surface **103** of the glass sheet **101**. In some embodiments, the height “h” can be constant along the central axis **200** and/or constant along the first direction **201**. For example, in some embodiments, the glass processing apparatus **100** can float at least a portion of the second major surface **103** (e.g., the entire second major surface **103**) of the glass sheet **101** on the cushion of fluid **105** at a constant height “h” as the at least a portion of the second major surface **103** conveys along the conveyance path **202** along a length (e.g., the entire length) of the central axis **200**. In some embodiments, the glass sheet **101** can include a planar profile (e.g., first major surface **102** and second major surface **103** are planar and parallel) while the glass sheet **101** floats on the cushion of fluid **105**. In some embodiments, floating the glass sheet **101** on the cushion of fluid **105** at a constant height “h” with the glass sheet **101** including a planar profile can reduce or eliminate bending stress that can otherwise be present in the glass sheet if, for example, the height “h” was to vary along the central axis **200** and/or along the first direction **201**.

In some embodiments, the height “h” can be from about 5 mm to about 15 mm; for example, from about 8 mm to about 12 mm; for example, about 10 mm. Floating the glass sheet **101** on the cushion of fluid **105** can facilitate processing (e.g., placement, transport, conveyance, packaging) of the glass sheet **101** in a non-contact manner, where only the cushion of fluid **105** physically contacts the glass sheet **101**. In some embodiments, non-contact processing of the glass sheet **101** can reduce the probability of damaging, for example scratching and/or cracking the glass sheet **101** that can otherwise occur, for example, when processing the glass sheet **101** in a manner that includes physically contacting the glass sheet **101** with one or more solid objects such as a machine, equipment, mechanical part, or other object. Additionally, in some embodiments, floating the glass sheet **101** on the cushion of fluid **105** at a predetermined height “h” can prevent contact between the glass sheet **101** and the glass processing apparatus **100** while processing the glass sheet **101**. For example, preventing contact between the glass sheet **101** and the glass processing apparatus **100** (e.g., one or more surfaces **112a-j** of the plurality of air bars **110** and/or one or more surfaces **122a-i** of the plurality of plates **120**) can reduce the probability of damaging, for example, scratching and/or cracking the glass sheet **101** that can otherwise occur, for example, when processing the glass sheet **101** in a manner that includes physically contacting the glass sheet **101** with the glass processing apparatus **100**.

Referring to FIG. 2, in some embodiments, the conveyance path **202** can extend along the central axis **200**, and the method can include conveying the glass sheet **101** along the conveyance path **202** on the cushion of fluid **105**. Additionally, in some embodiments, the method can include passing at least a portion of the emitted fluid through the plurality of fluid inlet ports of each of the plurality of plates **120** after providing the cushion of fluid **105**. For example, as shown by arrows **121a-i**, at least a portion of the emitted fluid can pass through a respective plurality of fluid inlet ports of respective plates **120a-i** of the plurality of plates **120**.

In some embodiments, the surface **112a-j** of each respective air bar **110a-j** can span a corresponding width **Wa-j** extending in the first direction **201** from a corresponding first edge **113a-j** of the respective air bar **110a-j** to a corresponding second edge **114a-j** of the respective air bar **110a-j**. In some embodiments, the width of each surface **112a-j** of the plurality of air bars **110** can be equal (e.g., width $W_a = \text{width } W_b = \text{width } W_c = \text{width } W_d = \text{width } W_e = \text{width } W_f = \text{width } W_g = \text{width } W_h = \text{width } W_i = \text{width } W_j$). In some embodiments, providing the surfaces **112a-j** of the plurality of air bars **110** with the relative widths **Wa-j** can facilitate creation and maintenance of the cushion of fluid **105** on which the glass sheet **101** can float.

As further shown in FIG. 2, in some embodiments, the surface **122a-i** of each of the respective plates **120a-i** can span a corresponding width **Pa-i** extending in the first direction **201** from a corresponding first edge **123a-i** of the respective plate **120a-i** to a corresponding second edge **124a-i** of the respective plate **120a-i**. When symmetrically arranged relative to the central axis **200**, in some embodiments, width $P_a = \text{width } P_i$, width $P_b = \text{width } P_h$, width $P_c = \text{width } P_g$, width $P_d = \text{width } P_t$. Additionally, in some embodiments, the width **Pa-i** of the surface **122a-i** of at least one plate **120a-i** of the plurality of plates **120** can be different than the width **Pa-i** of the surface **122a-i** of one or more other plates **120a-i** of the plurality of plates **120**. For example, in some embodiments, the width of the surface of one or more central plates of the plurality of plates **120** can be greater than the width of the surface of one or more outer

plates of the plurality of plates **120**. The locations of central plates and outer plates can correspond to a position of one or more plates of the plurality of plates **120** along the first direction **201** relative to the central axis **200**, with one or more plates positioned relatively closer to the central axis **200** being considered central plates relative to one or more plates positioned relatively farther from the central axis **200**.

For example, in some embodiments, the width **Pb** of surface **122b** of plate **120b** can be greater than the width **Pa** of surface **122a** of plate **120a**, and the width **Ph** of surface **122h** of plate **120h** can be greater than the width **Pi** of surface **122i** of plate **120i**. In some embodiments, the width **Pd** of surface **122d** of plate **120d**, the width **Pe** of surface **122e** of plate **120e**, and the width **Pf** of surface **122f** of plate **120f** can be equal to each other and also greater than the width **Pc** of surface **122c** of plate **120c** and the width **Pg** of surface **122g** of plate **120g** which can be equal to each other and also greater than the width **Pa** of surface **122a** of plate **120a** and the width **Pi** of surface **122i** of plate **120i** which can be equal to each other. In some embodiments, the width of a surface (e.g., surface **122e**) of a centermost plate (e.g., plate **120e**) of the plurality of plates **120** can be greater than the width of a surface (e.g., surface **122a**, surface **122i**) of an outermost plate (e.g., plate **120a**, plate **120i**) of the plurality of plates **120**. In some embodiments, width $P_e > (\text{width } P_d = \text{width } P_f) > (\text{width } P_c = \text{width } P_g) > (\text{width } P_b = \text{width } P_h) > (\text{width } P_a = \text{width } P_i)$. In some embodiments, providing the surfaces **122a-i** of the plurality of plates **120** with the relative widths **Pa-i** described can facilitate creation and maintenance of the cushion of fluid **105** on which the glass sheet **101** can float.

Turning back to FIG. 1, in some embodiments, the surface **112a-j** of each of the corresponding air bars **110a-j** and the surface **122a-i** of each of the corresponding plates **120a-i** can extend along a common plane **130**. For example, in some embodiments, the surfaces **112a-j** of each of the corresponding air bars **110a-j** and the surfaces **122a-i** of each of the plurality of the corresponding plates **120a-i** can define a continuous surface. For example, in some embodiments, the first edge **113a** of air bar **110a** can define a first outermost edge of the continuous surface and the second edge **114j** of air bar **110j** can define a second outermost edge of the continuous surface. The surfaces **112a-j** of the plurality of air bars **110** and the surfaces **122a-i** of the plurality of plates **120** can continuously span along the first direction **201** from the first outermost edge to the second outermost edge, thereby defining the continuous surface. In some embodiments, the continuous surface can be planar (e.g., coplanar with common plane **130**). Additionally, in some embodiments, the continuous surface and/or the common plane **130** can be perpendicular relative the direction of gravity.

In some embodiments, the continuous surface defined by the surfaces **112a-j** of the plurality of air bars **110** and the surfaces **122a-i** of the plurality of plates **120** can be provided as a single continuous piece of material defining the continuous surface. Alternatively, in some embodiments, the continuous surface defined by the surfaces **112a-j** of the plurality of air bars **110** and the surfaces **122a-i** of the plurality of plates **120** can be provided by positioning the plurality of air bars **110** and the plurality of plates **120** in abutting relationship with respect to each other. For example, in some embodiments, the second edge **114a** of air bar **110a** can abut the first edge **123a** of plate **120a**, the second edge **124a** of plate **120a** can abut the first edge **113b** of air bar **110b**, the second edge **114b** of air bar **110b** can abut the first edge **123b** of plate **120b**, the second edge **124b**

of plate **120b** can abut the first edge **113c** of air bar **110c**, the second edge **114c** of air bar **110c** can abut the first edge **123c** of plate **120c**, the second edge **124c** of plate **120c** can abut the first edge **113d** of air bar **110d**, the second edge **114d** of air bar **110d** can abut the first edge **123d** of plate **120d**, the second edge **124d** of plate **120d** can abut the first edge **113e** of air bar **110e**, the second edge **114e** of air bar **110e** can abut the first edge **123e** of plate **120e**, the second edge **124e** of plate **120e** can abut the first edge **113f** of air bar **110f**, the second edge **114f** of air bar **110f** can abut the first edge **123f** of plate **120f**, the second edge **124f** of plate **120f** can abut the first edge **113g** of air bar **110g**, the second edge **114g** of air bar **110g** can abut the first edge **123g** of plate **120g**, the second edge **124g** of plate **120g** can abut the first edge **113h** of air bar **110h**, the second edge **114h** of air bar **110h** can abut the first edge **123h** of plate **120h**, the second edge **124h** of plate **120h** can abut the first edge **113i** of air bar **110i**, the second edge **114i** of air bar **110i** can abut the first edge **123i** of plate **120i**, and the second edge **124i** of plate **120i** can abut the first edge **113j** of air bar **110j**.

In some embodiments, by providing the plurality of air bars **110** and the plurality of plates **120** to include the common plane **130** and/or the continuous surface, the plurality of air bars **110** and the plurality of plates **120** can, together, provide the glass processing apparatus **100** with structure that facilitates creation and maintenance of a uniform, stable cushion of fluid **105** on which the glass sheet **101** can float. For example, in some embodiments, the fluid emitted from the plurality of air bars **110** can form the cushion of fluid **105**, thereby lifting the glass sheet **101** away from the surfaces **112a-j** of each of the corresponding air bars **110a-j**. In some embodiments, the plurality of plates **120** can regulate the flow (e.g., pressure, velocity, volume) of the emitted fluid to provide a stable, uniform cushion of fluid **105**. For example, in some embodiments, the surfaces **122a-i** of the corresponding plates **120a-i** can contain at least a portion of the emitted fluid between the plurality of plates **120** and the glass sheet **101** to form the cushion of fluid **105**. Additionally, the plurality of fluid inlet ports of the plurality of plates **120** can permit at least a portion of the emitted fluid to pass through a respective plurality of fluid inlet ports of the plurality of plates **120**, thereby regulating the amount (e.g., volume) of fluid defining the cushion of fluid **105** as well as regulating the pressure and velocity of the fluid defining the cushion of fluid **105**.

As shown in FIG. 2, in some embodiments, the plurality of air bars **110** can be spaced a widthwise distance **Dab**, **Dbc**, **Dcd**, **Dde**, **Def**, **Dfg**, **Dgh**, **Dhi**, **Dij** extending in the first direction **201** from each other. In some embodiments, the widthwise distance can be measured from a centerline of each of the plurality of air bars **110**. For example, air bar **110a** can be spaced a widthwise distance **Dab** from air bar **110b**; air bar **110b** can be spaced a widthwise distance **Dbc** from air bar **110c**; air bar **110c** can be spaced a widthwise distance **Dcd** from air bar **110d**; air bar **110d** can be spaced a widthwise distance **Dde** from air bar **110e**; air bar **110e** can be spaced a widthwise distance **Def** from air bar **110f**; air bar **110f** can be spaced a widthwise distance **Dfg** from air bar **110g**; air bar **110g** can be spaced a widthwise distance **Dgh** from air bar **110h**; air bar **110h** can be spaced a widthwise distance **Dhi** from air bar **110i**; and air bar **110i** can be spaced a widthwise distance **Dij** from air bar **110j**.

In some embodiments, a widthwise distance extending in the first direction **201** between immediately adjacent outer air bars (e.g., widthwise distance **Dab** between air bar **110a** and air bar **110b**, widthwise distance **Dij** between air bar **110i** and air bar **110j**) of the plurality of air bars **110** can be

less than a widthwise distance extending in the first direction **201** between immediately adjacent central air bars (e.g., one or more of widthwise distance **Def** between air bar **110e** and air bar **110f**, widthwise distance **Dde** between air bar **110d** and air bar **110e**, widthwise distance **Dfg** between air bar **110f** and air bar **110g**, widthwise distance **Dcd** between air bar **110c** and air bar **110d**, widthwise distance **Dgh** between air bar **110g** and air bar **110h**, widthwise distance **Dbc** between air bar **110b** and air bar **110c**, widthwise distance **Dhi** between air bar **110h** and air bar **110i**) of the plurality of air bars **110**. In some embodiments, widthwise distance $Def > (\text{widthwise distance } Dde = \text{widthwise distance } Dfg) > (\text{widthwise distance } Dcd = \text{widthwise distance } Dgh) > (\text{widthwise distance } Dbc = \text{widthwise distance } Dhi) > (\text{widthwise distance } Dab = \text{widthwise distance } Dij)$. In some embodiments, widthwise distance **Def** can be about 340 millimeters (mm), widthwise distance **Dde** and widthwise distance **Dfg** can be about 330 mm, widthwise distance **Dcd** and widthwise distance **Dgh** can be about 320 mm, widthwise distance **Dbc** and widthwise distance **Dhi** can be about 315 mm, and widthwise distance **Dab** and widthwise distance **Dij** can be about 265 mm. In some embodiments, providing the plurality of air bars **110** spaced apart from each other at the relative widthwise distances described can facilitate creation and maintenance of the cushion of fluid **105** on which the glass sheet **101** can float.

Turning back to FIG. 1, in some embodiments, the glass processing apparatus **100** can further include a fluid source **150** (e.g., blower, pump, fan) connected to the plurality of air bars **110**. For example, fluid line **155** can connect the fluid source **150** to the plurality of air bars **110**. In some embodiments, the fluid source **150** can be operable to provide fluid to each of the plurality of air bars **110** and to then emit fluid from the plurality of fluid outlet ports of each air bar **110a-j**. In some embodiments, a single fluid source **150** can be provided; however, in some embodiments, more than one fluid source can be provided. For example, in some embodiments, a separate, dedicated fluid source can be provided for each air bar **110a-j** of the plurality of air bars **110**. In some embodiments, the plurality of fluid inlet ports of each plate **120a-i** of the plurality of plates **120** can be provided without a fluid source connected to the plurality of fluid inlet ports of the plurality of plates **120**. For example, in some embodiments, fluid flow through the plurality of fluid inlet ports of the plurality of plates **120** can occur naturally (e.g., based on the flow of the emitted flow and other fluid flow existing in a flow region around the plurality of plates) without external influence from a separate fluid source (e.g., blower, pump, fan, vacuum) connected to the plurality of fluid inlet ports of the plurality of plates **120**. Alternatively, in some embodiments, a vacuum source (not shown) can be provided to draw (e.g., suck) the emitted fluid through the plurality of fluid inlet ports of the plurality of plates **120**. In some embodiments, providing the plurality of fluid inlet ports of each plate **120a-i** of the plurality of plates **120** without a fluid source or, optionally, with a vacuum source can facilitate creation and maintenance of the cushion of fluid **105** on which the glass sheet **101** can float.

In some embodiments, the fluid source **150** can be operable to independently provide fluid to each of the plurality of air bars **110**. For example, in some embodiments, one or more control valves and flow regulators **152** can be provided to independently control one or more of a volume, pressure, and velocity of the flow of fluid to each of the plurality of air bars **110**. In some embodiments, fluid line **155a** can connect the fluid source **150** to air bar **110a** to emit fluid (as shown by arrow **111a**); fluid line **155b** can connect the fluid

11

source **150** to air bar **110b** to emit fluid (as shown by arrow **111b**); fluid line **155c** can connect the fluid source **150** to air bar **110c** to emit fluid (as shown by arrow **111c**); fluid line **155d** can connect the fluid source **150** to air bar **110d** to emit fluid (as shown by arrow **111d**); fluid line **155e** can connect the fluid source **150** to air bar **110e** to emit fluid (as shown by arrow **111e**); fluid line **155f** can connect the fluid source **150** to air bar **110f** to emit fluid (as shown by arrow **111f**); fluid line **155g** can connect the fluid source **150** to air bar **110g** to emit fluid (as shown by arrow **111g**); fluid line **155h** can connect the fluid source **150** to air bar **110h** to emit fluid (as shown by arrow **111h**); fluid line **155i** can connect the fluid source **150** to air bar **110i** to emit fluid (as shown by arrow **111i**); and fluid line **155j** can connect the fluid source **150** to air bar **110j** to emit fluid (as shown by arrow **111j**).

In some embodiments, the fluid source **150** can be operable to emit fluid of differing pressures from the plurality of fluid outlet ports of one or more air bars of the plurality of air bars **110**. For example, in some embodiments, the fluid source **150** can be operable to emit fluid of a first pressure from the plurality of fluid outlet ports of two centermost air bars (e.g., air bar **110e** and air bar **110f**) of the plurality of air bars **110** and fluid of a second pressure from the plurality of fluid outlet ports of a first outermost air bar (e.g., air bar **110a**) of the plurality of air bars **110** and a second outermost air bar (e.g., air bar **110j**) of the plurality of air bars **110**. In some embodiments, the first pressure can be greater than the second pressure. In some embodiments, the fluid source **150** can be operable to emit fluid of a third pressure from the plurality of fluid outlet ports of a first of three air bars (e.g., air bar **110b**, air bar **110c**, air bar **110d**) of the plurality of air bars **110** positioned between the first outermost air bar (e.g., air bar **110a**) and the two centermost air bars (e.g., air bar **110e**, air bar **110f**) and from the plurality of fluid outlet ports of a second of three air bars (e.g., air bar **110g**, air bar **110h**, air bar **110i**) of the plurality of air bars **110** positioned between the second outermost air bar (e.g., air bar **110j**) and the two centermost air bars (e.g., air bar **110e**, air bar **110f**). In some embodiments, the third pressure can be less than the second pressure.

In some embodiments, the differing fluid pressures from the plurality of fluid outlet ports of one or more air bars of the plurality of air bars **110** can be controlled by selecting a velocity at which the air can be emitted from the plurality of fluid outlet ports of the plurality of air bars **110**. In some embodiments, a first velocity providing the first pressure can be greater than a second velocity providing the second pressure. Additionally, in some embodiments, a third velocity providing the third pressure can be less than the second velocity providing the second pressure. For example, in some embodiments, the first pressure from the plurality of fluid outlet ports of two centermost air bars (e.g., air bar **110e** and air bar **110f**) can be controlled by emitting air at a first velocity of about 21.2 meters/second (m/s). In some embodiments, the second pressure from the plurality of fluid outlet ports of the first outermost air bar (e.g., air bar **110a**) and the second outermost air bar (e.g., air bar **110j**) can be controlled by emitting air at a second velocity of about 20 m/s. In some embodiments, the third pressure from the plurality of fluid outlet ports of the first of three air bars (e.g., air bar **110b**, air bar **110c**, air bar **110d**) positioned between the first outermost air bar (e.g., air bar **110a**) and the two centermost air bars (e.g., air bar **110e**, air bar **110f**) and from the plurality of fluid outlet ports of the second of three air bars (e.g., air bar **110g**, air bar **110h**, air bar **110i**) positioned between the second outermost air bar (e.g., air bar **110j**) and the two centermost air bars (e.g., air bar **110e**, air bar **110f**) can be

12

controlled by emitting air at a third velocity of about 18.75 m/s. Accordingly, by selecting relative velocities at which air can be emitted from the plurality of fluid outlet ports of the respective plurality of air bars **110**, fluid of differing pressures can be emitted from the plurality of fluid outlet ports of one or more air bars of the plurality of air bars **110**.

In some embodiments, an effective area of the plurality of fluid outlet ports of each air bar of the plurality of air bars **110** can be equal. For example, with respect to FIG. 3, an effective area of the fluid outlet ports **301e** of air bar **110e** can be equal to an effective area of the fluid outlet ports **301f** of air bar **110f**. Likewise, with respect to FIG. 4, an effective area of the fluid outlet ports **301a** of air bar **110a** can be equal to an effective area of the fluid outlet ports **301b** of air bar **110b**. In some embodiments, the effective area can be calculated as the sum of the area of the opening of each fluid outlet port of the plurality of fluid outlet ports for a representative region of the respective air bar. For example, the area of a single fluid outlet port can be calculated based on the shape and size of the opening of the fluid outlet port. For a circular opening, the area of a single fluid outlet port could, therefore, be calculated as $A=\pi r^2$. For fluid outlet ports having openings of other shapes (e.g., squares, rectangles, triangles, etc.) the area can be calculated in a similar manner using a corresponding equation. The effective area of the fluid outlet ports of the plurality of air bars **110** can then be determined by summing the individual areas of the openings of each fluid outlet port of the plurality of fluid outlet ports for the representative region.

In addition or alternatively, in some embodiments, an effective area of the plurality of fluid inlet ports of at least one plate of the plurality of plates **120** can be different than an effective area of the plurality of fluid inlet ports of one or more other plates of the plurality of plates **120**. The effective area of the plurality of fluid inlet ports of the plurality of plates **120** can be calculated in a same or similar manner as the effective area of the plurality of fluid outlet ports of the plurality of air bars **110**. In some embodiments, providing different effective areas of the plurality of fluid inlet ports of the plurality of plates **120** can control one or more of an air pressure, velocity, and volume of fluid of the cushion of fluid **105** to provide a uniform, stable cushion of fluid **105** on which the glass sheet **101** can float. For example, in some embodiments, an effective area of the plurality of fluid inlet ports of each of three centermost plates (e.g., plate **120d**, plate **120e**, plate **120f**) of the plurality of plates **120** can be greater than an effective area of the plurality of fluid inlet ports of each of a first outermost plate (e.g., plate **120a**) of the plurality of plates **120** and a second outermost plate (e.g., plate **120i**) of the plurality of plates **120**.

In some embodiments, an effective area of the plurality of fluid inlet ports of a first intermediate plate (e.g., plate **120c**) of the plurality of plates **120** positioned between the first outermost plate (e.g., plate **120a**) and the three centermost plates (e.g., plate **120d**, plate **120e**, plate **120f**) can be less than the effective area of the plurality of fluid inlet ports of each of the three centermost plates (e.g., plate **120d**, plate **120e**, plate **120f**) and greater than the effective area of the plurality of fluid inlet ports of the first outermost plate (e.g., plate **120a**). Additionally, in some embodiments, an effective area of the plurality of fluid inlet ports of a second intermediate plate (e.g., plate **120g**) of the plurality of plates **120** positioned between the second outermost plate (e.g., plate **120i**) and the three centermost plates (e.g., plate **120d**, plate **120e**, plate **120f**) can be less than the effective area of the plurality of fluid inlet ports of each of the three centermost plates (e.g., plate **120d**, plate **120e**, plate **120f**) and

greater than the effective area of the plurality of fluid inlet ports of the second outermost plate (e.g., plate 120i).

In some embodiments, an effective area of the plurality of fluid inlet ports of a third intermediate plate (e.g., plate 120b) of the plurality of plates positioned between the first outermost plate (e.g., plate 120a) and the first intermediate plate (e.g., plate 120c) can be equal to the effective area of the plurality of fluid inlet ports of each of the three centermost plates (e.g., plate 120d, plate 120e, plate 120f). Additionally, in some embodiments, an effective area of the plurality of fluid inlet ports of a fourth intermediate plate (e.g., plate 120h) of the plurality of plates positioned between the second outermost plate (e.g., plate 120i) and the second intermediate plate (e.g., plate 120g) can be equal to the effective area of the plurality of fluid inlet ports of each of the three centermost plates (e.g., plate 120d, plate 120e, plate 120f).

In some embodiments, the effective area of the plurality of fluid inlet ports of the plurality of plates 120 can be selected by providing a predetermined quantity of fluid inlet ports having openings of the same size for a representative region of a respective plate of the plurality of plates 120. In addition or alternatively, in some embodiments, the effective area of the plurality of fluid inlet ports of the plurality of plates 120 can be selected by providing a plurality of fluid inlet ports having openings of different shapes and sizes for a representative region of a respective plate of the plurality of plates 120.

For example, as shown in FIG. 4, plate 120a can include three fluid inlet ports 302a arranged on the surface 122a between the first edge 123a and the second edge 124a along the first direction 201. Likewise, as shown in FIG. 3, plate 120e can include five fluid inlet ports 302e arranged on the surface 122e between the first edge 123e and the second edge 124e along the first direction 201. In some embodiments, plate 120d and plate 120f can include five fluid inlet ports (not shown) respectively arranged on the surface 122d between the first edge 123d and the second edge 124d along the first direction 201, and the surface 122f between the first edge 123f and the second edge 124f along the first direction 201. In some embodiments, plate 120i can include three fluid inlet ports (not shown) arranged on the surface 122i between the first edge 123i and the second edge 124i along the first direction 201. In some embodiments, plate 120b and plate 120h can include five fluid inlet ports (not shown) respectively arranged on the surface 122b between the first edge 123b and the second edge 124b along the first direction 201, and the surface 122h between the first edge 123h and the second edge 124h along the first direction 201. In some embodiments, plate 120c and plate 120g can include four fluid inlet ports (not shown) respectively arranged on the surface 122c between the first edge 123c and the second edge 124c along the first direction 201, and the surface 122g between the first edge 123g and the second edge 124g along the first direction 201.

In some embodiments, providing glass processing apparatus 100 with one or more of the features of the exemplary embodiments of the disclosure, the plurality of air bars 110 and the plurality of plates 120 can facilitate creation and maintenance of the cushion of fluid 105 on which the glass sheet 101 can float.

It will be appreciated that the various disclosed embodiments may involve particular features, elements or steps that are described in connection with that particular embodiment. It will also be appreciated that a particular feature, element or step, although described in relation to one particular

embodiment, may be interchanged or combined with alternate embodiments in various non-illustrated combinations or permutations.

It is to be understood that, as used herein the terms “the,” “a,” or “an,” mean “at least one,” and should not be limited to “only one” unless explicitly indicated to the contrary. Thus, for example, reference to “a component” includes embodiments having two or more such components unless the context clearly indicates otherwise.

Ranges can be expressed herein as from “about” one particular value, and/or to “about” another particular value. When such a range is expressed, embodiments include from the one particular value and/or to the other particular value. Similarly, when values are expressed as approximations, by use of the antecedent “about,” it will be understood that the particular value forms another aspect. It will be further understood that the endpoints of each of the ranges are significant both in relation to the other endpoint, and independently of the other endpoint.

Unless otherwise expressly stated, it is in no way intended that any method set forth herein be construed as requiring that its steps be performed in a specific order. Accordingly, where a method claim does not actually recite an order to be followed by its steps or it is not otherwise specifically stated in the claims or descriptions that the steps are to be limited to a specific order, it is no way intended that any particular order be inferred.

While various features, elements or steps of particular embodiments may be disclosed using the transitional phrase “comprising,” it is to be understood that alternative embodiments, including those that may be described using the transitional phrases “consisting” or “consisting essentially of,” are implied. Thus, for example, implied alternative embodiments to an apparatus that comprises A+B+C include embodiments where an apparatus consists of A+B+C and embodiments where an apparatus consists essentially of A+B+C.

It will be apparent to those skilled in the art that various modifications and variations can be made to the present disclosure without departing from the spirit and scope of the disclosure. Thus, it is intended that the present disclosure cover the modifications and variations of this disclosure provided they come within the scope of the appended claims and their equivalents.

What is claimed is:

1. A glass processing apparatus to convey a glass sheet along a conveyance path, comprising:
 - a plurality of air bars spaced apart from each other along a first direction extending perpendicular to a central axis, each air bar comprising a surface with a plurality of fluid outlet ports; and
 - a plurality of plates, at least one of the plurality of plates positioned between ones of the plurality of air bars, each plate comprising a surface with a plurality of fluid inlet ports, the plurality of air bars and the plurality of plates symmetrically arranged relative to the central axis, wherein a widthwise distance extending in the first direction between immediately adjacent outer air bars of the plurality of air bars is less than a widthwise distance extending in the first direction between immediately adjacent central air bars of the plurality of air bars.
2. The glass processing apparatus of claim 1, wherein the surface of each of the plurality of air bars and the surface of each of the plurality of plates extend along a common plane.

15

3. The glass processing apparatus of claim 1, wherein the surface of each of the plurality of air bars and the surface of each of the plurality of plates define a continuous surface.

4. The glass processing apparatus of claim 1, wherein the surface of each of the plurality of air bars spans a width extending in the first direction from a first edge of the air bar to a second edge of the air bar, and wherein the width of the surface of each of the plurality of air bars is equal.

5. The glass processing apparatus of claim 1, wherein an effective area of the plurality of fluid outlet ports of each air bar of the plurality of air bars is equal.

6. The glass processing apparatus of claim 1, wherein the surface of each of the plurality of plates spans a width extending in the first direction from a first edge of each plate to a second edge of each plate, and wherein the width of the surface of at least one plate of the plurality of plates is different than the width of the surface of one or more other plates of the plurality of plates.

7. The glass processing apparatus of claim 6, wherein the width of the surface of a central plate of the plurality of plates is greater than the width of the surface of an outer plate of the plurality of plates.

8. The glass processing apparatus of claim 1, wherein an effective area of the plurality of fluid inlet ports of at least one plate of the plurality of plates is different than an effective area of the plurality of fluid inlet ports of one or more other plates of the plurality of plates.

9. The glass processing apparatus of claim 8, wherein an effective area of the plurality of fluid inlet ports of each of three centermost plates of the plurality of plates is greater than an effective area of the plurality of fluid inlet ports of each of a first outermost plate of the plurality of plates and a second outermost plate of the plurality of plates.

10. The glass processing apparatus of claim 9, wherein an effective area of the plurality of fluid inlet ports of a first intermediate plate of the plurality of plates positioned between the first outermost plate and the three centermost plates is less than the effective area of the plurality of fluid inlet ports of each of the three centermost plates and greater than the effective area of the plurality of fluid inlet ports of a second intermediate plate of the plurality of plates positioned between the second outermost plate and the three centermost plates is less than the effective area of the plurality of fluid inlet ports of each of the three centermost plates and greater than the effective area of the plurality of fluid inlet ports of the second outermost plate.

11. The glass processing apparatus of claim 10, wherein an effective area of the plurality of fluid inlet ports of a third intermediate plate of the plurality of plates positioned between the first outermost plate and the first intermediate plate is equal to the effective area of the plurality of fluid inlet ports of each of the three centermost plates, and an effective area of the plurality of fluid inlet ports of a fourth intermediate plate of the plurality of plates positioned between the second outermost plate and the second intermediate plate is equal to the effective area of the plurality of fluid inlet ports of each of the three centermost plates.

12. A method of processing a glass sheet using the glass processing apparatus of claim 1, the conveyance path extending along the central axis, the method comprising conveying the glass sheet along the conveyance path.

13. The glass processing apparatus of claim 1, further comprising a fluid source connected to the plurality of air bars, the fluid source operable to provide fluid to each of the plurality of air bars and to emit fluid from the plurality of fluid outlet ports of each air bar.

16

14. The glass processing apparatus of claim 13, wherein the fluid source is operable to independently provide fluid to each of the plurality of air bars.

15. The glass processing apparatus of claim 13, wherein the fluid source is operable to emit fluid of differing pressures from the plurality of fluid outlet ports of one or more air bars of the plurality of air bars.

16. The glass processing apparatus of claim 15, wherein the fluid source is operable to emit fluid of a first pressure from the plurality of fluid outlet ports of two centermost air bars of the plurality of air bars and fluid of a second pressure from the plurality of fluid outlet ports of a first outermost air bar of the plurality of air bars and a second outermost air bar of the plurality of air bars, and wherein the first pressure is greater than the second pressure.

17. The glass processing apparatus of claim 16, wherein the fluid source is operable to emit fluid of a third pressure from the plurality of fluid outlet ports of a first of three air bars of the plurality of air bars positioned between the first outermost air bar and the two centermost air bars and from the plurality of fluid outlet ports of a second of three air bars of the plurality of air bars positioned between the second outermost air bar and the two centermost air bars, and wherein the third pressure is less than the second pressure.

18. The glass processing apparatus of claim 13, wherein the plurality of fluid inlet ports of each plate of the plurality of plates are provided without a fluid source connected to the plurality of fluid inlet ports.

19. A method of processing a glass sheet using the glass processing apparatus of claim 13, comprising emitting fluid from the plurality of fluid outlet ports of each of the plurality of air bars, thereby providing a cushion of fluid.

20. The method of claim 19, comprising floating the glass sheet on the cushion of fluid.

21. The method of claim 19, the conveyance path extending along the central axis, the method comprising conveying the glass sheet along the conveyance path on the cushion of fluid.

22. The method of claim 19, comprising passing at least a portion of the emitted fluid through the plurality of fluid inlet ports of each of the plurality of plates after providing the cushion of fluid.

23. The glass processing apparatus of claim 1, wherein the plurality of fluid outlet ports of one or more air bars of the plurality of air bars emit fluid at differing pressures.

24. The glass processing apparatus of claim 1, wherein the plurality of fluid outlet ports of two centermost air bars of the plurality of air bars emit fluid at a first pressure and the plurality of fluid outlet ports of a first outermost air bar of the plurality of air bars and a second outermost air bar of the plurality of air bars emit fluid at a second pressure, and wherein the first pressure is greater than the second pressure.

25. A glass processing apparatus to convey a glass sheet along a conveyance path, comprising:

a plurality of air bars spaced apart from each other along a first direction extending perpendicular to a central axis, each air bar comprising a surface with a plurality of fluid outlet ports;

a plurality of plates, at least one of the plurality of plates positioned between ones of the plurality of air bars, each plate comprising a surface with a plurality of fluid inlet ports, the plurality of air bars and the plurality of plates symmetrically arranged relative to the central axis; and

a fluid source connected to the plurality of air bars, wherein the fluid source is operable to emit fluid of

differing pressures from the plurality of fluid outlet
ports of one or more air bars of the plurality of air bars.

* * * * *