

US011224536B2

(12) **United States Patent**  
**Baker et al.**

(10) **Patent No.:** **US 11,224,536 B2**  
(45) **Date of Patent:** **\*Jan. 18, 2022**

(54) **DEVICE, SYSTEM AND METHOD OF REMOVING HEAT FROM SUBCUTANEOUS LIPID-RICH CELLS**

(71) Applicant: **Zeltiq Aesthetics, Inc.**, Pleasanton, CA (US)

(72) Inventors: **Mark William Baker**, Livermore, CA (US); **Joseph Coakley**, Dublin, CA (US); **Paul William Martens**, Pleasanton, CA (US); **Albert L. Ollerdessen**, Danville, CA (US); **William Patrick Pennybacker**, Livermore, CA (US); **Jesse N. Rosen**, Albany, CA (US); **Peter Yee**, San Ramon, CA (US); **John W. Allison**, Los Altos, CA (US)

(73) Assignee: **Zeltiq Aesthetics, Inc.**, Pleasanton, CA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 748 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **15/847,688**

(22) Filed: **Dec. 19, 2017**

(65) **Prior Publication Data**  
US 2018/0161197 A1 Jun. 14, 2018

**Related U.S. Application Data**  
(63) Continuation of application No. 14/205,794, filed on Mar. 12, 2014, now Pat. No. 9,861,520, which is a (Continued)

(51) **Int. Cl.**  
**A61F 7/00** (2006.01)  
**A61F 7/02** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **A61F 7/007** (2013.01); **A61F 2007/0022** (2013.01); **A61F 2007/0075** (2013.01); (Continued)

(58) **Field of Classification Search**  
CPC ..... **A61F 2007/029**  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

97,207 A 11/1869 Martz  
177,075 A 5/1876 Nicholson  
(Continued)

FOREIGN PATENT DOCUMENTS

AU 2011253768 A1 6/2012  
CA 2441489 A1 3/2005  
(Continued)

OTHER PUBLICATIONS

“ThermaCool Monopolar Capacitive Radiofrequency, the one choice for nonablative tissue tightening and contouring”, Thermage, Inc. Tech Brochure, Nov. 30, 2005, 8 pgs.  
(Continued)


*Primary Examiner* — Kaitlyn E Smith

(74) *Attorney, Agent, or Firm* — Perkins Coie LLP

(57) **ABSTRACT**

Devices, systems and methods for removing heat from subcutaneously disposed lipid-rich cells are disclosed. In selected embodiments, suction and/or heat removal sources are coupled to an applicator. The applicator includes a flexible portion and a rigid portion. The rigid portion includes a thermally conductive plate and a frame coupling the thermally conductive plate and the flexible portion. An interior cavity of the applicator is in fluid communication with the suction source, and the frame maintains contiguous engagement between the heat removal source and the thermally conductive plate.

**20 Claims, 31 Drawing Sheets**



<b>Related U.S. Application Data</b>		4,906,463 A	3/1990	Cleary et al.
continuation of application No. 12/772,040, filed on		4,930,317 A	6/1990	Klein
Apr. 30, 2010, now Pat. No. 8,702,774.		4,935,345 A	6/1990	Guilbeau et al.
		4,961,422 A	10/1990	Marchosky et al.
		4,962,761 A	10/1990	Golden
		4,990,144 A	2/1991	Blott et al.
(60)	Provisional application No. 61/174,487, filed on Apr.	5,007,433 A	4/1991	Hermesdoerffer et al.
	30, 2009.	5,018,521 A	5/1991	Campbell et al.
		5,024,650 A	6/1991	Hagiwara et al.
(52)	<b>U.S. Cl.</b>	5,065,752 A	11/1991	Sessions et al.
	CPC ..... <i>A61F 2007/0093</i> (2013.01); <i>A61F</i>	5,069,208 A	12/1991	Noppel et al.
	<i>2007/0096</i> (2013.01); <i>A61F 2007/029</i>	5,084,671 A	1/1992	Miyata et al.
	(2013.01)	5,108,390 A	4/1992	Potocky et al.
		5,119,674 A	6/1992	Nielsen
		5,139,496 A	8/1992	Hed
(56)	<b>References Cited</b>	5,143,063 A	9/1992	Fellner
U.S. PATENT DOCUMENTS		5,148,804 A	9/1992	Hill et al.
		5,158,070 A	10/1992	Dory
		5,169,384 A	12/1992	Bosniak et al.
		5,197,466 A	3/1993	Marchosky et al.
681,806 A	9/1901 Mignault et al.	5,207,674 A	5/1993	Hamilton
889,810 A	6/1908 Robinson et al.	5,221,726 A	6/1993	Dabi et al.
1,093,868 A	4/1914 Leighty	5,264,234 A	11/1993	Windhab et al.
2,516,491 A	7/1950 Swastek	5,277,030 A	1/1994	Miller
2,521,780 A	9/1950 Dodd et al.	5,314,423 A	5/1994	Seney et al.
2,726,658 A	12/1955 Chessey	5,327,886 A	7/1994	Chiu
2,766,619 A	10/1956 Tribus et al.	5,330,745 A	7/1994	Mcdow et al.
2,851,602 A	9/1958 Cramwinckel et al.	5,333,460 A	8/1994	Lewis et al.
3,093,135 A	6/1963 Hirschhorn	5,334,131 A	8/1994	Omandam et al.
3,132,688 A	5/1964 Nowak	5,336,616 A	8/1994	Livesey et al.
3,133,539 A	5/1964 William et al.	5,339,541 A	8/1994	Owens
3,282,267 A	11/1966 Eidus	5,342,617 A	8/1994	Gold et al.
3,341,230 A	9/1967 Louis	5,351,677 A	10/1994	Kami et al.
3,502,080 A	3/1970 Hirschhorn	5,358,467 A	10/1994	Milstein et al.
3,587,577 A	6/1971 Zubkov et al.	5,362,966 A	11/1994	Rosenthal et al.
3,591,645 A	7/1971 Selwitz	5,363,347 A	11/1994	Nguyen
3,692,338 A	9/1972 Didier	5,372,608 A	12/1994	Johnson
3,703,897 A	11/1972 Mack et al.	5,386,837 A	2/1995	Sterzer
3,710,784 A	1/1973 Taylor	5,411,541 A	5/1995	Bell et al.
3,786,814 A	1/1974 Armao	5,427,772 A	6/1995	Hagan et al.
3,827,436 A	8/1974 Andera et al.	5,433,717 A	7/1995	Rubinsky et al.
3,942,519 A	3/1976 Shock	5,456,703 A	10/1995	Beeuwkes, III et al.
3,948,269 A	4/1976 Zimmer	5,472,416 A	12/1995	Blugerman et al.
3,986,385 A	10/1976 Johnston et al.	5,486,207 A	1/1996	Mahawili
3,993,053 A	11/1976 Grossan	5,497,596 A	3/1996	Zatkulak
4,002,221 A	1/1977 Buchalter	5,501,655 A	3/1996	Rolt et al.
4,008,910 A	2/1977 Roche	5,505,726 A	4/1996	Meserol
4,026,299 A	5/1977 Sauder	5,505,730 A	4/1996	Edwards et al.
4,140,130 A	2/1979 Storm	5,507,790 A	4/1996	Weiss
4,149,529 A	4/1979 Copeland et al.	5,514,105 A	5/1996	Goodman, Jr. et al.
4,178,429 A	12/1979 Scheffer	5,514,170 A	5/1996	Mauch
4,202,336 A	5/1980 Van Gerven	5,516,505 A	5/1996	Mcdow
4,266,043 A	5/1981 Fujii et al.	5,531,742 A	7/1996	Barken
4,269,068 A	5/1981 Molina	5,558,376 A	9/1996	Woehl
4,381,009 A	4/1983 Del Bon	5,562,604 A	10/1996	Yablon et al.
4,396,011 A	8/1983 Mack et al.	5,571,801 A	11/1996	Segall et al.
4,459,854 A	7/1984 Richardson et al.	5,575,812 A	11/1996	Owens et al.
4,470,263 A	9/1984 Lehovec et al.	5,603,221 A	2/1997	Maytal
4,483,341 A	11/1984 Witteles	5,628,769 A	5/1997	Saringer
4,528,979 A	7/1985 Marchenko et al.	5,634,890 A	6/1997	Morris
4,531,524 A	7/1985 Mioduski	5,634,940 A	6/1997	Panyard
4,548,212 A	10/1985 Leung	5,647,051 A	7/1997	Neer
4,555,313 A	11/1985 Duchane et al.	5,647,868 A	7/1997	Chinn
4,585,002 A	4/1986 Kissin	5,650,450 A	7/1997	Lovette et al.
4,603,076 A	7/1986 Bowditch et al.	5,651,773 A	7/1997	Perry et al.
4,614,191 A	9/1986 Perler et al.	5,654,279 A	8/1997	Rubinsky et al.
4,644,955 A	2/1987 Mioduski	5,654,546 A	8/1997	Lindsay et al.
4,664,110 A	5/1987 Schanzlin	5,660,836 A	8/1997	Knowlton et al.
4,700,701 A	10/1987 Montaldi	5,665,053 A	9/1997	Jacobs
4,718,429 A	1/1988 Smidt	5,672,172 A	9/1997	Zupkas
4,741,338 A	5/1988 Miyamae	5,700,284 A	12/1997	Owens et al.
4,758,217 A	7/1988 Gueret	5,725,483 A	3/1998	Podolsky
4,764,463 A	8/1988 Mason et al.	5,733,280 A	3/1998	Avitall
4,802,475 A	2/1989 Weshahy	5,741,248 A	4/1998	Stern et al.
4,832,022 A	5/1989 Tjulkov et al.	5,746,702 A	5/1998	Gelfgat et al.
4,846,176 A	7/1989 Golden	5,746,736 A	5/1998	Tankovich
4,850,340 A	7/1989 Onishi	5,755,663 A	5/1998	Larsen et al.
4,869,250 A	9/1989 Bitterly	5,755,753 A	5/1998	Knowlton et al.
4,880,564 A	11/1989 Abel et al.	5,755,755 A	5/1998	Panyard
4,905,697 A	3/1990 Heggs et al.			



(56)

## References Cited

## U.S. PATENT DOCUMENTS

5,759,182 A	6/1998	Varney et al.	6,387,380 B1	5/2002	Knowlton
5,759,764 A	6/1998	Polovina et al.	6,401,722 B1	6/2002	Krag
5,769,879 A	6/1998	Richards et al.	6,405,090 B1	6/2002	Knowlton
5,785,955 A	7/1998	Fischer	6,413,255 B1	7/2002	Stern
5,792,080 A	8/1998	Ookawa et al.	6,425,912 B1	7/2002	Knowlton
5,800,490 A	9/1998	Patz et al.	6,426,445 B1	7/2002	Young et al.
5,802,865 A	9/1998	Strauss	6,430,446 B1	8/2002	Knowlton
5,814,040 A	9/1998	Nelson et al.	6,430,956 B1	8/2002	Haas et al.
5,817,050 A	10/1998	Klein et al.	6,438,424 B1	8/2002	Knowlton
5,817,149 A	10/1998	Owens et al.	6,438,954 B1	8/2002	Goetz et al.
5,817,150 A	10/1998	Owens et al.	6,438,964 B1	8/2002	Giblin
5,830,208 A	11/1998	Muller et al.	6,453,202 B1	9/2002	Knowlton
5,833,685 A	11/1998	Tortal et al.	6,458,888 B1	10/2002	Hood et al.
5,844,013 A	12/1998	Kenndoff et al.	6,461,378 B1	10/2002	Knowlton
5,853,364 A	12/1998	Baker et al.	6,470,216 B1	10/2002	Knowlton
5,865,841 A	2/1999	Kolen et al.	6,471,693 B1	10/2002	Carroll et al.
5,871,524 A	2/1999	Knowlton	6,475,211 B2	11/2002	Chess et al.
5,871,526 A	2/1999	Gibbs et al.	6,478,811 B1	11/2002	Dobak, III et al.
5,885,211 A	3/1999	Eppstein et al.	6,494,844 B1	12/2002	Van Bladel et al.
5,891,617 A	4/1999	Watson et al.	6,497,721 B2	12/2002	Ginsburg et al.
5,895,418 A	4/1999	Saringer	6,508,831 B1	1/2003	Kushnir
5,901,707 A	5/1999	Goncalves	6,514,244 B2	2/2003	Pope et al.
5,902,256 A	5/1999	Benaron	6,519,964 B2	2/2003	Bieberich
5,919,219 A	7/1999	Knowlton et al.	6,523,354 B1	2/2003	Tolbert
5,944,748 A	8/1999	Mager et al.	6,527,765 B2	3/2003	Kelman et al.
5,948,011 A	9/1999	Knowlton et al.	6,527,798 B2	3/2003	Ginsburg et al.
5,954,680 A	9/1999	Augustine et al.	6,544,248 B1	4/2003	Bass
5,964,092 A	10/1999	Tozuka et al.	6,547,811 B1	4/2003	Becker et al.
5,964,749 A	10/1999	Eckhouse et al.	6,548,297 B1	4/2003	Kuri-Harcuch et al.
5,967,976 A	10/1999	Larsen et al.	6,551,255 B2	4/2003	Van Bladel et al.
5,980,561 A	11/1999	Kolen et al.	6,551,341 B2	4/2003	Boylan et al.
5,986,167 A	11/1999	Arteman et al.	6,551,348 B1	4/2003	Blalock et al.
5,989,286 A	11/1999	Owens et al.	6,551,349 B2	4/2003	Lasheras et al.
5,997,530 A	12/1999	Nelson et al.	6,569,189 B1	5/2003	Augustine et al.
6,017,337 A	1/2000	Pira	6,585,652 B2	7/2003	Lang et al.
6,023,932 A	2/2000	Johnston	6,592,577 B2	7/2003	Abboud et al.
6,032,675 A	3/2000	Rubinsky	6,605,080 B1	8/2003	Altshuler et al.
6,039,694 A	3/2000	Larson et al.	6,607,498 B2	8/2003	Eshel
6,041,787 A	3/2000	Rubinsky	6,620,187 B2	9/2003	Carson et al.
6,047,215 A	4/2000	McClure et al.	6,620,188 B1	9/2003	Ginsburg et al.
6,049,927 A	4/2000	Thomas et al.	6,620,189 B1	9/2003	Machold et al.
6,051,159 A	4/2000	Hao et al.	6,623,430 B1	9/2003	Slayton et al.
6,071,239 A	6/2000	Cribbs et al.	6,626,854 B2	9/2003	Friedman et al.
6,074,415 A	6/2000	Der Ovanesian	6,632,219 B1	10/2003	Baranov et al.
6,093,230 A	7/2000	Johnson et al.	6,635,053 B1	10/2003	Lalonde et al.
6,102,885 A	8/2000	Bass	6,643,535 B2	11/2003	Damasco et al.
6,104,952 A	8/2000	Tu et al.	6,645,162 B2	11/2003	Friedman et al.
6,104,959 A	8/2000	Spertell et al.	6,645,229 B2	11/2003	Matsumura et al.
6,106,517 A	8/2000	Zupkas	6,645,232 B2	11/2003	Carson
6,113,558 A	9/2000	Rosenschein et al.	6,648,904 B2	11/2003	Altshuler et al.
6,113,559 A	9/2000	Klopotek	6,656,208 B2	12/2003	Grahn et al.
6,113,626 A	9/2000	Clifton et al.	6,660,027 B2	12/2003	Gruszecki et al.
6,120,519 A	9/2000	Weber et al.	6,662,054 B2	12/2003	Kreindel et al.
6,139,544 A	10/2000	Mikus et al.	6,682,550 B2	1/2004	Clifton et al.
6,150,148 A	11/2000	Nanda et al.	6,685,731 B2	2/2004	Kushnir et al.
6,151,735 A	11/2000	Koby et al.	6,694,170 B1	2/2004	Mikus et al.
6,152,952 A	11/2000	Owens et al.	6,695,874 B2	2/2004	Machold et al.
6,171,301 B1	1/2001	Nelson et al.	6,697,670 B2	2/2004	Chornenky
6,180,867 B1	1/2001	Hedengren et al.	6,699,237 B2	3/2004	Weber et al.
6,226,996 B1	5/2001	Weber et al.	6,699,266 B2	3/2004	Lachenbruch et al.
6,241,753 B1	6/2001	Knowlton	6,699,267 B2	3/2004	Voorhees et al.
6,264,649 B1	7/2001	Whitcroft et al.	6,718,785 B2	4/2004	Bieberich
6,273,884 B1	8/2001	Altshuler et al.	6,741,895 B1	5/2004	Gafni et al.
6,290,988 B1	9/2001	Van Vilsteren et al.	6,743,222 B2	6/2004	Durkin et al.
6,311,090 B1	10/2001	Knowlton	6,746,474 B2	6/2004	Saadat
6,311,497 B1	11/2001	Chung	6,749,624 B2	6/2004	Knowlton
6,312,453 B1	11/2001	Stefanile et al.	6,764,493 B1	7/2004	Weber et al.
6,350,276 B1	2/2002	Knowlton	6,764,502 B2	7/2004	Bieberich
6,354,297 B1	3/2002	Eiseman	6,789,545 B2	9/2004	Littrup et al.
6,357,907 B1	3/2002	Cleveland et al.	6,795,728 B2	9/2004	Chornenky et al.
6,375,673 B1	4/2002	Clifton et al.	6,820,961 B2	11/2004	Johnson
6,377,854 B1	4/2002	Knowlton	6,821,274 B2	11/2004	McHale et al.
6,377,855 B1	4/2002	Knowlton	6,840,955 B2	1/2005	Ein
6,381,497 B1	4/2002	Knowlton	6,849,075 B2	2/2005	Bertolero et al.
6,381,498 B1	4/2002	Knowlton	6,878,144 B2	4/2005	Altshuler et al.
			6,889,090 B2	5/2005	Kreindel
			6,892,099 B2	5/2005	Jaafar et al.
			6,904,956 B2	6/2005	Noel
			6,918,903 B2	7/2005	Bass



(56)

## References Cited

## U.S. PATENT DOCUMENTS

6,927,316 B1	8/2005	Faries, Jr. et al.	8,672,848 B2	3/2014	Slayton et al.
6,942,022 B2	9/2005	Blangetti et al.	8,676,332 B2	3/2014	Fahey
6,945,942 B2	9/2005	Van Bladel et al.	8,690,778 B2	4/2014	Slayton et al.
6,948,903 B2	9/2005	Ablabutyan et al.	8,690,779 B2	4/2014	Slayton et al.
6,969,399 B2	11/2005	Schock et al.	8,690,780 B2	4/2014	Slayton et al.
7,005,558 B1	2/2006	Johansson et al.	8,702,774 B2	4/2014	Baker et al.
7,006,874 B2	2/2006	Knowlton et al.	8,758,215 B2	6/2014	Legendre et al.
7,022,121 B2	4/2006	Stern et al.	8,764,693 B1	7/2014	Graham et al.
7,037,326 B2	5/2006	Lee	8,834,547 B2	9/2014	Anderson et al.
7,054,685 B2	5/2006	Dimmer et al.	9,149,322 B2	10/2015	Knowlton
7,060,061 B2	6/2006	Altshuler et al.	10,765,552 B2 *	9/2020	Root ..... A61F 7/007
7,077,858 B2	7/2006	Fletcher et al.	2001/0005791 A1	6/2001	Ginsburg et al.
7,081,111 B2	7/2006	Svaasand et al.	2001/0007952 A1	7/2001	Shimizu
7,083,612 B2	8/2006	Littrup et al.	2001/0023364 A1	9/2001	Ahn
7,096,204 B1	8/2006	Chen et al.	2001/0031459 A1	10/2001	Fahy et al.
7,112,712 B1	9/2006	Ancell	2001/0039439 A1	11/2001	Elkins et al.
7,115,123 B2	10/2006	Knowlton et al.	2001/0045104 A1	11/2001	Bailey, Sr. et al.
7,141,049 B2	11/2006	Stern et al.	2001/0047196 A1	11/2001	Ginsburg et al.
7,183,360 B2	2/2007	Daniel et al.	2002/0026226 A1	2/2002	Ein
7,189,252 B2	3/2007	Krueger	2002/0032473 A1	3/2002	Kushnir et al.
7,192,426 B2	3/2007	Baust et al.	2002/0042607 A1	4/2002	Palmer et al.
7,204,832 B2	4/2007	Altshuler et al.	2002/0049483 A1	4/2002	Knowlton
7,220,778 B2	5/2007	Anderson et al.	2002/0058975 A1	5/2002	Bieberich
7,229,436 B2	6/2007	Stern et al.	2002/0062142 A1	5/2002	Knowlton
7,258,674 B2	8/2007	Cribbs et al.	2002/0068338 A1	6/2002	Nanda et al.
7,267,675 B2	9/2007	Stern et al.	2002/0068874 A1	6/2002	Zuckerwar et al.
7,276,058 B2	10/2007	Altshuler et al.	2002/0082668 A1	6/2002	Ingman
7,318,821 B2	1/2008	Lalonde et al.	2002/0103520 A1	8/2002	Latham
7,331,951 B2	2/2008	Eshel et al.	2002/0107558 A1	8/2002	Clifton et al.
7,347,855 B2	3/2008	Eshel et al.	2002/0117293 A1	8/2002	Campbell
7,367,341 B2	5/2008	Anderson et al.	2002/0120315 A1	8/2002	Furuno et al.
7,532,201 B2	5/2009	Quistgaard et al.	2002/0128648 A1	9/2002	Weber et al.
7,572,268 B2	8/2009	Babaev	2002/0151830 A1	10/2002	Kahn
7,604,632 B2	10/2009	Howlett et al.	2002/0151887 A1	10/2002	Stern et al.
7,613,523 B2	11/2009	Eggers et al.	2002/0156509 A1	10/2002	Cheung
7,615,016 B2	11/2009	Barthe et al.	2002/0188286 A1	12/2002	Quijano et al.
7,713,266 B2	5/2010	Elkins et al.	2002/0198518 A1	12/2002	Mikus et al.
7,780,656 B2	8/2010	Tankovich	2003/0032900 A1	2/2003	Ella
7,799,018 B2	9/2010	Goulko	2003/0044764 A1	3/2003	Soane et al.
7,824,437 B1	11/2010	Saunders	2003/0055414 A1	3/2003	Altshuler et al.
7,828,831 B1	11/2010	Tanhehco et al.	2003/0062040 A1	4/2003	Lurie et al.
7,850,683 B2	12/2010	Elkins et al.	2003/0069618 A1	4/2003	Smith, III et al.
7,854,754 B2	12/2010	Ting et al.	2003/0077326 A1	4/2003	Newton et al.
7,862,558 B2	1/2011	Elkins et al.	2003/0077329 A1	4/2003	Kipp et al.
RE42,277 E	4/2011	Jaafar et al.	2003/0079488 A1	5/2003	Bieberich
7,938,824 B2	5/2011	Chornenky et al.	2003/0100936 A1	5/2003	Altshuler et al.
7,959,657 B1	6/2011	Harsy et al.	2003/0109908 A1	6/2003	Lachenbruch et al.
7,963,959 B2	6/2011	Da Silva et al.	2003/0109910 A1	6/2003	Lachenbruch et al.
7,967,763 B2	6/2011	Deem et al.	2003/0109911 A1	6/2003	Lachenbruch et al.
7,993,330 B2	8/2011	Goulko	2003/0114885 A1	6/2003	Nova et al.
7,998,137 B2	8/2011	Elkins et al.	2003/0120268 A1	6/2003	Bertolero et al.
RE42,835 E	10/2011	Chornenky et al.	2003/0125649 A1	7/2003	McIntosh et al.
RE43,009 E	12/2011	Chornenky et al.	2003/0187488 A1	10/2003	Kreindel et al.
8,133,180 B2	3/2012	Slayton et al.	2003/0199226 A1	10/2003	Sommer et al.
8,133,191 B2	3/2012	Rosenberg et al.	2003/0199859 A1	10/2003	Altshuler et al.
8,192,474 B2	6/2012	Levinson	2003/0220594 A1	11/2003	Halvorson et al.
8,246,611 B2	8/2012	Paithankar et al.	2003/0220635 A1	11/2003	Knowlton et al.
8,275,442 B2	9/2012	Allison	2003/0220674 A1	11/2003	Anderson et al.
8,285,390 B2	10/2012	Levinson et al.	2003/0236487 A1	12/2003	Knowlton
8,333,700 B1	12/2012	Barthe et al.	2004/0002705 A1	1/2004	Knowlton et al.
8,337,539 B2	12/2012	Ting et al.	2004/0006328 A1	1/2004	Anderson
8,366,622 B2	2/2013	Slayton et al.	2004/0009936 A1	1/2004	Tang et al.
8,372,130 B2	2/2013	Young et al.	2004/0024437 A1	2/2004	Machold et al.
8,397,518 B1	3/2013	Vistakula et al.	2004/0030332 A1	2/2004	Knowlton et al.
8,414,631 B2	4/2013	Quisenberry et al.	2004/0034341 A1	2/2004	Altshuler et al.
8,433,400 B2	4/2013	Prushinskaya et al.	2004/0039312 A1	2/2004	Hillstead et al.
8,506,486 B2	8/2013	Slayton et al.	2004/0044384 A1	3/2004	Leber et al.
8,523,775 B2	9/2013	Barthe et al.	2004/0049178 A1	3/2004	Abboud et al.
8,523,791 B2	9/2013	Castel	2004/0073079 A1	4/2004	Altshuler et al.
8,523,927 B2	9/2013	Levinson et al.	2004/0074629 A1	4/2004	Noel
8,535,228 B2	9/2013	Slayton et al.	2004/0077977 A1	4/2004	Ella et al.
8,603,073 B2	12/2013	Allison	2004/0082886 A1	4/2004	Timpson
8,636,665 B2	1/2014	Slayton et al.	2004/0093042 A1	5/2004	Altshuler et al.
8,641,622 B2	2/2014	Barthe et al.	2004/0104012 A1	6/2004	Zhou et al.
8,663,112 B2	3/2014	Slayton et al.	2004/0106867 A1	6/2004	Eshel et al.
			2004/0133251 A1	7/2004	Altshuler et al.
			2004/0162596 A1	8/2004	Altshuler et al.
			2004/0176667 A1	9/2004	Mihai et al.
			2004/0186535 A1	9/2004	Knowlton



(56)

## References Cited

## U.S. PATENT DOCUMENTS

2004/0199226 A1	10/2004	Shaddock	2007/0249519 A1	10/2007	Guha et al.
2004/0206365 A1	10/2004	Knowlton	2007/0255187 A1	11/2007	Branch
2004/0210214 A1	10/2004	Knowlton	2007/0255274 A1	11/2007	Stern et al.
2004/0210287 A1	10/2004	Greene	2007/0255362 A1	11/2007	Levinson et al.
2004/0215294 A1	10/2004	Littrup et al.	2007/0265585 A1	11/2007	Joshi et al.
2004/0249427 A1	12/2004	Nabils et al.	2007/0265614 A1	11/2007	Stern et al.
2004/0259855 A1	12/2004	Anderson et al.	2007/0270925 A1	11/2007	Levinson
2004/0260209 A1	12/2004	Ella et al.	2007/0282249 A1	12/2007	Quisenberry et al.
2004/0260210 A1	12/2004	Ella et al.	2007/0282318 A1	12/2007	Spooner et al.
2004/0260211 A1	12/2004	Maalouf	2008/0014627 A1	1/2008	Merchant et al.
2004/0267339 A1	12/2004	Yon et al.	2008/0046047 A1	2/2008	Jacobs
2005/0010197 A1	1/2005	Lau et al.	2008/0058784 A1	3/2008	Manstein et al.
2005/0033957 A1	2/2005	Enokida	2008/0077201 A1	3/2008	Levinson et al.
2005/0049526 A1	3/2005	Baer	2008/0077202 A1	3/2008	Levinson
2005/0049543 A1	3/2005	Anderson et al.	2008/0077211 A1	3/2008	Levinson et al.
2005/0049661 A1	3/2005	Koffroth	2008/0139901 A1	6/2008	Altshuler et al.
2005/0113725 A1	5/2005	Masuda	2008/0140061 A1	6/2008	Toubia et al.
2005/0143781 A1	6/2005	Carbunaru et al.	2008/0140371 A1	6/2008	Warner
2005/0145372 A1	7/2005	Noel	2008/0161892 A1	7/2008	Mercuro et al.
2005/0149153 A1	7/2005	Nakase et al.	2008/0183164 A1	7/2008	Elkins et al.
2005/0154314 A1	7/2005	Quistgaard	2008/0188915 A1	8/2008	Mills et al.
2005/0154431 A1	7/2005	Quistgaard et al.	2008/0248554 A1	10/2008	Merchant et al.
2005/0159986 A1	7/2005	Breeland et al.	2008/0269851 A1	10/2008	Deem et al.
2005/0182462 A1	8/2005	Chornenky et al.	2008/0287839 A1	11/2008	Rosen et al.
2005/0187495 A1	8/2005	Quistgaard et al.	2008/0300529 A1	12/2008	Reinstein
2005/0187597 A1	8/2005	Vanderschuit	2008/0312651 A1	12/2008	Pope et al.
2005/0203446 A1	9/2005	Takashima	2009/0012434 A1	1/2009	Anderson
2005/0215987 A1	9/2005	Slatkine	2009/0018623 A1	1/2009	Levinson et al.
2005/0222565 A1	10/2005	Manstein	2009/0018624 A1	1/2009	Levinson et al.
2005/0251117 A1	11/2005	Anderson et al.	2009/0018625 A1	1/2009	Levinson et al.
2005/0251120 A1	11/2005	Anderson et al.	2009/0018626 A1	1/2009	Levinson et al.
2005/0261753 A1	11/2005	Littrup et al.	2009/0018627 A1	1/2009	Levinson et al.
2005/0277859 A1	12/2005	Carlsmith et al.	2009/0024023 A1	1/2009	Welches et al.
2005/0283144 A1	12/2005	Shiono et al.	2009/0076488 A1	3/2009	Welches et al.
2006/0030778 A1	2/2006	Mendlein et al.	2009/0112134 A1	4/2009	Avni
2006/0035380 A1	2/2006	Saint-Leger	2009/0118722 A1	5/2009	Ebbbers et al.
2006/0036300 A1	2/2006	Kreindel	2009/0149929 A1	6/2009	Levinson et al.
2006/0041704 A1	2/2006	Choi	2009/0149930 A1	6/2009	Schenck
2006/0074313 A1	4/2006	Slayton et al.	2009/0171253 A1	7/2009	Davenport
2006/0079852 A1	4/2006	Bubb et al.	2009/0171334 A1	7/2009	Elkins et al.
2006/0094988 A1	5/2006	Tosaya et al.	2009/0221938 A1	9/2009	Rosenberg et al.
2006/0106836 A1	5/2006	Masugi et al.	2009/0226424 A1	9/2009	Hsu
2006/0111613 A1	5/2006	Boutillette et al.	2009/0276018 A1	11/2009	Brader
2006/0122509 A1	6/2006	Desilets	2009/0281464 A1	11/2009	Cioanta et al.
2006/0189964 A1	8/2006	Anderson et al.	2009/0299234 A1	12/2009	Cho et al.
2006/0195168 A1	8/2006	Dunbar et al.	2009/0306749 A1	12/2009	Mulindwa
2006/0200063 A1	9/2006	Munro et al.	2009/0312676 A1	12/2009	Rousso et al.
2006/0206040 A1	9/2006	Greenberg et al.	2009/0312693 A1	12/2009	Thapliyal et al.
2006/0206110 A1	9/2006	Knowlton et al.	2009/0326621 A1	12/2009	El-Galley
2006/0234899 A1	10/2006	Nekmard et al.	2010/0015190 A1	1/2010	Hassler
2006/0259102 A1	11/2006	Slatkine	2010/0028969 A1	2/2010	Mueller et al.
2006/0265032 A1	11/2006	Hennings et al.	2010/0030306 A1	2/2010	Edelman et al.
2006/0270745 A1	11/2006	Hunt et al.	2010/0036295 A1	2/2010	Altshuler et al.
2006/0293734 A1	12/2006	Scott et al.	2010/0042087 A1	2/2010	Goldboss et al.
2007/0010811 A1	1/2007	Stern et al.	2010/0049178 A1	2/2010	Deem et al.
2007/0010861 A1	1/2007	Anderson et al.	2010/0081971 A1	4/2010	Allison
2007/0032561 A1	2/2007	Lin et al.	2010/0087806 A1	4/2010	Da Silva et al.
2007/0038156 A1	2/2007	Rosenberg	2010/0152824 A1	6/2010	Allison
2007/0055156 A1	3/2007	Desilets et al.	2010/0168726 A1	7/2010	Brookman
2007/0055173 A1	3/2007	DeLonzor et al.	2010/0179531 A1	7/2010	Nebrigic et al.
2007/0055179 A1	3/2007	Deem et al.	2010/0198064 A1	8/2010	Perl et al.
2007/0055180 A1	3/2007	Deem et al.	2010/0217349 A1	8/2010	Fahey et al.
2007/0055181 A1	3/2007	Deem et al.	2010/0241023 A1	9/2010	Gilbert
2007/0073367 A1	3/2007	Jones et al.	2010/0268220 A1	10/2010	Johnson et al.
2007/0078502 A1	4/2007	Weber et al.	2010/0280582 A1	11/2010	Baker et al.
2007/0100398 A1	5/2007	Sloan	2011/0009860 A1	1/2011	Chornenky et al.
2007/0106342 A1	5/2007	Schumann	2011/0040235 A1	2/2011	Castel
2007/0129714 A1	6/2007	Elkins et al.	2011/0040299 A1*	2/2011	Kim ..... A61N 5/04
2007/0135876 A1	6/2007	Weber			606/33
2007/0141265 A1	6/2007	Thomson	2011/0046523 A1	2/2011	Altshuler et al.
2007/0179482 A1	8/2007	Anderson	2011/0060323 A1	3/2011	Baust et al.
2007/0198071 A1	8/2007	Ting et al.	2011/0066083 A1	3/2011	Tosaya et al.
2007/0219540 A1	9/2007	Masotti et al.	2011/0066216 A1	3/2011	Ting et al.
2007/0239075 A1	10/2007	Rosenberg et al.	2011/0077557 A1	3/2011	Wing et al.
2007/0239150 A1	10/2007	Zvuloni et al.	2011/0077723 A1	3/2011	Parish et al.
			2011/0112405 A1	5/2011	Barthe et al.
			2011/0112520 A1	5/2011	Kreindel
			2011/0144631 A1	6/2011	Elkins et al.
			2011/0152849 A1	6/2011	Baust et al.



(56)

**References Cited****U.S. PATENT DOCUMENTS**

2011/0172651 A1 7/2011 Altshuler et al.  
 2011/0189129 A1 8/2011 Qiu et al.  
 2011/0196395 A1 8/2011 Maschke  
 2011/0196438 A1 8/2011 Mnozil et al.  
 2011/0202048 A1 8/2011 Nebrigic et al.  
 2011/0238050 A1 9/2011 Allison et al.  
 2011/0238051 A1 9/2011 Levinson et al.  
 2011/0257642 A1 10/2011 Griggs, III  
 2011/0288537 A1 11/2011 Halaka  
 2011/0300079 A1 12/2011 Martens et al.  
 2011/0301585 A1 12/2011 Goulko  
 2011/0313411 A1 12/2011 Anderson et al.  
 2011/0313412 A1 12/2011 Kim et al.  
 2012/0010609 A1 1/2012 Deem et al.  
 2012/0016239 A1 1/2012 Barthe et al.  
 2012/0022518 A1 1/2012 Levinson  
 2012/0022622 A1 1/2012 Johnson et al.  
 2012/0035475 A1 2/2012 Barthe et al.  
 2012/0035476 A1 2/2012 Barthe et al.  
 2012/0046547 A1 2/2012 Barthe et al.  
 2012/0053458 A1 3/2012 Barthe et al.  
 2012/0065629 A1 3/2012 Elkins et al.  
 2012/0083862 A1 4/2012 Altshuler et al.  
 2012/0101549 A1 4/2012 Schumann  
 2012/0109041 A1 5/2012 Munz  
 2012/0158100 A1 6/2012 Schomacker  
 2012/0209363 A1 8/2012 Williams, III et al.  
 2012/0233736 A1 9/2012 Tepper et al.  
 2012/0239123 A1 9/2012 Weber et al.  
 2012/0253416 A1 10/2012 Erez et al.  
 2012/0259322 A1 10/2012 Fourkas et al.  
 2012/0277674 A1 11/2012 Clark, III et al.  
 2012/0310232 A1 12/2012 Erez  
 2013/0018236 A1 1/2013 Altshuler et al.  
 2013/0019374 A1 1/2013 Schwartz  
 2013/0066309 A1 3/2013 Levinson  
 2013/0073017 A1 3/2013 Liu et al.  
 2013/0079684 A1 3/2013 Rosen et al.  
 2013/0116758 A1 5/2013 Levinson et al.  
 2013/0116759 A1 5/2013 Levinson et al.  
 2013/0150844 A1 6/2013 Deem et al.  
 2013/0158440 A1 6/2013 Allison  
 2013/0158636 A1 6/2013 Ting et al.  
 2013/0166003 A1 6/2013 Johnson et al.  
 2013/0190744 A1 7/2013 Avram et al.  
 2013/0238062 A1 9/2013 Ron Edoute et al.  
 2013/0245507 A1 9/2013 Khorassani Zadeh  
 2013/0253384 A1 9/2013 Anderson et al.  
 2013/0253493 A1 9/2013 Anderson et al.  
 2013/0253494 A1 9/2013 Anderson et al.  
 2013/0253495 A1 9/2013 Anderson et al.  
 2013/0253496 A1 9/2013 Anderson et al.  
 2013/0303904 A1 11/2013 Barthe et al.  
 2013/0303905 A1 11/2013 Barthe et al.  
 2013/0331914 A1 12/2013 Lee et al.  
 2014/0005759 A1 1/2014 Fahey et al.  
 2014/0005760 A1 1/2014 Levinson et al.  
 2014/0067025 A1 3/2014 Levinson et al.  
 2014/0142469 A1 5/2014 Britva et al.  
 2014/0200487 A1 7/2014 Ramdas et al.  
 2014/0200488 A1 7/2014 Seo et al.  
 2014/0222121 A1 8/2014 Spence et al.  
 2014/0277219 A1 9/2014 Nanda  
 2014/0277302 A1 9/2014 Weber et al.  
 2014/0277303 A1 9/2014 Biser et al.  
 2014/0303697 A1 10/2014 Anderson et al.  
 2015/0209174 A1 7/2015 Abreu  
 2015/0216719 A1 8/2015 DeBenedictis et al.  
 2015/0216720 A1 8/2015 DeBenedictis et al.  
 2015/0216816 A1 8/2015 O'Neil et al.  
 2015/0223975 A1 8/2015 Anderson et al.  
 2015/0283022 A1 10/2015 Lee et al.  
 2015/0328077 A1 11/2015 Levinson  
 2015/0335468 A1 11/2015 Rose et al.  
 2015/0342780 A1 12/2015 Levinson et al.

2016/0051308 A1 2/2016 Pennybacker et al.  
 2016/0051401 A1 2/2016 Yee et al.  
 2016/0135985 A1 5/2016 Anderson  
 2016/0324684 A1 11/2016 Levinson et al.  
 2017/0007309 A1 1/2017 DeBenedictis et al.  
 2017/0079833 A1 3/2017 Frangineas, Jr. et al.  
 2017/0105869 A1 4/2017 Frangineas, Jr. et al.  
 2017/0165105 A1 6/2017 Anderson et al.  
 2017/0196731 A1 7/2017 DeBenedictis et al.  
 2017/0239079 A1 8/2017 Root et al.  
 2017/0325992 A1 11/2017 DeBenedictis et al.  
 2017/0325993 A1 11/2017 Jimenez Lozano et al.  
 2017/0326042 A1 11/2017 Zeng et al.  
 2017/0326346 A1 11/2017 Jimenez Lozano et al.  
 2018/0185081 A1 7/2018 O'neil et al.  
 2018/0185189 A1 7/2018 Weber et al.  
 2018/0263677 A1 9/2018 Hilton et al.  
 2018/0271767 A1 9/2018 Jimenez Lozano et al.  
 2018/0310950 A1 11/2018 Yee et al.

**FOREIGN PATENT DOCUMENTS**

CA 2585214 A1 10/2007  
 CH 333982 A 11/1958  
 CN 86200604 U 10/1987  
 CN 2514795 Y 10/2002  
 CN 2514811 Y 10/2002  
 CN 1511503 A 7/2004  
 CN 1741777 A 3/2006  
 CN 1817990 A 8/2006  
 CN 2843367 Y 12/2006  
 CN 2850584 Y 12/2006  
 CN 2850585 Y 12/2006  
 CN 200970265 Y 11/2007  
 CN 101259329 A 9/2008  
 CN 101309657 A 11/2008  
 DE 532976 C 9/1931  
 DE 2851602 A1 6/1980  
 DE 4213584 A1 11/1992  
 DE 4224595 A1 1/1994  
 DE 4238291 A1 5/1994  
 DE 4445627 A1 6/1996  
 DE 19800416 A1 7/1999  
 EP 263069 A2 4/1988  
 EP 0397043 A1 11/1990  
 EP 0406244 A1 1/1991  
 EP 560309 A1 9/1993  
 EP 0598824 A1 6/1994  
 EP 1030611 A1 8/2000  
 EP 1201266 A1 5/2002  
 EP 1568395 A1 8/2005  
 EP 2260801 A2 12/2010  
 EP 2289598 A1 3/2011  
 EP 2527005 A1 11/2012  
 FR 854937 A 4/1940  
 FR 2744358 A1 8/1997  
 FR 2745935 A1 9/1997  
 FR 2767476 A1 2/1999  
 FR 2776920 A1 10/1999  
 FR 2789893 A1 8/2000  
 FR 2805989 A1 9/2001  
 GB 387960 A 2/1933  
 GB 2120944 A 12/1983  
 GB 2202447 A 9/1988  
 GB 2248183 A 4/1992  
 GB 2263872 A 8/1993  
 GB 2286660 A 8/1995  
 GB 2323659 A 9/1998  
 JP 58187454 A 11/1983  
 JP S6094113 U 6/1985  
 JP 62082977 A 4/1987  
 JP 63076895 A 4/1988  
 JP 01223961 A 9/1989  
 JP 03051964 A 3/1991  
 JP 03259975 A 11/1991  
 JP 04093597 A 3/1992  
 JP 06261933 A 9/1994  
 JP 07194666 A 8/1995  
 JP 07268274 A 10/1995



(56)

## References Cited

## FOREIGN PATENT DOCUMENTS

JP 09164163 A 6/1997  
 JP 10216169 A 8/1998  
 JP 10223961 A 8/1998  
 JP 2000503154 A 3/2000  
 JP 3065657 B2 7/2000  
 JP 2001046416 A 2/2001  
 JP 2002125993 A 5/2002  
 JP 0200602 A1 8/2002  
 JP 2002224051 A 8/2002  
 JP 2002282295 A 10/2002  
 JP 2002290397 A 10/2002  
 JP 2002543668 A 12/2002  
 JP 2003190201 A 7/2003  
 JP 2004013600 A 1/2004  
 JP 2004073812 A 3/2004  
 JP 2004159666 A 6/2004  
 JP 2005039790 A 2/2005  
 JP 2005065984 A 3/2005  
 JP 2005110755 A 4/2005  
 JP 2005509977 A 4/2005  
 JP 3655820 B2 6/2005  
 JP 2005520608 A 7/2005  
 JP 2005237908 A 9/2005  
 JP 2005323716 A 11/2005  
 JP 2006026001 A 2/2006  
 JP 2006130055 A 5/2006  
 JP 2006520949 A 9/2006  
 JP 2007270459 A 10/2007  
 JP 2008532591 A 8/2008  
 JP 2009515232 A 4/2009  
 JP 2009189757 A 8/2009  
 KR 200173222 Y1 12/1999  
 KR 1020040094508 A 11/2004  
 KR 20090000258 U 1/2009  
 KR 1020130043299 A 4/2013  
 KR 1020140038165 A 3/2014  
 RU 2036667 C1 6/1995  
 SU 532976 A1 11/1978  
 TW 0476644 B 2/2002  
 WO 8503216 A1 8/1985  
 WO 9114417 A1 10/1991  
 WO 9404116 A1 3/1994  
 WO 9623447 A1 8/1996  
 WO 9626693 A1 9/1996  
 WO 9636293 A1 11/1996  
 WO 9637158 A1 11/1996  
 WO 97503154 11/1996  
 WO 9704832 A1 2/1997  
 WO 9705828 A1 2/1997  
 WO 9722262 A2 6/1997  
 WO 9724088 A1 7/1997  
 WO 9725798 A1 7/1997  
 WO 9748440 A1 12/1997  
 WO 9829134 A2 7/1998  
 WO 9831321 A1 7/1998  
 WO 9841156 A1 9/1998  
 WO 9841157 A1 9/1998  
 WO 9909928 A1 3/1999  
 WO 9916502 A1 4/1999  
 WO 9938469 A1 8/1999  
 WO 9949937 A1 10/1999  
 WO 0044346 A1 8/2000  
 WO 0044349 A1 8/2000  
 WO 0065770 A1 11/2000  
 WO 0067685 A1 11/2000  
 WO 0100269 A1 1/2001  
 WO 0113989 A1 3/2001  
 WO 0114012 A1 3/2001  
 WO 0134048 A1 5/2001  
 WO 0205736 A1 1/2002  
 WO 02102921 A1 12/2002  
 WO 03007859 A1 1/2003  
 WO 03078596 A2 9/2003  
 WO 03079916 A1 10/2003  
 WO 2004000098 A2 12/2003

WO 2004080279 A2 9/2004  
 WO 2004090939 A2 10/2004  
 WO 2005033957 A1 4/2005  
 WO 2005046540 A1 5/2005  
 WO 2005060354 A2 7/2005  
 WO 2005096979 A1 10/2005  
 WO 2005112815 A1 12/2005  
 WO 2006066226 A1 6/2006  
 WO 2006094348 A1 9/2006  
 WO 2006106836 A1 10/2006  
 WO 2006116603 A2 11/2006  
 WO 2006127467 A2 11/2006  
 WO 2007012083 A2 1/2007  
 WO 2007028975 A1 3/2007  
 WO 2007041642 A2 4/2007  
 WO 2007101039 A1 9/2007  
 WO 2007127924 A2 11/2007  
 WO 2007145421 A1 12/2007  
 WO 2007145422 A1 12/2007  
 WO 2008006018 A2 1/2008  
 WO 2008039556 A1 4/2008  
 WO 2008039557 A1 4/2008  
 WO 2008055243 A2 5/2008  
 WO 2008143678 A1 11/2008  
 WO 2009011708 A1 1/2009  
 WO 2009026471 A1 2/2009  
 WO 2010077841 A1 7/2010  
 WO 2010127315 A2 11/2010  
 WO 2012012296 A1 1/2012  
 WO 2012103242 A1 8/2012  
 WO 2013013059 A1 1/2013  
 WO 2013075006 A1 5/2013  
 WO 2013075016 A1 5/2013  
 WO 2013190337 A1 12/2013  
 WO 2014151872 A3 9/2014  
 WO 2014191263 A1 12/2014  
 WO 2015117001 A1 8/2015  
 WO 2015117005 A1 8/2015  
 WO 2015117026 A2 8/2015  
 WO 2015117032 A1 8/2015  
 WO 2015117036 A2 8/2015  
 WO 2016028796 A1 2/2016  
 WO 2016048721 A1 3/2016

## OTHER PUBLICATIONS

Aguilar et al., "Modeling Cryogenic Spray Temperature and Evaporation Rate Based on Single-Droplet Analysis," Eighth International Conference on Liquid Atomization and Spray Systems, Pasadena, CA, USA, Jul. 2000, 7 pages.  
 Al-Sakere, B. et al. "Tumor Ablation with Irreversible Electroporation," PLoS One, Issue 11, Nov. 2007, 8 pages.  
 Alster, T. et al., "Cellulite Treatment Using a Novel Combination Radiofrequency, Infrared Light, and Mechanical Tissue Manipulation Device," Journal of Cosmetic and Laser Therapy, vol. 7, 2005, pp. 81-85.  
 Ardevol, A. et al., "Cooling Rates of Tissue Samples During Freezing with Liquid Nitrogen," Journal of Biochemical and Biophysical Methods, vol. 27, 1993, pp. 77-86.  
 Arena, C. B. et al., "High-Frequency Irreversible Electroporation (H-FIRE) for Non-Thermal Ablation Without Muscle Contraction," BioMedical Engineering OnLine 2011, 10:102, Nov. 21, 2011, 21 pgs.  
 Becker, S. M. et al. "Local Temperature Rises Influence In Vivo Electroporation Pore Development: A Numerical Stratum Corneum Lipid Phase Transition Model," Journal of Biomechanical Engineering, vol. 129, Oct. 2007, pp. 712-721.  
 Bohm, T. et al., "Saline-Enhanced Radiofrequency Ablation of Breast Tissue: an in Vitro Feasibility Study," Investigative Radiology, vol. 35 (3), 2000, pp. 149-157.  
 Bondei, E. et al., "Disorders of Subcutaneous Tissue (Cold Panniculitis)," Dermatology in General Medicine, Fourth Edition, vol. 1, Chapter 108, 1993, Section 16, pp. 1333-1334.  
 Burge, S.M. et al., "Hair Follicle Destruction and Regeneration in Guinea Pig Skin after Cutaneous Freeze Injury," Cryobiology, 27(2), 1990, pp. 153-163.



(56)

**References Cited**

## OTHER PUBLICATIONS

- Coban, Y. K. et al., "Ischemia-Reperfusion Injury of Adipofascial Tissue: An Experimental Study Evaluating Early Histologic and Biochemical Alterations in Rats," *Mediators of Inflammation*, 2005, 5, pp. 304-308.
- Del Pino, M. E. et al. "Effect of Controlled Volumetric Tissue Heating with Radiofrequency on Cellulite and the Subcutaneous Tissue of the Buttocks and Thighs," *Journal of Drugs in Dermatology*, vol. 5, Issue 8, Sep. 2006, pp. 714-722.
- Donski, P. K. et al., "The Effects of Cooling no Experimental Free Flap Survival," *British Journal of Plastic Surgery*, vol. 33, 1980, pp. 353-360.
- Duck, F. A., *Physical Properties of Tissue*, Academic Press Ltd., chapters 4 & 5, 1990, pp. 73-165.
- Duncan, W. C. et al., "Cold Panniculitis," *Archives of Dermatology*, vol. 94, Issue 6, Dec. 1966, pp. 722-724.
- Epstein, E. H. et al., "Popsicle Panniculitis," *The New England Journal of Medicine*, 282(17), Apr. 23, 1970, pp. 966-967.
- European Search Report; Application No. EP10770461; dated Aug. 31, 2012; Applicant: Zeltiq Aesthetics, Inc. 5 pgs.
- European Search Report; Application No. EP14156801.4; dated Aug. 22, 2014; Applicant: Zeltiq Aesthetics, Inc. 5 pgs.
- Fournier, L. et al. "Lattice Model for the Kinetics of Rupture of Fluid Bilayer Membranes," *Physical Review*, vol. 67, 2003, pp. 051908-1-051908-11.
- Gabriel, S. et al., "The Dielectric Properties of Biological Tissues: II. Measurements in the Frequency Range 10 Hz to 20 GHz," *Physics in Medicine and Biology*, vol. 41, 1996, pp. 2251-2269.
- Gage, A. "Current Progress in Cryosurgery," *Cryobiology* 25, 1988, pp. 483-486.
- Gatto, H. "Effects of Thermal Shocks on Interleukin-1 Levels and Heat Shock Protein 72 (HSP72) Expression in Normal Human Keratinocytes," *PubMed, Archives of Dermatological Research*, vol. 284, Issue 7, 1992: pp. 414-417 [Abstract].
- Hale, H. B. et al., "Influence of Chronic Heat Exposure and Prolonged Food Deprivation on Excretion of Magnesium, Phosphorus, Calcium, Hydrogen Ion & Ketones," *Aerospace Medicine*, vol. 39—No. 9, Sep. 1968, pp. 919-926.
- Heller Page, E. et al., "Temperature-dependent skin disorders," *Journal of the American Academy of Dermatology*, vol. 18, No. 5, Pt 1, May 1988, pp. 1003-1019.
- Hemmingsson, A. et al. "Attenuation in Human Muscle and Fat Tissue in Vivo and in Vitro," *Acta Radiologica Diagnosis*, vol. 23, No. 2, 1982, pp. 149-151.
- Henry, F. et al., "Les Dermatoses Hivernales," *Rev Med Liege*, 54:11, 1999, pp. 864-866.
- Hernan, P. et al., "Study for the evaluation of the efficacy of Lipocryolysis (EEEL)," Nov. 30, 2011.
- Hernan, R. P., "A Study to Evaluate the Action of Lipocryolysis," 33(3) *CryoLellers*, 2012, pp. 176-180.
- Holland, DB. et al. "Cold shock induces the synthesis of stress proteins in human keratinocytes," *PubMed Journal of Investigative Dermatology*; 101(2): Aug. 1993, pp. 196-199.
- Holman, W. L. et al., "Variation in Cryolesion Penetration Due to Probe Size and Tissue Thermal Conductivity," *The Annals of Thoracic Surgery*, vol. 53, 1992, pp. 123-126.
- Hong, J.S. et al., "Patterns of Ice Formation in Normal and Malignant Breast Tissue," *Cryobiology* 31, 1994, pp. 109-120.
- Huang et al. "Comparative Proteomic Profiling of Murine Skin," *Journal of Investigative Dermatology*, vol. 121(1), Jul. 2003, pp. 51-64.
- International Search Report and Written Opinion for PCT/US2010/033290; Applicant: Zeltiq Aesthetics, Inc.; dated Feb. 25, 2011, 12 pages.
- Isambert, H. "Understanding the Electroporation of Cells and Artificial Bilayer Membranes," *Physical Review Letters*, vol. 80, No. 15, 1998, pp. 3404-3707.
- Jalian, H. R. et al., "Cryolipolysis: A Historical Perspective and Current Clinical Practice," 32(1) *Semin. Cutan. Med. Surg.*, 2013, pp. 31-34.
- Kellum, R. E. et al., "Sclerema Neonatorum: Report of Case and Analysis of Subcutaneous and Epidermal-Dermal Lipids by Chromatographic Methods," *Archives of Dermatology*, vol. 97, Apr. 1968, pp. 372-380.
- Koska, J. et al., "Endocrine Regulation of Subcutaneous Fat Metabolism During Cold Exposure in Humans," *Annals of the New York Academy of Sciences*, vol. 967, 2002, pp. 500-505.
- Kumakura et al.; Office Action: Notification of Reason for Rejection; Japanese Patent Application No. 2010-213871; Dispatch No. 254910; dated Apr. 16, 2012; Drawn up on: Apr. 12, 2012.
- Kundu, S. K. et al., "Breath Acetone Analyzer: Diagnostic Tool to Monitor Dietary Fat Loss," *Clinical Chemistry*, vol. 39, Issue (1), 1993, pp. 87-92.
- Kundu, S. K. et al., "Novel Solid-Phase Assay of Ketone Bodies in Urine," *Clinical Chemistry*, vol. 37, Issue (9), 1991, pp. 1565-1569.
- Kuroda, S. et al. "Thermal Distribution of Radio-Frequency Inductive Hyperthermia Using an Inductive Aperture-Type Applicator: Evaluation of the Effect of Tumor Size and Depth," *Medical and Biological Engineering and Computing*, vol. 37, 1999, pp. 285-290.
- Laugier, P. et al., "In Vivo Results with a New Device for Ultrasonic Monitoring of Pig Skin Cryosurgery: The Echographic Cryoprobe," *The Society for Investigative Dermatology, Inc.*, vol. 111, No. 2, Aug. 1998, pp. 314-319.
- Levchenko et al., "Effect of Dehydration on Lipid Metabolism" *Ukrainskii Biokhimicheskii Zhurnal*, vol. 50, Issue 1, 1978, pp. 95-97.
- Lidagoster, MD et al., "Comparison of Autologous Fat Transfer in Fresh, Refrigerated, and Frozen Specimens: An Animal Model," *Annals of Plastic Surgery*, vol. 44, No. 5, May 2000, pp. 512-515.
- Liu, A. Y.-C. et al., "Transient Cold Shock Induces the Heat Shock Response upon Recovery at 37 C in Human Cells," *Journal of Biological Chemistry*, , 269(20), May 20, 1994, pp. 14768-14775.
- L'Vova, S.P. "Lipid Levels and Lipid Peroxidation in Frog Tissues During Hypothermia and Hibernation" *Ukrainskii Biokhimicheskii Zhurnal*, vol. 62, Issue 1, 1990, pp. 65-70.
- Maize, J.C. "Panniculitis," *Cutaneous Pathology*, Chapter 13, 1998, 327-344.
- Malcolm, G. T. et al., "Fatty Acid Composition of Adipose Tissue in Humans: Differences between Subcutaneous Sites," *The American Journal of Clinical Nutrition*, vol. 50, 1989, pp. 288-291.
- Manstein, D. et al. "A Novel Cryotherapy Method of Non-invasive, Selective Lipolysis," *Lasers Surg. Med* 40:S20, 2008, p. 104.
- Manstein, D. et al. "Selective Cryolysis: A Novel Method of Non-Invasive Fat Removal," *Lasers in Surgery and Medicine: The Official Journal of the ASLMS*, vol. 40, No. 9, Nov. 2008, pp. 595-604.
- Mayoral, "Case Reports: Skin Tightening with a Combined Unipolar and Bipolar Radiofrequency Device," *Journal of Drugs in Dermatology*, 2007, pp. 212-215.
- Mazur, P. "Cryobiology: The Freezing of Biological Systems," *Science*, 68, 1970, pp. 939-949.
- Merrill, T. "A Chill to the Heart: A System to Deliver Local Hypothermia Could One Day Improve the Lives of Heart-Attack Patients," *Mechanical Engineering Magazine*, Oct. 2010, 10 pages.
- Miklavcic, D. et al. "Electroporation-Based Technologies and Treatments," *The Journal of Membrane Biology* (2010) 236:1-2, 2 pgs.
- Moschella, S. L. et al., "Diseases of the Subcutaneous Tissue," in *Dermatology*, Second Edition, vol. 2, 1985 Chapter 19, Section II (W.B. Saunders Company, 1980) pp. 1169-1181.
- Murphy, J. V. et al., "Frostbite: Pathogenesis and Treatment" *The Journal of Trauma: Injury, Infection, and Critical Care*, vol. 48, No. 1, Jan. 2000, pp. 171-178.
- Nagao, T. et al., "Dietary Diacylglycerol Suppresses Accumulation of Body Fat Compared to Triacylglycerol in Men a Double-Blind Controlled Trial," *The Journal of Nutrition*, vol. 130, Issue (4), 2000, pp. 792-797.
- Nagle, W. A. et al. "Cultured Chinese Hamster Cells Undergo Apoptosis After Exposure to Cold but Nonfreezing Temperatures," *Cryobiology* 27, 1990, pp. 439-451.
- Nagore, E. et al., "Lipoatrophia Semicircularis-a Traumatic Panniculitis: Report of Seven Cases and Review of the Literature," *Journal of the American Academy of Dermatology*, vol. 39, Nov. 1998, pp. 879-881.



(56)

**References Cited**

## OTHER PUBLICATIONS

Nanda, G.S. et al., "Studies on electroporation of thermally and chemically treated human erythrocytes," *Bioelectrochemistry and Bioenergetics*, 34, 1994, pp. 129-134, 6 pgs.

Narins, D.J. et al. "Non-Surgical Radiofrequency Facelift", *The Journal of Drugs in Dermatology*, vol. 2, Issue 5, 2003, pp. 495-500.

Nielsen, B. "Thermoregulation in Rest and Exercise," *Acta Physiologica Scandinavica Supplementum*, vol. 323 (Copenhagen 1969), pp. 7-74.

Nishikawa, H. et al. "Ultrastructural Changes and Lipid Peroxidation in Rat Adipomusculocutaneous Flap Isotransplants after Normothermic Storage and Reperfusion," *Transplantation*, vol. 54, No. 5, 1992, pp. 795-801.

Non-Final Office Action dated Jun. 5, 2013; U.S. Appl. No. 12/772,040; 5 pages.

Nurnberger, F. "So-Called Cellulite: An Invented Disease," *Journal of Dermatologic Surgery and Oncology*, Mar. 1978, pp. 221-229.

Pease, G. R. et al., "An Integrated Probe for Magnetic Resonance Imaging Monitored Skin Cryosurgery," *Journal of Biomedical Engineering*, vol. 117, Feb. 1995, pp. 59-63.

Pech, P. et al., "Attenuation Values, Volume Changes and Artifacts in Tissue Due to Freezing," *Acta Radiologica*, vol. 28, Issue 6, 1987, pp. 779-782.

Peterson, L. J. et al., "Bilateral Fat Necrosis of the Scrotum," *Journal of Urology*, vol. 116, 1976, pp. 825-826.

Phinney, S. D. et al., "Human Subcutaneous Adipose Tissue Shows Site-Specific Differences in Fatty Acid Composition," *The American Journal of Clinical Nutrition*, vol. 60, 1994, pp. 725-729.

Pierard, G.E. et al., "Cellulite: From Standing Fat Herniation to Hypodermal Stretch Marks," *The American Journal of Dermatology*, vol. 22, Issue 1, 2000, pp. 34-37.

Pope, K. et al. "Selective Fibrous Septae Heating: An Additional Mechanism of Action for Capacitively Coupled Monopolar Radiofrequency" *Thermage, Inc. Article*, Feb. 2005, 6pgs.

Quinn, P. J. "A Lipid-Phase Separation Model of Low-Temperature Damage to Biological Membranes," *Cryobiology*, 22, 1985, 128-146.

Rabi, T. et al., "Metabolic Adaptations in Brown Adipose Tissue of the Hamster in Extreme Ambient Temperatures," *American Journal of Physiology*, vol. 231, Issue 1, Jul. 1976, pp. 153-160.

Renold, A.E. et al. "Adipose Tissue" in *Handbook of Physiology*, Chapter 15, (Washington, D.C., 1965) pp. 169-176.

Rossi, A. B. R. et al. "Cellulite: a Review," *European Academy of Dermatology and Venereology*, 2000, pp. 251-262, 12 pgs.

Rubinsky, B. "Principles of Low Temperature Cell Preservation," *Heart Failure Reviews*, vol. 8, 2003, pp. 277-284.

Rubinsky, B. et al., "Cryosurgery: Advances in the Application of low Temperatures to Medicine," *International Journal of Refrigeration*, vol. 14, Jul. 1991, pp. 190-199.

Saleh, K.Y. et al., "Two-Dimensional Ultrasound Phased Array Design for Tissue Ablation for Treatment of Benign Prostatic Hyperplasia," *International Journal of Hyperthermia*, vol. 20, No. 1, Feb. 2004, pp. 7-31.

Schoning, P. et al., "Experimental Frostbite: Freezing Times, Rewarming Times, and Lowest Temperatures of Pig Skin Exposed to Chilled Air," *Cryobiology* 27, 1990, pp. 189-193.

Shephard, R. J. "Adaptation to Exercise in the Cold," *Sports Medicine*, vol. 2, 1985, pp. 59-71.

SIGMA-ALDRICH "Poly (ethylene glycol) and Poly (ethylene oxide)," <http://www.sigmaaldrich.com/materials-science/materialscience-products.html?TablePage=20204110>, accessed Oct. 19, 2012.

Smalls, L. K. et al. "Quantitative Model of Cellulite: Three Dimensional Skin Surface Topography, Biophysical Characterization, and Relationship to Human Perception," *International Journal of Cosmetic Science*, vol. 27, Issue 5, Oct. 2005, 17 pgs.

Thermage, News Release, "Study Published in Facial Plastic Surgery Journal Finds Selective Heating of Fibrous Septae Key to Success and Safety of Thermage ThermoCool System," Jun. 20, 2005, 2 pages.

Vallerand et al. "Cold Stress Increases Lipolysis, FFA Ra and TG/FFA Cycling in Humans," *Aviation, Space, and Environmental Medicine* 70(1), 1999, pp. 42-50.

Wang, X. et al., "Cryopreservation of Cell/Hydrogel Constructs Based on a new Cell-Assembling Technique," Sep. 5, 2009, 40 pages.

Wharton, D. A. et al., "Cold Acclimation and Cryoprotectants in a Freeze-Tolerant Antarctic Nematode, *Panagrolaimus Davidi*," *Journal of Comparative Physiology*, vol. 170, No. 4, Mar. 2000, 2 pages.

Winkler, C. et al., "Gene Transfer in Laboratory Fish: Model Organisms for the Analysis of Gene Function," in *Transgenic Animals, Generation and Use* (The Netherlands 1997), pp. 387-395.

Young, H. E. et al. "Isolation of Embryonic Chick Myosatellite and Pluripotent Stem Cells" *The Journal of Tissue Culture Methods*, vol. 14, Issue 2, 1992, pp. 85-92.

Zelickson, B. et al., "Cryolipolysis for Noninvasive Fat Cell Destruction: Initial Results from a Pig Model", *35 Dermatol. Sug.*, 2009, pp. 1-9.

Zouboulis, C. C. et al., "Current Developments and Uses of Cryosurgery in the Treatment of Keloids and Hypertrophic Scars," *Wound Repair and Regeneration*, vol. 10, No. 2, 2002, pp. 98-102.

\* cited by examiner







FIG. 1





**FIG. 2**






FIG. 3A




FIG. 3C






FIG. 3B






FIG. 3D






FIG. 3E






FIG. 4A




FIG. 4B






FIG. 4C





FIG. 4D





**FIG. 5A**




FIG. 5B






FIG. 5C




FIG. 5D




FIG. 6A






FIG. 6B




FIG. 6C




FIG. 7A




FIG. 7B




FIG. 7C






FIG. 7D




FIG. 7E





FIG. 7F



FIG. 8






FIG. 9A




FIG. 9B






FIG. 9C




FIG. 9D

FIG. 10







FIG. 11A












FIG. 12A










FIG. 14




FIG. 15A




FIG. 15B




FIG. 16A




FIG. 16B






FIG. 17A




FIG. 17B



# DEVICE, SYSTEM AND METHOD OF REMOVING HEAT FROM SUBCUTANEOUS LIPID-RICH CELLS

## CROSS-REFERENCE TO RELATED APPLICATIONS

This patent application is a continuation of U.S. patent application Ser. No. 14/205,794, filed Mar. 12, 2014, now U.S. Pat. No. 9,861,520, which is a continuation of U.S. patent application Ser. No. 12/772,040, filed on Apr. 30, 2010, now U.S. Pat. No. 8,702,774, which claims the benefit of U.S. Provisional Patent Application No. 61/174,487, filed on Apr. 30, 2009. Each of these applications is incorporated by reference herein in its entirety.

## INCORPORATION BY REFERENCE OF COMMONLY-OWNED APPLICATIONS

The following commonly-assigned U.S. Patent Applications are incorporated herein by reference in their entirety:

U.S. Patent Publication No. 2008/0287839 entitled "METHOD OF ENHANCED REMOVAL OF HEAT FROM SUBCUTANEOUS LIPID-RICH CELLS AND TREATMENT APPARATUS HAVING AN ACTUATOR";

U.S. Pat. No. 6,032,675 entitled "FREEZING METHOD FOR CONTROLLED REMOVAL OF FATTY TISSUE BY LIPOSUCTION";

U.S. Patent Publication No. 2007/0255362 entitled "CRYOPROTECTANT FOR USE WITH A TREATMENT DEVICE FOR IMPROVED COOLING OF SUBCUTANEOUS LIPID-RICH CELLS";

U.S. Patent Publication No. 2007/0198071 entitled "COOLING DEVICE FOR REMOVING HEAT FROM SUBCUTANEOUS LIPID-RICH CELLS";

U.S. Patent Publication No. 2008/0077201 entitled "COOLING DEVICES WITH FLEXIBLE SENSORS";

U.S. Patent Publication No. 2008/0077211 entitled "COOLING DEVICE HAVING A PLURALITY OF CONTROLLABLE COOLING ELEMENTS TO PROVIDE A PREDETERMINED COOLING PROFILE";

U.S. Patent Publication No. 2009/0118722 entitled "METHOD AND APPARATUS FOR COOLING SUBCUTANEOUS LIPID-RICH CELLS OR TISSUE";

U.S. Patent Publication No. 2009/0018624 entitled "LIMITING USE OF DISPOSABLE SUBJECT PROTECTION DEVICES";

U.S. Patent Publication No. 2009/0018623 entitled "SYSTEM FOR TREATING LIPID-RICH REGIONS";

U.S. Patent Publication No. 2009/0018625 entitled "MANAGING SYSTEM TEMPERATURE TO REMOVE HEAT FROM LIPID-RICH REGIONS";

U.S. Patent Publication No. 2009/0018627 entitled "SECURE SYSTEM FOR REMOVING HEAT FROM LIPID-RICH REGIONS";

U.S. Patent Publication No. 2009/0018626 entitled "USER INTERFACES FOR A SYSTEM THAT REMOVES HEAT FROM LIPID-RICH REGIONS";

U.S. Pat. No. 6,041,787 entitled "USE OF CRYOPROTECTIVE AGENT COMPOUNDS DURING CRYOSURGERY";

U.S. Patent Publication No. 2009/0149929 entitled "MONITORING THE COOLING OF SUBCUTANEOUS LIPID-RICH CELLS, SUCH AS THE COOLING OF ADIPOSE TISSUE";

U.S. Patent Publication No. 2010/0081971 entitled "TREATMENT PLANNING SYSTEMS AND METHODS FOR BODY CONTOURING APPLICATIONS";

U.S. patent application Ser. No. 12/337,544 entitled "SYSTEMS AND METHODS WITH INTERRUPT/RESUME CAPABILITIES FOR COOLING SUBCUTANEOUS LIPID-RICH CELLS";

U.S. Patent Publication No. 2008/0077202 entitled "TISSUE TREATMENT METHODS"; and

U.S. Provisional Patent Application Ser. No. 61/298,175 entitled "HOME CARE METHODS AND SYSTEMS FOR REDUCING SUBCUTANEOUS FAT."

U.S. Patent Publication No. 2007/0270925 entitled "METHOD AND APPARATUS FOR NON-INVASIVELY REMOVING HEAT FROM SUBCUTANEOUS LIPID RICH CELLS INCLUDING A COOLANT HAVING A PHASE TRANSITION TEMPERATURE";

U.S. Provisional Patent Application Ser. No. 61/297,238 entitled "COMPOSITIONS FOR USE WITH A SYSTEM FOR IMPROVED COOLING OF SUBCUTANEOUS LIPID-RICH CELLS".

## TECHNICAL FIELD

The present application relates generally to treatment devices, systems, and methods for removing heat from subcutaneous lipid-rich cells. In particular, several embodiments are directed toward a treatment device including a vacuum applicator to effect heat removal or extraction from subcutaneous lipid-rich cells.

## BACKGROUND

Excess body fat, or adipose tissue, may be present in various locations of the body, including, for example, the thigh, buttocks, abdomen, knees, back, face, arms, chin, and other areas. Moreover, excess adipose tissue is thought to magnify the unattractive appearance of cellulite, which forms when subcutaneous fat protrudes into the dermis and creates dimples where the skin is attached to underlying structural fibrous strands. Cellulite and excessive amounts of adipose tissue are often considered to be unappealing. Moreover, significant health risks may be associated with higher amounts of excess body fat.

A variety of methods have been used to treat individuals having excess body fat and, in many instances, non-invasive removal of excess subcutaneous adipose tissue can eliminate unnecessary recovery time and discomfort associated with invasive procedures such as liposuction. Conventional non-invasive treatments for removing excess body fat typically include topical agents, weight-loss drugs, regular exercise, dieting, or a combination of these treatments. One drawback of these treatments is that they may not be effective or even possible under certain circumstances. For example, when a person is physically injured or ill, regular exercise may not be an option. Similarly, weight-loss drugs or topical agents are not an option when they cause an allergic or negative reaction. Furthermore, fat loss in selective areas of a person's body often cannot be achieved using general or systemic weight-loss methods.

Other methods designed to reduce subcutaneous adipose tissue include laser-assisted liposuction and mesotherapy. Newer non-invasive methods include applying radiant energy to subcutaneous lipid-rich cells via, e.g., radio frequency and/or light energy, such as described in U.S. Patent Publication No. 2006/0036300 and U.S. Pat. No. 5,143,063, or via, e.g., high intensity focused ultrasound (HIFU) radia-



3

tion such as described in U.S. Pat. Nos. 7,258,674 and 7,347,855. In contrast, methods and devices for non-invasively reducing subcutaneous adipose tissue by cooling are disclosed in U.S. Pat. No. 7,367,341 entitled “METHODS AND DEVICES FOR SELECTIVE DISRUPTION OF FATTY TISSUE BY CONTROLLED COOLING” to Anderson et al. and U.S. Patent Publication No. 2005/0251120 entitled “METHODS AND DEVICES FOR DETECTION AND CONTROL OF SELECTIVE DISRUPTION OF FATTY TISSUE BY CONTROLLED COOLING” to Anderson et al., the entire disclosures of which are incorporated herein by reference.

### BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings, identical reference numbers identify similar elements or acts. The sizes and relative positions of elements in the drawings are not necessarily drawn to scale. For example, the shapes of various elements and angles are not necessarily drawn to scale, and some of these elements are arbitrarily enlarged and positioned to improve drawing legibility. Further, the particular shapes of the elements as drawn are not necessarily intended to convey any information regarding the actual shape of the particular elements, and are generally selected for ease of recognition in the drawings.

FIG. 1 is an isometric view schematically illustrating a treatment system for treating subcutaneous lipid-rich regions of a subject 11 in accordance with an embodiment of the disclosure.

FIG. 2 is a schematic illustrating a treatment device for treating subcutaneous lipid-rich areas of a subject 11 in accordance with an embodiment of the disclosure.

FIG. 3A is a side view showing an embodiment of a device for a treatment to removing or extracting heat from subcutaneous lipid-rich cells.

FIG. 3B is a top view showing a control panel of the treatment device shown in FIG. 3A.

FIG. 3C is a bottom view showing the treatment device shown in FIG. 3A.

FIG. 3D is a partially exploded perspective view of the treatment device shown in FIG. 3A.

FIG. 3E is a detail view of a component of the treatment device shown in FIG. 3A.

FIGS. 4A-4D show different stages of assembling an embodiment of a rigid portion of the treatment device shown in FIG. 3A.

FIG. 5A shows a front view of an embodiment of a flexible portion of the treatment device shown in FIG. 3A.

FIG. 5B is an end view of the flexible portion shown in FIG. 5A.

FIG. 5C is a top view of the flexible portion shown in FIG. 5A.

FIG. 5D is a bottom view of the flexible portion shown in FIG. 5A.

FIG. 6A is a perspective view showing an embodiment of a subject 11 liner for the treatment device shown in FIG. 3A.

FIG. 6B is an exploded view of the subject 11 liner shown in FIG. 6A.

FIG. 6C is a perspective view of the subject 11 liner shown in FIG. 6A.

FIG. 7A shows a perspective view of an embodiment of a token interfacing with the treatment device shown in FIG. 3A.

FIG. 7B shows a perspective view of the token shown in FIG. 6A.

4

FIG. 7C shows a perspective view of an embodiment of a receptacle for receiving the token shown in FIG. 7A.

FIG. 7D shows another embodiment of a receptacle for the treatment device shown in FIG. 3A.

FIG. 7E shows another embodiment of a token for the treatment device shown in FIG. 3A.

FIG. 7F shows an adjustor for the treatment devices described herein.

FIG. 8 is a perspective view showing an embodiment of another applicator for a treatment to remove or extract heat from lipid-rich cells disposed under a cutaneous layer.

FIG. 9A is an elevation view of a flexible portion of the applicator shown in FIG. 8.

FIG. 9B is a side view of a flexible portion of the applicator shown in FIG. 8.

FIG. 9C is a plan view of a flexible portion of the vacuum applicator shown in FIG. 8.

FIG. 9D is a bottom view of a flexible portion of the vacuum applicator shown in FIG. 8.

FIG. 10 is a perspective view of a panel of a rigid portion of the vacuum applicator shown in FIG. 8.

FIG. 11A is an exploded perspective view a frame of the vacuum applicator shown in FIG. 8.

FIG. 11B is a perspective view of a first frame portion of the frame shown in FIG. 11A.

FIG. 11C is a perspective view of a second frame portion of the frame shown in FIG. 11A.

FIG. 12A is an exploded side view of a subassembly of the vacuum applicator shown in FIG. 8 including the panels and the second frame portions.

FIG. 12B is an exploded, perspective view of an assembly of the vacuum applicator shown in FIG. 8 including the flexible portion, the first frame portions, and the subassembly shown in FIG. 12A.

FIG. 13A is a cross-section view showing an embodiment of a fluid separator in fluid communication between an interior cavity and a port of the vacuum applicator shown in FIG. 8.

FIG. 13B is a cross-section view showing another embodiment of a fluid separator in fluid communication between an interior cavity and a port of the vacuum applicator shown in FIG. 8.

FIG. 14 is a plan view of a personal protection device usable with a vacuum applicator in accordance with an embodiment of the disclosure.

FIGS. 15A and 15B illustrate an embodiment of an applicator according to the present invention.

FIGS. 16A and 16B illustrate another embodiment of an applicator according to the present invention.

FIGS. 17A and 17B illustrate yet another embodiment of an applicator according to the present invention.

### DETAILED DESCRIPTION

#### Overview

Devices, systems, and methods for monitoring and closed loop controlling of the treatment (including cooling) of subcutaneous tissue, such as adipose tissue, are described. Several of the details set forth below are provided to describe the following examples and methods in a manner sufficient to enable a person skilled in the relevant art to practice, make and use them. Several of the details and advantages described below, however, may not be necessary to practice certain examples and methods of the technology.



Additionally, the technology may include other examples and methods that are within the scope of the claims but are not described in detail.

Reference throughout this specification to “one example,” “an example,” “one embodiment,” or “an embodiment” means that a particular feature, structure, or characteristic described in connection with the example is included in at least one example of the present technology. Thus, the occurrences of the phrases “in one example,” “in an example,” “one embodiment,” or “an embodiment” in various places throughout this specification are not necessarily all referring to the same example. Furthermore, the particular features, structures, routines, steps, or characteristics may be combined in any suitable manner in one or more examples of the technology. The headings provided herein are for convenience only and are not intended to limit or interpret the scope or meaning of the claimed technology.

Aspects of the present invention are generally directed toward a device for treating subcutaneous lipid-rich cells. One aspect of certain embodiments is directed toward a rigid portion and a flexible portion. The rigid portion includes a thermal conductor that has an inside surface and an outside surface positioned opposite the inside surface. The flexible portion has an inner surface, an outer surface positioned opposite the inner surface, and a cutout extending between the inner and outer surfaces. The thermal conductor is positioned in the cutout and the flexible and rigid portions define a body. The body has an interior surface and an exterior surface. The interior surface includes the inside face of the rigid portion and the inner surface of the flexible portion, and the exterior surface includes the outside face of the rigid portion and the outer surface of the flexible portion.

Other aspects of the present invention are generally directed toward a system for treating subcutaneous lipid-rich cells in a target area. One aspect of certain embodiments is directed toward a treatment device and a token. The treatment device includes an applicator that is configured to operably engage the target area. The applicator includes a heat removal source that is configured to remove heat from the lipid-rich cells. The token interfaces with the treatment device to permit a treatment with the treatment device. The token includes a microelectronic device that is electrically coupled with the heat removal source while the token interfaces with the treatment device.

Other aspects of the present invention are generally directed toward a method for treating subcutaneous lipid-rich cells in a target area. One aspect of certain embodiments is directed toward configuring a treatment device for the target area, permitting use of the treatment device within a predetermined limit, verifying that continued use of the treatment device is within the predetermined limit and prohibiting use of the treatment device when the predetermined limit is exceeded. The treatment device includes a heat removal source configured to remove heat from the lipid rich cells.

Other aspects of the present invention are generally directed toward a vacuum applicator for treating subcutaneous lipid-rich cells with a cooling/heating unit. One aspect of certain embodiments is directed toward a rigid portion and a flexible portion. The rigid portion has an inside surface, an outside surface, and a rigid edge that extends between the inside and outside surfaces. The rigid portion includes a thermal conductor coupling the inside and outside surfaces. The flexible portion has an inner surface, an outer surface positioned opposite the inner surface, and a flexible edge that extends between the inner and outer surfaces. The flexible and rigid portions define a body that has an interior

surface, an exterior surface, and an aperture. The interior surface includes the inside face of the rigid portion and the inner surface of the flexible portion. The exterior surface includes the outside face of the rigid portion and the outer surface of the flexible portion. The aperture includes the rigid edge of the rigid portion and the flexible edge of the flexible portion.

Other aspects of the present invention are generally directed toward a method for treating lipid-rich cells disposed under a cutaneous layer. One aspect of certain embodiments is directed toward coupling a heat removal source to an exterior surface of a thermally conductive plate of a vacuum applicator, coupling a suction source to an interior cavity of the vacuum applicator, placing the vacuum applicator on the cutaneous layer, activating the suction source to draw the cutaneous layer into the interior cavity of the vacuum applicator, and activating the heat removal source to remove heat from the lipid-rich cells.

Other aspects of the present invention are generally directed toward a device for treating lipid-rich cells disposed under a cutaneous layer. One aspect of certain embodiments is directed toward a base, a fitting, and a thermal conductor. The base includes a first attachment. The fitting includes a first portion of a contour that defines a mouth of a cavity. The fitting also includes a second attachment that is coupled to the first attachment in a first device arrangement and is decoupled from the first attachment in a second device arrangement. The thermal conductor is disposed about at least a portion of the cavity and is configured for heat transfer with respect to the lipid-rich cells when the contour engages the cutaneous layer in the first device arrangement.

Other aspects of the present invention are generally directed toward a device for treating lipid-rich cells disposed under a cutaneous layer. One aspect of certain embodiments is directed toward a vacuum cup that defines an interior cavity, a thermal conductor disposed about at least a portion of the cavity, and an adjustor. The vacuum cup includes a contour that defines a mouth of a cavity. The thermal conductor is configured for heat transfer with respect to the lipid-rich cells when the contour engages the cutaneous layer. The adjustor is configured to adjust at least one of (a) dimensions of the interior cavity, and (b) position of the thermal conductor with respect to the interior cavity.

Other aspects of the present invention are generally directed toward a system for treating subcutaneous lipid-rich cells in a target area. One aspect of certain embodiments is directed toward a base, a first fitting, a second fitting, and a thermal conductor. The base includes a first attachment. The first fitting includes a portion of a first contour that defines a first mouth of a first cavity. The fitting includes a second attachment that is coupled to the first attachment in a first device arrangement and is decoupled from the first attachment in a second device arrangement. The second fitting includes a portion of a second contour that defines a second mouth of a second cavity. The second fitting includes a third attachment that is coupled to the first attachment in a third device arrangement. The thermal conductor is disposed about at least a portion of the cavity. The thermal conductor is configured for heat transfer with respect to the lipid-rich cells when the first contour engages the cutaneous layer in the first arrangement and when the second contour engages the cutaneous layer in the third arrangement.

Other aspects of the present invention are generally directed toward a method. One aspect of certain embodiments is directed toward coupling a first fitting to a base of a vacuum applicator, placing the first fitting on a first cutaneous layer area, transferring heat between a thermal



conductor and lipid-rich cells disposed under the first cutaneous layer area, displacing the first fitting from the first cutaneous layer area, decoupling the first fitting from the base, coupling a second fitting to the base, placing the second fitting on a second cutaneous layer area, and transferring heat between the thermal conductor and lipid-rich cells disposed under the second cutaneous layer area.

#### Suitable Treatment System

FIG. 1 and the following discussion provide a brief, general description of a suitable treatment system 10 in which aspects of the disclosure can be implemented. Those skilled in the relevant art will appreciate that the disclosure can be practiced with other treatment systems and treatment protocols, including invasive, minimally invasive, other non-invasive medical treatment systems, and/or combinations of one or more of the above for treating a subject 11. In general, the term “treatment system”, as used generally herein, refers to any of the above system categories of medical treatment as well as any treatment regimes or medical device usage.

The treatment system 10 is suitable for treating a subject's subcutaneous adipose tissue, such as by cooling. “Subcutaneous tissue” can include tissue lying beneath the dermis and includes subcutaneous fat, or adipose tissue that may be composed primarily of lipid-rich cells, or adipocytes. When cooling subcutaneous tissues to a temperature lower than 37° C., subcutaneous lipid-rich cells can be affected selectively. In general, the epidermis and dermis of the subject 11 lack lipid-rich cells compared to the underlying lipid-rich cells forming the adipose tissue. Because non-lipid-rich cells usually can withstand colder temperatures better than lipid-rich cells, the subcutaneous lipid-rich cells can be affected selectively without affecting the non-lipid-rich cells in the dermis, epidermis and other surrounding tissue. In some embodiments, the treatment system 10 can apply cooling temperatures to the skin of the subject 11 in a range of from about -20° C. to about 20° C. In other embodiments, the cooling temperatures can be from about -20° C. to about 10° C., from about 0° C. to about 20° C., from about -15° C. to about 5° C., from about -5° C. to about 15° C., or from about -10° C. to about 0° C.

Without being bound by theory, the selective effect of cooling on lipid-rich cells is believed to result in, for example, membrane disruption, cell shrinkage, disabling, destroying, removing, killing or other method of lipid-rich cell alteration. Such alteration is believed to stem from one or more mechanisms acting alone or in combination. It is thought that such mechanism or mechanisms trigger an apoptotic cascade, which is believed to be the dominant form of lipid-rich cell death by non-invasive cooling.

Apoptosis, also referred to as “programmed cell death”, is a genetically-induced death mechanism by which cells self-destruct without incurring damage to surrounding tissues. An ordered series of biochemical events induce cells to morphologically change. These changes include cellular blebbing, loss of cell membrane asymmetry and attachment, cell shrinkage, chromatin condensation, and chromosomal DNA fragmentation. Injury via an external stimulus, such as cold exposure, is one mechanism that can induce cellular apoptosis in cells. Nagle, W. A., Soloff, B. L., Moss, A. J. Jr., Henle, K. J. “Cultured Chinese Hamster Cells Undergo Apoptosis After Exposure to Cold but Nonfreezing Temperatures” *Cryobiology* 27, 439-451 (1990).

One aspect of apoptosis, in contrast to cellular necrosis (a traumatic form of cell death causing local inflammation), is that apoptotic cells express and display phagocytic markers on the surface of the cell membrane, thus marking the cells

for phagocytosis by macrophages. As a result, phagocytes can engulf and remove the dying cells (e.g., the lipid-rich cells) without eliciting an immune response. Temperatures that elicit these apoptotic events in lipid-rich cells may contribute to long-lasting and/or permanent reduction and reshaping of subcutaneous adipose tissue.

One mechanism of apoptotic lipid-rich cell death by cooling is believed to involve localized crystallization of lipids within the adipocytes at temperatures that do not induce crystallization in non-lipid-rich cells. The crystallized lipids selectively may injure these cells, inducing apoptosis (and may also induce necrotic death if the crystallized lipids damage or rupture the bi-lipid membrane of the adipocyte). Another mechanism of injury involves the lipid phase transition of those lipids within the cell's bi-lipid membrane, which results in membrane disruption, thereby compromising the integrity and/or function of the cell membrane and inducing apoptosis. This mechanism is well-documented for many cell types and may be active when adipocytes, or lipid-rich cells, are cooled. Mazur, P., “Cryobiology: the Freezing of Biological Systems” *Science*, 68: 939-949 (1970); Quinn, P. J., “A Lipid Phase Separation Model of Low Temperature Damage to Biological Membranes” *Cryobiology*, 22: 128-147 (1985); Rubinsky, B., “Principles of Low Temperature Preservation” *Heart Failure Reviews*, 8, 277-284 (2003). Other yet-to-be understood apoptotic mechanisms may exist, based on the relative sensitivity of lipid-rich cells to cooling compared to non-lipid rich cells.

In addition to the apoptotic mechanisms involved in lipid-rich cell death, local cold exposure also is believed to induce lipolysis (i.e., fat metabolism) of lipid-rich cells and has been shown to enhance existing lipolysis which serves to further increase the reduction in subcutaneous lipid-rich cells. Vallerand, A. L., Zamecnik, J., Jones, P. J. H., Jacobs, I. “Cold Stress Increases Lipolysis, FFA Ra and TG/FFA Cycling in Humans” *Aviation, Space and Environmental Medicine* 70, 42-50 (1999).

In various embodiments, the treatment system 10 includes a controller, a computing device, a data acquisition device, a chiller, and one or more applicators. The treatment system 10 can employ these components in various embodiments to receive a selection of a treatment profile and apply the selected treatment to a subject 11.

FIG. 1 is a perspective view illustrating a treatment system 10 for non-invasively removing heat from subcutaneous lipid-rich target areas of a subject 11 such as an abdominal area 12 or another suitable area. The system 10 may include a treatment device 14 that engages the target area of the subject 11 for cooling or removing heat from the subcutaneous lipid-rich cells of the subject 11. It will be understood that treatment devices 14 can have various, configurations, shapes and sizes suitable for different body parts such that removing heat from any subcutaneous lipid-rich target area of the subject 11 can be achieved.

The treatment device 14 includes an applicator 15 that cools a target area of the subject 11, such as a human or animal (i.e., “subject 11”). Various types of applicators may be applied during treatment, such as a vacuum applicator (which may be used in combination with a massage or vibrating capability). Each applicator may be designed to treat target areas of the patient's body, such as chin, cheeks, arms, pectoral areas, thighs, calves, buttocks, back, abdomen, “love handles,” and so forth. For example, a vacuum applicator may be applied at the back region with or without massage or vibration. Examples of applicators and their configurations usable with system 10 are described variously



in, e.g., commonly assigned U.S. Patent Publication Nos. 2007/0198071, 2008/0077201, and 2008/0077211 and in U.S. patent application Ser. No. 11/750,953. In certain embodiments, the system **10** may also include a patient protective device, e.g., a sleeve or liner, for preventing direct contact between the applicator **15** and a patient's skin, and thereby reducing the likelihood of cross-contamination between patients, minimizing cleaning requirements for the applicator **15**, etc. In certain other embodiments, the patient protection device may also include or incorporate various storage, computing, and communications devices, such as a radio frequency identification (RFID) component, allowing for example, use to be monitored and/or metered. Examples of liners or patient protection devices are described herein and in commonly assigned U.S. Patent Publication No. 2008/0077201.

The system **10** may further include a treatment unit **16** and supply and return fluid lines **18a** and **18b** between the treatment device **14** and the treatment unit **16**. The treatment unit **16** can remove heat from a coolant to a heat sink and provide a chilled coolant to the treatment device **14** via the fluid lines **18a** and **18b**. Alternatively, the treatment unit **16** can circulate warm coolant to the treatment device **14** during periods of warming. Examples of the circulating coolant include water, glycol, synthetic heat transfer fluid, oil, a refrigerant, and/or any other suitable heat-conducting fluid. The fluid lines **18a** and **18b** may be hoses or other conduits constructed from polyethylene, polyvinyl chloride, polyurethane, and/or other materials that can accommodate the particular circulating coolant. The treatment unit **16** may be a refrigeration unit, a cooling tower, a thermoelectric chiller or cooler, or any other device capable of removing heat from a coolant. Alternatively, a municipal water supply (i.e., tap water) may be used in place of the treatment unit. Furthermore, one skilled in the art will recognize that there are a number of other cooling technologies that could be used such that the treatment unit or chiller need not be limited to those described herein.

In the embodiment illustrated in FIG. 1, the treatment device **14** may provide mechanical energy to create a vibratory, massage, and/or pulsatile effect, such as described in, e.g., U.S. Pat. No. 7,367,341 and commonly assigned U.S. Patent Publication No. 2008/0287839. The treatment device **14** may include one or more actuators, such as motors with eccentric weight, or other vibratory motors such as hydraulic motors, electric motors, pneumatic motors, solenoids, other mechanical motors, piezoelectric shakers, and so on, to provide vibratory energy to the treatment site. Further examples include a plurality of actuators for use in connection with a single treatment device **14** and/or applicator **15** in any desired combination. For example, an eccentric weight actuator (not shown) may be coupled to a housing **14a** (FIG. 3D) of the treatment device **14** and a pneumatic motor (not shown) may also be coupled to the housing **14a** such that different effects may be provided to different sections of the same treatment device **14**. This, for example, would give the operator of treatment system **10** options for differential treatments of lipid rich cells within a single target area or among multiple target areas of subject **11**. The use of one or more actuators and actuator types in various combinations and configurations with a treatment device **14** or applicator **15** may be possible.

The treatment device **14** may include one or more Peltier-type thermoelectric elements. For example, the treatment device **14** may have a plurality of individually controlled thermal segments to create a custom spatial cooling profile and/or a time-varying cooling profile. Each custom treat-

ment profile can include one or more segments, and each segment can include a specified duration, a target temperature, and control parameters for features such as vibration, massage, vacuum, and other treatment modes. Cooling devices having multiple individually controlled heat exchanging units are described, e.g., in commonly assigned U.S. Patent Publication No. 2008/0077211.

The system **10** may further include a power supply **20** and a processing unit **24** operatively coupled to the treatment device **14** and the applicator **15**. In one example, the power supply **20** provides a direct current voltage via a power line **22** to a thermoelectric element that is coupled to the applicator **15** to remove heat from the subject **11**. The processing unit **24** may monitor process parameters via sensors (not shown) placed proximate to the treatment device **14** through a signal line **26** to, among other things, adjust the heat removal rate based on the process parameters. The processing unit **24** may further monitor process parameters to adjust the applicator **15** based on the process parameters.

The processing unit **24** may be in direct electrical communication with treatment device **14** through the signal line **26** as shown in FIG. 1; alternatively, processing unit **24** may be connected to treatment device via a wireless or an optical communication link. Processing unit **24** may be any processor, programmable logic controller, distributed control system, and so on. Note that power line **22** and the signal line **26** are shown in FIG. 1 without any support structure. Alternatively, power line **22** and the signal line **26** (and other lines including, but not limited to fluid lines **18a** and **18b**) may be bundled into or otherwise accompanied by a conduit or the like to protect such lines, enhance user safety and ergonomic comfort, ensure unwanted motion (and thus potential inefficient removal or extraction of heat from subject **11**) is minimized, provide electrical and thermal insulation and to provide an aesthetic appearance to system **10**. Examples of such a conduit include a flexible polymeric, fabric, or composite sheath, an adjustable arm, etc. Such a conduit (not shown) may be designed (via adjustable joints, etc.) to "set" the conduit in place for the treatment of subject **11**.

In another aspect, the processing unit **24** may be in electrical or other communication with an input device **28**, an output device **30**, and/or a control panel **14b** on the housing **14a** of the treatment device **14** (shown in FIG. 3B). The input device **28** may be a keyboard, a mouse, a touch screen, a push button, a switch, a potentiometer, any combination thereof, and any other device or devices suitable for accepting user input. The output device **30** may include a display or touch screen, a printer, a medium reader, an audio device, a visual device, any combination thereof, and any other device or devices suitable for providing user feedback. In the embodiment of FIG. 1, the input device **28** and the output device **30** may be combined in a single unit such as a touch screen. The control panel **14b** may include visual indicator devices or controls (lights, numerical displays, etc.) and/or audio indicator devices or controls. The control panel **14b** may be a component separate from the input device and/or output device as shown in FIG. 3B, may be integrated with one or more of the input and output devices **28** and **30**, may be partially integrated with one or more of the input and output devices **28** and **30**, may be in another location, and so on. In this example, processing unit **24**, power supply **20**, control panel, treatment unit **16**, input device **28**, and output device **30** are carried by a rack or cart **34** with wheels **36** for portability. In alternative examples, the processing unit **24** may be contained in, attached to, or integrated with the treatment device **14** and/or the applicator



## 11

15 and/or the subject 11 protection device described above. In yet another example, the various components may be fixedly installed or integrated with patient supports (e.g., chair, gurney, etc.) or other appliances in a treatment suite. Further details with respect to components and/or operation of treatment device 14, applicator 15, and other components may be found in commonly-assigned U.S. Patent Publication No. 2008/0287839.

Without being bound by theory, it is believed that in operation effective cooling from the applicator 15, which cools through conduction, depends on a number of factors. Examples of factors that impact heat removal or extraction from the skin area and related tissue include, for example, the surface area of the treatment unit, the temperature of the interface member, and the mechanical energy delivered to the tissue. More specifically, in operation, and upon receiving input to start a treatment protocol, the processing unit 24 can cause the treatment device 14 to cycle through each segment of a prescribed treatment plan. In so doing, the treatment device 14 applies power to one or more cooling segments, such as thermoelectric coolers (e.g., TEC “zones”), to begin a cooling cycle and, for example, activate features or modes such as vibration, massage, vacuum, etc. Using temperature or heat flux sensors (not shown in FIG. 1) proximate to the one or more treatment devices 14, the applicator 15, a subject 11 liner or device, the patient’s skin, or other locations or combinations thereof, the processing unit 24 determines whether a temperature or heat flux that is sufficiently close to the target temperature or heat flux has been reached. It will be appreciated that while a region of the body (e.g., adipose tissue) has been cooled or heated to the target temperature or by a target heat flux, in actuality that region of the body may be close but not equal to the target temperature, e.g., because of the body’s natural heating and cooling variations. Thus, although the system may attempt to heat or cool to the target temperature or by a target heat flux, a sensor may measure a sufficiently close temperature. If the target temperature has not been reached, power can be increased or decreased to change heat flux, as needed, to maintain the target temperature or “set-point.” When the prescribed segment duration expires, the processing unit 24 may apply the temperature and duration indicated in the next treatment profile segment. In some embodiments, temperature can be controlled using a variable other than, or in addition to, power.

According to examples of the system, the treatment device 14 and the applicator 15 enhance disruption of cooled adipose tissue. Further, the examples may provide reduced treatment time, reduced discomfort to the subject 11 and increased efficacy of treatment.

Examples of the system may provide the treatment device 14 and the applicator 15 which damage, injure, disrupt or otherwise reduce subcutaneous lipid-rich cells generally without collateral damage to non-lipid-rich cells in the treatment target area. In general, it is believed that lipid-rich cells can be affected selectively (e.g., damaged, injured, or disrupted) by exposing such cells to low temperatures that do not so affect non-lipid-rich cells to the same extent or in the same manner. As a result, lipid-rich cells, such as subcutaneous adipose tissue, can be damaged while other cells in the same region are generally not damaged even though the non-lipid-rich cells at the surface are subject to even lower temperatures. The mechanical energy provided by the applicator may further enhance the effect on lipid-rich cells by mechanically disrupting the affected lipid-rich cells.

In some examples of the system, the treatment device may be used with a substance that may (a) provide a thermal

## 12

coupling between the subject’s skin and the cooling unit(s) 50 to improve heat transfer therebetween; and/or (b) protect biological tissues of a subject from freezing damage (e.g., damage due to ice formation). The substance may be a fluid, e.g., a liquid, a gel, or a paste, which may be hygroscopic, thermally conductive, and biocompatible. Some embodiments according to the present disclosure may use a cryoprotectant including a temperature depressant that can assist in preventing freezing of non lipid-rich tissue (e.g., dermal tissue) during treatment. Suitable cryoprotectants and processes for implementing cryoprotectants are described in commonly-assigned U.S. Patent Publication No. 2007/0255362. The temperature depressant can be part of a cryoprotectant that may additionally include a thickening agent, a pH buffer, a humectant, a surfactant, and/or other additives. The temperature depressant may include, for example, polypropylene glycol (PPG), polyethylene glycol (PEG), dimethyl sulfoxide (DMSO), or other suitable alcohol compounds. In a particular embodiment, a cryoprotectant may include about 30% polypropylene glycol, about 30% glycerin (a humectant), and about 40% ethanol. In another embodiment, a cryoprotectant may include about 40% propylene glycol, about 0.8% hydroxyethylcellulose (a thickening agent), and about 59.2% water. In a further embodiment, a cryoprotectant may include about 50% polypropylene glycol, about 40% glycerin, and about 10% ethanol.

In one mode of operation, the applicator 15 is coupled to a treatment device 14. As described below, applying the treatment device 14 with a vacuum type force to the skin of the subject 11 may be advantageous to achieve efficient treatment. In general, the subject 11 has a body temperature of about 37° C., and the blood circulation is one mechanism for maintaining a constant body temperature. As a result, blood flow through the skin and subcutaneous layer of the region to be treated may be viewed as a heat source that counteracts the cooling of the subdermal fat. Cooling the tissue of interest accordingly requires not only removing the heat from such tissue but also that of the blood circulating through this tissue. Thus, temporarily reducing or eliminating blood flow through the treatment region, by means such as, e.g., applying a vacuum can improve the efficiency of tissue cooling. Additionally, a vacuum may pull skin and underlying adipose tissue away from the body which can assist in cooling underlying tissue by, e.g., lengthening the distance between the subcutaneous fat and the relatively well-perfused muscle tissue and by allowing the underlying adipose tissue simultaneously to be cooled from two sides. Embodiments according to the present disclosure may include an interior cavity into which the tissue is pulled. The interior cavity may be provided with a single cooling surface or a plurality of cooling surfaces disposed at discrete locations anywhere around the interior cavity, or the interior cavity may be partially or entirely provided with cooling surface(s).

By cooling the subcutaneous tissue to a temperature lower than 37° C., subcutaneous lipid-rich cells may be damaged selectively. In general, the epidermis and dermis of the subject 11 have lower amounts of fatty acids compared to the underlying lipid-rich cells forming the subcutaneous tissues. Because non-lipid-rich cells usually can withstand colder temperatures better than lipid-rich cells, the subcutaneous lipid-rich cells can be injured selectively while maintaining the non-lipid-rich cells in the dermis and epidermis. For example, the temperature range may be from about –20° C. to about 10° C., from about 0° C. to about 20° C., from about



## 13

−15° C. to about 5° C., from about −5° C. to about 15° C., or from about −10° C. to about 0° C.

FIG. 2 is a schematic illustrating a treatment device 14 for removing heat from subcutaneous lipid-rich cells. Treatment device 14 may include an applicator 15 with a cooling unit 50 and an interface layer 60. Interface layer 60 may be a plate, a film, a covering, or other suitable materials described herein and may serve as a subject 11 protection device described herein. The interface layer 60 is located between the cooling unit 50 and the skin 70 of a subject 11 receiving treatment via the treatment device 14. The cooling unit 50 may contain a communication component 55 that communicates with a controlling device 80 as described herein, and a measurement component 57 that measures one or more process parameters such as heat flux or the temperature of the cooling plate 50. The interface layer 60 may also contain a similar communication component 65 and a measurement component 67 that measures one or more process parameters such as heat flux or the temperature of the interface layer 60. For example, communication components 55, 65, and/or both may receive and transmit information from controlling device 80, such as temperature information determined by measurement units 57, 67, and/or both. The device 14 may also contain power components and other components described with respect to FIG. 1 and related applications.

In some cases, the patient protection device may include a sleeve and/or interface layer that is used to contact the patient's skin. One example of such a sleeve has a first sleeve portion and a second sleeve portion. The first sleeve portion may contact and/or facilitate the contact of the treatment device with the patient's skin. The second sleeve portion may be an isolation layer extending from the first sleeve portion. For example, the second sleeve portion may be constructed from latex, rubber, nylon, Kevlar®, or other substantially impermeable or semi-permeable material. The second sleeve portion may prevent contact between the patient's skin and the cooling plates, among other things. Further details regarding a patient protection device may be found in U.S. Patent Publication No. 2008/0077201.

The treatment device of the present disclosure may use vacuum to assist in forming a contact between the treatment device and the patient's skin. The vacuum may also be used to impart mechanical energy during treatment. Imparting mechanical vibratory energy to a target area by, e.g., repeatedly applying and releasing a vacuum to the subject's tissue, or for instance, modulating a vacuum level applied to the subject's tissue, creates a massage action during treatment.

FIG. 3A is a side view showing a portion of a treatment device 14 for removing heat from subcutaneous lipid-rich cells according to one embodiment of the present technology. FIG. 3B is a top view of the treatment device 14 showing the housing 14a and the control panel 14b, and FIG. 3C is a bottom view showing the applicator 15 coupled to the treatment device 14. FIG. 3D is a partially exploded perspective view of the treatment device 14 illustrating certain features of the applicator 15. FIG. 3E is a detail view of a component of the applicator 15. The applicator 15 may include a flexible portion 100, at least one generally rigid portion, for example, panels 200a and 200b, and at least one frame 300 (shown individually as frames 300a and 300b in FIG. 3E) between the panels 200a and 200b and the flexible portion 100. In the illustrated embodiment, the applicator 15 has an interior surface 92 and an exterior surface 94. The interior surface 92 defines an interior cavity 96 in which a vacuum may be drawn.

Referring to FIG. 3B, the control panel 14b may be located on the treatment device 14 so as to be readily

## 14

accessible to the operator of treatment system 10. The control panel 14b may provide the operator with the ability to control and/or monitor the treatment at the treatment device 14. For example, a first ON/OFF button may toggle the initiation or termination of a treatment and a second ON/OFF button may actuate a pump (not shown) for drawing a vacuum in the interior cavity 96. Indicator lights may provide a visual indication of, for example, whether a treatment is proceeding and/or whether the vacuum pump is activated.

Referring to FIG. 3C, the applicator 15 may be coupled to the treatment device 14 by a mounting plate 110 that clamps the flexible portion 100 into fluid-tight engagement with the housing 14a. The mounting plate 110 may be integrally formed with the flexible portion 100 or separately coupled to the flexible portion 110. An aperture 112 in the mounting plate 110 provides a passage for drawing a vacuum in the interior cavity 96. At least one fastener 114, e.g., four screws are shown in FIG. 3C, may releasably secure the mounting plate 110 to the housing 14a. Accordingly, removing the fasteners 114 allows the applicator 15 to be replaced with respect to the treatment device 14. In other embodiments, adhesive or another type of fastener may be used to couple the applicator 15 to the treatment device 14 either with or without using the mounting plate 110. The mounting plate 110 may also include one or more magnets 116 (two magnets 116a and 116b are shown in FIG. 3C) for releasably retaining the interface layer 60 (FIG. 2). Additionally, a sensor such as an electrical conductivity circuit detector (not shown) may be coupled through the at least two magnets 116 for sensing whether a liner 400 (FIGS. 6A-6C) is disposed in the interior cavity 96 of the applicator 15.

Referring to FIG. 3D, each rigid portion 200 may include a cold plate 210, at least one thermoelectric cooler (TEC) 230, a heat exchanger 240, a flexible printed circuit 250, and a protective housing 260 that covers the rigid portion 200. Individual rigid portions 200 are relatively stiff as compared to the flexible portion 100. Accordingly, the rigid portions 200 may resist bowing or other deformation as a vacuum is drawn in the interior cavity 96. Such deformation could reduce the ability of the TEC 230 to draw heat through the cold plate 210 from the subcutaneous lipid-rich cells.

FIGS. 4A-4D show different stages of assembling an individual rigid portion 200. In particular, FIG. 4A shows an embodiment of the cold plate 210, FIG. 4B shows an example of three measurement components 57 (FIG. 2) positioned on the cold plate 210, FIG. 4C shows three TECs 230 (shown individually as TECs 230a-230c) positioned over the measurement components 57, and FIG. 4D shows the heat exchanger 240 covering the TECs 230.

Referring to FIG. 4A, the cold plate 210 may be an aluminum or copper panel having a first surface 212 and a second surface 214. In other embodiments, the cold plate 210 may include other materials that are suitably rigid and thermally conductive. The cold plates 210 resist deformation, such as bowing while a vacuum is drawn in the interior cavity 96 (FIG. 3D), and maintain a thermal path between the TECs 230 (FIG. 3D) and the subject 11. The first surface 212, which may have a concave profile as shown in FIG. 4A, may include one or more recesses 216 (three recesses 216a-216c are shown in FIG. 4A) to receive the measurement components 57 (FIG. 2) and may include one or more shoulders 218 (four shoulders 218a-218d are shown in FIG. 4A) to position the TECs 230. The periphery of the first surface 212 may include a mounting flange 212a having one or more features (e.g., four apertures are shown) for coupling the rigid portion 200 to a frame 300 (FIGS. 3D and



15

3E). The cold plate **210** may also include a cutout **210a** through which wires for the measurement components **57** and/or the TECs **230** may pass.

Referring to FIG. 4B, the measurement components **57** (FIG. 2) may include, for example, at least one temperature sensor **220** (three temperature sensors **220a-220c** are shown in FIG. 4B) that are positioned on the first surface **212** to detect the temperature of the cold plate **210**. According to certain embodiments, the temperature sensors **220** may include thermistors (e.g., BetaTherm model 10K3MBD12 thermistors) or other types of sensors suitable for detecting the temperature at one or more locations on the cold plate **210**. Electrical wires from the temperature sensors **220** may be temporarily held in place by an adhesive coated polyimide film, such as Kapton®, or another suitable tape. Alternatively, the temperature sensors **220** may be inserted in the recesses **216a-216c** (FIG. 4A) with their wires passing through the cutout **210a** (FIG. 4A). Some embodiments according to the present disclosure may include measurement components **57** and **67** that measure parameters other than temperature, e.g., heat flux. Further, the measurement components **57** and **67** may use differential signals to reduce the coupling or influence of ambient noise into the measurement component signal(s).

Referring to FIG. 4C, the shoulders **218** may be used to position the TECs **230** over the temperature sensors **220** on the first surface **212**. The TECs **230** may be coupled with respect to the first surface **212** by a thermal interface pad (not shown), e.g., Loctite® Powerstrate® Xtreme™, or any suitable adhesive that does not provide appreciable thermal insulation between the TECs **230** and the cold plate **210**. The TECs **230** may include a Peltier device or another solid-state active heat pump that uses electricity to transfer heat from one side to the other side of the TECs **230**. In operation, the TECs **230** transfer heat from a “cold” side that is thermally coupled to the cold plate **210** to a “hot” side that is thermally coupled to the heat exchanger **240** (FIG. 3D). A sealant **232** (FIG. 4D), which may be a thermally conductive adhesive, bonds and provides a seal between the TECs and the cold plate **210**, bonds and provides a seal between the cold plate **210** and the heat exchanger **240**, and provides a seal around the wires leading from the temperature sensors **220** (FIG. 4B). Sealant **232** also serves to minimize the thermal resistance between the components with which it comes into contact. An example of a suitable sealant material is a thermally conductive elastomer available from the Dow Corning Corporation, Catalog No. 3-6651.

Referring to FIG. 4D, the heat exchanger **240** is positioned over the TECs **230** (FIG. 4C) and sealed relative to the cold plate **210** with the sealant **232**. The heat exchanger **240** includes a fluid inlet **242** and a fluid outlet **244** that cooperatively engage corresponding tubing (not shown) from the housing **14a** of the applicator **14**. The heat exchanger **240** may also include a cover **246** (also FIG. 3D) that provides access to the interior of the heat exchanger **240**. In operation, coolant may flow from the treatment unit **16** (FIG. 2), through the fluid supply line **18a** (FIG. 2), through the housing **14a**, through the fluid inlet **242**, to the heat exchanger **240**. The fluid absorbs heat from the “hot” side of the TECs **230** in the heat exchanger **240** and then flows through the fluid outlet **244**, through the housing **14a**, through the fluid return line **18b** (FIG. 2), to the treatment unit **16**. Accordingly, the treatment unit **16** can provide a heat sink for removing heat transferred by the TECs **230**, via the cold plate **210**, from the subcutaneous lipid-rich cells.

The flexible printed circuit **250** (FIG. 3D) may be coupled, e.g., adhered, to the second surface **214** of the cold

16

plate **210** and may include one or more heat flux or temperature sensors **252** (three temperature sensors **252a-252c** are shown in FIG. 3D) to detect the temperature of the patient’s skin. According to certain embodiments, the temperature sensors **252** may include thermistors, thermocouples, thermopiles, or other types of sensors suitable for detecting the temperature and/or heat flux at one or more locations on the patient’s skin. In order to provide a flat surface confronting the patient’s skin, the temperature sensors **252** can be mounted on the surface of the flexible printed circuit **250** that faces the cold plate **210**. The physical volume that each temperature sensor **252** occupies can be accommodated in corresponding recesses **214a** (FIG. 3D) that are formed in the second surface **214**. Any unoccupied volume in the recesses **214a** may be filled with foam, a room temperature vulcanizing material, or another backing material so that the flexible printed circuit **250** cannot deflect into the recesses **214a**. Kapton®, another polyimide film, or another suitable material may be included as a substrate for the flexible printed circuit **250**.

The signals output from the temperature sensors **252** can be electrically coupled via conductive traces (not shown) that may extend into the housing **14a** and electrically couple the temperature sensors **252** to electric circuitry (not shown) in the housing **14a** of the applicator **14** and/or to the electrical line **22** (FIG. 1). According to other embodiments, the signals output from the temperature sensors **252** can be transmitted wirelessly rather than via the conductive traces. In operation, the temperature sensors **252** can detect a temperature that can be correlated to the patient’s skin temperature, e.g., compensating for the presence of the interface layer **60** (FIG. 2), a thermal coupling fluid, and/or other factors that may cause the temperature measured by the temperature sensors **252** to deviate from the actual temperature of the patient’s skin or subcutaneous adipose tissue at a pre-defined depth.

The printed circuit **250** may also include a microelectronic device (not shown) that may include a microprocessor, memory, an input/output device, or combinations thereof. The microelectronic device may be electrically coupled to the signals output from the temperature sensors **252** and provide, for example, storage, computing, and/or communications for the output signals.

FIG. 5A shows a front view of an embodiment of the flexible portion **100** of the applicator **15**. FIG. 5B is an end view, FIG. 5C is a top view, and FIG. 5D is a bottom view of the flexible portion **100** shown in FIG. 5A. The flexible portion **100** can be molded from an elastically deformable plastic, e.g., silicone, elastomer, or another material that is suitably flexible. The flexible portion **100** may be transparent to facilitate viewing the skin through the flexible portion **100**. In other embodiments, the flexible portion **100** can be translucent or opaque. The flexible portion **100** may include a generally rectangular top surface coupled to the housing **14a** and a bottom surface including parallel or nearly parallel sides and elliptical ends.

Referring to FIG. 5A, the flexible portion **100** includes a central portion **120**, ends **140** (shown individually as ends **140a** and **140b**), and connectors **160** (shown individually as connectors **160a** and **160b**) that extend between and couple the bottoms of the ends **140**, i.e., opposite from the central portion **120**. In the embodiment shown in FIGS. 5A-5D, a “contour” or the shape of the applicator **15** that is fitted to the subject **11** includes a combination of the lips **144** and the connectors **160**. The flexible portion **100** also includes an interior surface **102**, an exterior surface **104**, and a port **106** that extends between the interior and exterior surfaces **102**



17

and 104 and through which a vacuum is drawn in the interior cavity 96 (FIG. 3D). The port 106 and the aperture 112 (FIG. 3C) are approximately aligned when the mounting plate 110 (FIG. 3C) is used to couple the flexible portion 100 to the housing 14a.

Referring to FIG. 5B, each end 140 has a top portion 142 extending from the central portion 120. The ends 140 and central portion 120 can be integrally molded or formed as separate components that are coupled together. As best shown in FIGS. 5B-5D, each end 140 has a lip 144 at the bottom, i.e., opposite from the top portion 142. The lip 144 may have a three dimensional geometry to facilitate conforming to a contour of a patient's skin. For example, with particular reference to FIG. 5D, a nominal configuration of the lip 144 may include straight segments 145a, arcuate segments 145b, or a combination of both when viewed from above or below. Concurrently, with particular reference to FIG. 5B, the nominal configuration of the lip 144 may include an arcuate profile view, and with particular reference to FIG. 5A, the frontal view of the nominal configuration of the lip 144 may include a downward slant with respect to the central portion 120. According to other embodiments, lip 144 may have different geometries suitable for conforming to the contours of given target areas of the applicator 15.

The individual ends 140 may have overall geometries between the top portion 142 and the lip 144 that also facilitate the lip 144 conforming to a contour of a cutaneous layer. In the embodiment shown in FIGS. 5A-5D, individual ends 140 may have a shoulder 146 that flares outwardly from the top portion 142 toward an arcuate waistline 148, an apron 150 including a conical flare between the waistline 148 and the lip 144, and flanks 152 including a panel in the shape of a five sided polygon. In the embodiment shown in FIG. 5A, individual flanks 152 extend from a tip at the top portion 142 to the lip 144, and extend from the shoulder and aprons 146 and 150 to a cutout 154. According to other embodiments, the ends 140 may have any suitable geometry that facilitates conformation of the lip 144 to the contours of individual target areas. For example, the shape of a typical human torso may vary between having a relative large radius of curvature, e.g., on the stomach or back, and having a relatively small radius of curvature, e.g., on the abdominal sides. Moreover, the size of a contour having an approximately consistent curvature may vary. Accordingly, an advantage of the present disclosure is the capability to provide flexible portions 100 with various geometries, e.g., shapes and sizes, to suitably conform to the cutaneous contours of individual target areas.

As shown in FIGS. 5A, 5B and 5C, the cutouts 154 (shown individually as cutouts 154a and 154b) are bounded by the flanks 152 of the ends 140, the central portion 120, and the connectors 160. The cutouts 154 receive the frames 300 (FIG. 3E) that, in turn, receive the rigid portions 200 as described herein.

According to certain embodiments of the present disclosure, the frames 300 (FIG. 3E) include rigid metal polygons, e.g., rectangles, around which the flexible portion 100 may be molded. Accordingly, the frames 300 may include a number of apertures, grooves, or other recesses into which the material of the flexible portion 100 may flow during a molding process to provide a strong, fluid-tight connection. Alternatively, the frames 300 can be adhered, welded or otherwise coupled to the flexible portion 100 in the openings 154. The frames 300 may also include materials other than metal, e.g., plastic, to which the rigid portions 200 can be secured. Alternatively, the flexible section can be clamped and/or bonded between two frames.

18

Each frame 300 (FIG. 3E) may be coupled to the cold plate 210 of an individual rigid portion 200 by any suitable fastener. For example, screws 302 (FIG. 3D) may extend through the apertures in the flange 212a (FIG. 4A) of the cold plate 210 and operably engage screw apertures (not shown) in the frame 300. Additionally, the frame 300 may be thermally coupled to the cold plate 210 via the flange 212a such that the TECs 230 may also transfer heat via the frame 300 from the subcutaneous lipid-rich cells.

FIG. 6A is a perspective view showing a disposable liner 400 on the applicator 15. FIG. 6B is an exploded view of the liner 400 and FIG. 6C is a perspective view showing the liner of FIG. 6A. The liner 400 may be one embodiment of the interface layer 60 (FIG. 2) for providing a barrier between the treatment device 14 and a subject 11 receiving a treatment via the treatment device 14.

Referring to FIGS. 6A and 6B, a cup shaped liner film 410 includes a central portion 412 and a peripheral portion 414. The central portion 412 generally lies against the interior surface 92 of the applicator 15. The peripheral portion 414 is sized and shaped to be folded back over the exterior surface 94 (FIGS. 6A and 3D) of the applicator 15, the protective housing 260 (FIG. 3D) of the rigid portion 200, and/or the housing 14a of the treatment device 14. Accordingly, the liner 400 shields the treatment device 14 from contact with the subject 11 and/or a thermal coupling fluid, e.g., a cryoprotectant gel including a temperature depressant, and provides a sanitary barrier that is inexpensive and thus disposable. With appropriate ancillary treatment or by use of a different design or materials, liner 400 may serve as a sterile barrier.

Referring to FIG. 6B, one embodiment of the liner film 410 includes an 80 Shore A polyether urethane film that is approximately 0.002 inches thick. This film may be cut to shape and then the edges may be welded or adhesively sealed to form the desired cup shape. The liner film 410 can alternatively include materials such as polyethylene or other thin gauge films that are generally impermeable, are generally 0.001-0.006 inches thick so as to avoid inhibiting heat movement from the subcutaneous lipid-rich cells, and have a Young's modulus of approximately 500-2,500 pounds per square inch (psi) to provide adequate elasticity.

The central portion 412 of the liner film 410 includes a hole or aperture 416 that aligns with the port 106 (FIGS. 5A, 5C and 5D) of the flexible portion 100 and the aperture 112 (FIG. 3C) of the mounting plate 110 when drawing a vacuum in the interior cavity 96. A membrane 420 is secured to the liner film 410 across aperture 416 to provide a selectively permeable barrier, e.g., a barrier that is generally permeable to air but is substantially impermeable to a thermal coupling material. The membrane 420 can include expanded polytetrafluoroethylene (ePTFE) or other hydrophilic or hydrophobic materials that have selective permeability. In the present example, membrane 420 includes ePTFE having a pore size in the range of approximately 0.1 to 10 microns that is bonded to a non-woven polyester backing (e.g., W.L. Gore & Associates, Flagstaff, Ariz., Part No. R10126). The periphery of the membrane 420 may be sealed to the central portion 412 by heat sealing, ultrasonic welding, adhesives, or any other suitable method that provides a fluid-tight coupling or joint.

A frame 430 may be coupled to the liner film 410 for shaping the central portion 412 of the liner film 410 in the vicinity of the flexible printed circuits 250 (FIG. 3D). The frame 430 may include a framework that generally corresponds to the shape and position of the frames 300 (FIG. 3E) along the interior surface 92 of the applicator 15. The frame



19

430 can include glycol-modified polyethylene terephthalate (PETG) or another material that can be bonded to the membrane 420 and liner film 410 on the central portion 412 by heat welding, ultrasonic welding, adhesives, or any other suitable method that provides a fluid-tight coupling or joint. Frame 430 may also serve to hold the liner film 410 taut over the flexible printed circuit 250 (FIG. 3D). Some embodiments according to the present disclosure may include a frame 430 that, along with the liner film 410, may be folded into a flattened arrangement that may facilitate packing one or more liners 400 in a container (not shown). Accordingly, the frame 430 may include segmentation perforations or one or more living hinges. Other embodiments according to the present invention may not include the framework corresponding to the frame 300 or other portions of a frame 430 shown in FIGS. 6B and 6C.

Magnetic or ferromagnetic strips 440 (shown individually as strips 440a and 440b) are coupled to the frame 430 for releasably attaching the liner 400 to the treatment device 14. The strips 440 may include a ferrous material and may be adhered on opposite sides of the aperture 416 using double sided tape (e.g., including acrylic adhesive 350) or another suitable adhesive for coupling strips 440 to frame 430 or liner film 410. The strips 440 cooperatively engage the magnets 116 on the mounting plate 110 to position and retain the liner 400 at the bottom of the cavity 96. Additionally, the strips 440 may be electrically conductive for closing a circuit (not shown) that detects the liner 440 is in position on the treatment applicator 14. Hang tabs 450 (shown individually as hang tabs 450a and 450b) may be coupled to the peripheral portion 414 of the liner film 410 for engaging cooperating features on treatment device 14 to retain the liner 440.

Referring to FIG. 6C, the convex side of the central portion 412 of the liner film 410 may be coupled to the membrane 420 and the frame 430 coupled over the membrane 420. Alternatively, the one or both of the membrane 420 and the frame 430 may be coupled on the concave side of the central portion 412, and/or the order in which the liner film 410, the membrane 420, and the frame 430 are coupled may be rearranged. The strips 440 are generally provided as the outermost layer on the convex side of the central portion 412 to facilitate their cooperation with the magnets 116, but the strips 440 may be coupled in other arrangements with respect to the liner film 410, the membrane 420, and the frame 430.

FIG. 7A shows a token 500 interfacing with the treatment device 14. FIG. 7B shows a perspective view of the token 500 and FIG. 7C shows an embodiment of a receptacle 520 on the treatment device for receiving the token 500. FIG. 7D shows alternate receptacles according to another embodiment and FIG. 7E shows alternate token according to another embodiment. According to the embodiment shown in FIG. 7A, the interface between the token 500 and the treatment device 14 may provide a number of structural and/or functional advantages. The structural advantages may include, for example, preventing the token 500 from being incorrectly coupled to the treatment device and the functional advantages may include, for example, monitoring the system 10.

Referring to FIG. 7B, the token 500 includes an enclosure 510, a microelectronic device 520 disposed within the enclosure 510, and a set of contacts 530 that are electrically coupled to the microelectronic device 520 and extend from the enclosure 510. The enclosure 510 includes a first asymmetric mating feature 512. In the embodiment shown in FIG. 7B, the first asymmetric mating feature 512 includes a

20

female recess 512a within a rim 512b. The set of contacts 530 may extend from the female recess 512a. As also shown in the embodiment of FIG. 7B, the shape of the rim 512b may include, for example, an arcuate side and three straight sides. Accordingly, the first asymmetric mating feature 512 in general and the shape of the rim 512b in particular are asymmetrical such that the enclosure 510 can matingly engage the receptacle 520 (FIG. 7C) in only one relative orientation. The asymmetrical mating feature 512 may be implemented adjacent to contacts 530 as shown in Figure B, or it may be implemented involving other portions of enclosure 510. Some embodiments according to the present disclosure may include a slot in the treatment device 14 that cooperatively receives some or all of the enclosure 510 in only one relative arrangement, e.g., to avoid or prevent inserting the token 500 into the slot in an unintended relative arrangement.

The microelectronic device 520 may include a microprocessor, memory, an input/output device, or combinations thereof that provide, for example, computing, storage, and/or communications. The microelectronic device 520 may, for example, meter the usage of the treatment device 14. According to some embodiments of the present disclosure, the microelectronic device 520 may count down from a predetermined limit. Use of the treatment device 14 is, accordingly, allowed when a non-zero number of counts remain and is prohibited when a zero number of counts remain prior to the intended use. The amount of treatments for which the treatment device 14 and/or system 10 can be used may be limited to an amount that is predetermined, e.g., pre-purchased by the system operator. Accordingly, when the microelectronic device 520 determines that the usage limit is reached, the microelectronic device 520 may communicate to the operator that it is necessary to obtain, e.g., purchase, additional treatments by replacing or replenishing the token 500. The token 500 may be replenished, for example, via the internet. Also, different operators may possess individual tokens 500 to monitor and limit their specific usage. The microelectronic device 520 may also, for example, store profiles of treatment parameters and limits. Examples of parameters may include identifying the body part that is to be targeted for treatment, the duration of a treatment, the number of cycles in a treatment, the heat extraction rate during a treatment, etc. Examples of limits that the microelectronic device 520 may store include, for example, limiting certain applicators, systems and/or operators in specific geographic regions to specific treatments.

The token 500 may also be used in conjunction with the treatment device 14 and the processing unit 24 (FIG. 2) to provide information about the system 10 (FIG. 2). For example, the token 500 may monitor the performance of the system 10, including storing a record of any system abnormalities, and/or to direct a prescribed maintenance schedule. When the token 500 is replaced or replenished, system information can be downloaded from the microelectronic device 520. The microelectronic device 520 can also be used to load software upgrades or operating parameters to the system 10 and provide new or modified profiles of treatment parameters.

The set of contacts 530 may provide a second asymmetric mating feature 532. In the embodiment shown in FIG. 7B, the second asymmetric mating feature 532 includes a first tab 532a and a second tab 532b that are different sizes. Accordingly, the tabs 532a and 532b are asymmetrical such that the set of contacts 530 can matingly engage the receptacle 520 (FIG. 7C) in only one relative orientation that also corresponds to the first asymmetric mating feature 512.



## 21

The set of contacts **530** can be located on only the first tab **532a**, on only the second tab **532b**, or distributed on both the first and second tabs **532a** and **532b**. Additionally, the set of contacts **530** can be located on only one face of the tabs **532a** and **532b**, on both faces of the tabs **532a** and **532b**, or a combination thereof. Moreover, the second asymmetric mating feature **532** may include more than one or two tabs.

Referring to FIG. 7C, the receptacle **520** provides the counterparts to the asymmetric mating features on the token **500**. In the embodiment shown in FIG. 7C, the receptacle **520** includes a male projection **522** that is shaped and sized to be received in the female recess **512a** of the token **500** (FIG. 7B) in only one relative orientation. Specifically, the male projection **522** may include, for example, an arcuate side and three straight sides that are the counterparts to the rim **512b** on the token **500** (FIG. 7B). As also shown in the embodiment of FIG. 7C, the receptacle **520** includes a first slot **524a** that is shaped and sized to receive the first tab **532a** of the token **500** (FIG. 7B) and a second slot **524b** that is shaped and sized to receive the second tab **532b** of the token **500** (FIG. 7B). Accordingly, the first and second slots **524a** and **524b** receive the first and second tabs **532a** and **532b**, respectively, in only one relative orientation.

The receptacle **520** may also include a wiper **526** for wiping any material, e.g., a thermal coupling fluid such as a cryoprotectant gel including a temperature depressant, off the set of contacts **530** when they are being inserted into the receptacle **520**. The wiper **526** may include, for example, a flap or another projection that is biased into contact with the set of contacts **530** so as to squeegee the material off the set of contacts **530**. Removing such material from the set of contacts **530** may avoid or eliminate interference in electrically connecting with the set of contacts **530** and protect the interior electronics from electrical shorts or corrosion.

The asymmetric mating features on the enclosure **510** and their counterparts on the receptacle **520** may help to avoid contaminating the interface between the token **500** and the treatment device **14**. For example, when the token **500** and the treatment device **14** are interfaced, the enclosure **500** and the receptacle **520** overlap one another such that debris would have to follow a tortuous path including moving over the rim **512b**, between the rim **512b** and the male projection **522**, across the top of the male projection **522**, and into the first and/or second slots **524a** and **524b**. Additionally, the male projection **522** may help to avoid contamination when the token **500** and the treatment device **14** are not interfaced because debris would have to climb the male projection **522** before entering the first and/or second slots **524a** and **524b**.

Other embodiments in accordance with the present disclosure may include reversing certain members. For example, the rim and female recess may be provided on the treatment device **14** and the male projection may extend from the token **500**. Also, the set of contacts may project from the treatment device **14** and the token **500** can include the counterpart connection(s) for electrically engaging the set of contacts.

The curved sides of the rim and male projection may be oriented to shed debris. Orienting convex surfaces upward in a nominal arrangement of the treatment device **14**, e.g., with the treatment device **14** sitting on the control panel **14b** (FIG. 3B) and the applicator **15** extending upward, may tend to shed debris rather than allowing it to collect on a flat or concave surface.

Referring to FIG. 7D, the housing **14a** may include one or more types of guides **530** (shown individually as guides **530a** and **530b**) to assist in orienting and inserting the token (not shown) into the treatment device **14**. For example, the

## 22

guides **530** may be desirable for orienting and inserting the token **500** perpendicular to a surface of the housing **14a**.

Referring to FIG. 7E, a single asymmetric mating feature may be provided to ensure that the token **500** correctly interfaces with the treatment device **14**. For example, a single tab may be implemented in lieu of the second asymmetric mating feature **532** (FIGS. 7B and 7C). Accordingly, the first asymmetric mating feature **512** (also FIGS. 7B and 7C) may provide sufficient asymmetry to ensure that the token **500** is not incorrectly inserted into the treatment device **14**.

Other embodiments in accordance with the present disclosure may include interfacing the token **500** with other features of the treatment system **10**. For example, the receptacle **520** for the token **500** may be disposed on the processing unit **24**, the input device **28**, the output device **30**, or elsewhere disposed on the cart **34** (FIG. 1). Receptacles **520** for matingly engaging the token **500** may also be provided at multiple locations on the treatment system **10**, including on the treatment device **14**.

Embodiments of some applicators according to the present disclosure include variable geometry cooling panels. For example, the number and relative arrangement of the cooling panels may be varied to position panels closer together or in various relative orientations.

Referring to FIG. 7F, an adjustor **600**, here shown as clamp **602**, is depicted. It may be advantageous for particular treatment regimens to adjust the dimensions of the interior cavity **96**, e.g., the shape of the contour, the distance between facing portions of flexible portion **100**, and/or facing portions **250a** and **250b** (not shown) of the flexible printed circuit **250** in interior cavity **96**, etc., when tissue is drawn into the applicator **15** during treatment. According to some embodiments of the present disclosure, the adjustor **600** shapes, sizes, fixes, or controls the dimensions of the interior cavity **96** to help ensure greater uniformity of cooling or heat extraction from the subcutaneous lipid-rich tissue that is drawn into the interior cavity **96** by vacuum during treatment. Such uniformity may be accompanied by improved efficiency of treatment and greater and/or more uniform selective damage, injury or disruption of the affected subcutaneous lipid-rich tissue. A distance between opposite faces of the interior cavity **96**, or gap width, of between approximately 0.5 and 3 or more inches may be desired. Alternatively, a gap width of between approximately 1.0 and 2.0 inches, or alternatively approximately 1.5 inches, may be desired.

In the embodiment of FIG. 7F, clamp **602** includes first clamp portion **602a** and second clamp portion **602b** having a fixed length that corresponds to the desired gap width. Two receiving portions **603** on each of first and second clamp portions **602a** and **602b** are affixed to two tabs **200c** on each of panels **200a**, **200b** by screws, adhesive, welding, etc., or it may be integrally formed with panels **200a**, **200b**. Any suitable material, such as a metal, polymeric or other material to include cast urethane, may be used for clamp **602**. An advantage of clamp **602** in the configuration shown in FIG. 7F is that it allows the lips (edges) of flexible portion **100** to remain flexible, in turn allowing the contour of applicator **15** to conform to different subject **11** body sizes and/or geometries. Other clamp **602** configurations may be used to affect the desired gap width control.

The adjuster **600** may be affixed to applicator **15** during the manufacturing or assembly process prior to treating a subject **11**. This ensures that as tissue of the subject **11** is drawn into the interior cavity **96** of flexible portion **100**, the desired gap width is achieved. Alternatively, adjuster **600**



may be temporarily affixed to applicator **15** so that an operator, such as a physician, may adjust the dimensions of the interior cavity **96** either before or after tissue has been drawn into the interior cavity **96**. The adjuster **600** may additionally or alternatively include clips, drawstrings, or other mechanisms suitable for reshaping and/or resizing the interior cavity of the applicator. The adjuster **600** may adjust any dimension of the cavity and is not limited to a single dimension. Some embodiments according to the present disclosure may include at least one insert that may be introduced into the interior cavity of the applicator to change at least one internal dimension of the cavity.

Embodiments of some applicators according to the present disclosure include variable orientation cooling panels. For example, cooling panels on opposite sides of a vacuum cup can be oriented in a splayed-out arrangement when applied to a relatively large tissue segment, and in a narrowed arrangement, e.g., with the cooling plates arranged roughly parallel to one another, when applied to a relatively small tissue segment. Two clamps **602**, e.g., one located nearer the contour mouth and one nearer the vacuum port **106** (FIGS. **5A**, **5C** and **5D**), may provide adjustable gap width control and/or controlling the relative cooling plate angle. The system **10** may include sensors (not shown) to sense the adjuster position or adjusted dimensions of the interior cavity **96**, the gap width, and/or cooling plate angle and use this information to modify one or more treatment parameters available for selection by a practitioner, e.g., to ensure consistent performance for the cavity dimensions selected by the practitioner.

Spacing and orienting the cooling panels between different arrangements may be used to reduce patient discomfort and affect the degree of tissue cooling that can be achieved within a treatment cycle. For example, the splayed-out arrangement of the cooling panels maintains a large enough mouth to allow tissue to pass easily into the cup and be drawn along the cooling panels for treatment without causing a high degree of patient discomfort. On the other hand, the narrowed arrangement provides faster cooling and shorter treatments to also decrease patient discomfort. Accordingly, angling or fluting the cup geometry may be used to optimize the time required to achieve sufficient cooling for subcutaneous fat layer reduction. Further, cooling tissue more quickly allows longer treatment times that, along with shorter treatment times, allows a practitioner to vary the dosage and thereby control efficacy in a single treatment cycle.

Additionally, a flared edge or taper on the cup edge may reduce the friction that the pad/liner/tissue experience when vacuum pressure is applied and they are drawn up into the applicator cup. A flare may also reduce a "pinch" point where an edge of the applicator comes into contact with the patient's soft tissue causing discomfort and potential bruising after the treatment.

According to a further embodiment, the token **500** and the treatment device **14** may each have corresponding arrangements that allow any relative orientation to be used for mating engagement. For example, the token **500** may include a symmetrical enclosure that can interface with the treatment device **14** in any of a plurality of relative orientations, and redundant sets of contacts may be distributed such that the proper electrical connections may be completed in any of the plurality of relative orientations.

In operation, an embodiment according to the present disclosure may include preparing a target area for treatment by topically applying to the patient's skin a pad, e.g., Webril® manufactured by Kendall, which is saturated with

thermal coupling fluid such as a cryoprotectant gel including a temperature depressant. The treatment device **14** is prepared by positioning the central portion **412** of a liner **400** in the interior cavity **96** with the strips **440** cooperatively engaging the magnets **116**, folding the peripheral portion **414** of the liner **400** over the exterior surface **94** of the applicator **15**, and coupling the hang tabs **450** to treatment device **14**. A token **500** is interfaced with the treatment device **14**, the treatment device is positioned over the pad on top of the target area of the patient's skin, and a treatment may be initiated using at least one of the control pad **14b** and the touch screen **28**.

FIG. **8** is a perspective view showing a vacuum applicator **1015** for a treatment to remove heat from subcutaneous lipid-rich cells in accordance with another embodiment of the technology. The vacuum applicator **1015** may have a generally rectangular top face and a bottom face including parallel sides and elliptical ends. In the illustrated embodiment, the vacuum applicator **1015** has an interior surface **1092** and an exterior surface **1094**. The interior surface **1092** defines an interior cavity **1096** in which a vacuum is drawn. The vacuum applicator **1015** may further include a flexible portion **1100** and at least one rigid portion including at least one panel **1200** (the embodiment of FIG. **8** includes individual panels **1200a** and **1200b**, however, only panel **1200a** is shown in FIG. **8**) and at least one frame **1300** (the embodiment shown in FIG. **8** includes individual frames **1300a** and **1300b**). In operation, a disposable patient protection device (PPD) **1400** may be used in conjunction with the vacuum applicator **1015**.

FIG. **9A** is a front view of an embodiment of the flexible portion **1100** of the vacuum applicator **1015**. FIG. **9B** is an end view, FIG. **9C** is a top view, and FIG. **9D** is a bottom view of the flexible portion **1100** shown in FIG. **9A**. The flexible portion **1100** can be molded from an elastically deformable plastic, e.g., silicone, or another material that is suitably flexible. The flexible portion **1100** may be transparent to facilitate viewing the skin through the flexible portion **1100**. In other embodiments, the flexible portion **1100** can be translucent or opaque.

Referring to FIG. **9A**, the flexible portion **1100** includes a central portion **1120**, ends **1140** (shown individually as ends **1140a** and **1140b**), an interior surface **1102**, and an exterior surface **1104**. The flexible portion **100** may also include a port **1122** having an obstruction **1128** that partially occludes the port **1122** to inhibit the skin or another solid structure from entering the port **1122** while permitting air or other fluids to pass through the port **1122**.

Referring to FIGS. **9A** and **9B**, each end **1140** has a top portion **1142** extending from the central portion **1120**. The ends **1140** and central portion **1120** can be integrally molded or separate components. As best shown in FIGS. **9A**, **9B** and **9D**, each end **1140** has a lip **1144** at the bottom, i.e., opposite from the top portion **1142**. The lip **1144** may have a three dimensional geometry to facilitate conforming to a contour of a cutaneous layer (not shown in FIGS. **9A-9D**). For example, with particular reference to FIG. **9D**, a nominal configuration of the lip **1144** may include straight segments **1145a**, arcuate segments **1145b**, or a combination of both when viewed from above or below. Concurrently, with particular reference to FIG. **9B**, the nominal configuration of the lip **1144** may include an arcuate profile view, and with particular reference to FIG. **9A**, the frontal view of the nominal configuration of the lip **1144** may include a downward slant with respect to the central portion **1120**. Accord-



25

ing to other embodiments, lip 1144 may have different geometries suitable for conforming to the contours of given cutaneous layers.

The individual ends 1140 may have overall geometries between the top portion 1142 and the lip 1144 that also facilitate the lip 1144 conforming to a contour of a cutaneous layer. In the embodiment shown in FIGS. 9A-9D, individual ends 1140 may have a shoulder 1146 that flares outwardly from the top portion 1142 toward an arcuate waistline 1148, an apron 1150 including a conical flare between the waistline 1148 and the lip 1144, and flanks 1152 including a panel in the shape of a five sided polygon. In the embodiment shown in FIG. 9A, individual flanks 1152 extend from a tip at the top portion 1142 to the lip 1144, and extend from the shoulder and aprons 1146 and 1150 to a periphery 1154. According to other embodiments, the ends 1140 may have any suitable geometry that facilitates conformation of the lip 1144 to the contours of individual cutaneous layers. For example, the shape of a typical human torso may vary between having a relative large radius of curvature, e.g., on the stomach or back, and having a relatively small radius of curvature, e.g., on the abdominal sides. Moreover, the size of a contour having an approximately consistent curvature may vary. Accordingly, an advantage of the present disclosure is the capability to provide flexible portions 1100 with various geometries, e.g., shapes and sizes, to suitably conform to the contours of individual cutaneous layers.

As shown in FIGS. 9A, 9C and 9D, the periphery 1154 extends up the flank 1152 of the end 1140a, across the central portion 1120, and down the flank 1152 of the end 1140b. The periphery 1154 may include grooves 1156 (FIG. 9D) and/or ribs 1158 (FIG. 9D) that provide the flexible portion 1100 with a fluid tight seal. The periphery 1154 may also include a plurality of apertures 1160 for coupling the flexible portion 1100 to one or more rigid portions 1200. The periphery 1154 accordingly defines a cutout from the flexible portion 1100, and the cutout receives an individual rigid portion.

FIG. 10 shows a perspective view of an embodiment of the panel 1200 for the rigid portion of vacuum applicator 1015. The panels 1200 resist deformation and are thermally conductive to provide a consistent mechanical and thermal interface between the cooling plates (not shown in FIG. 10) and the subject 11. In the embodiment shown in FIG. 10, the panels 1200 may be an aluminum panel having an interior surface 1202 and an exterior surface 1204. In other embodiments, the panels 1200 may include other materials that are suitably rigid and thermally conductive. The panels 1200 resist deformation, such as bowing, while a vacuum is drawn in the interior cavity 1096 to maintain an uninterrupted thermal path between the cooling plates 50 (FIG. 2) and the subject 11. More specifically, deformation of the panels 1200 could cause the vacuum applicator 1015 to separate from the cooling plates 50 and thereby reduce the ability of the cooling plates 50 to draw heat from the interior cavity 1096 of the vacuum applicator 1015. The panels 1200 may be coupled to the flexible portion 1100 with individual frames 1300.

FIG. 11A shows an exploded perspective view of an embodiment according to the present disclosure of an individual frame 1300 of the vacuum applicator 15. The individual frame 1300 may include a first frame portion 1310 and a second frame portion 1340. In the embodiment shown in FIG. 11A, the first frame portion 1310 may have a plurality of tabs 1312 and/or pins 1314 that may be received in corresponding recesses 1342, slots 1344 and/or apertures 1346 of the second frame portion 1340 to secure the first and

26

second frame portions 1310 and 1340 together. For example, tips of the pins 1314 may subsequently be deformed, e.g., by heating and pressing, to prevent the pins 1314 from disengaging the slots 1344 and/or apertures 1346. In other embodiments, screws or any suitable fasteners may be used for securing together the first and second frame portions 1310 and 1340.

FIG. 11B shows a perspective view of an embodiment of the first frame portion 1310. In the embodiment shown in FIG. 11B, the first frame portion 1310 has a generally rectangular configuration that includes a bottom bar 1316, two side bars 1318a and 1318b, and a top bar 1320. Individual tabs 1312 can project from the bottom bar 1316, and individual pins 1314 may project from the side bars 1318a and 1318b and from the top bar 1320. In the embodiment shown in FIG. 9B, the side bars 1318a and 1318b and the top bar 1320 may include grooves 1322 and/or rib 1324 that provide the first frame portion 310 with a fluid tight seal.

FIG. 11C shows a perspective view of an embodiment according to the present disclosure of the second frame portion 340. In the embodiment shown in FIG. 11C, the second frame portion 1340 may have a generally rectangular configuration including a bottom bar 1348, two side bars 1350a and 1350b, and a top bar 1352. Individual recesses 1342 may be formed in the bottom bar 1348, and individual slots 1344 and/or apertures 1346 may be formed in the side bars 1350a and 1350b and in the top bar 1352. The bottom bar 1348, side bars 1350a and 1350b, and top bar 1352 may mutually define a rectangular surface 1354 surrounding an opening 1354a. The individual side bars 1350 may include one or more cams 1356 that may have inclined surfaces 1356a. The individual side bars 1350 may also include individual latches 1358. In the embodiment shown in FIG. 11C, individual latches 1358 are positioned on individual side bars 1350, e.g., on opposite sides of the opening 1354a, and individual cams 1356 are positioned on confronting lateral sides of the individual side bars 1350.

Several embodiments of the frame 1300 may provide a fluid tight coupling joining the flexible portion 1100 and the panels 1200. This feature may reduce or eliminate leaks that could adversely affect drawing a vacuum in the vacuum applicator 1015. Additionally, the cams 1356 on an individual frame portion 1340 may drive the cooling plates 50 against the panels 1200. The frames 1300 may accordingly provide consistent, uninterrupted thermal contact between the cooling plates 50 and the vacuum applicator 1015 for controlled cooling of the subject 11. Further, the latches 1358 on the second frame portions 1340 may releasably retain the cooling plates 50 with respect to the vacuum applicator 1015 to quickly and easily detach the cooling plates 50 from the panels 1200. This design has the additional benefit of allowing flexible portion 1100 having a different profile or geometry to suit or match particular subject 11 body shapes or profiles. Alternatively, rather than two frame portions 1310 and 1340, the same or a similar functionality may be achieved with a single frame portion (not shown) that is bonded, heat staked, insert molded, or otherwise affixed into flexible portion 1100.

The assembly of an embodiment according to the present disclosure of a vacuum applicator 1015 will now be described with respect to FIGS. 12A and 12B. FIG. 12A is an exploded view of an embodiment of a subassembly 1500 of the vacuum applicator 1015. The subassembly 1500 may include the panels 1200 (the embodiment shown in FIG. 12A includes individual panels 1200a and 1200b) and the second frame portions 1340 (the embodiment shown in FIG. 12A includes individual frame portions 1340a and 1340b).



The individual rectangular surfaces **1354** of the second frame portions **1340** overlay the individual exterior surfaces **1204** of individual panels **1200** and may be secured thereto, e.g., with an adhesive. The exterior surfaces **1204** of the panels **1200** are exposed by the openings **1354a** in the second frame portions **1340** to engage the cooling plates **50** (FIG. 2).

FIG. 12B is an exploded view showing an embodiment of a relationship of the flexible portion **1100**, the first frame portion **1310**, and the subassembly **1500**. The first frame portion **1310** is positioned with respect to the flexible portion **1100** such that (1) individual pins **1314** on the first frame portion **1310** may project through individual apertures **1160** in the flexible portion **1100**, and (2) the grooves **1322** on the top bar **1320** of the first frame portion **1310** may form a fluid tight seal with the ribs **1158** on the periphery **1154** of the flexible portion **1100**. The subassembly **1500** is then positioned on the flexible portion **1100** such that individual pins **1314** on the first frame portion **1310** are received in individual slots **1344** and/or apertures **1346** of the second frame portion **1340**. The second frame portion **1340** is moved with respect to the first frame portion **1310** such that individual tabs **1312** on the bottom bar **1316** of the first frame portion **1310** engage in individual recesses **1342** on the bottom bar **1348** of the second frame portion **1340**. The tips of the pins **1314** may subsequently be deformed, e.g., by heating and pressing, to prevent the pins **1314** from pulling out of the slots **1344** and/or apertures **1346**. Accordingly, the frames **1300** provide a fluid-tight connection between the flexible portion **1100** and the panels **1200**. The lips **1144** of the flexible portion **1100** in combination with the panels **1200** and the bottom bar **1348** of the second frame portion **1340** define a vacuum applicator aperture for contiguously engaging the skin **70** during a treatment.

FIG. 13A is a cross-section view showing an embodiment of a fluid separator **1170** in fluid communication between the interior cavity **1096** and the port **1122** of the vacuum applicator **1015**. In the embodiment shown in FIG. 13A, the fluid separator **1170** includes a pad **1172**, e.g., a foam pad, through which a gaseous fluid may flow but through which a liquid or gel flow is avoided. A moat **1174** may be formed in a gap between the pad **1172** and the interior surface **1012** of the vacuum applicator **1015**. The moat **1174** may provide a holding space for excess liquid or gel so as to make available a relatively liquid or gel free path through a top surface **1176** of the pad **1172** if the vacuum applicator **1015** were to be inverted such that the aperture **1018** was disposed above the pad **1172**.

FIG. 13B is a cross-section view showing another embodiment of a fluid separator **1180** in fluid communication between the interior cavity **1096** and the port **1122** of the vacuum applicator **1015**. In the embodiment shown in FIG. 13B, the fluid separator **1180** includes a tortuous path **1182**, e.g., a labyrinth, through which a gaseous fluid may flow but through which a liquid or gel flow is avoided. An opening **1184** to the tortuous path **1182** may be positioned in the interior cavity **1096** spaced from the interior surface **1102** so as to avoid ingesting a liquid or gel into the tortuous path **1182**.

FIG. 14 shows a plan view of an embodiment according to the present disclosure of the PPD **1400**. The PPD **1400** is one example of the interface layer **60** (FIG. 2) positioned between the vacuum applicator **1015** and the skin **70** of a subject. The PPD **1400** includes a substrate **1410** having a first surface **1402** for contacting the skin **70** of the subject **11** and a second surface **1404** that faces opposite the first

surface **1402**. The flexible PPD **1400** may be releasably attached to the vacuum applicator **1015** to be disposed of following a treatment.

The PPD **1400** may include temperature sensors **1420** (the embodiment shown in FIG. 14 includes individual temperature sensors **1420a-1420f**) such as thermistors. The signals output from the temperature sensors **1420** can be electrically coupled via conductive traces **1422** to an output connector **1424**. According to other embodiments, the signals output from the temperature sensors **1420** can be transmitted wirelessly rather than via the conductive traces **1422**. As shown in FIG. 14, the PPD **1400** may also have a microelectronic device **1426**. The microelectronic device **1426** may be electrically coupled to the signals output from the temperature sensors **1420** and provide, for example, storage, computing, and/or communications for the output signals.

Embodiments of the applicators **15** and **1015** according to the present disclosure include lips **144** and **1144**, respectively, which define at least a portion of the contour that contacts the skin **70** of the subject **11**. Contact may be via an interposed pad, e.g., Webril® manufactured by Kendall, which may be saturated with a gel. The shape of the contour should fit easily around a discrete tissue segment that has been identified for treatment. Longitudinal ends of the contour; also referred to as lips **144** with regard to the embodiment shown in FIGS. 5A-5D, may be shaped like ears to correspond to a curved body contour, e.g., the flank of a torso also referred to as a “love handle” area of the body. An approximately air-tight seal may be made between the applicator **15** or **1015** and the pad/skin surface if the contour closely fits the body contour without applying undo force to press the applicator **15** or **1015** against the subject **11**. The approximately air-tight seal and the vacuum pressure in the interior cavity **96** or **1096** of the applicator **15** or **1015** act on the subcutaneous fat and overlying skin to draw a tissue segment into the cup for treatment. If the contour does not fit the body of the subject **11**, then the approximately air-tight seal may not be achieved and the vacuum pressure is not established in the interior cavity **96** or **1096** to draw tissue into the applicator **15** or **1015** for treatment. An approximately air-tight seal may also be created by applying force to press the applicator **15** or **1015** into the soft tissue; however, the vacuum pressure therefore acts on subcutaneous fat and overlying skin that is under compression by the lips **144** and **1144**. Accordingly, less tissue/fat may be drawn into the applicator **15** or **1015** for treatment. Additionally, movement by the subject **11** during the course of treatment may sufficiently increase tension of the skin **70** in the treatment area to pull the skin **70** away from the applicator **15** or **1015**. As a result, the applicator **15** or **1015** may lose the approximately air-tight seal with the skin **70**, lose the vacuum pressure drawing tissue into the interior cavity **96** or **1096** for treatment, and cause the applicator **15** or **1015** to separate from the body of the subject **11**.

The inventors of the present disclosure have derived various contours suitable for treatments of a variety of lipid-rich cell deposits that may be naturally found on the human body. Accordingly, particular contours may be fitted to individual lipid-rich cell deposits to achieve an approximately air-tight seal, achieve the vacuum pressure for drawing tissue into an interior cavity for treatment, and use little or no force to maintain contact between an applicator and a patient. Such an approach may, however, become impractical because of the large number of unique shapes, their cost, and their storage. Embodiments of applicators according to the present disclosure include a firm or approximately rigid cup and one or more flexible or approximately rigid contour



elements that may be attached and detached with respect to the cup. Attaching one or more contour elements to an edge of a cup cavity creates a specific contour to approximately fit a tissue segment to be treated. The contour elements can be attached and detached in a plurality of combinations to achieve a desired contour for a treatment. Accordingly, a single applicator including a cup, rigid cooling panels, a vacuum port, control housing and/or umbilical cable may be combined with a set of interchangeable contour elements to form a wide variety of contours for treating different lipid-rich cell deposits in a cost effective manner. Further, a practitioner performing the treatment can demonstrate their expertise to the patient by tailoring the applicator contour to the specific body parts being treated for lipid-rich cell removal. In this manner, the patient understands that their treatment is customized to their body for better comfort and for better treatment results.

Embodiments of some applicators according to the present disclosure include single element attachment systems, two element attachment systems, or attachment systems for any number of contour elements to create a desired applicator contour. The interfaces between cup cavity edges and contour elements cooperate to achieve the approximately air tight seal and achieve the vacuum pressure for drawing tissue into an interior of the cup cavity for treatment. It is desirable for these approximately air tight seals to be sufficiently robust to withstand contour element flex during a vacuum pressure treatment, tissue massage, gravity and patient movement.

Embodiments of some applicators according to the present disclosure may include registers to assure proper positioning of a contour element and/or detectors to determine placement of a contour element. Examples of registers and detectors include mechanical interlocks, magnets, electrical sensors, radio frequency transmitters and receivers, optical sensors, etc. According to some embodiments of the present disclosure, registers and/or detectors may be used to ensure that an applicator can operate only with some form of contour element attached in place. Alternatively, a cup may be configured for an applicator to operate without a contour element attached in place, thereby reducing the need, complexity, and cost associated with including contour element registers or contour element detectors.

Embodiments of some applicators according to the present disclosure include flexible contours that may adjust to allow adaptation to a patient's body while the applicator is applied to the body. In some embodiments, the flexible contour may be adjustable until a steady state condition is achieved, e.g., when tissue is drawn into the cup for treatment. Accordion ribbing and a single piece of material including relatively flexible portions are two examples of a flexible contour. Another example of a flexible contour may include composite parts having different durometers or flexibilities that provide greater strength and rigidity to counter stresses encountered during a treatment while allowing a softer, more flexible contour edge to contact with the patient for greater comfort during the treatment.

Other embodiments of applicators according to the present disclosure include interchangeable cups having different contours. An entire cup could be removed from the applicator housing and replaced with another cup having a contour suitable for treating a lipid-rich cell deposit.

FIGS. 15A and 15B illustrate an embodiment of an applicator according to the present invention. In particular, FIG. 15A shows an example of a single piece contour element 2200 that is magnetically attached to a base 2000, and FIG. 15B shows the contour element 2200 detached

therefrom. The magnetically attached contour element 2200 includes a single, integral unit that defines that entire contour. Accordingly, the contour element 2200 is magnetically attached and detached as an integral unit with respect to the base 2000 and is interchangeable with other magnetically attached contour elements providing the same or different contours. Other embodiments according to the present disclosure may include multiple-piece magnetically attached contour elements (not shown). Base 2000 can be generally rigid, e.g., may include a plurality of cooling surfaces as part of the cavity surface 96.

Each magnetically attached contour element 2200 may include lips 2220 (individual lips 2220a and 2220b are indicated) disposed at longitudinal ends and laterally spaced wings 2230 (individual wings 2230a and 2230b are indicated) extending between and coupling the lips 2220. The lips 2220 may provide portions of the contour that fit relatively curved body surfaces of a subject 11, and the wings 2230 may provide portions of the contour that fit relatively flat body surfaces of a subject 11. Wings 2230 may also provide a contour shape such that there is not a flat segment of the contour. The radius of curvature of the lips 2220, the distance that the lips 2220 project from the wings 2230, the lateral spacing between the wings 2230, the longitudinal length of the wings 2230, and any curvature of the wings 2230 define the suitability of a contour element 2200 to achieve an approximately air-tight seal for treating various size and shape areas of the subject 11. The contour element 2200 shown in FIGS. 15A and 15B includes a generally symmetrical contour; however, asymmetrical contours may also be provided by another contour element 2200.

The contour element 2200 also includes an attachment surface 2240 that is opposite the contour defined by the lips 2220 and the wings 2230. The attachment surface 2240 cooperatively engages a base surface 2002 on a cup edge 2004 cincturing an interior cavity 2006 of the base 2000. In the attached arrangement shown in FIG. 15A, the attachment surface 2240 sealingly engages the base surface 2002 for achieving a pressure vacuum in the interior cavity 2006 during a treatment. Each interchangeable contour element 2200 includes a similar attachment surface 2240 but may have a different contour as defined by the lips 2220 and the wings 2230 of an individual contour element 2200.

The wings 2230 are magnetically coupled to the cup edge 2004 of the base 2000 in the attached arrangement (FIG. 15A). In particular, the contour element 2200 includes first connectors 2250 that are magnetically attracted to second connectors 2260 of the base 2000. As shown in FIG. 15A, the wings 2230 may include first connectors 2250 (individual first connectors 2150a-2150d are indicated) that cooperatively mate with second connectors 2260 (individual second connectors 2260a and 2260b are indicated) on the base 2000. The first and second connectors 2250 and 2260 can include magnets and/or ferrous materials that are embedded in or lie proximate to the attachment surface 2240 or the base surface 2002 for aligning and releasably retaining the base 2000 and the contour element 2200 together in the attached arrangement (FIG. 15A) and permitting separation of the base 2000 from the contour element 2200 in the detached arrangement (FIG. 15B).

The magnetic attraction between the first and second connectors 2250 and 2260 make the base 2000 and the contour element 2200 self-aligning and self-locking to prevent or avoid unintended separation in the attached arrangement (FIG. 16A). Accordingly, the base 2000 may include an unlocking feature 2270 to permit intended separation in



## 31

the detached arrangement (FIG. 16B). One embodiment of the unlocking feature **2270** according to the present disclosure includes a release **2010** that is relatively movable with respect to the base **2000** for shuttling the second connectors **2260** to an unlocking position that breaks the magnetic fields between the first and second connectors **2250** and **2260**, which accordingly permits separation between the base **2000** and the contour element **2200**. A single release **2010** may concurrently enable plural unlocking features **2270**, individual releases **2010** may independently disable corresponding unlocking features **2270**, or a combination thereof may be used for permitting separation between the base **2000** and the contour element **2200**.

FIGS. 16A and 16B illustrate another embodiment of an applicator according to the present invention. In particular, FIG. 16A shows an example of a contour element **2300** attached to the base **2000**, and FIG. 16B shows the contour element **2300** detached therefrom. The contour element **2300** may include a single, integral unit that defines that entire contour. Accordingly, the contour element **2300** is attached and detached as an integral unit with respect to the base **2000** and is interchangeable with other contour elements providing the same or different contours. Other embodiments according to the present disclosure may include multiple pieces magnetically attached contour elements (not shown).

The contour elements **2300** may include lips **2320** (individual lips **2320a** and **2320b** are indicated), wings **2330** (individual wings **2330a** and **2330b** are indicated), and an attachment surface **2340** that are similar to the lips **2120**, wings **2130** and attachment surface **2140** described with respect to FIGS. 15A and 15B. In contrast to the contour element **2200**, the base **2000** and the contour element **2300** include a toe clip **2350** and a heel lock **2360** disposed at opposite longitudinal ends of the contour element **2300**.

The toe clip **2350** includes at least one first projection **2352** that is cooperatively received in a pivot slot **2354** in the attached arrangement (FIG. 16A). According to the embodiment shown in FIGS. 16A and 16B, the toe clip **2350** includes a pair of the first projections **2352** (only one is indicated in FIG. 16A) that extend laterally from the contour element **2300** and a pair of the pivot slots **2354** (only one is indicated in FIGS. 16A and 16B) that are disposed on opposite lateral sides of the base **2000**. The first projections **2352** may be located generally proximate to the juncture between the lips **2320** and the wings **2330** to ensure a seal in that vicinity between the attachment surface **2340** and the base surface **2002**. Other embodiments according to the present disclosure may include a single first projection **2352** located at a longitudinal end of the contour element **2300** and cooperatively received in a single pivot slot **2354** located at a longitudinal end of the base **2000**.

The heel lock **2360** includes at least one second projection **2362** that cooperatively engages at least one swing arm **2364** in the attached arrangement (FIG. 16A). According to the embodiment shown in FIGS. 16A and 16B, the heel lock **2360** includes a pair of the second projections **2362** (only one is indicated in FIG. 16B) that extend laterally from the contour element **2300** and a bifurcated swing arm **2364** pivotally coupled to opposite lateral sides of the base **2000**. The second projections **2362** may be located generally proximate to the juncture between the lips **2320** and the wings **2330** to ensure a seal in that vicinity between the attachment and base surfaces **2340** and **2002**. The swing arm **2364** includes individual cam(s) **2366** that cooperatively engage a corresponding second projection(s) **2362** in the attached arrangement (FIG. 16A).

## 32

Attaching the contour element **2300** to the base **2000** includes engaging the first projection(s) **2352** and the pivot slot(s) **2354** of the toe clip **2350** while the attachment surface **2340** is oriented at an acute angle with respect to the base surface **2002**. The contour element **2300** and the base **2000** are then pivoted toward each other until the attachment and base surfaces **2340** and **2002** engage one another for forming the approximately air-tight seal cincturing the interior cavity **2006** of the base **2000**. The heel lock **2360** is then applied by pivoting the swing arm **2364** with respect to the base **2000** so that the cam(s) **2366** swing into contiguous engagement with the second projection(s) **2362**. Continuing to pivot the swing arm **2364** to its locked position (FIG. 16A) causes the cam(s) **2366** to act on the second projection(s) **2362** to compress the contour element **2300** against the base **2000** so as to achieve the approximately air-tight seal cincturing the interior cavity **2006** of the base **2000**. Detaching the contour element **2300** from the base **2000** may be accomplished by reversing the attaching process.

The base **2000** and the contour element **2300** may include a locking feature to prevent or avoid unintended separation in the attached arrangement (FIG. 16A). One embodiment of the locking feature according to the present disclosure includes pivoting the swing arm **2364** in an overcenter manner to its locked position (FIG. 16A).

Attaching the base **2000** and the contour element **2300** may provide a non-visual sense of positive engagement. Examples of devices that may provide a sense of positive engagement (or disengagement) can include an overcenter mechanism disposed between the base **2000** and the contour element **2100** to provide a tactile sense, a click stop to provide an audible sense, or requiring a greater force during attachment than during detachment to also provide a tactile sense.

FIGS. 17A and 17B illustrate yet another embodiment of an applicator according to the present invention. In particular, FIG. 17A shows an example of a two-piece contour element **2400** attached to the base **2000**, and FIG. 17B shows the two-piece contour element **2400** detached therefrom. The two-piece contour element **2400** includes two independent pieces **2400a** and **2400b** that partially define the contour. Each piece **2400a** and **2400b** is attached and detached independently with respect to the base **2000** and each piece is independently interchangeable with other two-piece contour elements to provide the same or different contours.

Each piece **2400a** and **2400b** provides a lip that is disposed at an opposite longitudinal end of the contour element **2400**. In contrast to the magnetically attached contour element **2200** described with reference to FIGS. 15A and 15B, the base surface **2002** on the cup edge **2004** of the base **2000** provides the portions of the contour between the pieces **2400a** and **2400b**. The contour element **2400** shown in FIGS. 17A and 17B includes a generally asymmetrical contour; however, symmetrical contours may also be provided by using pieces **2400a** and **2400b** that have generally similar shapes and sizes.

Each piece **2400a** and **2400b** may include an attachment surface **2440** that cooperatively engages the base surface **2002** for providing an approximately air-tight seal to achieve a pressure vacuum in the interior cavity **2006** during a treatment. Each interchangeable piece of the contour element **2400** includes a similar attachment surface **2440** and still defines portions of different contours.

The base **2000** and the contour element **2400** may include a locking feature **2450** to prevent or avoid unintended separation in the attached arrangement (FIG. 17A) and to permit intended separation in the detached arrangement



(FIG. 17B). One embodiment of the locking feature **2450** according to the present disclosure includes at least one resiliently deformable snap arm **2452** that is cooperatively received by a snap pocket **2544** in the attached arrangement (FIG. 17A). The embodiment shown in FIG. 17A shows a pair of the snap arms **2452** (individual snap arms **2452a** and **2452b** are indicated) for each piece **2400a** or **2400b**, and corresponding pairs of the snap pockets **2454** (individual snap pockets **2454a** and **2454b** are indicated) are provided on the base **2000**.

The base **2000** and the contour element **2400** may also include an alignment feature **2460** to prevent or avoid unintended deformation of the contour in the attached arrangement (FIG. 17A), which could prevent achieving a pressure vacuum in the interior cavity **2006** during a treatment. One embodiment of the alignment feature **2460** according to the present disclosure includes at least one pin **2462** that is cooperatively received by a hole **2464** in the attached arrangement (FIG. 17A). The embodiment shown in FIG. 17A shows a pair of the pins **2462** (individual pins **2462a** and **2462b** are indicated) for each piece **2400a** or **2400b**, and corresponding pairs of the holes **2464** (individual holes **2464a** and **2464b** are indicated) are provided on the base **2000**. The alignment feature **2460** may be located generally proximate to the juncture between tips of the contour elements **2400** and the base surface **2002** to ensure a seal in that vicinity between the attachment and base surfaces **2440** and **2002**.

Attaching the contour element **2400** to the base **2000** includes aligning the pin(s) **2462** and the hole(s) **2464** while sliding the snap arm(s) **2452** into the snap pocket(s) **2454**. Detaching the contour element **2400** from the base **2000** may be achieved by resiliently deforming the snap arm(s) **2452**, e.g., pressing them toward one another, and sliding the contour element away from the applicator.

Embodiments according to the present disclosure may include other attachment devices and/or seals between an applicator and one or more contour elements. For example, the applicator and contour element may include cams, interlocking channel sections, elastic skirts, resilient straps, latches, and other attachments suitable for providing an at least approximately air-tight coupling that may be released to permit interchanging contour elements with respect to the applicator.

Embodiments according to the present disclosure may provide one or more additional advantages. For example, the size, shape and other physical properties of the panels and the frames may be selected to accommodate a standard heat removal source that may be used/reused with individual vacuum applicators. Accordingly, modifications to the flexible portion of individual vacuum applicators may enable the use of a standard heat removal source and accommodate different contours of individual cutaneous layers. In turn, this may make it possible to reuse the relatively expensive heat removal and suction sources, and to dispose of the relatively inexpensive personal protection devices and/or vacuum applicators for different treatments. The rigid portions of the vacuum applicators, which are relatively stiff with respect to the flexible portion, provide an attachment point for the heat removal sources that may resist bowing into the interior cavity and possibly separating from the heat removal sources when a partial vacuum is drawn in the vacuum applicators. The separator may allow the vacuum applicator to retain a thermal coupling fluid, e.g., a cryoprotectant gel including a temperature depressant, in the interior cavity and avoid passage of the fluid through the suction port in the event that the vacuum applicator is

inverted. The cams and latches may press and hold the heat removal sources to the rigid portions and thereby facilitate reliable thermal conductivity between the interior cavity of the vacuum applicator and the heat removal source. Disposing the temperature sensors inside the vacuum applicators, e.g., on the patient protection devices, may more accurately measure the temperature of the cutaneous layer. The flexible section also allows some compliance to different subject body contours or geometries.

From the foregoing, it will be appreciated that specific embodiments of the disclosure have been described herein for purposes of illustration, but that various modifications may be made without deviating from the disclosure. For example, structures and/or processes described in the context of particular embodiments may be combined or eliminated in other embodiments. In particular, the attachment features described above with reference to particular embodiments may include one or more additional features or components, or one or more of the features described above may be omitted. Moreover, while advantages associated with certain embodiments of the disclosure have been described in the context of these embodiments, other embodiments may also exhibit such advantages, and not all embodiments need necessarily exhibit such advantages to fall within the scope of the disclosure. Accordingly, the disclosure may include other embodiments not shown or described above.

We claim:

1. A device for treating lipid rich cells disposed under a cutaneous layer, the device comprising:
  - a base including a first attachment, a vacuum cup defining a portion of a cavity for receiving the cutaneous layer;
  - a fitting detachably coupleable to the base and including a first portion of a contoured lip that defines a mouth of the cavity, the fitting includes an attachment surface and a second attachment, the attachment surface is configured to cooperatively engage the base to cincture the portion of the cavity, the second attachment is coupled to the first attachment in a first device arrangement and the second attachment is decoupled from the first attachment in a second device arrangement, wherein the contoured lip is configured to contact a curved body part of a subject to form a generally air-tight seal between the contoured lip and the subject's skin for drawing the subject's tissue through the mouth, past the attachment surface, and into the vacuum cup; and
  - a thermal conductor disposed along a sidewall of the vacuum cup, the thermal conductor is configured for heat transfer with respect to the lipid rich cells when the contour forms the generally air-tight seal with the cutaneous layer such that the subject's tissue extends through the mouth, past the attachment surface, and into the portion of the cavity.
2. The device of claim 1, wherein the fitting is relatively flexible with respect to the base.
3. The device of claim 1, wherein the base defines a first portion of the cavity and the fitting defines a second portion of the cavity.
4. The device of claim 1, wherein the fitting comprises first and second lips defining the first portion of the contour.
5. The device of claim 4, wherein the first lip includes the first attachment and the second lip includes a third attachment that is coupled by a fourth attachment to the base.
6. The device of claim 1, wherein the mouth flares outwardly with respect to the cavity.



35

7. The device of claim 1, further comprising a vacuum pressure port in fluid communication with the cavity when the contour engages the cutaneous layer in the first device arrangement.

8. The device of claim 1, wherein one of the first and second attachments comprises a projection and another of the first and second attachments comprises a groove configured to receive the projection in the first arrangement.

9. The device of claim 1, wherein one of the first and second attachments comprises a resilient snap lever and another of the first and second attachments comprises a snap pocket configured to receive the snap lever in the first arrangement.

10. The device of claim 1, further comprising an approximately air tight seal between the base and fitting.

11. The device of claim 1, further comprising:  
a first aligner disposed on one of the base and fitting; and  
a second aligner disposed on another of the base and fitting;

wherein the first and second aligners are configured to align the base and fitting in the second arrangement.

12. The device of claim 1, wherein the vacuum cup has a cup edge surrounding the cavity, the attachment surface is configured to engage a base surface on the cup edge, and the attachment surface is between the mouth and the base surface when the second attachment is coupled to the first attachment in the first device arrangement.

13. The device of claim 1, wherein  
the vacuum cup includes a cup edge with a base surface surrounding an entrance of the portion of the cavity defined by the vacuum cup, and  
the attachment surface is opposite the contour and engages the base surface when the second attachment is coupled to the first attachment in the first device arrangement.

14. The device of claim 1, wherein one of the first and second attachments comprises a projection and another of

36

the first and second attachments comprises a receiver configured to receive the projection.

15. The device of claim 1, wherein the contoured lip has a varying height along a circumference of the mouth.

16. A vacuum cooling device for treating lipid rich cells disposed under a subject's cutaneous layer, comprising:

a base including an interior cavity and one or more cooling surfaces positioned to cool the subject's tissue located in the interior cavity; and

a contour element detachably coupleable to the base to define a mouth to the interior cavity, the contour element including at least one lip for contacting a relatively curved body surface of the subject to provide an approximately air-tight seal between the contour element and the subject's skin for drawing the tissue past an interface between the base and the contour element and into the interior cavity.

17. The vacuum cooling device of claim 16, wherein the base is configured to draw a vacuum to draw tissue through the mouth and into contact with the one or more cooling surfaces for heat transfer with respect to subcutaneous lipid-rich cells when the at least one lip engages the curved body surface.

18. The vacuum cooling device of claim 16, further comprising an attachment that moves the contour element toward the base to form the approximately air-tight seal.

19. The vacuum cooling device of claim 16, wherein the base has a locked configuration for holding the contour element to form a generally air-tight seal between the base and the contour element, and the base has a released configuration for releasing the contour element from the base.

20. The vacuum cooling device of claim 16, further including a frame and a liner, and wherein the liner is configured to cover at least a portion of the interior cavity when the frame engages the base.

\* \* \* \* \*