



US011247290B2

(12) **United States Patent**  
**Sigl et al.**

(10) **Patent No.:** **US 11,247,290 B2**  
(45) **Date of Patent:** **Feb. 15, 2022**

(54) **SYSTEMS, METHODS, AND APPARATUS TO PREHEAT WELDING WIRE**

(2013.01); **B23K 9/26** (2013.01); **B23K 9/285** (2013.01); **B23K 9/295** (2013.01)

(71) Applicant: **Illinois Tool Works Inc.**, Glenview, IL (US)

(58) **Field of Classification Search**  
CPC ..... **B23K 9/1043**; **B23K 9/1093**; **B23K 9/285**  
See application file for complete search history.

(72) Inventors: **Dennis Roland Sigl**, Greenville, WI (US); **James Lee Uecker**, Appleton, WI (US); **Jake Zwayner**, Appleton, WI (US); **Nicholas Matiash**, Oshkosh, WI (US); **Jeffrey Wells**, Belle River (CA); **Nauman Basit**, Windsor (CA)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,365,958 A 12/1944 Holslag  
2,416,047 A 2/1947 Dolan  
(Continued)

(73) Assignee: **Illinois Tool Works Inc.**, Glenview, IL (US)

FOREIGN PATENT DOCUMENTS

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 68 days.

AT 413801 6/2006  
CA 2072711 12/1992  
(Continued)

(21) Appl. No.: **16/005,447**

OTHER PUBLICATIONS

(22) Filed: **Jun. 11, 2018**

“ALT 304,” Miller—The Power of Blue, Jun. 2001.  
(Continued)

(65) **Prior Publication Data**

US 2018/0354055 A1 Dec. 13, 2018

**Related U.S. Application Data**

(60) Provisional application No. 62/517,531, filed on Jun. 9, 2017.

(51) **Int. Cl.**

**B23K 9/10** (2006.01)  
**B23K 9/28** (2006.01)  
**B23K 9/12** (2006.01)  
**B23K 9/26** (2006.01)  
**B23K 9/173** (2006.01)  
**B23K 9/29** (2006.01)


(57) **ABSTRACT**

Systems, methods, and apparatus to preheat weld wire are disclosed. An example welding torch includes a first contact tip configured to conduct welding current to a consumable electrode, a second contact tip configured to conduct preheating current to the consumable electrode, and a plurality of liquid cooling assemblies configured to conduct the preheating current and to conduct the welding current to the consumable electrode.

(52) **U.S. Cl.**

CPC ..... **B23K 9/1093** (2013.01); **B23K 9/1043** (2013.01); **B23K 9/123** (2013.01); **B23K 9/173**

**17 Claims, 22 Drawing Sheets**



(56)

References Cited

U.S. PATENT DOCUMENTS

|               |         |             |                 |         |                    |
|---------------|---------|-------------|-----------------|---------|--------------------|
| 2,976,462 A   | 3/1961  | Miller      | 6,107,602 A     | 8/2000  | Geissler           |
| 3,030,495 A   | 4/1962  | Anderson    | 6,115,273 A     | 9/2000  | Geissler           |
| 3,288,982 A   | 11/1966 | Haruyoshi   | 6,160,241 A     | 12/2000 | Stava              |
| 3,549,857 A   | 12/1970 | Carter      | 6,169,263 B1    | 1/2001  | Derby              |
| 3,725,629 A   | 4/1973  | Vickers     | 6,204,476 B1    | 3/2001  | Reynolds           |
| 3,809,853 A   | 5/1974  | Manz        | 6,248,976 B1    | 6/2001  | Blankenship        |
| 3,849,871 A   | 11/1974 | Kaunitz     | 6,259,059 B1    | 7/2001  | Hsu                |
| 3,912,980 A   | 10/1975 | Crump       | 6,265,688 B1    | 7/2001  | Lyshkow            |
| 3,946,349 A   | 3/1976  | Haldeman    | 6,274,845 B1    | 8/2001  | Stava              |
| 4,160,967 A   | 7/1979  | Beech       | 6,278,074 B1    | 8/2001  | Morlock            |
| 4,188,419 A   | 2/1980  | Detert      | 6,292,715 B1    | 9/2001  | Rongo              |
| 4,222,023 A   | 9/1980  | Beech       | 6,331,694 B1    | 12/2001 | Blankenship        |
| 4,329,561 A   | 5/1982  | Schafer     | 6,359,258 B1    | 3/2002  | Blankenship        |
| 4,426,565 A   | 1/1984  | Rueter      | 6,479,792 B1    | 11/2002 | Beiermann          |
| 4,447,703 A   | 5/1984  | Stol        | 6,486,439 B1    | 11/2002 | Spear              |
| 4,467,176 A   | 8/1984  | Mizuno      | 6,515,259 B1    | 2/2003  | Hsu                |
| 4,493,971 A   | 1/1985  | Nawa        | 6,559,416 B1    | 5/2003  | Steenis            |
| 4,531,040 A   | 7/1985  | Nawa        | 6,583,386 B1    | 6/2003  | Ivkovich           |
| 4,536,634 A   | 8/1985  | Nawa        | 6,596,970 B2    | 7/2003  | Blankenship        |
| 4,546,234 A   | 10/1985 | Ogasawara   | 6,624,388 B1    | 9/2003  | Blankenship et al. |
| 4,547,654 A   | 10/1985 | Stol        | 6,642,482 B2    | 11/2003 | Rappl              |
| 4,580,026 A   | 4/1986  | Stol        | 6,670,579 B2    | 12/2003 | Davidson           |
| 4,614,856 A   | 9/1986  | Hori        | 6,707,001 B1    | 3/2004  | Ulrich             |
| 4,628,182 A   | 12/1986 | Hori        | 6,710,297 B1    | 3/2004  | Artelsmair         |
| 4,631,385 A   | 12/1986 | Rothermel   | 6,720,529 B2    | 4/2004  | Davidson           |
| 4,667,083 A * | 5/1987  | Stol .....  | 6,744,012 B2    | 6/2004  | Ueda               |
|               |         |             | 6,747,247 B2    | 6/2004  | Holverson          |
|               |         |             | 6,849,828 B2    | 2/2005  | Aigner             |
|               |         |             | 6,906,284 B2    | 6/2005  | Kim                |
|               |         |             | 6,909,067 B2    | 6/2005  | Davidson           |
|               |         |             | 6,933,466 B2    | 8/2005  | Hutchison          |
|               |         |             | 6,958,263 B2    | 10/2005 | Bhattacharyya      |
| 4,675,494 A   | 6/1987  | Dilay       | 6,974,931 B2    | 12/2005 | Holverson          |
| 4,728,761 A   | 3/1988  | Mucha       | 6,974,932 B2    | 12/2005 | Holverson          |
| 4,897,523 A   | 1/1990  | Parks       | 6,984,806 B2    | 1/2006  | Huismann           |
| 4,950,348 A   | 8/1990  | Larsen      | 6,995,338 B2    | 2/2006  | Hutchison          |
| 4,954,691 A   | 9/1990  | Parks       | 7,002,103 B2    | 2/2006  | Holverson          |
| 4,973,821 A   | 11/1990 | Martin      | 7,105,775 B2    | 9/2006  | Giese              |
| 5,001,326 A   | 3/1991  | Stava       | 7,129,443 B2    | 10/2006 | Davidson           |
| 5,043,557 A   | 8/1991  | Tabata      | 7,145,101 B2    | 12/2006 | Tong               |
| 5,086,207 A   | 2/1992  | Deam        | 7,244,905 B2    | 7/2007  | Das                |
| 5,101,086 A   | 3/1992  | Dion        | 7,265,320 B2    | 9/2007  | Ou                 |
| 5,118,028 A   | 6/1992  | Ogawa       | 7,304,269 B2    | 12/2007 | Fulmer             |
| 5,140,123 A   | 8/1992  | Mitani      | 7,307,240 B2    | 12/2007 | Holverson          |
| 5,148,001 A   | 9/1992  | Stava       | 7,351,933 B2    | 4/2008  | Huismann           |
| 5,208,433 A   | 5/1993  | Hellegouarc | 7,381,923 B2    | 6/2008  | Gordon             |
| 5,270,516 A   | 12/1993 | Hamamoto    | 7,576,300 B2    | 8/2009  | Giese              |
| 5,278,390 A   | 1/1994  | Blankenship | 7,683,290 B2    | 3/2010  | Daniel             |
| 5,315,089 A   | 5/1994  | Hughes      | 8,203,100 B2    | 6/2012  | Ueda               |
| 5,319,179 A   | 6/1994  | Joecks      | 8,288,686 B2    | 10/2012 | Kaufman            |
| 5,343,023 A   | 8/1994  | Geissler    | 8,304,693 B2    | 11/2012 | Ma                 |
| 5,349,156 A   | 9/1994  | Madigan     | 8,357,877 B2    | 1/2013  | Ma                 |
| 5,352,871 A   | 10/1994 | Ross        | 8,487,215 B2    | 7/2013  | Holverson          |
| 5,367,138 A   | 11/1994 | Moss        | 8,604,388 B2    | 12/2013 | Dingeldein         |
| 5,412,184 A   | 5/1995  | McGaffigan  | 9,095,928 B2    | 8/2015  | Ash                |
| 5,461,215 A   | 10/1995 | Haldeman    | 9,162,312 B2    | 10/2015 | Ma                 |
| 5,466,916 A   | 11/1995 | Iguchi      | 9,193,004 B2    | 11/2015 | Enyedy             |
| 5,504,309 A   | 4/1996  | Geissler    | 9,193,005 B2    | 11/2015 | Ma                 |
| 5,521,355 A   | 5/1996  | Lorentzen   | 9,403,231 B2    | 8/2016  | Hutchison          |
| 5,526,561 A   | 6/1996  | McGaffigan  | 9,409,250 B2    | 8/2016  | Daniel             |
| 5,644,461 A   | 7/1997  | Miller      | 9,463,523 B2    | 10/2016 | Roth               |
| 5,710,413 A   | 1/1998  | King        | 9,539,662 B2    | 1/2017  | Hutchison          |
| 5,714,738 A   | 2/1998  | Hauschulz   | 9,669,486 B2    | 6/2017  | Dingeldein         |
| 5,739,506 A   | 4/1998  | Hanton      | 9,950,383 B2    | 4/2018  | Davidson           |
| 5,742,029 A   | 4/1998  | Stava       | 2002/0008095 A1 | 1/2002  | Norrish            |
| 5,756,967 A   | 5/1998  | Quinn       | 2002/0045970 A1 | 4/2002  | Krause             |
| 5,760,373 A   | 6/1998  | Colling     | 2002/0107825 A1 | 8/2002  | Manicke            |
| 5,773,799 A   | 6/1998  | Maxfield    | 2002/0117487 A1 | 8/2002  | Corby              |
| 5,783,799 A   | 7/1998  | Geissler    | 2002/0117488 A1 | 8/2002  | Arndt              |
| 5,844,193 A   | 12/1998 | Nomura      | 2003/0010756 A1 | 1/2003  | Enyedy             |
| 5,963,022 A   | 10/1999 | Buda        | 2003/0058149 A1 | 3/2003  | Jayadeva           |
| 5,968,587 A   | 10/1999 | Frankel     | 2004/0010342 A1 | 1/2004  | Thelen             |
| 5,994,659 A   | 11/1999 | Offer       | 2004/0069759 A1 | 4/2004  | Davidson           |
| 6,002,104 A   | 12/1999 | Hsu         | 2004/0182828 A1 | 9/2004  | Schmidt            |
| 6,008,470 A   | 12/1999 | Zhang       | 2004/0222204 A1 | 11/2004 | Hutchison          |
| 6,043,471 A   | 3/2000  | Wiseman     | 2004/0238511 A1 | 12/2004 | Matus              |
| 6,051,810 A   | 4/2000  | Stava       | 2005/0072762 A1 | 4/2005  | Delgado            |
| 6,077,369 A   | 6/2000  | Kusano      | 2005/0184039 A1 | 8/2005  | Stava              |
| 6,078,023 A   | 6/2000  | Jones       | 2005/0218132 A1 | 10/2005 | Wells              |
| 6,090,067 A   | 7/2000  | Carter      |                 |         |                    |

B23K 9/295  
219/136

(56)

## References Cited

| U.S. PATENT DOCUMENTS |     |         |                          | FOREIGN PATENT DOCUMENTS |           |         |                           |
|-----------------------|-----|---------|--------------------------|--------------------------|-----------|---------|---------------------------|
| 2005/0269306          | A1  | 12/2005 | Fulmer                   | 2014/0263229             | A1        | 9/2014  | Peters                    |
| 2006/0138115          | A1  | 6/2006  | Norrish                  | 2014/0263230             | A1        | 9/2014  | Peters                    |
| 2006/0163227          | A1  | 7/2006  | Hillen                   | 2014/0263231             | A1        | 9/2014  | Peters                    |
| 2006/0163229          | A1  | 7/2006  | Hutchison                | 2014/0263234             | A1        | 9/2014  | Peters                    |
| 2007/0051711          | A1  | 3/2007  | Kachline                 | 2014/0263237             | A1        | 9/2014  | Daniel                    |
| 2007/0084840          | A1  | 4/2007  | Davidson                 | 2014/0263241             | A1        | 9/2014  | Henry                     |
| 2007/0102407          | A1  | 5/2007  | Uezono                   | 2014/0263243             | A1        | 9/2014  | Marschke                  |
| 2007/0170163          | A1  | 7/2007  | Narayanan                | 2014/0263251             | A1        | 9/2014  | Enyedy                    |
| 2007/0235434          | A1  | 10/2007 | Davidson                 | 2014/0319103             | A1        | 10/2014 | Stabb et al.              |
| 2007/0267394          | A1  | 11/2007 | Beck                     | 2014/0367370             | A1        | 12/2014 | Hutchison                 |
| 2008/0264916          | A1  | 10/2008 | Nagano                   | 2014/0374391             | A1        | 12/2014 | Cole                      |
| 2008/0264917          | A1  | 10/2008 | White                    | 2015/0001184             | A1        | 1/2015  | Cole                      |
| 2008/0264923          | A1  | 10/2008 | White                    | 2015/0001197             | A1        | 1/2015  | Marschke                  |
| 2009/0026188          | A1  | 1/2009  | Schorghuber              | 2015/0014283             | A1        | 1/2015  | Peters                    |
| 2009/0039066          | A1  | 2/2009  | Centner                  | 2015/0028010             | A1        | 1/2015  | Peters                    |
| 2009/0173726          | A1  | 7/2009  | Davidson                 | 2015/0028011             | A1        | 1/2015  | Peters                    |
| 2009/0215302          | A1* | 8/2009  | Roberts ..... B23K 9/324 | 2015/0028012             | A1        | 1/2015  | Peters                    |
|                       |     |         | 439/350                  | 2015/0083702             | A1        | 3/2015  | Scott                     |
| 2010/0012637          | A1* | 1/2010  | Jaeger ..... B23K 9/295  | 2015/0090703             | A1        | 4/2015  | Peters                    |
|                       |     |         | 219/136                  | 2015/0105898             | A1        | 4/2015  | Adams                     |
| 2010/0059493          | A1  | 3/2010  | McAninch                 | 2015/0151375             | A1        | 6/2015  | Peters                    |
| 2010/0096373          | A1  | 4/2010  | Hillen                   | 2015/0158105             | A1        | 6/2015  | Peters                    |
| 2010/0096436          | A1  | 4/2010  | Nangle                   | 2015/0158106             | A1        | 6/2015  | Peters                    |
| 2010/0133250          | A1  | 6/2010  | Sardy                    | 2015/0158107             | A1        | 6/2015  | Latessa                   |
| 2010/0176104          | A1  | 7/2010  | Peters                   | 2015/0158108             | A1        | 6/2015  | Peters                    |
| 2010/0308026          | A1  | 12/2010 | Vogel                    | 2015/0183044             | A1        | 7/2015  | Peters                    |
| 2010/0308027          | A1  | 12/2010 | Vogel                    | 2015/0183045             | A1        | 7/2015  | Peters                    |
| 2010/0314371          | A1  | 12/2010 | Davidson                 | 2015/0209889             | A1        | 7/2015  | Peters                    |
| 2011/0108527          | A1  | 5/2011  | Peters                   | 2015/0209905             | A1        | 7/2015  | Matthews                  |
| 2011/0114612          | A1  | 5/2011  | Holverson                | 2015/0209906             | A1        | 7/2015  | Denney                    |
| 2011/0163080          | A1  | 7/2011  | Beck                     | 2015/0209907             | A1        | 7/2015  | Narayanan                 |
| 2011/0204034          | A1  | 8/2011  | Schartner                | 2015/0209908             | A1        | 7/2015  | Peters                    |
| 2011/0204035          | A1  | 8/2011  | Grossauer                | 2015/0209910             | A1        | 7/2015  | Denney                    |
| 2011/0297658          | A1  | 8/2011  | Peters                   | 2015/0209913             | A1        | 7/2015  | Denney                    |
| 2011/0248007          | A1  | 10/2011 | Takeda                   | 2015/0213921             | A1        | 7/2015  | Koide                     |
| 2011/0266269          | A1  | 11/2011 | Kachline                 | 2015/0251275             | A1        | 9/2015  | Denney                    |
| 2012/0024828          | A1  | 2/2012  | Oowaki                   | 2015/0273612             | A1        | 10/2015 | Peters                    |
| 2012/0061362          | A1  | 3/2012  | Davidson                 | 2015/0283638             | A1        | 10/2015 | Henry                     |
| 2012/0074112          | A1  | 3/2012  | Kotera                   | 2015/0283639             | A1        | 10/2015 | Henry                     |
| 2012/0097655          | A1  | 4/2012  | Daniel                   | 2016/0074954             | A1        | 3/2016  | Marschke                  |
| 2012/0248080          | A1  | 10/2012 | Hutchison                | 2016/0074973             | A1*       | 3/2016  | Kachline ..... B23K 9/285 |
| 2012/0285932          | A1  | 11/2012 | Yuan                     |                          |           |         | 219/74                    |
| 2012/0291172          | A1  | 11/2012 | Wills                    | 2016/0144444             | A1        | 5/2016  | Davidson                  |
| 2012/0298642          | A1  | 11/2012 | Lambert                  | 2016/0167151             | A1        | 6/2016  | Mehn                      |
| 2013/0112674          | A1  | 5/2013  | Mnich                    | 2016/0175975             | A1        | 6/2016  | Lattner                   |
| 2013/0112676          | A1  | 5/2013  | Hutchison                | 2016/0199939             | A1        | 7/2016  | Hartman                   |
| 2013/0213942          | A1  | 8/2013  | Peters                   | 2016/0221105             | A1        | 8/2016  | Henry                     |
| 2013/0264323          | A1  | 10/2013 | Daniel                   | 2016/0288235             | A1        | 10/2016 | Davidson                  |
| 2013/0270245          | A1  | 10/2013 | Holverson                | 2016/0318112             | A1        | 11/2016 | Hutchison                 |
| 2014/0008328          | A1  | 1/2014  | Enyedy                   | 2017/0080512             | A1        | 3/2017  | Centner                   |
| 2014/0008331          | A1  | 1/2014  | Ogborn                   | 2017/0165778             | A1        | 6/2017  | Hsu                       |
| 2014/0008339          | A1  | 1/2014  | Ogborn                   | 2017/0225255             | A1        | 8/2017  | Zwayer                    |
| 2014/0008343          | A1  | 1/2014  | Ash                      | 2018/0236585             | A1        | 8/2018  | Davidson                  |
| 2014/0008344          | A1  | 1/2014  | Enyedy                   |                          |           |         |                           |
| 2014/0008354          | A1  | 1/2014  | Pletcher                 | CA                       | 2883947   | 3/2014  |                           |
| 2014/0021183          | A1  | 1/2014  | Peters                   | CN                       | 2125475   | 12/1992 |                           |
| 2014/0021186          | A1  | 1/2014  | Denney                   | CN                       | 2181354   | 11/1994 |                           |
| 2014/0021187          | A1  | 1/2014  | Denney                   | CN                       | 1298778   | 6/2001  |                           |
| 2014/0021188          | A1  | 1/2014  | Denney                   | CN                       | 1496774   | 5/2004  |                           |
| 2014/0034621          | A1  | 2/2014  | Daniel                   | CN                       | 1600486   | 3/2005  |                           |
| 2014/0034622          | A1  | 2/2014  | Barrett                  | CN                       | 1640603   | 7/2005  |                           |
| 2014/0035279          | A1  | 2/2014  | Narayanan                | CN                       | 1712168   | 12/2005 |                           |
| 2014/0042129          | A1  | 2/2014  | Daniel                   | CN                       | 1714978   | 1/2006  |                           |
| 2014/0042138          | A1  | 2/2014  | Matthews                 | CN                       | 1836818   | 9/2006  |                           |
| 2014/0048524          | A1  | 2/2014  | Ash                      | CN                       | 1871093   | 11/2006 |                           |
| 2014/0116994          | A1  | 5/2014  | Peters                   | CN                       | 101062530 | 10/2007 |                           |
| 2014/0131321          | A1  | 5/2014  | Enyedy                   | CN                       | 201098775 | 8/2008  |                           |
| 2014/0158669          | A1  | 6/2014  | Davidson                 | CN                       | 101376191 | 3/2009  |                           |
| 2014/0177109          | A1  | 6/2014  | Curtis                   | CN                       | 201249331 | 6/2009  |                           |
| 2014/0183176          | A1  | 7/2014  | Hutchison                | CN                       | 101804495 | 8/2010  |                           |
| 2014/0217077          | A1  | 8/2014  | Davidson                 | CN                       | 101862886 | 10/2010 |                           |
| 2014/0251971          | A1  | 9/2014  | Hearn                    | CN                       | 102059476 | 5/2011  |                           |
| 2014/0263193          | A1  | 9/2014  | Denney                   | CN                       | 102470473 | 5/2012  |                           |
| 2014/0263194          | A1  | 9/2014  | Narayanan                | CN                       | 102554418 | 7/2012  |                           |
| 2014/0263228          | A1  | 9/2014  | Peters                   | CN                       | 102596475 | 7/2012  |                           |
|                       |     |         |                          | CN                       | 102770228 | 11/2012 |                           |
|                       |     |         |                          | CN                       | 102825370 | 12/2012 |                           |

(56)

References Cited

FOREIGN PATENT DOCUMENTS

|    |               |         |
|----|---------------|---------|
| CN | 202824943     | 3/2013  |
| CN | 104968465     | 10/2015 |
| DE | 2501928       | 7/1976  |
| DE | 19808383      | 9/1999  |
| DE | 212004000048  | 6/2006  |
| EP | 0150543       | 8/1985  |
| EP | 0194045       | 9/1986  |
| EP | 0204559       | 12/1986 |
| EP | 0387223       | 9/1990  |
| EP | 0936019 A2    | 8/1999  |
| EP | 0936019 A3    | 3/2001  |
| EP | 1232825       | 8/2002  |
| EP | 2218537       | 8/2010  |
| EP | 2286949       | 2/2011  |
| EP | 2322315       | 5/2011  |
| EP | 2522453       | 11/2012 |
| EP | 2892680       | 7/2015  |
| EP | 2781291       | 10/2015 |
| FR | 1443701       | 6/1966  |
| JP | S5719166      | 2/1982  |
| JP | S57109573     | 7/1982  |
| JP | S583784       | 1/1983  |
| JP | S58119466     | 7/1983  |
| JP | S60108175     | 6/1985  |
| JP | S60108176     | 6/1985  |
| JP | S60170577     | 9/1985  |
| JP | 61186172      | 8/1986  |
| JP | S629773       | 1/1987  |
| JP | S6471575      | 3/1989  |
| JP | H03285768     | 12/1991 |
| JP | H06277840     | 10/1994 |
| JP | H07204848     | 8/1995  |
| JP | H1097327      | 4/1998  |
| JP | H11156542     | 6/1999  |
| JP | 2001276971    | 10/2001 |
| JP | 2003205385    | 7/2003  |
| JP | 2003311409    | 11/2003 |
| JP | 2005034853    | 2/2005  |
| JP | 2006205189    | 8/2006  |
| JP | 2009072814    | 4/2009  |
| JP | 4950819       | 6/2012  |
| JP | 2014176890    | 9/2014  |
| KR | 1020060133016 | 12/2006 |
| KR | 20080009816   | 1/2008  |
| KR | 20100120562   | 11/2010 |
| KR | 1020120027764 | 3/2012  |
| KR | 101497460     | 3/2015  |
| SU | 872102        | 10/1981 |
| WO | 9640465       | 12/1996 |
| WO | 0132347       | 5/2001  |
| WO | 0153030       | 7/2001  |
| WO | 2005030422    | 4/2005  |
| WO | 2014140783    | 9/2014  |
| WO | 2015125008    | 8/2015  |

OTHER PUBLICATIONS

“Maxstar 200 SD, DX, and LX,” Miller Electric Mfg. Co., Oct. 2003.  
 Bondy et al., “Graph Theory with Applications,” Department of Combinatorics and Optimization, University of Waterloo, 1976, p. 7-8.  
 Int’l Search Report and Written Opinion for PCT/US2016/065265 dated Mar. 14, 2017 (16 pages).  
 Int’l Search Report and Written Opinion for PCT/US2018/029770 dated Sep. 12, 2018 (13 pgs.).  
 Int’l Search Report and Written Opinion for PCT/US2018/036906 dated Oct. 1, 2018 (15 pgs.).  
 Int’l Search Report and Written Opinion for PCT/US2018/036914 dated Oct. 2, 2018 (14 pgs.).

Int’l Search Report and Written Opinion for PCT/US2018/036915 dated Oct. 1, 2018 (15 pgs).  
 Int’l Search Report and Written Opinion for PCT/US2018/036919 dated Oct. 2, 2018 (13 pgs.).  
 International Search Report from PCT application No. PCT/US2014/017864, dated Aug. 22, 2014, 9 pgs.  
 International Search Report from PCT application No. PCT/US2014/041201, dated Nov. 4, 2014, 11 pg.  
 International Search Report from PCT application No. PCT/US2014/045872, dated Nov. 4, 2014, 10 pgs.  
 International Search Report from PCT Application No. PCT/US2014/055529, dated Mar. 6, 2015, 9 pgs.  
 International Search Report from PCT application No. PCT/US2015/045715, dated Jan. 7, 2016, 12 pgs.  
 International Search Report from PCT application No. PCT/US2015/055040, dated Feb. 3, 2016, 11 pgs.  
 International Search Report from PCT application No. PCT/US2015/056121, dated Apr. 4, 2016, 11 pgs.  
 International Search Report from PCT application No. PCT/US2016/017385, dated Jul. 19, 2016, 13 pgs.  
 International Search Report from PCT application No. PCT/US2013/073490 dated May 13, 2014, 10 pgs.  
 International Search Report from PCT application No. PCT/US2013/073863 dated May 2, 2014, 15 pgs.  
 International Search Report from PCT application No. PCT/US2013/077710 dated May 9, 2014, 12 pgs.  
 International Search Report from PCT application No. PCT/US2014/014241 dated May 9, 2014, 8 pgs.  
 Office Action from U.S. Appl. No. 15/498,249 dated Apr. 20, 2018.  
 PCT International Search Report & Written Opinion of PCT/US2012/063783 dated Mar. 1, 2013, 12 pages.  
 Canadian Office Action Appln No. 3,005,408 dated Mar. 19, 2019.  
 Gupta, “A low temperature hydrogen sensor based on palladium nanoparticles,” Published in 2014.  
 Int’l Search Report and Written Opinion Appln No. PCT/U2019/049109 dated Dec. 2, 2019 (11 pgs).  
 Int’l Search Report and Written Opinion Appln No. PCT/US2019/050972, dated Nov. 14, 2019, (13 pgs).  
 Int’l Search Report and Written Opinion for PCT/US2018/035087 dated Sep. 19, 2018 (15 pgs.).  
 Int’l Search Report and Written Opinion for PCT/US2018/036852 dated Oct. 2, 2018 (17 pgs.).  
 Int’l Search Report and Written Opinion for PCT/US2018/036898 dated Oct. 1, 2018 (14 pgs.).  
 Int’l Search Report and Written Opinion for PCT/US2018/036900 dated Oct. 5, 2018 (15 pgs.).  
 Int’l Search Report and Written Opinion for PCT/US2018/049888 dated Feb. 1, 2019 (14 pgs.).  
 Int’l Search Report and Written Opinion for PCT/US2018/052384 dated Feb. 12, 2019 (12 pgs.).  
 Lincoln Electric, “Storing and Redrying Electrodes,” Published in 2011.  
 N.A.: “Drahtgluה”, Aug. 23, 2016 (Aug. 23, 2016), XP055510057, Wikipedia, Retrieved from the Internet: URL:<https://de.wikipedia.org/w/index.php?title=Drahtgl%C3%BChe&oldid=157333005>, [retrieved on Sep. 26, 2018], with machine translation, 2 pages.  
 Non-Final Office Action U.S. Appl. No. 15/343,992 dated Mar. 7, 2019 (18 pgs.).  
 Non-Final Office Action U.S. Appl. No. 15/498,249 dated Sep. 23, 2019 (43 pgs).  
 PCT, IPRP, issued in connection with PCT/US2018/036898, dated Dec. 19, 2019, 7 pages.  
 PCT, IPRP, issued in connection with PCT/US2018/036900, dated Dec. 19, 2019, 7 pages.  
 Pitrun, “The effect of welding parameters on levels of diffusible hydrogen in weld metal deposited using gas shield rutile flux cored wires,” Published in 2004.  
 Canadian Office Action Appln No. 3,066,687 dated Mar. 16, 2021.

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5







FIG. 6






FIG. 8




FIG. 9




FIG. 10




FIG. 11B




FIG. 11A




FIG. 12A




FIG. 12B




FIG. 11C





FIG. 13B






FIG. 14A




FIG. 14B






FIG. 15A




FIG. 15B




FIG. 16




FIG. 17

908, 910




FIG. 18




FIG. 19




FIG. 20




FIG. 21






FIG. 22




FIG. 23

1

## SYSTEMS, METHODS, AND APPARATUS TO PREHEAT WELDING WIRE

### RELATED APPLICATIONS

This patent claims priority to U.S. Provisional Patent Application Ser. No. 62/517,531, filed Jun. 9, 2007, entitled "Systems, Methods, and Apparatus to Preheat Welding Wire." The entirety of U.S. Provisional Patent Application Ser. No. 62/517,531 is incorporated herein by reference.

### BACKGROUND

This disclosure relates generally to welding and, more particularly, to welding torches and methods to provide wire preheating for welding.

Welding is a process that has increasingly become ubiquitous in all industries. Welding is, at its core, simply a way of bonding two pieces of metal. A wide range of welding systems and welding control regimes have been implemented for various purposes. In continuous welding operations, metal inert gas (MIG) welding and submerged arc welding (SAW) techniques allow for formation of a continuing weld bead by feeding welding wire shielded by inert gas from a welding torch and/or by flux. Such wire feeding systems are available for other welding systems, such as tungsten inert gas (TIG) welding. Electrical power is applied to the welding wire and a circuit is completed through the workpiece to sustain a welding arc that melts the electrode wire and the workpiece to form the desired weld.

While very effective in many applications, these welding techniques may experience different initial welding performance based upon whether the weld is started with the electrode "cold" or "hot." In general, a cold electrode start may be considered a start in which the electrode tip and adjacent metals are at or relatively near the ambient temperature. Hot electrode starts, by contrast, are typically those in which the electrode tip and the adjacent metals' temperature are much more elevated, but below the melting point of the electrode wire. In some applications, it is believed that initiation of welding arcs and welds is facilitated when the electrode is hot. However, the current state of the art does not provide regimes designed to ensure that the electrode is heated prior to initiation of a welding operation.

### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates an example robotic welding system in which a robot is used to weld a workpiece using a welding tool, in accordance with aspects of this disclosure.

FIG. 2 illustrates an example liquid-cooled welding torch, in accordance with aspects of this disclosure.

FIG. 3 illustrates an exploded view of the example liquid-cooled welding torch of FIG. 2.

FIG. 4 is a more detailed depiction of an example liquid cooling assembly that may be used to implement the liquid cooling assemblies of FIG. 2.

FIG. 5 is a cross-section view of the liquid-cooled power cable assembly of FIG. 4.

FIG. 6 is an exploded view of the example liquid-cooled power cable assembly of FIG. 3.

FIGS. 7A, 7B, and 7C are views of the example cooler body of FIG. 6.

FIG. 8 is a cross-section view of the liquid cooling assembly and the quick-disconnect assembly of FIG. 2 coupled to the liquid cooling assembly of FIG. 4.

2

FIG. 9 illustrates the example welding assembly and the example liquid cooling assemblies of FIG. 2 disconnected from the remainder of the torch via the quick-disconnect assembly.

FIG. 10 is a cross-section view of the example welding assembly of FIG. 2.

FIGS. 11A, 11B, and 11C show an example implementation of the first contact tip of FIG. 10.

FIGS. 12A and 12B show an example implementation of the wire guide of FIG. 10.

FIGS. 13A, 13B, and 13C show an example implementation of the second contact tip of FIG. 10.

FIGS. 14A and 14B illustrate views of the example diffuser of FIGS. 3 and 10.

FIG. 15A illustrates a conventional robotic welding torch having a first tool center point distance and torch neck angle, in accordance with aspects of this disclosure.

FIG. 15B illustrates an example implementation of the liquid-cooled welding torch of FIG. 2 configured to replace the conventional torch of FIG. 15A while maintaining a same tool center point distance and torch neck angle.

FIG. 16 is a cross section of an example welding cable that may be used to provide cooling liquid, welding current, and preheating current to a welding torch, and to carry cooling liquid away from the welding torch, in accordance with aspects of this disclosure.

FIG. 17 illustrates a functional diagram of an example welding system including the example welding torch of FIG. 2, and which may be used with the welding system of FIG. 1.

FIG. 18 is a block diagram of an example implementation of the power supplies of FIG. 17.

FIG. 19 illustrates another example liquid-cooled welding torch, in accordance with aspects of this disclosure.

FIG. 20 is an exploded view of the example welding torch of FIG. 19.

FIG. 21 is a cross-sectional plan view of the example welding assembly of FIG. 19.

FIG. 22 is a cross-sectional plan view of the example power and liquid transfer assembly of FIG. 19.

FIG. 23 is a view of the example power and liquid transfer assembly of FIG. 19.

The figures are not to scale. Where appropriate, the same or similar reference numerals are used in the figures to refer to similar or identical elements.

### DETAILED DESCRIPTION

For the purpose of promoting an understanding of the principles of this disclosure, reference will be now made to the examples illustrated in the drawings and specific language will be used to describe the same. It will nevertheless be understood that no limitation of the scope of the claims is intended by this disclosure. Modifications in the illustrated examples and such further applications of the principles of this disclosure as illustrated therein are contemplated as would typically occur to one skilled in the art to which this disclosure relates.

As used herein, the word "exemplary" means "serving as an example, instance, or illustration." The embodiments described herein are not limiting, but rather are exemplary only. It should be understood that the described embodiments are not necessarily to be construed as preferred or advantageous over other embodiments. Moreover, the terms "embodiments of the invention," "embodiments," or "inven-

tion” do not require that all embodiments of the invention include the discussed feature, advantage, or mode of operation.

As utilized herein the terms “circuits” and “circuitry” refer to physical electronic components (i.e. hardware) and any software and/or firmware (code) that may configure the hardware, be executed by the hardware, and or otherwise be associated with the hardware. As used herein, for example, a particular processor and memory may comprise a first “circuit” when executing a first set of one or more lines of code and may comprise a second “circuit” when executing a second set of one or more lines of code. As utilized herein, “and/or” means any one or more of the items in the list joined by “and/or”. As an example, “x and/or y” means any element of the three-element set  $\{(x), (y), (x, y)\}$ . In other words, “x and/or y” means “one or both of x and y.” As another example, “x, y, and/or z” means any element of the seven-element set  $\{(x), (y), (z), (x, y), (x, z), (y, z), (x, y, z)\}$ . In other words, “x, y, and/or z” means “one or more of x, y and z”. As utilized herein, the term “exemplary” means serving as a non-limiting example, instance, or illustration. As utilized herein, the terms “e.g.” and “for example” set off lists of one or more non-limiting examples, instances, or illustrations. As utilized herein, circuitry is “operable” to perform a function whenever the circuitry comprises the necessary hardware and code (if any is necessary) to perform the function, regardless of whether performance of the function is disabled or not enabled (e.g., by an operator-configurable setting, factory trim, etc.).

As used herein, a wire-fed welding-type system refers to a system capable of performing welding (e.g., gas metal arc welding (GMAW), gas tungsten arc welding (GTAW), etc.), brazing, cladding, hardfacing, and/or other processes, in which a filler metal is provided by a wire that is fed to a work location, such as an arc or weld puddle.

As used herein, a welding-type power source refers to any device capable of, when power is applied thereto, supplying welding, cladding, plasma cutting, induction heating, laser (including laser welding and laser cladding), carbon arc cutting or gouging and/or resistive preheating, including but not limited to transformer-rectifiers, inverters, converters, resonant power supplies, quasi-resonant power supplies, switch-mode power supplies, etc., as well as control circuitry and other ancillary circuitry associated therewith.

As used herein, preheating refers to heating the electrode wire prior to a welding arc and/or deposition in the travel path of the electrode wire.

As used herein, the terms “front” and/or “forward” refer to locations closer to a welding arc, while “rear,” “back,” “behind,” and/or “backward” refers to locations farther from a welding arc.

Some disclosed examples describe electric currents being conducted “from” and/or “to” locations in circuits and/or power supplies. Similarly, some disclosed examples describe “providing” electric current via one or more paths, which may include one or more conductive or partially conductive elements. The terms “from,” “to,” and “providing,” as used to describe conduction of electric current, do not necessitate the direction or polarity of the current. Instead, these electric currents may be conducted in either direction or have either polarity for a given circuit, even if an example current polarity or direction is provided or illustrated.

Disclosed example welding torches include: a first contact tip configured to conduct welding current to a consumable electrode; a second contact tip configured to conduct preheating current to the consumable electrode; and a plurality

of liquid cooling assemblies configured to conduct the preheating current and to conduct the welding current to the consumable electrode.

In some examples, the plurality of liquid cooling assemblies includes: a first liquid cooling assembly configured to conduct the welding current; and a second liquid cooling assembly configured to conduct the preheating current. In some examples, the first liquid cooling assembly is configured to conduct the preheating current. Some example welding torches further include: a first socket having a first fluid valve and configured to permit fluid transfer with a first one of the liquid cooling assemblies when the first fluid valve is open; and a second socket electrically coupled to the first socket, wherein the first one of the liquid cooling assemblies comprises a first power connector pin configured to be inserted into the first socket and the second socket to transfer the fluid and to be electrically coupled to the second socket, the first fluid valve configured to open when the first power connector pin is inserted into the first socket and to close when the first power connector pin is removed from the first socket.

Some example welding torches further include a power connector pin retention mechanism configured to physically resist removal of the first power connector pin from the first socket and the second socket when engaged. Some example welding torches further include a retaining ring configured to attach the power connector pin retention mechanism to the first power connector pin. Some example welding torches further include a third socket having a second fluid valve and configured to permit fluid transfer with a second one of the liquid cooling assemblies when the second fluid valve is open. In some examples, the second socket includes a plurality of contacts arranged circumferentially around an interior surface of the second socket, the plurality of contacts configured to contact the first power connector pin to transfer at least one of the welding current or the preheating current.

In some examples, the plurality of liquid cooling assemblies include a first liquid cooling assembly configured to conduct the welding current and to provide a return path for the preheating current; and a second liquid cooling assembly. Some example welding torches further include a welding assembly having the first contact tip and the second contact tip, in which the welding assembly fluidly is coupled to the plurality of liquid cooling assemblies. In some examples, a first one of the liquid cooling assemblies includes an inner conductive layer configured to conduct at least one of the welding current or the preheating current; and an insulative layer exterior to the inner conductive layer. In some examples, the first one of the liquid cooling assemblies further includes an outer protective layer exterior to the insulative layer.

Some example welding torches further include a power and liquid transfer assembly configured to be fluidly and electrically coupled to the plurality of liquid cooling assemblies and, when fluidly and electrically coupled to the plurality of liquid cooling assemblies, to transfer current and coolant with the plurality of liquid cooling assemblies. Some example welding torches further include a securing mechanism configured to secure the power and liquid transfer assembly to the plurality of liquid cooling assemblies.

Some example welding torches further include a torch neck configured to detachably attach a welding assembly to a torch body, in which the welding assembly includes the first contact tip and the second contact tip, and the plurality of liquid cooling assemblies are mechanically coupled to the

## 5

torch neck. In some examples, the power and liquid transfer assembly is mechanically coupled to the torch body.

Some example welding torches further include a weld cable configured to conduct the preheating current, welding gas, and the consumable electrode to the welding torch. In some examples, the weld cable is an air-cooled or gas-cooled cable.

Referring to FIG. 1, an example welding system 100 is shown in which a robot 102 is used to weld a workpiece 106 using a welding tool 108, such as the illustrated bent-neck (i.e., gooseneck design) welding torch (or, when under manual control, a handheld torch), to which power is delivered by welding equipment 110 via conduit 118 and returned by way of a ground conduit 120. The welding equipment 110 may comprise, inter alia, one or more power sources (each generally referred to herein as a “power supply”), a source of a shield gas, a wire feeder, and other devices. Other devices may include, for example, water coolers, fume extraction devices, one or more controllers, sensors, user interfaces, communication devices (wired and/or wireless), etc.

The welding system 100 of FIG. 1 may form a weld (e.g., at weld joint 112) between two components in a weldment by any known electric welding techniques. Known electric welding techniques include, inter alia, shielded metal arc welding (SMAW), MIG, flux-cored arc welding (FCAW), TIG, laser welding, sub-arc welding (SAW), stud welding, friction stir welding, and resistance welding. MIG, TIG, hot wire cladding, hot wire TIG, hot wire brazing, multiple arc applications, and SAW welding techniques, inter alia, may involve automated or semi-automated external metal filler (e.g., via a wire feeder). In multiple arc applications (e.g., open arc or sub-arc), the preheater may pre-heat the wire into a pool with an arc between the wire and the pool. The welding equipment 110 may be arc welding equipment having one or more power supplies, and associated circuitry, that provides a direct current (DC), alternating current (AC), or a combination thereof to an electrode wire 114 of a welding tool (e.g., welding tool 108). The welding tool 108 may be, for example, a TIG torch, a MIG torch, or a flux cored torch (commonly called a MIG “gun”). The electrode wire 114 may be tubular-type electrode, a solid type wire, a flux-core wire, a seamless metal core wire, and/or any other type of electrode wire.

As will be discussed below, the welding tool 108 employs a contact tip assembly that heats the electrode wire 114 prior to forming a welding arc using the electrode wire 114. Suitable electrode wire 114 types includes, for example, tubular wire, metal cored wire, aluminum wire, solid gas metal arc welding (GMAW) wire, composite GMAW wire, gas-shielded FCAW wire, SAW wire, self-shielded wire, etc.

In the welding system 100, the robot 102, which is operatively coupled to welding equipment 110 via conduit 118 and ground conduit 120, controls the location of the welding tool 108 and operation of the electrode wire 114 (e.g., via a wire feeder) by manipulating the welding tool 108 and triggering the starting and stopping of the current flow (whether a preheat current and/or welding current) to the electrode wire 114 by sending, for example, a trigger signal to the welding equipment 110. When welding current is flowing, a welding arc is developed between the electrode wire 114 and the workpiece 106, which ultimately produces a weldment. The conduit 118 and the electrode wire 114 thus deliver welding current and voltage sufficient to create the electric welding arc between the electrode wire 114 and the workpiece 106. At the point of welding between the electrode wire 114 and the workpiece 106, the welding arc

## 6

locally melts the workpiece 106 and electrode wire 114 supplied to the weld joint 112, thereby forming a weld joint 112 when the metal cools.

In certain aspects, in lieu of a robot 102’s robotic arm, a human operator may control the location and operation of the electrode wire 114. For example, an operator wearing welding headwear and welding a workpiece 106 using a handheld torch to which power is delivered by welding equipment 110 via conduit 118. In operation, as with the system 100 of FIG. 1, an electrode wire 114 delivers the current to the point of welding on the workpiece 106 (e.g., a weldment). The operator, however, could control the location and operation of the electrode wire 114 by manipulating the handheld torch and triggering the starting and stopping of the current flow via, for example, a trigger. A handheld torch generally comprises a handle, a trigger, a conductor tube, a nozzle at the distal end of the conductor tube, and a contact tip assembly. Applying pressure to the trigger (i.e., actuating the trigger) initiates the welding process by sending a trigger signal to the welding equipment 110, whereby welding current is provided, and the wire feeder is activated as needed (e.g., to drive the electrode wire 114 forward to feed the electrode wire 114 and in reverse to retract the electrode wire 114). Commonly owned U.S. Pat. No. 6,858,818 to Craig S. Knoener, for example, describes an example system and method of controlling a wire feeder of a welding-type system.

FIG. 2 illustrates an example liquid-cooled welding torch 200. The liquid-cooled welding torch 200 may be used to implement the welding tool 108 of FIG. 1 to deliver the electrode wire 114 to a workpiece while providing both resistive preheating power and welding-type power.

The liquid-cooled welding torch 200 includes a welding assembly 202, a mounting assembly 204, a weld cable 206, liquid cooling assemblies 208, 210, 212, 214, and a power and liquid transfer assembly 216. As disclosed herein, the example liquid-cooled welding torch 200 may be used to replace conventional robotic welding torches with resistive preheating-enabled welding torches having a same tool center point (TCP). By replacing a torch with another torch having a same TCP, the robot may be capable of continuing a welding program using the replacement torch with little or no reprogramming of tool points.

The welding assembly 202 receives weld current and preheating current, conducts the weld current to the electrode wire 114, and conducts the preheating current through a portion of the electrode wire 114. The example welding assembly 202 is liquid-cooled by liquid provided via the liquid cooling assemblies 208-214. The example welding assembly 202 of FIG. 2 receives the weld current via one or more of the weld cable 206, the liquid cooling assemblies 208 and 212, and/or the liquid cooling assemblies 210 and 214. Because the workpiece provides the return path for the weld current to the power supply, no return path is provided via the weld cable 206 or the liquid cooling assemblies 208. The weld cable 206 is an air-cooled (or gas-cooled) cable. However, the weld cable 206 may also be liquid-cooled.

The example welding assembly 202 receives the preheating current via the weld cable 206, the liquid cooling assemblies 208 and 212, and/or the liquid cooling assemblies 210 and 214. In the example of FIG. 2, the weld current is conducted via a different one of the weld cable 206, the liquid cooling assemblies 208 and 212, or the liquid cooling assemblies 210 and 214 than the preheating current that has the same polarity (i.e., current flow direction). The welding assembly 202 conducts the preheating current through a section of the electrode wire 114 to heat the electrode wire

via resistive heating (e.g., I<sup>2</sup>R heating). The preheat current then returns to a preheating power supply via a different one of weld cable **206**, the liquid cooling assemblies **208** and **212**, or the liquid cooling assemblies **210** and **214** to complete a preheating circuit.

In the example of FIG. 2, the weld current path, the preheating current supply path, and the preheating current return path may all be different ones of the weld cable **206**, the liquid cooling assemblies **208** and **212**, and the liquid cooling assemblies **210** and **214**. In some examples, the weld current path may be superimposed with the preheating current supply path or the preheating current return path to reduce the net current in the conductor. For example, if the weld current is 300 A and the preheating current is 100 A, the weld current and the preheating current may be superimposed to result in a net current of 200 A.

As described in more detail below, the welding assembly **202** and the liquid cooling assemblies **212**, **214** may be separated from the remainder of the liquid-cooled welding torch **200** via the power and liquid transfer assembly **216**.

FIG. 3 illustrates an exploded view of the example liquid-cooled welding torch **200** of FIG. 2.

As shown in FIG. 3, the example welding assembly **202** includes a nozzle **302**, a diffuser insulator **304**, a first contact tip **306**, a wire guide **308**, a gas diffuser **310**, a first contact tip insulator **312**, a second contact tip **314**, a second contact tip insulator **316**, a nozzle mount **318**, and a nozzle mount clamp **320**.

A liquid-cooled power cable assembly **322** includes the liquid cooling assemblies **212**, **214**, a cooler **324**, and power connector pins **326**, **328**. The liquid-cooled power cable assembly **322** is described below in more detail with reference to FIGS. 6, 7A, 7B, and 8.

The power and liquid transfer assembly **216** enables quick separation of the welding assembly **202** and the liquid-cooled power cable assembly **322** from the mounting assembly **204**. In the example of FIG. 3, the power and liquid transfer assembly **216** includes a saddle **330**, a saddle cover **332**, a saddle clasp **334**, and saddle clamps **336**. The power and liquid transfer assembly **216** is described below in more detail with reference to FIGS. 4 and 5.

The example mounting assembly **204** includes a torch body **338**, a neck **340**, and a robot link assembly **342** including, for example, a bracket, a link arm, and a robot mounting disk.

FIG. 4 is a more detailed depiction of an example liquid cooling assembly **400** that may be used to implement the liquid cooling assemblies **208**, **210** of FIG. 2. FIG. 5 is a cross-section view of the liquid cooling assembly **400** of FIG. 4.

The liquid cooling assembly **400** includes a power cable socket **402** that holds a power transfer socket **404** and a liquid shutoff valve **406**. The liquid cooling assembly **400** also includes a hose **408** and an internal conductor **410**. The hose **408** is coupled to the power cable socket **402** on a first end and coupled to a power cable fitting **412** on a second end.

The power cable socket **402** receives one of the power connector pins **326**, **328** to transfer cooling liquid and welding current and/or preheating current to a corresponding one of the liquid cooling assemblies **212**, **214**. The power transfer socket **404** enables insertion of the power connector pin **326**, **328**, and transfers current to and/or from an inserted power connector pin **326**, **328**. An example power transfer socket that may be used to implement the power transfer socket **404** is a PowerBud® power contact, sold by Methode

Electronics, Inc., which provides multiple contact points between the power transfer socket and an inserted power connector pin **326**, **328**.

The liquid shutoff valve **406** selectively permits flow of liquid from the hose **408** to the power transfer socket **404** and to a connected liquid cooling assembly **212**, **214**. The example liquid shutoff valve **406** is a Schrader valve. However, other types of valves may be used to implement the liquid shutoff valve **406**. When a power connector pin **326**, **328** is inserted (e.g., fully inserted) into the power transfer socket **404**, the power connector pin **326**, **328** displaces (e.g., unseats) a stem **414** from a core **416** of the valve **406**, which permits liquid to flow to and/or from the hose **408**. When the power connector pin **326**, **328** is removed or partially removed, the stem **414** is forced back into the core **416** and stops flow of liquid.

The hose **408** is coupled to the power cable fitting **412** via a ferrule **418** and a fitting nut **420**. The power cable fitting **412** is coupled to a source of weld current and/or preheating current, and is electrically connected to transfer the weld current and/or preheating current to or from the internal conductor **410** of the hose **408**. The hose **408** is also coupled to the power cable socket **402** via a ferrule **418**. The example power cable fitting **412**, the example power cable socket **402**, and/or the hose **408** include hose barbs to secure the hose **408**. However, other methods of securing the hose to the power cable fitting **412** and/or the power cable socket **402** may be used, such as clamps, compression fittings, or any other hose fittings.

During operation, when the power cable fitting **412** is coupled to a power source and a liquid cooling device, and the power cable socket **402** is coupled to a liquid cooling assembly **212**, **214**, the example liquid cooling assembly **400** permits liquid to flow through the power cable fitting **412**, the hose **408**, the valve **406**, the power cable socket **402**, and the power transfer socket **404**, either to or from the liquid cooling device (e.g., based on whether the assembly is configured as the liquid supply or the liquid return). The example liquid cooling assembly **400** also conducts current from and/or to a weld power supply and/or a preheating power supply. For example, the current is conducted through the power cable fitting **412**, the internal conductor **410**, the power cable socket **402**, and the power transfer socket **404**.

FIG. 6 is an exploded view of the example liquid-cooled power cable assembly **322** of FIG. 3. The liquid-cooled power cable assembly **322** provides cooling liquid supply and return paths from the liquid cooling assemblies **212**, **214** to the welding assembly **202** of FIG. 3. The liquid-cooled power cable assembly **322** includes the liquid cooling assemblies **212**, **214**, the power connector pins **326**, **328**, a cooling body **602**, and a cooling body cover **604**.

Each of the example liquid cooling assemblies **212**, **214** includes three layers: an inner conductive layer **606a**, **606b**; an insulative layer **608a**, **608b**; and an outer protective layer **610a**, **610b**. The inner conductive layer **606a**, **606b** conduct current and liquid, and is constructed of a conductive material such as copper. The insulative layers **608a**, **608b** provide electrical insulation between the inner conductive layers **606a**, **606b** and the outer protective layers **610a**, **610b**. The example insulative layers **608a**, **608b** may be silicone, PTFE, PET, and/or any other suitable electrically insulative material or combination of materials. The outer protective layers **610a**, **610b** provide rigidity and/or physical protection from damage, such as punctures. The outer protective layers **610a**, **610b** may be a rigid material such as aluminum or any other appropriate material or combination of materials.

In some examples, two or more of the layers **606a-610a**, **606b-610b** may be combined. For example, the insulative layers **608a**, **608b** may also serve as the outer protective layers **610a**, **610b**, or vice versa. In other examples, the outer protective layers **610a**, **610b** may be omitted.

The inner conductive layers **606a**, **606b** are contained within the insulative layers **608a**, **608b**. The insulative layers **608a**, **608b** are similar contained within the outer protective layers **610a**, **610b**.

One of the liquid cooling assemblies **212**, **214** supplies cooling liquid to the cooling body **602**, and the other of the liquid cooling assemblies **212**, **214** receives the liquid from the cooling body **602**. The cooling body **602** circulates the liquid through a tortuous path **612** between a liquid input port and a liquid output port. The cooling body **602** is coupled to the welding assembly **202** to conduct heat from the components in the welding assembly **202** to the liquid, thereby cooling the welding assembly **202**. The cooling body cover **604** is attached to the cooling body **602** to contain the fluid within the tortuous path **606**. In some examples, the cooling body **602** and a cooling body cover **604** may be a single unit (e.g., constructed using additive manufacturing techniques).

FIGS. **7A**, **7B**, and **7C** are views of the example cooler body **602** of FIG. **6**. As illustrated in FIGS. **7A**, **7B**, and **7C**, the tortuous path **612** includes a continuous path around a circumference of the cooler body **602**. In the illustrated example, the liquid cooling assembly **214** supplies cooling liquid to the cooler body **602** and the liquid cooling assembly **212** returns the cooling liquid to a liquid cooler. The cooling liquid follows a flow path **702** (shown using a dotted line) through the tortuous path **612** to increase heat transfer from the welding assembly **202** to the liquid. Continuities A and B from one view to the next are shown in FIGS. **7A**, **7B**, and **7C**.

FIG. **8** is a cross-section view of the liquid cooling assembly **212**, **214** and the power and liquid transfer assembly **216** of FIG. **2** coupled to the liquid cooling assembly **400** of FIG. **4**.

As illustrated in FIG. **8**, the power cable socket **402** is seated in the saddle **330**, which prevents movement of the power cable socket **402**. The example power connector pin **326** is inserted into the power cable socket **402** and the power transfer socket **404**. The power connector pin **326** includes an inner liquid coolant passage **802**, one or more liquid coolant ports **804** to enable liquid to flow into and/or out of the liquid coolant passage **802**, and a seal **806**. When inserted, the power connector pin **326** opens the valve **406** to permit liquid to flow through the valve **406**, the liquid coolant ports **804**, the liquid coolant passage **802**, and the inner conductive layer **606a**. A retaining ring **808** may be included in the saddle cover **332** to hold the power connector pin **326** in place.

In addition to placing the liquid cooling assembly **212** in fluid communication with the liquid cooling assembly **208**, the example power connector pin **326** also conducts weld current and/or preheating current between the liquid cooling assembly **212** and the liquid cooling assembly **208**. The example inner conductive layer **606a** is in electrical contact with the power transfer pin **326**, which is a conductive material (e.g., copper) and is in electrical contact with the power transfer socket **404**.

While the examples are described with reference to the liquid cooling assembly **208**, the liquid cooling assembly **212**, and the power connector pin **326**, these examples are

similarly applicable to the liquid cooling assembly **210**, the liquid cooling assembly **214**, and the power connector pin **328**.

FIG. **9** illustrates the example welding assembly **202** and the example liquid cooling assemblies **212**, **214** of FIG. **2** disconnected from the remainder of the torch **200** via the power and liquid transfer assembly **216**. For detachment of the example liquid cooling assemblies **212**, **214**, the example saddle clasp **334** is unhooked or otherwise detached from a retention pin **902** on the saddle **330**. When the saddle clasp **334** is unhooked, the power connector pin **328** can be disengaged from the power cable socket **402** and the saddle cover **332** can be simultaneously lifted from the saddle **330**. Conversely, to install the liquid cooling assemblies **212**, **214**, the power connector pins **326**, **328** are inserted into corresponding power cable sockets **402** while the saddle cover **332** is placed onto the saddle **330**. When the power connector pins **326**, **328** and the saddle cover **332** are in place on the saddle **330**, the saddle clasp **334** is hooked into the retention pin **902** to hold the power connector pins **326**, **328** in place.

FIG. **10** is a cross-section view of the example welding assembly **202** of FIG. **2**. The welding assembly **202** is liquid-cooled via the liquid cooling assemblies **212**, **214**. The liquid cooling assemblies **212**, **214** and/or a torch neck **1002** provide weld current and preheating current to the welding assembly **202** for preheating the electrode wire **114** and for generating a welding arc.

The example welding assembly **202** includes the nozzle **302**, the diffuser insulator **304**, the first contact tip **306**, the wire guide **308**, the gas diffuser **310**, the first contact tip insulator **312**, the second contact tip **314**, the second contact tip insulator **316**, the nozzle mount **318**, the nozzle mount clamp **320**, the cooling body **602**, and the cooling body cover **604**. The welding assembly **202** is attached to a torch neck **1002**, through which a wire liner **1004** conveys the electrode wire **114** and/or shielding gas to the welding assembly **202**.

The first contact tip **306** delivers welding current to the electrode wire **114** for arc welding. The first contact tip **306** is threaded into a gas diffuser **310**, which is in turn threaded into the diffuser insulator **304**. The diffuser insulator **304** provides electrical and thermal insulation between the gas diffuser **310** and the nozzle **302**.

The gas diffuser **310** is threaded into the cooling body **602**. The cooling body **602** conducts welding current and/or preheating current from the liquid-cooled power cable assembly **322** (e.g., from the inner conductive layer(s) **606a**, **606b**) to the diffuser **310**, which is electrically connected to the first contact tip **306**. The first contact tip insulator **312** and the diffuser insulator **304** provide electrical insulation between the weld current and preheat current path(s) and the nozzle **302**.

The second contact tip **314** is electrically coupled to the torch neck **1002** to conduct preheating current to and/or from the electrode wire **114**. The preheating circuit includes the torch neck **1002**, the second contact tip **314**, the first contact tip **306**, a portion of the electrode wire **1006** between the second contact tip **314** and the first contact tip **306**, the diffuser **310**, the cooling body **602**, and one or both of the inner conductive layers **606a**, **606b** in the liquid-cooled power cable assembly **322**.

The second contact tip insulator **316** provides electrical insulation between the second contact tip **314** and the cooling body **602**. The second contact tip insulator **316** includes a seal **1008** (e.g., an o-ring) to reduce or prevent welding gas leakage.

## 11

The nozzle mount **318** and the nozzle mount clamp **320** provide an attachment point for threading the welding assembly **202** onto the torch neck **1002**. The nozzle mount **318** physically couples and/or provides support to the liquid-cooled power cable assembly **322** from the torch neck **1002**, which is rigid.

In addition to the welding assembly **202**, the liquid-cooled power cable assembly **322**, and the torch neck **1002** being detachable from the mounting assembly **204** (e.g., via the power and liquid transfer assembly **216** and a conventional disconnection feature between the torch neck **1002** and the mounting assembly **204**), the welding assembly **202** may be completely or partially disassembled to access one or more of the components in the welding assembly **202**.

In the example of FIG. **10**, the first contact tip **306**, the wire guide **308**, and/or the second contact tip **314** are removable via the tip of the nozzle **302**. FIGS. **11A**, **11B**, and **11C** show an example implementation of the first contact tip **306**, FIGS. **12A** and **12B** show an example implementation of the wire guide **308**, and FIGS. **13A**, **13B**, and **13C** show an example implementation of the second contact tip **314**.

As shown in FIGS. **10** and **11A**, a first end **1102** of the first contact tip **306** has a hexagonal cross-section. The hexagonal cross-section enables the first contact tip **306** to be unthreaded from the diffuser **310** via the opening in the nozzle **302**. Other exterior geometries may be used for the cross-section of the first end **1102** of the first contact tip **306**. Additionally or alternatively, an interior geometry may be used (e.g., in combination with a corresponding tool) to unthread the first contact tip **306** from the diffuser **310**.

After removal of the first contact tip **306** from the welding assembly **202** via the nozzle **302**, the wire guide **308** may also be removed via the nozzle **302**. As shown in FIGS. **10**, **12A**, and **12B**, an outer surface **1202** of the wire guide **308** is relatively smooth (e.g., not threaded) and can be inserted into and removed from of an inner diameter **1010** of the cooling body **602** without threading. The wire guide **308** has a wire path **1204** to guide the wire from the second contact tip **314** to the first contact tip **306**. In some examples, the wire guide **308** is a nonconductive material such as ceramic, so that the electrode wire **114** is the only conductive path between the second contact tip **314** and the first contact tip **306**.

As shown in FIGS. **13A**, **13B**, and **13C**, the second contact tip **314** includes a hexagonal cross-section on a first end **1302** of the second contact tip **314**. An interior surface **1304** and/or an exterior surface **1306** (e.g., a head) of the first end **1302** may provide the hexagonal cross-section and/or any other shape that enables the second contact tip to be unthreaded from the torch neck **1002**. The example second contact tip **314** includes threads **1305** to enable the second contact tip **314** to be threaded into the second contact tip insulator **316**. The exterior surface **1306** has a smaller diameter than the major diameter of the threads **1305**, which can improve access to the exterior surface **1306** for removal and/or installation of the second contact tip **314**.

As shown in FIG. **10**, the outer diameter of the second contact tip **314** is equal to or less than the inner diameter **1010** of the cooling body **602** and less than an inner diameter **1012** of the second contact tip insulator **316** to enable the second contact tip **314** to be removed via the tip of the nozzle **302**, the cooling body **602**, and the second contact tip insulator **316**. The first end **1302** may be manipulated (e.g., via a tool inserted through the nozzle **302**) to unthread the second contact tip **314** from the torch neck **1002**, after which

## 12

the second contact tip **314** can be removed from the welding assembly **202** without disassembly of the welding assembly **202**.

As shown in FIGS. **13A**, **13B**, and **13C**, the second contact tip **314** includes slots **1308** running longitudinally on the exterior of the second contact tip **314** through the threads **1305**. The slots **1308** permit the flow of welding gas from the interior of the torch neck **1002** to the diffuser **310** via the cooling body **602** (e.g., through the interior of the cooling body **602** through and/or around the wire guide **308**).

The second contact tip **314** includes a first bore **1310** having a first diameter. The electrode wire **114** makes electrical contact with the first bore **1310**. The example second contact tip **314** may also have a second, larger bore **1312** on a rear side of the contact tip **314** from the first bore **1310**. The length of the second bore **1312** may be selected to control a contact length of the first bore **1310**.

As illustrated in FIG. **10**, the example contact tip **314** may have an insert **1012** inserted within the first bore **1310** to improve contact with the electrode wire **114**, improve current transfer with the electrode wire **114**, and/or improve mechanical strength at operating temperatures.

FIGS. **14A** and **14B** illustrate views of the example diffuser **310** of FIGS. **3** and **10**. As discussed above with reference to FIG. **10**, the diffuser **310** includes two sets of exterior threads for installation into the diffuser insulator **304** and the cooling body **602**, and a set of interior threads for installation of the first contact tip **306** into the diffuser **310**. The diffuser **310** includes gas outlets **1402** to enable the flow of gas from the inner diameter **1010** of the cooling body **602** to the nozzle **302** for output to the weld.

FIG. **15A** illustrates a conventional robotic welding torch **1500** having a first tool center point distance and torch neck angle. FIG. **15B** illustrates an example implementation of the liquid-cooled welding torch **200** of FIG. **2** configured to replace the conventional torch **1500** of FIG. **15A** while maintaining a same tool center point distance and torch neck angle.

The tool center point distance **1502** of the conventional torch **1500** is a function of a stickout distance **1504**, a nozzle length **1506**, a nozzle angle **1508**, a neck bend angle **1510**, a tool center point area **1512**, and a spacer width **1514**. The tool center point area **1512** (e.g.,  $Area_{TCP}$ ) is defined using Equation 1 below:

$$Area_{TCP} = 0.5 * ((TCP - \text{spacer width } 1514)^2 * \tan(\text{nozzle angle } 1508) + ((TCP - \text{spacer width } 1514) - (\text{nozzle length } 1506 + \text{stickout } 1504)) * \cos(\text{nozzle angle } 1508))^2 * (\tan(\text{nozzle angle } 1508) - \text{neck bend angle } 1510) - 1) \quad (\text{Equation 1})$$

The example welding assembly **202** described above with reference to FIGS. **10**, **11A-11C**, **12A**, **12B**, **13A-13C**, **14A**, and/or **14B** may have a same nozzle length **1506** as conventional nozzles. In other examples, the welding assembly **202** may require a longer nozzle **302** than a nozzle of the conventional torch. In some examples, such as the welding torch described below with reference to FIGS. **19-23**, the welding assembly may have a nozzle that is shorter than conventional nozzles. However, the length of the example torch neck **1002** and/or the length and/or one or more dimensions of the example mounting assembly **204** may be adjusted to compensate for differences in the nozzle length.

Using the example welding assembly **202** disclosed herein, the example liquid-cooled welding torch **200** may be dimensioned to be a replacement for any standard tool center point distance (e.g., 350 mm, 400 mm, 450 mm, 500 mm, etc.) and/or torch neck angle (e.g., 0 degree, 22 degree, 35 degree, 45 degree, etc.) to maintain the same TCP, torch



## 13

neck angle, and tool center point area after replacement. In other words, disclosed example welding assemblies **202** and/or liquid-cooled welding torches **200** may be used as replacements for conventional robotic weld torches such that a robot on which the replacement occurs does not require reprogramming or recalibration of new tool center point(s) or torch neck angle(s). After replacement of the conventional welding torch with disclosed example liquid-cooled welding torches, the robot subject to replacement is capable of higher deposition rates, improved welding starts, and/or other advantages over conventional welding torches. As a result, reprogramming of welding voltages, currents, and/or torch travel speeds may be performed to realize the advantages of the liquid-cooled welding torch **200** for previously programmed welding tasks.

In addition to the tool center point distance **1502**, the stickout distance **1504**, the nozzle length **1506**, the nozzle angle **1508**, the neck bend angle **1510**, the tool center point area **1512**, and the spacer width **1514** dimensions of the conventional welding torch **1500**, the example welding torch **200** includes a preheat distance **1516** within the nozzle. The nozzle length **1506** is subdivided into the stickout distance **1504**, the preheat distance **1516**, and a neck-to-contact tip length **1518**. The conventional torch **1500** may be considered to have a preheat distance **1516** of 0. By replacing a conventional weld torch **1500** with a weld torch **200** having substantially the same tool center point distance **1502**, the stickout distance **1504**, the nozzle length **1506**, the nozzle angle **1508**, the neck bend angle **1510**, and the tool center point area **1512**, the replacement reduces the programming needed to avoid an increased risk of collisions.

Tables 1 and 2 below illustrates example comparisons of the dimensions **1502-1516** for two example tool center point distances **1502**, 350 mm and 400 mm.

TABLE 1

| 350 mm TCP Dimensions for Conventional and Disclosed example welding torches |          |          |               |              |                                 |                    |                     |                   |                    |
|--|----------|----------|---------------|--------------|---------------------------------|--------------------|---------------------|-------------------|--------------------|
| #  | TCP (mm) | TCP (in) | Stickout (in) | Preheat (in) | Neck-to-contact tip length (in) | Nozzle length (in) | Nozzle angle (deg.) | Neck angle (deg.) | TCP area (sq. in.) |
| 1  | 350      | 13.78    | 0.59          | 0.00         | 4.33                            | 4.92               | 45                  | 22                | 51.59              |
| 2  | 350      | 13.78    | 0.75          | 3.29         | 1.78                            | 5.82               | 45                  | 22                | 54.61              |
| 3  | 350      | 13.78    | 0.75          | 2.40         | 1.78                            | 4.93               | 45                  | 22                | 51.61              |

TABLE 2

| 400 mm TCP Dimensions for Conventional and Disclosed example welding torches |          |          |               |              |                                 |                    |                     |                   |                    |
|--|----------|----------|---------------|--------------|---------------------------------|--------------------|---------------------|-------------------|--------------------|
| #  | TCP (mm) | TCP (in) | Stickout (in) | Preheat (in) | Neck-to-contact tip length (in) | Nozzle length (in) | Nozzle angle (deg.) | Neck angle (deg.) | TCP area (sq. in.) |
| 4  | 400      | 15.75    | 0.59          | 0.00         | 4.33                            | 4.92               | 45                  | 22                | 66.44              |
| 5  | 400      | 15.75    | 0.75          | 3.29         | 1.78                            | 5.82               | 45                  | 22                | 70.17              |
| 6  | 400      | 15.75    | 0.75          | 2.40         | 1.78                            | 4.93               | 45                  | 22                | 66.46              |

A welding torch having a preheat length of 3.29 inches (e.g., torches 2 and 5 of Tables 1 and 2 above) may be used with an air-cooled torch. A welding torch having a preheat length of 2.40 inches results in a nozzle length **1506** and TCP area **1512** of a welding torch **200** that substantially match the nozzle length and TCP area **1512** of the conventional torch **1500**. However, the current density may increase enough to require an increase in the radius of the welding

## 14

assembly **202** (e.g., increased components in the welding assembly **202**) to continue to use air cooling (as in torches 2 and 5 of Tables 1 and 2). Additionally or alternatively, the preheat distance of 2.40 inches may be used with the example liquid cooled welding torch **200** disclosed herein.

Any of the dimensions of Tables 1 and 2 (or similar dimensions) may be selected based on a specification of another of the dimensions. For example, the preheating length (and, thus, the dimensions of the welding assembly) may be selected based on any of the TCP, the stickout, the neck-to-contact tip length, the nozzle length, the nozzle angle, the neck angle, and/or the TCP area. Additionally or alternatively, the neck-to-contact tip length is based on at least one of a nozzle length, a preheat distance, a nozzle angle, or a neck angle.

Preheat lengths **1516** that are longer than the 3.29 inches of the examples of Tables 1 and 2 may result in a torch envelope that is larger than the envelope of the conventional torches **1500** by more than an acceptable amount. Torches having an envelope that is excessively large may require more robot programming to serve as a replacement for a conventional torch and/or has a higher chance of collision during operation. Additional programming and collisions are undesirable effects of replacement, and disclosed examples reduce or prevent such effects while providing the benefits of electrode preheating at the welding assembly **202**.

While the example welding assembly **202** includes the first contact tip **306** and the second contact tip **314** such that both of the contact tips **306**, **314** are on a distal end of the bend in the torch neck **1002**, in some other examples the second contact tip **314** is on a proximal side of the bend in the torch neck **1002**. Additionally or alternatively, a third contact tip is further located on the proximal side of the bend in the torch neck **1002** so that preheating occurs between the

second contact tip **314** (on either side of the bend) and the third contact tip (on the proximal side of the bend).

When the electrode wire **114** is heated beyond a particular temperature, the column strength of the electrode wire **114** may be reduced to a point that the heated electrode wire **114** can no longer be pushed around the bend in the torch neck **1002** without buckling. In some such examples, the liquid-

15

cooled welding torch **200** is provided with a pull motor to assist the push motor located in the wire feeder.

The bend in the torch neck **1002** may be provided with ceramic bearings to reduce the friction force between the wire liner **1004** and the electrode wire **114**, which increases the temperature to which the electrode wire **114** may be preheated before buckling becomes likely.

In some examples, the length between the first and second contact tips **306**, **314** (e.g., the preheat length) is adjustable to change the length of the electrode wire **114** that is being preheated. As the preheat length increases, the energy added to the electrode wire **114** is increased per unit of current. To change the preheat length, one or both of the contact tips **306**, **314** may be configured to be translated in the axial direction via manual and/or automatic methods.

Using the second contact tip **314** as an example, the second contact tip **314** may be threaded into an intermediate device between the second contact tip **314** and the torch neck **1002**. The intermediate device may be automatically rotated (e.g., with a motor coupled to the contact tip) and/or manually rotated (e.g., with a thumb wheel or other device configured to cause rotation in the contact tip) while limiting rotation of the second contact tip **314**, which causes the threads of the second contact tip **314** to carry the second contact tip **314** toward or away from the first contact tip **306**.

Additionally or alternatively, the first and/or second contact tips **306**, **314** may be configured to be reversible to change the preheat length. For example, if the first contact tip **306** has a contact location with the electrode wire **114** that is closer than a midpoint of the first contact tip **306** to the second contact tip **314**, reversing the first contact tip **306** changes the contact location with the electrode wire **114** and extends the preheat length. In some examples, different contact tips have different contact points, so that changing contact tips changes the preheat length. In some other examples, the welding assembly **202** may be replaced with a different welding assembly that has a different preheat length such as different spacing between the contact tips **306**, **314** (which may require a different robotic program to be run that accounts for a different nozzle length).

The change in preheat length may be automatically controlled based on, for example, a temperature of the electrode wire **114** and/or based on a desired preheat level or heat input to the weld specified by a user. In some examples, a current controlled control loop is used to control preheat current when the preheat length is automatically adjustable.

The power and liquid transfer assembly **216** is attached to the torch body **338** on a side of the torch body **338** opposite the mounting assembly **204**, or opposite a direction of the bend in the torch neck **1002**. Because the power and liquid transfer assembly **216** increasing a volume of the torch **200**, locating the power and liquid transfer assembly **216** opposite the mounting assembly **204** and/or opposite a direction of the bend in the torch neck **1002** may reduce the chances of collision with a workpiece when using the same program with the replacement preheating weld torch **200** as used with a conventional weld torch.

In still other examples, the welding assembly **202** may be provided with a wire oscillator to cause physical oscillation or weave at a tip of the electrode wire **114**. An example implementation of the wire oscillator that may be used to provide wire oscillation is described in U.S. Pat. No. 4,295,031. Using both the wire oscillator and the contact tips **306**, **314**, disclosed example welding torches may provide both wire oscillation and resistive preheating to a weld to further improve deposition rates and weld quality.

16

FIG. **16** is a cross section of an example welding cable **1600** that may be used to provide cooling liquid, welding current, and preheating current to a welding torch, and to carry cooling liquid away from the welding torch. The example welding cable **1600** may be used instead of the liquid cooling assemblies **208**, **210**, in cases in which the first contact tip **306** is part of the preheating circuit and the welding circuit.

The welding cable **1600** is a coaxial-type welding cable, in which the electrode wire **114** is fed through a wire guide **1602**. The wire guide **1602** is surrounded by a jacket **1604**. A first conductor **1606** provides a first electrical path for preheating current, or welding current and preheating current. The first conductor **1606** may be, for example, a copper sheath or webbing rated to conduct welding current. The first conductor **1606** is surrounded by a jacket **1608**.

A second conductor **1610** provides a second electrical path for preheat current, or welding current and preheating current. In the example of FIG. **16**, a first one of the first conductor **1606** or the second conductor **1610** provides a path for the preheating current and is coupled to a preheating power supply. The second conductor **1610** is surrounded by a jacket **1612**. In some examples, another protective layer may be present outside of the jacket **1612** to protect the welding cable **1600** from damage. In some examples, the jacket **1612** provides both physical and electrical protection to the cable **1600**.

An annulus **1614** between the jacket **1604** and the first conductor **1606** and/or the jacket **1608** conducts cooling liquid in a first direction (e.g., from a liquid cooler to the welding torch, from the welding torch to the liquid cooler). An annulus **1616** between the jacket **1608** and the second conductor **1610** and/or the jacket **1612** conducts the cooling liquid in a second direction opposite the liquid flow direction in the annulus **1614**.

FIG. **17** illustrates a functional diagram of an example welding system **1700** including the example welding torch **200** of FIG. **2**, and which may be used with the welding system **100** of FIG. **1**. The welding system **1700** includes the weld torch **200** having the first contact tip **306** and a second contact tip **314**. The system **1700** further includes the electrode wire **114** fed from a wire feeder **1702** having a wire drive **1704** and a wire spool **1706**, a preheating power supply **1708**, and a welding power supply **1710**. The system **1700** is illustrated in operation as producing a welding arc **1712** between the electrode wire **114** and a workpiece **106**.

In operation, the electrode wire **114** passes from the wire spool **1706** through the second contact tip **314** and the first contact tip **306**, between which the preheating power supply **1708** generates a preheating current to heat the electrode wire **114**. Specifically, in the configuration shown in FIG. **17**, the preheating current enters the electrode wire **114** via the second contact tip **314** (e.g., via the wire drive **1704** and/or the torch neck **1002** of FIG. **10**) and exits via the first contact tip **306**. At the first contact tip **306**, a welding current may also enter the electrode wire **114** (e.g., via the liquid cooling assemblies **208** and **212**, and/or **210** and **214**). The welding current is generated, or otherwise provided by, the welding power supply **1710**. The welding current exits the electrode wire **114** via the workpiece **106**, which in turn generates the welding arc **1712**. When the electrode wire **114** makes contact with a target metal workpiece **106**, an electrical circuit is completed and the welding current flows through the electrode wire **114**, across the metal workpiece(s) **106**, and returns to the welding power supply **1710**. The welding current causes the electrode wire **114** and the parent metal of the work piece(s) **106** in contact with the

electrode wire **114** to melt, thereby joining the work pieces as the melt solidifies. By preheating the electrode wire **114**, a welding arc **1712** may be generated with drastically reduced arc energy. Generally speaking, the preheating current is proportional to the distance between the contact tips **306**, **314** and the electrode wire **114** size.

The welding current is generated, or otherwise provided by, a welding power supply **1710**, while the preheating current is generated, or otherwise provided by, the preheating power supply **1708**. The preheating power supply **1708** and the welding power supply **1710** may ultimately share a common power source (e.g., a common generator or line current connection), but the current from the common power source is converted, inverted, and/or regulated to yield the two separate currents—the preheating current and the welding current. For instance, the preheat operation may be facilitated with a single power source and associated converter circuitry, in which case three leads may extend from a single power source.

During operation, the system **1700** establishes a welding circuit to conduct welding current from the welding power supply **1710** to the first contact tip **306** via the liquid cooling assemblies **208** and **212** and/or **210** and **214**, and returns to the power supply **1710** via the welding arc **1712**, the workpiece **106**, and a work lead **1718**. To enable connection between the welding power supply **1710** and the first contact tip **306** and the workpiece **106**, the welding power supply **1710** includes terminals **1720**, **1722** (e.g., a positive terminal and a negative terminal).

During operation, the preheating power supply establishes a preheating circuit to conduct preheating current through a section **1726** of the electrode wire **114**. To enable connection between the preheating power supply **1708** and the contact tips **306**, **314**, the preheating power supply **1708** includes terminals **1728**, **1730**. The preheating current flows from the welding power supply **1710** to the second contact tip **314** (e.g., via the torch neck **1002**), the section **1726** of the electrode wire **114**, the first contact tip **306**, and returns to the preheating power supply **1708** via a cable **1732** connecting the terminal **1720** of the welding power supply **1710** to the terminal **1730** of the preheating power supply **1708**.

Because the preheating current path is superimposed with the welding current path over the connection between the first contact tip **306** and the power supplies **1708**, **1710**, the cable **1732** may enable a more cost-effective single connection between the first contact tip **306** and the power supplies **1708**, **1710** (e.g., a single cable) than providing separate connections for the welding current to the first contact tip **306** and for the preheating current to the first contact tip **306**. In other examples, the terminal **1730** of the preheating power supply **1708** is connected to the first contact tip **306** via a separate path than the path between the first contact tip **306** and the welding power supply **1710**. For example, the welding current may be conducted via the liquid cooling assemblies **208** and **212** while the preheating current is conducted via the liquid cooling assemblies **210** and **214** (or vice versa).

In some examples, the welding torch may include a push-pull wire feed system by including a feed motor located at or near the weld torch to pull the electrode wire **114**. In some examples, the inclusion of the pulling feed motor enables the portion of the electrode wire **114** that is preheated to a different location along the wire feed path than in the examples of FIGS. **2**, **3**, and **10**. For example, the second contact tip **314** may be moved into the neck **1002** (e.g., prior to the bend in the torch neck **1002** in the feed direction of the electrode wire **114**) and/or in the torch body

(e.g., the mounting assembly **204** of FIG. **2**) and/or multiple contact tips may be positioned at locations along the length of the electrode wire **114** to provide a preheating circuit that is separate from the welding circuit (e.g., does not share a same contact tip with the welding circuit) and/or provides an additional preheating circuit (e.g., a first preheating current applied to a first portion of the electrode wire **114** and a second preheat current applied to a second portion of the preheating wire). In some examples, the idler roller of a push-pull wire feed system may function as a contact tip to conduct preheating current. By moving all or a portion of the preheating circuit to the wire source side of the bend in the torch neck **1002** (e.g., the side of the bend closer to the wire spool in the electrode feed path), the size of the welding assembly may be reduced, the preheat length may be increased, and/or the preheating current may be reduced. Reduction in the size of the welding assembly and reduction in the preheating current enables torch dimensions that are closer to those of conventional, non-resistive preheating torches, further improving the ease of replacement of conventional torches with torches providing resistive preheating.

FIG. **18** is a block diagram of an example implementation of the power supplies **1708**, **1710** of FIG. **17**. The example power supply **1708**, **1710** powers, controls, and supplies consumables to a welding application. In some examples, the power supply **1708**, **1710** directly supplies input power to the welding tool **108**. In the illustrated example, the power supply **1708**, **1710** is configured to supply power to welding operations and/or preheating operations. The example power supply **1708**, **1710** also provides power to a wire feeder to supply the electrode wire **114** to the welding tool **108** for various welding applications (e.g., GMAW welding, flux core arc welding (FCAW)).

The power supply **1708**, **1710** receives primary power **1808** (e.g., from the AC power grid, an engine/generator set, a battery, or other energy generating or storage devices, or a combination thereof), conditions the primary power, and provides an output power to one or more welding devices and/or preheating devices in accordance with demands of the system. The primary power **1808** may be supplied from an offsite location (e.g., the primary power may originate from the power grid). The power supply **1708**, **1710** includes a power converter **1810**, which may include transformers, rectifiers, switches, and so forth, capable of converting the AC input power to AC and/or DC output power as dictated by the demands of the system (e.g., particular welding processes and regimes). The power converter **1810** converts input power (e.g., the primary power **1808**) to welding-type power based on a weld voltage setpoint and outputs the welding-type power via a weld circuit.

In some examples, the power converter **1810** is configured to convert the primary power **1808** to both welding-type power and auxiliary power outputs. However, in other examples, the power converter **1810** is adapted to convert primary power only to a weld power output, and a separate auxiliary converter is provided to convert primary power to auxiliary power. In some other examples, the power supply **1708**, **1710** receives a converted auxiliary power output directly from a wall outlet. Any suitable power conversion system or mechanism may be employed by the power supply **1708**, **1710** to generate and supply both weld and auxiliary power.

The power supply **1708**, **1710** includes a controller **1812** to control the operation of the power supply **1708**, **1710**. The power supply **1708**, **1710** also includes a user interface **1814**. The controller **1812** receives input from the user

interface **1814**, through which a user may choose a process and/or input desired parameters (e.g., voltages, currents, particular pulsed or non-pulsed welding regimes, and so forth). The user interface **1814** may receive inputs using any input device, such as via a keypad, keyboard, buttons, touch screen, voice activation system, wireless device, etc. Furthermore, the controller **1812** controls operating parameters based on input by the user as well as based on other current operating parameters. Specifically, the user interface **1814** may include a display **1816** for presenting, showing, or indicating, information to an operator. The controller **1812** may also include interface circuitry for communicating data to other devices in the system, such as the wire feeder. For example, in some situations, the power supply **1708**, **1710** wirelessly communicates with other welding devices within the welding system. Further, in some situations, the power supply **1708**, **1710** communicates with other welding devices using a wired connection, such as by using a network interface controller (NIC) to communicate data via a network (e.g., ETHERNET, 10baseT, 10base100, etc.). In the example of FIG. **18**, the controller **1812** communicates with the wire feeder via the weld circuit via a communications transceiver **1818**.

The controller **1812** includes at least one controller or processor **1820** that controls the operations of the welding power supply **1802**. The controller **1812** receives and processes multiple inputs associated with the performance and demands of the system. The processor **1820** may include one or more microprocessors, such as one or more "general-purpose" microprocessors, one or more special-purpose microprocessors and/or ASICs, and/or any other type of processing device. For example, the processor **1820** may include one or more digital signal processors (DSPs).

The example controller **1812** includes one or more storage device(s) **1823** and one or more memory device(s) **1824**. The storage device(s) **1823** (e.g., nonvolatile storage) may include ROM, flash memory, a hard drive, and/or any other suitable optical, magnetic, and/or solid-state storage medium, and/or a combination thereof. The storage device **1823** stores data (e.g., data corresponding to a welding application), instructions (e.g., software or firmware to perform welding processes), and/or any other appropriate data. Examples of stored data for a welding application include an attitude (e.g., orientation) of a welding torch, a distance between the contact tip and a workpiece, a voltage, a current, welding device settings, and so forth.

The memory device **1824** may include a volatile memory, such as random access memory (RAM), and/or a nonvolatile memory, such as read-only memory (ROM). The memory device **1824** and/or the storage device(s) **1823** may store a variety of information and may be used for various purposes. For example, the memory device **1824** and/or the storage device(s) **1823** may store processor executable instructions **1825** (e.g., firmware or software) for the processor **1820** to execute. In addition, one or more control regimes for various welding processes, along with associated settings and parameters, may be stored in the storage device **1823** and/or memory device **1824**, along with code configured to provide a specific output (e.g., initiate wire feed, enable gas flow, capture welding current data, detect short circuit parameters, determine amount of spatter) during operation.

In some examples, the welding power flows from the power converter **1810** through a weld cable **1826**. The example weld cable **1826** is attachable and detachable from weld studs at each of the power supply **1708**, **1710** (e.g., to enable ease of replacement of the weld cable **1826** in case of wear or damage). Furthermore, in some examples, welding

data is provided with the weld cable **1826** such that welding power and weld data are provided and transmitted together over the weld cable **1826**. The communications transceiver **1818** is communicatively coupled to the weld cable **1826** to communicate (e.g., send/receive) data over the weld cable **1826**. The communications transceiver **1818** may be implemented based on various types of power line communications methods and techniques. For example, the communications transceiver **1818** may utilize IEEE standard P1901.2 to provide data communications over the weld cable **1826**. In this manner, the weld cable **1826** may be utilized to provide welding power from the power supply **1708**, **1710** to the wire feeder and the welding tool **108**. Additionally or alternatively, the weld cable **1826** may be used to transmit and/or receive data communications to/from the wire feeder and the welding tool **108**. The communications transceiver **1818** is communicatively coupled to the weld cable **1826**, for example, via cable data couplers **1827**, to characterize the weld cable **1826**, as described in more detail below. The cable data coupler **1827** may be, for example, a voltage or current sensor.

In some examples, the power supply **1708**, **1710** includes or is implemented in a wire feeder.

The example communications transceiver **1818** includes a receiver circuit **1821** and a transmitter circuit **1822**. Generally, the receiver circuit **1821** receives data transmitted by the wire feeder via the weld cable **1826** and the transmitter circuit **1822** transmits data to the wire feeder via the weld cable **1826**. As described in more detail below, the communications transceiver **1818** enables remote configuration of the power supply **1708**, **1710** from the location of the wire feeder and/or compensation of weld voltages by the power supply **1708**, **1710** using weld voltage feedback information transmitted by the wire feeder **104**. In some examples, the receiver circuit **1821** receives communication(s) via the weld circuit while weld current is flowing through the weld circuit (e.g., during a welding-type operation) and/or after the weld current has stopped flowing through the weld circuit (e.g., after a welding-type operation). Examples of such communications include weld voltage feedback information measured at a device that is remote from the power supply **1708**, **1710** (e.g., the wire feeder) while the weld current is flowing through the weld circuit.

Example implementations of the communications transceiver **1818** are described in U.S. Pat. No. 9,012,807. The entirety of U.S. Pat. No. 9,012,807 is incorporated herein by reference. However, other implementations of the communications transceiver **1818** may be used.

The example wire feeder **104** also includes a communications transceiver **1819**, which may be similar or identical in construction and/or function as the communications transceiver **1818**.

In some examples, a gas supply **1828** provides shielding gases, such as argon, helium, carbon dioxide, and so forth, depending upon the welding application. The shielding gas flows to a valve **1830**, which controls the flow of gas, and if desired, may be selected to allow for modulating or regulating the amount of gas supplied to a welding application. The valve **1830** may be opened, closed, or otherwise operated by the controller **1812** to enable, inhibit, or control gas flow (e.g., shielding gas) through the valve **1830**. Shielding gas exits the valve **1830** and flows through a cable **1832** (which in some implementations may be packaged with the welding power output) to the wire feeder which provides the shielding gas to the welding application. In some examples, the power supply **1708**, **1710** does not include the gas supply **1828**, the valve **1830**, and/or the cable **1832**.

## 21

FIG. 19 illustrates another example liquid-cooled welding torch 1900. Like the torch 200 of FIGS. 2-14B, the example liquid-cooled welding torch 1900 resistively preheats an electrode wire 114 via multiple contact points (e.g., contact tips) in the torch 1900.

The torch 1900 of FIG. 19 includes a welding assembly 1902, a mounting assembly 1904, a weld cable 1906, liquid cooling assemblies 1908, 1910, 1912, 1914, and a power and liquid transfer assembly 1916. The example liquid-cooled welding torch 1900 may be used to replace conventional robotic welding torches with resistive preheating-enabled welding torches having a same tool center point (TCP).

The welding assembly 1902 receives weld current and preheating current, conducts the weld current to the electrode wire 114, and conducts the preheating current through a portion of the electrode wire 114. The example welding assembly 1902 is liquid-cooled by liquid provided via the liquid cooling assemblies 1908-214. The example welding assembly 1902 of FIG. 19 receives the weld current via one or more of the weld cable 1906, the liquid cooling assemblies 1908 and 1912, and/or the liquid cooling assemblies 1910 and 1914. Because the workpiece provides the return path for the weld current to the power supply, no return path is provided via the weld cable 1906 or the liquid cooling assemblies 1908. The weld cable 1906 is a air-cooled (or gas-cooled) cable. However, the weld cable 1906 may also be liquid-cooled.

The example welding assembly 1902 receives the preheating current via the weld cable 1906, the liquid cooling assemblies 1908 and 1912, and/or the liquid cooling assemblies 1910 and 1914. In the example of FIG. 19, the weld current is conducted via a different one of the weld cable 1906, the liquid cooling assemblies 1908 and 1912, or the liquid cooling assemblies 1910 and 1914 than the preheating current that has the same polarity (i.e., current flow direction). The welding assembly 1902 conducts the preheating current through a section of the electrode wire 114 to heat the electrode wire via resistive heating (e.g.,  $I^2R$  heating). The preheat current then returns to a preheating power supply via a different one of weld cable 1906, the liquid cooling assemblies 1908 and 1912, or the liquid cooling assemblies 1910 and 1914 to complete a preheating circuit.

In the example of FIG. 19, the weld current path, the preheating current supply path, and the preheating current return path may all be different ones of the weld cable 1906, the liquid cooling assemblies 1908 and 1912, and the liquid cooling assemblies 1910 and 1914. In some examples, the weld current path may be superimposed with the preheating current supply path or the preheating current return path to reduce the net current in the conductor. For example, if the weld current is 300 A and the preheating current is 100 A, the weld current and the preheating current may be superimposed to result in a net current of 1900 A.

As described in more detail below, the welding assembly 1902 and the liquid cooling assemblies 1912, 1914 may be separated from the remainder of the liquid-cooled welding torch 1900 via the power and liquid transfer assembly 1916, and may be simultaneously separated from the mounting assembly 1904.

FIG. 20 is an exploded view of the example welding assembly 1902 of the welding torch 1900 of FIG. 19. The welding assembly 1902 includes a front portion 2002 and a rear portion 2004. FIG. 21 is a cross-sectional plan view of the example welding assembly 1902 of FIG. 19 in which the front portion 2002 is coupled to the rear portion 2004. As described in more detail below, the front portion 2002 is

## 22

detachable from the rear portion to enable access to a rear contact tip 2006 (e.g., a preheating contact tip).

The front portion 2002 includes a nozzle 2008, a nozzle insulator 2010, a front contact tip 2012, a diffuser 2014, a wire guide 2016, a cooling body 2018, a hand nut 2020, and a hand nut insulator 2022. The rear portion 2004 includes a valve assembly 2024, a valve assembly insulator 2026, and a valve assembly housing 2028.

The example hand nut 2020 secures the cooling body 2018, and the components 2008-2016 connected to the cooling body 2018, to the rear portion 2004. In the example of FIG. 20, the hand nut 2020 has internal screw threads to be threaded onto external screw threads 2030 of the valve assembly 2024. A tapered edge 2032 of the hand nut 2020 mates with a shoulder of the cooling body 2018 to force the cooling body 2018 toward the valve assembly 2024. The hand nut insulator 2022 electrically insulates the hand nut to reduce or prevent an operator contacting weld voltage and/or preheating voltage via the hand nut 2020.

The example valve assembly 2024 includes fluid valves 2034a, 2034b positioned within fluid channels 2036a, 2036b, respectively. The fluid channels 2036a, 2036b are in fluid communication with the liquid cooling assemblies 1912, 1914 to circulate fluid through the welding assembly 1902. The example valves 2034a, 2034b are Shrader valves that cut off fluid flow when the valves are not actuated. To actuate the valves, the example cooling body 2018 includes valve actuators 2038a, 2038b, which are located within channels 2040a, 2040b of the cooling body 2018. The valve actuators 2038a, 2038b actuate the valves 2034a, 2034b when the front portion 2002 (including the cooling body 2018) is secured to the rear portion 2004.

When the valves are actuated, the cooling body 2018 is in fluid communication with the liquid cooling assemblies 1912, 1914. The example cooling body 2018 includes one or more internal channels to direct fluid from one of the valve actuators 2038a, 2038b to a second one of the valve actuators 2038a, 2038b. In other words, one of the valve actuators 2038a, 2038b is an inlet to the channel(s) 2102 in the cooling body 2018 from one of the liquid cooling assemblies 1912, 1914 and the other of the valve actuators 2038a, 2038b is an outlet from the channel(s) 2102 to the other of the liquid cooling assemblies 1912, 1914. The example channels 2102 run circumferentially within the cooling body 2018 between the valve actuators 2038a, 2038b to transfer heat from the nozzle 2008 to the fluid within the channels 2102.

The example nozzle 2008 includes internal threads 2104 that couple the nozzle 2008 to a threaded ring 2042 coupled to an exterior of the cooling body 2018. When coupled, heat from the nozzle 2008 is transferred to the cooling body 2018 for further dissipation to the cooling liquid.

When secured (e.g., threaded together), the cooling body 2018 and the valve assembly 2024 are in electrical contact to transfer welding current and/or preheating current with the front contact tip 2012 via the diffuser 2014. The welding current and/or preheating current are conducted via one or more of the liquid cooling assemblies 1912, 1914. For example, one or both of the liquid cooling assemblies 1912, 1914 include a conductor layer electrically coupled to the front contact tip 2012 via the diffuser 2014, the cooling body 2018, and the valve assembly 2024. Preheating current is conducted to the rear contact tip 2006 from the weld cable 1906 via a torch neck 2044, which includes one or more layers of conductors, a wire liner to transfer the electrode wire 114, and an annulus to provide gas flow to the weld assembly 1902 for output to the weld via the diffuser 2014.

As illustrated in FIG. 20, the liquid cooling assemblies 1912, 1914 may be secured to the torch neck 2044 via bracket 2046 or other attachment technique.

The example wire guide 2016 may be similar or identical to the wire guide 308 of FIG. 3. The wire guide 2016 is held within a bore in the diffuser 2014. The nozzle insulator 2010 electrically and thermally insulates the nozzle 2008 from the front contact tip 2012 and the diffuser 2014. The nozzle 2008 is electrically insulated from the cooling body 2018 by one or more additional electrical insulator(s) 2110 located on the cooling body 2018. The example electrical insulator(s) 2110 may be thermally conductive to conduct heat from the nozzle 2008 to the cooling body 2018. Polyether ether ketone (PEEK) and/or other thermoplastics may be used to implement the example electrical insulator(s) 2110.

The example cooling body 2018 may include any number of electrical insulators and/or fluid seals to enable conduction of current to the diffuser 2014, reduce or prevent conduction of current to unneeded or undesired components (e.g., exterior components), and/or to reduce or prevent fluid leaks from the cooling body 2018. In the example of FIG. 21, the cooling body 2018 includes an inner body 2106 defining the channel(s) 2102 and a cover 2108 configured to enclose the channels 2102.

The example rear contact tip 2006 may be similar or identical to the second contact tip 314 of FIGS. 3 and 13A-13C.

FIG. 22 is a cross-sectional plan view of the example power and liquid transfer assembly 1916 of FIG. 19. FIG. 23 is a partially exploded elevation view of the example power and liquid transfer assembly 1916 of FIG. 19.

The example power and liquid transfer assembly 1916 is similar to the power and liquid transfer assembly 216 of FIGS. 2, 3, and 8, in that the power and liquid transfer assembly 1916 includes multiple liquid transfer valves, corresponding valve actuators, and one or more electrical power transfer sockets, and in that the power and liquid transfer assembly 1916 enables disconnection of the liquid cooling assemblies 1912, 1914 from the power and liquid transfer assembly 1916 and cuts off fluid transfer in response to disconnection.

The example power and liquid transfer assembly 1916 is coupled to the liquid cooling assemblies 1908, 1910, which provide supply and return lines for the cooling liquid to a liquid cooler. The example liquid cooling assembly 1908 includes an internal conductor 2202 to conduct welding current (e.g., to the welding power supply 1710 of FIG. 17) and/or preheating current (e.g., to the preheating power supply 1708). The conductor 2202 is in electrical contact with a socket 2204, which permits fluid to flow from an exterior of the socket 2204 to an interior of the socket 2204, into which a fluid fitting 2206 of the power and liquid transfer assembly 1916 is fitted to make a fluid connection with the liquid cooling assembly 1908 and electrical contact with the socket 2204. In the example of FIG. 22, the liquid cooling assembly 1910 only includes tubing to transfer liquid, and does not include an internal conductor or a socket. In other examples, the liquid cooling assembly 1910 also includes a conductor and has a construction similar or identical to the liquid cooling assembly 1908.

Each of the example liquid cooling channels of the power and liquid transfer assembly 1916 includes a liquid shutoff valve 2208a, 2208b within a fluid socket 2209a, 2209b. The channel coupled to the liquid cooling assembly 1908 (e.g., carrying current and liquid) includes a power transfer socket 2210. The channel coupled to the liquid cooling assembly 1910 (e.g., carrying only liquid) may include a non-conduc-

tive socket 2212 having similar, the same, or different dimensions as the power transfer socket 2210.

The power cable socket 2210 receives a power connector pin 2214 of the liquid cooling assembly 1912 to transfer cooling liquid and welding current and/or preheating current to the liquid cooling assembly 1912. The nonconductive socket 2212 likewise receives a power connector pin or other pin corresponding to the dimensions of the socket 2212. The power transfer socket 2210 enables insertion of the power connector pin 2214, and transfers current to and/or from an inserted power connector pin 2214. An example power transfer socket that may be used to implement the power transfer socket 2210 is a PowerBud® power contact, sold by Methode Electronics, Inc., which provides multiple contact points between the power transfer socket and an inserted power connector pin 2214.

The liquid shutoff valves 2208a, 2208b selectively permit flow of liquid from liquid cooling assemblies 1908, 1910 to the sockets 2210, 2212 and to a connected liquid cooling assembly 1912, 1914. The example liquid shutoff valves 2208a, 2208b are Schrader valves. However, other types of valves may be used to implement the liquid shutoff valves 2208a, 2208b. When a power connector pin 2214, 2216 is inserted (e.g., fully inserted) into the sockets 2210, 2212, the power connector pin 2214, 2216 displaces (e.g., unseats) a stem 2218 from a core 2220 of the valve 2208a, 2208b, which permits liquid to flow to and/or from the hose liquid cooling assemblies 1908-1914. When the power connector pins 2214, 2216 are removed or partially removed, the stems 2218 are forced back into the cores 2220 and stop flow of liquid.

A hose 2222 of the liquid cooling assemblies 1908 is coupled to the fluid socket 2209a via a ferrule 2224. The example the example sockets 2209a, 2209b and/or the hoses 2222 include hose barbs to secure the hoses 2222. However, other methods of securing the hose to the sockets 2209a, 2209b may be used, such as clamps, compression fittings, or any other hose fittings.

The example power and liquid transfer assembly 1916 may operate as described above with reference to the power and liquid transfer assembly 216 of FIG. 8.

As illustrated in FIG. 23, the liquid cooling assemblies 1912, 1914 may be secured to the power and liquid transfer assembly 1916 at least partly using a cover 2302 configured to prevent disconnection of the power connector pins 2214, 2216 from the power and liquid transfer assembly 1916. For example, the cover 2302 may include a shoulder and/or other features configured to prevent movement of the power connector pins 2214, 2216 away from the power and liquid transfer assembly 1916. The cover 2302 may be secured by a fastener, such as a bolt, and/or any other type of fastener or fastening technique.

While the present method and/or system has been described with reference to certain implementations, it will be understood by those skilled in the art that various changes may be made and equivalents may be substituted without departing from the scope of the present method and/or system. In addition, many modifications may be made to adapt a particular situation or material to the teachings of the present disclosure without departing from its scope. For example, systems, blocks, and/or other components of disclosed examples may be combined, divided, re-arranged, and/or otherwise modified. Therefore, the present method and/or system are not limited to the particular implementations disclosed. Instead, the present method and/or system

will include all implementations falling within the scope of the appended claims, both literally and under the doctrine of equivalents.

All documents cited herein, including journal articles or abstracts, published or corresponding U.S. or foreign patent applications, issued or foreign patents, or any other documents are each entirely incorporated by reference herein, including all data, tables, figures, and text presented in the cited documents.

What is claimed is:

1. A welding torch, comprising:
  - a first contact tip configured to conduct welding current to a consumable electrode;
  - a second contact tip configured to conduct preheating current to the consumable electrode;
  - a plurality of liquid cooling assemblies configured to conduct the preheating current and to conduct the welding current to the consumable electrode;
  - a first socket having a first fluid valve and configured to permit fluid transfer with a first one of the liquid cooling assemblies when the first fluid valve is open; and
  - a second socket electrically coupled to the first socket, wherein the first one of the liquid cooling assemblies comprises a first power connector pin configured to be inserted into the first socket and the second socket to transfer the fluid and to be electrically coupled to the second socket, the first fluid valve configured to open when the first power connector pin is inserted into the first socket and to close when the first power connector pin is removed from the first socket.
2. The welding torch as defined in claim 1, wherein the plurality of liquid cooling assemblies comprises:
  - a first liquid cooling assembly configured to conduct the welding current; and
  - a second liquid cooling assembly configured to conduct the preheating current.
3. The welding torch as defined in claim 2, wherein the first liquid cooling assembly is configured to conduct the preheating current.
4. The welding torch as defined in claim 1, further comprising a power connector pin retention mechanism configured to physically resist removal of the first power connector pin from the first socket and the second socket when engaged.
5. The welding torch as defined in claim 4, further comprising a retaining ring configured to attach the power connector pin retention mechanism to the first power connector pin.
6. The welding torch as defined in claim 1, further comprising:
  - a third socket having a second fluid valve and configured to permit fluid transfer with a second one of the liquid cooling assemblies when the second fluid valve is open.
7. The welding torch as defined in claim 1, wherein the second socket comprises a plurality of contacts arranged circumferentially around an interior surface of the second

socket, the plurality of contacts configured to contact the first power connector pin to transfer at least one of the welding current or the preheating current.

8. The welding torch as defined in claim 1, wherein the plurality of liquid cooling assemblies comprise:

- a first liquid cooling assembly configured to conduct the welding current and to provide a return path for the preheating current; and
- a second liquid cooling assembly.

9. The welding torch as defined in claim 1, further comprising a welding assembly comprising the first contact tip and the second contact tip, the welding assembly fluidly coupled to the plurality of liquid cooling assemblies.

10. The welding torch as defined in claim 1, wherein a first one of the liquid cooling assemblies comprises:

- an inner conductive layer configured to conduct at least one of the welding current or the preheating current; and
- an insulative layer exterior to the inner conductive layer.

11. The welding torch as defined in claim 10, wherein the first one of the liquid cooling assemblies further comprises an outer protective layer exterior to the insulative layer.

12. The welding torch as defined in claim 1, further comprising a power and liquid transfer assembly configured to be fluidly and electrically coupled to the plurality of liquid cooling assemblies and, when fluidly and electrically coupled to the plurality of liquid cooling assemblies, to transfer current and coolant with the plurality of liquid cooling assemblies.

13. The welding torch as defined in claim 12, further comprising a securing mechanism configured to secure the power and liquid transfer assembly to the plurality of liquid cooling assemblies.

14. The welding torch as defined in claim 12, further comprising a torch neck configured to detachably attach a welding assembly to a torch body, the welding assembly comprising the first contact tip and the second contact tip, the plurality of liquid cooling assemblies being mechanically coupled to the torch neck.

15. The welding torch as defined in claim 14, wherein the power and liquid transfer assembly is mechanically coupled to the torch body.

16. A welding torch, comprising:

- a first contact tip configured to conduct welding current to a consumable electrode;
- a second contact tip configured to conduct preheating current to the consumable electrode;
- a plurality of liquid cooling assemblies configured to conduct the preheating current and to conduct the welding current to the consumable electrode; and
- a weld cable configured to conduct the preheating current, welding gas, and the consumable electrode to the welding torch.

17. The welding torch as defined in claim 16, wherein the weld cable is an air-cooled or gas-cooled cable.