

US011261065B2

(12) **United States Patent**
Shin

(10) **Patent No.:** **US 11,261,065 B2**
(45) **Date of Patent:** **Mar. 1, 2022**

(54) **LIFTING APPARATUS FOR
HIGHLY-MOUNTED DEVICE**

(58) **Field of Classification Search**

CPC H04N 5/2253; F21V 21/38; A62C 99/009;
B66D 2700/025; B66D 1/12; B66D 1/34;

(Continued)

(71) Applicant: **REEL TECH CO., LTD.**, Suncheon-si
(KR)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(72) Inventor: **Jeong Hoon Shin**, Suncheon-si (KR)

6,520,484 B1 2/2003 Shimizu et al.
10,502,362 B2 * 12/2019 Shin H04N 5/2253

(Continued)

(73) Assignee: **Reel Tech Co., Ltd.**, Suncheon-si (KR)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 54 days.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **16/759,047**

CN 1345691 A 4/2002
CN 101421176 A 4/2009

(Continued)

(22) PCT Filed: **Oct. 26, 2018**

(86) PCT No.: **PCT/KR2018/012797**

OTHER PUBLICATIONS

§ 371 (c)(1),

(2) Date: **Apr. 24, 2020**

International Search Report of corresponding PCT Application No.
PCT/KR2018/012797—4 pages (dated Feb. 19, 2019).

(87) PCT Pub. No.: **WO2019/083314**

Primary Examiner — Michael E Gallion

PCT Pub. Date: **May 2, 2019**

(74) *Attorney, Agent, or Firm* — Knobbe Martens Olson
& Bear LLP

(65) **Prior Publication Data**

US 2020/0317478 A1 Oct. 8, 2020

(57) **ABSTRACT**

(30) **Foreign Application Priority Data**

Oct. 27, 2017 (KR) 10-2017-0141517

Aug. 3, 2018 (KR) 10-2018-0090971

A lifting apparatus for a highly-mounted device includes a main body installed at a predetermined height so that a drum for winding a wire rope and a first driving motor for giving a rotating force to the drum are installed thereto; a lifting body suspended from the wire rope and having a device coupling portion provided at a lower end thereof; an accommodation structure located at a lower portion of the main body and having an open lower portion so as to be coupled with the lifting body; a stopper installed at the accommodation structure and caught by a suspending protrusion provided to the lifting body to give an anti-falling function for the lifting body; and an upper contact point and a lower contact point respectively installed at the main body and the lifting body to make contact with each other when the lifting body is moved up.

(51) **Int. Cl.**

B66D 1/48 (2006.01)

B66D 1/36 (2006.01)

(Continued)

(52) **U.S. Cl.**


CPC **B66D 1/48** (2013.01); **B66D 1/12**

(2013.01); **B66D 1/34** (2013.01); **B66D 1/36**

(2013.01);

(Continued)

4 Claims, 6 Drawing Sheets



- (51) **Int. Cl.** 2010/0051767 A1* 3/2010 Erel B66C 23/02
B66D 1/34 (2006.01) 248/205.1
B66D 1/56 (2006.01) 2017/0009937 A1* 1/2017 Shin H04N 5/2253
B66D 1/60 (2006.01)
B66D 1/12 (2006.01)
B66D 1/54 (2006.01)
A62C 99/00 (2010.01)
F21V 21/38 (2006.01)
H04N 5/225 (2006.01)

FOREIGN PATENT DOCUMENTS

- (52) **U.S. Cl.**
 CPC *B66D 1/54* (2013.01); *B66D 1/56*
 (2013.01); *B66D 1/60* (2013.01); *A62C 99/009*
 (2013.01); *B66D 2700/025* (2013.01); *F21V*
21/38 (2013.01); *H04N 5/2253* (2013.01)

- (58) **Field of Classification Search**
 CPC ... B66D 1/48; B66D 1/54; B66D 1/56; B66D
 1/60
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- 2004/0012969 A1 1/2004 Sin
 2005/0230670 A1* 10/2005 Kataoka B66D 1/36
 254/335
 2008/0217460 A1 9/2008 Shin

- CN 201439929 U 4/2010
 CN 202322245 U 7/2012
 CN 202449775 U 9/2012
 CN 10674409 A 5/2017
 CN 106744409 A 5/2017
 CN 206156653 U 5/2017
 FR 2683617 A1 5/1993
 JP 05-028816 A 2/1993
 JP 08-129906 A 5/1996
 JP H08-192995 A 7/1996
 JP H09-104592 A 4/1997
 JP H10-59700 A 3/1998
 JP 2000-016766 A 1/2000
 JP 2009-202976 A 9/2009
 JP 2010-100423 A 5/2010
 JP 4746509 B2 8/2011
 JP 4819578 B2 11/2011
 KR 10-0679998 B1 2/2007
 KR 10-0726578 B1 6/2007
 KR 10-0908039 B1 7/2009
 KR 10-2010-0024884 A 3/2010
 KR 10-1056847 B1 8/2011
 KR 10-1184989 B1 10/2012
 KR 10-1589715 B1 1/2016
 WO 2007/133032 A1 11/2007

* cited by examiner

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5





FIG. 6



1

**LIFTING APPARATUS FOR
HIGHLY-MOUNTED DEVICE**

TECHNICAL FIELD

The present application claims priority to Korean Patent Application No. 10-2017-0141517 filed on Oct. 27, 2017 and Korean Patent Application No. 10-2018-0090971 filed on Aug. 3, 2018 in the Republic of Korea, the disclosures of which are incorporated herein by reference.

The present disclosure relates to a lifting apparatus for a highly-mounted device, and more particularly, to a lifting apparatus for a highly-mounted device, which has a structure for moving the highly-mounted device upward or downward by winding or releasing a wire rope around a drum.

BACKGROUND ART

In general, a so-called highly-mounted light is installed at a hotel lobby, a factory ceiling, a gymnasium and a street-light. The highly-mounted light is mainly equipped with a sodium light bulb or a mercury light bulb, and the life of the highly-mounted light is limited to 5000 to 6000 hours and should be changed periodically. In addition, the highly-mounted lights installed in service companies such as hotel lobbies and wedding halls need to replace light bulbs along with periodic cleaning for keeping exterior and exhibition effects.

Since the highly-mounted light is located at a height of 7 to 10 m in the case of a streetlight, an aerial crane or a ladder truck equipped with a basket should be used for cleaning or replacing the light bulb of the highly-mounted light. In addition, in a wedding hall, a hotel lobby, or the like, which has a relatively low height, a ladder is installed to clean or replace the light bulb, but in this case, there is a risk of accidents caused by falling. Moreover, at least three persons should be working in a group to carry out the cleaning or replacing work. Further, since large work facilities such as a crane and a ladder truck are used in the work place for the highly-mounted light, the work time is delayed and the work space is increased. Thus, when repairing or replacing highly-mounted light, a factory line should be stopped or the gymnasium cannot be used for a long time, so the repairing or replacing work should be finished quickly. In particular, when the streetlight is required or replaced, a cargo crane occupies one lane, thereby causing problems such as traffic jams.

As an alternative, a working method using a highly-mounted light, in which the highly-mounted light is lowered to the ground where a worker is located and then raised and fixed to the ceiling again, without working at a high spot where the highly-mounted light is located, and a device for the working method have been consistently developed.

As a device for lowering the highly-mounted light attached to the ceiling to the ground, there are proposed a manual lifting device for a highly-mounted light, in which a wire rope is fixed to the light and the wire rope is wound on a pulley fixed to the ground via the ceiling so that a user lifts the highly-mounted light by manipulating a handle bar connected to the pulley, and an automatic lifting device for a highly-mounted light, which uses a driving motor instead of the handle bar.

In general, the automatic lifting device for a highly-mounted light includes a socket (main body) fixed at a given height on the ceiling, a light fitting (lifting body) inserted into the socket to make a point contact with the socket and

2

having a lower side to which a light bulb is mounted, a wire rope having one end fixed on an upper side of the light fitting and the other end provided on a drum installed at a predetermined location of the socket in a state of being wound by a predetermined length, and a driving motor configured to automatically wind/unwind the wire rope on the drum according to the selection of a user to move the light fitting upward or downward.

The technique related to the configuration of unwinding and winding the wire rope in the automatic lifting device for a highly-mounted light is disclosed in, for example, Korean Patent No. 10-1056847. The lifting device for a highly-mounted light disclosed in Korean Patent No. 10-1056847 includes a sensing plate, which is pushed in the outer direction of a drum as the layer of wire rope wound around the drum increases, and a drive switch pressed by the contact of the sensing plate when the sensing plate is pushed to a set position to stop the operation of the driving unit for rotating the drum, wherein the drum is arranged to be placed in a standing state in the main body.

When the highly-mounted light is completely installed, the lifting body is caught by a stopper located at a lower end thereof to keep its fixed state. However, this structure is vulnerable since the lifting body may be easily shaken by external forces such as wind and vibration in a state where the lifting body is caught by the stopper. If the lifting body is shaken by the wind, the highly-mounted light is also shaken simultaneously, which may degrade the function. Also, if a strong wind is applied, the highly-mounted light may fall.

This problem also appears in a lifting-type CCTV camera system. In other words, the camera is shaken along with the lifting body due to the wind, the shooting may not be performed properly, and the camera may fall due to the strong wind.

DISCLOSURE

Technical Problem

The present disclosure is designed to solve the problems of the related art, and therefore the present disclosure is directed to providing a lifting apparatus for a highly-mounted device, which has a structure for stably fixing the highly-mounted device so that the highly-mounted device is not shaken by an external force such as wind in a state where the highly-mounted device such as a highly-mounted light or CCTV camera is completely installed.

Technical Solution

In one aspect of the present disclosure, there is provided a lifting apparatus for a highly-mounted device, comprising: a main body installed at a predetermined height so that a drum for winding a wire rope and a first driving motor for giving a rotating force to the drum are installed thereto; a lifting body suspended from the wire rope and having a device coupling portion provided at a lower end thereof; an accommodation structure located at a lower portion of the main body and having an open lower portion so as to be coupled with the lifting body; a stopper installed at the accommodation structure and caught by a suspending protrusion provided to the lifting body to give an anti-falling function for the lifting body; an upper contact point and a lower contact point respectively installed at the main body and the lifting body to make contact with each other when the lifting body is moved up and coupled to the main body

3

by winding the wire rope; at least one guide roll disposed at a side portion and an upper portion of the drum to support the wire rope unwound from the drum and guide the unwound wire rope into the accommodation structure; and a fixing instrument configured to apply a force to any one of the upper contact point and the lifting body in a state where the lifting body is moved up and coupled to the main body by winding the wire rope, so that the lifting body comes into close contact with the stopper.

The fixing instrument may include a second driving motor fixed to the main body, and a screw bolt rotated by the second driving motor and coupled to a screw nut to be movable forward and backward in an upper and lower direction or in a left and right direction, and when the screw bolt moves forward, the screw bolt may compress the lifting body, or a portion connected to the lifting body, to push the lifting body downward so that the lifting body comes into close contact with the stopper.

The fixing instrument may be provided in plural, and the plurality of fixing instruments may be arranged at sides of the main body symmetrically based on the center of the main body to operate simultaneously.

When fixing the lifting body, the fixing instrument may instantly operate the second driving motor with a first power that is a high power so that the screw bolt starts moving downward, and then the fixing instrument may move the screw bolt downward with a second power that is a relatively low power to press the lifting body, and when releasing the fixation of the lifting body, the fixing instrument may instantly operate the second driving motor with the first power that is a high power so that the screw bolt starts moving upward, and then the fixing instrument may move the screw bolt upward with the second power that is a relatively low power to restore the screw bolt.

At least one selected from a CCTV camera, a light, a fire detector and a promotional banner may be coupled to the device coupling portion.

Advantageous Effects

According to the present disclosure, when the highly-mounted device is completely installed, the lifting body is in close contact with the stopper by the fixing instrument, which prevents the lifting body from shaking and reduces the risk of performance deterioration or fall of the highly-mounted device.

In addition, since the lifting body is prevented from shaking by the fixing instrument, it is possible to improve the contact reliability between the upper contact point and the lower contact point.

DESCRIPTION OF DRAWINGS

The accompanying drawings illustrate a preferred embodiment of the present disclosure and together with the foregoing disclosure, serve to provide further understanding of the technical features of the present disclosure, and thus, the present disclosure is not construed as being limited to the drawing.

FIG. 1 is a side view showing a lifting apparatus for a highly-mounted device according to a preferred embodiment of the present disclosure.

FIG. 2 is a side view showing a state where a screw bolt is moved backward to be restored in FIG. 1.

FIG. 3 is a side view showing a state where a lifting body is moved down in FIG. 2.

4

FIG. 4 is a side view showing a lifting apparatus for a highly-mounted device according to another embodiment of the present disclosure.

FIG. 5 is a side view showing a state where screw bolt is moved backward to be restored in FIG. 4.

FIG. 6 is a side view showing a state where a lifting body is moved down in FIG. 5.

BEST MODE

FIG. 1 is a side view showing a lifting apparatus for a highly-mounted device according to a preferred embodiment of the present disclosure.

Referring to FIG. 1, the lifting apparatus for a highly-mounted device according to a preferred embodiment of the present disclosure includes a main body 100 installed at a predetermined height so that a drum 101 is installed therein, a coupling unit located at a lower portion of the main body 100 and having a stopper 106 capable of being caught by the lifting body 200, a lifting body 200 suspending from a wire rope 1 wound on the drum 101 and having a device coupling portion 204 formed at a lower end thereof so that a highly-mounted device is mounted thereto, an upper contact point 109 installed at the main body 100, a lower contact point 202 disposed at an upper portion of the lifting body 200 to contact the upper contact point 109 when the lifting body 200 is moved upward and coupled to the main body 100 through the coupling unit, a plurality of guide rolls 103 for supporting and guiding the wire rope 1, and a fixing instrument 120 installed at the main body 100 to closely contact the lifting body 200 with the stopper 106.

The main body 100 is installed at a predetermined height at an upper end of a supporting structure such as the ceiling of a building or a streetlamp. For the installation of the main body 100, a mounting member 111, for example, made of a ring bolt is provided at an upper end of the main body 100. Alternatively, the main body 100 may be connected to a predetermined support bracket (not shown) that may be coupled to a predetermined H beam provided on the ceiling of the building.

In the main body 100, a drum 101 around which the wire rope 1 may be wound and a first driving motor (not shown) coupled to the drum 101 through a predetermined gear assembly to provide a forward and reverse rotating force. A geared motor is preferably adopted as the first driving motor. The technical configuration of transmitting the rotating force of the first driving motor to the drum 101 arranged horizontally using the gear assembly is disclosed in detail in Korean Patent Application No. 10-2013-0070072 filed by the applicant of this application.

The drum 101 is a cylindrical bobbin that is capable of winding and unwinding the wire rope 1. Though it is shown that the drum 101 is disposed to stand upright, it is also possible that the drum 101 is rotatably installed in the main body 100 in a state of laying down so that its hollow is opened substantially vertically with respect to the ground.

In order to mediate the coupling between the main body 100 and the lifting body 200, a coupling unit having an accommodation structure 105 with a hollow is formed to a lower portion of the main body 100.

The coupling unit is located at the lower portion of the main body 100 and serves to mediate the coupling of the lifting body 200 at a correct position of the main body 100 when the lifting body 200 is moved up to a given point by winding the wire rope 1. Specifically, the coupling unit includes an accommodation structure 105 having a predetermined shape and guiding the lifting body 200 to be

5

aligned at the lower portion of the center of the main body **100**, and a stopper **106** selectively caught by a suspending protrusion **201** having a suspending protrusion shape and formed on an upper end of the lifting body **200** to fix the coupling state of the lifting body **200** to the main body **100**.

The receiving structure **105** has a cylindrical shape having an open lower portion and having an inner space through which at least an upper portion of the lifting body **200** may move in and out. The receiving structure **105** may be integrally formed with the main body **100**. Alternatively, the receiving structure **105** may be formed as a separate member from the main body **100** and detachably coupled to the lower portion of the main body **100**.

The stopper **106** is installed to be accessible to selectively protrude from an inner wall of the accommodation structure **105** and fixes the position of the lifting body **200** fitted into the accommodation structure **105**. The stopper **106** may be provided in a pair such that the pair of stoppers **106** are installed to face each other based on the center of the accommodation structure **105**. Alternatively, a plurality of stoppers **106** may be installed at regular intervals in the circumferential direction.

The stopper **106** has a wedge-shaped body with a front lower surface inclined with a slope and is installed to protrude from the inner wall surface of the accommodation structure **105** selectively by, for example, a driving means such as a solenoid.

The lifting body **200** is installed to be suspended from the wire rope **1** and is lifted up and down simultaneously with winding and unwinding the wire rope **1**. A device coupling portion of a predetermined type is provided to the lower portion of the lifting body **200**, and a highly-mounted device is coupled to the device coupling portion. As the highly-mounted device, various devices such as a CCTV camera shown in the figures, a light, a fire detector and a promotional banner may be employed.

The suspending protrusion **201** corresponding to the stopper **106** is formed at an upper end of the outer surface of the lifting body **200**. The stopper **106** is coupled to a groove portion of the suspending protrusion **201** to fix the position of the lifting body **200**.

The wire rope **1** unwound from the drum **101** extends below the main body **100** and is connected to the lifting body **200**. To this end, a plurality of guide rolls **103** are arranged around the drum **101** to guide the wire rope **1** unwound from the drum **101** to the lower portion of the main body **100**.

The fixing instrument **120** is configured to apply the force to any one of the upper contact point **109** and the lifting body **200** in a state where the lifting body **200** is moved up by winding the wire rope **1** and is coupled to the main body **100**, so that the lifting body **200** comes into close contact with the stopper **106**. For this purpose, a metal plate **210** is fixed around the lifting body **200**, and the fixing instrument **120** includes a second driving motor **121** accommodated in a tubular housing **122** and fixed to the main body **100**, and a screw bolt **124** rotated by the second driving motor **121** and coupled to a screw nut **123** to move forward and backward in a vertical direction.

By forward rotation of the second driving motor **121**, the screw bolt **124** moves forward (downward) and compresses the lifting body **200**, or a portion connected to the lifting body **200**, downward at a predetermined point to push the lifting body **200** so as to be in close contact with the stopper **106**. FIG. 1 shows a configuration in which the screw bolt **124** pushes the lifting body **200** downward by compressing the metal plate **210**, which is a portion connected to the lifting body **200**.

6

If the screw bolt **124** moves backward (upward) due to the backward rotation of the second driving motor **121**, the screw bolt **124** is separated from the metal plate **210** and releases the fixation by removing the force applied to the lifting body **200**.

As a modification of the present disclosure, the screw bolt **124** may also be configured to move forward and backward in the horizontal direction to selectively compress the lifting body **200** so that the lifting body **200** comes into close contact with the stopper **106**. As an alternative, the screw bolt **124** may be replaced by a predetermined wedge structure having an inclined surface formed at a front portion thereof, so that, when moving forward, the wedge structure pushes the lifting body **200** to be in close contact with the stopper **106**.

The fixing instrument **120** is fixed to a side of the main body **100**, and it is preferable that a plurality of fixing instruments **120** are arranged at sides of the main body **100** symmetrically with respect to the center of the main body **100** and operated simultaneously to press the lifting body **200** in all directions.

When fixing the lifting body **200**, the fixing instrument **120** instantly operates the second driving motor **121** with a first power that is a high power so that the screw bolt **124** starts moving downward, and then, the fixing instrument **120** moves the screw bolt **124** downward with a second power that is a relatively low power to press the metal plate **210**. Similarly, when releasing the fixation of the lifting body **200**, the fixing instrument **120** instantly operates the second driving motor **121** with a first power that is a high power so that the screw bolt **124** starts moving upward, and then, the fixing instrument **120** moves the screw bolt **124** upward with a second power that is a relatively low power to restore the screw bolt **124**. Here, the first power is preferably set to about twice the second power. If the first power is set to be higher than the second power, the screw bolt **123** instantly rotates strongly and overcomes the friction with the screw nut **123** to move upward without being stuck to the screw nut **123**.

The screw bolt **124** is connected to a rotary shaft of the second driving motor **121** and disposed perpendicular to the ground. In order to omit the complicated gear assembly for transmitting a rotating force between the second driving motor **121** and the screw bolt **124**, it is preferable that the second driving motor **121** and the screw bolt **124** are moved upward and downward integrally when the fixing instrument **120** is operated. For this purpose, the screw nut **123** is fixed to a lower portion of the tubular housing **122** installed to the side of the main body **100**, the second driving motor **121** and the screw bolt **124** are disposed inside the tubular housing **122**, and the screw bolt **124** is fitted into the screw nut **123** to move integrally. In order to prevent the second driving motor **121** from running idle inside the tubular housing **122**, the second driving motor **121** preferably has a non-circular circumferential surface. FIG. 2 shows an example where the second driving motor **121** and the screw bolt **124** are moved up integrally.

FIGS. 4 to 6 show an embodiment in which the fixing instrument **120** is installed inside the main body **100** to apply a force to the upper contact point **109** so that the lifting body **200** comes into close contact with the stopper **106**. In this embodiment, since the screw bolt **124** presses the upper contact point **109**, the fixing instrument **120** pushes the lifting body **200** downward together with the lower contact point **202** in contact with the lower portion of the upper contact point **109** so as to be in close contact with the stopper **106**. At this time, the upper contact point **109** preferably is

located at a lower end of the main body **100** and is installed to be elastically movable upward and downward as much as at least a gap **G** by a predetermined elastic body. That is, the upper contact point **109** is installed to apply an elastic force in the restoring direction when being pressed by the screw bolt **124** and moved downward.

The fixing instrument **120** includes a second driving motor **121** accommodated in the tubular housing **122** and fixed to the main body **100**, and a screw bolt **124** rotated by the second driving motor **121** and coupled with the screw nut **123** to move upward and downward in the vertical direction. As an alternative, the screw bolt **124** may also be configured to move forward and backward in the left and right direction to selectively compress the upper contact point **109** so that the lifting body **200** comes into close contact with the stopper **106**. As another alternative, the screw bolt **124** may also be replaced by a predetermined wedge structure having an inclined surface formed at a front portion thereof, so that, when moving forward, the wedge structure pushes the upper contact point **109** to bring the lifting body **200** into close contact with the stopper **106**.

In the lifting apparatus for a highly-mounted device configured as above according to a preferred embodiment of the present disclosure, when the lifting body **200** ascends and is coupled with the main body **100** by winding the wire rope **1**, the upper contact point **109** and the lower contact point **202** make contact with each other so that power is supplied to the highly-mounted device **10** mounted to the lifting body **200**.

The operation of winding the wire rope **1** is performed by the drum **101** that rotates in a forward direction by the first driving motor installed in the main body **100**. At this time, the wire rope **1** is pulled up while passing through the hollow of the accommodation structure **105**, and then changes its moving direction by the guide roll **103** and is wound around the drum **101**.

When the lifting body **200** ascends and reaches a predetermined point by winding the wire rope **1**, the arrival state is detected by a predetermined limit switch (not shown), and the rotation of the drum **101** is stopped according to the detection signal. In addition, the suspending protrusion **201** provided at the upper end of the outer peripheral surface of the lifting body **200** is caught by the stopper **106** protruding from the inner wall of the receiving structure **105** of the coupling unit **104**, thereby fixing the lifting body **200** to the main body **100**.

When the lifting body **200** is moved up and reaches a given point by winding the wire rope **1**, as shown in FIG. 2 or 5, the load of the lifting body **200** is applied to the wire rope **1** so that the wire rope **1** keeps a tight state and the stopper **106** moving forward is inserted into the suspending protrusion **201** with the gap **G**.

Subsequently, as shown in FIG. 1 or 4, the fixing instrument **120** moves the screw bolt **124** downward to directly or indirectly press the lifting body **200** downward so that the suspending protrusion **201** comes into close contact with the stopper **106**. Thus, it is possible to prevent the lifting body **200** from being shaken and reduce the risk of performance deterioration or fall of the highly-mounted device **10**.

When the lifting body **200** is inserted into and fixed to the accommodation structure **105**, the upper contact point **109** and the lower contact point **202** are in contact with each other and electrically connected. Here, the contact between the upper contact point **109** and the lower contact point **202** is made in the hollow of the accommodation structure **105**.

When cleaning or replacing the highly-mounted device **30**, first, as shown in FIG. 2 or 5, the screw bolt **124** of the

fixing instrument **120** is moved upward to be restored, thereby releasing the force pressing the lifting body **200**.

Next, the stopper **106** is moved backward to release the stopping state of the stopper **106** to the lifting body **200**, and then the drum **101** is rotated in the rearward direction to release the wire rope **1** through the hollow of the accommodation structure **105** so that the lifting body **200** is lowered to the ground as shown in FIG. 3. In order to release the stopping state of the stopper **106**, the drum **101** may be driven to lift the lifting body **200** upward a little by rotating in a forward direction as much as a predetermined interval. By this process, the stopper **106** deviates from the suspending protrusion **201** of the lifting body **200** and returns to its original position, and accordingly the lifting body **200** may come into a state capable of freely descending.

As described above, in the lifting apparatus for a highly-mounted device according to the present disclosure, when the highly-mounted device **10** is completely moved upward, the lifting body **200** is substantially pushed downward by the screw bolt **124** of the fixing instrument **120** so that the suspending protrusion **201** at the upper end of the lifting body **200** is in close contact with the stopper **106**, thereby preventing the lifting body **200** from being shaken and reducing the risk of performance deterioration or fall of the highly-mounted device.

INDUSTRIAL APPLICABILITY

If the present disclosure is applied, it is possible to prevent the lifting body from shaking, thereby reducing the risk of performance deterioration or fall of the highly-mounted device and improving the contact reliability between the upper contact point and the lower contact point.

What is claimed is:

1. A lifting apparatus for a highly-mounted device, comprising:
 - a main body installed at a predetermined height so that a drum for winding a wire rope and a first driving motor for giving a rotating force to the drum are installed thereto;
 - a lifting body suspended from the wire rope and having a device coupling portion provided at a lower end thereof;
 - an accommodation structure located at a lower portion of the main body and having an open lower portion so as to be coupled with the lifting body;
 - a stopper installed at the accommodation structure and caught by a suspending protrusion provided to the lifting body to give an anti-falling function for the lifting body;
 - an upper contact point and a lower contact point respectively installed at the main body and the lifting body to make contact with each other when the lifting body is moved up and coupled to the main body by winding the wire rope;
 - at least one guide roll attached to the main body to support the wire rope unwound from the drum and guide the unwound wire rope into the accommodation structure; and
 - a fixing instrument configured to apply a force to the lifting body in a state where the lifting body is moved up and coupled to the main body by winding the wire rope, so that the lifting body comes into close contact with the stopper,
- wherein the fixing instrument includes a second driving motor fixed to the main body, and a screw bolt rotated

9

by the second driving motor and coupled to a screw nut to be movable forward and backward in an upper and lower direction, and

wherein when the screw bolt moves forward, the screw bolt compresses the lifting body, or a portion connected to the lifting body, to push the lifting body downward so that the lifting body comes into close contact with the stopper.

2. The lifting apparatus for a highly-mounted device according to claim 1, further comprising an additional fixing instrument,

wherein the fixing instrument and the additional fixing instrument are arranged at sides of the main body symmetrically based on the center of the main body to operate simultaneously.

3. The lifting apparatus for a highly-mounted device according to claim 1,

wherein when fixing the lifting body, the fixing instrument instantly operates the second driving motor with a first

10

power that is a high power so that the screw bolt starts moving downward, and then the fixing instrument moves the screw bolt downward with a second power that is a relatively low power to press the lifting body, and

wherein when releasing the fixation of the lifting body, the fixing instrument instantly operates the second driving motor with the first power that is a high power so that the screw bolt starts moving upward, and then the fixing instrument moves the screw bolt upward with the second power that is a relatively low power to restore the screw bolt.

4. The lifting apparatus for a highly-mounted device according to claim 1,

wherein at least one selected from a CCTV camera, a light, a fire detector and a promotional banner is coupled to the device coupling portion.

* * * * *