

US011267639B2

(12) **United States Patent**
Guerdrum et al.

(10) **Patent No.:** **US 11,267,639 B2**
(45) **Date of Patent:** **Mar. 8, 2022**

(54) **COLLAPSIBLE PORTABLE STORAGE CONTAINER**

(71) Applicant: **OTTER PRODUCTS, LLC**, Fort Collins, CO (US)

(72) Inventors: **Jonathan H. Guerdrum**, Fort Collins, CO (US); **Douglas A. Kempel**, Fort Collins, CO (US); **Matthew M. Glanzer**, Fort Collins, CO (US); **Richard W. Vinson**, Fort Collins, CO (US); **Patrick G. Skovsted**, Fort Collins, CO (US); **Jason Sagen**, Fort Collins, CO (US); **Alan V. Morine**, Fort Collins, CO (US); **Todd Eichinger**, Fort Collins, CO (US); **Alex S. Breeden**, Fort Collins, CO (US); **Taylor S. Massey**, Fort Collins, CO (US); **Peter Goldsmith**, Fort Collins, CO (US)

(73) Assignee: **Otter Products, LLC**, Fort Collins, CO (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **17/112,251**

(22) Filed: **Dec. 4, 2020**

(65) **Prior Publication Data**

US 2021/0086979 A1 Mar. 25, 2021

Related U.S. Application Data

(63) Continuation of application No. 15/982,246, filed on May 17, 2018, now Pat. No. 10,906,723.
(Continued)

(51) **Int. Cl.**
B65D 81/38 (2006.01)
B65D 43/02 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **B65D 81/3813** (2013.01); **A45C 7/0036** (2013.01); **B65D 11/1826** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC **B65D 81/3813**; **B65D 11/1826**; **B65D 21/068**; **B65D 43/0202**; **B65D 45/02**;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,468,563 A 9/1923 Girard
2,627,993 A 2/1953 Hafner
(Continued)

FOREIGN PATENT DOCUMENTS

EP 3061704 A1 8/2016
WO 2004029526 A1 4/2004
(Continued)


OTHER PUBLICATIONS

Amazon.com, "Farberware 5190590 3-piece cutting board set," dated Jul. 23, 2011, downloaded from https://www.amazon.com/Farberware-5190590-3-Piece-Plastic-Assorted/dp/80731KDNMP/ref=cm_cr_ar_p_d_product_top?e=UTF8 Mar. 11, 2019, 8 pages.
(Continued)

Primary Examiner — Don M Anderson
Assistant Examiner — Jennifer Castriotta

(57) **ABSTRACT**

A shipping container includes an insulated base, an upper perimeter portion including one or more securing mechanisms, insulated side panels, and an insulated lid. Each of the insulated side panels is movable between a respective first position and a respective second position, wherein the shipping container is in the first configuration when all of the insulated side panels are in the first positions and collapses into the second configuration when all of the side panels are in the second positions. The insulated lid is removably
(Continued)



attachable for selectively closing and accessing an internal storage volume. Each of the securing mechanisms is configured to removably secure the upper perimeter portion to the insulated base when the shipping container is in the second configuration. Each of the securing mechanisms is also configured to removably secure the insulated lid to the upper perimeter portion in both the first and the second configurations.

19 Claims, 49 Drawing Sheets

Related U.S. Application Data

(60) Provisional application No. 62/585,630, filed on Nov. 14, 2017, provisional application No. 62/515,004, filed on Jun. 5, 2017.

(51) **Int. Cl.**

B65D 21/08 (2006.01)
B65D 45/20 (2006.01)
B65D 45/02 (2006.01)
A45C 7/00 (2006.01)
B65D 21/06 (2006.01)
B65D 25/06 (2006.01)
B65D 6/18 (2006.01)
B65D 25/16 (2006.01)
B65D 25/28 (2006.01)

(52) **U.S. Cl.**

CPC *B65D 21/068* (2013.01); *B65D 21/086* (2013.01); *B65D 25/06* (2013.01); *B65D 43/0202* (2013.01); *B65D 45/02* (2013.01); *B65D 45/20* (2013.01); *A45C 2200/20* (2013.01); *B65D 25/16* (2013.01); *B65D 25/2805* (2013.01); *B65D 25/2808* (2013.01); *B65D 2543/00194* (2013.01); *B65D 2543/00277* (2013.01); *B65D 2543/00296* (2013.01); *B65D 2543/00518* (2013.01); *B65D 2543/00842* (2013.01); *B65D 2543/00972* (2013.01); *F25D 2323/061* (2013.01)

(58) **Field of Classification Search**

CPC . *B65D 45/20*; *B65D 21/086*; *F25D 2323/061*; *A45C 7/0036*
 USPC 206/546; 220/6, 7, 4.28, 666
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,347,060 A 10/1967 Barkan
 3,395,550 A 8/1968 Dungan
 3,850,398 A 11/1974 Kantor
 3,868,829 A 3/1975 Mann et al.
 3,939,986 A 2/1976 Pierro
 4,024,731 A 5/1977 Branscum
 4,213,310 A 7/1980 Buss
 D275,822 S 10/1984 Gatland et al.
 4,515,421 A 5/1985 Steffes
 4,560,128 A 12/1985 Willeby et al.
 4,606,461 A 8/1986 Bolton
 RE32,740 E 8/1988 Steffes
 4,841,661 A 6/1989 Moore
 4,964,528 A 10/1990 Wagoner
 4,988,216 A 1/1991 Lyman
 5,052,185 A 10/1991 Spahr
 D325,323 S 4/1992 Kahl
 5,103,884 A 4/1992 Roman
 D328,389 S 8/1992 Pardo

D330,488 S 10/1992 Daniels
 5,181,612 A 1/1993 Liu
 5,215,248 A 6/1993 Moser
 5,285,656 A 2/1994 Peters
 D353,082 S 12/1994 Keven
 D354,419 S 1/1995 Kahl et al.
 5,403,095 A 4/1995 Melk
 5,509,279 A 4/1996 Brown et al.
 5,562,228 A 10/1996 Ericson
 5,605,056 A 2/1997 Brown et al.
 5,622,276 A 4/1997 Simmons
 5,669,233 A 9/1997 Cook et al.
 D387,249 S 12/1997 Mogil
 1,391,121 A 2/1998 Melk
 5,816,432 A 10/1998 Hammen et al.
 5,845,515 A 12/1998 Nelson
 5,850,915 A 12/1998 Tajima
 5,857,778 A 1/1999 Ells
 5,913,448 A 6/1999 Mann et al.
 D419,297 S 1/2000 Richardson et al.
 D419,767 S 2/2000 Richardson et al.
 D419,768 S 2/2000 Richardson et al.
 6,039,202 A 3/2000 Olstad et al.
 D425,761 S 5/2000 Philipson et al.
 6,065,873 A 5/2000 Fowler
 D435,196 S 12/2000 Gregor et al.
 6,185,860 B1 2/2001 Thibodeaux
 6,193,097 B1 2/2001 Perianes
 6,234,677 B1 5/2001 Mogil
 6,244,458 B1 6/2001 Frysinger et al.
 D444,683 S 7/2001 Corrion
 6,276,579 B1 8/2001 DeLoach
 D451,765 S 12/2001 Israel et al.
 6,325,281 B1 12/2001 Grogan
 6,328,179 B1 12/2001 Conrado et al.
 D455,934 S 4/2002 Culp et al.
 6,409,066 B1 6/2002 Schneider et al.
 1,465,134 A1 11/2002 Joss
 6,474,095 B1 11/2002 Chan
 6,505,479 B2 1/2003 Defelice et al.
 D472,384 S 4/2003 Richardson
 6,595,687 B2 7/2003 Godshaw et al.
 6,736,309 B1 5/2004 Westerman et al.
 6,751,963 B2 6/2004 Navedo et al.
 D502,599 S 3/2005 Cabana et al.
 6,895,778 B1 5/2005 Ackerman
 D513,123 S 12/2005 Richardson et al.
 D514,808 S 2/2006 Morine et al.
 6,993,931 B1 2/2006 Hamilton
 D516,807 S 3/2006 Richardson et al.
 D527,226 S 8/2006 Maldonado
 D527,953 S 9/2006 Gal
 7,140,507 B2 11/2006 Maldonado et al.
 7,296,433 B2 11/2007 Uihlein et al.
 7,389,608 B1 6/2008 MacKay
 7,415,794 B1 8/2008 Thompson
 7,682,080 B2 3/2010 Mogil
 7,791,003 B2 9/2010 Lockhart et al.
 7,900,816 B2 3/2011 Kastanek et al.
 D635,832 S 4/2011 Bergin
 D637,044 S 5/2011 Davis
 8,011,194 B2 9/2011 Dimmitt
 8,043,004 B2 10/2011 Mogil
 8,065,889 B1 11/2011 Silberman
 8,209,995 B2 7/2012 Kieling et al.
 8,246,190 B2 8/2012 Boiteau et al.
 8,317,046 B2 11/2012 Vanderberg et al.
 8,365,944 B2 2/2013 Vanderberg et al.
 8,403,162 B2 3/2013 Vanderberg et al.
 8,424,699 B2 4/2013 Vanderberg et al.
 8,430,265 B2 4/2013 Vanderberg et al.
 8,448,813 B2 5/2013 Vanderberg et al.
 D712,720 S 9/2014 Seiders
 D712,721 S 9/2014 Seiders
 D712,722 S 9/2014 Seiders
 D712,723 S 9/2014 Seiders
 D714,125 S 9/2014 Seiders
 8,863,546 B2 10/2014 Oberweis
 8,875,964 B1 11/2014 Vanderberg

(56)

References Cited

U.S. PATENT DOCUMENTS

8,910,819 B2 12/2014 Seiders
 8,919,082 B1 12/2014 Cataldo
 8,925,752 B2 1/2015 Smith
 D722,474 S 2/2015 Seiders
 D722,475 S 2/2015 Seiders
 D732,348 S 6/2015 Seiders et al.
 D732,349 S 6/2015 Seiders et al.
 D732,350 S 6/2015 Seiders et al.
 D732,899 S 6/2015 Seiders et al.
 9,139,352 B2 9/2015 Seiders et al.
 9,187,232 B2 11/2015 Seiders
 D752,347 S 3/2016 Seiders et al.
 9,316,428 B2 4/2016 Meeh
 9,389,010 B1 7/2016 Booker
 9,408,445 B2 8/2016 Mogil et al.
 9,433,200 B2 9/2016 Norman
 9,446,847 B2 9/2016 Richardson et al.
 9,500,400 B2 11/2016 Smith
 9,834,342 B2 4/2017 Seiders
 D786,559 S 5/2017 Seiders et al.
 D786,560 S 5/2017 Seiders et al.
 D786,561 S 5/2017 Seiders et al.
 D786,562 S 5/2017 Seiders et al.
 D787,187 S 5/2017 Seiders et al.
 D797,454 S 9/2017 Seiders et al.
 D797,455 S 9/2017 Seiders et al.
 D798,670 S 10/2017 Seiders et al.
 D799,276 S 10/2017 Seiders et al.
 D799,277 S 10/2017 Seiders et al.
 D799,905 S 10/2017 Seiders et al.
 D801,123 S 10/2017 Seiders et al.
 9,796,517 B2 10/2017 Seiders et al.
 D802,373 S 11/2017 Seiders et al.
 D804,905 S 12/2017 Seiders et al.
 D805,851 S 12/2017 Seiders et al.
 D820,646 S 6/2018 Yockey
 D821,165 S 6/2018 Guerdrum et al.
 D821,825 S 7/2018 Sullivan et al.
 D823,064 S 7/2018 Eichinger et al.
 D823,065 S 7/2018 Eichinger et al.
 D823,066 S 7/2018 Eichinger et al.
 10,029,842 B2 7/2018 Seiders et al.
 D824,730 S 8/2018 Guerdrum et al.
 10,092,137 B1 10/2018 Nelson et al.
 D835,470 S 12/2018 Seiders et al.
 D835,471 S 12/2018 Seiders et al.
 D835,472 S 12/2018 Seiders et al.
 D835,946 S 12/2018 Seiders et al.
 D838,983 S 1/2019 Seiders et al.
 D838,984 S 1/2019 Seiders et al.
 D840,150 S 2/2019 Seiders et al.
 10,221,005 B2 3/2019 James
 D850,865 S 6/2019 Smith et al.
 10,443,918 B2 10/2019 Li et al.
 2003/0038138 A1 2/2003 Komurke
 2003/0106895 A1 6/2003 Kalal
 2003/0136702 A1 7/2003 Redzisz et al.
 2003/0141424 A1 7/2003 Thomas
 2004/0178208 A1 9/2004 Leba et al.
 2004/0238543 A1 12/2004 Askew
 2004/0262319 A1 12/2004 Fisher
 2005/0006268 A1 1/2005 Futemick
 2005/0133557 A1 6/2005 McKenzie et al.
 2005/0263527 A1 12/2005 Maldonado et al.
 2005/0263528 A1 12/2005 Maldonado et al.
 2005/0279123 A1 12/2005 Maldonado et al.
 2005/0279124 A1 12/2005 Maldonado
 2006/0065655 A1 3/2006 Taylor
 2006/0180624 A1 8/2006 Sadow et al.
 2007/0137958 A1 6/2007 Hamlin
 2007/0278234 A1 12/2007 Mogil
 2008/0094853 A1 4/2008 Kim et al.
 2008/0260303 A1 10/2008 Lesseux et al.
 2009/0159471 A1 6/2009 Koppe
 2009/0218342 A1 9/2009 Pickles

2010/0065466 A1 3/2010 Perkins
 2010/0072215 A1 3/2010 Coon
 2010/0287976 A1 11/2010 Roof et al.
 2011/0056233 A1 3/2011 Flaker et al.
 2011/0182532 A1 7/2011 Baltus
 2011/0203297 A1 8/2011 Oberweis
 2011/0220531 A1 9/2011 Meether et al.
 2011/0289958 A1 12/2011 White et al.
 2013/0228583 A1 9/2013 Mayer
 2013/0264161 A1 10/2013 Thompson
 2014/0013789 A1 1/2014 Conrad et al.
 2014/0248003 A1 9/2014 Mogil et al.
 2015/0158539 A1 6/2015 Jensen et al.
 2015/0210444 A1 7/2015 Mercado et al.
 2015/0241107 A1 8/2015 Meeh
 2015/0298886 A1 10/2015 Knight et al.
 2015/0369529 A1 12/2015 Monroe
 2016/0101924 A1 4/2016 Mitchell et al.
 2016/0257479 A1 9/2016 Seiders et al.
 2016/0279840 A1 9/2016 French et al.
 2016/0347507 A1 12/2016 Kendrick
 2017/0001785 A1 1/2017 Ripley et al.
 2017/0023289 A1 1/2017 Anderson
 2017/0073146 A1 3/2017 Kuhn et al.
 2017/0073147 A1 3/2017 Kuhn
 2017/0121059 A1 5/2017 Faris
 2017/0233139 A1 8/2017 Averill
 2017/0245486 A1 8/2017 Larson et al.
 2017/0305639 A1 10/2017 Kuhn et al.
 2017/0350635 A1 12/2017 Thirumurugavel
 2018/0015938 A1 1/2018 DeFrancia
 2018/0141718 A1 5/2018 Ahlström et al.
 2018/0149400 A1 5/2018 Valencia
 2018/0186547 A1 7/2018 Morine et al.
 2018/0186550 A1 7/2018 Morine et al.
 2018/0263346 A1 9/2018 Stephens
 2018/0290814 A1 10/2018 Smith
 2018/0335241 A1 11/2018 Li et al.
 2018/0353379 A1 12/2018 Chou et al.
 2019/0023480 A1 1/2019 Lin

FOREIGN PATENT DOCUMENTS

WO 2006007266 A2 1/2006
 WO 2006009537 A1 1/2006
 WO 2014105962 A1 7/2014
 WO 2016154105 A1 9/2016

OTHER PUBLICATIONS

Best Cooler Reviews, Best Folding and Collapsible Cooler—It’s All About Convenience, downloaded from <https://bestcooler.reviews/best-folding-collapsible-cooler/> Jan. 15, 2018, 8 pages.
 CleverMade, CleverMade CleverCrates 45 Liter Collapsible Storage Bin/Container; Grated Wall Utility Basket/Tote, Royal Blue, downloaded from https://www.amazon.com/CleverMade-CleverCrates-Collapsible-Storage-Container/dp/B00UM4D63W/ref=sr_1_8?ie=UTF8&qid=1516048768&sr=8-8&keywords=collapsible%2Bmilk%2Bcrate&th=1 Jan. 15, 2018, 13 pages.
 Coleman, 75 Can Collapsible Sport Cooler, downloaded from <https://www.coleman.com/large-sport-collapsible/2000015225.html> Jan. 15, 2018, 3 pages.
 Digital Trends, “The new Venture coolers from Otterbox . . .”, Posted May 9, 2017. (<https://www.digitaltrends.com/outdoors/otterbox-venture-coolers/>).
 Duluth Trading Co, Folding Milk Crate, downloaded from <https://www.duluthtrading.com/store/product/folding-milk-crate-78536.aspx> on Jan. 15, 2018, 6 pages.
 Fulton, Wil, All the Major Meal Delivery Services, Tested and Ranked, dated Oct. 7, 2016, downloaded from <https://www.thrillist.com/eat/nation/best-meal-delivery-services-food-subscription-boxes-ranked> on Jan. 15, 2018, 18 pages.
 Ice Chest Guide, “Top 10 Best Soft Cooler Reviews and Buying Guide for 2018”, downloaded from <http://www.icechestguide.com/top-10-best-soft-cooler-reviews-and-buying-guide.html> Jan. 25, 2018, 12 pages.

(56)

References Cited

OTHER PUBLICATIONS

Igloo, Marine Ultra TM Collapse and Cool TM 50, downloaded from <https://www.igloocoolers.com/products/61582-marine-ultra-collapse-and-cool-50-can-cooler-bag-white> Jan. 15, 2018, 4 pages.

Kelty Folding Cooler, downloaded from <https://www.kelty.com/folding-cooler/> Jan. 18, 2018, 6 pages.

Morris, David Z., This box opens up new possibilities for fresh food delivery, dated Aug. 3, 2015, downloaded from <http://fortune.com/2015/08/03/freshrealm-cold-delivery/> Jan. 15, 2018, 4 pages.

OtterBox, “Rugged Venture Coolers”, Accessed Jan. 16, 2018. (<https://www.otterbox.com/en-US/venture-coolers.html>).

Pelican Consumer, Coolers—Hunting, Fishing, Camping, downloaded from <http://www.pelican.com/us/en/products/coolers> May 8, 2017, 2 pages.

Pelican Products, “70QT Cooler”, Accessed Jan. 16, 2018. (<http://www.pelican.com/us/en/product/outdoor-heavy-dutycoolers/elite-cooler/cooler/70QT/>).

Picnic at Ascot, 396-RB 60 Can Collapsible Rolling Cooler, downloaded from <http://www.picnicatascot.com/main/default/ProductsDetail.aspx?id=136> Jan. 15, 2018, 2 pages.

Polar Bear Coolers, “24 Pack Eclipse Cooler,” downloaded from <http://www.polarbearcoolers.com/product/PB327.html> Jan. 30, 2018, 6 pages.

Polar Bear Coolers, “Eclipse Backpack Cooler,” downloaded from <http://www.polarbearcoolers.com/product/PB397.html> Jan. 29, 2018, 4 pages.

REI Co-Op, “Soft-sided Coolers”, downloaded from <https://www.rei.com/c/soft-sided-coolers?r-c&origin+web&ir=category%3Asoft-sided-coolers%page=1> Jan. 25, 2018, 6 pages.

RTIC, “RTIC Soft Pack Coolers,” downloaded from <https://www.rticcoolers.com/shop/coolers/softpak> Jan. 25, 2018, 16 pages.

RTIC, Cooler Accessories, downloaded May 8, 2017 from <http://www.rticcoolers.com/shop/coolers/accessories>, 14 pages.

Stay Cool Hot Stuff, Flip-Box XL Collapsible Cooler and Insulation Box, downloaded from <https://staycoolhotstuff.com/products/flip-box-xl-collapsible-cooler-and-insulation-box> Jan. 18, 2018, 5 pages.

The Cooler Box, “Cordova Coolers vs Yeti—Is This New Cooler Better Than Yeti?”, Published Oct. 24, 2016. (<http://thecoolerbox.com/cordova-coolers-vs-yeti/>).

The Good Housekeeping Institute, Thermos Cold N’ Fold Cooler, dated Jul. 2007, downloaded from <http://www.goodhousekeeping.com/travel-products/food-cooler-reviews/a28866/thermos-cold-n-fold-cooler-101/> Jan. 18, 2018, 5 pages.

Walmart, ECR4Kids Large Vented Collapsible Crate, 12pk, downloaded from <https://www.walmart.com/ip/ECR4Kids-Large-Vented-Collapsible-Crate-12pk/34702630> on Jan. 15, 2018, 7 pages.

YETI Coolers, “Hopper Soft Sided Portable Coolers,” downloaded from <https://www.yeti.com/soft-coolers> Jan. 25, 2018, 6 pages.

YETI Coolers, “Tundra Cooler Divider,” dated Mar. 11, 2014, downloaded from https://www.yeti.com/en_US/accessories/tundra-dividers/DV.html?cg_id=accessories# Mar. 11, 2019, 9 pages.

YETI Coolers, Tundra Cooler Divider, downloaded from www.yeti.com/tundra-dividers May 8, 2017, 4 pages.

YETI Coolers, Tundra Ice Chests, downloaded from <http://yeti.com/tundra> May 8, 2017, 7 pages.

YETI Coolers, YETI Accessories & Parts, downloaded from <http://yeti.com/accessories> May 8, 2017, 5 pages.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11A




FIG. 11B




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39A




FIG. 39B




FIG. 39C




FIG. 40




FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45





FIG. 46






FIG. 48




FIG. 49




FIG. 50

COLLAPSIBLE PORTABLE STORAGE CONTAINER

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 15/982,246, filed on May 17, 2018, which claims priority to U.S. Provisional Application Nos. 62/515,004, filed Jun. 5, 2017, and 62/585,630, filed Nov. 14, 2017, the disclosures of which are hereby incorporated by reference in their entirety.

FIELD

This disclosure relates generally to a portable storage container for storing objects, such as food and/or beverages.

BACKGROUND

It is often desirable to bring along food or beverages when traveling or when participating in remote leisure activities. Often, the food may be perishable and the ambient temperature may be high (for instance, at a beach location), so it is desirable to keep the perishable food in a temperature controlled environment to avoid spoiling. Similarly, beverages, such as canned or bottled beverages, may also be consumed, and it is desired to keep such beverages cool until consumption. Meal delivery kits including perishable items are shipped to consumers in shipping containers. Portable storage containers, including insulated and non-insulated storage containers, coolers, and/or insulated shipping containers, may also be used for a variety of other purposes or activities including hunting, fishing, camping, medical purposes, general storage, grocery delivery, meal kit shipping, other food delivery, and/or other business or personal purposes. Exemplary portable storage containers are disclosed in U.S. application Ser. Nos. 15/398,468, filed Jan. 4, 2017, 15/494,020, filed Apr. 21, 2017, and 62/508,099, filed May 18, 2017, the disclosures of each of which are hereby incorporated by reference in their entirety.

Transporting or shipping the storage containers may be relatively difficult or expensive due to the relatively large volume of the container. In some situations, it may be desirable for the storage container to have an expanded configuration providing a larger interior space for storing food and/or beverages and a collapsed, smaller configuration for transporting an empty container.

SUMMARY

Portable storage containers are used for a variety of purposes and in conjunction with a variety of activities. In some exemplary embodiments, the storage container may be insulated to assist in keeping one or more items cool, cold, frozen, warm, or hot. The storage container may also be used to protect one or more items from damage, bumps, scratching, impact, water, rain, snow, mud, dust, dirt, light, visibility, theft, chemicals, and/or contaminants. The storage container may also be used to organize and/or transport items stored therein. While most of the examples discussed herein are illustrated with respect to a “cooler,” it should be understood that the techniques and features disclosed herein are applicable to other types of storage containers or temperature control containers. Further, shipping containers of the type disclosed herein may be used for storage or transportation purposes and need not necessarily include insu-

lating characteristics. The containers disclosed herein may be configured to be carried or transported in a plurality of ways or configurations.

In one exemplary embodiment a portable insulated storage container is provided. The storage container includes an insulated body having an internal cavity for storing one or more items, the insulated body having a base, first and second opposing end panels, and first and second opposing side panels. The first and second opposing end panels are each configured to move between a first vertical position and a second horizontal position. Each of the first and second opposing side panels includes an upper portion connected to a lower portion by a respective hinge. The first and second opposing side panels are each configured to rotate about their corresponding hinge between a first vertical storage position and a second stacked position. The container includes an insulated lid configured to engage the insulated body to close the internal cavity.

In a more particular embodiment, the storage container includes a flexible liner covering at least a portion of the internal cavity. In another more particular embodiment of any of the above or below embodiments, the hinge on each side panel is a living hinge. In another more particular embodiment of any of the above or below embodiments, the insulated body includes an upper perimeter portion. The first and second opposing end panels are configured to releasably attach direct to the perimeter portion in the second horizontal orientation. In another more particular embodiment of any of the above or below embodiments, the insulated body includes an upper perimeter portion and the first and second opposing end panels are positioned within a space defined by the upper perimeter portion in the second horizontal orientation. In another more particular embodiment of any of the above or below embodiments, the body is configured to releasably attach directly to the base when the first and second opposing side panels are in the stacked configuration. In another more particular embodiment of any of the above or below embodiments, the container has a first height when the first and second opposing end panels are in the first vertical position and the first and second opposing side panels are in the first vertical position and a second height when the first and second opposing end panels are in the second horizontal position and a second horizontal position and the first and second opposing side panels are in the second stacked position, the first height being greater than the second height.

In one exemplary embodiment a collapsible shipping container is provided. The container has a first configuration and a second configuration. The container includes an insulated base and an insulated upper perimeter portion. The container includes a plurality of insulated side panels extending between the upper perimeter portion and the base, each of the plurality of the insulated side panels being movable between a respective first position and a respective second position. The shipping container is in the first configuration when all of the insulated side panels are in the respective first positions. The shipping container collapses into the second configuration when all of the side panels are in the respective second positions. The collapsible shipping container has a height in the first configuration that is greater than a height of the shipping container in the second configuration. The container includes an insulated lid removably attachable to the upper perimeter portion for selectively closing and accessing an internal storage volume of the shipping container. The internal storage volume is defined by the insulated base, the plurality of insulated side panels, the insulated upper perimeter portion and the insu-

3

lated lid. The container includes a latching mechanism for temporarily maintaining the shipping container in the first configuration. The latching mechanism latches at least two of the insulated side panels in the respective first positions to temporarily maintain the shipping container in the first configuration. The container includes a flexible liner attached to the upper perimeter portion and configured to line the internal storage volume. The flexible liner has a first surface facing the internal storage volume and a second surface facing at least one of the insulated base and the insulated side panels. The flexible liner has a handle attached to the first surface and accessible from inside the internal storage volume. The container includes a strap attached to the second surface of the flexible liner and attached to the latching mechanism. The strap disengages the latching mechanism when the handle of the flexible liner is pulled from the internal storage volume, the disengaging of the latching mechanism permitting the shipping container to transition from the first configuration to the second configuration.

In a more particular embodiment, the latching mechanism includes a first latching apparatus associated with a first panel of the plurality of insulated side panels and a second latching apparatus associated with a second panel of the plurality of side panels, the second panel being opposite the first panel. In another more particular embodiment of any of the above or below embodiments, the first and second panels pivot inward toward the internal storage volume enabling the shipping container to transition from the first configuration to the second configuration. In another more particular embodiment of any of the above or below embodiments, a third panel of the plurality of insulated side panels is opposite a fourth panel of the plurality of insulated side panels, each of the third and fourth panels having an upper portion connected to a lower portion by a hinging element. In another more particular embodiment of any of the above or below embodiments, each latching apparatus includes a movable biased tab attached to the respective side panel, the movable biased tab extending into a slot in the insulated base to temporarily retain the respective side panel in the respective first position. In another more particular embodiment of any of the above or below embodiments, a force applied to the strap retracts the biased tabs from the slots in the insulated base to unlatch the latching mechanism. In another more particular embodiment of any of the above or below embodiments, the strap is attached to the flexible liner without piercing the flexible liner. In another more particular embodiment of any of the above or below embodiments, the strap is detachable from the flexible liner and/or the latching mechanism. In another more particular embodiment of any of the above or below embodiments, the flexible liner is removable from the collapsible shipping container. In another more particular embodiment of any of the above or below embodiments, the flexible liner is liquid impermeable. In another more particular embodiment of any of the above or below embodiments, the flexible liner has insulating characteristics. In another more particular embodiment of any of the above or below embodiments, the insulated lid includes one or more receptacles for receiving a temperature control element and one or more shelves for retaining the temperature control element, each shelf including one or more convection apertures.

In one exemplary embodiment, a configurable shipping container has a first configuration and a second configuration. The shipping container includes a base and an upper portion. The shipping container includes a plurality of side panels extending between the upper portion and the base,

4

each of the plurality of the side panels being movable between a first position and a second position. The shipping container is in the first configuration when all of the side panels are in the respective first positions. The shipping container is in the second configuration when all of the side panels are in the respective second positions. The first configuration of the shipping container has a height that is greater than a height of the second configuration. The shipping container includes a lid for selectively accessing and closing an internal storage volume of the shipping container, the internal storage volume defined by the base, the upper portion, the plurality of side panels, and the lid. The shipping container includes latching mechanisms for temporarily maintaining the shipping container in the first configuration. The latching mechanisms temporarily latch at least two of the side panels in the respective first positions to temporarily maintain the shipping container in the first configuration. The shipping container includes a flexible liner attached to the upper portion and configured to line at least a portion of the internal storage volume of the shipping container. The shipping container includes a strap attached to the flexible liner and the latching mechanisms. The strap disengages the latching mechanisms when the flexible liner is pulled away from the internal storage volume. The disengaging of the latching mechanisms releases the at least two of the side panels from the respective first positions thereby permitting the shipping container to transition from the first configuration to the second configuration.

In a more particular embodiment, the flexible liner includes a handle attached to an inner surface of the flexible liner, the handle being accessible from the internal storage volume. In another more particular embodiment of any of the above or below embodiments, the side panels, and the lid include vacuum insulated panels. In another more particular embodiment of any of the above or below embodiments, the container includes a securing mechanism for securing the configurable shipping container in the second configuration. In another more particular embodiment of any of the above or below embodiments, the at least two of the side panels are opposite each other and hinge inward toward the internal storage volume when in the respective second positions. In another more particular embodiment of any of the above or below embodiments, the flexible liner is replaceable.

In one exemplary embodiment, a portable insulated storage container has at least two configurations. The container includes an insulated body having an internal cavity for storing one or more items. The insulated body includes a base. The body includes first and second opposing end panels each configured to move between a first vertical orientation and a second horizontal orientation, each of the first and second opposing end panels including a respective latching mechanism for engaging the base for temporarily maintaining the first and second opposing end panels in the first vertical orientation. The body includes first and second opposing side panels each including an upper portion connected to a lower portion by a respective hinge. The first and second opposing side panels are each configured to rotate about their respective hinge between a first vertical configuration and a second stacked configuration. The portable insulated storage container is in a collapsed configuration when each of the opposing side panels are in the second stacked configuration and each of the opposing end panels are in the second horizontal orientation. The container includes an insulated lid configured to close an opening of the insulated body to close the internal cavity. The container includes a strap removably attached to the respective latching mechanisms of the first and second opposing end panels

5

for releasing both the first and second opposing end panels from the first vertical orientation to the second horizontal orientation when the strap is pulled.

In a more particular embodiment, the container includes a liquid impermeable liner which lines the internal cavity of the insulated body, wherein the strap is removably adhered to a surface of the liquid impermeable liner that is opposite a surface of the liquid impermeable liner facing into the internal cavity. In another more particular embodiment of any of the above or below embodiments, the container includes a handle adhered to the surface of the liquid impermeable liner facing into the internal cavity of the insulated body, wherein the strap and the handle are adhered to the liquid impermeable liner without puncturing the liquid impermeable liner. In another more particular embodiment of any of the above or below embodiments, the liquid impermeable liner includes one or more of an antimicrobial coating and an insulating layer.

In one exemplary embodiment, a portable storage container has an expanded configuration and a collapsed configuration. The portable storage container includes a body having an internal cavity for storing one or more items. The body includes an upper perimeter portion, a base, and first and second opposing side panels each connecting the body to the base. The body includes first and second opposing end panels pivotably attached to the upper perimeter portion. The first end panel includes a movable locking member extending from a surface of the first end panel. The movable locking member is configured to be movable between a locked position. The movable locking member is received in a recess of the base and an unlocked position. The movable locking member prevents the first end panel from pivoting with respect to the upper perimeter member when the movable locking member is in the locked position. The movable locking member permits the first end panel to pivot with respect to the upper perimeter when the movable locking member is in the unlocked position. The container includes a liner at least partially positioned in the internal cavity, the liner having opposing inner and outer surfaces, the inner surface including a handle, the handle operably connected to the movable locking member. The handle is configured such that a first movement of the handle is configured to move the movable locking member from the locked to the unlocked position and the portable storage container from the expanded configuration to the collapsed configuration.

In a more particular embodiment, the first movement includes moving the handle in a direction away from the base. In another more particular embodiment of any of the above or below embodiments, the first and second opposing end panels each extend between the perimeter portion and the base in a vertical storage position when the portable storage container is in the expanded configuration. In another more particular embodiment of any of the above or below embodiments, the first and second opposing end panels each extend from the perimeter portion substantially parallel to the base in a horizontal shipping position when the portable storage container is in the collapsed configuration. In another more particular embodiment of any of the above or below embodiments, the handle is independently connected to the first and second opposing end panels such that the first movement of the handle results in the movement of the first and second opposing end panels from the vertical storage position to the horizontal shipping position.

In another more particular embodiment of any of the above or below embodiments, the movable locking member is positioned proximate a bottom surface of the first end

6

panel. In another more particular embodiment of any of the above or below embodiments, the first end panel includes a biasing member attached to the movable locking member, the biasing member biasing the movable locking member in the locked position. In another more particular embodiment of any of the above or below embodiments, the handle is operably connected to a strap, the strap being connected to the biasing member, wherein the strap is configured such that a first movement of the handle transmits a force through the strap and the biasing member to move the movable locking member from the locked to the unlocked position. In another more particular embodiment of any of the above or below embodiments, the handle is attached to the inner surface of the liner and the strap is attached to the outer surface of the liner. In another more particular embodiment of any of the above or below embodiments, the handle and strap are independently attached to the liner with an adhesive and wherein the inner surface and the outer surface of the liner are each continuous proximate the handle and the strap.

In another more particular embodiment of any of the above or below embodiments, the second end panel includes a second movable locking member extending from a surface of the second end panel, the second movable locking member configured to be movable between a locked position wherein the second movable locking member is received in a second recess of the base and an unlocked position wherein the second movable locking member prevents the second end panel from pivoting with respect to the upper perimeter member when the second movable locking member is in the locked position and the second movable locking member permits the second end panel to pivot with respect to the upper perimeter when the second movable locking member is in the unlocked position. The second end panel includes a second biasing member attached to the second movable locking member, the second biasing member biasing the movable locking member in the locked position. In another more particular embodiment of any of the above or below embodiments, the handle is operably connected to a strap, the strap being connected to the first biasing member and the second biasing member, wherein the strap is configured such that a first movement of the handle transmits a first force through the strap and the biasing member to move the movable locking member from the locked to the unlocked position and a second force through the strap and the second biasing member to move the second movable locking member from the locked to the unlocked position.

In another more particular embodiment of any of the above or below embodiments, the container includes a lid configured to removably engage the body to removably seal the internal cavity. In another more particular embodiment of any of the above or below embodiments, the internal cavity is defined by the base, the first and second opposing end panels, the first and second opposing side panels, and the engaged lid. In another more particular embodiment of any of the above or below embodiments, the internal cavity defines an expanded volume when the portable storage container is in the expanded configuration and a collapsed volume when the portable storage container is in the collapsed configuration, the expanded volume being greater than the collapsed volume.

In another more particular embodiment of any of the above or below embodiments, the first and second opposing end panels are each pivotably attached to the perimeter portion. In another more particular embodiment of any of the above or below embodiments, the first and second opposing end panels each extend between the perimeter portion and

the base in a vertical storage position when the portable storage container is in the expanded configuration. In another more particular embodiment of any of the above or below embodiments, the first and second opposing end panels each extend from the perimeter portion substantially parallel to the base in a horizontal shipping position when the portable storage container is in the collapsed configuration. In another more particular embodiment of any of the above or below embodiments, the first side panel is pivotably attached to at least one of the perimeter portion and the base. In another more particular embodiment of any of the above or below embodiments, the first side panel includes an upper portion pivotably attached to the perimeter portion and a lower portion pivotably attached to the base. In another more particular embodiment of any of the above or below embodiments, the upper portion is connected to the lower portion by a hinge. In another more particular embodiment of any of the above or below embodiments, the container includes a hoop configured to secure the liner to the upper perimeter portion.

In one exemplary embodiment, an insulated portable storage container movable between an expanded configuration and a collapsed configuration is provided. The container includes a body having an internal cavity for storing one or more items. The body includes an insulated upper perimeter portion, an insulated base, first and second opposing side panels each connecting the body to the base. The first side panel includes an insulated first upper portion pivotably attached to the perimeter portion and an insulated first lower portion pivotably attached to the base and the second side panel includes an insulated second upper portion pivotably attached to the perimeter portion and an insulated second lower portion pivotably attached to the base, and first and second opposing insulated end panels pivotably attached to the upper perimeter portion. The first and second opposing end panels each extend between the perimeter portion and the base in a vertical storage position when the portable storage container is in the expanded configuration. The first and second opposing end panels each extend from the perimeter portion substantially parallel to the base in a horizontal shipping position when the portable storage container is in the collapsed configuration. The container includes a liner at least partially positioned in the internal cavity, the liner including a handle operably connected to the first end panel. The handle is configured such that a first movement of the handle is configured to move the first end panel from the vertical storage position to the horizontal shipping position. The liner includes an insulated lid configured to engage the body to removably seal the internal cavity.

In a more particular embodiment, the first upper portion is connected to the first lower portion by a first hinge and wherein the second upper portion is connected to the second lower portion by a second hinge. In another more particular embodiment of any of the above or below embodiments, the first end panel includes a movable locking member extending from a surface of the first end panel, wherein the locking member is configured such that the first movement of the handle moves the locking member from a locked position in which the locking member resists the movement of the first end panel from the vertical storage position to the horizontal shipping position to an unlocked position in which the locking member permits the movement of the first end panel from the vertical storage position to the horizontal shipping position. In another more particular embodiment of any of the above or below embodiments, the first end panel includes a biasing member attached to the movable locking

member, the biasing member biasing the movable locking member in the locked position.

In another more particular embodiment of any of the above or below embodiments, the handle is operably connected to a strap, the strap being connected to the biasing member, wherein the strap is configured such that a first movement of the handle transmits a force through the strap and the biasing member to move the movable locking member from the locked to the unlocked position. In another more particular embodiment of any of the above or below embodiments, the base includes a recess for receiving the movable locking member when the movable locking member is in the locked position.

In another more particular embodiment of any of the above or below embodiments, at least one of the upper perimeter portion, the base, the first side panel, the second side panel, the first end panel, the second panel, and the lid includes a vacuum insulated panel. In another more particular embodiment of any of the above or below embodiments, the upper perimeter portion, the base, the first side panel, the second side panel, the first end panel, the second panel, and the lid each includes one or more vacuum insulated panels. In another more particular embodiment of any of the above or below embodiments, the container includes an insulating gasket between the upper perimeter portion and at least one of the first side panel, the second side panel, the first end panel, the second panel, and the lid.

In one exemplary embodiment, a portable storage container has an expanded configuration and a collapsed configuration. The portable storage container includes a body having an internal cavity for storing one or more items, the body including an upper perimeter portion, a base, first and second opposing side panels each connecting the body to the base. The body includes first and second opposing end panels pivotably attached to the upper perimeter portion. The container includes an insulated lid configured to engage the body to removably seal the internal cavity and a liner at least partially positioned in the internal cavity and connected to the first and second opposing end panels, the liner including a handle connected to a movable locking mechanism of the first end, the movable locking mechanism including a projection configured to be moved between a locked position and an unlocked position upon a first movement of the handle, the projection engaging the base to resist movement of the first end relative to the base when the projection is in the locked position, and the projection permitting movement of the first end relative to the base when the projection is in the unlocked position.

In a more particular embodiment, the first and second opposing end panels each extend between the perimeter portion and the base in a vertical storage position when the portable storage container is in the expanded configuration and wherein the first and second opposing end panels each extend from the perimeter portion substantially parallel to the base in a horizontal shipping position when the portable storage container is in the collapsed configuration. In another more particular embodiment of any of the above or below embodiments, the first end is configured such that the first movement of the handle moves the first end panel from the vertical storage position to the horizontal shipping position. In another more particular embodiment of any of the above or below embodiments, the first movement includes moving the handle in a direction away from the base.

In another more particular embodiment of any of the above or below embodiments, the first side panel includes an insulated first upper portion pivotably attached to the perim-

eter portion and an insulated first lower portion pivotably attached to the base and the second side panel includes an insulated second upper portion pivotably attached to the perimeter portion and an insulated second lower portion pivotably attached to the base. In another more particular embodiment of any of the above or below embodiments, the first upper portion is connected to the first lower portion by a first hinge and wherein the second upper portion is connected to the second lower portion by a second hinge. In another more particular embodiment of any of the above or below embodiments, the first upper portion includes a first outer surface and an opposing first inner surface and the first lower portion includes a second outer surface and a second inner surface, wherein the first outer surface and the second outer surface form an outer side surface of the portable storage container when the portable storage container is in the expanded configuration. In another more particular embodiment of any of the above or below embodiments, the first outer surface is adjacent the second outer surface when the portable storage container is in the collapsed configuration.

In another more particular embodiment of any of the above or below embodiments, the internal cavity defines an extended volume when the portable storage container is in the expanded configuration and a collapsed volume when the portable storage container is in the collapsed configuration, the expanded volume being greater than the collapsed volume. In another more particular embodiment of any of the above or below embodiments, the container has an expanded volume when the container is in the expanded configuration and a collapsed height when the container is in the collapsed configuration, the expanded height being greater than the collapsed height.

In one exemplary embodiment, a portable storage container is provided. The container includes a body having an internal cavity for storing one or more items, the body including a base, a perimeter portion, first and second opposing end panels extending from the perimeter portion, and first and second opposing side panels extending from the perimeter portion, and a lid configured to engage the body to close the internal cavity. The perimeter portion includes a securing mechanism including a locking lip, the portable storage container having an expanded configuration in which the locking lip is configured to releasably engage a side panel locking portion of the first side panel to prevent movement of the first side panel relative to the upper perimeter portion when the portable storage container is in the expanded configuration, and the portable storage container having a collapsed configuration in which the locking lip is configured to releasably engage a base locking portion of the base to prevent movement of the base relative to the upper perimeter portion when the portable storage container is in the collapsed configuration.

In a more particular embodiment, the side panel locking portion includes a groove, the locking lip being received within the groove to prevent movement of the first side panel relative to the perimeter portion when the portable storage container is in the expanded configuration. In another more particular embodiment of any of the above or below embodiments, the base panel locking portion includes a groove, the locking lip being received within the groove to prevent movement of the base relative to the perimeter portion when the portable storage container is in the collapsed configuration.

In another more particular embodiment of any of the above or below embodiments, the upper perimeter portion includes a rotatable portion movable between a locked

position and an unlocked position, the rotatable portion including the locking lip. In another more particular embodiment of any of the above or below embodiments, the locking lip is configured to engage the side panel locking portion when the rotatable portion is in the locked position and the portable storage container is in the expanded configuration, the locking lip is configured to engage the base locking portion when the rotatable portion is in the locked position and the portable storage container is in the collapsed configuration, and the locking lip is configured to not engage either the side panel locking portion or the base locking portion when the rotatable portion is in the unlocked position. In another more particular embodiment of any of the above or below embodiments, the container includes a button movable between an expanded configuration and a depressed configuration, wherein the button is configured to maintain the rotatable portion in the locked position when the button is in the expanded configuration and the button is configured to allow the rotatable portion to move between the locked position and the unlocked position when the button is in the depressed configuration. In another more particular embodiment of any of the above or below embodiments, the container includes a biasing element configured to bias the button in the expanded configuration.

In another more particular embodiment of any of the above or below embodiments, the securing mechanism includes a second locking lip, the second locking lip configured to releasably engage a lid locking portion of the lid. In another more particular embodiment of any of the above or below embodiments, the lid locking portion includes a groove, the second locking lip being received within the groove to prevent movement of the engaged lid relative to the body. In another more particular embodiment of any of the above or below embodiments, the perimeter portion includes a rotatable portion movable between a locked position and an unlocked position, the rotatable portion including the locking lip and the second locking lip. In another more particular embodiment of any of the above or below embodiments, the internal cavity is defined by the base, the first and second opposing end panels, the first and second opposing side panels, and the engaged lid.

In another more particular embodiment of any of the above or below embodiments, the internal cavity defines an extended volume when the portable storage container is in the expanded configuration and a collapsed volume when the portable storage container is in the collapsed configuration, the expanded volume being greater than the collapsed volume.

In another more particular embodiment of any of the above or below embodiments, the first and second opposing end panels are each pivotably attached to the perimeter portion. In another more particular embodiment of any of the above or below embodiments, the first and second opposing end panels each extend between the perimeter portion and the base in a vertical storage position when the portable storage container is in the expanded configuration. In another more particular embodiment of any of the above or below embodiments, the first and second opposing end panels each extend from the perimeter portion substantially parallel to the base in a horizontal shipping position when the portable storage container is in the collapsed configuration. In another more particular embodiment of any of the above or below embodiments, the first side panel is pivotably attached to at least one of the perimeter portion and the base. In another more particular embodiment of any of the above or below embodiments, the first side panel includes an upper portion pivotably attached to the perimeter portion

11

and a lower portion pivotably attached to the base. In another more particular embodiment of any of the above or below embodiments, the upper portion is connected to the lower portion by a hinge.

In one exemplary embodiment, a portable storage container having an expanded configuration and a collapsed configuration is provided. The portable storage container includes a body having an internal cavity for storing one or more items. The body includes an upper perimeter portion including a rotatable portion having a locking lip movable between a locked position and an unlocked position, a base including a groove configured to receive the locking lip when the portable storage container is in the collapsed configuration, first and second opposing end panels, the first end panel including a groove configured to receive the locking lip when the portable storage container is in the expanded configuration, and first and second opposing side panels each extending between the upper perimeter portion and the base.

In a more particular embodiment, the locking lip is configured to prevent movement of the first side panel relative to the upper perimeter portion when the portable storage container is in the expanded configuration, and locking lip is configured to prevent movement of the base relative to the upper perimeter portion when the portable storage container is in the collapsed configuration. In another more particular embodiment of any of the above or below embodiments, the locking lip is configured to be received within the groove of the first end panel when the rotatable portion is in the locked position and the portable storage container is in the expanded configuration, the locking lip is configured to be received within the groove of the base when the rotatable portion is in the locked position and the portable storage container is in the collapsed configuration, and the locking lip is configured to not be received within either the groove of the first end panel or the groove of the base when the rotatable portion is in the unlocked position.

In another more particular embodiment of any of the above or below embodiments, the upper perimeter portion includes a second rotatable portion having a second locking lip movable between a locked position and an unlocked position, the base includes a second groove configured to receive the second locking lip when the portable storage container is in the collapsed configuration, and the second end panel includes a second groove configured to receive the locking lip when the portable storage container is in the expanded configuration.

In another more particular embodiment of any of the above or below embodiments, the container includes a button movable between an expanded configuration and a depressed configuration, wherein the button is configured to maintain the rotatable portion in the locked position when the button is in the expanded configuration and the button is configured to allow the rotatable portion to move between the locked position and the unlocked position when the button is in the depressed configuration. In another more particular embodiment of any of the above or below embodiments, the container includes a biasing element configured to bias the button in the expanded configuration.

In another more particular embodiment of any of the above or below embodiments, the container includes a lid configured to removably engage the body to close the internal cavity. In another more particular embodiment of any of the above or below embodiments, the securing mechanism includes a second locking lip, the second locking lip configured to releasably engage a groove of the lid,

12

the second locking lip configured to be received within the groove of the lid to prevent movement of the engaged lid relative to the body. In another more particular embodiment of any of the above or below embodiments, the locking lip is configured to be received within the groove of the first end panel and the second locking lip is configured to be received within the groove of the engaged lid when the rotatable portion is in the locked position and the portable storage container is in the expanded configuration, the locking lip is configured to be received within the groove of the base and the second locking lip is configured to be received within the groove of the engaged lid when the rotatable portion is in the locked position and the portable storage container is in the collapsed configuration, and the locking lip is configured to not be received within either the groove of the first end panel or the groove of the base and the second locking lip is configured to not be received within the groove of the engaged lid when the rotatable portion is in the unlocked position.

In another more particular embodiment of any of the above or below embodiments, the upper portion includes a post about which the rotatable portion rotates to move the locking lip between the locked position and the unlocked position. In another more particular embodiment of any of the above or below embodiments, the locking lip, the post, and the second locking lip are positioned in a substantially straight line.

In one exemplary embodiment, a portable storage container has an expanded configuration and a collapsed configuration. The portable storage container includes a body having an internal cavity for storing one or more items. The body includes an upper perimeter portion, a base, first and second opposing end panels, and first and second opposing side panels. The upper perimeter portion includes means for selectively engaging the first side panel when the portable storage container is in the expanded configuration and the base when the portable storage container is in the collapsed configuration.

In a more particular embodiment, the container includes a lid configured to engage the body to removably seal the internal cavity and wherein the upper perimeter portion includes means for selectively engaging the lid.

In one exemplary embodiment, a configurable shipping container has an expanded configuration and a collapsed configuration is provided. The shipping container includes an insulated base and an insulated upper portion. The container includes a plurality of insulated side panels extending between the upper portion and the base, the side panels movable to transition the shipping container between the expanded configuration and the collapsed configuration. The shipping container has a height in the expanded configuration that is greater than a height of the shipping container in the collapsed configuration. The container includes an insulated lid configured to close an internal storage volume of the shipping container when the lid is in a closed position and provide access to the internal storage volume when the lid is in an opened position. The lid includes a first receptacle and a second receptacle that face the internal storage volume when the lid is in the closed position, each of the first and second receptacles configured to receive one or more temperature control elements. The lid includes a first shelf and a second shelf, each shelf configured to cover at least a portion of a respective one of the first and second receptacles to hold the one or more ice packs in the respective one of the receptacles; and a slot between the first and second receptacles. The container includes a removable divider for dividing the internal storage volume into a

first storage compartment and a second storage compartment when the shipping container is in the expanded configuration. A slot proximate the base and the slot in the lid receive respective edges of the divider for holding the divider in place. The first receptacle is associated with the first storage compartment and the second receptacle is associated with the second storage compartment.

In a more particular embodiment the container includes a removable flexible liner configured to line at least a portion of the internal storage volume. In another more particular embodiment of any of the above or below embodiments, the flexible liner is liquid impermeable and/or has anti-microbial characteristics. In another more particular embodiment, the slot proximate the base is formed in the base, in the liner, or in a handle coupled to the liner.

In another more particular embodiment of any of the above or below embodiments, one or more of the plurality of side panels includes a slot for receiving an edge of the removable divider. In another more particular embodiment of any of the above or below embodiments, the base includes a second slot and the lid includes a corresponding second slot for receiving the respective edges of the divider for holding the divider in place in a second position. In another more particular embodiment of any of the above or below embodiments, at least one of the shelves includes one or more apertures for allowing convective air movement between the associated storage compartment and the associated receptacle. In another more particular embodiment of any of the above or below embodiments, the base includes a second slot for receiving a second divider for defining a third storage compartment in the internal storage volume, and the lid includes a third receptacle, a third shelf, and a second slot for receiving the second divider. In another more particular embodiment of any of the above or below embodiments, the container includes a securing mechanism configured to secure the lid in the closed position when the shipping container is in the expanded configuration, and secure the lid in the closed position and secure the shipping container in the collapsed configuration when the shipping container is in the collapsed configuration. In another more particular embodiment of any of the above or below embodiments, the divider is insulated.

In one exemplary embodiment, a configurable shipping container system is provided. The system includes a configurable shipping container having an expanded configuration and a collapsed configuration. The shipping container includes an insulated base, an insulated upper portion, a plurality of insulated side panels extending between the upper portion and the base, the side panels movable to transition the shipping container between the expanded configuration and the collapsed configuration. The shipping container has a height in the expanded configuration that is greater than a height of the shipping container in the collapsed configuration, and an insulated lid configured to close an internal storage volume of the shipping container when the lid is in a closed position and provide access to the internal storage volume when the lid is in an opened position, the lid including a first receptacle and a second receptacle each facing the internal storage volume when the lid is in the closed position, each of the first and second receptacles configured to receive one or more temperature control elements, the lid including a slot positioned between the first and second receptacles. The system includes a first shelf and a second shelf, each shelf configured to cover at least a portion of a respective one of the first and second receptacles to hold the one or more ice packs in the respective one of the receptacles, each of the first and second

shelves including one or more convection apertures, and a removable divider for dividing the internal storage volume into a first storage compartment and a second storage compartment when the shipping container is in the expanded configuration. A slot proximate the base and the slot in the lid receive respective edges of the divider for holding the divider in place. The first receptacle is associated with the first storage compartment and the second receptacle is associated with the second storage compartment.

In a more particular embodiment, the system includes a removable flexible liner configured to line at least a portion of the internal storage volume. In another more particular embodiment, the slot proximate the base is formed in the base, in the liner, or in a handle coupled to the liner. In another more particular embodiment of any of the above or below embodiments, the system includes a strap for releasing the configurable shipping container from the expanded configuration to the collapsed configuration, the strap attached to two or more of the insulated side panels. In another more particular embodiment of any of the above or below embodiments, the strap is attached to the flexible liner. In another more particular embodiment of any of the above or below embodiments, the flexible liner is liquid impermeable and has anti-microbial characteristics. In another more particular embodiment of any of the above or below embodiments, the system includes a securing mechanism configured to: secure the lid in the closed position when the shipping container is in the expanded configuration, and secure the lid in the closed position and secure the shipping container in the collapsed configuration when the configurable shipping container is in the collapsed configuration. In another more particular embodiment of any of the above or below embodiments, the shipping container is configurable to maintain the first storage compartment in a first temperature range that is different than a second temperature range of the second storage compartment. In another more particular embodiment of any of the above or below embodiments, the system includes a second divider. In another more particular embodiment of any of the above or below embodiments, the system includes a tamper resistant closure or tamper evident closure for the insulated lid. In another more particular embodiment of any of the above or below embodiments, the system includes a lock for the insulated lid.

In one exemplary embodiment, a portable storage container is provided. The container includes a body having an internal cavity for storing one or more items, the body including a base and a plurality sides, each of the plurality of sides having an internal surface and an opposing external surface, the body having an upper perimeter including an internal lip extending around the internal cavity. The container includes a liner at least partially positioned in the internal cavity and covering an interior surface of the base and the internal surface of each of the plurality of sides, the liner including an edge region around a perimeter of the body to the edge region of the liner. The hoop includes an upper perimeter portion, a connecting portion extending downward from the upper perimeter portion, and a securing portion extending upward from the connecting portion, the securing portion exerting a force through the liner against the plurality of sides to secure the liner in the internal cavity.

In one more particular embodiment, the securing portion exerts a force through the liner against the internal lip of the body to resist the hoop from being removed from the body. In another more particular embodiment of any of the above or below embodiments, the securing portion includes an

outer surface and a distal end, the outer surface exerting the force through the liner against the plurality of sides to secure the liner in the internal cavity, and the distal end exerting the force through the line against the internal lip of the body to resist the hoop from being removed from the body. In another more particular embodiment of any of the above or below embodiments, the connecting portion has a thickness substantially similar to a thickness of the securing portion, and wherein an intermediate portion connecting the connecting portion and the securing portion has a thickness less than the thickness of the connecting portion. In another more particular embodiment of any of the above or below embodiments, the upper perimeter includes a recess extending around the internal cavity, the hoop being received within the recess. In another more particular embodiment of any of the above or below embodiments, the container includes a lid configured to be removably attached to the body. In another more particular embodiment of any of the above or below embodiments, the container includes a gasket positioned in a recess formed in one of the hoop and the lid, the gasket contacting the other of the hoop and the lid when the lid is attached to the body to thermally seal the internal cavity of the body. In another more particular embodiment of any of the above or below embodiments, the recess extends around an upper surface of the hoop. In another more particular embodiment of any of the above or below embodiments, the plurality of sides includes one or more vacuum insulated panels. In another more particular embodiment of any of the above or below embodiments, the hoop includes a plurality of sides, the upper perimeter portion and the connecting portion forming a continuous perimeter around the plurality of sides of the hoop.

In one exemplary embodiment, a portable storage container is provided. The container includes a body having an internal cavity for storing one or more items, the body including a base and a plurality sides, each of the plurality of sides having an upper surface, an internal surface and an opposing external surface, a liner at least partially positioned in the internal cavity and covering an interior surface of the base, the internal surface of each of the plurality of sides, and at least a portion of the upper surface of each of the plurality of sides, and a hoop coupled to the upper surface of each of the plurality of sides, the hoop having a plurality of outwardly engaging projections applying a force through the liner to the body, the hoop securing the liner in the body.

In one more particular embodiment, the body includes a recess positioned in the upper surface of each of the plurality of sides, the recess forming a perimeter extending around the internal cavity, the hoop being positioned in the recess. In another more particular embodiment of any of the above or below embodiments, the body includes an internal lip extending outward from the internal surface of one of the plurality of sides, the outwardly engaging projections engaging the internal lip through the liner to maintain the hoop in the internal cavity. In another more particular embodiment of any of the above or below embodiments, the outwardly engaging projections have a bias in a direction towards the body.

In one exemplary embodiment, a method of assembly a storage container is provided. The method includes providing a body having an internal cavity for storing one or more items, the body including a base and a plurality sides each having a top surface, an internal surface and an opposing external surface, the body having an upper perimeter including an internal lip extending around the internal cavity, each of the plurality of sides having an internal side and an opposing external side, the body having an upper perimeter

including an internal lip extending around the internal cavity. The method also includes inserting a liner having a perimeter region into the internal cavity, the liner fully covering the internal lip and internal surface of each of the plurality of sides. The method also includes attaching a hoop to the body, the hoop including an upper perimeter portion, a connecting portion extending downward from the upper perimeter portion, and a securing portion extending upward from the connecting portion, whereby attaching the hoop compresses the securing portion against the connecting portion causing the securing portion to exert a force through the liner to the internal surface of each of the plurality of sides, the force securing the liner between the body and the hoop.

In another embodiment, a collapsible shipping container includes an insulated base, an upper perimeter portion including one or more securing mechanisms, a plurality of insulated side panels, and an insulated lid. The plurality of insulated side panels extend between the upper perimeter portion and the base. Each of the plurality of insulated side panels is movable between a respective first position and a respective second position, wherein the collapsible shipping container is in the first configuration when all of the insulated side panels are in the respective first positions and wherein the collapsible shipping container collapses into the second configuration when all of the side panels are in the respective second positions. The collapsible shipping container has a height in the first configuration that is greater than a height of the collapsible shipping container in the second configuration. The insulated lid is removably attachable to the upper perimeter portion for selectively closing and accessing an internal storage volume. The internal storage volume is defined by the insulated base, the plurality of insulated side panels, the upper perimeter portion, and the insulated lid. Each of the one or more securing mechanisms of the upper perimeter portion is configured to removably secure a lower edge of the upper perimeter portion to the insulated base when the collapsible shipping container is in the second configuration. Each of the one or more securing mechanisms is also configured to removably secure the insulated lid to an upper edge of the upper perimeter portion in both the first and the second configurations.

Other variations and embodiments are possible, including variations and embodiments which do not necessarily include all of the elements described above or below and/or variations and embodiments which may include additional elements.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates an elevated perspective view of an exemplary portable storage container in a first expanded configuration in accordance with the techniques and improvements disclosed herein;

FIG. 2 illustrates a side view of the container of FIG. 1;

FIG. 3 illustrates an end view of the container of FIG. 1;

FIG. 4 illustrates an exploded view of an exemplary container including a divider;

FIG. 5 illustrates an exploded view of an exemplary container including a liner;

FIG. 6 illustrates the container of FIG. 1 with the lid removed and end panels raised in the horizontal shipping position;

FIG. 7 illustrates the container of FIG. 1 with the lid removed, end panels raised, and side panels collapsed in the collapsed position;

17

FIG. 8 illustrates an elevated perspective view of the container of FIG. 1 in a second collapsed configuration;

FIG. 9 illustrates a side view of the container of FIG. 8;

FIG. 10 illustrates an end view of the container of FIG. 8;

FIG. 11A illustrates another exemplary portable storage container in an expanded configuration;

FIG. 11B illustrates the portable storage container of FIG. 11A with section cut lines referenced in subsequent figures;

FIG. 12 illustrates an exploded view of the container of FIG. 11A showing the liner and divider;

FIG. 13 illustrates another exploded view of the container of FIG. 11A further showing the hoop and gasket;

FIG. 14 illustrates still another exploded view of the container of FIG. 11A with the liner removed;

FIG. 15 illustrates a top view of the container of FIG. 11A;

FIG. 16 illustrates a side view of the container of FIG. 11A in the expanded configuration;

FIG. 17 illustrates an end view of the container of FIG. 11A in the expanded configuration;

FIG. 18 illustrates a bottom view of the container of FIG. 11A;

FIG. 19 illustrates a view of the exemplary portable storage container of FIG. 11A in a collapsed configuration;

FIG. 20 illustrates a side view of the container of FIG. 19 in the collapsed configuration;

FIG. 21 illustrates an end view of the container of FIG. 19 in the collapsed configuration;

FIG. 22 illustrates an exemplary lid for the portable storage container of FIG. 11A;

FIG. 23 illustrates an end view of the lid of FIG. 22;

FIG. 24 illustrates an exemplary handle of the lid of FIG. 22;

FIG. 25 illustrates a side view of the lid of FIG. 22;

FIG. 26 illustrates a bottom view of the lid of FIG. 22;

FIG. 27 illustrates a sectional view of the portable storage container of FIG. 11B in the expanded configuration;

FIG. 28 illustrates a detail portion of FIG. 27 showing the divider and the lid;

FIG. 29 illustrates another detail portion of FIG. 27 showing the divider and the base;

FIG. 30 illustrates an exemplary hoop for the portable storage container of FIG. 11A;

FIG. 31 illustrates a side view of the hoop of FIG. 30;

FIG. 32 illustrates a bottom perspective view of a portion of the hoop of FIG. 30;

FIG. 33 illustrates a sectional view of the portable storage container of FIG. 11B showing the hoop and liner;

FIG. 34 illustrates an end view of an exemplary securing mechanism of the portable storage container of FIG. 11A;

FIG. 35 illustrates a rear perspective view of the securing mechanism of FIG. 34;

FIG. 36 illustrates a side view of the securing mechanism of FIG. 34;

FIG. 37 illustrates a sectional view of the securing mechanism of FIG. 34;

FIG. 38 illustrates an exemplary end panel of the portable storage container of FIG. 11A;

FIG. 39A illustrates a side view of the end panel in FIG. 11B;

FIG. 39B illustrates a detail portion of FIG. 39A;

FIG. 39C illustrates a bottom perspective view of the end panel of FIG. 38;

FIG. 40 illustrates a front view of an end portion of an exemplary base of the portable storage container of FIG. 11A;

18

FIG. 41 illustrates a rear view of an end portion of the base of FIG. 40;

FIG. 42 illustrates a sectional view of the portable storage container of FIG. 11B in the expanded configuration showing an exemplary locking member;

FIG. 43 illustrates a top sectional view of the portable storage container of FIG. 11B in the expanded configuration showing the internal storage area and handle;

FIG. 44 illustrates a top sectional view of the portable storage container of FIG. 11B in the expanded configuration showing the internal storage area and handle with the liner not pictured;

FIG. 45 illustrates a close up view of the portable storage container of FIG. 44 in the expanded configuration showing the handle and strap;

FIG. 46 illustrates the exemplary locking member of FIG. 42;

FIG. 47 illustrates a detail portion of FIG. 46 showing a portion of the locking member;

FIG. 48 illustrates the locking member of FIG. 46 showing the strap and base locking member;

FIG. 49 illustrates another view of the locking member of FIG. 46 showing the side locking member; and

FIG. 50 illustrates still another view of the locking member of FIG. 46 showing the base locking member.

DETAILED DESCRIPTION

FIG. 1 illustrates a portable storage container 100, illustratively a cooler, in accordance with the techniques and improvements disclosed herein. Although illustrated as a cooler, in other embodiments, the portable storage container 100 may be an insulated or non-insulated portable shipping or storage container.

Container 100 includes a body 110 and a lid 120. Body 110 provides an internal cavity, storage compartment, or storage area 102 (FIG. 4) which is accessible by removing lid 120 from body 110. Body 110 and/or lid 120 may be made from one or more plastics, metals, and/or natural materials. Body 110 and/or lid 120 may be molded, injection molded, roto-molded, pressure-formed, 3-D printed, machined, and/or stamped. Each of body 110 and lid 120 may comprise a single component or may be made of multiple components. Each of body 110 and lid 120 may also include insulation or one or more insulating elements, such as foam, expanding foam, closed cell foam, structural foam, spray foam, blanket materials, one more evacuated cavities, one more vacuum panels, or combinations thereof. In other embodiments, body 110 and/or lid 120 may not include any insulation or insulating elements.

Body 110 and/or lid 120 may be rigid or may contain portions that are flexible, bendable, soft, compliant, stretchable, and/or compressible. In some cases, one or more portions of container 100 may be partially or fully collapsible when not in use as described herein. Various portions of container 100 may be attached using one or more methods including sewing, gluing, adhesive, electro-welding, thermoplastic welding, co-molding, melting, and/or fasteners. One or more parts of container 100 may be waterproof, water-resistant, abrasion resistant, tear resistant, and/or puncture resistant.

Lid 120 may be fully removable from body 110 (as illustrated in FIGS. 4 and 5) or may be attached to body 110. Lid 120 is removably held in a closed position against body 110 using one or more latches, clasps, fasteners, clips, and/or levers, such as latches 150 (see FIGS. 1-3) or securing mechanism 180 (see FIG. 11A). Latches 150 and/or securing

19

mechanism **180** illustratively secure lid **120** by attaching to a corresponding groove **122** on lid **120**. Container **100** may also include one or more carrying handles **124** which may be integrated with or separate from latches **150** and/or securing mechanism **180**. Latches **150** and/or securing mechanism **180** may provide a closure that is waterproof, water-resistant, childproof, child resistant, animal proof, and/or animal resistant. Latches **150** and/or securing mechanism **180** may include one or more components made of plastic, metal, wood, ceramic, rubber, and/or silicone. Further, latches **150** and/or securing mechanism **180** may include a locking mechanism or may include an interface for use with one or more locks or access control devices, such as an electronic lock or a seal which indicates tampering. One or more gaskets or seals may be used between lid **120** and body **110**.

Referring to FIGS. 1-4, body **110** illustratively includes base **112** and an upper perimeter portion **114**. Base **112** forms at least a portion of the bottom surface of container **100**. Upper perimeter portion **114** illustratively extends around at least a portion of an upper perimeter of body **110**. Upper perimeter portion **114** is separated from base **112** with one or more end panels **116** and one or more side panels **118**. As shown in FIGS. 1-3, body **110** includes first and second end panels **116** at opposite ends of body **110** and first and second side panels **118** extending between the first and second end panels **116** along opposite sides of body **110**. Although end panels **116** are illustrated as having a shorter length than side panels **118** in FIGS. 1-3, in other embodiments end panels **116** and side panels **118** may have the same length, or end panels **116** may have a longer length than side panels **118**.

In some exemplary embodiments, container **100** has a first expanded configuration as illustrated in FIGS. 1-3 and a second collapsed configuration as illustrated in FIGS. 8-10. The height of the container **100** in the expanded configuration is greater than the height of the container **100** in the collapsed configuration. The interior volume of the container **100** in the expanded configuration is greater than the interior volume of the cooler in the collapsed configuration.

An upper portion of each end panel **116** is pivotably connected to upper perimeter portion **114** of body **110**. A lower portion of each end panel is releasably coupled to base **112** by an attachment mechanism **132**, such as by a snap or detente or other suitable mechanism (see FIG. 6). As described below with respect to FIGS. 6 and 7, this allows the lower portion of end panel **116** to be disconnected from the base **112** and the end panel **116** to rotate about upper perimeter portion **114** from the vertical storage position of end panels **116** illustrated in FIGS. 1-3 to a horizontal shipping position illustrated in FIGS. 8-10. As shown in FIGS. 8-10, in the shipping position, the end panels **116** are at least partially housed within a space defined by upper perimeter portion **114** of body **110**. Although the exemplary end panels **116** as illustrated in FIGS. 1-3 are pivotably connected the upper perimeter portion **114**, in other embodiments, one or more of the end panels **116** may instead pivotably connected to the base **112**, allowing end panel **116** to rotate to a horizontal shipping position in which the end panel **116** is positioned adjacent a portion of base **112**.

Each side panel **118** is illustratively formed from a lower side panel **118A** and an upper side panel **118B**. Each lower side panel **118A** is pivotably connected to the base **112** with one or more pins **138**. Each upper side panel **118B** is pivotably connected to the upper perimeter portion **114** with one or more pins **138**. Lower side panel **118A** and upper side panel **118B** are illustratively connected by a hinge **130**, such as a living hinge. As described below with respect to FIGS.

20

6 and 7, hinge **130** allows lower side panel **118A** to pivot with respect to upper side panel **118B**, bringing a portion of base **112** in closer proximity to a portion of upper perimeter portion **114**.

Referring to FIG. 4, in some embodiments, an internal wall or divider **140** may divide storage area **102** into two or more separate storage areas **102A** and **102B**. The storage area **102** may be bounded by one or more liners **148** (FIG. 5). Divider **140** may be insulated in addition to the outer walls and/or bottom of body **110** being insulated. Divider **140** is illustratively removably and slidably received by a pair of guides or slots **128** positioned in an interior of storage area **102**. It should be understood that although FIG. 4 illustrates a container **100** having two storage areas **102** separated by divider **140**, in other embodiments, container **100** has only a single storage area **102**, or has three or more storage areas **102**. Beneficially, different types of items with different requirements can be stored in each of the different storage areas. The requirements of the items may vary based on temperature requirements. In one example, one storage area may be used for frozen items, while the second is used for cold beverages. A grocery delivery company or meal kit company may place different products or ingredients and different compartments that best suit them for shipping. In other examples, one or more of the storage areas **102** may be used for items that preferably remain at room/neutral/outside temperature. In other examples, one or more of the storage areas **102** may be used for items that must be kept warm or hot relative to other items. In yet other examples, various storage areas **102** may be used for pharmaceuticals or other medical items that have different temperature requirements. The different storage areas **102** may also be used for items or groups of items that have varying level of sensitivity to humidity or water exposure.

Referring to FIG. 5, container **100** may include a liner **148** and a liner securing component or hoop **142** attaching the liner **148** to the body **110** of container **100**. Hoop **142** surrounds an upper perimeter of one or more interior storage areas **102**. Hoop **142** may include one or more grooves **146** for receiving divider **140**. Hoop **142** illustratively is removably secured to body **110** by snapping hoop **142** into a channel or recess **256** formed in an upper perimeter portion **114** of body **110** (see FIG. 33). Other suitable methods of securing hoop **142** to body **110** may also be used.

Liner **148** is illustratively formed from a bendable, and/or flexible material, such as a polymer or fabric. Beneficially, the bendable and/or flexible nature of liner **148** allows the liner to conform to the size of the storage area **102** when the container **100** is configured as illustrated in FIG. 1, and then be crushed, folded, squashed, or removed to allow the cooler to be configured as illustrated in FIG. 8. In some embodiments, liner **148** is water proof or water resistant, restricting the movement of fluid out of storage areas **102** and allowing for easier cleaning of container **100**. In some embodiments, liner **148** is removed and replaced in container **100** by removing hoop **142**, removing and discarding a first liner **148**, placing a second liner **148** into the interior of body **110**, and re-attaching hoop **142**. In other embodiments, liner **148** and hoop **142** are provided as a single unit that can be removed from body **110** and replaced with a corresponding new unit.

Referring next to FIGS. 6 and 7, the lid **120**, divider **140**, and liner **148** have been removed from the drawings to show details of the end panels **116** and side panels **118**.

In FIG. 6, the lower portion of end panels **116** have been released from the attachment mechanism **132** of base **112**. The end panels **116** are then rotated about pins **134** in upper

perimeter portion 114 until the end panels 116 are completely within a space defined by upper portion 114. As illustrated in FIG. 6, the end panels 116 may be locked in the upper position with a suitable snap or détente mechanism 136 between upper perimeter portion 114 and each end panel 116.

In FIG. 7, the hinge 130 is collapsed inward, causing each lower side panel 118A and upper side panel 118B to rotate about pins 138 and the outer surface of each lower side panel 118A to be moved adjacent to the outer surface of the corresponding upper side panel 118B. As illustrated in FIG. 7, the effect of this movement is to move the base 112 closer to the upper perimeter portion 114 of body 110, thereby decreasing the overall height of body 110. In the exemplary embodiment illustrated in FIG. 7, the lower edge of upper portion 114 is brought into contact with an upper edge of base 112, and the lower side panel 118A and upper side panel 118B are positioned completely within a space defined by upper perimeter portion 114 and/or base 112. In some embodiments, upper perimeter portion 114 is releasably secured or attached to base 112 with a suitable snap or détente mechanism.

Although not illustrated in FIGS. 6 and 7, divider 140 and liner 148 may be raised above the level of end panels 116 prior to rotating the end panels 116 into the upper position illustrated in FIG. 6. In some embodiments, at least a portion of divider 140 and liner 148 may be positioned in a space defined by lid 120.

Referring next to FIGS. 8-10, the container 100 is illustrated in a shorter, collapsed shipping position. Beneficially, the collapsed configuration illustrated in FIGS. 8-10 has a shorter height dimension than the taller, storage position illustrated in FIGS. 1-3. In some embodiments, the shorter height allows for more containers 100 to be stacked in a given space and/or to require less space for shipping. In some exemplary embodiments, divider 140 and/or liner 148 may be positioned within interior storage area 102 when the container 100 is in the collapsed configuration.

Referring next to FIGS. 11A-21, another exemplary storage container 100 is illustrated. The container 100 shown in FIGS. 11A-21 is similar to the container illustrated in FIGS. 1-10, and similar part numbers are used to indicate similar features. Those of ordinary skill in the art will recognize that any of the particular features described and/or illustrated may be implemented in combination with any other features described and/or illustrated herein.

As illustrated in FIGS. 11A-13, container 100 includes a body 110 and a lid 120. Lid 120 is removably attached to an upper perimeter portion 114 of body 120 through securing mechanism 180. Securing mechanism 180 is configured to secure the lid 120 in the closed position and maintain the container 100 in the expanded configuration when the container 100 is in the expanded configuration and secure the lid in the closed position and secure the container 100 in the collapsed configuration when the container 100 is in the collapsed configuration. The lid 120 is configured to selective close or permit access to the internal storage area 102 defined by the base 112, end panels 116, side panels 118, upper perimeter portion 114, and lid 120. In some exemplary embodiments, lid 120 includes insulation or one or more insulating elements.

As illustrated in FIG. 14, body 110 illustratively includes a base 112 and an upper perimeter portion 114 including a securing mechanism 180 for securing the body 110 to the lid 120. As described in more detail below, securing mechanism 180 may also serve to alternately secure the upper perimeter

portion 114 to either the end panel 116 or base 112 to secure the container 100 in either the expanded or collapsed configuration.

Body 110 further includes first and second opposing end panels 116 extending downwardly from upper perimeter portion 114. Each end panel 116 includes a pivoting connector 214, such as a circular or semi-circular end, to rotatably attach the end panel 116 to the upper perimeter portion 114 with one or more pins 134.

Body 110 further includes first and second opposing side panels 118, each including a lower portion 118A extending upwardly from the base 112 and an upper portion 118B extending downwardly from upper perimeter portion 114. Each lower portion 118A is rotatably attached to a corresponding upper portion 118B with a hinge 130, such as a living hinge. Each panel portion 118A, 118B includes a pivoting connector 214, such as a circular or semi-circular end, to rotatably attach the panel portion 118A, 118B to either the base or the upper perimeter portion 114 with one or more pins 138.

In the illustrative embodiments shown in FIGS. 12 and 13, container 100 further includes a removable divider 140 for dividing the interior storage area 102 of container into a first storage compartment 102A and a second storage compartment 102B when the container 100 is in the expanded configuration (see FIG. 27). In some exemplary embodiments, divider 140 is insulated. In some exemplary embodiments, the divider 140 may be positioned within one or more slots 168, 170 in a vertical dividing position when the container 100 is in the expanded configuration. In some exemplary embodiments, the divider 140 and/or liner 148 may be placed in a horizontal storage position within the interior storage area 102 when the container 100 is in the collapsed configuration.

In some exemplary embodiments, container 100 further includes a flexible liner 148 separating the interior storage area 102 from the body 110 of container 100. Liner 148 is attached to upper perimeter portion with hoop 142. Liner 148 includes a first surface 148A facing the internal storage area 102 of container 100 and a second opposing surface 148B facing at least one of the base 112, end panels 116, and side panels 118 (see FIG. 12). In some exemplary embodiments, the liner is liquid impermeable. In some exemplary embodiments, the liner has insulating characteristics. In some exemplary embodiments, the liner has anti-microbial properties.

In some embodiments, liner 148 is removably and/or replaceably attached to upper perimeter portion 114 with hoop 142. In other embodiments, liner 148 may be permanently attached to upper perimeter portion 114. Upper perimeter portion 114 and/or hoop 142 may include one or more gaskets 144 for sealing with lid 120 when lid is attached to body 110.

In some exemplary embodiments, one or more of base 112, upper perimeter portion 114, end panels 116, side panels 118, and lid 120 include insulation or one or more insulating elements, such as foam, expanding foam, closed cell foam, structural foam, spray foam, blanket materials, one more evacuated cavities, one more vacuum panels 108 (see FIG. 33), or combinations thereof. In some embodiments, each of base 112, upper perimeter portion 114, end panels 116, side panels 118, and lid 120 include insulation or one or more insulating elements. In other embodiments, body 110 and/or lid 120 may not include any insulation or insulating elements.

FIGS. 11A and 15-18 illustrate exemplary portable storage container 100 in a first, expanded configuration suitable

for storing items in an interior storage area **102** of container **100**. FIG. **11A** illustrates a perspective view of portable storage container **100** in the expanded configuration. FIG. **15** illustrates a top view of portable storage container **100** in the expanded configuration. FIG. **16** illustrates a side view of portable storage container **100** in the expanded configuration. FIG. **17** illustrates a front view of portable storage container **100** in the expanded configuration. FIG. **18** illustrates a bottom view of portable storage container **100** in the expanded configuration.

FIGS. **19-21** illustrate container **100** in a second, collapsed configuration suitable for shipping container **100**. The height of the container **100** in the expanded configuration is greater than the height of the container **100** in the collapsed configuration. The interior volume of the container **100** in the expanded configuration is greater than the interior volume of the container in the collapsed configuration. FIG. **19** illustrates a perspective view of the portable storage container **100** in the collapsed configuration. FIG. **20** illustrates a side view of the container **100** in the collapsed configuration. FIG. **21** illustrates a front view of the container **100** in the collapsed configuration. Although FIG. **15** illustrates the top view of container **100** and FIG. **18** illustrates the bottom view of the container **100** in the expanded configuration, it should be recognized that the corresponding top and bottom views in the collapsed configuration are similar.

The sides of container **100**, namely end panels **116** and side panels **118**, are movable between a first vertical storage position when the container is in the first expanded configuration, such as shown in FIG. **11A**, and a second horizontal shipping position (see FIG. **7**) when the container is in the second collapsed configuration, such as shown in FIG. **19**. In some embodiments, an attachment mechanism **132** of an upper portion of each end panel **116** is pivotably attached to an upper perimeter portion **114** of body **110** by pins **134** and side panel **118** is pivotably attached to upper perimeter portion **114** of body **110** by pins **138**. An additional attachment mechanism **132** of a lower portion of each side panel **118** is pivotably attached to a receiver **228** in the base **112** by a pin **138** (see FIG. **41**). To transition from the expanded configuration to the collapsed configuration, the end panels **116** are pivoted with respect to the upper perimeter portion **114** about the pins **134** to a substantially horizontal position (see FIG. **6**). Each of the lower side panels **118A** then pivots with respect to the base and each of the upper side panels **118B** pivots with respect to the upper perimeter portion **114** as the side panels **118** collapse about hinge **130** (see FIG. **7**), such that an external surface of the lower side panel **118A** is brought into contact with an external side surface of the upper side panel **118B** thereby placing side panels **118** into the collapsed position.

Referring next to FIGS. **22-26**, an exemplary lid **120** for container **100** is illustrated. FIG. **22** illustrates a perspective view of lid **120**. FIG. **23** illustrates a front view of lid **120**. FIG. **24** illustrates a portion of a handle **124** of lid **120**. FIG. **25** illustrates a side view of lid **120**. FIG. **26** illustrates a bottom view of lid **120**. Lid **120** is configured to close the internal storage area **102** of container **100** when the lid **120** is in a closed position, such as illustrated in FIGS. **11A** and **19**, and provides access to the internal storage area **102** when the lid is in an opened position. In some exemplary embodiments, lid **120** may include a lock, a tamper resistant or tamper-evident closure.

In the embodiment illustrated in FIG. **22**, an upper portion **166** of lid **120** includes shipping label area **126** for receiving a shipping label. In some exemplary embodiments, shipping

label area **126** includes a pouch or envelope for at least partially enclosing a shipping label. In some exemplary embodiments, shipping label area **126** has a substantially flat surface to which a shipping label can be adhered.

Lid **120** illustratively includes one or more handles **124**. As illustrated in FIGS. **22-24**, each handle extends outwardly from the upper portion **166** of lid **120**, providing a user with a convenient area for grasping container **100**. Handle **124** illustratively includes a lid locking portion **152** and lid locking groove **154** for receiving an upper locking lip **194** of upper locking portion **192** of securing mechanism **180** (see FIG. **37**).

As illustrated in FIG. **23**, lid **120** further includes a lower portion **156** attached to upper portion **166**. Lower portion **156** illustratively extends into the storage area **102** of container **100** when the lid **120** is coupled to the body **110** (see FIG. **27**).

In the exemplary embodiment illustrated in FIGS. **25** and **26**, lid **120** includes a plurality of compartments or receptacles **158** configured to receive one or more temperature control element, such as an ice pack, reusable cold pack, dry ice, or warming pack. The receptacles face the internal storage area **102** when the lid is in the closed position.

In some exemplary embodiments, the lid includes a plurality of shelves **160**, each configured to cover at least a portion of one of the receptacles **158**. The receptacles **158** are held in place by one or more tabs **162** on the bottom portion of lid **120**. Each shelf **160** is configured to hold or support the temperature control element positioned in the corresponding receptacle **158**. In other exemplary embodiments, the temperature control element may be directly attached to lid **120**, such as snapping into tabs **162** of lid **120**, or movable retaining element such as a screw or rotatable tab.

As illustrated in FIG. **26**, each shelf **160** includes a plurality of apertures **164** (not all apertures are numbered in FIG. **26**) allowing for convective air movement between the receptacle **158** and internal storage area **102**. As an example, air cooled by a cooling element such as an ice pack in receptacle **158** moves through the apertures **164** into the internal storage area **102** to cool the internal storage area **102**, while warmer air from internal storage area **102** moves through the apertures into the receptacle **158** where it is cooled by the cooling element positioned therein.

Referring next to FIGS. **27** and **28**, the lid **120** further includes one or more slots **168** separating adjacent receptacles **158**. As shown in FIG. **27**, lid **120** may include first and second slots **168A**, **168B** dividing lower portion **156** of lid **120** into three receptacles **158**. In other embodiments, lid **120** may include more or fewer slots **168** and lower portion **156** may be divided into more or fewer receptacles **158**. Each slot **168** is configured to receive an upper edge of divider **140** to divide internal storage area **102** into a first portion **102A** and a second portion **102B**. In some exemplary embodiments, the upper perimeter portion **114** and/or one or more side panels **118** also include a slot **128** (see FIG. **4**) to further secure the divider **140** in place.

In some exemplary embodiments, at least one of liner **148** and body **110** includes slots **128** at least partially extending around installed divider **140** to support the container **100** in the expanded configuration.

Referring next to FIGS. **27** and **29**, at least one of the base **112**, the liner **148**, and the handle **230** includes one or more slots **170** proximate the base **112** and corresponding to and substantially vertically aligned with each of the slots **168** for divider **140** in lid **120**. As illustrated in FIG. **29**, in some embodiments, the slots **170** may be formed in a handle **230**

25

attached to the liner 148. In other exemplary embodiments, the slots 170 may be formed directly in an inner surface of the base 112 and/or the inner surface 148A of liner 148. As shown in FIG. 27, first and second slots 170A, 170B may be provided. In other embodiments, more or fewer slots 170 may be provided. Each slot 170 is configured to receive a lower edge of divider 140 to divide internal storage area 102 into a first portion 102A and a second portion 102B. In some exemplary embodiments, one or more side panels 118 may also include a slot 170 to further secure the divider 140 in place.

As illustrated in FIG. 27, positioning divider 140 into the slot 168A and slot 170A as shown results in a first storage area portion 102A associated with first receptacle 158A and second receptacle 158B, and a second storage area portion 102B associated with third receptacle 158C. Similarly, positioning divider 140 into the slot 168B and slot 170B would result in a first storage area portion associated with first receptacle 158A and a second storage area portion associated with second receptacle 158B and third receptacle 158C. Positioning a first divider 140 into slot 168A and 170A and a second divider 140 (not shown) into slot 168B and 170B would result in a first storage area portion associated with first receptacle 158A, a second storage area portion associated with second receptacle 158B, and a third storage area portion associated with third receptacle 158C.

In some exemplary embodiments, it may be desirable to thermally isolate adjacent first portion 102A and second portion 102B of internal storage area 102. In these embodiments, a first temperature control element may be placed in first receptacle 158A to maintain the first portion 102A at a first temperature and a second temperature control element may be placed in second receptacle 158B to maintain the second portion 102B at a second temperature that is different than the first temperature. In one embodiment, the first temperature control element is dry ice and the second temperature control element is an ice pack or reusable cold pack to maintain a first temperature that is colder than the second temperature.

In some exemplary embodiments, slots 128 form a seal with an insulated divider 140 to thermally isolate adjacent first portion 102A and second portion 102B of internal storage area 102. In some exemplary embodiments, divider 140 is formed as a part of liner 148 to thermally isolate adjacent first portion 102A and second portion 102B of internal storage area 102.

Each slot 168 in the lid 120 and/or side panels 118, as well as each slot 170 in the handle 230 or base 112 illustratively acts as a divider 140 positioning feature to maintain the position of divider 140 within the internal storage area 102. When positioned one or more slots 168, 170, divider 140 supports the shape of container 100.

Referring next to FIGS. 30-32, an illustrative hoop 142 for securing the liner 148 in the internal storage area 102 is illustrated. As shown in FIGS. 30 and 31, the hoop 142 has a plurality of sides forming a continuous perimeter and includes an upper perimeter portion 174 and a lower perimeter portion 176. In some embodiments, an upper surface of the upper perimeter portion 174 includes a channel 178 for receiving a gasket 144 to seal the body 110 to the lid 120 when the lid 120 is in the closed position.

As shown in FIG. 32, the lower perimeter portion 176 of hoop 142 includes a connecting portion 264 extending downwardly from the upper perimeter portion 174. The connecting portion 264 is flexibly attached to a securing portion 266 by an intermediate portion 268. Securing por-

26

tion 266 includes a plurality of projections that each extend substantially upward in relation to the intermediate portion 268.

In some exemplary embodiments, the intermediate portion 268 has a thinner cross sectional area relative to the connecting portion 264 and/or securing portion 266, allowing the securing portion 266 to flex about the intermediate portion 268 relative to the securing portion 266. In one exemplary embodiment, the flexible intermediate portion 268 biases the securing portion 266 at an angle to the vertical connecting portion 264 in a direction towards the exterior surface of the container 100 when the hoop 142 is installed in the upper perimeter portion 114. In some exemplary embodiments, the connecting portion 264 and the securing portion 266 have substantially similar cross-sectional areas.

In some embodiments, the lower perimeter portion 176 is formed by molding the hoop 142 out of a plastic material such that the connecting portion 264, intermediate portion 268, and securing portion 266 form a substantially straight line. While the hoop 142 is warm, the securing portion 266 is then pushed upward to be almost parallel with the connecting portion 264 and the hoop 142 is cooled. The resulting strain in the intermediate portion 268 provides an outward biasing force to the securing portion 266.

Referring next to the cross-section illustrated in FIG. 33, the upper perimeter portion 114 includes an internal lip 254 extending in a direction towards the internal storage area 102 of container 102. An edge region 172 of liner 148 extends up an inner surface 258 of the upper perimeter portion 114, over the lip 254, and onto the top surface 262 of the upper perimeter portion 114. The hoop 142 is then positioned within a channel or recess 256 on the top surface 262 of the upper perimeter portion. Hoop 142 may include a channel or recess 178 for receiving gasket 144. In one exemplary embodiment, gasket 144 is secured in recess 178 by a friction fit or adhesive. In another exemplary embodiment, gasket 144 is secured to lid 120 and received within recess 178 when the lid is in the closed position.

As the hoop 142 is positioned, the securing portion 266 of the hoop 142 is compressed by the lip 254 towards the connecting portion 264. After the distal end 272 of the securing portion 266 passes the lip 254, the securing portion 266 is compressed against the liner 148, exerting a force through the liner 148 against the inner surface 258 of the upper perimeter portion. The hoop 142 is maintained in position by the distal end 272 of the securing portion 266, which is prevented from moving upward by the lip 254. In some embodiments, the hoop 142 provides a force on two, three, or four sides of the upper perimeter portion 114 to secure the liner 148 in place. In some exemplary embodiments, the thinner intermediate portion 268 is configured to break if a strong enough upward force is exerted on the hoop 142, allowing hoop 142 and liner 148 to be removed from the interior storage area 102 of the container 100.

In some embodiments, the container 100 is assembled by providing the base, upper perimeter portion 114, end panels 116, and side panels 118. The liner 148 is inserted into the internal storage area 102 of the body 110, covering the internal lip 254 of the upper perimeter portion 114. The hoop 142 is then received within the recess 256 in the upper perimeter portion 114, such that the outer surface 270 of securing portion 266 exerts a force through the liner 148 against the upper perimeter portion to secure the liner 148 in place. The hoop 142 is retained in position by the distal end 272 of the securing portion 266 abutting the internal lip 254 of the upper perimeter portion 114.

Referring next to FIGS. 34-36, an exemplary securing mechanism 180 is illustrated. FIG. 34 illustrates a front view of the securing mechanism 180. FIG. 35 illustrates a rear perspective view of the securing mechanism 180. FIG. 36 illustrates a side view of the securing mechanism.

In some embodiments, securing mechanism 180 includes a rotating portion 186 which rotates about a rotation post 190 secured to upper perimeter portion 114. Rotating portion 186 is configured to be rotatable between a locked position in which securing mechanism 180 is releasably coupled to one or more of base 112, end panel 116, and lid 120, and an unlocked position in which securing mechanism 180 is not releasably coupled to one or more of base 112, end panel 116, and lid 120. Rotating portion 186 rotates clockwise and counterclockwise about post 190 between the locked position and unlocked position within a circular recess 212 formed in the outer perimeter surface 210 of upper perimeter portion 114.

As shown in FIGS. 34 and 37, securing mechanism 180 includes a locking button 182 received within a recess 274 in rotating portion 186. Button 182 is illustratively movable between the extended position as illustrated in FIG. 37, and a depressed position. A biasing member, such as a spring 184, biases the button 182 in the extended position. As shown in FIG. 37, when the rotating portion 186 is in the locked position, the button can move between the extended position and the depressed position. In the extended position, the button 182 partially extends into the recess 274 of the rotating portion 186, preventing the rotating portion from rotating out of the locked position. A user can apply a force to the button 182 to overcome the force of spring 184 and move button 182 from the extended position to a depressed position in which the button 182 is moved behind a back surface 188 of rotating portion 186, allowing rotating portion 186 to rotate from the locked position to the unlocked position.

Rotating portion 186 includes an upper locking portion 192 for releasably coupling a corresponding lid locking portion 152 of lid 120 (see FIG. 23). As illustrated in FIGS. 35 and 36, upper locking portion 192 includes an upper locking lip 194. Upper locking lip 194 is configured to be received within groove 154 of lid locking portion 152 of lid 120 (see FIG. 24). As illustrated in FIG. 37, when locking lip 194 is received within groove 154 of lid locking portion 152, the upper locking portion 192 prevents movement of the lid 120 relative to the securing mechanism 180, thereby releasably and removably securing the lid 120 to the body 110 of container 100.

Rotating portion 186 includes a lower locking portion 196 for releasably coupling either a corresponding panel locking portion 200 positioned on end panel 116 (see FIG. 38) when the container 100 is in the expanded configuration or a corresponding base locking portion 204 positioned on base 112 (see FIG. 40) when the container is in the collapsed configuration. As illustrated in FIG. 36, lower locking portion 196 includes a lower locking lip 198.

When container 100 is in the expanded configuration (see FIG. 11A), lower locking lip 198 is configured to be received within groove 202 of panel locking portion 200 of end panel 116 (see FIG. 24). As illustrated in FIG. 37, when locking lip 198 is received within groove 202 of panel locking portion 200, the lower locking portion 196 prevents movement of the end panel 116 relative to the securing mechanism 180, thereby securing the end panel 116 in the vertical storage position and the container 100 in the expanded configuration.

When container 100 is in the collapsed configuration (see FIG. 19), lower locking lip 198 is configured to be received within groove 206 of base locking portion 204 of base 112 (see FIG. 40). When locking lip 198 is received within groove 206 of base locking portion 204, the lower locking portion 196 prevents movement of the base relative to the securing mechanism 180, thereby securing the container 100 in the collapsed configuration. As shown in FIG. 40, base 112 may further include a base locking guard 208 extending from the bottom of base 112. Guard 208 illustratively protects lower locking lip 198 to prevent securing mechanism 180 being inadvertently moved from a locked position to an unlocked position, such as during shipping of container 100.

In some exemplary embodiments, rotating the rotating portion 186 of securing mechanism 180 between the locked and unlocked positions moves the upper locking lip 194 of upper locking portion 192 from a locked position within the groove 154 of lid locking portion 152 to an unlocked position not within the groove 154, and simultaneously moves the lower locking lip 198 of lower locking portion 196 from a locked position within either the groove 202 of panel locking portion 200 or the groove 206 of base locking portion 204 to an unlocked position not within either groove 202 or 206. In some exemplary embodiments, the post 190, upper locking lip 194, and lower locking lip 198 are positioned in a substantially straight line. In some exemplary embodiments, the post 190, upper locking lip 194, lower locking lip 198, and button 182 are positioned in a substantially straight line.

As illustrated in FIGS. 14, 16, and 20, in some exemplary embodiments the container 100 includes two or more securing mechanisms 180. As shown in FIG. 14, the container 100 includes a first securing mechanism 180 positioned on a front side of upper perimeter portion 114 and configured to releasably engage a first lid locking portion 152 positioned on a front side of lid 120 and either a first panel locking portion 200 positioned on a front end panel 116 when the container 100 is in the expanded configuration (see FIG. 16) or a first base locking portion 204 positioned on a front side of base 112 when the container 100 is in the collapsed configuration (see FIG. 20). Container 100 is illustrated as also including a second securing mechanism 180 positioned on an opposite back side of upper perimeter portion 114 and configured to releasably engage a second lid locking portion 152 positioned on a back side of lid 120 and either a second panel locking portion 200 positioned on a back end panel 116 when the container 100 is in the expanded configuration (see FIG. 16) or a second base locking portion 204 positioned on a back side of base 112 when the container 100 is in the collapsed configuration (see FIG. 20).

Referring next to FIGS. 38, 39A, 39B, and 39C, an exemplary end panel 116 is illustrated. End panel 116 includes pivoting connectors 214 configured to rotatably connect end panel 116 to a receiver 228 in upper perimeter portion 114 with a pin 134. In some exemplary embodiments, each pivoting connector 214 has a substantially circular or semi-circular aperture for receiving pin 134. End panel 116 further includes a panel locking portion 200 on an outer surface 216. Panel locking portion 200 includes a groove 202 for receiving the lower locking lip 198 of securing mechanism 180. When the locking lip 198 is received within groove 202, the securing mechanism 180 resists the end panel 116 from rotating about the pivoting connectors 214 to move from the vertical storage position in

the expanded configuration of container 100 to the horizontal shipping position in the collapsed configuration of container 100.

As shown in FIG. 39C, in some exemplary embodiments the outer surface 216 of end panel 116 further includes locking latches 224. Each locking latch 224 is configured to be received within a corresponding recessed lip 226 of base 112 (see FIGS. 41 and 49). Each locking latch 224 is illustratively formed from a resilient or flexible material, such that the locking latch 224 deforms slightly as it is received within the corresponding recessed lip 226, and then locks the motion of end panel 116 with respect to base 112. Upon an application of a large enough force, the locking latch 224 again deforms and is released from the recessed lip 226, allowing movement of end panel 116 relative to base 112.

In some exemplary embodiments, a release mechanism 250 including a locking latch 220 is formed on a bottom surface 218 of end panel 116. Locking latch 220 is illustratively attached to the bottom surface 218 end panel 116 by a biasing member 246, and is moveable between a down, locked or latched position engaging a corresponding channel 222 in base 112 and an up, unlocked or unlatched position disengaging the channel 222 (see FIG. 41). In the exemplary embodiment illustrated in FIG. 39C, locking latch 220 is attached to a central portion of biasing member 246, while each end portion 252 of the biasing member is secured to the bottom surface 218 of end panel 116. In some exemplary embodiments, the biasing member is a spring biasing the locking latch 220 in a down, locked position.

Locking latch 220 is illustratively received within a recess or channel 222 formed in base 112 (see FIG. 41) when locking latch 220 is in the locked position. As shown in FIG. 50, when locking latch 220 is in the locked position, channel 222 prevents locking latch 220 and the entire end panel 116 from moving relative to the base 112, thereby securing end panel 116 in the vertical storage position and container 100 in the expanded configuration. When locking latch 220 is moved from the locked position to the unlocked position, locking latch 220 clears the lip of channel 222, allowing end panel 116 to rotate from the vertical storage position to the horizontal shipping position, and thereby allowing container 100 to be placed in the collapsed configuration.

Referring next to FIG. 43, a top view of container 100 with lid 120 removed is shown. FIG. 44 shows a sectional top view of the interior storage area 102 with the liner 148 not shown. FIG. 45 illustrates a side sectional view of the container 100 showing the handle 230 attached to the biasing member 246 and locking latch 220.

Handle 230 is accessed through the internal storage area 102 with the lid 120 removed. In some exemplary embodiments, handle 230 includes a grasping portion 232 extending above the surface of liner 148 and configured to be grasped by a user. The grasping portion 232 extends between end portions 234. The handle 230 may include one or more slots 170 for receiving divider 140. Each end portion 234 is illustratively attached to the liner 148.

In one exemplary embodiment, the end portion 234 is attached to a strap 240 extending below the liner 148 by an anchor 236 coupled to both the end portion 234 and the strap 240 and extending through liner 148. In some exemplary embodiments, strap 240 is detachable from liner 148 and/or biasing member 246.

In another exemplary embodiment (see FIG. 45), the end portion is attached to an anchor 236 that is attached to the inner surface 148A of liner 148, such as with a layer of suitable adhesive 238. The portion 242 of strap 240 under

handle 230 is attached to the outer surface 148B of liner 148, such as with a layer of suitable adhesive 238. The inner surface 148A and outer surface 148B are continuous in the area of the liner proximate the handle 230, such that the liner is not pierced, punctured, or otherwise transversely by the attachment of the handle 230 to the strap 240.

As illustrated in FIG. 44, the handle 230 is operably coupled to a first biasing member 246 and first locking latch 220 on a front end panel 116 and a second biasing member 246 and second locking latch 220 on a back end panel 116 opposite the front end panel 116.

Referring next to FIGS. 42, 46, 47, and 48, a sectional view of body 110 and end panel 116 is illustrated. A lower portion of end panel 116 includes an aperture or slot 248 providing access to biasing member 246 from the internal storage area 102 of body 110. Strap 240 includes a portion 244 extending away from the handle 230 and the internal storage area 102 through slot 248 and engages biasing member 246 at a position below that of slot 248. When handle 230 is moved in a direction away from base 112, strap 240 pulls biasing member 246 in an upward direction towards slot 248 to move locking latch 220 from the locked position to an unlocked position. In some exemplary embodiments slot 248 does not permit biasing member 246 to pass into slot 248, transferring additional force and/or movement from the strap 240 to a lower portion of end panel 116.

With the container 100 in the expanded configuration, the button 182 of securing mechanism 180 is moved to the depressed position and the rotating portion 186 of securing mechanism 180 is moved from the locked position to the unlocked position, such that the lower locking lip 196 is not positioned within the panel locking groove 202. With the lid 120 removed, the handle 230 is configured such that as the handle 230 is moved, the strap 240 extending through the slots 248 in each end panel 116 exerts a force on the locking latch 220. Once the force overcomes the downward force of the biasing member 246, the locking latch 220 moves from the locked position to the unlocked position. Continued movement of the handle in a direction away from the base 112 results in the strap 240 continuing to pull both of the end panels 116 from a region near bottom surface 218, resulting in the locking latches 224 deforming and releasing from the recessed lips 226 of base 112, and each panel 116 moving from the vertical storage position to the horizontal shipping position. The panels 116 may be secured in the horizontal shipping position with one or more snap/détente 136. The hinge 130 of each side panel 118 is then collapsed inward, causing each lower side panel 118A and upper side panel 118B to rotate about pins 138 and the outer surface of each lower side panel 118A to be moved adjacent to the outer surface of the corresponding upper side panel 118B. The lid 120 may then be replaced on the body 110, and the rotating portion 186 of securing mechanism 180 is rotated back to the locked position until the spring 184 returns the button 182 to the extended position, the lower locking lip 198 is received within base locking groove 206, and the upper locking lip 194 is received within the lid locking groove 154, thereby securing the container 100 in the collapsed configuration.

With the container 100 in the collapsed configuration, the button 182 of securing mechanism 180 is moved to the depressed position and the rotating portion 186 of securing mechanism 180 is moved from the locked position to the unlocked position, such that the lower locking lip 196 is not positioned within the panel locking groove 202 and upper locking lip 194 is not positioned within the lid locking groove 154. The lid 120 may be removed, and the hinge 130

of each side panel **118** is expanded, causing each lower side panel **118A** and upper side panel **118B** to rotate about pins **138** and the outer surface of each lower side panel **118A** to be moved substantially continuous to the outer surface of the corresponding upper side panel **118B** to form an outer surface of the side **260**. The end panels **116** are then pivoted downwardly with respect to the upper perimeter portion from the horizontal shipping position to the vertical storage position. The locking latch **220** of each end panel **116** is received within the corresponding channel **222** in the base **112**, and locking latches **224** are received within the corresponding recessed lips **226** of the base **112**. The biasing member moves the locking latch **220** to the locked position. The liner **148** may be pushed into the storage area **102** until the outer surface **148** contacts the base **112**. The lid **120** may then be replaced on the body **110**, and the rotating portion **186** of securing mechanism **180** is rotated back to the locked position until the spring **184** returns the button **182** to the extended position, the lower locking lip **198** is received within panel locking groove **202**, and the upper locking lip **194** is received within the lid locking groove **154**, thereby securing the container **100** in the expanded configuration.

In addition to the primary internal storage areas or compartments, container **100** may also include one or more other storage areas, storage pockets, or storage compartments for carrying other items. Container **100** may also include one or more other accessories, such as a rechargeable battery, a solar cell, a light, a liquid storage bladder, a first aid kit, a toolkit, and/or one or more thermometers for indicating temperature of one or more of the storage areas. In some configurations, one or more of the additional pockets, storage compartments, and/or dry storage areas may be on an interior surface of container **100**.

In addition, container **100** may include one or more powered cooling or heating units for assisting in keeping items cold or warm, respectively, before transport, after delivery, and/or for some portion of the shipping process. In other words, the features disclosed herein may be supplemented by a powered cooling or heating unit when power is available and container **100** can be attached to the power source. In further examples, container **100** may include one or more contained power sources, such as a battery or solar panel, for temporarily providing power to the cooling or heating unit without tethering it to a power source.

Container **100** may also include one or more attachment areas or attachment points for removably attaching one or more accessories or other items to container **100**. Attachment points may include any of a variety of attachment mechanisms, structures, elements, or features including any described in U.S. patent application Ser. No. 15/398,468, filed Jan. 4, 2017, which is hereby incorporated by reference in its entirety.

Any of the techniques, improvements, features, functions, or processes described herein may be implemented in the form of a system or a kit. The system or kit may include any combination of the devices, components, elements, and/or modules disclosed herein.

The elements, components, and steps described herein are meant to exemplify some types of possibilities. In no way should the aforementioned examples limit the scope of the invention, as they are only exemplary embodiments.

The phrases “in some embodiments,” “in an exemplary embodiment,” “in one exemplary embodiment,” “in some exemplary embodiments,” “according to some embodiments,” “in the embodiments shown,” “in other embodiments,” “in some examples,” “in other examples,” “in some cases,” “in some situations,” “in one configuration,” “in

another configuration,” and the like generally mean that the particular technique, feature, structure, or characteristic following the phrase is included in at least one embodiment of the present invention and/or may be included in more than one embodiment of the present invention. In addition, such phrases do not necessarily refer to the same embodiments or to different embodiments.

The foregoing disclosure has been presented for purposes of illustration and description. Other modifications and variations of the disclosed techniques may be possible in view of the above teachings. The embodiments described in the foregoing disclosure were chosen to explain the principles of the concept and its practical application to enable others skilled in the art to best utilize the invention. It is intended that the claims be construed to include other alternative embodiments of the invention, except as limited by the prior art.

What is claimed is:

1. A collapsible shipping container having a first configuration and a second configuration, the collapsible shipping container comprising:

an insulated base;

an upper perimeter portion including one or more securing mechanisms;

a plurality of insulated side panels extending between the upper perimeter portion and the base, each of the plurality of the insulated side panels being movable between a respective first position and a respective second position, wherein the collapsible shipping container is in the first configuration when all of the insulated side panels are in the respective first positions and wherein the collapsible shipping container collapses into the second configuration when all of the side panels are in the respective second positions, the collapsible shipping container having a height in the first configuration that is greater than a height of the collapsible shipping container in the second configuration; and

an insulated lid removably attachable to the upper perimeter portion for selectively closing and accessing an internal storage volume of the collapsible shipping container, the internal storage volume defined by the insulated base, the plurality of insulated side panels, the upper perimeter portion, and the insulated lid;

wherein each of the one or more securing mechanisms of the upper perimeter portion is configured to removably secure a lower edge of the upper perimeter portion to the insulated base when the collapsible shipping container is in the second configuration and also configured to removably secure the insulated lid to an upper edge of the upper perimeter portion in both the first and the second configurations.

2. The collapsible shipping container of claim **1** wherein the insulated lid includes one or more receptacles for receiving an ice pack and one or more shelves for retaining the ice pack, each shelf including one or more convection apertures.

3. The collapsible shipping container of claim **1** wherein each of the one or more securing mechanisms includes a rotating portion configured to rotate between a locked position and an unlocked position.

4. The collapsible shipping container of claim **3** wherein the rotation of each of the one or more securing mechanisms to the locked position simultaneously captures locking portions of each of the insulated base and the insulated lid when the collapsible shipping container is in the second configuration.

5. The collapsible shipping container of claim 4 wherein each of the one or more securing mechanism includes a spring loaded lock button.

6. The collapsible shipping container of claim 1 further comprising a latching mechanism for temporarily maintain- 5 ing the collapsible shipping container in the first configuration, wherein the latching mechanism latches at least two of the insulated side panels in the respective first positions to temporarily maintain the collapsible shipping container in the first configuration. 10

7. The collapsible shipping container of claim 6 further comprising a flexible liner attached to the upper perimeter portion and configured to line the internal storage volume, the flexible liner having a first surface facing the internal storage volume and a second surface facing at least one of 15 the insulated base and the insulated side panels.

8. The collapsible shipping container of claim 7 where the flexible liner includes a handle attached to the first surface, the handle accessible from inside the internal storage volume. 20

9. The collapsible shipping container of claim 8 further comprising a strap attached to the second surface of the flexible liner and to the latching mechanism, wherein the strap disengages the latching mechanism when the handle of the flexible liner is pulled from inside the internal storage 25 volume, the disengaging of the latching mechanism permitting the collapsible shipping container to transition from the first configuration to the second configuration.

10. The collapsible shipping container of claim 9 wherein a force applied to the strap disengages the latching mechanism. 30

11. The collapsible shipping container of claim 9 wherein the strap is attached to the flexible liner without piercing the flexible liner, the strap is detachable from the flexible liner, and the flexible liner is removable from the collapsible 35 shipping container.

12. The collapsible shipping container of claim 1 wherein one or more of the base, the side panels, and the lid include a vacuum insulated panel.

13. A collapsible shipping container having an expanded 40 configuration and a collapsed configuration, the collapsible shipping container comprising:

a base;

an upper portion including at least one securing mechanism; 45

a plurality of side panels extending between the upper portion and the base, wherein each of the plurality of the side panels is adapted to hinge between a respective first position and a respective second position, wherein the collapsible shipping container is in the expanded 50 configuration when all of the side panels are in the respective first positions, wherein the collapsible ship-

ping container collapses into the collapsed configuration when all of the side panels are in the respective second positions, and wherein the collapsible shipping container has a height in the expanded configuration that is greater than a height of the collapsible shipping container in the collapsed configuration; and

a lid removably attachable to the upper portion for selectively closing and accessing an internal storage volume of the collapsible shipping container, the internal storage volume defined by the base, the plurality of side panels, the upper portion, and the lid;

wherein the at least one securing mechanism of the upper portion is adapted to simultaneously secure both the base and the lid to the upper portion when the collapsible shipping container is in the collapsed configuration and further adapted to secure the lid to the upper portion when the collapsible shipping container is in the expanded configuration.

14. The collapsible shipping container of claim 13 further comprising a latching mechanism for temporarily maintain- 20 ing the collapsible shipping container in the expanded configuration, wherein the latching mechanism is adapted to hold at least two of the side panels in the respective first positions to temporarily maintain the collapsible shipping container in the expanded configuration. 25

15. The collapsible shipping container of claim 14 further comprising a flexible liner attached to the upper portion lining the internal storage volume, wherein the flexible liner includes a first surface facing the internal storage volume and a second surface facing at least one of the base and the side panels, and wherein the flexible liner includes a handle 30 attached to the first surface, the handle being accessible from inside the internal storage volume.

16. The collapsible shipping container of claim 15 further comprising a strap attached to the second surface of the flexible liner and to the latching mechanism, wherein the strap disengages the latching mechanism when the handle of the flexible liner is pulled, the disengaging of the latching mechanism permitting the collapsible shipping container to 35 transition from the expanded configuration to the collapsed configuration.

17. The collapsible shipping container of claim 16 wherein the strap is attached to the flexible liner without piercing the flexible liner, the strap is detachable from the flexible liner, and the flexible liner is removable from the collapsible shipping container. 45

18. The collapsible shipping container of claim 13 further comprising a gasket between the lid and the upper portion.

19. The collapsible shipping container of claim 13 wherein two or more of the plurality of side panels each includes a first portion hingedly attached to a second portion. 50

* * * * *