

US011302160B2

(12) **United States Patent**  
**Cornell et al.**

(10) **Patent No.:** **US 11,302,160 B2**  
(45) **Date of Patent:** **\*Apr. 12, 2022**

(54) **SYSTEMS AND METHODS FOR ARTIFICIAL INTELLIGENCE (AI) THEFT PREVENTION AND RECOVERY**

(58) **Field of Classification Search**  
None  
See application file for complete search history.

(71) Applicant: **The Travelers Indemnity Company,**  
Hartford, CT (US)

(56) **References Cited**

(72) Inventors: **Scott Cornell,** Peoria, AZ (US);  
**Ernesto Jaramillo,** Avon, CT (US);  
**Oleg M. Kirshon,** West Hartford, CT  
(US); **Prabir Das,** Ellington, CT (US);  
**Yamiel L. Zea,** Hartford, CT (US);  
**Lauren C. Berry,** Canton, CT (US)

U.S. PATENT DOCUMENTS

7,253,731	B2	8/2007	Joao
7,482,920	B2	1/2009	Joao
7,610,210	B2	10/2009	Helitzer et al.
7,711,584	B2	5/2010	Helitzer et al.
7,945,105	B1	5/2011	Jaenisch
8,271,303	B2	9/2012	Helitzer et al.
8,515,788	B2	8/2013	Tracy et al.
8,731,978	B2	5/2014	Tracy et al.
9,847,029	B2	12/2017	Joao
10,134,205	B2	11/2018	Arena

(Continued)

(73) Assignee: **The Travelers Indemnity Company,**  
Hartford, CT (US)

FOREIGN PATENT DOCUMENTS

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

WO WO-2017178712 A1 \* 10/2017 ..... G06N 20/00

This patent is subject to a terminal disclaimer.

OTHER PUBLICATIONS

(21) Appl. No.: **16/951,810**

O'Connell, John, "Marine Cargo Security", Risk Management 51.3 (Mar. 2004), pp. 1-5; 5 pps.

(22) Filed: **Nov. 18, 2020**

(Continued)

(65) **Prior Publication Data**

US 2021/0118274 A1 Apr. 22, 2021

**Related U.S. Application Data**

(63) Continuation of application No. 16/655,529, filed on Oct. 17, 2019, now Pat. No. 10,854,055.

*Primary Examiner* — Stefan Gadomski

(74) *Attorney, Agent, or Firm* — RowanTree Law Group, PLLC; Carson C. K. Fincham


(51) **Int. Cl.**  
**G08B 13/194** (2006.01)  
**G08B 3/10** (2006.01)  
**G06K 9/00** (2006.01)

(57) **ABSTRACT**

Systems, apparatus, methods, and articles of manufacture for Artificial Intelligence (AI) theft prevention and recovery, such as by utilizing image object analysis to identify and report pilfering-type cargo or materials theft events.

(52) **U.S. Cl.**  
 CPC ..... **G08B 13/194** (2013.01); **G06K 9/00771** (2013.01); **G08B 3/1016** (2013.01)

**15 Claims, 14 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

10,152,876 B2 12/2018 Joao  
 10,181,109 B2 1/2019 Joao  
 10,262,410 B2 4/2019 Chen  
 2005/0038682 A1 2/2005 Gandee et al.  
 2005/0049962 A1 3/2005 Porter et al.  
 2005/0055248 A1 3/2005 Helitzer et al.  
 2005/0055249 A1 3/2005 Helitzer et al.  
 2006/0036473 A1 2/2006 Taylor  
 2008/0065427 A1 3/2008 Helitzer et al.  
 2009/0265193 A1 10/2009 Collins et al.  
 2010/0036783 A1 2/2010 Rodriquez  
 2010/0106533 A1 4/2010 Alvarez  
 2010/0153140 A1 6/2010 Helitzer et al.  
 2010/0174566 A1 7/2010 Helitzer et al.  
 2011/0137685 A1 6/2011 Tracy et al.  
 2013/0078968 A1 3/2013 Breed  
 2014/0036072 A1 2/2014 Lyall  
 2016/0180186 A1 6/2016 Sun  
 2016/0189087 A1 6/2016 Morton  
 2017/0161586 A1 6/2017 Xu  
 2017/0313269 A1 11/2017 Breed  
 2018/0052462 A1 2/2018 Arena  
 2018/0130016 A1 5/2018 Arena  
 2018/0247262 A1 8/2018 Arena  
 2018/0249130 A1 8/2018 Arena  
 2018/0255443 A1 9/2018 Arena  
 2018/0300675 A1 10/2018 Arena  
 2018/0308045 A1 10/2018 Arena  
 2018/0339865 A1 11/2018 Schroader

2018/0352198 A1 12/2018 Raasch  
 2019/0130351 A1 5/2019 Arena  
 2019/0132714 A1 5/2019 Arena  
 2020/0074402 A1 3/2020 Adato  
 2020/0128226 A1 4/2020 Krishnamurthy

OTHER PUBLICATIONS

Purtell, Dan et al. "Assessing Cargo Supply Risk", Security Management 50.11 (Nov. 2006), pp. 78, 80, 82-84, 86-87; 5 pps.  
 Drake, David, "Taking the Guesswork Out of Managing Cargo Supply Risk", National Underwriter Property Casualty/risk & benefits management ed. 108.6, (Feb. 16, 2004), pp. 18-19; 2 pps.  
 Ojasalo, Jukka, "A Model of Risk Management in Globalizing Companies", The Business Review, Cambridge, 13.1 (Summer 2009), pp. 200-209; 2 pps.  
 Morton, Roger, "Keep Product from wandering off", Transportation & Distribution, 40.6 (Jun. 1999), pp. 84-88. 37 pps.  
 Notice of Allowance for U.S. Appl. No. 13/927,402 dated Jan. 6, 2014; 15 pps.  
 Office Action for U.S. Appl. No. 12/876,794 dated Aug. 15, 2012; 11 pps.  
 Notice of Allowance for U.S. Appl. No. 12/876,794 dated Mar. 6, 2013; 14 pps.  
 Website: "https://over-haul.com/"; download date Dec. 6, 2019; 8 pps.  
 Website: "https://www.babaco.com/"; download date Dec. 6, 2019.  
 Notice of Allowance for U.S. Appl. No. 16/655,529 dated Jul. 24, 2020; 10 pps.

\* cited by examiner





FIG. 1










FIG. 2B




FIG. 3



400 ↗




FIG. 4




FIG. 5A






FIG. 5B




FIG. 5C






FIG. 5D





FIG. 5E





*FIG. 6*






FIG. 7A







*FIG. 7B*



*FIG. 7C*



*FIG. 7D*



*FIG. 7E*



# SYSTEMS AND METHODS FOR ARTIFICIAL INTELLIGENCE (AI) THEFT PREVENTION AND RECOVERY

## CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims benefit and priority under 35 U.S.C. § 120 to, and is a Continuation of, U.S. patent application Ser. No. 16/655,529 filed on Oct. 17, 2019 and titled “SYSTEMS AND METHODS FOR ARTIFICIAL INTELLIGENCE (AI) THEFT PREVENTION AND RECOVERY”, issuing as U.S. Pat. No. 10,854,055 on Dec. 1, 2020, which is hereby incorporated by reference herein in its entirety.

## COPYRIGHT NOTICE

A portion of the disclosure of this patent document contains material which is subject to copyright protection. The copyright owner has no objection to the facsimile reproduction by anyone of the patent document or the patent disclosure, as it appears in the U.S. Patent and Trademark Office patent file or records, but otherwise reserves all copyright rights whatsoever.

## BACKGROUND

Theft of cargo, payloads, and other supplies or materials causes billions of dollars of losses annually. While such theft may be of various sorts and occur in various locations, one aspect that most thefts have in common is that the chances of recovery of stolen goods drops dramatically as time passes. It is common, for example, for the chance of recovery to drop by approximately forty-five percent (45%) in the first twenty-four hours (24 hrs) from the occurrence of the theft event. Any delay in realizing or reporting a theft event may accordingly have significant negative impacts on the chances of recovery. Existing systems provide advantages in cargo and material documentation and tracking, each of which may benefit recovery efforts. Such systems do not however, provide solutions for theft prevention or identification of theft events.

## BRIEF DESCRIPTION OF THE DRAWINGS

The figures depict embodiments for purposes of illustration only. One skilled in the art will readily recognize from the following description that alternative embodiments of the systems and methods illustrated herein may be employed without departing from the principles described herein, wherein:

FIG. 1 is a block diagram of a system according to some embodiments;

FIG. 2A and FIG. 2B are perspective diagrams of a system at different points in time, according to some embodiments;

FIG. 3 is a diagram of an example augmented reality interface system according to some embodiments;

FIG. 4 is a flow diagram of a method according to some embodiments;

FIG. 5A, FIG. 5B, FIG. 5C, FIG. 5D, and FIG. 5E are diagrams of an example interface system according to some embodiments;

FIG. 6 is a block diagram of an apparatus according to some embodiments; and

FIG. 7A, FIG. 7B, FIG. 7C, FIG. 7D, and FIG. 7E are perspective diagrams of exemplary data storage devices according to some embodiments.

## DETAILED DESCRIPTION

### I. Introduction

Existing systems for cargo and material documentation and tracking offer some advantages in assisting recovery efforts for stolen items but, fail to prevent theft occurrences or to enhance theft (and/or damage or other loss) event detection. Documentation applications allow for better cargo management practices that may facilitate record keeping, which may aid in recovery efforts by more readily identifying recovered items. Tracking is a well-known (but often expensive) means of locating lost property in response to a theft event. Neither of these options, however, facilitates theft prevention or identification.

In accordance with embodiments herein, these and other deficiencies of existing systems are remedied by providing systems, apparatus, methods, and articles of manufacture for Artificial Intelligence (AI) theft prevention and recovery utilizing image object analysis to identify theft (and/or damage or other loss) events and provide AI-based theft/loss prevention guidance. In some embodiments, for example, images (or other sensor data) of cargo, payloads, materials, contents, and/or other objects may be captured at different points in time and automatically compared and analyzed by stored AI logic and/or routines to identify theft, damage, and/or other loss events. According to some embodiments, AI logic may be utilized to analyze theft and/or loss event data to provide predictive guidance for current and/or future cargo, payload, material, contents, and/or other object transportation and/or storage.

### II. AI Theft Prevention and Recovery Systems

Referring first to FIG. 1, a block diagram of a system **100** according to some embodiments is shown. In some embodiments, the system **100** may comprise a plurality of user devices **102a-b** in communication via or with a network **104**. According to some embodiments, one or more of the user devices **102a-b** (such as a second user device **102b**, as depicted) may be disposed in, in communication with, and/or otherwise associated with a vehicle **106** (or other area, location, building, object, etc.). In some embodiments, the system **100** may comprise and/or the user devices **102a-b** may be in communication with a third-party device **108** and/or a server **110**. In some embodiments, the vehicle **106** may comprise a sensor **116** (e.g., oriented and/or disposed to capture images, video, audio, and/or other readings descriptive of contents **130** of the vehicle **106**). According to some embodiments, the sensor **116** may be coupled to and/or comprise a portion of the contents **130**.

In some embodiments, any or all of the devices **102a-b**, **106**, **108**, **110**, **116** may comprise and/or be in communication with a data storage and/or memory device **140a-c**. A first user device **102a** may comprise a mobile electronic device, such as a laptop or tablet computer housing a first local or first memory device **140a**, for example, and/or the second user device **102b** may comprise a mobile electronic device, such as a smartphone housing a second local or second memory device **140b**. According to some embodiments, the server **110** may comprise (and/or be in communication with) a third memory device **140c**. As depicted in FIG. 1, any or all of the devices **102a-b**, **106**, **108**, **110**, **116**,



**140a-c** (or any combinations thereof) may be in communication via the network **104**. In some embodiments, communications between and/or within the devices **102a-b**, **106**, **108**, **110**, **116**, **140a-c** of the system **100** may be utilized to capture and analyze images and/or other readings or input from the sensor **116** with respect to (and/or descriptive of) the contents **130** of the vehicle **106**. Either user device **102a-b** may output an indication of a theft or loss event and/or theft or loss prevention guidance, based on input received from the sensor **116**, for example, by execution of an application (or “app”) **142a-b** stored in the first memory device **140a** or the second memory device **140b**, respectively. According to some embodiments, such indication may be calculated, looked up, derived, defined, computed, and/or otherwise determined by analysis of imagery or other data captured by the sensor **116** (and/or by the user devices **102a-b** and/or the vehicle **106**) pursuant to an execution of AI code defined by the server **110** and/or by the app **142a-b** stored in the respective memory device **140a-b** of the user devices **102a-b**.

Fewer or more components **102a-b**, **106**, **108**, **110**, **116**, **140a-c**, **142a-b** and/or various configurations of the depicted components **102a-b**, **106**, **108**, **110**, **116**, **140a-c**, **142a-b** may be included in the system **100** without deviating from the scope of embodiments described herein. In some embodiments, the components **102a-b**, **106**, **108**, **110**, **116**, **140a-c**, **142a-b** may be similar in configuration and/or functionality to similarly named and/or numbered components as described herein. In some embodiments, the system **100** (and/or portion thereof) may comprise an AI-based theft prevention and recovery system and/or platform programmed and/or otherwise configured to execute, conduct, and/or facilitate the method **400** of FIG. **4** herein, and/or portions thereof.

The user devices **102a-b**, in some embodiments, may comprise any type or configuration of computing, mobile electronic, network, user, and/or communication devices that are or become known or practicable. The user devices **102a-b** may, for example, comprise one or more Personal Computer (PC) devices, computer workstations, tablet computers, such as an iPad® manufactured by Apple®, Inc. of Cupertino, Calif., and/or cellular and/or wireless telephones, such as an iPhone® (also manufactured by Apple®, Inc.) or an LG V50 THINQ™ 5G smart phone manufactured by LG® Electronics, Inc. of San Diego, Calif., and running the Android® operating system from Google®, Inc. of Mountain View, Calif. In some embodiments, the user devices **102a-b** may comprise one or more devices owned and/or operated by one or more users (not shown), such as a driver of the vehicle **106** (e.g., human and/or AI) and/or an electronic product (e.g., underwriting product) customer (or potential customer). The first user device **102a** may be operated by a cargo/payload loading entity that loads the contents **130** in/on the vehicle **106**, for example, and/or the second user device **102b** may be operated by a driver of the vehicle **106**. According to some embodiments, the user devices **102a-b** may communicate with the server **110** either directly or via the network **104** to (i) provide input from the sensor **116**, (ii) provide information descriptive of the contents **130** and/or the vehicle **106**, (iii) to retrieve/receive AI analysis results, (iv) to retrieve/receive theft/loss alerts and/or notifications, (v) to retrieve/receive theft/loss prevention suggestions/guidance, and/or (vi) to trigger and/or authorize one or more third-party alerts by automatically contacting a police authority and/or insurance carrier, in accordance with AI theft prevention and recovery processes as described herein.

The network **104** may, according to some embodiments, comprise a Local Area Network (LAN; wireless and/or wired), cellular telephone, Bluetooth®, Near Field Communication (NFC), and/or Radio Frequency (RF) network with communication links between the server **110**, the user devices **102a-b**, the third-party device **108**, and/or the memory devices **140a-c**. In some embodiments, the network **104** may comprise direct communication links between any or all of the components **102a-b**, **106**, **108**, **110**, **116**, **140a-c** of the system **100**. The user devices **102a-b** may, for example, be directly interfaced or connected to one or more of the server **110** and/or the third-party device **108** via one or more wires, cables, wireless links, and/or other network components, such network components (e.g., communication links) comprising portions of the network **104**. In some embodiments, the network **104** may comprise one or many other links or network components other than those depicted in FIG. **1**. The server **110** may, for example, be connected to the vehicle **106** via various cell towers, routers, repeaters, ports, switches, and/or other network components that comprise the Internet and/or a cellular telephone (and/or Public Switched Telephone Network (PSTN)) network, and which comprise portions of the network **104**.

While the network **104** is depicted in FIG. **1** as a single object, the network **104** may comprise any number, type, and/or configuration of networks that is or becomes known or practicable. According to some embodiments, the network **104** may comprise a conglomeration of different sub-networks and/or network components interconnected, directly or indirectly, by the components **102a-b**, **106**, **108**, **110**, **116**, **140a-c** of the system **100**. The network **104** may comprise one or more cellular telephone networks with communication links between the second user device **102b** and the server **110**, for example, and/or may comprise an NFC or other short-range wireless communication path, with communication links between the sensor **116**, the first user device **102a**, and/or one or more of the memory devices **140a-c**, for example.

According to some embodiments, the vehicle **106** may comprise any type, quantity, and/or configuration of transportation or other object or area that is or becomes known or practicable. The vehicle **106** may comprise a passenger vehicle or fleet vehicle (e.g., a car, truck, train, boat, ship, and/or airplane), for example, that is utilized to transport or move the contents **130** from a first location (e.g., an origin) to a second location (e.g., a destination). In some embodiments, the vehicle **106** may comprise a flatbed, lowboy, box, refrigerator (or “reefer”), container, tanker, dump, dry bulk, and/or car hauler semi-trailer, and/or associated tractor unit, and the contents **130** may comprise a payload or cargo thereof. According to some embodiments, the vehicle **106** may instead comprise a location, such as a jobsite, construction site, and/or storage unit or site, and the contents **130** may comprise materials and/or supplies, such as, but not limited to, construction materials and/or equipment, tools, and/or building supplies and/or materials.

The third-party device **108**, in some embodiments, may comprise any type or configuration of a computerized processing device, such as a PC, laptop computer, computer server, database system, and/or other electronic device, devices, or any combination thereof. In some embodiments, the third-party device **108** may be owned and/or operated by a third-party (i.e., an entity different than any entity owning and/or operating either the user devices **102a-b** or the server **110**; such as a certificate, authentication, or cryptographic service provider, a police or other law enforcement agency system, and/or an underwriting product company). The



third-party device **108** may, for example, execute one or more web services that provide for centralized firmware and/or logic updating functionality, online AI object and/or image analysis, online AI theft/loss prevention analysis, and/or online navigational routing functionality. In some embodiments, the third-party device **108** may provide and/or transmit data (e.g., AI analysis results and/or law enforcement data) to the second user device **102b** and/or the server **110**. According to some embodiments, the third-party device **108** may comprise a plurality of devices and/or may be associated with a plurality of third-party entities (not shown).

In some embodiments, the server **110** may comprise an electronic and/or computerized controller device, such as a computer server communicatively coupled to interface with the user devices **102a-b** and/or the third-party device **108a** (directly and/or indirectly). The server **110** may, for example, comprise one or more PowerEdge™ R830 rack servers manufactured by Dell®, Inc. of Round Rock, Tex. which may include one or more Twelve-Core Intel® Xeon® E5-4640 v4 electronic processing devices. In some embodiments, the server **110** may comprise a plurality of processing devices specially programmed to execute and/or conduct processes that are not practicable without the aid of the server **110**. The server **110** may, for example, execute one or more coded rules to manage wireless communications of the user devices **102a-b** (e.g., a cellphone service provider) and/or the third-party device **108**, and/or may provide complex AI-based image/object analysis services, either of which may not be capable of being conducted without the benefit of the specially-programmed server **110**. According to some embodiments, the server **110** may be located remotely from one or more of the user devices **102a-b**, the vehicle **106**, and/or the third-party device **108**. The server **110** may also or alternatively comprise a plurality of electronic processing devices located at one or more various sites and/or locations.

According to some embodiments, the server **110** may store and/or execute specially programmed instructions (e.g., stored in the third memory device **140c**, but not separately depicted in FIG. 1) to operate in accordance with embodiments described herein. The server **110** may, for example, execute one or more programs, modules, and/or routines (e.g., the app **142a-b**) that facilitate the analysis, monitoring, and/or safeguarding of the contents **130** of the vehicle **106**, as described herein. According to some embodiments, the server **110** may comprise a computerized processing device, such as a centralized server utilized, for example, to (i) identify correlations between portions of received images and/or sensor readings descriptive of the contents **130** and items that comprise the contents **130**, (ii) identify differences between images/sensor readings descriptive of the contents **130** over time, (iii) classify the differences, (iv) trigger an alert and/or notification based on the classification, (v) classify a theft/loss risk based on information descriptive of the contents **130**, and/or (vi) trigger and/or provide theft/loss prevention guidance based on the classification of the contents **130**, as described herein.

The sensor **116**, in some embodiments, may comprise any type, quantity, and/or configuration of data gathering and/or input device that is or becomes known or practicable. According to some embodiments, the sensor **116** may comprise one or more sensors configured and/or coupled to sense, measure, calculate, and/or otherwise process or determine data descriptive of the contents **130**, the vehicle **106**, and/or an environment (not separately depicted) in which they are disposed, such as light measurements, strain mea-

surements, temperature readings, moisture and/or humidity readings, sound readings, vibration readings, weight readings, Infrared Radiation (IR) and/or microwave readings (e.g., motion sensor readings and/or IR intensity readings), and/or location readings. In some embodiments, the sensor **116** may be disposed and/or positioned to acquire data descriptive of the contents **130**, the vehicle **106**, and/or the environment(s) thereof, but may be part of a separate device and/or object, such as the vehicle **106** and/or the user devices **102a-b**. The sensor **116** may comprise, for example, a camera and/or other sensor of one or more of the user devices **102a-b**. In some embodiments, sensor data may be provided to the apps **142a-b** and/or the server **110** to identify changes in the contents **130**, e.g., to predict, prevent, and/or identify theft and/or loss events thereof.

In some embodiments, the user devices **102a-b**, the third-party device **108**, the sensor **116**, and/or the server **110** may be in communication with and/or comprise the memory devices **140a-c**. The memory devices **140a-c** may comprise, for example, various databases and/or data storage mediums that may store, for example, image (and/or other sensor) data, object identification rules, object data, cargo/material rule and/or scenario data, location data, theft/loss prevention rules and/or data, cryptographic keys and/or data, login and/or identity credentials, and/or instructions (e.g., AI-based theft/loss prevention and/or recovery instructions and/or guidance) that cause various devices (e.g., the third-party device **108** and/or the user devices **102a-b**) to operate in accordance with embodiments described herein.

The memory devices **140a-c** may store, for example, the apps **142a-b**, each of which may, when executed, participate in and/or cause AI-based theft/loss prevention and/or recovery, as described herein. In some embodiments, the memory devices **140a-c** may comprise any type, configuration, and/or quantity of data storage devices that are or become known or practicable. The memory devices **140a-c** may, for example, comprise an array of optical and/or solid-state hard drives configured to store digital image and/or video data, image and/or object analysis data and/or cargo/material analysis data (e.g., analysis formulas and/or mathematical models), credentialing instructions and/or keys, and/or various operating instructions, drivers, etc. While the memory devices **140a-c** are depicted as stand-alone components of the user devices **102a-b** and the server **110**, the memory devices **140a-c** may comprise multiple components. In some embodiments, a multi-component memory device **140a-c** may be distributed across various devices and/or may comprise remotely dispersed components. Any or all of the user devices **102a-b**, the vehicle **106**, the contents **130**, the third-party device **108**, and/or the server **110** may comprise the memory devices **140a-c** or a portion thereof, for example.

Referring now to FIG. 2A and FIG. 2B, perspective diagrams of a system **200** at different points in time according to some embodiments are shown. The system **200** may comprise, for example, a user device **202** and a vehicle **206**, with the user device **202** being in communication with a remotely positioned server **210**. According to some embodiments, the user device **202** may be disposed near or in (e.g., coupled to) the vehicle **206** and/or may comprise a camera **216a** (and/or other sensor) and/or the vehicle **206** may comprise a sensor **216b**. According to some embodiments, the user device **202** may comprise and/or output an interface **220** that, e.g., displays information related to data captured by the camera **216a** and/or the sensor **216b**. In some embodiments (such as depicted), the user device **202** (and/or the camera **216a** thereof) and/or the sensor **216b** may be



disposed and/or oriented to capture data descriptive of cargo **230a-c** being transported by (or loaded or stored within) the vehicle **206**. As depicted for non-limiting purposes of example in FIG. 2A and FIG. 2B, the cargo **230a-c** may comprise a first cargo pallet **230a**, a second cargo pallet **230b**, and/or a third cargo pallet **230c** loaded within the vehicle **206**. The cargo pallets **230a-c** may comprise any number, type, and/or configuration of materials, payload, cargo, contents, supplies, tools, and/or other objects that are or become known or practicable. In some embodiments, the cargo pallets **230a-c** may comprise individual items, such as boxes, crates, and/or other objects. As depicted in FIG. 2A, for example, the first cargo pallet **230a** may comprise a first box **230a-1** and a second box **230a-2** and/or the third cargo pallet **230c** may comprise a first crate **230c-1** and a second crate **230c-2**.

According to some embodiments, the user device **202** and/or the server **210** may process data from the camera **216a** and/or from the sensor **216b** and execute specially programmed code (software and/or firmware code) to identify the boxes **230a-1**, **230a-2**, the crates **230c-1**, **230c-2**, and/or other objects, characteristics, and/or items descriptive of the cargo **230a-c**, such as labels **232a-1**, **232a-2**, **232c**, pallet straps or seals **234**, box or crate straps or seals **236**, and/or vehicle indicia **238** (e.g., a license plate, VIN, trailer number, freight carrier logo, etc.). The server **210** may utilize the detection of the objects **230a-1**, **230a-2**, **230c-1**, **230c-2**, **230a-c**, **232a-1**, **232a-2**, **232c**, **234**, **236**, **238** in various manners to derive information and/or compute classifications and/or conclusions regarding the cargo **230a-c** and/or the vehicle **206**. In some embodiments, for example, the server **210** and/or the user device **202** may identify a first box label **232a-1** of the first box **230a-1** (e.g., based on input received from the camera **216a** and/or the sensor **216b**) and execute an Optical Character Recognition (OCR) algorithm to identify alphanumeric data depicted on the first box label **232a-1**. In the example case depicted in FIG. 2A and FIG. 2B, the server **210** and/or the user device **202** may identify that the vehicle indicia **238** comprises a license plate and that a partial plate number reads "11M". According to some embodiments, any data descriptive of any of the objects **230a-1**, **230a-2**, **230c-1**, **230c-2**, **230a-c**, **232a-1**, **232a-2**, **232c**, **234**, **236**, **238**, such as recognized indicia thereof, location, size, shape, quantity, color, etc., may be stored in a database or memory device **240**. The server **210** (and/or the user device **202**) may comprise or be in communication with the memory device **240**, for example, and may store data descriptive of the cargo **230a-c** and/or the vehicle **206** therein. In some embodiments, the memory device **240** may store AI code **242** that is specially programmed to (i) predict risks to the cargo **230a-c** based on the data descriptive of the objects **230a-1**, **230a-2**, **230c-1**, **230c-2**, **230a-c**, **232a-1**, **232a-2**, **232c**, **234**, **236**, **238** and/or (ii) identify indications of theft or loss based on the data descriptive of the objects **230a-1**, **230a-2**, **230c-1**, **230c-2**, **230a-c**, **232a-1**, **232a-2**, **232c**, **234**, **236**, **238**.

The AI code **242** may be utilized (e.g., executed) by the server **210** and/or the use device **202**, for example, to identify a type of cargo **230a-c** (e.g., from labels **232a-1**, **232a-2**, **232c**) and identify or calculate, for the specific type of cargo **230a-c** one or more risks. In the case that the cargo **230a-c** comprises home theatre electronic components, for example, historic loss data stored in the memory device **240** may be queried and/or analyzed to determine that such cargo **230a-c** frequently suffers damage from high humidity levels. According to some embodiments, the interface **220** may be utilized to output guidance to a user/driver (not shown) that

is descriptive of the sensitivity to humidity levels. Similarly, the sensor **216b** may be utilized to detect or measure humidity levels that are then compared, by the AI code **242** to a stored threshold to determine whether the current conditions of the cargo **230a-c** are within acceptable levels (e.g., to minimize the chances of damage). In some embodiments, the type of cargo **230a-c** may be correlated to historic theft occurrences to identify characteristics that have been realized with some frequency in previous theft scenarios. The AI code **242** may determine, for example, that home theatre equipment types of cargo **230a-c** are most frequently stolen after dark and/or when it is not raining. In such embodiments, the interface **220** may be utilized to alert or notify the user/driver regarding impending or current weather and/or time-of-day conditions that increase theft risk to the cargo **230a-c**. In some embodiments, potential discrepancies in the cargo **230a-c** may be identified by object recognition executed by the AI code **242**. The AI code **242** may, for example, identify that the first box label **232a-1** does not match a second box label **232a-2** and/or that a logo or label **232c** of the second crate **230c-2** does not appear on the first crate **230c-1**. Either of these identifications may be evidence of improper loading or packing, mixed-goods cargo **230a-c**, and/or other characteristics of the cargo **230a-c**.

In some embodiments, the server **210** and/or the user device **202** may execute the AI code **242** that analyzes the cargo **230a-c** over time to derive data descriptive of possible theft, damage, and/or other loss events in relation to the cargo **230a-c** and/or the vehicle **206**. As depicted in FIG. 2A, for example, the camera **216a** of the user device **202** may capture an image (or other data) descriptive of the cargo **230a-c** (or a portion thereof, such as the third cargo pallet **230c**) at a first point in time and may identify various attributes and/or characteristics of the first instance of the cargo **230a-c**, such as a dimension/height, shape, location (absolute and/or relative to other objects), etc. According to some embodiments, the user device **202** may transmit the image to the server **210** and the server may execute the AI code **242** to identify objects in the image, such as the first cargo pallet **230a**, the third cargo pallet **230c**, and/or the pallet straps **234** of the third cargo pallet **230c**. In some embodiments, such as in the case that the first cargo pallet **230a**, the third cargo pallet **230c**, and/or the pallet straps **234** of the third cargo pallet **230c** are found to be present in multiple images and/or video frames captured by the camera **216a**, the server **210** may identify a second instance or view of the cargo **230a-c** at a second time, as depicted in FIG. 2B. According to some embodiments, execution of the AI code **242** may cause a comparison of any initial or first attributes of the first instance of the cargo **230a-c** to an identified second attribute of the second instance of the cargo **230a-c** to derive, compute, and/or calculate a characteristic of the cargo **230a-c**. In the example depicted in FIG. 2A and FIG. 2B, for example, the AI code **242** may determine (e.g., via an object-based analysis of data descriptive of the cargo **230a-c** captured at different times) one or more instances of missing objects **260a-b**, damaged objects **262**, damaged pallet straps **264**, and/or damaged crate seals **266**.

According to some embodiments, the comparison of the attributes may be utilized to lookup, calculate, and/or otherwise compute quantitative metrics regarding the cargo **230a-c**. Based on the magnitude of the differences in dimensions/measurements, textures, heat signatures, colors, and/or locations, for example, the AI code **242** may (i) identify an instance of a missing pallet **260a**, (ii) identify an instance of a missing crate **260b**, (iii) identify an instance of a damaged



crate **262**, (iv) identify an instance of a compromised pallet strap **264**, and/or (v) identify an instance of a compromised crate seal **266**. In some embodiments, the presence or absence of the sensor **216b** may also or alternatively be taken into account when analyzing a status or classification of the cargo **230a-c**. In the case that the identified missing crate **260b** was a crate to which the sensor **216b** was coupled, for example, the instance of the missing crate **260b** may be identified by object detection and analysis and/or by analyzing signals from the sensor **216b**. In the case that no signal from the sensor **216b** can be detected, for example, it may be presumed that the sensor **216b** and associated crate are missing from the third cargo pallet **230c**. In some embodiments, such as in the case that the sensor **216b** comprises a location tracking device, such as an RFID and/or GPS device, data received from the sensor **216b** may indicate that the sensor **216b** and associated crate are not located proximate to the vehicle **206**, e.g., an indication of theft. According to some embodiments, the interface **220** may output an indication of the missing and/or damaged objects **260a-b**, **262**, **264**, **266** and/or may provide a mechanism for the user to initiate an automatic reporting of the missing and/or damaged objects **260a-b**, **262**, **264**, **266** (e.g., to a law enforcement agency, underwriting agency, shipping company, etc.).

### III. AI Theft Prevention and Recovery Augmented Reality Interface Systems

Turning now to FIG. 3, a diagram of an example augmented reality interface system **300** according to some embodiments is shown. In some embodiments, the augmented reality interface system **300** may comprise a mobile electronic user device **302** that outputs one or more interfaces **320**. According to some embodiments, the interface **320** may comprise one or more of a web page, web form, database entry form, API, spreadsheet, table, and/or application or other GUI via which a user or other entity may receive and/or enter data (e.g., provide or define input) in association with AI theft prevention and recovery, as described herein. The interface **320** may, for example, comprise a front-end of an AI theft/loss prevention and/or recovery program and/or platform programmed and/or otherwise configured to execute, conduct, and/or facilitate the method **400** of FIG. 4 herein, and/or portions thereof. In some embodiments, the interface **320** may be output via one or more computerized and/or specially-programmed computers (e.g., the user devices **102a-b**, **202**, **302**, **502**, the third-party device **108**, the servers **110**, **210**, **610** all of FIG. 1, FIG. 2A, FIG. 2B, FIG. 3, FIG. 5A, FIG. 5B, FIG. 5C, FIG. 5D, FIG. 5E, and/or FIG. 6 herein), computer terminals, computer servers, computer systems and/or networks, and/or any combinations thereof (e.g., by one or more multi-threaded and/or multi-core processing units of an online and/or client-server AI object analysis processing system).

According to some embodiments, the interface **320** may comprise one or more tabs and/or other segmented and/or logically-presented data forms, areas, and/or fields. In some embodiments, the interface **320** may be configured and/or organized to allow and/or facilitate management of cargo, supplies, payloads, materials, and/or other objects by facilitating theft and/or damage event identification. According to some embodiments, the interface **320** may comprise an output of a mobile device application that facilitates theft/loss identification by utilizing augmented reality overlays on images/video feed descriptive of cargo or other objects of

interest. As depicted in FIG. 3, for example, a first version (or page or instance) of the interface **320** may comprise a “Cargo Check” interface (e.g., defining a first input and/or output mechanism) that provides and/or includes an augmented reality display **320-1**, a missing pallet indicator **320-2**, a missing crate indicator **320-3**, a damaged crate indicator **320-4**, a report theft button **320-5**, and/or a report damage button **320-6** (e.g., each of which may comprise one or more data entry mechanisms, tools, objects, and/or features). While the interface **320** of FIG. 3 depicts output that is provided as a two-dimensional (2D) representation of, e.g., a rear view of a trailer or storage container, the interface **320** may also or alternatively be provided as a three-dimensional (3D), perspective, top-down or overhead, cross sectional, and/or other view or representation that is or becomes known or practicable. According to some embodiments, the interface **320** may comprise different layers of data for the augmented reality display **320-1**, such that a user may scroll or browse through different views to better inspect all items of a cargo or material pile/area, e.g., such that items hidden from view by other items may be readily inspected.

In some embodiments, the first version (or page or instance) of the interface **320** may be utilized by a user (such as a truck driver, cargo loader/unloader, cargo carrier entity, customs official) to readily identify whether one or more objects have been subject to theft, damage, or other loss. An image, video, and/or other sensor-reading display of an object, such as cargo **330a-c** (e.g., the cargo **230a-c** of FIG. 2A and FIG. 2B), may, for example, be overlaid and/or represented by the augmented reality display **320-1**. The augmented reality display **320-1** may comprise, in some embodiments, a virtual representation of the objects identified in the cargo **330a-c** and/or may comprise virtual representations and/or graphics overlaid upon a previously captured image/video/etc. of the cargo **330a-c**. According to some embodiments, the augmented reality display **320-1** may comprise graphical items overlaid on a live feed from a camera (not shown) of the user device **302**. In some embodiments, the live feed or captured image(s) may be compared to previous image/sensor data descriptive of the cargo **330a-c** by utilizing AI object detection algorithms as described herein.

According to some embodiments, the augmented reality display **320-1** may generate and display the missing pallet indicator **320-2** on a portion of the augmented reality display **320-1** that is computed to coincide with a previous location of a first item of cargo **330a** (e.g., the first cargo pallet **230a** of FIG. 2A). In some embodiments, the missing pallet indicator **320-2** may comprise a virtual representation of the size, shape, color, location, and/or other characteristic and/or attribute of a missing cargo pallet comprising the first cargo item **330a**. As depicted, the missing pallet indicator **320-2** may comprise a highlighted, animated (e.g., flashing), and/or otherwise distinctive graphical object (e.g., annotated with the descriptor “missing”) overlaid on the augmented reality display **320-1** in a position that represents where the first cargo item **330a** should be (e.g., was previously located). According to some embodiments, the missing pallet indicator **320-2** may comprise an interactive input/output element. In the case that the missing pallet indicator **320-2** is activated upon a triggering and/or receipt of input from the user (e.g., a properly positioned click of a mouse or other pointer with respect to the missing pallet indicator **320-2**), for example, data descriptive of the missing cargo pallet **330a** may be provided (e.g., size, weight, ID numbers, content descriptions, value, etc.).



In some embodiments, the augmented reality display **320-1** may generate and display the missing crate indicator **320-3** on a portion of the augmented reality display **320-1** that is computed to coincide with a previous location of a portion of a third item of cargo **330c** (e.g., a portion of the third cargo pallet **230c** of FIG. 2A and/or FIG. 2B). In some embodiments, the missing crate indicator **320-3** may comprise a virtual representation of the size, shape, color, location, and/or other characteristic and/or attribute of a missing crate of the third item of cargo **330c**. As depicted, the missing crate indicator **320-3** may comprise a highlighted, animated (e.g., flashing), and/or otherwise distinctive graphical object (e.g., annotated with the descriptor “missing”) overlaid on the augmented reality display **320-1** in a position that represents where the missing crate from the third item of cargo **330c** should be (e.g., was previously located). According to some embodiments, the missing crate indicator **320-3** may comprise an interactive input/output element. In the case that the missing crate indicator **320-3** is activated upon a triggering and/or receipt of input from the user (e.g., a properly positioned click of a mouse or other pointer with respect to the missing crate indicator **320-3**), for example, data descriptive of the missing crate from the third item of cargo **330c** may be provided (e.g., size, weight, ID numbers, content descriptions, value, etc.).

According to some embodiments, areas of damage or other indications of loss that are identified via AI logic object-based analysis may be depicted via the augmented reality display **320-1** by generation of the damaged crate indicator **320-4**. The damaged crate indicator **320-4** may comprise, for example, a virtual representation of the size, shape, color, location, and/or other characteristic and/or attribute of a damaged portion of a crate of the third item of cargo **330c**. As depicted, the damaged crate indicator **320-4** may comprise a highlighted, animated (e.g., flashing), and/or otherwise distinctive graphical object (e.g., annotated with the descriptor “damaged”) overlaid on the augmented reality display **320-1** in a position that represents where the damage to the crate from the third item of cargo **330c** is located (e.g., where it has been identified by the AI analysis). According to some embodiments, the damaged crate indicator **320-4** may comprise an interactive input/output element. In the case that the damaged crate indicator **320-4** is activated upon a triggering and/or receipt of input from the user (e.g., a properly positioned click of a mouse or other pointer with respect to the damaged crate indicator **320-4**), for example, data descriptive of the identified damage and/or descriptive of the crate from the third item of cargo **330c** may be provided (e.g., estimated type of damage, size, weight, ID numbers, content descriptions, value of crate contents, estimated damaged value (e.g., loss amount), etc.).

In some embodiments, the first version (or page or instance) of the interface **320** may comprise either or both of the report theft button **320-5** and the report damage button **320-6**. The report theft button **320-5** may be utilized, for example, to report a suspected instance of theft (as indicated by the missing pallet indicator **320-2** and/or the missing crate indicator **320-3**) to various entities, such as law enforcement, an insurance carrier, a shipping company, customer, supplier, etc. Selection of the report theft button **320-5** may, in some embodiments, trigger an automatic transmission to such entities (e.g., from the user device **302** and/or a centralized server device—not shown in FIG. 3). According to some embodiments, the transmission may comprise data descriptive of the missing cargo **330a-c** and/or portions of missing cargo (e.g., crates, boxes), data descriptive of a vehicle (not shown) and/or location of the

suspected theft, a timestamp, cryptographic information, cargo identifiers, cargo tracking information, etc. Similarly, the report damage button **320-6** may be utilized to report a suspected instance of damage or loss (as indicated by the damaged crate indicator **320-4**) to various entities, such as an insurance carrier, a shipping company, customer, supplier, etc. Selection of the report damage button **320-6** may, in some embodiments, trigger an automatic transmission to such entities (e.g., from the user device **302** and/or a centralized server device—not shown in FIG. 3). According to some embodiments, the transmission may comprise data descriptive of the damaged cargo **330a-c** and/or portions of damaged cargo (e.g., crates, boxes), data descriptive of characteristics and/or attributes of a vehicle (not shown) and/or location of the damage discovery (e.g., weather conditions, sensor readings), a timestamp, cryptographic information, cargo identifiers, cargo tracking information, etc.

According to some embodiments, the interface **320** may permit a user to selectively report and/or investigate specific identified instances of suspected theft and/or loss. In the case that the user believes the first cargo item **330a** is not missing, but has recently been unloaded, for example, the user may select the missing crate indicator **320-3** to designate the missing crate from the third item of cargo **330c** for reporting, and then select the report theft button **320-5** to automatically transmit details of the missing crate from the third item of cargo **330c** to a pre-programmed entity address (e.g., a law enforcement e-mail address, a security company fax number, a freight company’s text reporting number, etc.). In some embodiments, multiple items of cargo **330a-c** and/or portions thereof may be selectively designated for reporting to different entities. In such a manner, for example, instances of theft and/or loss may be quickly and easily identified and reported, and any or all relevant information that may be useful for recovery efforts may be automatically provided to various remote and/or relevant parties.

#### IV. AI Theft Prevention and Recovery Processes

Referring now to FIG. 4, a flow diagram of a method **400** according to some embodiments is shown. In some embodiments, the method **400** may be performed and/or implemented by and/or otherwise associated with one or more specialized and/or specially-programmed computers (e.g., the user devices **102a-b**, **202**, **302**, **502**, the third-party device **108**, the servers **110**, **210**, **610** all of FIG. 1, FIG. 2A, FIG. 2B, FIG. 3, FIG. 5A, FIG. 5B, FIG. 5C, FIG. 5D, FIG. 5E, and/or FIG. 6 herein), computer terminals, computer servers, computer systems and/or networks, and/or any combinations thereof. In some embodiments, the method **400** may be embodied in, facilitated by, and/or otherwise associated with various input mechanisms and/or interfaces (e.g., the interfaces **220**, **520a-e**, **620** of FIG. 2A, FIG. 2B, FIG. 5A, FIG. 5B, FIG. 5C, FIG. 5D, FIG. 5E, and/or FIG. 6 herein).

The process diagrams and flow diagrams described herein do not necessarily imply a fixed order to any depicted actions, steps, and/or procedures, and embodiments may generally be performed in any order that is practicable unless otherwise and specifically noted. While the order of actions, steps, and/or procedures described herein is generally not fixed, in some embodiments, actions, steps, and/or procedures may be specifically performed in the order listed, depicted, and/or described and/or may be performed in response to any previously listed, depicted, and/or described action, step, and/or procedure. Any of the processes and



methods described herein may be performed and/or facilitated by hardware, software (including microcode), firmware, or any combination thereof. For example, a storage medium (e.g., a hard disk, Random Access Memory (RAM) device, cache memory device, Universal Serial Bus (USB) mass storage device, and/or Digital Video Disk (DVD); e.g., the memory devices **140a-c**, **240**, **640**, **740a-e** of FIG. 1, FIG. 2A, FIG. 2B, FIG. 6, FIG. 7A, FIG. 7B, FIG. 7C, FIG. 7D, and/or FIG. 7E herein) may store thereon instructions that when executed by a machine (such as a computerized processor) result in performance according to any one or more of the embodiments described herein.

In some embodiments, the method **400** may comprise receiving (e.g., via an electronic network and/or by an electronic processing device) cargo data (e.g., at or before a first point in time), at **402**. A mobile electronic device may be utilized, for example, to input and/or transmit a bill of lading, manifest, Stock Keeping Unit (SKU) list, origin, destination, freight company information, assigned or required vehicle or equipment information, characteristic, quantity, and/or attribute data descriptive of a cargo, payload, materials, contents, supplies, tools, and/or other desired grouping of objects. According to some embodiments, the cargo data may define various attributes, such as size, mass, weight, quantity, IR-signature, color, etc. In some embodiments, the cargo data may comprise a correlation of one or more identifiers (such as SKU identifiers, serial numbers, security tag or seal identifiers) with the attributes and/or characteristics of a unit of cargo/materials/etc. According to some embodiments, the cargo data may be input, acquired, transmitted (e.g., by a user device), and/or received (e.g., by a centralized server device) upon loading, purchase, and/or acquisition of the cargo. Freight loading personnel may, for example, utilize a smartphone executing a specially programmed application to document details of the cargo loaded onto a particular vehicle once the vehicle is loaded.

According to some embodiments, the method **400** may comprise receiving (e.g., via the electronic network and/or by the electronic processing device) at least one first cargo "image" at a first point in time, at **404**. The "image" may comprise, for example, a still photo, video footage, and/or a list, table, and/or matrix of data values, e.g., captured, sensed, and/or recorded by a camera and/or other sensor. In some embodiments, the image may be captured at a time after or concurrently with the receiving of the cargo data at **402**. According to some embodiments, an AI device, such as a server and/or mobile user device, may comprise both of a Graphics Processing Unit (GPU) to permit real-time analysis of captured data and AI processing logic and/or algorithms for analyzing the captured data. According to some embodiments, images and/or other data captured or sensed by the camera/sensor may be sent to the GPU, which may receive and process the data (e.g., in accordance with stored (software and/or firmware) graphics processing algorithms or rules). In some embodiments, the GPU may send the processed data/images to a Central Processing Unit (CPU) or other logical device that may, for example, receive and process the GPU-processed data/images, e.g., in accordance with stored AI instructions. According to some embodiments, the image may be received by a processing device of a server from a mobile electronic device of a user, such as a freight loader, shipper, etc. In some embodiments, the first image(s) may be captured, acquired, sensed, and/or received automatically by an affixed security camera and/or sensor coupled to detect data descriptive of the cargo/materials.

In some embodiments, the method **400** may comprise computing a correlation (e.g., via AI analysis performed by a CPU and/or processing device) between portions of the at least one image and cargo items, at **406**. AI instructions may comprise one or more object detection algorithms, for example, that are coded to identify various types of objects in the image data descriptive of the cargo, such as, but not limited to, boxes, crates, seals, straps, labels, tags, logos, and/or shapes. Object detection algorithms may generally store predefined shapes, colors, and/or patterns that the AI device (e.g., server and/or user device) may utilize to search through captured images/data to identify occurrences of such shapes, colors, and/or patterns, and thereby identify one or more objects comprising the cargo. According to some embodiments, identified objects may be classified into different types, such as boxes, crates, etc. According to some embodiments, information may be acquired from various identified objects, such as product identifiers (from labels), model numbers (from labels and/or logos), serial numbers (from labels or RFID tags), and/or locations (e.g., based on GPS coordinates and/or estimated distances from other objects). In such a manner, for example, various portions of the image(s) may be tagged (e.g., in a memory device) as being associated with certain items identified in the cargo data, such as certain cargo pallets, crates, boxes, shipments, etc.

According to some embodiments, the method **400** may comprise determining (e.g., by the CPU/processing device) whether more cargo should be analyzed, at **408**. In the case that no cargo objects/items have been identified and/or correlated (and/or additional objects/items should be identified and/or correlated), the method **400** may proceed back to receiving additional cargo images at **404** (and/or to receiving additional cargo data at **402**). In the case that at least one object/item has been identified and/or correlated (at **406**) and/or no additional objects/items should be identified, the method **400** may proceed to and/or comprise receiving (e.g., via the electronic network and/or by the electronic processing device) at least one second cargo image at a second point in time, at **410**. In some embodiments, the second image(s) may be received by a user device (e.g., as camera and/or sensor input) and/or by a server (e.g., from a user device) at some time after a receiving of the first image(s) at **404**. In the case that the first image(s) at **404** are received at a time of loading, delivery, and/or shipping origin, for example, the second image(s) may be captured and/or received at a waypoint (e.g., truck stop/fuel station), destination, transfer point, weigh station, customer and/or job site, etc. According to some embodiments, the second image(s) may be acquired from a similar perspective and/or under similar guidelines as the first image(s), for example, comprising digital photographs taken from a similar vantage point with respect to the cargo/materials. In some embodiments, guidance may be defined and/or output to direct a user to acquire the second image(s) in a manner that is conducive to comparing the second image(s) to the first image(s). The user may be directed by directional guidance prompts output via an interface of the user's mobile device, for example, to position the mobile device at a certain location and/or angle to capture the second image(s) from the desired perspective. In some embodiments, the second image(s) may be captured, acquired, sensed, and/or received automatically by an affixed security camera and/or sensor coupled to detect data descriptive of the cargo/materials.

In some embodiments, the method **400** may comprise identifying (e.g., by the CPU/processing device and/or by a server device and/or a mobile device application) a portion



of the images that differs between the points in time, at **412**. The AI code may be utilized, for example, to compare the first and second image(s) to identify differences therein. According to some embodiments, such a comparison may comprise matching or aligning the images. Objects and/or features detected and/or identified in the first and second images may, for example, be compared to determine an alignment and/or correlation between the first and second image(s). In the case that the first and second image(s) are not representative of the same angle or perspective of the cargo/materials, for example, objects in the images may be analyzed to achieve an alignment of at least one portion of the first image(s) and at least one portion of the second image(s). According to some embodiments, after matching/corresponding objects have been utilized to align the images, differences between the images may be identified. AI object recognition algorithms may be executed, for example, to identify or locate any objects previously identified in the first image(s) (e.g., and correlated to items of the cargo/materials). In some embodiments, AI-based object analysis may identify one or more objects in the images that have (i) moved, (ii) changed appearance (and/or changed with respect to another attribute, such as heat signature, RF reading), and/or (iii) failed to be located (e.g., in either the first image(s) for newly-identified objects or in the second image(s) for originally-identified objects). According to some embodiments, the type of difference in the identified objects may be classified (e.g., categorized), such as a moved object, a missing object, a new object, and/or a damaged (or presumed damaged) object.

According to some embodiments, the method **400** may comprise identifying (e.g., by the CPU/processing device and/or by a server device and/or a mobile device application) a changed cargo item, at **414**. Based on the correlation at **406**, for example, any objects identified as changed (at **412**) within the images between the two points in time, may be cross-referenced with known/identified items of cargo, e.g., as identified by the cargo data received at **402**. In some embodiments, the classification of the change may be analyzed with respect to the particular item of cargo to derive and/or compute a status classification. In the case of living cargo, such as a horse, for example, since movement is to be expected, an identified movement of the item may be classified as “acceptable” or as a non-event. In the case of a fragile item packed in a shipping crate with a certain end intended to face upwards, however, a tipping, rotation, or other movement that exceeds a threshold (e.g., linear and/or radial) may be classified as excessive movement, potential damage, rough handling, etc. In some embodiments, a status classification may be calculated or computed for each item of cargo that can be identified by the AI logic. In some embodiments, the AI logic may be specifically trained to identify normal or expected movements or changes such as shifting cargo items, moving livestock, and/or changes in appearance due to different lighting, timing, or other conditions.

According to some embodiments, the method **400** may comprise determining (e.g., by the CPU/processing device) whether there are (or should be) more changes, at **416**. In the case that no changes in or of objects/items have been identified (and/or additional changes and/or objects/items should be identified), for example, the method **400** may proceed back to capture or receive more second images/data at **410** (and/or identify more changes/differences at **412**). In some embodiments, the AI image/object analysis may be scheduled to automatically occur at various times. In such embodiments, the capturing and/or receiving of second

images/data at **410**, the identifying of changes in the images at **412**, and/or the identifying of the changes in the cargo items at **414** may proceed and/or be repeated automatically upon certain triggering events (e.g., vehicle stops, elapsed miles driven, detection of bumps, tipping, or hard stops, detection of an opened trailer/cargo door, detection of excessive noise levels, etc.) and/or upon expiration of a predefined time period/window (e.g., every hour). In some embodiments, the AI analysis (at **410**, **412**, **414**) may be selectively initiated and/or triggered by user input. The driver of a tractor trailer may, for example, select a button on an interface of a mobile electronic device to initiate an AI scan of a payload to check on the status of the freight items being hauled. In the case of a self-driving and/or autonomous vehicle, the AI and/or other driving logic may automatically initiate the payload scan based on stored rules and/or logic. In some embodiments, a contractor may selectively initiate a scan of a pile of lumber and/or other materials upon arriving at a jobsite in the morning to check and make sure that no theft has occurred overnight.

In the case that no more input and/or analysis is available and/or needed, the method **400** may proceed to output a changed cargo alert, at **418**. In some embodiments, the user’s mobile device and/or an in-vehicle device may be utilized to output status check results at various points in time (e.g., at the close of a time window). According to some embodiments, a cargo sensor may comprise a short-range communication device operable to transmit an indication of the cargo status (e.g., images, sensor data, calculations) to the vehicle and/or to a mobile electronic device (e.g., a smart phone) utilized by a driver thereof. In some embodiments, the result/status may be output via a webpage served by a web server in communication with the sensor and, e.g., displayed via a user’s mobile device. According to some embodiments, a specially programmed mobile device application of a user’s device may be coded to receive and/or capture image data (e.g., from the sensor device and/or from an integrated sensor/camera), process the data, transmit the data to a server, and/or receive cargo status AI-processing results from the server (e.g., an AI algorithm execution server) that operates in conjunction therewith. In some embodiments, the method **400** may comprise receiving user input and/or commands in response to the cargo status. The user may review possible instances of theft, damage, and/or other loss or concern, for example, and may provide input that triggers an alert, notification, and/or report to be transmitted to a third-party, such as a law enforcement agency, customs, border, or import agency, insurance carrier, freight carrier, freight broker, shipper, supplier, customer, etc. According to some embodiments, alerts, notifications, and/or reports may be automatically sent based on stored rules and stored contact/address information.

#### V. AI Theft Prevention and Recovery Interfaces

Turning now to FIG. **5A**, FIG. **5B**, FIG. **5C**, FIG. **5D**, and FIG. **5E**, diagrams of an example interface system **500** according to some embodiments are shown. In some embodiments, the interface system **500** may comprise a mobile electronic user device **502** that outputs one or more interfaces **520a-e**. According to some embodiments, the interfaces **520a-e** may comprise one or more of a web page, web form, database entry form, API, spreadsheet, table, and/or application or other GUI via which a user or other entity may receive and/or enter data (e.g., provide or define input) in association with AI theft prevention and recovery, as described herein. The interfaces **520a-e** may, for example,



comprise a front-end of an AI theft prevention and recovery program and/or platform programmed and/or otherwise configured to execute, conduct, and/or facilitate the method **400** of FIG. **4** herein, and/or portions thereof. In some embodiments, the interfaces **520a-e** may be output via one or more computerized and/or specially-programmed computers (e.g., the user devices **102a-b**, **202**, **302**, **502**, the third-party device **108**, the servers **110**, **210**, **610** all of FIG. **1**, FIG. **2A**, FIG. **2B**, FIG. **3**, FIG. **5A**, FIG. **5B**, FIG. **5C**, FIG. **5D**, FIG. **5E**, and/or FIG. **6** herein), computer terminals, computer servers, computer systems and/or networks, and/or any combinations thereof (e.g., by one or more multi-threaded and/or multi-core processing units of an online and/or client-server AI object analysis processing system).

According to some embodiments, the interfaces **520a-e** may comprise one or more tabs and/or other segmented and/or logically-presented data forms and/or fields. In some embodiments, the interfaces **520a-e** may be configured and/or organized to allow and/or facilitate viewing, retrieval, and/or selection of various object identification, theft/loss event identification, cargo status, and/or theft/loss reporting data, e.g., for a particular location, driver, group of drivers, and/or vehicle or group of vehicles (e.g., a fleet). According to some embodiments, the interfaces **520a-e** may comprise a menu or “home” page from which a user may select one or more options that initiate specific functionality of a mobile device application. As depicted in FIG. **5A**, for example, a first version (or page or instance) of the interface **520a** may comprise a “Cargo Loading” interface (e.g., defining a first input and/or output mechanism) that provides and/or includes a cargo manifest **520-1**, a setup sensor button **520-2**, a scan item button **520-3**, an edit details button **520-4**, and/or “Push When Loading Complete” button **520-5** (e.g., each of which may comprise one or more data entry mechanisms, tools, objects, and/or features).

In some embodiments, the first version (or page or instance) of the interface **520a** may be utilized by a user, such as a cargo loader/rigger to document cargo loaded into/onto a vehicle. Each item loaded may be scanned, imaged, and/or entered into the manifest **520-1**, for example, as it is loaded. In some embodiments, data defining the manifest **520-1** and/or a portion thereof may be received (e.g., downloaded) from one or more remote devices (not shown; such as the third-party device **108** of FIG. **1** herein). According to some embodiments, the setup sensor button **520-2** may be utilized to initialize and/or configure a sensor coupled to an item of cargo and/or to the vehicle (e.g., a trailer security sensor). In some embodiments, the scan item button **520-3** may be utilized to enter a new item or group of items into the manifest **520-1**. The scan item button **520-3** may, for example, cause a camera and/or other sensor (not shown) to capture images, video, audio, and/or sensor data, such as temperature, humidity, and/or light readings, etc., descriptive of one or more items of cargo. In some embodiments, the scan item button **520-3** may cause a barcode or other machine-readable indicia to be interrogated, read, and/or decoded. According to some embodiments, the scan item button **520-3** may cause an AI object-based analysis of image data to identify loaded items and/or to correlate identified objects to items already entered into the manifest **520-1**. The edit details button **520-4** may, for example, be utilized by the user/loader to enter and/or modify details defining characteristics and/or attributes of cargo items. In some embodiments, acceptable temperature, light, humidity, and/or vibration thresholds, safety data (e.g., flash points, hazardous material parameters), and/or weights and dimensions may be entered into the manifest **520-1** and/or stored

in association with items identified by the manifest **520-1**. In some embodiments, the “Push When Loading Complete” button **520-5** may, upon a triggering and/or receipt of input from the user (e.g., a properly positioned click of a mouse or other pointer with respect to the “Push When Loading Complete” button **520-5**), call, initialize, and/or cause a generation of a second version (or page or instance) of the interface **520b**.

As depicted in FIG. **5B**, for example, the second version (or page or instance) of the interface **520b** may comprise a “Cargo Pickup” interface (e.g., defining a second input and/or output mechanism) that provides and/or includes shipment details **520-6**, a verify ID button **520-7**, a download manifest button **520-8**, an inspect cargo button **520-9**, a pair sensor button **520-10**, and/or “Push When Pickup Complete” button **520-11** (e.g., each of which may comprise one or more data entry mechanisms, tools, objects, and/or features). In some embodiments, the second version (or page or instance) of the interface **520b** may be utilized by a user, such as a freight hauler or driver, to document and/or verify transfer of custody of the cargo from the loader to the driver. The driver may readily view the shipment details **520-6** to verify that the correct cargo is being picked up, for example, and/or may select the verify ID button **520-7** to authenticate the loader, rigging company, supplier, etc. The verify ID button **520-7** may permit the driver to view a photo of authorized loading personnel, for example, and/or may initiate a cryptographic routine to authenticate a code or identifier provided by the loader.

According to some embodiments, the loader may perform a similar function on an alternate version of the second version of the interface **520b** (not shown) to verify the driver’s credentials and/or identity. In some embodiments, the download manifest button **520-8** may be utilized to query, pull, and/or acquire a copy of the manifest **520-1** from the loader. The user device **502** of FIG. **5B** may be utilized by the driver, for example, to download a copy of the manifest **520-1** directly from the user device **502** utilized by the loader in FIG. **5A**. According to some embodiments, in the case that the manifest **520-1** is saved remotely, e.g., to a server (not shown), the user device **502** may access the server to download the manifest **520-1**. In some embodiments, the manifest **520-1** may only be capable of being downloaded by the driver in the case that the driver’s identify is verified by the loader or in the case that the loader otherwise enables the user device **502** to access the information.

In some embodiments, the inspect cargo button **520-9** may be utilized to initiate an AI scan of the cargo and/or cargo images and/or sensor data to set a baseline for the characteristics and/or attributes of the cargo and/or to verify that the cargo characteristics and/or attributes match those as detailed in or stored in relation to the manifest **520-1**. According to some embodiments, the inspect cargo button **520-9** may initiate an AI routine that is specially programmed to identify proper or improper loading of goods. In some embodiments, the inspect cargo button **520-9** may cause an interrogation of one or more sensors coupled to detect information descriptive of the cargo.

According to some embodiments, the pair sensor button **520-10** may be utilized to initiate communications between the user device **502** and a sensor (not shown) associated with the cargo. One or more short-range wireless cameras, RFID devices, GPS devices, light sensors, weight sensors, temperature sensors, humidity sensors, etc., may, for example, be connected to the user device **502** by sharing various electronic handshake data, identifiers, codes, cryptographic



keys, etc. According to some embodiments, the loader may authorize the pairing and/or provide the necessary keys and/or codes to the driver so that the driver may receive data from any utilized cargo sensors. In some embodiments, the “Push When Pickup Complete” button **520-11** may, upon a triggering and/or receipt of input from the user (e.g., a properly positioned click of a mouse or other pointer with respect to the “Push When Pickup Complete” button **520-11**), call, initialize, and/or cause a generation of a third version (or page or instance) of the interface **520c**.

As depicted in FIG. 5C, for example, the third version (or page or instance) of the interface **520c** may comprise a “Routing” interface (e.g., defining a third input and/or output mechanism) that provides and/or includes a routing map **520-12**, a suggested route button **520-13**, a minimize theft button **520-14**, a minimize damage button **520-15**, and/or “Push When Ready to Begin Route” button **520-16** (e.g., each of which may comprise one or more data entry mechanisms, tools, objects, and/or features). In some embodiments, the third version (or page or instance) of the interface **520c** may be utilized by a user, such as a freight hauler or driver, to plan, select, and/or begin traversal of a route for delivery of the cargo. According to some embodiments, AI logic and/or algorithms may be utilized to suggest multiple routes “A”, “B”, and/or “C” to the driver. As depicted in FIG. 5C, each of the available and/or suggested routes may be output and/or depicted to the driver via the routing map **520-12**. In some embodiments, characteristics and/or attributes of the payload, cargo, and/or materials/contents may be utilized to compute the routes “A”, “B”, and/or “C” and the driver/user may review and/or select one or more of the routes “A”, “B”, and/or “C” by activation of a respective one of the suggested route button **520-13**, the minimize theft button **520-14**, and/or the minimize damage button **520-15**.

According to some embodiments, the suggested route that may be chosen via the suggested route button **520-13** may comprise a route calculated to achieve the lowest possible expected likelihood of theft and damage to the cargo. Historic loss data may be analyzed to determine, for example, roads, areas, times of day, weather conditions, and/or other variables that have statistically been associated with higher likelihood of loss. In some embodiments, these likelihoods may be based on cargo type, vehicle type, and/or driver identity. According to some embodiments, the type of cargo (and/or one or more attributes and/or characteristics thereof, such as weight, temperature thresholds, packing materials used) may be utilized to identify route attributes that contribute to increases in likelihood of theft and/or damage. It may be determined, for example, that refrigerated goods tend to experience heat damage (even when transported in reefer trailers) when a first route has been taken for delivery, but experience less tendency for heat damage when a second route has been taken. Similarly, it may be determined that flat screen TVs experience a higher level of theft when transported through certain truck stops in a certain area, but a lower level of theft when stops are made at standard fueling stations. According to some embodiments, route plans culminating in the lowest calculated likelihood of theft may be suggested and/or selected via the minimize theft button **520-14**, and/or route plans culminating in the lowest calculated likelihood of damage may be suggested and/or selected via the minimize damage button **520-15**.

In some embodiments, the “Push When Ready to Begin Route” button **520-16** may, upon a triggering and/or receipt of input from the user (e.g., a properly positioned click of a mouse or other pointer with respect to the “Push When

Ready to Begin Route” button **520-16**), call, initialize, and/or cause a generation of a routing application interface (not shown) and/or a fourth version (or page or instance) of the interface **520d**. As depicted in FIG. 5D, for example, the fourth version (or page or instance) of the interface **520d** may comprise a “Cargo Status Check” interface (e.g., defining a fourth input and/or output mechanism) that provides and/or includes a status manifest **520-17**, an initiate AR view button **520-18**, a sensor calibration button **520-19**, a “refresh all” button **520-20**, and/or “Push to Initiate Reporting” button **520-21** (e.g., each of which may comprise one or more data entry mechanisms, tools, objects, and/or features). According to some embodiments, the fourth version (or page or instance) of the interface **520d** may be provided in response to an automated cargo check performed at predefined time intervals, in response to a triggering event (e.g., a temperature or other sensor threshold violation), and/or randomly. In some embodiments, the fourth version (or page or instance) of the interface **520d** may be utilized by a user, such as a freight hauler or driver, to view, update, and/or manage the status of the transported cargo. According to some embodiments, the status manifest **520-17** may comprise an indication of the status of one or more items of cargo and/or may include selectable options for scanning, viewing, locating, and/or selecting various items of cargo. In some embodiments, the initiate AR view button **520-18** may cause an AR interface (not shown; such as the interface **320** of FIG. 3) to be displayed to the user, via which the user may view graphical representations of the status of various cargo items. According to some embodiments, the sensor calibration button **520-19** may allow the user to calibrate, reset, and/or manage one or more cargo sensors, e.g., to reduce false positive alarms and/or to account for local environmental conditions (such as high humidity areas, rough roads, extreme cold areas). In some embodiments, the “refresh all” button **520-20** may allow the user to query and/or update all available status metrics at once, e.g., as opposed to selectively reviewing and/or checking individual items from the status manifest **520-17**.

According to some embodiments, the “Push to Initiate Reporting” button **520-21** may, upon a triggering and/or receipt of input from the user (e.g., a properly positioned click of a mouse or other pointer with respect to the “Push to Initiate Reporting” button **520-21**), call, initialize, and/or cause a generation of a fifth version (or page or instance) of the interface **520e**. As depicted in FIG. 5E, for example, the fifth version (or page or instance) of the interface **520e** may comprise a “Reporting and Recovery” interface (e.g., defining a fifth input and/or output mechanism) that provides and/or includes law enforcement contact data **520-22**, insurance carrier contact data **520-23**, a find nearest police button **520-24**, an upload theft data button **520-25**, a policy query button **520-26**, an upload claim data button **520-27**, an activate tracking button **520-28**, an auto report settings button **520-29**, and/or an order replacement goods button **520-30** (e.g., each of which may comprise one or more data entry mechanisms, tools, objects, and/or features). In some embodiments, the fifth version (or page or instance) of the interface **520e** may be utilized by a driver, contractor, and/or other user to report a theft and/or loss event, e.g., that has been automatically identified by AI analysis.

According to some embodiments, the law enforcement contact data **520-22** may comprise data identifying one or more law enforcement agencies that may be contacted to report a theft event. The law enforcement contact data **520-22** may comprise, for example, links, buttons, and/or features to permit the user to place a phone call and/or



initiate a text messaging session with the identified agency. In some embodiments, the find nearest police button **520-24** may be utilized to automatically search for and/or identify a local police authority (e.g., in the case that the cargo is in-transit and the driver is unfamiliar with the local police contact information). According to some embodiments, the upload theft data button **520-25** may be utilized to automatically transmit one or more files and/or data elements descriptive of the stolen cargo to the identified agency. The transmitted data may comprise, for example, images of the cargo, identification numbers, sensor and/or tracking data, value information, theft event location, time, etc.

In some embodiments, the insurance carrier contact data **520-23** may comprise data identifying an insurance carrier, bonding agent, broker, and/or other underwriting agency that may be contacted to file a claim based on a loss event (e.g., theft and/or damage). The insurance carrier contact data **520-23** may comprise, for example, links, buttons, and/or features to permit the user to place a phone call and/or initiate a text messaging session with the identified carrier/agency. In some embodiments, the policy query button **520-26** may be utilized to automatically access and/or evaluate insurance policy terms, such as deductibles, loss parameters, coverage limits, etc. According to some embodiments, the upload claim data button **520-27** may be utilized to automatically transmit one or more files and/or data elements descriptive of the stolen and/or damaged cargo to the identified carrier/agency. The transmitted data may comprise, for example, images of the cargo, identification numbers, sensor and/or tracking data, value information, theft and/or damage event location, time, etc.

According to some embodiments, the activate tracking button **520-28** may be utilized to initialize an active tracking device associated with stolen cargo items. A GPS or other satellite-based communication, tracking, and/or location homing device may be activated, for example, so that the stolen goods may be tracked down. In some embodiments, the auto report settings button **520-29** may be utilized to access, set, and/or edit various parameters, contact data, and/or preferences regarding how and/or when parties may be automatically contacted based on triggering events. According to some embodiments, the order replacement goods button **520-30** may be utilized to automatically place an order for additional goods to replace any stolen and/or damaged goods. In such a manner, for example, the delay in shipping and/or receiving of the full complement of cargo items may be minimized by quickly initiating replacements.

While various components of the interfaces **520a-e** have been depicted with respect to certain labels, layouts, headings, titles, and/or configurations, these features have been presented for reference and example only. Other labels, layouts, headings, titles, and/or configurations may be implemented without deviating from the scope of embodiments herein. Similarly, while a certain number of tabs, information screens, form fields, and/or data entry options have been presented, variations thereof may be practiced in accordance with some embodiments.

## VI. AI Driving Analysis and Incentive Apparatus and Articles of Manufacture

Turning to FIG. 6, a block diagram of an AI device or other apparatus **610** according to some embodiments is shown. In some embodiments, the apparatus **610** may be similar in configuration and/or functionality to any of the user devices **102a-b**, **202**, **302**, **502**, the third-party device **108**, the servers **110**, **210**, **610** all of FIG. 1, FIG. 2A, FIG.

**2B**, FIG. 3, FIG. 5A, FIG. 5B, FIG. 5C, FIG. 5D, FIG. 5E, and/or FIG. 6 herein. The apparatus **610** may, for example, execute, process, facilitate, and/or otherwise be associated with the method **400** of FIG. 4 herein, and/or portions thereof. In some embodiments, the apparatus **610** may comprise a processing device **612**, a transceiver device **614**, an input device **616**, an output device **618**, an interface **620**, a memory device **640** (storing various programs and/or instructions **642** and data **644**), and/or a cooling device **650**. According to some embodiments, any or all of the components **612**, **614**, **616**, **618**, **620**, **640**, **642**, **644**, **650** of the apparatus **610** may be similar in configuration and/or functionality to any similarly named and/or numbered components described herein. Fewer or more components **612**, **614**, **616**, **618**, **620**, **640**, **642**, **644**, **650** and/or various configurations of the components **612**, **614**, **616**, **618**, **620**, **640**, **642**, **644**, **650** be included in the apparatus **610** without deviating from the scope of embodiments described herein.

According to some embodiments, the processor **612** may be or include any type, quantity, and/or configuration of processor that is or becomes known. The processor **612** may comprise, for example, an Intel® IXP 2800 network processor or an Intel® XEON™ Processor coupled with an Intel® E6501 chipset. In some embodiments, the processor **612** may comprise multiple inter-connected processors, microprocessors, and/or micro-engines. According to some embodiments, the processor **612** (and/or the apparatus **610** and/or other components thereof) may be supplied power via a power supply (not shown), such as a battery, an Alternating Current (AC) source, a Direct Current (DC) source, an AC/DC adapter, solar cells, and/or an inertial generator. In the case that the apparatus **610** comprises a server, such as a blade server, necessary power may be supplied via a standard AC outlet, power strip, surge protector, and/or Uninterruptible Power Supply (UPS) device.

In some embodiments, the transceiver device **614** may comprise any type or configuration of communication device that is or becomes known or practicable. The transceiver device **614** may, for example, comprise a Network Interface Card (NIC), a telephonic device, a cellular network device, a router, a hub, a modem, and/or a communications port or cable. According to some embodiments, the transceiver device **614** may also or alternatively be coupled to the processor **612**. In some embodiments, the transceiver device **614** may comprise an IR, RF, Bluetooth™, Near-Field Communication (NFC), and/or Wi-Fi® network device coupled to facilitate communications between the processor **612** and another device (not shown).

According to some embodiments, the input device **616** and/or the output device **618** may be communicatively coupled to the processor **612** (e.g., via wired and/or wireless connections and/or pathways) and they may generally comprise any types or configurations of input and output components and/or devices that are or become known, respectively. The input device **616** may comprise, for example, a keyboard that allows an operator of the apparatus **610** to interface with the apparatus **610** (e.g., a driver to retrieve AI cargo status data, as described herein). The output device **618** may, according to some embodiments, comprise a display screen and/or other practicable output component and/or device. The output device **618** may, for example, provide an interface (such as the interface **620** and/or the interfaces **320**, **520a-e** of FIG. 3, FIG. 5A, FIG. 5B, FIG. 5C, FIG. 5D, and/or FIG. 5E herein) via which AI theft prevention and/or recovery data or information is provided to a user (e.g., via a website and/or mobile application). According to some embodiments, the input device **616** and/or the output



device 618 may comprise and/or be embodied in a single device, such as a touch-screen monitor or display.

The memory device 640 may comprise any appropriate information storage device that is or becomes known or available, including, but not limited to, units and/or combinations of magnetic storage devices (e.g., a hard disk drive), optical storage devices, and/or semiconductor memory devices, such as RAM devices, Read Only Memory (ROM) devices, Single Data Rate Random Access Memory (SDR-RAM), Double Data Rate Random Access Memory (DDR-RAM), and/or Programmable Read Only Memory (PROM). The memory device 640 may, according to some embodiments, store one or more of object detection instructions 642-1, routing instructions 642-2, loss instructions 642-3 (e.g., detection and/or classification), interface instructions 642-4, vehicle data 644-1, sensor data 644-2, contents data 644-3, tracking data 644-4, and/or insurance data 644-5. In some embodiments, the object detection instructions 642-1, routing instructions 642-2, loss instructions 642-3 (e.g., detection and/or classification), interface instructions 642-4, vehicle data 644-1, sensor data 644-2, contents data 644-3, tracking data 644-4, and/or insurance data 644-5 may be utilized by the processor 612 to provide output information via the output device 618 and/or the transceiver device 614.

According to some embodiments, the object detection instructions 642-1 may be operable to cause the processor 612 to process vehicle data 644-1, sensor data 644-2, contents data 644-3, tracking data 644-4, and/or insurance data 644-5 in accordance with embodiments as described herein. Vehicle data 644-1, sensor data 644-2, contents data 644-3, tracking data 644-4, and/or insurance data 644-5 received via the input device 616 and/or the transceiver device 618 may, for example, be analyzed, sorted, filtered, decoded, decompressed, ranked, scored, plotted, and/or otherwise processed by the processor 612 in accordance with the object detection instructions 642-1. In some embodiments, vehicle data 644-1, sensor data 644-2, contents data 644-3, tracking data 644-4, and/or insurance data 644-5 may be fed by the processor 612 through one or more mathematical and/or statistical formulas and/or models in accordance with the object detection instructions 642-1 to analyze captured data, such as captured image data descriptive of cargo and/or materials or other contents, to identify one or more objects, as described herein.

In some embodiments, the routing instructions 642-2 may be operable to cause the processor 612 to process the vehicle data 644-1, sensor data 644-2, contents data 644-3, tracking data 644-4, and/or insurance data 644-5 in accordance with embodiments as described herein. Vehicle data 644-1, sensor data 644-2, contents data 644-3, tracking data 644-4, and/or insurance data 644-5 received via the input device 616 and/or the transceiver device 618 may, for example, be analyzed, sorted, filtered, decoded, decompressed, ranked, scored, plotted, and/or otherwise processed by the processor 612 in accordance with the routing instructions 642-2. In some embodiments, vehicle data 644-1, sensor data 644-2, contents data 644-3, tracking data 644-4, and/or insurance data 644-5 may be fed by the processor 612 through one or more mathematical and/or statistical formulas and/or models in accordance with the routing instructions 642-2 to identify, calculate, and/or compute one or more cargo, vehicle, and/or driver-specific transportation routes to reduce the likelihood of loss based on historical loss data, as described herein.

According to some embodiments, the loss instructions 642-3 may be operable to cause the processor 612 to process the vehicle data 644-1, sensor data 644-2, contents data 644-3, tracking data 644-4, and/or insurance data 644-5 in

accordance with embodiments as described herein. Vehicle data 644-1, sensor data 644-2, contents data 644-3, tracking data 644-4, and/or insurance data 644-5 received via the input device 616 and/or the transceiver device 618 may, for example, be analyzed, sorted, filtered, decoded, decompressed, ranked, scored, plotted, and/or otherwise processed by the processor 612 in accordance with the loss instructions 642-3. In some embodiments, vehicle data 644-1, sensor data 644-2, contents data 644-3, tracking data 644-4, and/or insurance data 644-5 may be fed by the processor 612 through one or more mathematical and/or statistical formulas and/or models in accordance with the loss instructions 642-3 to identify, detail, and/or report theft, damage, and/or other loss events utilizing AI logic, as described herein.

In some embodiments, the interface instructions 642-4 may be operable to cause the processor 612 to process the vehicle data 644-1, sensor data 644-2, contents data 644-3, tracking data 644-4, and/or insurance data 644-5 in accordance with embodiments as described herein. Vehicle data 644-1, sensor data 644-2, contents data 644-3, tracking data 644-4, and/or insurance data 644-5 received via the input device 616 and/or the transceiver device 618 may, for example, be analyzed, sorted, filtered, decoded, decompressed, ranked, scored, plotted, and/or otherwise processed by the processor 612 in accordance with the interface instructions 642-4. In some embodiments, vehicle data 644-1, sensor data 644-2, contents data 644-3, tracking data 644-4, and/or insurance data 644-5 may be fed by the processor 612 through one or more mathematical and/or statistical formulas and/or models in accordance with the interface instructions 642-4 to provide an interface (such as the interfaces 320, 520a-3 of FIG. 2, FIG. 5A, FIG. 5B, FIG. 5C, FIG. 5D, and/or FIG. 5E herein) via which input and/or output descriptive of AI theft prevention and recovery may be provided, as described herein.

According to some embodiments, the apparatus 610 may comprise the cooling device 650. According to some embodiments, the cooling device 650 may be coupled (physically, thermally, and/or electrically) to the processor 612 and/or to the memory device 640. The cooling device 650 may, for example, comprise a fan, heat sink, heat pipe, radiator, cold plate, and/or other cooling component or device or combinations thereof, configured to remove heat from portions or components of the apparatus 610.

Any or all of the exemplary instructions and data types described herein and other practicable types of data may be stored in any number, type, and/or configuration of memory devices that is or becomes known. The memory device 640 may, for example, comprise one or more data tables or files, databases, table spaces, registers, and/or other storage structures. In some embodiments, multiple databases and/or storage structures (and/or multiple memory devices 640) may be utilized to store information associated with the apparatus 610. According to some embodiments, the memory device 640 may be incorporated into and/or otherwise coupled to the apparatus 610 (e.g., as shown) or may simply be accessible to the apparatus 610 (e.g., externally located and/or situated).

Referring now to FIG. 7A, FIG. 7B, FIG. 7C, FIG. 7D, and FIG. 7E, perspective diagrams of exemplary data storage devices 740a-e according to some embodiments are shown. The data storage devices 740a-e may, for example, be utilized to store instructions and/or data, such as the object detection instructions 642-1, routing instructions 642-2, loss instructions 642-3 (e.g., detection and/or classification), interface instructions 642-4, vehicle data 644-1, sensor data 644-2, contents data 644-3, tracking data 644-4, and/or



insurance data **644-5**, each of which is presented in reference to FIG. **6** herein. In some embodiments, instructions stored on the data storage devices **740a-e** may, when executed by a processor, cause the implementation of and/or facilitate the method **400** of FIG. **4** herein, and/or portions thereof.

According to some embodiments, the first data storage device **740a** may comprise one or more various types of internal and/or external hard drives. The first data storage device **740a** may, for example, comprise a data storage medium **746** that is read, interrogated, and/or otherwise communicatively coupled to and/or via a disk reading device **848**. In some embodiments, the first data storage device **740a** and/or the data storage medium **746** may be configured to store information utilizing one or more magnetic, inductive, and/or optical means (e.g., magnetic, inductive, and/or optical-encoding). The data storage medium **746**, depicted as a first data storage medium **746a** for example (e.g., breakout cross-section “A”), may comprise one or more of a polymer layer **746a-1**, a magnetic data storage layer **746a-2**, a non-magnetic layer **746a-3**, a magnetic base layer **746a-4**, a contact layer **746a-5**, and/or a substrate layer **746a-6**. According to some embodiments, a magnetic read head **748a** may be coupled and/or disposed to read data from the magnetic data storage layer **746a-2**.

In some embodiments, the data storage medium **746**, depicted as a second data storage medium **746b** for example (e.g., breakout cross-section “B”), may comprise a plurality of data points **746b-2** disposed with the second data storage medium **746b**. The data points **746b-2** may, in some embodiments, be read and/or otherwise interfaced with via a laser-enabled read head **748b** disposed and/or coupled to direct a laser beam through the second data storage medium **746b**.

In some embodiments, the second data storage device **740b** may comprise a CD, CD-ROM, DVD, Blu-Ray™ Disc, and/or other type of optically-encoded disk and/or other storage medium that is or becomes known or practicable. In some embodiments, the third data storage device **740c** may comprise a USB keyfob, dongle, and/or other type of flash memory data storage device that is or becomes known or practicable. In some embodiments, the fourth data storage device **740d** may comprise RAM of any type, quantity, and/or configuration that is or becomes practicable and/or desirable. In some embodiments, the fourth data storage device **740d** may comprise an off-chip cache, such as a Level 2 (L2) cache memory device. According to some embodiments, the fifth data storage device **740e** may comprise an on-chip memory device, such as a Level 1 (L1) cache memory device.

The data storage devices **740a-e** may generally store program instructions, code, and/or modules that, when executed by a processing device cause a particular machine to function in accordance with one or more embodiments described herein. The data storage devices **740a-e** depicted in FIG. **7A**, FIG. **7B**, FIG. **7C**, FIG. **7D**, and FIG. **7E** are representative of a class and/or subset of computer-readable media that are defined herein as “computer-readable memory” (e.g., non-transitory memory devices as opposed to transmission devices or media).

Throughout the description herein and unless otherwise specified, the following terms may include and/or encompass the example meanings provided. These terms and illustrative example meanings are provided to clarify the language selected to describe embodiments both in the specification and in the appended claims, and accordingly, are not intended to be generally limiting. While not generally limiting and while not limiting for all described embodiments, in some embodiments, the terms are specifically

limited to the example definitions and/or examples provided. Other terms are defined throughout the present description.

Some embodiments described herein are associated with a “user device” or a “network device”. As used herein, the terms “user device” and “network device” may be used interchangeably and may generally refer to any device that can communicate via a network. Examples of user or network devices include a PC, a workstation, a server, a printer, a scanner, a facsimile machine, a copier, a Personal Digital Assistant (PDA), a storage device (e.g., a disk drive), a hub, a router, a switch, and a modem, a video game console, or a wireless phone. User and network devices may comprise one or more communication or network components. As used herein, a “user” may generally refer to any individual and/or entity that operates a user device. Users may comprise, for example, customers, consumers, product underwriters, product distributors, customer service representatives, agents, brokers, etc.

As used herein, the term “network component” may refer to a user or network device, or a component, piece, portion, or combination of user or network devices. Examples of network components may include a Static Random Access Memory (SRAM) device or module, a network processor, and a network communication path, connection, port, or cable.

In addition, some embodiments are associated with a “network” or a “communication network”. As used herein, the terms “network” and “communication network” may be used interchangeably and may refer to any object, entity, component, device, and/or any combination thereof that permits, facilitates, and/or otherwise contributes to or is associated with the transmission of messages, packets, signals, and/or other forms of information between and/or within one or more network devices. Networks may be or include a plurality of interconnected network devices. In some embodiments, networks may be hard-wired, wireless, virtual, neural, and/or any other configuration of type that is or becomes known. Communication networks may include, for example, one or more networks configured to operate in accordance with the Fast Ethernet LAN transmission standard 802.3-2002® published by the Institute of Electrical and Electronics Engineers (IEEE). In some embodiments, a network may include one or more wired and/or wireless networks operated in accordance with any communication standard or protocol that is or becomes known or practicable.

As used herein, the terms “information” and “data” may be used interchangeably and may refer to any data, text, voice, video, image, message, bit, packet, pulse, tone, waveform, and/or other type or configuration of signal and/or information. Information may comprise information packets transmitted, for example, in accordance with the Internet Protocol Version 6 (IPv6) standard as defined by “Internet Protocol Version 6 (IPv6) Specification” RFC 1883, published by the Internet Engineering Task Force (IETF), Network Working Group, S. Deering et al. (December 1995). Information may, according to some embodiments, be compressed, encoded, encrypted, and/or otherwise packaged or manipulated in accordance with any method that is or becomes known or practicable.

In addition, some embodiments described herein are associated with an “indication”. As used herein, the term “indication” may be used to refer to any indicia and/or other information indicative of or associated with a subject, item, entity, and/or other object and/or idea. As used herein, the phrases “information indicative of” and “indicia” may be used to refer to any information that represents, describes,



and/or is otherwise associated with a related entity, subject, or object. Indicia of information may include, for example, a code, a reference, a link, a signal, an identifier, and/or any combination thereof and/or any other informative representation associated with the information. In some embodiments, indicia of information (or indicative of the information) may be or include the information itself and/or any portion or component of the information. In some embodiments, an indication may include a request, a solicitation, a broadcast, and/or any other form of information gathering and/or dissemination.

Numerous embodiments are described in this patent application, and are presented for illustrative purposes only. The described embodiments are not, and are not intended to be, limiting in any sense. The presently disclosed invention(s) are widely applicable to numerous embodiments, as is readily apparent from the disclosure. One of ordinary skill in the art will recognize that the disclosed invention(s) may be practiced with various modifications and alterations, such as structural, logical, software, and electrical modifications. Although particular features of the disclosed invention(s) may be described with reference to one or more particular embodiments and/or drawings, it should be understood that such features are not limited to usage in the one or more particular embodiments or drawings with reference to which they are described, unless expressly specified otherwise.

Devices that are in communication with each other need not be in continuous communication with each other, unless expressly specified otherwise. On the contrary, such devices need only transmit to each other as necessary or desirable, and may actually refrain from exchanging data most of the time. For example, a machine in communication with another machine via the Internet may not transmit data to the other machine for weeks at a time. In addition, devices that are in communication with each other may communicate directly or indirectly through one or more intermediaries.

A description of an embodiment with several components or features does not imply that all or even any of such components and/or features are required. On the contrary, a variety of optional components are described to illustrate the wide variety of possible embodiments of the present invention(s). Unless otherwise specified explicitly, no component and/or feature is essential or required.

Further, although process steps, algorithms or the like may be described in a sequential order, such processes may be configured to work in different orders. In other words, any sequence or order of steps that may be explicitly described does not necessarily indicate a requirement that the steps be performed in that order. The steps of processes described herein may be performed in any order practical. Further, some steps may be performed simultaneously despite being described or implied as occurring non-simultaneously (e.g., because one step is described after the other step). Moreover, the illustration of a process by its depiction in a drawing does not imply that the illustrated process is exclusive of other variations and modifications thereto, does not imply that the illustrated process or any of its steps are necessary to the invention, and does not imply that the illustrated process is preferred.

“Determining” something can be performed in a variety of manners and therefore the term “determining” (and like terms) includes calculating, computing, deriving, looking up (e.g., in a table, database or data structure), ascertaining and the like. The term “computing” as utilized herein may generally refer to any number, sequence, and/or type of electronic processing activities performed by an electronic device, such as, but not limited to looking up (e.g., accessing

a lookup table or array), calculating (e.g., utilizing multiple numeric values in accordance with a mathematic formula), deriving, and/or defining.

It will be readily apparent that the various methods and algorithms described herein may be implemented by, e.g., appropriately and/or specially-programmed computers and/or computing devices. Typically a processor (e.g., one or more microprocessors) will receive instructions from a memory or like device, and execute those instructions, thereby performing one or more processes defined by those instructions. Further, programs that implement such methods and algorithms may be stored and transmitted using a variety of media (e.g., computer readable media) in a number of manners. In some embodiments, hard-wired circuitry or custom hardware may be used in place of, or in combination with, software instructions for implementation of the processes of various embodiments. Thus, embodiments are not limited to any specific combination of hardware and software.

A “processor” generally means any one or more microprocessors, CPU devices, computing devices, microcontrollers, digital signal processors, or like devices, as further described herein.

The term “computer-readable medium” refers to any medium that participates in providing data (e.g., instructions or other information) that may be read by a computer, a processor or a like device. Such a medium may take many forms, including but not limited to, non-volatile media, volatile media, and transmission media. Non-volatile media include, for example, optical or magnetic disks and other persistent memory. Volatile media include DRAM, which typically constitutes the main memory. Transmission media include coaxial cables, copper wire and fiber optics, including the wires that comprise a system bus coupled to the processor. Transmission media may include or convey acoustic waves, light waves and electromagnetic emissions, such as those generated during RF and IR data communications. Common forms of computer-readable media include, for example, a floppy disk, a flexible disk, hard disk, magnetic tape, any other magnetic medium, a CD-ROM, DVD, any other optical medium, punch cards, paper tape, any other physical medium with patterns of holes, a RAM, a PROM, an EPROM, a FLASH-EEPROM, any other memory chip or cartridge, a carrier wave, or any other medium from which a computer can read.

The term “computer-readable memory” may generally refer to a subset and/or class of computer-readable medium that does not include transmission media, such as waveforms, carrier waves, electromagnetic emissions, etc. Computer-readable memory may typically include physical media upon which data (e.g., instructions or other information) are stored, such as optical or magnetic disks and other persistent memory, DRAM, a floppy disk, a flexible disk, hard disk, magnetic tape, any other magnetic medium, a CD-ROM, DVD, any other optical medium, punch cards, paper tape, any other physical medium with patterns of holes, a RAM, a PROM, an EPROM, a FLASH-EEPROM, any other memory chip or cartridge, computer hard drives, backup tapes, Universal Serial Bus (USB) memory devices, and the like.

Various forms of computer readable media may be involved in carrying data, including sequences of instructions, to a processor. For example, sequences of instruction (i) may be delivered from RAM to a processor, (ii) may be carried over a wireless transmission medium, and/or (iii) may be formatted according to numerous formats, standards or protocols, such as Bluetooth™, TDMA, CDMA, 3G.



Where databases are described, it will be understood by one of ordinary skill in the art that (i) alternative database structures to those described may be readily employed, and (ii) other memory structures besides databases may be readily employed. Any illustrations or descriptions of any sample databases presented herein are illustrative arrangements for stored representations of information. Any number of other arrangements may be employed besides those suggested by, e.g., tables illustrated in drawings or elsewhere. Similarly, any illustrated entries of the databases represent exemplary information only; one of ordinary skill in the art will understand that the number and content of the entries can be different from those described herein. Further, despite any depiction of the databases as tables, other formats (including relational databases, object-based models and/or distributed databases) could be used to store and manipulate the data types described herein. Likewise, object methods or behaviors of a database can be used to implement various processes, such as the described herein. In addition, the databases may, in a known manner, be stored locally or remotely from a device that accesses data in such a database.

The present invention can be configured to work in a network environment including a computer that is in communication, via a communications network, with one or more devices. The computer may communicate with the devices directly or indirectly, via a wired or wireless medium, such as the Internet, LAN, WAN or Ethernet, Token Ring, or via any appropriate communications means or combination of communications means. Each of the devices may comprise computers, such as those based on the Intel® Pentium® or Centrino™ processor, that are adapted to communicate with the computer. Any number and type of machines may be in communication with the computer.

The present disclosure provides, to one of ordinary skill in the art, an enabling description of several embodiments and/or inventions. Some of these embodiments and/or inventions may not be claimed in the present application, but may nevertheless be claimed in one or more continuing applications that claim the benefit of priority of the present application. Applicant intends to file additional applications to pursue patents for subject matter that has been disclosed and enabled but not claimed in the present application.

It will be understood that various modifications can be made to the embodiments of the present disclosure herein without departing from the scope thereof. Therefore, the above description should not be construed as limiting the disclosure, but merely as embodiments thereof. Those skilled in the art will envision other modifications within the scope of the invention as defined by the claims appended hereto.

What is claimed is:

1. A method of operating an Artificial Intelligence (AI) cargo management system, comprising:

receiving, via an electronic transceiver device and from a first remote mobile electronic device, data descriptive of a plurality of items comprising an instance of cargo; receiving, via the electronic transceiver device and from the first remote mobile electronic device, at least one first image descriptive of the instance of cargo at a first point in time;

computing, by an execution of AI image analysis logic by the electronic processing device, a correlation between one or more portions of the at least one first image and one or more respective items from the plurality of items comprising the instance of cargo;

receiving, via the electronic transceiver device and from a second remote mobile electronic device, at least one second image descriptive of the instance of cargo at a second point in time;

identifying, by an execution of the AI image analysis logic by the electronic processing device, a difference between the images, comprising at least one portion of the at least one second image that differs from a corresponding portion of the at least one first image;

identifying, based on the correlation between the one or more portions of the at least one first image and the one or more respective items from the plurality of items comprising the instance of cargo, a first item from the plurality of items comprising the instance of cargo that corresponds to the identified difference between the images; and

generating an alert including information that identifies the first item from the plurality of items comprising the instance of cargo.

2. The method of claim 1, further comprising:

categorizing, by an execution of the AI image analysis logic by the electronic processing device, the difference between the images as one or more of a plurality of pre-defined types of differences.

3. The method of claim 2, wherein the generating of the alert further comprises:

generating an alert including the categorized one or more of the plurality of pre-defined types of differences.

4. The method of claim 2, wherein the plurality of pre-defined types of differences comprises: (i) a movement of the first item; (ii) a change in a appearance of the first item; and (iii) a disappearance of the first item.

5. The method of claim 1, wherein the computing of the correlation between the one or more portions of the at least one first image and the one or more respective items from the plurality of items comprising the instance of cargo, comprises:

identifying, from the at least one first image, at least one of: (i) a seal number; (ii) a serial number; (iii) a shape; (iv) a color; and (v) a dimension.

6. The method of claim 1, wherein the data descriptive of the plurality of items comprises data descriptive of at least one of: (i) a quantity; (ii) a type; (iii) a position; (iv) a location; (v) an identifier; (vi) a characteristic parameter; (vii) a monetary value; (viii) an origin location; (ix) a destination location; (x) a manufacturer; and (xi) a model.

7. The method of claim 1, wherein the first remote mobile electronic device and the second remote mobile electronic device comprise the same device.

8. The method of claim 1, wherein the first remote mobile electronic device is associated with a loader of the cargo and the first point in time comprises a time of loading the cargo into a cargo container, and wherein the second remote mobile electronic device is associated with a transporter of the cargo and the second point in time comprises a time of transporting the cargo via the cargo container.

9. The method of claim 1, further comprising:

transmitting, via the electronic transceiver device and to the first remote mobile electronic device, identifying information descriptive of the transporter.

10. The method of claim 9, further comprising:

receiving, via the electronic transceiver device and from the first remote mobile electronic device, an indication that the identity of the transporter has been verified based on the identifying information descriptive of the transporter.



## 31

11. The method of claim 10, further comprising:  
 transmitting, via the electronic transceiver device and to  
 a starter device of a transport vehicle coupled to the  
 instance of cargo, and in response to the receiving of  
 the indication that the identity of the transporter has  
 been verified based on the identifying information  
 descriptive of the transporter, a command that autho-  
 rizes movement of the transport vehicle.

12. The method of claim 8, further comprising:  
 transmitting, via the electronic transceiver device and to  
 the second remote mobile electronic device, identifying  
 information descriptive of the loader.

13. The method of claim 12, further comprising:  
 receiving, via the electronic transceiver device and from  
 the second remote mobile electronic device, an indica-  
 tion that the identity of the loader has been verified  
 based on the identifying information descriptive of the  
 loader.

14. The method of claim 13, further comprising:  
 transmitting, via the electronic transceiver device and to  
 a starter device of a transport vehicle coupled to the

## 32

instance of cargo, and in response to the receiving of  
 the indication that the identity of the loader has been  
 verified based on the identifying information descrip-  
 tive of the loader, a command that authorizes move-  
 ment of the transport vehicle.

15. The method of claim 1, wherein the data descriptive  
 of the plurality of items comprising the instance of cargo  
 comprises data identifying at least one physical charac-  
 teristic of the instance of cargo, and wherein the method further  
 comprises:

computing, by an execution of risk-based navigational  
 routing rules by the electronic processing device, and  
 based at least in part on the at least one physical  
 characteristic of the instance of cargo, a risk-based  
 navigational route for transporting the instance of cargo  
 from a first location to a second location; and

transmitting, via the electronic transceiver device and to  
 the second remote mobile electronic device, graphical  
 information descriptive of the risk-based navigational  
 route.

\* \* \* \* \*