

US011304561B2

(12) **United States Patent**
Gill et al.

(10) **Patent No.:** **US 11,304,561 B2**
(45) **Date of Patent:** ***Apr. 19, 2022**

(54) **COOKING DEVICE AND COMPONENTS THEREOF**

(71) Applicant: **SharkNinja Operating LLC**,
Needham, MA (US)

(72) Inventors: **Aaron Michael Gill**, Boston, MA (US);
Ross Richardson, Dover, MA (US);
Naomi Kalia Williams Zabel, Oakland,
CA (US); **Da Deng**, Newton, MA (US);
Mete Gursel, Istanbul (TR); **Andrew**
John Roy Tattersfield, London (GB);
Niall Christopher Denham, London
(GB); **Roger Neil Jackson**, Cornwall
(GB); **Ronan Patrick Leahy**, London
(GB); **Evan James White**, Brookline,
MA (US); **Thomas Guerin**, Boston,
MA (US); **Chris Martin**, Concord, MA
(US); **Nathaniel R. Lavins**, Somerville,
MA (US); **Mackenzie Lee Swanhart**,
Boston, MA (US); **Samuel Andrew**
Ferguson, Medford, MA (US); **Scott**
James Stewart, Boston, MA (US)

(73) Assignee: **SharkNinja Operating LLC**,
Needham, MA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 12 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **16/357,194**

(22) Filed: **Mar. 18, 2019**

(65) **Prior Publication Data**
US 2019/0231127 A1 Aug. 1, 2019

Related U.S. Application Data
(63) Continuation of application No. 16/059,876, filed on
Aug. 9, 2018.
(Continued)

(51) **Int. Cl.**
A47J 37/06 (2006.01)
A47J 27/04 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC *A47J 37/0641* (2013.01); *A23L 5/17*
(2016.08); *A47J 27/04* (2013.01); *A47J 27/08*
(2013.01);
(Continued)

(58) **Field of Classification Search**
CPC *A47J 37/0641*; *A47J 27/04*; *A47J 27/0802*;
A47J 39/003; *A47J 27/0804*; *A47J 27/08*;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

472,002 A 3/1892 Ross et al.
1,254,384 A 1/1918 Albro
(Continued)

FOREIGN PATENT DOCUMENTS


CN 1139304 A 11/1995
CN 2253170 Y 4/1997
(Continued)

OTHER PUBLICATIONS

Notification of Transmittal of the International Search Report of the
International Searching Authority, or the Declaration. PCT/US2018/
046077, dated Dec. 19, 2018, 7 pages.
(Continued)

Primary Examiner — Eric S Stapleton
(74) *Attorney, Agent, or Firm* — Mintz Levin Cohn Ferris
Glovsky and Popeo, PC; Lisa Adams

(57) **ABSTRACT**
Disclosed herein is a cooking system for cooking food, the
system including a housing defining a hollow chamber
configured to receive a food container. The housing has an
upper portion defining an opening to the hollow chamber. A
(Continued)



lid is attachable about the upper portion of the housing and is configured to extend across the opening to the hollow chamber. At least one heating element is associated with at least one of said housing and said lid. The cooking system is operable in a plurality of modes including a pressure cooking mode and a convective cooking mode. In the pressure cooking mode, the cooking system is operable as a pressure cooker and in the convective cooking mode, the cooking system is operable as a convection cooker.

27 Claims, 30 Drawing Sheets

Related U.S. Application Data

- (60) Provisional application No. 62/543,082, filed on Aug. 9, 2017.
- (51) **Int. Cl.**
A47J 27/08 (2006.01)
A23L 5/10 (2016.01)
A47J 39/00 (2006.01)
A47J 36/12 (2006.01)
A47J 37/12 (2006.01)
- (52) **U.S. Cl.**
 CPC *A47J 27/0802* (2013.01); *A47J 39/003* (2013.01); *A47J 36/12* (2013.01); *A47J 37/0623* (2013.01); *A47J 37/1266* (2013.01)
- (58) **Field of Classification Search**
 CPC *A47J 43/0772*; *A47J 27/086*; *A47J 27/004*; *A47J 36/12*; *A47J 37/0623*; *A47J 37/1266*
 USPC 99/330
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,986,088 A * 1/1935 Lanoelet F24C 15/325
 219/400
 2,055,972 A * 9/1936 Fritsche A47J 37/0623
 219/452.13
 2,188,757 A * 1/1940 Moon A47J 37/0623
 99/340
 2,235,911 A 3/1941 Wilcox
 2,253,833 A * 8/1941 Volks A47J 37/0676
 99/446
 2,313,968 A * 3/1943 Reich A47J 36/06
 99/375
 2,378,950 A * 6/1945 Reich A47J 37/015
 426/523
 2,429,282 A 10/1947 Ness
 2,430,582 A 11/1947 Ernest
 2,462,287 A 2/1949 Richesan et al.
 2,532,639 A 12/1950 Payne
 2,622,591 A 12/1952 Bramberry, Jr.
 2,952,764 A 9/1960 Yoshitada
 2,622,231 A 1/1962 Gray
 3,076,405 A * 2/1963 Lang A47J 37/108
 99/445
 3,122,134 A * 2/1964 Reeves A47J 37/0688
 126/41 R
 3,514,301 A * 5/1970 Berger A47J 37/0676
 99/390
 3,529,582 A * 9/1970 Bohdan F24C 15/325
 126/21 R
 3,610,885 A * 10/1971 Zingg A47J 37/0629
 219/451.1
 3,821,454 A * 6/1974 Lobel A22C 9/00
 426/524

3,828,760 A * 8/1974 Farber A21B 1/02
 126/21 A
 4,071,739 A 1/1978 Jenn et al.
 4,106,486 A * 8/1978 Lee A47J 27/04
 126/369
 4,106,488 A * 8/1978 Gordon A61K 9/5094
 128/898
 4,148,250 A * 4/1979 Miki A47J 36/06
 220/374
 4,162,741 A * 7/1979 Walker A47J 27/092
 220/203.05
 4,164,174 A 8/1979 Wallsten
 4,210,072 A * 7/1980 Pedrini A47J 37/0623
 99/340
 4,241,288 A 12/1980 Aoshima et al.
 4,268,741 A * 5/1981 O'Brien H05B 3/68
 219/430
 4,313,051 A 1/1982 Aoshima
 4,315,138 A 2/1982 Miwa
 4,374,318 A * 2/1983 Gilliom A47J 37/0623
 126/21 A
 4,410,030 A 10/1983 Skala
 4,430,557 A 2/1984 Eichelberger et al.
 4,484,063 A * 11/1984 Whittenburg F24C 15/325
 126/21 A
 4,484,083 A * 11/1984 Jefferies B60K 6/105
 290/45
 4,509,412 A * 4/1985 Whittenburg A47J 27/04
 126/20
 4,528,975 A 7/1985 Wang
 4,591,698 A * 5/1986 Chang A47J 37/015
 219/386
 4,622,231 A 11/1986 Swartley
 4,625,097 A 11/1986 Miwa
 4,670,282 A 6/1987 Onishi et al.
 4,728,762 A * 3/1988 Roth A47J 36/027
 219/681
 4,771,162 A * 9/1988 Schatz A61C 13/14
 126/21 A
 4,829,158 A 5/1989 Burnham
 4,848,217 A * 7/1989 Koziol A47J 37/0694
 99/426
 4,889,972 A * 12/1989 Chang A47J 37/015
 219/472
 4,920,251 A 4/1990 Whitenack et al.
 4,980,171 A 12/1990 Fels et al.
 4,995,313 A 2/1991 Delau et al.
 5,000,085 A * 3/1991 Archer A47J 37/0623
 126/21 A
 5,012,071 A * 4/1991 Henke A47J 36/38
 126/299 C
 5,029,519 A * 7/1991 Boyen A47J 36/38
 126/21 A
 5,031,519 A * 7/1991 Toida A47J 27/002
 126/369
 5,036,179 A * 7/1991 Westerberg A47J 37/0635
 219/411
 5,048,400 A * 9/1991 Ueda A47J 27/092
 99/332
 5,067,396 A 11/1991 Sorensen et al.
 5,092,229 A * 3/1992 Chen A47J 27/0811
 126/348
 5,105,725 A * 4/1992 Haglund A47J 37/0704
 126/25 R
 5,205,274 A * 4/1993 Smith A21B 1/245
 126/21 A
 5,251,542 A * 10/1993 Itoh A47J 36/10
 206/545
 5,280,749 A 1/1994 Smit
 5,329,919 A 7/1994 Chang
 5,355,777 A * 10/1994 Chen A47J 39/00
 206/545
 5,416,950 A * 5/1995 Dornbush A21B 3/132
 126/275 E
 5,431,092 A 7/1995 Guillory
 5,445,061 A * 8/1995 Barradas A21B 7/005
 219/400

(56)

References Cited

U.S. PATENT DOCUMENTS

- 5,445,081 A * 8/1995 Kunczynski B61B 9/00
104/165
- 5,466,912 A 11/1995 Dornbush et al.
- 5,485,780 A * 1/1996 Koether F24C 15/006
219/400
- 5,513,558 A * 5/1996 Erickson A47J 37/015
126/21 A
- 5,526,734 A * 6/1996 Harrison A47J 37/0641
126/21 A
- 5,528,734 A * 6/1996 Sanchez G06F 3/1206
358/1.16
- 5,549,039 A * 8/1996 Ito A47J 36/10
16/383
- 5,567,458 A * 10/1996 Wu A47J 27/004
219/433
- 5,588,352 A * 12/1996 Harrison A47J 37/0641
99/339
- 5,590,583 A * 1/1997 Harrison A47J 37/0623
99/327
- 5,615,607 A * 4/1997 Delaquis A47J 36/08
210/464
- 5,619,983 A * 4/1997 Smith A47J 27/16
126/20
- 5,632,403 A * 5/1997 Deng A47J 27/08
220/203.07
- 5,649,476 A * 7/1997 Montagnino A47J 27/04
122/31.1
- 5,676,044 A * 10/1997 Lara, Jr. A21B 1/245
126/21 A
- 5,699,722 A * 12/1997 Erickson A47J 37/0623
126/21 A
- 5,740,721 A * 4/1998 Bizard H01H 3/16
99/337
- 5,768,976 A * 6/1998 Suk A47J 27/0806
99/337
- 5,839,357 A * 11/1998 Ha A47J 27/0813
99/337
- 5,896,808 A * 4/1999 Graur A47J 37/0623
219/386
- 5,932,130 A * 8/1999 Taino F24C 7/087
219/702
- 5,967,021 A * 10/1999 Yung A21B 7/005
366/144
- 5,970,858 A 10/1999 Boehm et al.
- 6,006,939 A * 12/1999 Wai A47J 27/09
220/201
- 6,014,986 A * 1/2000 Baumgarten A47J 27/09
137/522
- 6,016,797 A 1/2000 Nowicke, Jr.
- 6,019,029 A * 2/2000 Chan A47J 27/0813
220/293
- 6,023,050 A * 2/2000 Violi F24C 15/327
126/20
- 6,037,570 A 3/2000 Noles
- 6,060,698 A * 5/2000 Petrides A47J 36/32
219/492
- 6,066,837 A * 5/2000 McCormick F24C 7/087
219/506
- 6,067,896 A * 5/2000 Elorza A47J 27/0813
220/293
- 6,070,518 A * 6/2000 Kao A47J 27/086
219/465.1
- 6,082,249 A * 7/2000 Su A47J 27/004
99/340
- 6,083,543 A * 7/2000 Kim A47J 36/32
426/231
- 6,097,016 A * 8/2000 Hirata H05B 6/6435
219/720
- 6,104,004 A * 8/2000 Ragland A47J 37/0635
219/386
- 6,105,808 A * 8/2000 Mendonca A47J 27/09
220/316
- 6,116,151 A * 9/2000 Fickert A47J 27/0813
220/316
- 6,125,737 A * 10/2000 Chang A47J 27/004
219/400
- 6,135,012 A * 10/2000 Kao A47J 27/0802
219/453.11
- 6,135,013 A * 10/2000 Barrena A47J 27/09
220/203.01
- 6,158,606 A * 12/2000 Oliver A47J 27/09
126/388.1
- 6,170,390 B1 1/2001 Backus et al.
- 6,173,643 B1 * 1/2001 Qian A47J 27/0802
219/439
- 6,178,876 B1 * 1/2001 Kao A47J 27/08
219/453.11
- 6,191,393 B1 * 2/2001 Park A47J 27/002
219/439
- 6,201,217 B1 * 3/2001 Moon A47J 37/0623
126/21 A
- 6,242,025 B1 * 6/2001 Lesky A47J 27/0802
426/231
- 6,252,206 B1 * 6/2001 Leukhardt, III F24C 7/087
219/410
- 6,255,630 B1 * 7/2001 Barnes F24C 7/082
219/395
- 6,257,124 B1 * 7/2001 Chen A47J 27/0813
220/314
- 6,262,396 B1 * 7/2001 Witt A47J 37/0623
219/409
- 6,267,046 B1 * 7/2001 Wanat A47J 27/05
99/332
- 6,268,592 B1 * 7/2001 Hu A47J 37/0676
219/450.1
- 6,269,737 B1 * 8/2001 Rigney A47J 27/04
126/369
- 6,271,504 B1 * 8/2001 Barritt A47J 37/0623
126/211
- 6,283,014 B1 * 9/2001 Ng A47J 27/0802
219/431
- 6,283,015 B1 * 9/2001 Kwon A47J 27/09
219/435
- 6,320,166 B1 * 11/2001 Park A47J 27/002
219/428
- 6,355,914 B1 * 3/2002 Stockley A47J 37/0623
219/398
- 6,384,381 B2 5/2002 Witt et al.
- 6,393,969 B1 5/2002 Kim
- D458,078 S 6/2002 Lin
- 6,399,925 B1 * 6/2002 Pickering A47J 37/0623
126/211
- 6,414,254 B1 * 7/2002 McNair A47J 27/0802
200/82 C
- 6,425,320 B1 * 7/2002 Chameroy A47J 27/0806
126/373.1
- 6,450,085 B1 * 9/2002 Riesselmann A47J 37/0623
219/400
- 6,450,361 B1 * 9/2002 Mendelson A47J 27/0811
220/202
- 6,455,085 B1 * 9/2002 Duta A47J 27/16
426/233
- 6,467,645 B2 * 10/2002 Park A47J 27/002
220/592.28
- 6,486,453 B1 * 11/2002 Bales H05B 6/6435
219/400
- 6,494,337 B1 * 12/2002 Moroni A47J 27/0813
220/314
- 6,505,545 B2 1/2003 Kennedy et al.
- 6,509,550 B1 * 1/2003 Li A47J 27/004
219/386
- 6,513,420 B1 * 2/2003 Park A47J 27/0813
220/314
- 6,515,262 B1 2/2003 Li
- 6,523,459 B1 * 2/2003 Chameroy A47J 27/09
220/316
- 6,528,772 B1 * 3/2003 Graves H05B 6/6435
219/506

(56)

References Cited

U.S. PATENT DOCUMENTS

6,540,097 B1 *	4/2003	Beck	A47J 27/0813 220/321	6,837,150 B2	1/2005	Backus et al.	
6,545,252 B2 *	4/2003	Wang	A47J 27/004 219/430	6,841,762 B2 *	1/2005	Suzuki	F24C 7/082 219/490
6,552,309 B1 *	4/2003	Kish	H05B 6/6441 219/413	6,845,707 B1 *	1/2005	Xu	A47J 36/165 99/339
6,559,427 B1 *	5/2003	Barnes	F24C 7/082 219/486	6,846,504 B1	1/2005	Yarnell	
6,565,903 B2	5/2003	Ng et al.		6,851,351 B2 *	2/2005	Payen	A47J 36/38 55/DIG. 36
6,568,314 B1	5/2003	Stepanova		6,872,921 B1	3/2005	Decobert et al.	
6,573,483 B1 *	6/2003	DeCobert	A47J 36/32 219/506	6,874,408 B2 *	4/2005	Backus	A47J 37/041 99/327
6,602,530 B1	8/2003	Weber et al.		6,877,633 B2 *	4/2005	Niese	A47J 27/08 220/315
6,603,099 B2	8/2003	Gouthiere		6,903,310 B1 *	6/2005	Lee, Jr	A47J 27/04 219/490
6,604,453 B2 *	8/2003	Niese	A47J 27/0813 220/314	6,917,017 B2 *	7/2005	Moon	A47J 37/0623 126/21 A
6,615,706 B1 *	9/2003	Wu	A47J 37/0611 99/331	6,930,286 B2	8/2005	Kim	
6,615,708 B1 *	9/2003	Lin	A47J 36/38 126/21 A	6,933,477 B2 *	8/2005	Becker	F24C 7/082 219/411
6,617,554 B2 *	9/2003	Moon	A47J 37/0623 219/481	6,935,223 B2 *	8/2005	Kobayashi	A47J 27/0817 126/374.1
6,631,824 B2 *	10/2003	Park	A47J 27/002 220/573.1	6,936,795 B1 *	8/2005	Moon	A47J 37/0623 126/21 A
6,648,162 B1 *	11/2003	Wooderson	A47J 27/0813 220/203.27	6,936,801 B1 *	8/2005	Head	H05B 6/6435 200/14
6,657,167 B2 *	12/2003	Loveless	A47J 37/0623 219/400	6,941,857 B2 *	9/2005	McLemore	A47J 37/1209 99/403
6,669,047 B2 *	12/2003	Wooderson	A47J 27/0813 220/203.27	6,972,397 B2	12/2005	Ha	
6,695,319 B1 *	2/2004	Anota	A47J 27/09 220/203.11	7,009,147 B1 *	3/2006	Schulte	F24C 7/06 219/400
D487,212 S *	3/2004	Park	D7/360	7,012,220 B2 *	3/2006	Boyer	F24C 7/082 219/395
6,698,337 B1 *	3/2004	Park	A47J 36/36 99/342	7,012,221 B2 *	3/2006	Li	A47J 27/004 219/386
6,703,061 B2	3/2004	Kennedy et al.		7,021,203 B2 *	4/2006	Backus	A47J 37/041 99/421 H
6,705,209 B2 *	3/2004	Yang	A47J 27/0802 219/440	7,021,204 B2 *	4/2006	Backus	A47J 37/041 99/339
6,723,963 B2 *	4/2004	Ronda	A47J 27/05 219/401	7,024,104 B2	4/2006	Moore et al.	
6,730,881 B1 *	5/2004	Arntz	F24C 1/02 219/393	7,045,745 B2	5/2006	Kim	
6,730,882 B2 *	5/2004	Atkinson	F24C 7/08 126/194	7,053,337 B2 *	5/2006	Ragan	A47J 37/0611 126/275 R
6,730,889 B1 *	5/2004	Jones-Lawlor	A47J 36/32 219/506	7,060,941 B1	6/2006	Embury et al.	
6,736,131 B2 *	5/2004	Yamamoto	A47J 37/1247 126/376.1	7,060,943 B2 *	6/2006	Hwang	H05B 6/6435 219/395
6,740,855 B1	5/2004	Decobert et al.		7,081,601 B2 *	7/2006	Boyer	F24C 7/082 219/412
6,742,445 B2 *	6/2004	Backus	A47J 37/041 126/194	7,082,871 B2 *	8/2006	Schultz	A47J 27/0813 220/316
6,747,250 B1 *	6/2004	Cha	A47J 37/0623 219/386	7,086,326 B2	8/2006	Yokoyama	
6,755,319 B2 *	6/2004	Park	A47J 27/0804 16/425	7,087,873 B2	8/2006	Hayakawa et al.	
6,758,132 B1 *	7/2004	Kuo	A47J 37/0676 219/386	7,091,454 B2	8/2006	Cho et al.	
6,777,651 B1 *	8/2004	Boyer	F24C 7/082 219/400	7,105,780 B2	9/2006	De	
6,782,805 B2	8/2004	Backus et al.		7,126,088 B2 *	10/2006	Horton	F24C 7/082 219/412
6,782,806 B2	8/2004	Backus et al.		7,148,451 B2 *	12/2006	Miyake	A47J 36/32 219/440
6,802,429 B1 *	10/2004	Wildman	A47J 36/06 220/244	7,154,069 B1 *	12/2006	Gordon	A47J 27/0817 219/440
6,809,297 B2 *	10/2004	Moon	A47J 37/0641 219/400	7,156,087 B1 *	1/2007	Churchill, III	A47J 27/04 126/25 R
6,812,433 B1 *	11/2004	Barritt	F24C 15/325 219/412	7,157,675 B2 *	1/2007	Imura	A47J 27/62 219/627
6,815,644 B1 *	11/2004	Muegge	F24C 1/04 126/332	7,166,822 B1 *	1/2007	Chang	A47J 27/022 219/430
6,831,254 B2 *	12/2004	Barritt	F24C 7/087 165/61	7,171,923 B2	2/2007	Hayakawa et al.	
6,833,534 B2	12/2004	Bellassai et al.		7,208,701 B2	4/2007	Fraccon et al.	
				7,208,702 B2	4/2007	Choi	
				7,238,921 B2	7/2007	Beesley et al.	
				7,250,587 B2	7/2007	Ely et al.	
				7,250,588 B2	7/2007	Ely et al.	
				7,261,101 B2	8/2007	Kim	
				7,276,677 B1 *	10/2007	Shelton	A47J 27/0817 126/373.1
				7,285,751 B2 *	10/2007	Li	A47J 37/0623 219/386

(56)

References Cited

U.S. PATENT DOCUMENTS

7,304,271 B2	12/2007	Cho et al.	7,935,914 B2 *	5/2011	Imura	A47J 27/0802 219/627
7,317,173 B2	1/2008	Bartelick et al.	7,943,888 B2	5/2011	Barnes et al.	
7,322,279 B2 *	1/2008	Cartigny	7,964,824 B2 *	6/2011	Moon	A47J 37/0623 219/413
7,322,280 B2 *	1/2008	Seurat Guiochet .	7,968,824 B2 *	6/2011	Lee	F24C 15/105 219/447.1
7,325,481 B2 *	2/2008	Helm	7,980,171 B2	7/2011	Groll	
			8,006,684 B2	8/2011	Lee et al.	
7,368,688 B2 *	5/2008	Kim	8,006,685 B2 *	8/2011	Bolton	A47J 37/0641 126/19 R
7,373,874 B2 *	5/2008	Seurat Guiochet .	8,011,293 B2 *	9/2011	McFadden	A21B 1/245 126/21 A
7,377,208 B2 *	5/2008	Ho	8,042,533 B2 *	10/2011	Dobie	A21B 1/245 126/19 R
7,389,721 B2	6/2008	Wanat	8,080,766 B2	12/2011	Frock et al.	
7,411,159 B2 *	8/2008	Oosterling	8,096,436 B2 *	1/2012	Rhetat	A47J 27/09 220/203.01
7,412,922 B2 *	8/2008	McLemore	8,096,440 B2 *	1/2012	Rhetat	A47J 27/0808 16/422
7,418,960 B2	9/2008	Saksena	8,152,083 B2	4/2012	Bower et al.	
7,451,691 B2 *	11/2008	Robertson	8,166,871 B2	5/2012	Veltrop et al.	
			8,205,543 B2 *	6/2012	Rhetat	A47J 27/0804 99/337
7,451,692 B2 *	11/2008	Baraille	8,247,751 B2 *	8/2012	Jagannathan	A47J 27/088 219/734
7,468,495 B2 *	12/2008	Carbone	8,258,435 B2 *	9/2012	Bonuso	F24C 15/325 126/21 A
7,523,696 B2 *	4/2009	Seurat Guiochet .	8,267,008 B2	9/2012	Yasuhara	
			D669,730 S	10/2012	Mandil	
7,530,302 B2 *	5/2009	Stephanou	8,276,507 B1 *	10/2012	Walker	A47J 27/08 16/110.1
7,537,004 B2	5/2009	Reay	8,286,548 B2 *	10/2012	Krishnan	A47J 37/0611 99/378
7,565,862 B2 *	7/2009	Cartigny				
			8,299,404 B2 *	10/2012	Van Der Weij	A47J 37/0623 126/21 A
7,605,349 B2 *	10/2009	Gaynor	8,302,800 B2 *	11/2012	Hasegawa	A47J 27/09 220/372
D604,098 S	11/2009	Hamlin	8,304,695 B2 *	11/2012	Bonuso	F24C 15/325 126/21 A
7,619,186 B2 *	11/2009	Cavada				
			8,330,083 B2 *	12/2012	Moon	A47J 37/0623 219/412
7,624,674 B2 *	12/2009	Chameroy				
			8,338,757 B2 *	12/2012	Isoda	H05B 6/062 219/450.1
7,637,206 B2 *	12/2009	Seurat Guiochet .				
			8,369,695 B2	2/2013	Lee et al.	
7,669,521 B2 *	3/2010	Cartigny	8,378,265 B2 *	2/2013	Greenwood	F24C 7/082 219/391
7,669,591 B2	3/2010	Fossati et al.	8,381,712 B1 *	2/2013	Simms, II	F24C 3/14 126/2
7,677,160 B2	3/2010	Tippmann et al.				
7,703,385 B2 *	4/2010	Seurat Guiochet	8,393,262 B1 *	3/2013	Molayem	A47J 27/092 219/440
7,718,928 B2 *	5/2010	He	8,420,983 B2	4/2013	Ohashi et al.	
			8,461,488 B2 *	6/2013	Jeong	F24C 15/325 219/399
7,726,508 B2 *	6/2010	Hasegawa				
			8,481,488 B2 *	7/2013	Carter	A61K 31/675 424/85.1
7,745,763 B2	6/2010	Fraccon et al.				
7,759,615 B2	7/2010	Ando et al.	8,517,006 B2	8/2013	Frock et al.	
7,762,420 B2 *	7/2010	Auwarter	8,517,205 B2 *	8/2013	Thelen	A47J 27/0806 220/293
7,766,003 B2 *	8/2010	Kim	8,525,081 B2	9/2013	Colburn et al.	
			8,544,381 B2	10/2013	Cartigny et al.	
7,775,390 B2 *	8/2010	de Bastos Reis Portugal	8,546,731 B2 *	10/2013	Pellerin	A47J 27/004 126/369
7,800,022 B2 *	9/2010	Kim	8,561,525 B2 *	10/2013	Bauchot	A47J 27/0802 219/440
7,810,488 B2	10/2010	Manganiello et al.	8,578,293 B2 *	11/2013	Breunig	F24C 7/082 715/812
7,838,799 B2 *	11/2010	Freedman				
			8,581,137 B2 *	11/2013	Egenter	F24C 7/083 219/100
7,856,875 B2	12/2010	Jeon et al.	8,601,939 B2	12/2013	Saksena et al.	
7,875,836 B2 *	1/2011	Imura	8,604,394 B2	12/2013	Wu et al.	
			8,618,447 B2 *	12/2013	De' Longhi	A47J 37/1209 126/376.1
7,915,568 B2	3/2011	Wang	8,637,797 B2	1/2014	Imura	
D635,393 S	4/2011	Nakatani	D699,514 S	2/2014	Lovley, II et al.	
7,921,768 B2	4/2011	Fernandez et al.	8,640,908 B2	2/2014	Yang et al.	

(56)

References Cited

U.S. PATENT DOCUMENTS

- 8,674,270 B2 * 3/2014 Anderson F24C 7/082
219/391
- 8,689,680 B2 * 4/2014 Park A47J 27/022
126/274
- 8,695,487 B2 4/2014 Sakane et al.
- 8,709,905 B2 * 4/2014 Crayfourd F24C 15/006
438/391
- 8,714,391 B2 * 5/2014 Milanese A47J 27/0808
220/203.03
- 8,726,792 B2 * 5/2014 Shealy A47J 37/0623
99/389
- 8,733,574 B2 * 5/2014 Heidrich A47J 27/09
220/203.04
- D707,078 S 6/2014 Rivera et al.
- 8,739,690 B2 * 6/2014 Chameroy A47J 27/0804
99/337
- 8,747,933 B1 * 6/2014 McGinn A47J 27/08
220/319
- 8,766,144 B2 * 7/2014 McLoughlin F24C 7/08
219/391
- 8,777,038 B2 * 7/2014 Wen A47J 27/092
220/89.1
- 8,783,498 B2 * 7/2014 Li A47J 27/0813
220/314
- 8,783,947 B2 * 7/2014 Ferron A47J 45/068
374/141
- D710,647 S 8/2014 Mandil et al.
- 8,800,803 B2 * 8/2014 Stellwag A47J 27/0813
220/203.1
- 8,808,772 B2 * 8/2014 Lubrina F24C 15/327
426/231
- 8,813,635 B2 8/2014 Dragan
- 8,813,989 B2 * 8/2014 Hoffmann A47J 27/0806
220/203.05
- 8,820,220 B2 * 9/2014 Thelen A47J 27/09
99/337
- 8,840,908 B2 * 9/2014 Reed A61K 39/0011
424/280.1
- 8,847,129 B2 * 9/2014 Kim A47J 37/0623
126/21 A
- 8,869,829 B2 * 10/2014 Hasegawa F16K 37/0058
137/543.13
- 8,887,939 B2 * 11/2014 Chameroy A47J 27/0813
220/324
- D719,398 S 12/2014 Deters
- D720,571 S 1/2015 Deters
- 8,931,402 B2 * 1/2015 Chameroy A47J 27/0806
99/352
- 8,931,659 B2 * 1/2015 Rhetat A47J 27/09
220/315
- 8,944,272 B2 2/2015 Chameroy et al.
- 8,944,273 B2 2/2015 Chameroy et al.
- 8,946,604 B2 2/2015 Kaiser et al.
- 8,960,081 B2 2/2015 Beard et al.
- 8,973,770 B2 * 3/2015 He B65D 45/16
220/203.2
- 8,985,372 B2 * 3/2015 Yang A47J 36/10
220/315
- 8,991,307 B2 * 3/2015 Grozinger A47J 27/08
219/440
- 8,993,934 B2 3/2015 Giazzon et al.
- D727,095 S 4/2015 Bak
- 9,018,566 B2 * 4/2015 Wang A47J 27/004
219/429
- 9,027,468 B2 * 5/2015 Rhetat A47J 27/0802
220/315
- 9,035,223 B2 * 5/2015 Noguchi H05B 6/062
219/627
- 9,055,618 B2 * 6/2015 Bunzel H05B 6/6435
- 9,057,526 B2 * 6/2015 Barritt F24C 7/082
- 9,066,523 B2 6/2015 Seitz et al.
- 9,115,905 B2 8/2015 Giazzon et al.
- 9,119,501 B2 * 9/2015 Xie A47J 36/32
- 9,125,513 B2 * 9/2015 Kim A47J 45/062
- 9,127,849 B2 9/2015 Kang et al.
- 9,138,106 B2 9/2015 Walker
- 9,173,408 B2 11/2015 Yamamoto et al.
- 9,177,460 B2 * 11/2015 Fissler A47J 27/0802
- 9,182,126 B2 11/2015 Cartwright et al.
- 9,191,998 B2 * 11/2015 Hegedis A47J 27/62
- 9,220,362 B2 * 12/2015 Eades A47J 27/004
- 9,237,829 B2 * 1/2016 Alet Vidal B01F 13/0033
- D749,906 S 2/2016 Lee
- 9,247,842 B2 2/2016 Cheung et al.
- 9,271,595 B2 * 3/2016 Lee A47J 36/06
- 9,295,354 B2 * 3/2016 Slood A47J 27/04
- 9,295,355 B2 3/2016 Kwag et al.
- D754,469 S 4/2016 Deters
- 9,301,644 B2 * 4/2016 Payen A47J 37/0641
- 9,314,134 B2 * 4/2016 Molnar A47J 37/0676
- 9,320,381 B2 * 4/2016 Chameroy B65D 53/00
- 9,326,633 B2 5/2016 Lin
- 9,339,145 B1 * 5/2016 Owczarzak A47J 37/0786
- 9,341,382 B2 * 5/2016 Kim F24C 15/322
- 9,345,358 B2 5/2016 Zhang et al.
- 9,351,495 B2 * 5/2016 McFadden A21B 1/245
- 9,353,954 B2 * 5/2016 Linnewiel A47J 37/0641
- 9,375,021 B2 6/2016 Raghavan et al.
- 9,414,713 B2 * 8/2016 Jinzhao A47J 37/015
- 9,433,036 B2 * 8/2016 Kurimoto F24C 7/087
- 9,439,530 B2 * 9/2016 Logan A47J 27/62
- D769,058 S 10/2016 Lee
- 9,456,713 B2 * 10/2016 Backaert A47J 36/027
- 9,470,423 B2 * 10/2016 Jacob F24C 7/087
- 9,474,412 B2 * 10/2016 Fung A47J 37/0611
- D772,648 S 11/2016 Palermo
- 9,480,364 B2 * 11/2016 McKee A47J 37/049
- D774,350 S 12/2016 Mandil
- D774,356 S 12/2016 Maiorana et al.
- D774,358 S * 12/2016 Joseph D7/510
- 9,526,367 B2 * 12/2016 Anota A47J 27/0813
- 9,545,168 B2 1/2017 Gabara
- 9,565,963 B2 2/2017 Jeon et al.
- 9,565,964 B2 2/2017 Yang et al.
- 9,585,509 B2 * 3/2017 Wassmus A47J 37/128
- 9,596,954 B2 3/2017 Park
- 9,615,408 B2 4/2017 Metz et al.
- 9,615,688 B2 4/2017 Shibuya et al.
- 9,615,691 B2 * 4/2017 Xiao A47J 37/1209
- 9,615,692 B2 * 4/2017 Hoffmann A47J 37/067
- 9,615,694 B2 4/2017 Yoshidome
- 9,629,499 B2 4/2017 Kim
- 9,629,500 B2 * 4/2017 Chance A47J 37/0694
- 9,636,618 B2 * 5/2017 Fung B01D 46/10
- 9,642,487 B1 * 5/2017 McGinn A47J 27/002
- 9,648,975 B2 5/2017 Imura
- 9,648,985 B2 * 5/2017 Huang A47J 36/32
- 9,675,197 B2 6/2017 Schobloch et al.
- 9,681,770 B2 * 6/2017 Backaert A47J 36/027
- 9,681,773 B2 6/2017 McKee et al.
- 9,683,747 B2 6/2017 Raghavan et al.
- 9,700,172 B2 7/2017 Tanaka et al.
- 9,706,870 B2 7/2017 Hoehn et al.
- 9,706,871 B2 * 7/2017 Matthijs A47J 36/2483
- 9,717,363 B2 8/2017 Pan
- 9,717,364 B2 * 8/2017 Sladeczek A47J 36/16
- 9,737,936 B2 * 8/2017 Linglin B23B 35/00
- 9,743,794 B2 8/2017 Shibuya et al.
- 9,750,089 B2 * 8/2017 Wiedemann H05B 6/6435
- 9,756,980 B1 * 9/2017 Li A47J 37/0629
- 9,756,981 B2 9/2017 Fung
- 9,763,531 B2 * 9/2017 Baraille A47J 27/09
- D801,106 S 10/2017 Mirchandani et al.
- 9,775,461 B2 * 10/2017 Yang A47J 27/62
- 9,788,678 B2 10/2017 Abe et al.
- 9,795,250 B2 * 10/2017 Huang A23L 5/17
- 9,801,487 B2 10/2017 Park et al.
- 9,801,491 B2 * 10/2017 Cohade A47J 27/082
- 9,814,355 B2 * 11/2017 Winter A47J 37/1223
- 9,841,261 B2 * 12/2017 Raghavan H05B 1/0263
- 9,854,931 B2 1/2018 Rockinger et al.

(56)		References Cited			
U.S. PATENT DOCUMENTS					
2005/0011370	A1 *	1/2005	Xu	A47J 36/165	2010/0089248 A1 * 4/2010 Jones
				99/409	A47J 37/0641
2005/0034716	A1 *	2/2005	Harbin	A47J 37/01	99/444
				126/25 R	2010/0136194 A1 * 6/2010 Schutte
2005/0089318	A1 *	4/2005	Lai	A47J 37/0623	A47J 36/22
				392/418	426/510
2005/0223906	A1 *	10/2005	Xu	A47J 27/004	2010/0147159 A1 * 6/2010 Fossati
				99/348	A47J 37/0676
2005/0284305	A1 *	12/2005	Angue	A47J 27/0808	99/339
				99/337	2010/0147824 A1 * 6/2010 Bonuso
2006/0005714	A1	1/2006	Siegel et al.		F24C 15/325
2006/0081235	A1 *	4/2006	Lundh	A47J 37/0623	219/400
				126/25 A	2010/0206289 A1 * 8/2010 Larsen
2007/0039606	A1	2/2007	Larsen et al.		F24C 15/022
2007/0045284	A1 *	3/2007	Balk	F24C 7/082	126/197
				219/497	2010/0282097 A1 * 11/2010 Schulte
2007/0095215	A1 *	5/2007	Ho	A47J 37/10	A21B 1/245
				99/342	99/476
2007/0125768	A1 *	6/2007	Kim	H05B 6/062	2011/0003048 A1 * 1/2011 Sugimoto
				219/626	A47J 27/004
2007/0158335	A1 *	7/2007	Mansbery	F24C 7/082	426/509
				219/505	2011/0095015 A1 * 4/2011 Kao
2007/0199557	A1 *	8/2007	von Kaenel	A47J 27/00	A47J 27/08
				126/25 R	219/433
2007/0295221	A1 *	12/2007	Seurat Guiochet	A47J 27/0813	2011/0120319 A1 * 5/2011 Chang
				99/337	A47J 37/0623
2008/0022861	A1 *	1/2008	Ferron	A47J 45/068	99/409
				99/342	2011/0126719 A1 * 6/2011 Valance
2008/0078371	A1 *	4/2008	Boscaino	A21B 3/04	A47J 43/0722
				126/20	99/340
2008/0078755	A1 *	4/2008	Jeon	A47J 27/04	2011/0146653 A1 * 6/2011 Kitatani
				219/401	A47J 37/0629
2008/0083730	A1 *	4/2008	Dolgov	A47J 27/004	126/19 R
				219/432	2011/0147365 A1 6/2011 Pellerin et al.
2008/0095905	A1 *	4/2008	Sells	F24C 15/327	2011/0147376 A1 * 6/2011 Ueda
				426/510	F24C 15/327
2008/0099008	A1 *	5/2008	Bolton	A21B 1/245	219/682
				126/21 A	2011/0168158 A1 * 7/2011 Barkhouse
2008/0099461	A1	5/2008	Li		A47J 36/06
2008/0105137	A1 *	5/2008	Genslak	A47J 37/0611	126/25 R
				99/350	2011/0248020 A1 * 10/2011 Yuan
2008/0142498	A1 *	6/2008	He	A47J 27/0817	A47J 37/0676
				219/442	219/618
2008/0163764	A1 *	7/2008	Payen	A47J 37/043	2011/0268153 A1 * 11/2011 He
				99/447	A47J 37/108
2008/0173631	A1	7/2008	Gagas et al.		374/179
2008/0206420	A1 *	8/2008	McFadden	A21B 1/245	2012/0003364 A1 * 1/2012 Kling
				426/523	F24C 7/08
2008/0213447	A1 *	9/2008	Payen	A47J 37/043	426/231
				426/438	2012/0009317 A1 * 1/2012 McLemore
2008/0223224	A1 *	9/2008	Martin	A23B 4/048	A47J 37/1209
				99/482	426/438
2008/0290090	A1 *	11/2008	Kindler	A47J 27/0802	2012/0012584 A1 * 1/2012 Chameroy
				220/203.05	A47J 27/0813
2008/0314258	A1 *	12/2008	Martin	A47J 27/004	220/203.01
				99/329 R	2012/0024164 A1 * 2/2012 Park
2009/0011101	A1 *	1/2009	Doherty	F24C 7/08	F24C 14/005
				426/523	99/339
2009/0013988	A1 *	1/2009	Kim	A47J 37/0623	2012/0024169 A1 2/2012 Hsu
				126/21 A	2012/0040067 A1 * 2/2012 Baraille
2009/0064868	A1 *	3/2009	Cartossi	A47J 27/0813	A47J 27/0802
				99/337	426/523
2009/0095166	A1 *	4/2009	Jian	A47J 27/0802	2012/0048843 A1 * 3/2012 Feng
				99/330	A47J 27/004
2009/0134140	A1 *	5/2009	Van Der Weij	A47J 37/0623	219/442
				219/400	2012/0125313 A1 * 5/2012 Van Der Weij
2009/0223380	A1 *	9/2009	Van Aken	A47J 37/0611	A47J 37/0641
				99/332	126/21 R
2009/0223386	A1 *	9/2009	Edwards	A23G 9/08	2012/0174797 A1 * 7/2012 Froza
				99/455	A47J 27/0802
2009/0250452	A1 *	10/2009	Tse	F24C 15/327	99/325
				219/401	2012/0181363 A1 * 7/2012 Huang
					A47J 43/0777
					241/65
					2012/0192722 A1 8/2012 Foster
					2012/0192726 A1 * 8/2012 Clearman
					A47J 37/0641
					99/447
					2012/0199591 A1 8/2012 Stellwag
					2012/0217236 A1 * 8/2012 Takagi
					A47J 27/004
					219/647
					2012/0217252 A1 * 8/2012 Jung
					A47J 27/002
					220/573.4
					2012/0222665 A1 9/2012 Ahmed
					2012/0222865 A1 * 9/2012 Larson
					E21B 33/038
					166/340
					2012/0318149 A1 * 12/2012 Ahmed
					A47J 37/0682
					99/445
					2013/0019759 A1 * 1/2013 Tumenbatur
					A47J 27/0802
					99/337
					2013/0061765 A1 3/2013 Reinhart
					2013/0074702 A1 * 3/2013 Difante
					A47J 36/20
					99/403
					2013/0092145 A1 * 4/2013 Murphy
					F24C 7/085
					126/21 R
					2013/0104875 A1 * 5/2013 Schultz
					A47J 27/0813
					126/377.1
					2013/0156906 A1 6/2013 Raghavan et al.
					2013/0180413 A1 * 7/2013 Tjerkgaast
					A47J 37/0641
					99/447

(56)	References Cited						
	U.S. PATENT DOCUMENTS						
2013/0180986	A1*	7/2013	He	A47J 27/0813	2015/0083107	A1* 3/2015 Busch A47J 36/38
					220/203.2		126/25 R
2013/0196038	A1*	8/2013	Liu	A47J 37/1266	2015/0122137	A1* 5/2015 Chang A47J 36/06
					426/233		99/447
2013/0255509	A1*	10/2013	He	A47J 27/0804	2015/0136769	A1* 5/2015 Quinn A47J 36/10
					99/352		220/203.01
2013/0276643	A1	10/2013	Krolick et al.			2015/0173551	A1 6/2015 Carbone et al.
2013/0278643	A1*	10/2013	Otsuka	G09G 5/02	2015/0190008	A1 7/2015 Baraille et al.
					345/690	2015/0192289	A1 7/2015 Gattei et al.
2013/0298781	A1*	11/2013	Ganuza	A47J 37/0623	2015/0201788	A1* 7/2015 Douma A47J 27/04
					99/447		99/330
2013/0305933	A1*	11/2013	Heidrich	A47J 36/321	2015/0201806	A1* 7/2015 Yoshidome A47J 27/004
					99/331		99/447
2013/0333685	A1*	12/2013	Jeong	F24C 15/322	2015/0208845	A1 7/2015 Robbins et al.
					126/21 A	2015/0208858	A1* 7/2015 Robbins A47J 45/068
2014/0021191	A1*	1/2014	Moon	F24C 7/088		426/231
					219/392	2015/0223627	A1* 8/2015 Li A47J 27/04
2014/0044851	A1	2/2014	Kennedy			2015/0226438	A1* 8/2015 Ozyurt F24C 7/087
2014/0083306	A1*	3/2014	Lee	A47J 36/20	2015/0250187	A1* 9/2015 Sakane A47J 36/20
					99/413		99/371
2014/0083992	A1*	3/2014	Linnewiel	A47J 37/0641	2015/0292750	A1* 10/2015 Delrue A47J 37/0641
					219/400		219/400
2014/0102315	A1*	4/2014	Park	A47J 27/022	2015/0305093	A1* 10/2015 Smith A47J 31/542
					99/330		219/391
2014/0157994	A1*	6/2014	Ryan	A47J 44/00	2015/0312964	A1 10/2015 Sorenson et al.
					99/332	2015/0313399	A1* 11/2015 Park A47J 36/06
2014/0175085	A1*	6/2014	Yang	F24C 15/327		99/342
					219/401	2015/0351578	A1* 12/2015 Song A47J 27/09
2014/0199454	A1*	7/2014	Storek	A47J 36/32		99/358
					426/508	2015/0354827	A1 12/2015 Faraldi et al.
2014/0199459	A1	7/2014	Jackson et al.			2015/0366393	A1 12/2015 Fareham et al.
2014/0201688	A1*	7/2014	Guilleminot	G06F 3/017	2015/0366399	A1 12/2015 Lee
					715/863	2015/0366402	A1* 12/2015 Wu A47J 37/0611
							99/340
2014/0220196	A1	8/2014	Veloo			2016/0007644	A1* 1/2016 Hack A47J 27/04
2014/0220198	A1*	8/2014	Konuklar	A23L 3/30		99/333
					426/238	2016/0007789	A1* 1/2016 Tiruvallur A47J 27/09
							99/337
2014/0227411	A1	8/2014	Popeil et al.			2016/0029829	A1* 2/2016 Klein A47J 37/0641
2014/0245898	A1*	9/2014	Froza	A47J 36/16		99/332
					99/341	2016/0033141	A1* 2/2016 Rizzuto F24C 7/085
							219/396
2014/0246419	A1	9/2014	Li			2016/0037955	A1* 2/2016 Kim A47J 27/57
2014/0251158	A1*	9/2014	Yang	A47J 27/04		99/344
					99/341	2016/0045067	A1* 2/2016 Liao A47J 37/0754
							126/25 R
2014/0251162	A1	9/2014	Zhou			2016/0051077	A1* 2/2016 Sloot A47J 27/04
2014/0318385	A1*	10/2014	Kim	F24C 15/322		426/233
					99/447	2016/0051078	A1* 2/2016 Jenkins A47J 27/62
2014/0318386	A1*	10/2014	Kim	F24C 15/322		99/331
					99/447	2016/0051086	A1* 2/2016 De' Longhi A47J 37/06
2014/0318387	A1*	10/2014	Kim	F24C 15/16		99/447
					99/447	2016/0066738	A1 3/2016 Shibuya et al.
2014/0318388	A1*	10/2014	Kim	F24C 15/322	2016/0073814	A1 3/2016 Kiriishi et al.
					99/447	2016/0081509	A1* 3/2016 Delrue A47J 37/047
2014/0318389	A1*	10/2014	Kim	F24C 7/06		426/231
					99/447	2016/0100707	A1* 4/2016 Huang A47J 27/092
							99/403
2014/0319119	A1	10/2014	Raghavan et al.			2016/0100713	A1* 4/2016 De Haas A23L 5/17
2014/0322417	A1*	10/2014	Kim	F24C 15/322		426/523
					426/523	2016/0113432	A1 4/2016 Cornelissen
2014/0348987	A1*	11/2014	Cheng	A47J 27/04	2016/0113442	A1* 4/2016 De Haas A47J 37/06
					426/231		426/523
2014/0353316	A1*	12/2014	Lin	A47J 36/10	2016/0120363	A1* 5/2016 Zwanenburg A47J 37/108
					220/573.1		426/523
2014/0360384	A1*	12/2014	Kim	A47J 27/0806	2016/0120364	A1* 5/2016 De Haas A47J 37/0641
					99/403		426/523
2014/0366746	A1*	12/2014	Tsai	A47J 37/00	2016/0123660	A1* 5/2016 Peng A47J 27/004
					99/403		219/623
2014/0370176	A1*	12/2014	Imura	A47J 36/06	2016/0150906	A1 6/2016 Lee et al.
					426/523	2016/0165676	A1* 6/2016 Imm A23L 5/15
							426/243
2014/0373729	A1	12/2014	Kim et al.			2016/0174749	A1* 6/2016 Eades A47J 27/004
2014/0377417	A1*	12/2014	Martinez	A47J 36/321		99/331
					426/231		
2015/0000535	A1*	1/2015	Yoshidome	F24C 15/327		
					99/331		
2015/0059595	A1	3/2015	Rand et al.				

(56)

References Cited

U.S. PATENT DOCUMENTS

2016/0174764	A1*	6/2016	Xiao	A47J 37/1209 99/447	2017/0295993	A1*	10/2017	Li	A23L 5/15
2016/0174771	A1*	6/2016	Benoit	A47J 44/02 99/331	2017/0303740	A1*	10/2017	Bonaccorso	A47J 37/0641
2016/0183722	A1*	6/2016	Fisher	A47J 37/0704 99/425	2017/0319006	A1	11/2017	Niizumi	
2016/0192808	A1*	7/2016	Van Der Burg	A47J 37/04 99/443 C	2017/0332823	A1	11/2017	Sanseverino	
2016/0198882	A1*	7/2016	Linglin	A47J 37/108 220/573.3	2017/0343221	A1	11/2017	Swayne et al.	
2016/0198883	A1*	7/2016	Wang	A47J 27/08 426/231	2017/0360238	A1*	12/2017	Bogazzi	F24B 1/207
2016/0206131	A1*	7/2016	Chien	A47J 27/09	2017/0360254	A1*	12/2017	Muhr	F24C 15/322
2016/0206139	A1*	7/2016	Johnson	A47J 37/06	2017/0360255	A1*	12/2017	Karau	A47J 37/0704
2016/0206140	A1*	7/2016	Johnson	A47J 37/06	2017/0367514	A1*	12/2017	In 'T Groen	A47J 36/38
2016/0219653	A1*	7/2016	Kim	H05B 6/68	2017/0370595	A1*	12/2017	Yang	F24C 7/006
2016/0220057	A1*	8/2016	Smith	A23L 5/15	2018/0000285	A1*	1/2018	Backus	A47J 37/129
2016/0235078	A1*	8/2016	Farina	A23B 4/052	2018/0007744	A1*	1/2018	Nonaka	H05B 6/6441
2016/0235239	A1*	8/2016	Patadia	A47J 44/00	2018/0014683	A1	1/2018	Glucksman	
2016/0253080	A1*	9/2016	Ban	F24C 7/086 715/771	2018/0028017	A1*	2/2018	Wu	A47J 37/0664
2016/0270596	A1*	9/2016	Allemand	A47J 39/003	2018/0035698	A1*	2/2018	McNerney	A23L 5/17
2016/0278563	A1*	9/2016	Choudhary	A47J 27/004	2018/0070596	A1	3/2018	Kim et al.	
2016/0278565	A1*	9/2016	Chameroy	A47J 27/0806	2018/0073739	A1*	3/2018	Dumenil	F24C 1/04
2016/0281994	A1*	9/2016	Nuessler	F24C 7/08	2018/0078089	A1*	3/2018	Sauer	A47J 37/0641
2016/0309940	A1	10/2016	Valance et al.		2018/0103796	A1*	4/2018	Park	A47J 27/002
2016/0309956	A1*	10/2016	Glucksman	A47J 37/041	2018/0110355	A1*	4/2018	Huang	A47J 27/09
2016/0316525	A1*	10/2016	Vainionpa	H05B 6/6473	2018/0110373	A1	4/2018	Zhang et al.	
2016/0316968	A1*	11/2016	Linglin	A47J 37/108	2018/0116264	A1*	5/2018	De Winter	A23P 20/12
2016/0324359	A1*	11/2016	Aboujassoum	A47J 36/00	2018/0116438	A1*	5/2018	He	A47J 27/08
2016/0327280	A1*	11/2016	Smith	A47J 37/0641	2018/0125293	A1	5/2018	McNerney et al.	
2016/0345766	A1*	12/2016	Sapire	A47J 27/0815	2018/0125294	A1*	5/2018	Conte	A47J 37/047
2016/0353913	A1*	12/2016	Chameroy	A47J 27/09	2018/0132648	A1	5/2018	Furlanetto et al.	
2016/0353914	A1*	12/2016	Chameroy	A47J 27/09	2018/0140126	A1*	5/2018	Van Dillen	A47J 27/16
2016/0353915	A1*	12/2016	Chameroy	A47J 27/0806	2018/0143086	A1*	5/2018	Stoufer	A47J 36/32
2016/0353916	A1*	12/2016	Chameroy	A47J 27/0806	2018/0146812	A1	5/2018	Choi	
2016/0360922	A1*	12/2016	Xiao	A47J 39/003	2018/0153329	A1*	6/2018	Glucksman	A47J 27/004
2016/0367061	A1*	12/2016	Chou	A47J 27/004	2018/0160840	A1*	6/2018	De' Longhi	A47J 27/002
2016/0374510	A1*	12/2016	Albizuri Landazabal	A47J 37/0713 99/330	2018/0160849	A1*	6/2018	Hebert, Jr	A47J 37/067
2017/0000293	A1*	1/2017	Sladeczek	A47J 37/0641	2018/0177322	A1*	6/2018	Kim	A47J 27/62
2017/0016623	A1	1/2017	Rabie et al.		2018/0177343	A1*	6/2018	Bonaccorso	B25G 3/18
2017/0020334	A1*	1/2017	Sorenson	A47J 37/0709	2018/0184843	A1*	7/2018	Kim	F24C 15/006
2017/0055770	A1*	3/2017	Case	A21B 1/00	2018/0184848	A1*	7/2018	De' Longhi	B01F 7/20
2017/0065127	A1*	3/2017	Bonaccorso	A47J 37/128	2018/0192825	A1*	7/2018	Popeil	A47J 37/1209
2017/0071034	A1*	3/2017	Metz	H05B 6/062	2018/0199615	A1	7/2018	Zhang et al.	
2017/0079475	A1*	3/2017	Buckley	A23L 5/17	2018/0199756	A1*	7/2018	Huang	A47J 37/0629
2017/0089590	A1*	3/2017	Bruin-Slot	F24C 15/16	2018/0206672	A1*	7/2018	Grace	A47J 36/04
2017/0095105	A1	4/2017	Clark et al.		2018/0206677	A1*	7/2018	Ivarsson	A47J 43/0716
2017/0099977	A1*	4/2017	Liu	A47J 27/004	2018/0213965	A1	8/2018	Li	
2017/0099984	A1*	4/2017	Koetz	A47J 36/00	2018/0220498	A1*	8/2018	Jeon	F24C 15/325
2017/0099990	A1*	4/2017	Magnouloux	A47J 36/00	2018/0220842	A1*	8/2018	Delrue	A47J 37/047
2017/0099995	A1*	4/2017	Magnouloux	A47J 45/071	2018/0228318	A1*	8/2018	Zwanenburg	A47J 37/108
2017/0119192	A1*	5/2017	Sanseverino	A47J 27/086	2018/0235396	A1	8/2018	Schönenberger	
2017/0127871	A1	5/2017	Leung		2018/0238560	A1*	8/2018	Deng	F24C 15/322
2017/0172335	A1*	6/2017	Colas	A47J 27/0806	2018/0255967	A1*	9/2018	Haas	B01D 46/0023
2017/0181564	A1*	6/2017	He	A47J 27/002	2018/0255971	A1*	9/2018	Moon	A47J 37/0641
2017/0199658	A1*	7/2017	Stouter	G06F 3/0482	2018/0263084	A1*	9/2018	Yoshino	H05B 6/062
2017/0224157	A1	8/2017	Rummel et al.		2018/0263402	A1	9/2018	Li	
2017/0231257	A1	8/2017	Thul et al.		2018/0266697	A1*	9/2018	Dash	A47J 37/0623
2017/0231415	A1*	8/2017	Cheng	A47J 27/002 374/141	2018/0270915	A1	9/2018	Koetz	
2017/0231430	A1*	8/2017	Moon	A47J 37/1266 99/331	2018/0271321	A1*	9/2018	Delrue	A47J 37/043
2017/0245674	A1*	8/2017	Imura	A47J 27/62	2018/0271322	A1	9/2018	Thai et al.	
2017/0245683	A1*	8/2017	Chen	A47J 37/0641	2018/0271323	A1*	9/2018	Zhang	A47J 37/0641
2017/0245686	A1*	8/2017	Man	A47J 37/0641	2018/0279832	A1*	10/2018	Ohta	A47J 44/02
2017/0251872	A1*	9/2017	Li	A47J 37/0629	2018/0289212	A1*	10/2018	Sladeczek	A47J 37/0641
2017/0251874	A1*	9/2017	Sladeczek	A47J 37/047	2018/0296019	A1*	10/2018	Kim	A47J 27/0802
2017/0258268	A1	9/2017	Kazanas et al.		2018/0299138	A1	10/2018	Faraldi et al.	
2017/0276378	A1	9/2017	Faraldi et al.		2018/0303285	A1*	10/2018	Cheng	A47J 37/0641
2017/0280914	A1*	10/2017	Kumar	A47J 27/62	2018/0317691	A1*	11/2018	Huang	A23L 5/17
2017/0290452	A1*	10/2017	Guillaume	A47J 27/0806	2018/0317692	A1*	11/2018	Huang	A23L 5/17
					2018/0317693	A1*	11/2018	Huang	A23L 5/17
					2018/0325311	A1	11/2018	Feldman et al.	
					2018/0325313	A1*	11/2018	De' Longhi	A47J 37/0641
					2018/0325318	A1*	11/2018	De' Longhi	A47J 37/1261
					2018/0325322	A1*	11/2018	De' Longhi	A47J 37/0641
					2018/0328645	A1	11/2018	Wang et al.	
					2018/0332993	A1	11/2018	Cho et al.	
					2018/0332994	A1	11/2018	Hasegawa	
					2018/0332999	A1	11/2018	Nie	
					2018/0333004	A1*	11/2018	De' Longhi	A23L 5/10
					2018/0333005	A1*	11/2018	Fritz	A47J 37/1266
					2018/0338636	A1	11/2018	Ceccoli	
					2018/0340695	A1	11/2018	Park et al.	
					2018/0344085	A1*	12/2018	Dutter	A47J 37/0694
					2018/0347829	A1*	12/2018	Martini	F24C 15/006
					2018/0353007	A1*	12/2018	Eberhart	A47J 36/38

(56)

References Cited

U.S. PATENT DOCUMENTS

2018/0353010 A1* 12/2018 Delrue A47J 37/1257
 2018/0359823 A1* 12/2018 Shin F24C 7/02
 2018/0363915 A1 12/2018 Bu
 2018/0368615 A1 12/2018 Luo et al.
 2019/0000267 A1* 1/2019 Li A47J 37/0807
 2019/0003718 A1 1/2019 Lee et al.
 2019/0008310 A1 1/2019 Kim et al.
 2019/0008316 A1* 1/2019 Kim A47J 36/10
 2019/0014940 A1 1/2019 Cheung et al.
 2019/0014943 A1 1/2019 Gill et al.
 2019/0021142 A1* 1/2019 Mizuta H05B 6/129
 2019/0021537 A1 1/2019 Park
 2019/0024904 A1 1/2019 Ueda et al.
 2019/0029459 A1 1/2019 Gao et al.
 2019/0045964 A1* 2/2019 Gill A47J 27/002
 2019/0045973 A1* 2/2019 Gill A47J 37/0641
 2019/0053521 A1* 2/2019 Tian A23P 30/38
 2019/0053655 A1 2/2019 Panasik et al.
 2019/0059627 A1 2/2019 Kitatani et al.
 2019/0059628 A1 2/2019 Liu et al.
 2019/0059647 A1* 2/2019 Floessholzer A47J 37/0641
 2019/0069719 A1* 3/2019 Huang A47J 37/0641
 2019/0075971 A1 3/2019 Noca et al.
 2019/0082876 A1* 3/2019 Shi A47J 27/004
 2019/0086075 A1 3/2019 Albert
 2019/0110629 A1 4/2019 Truong et al.
 2019/0110640 A1 4/2019 Te Velde et al.
 2019/0117005 A1 4/2019 Kettavong et al.
 2019/0137112 A1 5/2019 Lego et al.
 2019/0142220 A1 5/2019 Shirali et al.
 2019/0174944 A1 6/2019 Luo et al.
 2019/0174945 A1 6/2019 Oti
 2019/0203944 A1 7/2019 Cho et al.
 2019/0231125 A1 8/2019 Gill et al.
 2019/0231126 A1 8/2019 Gill et al.
 2019/0231128 A1 8/2019 Gill et al.
 2019/0231129 A1 8/2019 Gill et al.
 2019/0231130 A1 8/2019 Gill et al.
 2019/0231131 A1 8/2019 Gill et al.
 2019/0231132 A1 8/2019 Gill et al.
 2019/0231133 A1 8/2019 Gill et al.
 2019/0231134 A1 8/2019 Gill et al.
 2019/0231135 A1 8/2019 Gill et al.
 2019/0231136 A1 8/2019 Gill et al.
 2019/0231137 A1 8/2019 Gill et al.
 2019/0231138 A1 8/2019 Gill et al.
 2019/0231139 A1 8/2019 Gill et al.
 2019/0231140 A1 8/2019 Gill et al.
 2019/0231141 A1 8/2019 Gill et al.
 2019/0231142 A1 8/2019 Gill et al.
 2019/0231143 A1 8/2019 Gill et al.
 2019/0239518 A1 8/2019 Mckee et al.
 2019/0246830 A1 8/2019 Ametepe et al.
 2019/0254473 A1 8/2019 Anthony et al.
 2019/0254474 A1 8/2019 Anthony et al.
 2019/0254476 A1 8/2019 Anthony et al.
 2019/0254479 A1 8/2019 De' Longhi et al.
 2019/0269276 A1 9/2019 Gvili
 2019/0282021 A1 9/2019 Dion et al.
 2019/0298100 A1 10/2019 Li et al.
 2019/0309955 A1 10/2019 Castillo et al.
 2019/0313832 A1 10/2019 Lee et al.
 2019/0313844 A1 10/2019 Nadendla et al.
 2019/0316783 A1 10/2019 Lee et al.
 2019/0327979 A1 10/2019 Yang et al.
 2019/0328169 A1 10/2019 Fogacci
 2019/0335934 A1 11/2019 Delrue et al.
 2019/0374058 A1 12/2019 Blond et al.
 2019/0380524 A1 12/2019 Guegan et al.
 2019/0381654 A1 12/2019 Oleynik
 2019/0387913 A1 12/2019 Lee et al.
 2019/0387922 A1 12/2019 Jin et al.
 2020/0000262 A1 1/2020 Delrue et al.
 2020/0018475 A1 1/2020 Sim et al.
 2020/0029721 A1 1/2020 Kang et al.

2020/0029731 A1 1/2020 Hunt
 2020/0046157 A1 2/2020 Leung
 2020/0054024 A1 2/2020 Sun et al.
 2020/0060472 A1 2/2020 Gill et al.
 2020/0060473 A1 2/2020 Gill et al.
 2020/0080726 A1 3/2020 Polster
 2020/0088415 A1 3/2020 Lee et al.
 2020/0121129 A1 4/2020 Wittig
 2020/0128995 A1 4/2020 Patel et al.
 2020/0138043 A1 5/2020 Hoerter
 2020/0138229 A1 5/2020 Kweon et al.
 2020/0146496 A1 5/2020 Patadia
 2020/0170437 A1 6/2020 Anthony et al.
 2020/0178583 A1 6/2020 Chen et al.
 2020/0182485 A1 6/2020 Ball et al.
 2020/0187697 A1 6/2020 Stewart et al.
 2020/0187698 A1 6/2020 Peng et al.
 2020/0191404 A1 6/2020 Song
 2020/0205245 A1 6/2020 Ma et al.
 2020/0405086 A1 12/2020 Dos Santos et al.
 2021/0000292 A1 1/2021 Siu et al.
 2021/0000296 A1 1/2021 Kennedy et al.

FOREIGN PATENT DOCUMENTS

CN 1301477 A 11/1998
 CN 2358794 Y 1/1999
 CN 1218653 A 6/1999
 CN 2389593 Y 8/2000
 CN 2450993 Y 10/2001
 CN 2469839 Y 1/2002
 CN 2479871 Y 3/2002
 CN 1139352 C 2/2004
 CN 1572189 A 3/2004
 CN 1148142 C 5/2004
 CN 1805700 A 5/2004
 CN 1158963 C 7/2004
 CN 2719176 Y 8/2005
 CN 1820685 A 2/2006
 CN 1959214 A 4/2006
 CN 1883351 A 12/2006
 CN 2855256 Y 1/2007
 CN 2904903 Y 5/2007
 CN 1981682 A 6/2007
 CN 1985727 A 6/2007
 CN 1989884 A 7/2007
 CN 100998476 A 7/2007
 CN 101023842 A 8/2007
 CN 101053485 A 10/2007
 CN 200987595 Y 12/2007
 CN 101099635 A 1/2008
 CN 101108064 A 1/2008
 CN 101112291 A 1/2008
 CN 101112292 A 1/2008
 CN 101112293 A 1/2008
 CN 101142448 A 3/2008
 CN 101185556 A 5/2008
 CN 100401957 C 7/2008
 CN 101209179 A 7/2008
 CN 101209180 A 7/2008
 CN 201079267 Y 7/2008
 CN 100425186 C 10/2008
 CN 100428906 C 10/2008
 CN 101273834 A 10/2008
 CN 201139427 Y 10/2008
 CN 101322614 A 12/2008
 CN 201197609 Y 2/2009
 CN 100464682 C 3/2009
 CN 100469289 C 3/2009
 CN 201207144 Y 3/2009
 CN 101432608 A 5/2009
 CN 101438929 A 5/2009
 CN 100496350 C 6/2009
 CN 201675699 U 7/2009
 CN 100522018 C 8/2009
 CN 100531628 C 8/2009
 CN 100534363 C 9/2009
 CN 101518409 A 9/2009
 CN 101666513 A 9/2009

(56)

References Cited

FOREIGN PATENT DOCUMENTS

CN	100559999	C	11/2009	CN	103375826	A	10/2013
CN	201365839	Y	12/2009	CN	104586233	A	10/2013
CN	101766439	A	1/2010	CN	203234602	U	10/2013
CN	100588351	C	2/2010	CN	203234613	U	10/2013
CN	101669761	A	3/2010	CN	203483269	U	10/2013
CN	101766443	A	7/2010	CN	203597771	U	10/2013
CN	101791190	A	8/2010	CN	102319018	B	11/2013
CN	101828856	A	9/2010	CN	104797178	A	11/2013
CN	101856086	A	10/2010	CN	203302862	U	11/2013
CN	201602600	U	10/2010	CN	103445669	A	12/2013
CN	201624512	U	11/2010	CN	103876645	A	12/2013
CN	101936550	A	1/2011	CN	203789747	U	12/2013
CN	101940273	A	1/2011	CN	102397005	B	1/2014
CN	201996364	U	1/2011	CN	103491830	A	1/2014
CN	101420893	B	2/2011	CN	203407931	U	1/2014
CN	101977536	A	2/2011	CN	203776720	U	2/2014
CN	102178443	A	3/2011	CN	103649643	A	3/2014
CN	201888709	U	7/2011	CN	204071670	U	3/2014
CN	201929758	U	8/2011	CN	103750730	A	4/2014
CN	201948771	U	8/2011	CN	105025764	A	4/2014
CN	102178445	A	9/2011	CN	203539138	U	4/2014
CN	102178464	A	9/2011	CN	203914511	U	4/2014
CN	201958652	U	9/2011	CN	104138200	A	5/2014
CN	101305890	B	11/2011	CN	203597772	U	5/2014
CN	102240164	A	11/2011	CN	203615383	U	5/2014
CN	202312830	U	11/2011	CN	203873601	U	5/2014
CN	102307500	A	1/2012	CN	203885342	U	5/2014
CN	102313306	A	2/2012	CN	203634023	U	6/2014
CN	102349791	A	2/2012	CN	203647141	U	6/2014
CN	202151310	U	2/2012	CN	203662545	U	6/2014
CN	102368936	A	3/2012	CN	204015964	U	6/2014
CN	102589016	A	3/2012	CN	103892696	A	7/2014
CN	202184614	U	4/2012	CN	103948308	A	7/2014
CN	101692958	B	5/2012	CN	104068757	B	7/2014
CN	202207075	U	5/2012	CN	203693372	U	7/2014
CN	202234720	U	5/2012	CN	203723888	U	7/2014
CN	202234761	U	5/2012	CN	204091762	U	7/2014
CN	202698888	U	5/2012	CN	104000478	A	8/2014
CN	202723624	U	5/2012	CN	105491924	A	8/2014
CN	202312886	U	7/2012	CN	203762926	U	8/2014
CN	102670079	A	9/2012	CN	203776718	U	8/2014
CN	202408428	U	9/2012	CN	203776719	U	8/2014
CN	202408455	U	9/2012	CN	203776729	U	8/2014
CN	102755120	A	10/2012	CN	204105799	U	8/2014
CN	102824120	A	12/2012	CN	203828675	U	9/2014
CN	103156532	A	12/2012	CN	203873602	U	10/2014
CN	202619362	U	12/2012	CN	203885286	U	10/2014
CN	102100481	B	1/2013	CN	203953373	U	11/2014
CN	102883641	A	1/2013	CN	205831638	U	11/2014
CN	202636678	U	1/2013	CN	20442779	U	12/2014
CN	103142134	A	3/2013	CN	203970073	U	12/2014
CN	103006045	A	4/2013	CN	203970160	U	12/2014
CN	103006092	A	4/2013	CN	203987492	U	12/2014
CN	202858889	U	4/2013	CN	203987520	U	12/2014
CN	103284618	B	5/2013	CN	203987550	U	12/2014
CN	203302892	U	5/2013	CN	203987551	U	12/2014
CN	103142128	A	6/2013	CN	204016055	U	12/2014
CN	103142151	A	6/2013	CN	204016056	U	12/2014
CN	103169371	A	6/2013	CN	204049362	U	12/2014
CN	103179884	A	6/2013	CN	204091768	U	1/2015
CN	202960194	U	6/2013	CN	204427801	U	1/2015
CN	202981682	U	6/2013	CN	204500391	U	1/2015
CN	203000535	U	6/2013	CN	104323708	A	2/2015
CN	103188947	A	7/2013	CN	104367182	A	2/2015
CN	103188970	A	7/2013	CN	106132256	A	2/2015
CN	103220947	A	7/2013	CN	204133165	U	2/2015
CN	103222807	A	7/2013	CN	204133291	U	2/2015
CN	104337407	A	7/2013	CN	204158183	U	2/2015
CN	203041954	U	7/2013	CN	104433841	A	3/2015
CN	203041955	U	7/2013	CN	107411542	A	3/2015
CN	102342739	B	8/2013	CN	204192406	U	3/2015
CN	203122175	U	8/2013	CN	204467861	U	3/2015
CN	103299132	A	9/2013	CN	204520386	U	3/2015
CN	203195497	U	9/2013	CN	104490294	A	4/2015
CN	203195499	U	9/2013	CN	102917623	B	5/2015
				CN	104613515	A	5/2015
				CN	104622274	A	5/2015
				CN	106292340	A	5/2015
				CN	104676681	A	6/2015

(56)

References Cited

FOREIGN PATENT DOCUMENTS

CN	104688019	A	6/2015	CN	105455628	A	4/2016
CN	104706212	A	6/2015	CN	105455664	A	4/2016
CN	204765165	U	6/2015	CN	105455671	A	4/2016
CN	204765167	U	6/2015	CN	105476461	A	4/2016
CN	204765168	U	6/2015	CN	105476464	A	4/2016
CN	104754992	A	7/2015	CN	105476472	A	4/2016
CN	104757872	A	7/2015	CN	105476491	A	4/2016
CN	106175477	A	7/2015	CN	105496184	A	4/2016
CN	106575469	A	7/2015	CN	105496185	A	4/2016
CN	106714634		7/2015	CN	105496224	A	4/2016
CN	204813499	U	7/2015	CN	205126014	U	4/2016
CN	104814665	A	8/2015	CN	105534269	A	5/2016
CN	104856561	A	8/2015	CN	105559571	A	5/2016
CN	104856563	A	8/2015	CN	105595792	A	5/2016
CN	105231802	A	8/2015	CN	105595803	A	5/2016
CN	204580991	U	8/2015	CN	105996748	A	5/2016
CN	104873098	A	9/2015	CN	107432668	A	5/2016
CN	104887063	A	9/2015	CN	205197727	U	5/2016
CN	204636063	U	9/2015	CN	205214967	U	5/2016
CN	104983318	A	10/2015	CN	205215045	U	5/2016
CN	104997394	A	10/2015	CN	205849309	U	5/2016
CN	204697804	U	10/2015	CN	205923705	U	5/2016
CN	205018872	U	10/2015	CN	205923803	U	5/2016
CN	205053851	U	10/2015	CN	206284788	U	5/2016
CN	105011741	A	11/2015	CN	102440681	B	6/2016
CN	105030035	A	11/2015	CN	102783908	B	6/2016
CN	105054772	B	11/2015	CN	103648337	B	6/2016
CN	105054773	B	11/2015	CN	105615638	A	6/2016
CN	105286491	A	11/2015	CN	105615639	A	6/2016
CN	105595802	A	11/2015	CN	105615686	A	6/2016
CN	106562680	A	11/2015	CN	105640299	A	6/2016
CN	204734374	U	11/2015	CN	105640302	A	6/2016
CN	204743846	U	11/2015	CN	105640309	A	6/2016
CN	204765197	U	11/2015	CN	105640351	A	6/2016
CN	204797615	U	11/2015	CN	105662112	A	6/2016
CN	204797616	U	11/2015	CN	105662125	A	6/2016
CN	205286098	U	11/2015	CN	105662126	A	6/2016
CN	103813738	B	12/2015	CN	105662127	A	6/2016
CN	105105624	A	12/2015	CN	105708312	A	6/2016
CN	105105626	A	12/2015	CN	205322075	U	6/2016
CN	105167591	B	12/2015	CN	206007050	U	6/2016
CN	105167592	A	12/2015	CN	206026097	U	6/2016
CN	105193301	A	12/2015	CN	206044409	U	6/2016
CN	106889875	A	12/2015	CN	206062947	U	6/2016
CN	106889876	A	12/2015	CN	206119971	U	6/2016
CN	106998961	A	12/2015	CN	206166699	U	6/2016
CN	204839219	U	12/2015	CN	206183062	U	6/2016
CN	204889693	U	12/2015	CN	206324671	U	6/2016
CN	205493586	U	12/2015	CN	104605727	B	7/2016
CN	105212693	B	1/2016	CN	105725730	A	7/2016
CN	105212730	A	1/2016	CN	105725829	A	7/2016
CN	105231811	A	1/2016	CN	105768859	A	7/2016
CN	105231812	A	1/2016	CN	105768860	A	7/2016
CN	105231813	A	1/2016	CN	105996805	B	7/2016
CN	105266565	A	1/2016	CN	107647773	A	7/2016
CN	105266577	A	1/2016	CN	206166710	U	7/2016
CN	105768844	A	1/2016	CN	206166711	U	7/2016
CN	204995259	U	1/2016	CN	206239100	U	7/2016
CN	105286496	A	2/2016	CN	103908166	B	8/2016
CN	105286498	A	2/2016	CN	105816023	A	8/2016
CN	105286627	A	2/2016	CN	105832176	A	8/2016
CN	105326332	A	2/2016	CN	105852667	A	8/2016
CN	105342454	A	2/2016	CN	105852668	A	8/2016
CN	105982532	A	2/2016	CN	105902144	A	8/2016
CN	205018878	U	2/2016	CN	105902150	A	8/2016
CN	205493513	U	2/2016	CN	105996809	A	8/2016
CN	205493593	U	2/2016	CN	106073519	A	8/2016
CN	105380512	A	3/2016	CN	106108697	B	8/2016
CN	105380513	A	3/2016	CN	106235892	A	8/2016
CN	105380514	A	3/2016	CN	106235893	A	8/2016
CN	105411378	A	3/2016	CN	107713774	A	8/2016
CN	105411379	A	3/2016	CN	205410811	U	8/2016
CN	105433778	A	3/2016	CN	205425108	U	8/2016
CN	105433779	A	3/2016	CN	205433281	U	8/2016
CN	105451610	A	3/2016	CN	205433317	U	8/2016
				CN	205433320	U	8/2016
				CN	206252365	U	8/2016
				CN	206261486	U	8/2016
				CN	206261487	U	8/2016

(56)

References Cited

FOREIGN PATENT DOCUMENTS

CN	206284794	U	8/2016	CN	106510449	A	3/2017
CN	206303774	U	8/2016	CN	106802584	A	3/2017
CN	206371926	U	8/2016	CN	106937820	A	3/2017
CN	206560353	U	8/2016	CN	206026100	U	3/2017
CN	206560354	U	8/2016	CN	206044349	U	3/2017
CN	105919411	A	9/2016	CN	207253261	U	3/2017
CN	105919417	A	9/2016	CN	106551617	A	4/2017
CN	105935244	A	9/2016	CN	106580074	A	4/2017
CN	105935258	A	9/2016	CN	106901592	A	4/2017
CN	105972653	A	9/2016	CN	106993928	A	4/2017
CN	106108630	A	9/2016	CN	206062888	U	4/2017
CN	107065634	B	9/2016	CN	206102391	U	4/2017
CN	205568641	U	9/2016	CN	206119969	U	4/2017
CN	205568772	U	9/2016	CN	106618154	A	5/2017
CN	205597052	U	9/2016	CN	106667244	A	5/2017
CN	206371913	U	9/2016	CN	106691171	A	5/2017
CN	206371930	U	9/2016	CN	107049054	A	5/2017
CN	206371931	U	9/2016	CN	206166726	U	5/2017
CN	206381064	U	9/2016	CN	206807803	U	5/2017
CN	206453694	U	9/2016	CN	206807804	U	5/2017
CN	206603656	U	9/2016	CN	207355971	U	5/2017
CN	105982529	A	10/2016	CN	207429001	U	5/2017
CN	105996737	A	10/2016	CN	207492655	U	5/2017
CN	105996752	A	10/2016	CN	207506440	U	5/2017
CN	105996753	A	10/2016	CN	207804077	U	5/2017
CN	106037448	A	10/2016	CN	207804095	U	5/2017
CN	106037457	A	10/2016	CN	207855533	U	5/2017
CN	106037458	A	10/2016	CN	106805744	A	6/2017
CN	106388625	A	10/2016	CN	106805746	A	6/2017
CN	106419618	B	10/2016	CN	106805747	A	6/2017
CN	106419620	A	10/2016	CN	106805749	A	6/2017
CN	206414178	U	10/2016	CN	106805750	A	6/2017
CN	206687631	U	10/2016	CN	106805752	A	6/2017
CN	106073481	A	11/2016	CN	106820951	A	6/2017
CN	106073517	A	11/2016	CN	106820954	A	6/2017
CN	106108627	A	11/2016	CN	106821017	A	6/2017
CN	106108631	A	11/2016	CN	106852641	A	6/2017
CN	106166030	A	11/2016	CN	106859298	A	6/2017
CN	106377165	A	11/2016	CN	107049058	A	6/2017
CN	108056670	A	11/2016	CN	109008597	A	6/2017
CN	205671926	U	11/2016	CN	207575048	U	6/2017
CN	205671927	U	11/2016	CN	207604862	U	6/2017
CN	206518479	U	11/2016	CN	207627136	U	6/2017
CN	206560359	U	11/2016	CN	207640235	U	6/2017
CN	206560361	U	11/2016	CN	106913201	A	7/2017
CN	206777230	U	11/2016	CN	106923655	A	7/2017
CN	106175412	A	12/2016	CN	106943000	A	7/2017
CN	106175476	A	12/2016	CN	106943002	A	7/2017
CN	106213979	A	12/2016	CN	106955017	A	7/2017
CN	106235878	A	12/2016	CN	106974548	A	7/2017
CN	106618156	A	12/2016	CN	106983360	A	7/2017
CN	106901591	A	12/2016	CN	207855579	U	7/2017
CN	108132958	A	12/2016	CN	207940738	U	7/2017
CN	108201338	A	12/2016	CN	207940739	U	7/2017
CN	205831665	U	12/2016	CN	107019418	A	8/2017
CN	206469994	U	12/2016	CN	107019419	A	8/2017
CN	206700038	U	12/2016	CN	107019420	A	8/2017
CN	206867128	U	12/2016	CN	107019423	A	8/2017
CN	106264085	A	1/2017	CN	107048976	A	8/2017
CN	106264095	A	1/2017	CN	107048991	A	8/2017
CN	106343895	A	1/2017	CN	107048993	A	8/2017
CN	205860134	U	1/2017	CN	107105914	A	8/2017
CN	207627123	U	1/2017	CN	208211922	U	8/2017
CN	106377158	A	2/2017	CN	104334066	B	9/2017
CN	106377159	A	2/2017	CN	107136910	A	9/2017
CN	106388565	A	2/2017	CN	107136911	A	9/2017
CN	106388572	A	2/2017	CN	107149395	A	9/2017
CN	106419486	A	2/2017	CN	107149398	A	9/2017
CN	106419521	A	2/2017	CN	105142473	B	10/2017
CN	106419524	A	2/2017	CN	107224188	A	10/2017
CN	207101150	U	2/2017	CN	107224197	A	10/2017
CN	207202762	U	2/2017	CN	107232962	A	10/2017
CN	102805554	B	3/2017	CN	107259978	A	10/2017
CN	106473623	A	3/2017	CN	107290094	A	10/2017
CN	106490967	A	3/2017	CN	107290094	A	10/2017
				CN	107296485	A	10/2017
				CN	107296486	A	10/2017
				CN	107296487	A	10/2017
				CN	107296488	A	10/2017
				CN	107296489	A	10/2017

(56)

References Cited

FOREIGN PATENT DOCUMENTS

CN	107296490	A	10/2017	CN	107928395	A	4/2018
CN	107296493	A	10/2017	CN	107951369	A	4/2018
CN	107296494	A	10/2017	CN	107951376	A	4/2018
CN	109996475	A	10/2017	CN	107951407	A	4/2018
CN	110213984	A	10/2017	CN	107969907	A	5/2018
CN	104643954	B	11/2017	CN	107969908	A	5/2018
CN	107307729	A	11/2017	CN	107981713	A	5/2018
CN	107307730	A	11/2017	CN	107997571	A	5/2018
CN	107361637	A	11/2017	CN	108013742	A	5/2018
CN	107397431	A	11/2017	CN	108013743	A	5/2018
CN	208300842	U	11/2017	CN	108030404	A	5/2018
CN	208808155	U	11/2017	CN	108041976	A	5/2018
CN	107411540	A	12/2017	CN	108852431	A	5/2018
CN	107440490	A	12/2017	CN	209518760	U	5/2018
CN	107468052	A	12/2017	CN	209863450	U	5/2018
CN	107495849	A	12/2017	CN	108095570	A	6/2018
CN	107495856	A	12/2017	CN	108113501	A	6/2018
CN	107510356	A	12/2017	CN	108143256	A	6/2018
CN	107510379	A	12/2017	CN	108143259	A	6/2018
CN	110430793	A	12/2017	CN	108143259	A	6/2018
CN	206687606	U	12/2017	CN	108143260	A	6/2018
CN	209136189	U	12/2017	CN	108143261	A	6/2018
CN	209136190	U	12/2017	CN	108143262	A	6/2018
CN	106213986	B	1/2018	CN	108143262	A	6/2018
CN	107550258	A	1/2018	CN	108143263	A	6/2018
CN	107616686	A	1/2018	CN	108143263	A	6/2018
CN	107647763	A	2/2018	CN	108143264	A	6/2018
CN	107647769	A	2/2018	CN	108143264	A	6/2018
CN	107647771	A	2/2018	CN	108158429	A	6/2018
CN	107647772	A	2/2018	CN	108209547	A	6/2018
CN	107647777	A	2/2018	CN	209252407	U	6/2018
CN	107660996	A	2/2018	CN	104207651	B	7/2018
CN	107660997	A	2/2018	CN	106175423	A	7/2018
CN	107684336	A	2/2018	CN	108244994	A	7/2018
CN	107684337	A	2/2018	CN	108244995	A	7/2018
CN	107684338	A	2/2018	CN	108244997	A	7/2018
CN	107684339	A	2/2018	CN	108244998	A	7/2018
CN	107684340	A	2/2018	CN	108244999	A	7/2018
CN	107684341	A	2/2018	CN	108245000	A	7/2018
CN	107684342	A	2/2018	CN	108261055	A	7/2018
CN	107692806	A	2/2018	CN	108261056	A	7/2018
CN	107702838	A	2/2018	CN	108261061	A	7/2018
CN	107713732	A	2/2018	CN	108272336	A	7/2018
CN	107713733	A	2/2018	CN	108272338	A	7/2018
CN	107713734	A	2/2018	CN	108294616	A	7/2018
CN	107726388	A	2/2018	CN	108309035	A	7/2018
CN	110475493	A	2/2018	CN	108324096	A	7/2018
CN	110520022	A	2/2018	CN	110868894	A	7/2018
CN	106419522	B	3/2018	CN	106388570	B	8/2018
CN	107752726	A	3/2018	CN	106419517	B	8/2018
CN	107752748	A	3/2018	CN	108354444	A	8/2018
CN	107752751	A	3/2018	CN	108354466	A	8/2018
CN	107752788	A	3/2018	CN	108378678	A	8/2018
CN	107773021	A	3/2018	CN	108378690	A	8/2018
CN	107773026	A	3/2018	CN	108402888	A	8/2018
CN	107773029	A	3/2018	CN	108402889	A	8/2018
CN	107773090	A	3/2018	CN	108402920	A	8/2018
CN	107788820	A	3/2018	CN	108420304	A	8/2018
CN	107788827	A	3/2018	CN	108433517	A	8/2018
CN	107811499	A	3/2018	CN	108433529	A	8/2018
CN	107811517	A	3/2018	CN	108451351	A	8/2018
CN	107811518	A	3/2018	CN	108451388	A	8/2018
CN	107822492	A	3/2018	CN	108464732	A	8/2018
CN	107822494	A	3/2018	CN	110179361	A	8/2018
CN	107822496	A	3/2018	CN	110200516	A	8/2018
CN	107836981	A	3/2018	CN	110250927	A	8/2018
CN	107836986	A	3/2018	CN	110279315	A	8/2018
CN	107836988	A	3/2018	CN	207754989	U	8/2018
CN	207084680	U	3/2018	CN	207755036	U	8/2018
CN	107874584	A	4/2018	CN	106539491	B	9/2018
CN	107874599	A	4/2018	CN	107019415	B	9/2018
CN	107874601	A	4/2018	CN	107019416	B	9/2018
CN	107874602	A	4/2018	CN	108477987	A	9/2018
CN	107898351	A	4/2018	CN	108497908	A	9/2018
CN	107928388	A	4/2018	CN	108497914	A	9/2018
				CN	108497918	A	9/2018
				CN	108497942	A	9/2018
				CN	108523647	A	9/2018
				CN	108523649	A	9/2018
				CN	108552969	A	9/2018
				CN	108552989	A	9/2018
				CN	108567309	A	9/2018
				CN	108567321	A	9/2018

(56)

References Cited

FOREIGN PATENT DOCUMENTS

CN	108567322	A	9/2018	CN	106724784	B	1/2019
CN	108577514	C	9/2018	CN	106820956	B	1/2019
CN	106264094	B	10/2018	CN	106820957	B	1/2019
CN	108606627	A	10/2018	CN	107019417	B	1/2019
CN	108618592	A	10/2018	CN	109247837	A	1/2019
CN	108618593	A	10/2018	CN	109567619	A	1/2019
CN	108618594	A	10/2018	CN	109602265	A	1/2019
CN	108618595	A	10/2018	CN	109674357	A	1/2019
CN	108618597	A	10/2018	CN	106388566	B	3/2019
CN	108618651	A	10/2018	CN	107174116	B	3/2019
CN	108634771	A	10/2018	CN	107174117	B	3/2019
CN	108634777	A	10/2018	CN	109393957	A	3/2019
CN	108634807	A	10/2018	CN	105640308	A	6/2019
CN	108652431	A	10/2018	DE	2705168	A1	2/1977
CN	108652432	A	10/2018	DE	2753827	A1	12/1977
CN	108670021	A	10/2018	DE	20207570	U1	5/2002
CN	108670023	A	10/2018	DE	102011002821	A1	1/2011
CN	108703644	A	10/2018	DE	202017102536	U1	4/2017
CN	108703645	A	10/2018	EP	0416030	A1	5/1989
CN	108703675	A	10/2018	EP	1780471	A2	3/2006
CN	109662607	A	10/2018	EP	1767860	A1	3/2007
CN	109744849	A	10/2018	EP	2003400	A2	5/2008
CN	106580073	B	11/2018	EP	2020574	A2	6/2008
CN	108720548	A	11/2018	EP	2532971	A1	6/2011
CN	108720577	A	11/2018	EP	2904953	A1	2/2013
CN	108720581	A	11/2018	EP	2910856	A1	2/2015
CN	108720584	A	11/2018	EP	2976977	A1	6/2015
CN	108720585	A	11/2018	EP	3033978	A1	11/2015
CN	108720586	A	11/2018	EP	3165134	A1	10/2016
CN	108720633	A	11/2018	EP	3491980	A1	7/2017
CN	108732958	A	11/2018	FR	2409736	A1	11/1977
CN	108771466	A	11/2018	GB	2398628	A	2/2003
CN	108784323	A	11/2018	GB	2479384	A	4/2010
CN	108784324	A	11/2018	JP	H03504891	A	5/1989
CN	108784330	A	11/2018	JP	H09164074	A	12/1995
CN	108784401	A	11/2018	JP	10028643	A	7/1996
CN	108814274	A	11/2018	JP	H1028643	A	7/1996
CN	108836104	A	11/2018	JP	2005147604	A	11/2003
CN	108836105	A	11/2018	JP	2007007027	A	6/2005
CN	108836107	A	11/2018	JP	2008018122	A	7/2006
CN	108836108	A	11/2018	JP	2009291417	A	6/2008
CN	108836131	A	11/2018	JP	2011010786	A	7/2009
CN	108851966	A	11/2018	JP	5827524	B2	9/2011
CN	108851969	A	11/2018	JP	2013106850	A	11/2011
CN	108888087	A	11/2018	JP	5590583	B2	2/2013
CN	108888099	A	11/2018	JP	2014200627	A	10/2014
CN	108903620	A	11/2018	JP	2014204770	A	10/2014
CN	108903621	A	11/2018	JP	2015145778	A	11/2014
CN	109605463	A	11/2018	JP	2020169799	A	2/2020
CN	106419520	B	12/2018	JP	2020169800	A	2/2020
CN	106419526	B	12/2018	JP	2020169802	A	2/2020
CN	108926239	A	12/2018	JP	2020169803	A	2/2020
CN	108926249	A	12/2018	JP	2020169804	A	2/2020
CN	108937520	A	12/2018	JP	2020169805	A	2/2020
CN	108937525	A	12/2018	JP	2020173085	A	2/2020
CN	108937556	A	12/2018	KR	100232445	B1	1/1990
CN	108937558	A	12/2018	WO	8911773	A1	11/1989
CN	108937559	A	12/2018	WO	9837796	A1	9/1998
CN	108937560	A	12/2018	WO	9930086	A1	6/1999
CN	108955959	A	12/2018	WO	9952328	A1	10/1999
CN	108968659	A	12/2018	WO	0044096		7/2000
CN	108968660	A	12/2018	WO	0049839	A1	8/2000
CN	108968662	A	12/2018	WO	2006132612	A1	6/2005
CN	108968663	A	12/2018	WO	2006122643	A1	11/2006
CN	108968667	A	12/2018	WO	2010034338	A1	9/2008
CN	108968668	A	12/2018	WO	2009043812	A1	4/2009
CN	108968669	A	12/2018	WO	2010034374	A1	8/2009
CN	108991918	A	12/2018	WO	2012007681	A2	7/2011
CN	108991919	A	12/2018	WO	2012051508	A2	10/2011
CN	109008595	A	12/2018	WO	2014132105	A1	4/2013
CN	109008598	A	12/2018	WO	2014084365	A1	11/2013
CN	109681927	A	12/2018	WO	2015006891	A1	1/2015
CN	208259529	U	12/2018	WO	2015028940	A1	3/2015
CN	106562666	B	1/2019	WO	2015081549	A1	6/2015
CN	106606293	B	1/2019	WO	2016012908	A1	7/2015
				WO	2016007002	A1	1/2016
				WO	2016119691	A1	1/2016
				WO	2016028549	A1	2/2016
				WO	2016091063	A1	6/2016

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	2016141009	A1	9/2016	WO	2018004226	A1	1/2018
WO	2016148492	A1	9/2016	WO	2018014806	A1	1/2018
WO	2016154114	A1	9/2016	WO	2018015695	A1	1/2018
WO	2016165198	A1	10/2016	WO	2018138078	A1	1/2018
WO	2016171385	A1	10/2016	WO	2017077571	A1	2/2018
WO	2016182975	A1	11/2016	WO	2018007218	A1	2/2018
WO	2016189440		12/2016	WO	2018018670	A1	2/2018
WO	2016193008	A1	12/2016	WO	2018023863	A1	2/2018
WO	2016193643	A1	12/2016	WO	2018024781	A1	2/2018
WO	2017005533	A1	1/2017	WO	2018024782	A1	2/2018
WO	2017039091	A1	3/2017	WO	2018024783	A1	2/2018
WO	2017045387	A1	3/2017	WO	2018026041	A1	2/2018
WO	2017049635	A1	3/2017	WO	2018026906	A1	2/2018
WO	2017049717	A1	3/2017	WO	2018026928	A1	2/2018
WO	2017050693	A2	3/2017	WO	2018032540	A1	2/2018
WO	2018157409	A1	3/2017	WO	2018032541	A1	2/2018
WO	2017063872	A1	4/2017	WO	2018032542	A1	2/2018
WO	2018191960	A1	4/2017	WO	2018032589	A1	2/2018
WO	2017072068	A1	5/2017	WO	2018032648	A1	2/2018
WO	2017074119	A1	5/2017	WO	2018142088	A1	2/2018
WO	2017076797	A1	5/2017	WO	2018037177	A1	3/2018
WO	2017081420	A1	5/2017	WO	2018040250	A1	3/2018
WO	2017085026	A1	5/2017	WO	2018041536	A1	3/2018
WO	2017085671	A1	5/2017	WO	2018045643	A1	3/2018
WO	2017085673	A1	5/2017	WO	2018050520	A1	3/2018
WO	2017086543	A1	5/2017	WO	2018050838	A1	3/2018
WO	2017092062	A1	6/2017	WO	2019104818	A1	3/2018
WO	2017092063	A1	6/2017	WO	2019183755	A1	3/2018
WO	2017094968	A1	6/2017	WO	2018058384	A1	4/2018
WO	2017097790	A1	6/2017	WO	2018058569	A1	4/2018
WO	2017104892	A1	6/2017	WO	2018058740	A1	4/2018
WO	2017104894	A1	6/2017	WO	2018059994	A1	4/2018
WO	2017104895	A1	6/2017	WO	2018060260	A1	4/2018
WO	2017104896	A1	6/2017	WO	2018060273	A1	4/2018
WO	2017104898	A1	6/2017	WO	2018060331	A1	4/2018
WO	2017104900	A1	6/2017	WO	2018065424	A1	4/2018
WO	2017105076	A2	6/2017	WO	2018068376	A1	4/2018
WO	2017111425	A1	6/2017	WO	2018068425	A1	4/2018
WO	2017121691	A1	7/2017	WO	2018068976	A1	4/2018
WO	2017127655	A1	7/2017	WO	2018212473	A1	4/2018
WO	2018161497	A1	7/2017	WO	2019066747	A2	4/2018
WO	2017144795	A1	8/2017	WO	2019153512	A1	4/2018
WO	2018189921	A1	8/2017	WO	2018076164	A1	5/2018
WO	2017149519	A1	9/2017	WO	2018076166	A1	5/2018
WO	2017152518	A1	9/2017	WO	2018076415	A1	5/2018
WO	2017153360	A1	9/2017	WO	2018082131	A1	5/2018
WO	2017158068	A1	9/2017	WO	2018090287	A1	5/2018
WO	2017166317	A1	10/2017	WO	2018093004	A1	5/2018
WO	2017177007	A1	10/2017	WO	2018095247	A1	5/2018
WO	2017177423	A1	10/2017	WO	2018095420	A1	5/2018
WO	2017178229	A1	10/2017	WO	2018095949	A1	5/2018
WO	2017178650	A1	10/2017	WO	2018120561	A1	5/2018
WO	2017178739	A1	10/2017	WO	2018216042	A1	5/2018
WO	2017179804	A1	10/2017	WO	2017104893	A1	6/2018
WO	2018227851	A1	10/2017	WO	2018099233	A1	6/2018
WO	2018227852	A1	10/2017	WO	2018102128	A1	6/2018
WO	2017191377	A1	11/2017	WO	2018107522	A1	6/2018
WO	2017191395	A1	11/2017	WO	2018107973	A1	6/2018
WO	2017195777	A1	11/2017	WO	2018116056	A1	6/2018
WO	2017197482	A1	11/2017	WO	2018116057	A1	6/2018
WO	2017198815	A1	11/2017	WO	2018235095	A1	6/2018
WO	2017198848	A1	11/2017	WO	2019015425	A1	6/2018
WO	2017201530	A1	11/2017	WO	2018121166	A1	7/2018
WO	2017202641	A1	11/2017	WO	2018121199	A1	7/2018
WO	2018171250	A1	11/2017	WO	2018133993	A1	7/2018
WO	2018227866	A1	11/2017	WO	2018137832	A1	8/2018
WO	2018233210	A1	11/2017	WO	2018140954	A1	8/2018
WO	2017209465	A1	12/2017	WO	2018147640	A1	8/2018
WO	2017211045	A1	12/2017	WO	2019026018	A1	8/2018
WO	2017213330	A2	12/2017	WO	2018165698	A1	9/2018
WO	2017213423	A1	12/2017	WO	2019064319	A1	9/2018
WO	2017215926	A1	12/2017	WO	2019082210	A1	10/2018
WO	2017215988	A1	12/2017	WO	2020052010	A1	10/2018
WO	2018104351	A1	12/2017	WO	2018197720	A1	11/2018
WO	2018227938	A1	12/2017	WO	2018207221	A1	11/2018
				WO	2019097545	A1	11/2018
				WO	2019153807	A1	11/2018
				WO	2018220659	A1	12/2018
				WO	2018223713	A1	12/2018

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	2019129598	A1	12/2018
WO	2020062651	A1	12/2018
WO	2020071590	A1	12/2018
WO	2019032876	A1	2/2019
WO	2019032878	A1	2/2019
WO	2019207325	A1	4/2019
WO	2019243922	A1	5/2019
WO	2019238605	A1	6/2019
WO	2019238794	A1	6/2019
WO	2019243093	A1	6/2019
WO	2020000046	A1	6/2019
WO	2020002064	A1	6/2019
WO	2020078010	A1	6/2019
WO	2020016084	A1	7/2019
WO	2020016085	A1	7/2019
WO	2020030462	A1	7/2019
WO	2020098748	A1	11/2019

OTHER PUBLICATIONS

Notification of Transmittal of the International Search Report of the International Searching Authority, or the Declaration; PCT/US2018/046079; dated Jan. 2, 2019, 7 pages.

Notification of Transmittal of the Written Opinion of the International Searching Authority, or the Declaration. PCT/US2018/046077, dated Dec. 19, 2018, 10 pages.

Notification of Transmittal of the Written Opinion of the International Searching Authority, or the Declaration; PCT/US2018/046079; dated Jan. 2, 2019, 10 pages.

WO2018122652A1; Jul. 5, 2018; English Abstract Only (3 Pages). DeLonghi, [online]; [retrieved on Mar. 18, 2019]; retrieved from the Internet <https://www.deionghi.com/en-us/products/kitchen/kitchen-appliances/low-oil-fryer-and-multicooker/multifry-fh11631bk-0125392006?TabSegment=support#supportDeLonghi>, "FH1163 FH1363 MultiFry", DeLonghi Instruction Manual, www.delonghi.com, 5712511041/05.15, pp. 1-11.

U.S. Appl. No. 16/357,141, filed Mar. 18, 2019; Interview Summary dated Jun. 17, 2019; 1-3 pages.

U.S. Appl. No. 16/357,238, filed Mar. 18, 2019; Interview Summary dated Jun. 26, 2019; 1-4 pages.

U.S. Appl. No. 16/357,250, filed Mar. 18, 2019; Interview Summary dated Jun. 17, 2019; 1-4 pages.

U.S. Appl. No. 16/357,274, filed Mar. 18, 2019; Interview Summary dated Jun. 5, 2019; 1-3 pages.

U.S. Appl. No. 16/357,276, filed Mar. 18, 2019; Interview Summary dated Jun. 5, 2019; 1-4 pages.

U.S. Appl. No. 16/357,277, filed Mar. 18, 2019; Interview Summary dated Jun. 3, 2019; 1-4 pages.

U.S. Appl. No. 16/357,279, filed Mar. 18, 2019; Interview Summary dated Jun. 19, 2019; 1-4 pages.

U.S. Appl. No. 16/357,280, filed Mar. 18, 2019; Interview Summary dated Jun. 17, 2019; 1-3 pages.

U.S. Appl. No. 16/357,282, filed Mar. 18, 2019; Non-Final Office Action dated Jun. 27, 2019; 19 pages.

U.S. Appl. No. 16/357,175, filed Mar. 18, 2019; Non-Final Office Action dated May 16, 2019; 49 pages.

U.S. Appl. No. 16/357,243, filed Mar. 18, 2019; Non-Final Office Action dated Jun. 3, 2019; 24 pages.

U.S. Appl. No. 16/357,223, filed Mar. 1, 2019; Non-Final Office Action dated May 23, 2019; 11 pages.

U.S. Appl. No. 16/357,227, filed Mar. 18, 2019; Non-Final Office Action dated May 23, 2019; 10 pages.

U.S. Appl. No. 16/357,234, filed Mar. 18, 2019; Non-Final Office Action dated May 24, 2019; 12 pages.

U.S. Appl. No. 16/357,238, filed Mar. 18, 2019; Non-Final Office Action dated May 28, 2019; 32 pages.

U.S. Appl. No. 16/357,250, filed Mar. 18, 2019; Non-Final Office Action dated May 24, 2019; 18 pages.

U.S. Appl. No. 16/357,271, filed Mar. 18, 2019; Non-Final Office Action dated May 15, 2019; 7 pages.

U.S. Appl. No. 16/357,273, filed Mar. 8, 2019; Non-Final Office Action dated May 17, 2019; 8 pages.

U.S. Appl. No. 16/357,274, filed Mar. 18, 2019; Non-Final Office Action dated May 10, 2019; 7 pages.

U.S. Appl. No. 16/357,276, filed Mar. 18, 2019; Non-Final Office Action dated May 10, 2019; 7 pages.

U.S. Appl. No. 16/357,277, filed Mar. 18, 2019; Non-Final Office Action dated May 9, 2019; 9 pages.

U.S. Appl. No. 16/357,279, filed Mar. 18, 2019; Non-Final Office Action dated May 30, 2019; 9 pages.

U.S. Appl. No. 16/402,023, filed May 2, 2019; Non-Final Office Action dated May 14, 2019; 8 pages.

U.S. Appl. No. 16/402,023, filed May 2, 2019; Non-Final Office Action dated May 30, 2019; 25 pages.

U.S. Appl. No. 16/402,029, filed May 2, 2019; Non-Final Office Action dated Jun. 13, 2019; 9 pages.

U.S. Appl. No. 16/357,141, filed Mar. 18, 2019; Non-Final Office Action dated May 16, 2019; 17 pages.

U.S. Appl. No. 16/357,250, filed Mar. 18, 2019; Final Office Action dated Sep. 13, 2019; 1-14 pages.

U.S. Appl. No. 16/357,280, filed Mar. 18, 2019; Final Office Action dated Sep. 13, 2019; 1-11 pages.

U.S. Appl. No. 16/357,141, filed Mar. 18, 2019; Final Office Action dated Aug. 30, 2019; 20 pages.

U.S. Appl. No. 16/357,251, filed Mar. 18, 2019; Non-Final Office Action dated Aug. 1, 2019; 186 pages.

U.S. Appl. No. 16/357,270, filed Mar. 18, 2019; Non-Final Office Action dated Jun. 14, 2019; 16 pages.

Civil Action No. 19-cv-24114, U.S. District Court, Southern District of Florida; Complaint; Plaintiff SharkNinja Operating LLC for Complaint for Patent Infringement and Demand for Jury Trial against Defendants D Tristar Products, Inc. and Emeril Lagasse, (Entered: Oct. 4, 2019) pp. 1-194.

Civil Action No. 19-cv-24114, U.S. District Court, Southern District of Florida; Defendant Emeril Lagasse's Motion To Dismiss for Improper Venue; *SharkNinja Operating LLC (Plaintiff) v. Tristar Products, Inc. and Emeril Lagasse (Defendants)*; Document 24 (Entered: Nov. 29, 2019) pp. 1-6.

Civil Action No. 19-cv-24114, U.S. District Court, Southern District of Florida; Defendant Tristar Products Inc.'s Answer To Plaintiff's Complaint and Counterclaims; *SharkNinja Operating LLC (Plaintiff) v. Emeril Lagasse (Defendant) and Tristar Products, Inc. (Defendant/Counterclaim Plaintiff) v. D SharkNinja Operating LLC, Daniel R. Gibson, Cantor Colburn LLP, Pedro Lopez-Baldrich (Counterclaim Defendants)*; Document 25 (Entered: Nov. 29, 2019) pp. 1-36.

European Application No. 1921797806-1004 filed Dec. 31, 2019; European Search Report dated Apr. 1, 2020; 7 pages.

European Application No. 19218088.3-1004 filed Dec. 19, 2019; European Search Report dated Jun. 3, 2020; 7 pages.

European Application No. 19218129.5-1004 filed Dec. 19, 2019; European Search Report dated May 19, 2020; 7 pages.

European Application No. 19218218.6-1004 filed: Dec. 19, 2019; European Search Report dated May 27, 2020; 6 pages.

European Application No. 19218240.0-1004 filed: Dec. 19, 2019; European Search Report dated May 27, 2020; 7 pages.

European Application No. 19218251.7-1004 filed Dec. 19, 2019; European Search Report dated May 27, 2020; 7 pages.

European Application No. 19218259.0-1004 filed Dec. 19, 2019; European Search Report dated May 27, 2020; 7 pages.

Extended European Search Report issued in European Application No. 21165149.2, dated Jul. 1, 2021, 8 pages.

Extended European Search Report issued in European Application No. 21165150.0, dated Oct. 6, 2021, 10 pages.

Extended European Search Report issued in European Application No. 21165153.4, dated Jul. 6, 2021, 7 pages.

(Apr. 7, 2013) Hip Cooking, [online]; [retrieved on Nov. 25, 2019]; retrieved from the Internet <https://www.hippressurecooking.com/pressure-cooker-psi-faq-the-stuff-you-didnt-think-to-ask/LauraPazzaglia>, "Pressure Cooker PSI FAQ: The Stuff You Didn't Think to Ask about Pressure," pp. 1-26.

(56)

References Cited

OTHER PUBLICATIONS

International Preliminary Report on Patentability for International Application No. PCT/US2018/046079, dated Feb. 20, 2020, 11 pages.

International Preliminary Report on Patentability received for PCT Application No. PCT/US2018/046077, dated Feb. 20, 2020, 12 pages.

International Search Report and Written Opinion received for International Application No. PCT/US2019/065662 dated Mar. 25, 2020; 7 pages.

International Search Report and Written Opinion received for PCT Application No. PCT/US2018/046077, dated Dec. 19, 2018, 17 pages.

International Search Report and Written Opinion received for PCT Patent International Application No. PCT/US2020/017203, dated Jun. 4, 2020, 6 pages.

International Search Report and Written Opinion received for PCT Patent International Application No. PCT/US2020/017205, dated Jul. 16, 2020; 8 pages.

International Search Report and Written Opinion received for PCT Patent International Application No. PCT/US2020/19664; dated Jun. 4, 2020; 6 pages.

Invitation to Pay Additional Fees for international Application No. PCT/US2020/017205; dated May 19, 2020; 61 pages.

Invitation to Pay Additional Fees for International Application No. PCT/US2020/019685, dated Oct. 13, 2020, 11 Pages.

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 1D




FIG. 2





FIG. 3A






FIG. 3C




FIG. 4




FIG. 5




FIG. 6A




FIG. 6B




FIG. 7




FIG. 8A




FIG. 8C




FIG. 8B




FIG. 8D




FIG. 9




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18

FUNCTION	DEFAULT TIME (HH:MM)	TIME SETTINGS	PRESSURE SETTINGS	DEFAULT TEMPERATURE (F)	TEMPERATURE SETTINGS	FAN SPEED SETTING (RPM)
PRESSURE	0:10 HI (DEFAULT)/ 0:10 LO	0:00-4:00, 1 MIN INCREMENTS FROM 0:00-1:00, 5 MIN INCREMENTS FROM 1:00-4:00	LO: 50 ± 10KPA HI: 80 ± 10KPA	N/A	N/A	N/A
SLOW COOK	4:00 HI (DEFAULT)/ 8:00 LO	4:00-12:00, 15 MIN INCREMENT HIGH, 6:00-12:00, 15 MIN INCREMENT LOW	N/A	HI	LO/HI	N/A
SEAR/SAUTE	N/A	NO TIME FUNCTIONALITY FOR SEAR/SAUTE	N/A	HI	LO / LO:MD / MD / MD:HI / HI (INCLUDE : WHERE SHOWN)	N/A
STEAM	0:10	0:01-0:30, 1 MIN INCREMENT	N/A	N/A	N/A	N/A
AIR CRISP	0:20	0:01-1:00, 1 MIN INCREMENT	N/A	390	300, 315, 325, 330, 345, 350, 360, 375, 390, 400	100% MOTOR POWER (TARGET 2650RPM)
ROAST	0:15	0:01-4:00, 1 MIN INCREMENTS FROM 0:01-1:00, 5 MIN INCREMENTS FROM 1:00-4:00	N/A	375	250, 260, 275, 290, 300, 315, 325, 330, 345, 350, 360, 375, 390, 400	100% MOTOR POWER (TARGET 2650RPM)
DEHYDRATE	6:00	1:00-12:00, 15 MIN INCREMENTS	N/A	150	105, 120, 135, 150, 165, 180, 195	50% MOTOR POWER (TARGET 1200RPM)
BROIL	00:10	0:01-0:30, 1 MIN INCREMENTS	N/A	450	450	100% MOTOR POWER (TARGET 2650RPM)

FIG. 19




FIG. 20




FIG. 21

COOKING DEVICE AND COMPONENTS THEREOF

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation application of U.S. Non-Provisional application Ser. No. 16/059,876, filed Aug. 9, 2018, which claims the benefit of U.S. Provisional Application Ser. No. 62/543,082, filed Aug. 9, 2017, which is incorporated herein by reference in its entirety.

BACKGROUND

Embodiments of the present disclosure relates generally to a cooking device and components thereof, and more specifically, a multifunction device configured to perform the operation of a plurality of distinct cooking devices, the multifunctional cooking device optionally employing various components for cooking in the distinct cooking modes.

Conventional cooking devices, such as pressure cookers and air fryers each perform a single cooking operation, and as such, these devices employ different components and method for cooking food items. As such, multiple devices are required to perform various cooking operations. For consumers that wish to enjoy food cooked in different ways via different operations, an accumulation of these devices can occur. Such an accumulation of cooking devices is often prohibitive from a standpoint of cost and storage space. For at least these reasons, it would be desirable to integrate the functionality of several cooking devices into a single user-friendly cooking device.

SUMMARY

Disclosed herein is a cooking system for cooking food, the system including a housing defining a hollow chamber configured to receive a food container. The housing has an upper portion defining an opening to the hollow chamber. A lid is attachable about the upper portion of the housing and is configured to extend across the opening to the hollow chamber. At least one heating element is associated with at least one of said housing and said lid. The cooking system is operable in a plurality of modes including a pressure cooking mode and a convective cooking mode. In the pressure cooking mode, the cooking system is operable as a pressure cooker and in the convective cooking mode, the cooking system is operable as a convection cooker.

In addition to one or more of the features described above, or as an alternative, in further embodiments including a food container that is receivable within said hollow chamber, said food container having a base and an open end, and wherein said lid is attachable to said upper portion of said housing and sealable about said open end of said food container when said food container is received within said hollow chamber.

In addition to one or more of the features described above, or as an alternative, in further embodiments said cooking system is operable in said pressure cooking mode when said lid is attached to said upper portion of said housing and seals said open end of said food container.

In addition to one or more of the features described above, or as an alternative, in further embodiments said upper portion of said housing is configured with a bayonet locking feature and said lid is configured with a compatible bayonet locking feature.

In addition to one or more of the features described above, or as an alternative, in further embodiments including a second lid that is adapted to abut said upper portion of said housing and cover said lid when said lid is attached to said upper portion of said housing and seals said open end of said food container.

In addition to one or more of the features described above, or as an alternative, in further embodiments including a second lid moveably attached to said housing, said second lid moveable between a first position that covers said opening to said hollow chamber and a second position where said second lid does not cover said opening to said hollow chamber, wherein said second lid includes a heating element.

In addition to one or more of the features described above, or as an alternative, in further embodiments said cooking system is operable in said convective cooking mode when said second lid is in said first position.

In addition to one or more of the features described above, or as an alternative, in further embodiments said cooking system is operable in either of said pressure cooking mode and said convective cooking mode when said second lid is in said first position.

In addition to one or more of the features described above, or as an alternative, in further embodiments said cooking system is operable in said pressure cooking mode when said second lid is in said first position.

In addition to one or more of the features described above, or as an alternative, in further embodiments when in said convective cooking mode the cooking system is operable as at least one of an air fryer, baking/roasting oven, broiler, and dehydrator.

In addition to one or more of the features described above, or as an alternative, in further embodiments said food container includes a food support surface, and food is receivable in said food container in contact with said food support surface in both said pressure cooking mode and said convective cooking mode.

In addition to one or more of the features described above, or as an alternative, in further embodiments said at least one heating element is a first heating element and a second heating element, said first heating element being disposed at or below a lower extent of said hollow chamber, and said second heating element being disposed at or above said opening to said hollow chamber.

In addition to one or more of the features described above, or as an alternative, in further embodiments said second heating element is disposed in said second lid.

In addition to one or more of the features described above, or as an alternative, in further embodiments said second heating element is disposed in said lid, and wherein a fan is also disposed in said lid at or above said opening to said hollow chamber.

In addition to one or more of the features described above, or as an alternative, in further embodiments the cooking system is operable in either said pressure cooking mode and said convective cooking mode without having to remove said food container from the hollow chamber.

In addition to one or more of the features described above, or as an alternative, in further embodiments said second lid is coupled to said housing when said cooking system is in said pressure cooking mode.

In addition to one or more of the features described above, or as an alternative, in further embodiments comprising an insert for supporting a food item in said hollow chamber.

In addition to one or more of the features described above, or as an alternative, in further embodiments said insert is

3

positionable within said food container to form an annulus between an inner wall of said food container and an outer wall of said insert.

In addition to one or more of the features described above, or as an alternative, in further embodiments said insert further comprises a base and an open end, said base including a plurality of apertures that allow fluid to flow through said base.

In addition to one or more of the features described above, or as an alternative, in further embodiments including a diffuser disposed in said hollow chamber, said diffuser including at least one vane configured to impart rotation to fluid circulating through said hollow chamber.

In addition to one or more of the features described above, or as an alternative, in further embodiments including a diffuser disposed beneath said base, said diffuser including at least one vane configured to impart rotation to fluid circulating through said plurality of apertures during said convective cooking mode.

In addition to one or more of the features described above, or as an alternative, in further embodiments including a fan and at least one heating element disposed at or above said opening to said hollow chamber, said fan being positioned to move heated air relatively downward through said annulus, relatively horizontally across a lower surface of said food container, and relatively upward through said diffuser and said plurality of apertures of said base when said insert is positioned in said food container and said food container is received within said hollow chamber.

In addition to one or more of the features described above, or as an alternative, in further embodiments said diffuser is configured to create a vortex of air circulating through said insert.

In addition to one or more of the features described above, or as an alternative, in further embodiments said food container includes an upward facing lower surface that is curved upward in a direction of an upper opening of said food container, and said diffuser includes downward facing lower surface that is curved or sloped to conform to said upward facing lower surface of said food container.

In addition to one or more of the features described above, or as an alternative, in further embodiments said fan is positioned to draw air relatively upward through said insert and through said at least one heating element in said convective cooking mode.

In addition to one or more of the features described above, or as an alternative, in further embodiments said lid abuts said housing about a substantial entirety of said upper surface thereof when said lid is in said closed position.

In addition to one or more of the features described above, or as an alternative, in further embodiments said housing is configured to surround said food container around a substantial entirety of at least a portion thereof when said food container is received within said hollow chamber.

BRIEF DESCRIPTION OF THE FIGURES

The accompanying drawings incorporated in and forming a part of the specification embodies several aspects of the present disclosure and, together with the description, serves to explain the principles of the disclosure. In the drawings:

FIG. 1A is a perspective front view of the cooking system according to an embodiment;

FIG. 1B is a bottom view of the cooking system according to an embodiment;

FIG. 1C is a side by side front view the cooking system according to an embodiment;

4

FIG. 1D is a rear view of the cooking system according to an embodiment;

FIG. 2 is a perspective view of the cooking system having a lid in an open position according to an embodiment;

FIG. 3A is a cross-sectional view of the cooking system having a secondary lid according to an embodiment;

FIG. 3B is a front view of a cooking system having a secondary lid according to an embodiment;

FIG. 3C is a lower view of a lid of the cooking system according to an embodiment;

FIG. 4 is a perspective view of a cooking system having both a lid and a secondary lid in an open position according to an embodiment;

FIG. 5 is a perspective view of a cooking system having both a lid and a secondary lid in a closed position according to an embodiment;

FIG. 6A is a perspective view of a lid of the cooking system according to an embodiment;

FIG. 6B is another perspective view of a lid of the cooking system according to an embodiment;

FIG. 7 is a schematic diagram of the cooking system according to an embodiment;

FIG. 8A is a perspective view of an air diffuser according to an embodiment;

FIG. 8B perspective lower view of an insert according to an embodiment;

FIG. 8C is a perspective view of an insert with attached diffuser according to an embodiment;

FIG. 8D is a side view of the insert according to an embodiment;

FIG. 9 is a perspective view of a diffuser received in a container according to an embodiment;

FIG. 10 is a perspective view of a cooking system having an insert positioned therein according to an embodiment;

FIG. 11 is a cross-sectional view of the cooking system according to an embodiment;

FIG. 12 is a block diagram illustrating a control path for a cooking system according to an embodiment;

FIG. 13 is a perspective view of the cooking system having a lid in an open position according to an embodiment;

FIG. 14 is a perspective view of a cooking rack for use in a cooking system according to an embodiment;

FIG. 15 is a perspective view of the cooking rack received in the cooking system according to an embodiment;

FIG. 16 is another perspective view of the cooking rack for use in the cooking system according to an embodiment;

FIG. 17 is a perspective view of the cooking rack received in the cooking system according to an embodiment;

FIG. 18 is another perspective view of the cooking rack for use in the cooking system according to an embodiment;

FIG. 19 is a table showing cooking parameters for use in a cooking system according to an embodiment;

FIG. 20 is a circuit diagram for use in a cooking system according to an embodiment;

FIG. 21 is a logic diagram for use in a cooking system according to an embodiment; and

FIGS. 22A, 22B, 22C, and 22D is an upper view of a series of lid positions in a cooking system according to an embodiment.

The detailed description explains embodiments of the disclosure, together with advantages and features, by way of example with reference to the drawings.

DETAILED DESCRIPTION

With reference first to FIGS. 1-7, a cooking system 20 configured to perform multiple cooking operations is illus-

5

trated. As shown, the cooking system 20 includes a housing 22 and a first or primary lid 32 permanently or removably attached, or more specifically hinged, to the housing 22. In an exemplary, non-limiting embodiment, the connection or hinge area between the lid 32 and the housing 22 occurs at an upper portion of a spine 39 of the housing 22. A bottom 106 of the housing 22 of the cooking system 20 (see FIG. 1B) may be supported on a surface by one or more feet 25 and 27, which may include shock absorbing pads 25a and 27a (of a material such as but not limited to rubber) at a bottom surface thereof. The feet 25, 27 may extend from the housing 22 to define a surface on which the cooking system 20 may contact an adjacent supporting surface, such as a countertop for example. The bottom surface of the feet 25, 27 or pads 25a, 27a may be flush with, or alternatively, may extend out of plane from the bottom 106 of the housing. In the illustrated, non-limiting embodiment, the housing 22 includes two feet 25, 27 arranged on opposing sides of the housing 22; however, it should be understood that a housing having any suitable number of feet 25 is within the scope of the disclosure.

Further, in the exemplary, non-limiting embodiment shown in at least FIGS. 1A-C, the foot 25 under the spine 39 is larger and extends out a greater distance from the side of the housing 22 than the foot 27. As shown in FIG. 1C, this allows for better support of the system 20 when the cooking system 20 is on a substantially flat surface or an inclined surface (up to 15 degrees in an exemplary embodiment) and the relatively heavy lid 32 is in an open position.

In the illustrated, non-limiting embodiment, one or more handles 26 extend outwardly from the exterior of the housing 22 to provide a user with a location to more easily grasp the system 20. Although two handles 26 are shown, embodiments having no handles, a single handle, or more than two handles are also within the scope of the disclosure. The housing 22 and/or the one or more handles 26 may be integrally or separately formed, such as from a molded plastic material for example. Referring now to some of the interior features of the system 20, an inner surface of the housing 22 defines a hollow interior 30. In an exemplary non-limiting embodiment, a liner 23 that may be formed from any suitable conductive material, such as aluminum for example is disposed within the hollow interior 30, and in some embodiments the liner 23 may be the inner surface defining the hollow interior (though surfaces inside the liner 23, such as the walls of the container, or outside the liner 23, such as plastic around the liner 23, may also define the hollow interior 30). In an exemplary, non-limiting embodiment, a food container 24 is receivable inside the hollow interior 30 defined by the liner 23. Spacing components, such as silicone bumpers (not shown) may be disposed along the inner surface of the liner 23 to keep the container 24 aligned properly within the hollow interior 30 during cooking. Although the container 24 is described herein as being removable from the housing 22, embodiments where the container 24 is integrally formed with the housing 22 are also contemplated herein. The container 24, which is shown in FIGS. 2 and 3A, has an interior 33 designed to receive and retain one or more consumable products, such as food products for example, therein. Examples of food products suitable for use with the cooking system 20, include but are not limited to, meats, fish, poultry, bread, rice, grains, pasta, vegetables, fruits, and dairy products, among others. The container 24 may be a pot formed from a ceramic, metal, or die cast aluminum material. In an embodiment, an interior surface of the container 24 includes a nano ceramic coating and an exterior surface of the container 24 includes a

6

silicone epoxy material. However, any suitable material capable of withstanding the high temperatures and pressures required for cooking food products is contemplated herein.

Referring with more detail not to the lid 32, it should be noted that the lid 32 is connectable to a surface of the container 24 and/or housing 22 to close off entry to the hollow interior 30 of the container 24. In an embodiment, a diameter of the lid 32 is generally complementary to a diameter of the housing 22 such that the lid 32 covers not only the container 24, but also an upper surface 34 of the housing 22. The lid 32 can be made of any suitable material, such as glass, aluminum, plastic, or stainless steel for example. Further, the lid 32 may, but need not, include one or more handles 36 for removably coupling the lid 32 to the remainder of the cooking system 20. In the illustrated, non-limiting embodiment, the lid 32 is coupled to the housing 22 via a hinge 38 (best shown in FIG. 3A just above the spine 39), such that the lid 32 is rotatable about an axis X between an open position (FIG. 3) and a closed position (FIG. 1A). In such embodiments, the hinge axis X may be located at a side surface of the cooking system 20, as shown in FIG. 2, or alternatively, at a back surface of the cooking system 20, such as vertically disposed relative to one or more handles 26 of the housing 22, as shown in FIG. 4. However, embodiments where the lid 32 is separable from the housing 22, or movable between the open and closed positions in another manner are also contemplated herein. One or more fastening mechanisms (not shown) may, but need not be used to secure the lid 32 to the housing 22 when the lid 32 is in the closed position. Any suitable type of fastening mechanism capable of withstanding the heat associated with the cooking system 20 is considered within the scope of the disclosure. In an embodiment, best shown in FIGS. 3A-C, 4-5, and 6A-B, the cooking system 20 additionally includes a secondary lid 37 configured to removably couple to the housing 22 and/or container 24 to seal the hollow interior 30. In an embodiment, the secondary lid 37 is press-fit onto an upper surface 34 of the housing 22 or directly to the container 24. In another embodiment, the secondary lid 37 is configured to thread-ably couple to the upper surface 34 of the housing 22 or the container 24. However, embodiments where the secondary lid 37 is configured to couple to at least one of the housing 22 and container 24 in another suitable manner, such as via a pressure tight mechanism for example, are also contemplated herein. The secondary lid 37 can be made of any suitable material, such as glass, aluminum, plastic, or stainless steel, or any combination thereof for example. In an embodiment, the secondary lid 37 is formed from a molded plastic material. In addition, the secondary lid 37 may, but need not, include one or more handles 41 for removably coupling the secondary lid 37 to the cooking system 20. The handle 41 may be integrally formed with the remainder of the lid 37, such as via a molding process, or alternatively, may be a separate component coupled to the lid 37.

As best shown in FIG. 6B, the secondary lid 37 includes an interior liner 43, also referred to as an "underliner" formed from any suitable material, such as stainless steel for example. In an embodiment, one or more threads may be formed in the underliner 43 to couple the lid 37 to an end of the container 24. As shown, the lid 37 may additionally include a lid support ring 45 having a diameter extending beyond the outer diameter of the underliner 43 about at least a portion of the circumference thereof. In an embodiment, a surface 47 of the lid support ring 45 may be configured to abut the upper surface 34 of the housing 22 when the secondary lid 37 is coupled to the container 24. A lid cushion

49, such as formed from a resilient or elastomeric material, such as rubber for example, may be disposed at an exterior surface of a portion of the lid 37, such as between the under-liner 43 and the lid support ring 45 for example. Further, a pressure relief valve 51 (see FIG. 6A) is formed in a surface of the secondary lid, such as the upper surface thereof for example. The pressure relief valve is configured to automatically open to release air from within the chamber formed between the secondary lid 37 and the container 24 when the pressure therein exceeds a predetermined threshold. Alternatively, or in addition, the pressure relief valve is manually operable to release air from within the chamber formed between the secondary lid 37 and the container 24.

To couple the secondary lid 37 to the housing 22, the primary lid 32 must be in an open position, as shown in FIGS. 3A and 3B. Further, in an embodiment, the primary lid 32 is not movable to the closed position relative to the housing 22 when the secondary lid 37 is affixed thereto. This may be due to the outer diameter of the secondary lid 37, or alternatively, because one or more components extending upwardly from the lid 37, such as handle 41, would interfere with a portion of the primary lid 32. However, in other embodiments, as shown in FIGS. 4 and 5, at least a portion of the secondary lid 37 may be nestable or receivable within the primary lid 32. In such embodiments, the outer diameter of the secondary lid 37 may be smaller than the inner diameter of the primary lid 32, such that the primary lid 32 substantially surrounds the secondary lid 37 when in the closed position. Accordingly, the enclosure defined by the hollow interior 30 of the container 24 and the secondary lid 37 is smaller than the enclosure formed by the hollow interior 30 of the container 24 and the primary lid 32. Although the cooking system 20 is illustrated and described herein including the secondary lid 37, it should be understood that in some embodiments the cooking system 20 includes only a primary lid 32 and does not include a secondary lid 37.

With reference again to FIG. 2, a condensation rim may be formed in the upper surface 34 of the housing 22, radially outward of the opening and/or container 24. During operation of the cooking system 20, condensation or other fluid circulating within the container 24 and/or hollowed interior 30 of the system 20 may collect within the condensation rim. In an embodiment, best shown in FIG. 1D, a condensation tray 53 is arranged in communication with the interior 30 of the container 24. The condensation tray 53, may, but need not, be arranged in fluid communication with the condensation rim of the upper surface 34. As shown, the condensation tray 53 is accessible via the back surface of the housing 22 and is configured to removably couple to the housing 22 to allow a user to empty the contents of the tray 53. When connected to the housing 22, the condensation tray 53 may be suitable to form a pressure tight seal with the housing 22.

With specific reference now to FIG. 7, the cooking system 20 includes at least one first heating element 82 and at least one second heating element 84 configured to impart heat to the hollow interior and/or container 24 during various modes of operation of the cooking system 20. As shown, one or more first heating elements 82 may be disposed at the base 28 of the housing 22, generally adjacent the bottom 31 of the container 24; though, embodiments where one or more of the first heating elements 82 are arranged adjacent a side of the housing 22, in addition to or in place of the base 28 of the housing 22, are also contemplated herein. The second heating element 84 may be positioned generally at or above an upper extent of the container 24, proximate an upper

opening of the container. However, in the exemplary non-limiting embodiment shown in the Figures, the second heating element 84 is disposed in the lid 32, and therefore completely outside of the container 24, above the upper extent thereof.

With reference again to FIGS. 1A, 4, 5, and reference to FIG. 10, a control panel or user interface 92 of the cooking system 20 is positioned adjacent one or more sides of the housing 22. The control panel 92 includes one or more inputs 94 associated with energizing the one or more heating elements 82, 84 of the cooking system 20 and for selecting various modes of operation of the cooking system 20. One or more of the inputs 94 may include a light or other indicator to show that the respective input has been selected. The control panel 92 may additionally include a display 96 separate from and associated with the at least one input 94. However, embodiments where the display 96 is integrated into the at least one input 94 are also contemplated herein.

Operation of the one or more inputs 94 will be described in more detail below. As shown in FIG. 12, a control system 100 of the cooking system 20 includes a controller or processor 102 for controlling operation of the heating elements 82, 84 (and air movement device 86 including the motor 88 and fan 90 associated therewith, which will be discussed in greater detail below), and in some embodiments for executing stored sequences of heating operation. The processor 102 is operably coupled to the control panel 92 and to the heating elements 82, 84 and the air movement device 86. In addition, in an exemplary embodiment, one or more sensors S for monitoring one or more parameters (such as temperature, pressure, lid configuration, etc.) associated with operation of the heating elements 82, 84 and/or lids 32, 37 may be arranged in communication with the processor 102. In an embodiment, a first temperature sensor extends from a bottom surface 108 of the liner 23 proximate the first heating element 82 and bottom surface of the container 24, and a second temperature sensor is located within the lid 32 proximate the second heating element 84. In such embodiments, the second sensor may be used, such as to monitor temperature for example, when the lid 32 is closed and the sensor S is arranged in fluid communication with the hollow interior 30 of the system 20. The first sensor may be used to monitor temperature in this manner, separately or in conjunction with the second temperature sensor.

In an embodiment, at least one input 94 on the control panel 92 is an on/off button which allows the user to activate or deactivate the control panel 92. When the control panel 92 is deactivated, none of the heating elements 82, 84 are energized. In an exemplary embodiment, the at least one input 94 is operable to select one or more manual modes of operation of at least one of the heating elements 82, 84. Alternatively, or in addition, at least one input 94 is operable to select a stored sequence of operation of at least one heating element 82, 84. In some cases, the stored sequences may be particularly well suited for a given method of food preparation and/or for particular ingredients or types of ingredients. The plurality of stored sequences associated with the at least one input 94 may be stored within a memory accessible by the processor 102. Alternatively, the plurality of stored sequences may be stored remotely from the cooking system 20, and may be accessed by the processor 102, such as via wireless communication for example.

In addition, a user may be able to enter a time associated with operation of the cooking system 20 in a desired manual mode. The time may be entered via the same input, or a separate input as used to select a mode of operation. Further in embodiments where the system 20 is in a mode configured

to perform a stored sequence in response to selection of one of the inputs **94**, the display **96** may indicate a time remaining on the display. Temperature and pressure parameters may also be entered via inputs **94**.

The at least one input **94** may include a distinct start button intended to initiate operation in a desired mode, a distinct stop button to cease all operation, or a stop/start button intended to initiate and cease functions. Alternatively, the cooking system **20** may be operable to automatically start operation after a predetermined time has elapsed once an input has been selected and any necessary information has been provided to the control panel. Alternatively, one or more of the other inputs **94**, such as the knob for example, may be operable, such as by pushing the knob towards the control panel **92**, to start and stop operation of the cooking system **20**, regardless of whether the system **20** is following a stored sequence or is in a manual mode.

The one or more inputs **94** are operable to initiate manual operation of the cooking system **20** in at least a first cooking mode and a second cooking mode. In an embodiment, the first cooking mode employs first heating element **82** to perform conductive cooking operations. Conductive cooking operations may generally be referred to as “wet cooking” operations, such as but not limited to pressure cooking, steam cooking, slow cooking, searing, and sautéing. To create a wet cooking environment the majority of the moisture within the container, i.e. liquid added to the container **24** or moisture released from the food within the container **24**, is retained within the container as the food is cooked. Although during conductive cooking operations a minimal amount of air having moisture entrained therein may be vented from the system, such air is passively removed from the cooking enclosure. Similarly, the second cooking mode employs the second heating element **84** to perform convective heating operations. Convective heating operations may generally be referred to as “dry cooking operations,” which include any cooking mode that creates a “dry cooking environment” within the container **24**, such as but not limited to air frying, broiling, baking/roasting and dehydrating. To create a dry cooking environment, air and moisture are actively exhausted or vented from the cooking enclosure to outside the cooking system **20**, thereby maintaining a minimum level of moisture within the container **24**. Parameters associated with the various exemplary but non-limiting cooking modes are shown at FIG. **19**.

As is noted above, the first cooking mode of the cooking system **20** includes pressure cooking. In such embodiments, the secondary lid **37** is affixed to the container **24** or housing **22** to form a pressure-tight, sealed enclosure with the container **24**. During operation in the pressure cooker mode, the controller **102** initiates operation of the first heating element **82**, causing the temperature and therefore the pressure, within the enclosure formed by the container **24** and the secondary lid **37** to rise. During operation in the pressure cooker mode, the second heating element **84** disposed within the primary lid **32** is typically not energized. In an embodiment, the cooking device **20** may include a sensor **S** configured to monitor the pressure within the enclosure. Upon detection that the pressure is at or exceeds a predetermined threshold, the controller **102** may de-energize the heating element **82** until the pressure within the enclosure has returned to an acceptable level. Alternatively, or in addition, a pressure relief valve **51** (see FIG. **6A**) may be formed in the secondary lid **37**, and may open to reduce the pressure within the enclosure to below the threshold. The pressure relief valve **51** may be configured to open automatically when the pressure is above the threshold, or the valve **51**

may be coupled to the controller **102** and may be operable in response to a signal generated by the controller **102**, for example in response to sensing a pressure above the threshold. In embodiments where the cooking system **20** is operable in a slow cooking mode, but not a pressure cooking mode, the liner **23** of the housing **22** may be formed from a light weight, cost effective material, such as aluminum for example. However, in embodiments where the cooking system **20** is operable in a pressure cooking mode, the liner **23** should be formed from a more rigid material capable of withstanding the pressure build up within the container **24**. As is noted above, the first cooking mode of the cooking system **20** also includes slow cooking, steaming, searing, and sautéing. When the cooking device **20** is operated in one of these non-pressure modes, either the secondary lid **37** may be affixed to the container **24** or housing **22** or the primary lid **32** may simply be closed.

During slow cooking, steaming, searing, and sautéing (or other conductive cooking means that do not involve “pressure cooking”), the controller **102** initiates operation of the first heating element **82**, causing the temperature within the container **24** and at the bottom surface thereof to increase. Upon detection that the temperature of the chamber **30** is equal to or exceeds a predetermined threshold, the controller **102** may de-energize the heating element **82** until the temperature has returned to an acceptable level. Such de-energization or power termination to the heating elements **82** and **84** based on detection of unsafe conditions by temperature or pressure sensors **S** will be discussed in greater detail below.

As previously suggested, the at least one input **94** is also usable to select operation of the cooking device **20** in a second cooking mode that employs convective cooking such as air frying. In an exemplary, non-limiting embodiment, air frying in the system **20** involves the use of various components such as the fan **90**, and a basket **52** and diffuser **40**.

With reference now to FIGS. **8A-D** and **9**, an air diffuser **40** is shown. The diffuser **40** is an optional system component that may benefit air circulation during the air frying mode. The diffuser is positionable anywhere in the hollow interior **30** (though typically near the bottom). In an exemplary, non-limiting embodiment, the diffuser is positioned in contact with a bottom surface **31** of the container **24**, and, as will be discussed in greater detail below, used in conjunction with an insert **52**.

As shown in the Figures, the air diffuser **40** may include a plurality of vanes **42** spaced about a center body **44**. Each of the plurality of vanes **42** is configured to impart swirl to an air flow circulating through the container **24**. In the illustrated, non-limiting embodiment, the air diffuser **40** includes four vanes **42**. However, embodiments where the air diffuser **40** includes one vane, two vanes, three vanes, or more than four vanes are also within the scope of the disclosure. Further, although the vanes **42** are illustrated as being substantially identical and equidistantly spaced about the center body **44**, embodiments where a configuration of one or more of the vanes **42** varies and/or the spacing between adjacent vanes **42** varies are also contemplated herein. In an embodiment, each of the vanes **42** of the air diffuser **40** has a radius of curvature such that the vanes **42** curve generally from the center body **44** of the air diffuser outwardly. In addition, the vanes **42** of the air diffuser **40** extend generally perpendicularly in an upward direction from the bottom surface **31** of the container **24**, and a lower extent of the vanes **42** generally lengthens as the vanes move out from the center body **44** towards the outer edge **46**.

11

However, an air diffuser 40 including one or more vanes having another configuration are also within the scope of the disclosure.

In an exemplary, non-limiting embodiment, the upper surface 48 and the distal ends 46 of the vanes 42 cooperate to define an area 50 within which the insert 52 may be removably mounted. With reference to FIGS. 8A-D and 9, the insert 52 includes a body 54 having a first, open end 56, second, aperture end 58, and at least one sidewall 60 extending between the first end 56 and second end 58 to define a hollow interior or chamber 62 defined by the body 54. The first end 56 is generally open to provide access for positioning one or more food items within the chamber 62. The second end 58 of the body 54 is partially closed to retain one or more food items within the chamber 62. In an exemplary, non-limiting embodiment, the closed second end 58 of the body 54 defines a plurality of apertures 59 (see FIG. 8B) to allow air, heat, and/or steam flowing within/through the interior 33 of the container 24 may pass through the apertures 59 in the end 58 to cook one or more food items within the chamber 62 of the body 54.

When the insert 52 is positioned within the area 50, in contact with the upper surface 48 of the air diffuser 40, and the insert 52 with air diffuser 40 is disposed within the interior 33 of the container 24, the bottom surface 58 of the insert 52 is positioned to be offset from the bottom surface 31 of the container 24. The offset spacing is via presence of the vanes 42 between the surfaces 58 and 31, allowing air moving through the system 20 to flow underneath the insert 52. In an embodiment, a tab 64, best shown in FIG. 8A, protrudes from the upwardly extending portion of each vane 42. As shown, the tabs 64 generally protrude inwardly, towards the center body 44 of the air diffuser 40. The tabs 64 may be sized and contoured to cooperate with a ridge or groove 65 formed in the exterior surface of the insert 52 to retain the insert 52 in position adjacent the air diffuser 40. Of course, embodiments wherein the diffuser 40 is integrally formed with either the insert 52 or bottom surface 31 and/or side surfaces of the container 24 are also contemplated.

Although the body 54 of the inserts 52 illustrated are shown having a single chamber, embodiments where the body 54 includes a plurality of chambers are also contemplated herein. As previously described, the closed second end 58 of the body 54 has a generally porous structure, which may also be formed via mesh or wire for example (see FIG. 10), so that heat and/or steam flowing through the interior 33 of the container 24 may pass through the openings in the porous structure to cook one or more food items within the chamber 62 of the body 54. One or more handles 66 may be associated with the body 54 to allow a user to easily grasp the insert 50. In the illustrated, non-limiting embodiment, the body 54 includes two handles 66 extending from the sidewall 60, or alternatively, integrally formed into the sidewall 60 of the body 54 as openings. However, any suitable configuration of the body 54 and/or handles 66 is within the scope of the disclosure. Such configurations may include removable handles.

In embodiments where the air diffuser 40 and the insert 52 may be integrally formed, as shown in FIG. 10, the insert 52 may additionally include a base 70 having an upper surface 72 and a lower surface (not shown). The base 70 may have a size and/or shape generally complementary to the body 54, and both the base 70 and body 54 may have a similar shape to the interior 33 of the container 24. In the illustrated, non-limiting embodiment, the interior 33, and the insert 52 are both generally cylindrical in shape.

12

The base 70 is generally offset from the second end 58 of the body 54 by a distance. As a result, a gap or clearance 74 defining a fluid flow path is formed between at least a portion of an upper surface 72 of the base 70 and the second end 58 of the body 54. In the illustrated, non-limiting embodiment, the lower surface (not shown) of the base 70 of the insert 52 has a generally planar configuration for directly contacting an adjacent supporting surface of the container 24, such as the bottom surface 31, when the insert 52 is installed therein. In embodiments where the supporting surface of the container 24 does not have a planar configuration, the configuration of the lower surface of the base 70 will be complementary to the supporting surface.

As previously described, in an embodiment, the air diffuser 40 comprising one or more vanes configured to impart swirl to air moving through the clearance 74 towards the second end 58 of the body 54 may be formed in the upper surface 72 of the base 70. In such embodiments, the configuration of the air diffuser 40 may be the same, or alternatively, different than in embodiments where the air diffuser 40 is a separate component. As shown, the vanes 42 of the air diffuser 40 integrally formed with the insert 52 have a radius of curvature such that the vanes 42 curve generally from an outer edge of the base 70 towards a center thereof. In addition, the vanes 42 of the air diffuser 40 extend generally perpendicular to the upper surface 72, and the height of the vanes 42 measured perpendicular to the upper surface 72 increases from the outer edge of the base 70 towards the center. Although the air diffuser 40 is described as being integrally formed with the insert 52, in other embodiments, all or a portion of the air diffuser may alternatively, or in addition, be integrally formed with a portion of the container 24.

Regardless of whether the insert 52 is integrally formed with or coupled to the air diffuser 40, when the insert 52 and air diffuser 40 are arranged within the interior 33 of the container 24, an annulus 76 is formed between an inner surface 78 of the container 24 and the sidewalls 60 of the body 54 (see FIG. 7). Further, in an exemplary non-limiting embodiment the height of the insert 52, when installed within the container 24 with the air diffuser 40, may be generally equal to or less than height of the container 24. In embodiments where the cooking system 20 includes a secondary lid 37, either the primary lid 32 or the secondary lid 37 may be used, i.e. coupled to the upper surface 34 of the housing 22 when the insert 52 is positioned generally within the hollow interior 30 of the system 20 or specifically within the interior 33 of the container 24.

It should be appreciated that the insert 52 may also be received directly in the hollow interior 30 as opposed to within the container 24 within the hollow interior 30. That is, the insert 52 (and diffuser 40) may be disposed in the system without the container 24, and food may be cooked in the insert 52 in accordance with of the second mode, convective cooking functions.

With further reference to second, convective cooking mode functions (particularly air frying modes), the second heating element 84 is configured to heat air as it passes there through via an air movement device 86, such as a fan for example. In embodiments where the insert 52 is arranged within the interior 33 of the container 24, the air movement device 86 draws air from the center of the insert 52, and moves it across the second heating element 84 before forcing the heated air through the annulus 76 between the container 24 and the insert 52 towards the clearance 74 formed between the bottom 58 of the insert and the bottom surface 31 of the container 23 (the arrows in FIG. 7 show

exemplary air flow through the system). This air movement may be facilitated via air guides such as a skirt/air guide **89** that creates a non-sealing air guide for air into the annulus **76**. In the illustrated, non-limiting embodiment of FIGS. **7** and **11**, the air movement device **86** is driven by a motor **88** having a separate cooling mechanism **90** coupled thereto. In an embodiment, a vent **91** is formed in the primary lid for exhausting hot air generated by operation of either the air movement device **86**, the motor **88**, or the separate cooling mechanism **90** to the exterior of the cooking system **20**. However, it should be understood that the second heating element **84** and the air movement device **86** may also be used to circulate air through the enclosure defined between the container **24** and the primary lid **32** when the insert **52** and/or air diffuser **40** are not arranged within the container **24**. As is shown in the exemplary embodiments of the Figures, the at least one second heating element **84** is disposed within the primary lid **32**. In an embodiment, the second heating element **84** has a diameter substantially equal to the diameter of the body **54** of the insert **52**. However, embodiments where the second heating element **84** has a diameter smaller than or greater than the diameter of the body **54** of the insert **52** are also contemplated herein.

When utilizing the second heating element **84** in the air fryer mode, the controller **102** initiates operation of the second heating element **84** and the air movement device **86** to circulate the hot air represented by the arrows in FIG. **7** through the enclosure formed between the container **24** and the lid **32**. During operation in the air fryer mode, the first heating element **82** is generally not energized. However, embodiments where the first heating element **82** is energized are also within the scope of the disclosure.

The air movement device **86** draws air upward through the adjacent heating element **84** and expels the hot air outwardly towards the guide **89** (which, in an exemplary embodiment, actually surrounds the fan **86**). The guide **89** deflects the air downwardly towards the annulus **76** along the sides of the container **24** (again, please see the arrows in FIG. **7**). The air travels down through the annulus **76** (still by actuation of the fan **86**) until it is deflected off the bottom surface **31** of the container **24** and drawn up by the fan **86** into the clearance **74** up towards the diffuser **40** and end **58** of the insert **52** with the aperture pattern **59**. The hot air flows over and between the plurality of vanes **42** of the air diffuser **40**, which impart a rotational motion to the hot air, thereby creating a vortex as the air is drawn through the apertures **59** and into the chamber **62** of the body **54** by the air movement device **86**. After traversing the chamber **62**, the air is drawn back up through the heating element **84** and into the fan **86** for further circulation.

As the air circulates through the chamber **62** in the manner described above, the hot air cooks and forms a crispy outer layer on the food items disposed therein as a result of the Maillard effect. In an embodiment, a liquid, such as oil or fat, is contained within the enclosure, such as adjacent the bottom surface **31** of the container **24**. The liquid may be added to the container **24** prior to operation in the air fry mode, or alternatively, may be produced as a residual material as the hot air passes over the food within the chamber **62**. In embodiments where a liquid is disposed at the bottom of the container **24**, as the air circulates through the interior **30** of the container **24**, a portion of the liquid becomes entrained in the air flow and is heated.

As is best shown in FIG. **3C**, in an exemplary embodiment the lid **32** includes a heater/fan cover **80** that protects a user from the heating element **84** and fan **86**, and protects the heating element **84** and fan **86** from the areas **31**, **33**, **64**

where food is cooked. The cover **80** may be included in embodiments of the cooking system **20** including only a primary lid **32**, or alternatively, in embodiments including both the primary and secondary lids **32**, **37**. In the illustrated, non-limiting embodiment, the cover **80** is formed from a nano ceramic coated and is mounted to the primary lid **32**, such as via one or more fasteners for example. In such embodiments, when the primary lid **32** is in the closed position, the cover **80** is arranged generally above the first open end of the container **24**. The cover **80** has a plurality of openings **81** formed therein to allow hot air circulating within the chamber of the container **24** to pass there through.

In another convection cooking embodiment, the second cooking mode of the cooking system **20** includes a dehydrator mode, such as used to make jerky for example. In such embodiments, the primary lid **32**, is typically affixed to the container **24** or housing **22**, though the secondary lid **32** may also be used. When the cooking device **20** is operated in the dehydration mode, the air diffuser **40** and/or insert **52** may, but need not be, positioned within the interior **30** of the container **24**. During operation in the dehydrator mode, air is configured to circulate through the container **24** in a manner similar to the air fryer mode.

In an embodiment, the air movement device **86** of the cooking system **20** is a variable speed fan operable at a plurality of rotational speeds. In an embodiment, the operational speed of the air movement device **86** may vary based on the cooking mode selected (see the exemplary, non-limiting parameters and speeds set forth in FIG. **19**). For example, the speed of the air movement device **86** during operation in an air fryer mode may be different than the speed of the air movement device during operation in a dehydrator mode. The operational speed of the air movement device **86** may be controlled by the controller **102** in response to one or more inputs **94**, including selection of a cooking mode. However, the controller **102** may also be configured to adjust the operational speed of the air movement device **86**, or alternatively, the power supplied to the one or more heating elements **82**, **84**, to control the temperature and/or pressure within the hollow interior **30** of the container **24**.

The first and second heating elements **82**, **84** are operable independently or in combination to apply one or more predetermined power settings to cook the food products within the container **24** and/or insert **52**. In operation, the heating elements **82**, **84** are capable of cooking the food products independent of the loading of the food products. In other words, the heating elements **82**, **84** are capable of cooking the food products independent of the amount of food products within the container **24**.

In some embodiments, the cooking system **20** is operable in more than two cooking modes. For example, the cooking system **20** may be independently operable in any of a slow cooking mode, a pressure cooking mode, an air fryer mode, and a dehydrator mode. Alternatively, or in addition, the at least one input **94** may be used to select operation of the cooking device **20** in a cooking mode that functions as a combination of two or more cooking modes. In such embodiments, the controller **102** may execute a stored sequence where the first heating mechanism **82** is operated during a first portion of the sequence and the second heating mechanism **84** and air movement device **86** are operated during a second portion of the sequence. For example, in the combination mode, a food item, such as a chicken for example, may be slowly cooked or pressure cooked via operation of the first heating element **82**. Then, the second heating element **84** and the air movement device **86** may be

operated to air fry the chicken to achieve a crispy exterior layer. However, the embodiments described herein are intended as an example only and any sequence of operation combining both the first and second heating elements is contemplated herein. When operated in a combination of two or more cooking modes, such as a pressure cooker and an air fryer, the food need not be removed from the hollow interior 30, or more specifically the container 24, or even more specifically from the chamber 62 of the insert 52 during such a transition.

As is alluded to above, the container 24 may be usable in both the first and second cooking modes. In an exemplary embodiment, convective cooking (first mode), and more specifically air frying is possible in a container (such as container 24) that is deformable for use in a pressure cooking environment (second mode). Containers in which pressure cooking occurs may deform in response to pressure conditions within the pot during cooking. A “domed” or curved shape 100 in a bottom surface 102 (see FIG. 11) of pressure pot such as container 24 may also be employed to handle pressure conditions and the deformity that may result therefrom. Accordingly, since the container 24 may also be used as an air frying chamber, exemplary embodiments of air frying components such as the insert 52 and diffuser 40 may be configured for use in pressure cooking environments. For example, the diffuser 40 may include a curved or sloped bottom surface 104 that conforms to the domed/curved/sloped shape 100 of the bottom surface 102 of the container 24. Indeed, the bottom surface 104 of the diffuser 40 may be curved or sloped to conform to a potentially domed surface of any container (again, such as container 24) used in for wet cooking modes such as but not limited to pressure, steam, slow cooking.

In accordance with the above, the insert 52 may be placed in the container 24 with food to be cooked in the first and second modes consecutively. For example, the insert 52 may be placed in the container 24 and food may be placed within the insert for cooking in a first, conductive modes such as pressure or slow cooking. The system 20 may then be switched into the second, convective mode, and the food still contained in the insert 52 contained in the container 24 can be cooked in accordance with a convection heating function. In an exemplary embodiment involving pressure cooking and air frying, such a process would involve placing food in the insert 52 and placing the insert in the container 24. The secondary lid 37 would be affixed to the system 20 and pressure cooking would/could occur. Once the pressure cooking is complete, the secondary lid 37 would be removed and replaced with a closed primary lid 32. The food may then be air fried, with all the cooking occurring within the insert 52 disposed within the container 24. Of course, while food would most commonly be cooked first in a conductive/wet mode followed by a convective/dry mode, the system 20 is certainly capable of cooking food first in a convective/dry mode followed by a conductive/wet mode.

In some embodiments, it also may be useful to be able to detect presence of the container 24 in the system 20 so operation of the various cooking modes can occur effectively and safely. For example, as shown in FIG. 13 a lower surface 108 of the hollow interior 30 may support a container detection sensor 110 (such as but not limited to a depression or plunger sensor). One or more depression sensors used for container detection and disposed along the vertical extents (i.e. sides) of the liner 23, as well as one or more optical sensors anywhere in the hollow interior 30, are also contemplated.

Referring now to FIGS. 14-18, a reversible insert 112 receivable in any or all of the hollow interior 30, container 24, and insert 52. In the non-limiting exemplary embodiment shown in the Figures, the insert 112 is received in the container 24. The insert includes a food supporting body or grate 114 with a first body surface 116 and an opposing second body surface 118. The insert 112 also includes first surface legs 120 and second surface legs 122.

The insert 112 is reversible into two different food holding/support configurations via a 180 degree rotation. The first, greater clearance configuration 124 is best shown in FIGS. 14 and 15. The second, lesser clearance configuration 126 is best shown in FIGS. 16 and 17. As shown, the second surface legs 122 have a greater length than the first surface legs 120. This allows the grate 114 to be positioned a relatively greater distance from a surface on which the insert 112 rests in the first configuration 124 than the second configuration 126. As shown in FIG. 15, in an exemplary embodiment the insert 112 rests on the lower surface of the container 24. The first, greater clearance configuration positions the grate 114 (and any food thereon) a relatively greater distance from the first heater 82 than in the second configuration. Such positioning of the food may be beneficial in convective heating modes for a few reasons.

First, when in a broiling mode, the first configuration of the insert 112 positions the food close enough to the second heater 84 to achieve good broiling benefits. In an exemplary embodiment, in the first configuration 124 the grate 114 of the insert 112 is positionable a vertical distance from the second heating element 84 (when the lid 32 is closed) of between 1.75 and 2 inches. These distance (and distances in between and around these distances) allow for enough food space and proximity to the heat source to impart good broiling results, particularly at or around 450 degrees F. Second, when for example in the baking/roasting mode, the large clearance between the grate 114 and lower surface of the container 24 allows food to be cooked at two different levels within the container 24, which may offer various convenience and flavor benefits.

As is additionally shown, the first surface legs 120 have a lesser length than the second surface legs 122. This allows the grate 114 to be positioned a relatively lesser distance from a surface it rests on in the second configuration 126 than in the first configuration 124. As shown in FIG. 17, in an exemplary embodiment the insert 112 again rests on the lower surface of the container 24. The second, lesser clearance configuration positions the grate 114 (and any food thereon) a relatively lesser distance from the first heater 82 than in the first configuration 124. Such positioning of the food may be beneficial in conductive heating modes. For example, in the steam cooking mode, the legs 120 provide just enough clearance to position the grate 114 and food above any water and comfortably in a steam zone.

It should be noted that when in the configuration where they are not supporting the grate 114, the legs 120, 122 act as handles for the insert 112. Further, and as shown in FIG. 18, the legs 122 are rotatable from an orthogonal orientation with said food support body to a parallel orientation (the Figure actually shows the legs 122 rotated beyond parallel) with the plane of the grate 114. This allows for easier storage of the insert 112.

As mentioned above, and with reference again to FIG. 1A, the system 20 includes a spine 39. In an exemplary embodiment, the spine 39 houses a power/high voltage circuit board under (PCBA in the Figures) the hinge. A UI circuit board is behind the UI (not shown). Referring to FIGS. 20 and 21, the system 20 also includes a first thermal cut off (Bottom or

Pressure or PC TCO/TCE) and a second thermal cut off (Upper or AF TCO/TCE). In an exemplary, non-limiting embodiment, the first thermal cut off is proximate the first heating element **82**, and is triggered to terminate power thereto in response to a failure of the first heating element. Similarly, the second thermal cut off is proximate the second heating element **84**, and is triggered to terminate power thereto in response to a failure of the second heating element **84**. It should be noted, however, that the first thermal cut off could get hot enough to trigger a system shut down in response to overheating resulting from the second heating element **84**, and the second thermal cut off could get hot enough to trigger a system shut down in response to overheating resulting from the first heating element **82**.

In addition, in an exemplary embodiment, a failure in the first thermal cut off proximate the first heating element **82** will trigger the power circuit board PCBA to terminate power to the system **20** including the first heating element **82**, the second heating element **84**, and both the power and UI circuit boards. Similarly, a failure in the second thermal cut off proximate the second heating element **84** will trigger the power PCBA to terminate power to the system **20** including the second heating element **84**, the first heating element **82**, and both the power and UI circuit boards. The system **20** is thereby wired in such a way in that if any thermal cut off is triggered, power is cut to both heating elements **82**, **84**, rendering the system **20** inoperable. For example, if the first thermal cut off is tripped/triggered during a first mode or wet cooking function, hardware cuts power to both heating elements **82**, **84**, thereby prohibiting the user from using any cooking function. This circuitry, as shown in FIG. **20**, creates a safer system for a user. In addition or alternatively, the controller **102** may also run software that employs a simple logic check that terminates power to both heating elements **82**, **84** if either of the first or second thermal cut offs are tripped/triggered.

Failures such as but not limited to excessive temperature or excessive pressure (as detected by sensors **S**) may result in the tripping/triggering the first and/or second thermal cut offs discussed above. Software algorithms that correlate temperature to pressure and vice versus may also be employed by the controller **102** to detect dangerous conditions that may trip/trigger the first and/or second thermal cut offs.

With reference now to FIGS. **2**, **3A**, **3B**, and **22A-D**, a safety system employing lid detection sensors will now be discussed. A first lid detection sensor **140** is disposed proximate the hinge **38** (and is represented schematically at **140** in FIG. **3A**). In an exemplary embodiment, the first sensor **140** is an actuating switch or micro switch that detects whether the primary lid **32** is open or closed. In an exemplary embodiment employing the actuating switch, a power connection to the lid heating element **84** is actually broken when the lid **32** is open. As such the lid heating element **84** (and fan **86**) can only receive power to actuate convection cooking modes when the lid **32** is closed. In addition or alternatively, the controller **102** may also run software that employs a simple logic check that terminates power to the heating element **84** when the lid **32** is open.

As shown in FIGS. **22A-D**, a second lid detection system **142** is shown, and includes a Reed switch/sensor **144** at a relative rear of the housing **22** and a magnet **146** disposed in a corresponding section of the lid **37**. As shown in the Figures, a dropped on lid **37** places the magnet **146** within range of the Reed switch **144**. When the lid **37** is in this dropped on configuration (**22A**), the controller **102** may employ a simple logic check that detects the Reed switch's

activated condition and terminates power to the whole system **20** or at least the heating elements **82**, **84**. When the lid **37** is partially engaged on the housing (up to 85% rotation onto a housing bayonet in the exemplary embodiment shown in FIG. **22B**), the controller **102** may again employ a simple logic check that detects the Reed switch's activated condition and terminates power to the whole system **20** or at least the heating elements **82**, **84**. When the lid **37** is fully engaged on the housing **22** (greater than 85% rotated onto a housing bayonet in the exemplary embodiment shown in FIG. **22C**), the controller **102** may employ a simple logic check that detects the Reed switch's deactivated condition and allow power to flow normally to the system **20**. Similarly, when the lid **37** is not present at all, the controller **102** may employ a simple logic check that detects the Reed switch's deactivated condition and allow power to flow normally to the system **20**. However, the controller **102** may also and again employ a simple logic check that detects a closed condition of the first lid **32**, and prevent power from flowing to the first heating element **82**.

Indeed, when a closed condition of the first lid **32** is detected using the above referenced sensor **140**, the controller **102** may deactivate at least the pressure cooking input **94** on the display **92**, and in an exemplary embodiment all inputs **94** for the conduction/wet cooking functions including the pressure cooking input **94**, slow cooking input **94**, steam input **94**, and sear/sauté input **94**. Similarly, when a closed condition of the second lid **37** (FIG. **22C**) is detected using the Reed switch **144**, the controller **102** may deactivate all inputs **94** for the convective/dry cooking functions including the air fry/crisp mode input **94**, bake/roast input **94**, broil input **94**, and dehydrate input **94**. In both cases, deactivation of the inputs **94** may include non-function of the inputs **94** and a termination of back lighting to the inputs **94**.

The cooking system **20** illustrated and described herein provides an enhanced user experience by combining the functionality of several conventional household products into a single user-friendly device.

All references, including publications, patent applications, and patents cited herein are hereby incorporated by reference to the same extent as if each reference were individually and specifically indicated to be incorporated by reference and were set forth in its entirety herein.

The use of the terms "a" and "an" and "the" and similar referents in the context of describing the disclosure (especially in the context of the following claims) is to be construed to cover both the singular and the plural, unless otherwise indicated herein or clearly contradicted by context. The terms "comprising," "having," "including," and "containing" are to be construed as open-ended terms (i.e., meaning "including, but not limited to,") unless otherwise noted. Recitation of ranges of values herein are merely intended to serve as a shorthand method of referring individually to each separate value falling within the range, unless otherwise indicated herein, and each separate value is incorporated into the specification as if it were individually recited herein. All methods described herein can be performed in any suitable order unless otherwise indicated herein or otherwise clearly contradicted by context. The use of any and all examples, or exemplary language (e.g., "such as") provided herein, is intended merely to better illuminate the disclosure and does not pose a limitation on the scope of the disclosure unless otherwise claimed. No language in the specification should be construed as indicating any non-claimed element as essential to the practice of the disclosure.

Exemplary embodiments of this disclosure are described herein, including the best mode known to the inventors for carrying out the disclosure. Variations of those embodiments may become apparent to those of ordinary skill in the art upon reading the foregoing description. The inventors expect skilled artisans to employ such variations as appropriate, and the inventors intend for the disclosure to be practiced otherwise than as specifically described herein. Accordingly, this disclosure includes all modifications and equivalents of the subject matter recited in the claims appended hereto as permitted by applicable law. Moreover, any combination of the above-described elements in all possible variations thereof is encompassed by the disclosure unless otherwise indicated herein or otherwise clearly contradicted by context.

What is claimed is:

1. A cooking system for cooking food, the system comprising:

a housing defining a hollow chamber configured to receive a food container, said housing having an upper portion defining an opening to said hollow chamber;
a lid attachable about said upper portion of said housing and configured to extend across said opening to said hollow chamber;

at least one heating element associated with at least one of said housing and said lid;

wherein said cooking system is operable in a plurality of modes including a pressure cooking mode and a convective cooking mode, wherein in said pressure cooking mode the cooking system is operable as a pressure cooker and in said convective cooking mode the cooking system is operable as a convection cooker; and

wherein in said pressure mode, the cooking system reaches a pressure of at least 40 kPa.

2. The cooking system of claim 1, further including a food container that is receivable within said hollow chamber, said food container having a base and an open end, and wherein said lid is attachable to said upper portion of said housing and sealable about said open end of said food container when said food container is received within said hollow chamber.

3. The cooking system of claim 2, wherein said cooking system is operable in said pressure cooking mode when said lid is attached to said upper portion of said housing and seals said open end of said food container.

4. The cooking system of claim 2, further including a second lid that is adapted to abut said upper portion of said housing and cover said lid when said lid is attached to said upper portion of said housing and seals said open end of said food container.

5. The cooking device of claim 2, wherein said food container includes a food support surface, and food is receivable in said food container in contact with said food support surface in both said pressure cooking mode and said convective cooking mode.

6. The cooking system of claim 2, wherein the cooking system is operable in either said pressure cooking mode and said convective cooking mode without having to remove said food container from the hollow chamber.

7. The cooking system of claim 2, further comprising an insert for supporting a food item in said hollow chamber.

8. The cooking system of claim 7, wherein said insert is positionable within said food container to form an annulus between an inner wall of said food container and an outer wall of said insert.

9. The cooking system of claim 7, wherein said insert further comprises a base and an open end, said base including a plurality of apertures that allow fluid to flow through said base.

10. The cooking system of claim 9, further including a diffuser disposed beneath said base, said diffuser including at least one vane configured to impart rotation to fluid circulating through said plurality of apertures during said convective cooking mode.

11. The cooking system of claim 10, further including a fan and at least one heating element disposed at or above said opening to said hollow chamber, said fan being positioned to move heated air relatively downward through said annulus, relatively horizontally across a lower surface of said food container, and relatively upward through said diffuser and said plurality of apertures of said base when said insert is positioned in said food container and said food container is received within said hollow chamber.

12. The cooking system of claim 11, wherein said fan is positioned to draw air relatively upward through said insert and through said at least one heating element in said convective cooking mode.

13. The cooking system of claim 10, wherein said diffuser is configured to create a vortex of air circulating through said insert.

14. The cooking system of claim 13, wherein said food container includes an upward facing lower surface that is curved upward in a direction of an upper opening of said food container, and said diffuser includes downward facing lower surface that is curved or sloped to conform to said upward facing lower surface of said food container.

15. The cooking system of claim 2, wherein said housing is configured to surround said food container around an entirety of at least a portion thereof when said food container is received within said hollow chamber.

16. The cooking system of claim 1, wherein said upper portion of said housing is configured with a bayonet locking feature and said lid is configured with a compatible bayonet locking feature.

17. The cooking system of claim 1, further including a second lid moveably attached to said housing, said second lid moveable between a first position that covers said opening to said hollow chamber and a second position where said second lid does not cover said opening to said hollow chamber, wherein said second lid includes a heating element.

18. The cooking system of claim 17, wherein said cooking system is operable in said convective cooking mode when said second lid is in said first position.

19. The cooking system of claim 17, wherein said cooking system is operable in either of said pressure cooking mode and said convective cooking mode when said second lid is in said first position.

20. The cooking system of claim 17, wherein said cooking system is operable in said pressure cooking mode when said second lid is in said first position.

21. The cooking system of claim 17, wherein said at least one heating element is a first heating element and a second heating element, said first heating element being disposed at or below a lower extent of said hollow chamber, and said second heating element being disposed at or above said opening to said hollow chamber.

22. The cooking system of claim 21, wherein said second heating element is disposed in said second lid.

21

23. The cooking system of claim **21**, wherein said second heating element is disposed in said lid, and wherein a fan is also disposed in said lid at or above said opening to said hollow chamber.

24. The cooking system of claim **21**, wherein said second lid is coupled to said housing when said cooking system is in said pressure cooking mode.

25. The cooking system of claim **1**, further including a diffuser disposed in said hollow chamber, said diffuser including at least one vane configured to impart rotation to fluid circulating through said hollow chamber.

26. The cooking system of claim **1**, wherein said lid abuts said housing about an entirety of said upper surface thereof when said lid is in said closed position.

27. A cooking system for cooking food, the system comprising:

22

a housing defining a hollow chamber configured to receive a food container, said housing having an upper portion defining an opening to said hollow chamber; a first lid and a second lid, said first lid and said second lid configured to cover said upper portion of said housing and said opening to said hollow chamber in a closed position; at least one heating element associated with at least one of said housing and said first lid; wherein said cooking system is operable in a plurality of modes including a pressure cooking mode and a convective cooking mode, wherein in said pressure cooking mode the cooking system is operable as a pressure cooker and in said convective cooking mode the cooking system is operable as a convection cooker, and wherein said second lid is affixable to said housing in a locked arrangement during said pressure mode.

* * * * *