

US011306783B2

(12) **United States Patent**
Capoldi

(10) **Patent No.:** **US 11,306,783 B2**
(45) **Date of Patent:** **Apr. 19, 2022**

(54) **BEARING WITH DISTANCE SENSORS AND TAPERED GROOVE**

6,113,276 A 9/2000 Bourgeois-Jacquet
6,119,504 A * 9/2000 Claus F16C 19/16
116/208

(71) Applicant: **Aktiebolaget SKF**, Gothenburg (SE)

10,041,545 B2 8/2018 Nicolas et al.
2006/0245677 A1 * 11/2006 Kenworthy F16C 19/522
384/448

(72) Inventor: **Daniel Capoldi**, Mettray (FR)

2008/0008410 A1 * 1/2008 Adachi G01P 3/443
384/448

(73) Assignee: **Aktiebolaget SKF**, Gothenburg (SE)

2009/0256551 A1 10/2009 Ito et al.

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **17/099,043**

CA 2884602 A1 * 9/2015 F16C 41/004
DE 202012011902 U1 * 1/2013 G01B 21/16
DE 102015219167 A1 * 4/2017 F16C 41/007
EP 0814338 B1 * 8/2003 F16C 41/007
EP 1653079 A2 * 5/2006 G01P 3/443
EP 1528356 B1 * 1/2015 G01M 13/04
FR 3041396 A1 3/2017

(22) Filed: **Nov. 16, 2020**

(65) **Prior Publication Data**

US 2021/0148409 A1 May 20, 2021

(Continued)

(30) **Foreign Application Priority Data**

Nov. 19, 2019 (DE) 102019217788.3

Primary Examiner — Phillip A Johnson

(51) **Int. Cl.**
F16C 41/00 (2006.01)

(74) *Attorney, Agent, or Firm* — Garcia-Zamor

(52) **U.S. Cl.**
CPC **F16C 41/007** (2013.01); **F16C 2233/00**
(2013.01)

Intellectual Property Law; Ruy Garcia-Zamor; Bryan Peckjian

(58) **Field of Classification Search**
CPC F16C 17/24; F16C 19/381; F16C 19/52;
F16C 41/007; F16C 43/00; F16C 33/586;
F16C 2300/14; F16C 2352/00; F16C
33/7886; G01M 13/04
USPC 384/448, 455, 565
See application file for complete search history.

(57) **ABSTRACT**


A bearing provides a first ring and a second ring capable of rotating concentrically relative to one another. At least one tapered groove is formed on a first axial cylindrical surface of the second ring and oriented towards the first ring. The bearing further provides at least one first distance sensor mounted on the first ring and facing a tapered wall of the tapered groove of the second ring that is inclined with respect to the axis of the bearing, a longitudinal axis of the first distance sensor being perpendicular to the axis, and at least one second distance sensor mounted on the first ring and distinct from the first distance sensor. The second distance sensor radially faces a second axial cylindrical surface of the second ring.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,798,299 A * 1/1989 Bayer B66C 23/84
212/282
5,971,619 A * 10/1999 Bourgeois-Jacquet
F16C 19/166
384/448

14 Claims, 2 Drawing Sheets



(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO WO-9931500 A1 * 6/1999 G01N 29/043
WO 2010028630 A1 3/2010

* cited by examiner

FIG. 1





FIG. 2



BEARING WITH DISTANCE SENSORS AND TAPERED GROOVE

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims priority to German Patent Application no. 102019217788.3, filed Nov. 19, 2019, the contents of which is fully incorporated herein by reference.

TECHNICAL FIELD OF THE INVENTION

The present invention relates to the field of bearings. The invention notably relates to the field of large-diameter rolling bearings that can accommodate axial and radial loads, and having an inner ring and an outer ring arranged concentrically about an axis of rotation running in an axial direction.

BACKGROUND OF THE INVENTION

Such large-diameter rolling bearings may be used for example in a tunnel boring machine, in a mining extraction machine or in a wind turbine.

A large-diameter rolling bearing comprises two concentric inner and outer rings, and at least two rows of rolling elements, such as rollers, arranged between the rings. Such rolling bearings are generally loaded both axially and radially, often with relatively large loads. In this case, reference is made to an orientation roller bearing or slewing roller bearing.

As a result of heavy loads, parts of the rolling bearing, more particularly raceways of the rolling elements, wear out. The wear of the rings and rolling elements leads to a significant increase of the initial bearing clearance. The wear exceeding a certain value can lead to a dramatic bearing failure.

Measuring the wear of the bearing through the clearance increase causing relative axial and radial displacement of the rings helps to predict bearing's residual life.

Such unwanted movements affect to proper functioning of the bearing and the application, with the risk that the bearing rings come in contact and collide. Other elements attached to the bearing rings may also collide.

It is common to replace the bearings when they are worn out. Such maintenance interventions are expensive, especially because of the downtime need for the machines or facilities. It is therefore desirable that such maintenance interventions are timely performed before any contact between the bearing rings, but not too early too.

In order to monitor the bearing condition during its service life, the rolling bearing disclosed in patent application FR-A1-3 041 396 comprises an annular magnetic target fixed to the inner ring, and a sensor mounted on the outer ring and facing the magnetic target. Accordingly, axial and angular relative movements between the inner and outer rings can be detected.

However, this requires the installation of the annular magnetic target on the inner ring that can be several meters diameters.

Besides, with the use of such magnetic target, measurement of the axial displacement between the inner and outer rings is affected by the radial one. As a matter of fact, when measuring axial displacement of a magnetic target, the airgap between target and sensor varies with the radial relative movement between the rings making measure less accurate or even impossible.

One aim of the present invention is to overcome these drawbacks.

SUMMARY OF THE INVENTION

The invention relates to a bearing comprising a first ring and a second ring capable of rotating concentrically relative to one another.

According to a general feature, at least one tapered groove is formed on a first axial cylindrical surface of the second ring and oriented towards the first ring.

According to another general feature, the bearing further comprises at least one first distance sensor mounted on the first ring and facing a tapered wall of the tapered groove of the second ring which is inclined with respect to the axis of the bearing. A longitudinal axis of the first distance sensor is perpendicular to the axis.

The bearing also comprises at least one second distance sensor mounted on the first ring and distinct from the first distance sensor. The second distance sensor radially faces a second axial cylindrical surface of the second ring.

Thanks to the invention, an axial relative displacement between the rings can be accurately detected. As a matter of fact, axial position of the tapered groove formed on the second ring relative to the first ring can be calculated from the total displacement detected by the first distance sensor and the pure radial displacement detected by the second distance sensor.

Consequently, the radial clearance of the bearing can also be measured at the same time with the second distance sensor.

Otherwise, there is no need to mount an annular magnetic target on one of the rings. The groove may be easily machined on the associated ring.

The tapered wall of the tapered groove may be a tapered bottom of the groove or any other tapered portion of the groove.

Preferably, the groove is annular. Thus, axial relative displacements between the rings can be detected regardless the rotational position of the rings.

Advantageously, the bearing further comprises a control unit connected to the first and second distance sensors and adapted to calculate the value of a relative axial displacement Da between the first and second rings on the basis of the formula:

$$Da = \left(\frac{\Delta M - Dr}{\sin \alpha} \right),$$

where

ΔM is the value of the differential measurement of the first distance sensor on the tapered wall of the second ring,

Dr is the value of a relative radial displacement between the first and second rings detected by the second distance sensor, and

α is the value of the angle formed between the tapered wall of the tapered groove and the first axial cylindrical surface of the second ring in a radial plane of the bearing.

The control unit may be located remote from the components of the bearing. Alternatively, the control unit could be mounted on one of the components of the bearing, for example the first or second ring.

Advantageously, the first ring comprises at least a first through-hole inside which the first distance sensor is at least partly disposed, and a second through-hole inside which the

3

second distance sensor is at least partly disposed. Each through-hole of the first ring may extend radially from an axial cylindrical surface located radially on the side opposite to the second ring, and opens on an opposite axial cylindrical surface of the first ring radially facing the second ring.

Accordingly, each of the first and second sensor is inserted into the associated through-hole and arranged in its final position in an easy way. The first ring may further comprise first and second plugs sealing respectively the first and second through-holes.

In one embodiment, the first axial cylindrical surface and the second axial cylindrical surface of the second ring are radially offset. Therefore, in this case, the first and second axial cylindrical surface are distinct from each other. Alternatively, the first and second axial cylindrical surface may be the same cylindrical surface.

In one embodiment, the first and second distance sensors are spaced apart from one another in the circumferential direction.

In one embodiment, the bearing further comprises at least one row of rolling elements arranged between raceways provided on the first and second rings.

The bearing further may comprise first and second seals disposed between the first and second rings and delimiting together a closed rolling space inside which the row of rolling elements and the first and second distance sensors are housed.

In one embodiment, the bearing may further comprise at least one additional seal located inside the closed rolling space and delimiting together with one of the first and second seals a closed detection space inside which opens the tapered groove.

In one embodiment, the bearing comprises at least one row of axial rolling elements arranged between radial raceways provided on the rings, and at least one row of radial rolling elements arranged between axial raceways provided on the rings, the second ring comprising a protruding nose engaged into an annular groove of the first ring and provided with the second axial cylindrical surface, the axial raceway of the second ring being formed onto the second axial cylindrical surface.

The terms "axial rolling elements" is understood to mean rolling elements adapted to accommodate axial loads whereas the terms "radial rolling elements" is understood to mean rolling elements adapted to accommodate radial loads.

The nose of the second ring may protrude radially from the first axial cylindrical surface of the second ring from which the tapered groove is formed. The nose of the second ring may be further provided with two opposite radial flanks delimiting axially the axial cylindrical surface, one of the radial flanks delimiting at least partly the radial raceway of the second ring.

In one embodiment, the bearing comprises at least two rows of axial rolling elements each arranged between radial raceways provided on the rings, the two rows of axial rolling elements being disposed axially on each side of the nose of the second ring.

In one embodiment, the first and/or the second distance sensors may be non-contact measurement sensors, i.e. proximity sensors, for example inductive sensors, ultrasonic sensors, or optical sensors.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention and its advantages will be better understood by studying the detailed description of a specific

4

embodiment given by way of a non-limiting example and illustrated by the appended drawings on which:

FIG. 1 is a partial cross-section of a rolling bearing according to an example of the invention, and

FIG. 2 is a detail view of FIG. 1 illustrating schematically an axial displacement of one ring of the bearing relative to another ring.

DETAILED DESCRIPTION OF THE INVENTION

The rolling bearing as illustrated on FIG. 1 is a large-diameter rolling bearing comprising a first ring 10 and a second ring 12. In the illustrated example, the first ring 10 is the outer ring whereas the second ring 12 is the inner ring. The rolling bearing may for example be used in a tunnel boring machine, a wind turbine or any other applications using a large diameter rolling bearing.

The outer and inner rings 10, 12 are concentric and extend axially along the bearing rotation axis X-X' which runs in an axial direction. The rings 10, 12 are of the solid type.

The outer ring 10 is formed as a split ring and comprises a first ring 14 and a second ring 16 stacked one relative to the other in the axial direction. Each of the first and second rings 14, 16 of the outer ring is provided with a plurality of aligned through-holes (not shown) in order to be joined by fitting bolts.

In the illustrated example, the rolling bearing comprises two rows of axial rollers 18, 20 which are arranged between the outer and inner rings 10, 12 in order to form an axial thrust, and a row of radial rollers 22 which are arranged between the rings to form a radial thrust.

As will be described later, the rolling bearing also comprises first and second distance sensors 24, 25 for detecting an axial relative displacement between the outer and inner rings 10, 12. In the illustrated example, the sensors 24, 25 are mounted on the outer ring 10. Each of the sensors 24, 25 measures radial distances to the inner ring 12. "A radial distance to the inner ring 12" is understood to mean a distance to the inner ring 12 with respect to the radial direction, the radial direction being perpendicular to the axis X-X' of the bearing.

The rollers 18, 20, 22 of one row are identical to one another. Each roller 18, 20, 22 comprises a cylindrical outer rolling surface and two opposite frontal end surfaces delimiting the outer rolling surface. The axis of rotation of each roller 22 is parallel to the axis X-X' of the bearing and perpendicular to the axes of each of the rollers 18, 20. In the illustrated example, the axial length of the rollers 18 is larger than the one of the rollers 20. Alternatively, the axial length of the rollers 18 may be smaller than, or may be equal to, the one of the rollers 20.

The rollers 18 are arranged axially between annular radial raceways 26, 28 respectively formed on the inner and outer rings 12, 10. Each radial raceway 26, 28 has in cross section a straight internal profile in contact with the rolling surfaces of the rollers 18. The raceways 26, 28 face each other in the axial direction.

The rollers 20 are arranged axially between annular radial raceways 30, 32 respectively formed on the inner and outer rings 12, 10. Each radial raceway 30, 32 has in cross section a straight internal profile in contact with the rolling surfaces of the rollers 20. The raceways 30, 32 axially face each other. The rows of rollers 18, 20 are spaced apart from each other in the axial direction.

The rollers 22 are arranged radially between annular axial raceways 34, 36 respectively formed on the inner and outer

5

rings 12, 10. Each axial raceway 34, 36 has in cross section a straight internal profile in contact with the rolling surfaces of the rollers 22. The raceways 34, 36 face each other in the radial direction. The row of rollers 22 is radially offset outwards with respect to the rows of rollers 18, 20. The row of rollers 22 is axially located between the rows of rollers 18, 20.

The outer ring 10 comprises an annular groove 38 opening in a radial direction inwardly towards the inner ring 12. The outer ring 10 comprises an inner stepped cylindrical surface or bore 10a from which the groove 38 is formed. The outer ring 10 also comprises an outer cylindrical surface 10b which is radially opposite to the bore 10a. The outer ring 10 further comprises two opposite radial frontal surfaces 10c, 10d which axially delimit the bore 10a and the outer surface 10b of the ring.

The inner ring 12 comprises an annular protruding nose 40 engaging into the annular groove 38 of the outer ring. The nose 40 extends radially outwards.

The inner ring 12 comprises an inner cylindrical bore 12a and a stepped outer cylindrical surface 12b which is radially opposite to the bore 12a. In the illustrated example, the bore 12a of the inner ring is provided with a gear teeth (not referenced). The inner ring 12 further comprises two opposite radial frontal surfaces 12c, 12d which axially delimit the bore 12a and the outer cylindrical surface 12b. The protruding nose 40 protrudes radially from the outer cylindrical surface 12b.

The rows of rollers 18, 20 are arranged axially between the nose 40 of the inner ring and the groove 38 of the outer ring. The rows of rollers 18, 20 are disposed on each side of the nose 40 of the inner ring. The radial raceway 26 is located on the nose 40 and on a radial portion of the outer stepped cylindrical surface 12b of the inner ring. Alternatively, the radial raceway 26 may be completely located on the nose 40. The radial raceway 30 is located on the nose 40. The radial raceways 28, 32 are located on the groove 38 of the outer ring.

More precisely, a first radial flank of the nose 40 partly delimits the radial raceway 26 for the rollers 18. A first radial flank of the groove 38, which axially faces the first radial flank of the nose 40, delimits the radial raceway 28 for the rollers 18. A second flank of the nose 40 and a facing second flank of the groove 38 respectively delimit the radial raceways 30, 32 for the rollers 20. The opposite first and second flanks of the nose 40 delimit axially the nose. Similarly, the opposite first and second flanks of the groove 38 delimit axially the groove. Each of the first and second flanks of the nose 40 extends radially the outer cylindrical surface 12b of the inner ring.

The row of rollers 22 is arranged radially between the nose 40 of the inner ring and the groove 38 of the outer ring. The axial raceways 34, 36 are respectively located on the nose 40 and the groove 38. An outer cylindrical surface of the nose 40 delimits the axial raceway 34. The outer cylindrical surface of the nose 40 and the outer cylindrical surface 12b are radially offset. As a result, the axial raceway 34 and the outer cylindrical surface 12b are also radially offset. The outer cylindrical surface of the nose 40 extends axially between the opposite radial flanks of the nose.

An axial bottom of the groove 38 delimits the axial raceway 36. In the illustrated example, an annular slot 41 is formed in the bottom of the groove 38 and delimits the axial raceway 36. The axial raceway 36 radially faces the outer cylindrical surface of the nose 40 onto which is formed the axial raceway 34.

6

In the illustrated example, the inner ring 12 is made in one part. Alternatively, the inner ring 12 may be divided in the axial direction in at least two separate parts secured together. In another variant, the nose 40 may be made separately from the main part of the inner ring.

As previously mentioned, the outer ring 10 is divided in the axial direction in two separate parts, the first ring 14 and the second ring 16. The first and second rings 14, 16 delimit together the groove 38. The radial raceway 28 is located on the first ring 14 and the radial raceway 32 is located on the second ring 16 of the outer ring.

The rolling bearing further comprises on each side an annular seal 42, 44 mounted on the inner ring 12 and provided to close the radial space that exists between the rings 10, 12. This radial space is defined between the bore 10a of the outer ring, and the outer cylindrical surface 12b and the outer surface of the nose 40 of the inner ring.

A closed space 46 is defined between the inner and outer ring 12, 14 and the seals 42, 44 in which the rows of rolling elements 18, 20 and 22, and the first and second distance sensors 24, 25 are housed.

Each seal 42, 44 is mounted into a groove (not referenced) formed on the outer cylindrical surface 12b of the inner ring and comes into contact with the outer ring 10. The seal 42 comes into contact with the radial frontal surface 10c of the outer ring. The seal 44 comes into contact with the bore 10a of the outer ring axially near the row of rollers 18. Alternatively, it could be possible to provide a reversed arrangement for at least one of the seals 42, 44 with the seal mounted on the outer ring 10 and coming into friction contact with the inner ring 12.

As previously mentioned, the first and second distance sensors 24, 25 are provided to detect an axial relative displacement between the outer and inner rings 10, 12. To this end, an annular tapered groove 50 is also formed on the inner ring 12. In the illustrated example, the groove 50 is formed on the outer cylindrical surface 12b of the inner ring.

The groove 50 extends radially inwards from the outer cylindrical surface 12b of the inner ring. The groove 50 comprises an annular tapered portion or wall 50a extending obliquely inwards. The tapered wall 50a has a frustoconical shape. The tapered wall 50a is inclined with respect to the axis X-X' of the rolling bearing. In other words, the tapered wall 50a is formed oblique to the axis X-X'. The tapered wall 50a is inclined with respect to the axial cylindrical surface 12b of the inner ring. In a radial plane of the rolling bearing as shown on FIG. 1, an angle α is formed between the tapered wall 50a of the groove and the axial cylindrical surface 12b. For example, the value of the angle α may be preferably comprised between 15° and 30°.

In the illustrated example, the tapered wall 50a extends the outer cylindrical surface 12b of the inner ring. Alternatively, the groove may be provided with an annular radial wall extending radially inwards the outer cylindrical surface 12b and from which extends the tapered wall 50a.

The groove 50 also comprises an annular side wall 50b connected to the outer cylindrical surface 12b of the inner ring. The side wall 50b extends radially. Alternatively, the side wall 50b may extend obliquely outwards. The side wall 50b is connected to the tapered wall 50a. Alternatively, the groove may be provided with a cylindrical bottom interconnecting the tapered wall 50a and the side wall 50b.

The first distance sensor 24 radially faces the groove 50 of the inner ring. The sensor 24 faces the tapered wall 50a of the groove. The sensor 24 measures radial distances to the tapered wall 50a of the groove.

The outer ring **14** is provided with a first radial through-hole **52** inside which the first distance sensor **24** is located. The through-hole **52** extends from the outer surface **10b** of the outer ring and opens on the bore **10a**. The through-hole **52** radially faces the groove **50** of the inner ring.

In the illustrated example, the sensor **24** is mounted into the through-hole **52** and protrudes radially into the radial space provided between the outer and inner rings **10**, **12** and into the groove **50** of the inner ring. The sensor **24** remains spaced apart from the tapered wall **50a** of the groove. Alternatively, the first sensor **24** may be entirely located inside the through-hole **52**. Preferably, the shape of the through-hole **52** is complementary to that of the sensor **24**.

The outer ring **10** further comprises a first plug **54** which closes and seals the through-hole **52**. The plug **54** is located radially into the through-hole **52**. The plug **54** is secured inside the through-hole **52** by any appropriate means, for example by force-fitting. The plug **54** is flush with the outer cylindrical surface **10b** of the outer ring.

The sensor **24** comprises a sensor body **56** mounted inside the through-hole **52** of the outer ring. The sensor body **56** is secured inside the through-hole **52** by any appropriate means, for example by force-fitting. The sensor body **56** radially faces the groove **50** of the inner ring. The sensor body **56** faces the tapered wall **50a** of the groove. The sensor body **56** protrudes radially into the groove **50**. The sensor body **56** remains spaced apart from the tapered wall **50a** of the groove.

In the disclosed example, the sensor **24** also comprises an output connecting cable **58** for transmitting sensing data which extends outwards relative to the sensor body **56**. The output cable **58** extends radially outwards. The plug **54** is provided with a through-opening (not referenced) wherein the output cable **58** can go through. The output cable **58** connects the sensor **24** to a control unit (not shown) of the rolling bearing so as to transmit sensed measurements. Alternatively, the sensor **24** may be deprived of such output cable in case of a wireless sensor.

The sensor body **56** of the sensor has a longitudinal axis **60** extending radially. The axis **60** also forms the longitudinal axis of the sensor **24**. The axis **60** is perpendicular to the axis X-X' of the rolling bearing. The axis **60** is perpendicular to the outer cylindrical surface **12b** of the inner ring onto which is formed the groove **50**.

The sensor **24** may be an inductive distance sensor, or an ultrasonic distance sensor, or an optical distance sensor. Alternatively, the sensor **24** may be a mechanical distance sensor provided with a contact stylus. In this last case, the mechanical sensor faces the tapered wall **50a** of the groove but also comes into contact with the tapered wall.

The second distance sensor **25** radially faces the outer cylindrical surface of the nose **40** of the inner ring delimiting the axial raceway **34**. The sensor **25** measures radial distances to the outer cylindrical surface of the nose **40**.

The outer ring **14** is provided with a second radial through-hole **62** inside which the second distance sensor **25** is located. The through-hole **62** extends from the outer surface **10b** of the outer ring and opens on the bore **10a**. The through-hole **62** radially faces the outer cylindrical surface of the nose **40** of the inner ring delimiting the axial raceway **34**.

In the illustrated example, the sensor **25** is mounted into the through-hole **62** and protrudes radially into the radial space provided between the nose **40** of the inner ring and the groove **38** of the outer ring. The sensor **25** remains spaced apart from the nose **40** of the inner ring. Alternatively, the first sensor **25** may be entirely located inside the through-

hole **62**. Preferably, the shape of the through-hole **62** is complementary to that of the sensor **25**.

The outer ring **10** further comprises a second plug **64** which closes and seals the through-hole **62**. The plug **64** is located radially into the through-hole **62**. The plug **64** is secured inside the through-hole **62** by any appropriate means, for example by force-fitting. The plug **64** is flush with the outer cylindrical surface **10b** of the outer ring.

The sensor **25** comprises a sensor body **66** mounted inside the through-hole **62** of the outer ring. The sensor body **66** is secured inside the through-hole **62** by any appropriate means, for example by force-fitting. The sensor body **66** radially faces the outer cylindrical surface of the nose **40** of the inner ring delimiting the axial raceway **34**. The sensor body **66** protrudes radially into the radial space provided between the nose **40** of the inner ring and the groove **38** of the outer ring. The sensor body **66** remains spaced apart from the nose **40**.

In the disclosed example, the sensor **25** also comprises an output connecting cable **68** for transmitting sensing data which extends outwards relative to the sensor body **66**. The output cable **68** extends radially outwards. The plug **64** is provided with a through-opening (not referenced) wherein the output cable **68** can go through. The output cable **68** connects the sensor **25** to the control unit so as to transmit sensed measurements. Alternatively, the sensor **25** may be deprived of such output cable in case of a wireless sensor.

The sensor body **66** of the sensor has a longitudinal axis **70** extending radially. The axis **70** also forms the longitudinal axis of the sensor **25**. The axis **70** is perpendicular to the axis X-X' of the rolling bearing. The axis **70** is perpendicular to the outer cylindrical surface of the nose **40** of the inner ring delimiting the axial raceway **34**.

Similarly to the first sensor **24**, the second **25** may be an inductive distance sensor, an ultrasonic distance sensor, an optical distance sensor, or a mechanical distance sensor.

As previously mentioned, the sensor **24** measures radial distances to the tapered wall **50a** of the groove of the inner ring, and the sensor **25** measures radial distances to the outer cylindrical surface of the nose **40** of the inner ring.

A pure axial displacement of the inner ring **12** relative to the outer ring **10** is shown schematically on FIG. 2. The groove **50** represented in dotted lines illustrates the position of the inner ring **12** after the axial displacement. The axial displacement D_a of the inner ring **12** relative to the outer ring **10** is illustrated by the arrow referenced **72**.

The arrow referenced **74** illustrates a first radial distance to the tapered wall **50a** of the groove measured by the sensor **24** before the displacement of the inner ring **12** relative to the outer ring **10**. A second radial distance to the tapered wall **50a** of the groove measured by the sensor **24** after this axial displacement is illustrated by the arrow referenced **76**.

ΔM illustrated by the arrow referenced **78** represents the radial displacement of the tapered wall **50a** of the groove relative to the outer ring **10**, which is detected by the sensor **24**. The value of the relative radial displacement ΔM is equal to the difference between the second and the first radial distances measured by the sensor **24**, i.e. the differential measurement of the sensor **24**.

In case of pure axial displacement of the inner ring **12** relative to the outer ring **10** as shown on FIG. 2, the value of the radial displacement ΔM of the tapered wall **50a** of the groove relative to the outer ring **10** is also equal to:

$\Delta M = D_a \sin \alpha$, where D_a is the value of the axial displacement of the inner ring **12** relative to the outer ring **10**, and α is the value of the angle of the tapered wall **50a** of the groove.

In case of combination of axial and radial displacements of the inner ring **12** relative to the outer ring **10**, the value of the radial displacement ΔM of the tapered wall **50a** of the groove relative to the outer ring **10** is equal to:

$\Delta M = (D_a \times \sin \alpha) + D_r$, where D_r is the value of the radial displacement of the outer cylindrical surface of the nose **40** of the inner ring relative to the outer ring **10**, which is detected by the sensor **25**. A first radial distance to the outer cylindrical surface of the nose **40** is measured by the sensor **25** before the displacement of the inner ring **12** relative to the outer ring **10**. A second radial distance to the outer cylindrical surface of the nose **40** is then measured by the sensor **25** after this displacement. The value of the relative radial displacement D_r is equal to the difference between the second and the first radial distances measured by the sensor **25**, i.e. the differential measurement of the sensor **25**.

Therefore, the value of the axial displacement D_a of the inner ring **12** relative to the outer ring **10** is equal to:

$$D_a = \frac{(\Delta M - D_r)}{\sin \alpha}$$

Accordingly, the axial displacement of the tapered groove **50** of the inner ring **12**, and more generally of the inner ring **12**, relative to the outer ring **10** can be calculated from the radial displacements measured by the sensors **24**, **25**. Advantageously, the control unit of the rolling bearing calculates these axial displacements of the inner ring **12** relative to the outer ring **10**.

Otherwise, the measurements made by the sensor **25** may be used by the control unit to determine the radial clearance of the rolling bearing.

In the illustrated example, the rolling bearing further comprises an additional seal **80** disposed inside the closed space **46** which is delimited by the seals **42**, **44**. The seal **80** is axially located near to the seal **42**. The seal **80** is axially disposed between the seal **42** and the row of axial rollers **20**. In the illustrated example, the seal **80** is mounted into a groove (not referenced) formed on the outer cylindrical surface **12b** of the inner ring and comes into contact with the outer ring **10**. The seal **80** comes into contact with the bore **10a** of the outer ring near to the through-hole **52**. Alternatively, the seal **80** may be mounted on the outer ring **14** and come into friction contact with the inner ring **12**.

Radially between the outer and inner rings **10** and **12**, the seal **80** delimits together with the seal **42** a closed detection space (not referenced) inside which open the groove **50** of the inner ring and the through-hole **52** of the outer ring. Only the groove **50**, the through-hole **52** and the sensor **24** are located inside the detection space. There is no row of rollers inside the detection space. This reduces the risk that pollution, such as grease, dust, water, reaches the sensor **24**.

In the illustrated example, the tapered groove **50** is formed on the outer cylindrical surface **12b** of the inner ring axially between the row of axial rollers **20** and the seal **42**. Alternatively, according to the design of the rolling bearing, it could be possible to provide the groove **50** on another zone of the outer cylindrical surface **12b**.

In another variant, it could also be possible to foresee an inverted arrangement between the sensors **24**, **25** with a groove **50** provided on the outer cylindrical surface of the nose **40** of the inner ring onto which is formed the axial raceway **34**. In this case, the sensor **24** is axially located between the row of radial rollers **22** and the row of axial rollers **20** or **18**.

In another variant, according to the design of the rolling bearing, it could also be possible to dispose the sensor **25** in front of the outer axial cylindrical surface of the inner ring onto which is formed the tapered groove **50**.

Otherwise, as previously mentioned, in this illustrated example, the first ring of the rolling bearing is the outer ring **10** whereas the second ring is the inner ring **12**.

As an alternative, it could be possible to provide a reversed arrangement with the first ring forming the inner ring and the second ring forming the outer ring. In this case, the tapered groove **50** is formed on the axial inner cylindrical surface of the outer ring, which forms the bore of the outer ring, and the sensors **24**, **25** are mounted on the inner ring.

In the described examples, the rolling bearing is provided with three rows of rolling elements. Alternatively, the rolling bearing may comprise only one row of rolling elements, or two rows of rolling elements, or four or more rows of rolling elements. In the illustrated example, the rolling elements are rollers. The rolling bearing may comprise other types of rolling elements, for example balls. In another variant, the bearing may also be a sliding bearing having no rolling elements.

The invention claimed is:

1. A bearing comprising:

a first ring and a second ring capable of rotating concentrically relative to one another, at least one tapered groove is formed on a first axial cylindrical surface of the second ring and oriented towards the first ring, at least one first distance sensor mounted on the first ring and facing a tapered wall of the tapered groove of the second ring which is inclined with respect to the axis of the bearing, a longitudinal axis of the first distance sensor being perpendicular to the axis, at least one second distance sensor mounted on the first ring and distinct from the first distance sensor, the second distance sensor radially facing a second axial cylindrical surface of the second ring, and a seal located on the second ring and configured to contact the first ring, the seal being located axially between the at least one first distance sensor and the at least one second distance sensor.

2. The bearing according to claim 1, wherein the tapered groove of the second ring is annular.

3. The bearing according to claim 1, wherein the first ring comprises at least first and second through-holes inside which the first and second distance sensors are respectively at least partly disposed.

4. The bearing according to claim 3, wherein each through-hole of the first ring extends radially from an axial cylindrical surface located radially on the side opposite to the second ring, and opens on an opposite axial cylindrical surface of the first ring radially facing the second ring.

5. The bearing according to claim 1, wherein the first axial cylindrical surface and the second axial cylindrical surface of the second ring are radially off set.

6. The bearing according to claim 1, further comprising at least one row of rolling elements arranged between raceways provided on the first and second rings.

7. The bearing according to claim 1, comprising at least one row of axial rolling elements arranged between radial raceways provided on the rings, and at least one row of radial rolling elements arranged between axial raceways provided on the rings, the second ring comprising a protruding nose engaged into an annular groove of the first ring and provided with the second axial cylindrical surface, the axial raceway of the second ring being formed onto the second axial cylindrical surface.

11

8. The bearing according to claim 7, wherein the nose protrudes radially from the first axial cylindrical surface of the second ring from which the tapered groove is formed.

9. The bearing according to claim 1, wherein each of the first and second distance sensors is a proximity sensor selected from the group consisting of an inductive sensor, an ultrasonic sensor, and an optical sensor.

10. The bearing according to claim 1, further comprising a control unit connected to the first and second distance sensors and adapted to calculate the value of a relative axial displacement between the first and second rings on the basis of the formula:

$$Da = \left(\frac{\Delta M - Dr}{\sin \alpha} \right),$$

where

ΔM is the value of the differential measurement of the first distance sensor on the tapered wall of the second ring, Dr is the value of a relative radial displacement between the first and second rings detected by the second distance sensor, and

α is the value of the angle formed between the tapered wall of the tapered groove and the first axial cylindrical surface of the second ring in a radial plane of the bearing.

11. A bearing comprising:

a first ring and a second ring capable of rotating concentrically relative to one another, at least one tapered groove is formed on a first axial cylindrical surface of the second ring and oriented towards the first ring, at least one first distance sensor mounted on the first ring and facing a tapered wall of the tapered groove of the second ring which is inclined with respect to the axis of the bearing, a longitudinal axis of the first distance sensor being perpendicular to the axis, at least one second distance sensor mounted on the first ring and distinct from the first distance sensor, the

12

second distance sensor radially facing a second axial cylindrical surface of the second ring, and a control unit connected to the first and second distance sensors and adapted to calculate the value of a relative axial displacement between the first and second rings on the basis of the formula:

$$Da = \left(\frac{\Delta M - Dr}{\sin \alpha} \right),$$

where

ΔM is the value of the differential measurement of the first distance sensor on the tapered wall of the second ring,

Dr is the value of a relative radial displacement between the first and second rings detected by the second distance sensor, and

α is the value of the angle formed between the tapered wall of the tapered groove and the first axial cylindrical surface of the second ring in a radial plane of the bearing.

12. The bearing according to claim 11, comprising at least one row of axial rolling elements arranged between radial raceways provided on the rings, and at least one row of radial rolling elements arranged between axial raceways provided on the rings, the second ring comprising a protruding nose engaged into an annular groove of the first ring and provided with the second axial cylindrical surface, the axial raceway of the second ring being formed onto the second axial cylindrical surface.

13. The bearing according to claim 12, wherein the nose protrudes radially from the first axial cylindrical surface of the second ring from which the tapered groove is formed.

14. The bearing according to claim 11, wherein each of the first and second distance sensors is a proximity sensor selected from the group consisting of an inductive sensor, an ultrasonic sensor, and an optical sensor.

* * * * *