



US011333340B1

(12) **United States Patent**
Lin et al.

(10) **Patent No.:** **US 11,333,340 B1**
(45) **Date of Patent:** **May 17, 2022**

(54) **TOUCH CONTROLLER FOR LED LIGHT STRING OR LIGHT STRIP**

(71) Applicant: **Changzhou Jutai Electronic Co., Ltd.**, Jiangsu (CN)

(72) Inventors: **Jun Lin**, Jiangsu (CN); **Wei Huang**, Jiangsu (CN); **Chengqian Pan**, Jiangsu (CN); **Bin Chen**, Jiangsu (CN)

(73) Assignee: **CHANGZHOU JUTAI ELECTRONIC CO., LTD.**, Changzhou (CN)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/989,922**

(22) Filed: **Aug. 11, 2020**

(51) **Int. Cl.**
F21V 23/00 (2015.01)
F21V 23/04 (2006.01)
G06F 3/041 (2006.01)
F21V 31/00 (2006.01)
F21Y 115/10 (2016.01)
G06F 3/044 (2006.01)

(52) **U.S. Cl.**
CPC *F21V 23/0485* (2013.01); *F21V 31/005* (2013.01); *G06F 3/0416* (2013.01); *F21V 23/004* (2013.01); *F21Y 2115/10* (2016.08); *G06F 3/044* (2013.01)

(58) **Field of Classification Search**
CPC F21V 23/00; F21V 23/003; F21V 23/004; F21V 23/0485; H03K 17/962; G06F 3/0416; G06F 3/044
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

8,674,986 B2 * 3/2014 Bin Zafar G06T 15/506 345/426
2003/0160518 A1 * 8/2003 Chang H03K 17/962 307/147
2017/0311407 A1 * 10/2017 Chen H05B 47/19
2020/0133431 A1 * 4/2020 Allore G06F 3/03547

* cited by examiner


Primary Examiner — Thai Pham

(74) *Attorney, Agent, or Firm* — Dragon Sun Law Firm, PC; Jinggao Li, Esq.

(57) **ABSTRACT**

A touch controller for an LED light string or light strip is disclosed. The touch controller includes a housing, an end cover connected with the housing, a liquid-sealed accommodating cavity being defined between the end cover and the housing, a printed circuit board positioned in the accommodating cavity, a light-emitting control circuit being arranged on the printed circuit board, a touch input unit positioned in the accommodating cavity, the touch input unit being electrically connected with the light-emitting control circuit, one part of the touch input unit being matched with the housing or the end cover, and when a touch behavior is applied to the part, matched with the touch input unit, of the housing or the end cover, a trigger signal is provided for the light-emitting control circuit through the touch input unit.

17 Claims, 29 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 4a




FIG. 5a




FIG. 5b




FIG. 5c




FIG. 5d




FIG. 5e




FIG. 5f




FIG. 5g




FIG. 6a




FIG. 6b




FIG. 6c




FIG. 6d




FIG. 6e




FIG. 6f




FIG. 6g




FIG. 7a




FIG. 7b




FIG. 7c




FIG. 7d




FIG. 7e




FIG. 7f




FIG. 7g




FIG. 8a




FIG. 8b




FIG. 8c




FIG. 8d




FIG. 8e




FIG. 8f




FIG. 8g




FIG. 9a




FIG. 9b




FIG. 9c




FIG. 9d




FIG. 9e




FIG. 9f




FIG. 9g




FIG. 10a




FIG. 10b




FIG. 10c




FIG. 10d




FIG. 10e




FIG. 10f




FIG. 10g




FIG. 11a




FIG. 11b




FIG. 11c




FIG. 11d




FIG. 11e




FIG. 11f




FIG. 11g




FIG. 12a




FIG. 12b




FIG. 12c




FIG. 12d




FIG. 12e




FIG. 12f




FIG. 12g




FIG. 13a




FIG. 13b




FIG. 13c




FIG. 13d




FIG. 13e




FIG. 13f




FIG. 13g




FIG. 14a




FIG. 14b




FIG. 14c




FIG. 14d




FIG. 14e




FIG. 14f




FIG. 14g




FIG. 15a




FIG. 15b




FIG. 15c




FIG. 15d




FIG. 15e




FIG. 15f




FIG. 15g




FIG. 16a




FIG. 16b




FIG. 16c




FIG. 16d




FIG. 16e




FIG. 16f




FIG. 16g




FIG. 17a




FIG. 17b




FIG. 17c




FIG. 17d




FIG. 17e




FIG. 17f




FIG. 17g




FIG. 18a




FIG. 18b




FIG. 18c




FIG. 18d




FIG. 18e



FIG. 18f




FIG. 18g




FIG. 19a




FIG. 19b




FIG. 19c




FIG. 19d




FIG. 19e




FIG. 19f




FIG. 19g




FIG. 20a




FIG. 20b




FIG. 20c




FIG. 20d




FIG. 20e




FIG. 20f




FIG. 20g




FIG. 21a




FIG. 21b




FIG. 21c




FIG. 21d




FIG. 21e




FIG. 21f




FIG. 21g




FIG. 22a




FIG. 22b




FIG. 22c




FIG. 22d




FIG. 22e




FIG. 22f




FIG. 22g




FIG. 23a




FIG. 23b




FIG. 23c




FIG. 23d




FIG. 23e




FIG. 23f




FIG. 23g




FIG. 24a




FIG. 24b




FIG. 24c




FIG. 24d




FIG. 24e




FIG. 24f




FIG. 24g




FIG. 25a




FIG. 25b




FIG. 25c




FIG. 25d




FIG. 25e




FIG. 25f




FIG. 25g



FIG. 26a




FIG. 26b




FIG. 26c




FIG. 26d




FIG. 26e




FIG. 26f




FIG. 26g




FIG. 27a




FIG. 27b




FIG. 27c




FIG. 27d




FIG. 27e




FIG. 27f




FIG. 27g




FIG. 28a




FIG. 28b




FIG. 28c




FIG. 28d




FIG. 28e




FIG. 28f




FIG. 28g




FIG. 29a




FIG. 29b




FIG. 29c




FIG. 29d




FIG. 29e




FIG. 29f




FIG. 29g

TOUCH CONTROLLER FOR LED LIGHT STRING OR LIGHT STRIP

CROSS REFERENCE

This application claims the priority benefit of Chinese Patent Application No. CN2020215059526, filed on Jul. 27, 2020, which is hereby incorporated by reference in its entirety.

TECHNICAL FIELD

The disclosure pertains to the technical field of LED lights, and specifically pertains to a touch controller for an LED light string or light strip.

BACKGROUND

An LED light string or light strip is usually connected with a power controller, an existing power controller comprises a housing, an end cover, a printed circuit board and a key switch, at least one part of the printed circuit board is positioned in the housing, a direct-current output circuit and a light-emitting control circuit are arranged on the printed circuit board, the end cover is fixed to the housing, an assembly hole is formed in the end cover, one end of the key switch is connected with the circuit board, the other end of the key switch is matched with the assembly hole, and the LED light string or light strip is usually used outdoors, so that a silica gel sleeve is usually installed in the assembly hole to seal a gap between the assembly hole and the key switch, and a waterproof purpose is achieved. In use, a trigger signal is provided for the light-emitting control circuit by pressing the key switch, and the light-emitting control circuit outputs a control instruction for changing a light-emitting mode according to the trigger signal and a program preset in the light-emitting control circuit, so that different light-emitting effects are achieved.

The structure has a good waterproof effect in the initial stage, but along with the increase of service time, on one hand, as the space defined by the housing and the end cover is closed, a part of heat emitted by electronic parts and components on the circuit board can act on the silica gel sleeve, the silica gel sleeve can be gradually hardened, and the sealing performance is gradually reduced; on the other hand, in use, acting force generated by a finger is transmitted to the key switch through the silicon rubber sleeve, so that the silica gel sleeve is stressed to deform in the pressing process, a gap is formed between the silica gel sleeve and the end cover, liquid existing on the end cover enters the housing along the gap, and adverse effects such as short circuit and the like are caused to a circuit on the circuit board; and the structure is complex in manufacturing process and high in cost.

SUMMARY

The disclosure provides a touch controller for an LED light string or light strip, which is good in waterproof effect and convenient to operate.

A touch controller for an LED light string or light strip, comprising:

a housing;

an end cover, after the end cover is connected with the housing, a liquid-sealed accommodating cavity being defined between the end cover and the housing;

a printed circuit board positioned in the accommodating cavity, a light-emitting control circuit being arranged on the printed circuit board; and

characterized by further comprising a touch input unit positioned in the accommodating cavity, the touch input unit being electrically connected with the light-emitting control circuit, one part of the touch input unit being matched with the housing or the end cover, and when a touch behavior is applied to the part, matched with the touch input unit, of the housing or the end cover, a trigger signal is provided for the light-emitting control circuit through the touch input unit.

According to the disclosure, entity keys in the prior art are cancelled, and a touch input unit is used for providing a trigger signal for a light-emitting control circuit, so that the advantage is that the touch input unit can generate the trigger signal as long as electric parameters are changed by touch, in this way, the touch input unit can be integrally packaged in an accommodating cavity defined by a housing and an end cover, so that through holes do not need to be formed in the housing and the end cover to install the touch input unit, therefore, guarantees are provided for realizing absolute waterproofness, the light-emitting effect is changed in a touch mode, and the advantage of convenience in use is achieved.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a profile of a touch controller;

FIG. 2 is a circuit block diagram of a touch input unit;

FIG. 3 is a schematic circuit diagram of the touch input unit;

FIG. 4 is a profile of another touch controller;

FIG. 4a is a profile of another touch controller;

FIG. 5a to FIG. 5g are external views of a first touch controller;

FIG. 6a to FIG. 6g are external views of a second touch controller;

FIG. 7a to FIG. 7g are external views of a third touch controller;

FIG. 8a to FIG. 8g are external views of a fourth touch controller;

FIG. 9a to FIG. 9g are external views of a fifth touch controller;

FIG. 10a to FIG. 10g are external views of a sixth touch controller;

FIG. 11a to FIG. 11g are external views of a seventh touch controller;

FIG. 12a to FIG. 12g are external views of an eighth touch controller;

FIG. 13a to FIG. 13g are external views of a ninth touch controller;

FIG. 14a to FIG. 14g are external views of a tenth touch controller;

FIG. 15a to FIG. 15g are external views of an eleventh touch controller;

FIG. 16a to FIG. 16g are external views of a twelfth touch controller;

FIG. 17a to FIG. 17g are external views of a thirteenth touch controller;

FIG. 18a to FIG. 18g are external views of a fourteenth touch controller;

FIG. 19a to FIG. 19g are external views of a fifteenth touch controller;

FIG. 20a to FIG. 20g are external views of a sixteenth touch controller;

FIG. 21a to FIG. 21g are external views of a seventeenth touch controller;

FIG. 22a to FIG. 22g are external views of an eighteenth touch controller;

FIG. 23a to FIG. 23g are external views of a nineteenth touch controller;

FIG. 24a to FIG. 24g are external views of a twentieth touch controller;

FIG. 25a to FIG. 25g are external views of a twenty-first touch controller;

FIG. 26a to FIG. 26g are external views of a twenty-second touch controller;

FIG. 27a to FIG. 27g are external views of a twenty-third touch controller;

FIG. 28a to FIG. 28g are external views of a twenty-fourth touch controller; and

FIG. 29a to FIG. 29g are external views of a twenty-fifth touch controller.

DESCRIPTION OF THE EMBODIMENTS

As shown in FIG. 1 and FIG. 2, a touch controller for an LED light string or light strip comprises a housing 10, an end cover 20, a printed circuit board 40 and a touch input unit 80, and the disclosure is described in details in conjunction with the following drawings:

As shown in FIG. 1, the housing 10 preferentially adopts the structure that a main body part of the housing 10 is in the shape of a barrel defined by an annular wall, one end of the housing 10 is closed, the other end of the housing 10 is provided with an opening, the housing 10 is made of PC or PVC material through injection molding, the closed end of the housing 10 is provided with inserted pins 90, the inserted pins 90 and the housing 10 are cast into a whole body so that the housing 10 is in liquid-sealed connection with the inserted pins 90, one end of each of the inserted pins 90 extends to the interior of the housing 10 to be electrically connected with the printed circuit board 40, the other ends of the inserted pins 90 are exposed out of the housing 10, and the inserted pins 90 are connected with a socket connected with an alternating-current power supply. Preferably, input plugging sheets are welded at one end of the printed circuit board 40, and after the printed circuit board 40 is inserted into the interior of the housing 10, the input plugging sheets are in plugging fit with the inserted pins 90.

As shown in FIG. 1, after the end cover 20 is connected with the housing 10, a liquid-sealed accommodating cavity 30 is defined between the end cover 20 and the housing 10, namely liquid cannot enter the accommodating cavity 30 through the housing 10 and the end cover 20 and the joint of the housing 10 and the end cover 20, the end cover 20 is in liquid-sealed connection with the housing 10, and the end cover 20 and the housing 10 are welded through ultrasonic waves preferentially. In the embodiment, in order to achieve absolute waterproofness, through holes for installing the touch input unit 80 do not need to be formed in the housing 10 or the end cover 20.

As shown in FIG. 1 and FIG. 2, the printed circuit board 40 is positioned in the accommodating cavity 30, a light-emitting control circuit 60 is arranged on the printed circuit board 40, in the embodiment, a direct-current output circuit 50 is further arranged on the printed circuit board 40, and the direct-current output circuit 50 preferentially adopts a circuit for converting alternating current into direct current. For example, the direct-current output circuit 50 can be composed of a rectification filter circuit and a voltage conversion circuit which are disclosed in CN103561507A, so that the inserted pins 90 are coupled with the alternating-current power supply, alternating current is converted into direct

current through the action of the direct-current output circuit 50, and the current required for work is provided for each circuit in the touch controller and the LED light string or light strip. The light-emitting control circuit 60 can be composed of a microcontroller and a bridge type drive circuit which are disclosed in CN103561507A, the microcontroller outputs pulse width modulation signals with different duty ratios, and the LED light string or light strip generates different light-emitting effects under the action of the bridge type drive circuit.

As shown in FIG. 1 and FIG. 2, in the embodiment, a connector 70 is arranged on the end cover 20, the connector 70 is used for connecting the LED light string or light strip, the connector 70 is electrically connected with the output end of the light-emitting control circuit 60 and the direct-current output circuit 50, the connector 70 is composed of a socket and conductive sheets, and the socket, the conductive sheets and the end cover 20 are integrally formed through injection molding, so that the connector 70 is in liquid-sealed connection with the end cover 20. The connector 70 is electrically connected with the printed circuit board 40, preferably, output plugging sheets are welded on the printed circuit board 40, and after the end cover 20 is combined with the housing 10, the conductive sheets in the connector 70 are in plugging connection with the output plugging sheets. In use, a plug of the LED light string or light strip is directly in plugging connection with the connector 70.

As shown in FIG. 1 and FIG. 2, the touch input unit 80 is positioned in the accommodating cavity 30, the touch input unit 80 is electrically connected with the light-emitting control circuit 60, one part of the touch input unit 80 is matched with the housing 10 or the end cover 20, and when a touch behavior is applied to the part, matched with the touch input unit 80, of the housing 10 or the end cover 20, a trigger signal is provided for the light-emitting control circuit 60 through the touch input unit 80.

As shown in FIG. 1 and FIG. 2, preferably, one part of the touch input unit 80 abuts against the housing 10 or the end cover 20, or is fixed to the housing 10 or the end cover 20, or is in clearance fit with the housing 10 or the end cover 20. The other part of the touch input unit 80 is arranged on the printed circuit board 40.

As shown in FIG. 1 and FIG. 2, the touch input unit 80 comprises a touch conduction part 801, a touch detection unit 802 and a touch control unit 803, and the touch conduction part 801 is matched with the housing 10 or the end cover 20. The touch conduction part 801 adopts a spring preferentially, after the housing 10 is connected with the end cover 20, the spring is compressed by the end cover 20 so that the spring abuts against the end cover 20, and the spring is welded and fixed with the printed circuit board 40.

As shown in FIG. 1 and FIG. 2, an installation part 100 matched with the touch input unit 80 is arranged on the inner wall surface of the housing 10 or the end cover 20, a touch identification part 101 for touching is arranged on the outer wall surface of the housing 10 or the end cover 20, the position of the touch identification part 101 corresponds to that of the installation part 100, and the touch behavior can be applied conveniently through the touch identification part 101.

As shown in FIG. 1 and FIG. 2, in the embodiment, the installation part 100 is preferentially an inner recess formed by recessing along the inner wall surface of the housing 10 or the end cover 20, the touch conduction part 801 abuts against the surface of the installation part 100, and the touch identification part 101 is preferentially an outer recess

5

formed by recessing along the outer wall surface of the housing 10 or the end cover 20.

As shown in FIG. 1 and FIG. 2, the touch detection unit 802 is electrically connected with the touch conduction part 801, when the touch behavior is applied to the part, matched with the touch conduction part 801, of the housing 10 or the end cover 20, the touch detection unit 802 generates the change of electrical parameters through the conduction of the touch conduction part 801, the touch control unit 803 is electrically connected with the touch detection unit 802, and when the touch control unit 803 judges that the touch behavior is effective according to the electrical parameters provided by the touch detection unit 802, the touch control unit 803 generates and outputs the trigger signal.

As shown in FIG. 3, the change of the electrical parameters preferentially adopts the change of oscillation frequency caused by the change of capacitance value, preferably, the touch detection unit 802 comprises a first capacitor C1, a first switch Q1, a first resistor R1, a second switch K and a constant current source D, the first capacitor C1 is connected with the touch control unit 803, the other end of the first capacitor C1 is grounded, the first switch Q1 is a triode, a collector of the first switch Q1 is connected with the touch control unit 803, an emitter of the first switch Q1 is connected with the ground, a base of the first switch Q1 is connected with the touch control unit 803 through the first resistor R1, and the second switch K is connected with the first capacitor C1, the touch control unit 803 and the constant current source D respectively.

After the touch control unit 803 controls the first switch K to be switched on, the constant current source D charges the first capacitor C1, the touch control unit 803 detects a voltage on the first capacitor C1, and when a set threshold value is reached, the touch control unit 803 outputs a high level to enable the first switch Q1 to discharge the first capacitor C1, and charging and discharging are carried out in this way to form oscillation frequency.

As shown in FIG. 3, reference frequency is set in the touch control unit 803. When no touch behavior occurs, the frequency input into the touch control unit 803 is within a specified range, or the frequency of an input signal is slightly changed under the action of an external interference signal, the touch control unit 803 calculates the frequency of the input signal and the reference frequency, the value of the reference frequency can be a range value, and if the frequency of the input signal is smaller than the minimum value of the reference frequency, it is indicated that the input signal is not an effective touch signal.

As shown in FIG. 3, when an operator applies the touch behavior to the part, matched with the touch input unit 80, of the housing 10 or the end cover 20, the touch conduction part 801 forms capacitance through a finger of the operator, at the moment, the total capacitance value is changed, and then the oscillation frequency of a signal input into the touch control unit 803 is changed, the touch control unit 803 calculates the frequency of the input signal and the reference frequency, if the frequency of the input signal is greater than the maximum value of the reference frequency, it is indicated that the input signal is an effective touch signal, therefore, the touch control unit 803 generates and outputs the trigger signal which is preferably a pulse signal, and the light-emitting control circuit 60 outputs the pulse width modulation signals with changed effects according to the pulse signal.

As shown in FIG. 3, the touch input unit 80 further comprises a reference adjustment unit 805 for adjusting and comparing the signal reference of the electrical parameters,

6

and the reference adjustment unit 805 is electrically connected with the touch conduction part 801 and the touch detection unit 802. The reference adjustment unit 805 comprises a second capacitor C2 and a second resistor R2, one end of the second capacitor C2 is connected with the touch conduction part 801, the other end of the second capacitor C2 is grounded, one end of the second resistor R2 is connected with the touch conduction part 801, the other end of the second resistor R2 is electrically connected with the touch detection unit 802, and the reference electrical parameters of the touch control unit 803, such as the frequency of the signals, input into the touch control unit 803 can be changed through the second capacitor C2 and the second resistor R2.

As shown in FIG. 3, the touch input unit 80 further comprises a voltage stabilizing unit 806 for providing a stabilized voltage for the touch control unit 803. The voltage stabilizing unit 806 is electrically connected with the touch control unit 803, and the voltage stabilizing unit 806 is composed of a voltage stabilizing diode and a capacitor in parallel.

As shown in FIG. 2 and FIG. 3, the touch input unit 80 further comprises a timing unit 804 for calculating the duration of the touch behavior, and the timing unit 804 is electrically connected with the touch control unit 803. The duration of the touch behavior is calculated by the timing unit 804, and when the touch behavior occurs continuously, for example, for more than 10 seconds, the touch control unit 803 can output a corresponding control signal voluntarily, for example, a power-on initial state is returned back. The situation is mainly aimed at misoperation, such as the change of the electrical parameters caused by the fact that the touch identification part 101 is covered with an object with a non-touch behavior, through the arrangement, a user is likely to find that the light-emitting effect of an LED lamp needs to be inconsistent with the light-emitting effect of a current LED lamp, and then the touch controller is checked so as to remove the object with which the touch identification part 101 is covered.

The disclosure is not limited to the embodiment, for example,

(a), as shown in FIG. 4, the touch conduction part 801 comprises a conductive sheet 801a and a conductive pin 801b, the conductive sheet 801a is matched with the housing 10 or the end cover 20, one end of the conductive pin 801b is connected with the conductive sheet 801a, and the other end of the conductive pin 801b is connected with the touch detection unit 802;

The installation part 100 comprises an inner recess formed by recessing along the inner wall surface of the housing 10 or the end cover 20, the conductive sheet 801a is preferentially bonded with the housing 10 or the end cover 20, the touch identification part 101 comprises an annular groove formed in the outer surface of the housing 10 or the end cover 20, preferably, a plastic or rubber nest is embedded in the annular groove, and the color of the plastic or rubber nest is different from that of the housing 10 or the end cover 20;

The installation part 100 and the touch identification part 101 may also be such configured that the touch identification part 101 adopts the structure described in (a), and the installation part 100 is a region on the inner wall surface of the housing 10 or the end cover 20;

(b), the installation part 100 is a cylinder or a cone, the touch conduction part 801 (spring) sleeves the cylinder or the cone, a gap is reserved between the touch conduction part 801 and the inner wall surface of the housing 10 or the

end cover **20**, the size of the gap is 0.5-1 mm, and the touch identification part **101** can be a protruding part or a label different from the housing **10** or the end cover **20** in other colors;

(c), the installation part **100** is not arranged on the inner wall surface of the housing **10** or the end cover **20**, the touch conduction part **801** abuts against the inner wall surface of the housing **10** or the end cover **20**, the touch identification part **101** is arranged on the outer wall surface of the housing **10** or the end cover **20**, and the touch identification part **101** corresponds to the position where the touch conduction part **801** abuts against the inner wall surface of the housing **10** or the end cover **20**;

(d), the number of the touch input units **80** can be two or more, for example, when the number of the touch input units **80** is two, one of the touch input units **80** outputs a trigger signal for changing a flashing mode, and the other touch input unit **80** outputs a trigger signal for changing lighting intensity;

(e) when the number of the touch input unit **80** is one, wherein two or more than two sets of touch conduction parts **801** and two or more than two sets of touch detection units **802** are arranged, for example, when the two or more than two sets of touch conduction parts **801** and the two or more than two sets of touch detection units **802** are arranged, one set of touch conduction parts **801** or one set of touch detection units **802** is used for enabling the touch control unit **803** to output the trigger signal for changing the flashing mode, and the other set of touch conduction parts or the other set of touch detection units is used for enabling the touch control unit **803** to output the trigger signal for changing lighting intensity; and

and (f), as shown in FIG. **18a** to FIG. **18g**, compared with the structure of the touch controller as shown in FIG. **1**, the structure is not provided with a plug sheet **90** or a connector **70**, the touch controller further can be powered by a direct-current power supply, such as an external direct-current stabilized power supply or a storage battery, the direct-current power supply is connected with the light-emitting control circuit **60** on the printed circuit board **40** through a wire so as to be used for the LED light string or the LED light strip, and the wire and the housing **10** can be subjected to waterproof treatment by heating a melt adhesive.

What is claimed is:

1. A touch controller for an LED light string or light strip, comprising:

a housing;

an end cover, after the end cover is connected with the housing, a liquid-sealed accommodating cavity being defined between the end cover and the housing;

a printed circuit board positioned in the accommodating cavity, a light-emitting control circuit being arranged on the printed circuit board; and

characterized by further comprising a touch input unit positioned in the accommodating cavity, the touch input unit being electrically connected with the light-emitting control circuit, one part of the touch input unit being matched with the housing or the end cover, and when a touch behavior is applied to the part, matched with the touch input unit, of the housing or the end cover, a trigger signal is provided for the light-emitting control circuit through the touch input unit.

2. The touch controller according to claim **1**, characterized in that the other part of the touch input unit is arranged on the printed circuit board and electrically connected with the light-emitting control circuit.

3. The touch controller according to claim **2**, characterized in that the touch input unit comprises:

a touch conduction part matched with the housing or the end cover;

a touch detection unit electrically connected with the touch conduction part, when the touch behavior is applied to the part, matched with the touch conduction part, of the housing or the end cover, the touch detection unit generating the change of electrical parameters through the conduction of the touch conduction part; and

a touch control unit electrically connected with the touch detection unit, when the touch control unit judges that the touch behavior is effective according to the electrical parameters provided by the touch detection unit, the touch control unit generating and outputting the trigger signal.

4. The touch controller according to claim **3**, characterized in that the touch input unit further comprises a reference adjustment unit for adjusting and comparing the signal reference of the electrical parameters, and the reference adjustment unit is electrically connected with the touch conduction part and the touch detection unit.

5. The touch controller according to claim **3**, characterized in that the touch input unit further comprises a voltage stabilizing unit for providing a stabilized voltage for the touch control unit.

6. The touch controller according to claim **3**, characterized in that the touch input unit further comprises a timing unit for calculating the duration of the touch behavior, and the timing unit is electrically connected with the touch control unit.

7. The touch controller according to claim **3**, characterized in that an installation part matched with the touch input unit is arranged on the inner wall surface of the housing or the end cover, a touch identification part is arranged on the outer wall surface of the housing or the end cover, and the position of the touch identification part corresponds to that of the installation part.

8. The touch controller according to claim **3**, characterized in that the touch conduction part is a spring, and after the housing is connected with the end cover, the spring is compressed by the end cover so that the spring abuts against the end cover.

9. The touch controller according to claim **3**, characterized in that the touch conduction part comprises a conductive sheet and a conductive pin, the conductive sheet is matched with the housing or the end cover, one end of the conductive pin is connected with the conductive sheet, and the other end of the conductive pin is connected with the touch detection unit.

10. The touch controller of an LED light string or light strip according to claim **1**, characterized in that one part of the touch input unit abuts against the housing or the end cover, or is fixed to the housing or the end cover, or is in clearance fit with the housing or the end cover.

11. The touch controller according to claim **1**, characterized in that the touch input unit comprises:

a touch conduction part matched with the housing or the end cover;

a touch detection unit electrically connected with the touch conduction part, when the touch behavior is applied to the part, matched with the touch conduction part, of the housing or the end cover, the touch detection unit generating the change of electrical parameters through the conduction of the touch conduction part; and

9

a touch control unit electrically connected with the touch detection unit, when the touch control unit judges that the touch behavior is effective according to the electrical parameters provided by the touch detection unit, the touch control unit generating and outputting the trigger signal.

12. The touch controller according to claim 11, characterized in that the touch input unit further comprises a reference adjustment unit for adjusting and comparing the signal reference of the electrical parameters, and the reference adjustment unit is electrically connected with the touch conduction part and the touch detection unit.

13. The touch controller according to claim 11, characterized in that the touch input unit further comprises a voltage stabilizing unit for providing a stabilized voltage for the touch control unit.

14. The touch controller according to claim 11, characterized in that the touch input unit further comprises a timing unit for calculating the duration of the touch behavior, and the timing unit is electrically connected with the touch control unit.

10

15. The touch controller according to claim 11, characterized in that an installation part matched with the touch input unit is arranged on the inner wall surface of the housing or the end cover, a touch identification part is arranged on the outer wall surface of the housing or the end cover, and the position of the touch identification part corresponds to that of the installation part.

16. The touch controller according to claim 11, characterized in that the touch conduction part is a spring, and after the housing is connected with the end cover, the spring is compressed by the end cover so that the spring abuts against the end cover.

17. The touch controller according to claim 11, characterized in that the touch conduction part comprises a conductive sheet and a conductive pin, the conductive sheet is matched with the housing or the end cover, one end of the conductive pin is connected with the conductive sheet, and the other end of the conductive pin is connected with the touch detection unit.

* * * * *