



US011358422B2

(12) **United States Patent**  
**Agarwal et al.**

(10) **Patent No.: US 11,358,422 B2**  
(45) **Date of Patent: Jun. 14, 2022**

(54) **ASSEMBLY FOR ATTACHING AN  
ELECTRONICS PACKAGE TO A TIRE**

(71) Applicant: **Bridgestone Americas Tire  
Operations, LLC**, Nashville, TN (US)

(72) Inventors: **Sheel P. Agarwal**, Solon, OH (US);  
**Adam K. Nesbitt**, Akron, OH (US)

(73) Assignee: **Bridgestone Americas Tire  
Operations, LLC**, Nashville, TN (US)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 99 days.

(21) Appl. No.: **16/831,974**

(22) Filed: **Mar. 27, 2020**

(65) **Prior Publication Data**

US 2020/0223266 A1 Jul. 16, 2020

**Related U.S. Application Data**

(62) Division of application No. 15/540,876, filed as  
application No. PCT/US2015/061059 on Nov. 17,  
2015, now Pat. No. 10,639,948.

(60) Provisional application No. 62/097,794, filed on Dec.  
30, 2014.

(51) **Int. Cl.**  
**B60C 23/04** (2006.01)  
**F16B 2/22** (2006.01)  
**H05K 5/02** (2006.01)  
**B29D 30/00** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **B60C 23/0493** (2013.01); **F16B 2/22**  
(2013.01); **H05K 5/0204** (2013.01); **B29D**  
**2030/0072** (2013.01); **B29D 2030/0077**  
(2013.01); **B29D 2030/0083** (2013.01)

(58) **Field of Classification Search**

CPC ..... B60C 23/0493  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

5,500,065 A \* 3/1996 Koch ..... B60C 23/0493  
156/110.1  
5,749,984 A 5/1998 Frey et al.  
5,960,844 A 10/1999 Hamaya  
5,977,870 A 11/1999 Rensel et al.  
6,030,478 A 2/2000 Koch et al.  
6,217,683 B1 \* 4/2001 Balzer ..... B60C 23/0493  
156/60

(Continued)

**FOREIGN PATENT DOCUMENTS**

AU 2012201759 9/2012  
DE 10357467 6/2005

(Continued)

**OTHER PUBLICATIONS**

Search Report and Written Opinion; Corresponding PCT Applica-  
tion No. PCT/US2015/061059, filed Nov. 17, 2015, Authorized  
Officer Bae, Geun Tae; Feb. 16, 2016.

(Continued)


*Primary Examiner* — Rockshana D Chowdhury

*Assistant Examiner* — Douglas R Burtner

(57) **ABSTRACT**

An assembly for attaching an electronics package to a tire  
includes a carriage for receiving an electronics package. The  
assembly also includes a locking clip connected to the  
carriage and a locking ring having a first side permanently  
affixed to an interior of the tire. The locking ring is config-  
ured to engage the locking clip.

**16 Claims, 7 Drawing Sheets**



(56)

## References Cited

## U.S. PATENT DOCUMENTS

6,444,069 B1 9/2002 Koch et al.  
6,462,650 B1 \* 10/2002 Balzer ..... B60C 23/0493  
73/146  
6,549,125 B2 \* 4/2003 Nigon ..... B60C 23/0408  
340/447  
6,788,192 B2 9/2004 Shimura  
6,809,700 B2 \* 10/2004 Benedict ..... B60C 23/0433  
343/872  
6,854,324 B2 2/2005 Landes et al.  
6,860,303 B2 3/2005 Rensel et al.  
6,885,291 B1 \* 4/2005 Pollack ..... B60C 23/0433  
116/34 R  
6,899,153 B1 5/2005 Pollack et al.  
6,970,076 B1 11/2005 Starkey  
7,040,155 B1 5/2006 Lundell et al.  
7,050,017 B2 5/2006 King et al.  
7,348,878 B2 3/2008 Fogelstrom  
7,513,144 B2 4/2009 Miyoshi  
7,592,902 B2 9/2009 Wilson et al.  
7,707,876 B2 5/2010 Miyoshi  
7,971,477 B2 7/2011 Kubota  
8,157,172 B2 4/2012 Fenkany  
8,511,355 B2 8/2013 Kleckner  
8,566,042 B2 10/2013 Wang et al.  
8,596,117 B2 \* 12/2013 Wilson ..... G01M 17/02  
73/146  
8,640,534 B2 2/2014 Sheikh-Bahaie  
8,661,885 B1 3/2014 Kanwar et al.  
9,884,525 B2 \* 2/2018 Brusarosco ..... B29D 30/0061  
10,611,199 B2 \* 4/2020 Sabatini ..... H05K 1/144  
10,688,837 B2 \* 6/2020 Mori ..... B60C 23/0488  
11,021,024 B2 \* 6/2021 Brusarosco ..... B60C 23/0493  
2004/0050170 A1 \* 3/2004 Koch ..... B60C 23/0493  
73/756  
2004/0182494 A1 9/2004 Dominak et al.  
2005/0076982 A1 4/2005 Metcalf et al.  
2005/0126668 A1 6/2005 Fornerod et al.  
2006/0059982 A1 \* 3/2006 Shimura ..... B60C 23/0498  
73/146  
2007/0169865 A1 \* 7/2007 Ichikawa ..... B60C 19/00  
152/152.1  
2007/0251620 A1 \* 11/2007 Perrier ..... B60C 23/0493  
220/666  
2008/0083482 A1 4/2008 Logan  
2009/0058667 A1 3/2009 Dixon et al.  
2009/0071249 A1 3/2009 Kitazaki et al.  
2009/0151829 A1 6/2009 Lionetti et al.  
2011/0041309 A1 2/2011 Shepler  
2012/0160409 A1 \* 6/2012 Townsend ..... B60C 23/0493  
156/281  
2012/0188695 A1 \* 7/2012 Yamaguchi ..... B60C 23/0493  
361/679.01  
2012/0204635 A1 \* 8/2012 Kutzscher ..... B60C 23/0493  
73/146.8

2013/0081457 A1 \* 4/2013 Wilson ..... G01M 17/02  
73/146  
2013/0131915 A1 5/2013 Masago  
2014/0007666 A1 \* 1/2014 Kutzscher ..... B60C 23/0498  
73/146.5  
2014/0060171 A1 \* 3/2014 Hu ..... B60C 23/0408  
73/146.8  
2014/0124636 A1 \* 5/2014 Nagaya ..... B60C 19/00  
248/205.3  
2014/0352420 A1 \* 12/2014 Brusarosco ..... B60C 23/0493  
73/146.5  
2017/0015149 A1 \* 1/2017 Yamaguchi ..... B60C 19/00  
2017/0015152 A1 \* 1/2017 Hartmann ..... B60C 23/0493  
2017/0349010 A1 \* 12/2017 Wilson ..... B60C 23/0493  
2020/0031178 A1 \* 1/2020 Ishii ..... B60C 19/00

## FOREIGN PATENT DOCUMENTS

DE 102004002150 8/2005  
DE 102011003707 8/2012  
EP 1798074 6/2007  
EP 2186658 5/2010  
JP 2002214060 7/2002  
JP 2004326158 11/2004  
JP 2006234578 9/2006  
JP 2006234579 9/2006  
JP 2006240495 9/2006  
JP 2006240598 9/2006  
JP 2007161031 6/2007  
JP 2007326536 12/2007  
JP 2008230411 10/2008  
JP 2009137497 6/2009  
JP 2009166745 7/2009  
JP 2010507515 3/2010  
JP 2010125920 6/2010  
JP 2010179888 8/2010  
JP 2011020557 2/2011  
JP 2012245888 12/2012  
JP 2013039911 2/2013  
KR 20040083132 A \* 10/2004  
KR 1020040083132 10/2004  
KR 100565029 3/2006  
KR 100672544 1/2007  
KR 20100082464 7/2010  
RU 2388622 5/2010  
WO 2007010755 1/2007  
WO 2008133314 11/2008  
WO WO-2008133314 A1 \* 11/2008 ..... B60C 23/0493  
WO 2013161762 10/2013

## OTHER PUBLICATIONS

Search Reoprt; Corresponding EP Application No. 15875886.2;  
Authorized Officer Karl Billen; dated Jul. 3, 2018.

\* cited by examiner




FIG. 1




FIG. 2






FIG. 3





FIG. 4



**FIG. 5**






FIG. 6



LOCKING CLIP - ON CARRIAGE

FIG. 7A



LOCKING RING - ON TIRE

FIG. 7B






FIG. 8

## 1

**ASSEMBLY FOR ATTACHING AN  
ELECTRONICS PACKAGE TO A TIRE****CROSS-REFERENCE TO RELATED  
APPLICATION**

This application is a divisional of U.S. patent application Ser. No. 15/540,876, filed on Jun. 29, 2017, which in turn is a National Stage Entry of PCT/US15/61059, filed on Nov. 17, 2015, which in turn claims the benefit of U.S. Provisional Patent Application No. 62/097,794, filed on Dec. 30, 2014. The disclosures of these documents are incorporated by reference herein in their entirety.

**FIELD OF INVENTION**

The present disclosure relates to assemblies for attaching an electronics package to the interior of a tire. More specifically, the present disclosure relates to assemblies for removeably attaching an electronics package to an attaching device affixed to the interior surface of a tire.

**BACKGROUND**

Mounting devices are used to attach objects to a tire, and particularly to an inner liner of a tire. One application is to attach a radio frequency identification (“RFID”) tag or chip to the inner liner of a tire. Another application is to secure a pressure or temperature-sensing device to the inner liner of the tire. Various fasteners are used to connect the object to the mounting device, including hook and loop fasteners, threaded connectors, clamps, pins, and snap-fit structures.

**SUMMARY**

In one embodiment, an assembly for mounting an electronics package to an interior of a tire includes a carriage having a base extending between two pairs of opposing sidewalls, thereby defining a recess configured to removeably receive an electronics package. A bottom of the carriage has a plurality of through holes. The assembly further includes an attaching device having a first side and a second side, the first side being permanently affixed to the interior of the tire. The attaching device is configured to receive the carriage to form a secure and locked connection.

In another embodiment, an assembly for attaching an electronics package to a tire includes a carriage for receiving an electronics package. The assembly also includes a locking clip connected to the carriage and a locking ring having a first side permanently affixed to an interior of the tire. The locking ring is configured to engage the locking clip.

In yet another embodiment, an assembly for mounting a component to an interior of a tire includes a locking ring having a first side and a second side. The first side of the locking ring is affixed to the interior of the tire. The locking ring includes a first pair of ramps extending therefrom. The assembly also includes a locking clip configured to fit onto the locking ring. The locking ring includes a second pair of ramps, each of the second pair of ramps being configured to engage one of the first pair of ramps of the locking ring.

**BRIEF DESCRIPTION OF THE DRAWINGS**

In the accompanying drawings, structures are illustrated that, together with the detailed description provided below, describe exemplary embodiments of the claimed invention. Like elements are identified with the same reference numer-

## 2

als. It should be understood that elements shown as a single component may be replaced with multiple components, and elements shown as multiple components may be replaced with a single component. The drawings are not to scale and the proportion of certain elements may be exaggerated for the purpose of illustration.

FIG. 1 is a perspective view of one embodiment of a carriage for holding an electronics package.

FIG. 2 is a top view of the carriage shown in FIG. 1.

FIG. 3 is a perspective view of an electronics package that can be used with the carriage of FIG. 1.

FIG. 4 is a perspective view of the electronics package of FIG. 3, being mounted into the carriage of FIG. 1.

FIG. 5 is a front view of the carriage of FIG. 1, held in place with a first embodiment of an attaching device.

FIG. 6 is a perspective view of another embodiment of a carriage, with a locking clip and locking ring.

FIG. 7A is a top view of the locking clip shown in FIG. 6.

FIG. 7B is a top view of a locking ring for use with the locking clip of FIG. 7A.

FIG. 8 is a cross section of another alternative embodiment of an attaching device, with a plurality of mushroom-like clips.

**DETAILED DESCRIPTION**

The following includes definitions of selected terms employed herein. The definitions include various examples or forms of components that fall within the scope of a term and that may be used for implementation. The examples are not intended to be limiting. Both singular and plural forms of terms may be within the definitions.

“Axial” and “axially” refer to a direction that is parallel to the axis of rotation of a tire.

“Equatorial plane” refers to the plane that is perpendicular to the tire’s axis of rotation and passes through the center of the tire’s tread.

“Radial” and “radially” refer to a direction perpendicular to the axis of rotation of a tire.

“Sidewall” refers to that portion of the tire between the tread and the bead.

“Tread” refers to that portion of the tire that comes into contact with the road or ground under normal inflation and load.

Directions are stated herein with reference to the axis of rotation of the tire. The terms “upward” and “upwardly” refer to a general direction towards the tread of the tire, whereas “downward” and “downwardly” refer to the general direction towards the axis of rotation of the tire. Thus, when relative directional terms such as “upper” and “lower” or “top” and “bottom” are used in connection with an element, the “upper” or “top” element is spaced closer to the tread than the “lower” or “bottom” element. Additionally, when relative directional terms such as “above” or “below” are used in connection with an element, an element that is “above” another element is closer to the tread than the other element.

The terms “inward” and “inwardly” refer to a general direction towards the equatorial plane of the tire, whereas “outward” and “outwardly” refer to a general direction away from the equatorial plane of the tire and towards the sidewall of the tire. Thus, when relative directional terms such as “inner” and “outer” are used in connection with an element, the “inner” element is spaced closer to the equatorial plane of the tire than the “outer” element.



3

FIG. 1 shows a perspective view of a carriage **100** for an electronics package. In this embodiment, carriage **100** is generally rectangular and has a rectangular protrusion at one end **110**. The carriage **100** has rectangular sidewalls **120** around the perimeter of a rectangular base **130**. Through holes **140** are located in the rectangular base **130**. The carriage is dimensioned to receive an electronics package, which may be secured in place with a pin **135**. Once secured to the carriage **100**, the electronics package will remain affixed while the tire is in operation. In other embodiments, the carriage may not include any through holes. In other alternative embodiments, the carriage and carriage components may be shaped as an oval, circle, or any geometric shape.

FIG. 2 shows a top view of the carriage **100** and through holes **140**. In this figure, carriage **100** has 13 holes, but any number of through holes can be included in alternative embodiments. The carriage **100** can be made from a variety of materials, including high density polyethylene ("HDPE"), low density polyethylene ("LDPE"), thermoplastic polyurethane ("TPU"), thermoplastic elastomer ("TPE"), nylon, or any other polymeric material.

FIG. 3 shows one embodiment of an electronics package **150** that can be used with carriage **100**. The electronics package comprises a hard outer shell that contains various sensors and communication components, which can monitor tire performance characteristics and relay the data to a remote location. In one embodiment, the electronics package **150** is an RFID tag. The electronics package may also include a sensor for measuring an internal temperature of a tire and a transmitter device, such as a radio frequency transmitter. In an alternative embodiment, the electronics package includes a sensor for measuring an internal pressure of a tire and a transmitter device. In another alternative embodiment, the electronics package includes one or more sensors for measuring both an internal temperature and an internal pressure of a tire, as well as a transmitter device. In other alternative embodiments, the electronics package may include accelerometers, stress gauges, strain gauges, sensors for counting tire revolutions, temperature sensors for measuring a temperature of tire materials, sensors for measuring tread depths, or any other known sensors. The electronics package may also include identification information.

Electronics package **150** further includes a first tab **160** located on a bottom of a first end, and a second tab **170** located on a bottom of a second end. First tab **160** and second tab **170** each include a horizontal through hole **180** and **190**, respectively.

FIG. 4 illustrates the electronics package **150** being mounted to carriage **100**. Initially, the first tab **160** of the electronics package is fit into the rectangular protrusion **110** of the carriage **100**. Then second tab **180** is aligned with a carriage through hole, and pin **135** is inserted into both the carriage through hole and the second tab through hole **190**. In this manner, electronics package is secured to carriage **100**.

In alternative embodiments (not shown), the electronics package can be secured to the carriage by other means. For example, the electronics package may be secured to the carriage via a snap-in connection, a buckle, a clamp, a magnet, a tie, a strap, or any other mechanical or electronic connection.

FIG. 5 shows a front view of the carriage **100** secured to one embodiment of an attaching device. In this embodiment, the attaching device is a clip component **300**. The clip component **300** has a base **310** affixed to an interior surface of a tire (not shown). The clip component **300** further

4

includes a pair of sidewalls **320** extending from opposite sides of the base **310**, with each sidewall **320** having a protruding flange **330**. In this embodiment, flanges **330** extend perpendicularly to the sidewalls **320** of clip component **300**, and each flange **330** include a tab **340** extending parallel to the sidewalls **320**. In other embodiments (not shown), more than two sidewalls, flanges, and/or tabs may be used, and may extend from more than two sides of the clip component **300**.

The tabs **340** in this embodiment are hook-shaped and snap around the carriage **300** when the carriage **300** is received between the sidewalls **320**. The sidewalls **320**, flanges **330**, and tabs **340** in this embodiment have a degree of elasticity to allow for ingress and egress of carriage **100**. When a user wants to insert the carriage into clip component **300**, sidewalls **320**, flanges **330** and tabs **340** may be manually pulled apart to allow clearance for carriage **100**. Once carriage **100** is positioned, the flanges **330** and tabs **340** are released to return to the position shown in FIG. 5, thereby securing the carriage **100** to the clip component **300**. In alternative embodiments (not shown), other structures may be used to secure the carriage instead of tabs, such as a clamping device, a locking pin, screws, or any other type of fastener.

In one embodiment, the clip component **300** can be affixed to the interior of a cured tire using a dual cure cement or dual cure gum. In other embodiments, other cements, gums, or adhesives may be used to bond the clip component **300** to the interior of the tire. In an alternative embodiment, the clip component **300** may be cured into the surface of the tire interior during a curing process. In further alternative embodiments, the clip component may be affixed to the surface of the tire interior using mechanical fasteners or magnets affixed to both the tire interior and the clip component.

The clip component **300** may be affixed to the interior of the tire at an affixation position selected by a designer. The affixation position may be selected based on properties of a specific tire type. For example, a tire may be tested to determine stresses, strains, vibrations, temperatures, and other characteristics at various locations during operation of the tire. A location with minimal stresses and strains may be a desirable affixation position, because such a location will minimize the stresses put on the mounting apparatus. Alternatively, a location with maximum stresses and strains may be a desirable affixation position, because an operator may wish to monitor a tire at a location where it is most likely to fail if operating conditions are too severe. Other desirable affixation positions will be apparent to those skilled in the art and include those positions at which an electronic device may transmit a signal to a receiver, without damage to the tire, the electronic device, or the mounting apparatus. The affixation location in the belt area may be a desirable location if the belt does not interfere with transmission.

FIG. 6 is a perspective view of an alternative embodiment of an attaching device and an alternative carriage **400**. In this embodiment, the attaching device includes a cylindrical locking clip **410** extending downwardly from the carriage **400** and a corresponding cylindrical locking ring **420** extending upwardly from an attaching device secured to an interior surface of a tire. Together, the locking clip **410** and the locking ring **420** form a secure locked connection when engaged with each other. Carriage **400** in this embodiment is shaped similarly to the carriage **100** of FIG. 1, but may take any other geometric shape in alternative embodiments (not shown).



## 5

Locking clip **410** is affixed to carriage **400**, and can be affixed as a separate piece or formed integrally with carriage **400**. Locking ring **420** is part of an attaching device that can be affixed to an interior surface of a tire via an adhesive, a magnet or other mechanical connection. Further, locking ring **420** can be cured with the tire to form an integral connection between locking ring **420** and the interior surface of the tire.

Locking clip **410** includes two ramps **430a** and **430b** that correspond with two ramps **440a** and **440b** of the locking ring **420**. Locking clip **410** is dimensioned to fit onto locking ring **420**, such that ramps **430a** and **430b** are aligned with **440a** and **440b**, respectively. When locking clip **410** is rotated, the ramps engage each other, and create a locking connection between the locking clip **410** and the locking ring **420**.

The ramps in this embodiment each individually cover approximately 25% of the circumference of the respective locking clip and locking ring. This corresponds to a 90° rotation for locking the locking clip into the locking ring. In alternative embodiments, the ramps may cover more or less of the circumference of the respective locking clip and locking ring, such that the locking clip can be rotated anywhere from 0 to 360 degrees to form a locking connection.

In alternative embodiments (not shown) the locking clip and locking ring may include more or fewer ramps, or no ramps. In an embodiment where no ramps are used, an alternative structure may be implemented to create a locking connection, such as a tab and slot or a spring loaded pin.

In another alternative embodiment (not shown), one of the locking clip and the locking ring may include tabs at the end of the respective ramps, and the other of the locking clip and the locking ring may include recesses configured to receive the tabs at the ends of the corresponding ramps. The tabs will fit into the recesses as the locking clip is rotated with the locking ring, to form a secure locking connection.

In still other alternative embodiments, the locking clip and locking ring are not cylindrical, and instead can take the form of any polygonal or non-polygonal shape.

The embodiment of FIG. 8 illustrates an alternative attaching device **510**, which utilizes a plurality of clips **520** to secure carriage **500**. Carriage **500** in this embodiment is substantially similar to the carriage **100** of FIG. 1, but may take any geometric shape. In this embodiment, the plurality of clips **520** fit through a plurality of holes located in carriage **500** to provide a secure connection. Clips **520** in this embodiment are mushroom-shaped clips, and each includes a cut-out portion along a diameter of the clip, with two protruding flanges **530** that can be bent elastically inward to fit through holes in the carriage **500**. Tabs **540** are located on top of flanges **530**, and are sized to fit through the holes in carriage **500** when the flanges are bent inwardly. Once the clips **520** are fit through holes, they can be released and will return to the state shown in FIG. 8. When in this state, the distance between each tab **540** on a single clip **520** is greater than the diameter of the carriage hole, so that the carriage **500** cannot be removed from the attaching device **510** unless the clips **520** are bent inwardly by a user.

When clips **520** are engaged with the carriage **500**, a gap **G** is formed between the bottom of tabs **540** and the top of the lower surface of carriage **500**. The holes of carriage **500** have a greater diameter than the clips **530**, and will cause play between the carriage **500** and the attaching device **510**. However, the holes in carriage **500** have a diameter less than the distance between tabs **540**, so that the carriage **500**

## 6

cannot be removed from attaching device **510** without manually bending the flanges **520**.

In alternative embodiments, there is no gap between the bottom of tabs **540** and a top of the lower surface of the carriage, such that  $G=0$ . In further alternative embodiments, the clips **520** may take a different form instead of mushroom clips. For example, the clips may be one-sided mushroom type clips, pins, lag bolt type fasteners, or other fasteners.

To the extent that the term “includes” or “including” is used in the specification or the claims, it is intended to be inclusive in a manner similar to the term “comprising” as that term is interpreted when employed as a transitional word in a claim. Furthermore, to the extent that the term “or” is employed (e.g., A or B) it is intended to mean “A or B or both.” When the applicants intend to indicate “only A or B but not both” then the term “only A or B but not both” will be employed. Thus, use of the term “or” herein is the inclusive, and not the exclusive use. See, Bryan A. Garner, A Dictionary of Modern Legal Usage 624 (2d. Ed. 1995). Also, to the extent that the terms “in” or “into” are used in the specification or the claims, it is intended to additionally mean “on” or “onto.” Furthermore, to the extent the term “connect” is used in the specification or claims, it is intended to mean not only “directly connected to,” but also “indirectly connected to” such as connected through another component or components.

While the present disclosure has been illustrated by the description of embodiments thereof, and while the embodiments have been described in considerable detail, it is not the intention of the applicants to restrict or in any way limit the scope of the appended claims to such detail. Additional advantages and modifications will readily appear to those skilled in the art. Therefore, the disclosure, in its broader aspects, is not limited to the specific details, the representative apparatus and method, and illustrative examples shown and described. Accordingly, departures may be made from such details without departing from the spirit or scope of the applicant's general inventive concept.

What is claimed is:

1. An assembly for mounting an electronics package to an interior of a tire, comprising:

a carriage having a base extending between two pairs of opposing sidewalls, thereby defining a recess configured to removably receive an electronics package, wherein a bottom of the carriage has a plurality of through holes;

an attaching device having a first side and a second side, the first side being permanently affixed to the interior of the tire, wherein the attaching device is configured to receive the carriage to form a secure and locked connection.

2. The assembly of claim 1, wherein the attaching device is a locking ring.

3. The assembly of claim 2, wherein the carriage further includes a locking clip that is configured to mate with the locking ring.

4. The assembly of claim 3, wherein the locking clip is configured to mate with the locking ring by rotating the locking clip with respect to the locking ring.

5. The assembly of claim 3, wherein the locking ring includes a first pair of ramps and the locking clip includes a second pair of ramps configured to engage the first pair of ramps.

6. The assembly of claim 5, wherein each of the first pair of rings covers 25% of a circumference of the locking ring.



7

7. The assembly of claim 5, wherein each of the second pair of rings covers 25% of a circumference of the locking clip.

8. The assembly of claim 1, further including an electronics package;

wherein a wall of the carriage includes a through hole;  
wherein the electronics package includes a through hole;  
and

wherein the electronics package is affixed to the carriage via a pin extending through the through hole of the wall of the carriage and the through hole of the electronics package.

9. An assembly for attaching an electronics package to a tire, comprising:

a carriage for receiving an electronics package;  
a locking clip affixed to and extending downwardly from the carriage; and

a locking ring having a first side permanently affixed to an interior of the tire, the locking ring being configured to engage the locking clip,

wherein the locking ring includes a first pair of ramps extending therefrom,

wherein the first pair of ramps extends outwards from the locking ring, and

wherein the locking clip includes a second pair of ramps.

10. The assembly of claim 9, wherein the locking clip is configured to fit onto the locking ring.

11. The assembly of claim 9, further comprising an electronics package;

8

wherein a sidewall of the carriage includes a through hole;  
wherein the electronics package includes a through hole;  
and

wherein the electronics package is fastened to the carriage via a pin extending through the through hole of the sidewall of the carriage and the through hole of the electronics package.

12. The assembly of claim 9, wherein the second pair of ramps extends inwards from the locking clip.

13. An assembly for mounting a component to an interior of a tire, the assembly comprising:

a locking ring having a first side and a second side, wherein the first side of the locking ring is affixed to the interior of the tire, and wherein the locking ring includes a first pair of ramps extending outwardly from the locking ring;

a locking clip configured to fit onto the locking ring, wherein the locking clip includes a second pair of ramps, each of the second pair of ramps being configured to engage one of the first pair of ramps of the locking ring.

14. The assembly of claim 13, wherein the component is a carriage configured to receive an electronics package.

15. The assembly of claim 14, wherein the carriage is separable from the locking clip.

16. The assembly of claim 13, wherein the second pair of ramps extends inwards from the locking clip.

\* \* \* \* \*