

US011377905B2

(12) **United States Patent**
Colson et al.

(10) **Patent No.: US 11,377,905 B2**
(45) **Date of Patent: *Jul. 5, 2022**

(54) **METHODS AND APPARATUS TO CONTROL AN ARCHITECTURAL OPENING COVERING ASSEMBLY**

(71) Applicant: **Hunter Douglas Inc.**, Pearl River, NY (US)

(72) Inventors: **Wendell B. Colson**, Weston, MA (US);
Daniel M. Fogarty, Framingham, MA (US)

(73) Assignee: **HUNTER DOUGLAS INC.**, Pearl River, NY (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **16/805,045**

(22) Filed: **Feb. 28, 2020**

(65) **Prior Publication Data**

US 2020/0199934 A1 Jun. 25, 2020

Related U.S. Application Data

(63) Continuation of application No. 15/205,816, filed on Jul. 8, 2016, now Pat. No. 10,590,701, which is a
(Continued)

(51) **Int. Cl.**
E06B 9/72 (2006.01)
E06B 9/42 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **E06B 9/72** (2013.01); **E06B 9/42** (2013.01); **E06B 9/68** (2013.01); **E06B 9/50** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC **E06B 9/72**; **E06B 2009/6818**; **E06B 2009/6845**; **E06B 9/42**; **E06B 9/68**;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,186,473 A 6/1965 Myers
4,372,367 A 2/1983 Baldanello et al.

(Continued)

FOREIGN PATENT DOCUMENTS

CN 1331945 1/2002
CN 1981311 6/2007

(Continued)

OTHER PUBLICATIONS

Patent Cooperation Treaty, "International Search Report", issued in connection with Application No. PCT/US2012/000429, dated Dec. 17, 2012, 3 pages.

(Continued)


Primary Examiner — Thai T Dinh

(74) *Attorney, Agent, or Firm* — Kilpatrick Townsend & Stockton LLP

(57) **ABSTRACT**

Methods and apparatus to control an architectural opening covering assembly are disclosed herein. An example system includes a first architectural opening covering assembly to identify a first position of a first covering as a first reference position in response to a first command to store a first speed at which the first assembly is to be driven. The first assembly is to operate a first motor to move the first covering at the first stored speed in response to a second command. The example system includes a second architectural opening covering assembly to store a second speed at which the second covering is to be driven in response to a third command. The second assembly is to operate a second motor at the second stored speed in response to a fourth command to move the second covering.

20 Claims, 6 Drawing Sheets



Related U.S. Application Data

continuation of application No. 14/213,188, filed on Mar. 14, 2014, now Pat. No. 9,399,888.

- (60) Provisional application No. 61/786,228, filed on Mar. 14, 2013.

- (51) **Int. Cl.**
E06B 9/68 (2006.01)
E06B 9/50 (2006.01)

- (52) **U.S. Cl.**
 CPC *E06B 2009/6818* (2013.01); *E06B 2009/6845* (2013.01); *E06B 2009/6872* (2013.01)

- (58) **Field of Classification Search**
 CPC E06B 2009/405; E06B 9/40; E06B 9/70; E06B 9/82
 See application file for complete search history.

- (56) **References Cited**

U.S. PATENT DOCUMENTS

4,413,665	A	11/1983	Corcoran	
4,519,554	A	5/1985	Dussoliet et al.	
4,766,941	A	8/1988	Sloop et al.	
4,794,715	A	1/1989	Cherwin	
4,807,686	A	2/1989	Schnebly et al.	
5,547,009	A	8/1996	Plumer	
5,671,387	A	9/1997	Jacobs et al.	
5,848,634	A	12/1998	Will et al.	
6,158,563	A	12/2000	Welfonder et al.	
6,259,218	B1	7/2001	Kovach et al.	
6,341,638	B1	1/2002	Thompson et al.	
6,346,889	B1	2/2002	Moss	
6,497,267	B1	12/2002	Azar et al.	
6,571,853	B1	6/2003	Ciuca et al.	
6,680,594	B2	1/2004	Collett et al.	
6,810,997	B2	11/2004	Schreiber et al.	
6,843,301	B2	1/2005	Carrillo et al.	
6,843,303	B2	1/2005	Siak et al.	
6,859,004	B2	2/2005	Hormann	
7,466,090	B2	12/2008	Meewis et al.	
7,599,612	B2	10/2009	Moseley et al.	
8,125,167	B1 *	2/2012	Mullet	E05F 15/70 318/265
8,299,734	B2	10/2012	Mullet et al.	
8,339,085	B2	12/2012	Feldstein et al.	
8,339,086	B2 *	12/2012	Feldstein	E06B 9/42 318/470
8,368,328	B2	2/2013	Mullet et al.	
8,575,872	B2	11/2013	Mullet et al.	
8,659,246	B2	2/2014	Mullet et al.	
8,692,498	B2 *	4/2014	Feldstein	E06B 9/72 318/470
8,791,658	B2	7/2014	Mullet et al.	
8,853,973	B2 *	10/2014	Lagarde	E06B 9/68 318/101
8,947,027	B2	2/2015	Mullet et al.	
9,018,868	B2	4/2015	Lucas et al.	
9,152,032	B2	10/2015	Mullet et al.	
9,194,179	B2	11/2015	Mullet et al.	
9,249,623	B2	2/2016	Mullet et al.	
9,376,862	B2	6/2016	Mullet et al.	
9,376,863	B2	6/2016	Mullet et al.	
9,394,743	B2	7/2016	Mullet et al.	
9,410,369	B2	8/2016	Mullet et al.	
9,611,690	B2	4/2017	Mullet et al.	
9,725,948	B2	8/2017	Mullet et al.	
9,725,952	B2	8/2017	Mullet et al.	
9,745,797	B2	8/2017	Mullet et al.	
9,771,755	B2	9/2017	Mullet et al.	
9,790,739	B2 *	10/2017	Colson	E06B 9/50
9,890,585	B2	2/2018	Mullet et al.	

9,896,882	B2	2/2018	Mullet et al.	
10,246,938	B2	4/2019	Mullet et al.	
10,590,701	B2	3/2020	Colson et al.	
2004/0011477	A1 *	1/2004	Walker	E06B 9/68 160/168.1 P
2005/0173080	A1 *	8/2005	Carmen	E06B 9/68 160/310
2005/0253710	A1	11/2005	Eskildsen	
2007/0273309	A1	11/2007	Carmen	
2007/0295460	A1 *	12/2007	Carmen	E06B 9/68 160/310
2008/0052034	A1	2/2008	David et al.	
2008/0283200	A1	11/2008	Hummel et al.	
2008/0313299	A1 *	12/2008	Ebbe	H04W 8/26 709/208
2009/0256021	A1	10/2009	Dorrough	
2010/0018654	A1	1/2010	Skinner et al.	
2010/0087958	A1 *	4/2010	Mullet	G05B 19/0421 700/279
2011/0048655	A1	3/2011	Andreasen et al.	
2011/0061818	A1 *	3/2011	Geriniere	E06B 9/68 160/168.1 P
2011/0203748	A1	8/2011	Mullet et al.	
2014/0262078	A1 *	9/2014	Colson	E06B 9/68 160/310
2016/0319597	A1	11/2016	Colson et al.	

FOREIGN PATENT DOCUMENTS

CN	101449018	6/2009
CN	102333469	1/2012
DE	29818023	12/1998
DE	202011051106	9/2011
EP	0783072	7/1997
EP	0838574	4/1998
EP	0940553	9/1999
EP	2192249	6/2010
JP	8199950	8/1996
JP	1046961	2/1998
JP	2002070465	3/2002
JP	2004237362	8/2004
WO	2010011751	1/2010
WO	2011106397	9/2011
WO	2011106398	9/2011
WO	2013059037	4/2013
WO	2014062504	4/2014
WO	2014169173	10/2014

OTHER PUBLICATIONS

Patent Cooperation Treaty, "Written Opinion of the International Searching Authority", issued in connection with Application No. PCT/US2012/000429, dated Dec. 17, 2012, 5 pages.

Patent Cooperation Treaty, "International Search Report", issued in connection with Application No. PCT/US2012/000428, dated Dec. 21, 2012, 2 pages.

Patent Cooperation Treaty, "Written Opinion of the International Searching Authority", issued in connection with Application No. PCT/US2012/000428, dated Dec. 21, 2012, 6 pages.

Patent Cooperation Treaty, "International Preliminary Report on Patentability", issued in connection with Application No. PCT/US2011/038469, dated Dec. 13, 2012, 10 pages.

Patent Cooperation Treaty, "International Search Report", issued in connection with Application No. PCT/US2011/038469, dated Sep. 23, 2011, 4 pages.

Patent Cooperation Treaty, "Written Opinion of the International Searching Authority", issued in connection with Application No. PCT/US2011/038469, dated Sep. 23, 2011, 7 pages.

United States Patent and Trademark Office, "Non-Final Office Action", issued in connection with U.S. Appl. No. 14/213,188, dated Sep. 16, 2015 (16 pages).

United States Patent and Trademark Office, "Notice of Allowance", issued in connection with U.S. Appl. No. 14/213,188, dated Mar. 24, 2016 (8 pages).

(56)

References Cited

OTHER PUBLICATIONS

United States Patent and Trademark Office, “Non-Final Office Action”, issued in connection with U.S. Appl. No. 14/044,832, dated May 19, 2016, 38 pages.

International Searching Authority, “International Preliminary Report on Patentability”, issued in connection with international application No. PCT/US2014/028534, dated Sep. 15, 2015, 6 pages.

IP Australia, “Examination report No. 2 for standard patent application”, issued in connection with AU Application No. 2014236413, dated Dec. 20, 2017, 4 pages.

State Intellectual Property Office, English translation of “Search Report”, issued in connection with Chinese Patent Application No. 2014800056062, dated May 25, 2017, 1 page.

United States Patent and Trademark Office, “Non-Final Office Action”, issued in connection with U.S. Appl. No. 15/205,816, dated Feb. 8, 2018, 25 pages.

United States Patent and Trademark Office, “Final Office Action”, issued in connection with U.S. Appl. No. 15/205,816, dated Nov. 16, 2018, 14 pages.

United States Patent and Trademark Office, “Advisory Action”, issued in connection with U.S. Appl. No. 15/205,816, dated Feb. 14, 2019, 5 pages.

United States Patent and Trademark Office, “Non-Final Office Action”, issued in connection with U.S. Appl. No. 15/205,816, dated Mar. 28, 2019, 13 pages.

United States Patent and Trademark Office, “Final Office Action”, issued in connection with U.S. Appl. No. 15/205,816, dated Aug. 8, 2019, 14 pages.

United States Patent and Trademark Office, “Notice of Allowance and Fee(s) Due”, issued in connection with U.S. Appl. No. 15/205,816, dated Oct. 17, 2019, 7 pages.

United States Patent and Trademark Office, “Corrected Notice of Allowability”, issued in connection with U.S. Appl. No. 15/205,816, dated Feb. 3, 2020, 2 pages.

* cited by examiner





FIG. 1







Fig. 3






FIG. 5




FIG. 6

METHODS AND APPARATUS TO CONTROL AN ARCHITECTURAL OPENING COVERING ASSEMBLY

RELATED APPLICATIONS

This patent arises from a continuation of U.S. patent application Ser. No. 15/205,816 (now U.S. Pat. No. 10,590,701), titled "METHODS AND APPARATUS TO CONTROL AN ARCHITECTURAL OPENING COVERING ASSEMBLY," filed Jul. 8, 2016, which is a continuation of U.S. patent application Ser. No. 14/213,188 (now U.S. Pat. No. 9,399,888), titled "METHODS AND APPARATUS TO CONTROL AN ARCHITECTURAL OPENING COVERING ASSEMBLY," filed Mar. 14, 2014, which claims the benefit of U.S. Provisional Application No. 61/786,228, titled "METHODS AND APPARATUS TO CONTROL AN ARCHITECTURAL OPENING COVERING ASSEMBLY," filed Mar. 14, 2013. U.S. patent application Ser. No. 15/205,816; U.S. patent application Ser. No. 14/213,188; and U.S. Provisional Application No. 61/768,228 are hereby incorporated by reference in their entireties.

FIELD OF THE DISCLOSURE

This disclosure relates generally to architectural opening covering assemblies and, more particularly, to methods and apparatus to control an architectural opening covering assembly.

BACKGROUND

Architectural opening covering assemblies such as roller blinds provide shading and privacy. Such assemblies generally include a motorized roller tube connected to covering fabric or other shading material. As the roller tube rotates, the fabric winds or unwinds around the tube to uncover or cover an architectural opening.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an isometric illustration of an example architectural opening covering assembly in which aspects of the present disclosure may be implemented.

FIG. 2 is a side, schematic view of an example first architectural opening covering assembly and an example second architectural opening covering assembly having coverings at the same speed setting position.

FIG. 3 is a side, schematic view of the example first architectural opening covering assembly and the example second architectural opening covering assembly of FIG. 2 having coverings at different speed setting positions.

FIG. 4 is a block diagram of an example controller disclosed herein, which may be used to control operation of the example architectural opening covering assembly of FIG. 1, the example first architectural opening covering assembly of FIGS. 2-3 and/or the example second architectural opening covering assembly of FIGS. 2-3.

FIG. 5 is a flowchart representative of example machine readable instructions for implementing the example controller of FIG. 4.

FIG. 6 is a block diagram of an example processor platform to execute the machine readable instructions of FIG. 5 to implement the example controller of FIG. 4.

The figures are not to scale. Instead, to clarify multiple layers and regions, the thickness of the layers may be enlarged in the drawings. Wherever possible, the same

reference numbers will be used throughout the drawing(s) and accompanying written description to refer to the same or like parts. As used in this patent, stating that any part (e.g., a layer, film, area, or plate) is in any way positioned on (e.g., positioned on, located on, disposed on, or formed on, etc.) another part, means that the referenced part is either in contact with the other part, or that the referenced part is above the other part with one or more intermediate part(s) located therebetween. Stating that any part is in contact with another part means that there is no intermediate part between the two parts.

DETAILED DESCRIPTION

Methods and apparatus to control an architectural opening covering assembly are disclosed herein. An example method disclosed herein includes determining a position of a covering of an architectural opening covering assembly, and determining a speed at which the covering is to move via a motor based on the position and a period of time. The example method also includes operating the motor to move the covering at the speed.

An example tangible computer readable storage medium disclosed herein includes instructions that, when executed, cause a machine to at least determine a distance of a portion of a covering of an architectural opening covering assembly from a reference position and determine a speed at which the covering is to move via a motor based on the distance and a period of time. The example instructions also cause the machine to at least operate the motor to move the covering at the speed.

An example apparatus disclosed herein includes a motor operatively coupled to a tube of an architectural opening covering assembly. The example tube is to support an architectural opening covering. The example apparatus also includes a sensor to determine an angular position of the tube. The example apparatus further includes a controller to determine a speed at which the motor is to rotate the tube based on the angular position of the tube and a period of time.

An example controller of an architectural opening covering assembly is disclosed herein. The example architectural opening covering assembly includes a motor to rotate a tube, and a covering at least partially wound around the tube. The example controller includes a motor controller to control the motor. The example controller also includes a tube angular position determiner to determine an angular position of the tube. The example controller further includes a tube rotational speed determiner to determine a speed at which the motor is to rotate the tube based on a period of time and the angular position of the tube relative to a reference position.

Example architectural opening covering assemblies disclosed herein may be controlled by one or more controllers. In some examples, a controller is communicatively coupled to a motor, which rotates a tube to wind or unwind (e.g., raise or lower) a covering wound at least partially around the tube. The example controllers disclosed herein control speeds at which the coverings move via the motors based on visual appearances of the architectural opening covering assemblies during a speed setting mode. For example, some example controllers disclosed herein enable the speeds at which the coverings are moved via the motors (e.g., rotational speeds at which motors rotate the tubes to wind or unwind the coverings) to be established (e.g., determined and/or set) based on a position of the covering relative to a reference position (e.g., a fully unwound position of the covering, a lower limit position of the covering, an upper

limit position of the covering, etc.). When some example controllers disclosed herein are in the speed setting mode, the positions of the coverings may be individually adjusted via input devices to desired positions (e.g., speed setting positions). For example, the position of the covering may be adjusted by control of the motor, operation of manual controls such as pull cords, physically positioning the covering by raising or pulling on the covering, and so forth. Based on the desired positions of the coverings, the controllers determine and/or set the speeds at which the motors are to move the coverings.

For example, if each of the coverings are moved to substantially the same position (e.g., a given distance from the fully unwound positions of the coverings), the controllers establish substantially the same speed at which the coverings are to move during operation (e.g., even if the tubes on which the coverings are wound are different sizes). In this manner, a plurality of example architectural opening covering assemblies disclosed herein may be coordinated to move their coverings in unison. In some examples, if the positions of the coverings are moved to different positions, the controllers establish different speeds at which the motors are to move the tubes and, thus, the coverings during operation. For example, if a first covering is moved to a first position that is three times as far from a reference position as a second position of a second covering, the motor operatively coupled to the first covering may move the first covering three times faster than a motor operatively coupled to the second covering.

FIG. 1 is an isometric illustration of an example architectural opening covering assembly 100 in accordance with the teachings of this disclosure. The example architectural opening covering assembly 100 of FIG. 1 is merely an example and, thus, other architectural opening covering assemblies may be used to implement the example methods and/or apparatus disclosed herein. For example, the architectural opening covering assemblies described in the following applications may be used: U.S. Provisional Application Ser. No. 61/542,760, entitled "CONTROL OF ARCHITECTURAL OPENING COVERINGS," filed Oct. 3, 2011; U.S. Provisional Application Ser. No. 61/648,011, entitled "METHODS AND APPARATUS TO CONTROL ARCHITECTURAL OPENING COVERING ASSEMBLIES," filed May 16, 2012; International Application No. PCT/US2012/000428, entitled "METHODS AND APPARATUS TO CONTROL ARCHITECTURAL OPENING COVERING ASSEMBLIES," filed on Oct. 3, 2012; and U.S. International Application No. PCT/US2012/000429, entitled "METHODS AND APPARATUS TO CONTROL ARCHITECTURAL OPENING COVERING ASSEMBLIES," filed on Oct. 3, 2012, the disclosures of which are hereby incorporated herein by reference in their entirety.

In the example of FIG. 1, the covering assembly 100 includes a headrail 108. The headrail 108 is a housing having opposed end caps 110, 111 joined by front 112, back 113 and top sides 114 to form an open bottom enclosure. The headrail 108 also has mounts 115 for coupling the headrail 108 to a structure above or behind an architectural opening such as a wall via mechanical fasteners such as screws, bolts, etc. A roller tube 104 is disposed between the end caps 110, 111. Although a particular example of a headrail 108 is shown in FIG. 1, many different types and styles of headrails exist and could be employed in place of the example headrail 108 of FIG. 1. Indeed, if the aesthetic effect of the headrail 108 is not desired, it can be eliminated in favor of mounting brackets.

In the example illustrated in FIG. 1, the architectural opening covering assembly 100 includes a covering 106, which is a cellular type of shade. In this example, the covering 106 includes a unitary flexible fabric (referred to herein as a "backplane") 116 and a plurality of cell sheets 118 that are secured to the backplane 116 to form a series of cells. The cell sheets 118 may be secured to the backplane 116 using any desired fastening approach such as adhesive attachment, sonic welding, weaving, stitching, etc. The covering 106 shown in FIG. 1 can be replaced by any other type of covering including, for instance, single sheet shades, blinds, other cellular coverings, and/or any other type of covering. In the illustrated example, the covering 106 has an upper edge mounted to the roller tube 104 and a lower, free edge. The upper edge of the example covering 106 is coupled to the roller tube 104 via a chemical fastener (e.g., glue) and/or one or more mechanical fasteners (e.g., rivets, tape, staples, tacks, etc.). The covering 106 is movable between a raised position and a lowered position (illustratively, the position shown in FIG. 1). When in the raised position, the covering 106 is wound about the roller tube 104.

The example architectural opening covering assembly 100 is provided with a motor 120 to move the covering 106 between the raised and lowered positions. The example motor 120 is controlled by a controller 122. In the illustrated example, the controller 122 and the motor 120 are disposed inside the tube 104 and communicatively coupled via a wire 124. Alternatively, the controller 122 and/or the motor 120 may be disposed outside of the tube 104 (e.g., mounted to the headrail 108, mounted to the mounts 115, located in a central facility location, etc.) and/or communicatively coupled via a wireless communication channel. As described in greater detail below, the example controller 122 controls speeds at which the covering 106 moves relative to an architectural opening.

The example architectural opening covering assembly 100 of FIG. 1 includes a tube angular position sensor 126 communicatively coupled to the controller 122. In the illustrated example, the tube angular position sensor 126 is a gravitational sensor (e.g., an accelerometer, the gravitational sensor made by Kionix® as part number KXTC9-2050, etc.). In other examples, the tube angular position sensor may include one or more other types of sensors (e.g., a potentiometer, a Hall Effect type sensor, a resolver, a rotary encoder employing, for example, light, a magnet, and/or any other type of angular position sensor). The example tube angular position sensor 126 of FIG. 1 is coupled to the tube 104 via a mount 128 to rotate with the tube 104. In the illustrated example, the tube angular position sensor 126 is disposed inside the tube 104 along an axis of rotation 130 of the tube 104 such that an axis of rotation of the tube angular position sensor 126 is substantially coaxial to the axis of rotation 130 of the tube 104. In the illustrated example, a central axis of the tube 104 is substantially coaxial to the axis of rotation 130 of the tube 104, and a center of the tube angular position sensor 126 is on (e.g., substantially coincident with) the axis of rotation 130 of the tube 104. In other examples, the tube angular position sensor 126 is disposed in other locations such as, for example, on an interior surface 132 of the tube 104, on an exterior surface 134 of the tube 104, on an end 136 of the tube 104, on the covering 106, and/or any other suitable location. The example tube angular position sensor 126 generates tube position information, which is used by the controller 122 to determine an angular position of the tube 104 and/or monitor movement of the tube 104 and, thus, the covering 106. In some examples, the

5

tube position information includes values corresponding to a position of the covering **106**. In some examples, the controller **122** controls an angular position of the tube **104** and/or a speed of rotation of the tube **104** based on the tube position information.

In some examples, the architectural opening covering assembly **100** is operatively coupled to an input device **138**, which may be used to automatically and/or selectively move the covering **106** between the raised and lowered positions. In some examples, the input device **138** sends a signal to the controller **122** to enter a programming mode (e.g., a speed setting mode) in which a speed of rotation of the tube **104** is determined, set and/or recorded. In some examples, one or more positions (e.g., a lower limit position, an upper limit position, a position between the lower limit position and the upper limit position, etc.) of the covering **106** are determined and/or recorded when the controller **122** enters the program mode. In the case of an electronic signal, the signal may be sent via a wired or wireless connection.

In some examples, the input device **138** is a mechanical input device such as, for example, a cord, a lever, a crank, and/or an actuator coupled to the motor **120** and/or the tube **104** to apply a force to rotate the tube **104**. In some examples, the input device **138** is implemented by the covering **106** and, thus, the input device **138** is eliminated (e.g., the covering **106** is lowered by pulling the covering **106** downward and the covering **106** is raised by lifting the covering **106**). In some examples, the input device **138** is an electronic input device such as, for example, a switch, a light sensor, a computer, a central controller, a smartphone, and/or any other device capable of providing instructions to the motor **120** and/or the controller **122** to raise or lower the covering **106**. In some examples, the input device **138** is a remote control, a smart phone, a laptop, and/or any other portable communication device, and the controller **122** includes a receiver to receive signals from the input device **138**. Some example architectural opening covering assemblies include other numbers of input devices (e.g., 0, 2, etc.).

In some examples, the input device **138** is disposed on the architectural opening covering assembly **100**. In other examples, the input device **138** is not disposed on the architectural opening covering assembly **100** (e.g., the input device **138** is disposed in a control room of a building in which the architectural opening covering assembly **100** is employed) and is remotely communicatively coupled to the controller **122** via, for example, wires, a wireless transmitter, and/or other manner. The example architectural opening covering assembly **100** may include any number and combination of input devices.

In some examples, a speed at which the covering **106** is raised and/or lowered via the motor **120** is determined, set and/or recorded (e.g., stored in a memory) during a speed setting mode (e.g., a programming or calibration mode). The example controller **122** of FIG. 1 enters the speed setting mode in response to a first command from the input device **138**. When the example controller **122** is in the speed setting mode, a user may move (e.g., raise or lower) the covering **106** to a desired position (e.g., a speed setting position) a given distance away from a reference position such as, for example, a fully unwound position, a lower limit position, an upper limit position, a previously stored position, and/or any other position. In some examples, the reference position is determined during the speed setting mode. In other examples, the reference position is previously determined and/or recorded during, for example, a programming mode described in U.S. Provisional Application Ser. No. 61/648, 011, International Application No. PCT/US2012/000428,

6

and/or U.S. International Application No. PCT/US2012/000429. The example controller **122** monitors the angular positions of the tube **104** based on the tube position information generated by the example tube angular position sensor **126** to determine the position of the covering **106** as the covering **106** is moved to the speed setting position.

In response to a second command from the input device **138**, the example controller **122** establishes (e.g., determines, sets and/or records) a speed at which the motor **120** is to rotate the tube **104** based on the speed setting position of the covering **106**. In some examples, the rotational speed of the tube **104** is determined by dividing a number of rotations of the tube **104** from the reference position to the speed setting position by a predetermined value. For example, the predetermined value may be an amount of time over which the covering **106** is to move the distance from the reference position to the speed setting position (e.g., ten seconds, twenty seconds, etc.). For example, if the speed setting position is ten revolutions of the tube **104** away from the reference position and the predetermined amount of time is 15 seconds, the controller **122** determines, sets and/or stores the rotational speed at which the motor **120** is to rotate the tube **104** to be ten revolutions per fifteen seconds (i.e., 40 revolutions per minute). As a result, during operation of the example architectural opening covering assembly **100** of FIG. 1, the example covering **106** raises and/or lowers at a speed corresponding to 40 revolutions of the tube **104** per minute.

FIG. 2 is a side, schematic view of a first architectural opening covering assembly **200** and a second architectural opening covering assembly **202** disclosed herein. The example architectural opening covering assembly **200** and/or the example architectural opening covering assembly **202** may be implemented using the example architectural opening covering of FIG. 1. The example architectural opening covering assemblies **200**, **202** may be located in the same room or building, positioned along a wall, and/or any other locations. As described in greater detail below, the example first architectural opening covering assembly **200** and the example second architectural opening covering assembly **202** are different sizes but are otherwise substantially similar.

In the illustrated example, the architectural opening covering assemblies **200**, **202** of FIG. 2 each include the following: a covering **204**, **206** at least partially wound about a tube **208**, **210**; a motor **212**, **214** operatively coupled to the tube **208**, **210**; and a controller **216**, **218** to control the motor **212**, **214**. The example coverings **204**, **206** each include an end rail **220**, **222** to provide stability to the example coverings **204**, **208**. The example architectural opening covering assemblies **200**, **202** are each supported by a frame **226**, **228** having a sill extending from the frame **226**, **228** into a path of the end rail **222**, **224**. For example, if the coverings **204**, **206** are lowered a given distance, the end rails **220**, **224** of the coverings **204**, **206** contact the sills **230**, **232**, respectively.

In the illustrated example, the sills **230**, **232** are at substantially similar heights relative to, for example, a floor. However, the example architectural opening covering assemblies **200**, **202** of FIG. 2 are different sizes. For example, in the illustrated example, a first radius **234** of the tube **208** of the first architectural opening covering assembly **200** is less than a second radius **236** of the tube **210** of the example second architectural opening covering assembly **202**. In some examples, an amount of the covering **204** wound around the tube **208** (e.g., a number of layers formed by the covering **204** wound around the tube **208**) and/or a

thickness of the covering **204** (e.g., a sheet thickness) is different than an amount of the covering **206** wound around the tube **210** and/or a thickness of the covering **206**. Also, the example frames **226**, **228** support the example architectural opening covering assemblies **200**, **202** at different heights (e.g., axes of rotation of the first tube **208** and the second tube **210** are at different distances from the respective sills **230**, **232**). In other examples, the frames **226**, **228** and/or the architectural opening covering assemblies **200**, **202** are substantially the same size, supported at substantially the same height and/or the coverings **204**, **206** have substantially the same thickness.

The example architectural opening covering assemblies **200**, **202** include a local input device **238**, **240**. In the illustrated example, the local input devices **238**, **240** are substantially similar to the example input device **138** of FIG. 1. Thus, the example local input devices **238**, **240** may be input devices operatively coupled to the tubes **208**, **210** and/or the motors **212**, **214** (e.g., a cord, crank, actuator, etc.) and/or input devices communicatively coupled to the controllers **216**, **218** and/or the motors **212**, **214** (e.g., a switch, a remote control, etc.), respectively, that enable a user to operate the respective architectural opening covering assemblies **200**, **202** (e.g., a user may raise and/or lower the covering **304** via the local input device **238**, and the user may raise or lower the covering **206** via the local input device **240**).

The example controllers **216**, **218** of FIG. 2 are substantially similar to and/or may be implemented using the example controller **122** of FIG. 1. Thus, the example controllers **216**, **218** of FIG. 2 monitor angular positions of the tubes **208**, **210** via tube angular position sensors **242**, **244** (e.g., gravitational sensors and/or any other type of angular position sensors), determine positions of the coverings **204**, **206**, determine rotational speeds of the tubes **208**, **210**, etc. In the illustrated example, the example controllers **216**, **218** are communicatively coupled to a central input device **246** such as, for example an input device similar to or identical to the example input device **138** of FIG. 1. In some examples, the central input device **246** is located remotely relative to the architectural opening covering assemblies **200**, **202** of FIG. 2. For example, the central input device **246** may be located in a different room than one or both of the architectural opening covering assemblies **200**, **202**.

In the illustrated example, the controllers **216**, **218** receive a first command from the central input device **246** to enter a speed setting mode. In some examples, the first command is transmitted in response to a user action (e.g., pressing a button). In the illustrated example, the speeds at which the coverings **204**, **206** are to move during operation are independently established while each of the controllers **216**, **218** are in the speed setting mode. In some examples, a user may coordinate the speeds at which the coverings **204**, **206** are to move during operation based on visual appearances of the respective architectural opening covering assemblies **200**, **202** such as, for example, distances of the end rails **222**, **224** from the sills **230**, **232**, a distance between the end rail **222** and the end rail **224**, and/or other positions of the coverings **204**, **206**. For example, the coverings **204**, **206** may be horizontally aligned to establish substantially the same speed at which the coverings **204**, **206** are to move during operation or the coverings **206**, **206** may be spaced apart vertically to establish different speeds at which the coverings **204**, **206** are to move during operation.

In the illustrated example, the reference positions of the coverings **204**, **206** are lower limit positions. In other examples, the reference positions are other positions (e.g.,

upper limit positions, fully unwound positions, and/or any other positions). In the illustrated example, the lower limit positions and thus, the reference positions of the coverings **204**, **206** are positions of the coverings **204**, **206** at which the end rails **222**, **224** contact the sills **230**, **232**, respectively. Further, while the example coverings **204**, **206** of FIG. 2 have substantially the same reference position, in other examples the coverings **204**, **206** have different reference positions from each other. For example, the reference position utilized by the example controller **216** may be the lower limit position of the covering **204**, and the reference position utilized by the controller **218** may be the upper limit position of the covering **206**. In some examples, the reference positions are established during the speed setting mode. In other examples, the reference positions are previously established during a programming mode such as one or more of the programming modes described in U.S. Provisional Application Ser. No. 61/648,011, International Application No. PCT/US2012/000428, and/or U.S. International Application No. PCT/US2012/000429.

While the example controllers **216**, **218** are in the speed setting mode, the coverings **204**, **206** may be moved to speed setting positions that are desired distances away from the reference positions. For example, the user may operate the local input devices **238**, **240** to move the coverings **204**, **206** relative to the reference positions. In some examples, the controllers **216**, **218** monitor movement and/or angular positions of the tubes **208**, **210**, respectively (e.g., relative to the reference position and/or other position(s)), in a manner similar or identical to the example controller **122** of FIG. 1 disclosed above and/or in a manner described in U.S. Provisional Application Ser. No. 61/648,011, International Application No. PCT/US2012/000428, and/or U.S. International Application No. PCT/US2012/000429. In the illustrated example, the controllers **216**, **218** determine the speed setting positions based on the angular positions of the tubes **208**, **210** when the central input device **246** communicates a second command. The coverings **204**, **206** illustrated in FIG. 2 are in speed setting positions a first distance **D1** away from the sills **230**, **232**, respectively. Thus, in the illustrated example, the speed setting positions of the coverings **204**, **206** are substantially the same distance away from the respective reference positions of the coverings **204**, **206**.

Once the example controllers **216**, **218** receive the second command from the example central input device **246** (e.g., in response to a user action), the controllers **216**, **218** establish the speeds at which the example coverings **204**, **206** are to be moved via the motors **212**, **214** during operation. In the illustrated example, the controllers **216**, **218** establish the speeds based on the speed setting positions of the coverings **204**, **206**. In the illustrated example, the controller **216** of the first architectural opening covering assembly **200** determines that the covering **204** is to move at a speed substantially equivalent to moving the first distance **D1** in a predetermined amount of time (e.g., 15 seconds, 20 seconds, 30 seconds, etc.). Likewise, the controller **218** of the second architectural opening covering assembly **202** determines that the covering **206** is to move at a speed substantially equivalent to the first distance **D1** in the predetermined amount of time. For example, if the predetermined amount of time is ten seconds and the first distance **D1** is one foot, the controllers **216**, **218** determine that the coverings **204**, **206** are to be moved via the motors **212**, **214** (e.g., be raised or lowered by the motor **212**, **214**) at a speed of approximately one foot per ten seconds.

Although the same predetermined amount of time is used by the controller **216** of the first architectural opening

covering assembly **200** and the controller **218** of the second architectural opening covering assembly **202** of FIG. **2** in the illustrated example, in other examples the first controller **216** and the second controller **218** use different predetermined amounts of time to determine the speeds at which the coverings **204**, **206**, respectively, are to move during operation. In some examples, the predetermined amounts of time are established during the example speed setting mode. In other examples, the controller **216** and/or the controller **218** utilizes one or more previously stored predetermined amounts of time.

In some examples, the controllers **216**, **218** determine the speeds based on a number of revolutions of the tubes **208**, **210** corresponding to the first distance **D1**. For example, if the controller **216** of the first architectural opening covering assembly **200** determines that the first distance **D1** corresponds to one revolution of the tube **208** (e.g., the tube **208** in the speed setting position is one revolution away from the reference position), the controller **216** determines that a rotational speed at which the motor **212** is to rotate the tube **208** is one revolution per ten seconds. If the example controller **218** of the second architectural opening covering assembly **202** determines that the first distance **D1** corresponds to 0.75 revolutions of the tube **210** (e.g., the tube **210** in the speed setting position is 0.75 revolutions away from the reference position), the controller **218** determines that a rotational speed at which the motor **214** is to rotate the tube **210** is 0.75 revolution per ten second. In some examples, the controllers **216**, **218** determine the speeds of the coverings **204**, **206** in other units of measurement (e.g., revolutions per minute, etc.).

Thus, by positioning the coverings **204**, **206** of the example architectural opening covering assemblies **200**, **202** of FIG. **2** to desired positions during the speed setting mode, the speeds at which the coverings **204**, **204** are to move during operation of the example architectural opening covering assemblies **200**, **202** are configured. In the illustrated example of FIG. **2**, by aligning the example rails **222**, **224** of the coverings **204**, **206** to the same height during the speed setting mode, the speeds at which the coverings **204**, **206** will move during operation will substantially match. More specifically, in the illustrated example, by moving the coverings **204**, **206** to the same speed setting positions during the speed setting mode, the motors **212**, **214** rotate the differently sized tubes **208**, **210** at different speeds to raise and lower the coverings **204**, **206** at substantially the same speed. As a result, the coverings **204**, **206** may move substantially in unison in response to a command from the central input device **246** to move the coverings **204**, **206** to a given position (e.g., an upper limit position, a lower limit position, an intermediate position, etc.). In this manner, the user may coordinate the speeds at which coverings of a plurality of architectural opening covering assemblies (e.g., located along a side of a building, in a room, etc.) raise and lower based on the visual appearance (e.g., covering positions) of the architectural opening covering assemblies.

FIG. **3** illustrates the example architectural opening covering assemblies **200**, **202** of FIG. **2** at different speed setting positions during the speed setting mode. In the illustrated example, the covering **204** of the first architectural opening covering assembly **200** is at a first speed setting position that is the first distance **D1** from the reference position (e.g., the lower limit position). Thus, in response to a command from the central input device **246** to establish the speed at which the motor **212** is to move the covering **204** during operation, the controller **216** establishes the speed based on a number of rotations of the tube **208** to move the covering **204** the first

distance **D1** in a predetermined amount of time. In the illustrated example, if the predetermined amount of time is ten seconds and the covering **204** moves the first distance **D1** in one revolution of the tube **208**, the example controller **216** determines that the speed at which the tube **208** is to rotate during operation of the example architectural opening covering assembly **200** is one revolution per ten seconds (i.e., six revolutions per minute).

The covering **206** of the example second architectural opening covering assembly **202** is raised (e.g., via the local input device **240**) to a second speed setting position that is a second distance **D2** away from the reference position (e.g., the lower limit position). Thus, the example controller **218** establishes the speed at which the motor **214** is to move the covering **206** during operation based on a number of rotations of the tube **210** to move the covering **206** the second distance **D2** (from the second speed setting position to the reference position) in a predetermined amount of time. In the illustrated example, if the predetermined amount of time is ten seconds and the second distance **D2** corresponds to 1.5 revolutions of the tube **210**, the example controller **216** determines that the speed at which the tube **210** is to rotate via the motor **214** during operation of the example architectural opening covering assembly **202** is 1.5 revolutions per ten seconds (i.e., nine revolutions per minute).

By moving the example coverings **204**, **206** to different speed setting positions during the speed setting mode in the illustrated example of FIG. **3**, the speeds at which the coverings **204**, **206** move via the motors **212**, **214** are configured such that the speeds are different. More specifically, because the reference position utilized by the example controllers **216**, **218** are substantially at the same height (e.g., relative to a floor) in the illustrated example, a difference between the speeds at which the coverings **204**, **206** are determined to move is based on a distance between the speed setting positions (**D1**, **D2**) of the coverings **204**, **206**. For example, if the second distance **D2** is twice the first distance **D1**, the covering **206** of the second example architectural opening covering assembly **202** moves twice as fast as the covering **204** of the first architectural opening covering assembly **200** during operation.

FIG. **4** is a block diagram of an example controller **400** disclosed herein, which implements the example controller **122** of FIG. **1**, the example controller **216** of FIGS. **2-3** and/or the example controller **218** of FIGS. **2-3**. In the illustrated example, the controller **400** includes an instruction processor **402**, a motor controller **404**, a tube rotational direction determiner **406**, a tube angular position determiner **408**, a covering position determiner **410**, a tube rotational speed determiner **412** and a memory **414**.

The example instruction processor **400** of FIG. **4** receives instructions or commands from a first input device **416** (e.g., the input device **138** of FIG. **1**, the local input device **238** of FIG. **2**, the local input device **240** of FIG. **2**, etc.) and/or a second input device **418** (e.g., the central input device **246** and/or any other input device). In some examples, a polarity of a voltage source (e.g., a power supply provided by the first input device **416** and/or the second input device **418**) is modulated (e.g., alternated) to communicate one or more instructions. The instructions may include a command to, for example lower a covering **420**, raise the covering **420**, enter the speed setting mode, move the covering **420** at a given speed, and/or other instructions. In some examples, the first input device **416** and/or the second input device **418** sends a signal (e.g., RF signals, network communications, etc.), which corresponds to a client action (e.g., raise the covering **420**, lower the covering, enter the speed setting mode, move

the covering 420 at a given speed, etc.). The example instruction processor 402 determines which of a plurality of actions are instructed by the signal and/or communication transmitted from the first input device 416 and/or the second input device 418. In some examples, the first input device 416 and/or the second input device 418 instructs the example instruction processor 402 to store a given position of a tube 422 (e.g., an angular position) as a reference position (e.g., a lower limit position, an upper limit position, a position between the upper limit position and the lower limit position, etc.) in the memory 414.

The example motor controller 404 of FIG. 4 controls a motor 424 (e.g., the example motor 120, the example motor 212, the example motor 214, etc.). For example, the example motor controller 404 of FIG. 4 sends a signal to the motor 424 to cause the motor 424 to operate the covering 420 (e.g., rotate the tube 422 to raise or lower the covering 420, prevent (e.g., brake, stop, etc.) rotation of the tube 422, etc.). The example motor controller 404 also controls a speed at which the motor 424 rotates the tube 422 rotates during operation of an example architectural opening covering assembly (e.g., the example architectural opening covering assembly 100, the example first architectural opening covering assembly 200 of FIG. 2, the example second architectural opening covering assembly 202 of FIG. 2, etc.). In some examples, the motor controller 404 controls the speed of rotation of the tube 422 via a speed controller such as, for example, a pulse width modulation speed controller, a brake, a voltage rectifier that supplies a voltage (e.g., power) to the motor 424 and/or any other component or device for operating the motor 424 and/or the tube 422.

The example tube rotational direction determiner 406 of FIG. 4 determines a direction of rotation (e.g., clockwise or counterclockwise) of the tube 422. In some examples, the tube rotational direction determiner 406 determines the direction of rotation of the tube 422 based on tube position information communicated by a tube angular position sensor 426 (e.g., the tube angular position sensor 122 of FIG. 1, the example tube angular position sensor 242 of FIG. 2, the example tube angular position sensor 244 of FIG. 2, etc.). In some examples, the tube angular position sensor 426 of FIG. 4 is a gravitational sensor (e.g., an accelerometer, the gravitational sensor made by Kionix® as part number KXTC9-2050, etc.). In other examples, the tube angular position sensor 426 may include one or more other types of sensors (e.g., a potentiometer, a Hall Effect type sensor, a resolver, rotary encoder employing, for example, light, a magnet, and/or any other type of angular position sensor). In some examples, the tube angular position sensor 426 outputs a plurality of values as the tube 422 rotates. In some examples, based on how those values are changing (e.g., increasing or decreasing, changing signs (e.g., positive to negative, negative to positive, etc.)), the tube rotational direction determiner 406 determines the direction of rotation of the tube 422. In some examples, the tube rotational direction determiner 406 associates the direction of rotation of the tube 422 with raising or lowering the example covering 420.

The example tube angular position determiner 408 determines an angular position of the tube 422 relative to a reference point, a reference position and/or a frame of reference (e.g., a gravitational field vector of Earth, an indicator (e.g., a marking, a light, a magnetic field, etc. on the tube 422 and/or other portion of the architectural opening covering assembly, a wall, an architectural opening frame (e.g., the example first frame 226 of FIG. 2, the example second frame 228 of FIG. 2, etc.), and/or any other

structure). In some examples, the tube angular position determiner 408 determines the angular position of the tube 422 based on tube position information communicated by the tube angular position sensor 426 and/or the rotational direction of the tube 422 determined by the example tube rotational direction determiner 406. In some examples, the tube angular position determiner 408 processes the tube position information (e.g., performs geometric calculations, converts a current signal to a voltage signal, etc.) to determine the angular position of the tube 422.

The example covering position determiner 410 of FIG. 4 determines a position of the covering 420 relative to a reference position (e.g., a previously stored position, a lower limit position, an upper limit position, and/or any other reference position). In some examples, the covering position determiner 410 determines the position of the covering 420 based on an angular displacement (e.g., an amount of rotation) of the tube 422 from the reference position. In some examples, the covering position determiner 410 determines that a given position of the covering 420 is the reference position based on a command from the first input device 416 and/or the second input device 418. For example, the first input device 416 and/or the second input device 418 communicates an instruction to the controller 400 to establish a reference position at a position of the covering 420 at a time when the instruction is received. In some examples, in response to the instruction, the covering position determiner 410 establishes the reference position and substantially continuously monitors subsequent positions of the covering 420 relative to the reference position. In some examples, the covering position determiner 410 determines the position of the covering 420 in units of degrees of rotation (e.g., 30 degrees, 720 degrees, etc.) of the tube 422 relative to the reference position, a number of rotations (e.g., 1, 2, 3, 3.4, etc.) of the tube 422 from the reference position and/or any other unit of measurement.

The example tube rotational speed determiner 412 of FIG. 4 determines a speed at which the example covering 420 is to move during operation of the example architectural opening covering assembly. In some examples, the example tube rotational speed determiner 412 determines the speed at which the example covering 420 is to move by determining a speed at which the motor controller 404 is to cause the motor 424 to rotate the tube 422. In the illustrated example, the tube rotational speed determiner 412 determines the speed of rotation of the tube 422 based on a value (e.g., a number of rotations, a distance measurement, and/or any other value) corresponding to a position of the covering 420.

In some examples, the tube rotational speed determiner 412 determines the speed of rotation of the tube 422 based on the position (e.g., a speed setting position) of the covering 420 relative to a reference position. In some examples, the first input device 416 and/or the second input device 418 communicates a command to the instruction processor 402 to establish (e.g., determine, set, adjust and/or change) the speed of rotation of the tube 422 based on the position of the covering 420 relative to the reference position at a given time. Based on the distance between the position of the covering 420 and the reference position (e.g., a number of rotations of the tube 422 away from the reference position) at the given time (e.g., when the command is received), the tube rotational speed determiner 412 determines (e.g., calculates) the speed at which the covering 420 is to move during operation of the example architectural opening covering assembly.

In some examples, the tube rotational speed determiner 412 determines the speed of rotation of the tube 422 based

13

on a predetermined amount of time in which the covering 420 is to move from the speed setting position (e.g., a position of the tube 422 at a time when the command is received to the reference position). For example, if the predetermined amount of time is fifteen seconds and the covering 420 is two rotations of the tube 422 from the reference position when the example controller 400 receives a command to establish the speed, the tube rotational speed determiner 412 determines that the tube 422 is to rotate two rotations per fifteen seconds (i.e., eight revolutions per minute). In this case, during subsequent operation of the example architectural opening covering assembly (e.g., raising the covering 420, lowering the covering 420, etc.), the example motor controller 404 controls the motor 424 to rotate the tube 422 at two rotations per fifteen seconds. Other examples use other predetermined amounts of time (e.g., 10 seconds, 20 seconds, 30 seconds, etc.) to determine the speed of rotation of the tube 422 based on the speed setting position of the tube 422. In some examples, the tube rotational speed determiner 412 uses a predetermined amount of time stored in the memory 414.

The example memory 414 of FIG. 4 organizes and/or stores information such as, for example, tube position information generated by the example tube angular position sensor 426, a position of the covering 420, a direction or rotation of the tube 422 to raise the covering 420, a direction of rotation of the tube 422 to lower the covering 420, one or more reference positions of the covering 420 (e.g., a fully unwound position, an upper limit position, a lower limit position, etc.), a speed at which the tube 422 is to rotate during operation of the example architectural opening covering assembly, one or more predetermined amounts of time, one or more instructions or commands corresponding to signals (e.g., a number of polarity changes) to be communicated by of the first input device 416 and/or the second input device 418, and/or any other information that may be utilized during the operation of the example architectural opening covering assembly.

While an example manner of implementing the example controller 122 of FIG. 1, the example controller 216 of FIGS. 2-3 and/or the example controller 218 of FIGS. 2-3 is illustrated in FIG. 4, one or more of the elements, processes and/or devices illustrated in FIG. 4 may be combined, divided, re-arranged, omitted, eliminated and/or implemented in any other way. Further, the example instruction processor 402, the example motor controller 404, the example tube rotational direction determiner 406, the example tube angular position determiner 408, the example covering position determiner 410, the example tube rotational speed determiner 412, the example memory 414, the example first input device 416, the example second input device 418, the example tube angular position sensor 426 and/or, more generally, the example controller 400 of FIG. 4 may be implemented by hardware, software, firmware and/or any combination of hardware, software and/or firmware. Thus, for example, any of the example instruction processor 402, the example motor controller 404, the example tube rotational direction determiner 406, the example tube angular position determiner 408, the example covering position determiner 410, the example tube rotational speed determiner 412, the example memory 414, the example first input device 416, the example second input device 418, the example tube angular position sensor 426 and/or, more generally, the example controller 400 of FIG. 4 could be implemented by one or more analog or digital

14

mable logic device(s) (PLD(s)) and/or field programmable logic device(s) (FPLD(s)). When reading any of the apparatus or system claims of this patent to cover a purely software and/or firmware implementation, at least one of the example, instruction processor 402, the example motor controller 404, the example tube rotational direction determiner 406, the example tube angular position determiner 408, the example covering position determiner 410, the example tube rotational speed determiner 412, the example memory 414, the example first input device 416, the example second input device 418, the example tube angular position sensor 426 and/or, more generally, the example controller 400 of FIG. 4 are hereby expressly defined to include a tangible computer readable storage device or storage disk such as a memory, a digital versatile disk (DVD), a compact disk (CD), a Blu-ray disk, etc. storing the software and/or firmware. Further still, the example controller 400 of FIG. 4 may include one or more elements, processes and/or devices in addition to, or instead of, those illustrated in FIG. 4, and/or may include more than one of any or all of the illustrated elements, processes and devices.

A flowchart representative of example machine readable instructions for implementing the example controller 400 of FIG. 4 is shown in FIG. 5. In this example, the machine readable instructions comprise a program for execution by a processor such as the processor 612 shown in the example processor platform 600 discussed below in connection with FIG. 6. The program may be embodied in software stored on a tangible computer readable storage medium such as a CD-ROM, a floppy disk, a hard drive, a digital versatile disk (DVD), a Blu-ray disk, or a memory associated with the processor 612, but the entire program and/or parts thereof could alternatively be executed by a device other than the processor 612 and/or embodied in firmware or dedicated hardware. Further, although the example program is described with reference to the flowchart illustrated in FIG. 4, many other methods of implementing the example controller 400 may alternatively be used. For example, the order of execution of the blocks may be changed, and/or some of the blocks described may be changed, eliminated, or combined.

As mentioned above, the example process of FIG. 5 may be implemented using coded instructions (e.g., computer and/or machine readable instructions) stored on a tangible computer readable storage medium such as a hard disk drive, a flash memory, a read-only memory (ROM), a compact disk (CD), a digital versatile disk (DVD), a cache, a random-access memory (RAM) and/or any other storage device or storage disk in which information is stored for any duration (e.g., for extended time periods, permanently, for brief instances, for temporarily buffering, and/or for caching of the information). As used herein, the term tangible computer readable storage medium is expressly defined to include any type of computer readable storage device and/or storage disk and to exclude propagating signals. As used herein, “tangible computer readable storage medium” and “tangible machine readable storage medium” are used interchangeably. Additionally or alternatively, the example process of FIG. 5 may be implemented using coded instructions (e.g., computer and/or machine readable instructions) stored on a non-transitory computer and/or machine readable medium such as a hard disk drive, a flash memory, a read-only memory, a compact disk, a digital versatile disk, a cache, a random-access memory and/or any other storage device or storage disk in which information is stored for any duration (e.g., for extended time periods, permanently, for brief instances, for temporarily buffering, and/or for caching of

15

the information). As used herein, the term non-transitory computer readable medium is expressly defined to include any type of computer readable device or disk and to exclude propagating signals. As used herein, when the phrase “at least” is used as the transition term in a preamble of a claim, it is open-ended in the same manner as the term “comprising” is open ended.

The example program **500** of FIG. **5** begins at block **502** when the covering position determiner **410** monitors a position of the covering **420** of an architectural opening covering assembly (e.g., the example architectural opening covering assembly of FIG. **1**, the example first architectural opening covering **200** assembly of FIG. **2**, the example second architectural opening covering assembly **202** of FIG. **2**, etc.). In some examples, the controller **400** receives a signal from the first input device **416** and/or the second input device **418** communicating a command to enter a speed setting mode. The example instruction processor **402** of FIG. **4** processes the signal, and the example controller **400** enters the speed setting mode and monitors the position of the covering **420** relative to a reference position such as, for example, a lower limit position, an upper limit position, etc. In some examples, while the controller **400** is in the speed setting mode, the covering **420** is moved via the first input device **416** and/or the second input device **418** (e.g., a user actuates a cord, actuates a switch, etc.), and the example covering position determiner **310** monitors the movement of the covering **410** based on tube position information generated via the tube angular position sensor **426**. In some examples, the controller **400** determines, sets and/or stores the reference position in response to the command to enter the speed setting mode. In other examples, the reference position is previously established in a programming or calibration mode.

At block **504**, the covering position determiner **410** determines a speed setting position of the covering **420** in response to a first command from the first input device **416** and/or the second input device **418** (e.g., the input device **138** of FIG. **1**, the central input device **346** of FIG. **2**, etc.). In some examples, the speed setting position is a position of the covering **420** relative to the reference position at a time when the example controller **400** receives the first command.

At block **506**, based on the speed setting position of the covering **420**, the tube rotational speed determiner **412** determines a speed at which to move the covering **420**. In some examples, the tube rotational speed determiner **412** determines the speed to move the covering **420** based on a distance from the speed setting position to the reference position and a predetermined amount of time (e.g., 10 seconds, 15 seconds, 20 seconds, 30 seconds, etc.). In some examples, the tube rotational speed determiner **412** uses a predetermined amount of time that is stored in the example memory **414**. For example, if the distance between the speed setting position and the reference position is one foot and the predetermined amount of time is 15 seconds, the tube rotational speed determiner **412** determines that the speed to move the covering **420** is one foot per fifteen seconds (i.e., 4 feet per minute).

In some examples, the tube rotational speed determiner **412** determines the distance between the speed setting position and the reference position by determining a number of rotations of the tube **422** to move the covering **420** from the speed setting position to the reference position. For example, if the reference position is one rotation of the tube **422** in a first direction from a fully unwound position of the covering **420**, and the covering position determiner **412**

16

determines that the speed setting position is five rotations of the tube **422** in the first direction from the fully unwound position, the distance between the speed setting position and the reference position is four rotations of the example tube **422**. In some examples, the tube rotational speed determiner **412** determines the speed at which to move the covering **420** by dividing the number of rotations by the predetermined amount of time. For example, if the tube rotational speed determiner **412** determines that the distance corresponds to four rotations and the predetermined amount of time is 15 seconds, the tube rotational speed determiner **412** determines the speed to move the covering **420** is four rotations of the tube **422** per fifteen seconds (i.e., 16 rotations of the tube per minute). In some examples, the tube rotational speed determiner **412** stores the speed in the memory **414**.

At block **508**, in response to a second command from the first input device **416** and/or the second input device **418** to move the covering **420** (e.g., raise or lower the covering **420**), the example motor controller **404** of FIG. **4** sends a signal to the motor **424** to move the covering at the determined speed. For example, the motor controller **404** sends a signal to the motor **424** to rotate the tube **422** at a speed of four rotations per fifteen seconds. In some examples, in response to the second command and/or another command, the example controller **400** exits the speed setting mode.

FIG. **6** is a block diagram of an example processor platform **600** capable of executing the instructions of FIG. **5** to implement the example controller **400** of FIG. **4**. The processor platform **600** can be, for example, a server, a personal computer, a mobile device (e.g., a cell phone, a smart phone, a tablet such as an iPad™), a personal digital assistant (PDA), an Internet appliance, or any other type of computing device.

The processor platform **600** of the illustrated example includes a processor **612**. The processor **612** of the illustrated example is hardware. For example, the processor **612** can be implemented by one or more integrated circuits, logic circuits, microprocessors or controllers from any desired family or manufacturer.

The processor **612** of the illustrated example includes a local memory **613** (e.g., a cache). The processor **612** of the illustrated example is in communication with a main memory including a volatile memory **614** and a non-volatile memory **616** via a bus **618**. The volatile memory **614** may be implemented by Synchronous Dynamic Random Access Memory (SDRAM), Dynamic Random Access Memory (DRAM), RAMBUS Dynamic Random Access Memory (RDRAM) and/or any other type of random access memory device. The non-volatile memory **616** may be implemented by flash memory and/or any other desired type of memory device. Access to the main memory **614**, **616** is controlled by a memory controller.

The processor platform **600** of the illustrated example also includes an interface circuit **620**. The interface circuit **620** may be implemented by any type of interface standard, such as an Ethernet interface, a universal serial bus (USB), and/or a PCI express interface.

In the illustrated example, one or more input devices **622** are connected to the interface circuit **620**. The input device(s) **622** permit(s) a user to enter data and commands into the processor **612**. The input device(s) can be implemented by, for example, an audio sensor, a microphone, a camera (still or video), a keyboard, a button, a mouse, a touchscreen, a switch, a track-pad, a trackball, isopoint and/or a voice recognition system.

One or more output devices **624** are also connected to the interface circuit **620** of the illustrated example. The output

17

devices **624** can be implemented, for example, by display devices (e.g., a light emitting diode (LED), an organic light emitting diode (OLED), a liquid crystal display, a cathode ray tube display (CRT), a touchscreen, a light emitting diode (LED), and/or speakers). The interface circuit **620** of the illustrated example, thus, typically includes a graphics driver card, a graphics driver chip or a graphics driver processor.

The interface circuit **620** of the illustrated example also includes a communication device such as a transmitter, a receiver, a transceiver, a modem and/or network interface card to facilitate exchange of data with external machines (e.g., computing devices of any kind) via a network **626** (e.g., an Ethernet connection, a digital subscriber line (DSL), a telephone line, coaxial cable, a cellular telephone system, etc.).

The processor platform **600** of the illustrated example also includes one or more mass storage devices **628** for storing software and/or data. Examples of such mass storage devices **628** include floppy disk drives, hard drive disks, compact disk drives, Blu-ray disk drives, RAID systems, and digital versatile disk (DVD) drives.

The coded instructions **632** of FIG. **5** may be stored in the mass storage device **628**, in the volatile memory **614**, in the non-volatile memory **616**, and/or on a removable tangible computer readable storage medium such as a CD or DVD.

From the foregoing, it will appreciate that the above disclosed methods, apparatus, systems and articles of manufacture enable a speed of a covering of an architectural opening covering assembly to be determined, set and/or stored based on a position of the covering. In this manner, speeds at which coverings of a plurality of architectural opening covering assemblies, which may include tubes having different sizes, move during operation may be easily coordinated (e.g., synchronized) by adjusting the positions of the coverings relative to reference positions and/or each other. Thus, the speeds may be set based on a visual appearance of one or more architectural opening covering assemblies (e.g., without a user having knowledge and/or concern for characteristics of the architectural opening covering assemblies such as a size of a tube).

Although certain example methods, apparatus and articles of manufacture have been disclosed herein, the scope of coverage of this patent is not limited thereto. On the contrary, this patent covers all methods, apparatus and articles of manufacture fairly falling within the scope of the claims of this patent.

What is claimed is:

1. An apparatus comprising:

a first end rail of a first covering;
a second end rail of a second covering;
a first motor to move the first end rail;
a second motor to move the second end rail;
one or more memories; and
one or more processors configured to:

while operating in a speed setting mode and in response to a first command to store speeds:

determine a first distance between a current position of the first end rail and a first reference position for the first end rail;

calculate a first speed at which the first motor is to move the first end rail based on the first distance and a predetermined amount of time;

store, in the one or more memories, the first speed in association with the first covering;

determine a second distance between a current position of the second end rail and a second reference position for the second end rail;

18

calculate a second speed at which the second motor is to move the second end rail based on the second distance and the predetermined amount of time; and

store, in the one or more memories, the second speed in association with the second covering; and
after exiting the speed setting mode and in response to a second command to move coverings at one or more user-selected speeds from the stored speeds:

determine, from the one or more memories, the first speed and the second speed; and

activate the first motor to move the first end rail at the first speed and activate the second motor to move the second end rail at the second speed such that the first end rail arrives at the first reference position at the same time as the second end rail arrives at the second reference position.

2. The apparatus of claim 1, wherein the one or more processors are further configured to receive the first command in the speed setting mode and to activate the first motor and the second motor in response to the second command after exiting the speed setting mode.

3. The apparatus of claim 2, wherein the second command is a wireless command signal from an electronic input device.

4. The apparatus of claim 3, wherein the electronic input device is a remote control.

5. The apparatus of claim 3, wherein the electronic input device is a smartphone.

6. The apparatus of claim 1, wherein the first reference position and the second reference position are stored in the one or more memories.

7. The apparatus of claim 6, wherein the predetermined amount of time is stored in the one or more memories.

8. The apparatus of claim 1, wherein the one or more processors are further configured to track a speed of the first end rail based on information from a first sensor and track a speed of the second end rail based on information from a second sensor.

9. The apparatus of claim 1, wherein the one or more processors are further configured to track a position of the first end rail based on information from a first sensor and track a position of the second end rail based on information from a second sensor.

10. The apparatus of claim 1, wherein the first reference position is a lower limit position or an upper limit position.

11. The apparatus of claim 1, wherein the one or more processors are configured to:
while operating in the speed setting mode:

determine, in response to the first command, a speed setting position that corresponds to the current position, wherein the current position is determined based on sensor data;

determine, in response to the first command and from the one or more memories, a user setting that corresponds to the predetermined amount of time, wherein the user setting is stored in the one or more memories prior to receiving the first command; and
calculate the first speed based on the speed setting position and the user setting.

12. A tangible machine readable storage medium comprising instructions that, when executed, cause at least one machine to at least:

while operating in a speed setting mode and in response to a first command to store speeds:

19

determine a first distance between a current position of a first end rail and a first reference position for the first end rail;

calculate a first speed at which a first motor is to move the first end rail based on the first distance and a predetermined amount of time; 5

determine a second distance between a current position of a second end rail and a second reference position for the second end rail;

calculate a second speed at which a second motor is to move the second end rail based on the second distance and the predetermined amount of time; and 10

store the first speed and the second speed; and

after exiting the speed setting mode and in response to a second command to move coverings at one or more user-selected speeds from the stored speeds: 15

determine first speed and the second speed as stored; and

activate the first motor to move the first end rail at the first speed and activate the second motor to move the second end rail at the second speed such that the first and second end rails move contemporaneously to the first and second reference positions, respectively. 20

13. The tangible machine readable storage medium of claim **12**, wherein the instructions, when executed, cause the at least one machine to receive the first command in the speed setting mode and active the first motor and the second motor in response to the second command after exiting the speed setting mode. 25

14. The tangible machine readable storage medium of claim **13**, wherein the second command is a wireless command signal from an electronic input device. 30

15. The tangible machine readable storage medium of claim **14**, wherein the electronic input device is a remote control. 35

16. The tangible machine readable storage medium of claim **14**, wherein the electronic input device is a smart-phone.

20

17. A method comprising:

while operating in a speed setting mode and in response to a first command to store speeds:

determining, with a logic circuit, a first distance between a current position of a first end rail and a first reference position for the first end rail;

calculating, with the logic circuit, a first speed at which a first motor is to move the first end rail based on the first distance and a predetermined amount of time;

determining, with the logic circuit, a second distance between a current position of a second end rail and a second reference position for the second end rail;

calculating, with the logic circuit, a second speed at which a second motor is to move the second end rail based on the second distance and the predetermined amount of time; and

storing the first speed and the second speed; and

after exiting the speed setting mode and in response to a second command to move coverings at one or more user-selected speeds from the stored speeds:

determining first speed and the second speed as stored; and

activating, with the logic circuit, the first motor to move the first end rail at the first speed and the second motor to move the second end rail at the second speed such that the first end rail arrives at the first reference position when the second end rail arrives at the second reference position.

18. The method of claim **17**, wherein the first command is received in the speed setting mode and the activating of the first motor and the second motor is in response to the second command after the speed setting mode is exited.

19. The method of claim **18**, wherein the second command is a wireless command signal from an electronic input device.

20. The method of claim **19**, wherein the electronic input device is a remote control.

* * * * *