



US011378039B2

(12) **United States Patent**
McCune et al.

(10) **Patent No.:** **US 11,378,039 B2**
(45) **Date of Patent:** **Jul. 5, 2022**

(54) **RING GEAR MOUNTING ARRANGEMENT WITH OIL SCAVENGE SCHEME**

(56) **References Cited**

(71) Applicant: **Raytheon Technologies Corporation**, Farmington, CT (US)

2,258,792 A 4/1941 New
2,288,792 A 7/1942 Daniels

(Continued)

(72) Inventors: **Michael E. McCune**, Colchester, CT (US); **Lawrence E. Portlock**, Bethany, CT (US); **Frederick M. Schwarz**, Glastonbury, CT (US)

FOREIGN PATENT DOCUMENTS

CN 1952435 4/2007
EP 0791383 8/1997

(Continued)

(73) Assignee: **RAYTHEON TECHNOLOGIES CORPORATION**, Farmington, CT (US)

OTHER PUBLICATIONS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

European Search Report for European Patent Application No. 19205494.8 completed Dec. 18, 2019.

(Continued)

(21) Appl. No.: **17/062,197**

(22) Filed: **Oct. 2, 2020**

Primary Examiner — Derek D Knight

(65) **Prior Publication Data**

US 2021/0017936 A1 Jan. 21, 2021

(74) *Attorney, Agent, or Firm* — Carlson, Gaskey & Olds, P.C.

Related U.S. Application Data

(63) Continuation of application No. 16/736,013, filed on Jan. 7, 2020, now Pat. No. 10,907,579, which is a (Continued)

(57) **ABSTRACT**

(51) **Int. Cl.**
F16H 57/04 (2010.01)
F02K 3/06 (2006.01)
F02C 7/36 (2006.01)


A gas turbine engine includes a bypass ratio greater than about ten (10). A fan is supported on a fan shaft and has a plurality of fan blades. A gear system is connected to the fan shaft. A plurality of planetary gears and a first set of opposed angled ring gear teeth are separated from a second set of opposed angled ring gear teeth. A lubricant flow path is located axially between the first set of opposed angled ring gear teeth and the second set of opposed angled ring gear teeth. A gear system support is relative to a fixed housing facilitating segregation of vibrations. An annular channel is axially aligned with the lubricant flow path. A low pressure turbine has an inlet, an outlet, and a low pressure turbine pressure ratio greater than 5:1.

(52) **U.S. Cl.**
CPC **F02K 3/06** (2013.01); **F02C 7/36** (2013.01); **F16H 57/04** (2013.01); (Continued)

(58) **Field of Classification Search**
CPC ... F02K 3/06; F02C 7/36; F16H 57/04; F16H 57/0479

See application file for complete search history.

30 Claims, 3 Drawing Sheets



Related U.S. Application Data

continuation of application No. 16/122,236, filed on Sep. 5, 2018, now Pat. No. 10,527,151, which is a continuation of application No. 15/892,210, filed on Feb. 8, 2018, now Pat. No. 10,082,105, which is a continuation of application No. 14/753,048, filed on Jun. 29, 2015, now Pat. No. 10,107,231, which is a continuation-in-part of application No. 13/346,120, filed on Jan. 9, 2012, now abandoned, which is a continuation-in-part of application No. 11/504,220, filed on Aug. 15, 2006, now Pat. No. 8,753,243.

(52) **U.S. Cl.**

CPC *F05D 2220/323* (2013.01); *F05D 2220/36* (2013.01); *F05D 2240/70* (2013.01); *F05D 2260/34* (2013.01); *F05D 2260/4031* (2013.01); *F05D 2260/40311* (2013.01); *F16H 57/0479* (2013.01); *F16H 57/0486* (2013.01)

(56)

References Cited

U.S. PATENT DOCUMENTS

2,684,591 A	7/1954	Lundquist	5,975,841 A	11/1999	Lindemuth et al.
2,936,655 A	5/1960	Peterson et al.	5,985,470 A	11/1999	Spitsberg et al.
3,021,731 A	2/1962	Stoeckicht	6,158,210 A	12/2000	Orlando
3,160,026 A	12/1964	Rosen	6,223,616 B1 *	5/2001	Sheridan F16H 57/0482 74/468
3,194,487 A	7/1965	Tyler et al.	6,315,815 B1	11/2001	Spadaccini et al.
3,287,906 A	11/1966	McCormick	6,318,070 B1	11/2001	Rey et al.
3,352,178 A	11/1967	Lindgren et al.	6,387,456 B1	5/2002	Eaton, Jr. et al.
3,412,560 A	11/1968	Gaubatz	6,402,654 B1	6/2002	Lanzon et al.
3,664,612 A	5/1972	Skidmore et al.	6,517,341 B1	2/2003	Brun et al.
3,722,323 A	3/1973	Welch	6,530,858 B1	3/2003	Uroso et al.
3,747,343 A	7/1973	Rosen	6,607,165 B1	8/2003	Manteiga et al.
3,754,484 A	8/1973	Roberts	6,669,597 B1	12/2003	Uroso et al.
3,765,623 A	10/1973	Donelson et al.	6,709,492 B1	3/2004	Spadaccini et al.
3,820,719 A	6/1974	Clark	6,732,502 B2	5/2004	Seda et al.
3,843,277 A	10/1974	Ehrich	6,814,541 B2	11/2004	Evans et al.
3,892,358 A	7/1975	Gisslen	6,883,303 B1	4/2005	Seda
3,932,058 A	1/1976	Harner et al.	7,021,042 B2	4/2006	Law
3,935,558 A	1/1976	Miller et al.	7,219,490 B2	1/2007	Dev
3,988,889 A	11/1976	Chamay et al.	7,328,580 B2	2/2008	Lee et al.
4,130,872 A	12/1978	Harloff	7,374,403 B2	5/2008	Decker et al.
4,220,171 A	9/1980	Ruehr	7,591,754 B2	9/2009	Duong et al.
4,240,250 A	12/1980	Harris	7,632,064 B2	12/2009	Somanath
4,284,174 A	8/1981	Salvana et al.	7,662,059 B2	2/2010	McCune
4,289,360 A	9/1981	Zirin	7,704,178 B2	4/2010	Sheridan et al.
4,478,551 A	10/1984	Honeycutt, Jr. et al.	7,806,651 B2	10/2010	Kennepohl et al.
4,583,413 A	4/1986	Lack	7,824,305 B2	11/2010	Duong et al.
4,649,114 A	3/1987	Miltenerburger et al.	7,828,682 B2	11/2010	Smook
4,696,156 A	9/1987	Burr et al.	7,926,260 B2	4/2011	Sheridan et al.
4,722,357 A	2/1988	Wynosky	7,950,151 B2	5/2011	Duong et al.
4,896,499 A	1/1990	Rice	7,997,868 B1	8/2011	Liang et al.
4,979,362 A	12/1990	Vershure, Jr.	8,074,440 B2	12/2011	Kohlenberg
5,058,617 A	10/1991	Stockman et al.	8,205,432 B2	6/2012	Sheridan
5,081,832 A	1/1992	Mowill	8,894,538 B2	11/2014	McCune
5,102,379 A	4/1992	Pagluica et al.	9,752,511 B2	9/2017	McCune et al.
5,141,400 A	8/1992	Murphy et al.	10,527,151 B1	1/2020	McCune
5,211,541 A	5/1993	Fledderjohn et al.	10,907,579 B2 *	2/2021	McCune F02C 7/36
5,302,031 A	4/1994	Yuasa	2002/0064232 A1	5/2002	Fukuhara et al.
5,317,877 A	6/1994	Stuart	2002/0064327 A1	5/2002	Toda et al.
5,361,580 A	11/1994	Ciokajlo et al.	2004/0112041 A1	6/2004	Law
5,391,125 A	2/1995	Turra et al.	2005/0026745 A1	2/2005	Mitrovic
5,433,674 A *	7/1995	Sheridan F01D 5/02 475/346	2006/0228206 A1	10/2006	Decker et al.
5,447,411 A	9/1995	Curley et al.	2007/0225111 A1	9/2007	Duong et al.
5,466,198 A	11/1995	McKibben et al.	2008/0003096 A1	1/2008	Kohli et al.
5,472,383 A	12/1995	McKibbin	2008/0006018 A1	1/2008	Sheridan et al.
5,524,847 A	6/1996	Brodell et al.	2008/0044276 A1	2/2008	McCune et al.
5,634,767 A	6/1997	Dawson	2008/0096714 A1	4/2008	McCune
5,677,060 A	10/1997	Terentieva et al.	2008/0116009 A1	5/2008	Sheridan et al.
5,778,659 A	7/1998	Duesler et al.	2008/0317588 A1	12/2008	Grabowski et al.
5,857,836 A	1/1999	Stickler et al.	2009/0053058 A1	2/2009	Kohlenberg et al.
5,915,917 A	6/1999	Eveker et al.	2009/0053606 A1	2/2009	Kim et al.
			2009/0056306 A1	3/2009	Suciu et al.
			2009/0056343 A1	3/2009	Suciu et al.
			2009/0081039 A1	3/2009	McCune et al.
			2009/0090096 A1	4/2009	Sheridan
			2009/0111639 A1	4/2009	Klingels
			2009/0293278 A1	12/2009	Duong et al.
			2009/0298640 A1	12/2009	Duong et al.
			2009/0304518 A1	12/2009	Kodama et al.
			2009/0314881 A1	12/2009	Suciu et al.
			2010/0105516 A1	4/2010	Sheridan et al.
			2010/0148396 A1	6/2010	Xie et al.
			2010/0150702 A1	6/2010	Sheridan et al.
			2010/0212281 A1	8/2010	Sheridan
			2010/0218483 A1	9/2010	Smith
			2010/0317478 A1	12/2010	McCune et al.
			2010/0331139 A1	12/2010	McCune
			2011/0130246 A1	6/2011	McCune
			2011/0159797 A1	6/2011	Beltman et al.
			2011/0293423 A1	12/2011	Bunker et al.
			2012/0124964 A1	5/2012	Hasel et al.
			2012/0243971 A1	9/2012	McCune et al.
			2012/0275904 A1	11/2012	McCune et al.
			2013/0023378 A1	1/2013	McCune et al.
			2014/0133958 A1	5/2014	McCune et al.
			2014/0154054 A1	6/2014	Sheridan et al.
			2014/0230403 A1	8/2014	Merry et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2015/0065285 A1 3/2015 McCune et al.
 2016/0131084 A1* 5/2016 Kupratis F02K 3/06
 60/226.1
 2018/0230942 A1* 8/2018 McCune F02K 3/06

FOREIGN PATENT DOCUMENTS

EP	1114949	7/2001
EP	1142850	10/2001
EP	1429005	6/2004
EP	1876338	1/2008
EP	1890054	2/2008
EP	1925855	5/2008
EP	2093407	8/2009
EP	2098704	9/2009
EP	2224100	9/2010
EP	2267338	12/2010
EP	2270361	1/2011
EP	2327859	6/2011
EP	2559913	2/2013
EP	2610463	7/2013
EP	2610527 A2	7/2013
FR	1357038	4/1964
GB	1516041	6/1978
GB	2041090	9/1980
GB	2426792	12/2006
JP	5248267	9/1993
JP	9317833	12/1997
JP	2001208146	8/2001
JP	3920031	5/2007
JP	4636927	2/2011
JP	2015137649	7/2015
WO	2007038674	4/2007
WO	20130147951	10/2013
WO	2015017041	2/2015

OTHER PUBLICATIONS

Winn, A. (Ed). (1990). Wide Chord Fan Club. Flight International, 4217(137). May 23-29, 1990. pp. 34-38.

Parker, R.G. and Lin, J. (2001). Modeling, modal properties, and mesh stiffness variation instabilities of planetary gears. Prepared for NASA. NASA/CR-2001-210939. May 2001. pp. 1-111.

Mancuso, J.R. and Corcoran, J.P. (2003). What are the differences in high performance flexible couplings for turbomachinery? Proceedings of the Thirty-Second Turbomachinery Symposium. 2003. pp. 189-207.

Dudley, D.W., Ed. (1954). Handbook of practical gear design. Lancaster, PA: Technomic Publishing Company, Inc. pp. 3.96-102 and 8.12-8.18.

Dudley, D.W., Ed. (1962). Gear handbook. New York, NY: McGraw-Hill. pp. 3.14-18 and 12.7-12.21.

Dudley, D.W., Ed. (1994). Practical gear design. New York, NY: McGraw-Hill. pp. 119-124.

Product Brochure. Garrett TFE731. Allied Signal. Copyright 1987. pp. 1-24.

Honeywell Learjet 31 and 35/36 TFE731-2 to 2C Engine Upgrade Program. Sep. 2005. pp. 1-4.

Honeywell Sabreliner 65 TFE731-3 to -3D Engine Upgrade Program. Oct. 2005. pp. 1-4.

U.S. Department of Transportation: Federal Aviation Administration Type Certificate Data Sheet No. E6WE. Dated: May 9, 2000. p. 1-9.

Kurzke, J. (2012). GasTurb 12: Design and off-design performance of gas turbines. Retrieved from: <https://www.scribd.com/document/153900429/GasTurb-12>.

Ahmad, F. and Mizramoghadam, A.V. (1999). Single v. two stage high pressure turbine design of modern aero engines. ASME. Presented at the International Gas Turbine & Aeroengine Congress & Exhibition. Indianapolis, Indiana. Jun. 7-10, 1999. pp. 1-9.

Riegler, C., and Bichlmaier, C. (2007). The geared turbofan technology—Opportunities, challenges and readiness status. Proceedings CEAS. Sep. 10-13, 2007. Berlin, Germany. pp. 1-12.

About GasTurb. Retrieved Jun. 26, 2018 from: <http://gasturb.de/about-gasturb.html>.

Kurzke, J. (2001). GasTurb 9: A program to calculate design and off-design performance of gas turbines. Retrieved from: <https://www.scribd.com/document/92384867/GasTurb9Manual>.

Tummers, B. (2006). DataThief III. Retrieved from: <https://datathief.org/DatathiefManual.pdf> pp. 1-52.

Manual. Student's Guide to Learning SolidWorks Software. Dassault Systemes—SolidWorks Corporation. pp. 1-156.

Macisaac, B. and Langston, R. (2011). Gas turbine propulsion systems. Chichester, West Sussex: John Wiley & Sons, Ltd. pp. 260-265.

Datasheet. CFM56-5B For the Airbus A320ceo family and CFM56-7B for the Boeing 737 family. <https://www.cfmaeroengines.com/>.

Turner, M. G., Norris, A., and Veres, J.P. (2004). High-fidelity three-dimensional simulation of the GE90. NASA/TM-2004-212981. pp. 1-18.

Defeo, A. and Kulina, M. (1977). Quiet clean short-haul experimental engine (QCSEE) main reduction gears detailed design final report. Prepared for NASA. NASA-CR-134872. Jul. 1977. pp. 1-221.

Amzketta, M., Iriarte, X., Ros, J., and Pintor, J. (2009). Dynamic model of a helical gear pair with backlash and angleVarying mesh stiffness. Multibody Dynamics 2009, ECCOMAS Thematic Conference. 2009. pp. 1-36.

Singh, A. (2005). Application of a system level model to study the planetary load sharing behavior. Journal of Mechanical Design. vol. 127. May 2005. pp. 469-476.

Smith-Boyd, L. and Pike, J. (1986). Expansion of epicyclic gear dynamic analysis program. Prepared for NASA. NASA CR-179563. Aug. 1986. pp. 1-98.

Wikipedia. Torsion spring. Retrieved Jun. 29, 2018 from: https://en.wikipedia.org/wiki/Torsion_spring.

AGMA Standard (2006). Design manual for enclosed epicyclic gear drives. Alexandria, VA: American Gear Manufacturers Association, pp. 1-104.

AGMA Standard (1997). Design and selection of components for enclosed gear drives, Alexandria, VA: American Gear Manufacturers Association, pp. 1-48.

Daly, M. Ed. (2007). Jane's Aero-Engine. Issue Twenty-three. Mar. 2008. p. 707-712.

AGMA Standard (1999). Flexible couplings—Mass elastic properties and other characteristics. Alexandria, VA: American Gear Manufacturers Association. pp. 1-46.

Wikipedia. Stiffness. Retrieved Jun. 28, 2018 from: <https://en.wikipedia.org/wiki/Stiffness>.

Damerau, J. (2014) What is the mesh stiffness of gears? Screen shot of query submitted by Vahid Dabbagh, answered by Dr. Jochan Damerau, Research General Manager at Bosch Corp., Japan. Retrieved from: https://www.researchgate.net/post/What_is_the_mesh_stiffness_of_gears.

Hill, P.G., Peterson, C.R. (1965). Mechanics and thermodynamics of propulsion. Addison-Wesley Publishing Company, Inc. pp. 307-308.

Hill, P.G., Peterson, C.R. (1992). Mechanics and thermodynamics of propulsion, 2nd Edition. Addison-Wesley Publishing Company, Inc. pp. 400-406.

Kasuba, R. and August, R. (1984). Gear mesh stiffness and load sharing in planetary gearing. American Society of Mechanical Engineers, Design Engineering Technical Conference, Cambridge, MA. Oct. 7-10, 1984. pp. 1-6.

Ciepluch, C. (1977). Quiet clean short-haul experimental engine (QCSEE) under-the-wing (UTW) final design report. Prepared for NASA. NASA-CP-134847. Retrieved from: <https://ntrs.nasa.gov/archive/nasa/casi.ntrs.nasa.gov/19800075257.pdf>.

Gray, D.E. and Gardner, W.B. (1983). Energy efficient engine program technology benefit/cost study—vol. 2. NASA CR-174766. Oct. 1983. pp. 1-118.

(56)

References Cited

OTHER PUBLICATIONS

- Groweneweg, J.F. (1994). Fan noise research at NASA. NASA-TM-106512. Prepared for the 1994 National Conference on Noise Control Engineering. Fort Lauderdale, FL. May 1-4, 1994. pp. 1-10.
- Groweneweg, J.F. (1994). Fan noise research at NASA. Noise-CON 94. Fort Lauderdale, FL. May 1-4, 1994. pp. 1-10.
- Heidelberg, L.J., and Hall, D.G. (1992). Acoustic mode measurements in the inlet of a model turbofan using a continuously rotating rake. NASA-TM-105989. Prepared for the 31st Aerospace Sciences Meeting. Reno, NV. Jan. 11-14, 1993. pp. 1-30.
- Heidelberg, L.J., and Hall, D.G. (1992). Acoustic mode measurements in the inlet of a model turbofan using a continuously rotating rake. AIAA-93-0598. 31st Aerospace Sciences Meeting. Reno, NV. Jan. 11-14, 1993. pp. 1-30.
- Howe, D.C., and Wynosky, T.A. (1985). Energy efficient engine program advanced turbofan nacelle definition study NASA-CR-174942. May 1985. pp. 1-60.
- Howe, D.C., and Wynosky, T.A. (1985). Energy efficient engine program advanced turbofan nacelle definition study NASA-CR-174942. May 1985. University of Washington dated Dec. 13, 1990. pp. 1-14.
- Wie, Y.S., Collier, F.S., Wagner, R.D., Viken, J.K., and Pfenniger, W. (1992). Design of a hybrid laminar flow control engine nacelle. AIAA-92-0400. 30th Aerospace Sciences Meeting & Exhibit. Jan. 6-9, 1992. pp. 1-14.
- Mattingly, J.D. (1996). Elements of gas turbine propulsion. New York, New York: McGraw-Hill, Inc. pp. 1-18, 30-62, 223-234, 462-479, 517-520, 757-767, and 862-864.
- Johnston, R.P., Hirschkron, R., Koch, C.C., Neitzel, R.E., and Vinson, P.W. (1978). Energy efficient engine: Preliminary design and integration study-final report. NASA CR-135444. Sep. 1978. pp. 1-401.
- Johnston, R.P. and Hemsworth, M.C. (1978). Energy efficient engine preliminary design and integration studies. Jun. 1, 1978. pp. 1-28.
- Awker, R.W. (1986). Evaluation of propfan propulsion applied to general aviation. NASA CR-175020. Mar. 1, 1986. pp. 1-140.
- Howe, D.C. and Wynosky, T.A. (1985). Energy efficient engine program advanced turbofan nacelle definition study NASA CR-174942. May 1, 1985. pp. 174.
- Singh, B. (1986). Small engine component technology (SECT) study. NASA CR-175079. Mar. 1, 1986. pp. 1-102.
- Liebeck, R.H., Andrastek, D.A., Chau, J., Girvin, R., Lyon, R., Rawdon, B.K., Scott, P.W. et al. (1995). Advanced subsonic airplane design & economics studies. NASACR-195443. Apr. 1995. pp. 1-187.
- Notice of Opposition of European Patent No. 2610464 (Application No. 12198045.2) by Safran Aircraft Engines dated Aug. 7, 2019.
- European Extended Search Report for European Patent Application No. 20191611.1 dated Dec. 15, 2020.
- 2003 NASA seal/secondary air system workshop. (2003). NASA/CP-2004-212963/VOL1. Sep. 1, 2004. pp. 1-408.
- Berton, J.J. and Guynn, M.D. (2012). Multi-objective optimization of a turbofan for an advanced, single-aisle transport. NASA/TM-2012-217428. pp. 1-26.
- Chapman, J.W. and Litt, U.S. (2017). Control design for an advanced geared turbofan engine. AIAA Joint Propulsion Conference 2017. Jul. 10, 2017-Jul. 12, 2017. Atlanta, GA. pp. 1-12.
- Dalton, III., W.N. (2003). Ultra high bypass ratio low noise engine study. NASA/CR-2003-212523. Nov. 2003. pp. 1-187.
- Edkins, D.P., Hirschkron, R., and Lee, R. (1972). TF34 turbofan quiet engine study. Final Report prepared for NASA. NASA-CR-120914. Jan. 1, 1972. pp. 1-99.
- Fisher, K., Berton, J., Guynn, M., Haller, B., Thurman, D., and Tong, M. (2012). NASA's turbofan engine concept study for a next-generation single-aisle transport. Presentation to ICAO's noise technology independent expert panel. Jan. 25, 2012. pp. 1-23.
- Greitzer, E.M., Bonnefoy, P.A., Delaroseblanco, E., Dorbian, C.S., Dreha, M., Hall, D.K., Hansman, R.J., Hileman, J.I., Liebeck, R.H., Levegren, J. (2010). N+3 aircraft concept designs and trade studies, final report. vol. 1. Dec. 1, 2010. NASA/CR-2010-216794/VOL1. pp. 1-187.
- Guynn, M.D., Berton, J.J., Fisher, K.L., Haller, W.J., Tong, M.T., and Thurman, D.R. (2009). Engine concept study for an advanced single-aisle transport. NASA/TM-2009-215784. pp. 1-97.
- Guynn, M.D., Berton, J.J., Fisher, K.L., Haller, W.J., Tong, M. T., and Thurman, D.R. (2009). Analysis of turbofan design options for an advanced single-aisle transport aircraft. American Institute of Aeronautics and Astronautics, pp. 1-13.
- Mavris, D.N., Schutte, J.S. (2016). Application of deterministic and probabilistic system design methods and enhancements of conceptual design tools for ERA project final report. NASA/CR-2016-219201. May 1, 2016. pp. 1-240.
- McCracken, R.C. (1979). Quiet short-haul research aircraft familiarization document. NASA-TM-81149. Nov. 1, 1979. pp. 1-76.
- Litt, J.S. (2018). Sixth NASA Glenn Research Center propulsion control and diagnostics (PCD) workshop. NASA/CP-2018-219891. Apr. 1, 2018. pp. 1-403.
- Rotordynamic instability problems in high-performance turbomachinery. (1986). NASA conference publication 2443. Jun. 2-4, 1986.
- Sargisson, D.F. (1985). Advanced propfan engine technology (APET) and single-rotation gearbox/pitch change mechanism. NASA Contractor Report-168113. R83AEB592. Jun. 1, 1985. pp. 1-476.
- Singh, R. and Houser, D.R. (1990). Non-linear dynamic analysis of geared systems. NASA-CR-180495. Feb. 1, 1990. pp. 1-263.
- Smith, C.E., Hirschkron, R., and Warren, R.E. (1981). Propulsion system study for small transport aircraft technology (STAT) Final report. NASA-CR-165330. May 1, 1981. pp. 1-216.
- Tong, M.T., Jones, S.M., Haller, W.J., and Handschuh, R.F. (2009). Engine conceptual design studies for a hybrid wing body aircraft. NASA/TM-2009-215680. Nov. 1, 2009. pp. 1-15.
- Whitaker, R. (1982). ALF 502: plugging the turbofan gap. Flight International, p. 237-241, Jan. 30, 1982.
- Munt, R. (1981). Aircraft technology assessment: Progress in low emissions engine. Technical Report. May 1981. pp. 1-171.
- Waters, M.H. and Schairer, E.T. (1977). Analysis of turbofan propulsion system weight and dimensions. NASA Technical Memorandum. Jan. 1977. pp. 1-65.
- Avco Lycoming Divison. ALF 502L Maintenance Manual. Apr. 1981. pp. 1-118.
- Type Certificate Data Sheet No. E6NE. Department of Transportation Federal Aviation Administration. Jun. 7, 2002. pp. 1-10.
- Trembley, Jr., H.F. (1977). Determination of effects of ambient conditions on aircraft engine emissions. Prepared for Environmental Protection Agency. Ann Arbor, Michigan. Sep. 1977. pp. 1-256.
- Honeywell LF502. Jane's Aero-engines, Aero-engines—Turbofan. Feb. 9, 2012.
- Honeywell LF502. Jane's Aero-engines, Aero-engines—Turbofan. Aug. 17, 2016.
- Dickey, T.A. and Dobak, E.R. (1972). The evolution and development status of ALF 502 turbofan engine. National Aerospace Engineering and Manufacturing Meeting. San Diego, California. Oct. 2-5, 1972. pp. 1-12.
- Cusick, M. (1981). Avco Lycoming's ALF 502 high bypass fan engine. Society of Automotive Engineers, inc. Business Aircraft Meeting & Exposition. Wichita, Kansas. Apr. 7-10, 1981. pp. 1-9.
- Rauch, D. (1972). Design study of an air pump and integral lift engine ALF-504 using the Lycoming 502 core. Prepare for NASA. Jul. 1972. pp. 1-182.
- Dassault Falcon 900EX Easy Systems Summary. Retrieved from: <http://www.smartcockpit.com/docs/F900EX-Engines.pdf> pp. 1-31.
- Honeywell TFE731 Pilot Tips. pp. 1-143.
- Honeywell TFE731-5AR to -5BR Engine Conversion Program. Sep. 2005. pp. 1-4.
- Garret TFE731 Turbofan Engine (CAT C). Chapter 79: Lubrication System. TFE731 Issue 2. 2010. pp. 1-24.
- McArdle, J.G. (1979). Static test-stand performance of the YF-102 turbofan engine with several exhaust configurations for the quiet short-haul research aircraft (QSRA). Nasa Technical Paper. Nov. 1979. pp. 1-68.
- The International Preliminary Report on Patentability for PCT Application No. PCT/US2012/071906, dated Jul. 24, 2014.

(56)

References Cited

OTHER PUBLICATIONS

- Meier, N (2005). Civil Turbojet/Turbofan Specifications. Retrieved from <http://www.jet-engine.net/civtfspec.html>.
- Zalud, "Gears Put a New Spin on Turbofan Performance" Machine Design, Nov. 5, 1998, 2010Penton Media, Inc., 5 pp.
- The European Search Report and Written Opinion for European Application No. EP 12198136, completed on Aug. 21, 2013.
- The International Search Report and Written Opinion for International Application No. PCT/US2012/071906, completed on Aug. 22, 2013.
- Kandebo; Geared-Turbofan Engine Design Targets Cost, Complexity, Aviation Week & Space Technology; New York; Feb. 23, 1998, 4 pp.
- Hendricks et al., "Performance and Weight Estimates for an Advanced Open Rotor Engine" NASA/TM-2012-217710, Sep. 2012, 20 pp.
- Gunston, "Jane's Aero-Engines" Pratt & Whitney/USA, Mar. 2000, JAEng-Issue 7, 5 pp.
- Japanese Office Action for Japanese Application No. 2007-202444, dated Aug. 3, 2010.
- European Search Report for EP Application No. 07253078.5, dated Dec. 5, 2007.
- Notice of Opposition to Patent No. 2610463. United Technologies Corporation opposed by Safran Aircraft Engines. Mailed Aug. 3, 2016.
- Decision Institution of Inter Partes Review. *General Electric Company*, Petitioner, v. *United Technologies Corp.*, Patent Owner. IPR2017-01001. U.S. Pat. No. 8,894,538. Entered Jul. 10, 2017. pp. 1-4.
- European Search Report for European Application No. 16183877.6 dated Jan. 5, 2017.
- Petition for Inter Partes Review of U.S. Pat. No. 8,894,538. *General Electric Company*, Petitioner, v. *United Technologies Corporation*, Patent Owner. Filed Mar. 1, 2017.
- Meyer, A.G. (1988). Transmission development of TEXTRON Lycoming's geared fan engine. Technical Paper. Oct. 1988. pp. 1-12.
- Dudley, D.W., Ed. (1962). Gear handbook. New York, NY: McGraw-Hill. pp. 14-17 (TOC, Preface, and Index).
- Wilfert, G. (2008). Geared fan. Aero-Engine Design: From State of the Art Turbofans Towards Innovative Architectures, von Karman Institute for Fluid Dynamics, Belgium, Mar. 3-7, 2008. pp. 1-26.
- European Search Report for European Application No. 16174068.3 dated Nov. 22, 2016.
- Extended European Search Report for European Application No. 16171476.1 dated Oct. 6, 2016.
- European Search Report for European Patent Application No. 12198045.2 completed Sep. 7, 2015.
- European Search Report for European Patent Application No. 18203501.4, completed Feb. 11, 2019.
- Anderson, R.D. (1985). Advanced Propfan Engine Technology (APET) definition study, single and counter-rotation gearbox/pitch change mechanism design. NASA CR-168115. Jul. 1, 1985. pp. 1-289.
- Newton, F.C., Liebeck, R.H., Mitchell, G.H., Mooiweer, M.A., Platte, M.M., Toogood, T.L., and Wright, R.A. (1986). Multiple Application Propfan Study (MAPS): Advanced tactical transport. NASA CR-175003. Mar. 1, 1986. pp. 1-101.
- Gliebe, P.R., Ho, P.Y., and Mani, R. (1995). UHB engine fan and broadband noise reduction study. NASA DR-198357. Jun. 1995. pp. 1-48.
- Holcombe, V. (2003). Aero-Propulsion Technology (APT) task V low noise ADP engine definition study. NASA CR-2003-212521. Oct. 1, 2003. pp. 1-73.
- Sutliff, D. (2005). Rotating rake turbofan duct mode measurement system. NASA TM-2005-213828. Oct. 1, 2005. pp. 1-34.
- Adamson, A.P. (1975). Quiet Clean Short-Haul Experimental Engine (QCSEE) design rationale. Society of Automotive Engineers Air Transportation Meeting. Hartford, CT. May 6-8, 1975. pp. 1-9.
- NASA Conference Publication. (1978). CTOL transport technology. NASA-CP-2036-PT-1. Jun. 1, 1978. pp. 1-531.
- Kandebo, S.W. (1998). Geared-Turbofan engine design targets cost, complexity. Aviation Week & Space Technology, 148(8). p. 34-5.
- Davis, D.G.M. (1973). Variable-pitch fans: Progress in Britain. Flight International. Apr. 19, 1973. pp. 615-617.
- Levintan, R.M. (1975). Q-Fan demonstrator engine. Journal of Aircraft. vol. 12(8). Aug. 1975. pp. 658-663.
- Technical Report. (1975). Quiet Clean Short-haul Experimental Engine (QCSEE) UTW fan preliminary design. NASA-CR-134842. Feb. 1, 1975. pp. 1-98.
- Aerospace Information Report. (2008). Advanced ducted propulsor in-flight thrust determination. SAE International AIR5450. Aug. 2008. p. 1-392.
- Daggett, D.L., Brown, S.T., and Kawai, R.T. (2003). Ultra-efficient engine diameter study. NASA/CR-2003-212309. May 2003. pp. 1-52.
- Haldenbrand, R. and Norgren, W.M. (1979). Airesearch QCGAT program [quiet clean general aviation turbofan engines]. NASA-CR-159758. pp. 1-199.
- Honeywell LF507. Jane's Aero-engines, Aero-engines—Turbofan. Feb. 9, 2012.
- Honeywell TFE731. Jane's Aero-engines, Aero-engines—Turbofan. Jul. 18, 2012.
- NASA Conference Publication. Quiet, powered-lift propulsion. Cleveland, Ohio. Nov. 14-15, 1978. pp. 1-420.
- "Civil Turbojet/Turbofan Specifications", Jet Engine Specification Database (Apr. 3, 2005).
- Kandebo, S.W. (1993). Geared-turbofan engine design targets cost, complexity. Aviation Week & Space Technology, 148(8). Start p. 32.
- Hendricks, E.S. and Tong, M.T. (2012). Performance and weight estimates for an advanced open rotor engine. NASA/TM-2012-217710. pp. 1-13.
- Guynn, M. D., Berton, J.J., Fisher, K. L., Haller, W.J., Tong, M. T., and Thurman, D.R. (2011). Refined exploration of turbofan design options for an advanced single-aisle transport. NASA/TM-2011-216883. pp. 1-27.
- Zalud, T. (1998). Gears put a new spin on turbofan performance. Machine Design, 70(20), p. 104.
- Kurzke, J. (2008). Preliminary Design, Aero-engine design: From state of the art turbofans towards innovative architectures, pp. 1-72.
- Zamboni, G. and Xu, L. (2009). Fan root aerodynamics for large bypass gas turbine engines: Influence on the engine performance and 3D design. Proceedings of ASME Turbo Expo 2009: Power for Land, Sea and Air. Jun. 8-12, 2009, Orlando, Florida, USA. pp. 1-12.
- Han, J., Dutta, S., and Ekkad, S.V. (2000). Gas turbine heat transfer and cooling technology. New York, NY: Taylor & Francis, pp. 1-25, 129-157, and 160-249.
- Mattingly, J.D. (1996). Elements of gas turbine propulsion. New York, New York: McGraw-Hill, Inc. pp. 1-18, 50-62, 85-87, 95-104, 121-123, 223-234, 242-245, 278-280, 303-309, 323-326, 462-479, 517-520, 563-565, 673-675, 682-685, 697-699, 703-705, 802-805, 862-864, and 923-925.
- Declaration of Reza Abhari, Ph.D. In re U.S. Pat. No. 8,844,265. Executed Jun. 28, 2016. pp. 1-91.
- Declaration of John Eaton, Ph.D. In re U.S. Pat. No. 8,869,568. Executed Mar. 28, 2016. pp. 1-87.
- Declaration of Reza Abhari. In re U.S. Pat. No. 8,695,920. Executed Nov. 30. pp. 1-67.
- Declaration of Reza Abhari. In re U.S. Pat. No. 8,448,895. Executed Nov. 28. pp. 1-81.
- Declaration of Reza Abhari. In re U.S. Pat. No. 8,695,920, claims 1-4, 7-14, 17 and 19. Executed Nov. 29. pp. 1-102.
- Declaration of Dr. Magdy Attia. In re U.S. Pat. No. 8,313,280. Executed Oct. 21, 2016. pp. 1-88.
- Lord, W.K., MacMartin, D.G., and Tillman, T.G. (2000). Flow control opportunities in gas turbine engines. American Institute of Aeronautics and Astronautics, pp. 1-15.
- Daly, M. Ed. (2010). Jane's Aero-Engine. Issue Twenty-seven. Mar. 2010. p. 633-636.
- Roux, E. (2007). Turbofan and turbojet engines database handbook. Editions Elodie Roux. Blagnac: France, pp. 1-595.
- Declaration of Dr. Magdy Attia. In re U.S. Pat. No. 8,517,668. Executed Dec. 8, 2016. pp. 1-81.

(56)

References Cited

OTHER PUBLICATIONS

- Cramoisi, G. Ed. (2012). *Death in the Potomac: The crash of Air Florida Flight 90*. Air Crash Investigations. Accident Report NTSB/AAR-82-8. p. 45-47.
- Norton, M. and Karczub, D. (2003). *Fundamentals of noise and vibration analysis for engineers*. Press Syndicate of the University of Cambridge New York: New York, p. 524.
- U.S. Department of Transportation: Federal Aviation Administration Advisory Circular. Runway overrun prevention. Dated: Nov. 6, 2007. p. 1-8 and Appendix 1 p. 1-15, Appendix 2 p. 1-6, Appendix 3 p. 1-3, and Appendix 4 p. 1-5.
- U.S. Department of Transportation: Federal Aviation Administration Advisory Circular. Standard operating procedures for flight deck crewmembers. Dated: Feb. 27, 2003 . . . p. 1-6 and Appendices.
- Vasudevan, A.K. and Petrovic, J.J. (1992). A comparative overview of molybdenum disilicide composites. *Materials Science and Engineering*, A155, 1992. pp. 1-17.
- Clarke, D.R. and Levi, C.G. (2003). Materials design for the next generation thermal barrier coatings. *Annual. Rev. Mater. Res.* vol. 33. 2003. pp. 383-417.
- Lee, K.N. (2000). Current status of environmental barrier coatings for Si-Based ceramics. *Surface and Coatings Technology* 133-134, 2000. pp. 1-7.
- Bornstein, N. (1993). Oxidation of advanced intermetallic compounds. *Journal de Physique IV*, 1993, 03 (C9), pp. C9-367-C9-373.
- Krenkel, W., Naslain, R., and Schneider, H. Eds. (2001). *High temperature ceramic matrix composites* pp. 224-229. Weinheim, DE: Wiley-VCH Verlag GmbH.
- Gibala, R., Ghosh, A.K., Van Aken, D.C., Srolovitz, D.J., Basu, A., Chang, H., . . . Yang, W. (1992). Mechanical behavior and interface design of MoSi₂-based alloys and composites. *Materials Science and Engineering*, A155, 1992 pp. 147-158.
- Shah, D.M. (1992). MoSi₂ and other silicides as high temperature structural materials. *Superalloys 1992. The Minerals, Metals, & Materials Society*, pp. 409-422.
- Zhao, J.C. and Westbrook, J.H. (2003). Ultrahigh-temperature materials for jet engines. *MRS Bulletin*. vol. 28 (9). Sep. 2003. pp. 622-630.
- Tsirlin, M., Pronin, Y.E., Florina, E.K., Mukhametov, S. Kh., Khatsernov, M.A., Yun, H.M., . . . Kroke, E. (2001). Experimental investigation of multifunctional interphase coatings on SiC fibers for non-oxide high temperature resistant CMCs. *High Temperature Ceramic Matrix Composites. 4th Int'l Conf, on High Temp. Ceramic Matrix Composites*. Oct. 1-3, 2001. pp. 149-156.
- Jacobson, N.S. (1993). Corrosion of silicon-based ceramics in combustion environments. *J. Am. Ceram. Soc.* 76 (1). pp. 3-28.
- Jorgensen, P.J., Wadsworth, M.E., and Cutler, I.B. (1961). Effects of water vapor on oxidation of silicon carbide. *J. Am. Ceram. Soc.* 44(6). pp. 248-261.
- Xu, Y., Cheng, L., Zhang, L., Ying, H., and Zhou, W. (1999). Oxidation behavior and mechanical properties of C/SiC composites with Si-MoSi₂ oxidation protection coating. *J. of Mat. Sci.* vol. 34. 1999. pp. 6009-6014.
- Sundaram, S.K., Hsu, J-Y., Speyer, R.F. (1995). Molten glass corrosion resistance of immersed combustion-heating tube materials in e-glass. *J. Am. Ceram. Soc.* 78(7). pp. 1940-1946.
- Jeng, Y.-L., Lavernia, E.J. (1994). Processing of molybdenum disilicide. *J. of Mat. Sci.* vol. 29. 1994. pp. 2557-2571.
- Suzuki, Y., Morgan, P.E.D., and Niihara, K. (1998). Improvement in mechanical properties of powder-processed MoSi₂ by the addition of Sc₂O₃ and Y₂O₃. *J. Am. Ceram. Soci.* 81(12). pp. 3141-3149.
- Webster, J.D., Westwood, M.E., Hayes, F.H., Day, R.J., Taylor, R., Duran, A., . . . Vogel, W.D. (1998). Oxidation protection coatings for C/SiC based on yttrium silicate. *Journal of European Ceramic Society* vol. 18. 1998. pp. 2345-2350.
- Petrovic, J.J., Castro, R.G., Vaidya, R.U., Peters, M.L, Mendoza, D., Hoover, R.C., and Gallegos, D.E. (2001). Molybdenum disilicide materials for glass melting sensor sheaths. *Ceramic Engineering and Science Proceedings* vol. 22(3). 2001. pp. 59-64.
- Kahn, H., Tayebi, N., Ballarini, R., Mullen, R.L., Heuer, A.H. (2000). Fracture toughness of polysilicon MEMS devices. *Sensors and Actuators* vol. 82. 2000. pp. 274-280.
- Muhlstein, C.L., Stach, E.A., and Ritchie, R.O. (2002). A reaction-layer mechanism for the delayed failure of micron-scale polycrystalline silicon structural films subjected to high-cycle fatigue loading. *Acta Materialia* vol. 50. 2002. pp. 3579-3595.
- Sundaram, S.K., Hsu, J-Y., Speyer, R.F. (1994). Molten glass corrosion resistance of immersed combustion-heating tube materials in soda-lime-silicate glass. *J. Am. Ceram. Soc.* 77(6). pp. 1613-1623.
- Leckie, F.A. and Dal Bello, D.J. (2009). *Strength and stiffness of engineering systems*. Mechanical Engineering Series. Springer. pp. 1-3.
- El-Sayad, A.F. (2008). *Aircraft propulsion and gas turbine engines*. Boca Raton, FL: CRC Press, pp. 215-219 and 855-860.
- Bunker, R.S. (2005). A review of shaped hole turbine film-cooling technology. *Journal of Heat Transfer* vol. 127. Apr. 2005. pp. 441-453.
- Summons to Attend Oral Proceedings for European Patent Application No. 12871934.1 dated Jan. 7, 2020.
- Bloomer, H.E., Loeffler, I.J., Kreim, W.J., and Coats, J.W. (1981). Comparison of NASA and contractor results from aeroacoustic tests of QCSEE OTW engine. *NASA Technical Memorandum* 81761. Apr. 1, 1981. pp. 1-30.
- Bloomer, H.E. and Samanich, N.E. (1982). QCSEE under-the-wing engine acoustic data. *NASA-TM-82691*. May 1, 1982. pp. 1-28.
- Bloomer, H.E. and Loeffler, I.J. (1982). QCSEE over-the-wing engine acoustic data. *NASA-TM-82708*. May 1, 1982. pp. 1-558.
- Bloomer, H.E. and Samanich, N.E. (1982). QCSEE under-the-wing engine-wing-flap aerodynamic profile characteristics. *NASA-TM-82890*. Sep. 1, 1982. pp. 1-48.
- Howard, D.F. (1976). QCSEE preliminary under the wing flight propulsion system analysis report. *NASA CR-134868*. Feb. 1, 1976. pp. 1-260.
- Misel, O.W. (1977). QCSEE main reduction gears test program. *NASA CR-134669*. Mar. 1, 1977. pp. 1-222.
- QCSEE Preliminary analyses and design report. vol. 1. (1974). *NASA-CR-134838*. Oct. 1, 1974. pp. 1-337.
- QCSEE preliminary analyses and design report. vol. II. (1974). *NASA-CR-134839*. Oct. 1, 1974. pp. 340-630.
- QCSEE under-the-wing engine composite fan blade design. (1975). *NASA-CR-134840*. May 1, 1975. pp. 1-51.
- QCSEE the aerodynamic and preliminary mechanical design of the QCSEE OTW fan. (1975). *NASA-CR-134841*. Feb. 1, 1975. pp. 1-74.
- QCSEE under-the-wing engine composite fan blade preliminary design test report. (1975). *NASA-CR-134846*. Sep. 1, 1975. pp. 1-56.
- QCSEE over-the-wing final design report. (1977). *NASA-CR-134848*. Jun. 1, 1977. pp. 1-503.
- QCSEE hamilton standard cam/harmonic drive variable pitch fan actuation system derail design report. (1976). *NASA-CR-134852*. Mar. 1, 1976. pp. 1-172.
- QCSEE main reduction gears bearing development program final report. (1975). *NASA-CR-134890*. Dec. 1, 1975. pp. 1-41.
- QCSEE under-the-wing engine digital control system design report. (1978). *NASA-CR-134920*. Jan. 1, 1978. pp. 1-309.
- QCSEE the aerodynamic and mechanical design of the QCSEE under-the-wing fan. (1977). *NASA-CR-135009*. Mar. 1, 1977. pp. 1-137.
- QCSEE under-the-wing engine composite fan blade final design test report. (1977). *NASA-CR-135046*. Feb. 1, 1977. pp. 1-55.
- QCSEE over-the-wing propulsion system test report vol. III—mechanical performance. (1978). *NASA-CR-135325*. Feb. 1, 1978. pp. 1-112.
- QCSEE ball spline pitch-change mechanism whirligig test report. (1978). *NASA-CR-135354*. Sep. 1, 1978. pp. 1-57.
- Quiet clean general aviation turbofan (QCGAT) technology study final report vol. I. (1975). *NASA-CR-164222*. Dec. 1, 1975. pp. 1-186.

(56)

References Cited

OTHER PUBLICATIONS

- Neitzel, R.E., Hirschkron, R. and Johnston, R.P. (1976). Study of unconventional aircraft engines designed for low energy consumption NASA-CR-135136. Dec. 1, 1976. pp. 1-153.
- Neitzel, R., Lee, R., and Chamay, A.J. (1973). Engine and installation preliminary design. Jun. 1, 1973. pp. 1-333.
- Parametric study of STOL short-haul transport engine cycles and operational techniques to minimize community noise impact. NASA-CR-114759. Jun. 1, 1974. pp. 1-398.
- Sowers, H.D. and Coward, W.E. (1978). QCSEE over-the-wing (OTW) engine acoustic design. NASA-CR-135268. Jun. 1, 1978. pp. 1-52.
- Schaefer, J.W., Sagerser, D.R., and Stakolich, E.G. (1977). Dynamics of high-bypass-engine thrust reversal using a variable-pitch fan. Technical Report prepared for NASA. NASA-TM-X-3524. May 1, 1977. pp. 1-33.
- Summons to Attend Oral Proceedings for European Application No. 16183877.6 dated Feb. 9, 2021.
- Notice of Opposition for European Patent No. 3456940 (18203501.4) dated May 11, 2021 by Safran Aircraft Engines.
- McMillian, A. (2008) Material development for fan blade containment casing. Abstract, p. 1. Conference on Engineering and Physics: Synergy for Success 2006. Journal of Physics: Conference Series vol. 105. London, UK. Oct. 5, 2006.
- Kurzke, J. (2009) Fundamental differences between conventional and geared turbofans. Proceedings of ASME Turbo Expo: Power for Land, Sea, and Air. 2009, Orlando, Florida, pp. 145-153.
- Agarwal, B.D and Broutman, L.J. (1990). Analysis and performance of fiber composites, 2nd Edition. John Wiley & Sons, Inc. New York: New York. pp. 1-30, 50-1, 56-8, 60-1, 64-71, 87-9, 324-9, 436-7.
- Carney, K., Pereira, M. Revilock, and Matheny, P. (2003) Jet engine fan blade containment using two alternate geometries. 4th European LS-DYNA Users Conference, pp. 1-10.
- Brines, G.L. (1990). The turbofan of tomorrow. Mechanical Engineering: The Journal of the American Society of Mechanical Engineers, 108(8), 65-67.
- Faghri, A. (1995). Heat pipe and science technology. Washington, D.C.: Taylor & Francis, pp. 1-60.
- Hess, C. (1998). Pratt & Whitney develops geared turbofan. Flug Revue 43(7). Oct. 1998.
- Grady, J.E., Weir, D.S., Lamoureux, M.C., and Martinez, M.M. (2007). Engine noise research in NASA's quiet aircraft technology project Papers from the International Symposium on Air Breathing Engines (ISABE). 2007.
- Griffiths, B. (2005). Composite fan blade containment case. Modern Machine Shop. Retrieved from: <http://www.mmsonline.com/articles/composite-fan-blade-containment-case> pp. 1-4.
- Hall, C.A. and Crichton, D. (2007). Engine design studies for a silent aircraft. Journal of Turbomachinery, 129, 479-487.
- Haque, A. and Shamsuzzoha, M., Hussain, F., and Dean, D. (2003). S20-glass/epoxy polymer nanocomposites: Manufacturing, structures, thermal and mechanical properties. Journal of Composite Materials, 37 (20), 1821-1837.
- Brennan, P.J. and Krolczek, E.J. (1979). Heat pipe design handbook. Prepared for National Aeronautics and Space Administration by B & K Engineering, Inc. Jun. 1979. pp. 1-348.
- Horikoshi, S. and Serpone, N. (2013). Introduction to nanoparticles. Microwaves in nanoparticle synthesis. Wiley-VCH Verlag GmbH & Co. KGaA. pp. 1-24.
- Kerrebrock, J.L. (1977). Aircraft engines and gas turbines. Cambridge, MA: The MIT Press, p. 11.
- Xie, M. (2008). Intelligent engine systems: Smart case system. NASA/CR-2008-215233. pp. 1-31.
- Knip, Jr., G. (1987). Analysis of an advanced technology subsonic turbofan incorporating revolutionary materials. NASA Technical Memorandum. May 1987. pp. 1-23.
- Willis, W.S. (1979). Quiet clean short-haul experimental engine (QCSEE) final report. NASA/CR-159473 pp. 1-289.
- Kojima, Y., Usuki, A. Kawasumi, M Okada, A., Fukushim, Y., Kurauchi, T., and Kamigaito, O. (1992). Mechanical properties of nylon 6-clay hybrid. Journal of Materials Research, 8(5), 1185-1189.
- Kollar, L.P. and Springer, G.S. (2003). Mechanics of composite structures. Cambridge, UK: Cambridge University Press, p. 465.
- Ramsden, J.M. (Ed). (1978). The new European airliner. Flight International, 113(3590). Jan. 7, 1978. pp. 39-43.
- Langston, L. and Faghri, A. Heat pipe turbine vane cooling. Prepared for Advanced Turbine Systems Annual Program Review. Morgantown, West Virginia. Oct. 17-19, 1995. pp 3-9.
- Oates, G.C. (Ed). (1989). Aircraft propulsion systems and technology and design. Washington, DC.: American Institute of Aeronautics, Inc. pp. 341-344.
- Lau, K., Gu, C., and Hui, D. (2005). A critical review on nanotube and nanotube/nanoclay related polymer composite materials. Composites: Part B 37(2006) 425-436.
- Shorter Oxford English dictionary, 6th Edition. (2007). vol. 2, N-Z. p. 1888.
- Lynwander, P. (1983). Gear drive systems: Design and application. New York, New York: Marcel Dekker, Inc. pp. 145, 355-358.
- Sweetman, B. and Sutton, O. (1998). Pratt & Whitney's surprise leap. Interavia Business & Technology, 53.621, p. 25.
- Mattingly, J.D. (1996). Elements of gas turbine propulsion. New York, New York: McGraw-Hill, Inc. pp. 8-15.
- Pyrograf-III Carbon Nanofiber. Product guide. Retrieved Dec. 1, 2015 from: http://pyrografproducts.com/Merchant5/merchant.mvc?Screen=cp_nanofiber.
- Nanocor Technical Data for Epoxy Nanocomposites using Nanomer 1.30E Nanoclay. Nnanacor, Inc. Oct. 2004.
- Ratna, D. (2009). Handbook of thermoset resins. Shawbury, UK: iSmithers. pp. 187-216.
- Wendus, B.E., Stark, D.F., Holler, R.P., and Funkhouser, M.E. (2003). Follow-on technology requirement study for advanced subsonic transport NASA/CR-2003-212467. pp. 1-37.
- Silverstein, C.C., Gottschlich, J.M., and Meininger, M. The feasibility of heat pipe turbine vane cooling. Presented at the International Gas Turbine and Aeroengine Congress and Exposition, The Hague, Netherlands. Jun. 13-16, 1994. pp. 1-7.
- Merriam-Webster's collegiate dictionary, 11th Ed. (2009). p. 824.
- Merriam-Webster's collegiate dictionary, 10th Ed. (2001). p. 1125-1126.
- Hughes, C. (2010). Geared turbofan technology. NASA Environmentally Responsible Aviation Project. Green Aviation Summit. NASA Ames Research Center. Sep. 8-9, 2010. pp. 1-8.
- Gliebe, P.R. and Janardan, B.A. (2003). Ultra-high bypass engine aeroacoustic study. NASA/CR-2003-21252. GE Aircraft Engines, Cincinnati, Ohio. Oct. 2003. pp. 1-103.
- Moxon, J. How to save fuel in tomorrow's engines. Flight International. Jul. 30, 1983. 3873(124). pp. 272-273.
- File History for U.S. Appl. No. 12/131,876.
- Fledderjohn, K.R. (1983). The IFE731-5: Evolution of a decade of business jet service. SAE Technical Paper Series Business Aircraft Meeting & Exposition. Wichita, Kansas. Apr. 12-15, 1983. pp. 1-12.
- Gunston, B. (Ed.) (2000). Jane's aero-engines, Issue seven. Coulsdon, Surrey, UK: Jane's Information Group Limited. pp. 510-512.
- Ivchenko-Progress D-436. Jane's Aero-engines, Aero-engines—Turbofan. Feb. 8, 2012.
- Ivchenko-Progress AI-727M. Jane's Aero-engines, Aero-engines—Turbofan. Nov. 27, 2011.
- Ivchenko-Progress D-727. Jane's Aero-engines, Aero-engines—Turbofan. Feb. 7, 2007.
- Turbomeca Aubisque. Jane's Aero-engines, Aero-engines—Turbofan. Nov. 2, 2009.
- Aviadgatel D-110. Jane's Aero-engines, Aero-engines—Turbofan. Jun. 1, 2010.
- Rolls-Royce M45H. Jane's Aero-engines, Aero-engines—Turbofan. Feb. 24, 2010.
- European Search Report for European Patent Application No. 20211628.1 completed Apr. 1, 2021.
- Davies, D. and Miller, D.C. (1971). A variable pitch fan for an ultra quiet demonstrator engine. 1976 Spring Convention: Seeds for Success in Civil Aircraft Design in the Next Two Decades, pp. 1-18.

(56)

References Cited

OTHER PUBLICATIONS

- Middleton, P. (1971). 614: VFW's jet feederliner. *Flight International*, Nov. 4, 1971. p. 725, 729-732.
- Schaefer, J.W., Sagerser, D.R., and Stakolich, E.G. (1977). Dynamics of high-bypass-engine thrust reversal using a variable-pitch fan. Technical Report prepared for NASA. NASA-TM-X-3524. May 1, 1977. pp. 1-33.
- Savelle, S.A. and Garrard, G.D. (1996). Application of transient and dynamic simulations to the U.S. Army T55-L-712 helicopter engine. The American Society of Mechanical Engineers. Presented Jun. 10-13, 1996. pp. 1-8.
- Drago, R.J. and Margasahayam, R.N. (1987). Stress analysis of planet gears with integral bearings; 3D finite-element model development and test validation. 1987 MSC NASTRAN World Users Conference. Los Angeles, CA. Mar. 1987. pp. 1-14.
- Baker, R.W. (2000). *Membrane technology and applications*. New York, NY: McGraw-Hill. pp. 87-153.
- Cheryan, M. (1998). *Ultrafiltration and microfiltration handbook*. Lancaster, PA: Technomic Publishing Company, Inc. pp. 171-236.
- Seader, J.D. and Henley, E.J. (1998). *Separation process principles*. New York, NY: John Wiley & Sons, Inc. pp. 722-726 and 764-771.
- Spadaccini, L.J., and Huang, H. (2002). On-line fuel deoxygenation for coke suppression. ASME, Jun. 2002. pp. 1-7.
- Darrah, S. (1987). Jet fuel deoxygenation. Interim Report for Period Mar. 1987-Jul. 1988. pp. 1-22.
- Bucknell, R.L. (1973). Influence of fuels and lubricants on turbine engine design and performance, fuel and lubricant analyses. Final Technical Report, Mar. 1971-Mar. 1973. pp. 1-252.
- Hazlett, R.N. (1991). *Thermal oxidation stability of aviation turbine fuels*. Philadelphia, PA: ASTM. pp. 1-163.
- Taylor, W.F. (1974). Deposit formation from deoxygenated hydrocarbons. I. General features. *Ind. Eng. Chem., Prod. Res. Develop.*, vol. 13(2). 1974. pp. 133-138.
- Taylor, W.F. (1974). Deposit formation from deoxygenated hydrocarbons. II. Effect of trace sulfur compounds. *Ind. Eng. Chem., Prod. Res. Dev.*, vol. 15(1). 1974. pp. 64-68.
- Taylor, W.F. and Frankenfeld, J.W. (1978). Deposit formation from deoxygenated hydrocarbons. 3. Effects of trace nitrogen and oxygen compounds. *Ind. Eng. Chem., Prod. Res. Dev.*, vol. 17(1). 1978. pp. 86-90.
- Frankenfeld, J.W. and Taylor, W.F. (1980). Deposit formation from deoxygenated hydrocarbons. 4. Studies in pure compound systems. *Ind. Eng. Chem., Prod. Res. Dev.*, vol. 19(1). 1978. pp. 65-70.
- Hemighaus, G., Boval, T., Bacha, J., Barnes, F., Franklin, M., Gibbs, L., . . . Morris, J. (2007). *Aviation fuels: Technical review*. Chevron Products Company, pp. 1-94. Retrieved from: https://www.cgabusinessdesk.com/document/aviation_tech_review.pdf.
- Spadaccini, L.J., Sobel, D.R., and Huang, H. (2001). Deposit formation and mitigation in aircraft fuels. *Journal of Eng. For Gas Turbine and Power*, vol. 123. Oct. 2001. pp. 741-746.
- Edwards, T. and Zabarnick, S. (1993). Supercritical fuel deposition mechanisms. *Ind. Eng. Chem. Res.* vol. 32. 1993. pp. 3117-3122.
- Huang, H., Sobel, D.R., and Spadaccini, L.J. (2002). Endothermic heat-sink of hydrocarbon fuels for scramjet cooling. *AIAA/ASME/SAE/ASEE*, Jul. 2002. pp. 1-7.
- Bessarabov, D.G., Jacobs, E.P., Sanderson, R.D., and Beckman, I.N. (1996). Use of nonporous polymeric flat-sheet gas-separation membranes in a membrane-liquid contactor: experimental studies. *Journal of Membrane Sciences*, vol. 113. 1996. pp. 275-284.
- Matsumoto, T., Toshiro, U., Kishida, A., Tsutomu, F., Maruyama, I., and Akashi, M. (1996). Novel functional polymers: Poly(dimethylsiloxane)-polyamide multiblock copolymer. VII. Oxygen permeability of aramid-silicone membranes in a gas-membrane-liquid system. *Journal of Applied Polymer Science*, vol. 64(6). May 9, 1997. pp. 1153-1159.
- Technical Data. Teflon. WS Hampshire Inc. Retrieved from: http://catalog.wshampshire.com/Asset/psg_teflon_ptfe.pdf.
- Anderson, N.E., Loewenthal, S.H., and Black, J.D. (1984). An analytical method to predict efficiency of aircraft gearboxes. NASA Technical Memorandum prepared for the Twentieth Joint Propulsion Conference. Cincinnati, OH. Jun. 11-13, 1984. pp. 1-25.
- Hughes, C. (2002). Aerodynamic performance of scale-model turbofan outlet guide vanes designed for low noise. Prepared for the 40th Aerospace Sciences Meeting and Exhibit. Reno, NV. NASA/TM-2001-211352. Jan. 14-17, 2002. pp. 1-38.
- Kaplan, B., Nicke, E., Voss, C. (2006). Design of a highly efficient low-noise fan for ultra-high bypass engines. Proceedings of GT2006 for ASME Turbo Expo 2006: Power for Land, Sea and Air. Barcelona, SP. May 8-11, 2006. pp. 1-10.
- Gates, D. Bombardier flies at higher market. *Seattle Times*. Jul. 13, 2008. pp. C6.
- Decker, S. and Clough, R. (2016). GE wins shot at voiding pratt patent in jet-engine clash. *Bloomberg Technology*. Retrieved from: <https://www.bloomberg.com/news/articles/2016-06-30/ge-wins-shot-to-invalid-pratt-airplane-engine-patent-in-u-s>.
- Trembley, Jr., H.F. (1977). Determination of effects of ambient conditions on aircraft engine emissions. ALF 502 combustor rig testing and engine verification test. Prepared for Environmental Protection Agency. Sep. 1977. pp. 1-256.
- Lewicki, D.G., Black, J.D., Savage, M., and Coy, J.J. (1985). Fatigue life analysis of a turboprop reduction gearbox. NASA Technical Memorandum. Prepared for the Design Technical Conference (ASME). Sep. 11-13, 1985. pp. 1-26.
- McCune, M.E. (1993). Initial test results of 40,000 horsepower fan drive gear system for advanced ducted propulsion systems. AIAA 29th Joint Conference and Exhibit. Jun. 28-30, 1993. pp. 1-10.
- Wright, G.H. and Russell, J.G. (1990). The M.45SD-02 variable pitch geared fan engine demonstrator test and evaluation experience. *Aeronautical Journal*, vol. 84(836). Sep. 1980. pp. 268-277.
- Drago, R.J. (1974). Heavy-lift helicopter brings up drive ideas. *Power Transmission Design*. Mar. 1987. pp. 1-15.
- Krantz, T.L. (1990). Experimental and analytical evaluation of efficiency of helicopter planetary stage. NASA Technical Paper. Nov. 1990. pp. 1-19.
- Heingartner, P., Mba, D., Brown, D. (2003). Determining power losses in the helical gear mesh; Case Study. ASME 2003 Design Engineering Technical Conferences. Chicago, IL. Sep. 2-6, 2003. pp. 1-7.
- Thulin, R.D., Howe, D.C., and Singer, I.D. (1982). Energy efficient engine: High pressure turbine detailed design report. Prepared for NASA. NASA CR-165608. pp. 1-178.
- Reshotko, M., Karchmer, A., Penko, P.F. (1977). Core noise measurements on a YF-102 turbofan engine. NASA TM X-73587. Prepared for Aerospace Sciences Meeting sponsored by the American Institute of Aeronautics and Astronautics. Jan. 24-26, 1977.
- Gray, D.E. (1978). Energy efficient engine preliminary design and integration studies. Prepared for NASA. NASA CR-135396. Nov. 1978. pp. 1-366.
- Reynolds, C.N. (1985). Advanced prop-fan engine technology (APET) single- and counter-rotation gearbox/pitch change mechanism. Prepared for NASA. NASA CR-168114 (vol. I). Jul. 1985. pp. 1-295.
- McArdle, J.G. and Moore, A.S. (1979). Static test-stand performance of the YF-102 turbofan engine with several exhaust configurations for the Quiet Short-Haul Research Aircraft (QSRA). Prepared for NASA. NASA-TP-1556. Nov. 1979. pp. 1-68.
- Mattingly, J.D. (1996). *Elements of gas turbine propulsion*. New York, New York: McGraw-Hill, Inc. pp. 1-18, 60-62, 85-87, 95-104, 121-123, 223-234, 242-245, 278-285, 303-309, 323-326, 462-479, 517-520, 563-565, 630-632, 668-670, 673-675, 682-685, 697-705, 726-727, 731-732, 802-805, 828-830 and appendices.
- Falchetti, F., Quiniou, H., and Verdier, L. (1994). Aerodynamic design and 3D Navier-Stokes analysis of a high specific flow fan. ASME. Presented at the International Gas Turbine and Aeroengine Congress and Exposition. The Hague, Netherlands. Jun. 13-16, 1994. pp. 1-10.
- Datasheet. CF6-80C2 high-bypass turbofan engines. Retrieved from <https://geaviation.com/sites/default/files/datasheet-CF6-80C2.pdf>.
- Salemme, C.T. and Murphy, G.C. (1979). Metal spar/superhybrid shell composite fan blades. Prepared for NASA. NASA-CR-159594. Aug. 1979. pp. 1-127.
- "Press release. The GE90 engine. Retrieved from: <https://www.geaviation.com/commercial/engines/ge90-engine>; <https://www>.

(56)

References Cited

OTHER PUBLICATIONS

[geaviation.com/press-release/ge90-engine-family/ge90-115b-fan-completing-blade-testing-schedule-first-engine-test](https://www.geaviation.com/press-release/ge90-engine-family/ge90-115b-fan-completing-blade-testing-schedule-first-engine-test); and <https://www.geaviation.com/press-release/ge90-engine-family/ge'scomposite-fan-blade-revolution-turns-20-years-old>".

Datasheet. Genx™ high bypass turbofan engines. Retrieved from: <https://www.geaviation.com/sites/default/files/datasheet-genx.pdf>.

Gray, D.E. (1978). Energy efficient engine preliminary design and integration studies. NASA-CP-2036-PT-1. Nov. 1978. pp. 89-110.

Kandebo, S.W. (1998). Pratt & Whitney launches geared turbofan engine. Aviation Week & Space Technology, 148 (8). p. 32-4.

Technical Report. (1977). Quiet Clean Short-haul Experimental Engine (QCSEE) Under-the-Wing (UTW) final design report. NASA-CR-134847. Jun. 1, 1977. pp. 1-697.

* cited by examiner







FIG.1






FIG.5




FIG.6

RING GEAR MOUNTING ARRANGEMENT WITH OIL SCAVENGE SCHEME

REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 16/736,013 filed Jan. 7, 2020, which is a continuation of U.S. patent application Ser. No. 16/122,236 filed on Sep. 5, 2018, which is now U.S. Pat. No. 10,527,151 granted Jan. 7, 2020, which is a continuation of U.S. patent application Ser. No. 15/892,210 filed on Feb. 8, 2018, which is now U.S. Pat. No. 10,082,105, granted Sep. 25, 2018, which is a continuation of U.S. patent application Ser. No. 14/753,048 filed on Jun. 29, 2015, which is now U.S. Pat. No. 10,107,231, granted Oct. 23, 2018, which is a continuation-in-part of U.S. patent application Ser. No. 13/346,120, filed on Jan. 9, 2012, which is a continuation-in-part of U.S. patent application Ser. No. 11/504,220, filed on Aug. 15, 2006, which is now U.S. Pat. No. 8,753,243 granted Jun. 17, 2014.

BACKGROUND OF THE INVENTION

This invention relates to a ring gear used in an epicyclic gear train of a gas turbine engine.

Gas turbine engines typically employ an epicyclic gear train connected to the turbine section of the engine, which is used to drive the turbo fan. In a typical epicyclic gear train, a sun gear receives rotational input from a turbine shaft through a compressor shaft. A carrier supports intermediate gears that surround and mesh with the sun gear. A ring gear surrounds and meshes with the intermediate gears. In arrangements in which the carrier is fixed against rotation, the intermediate gears are referred to as “star” gears and the ring gear is coupled to an output shaft that supports the turbo fan.

Typically, the ring gear is connected to the turbo fan shaft using a spline ring. The spline ring is secured to a flange of the turbo fan shaft using circumferentially arranged bolts. The spline ring includes splines opposite the flange that supports a splined outer circumferential surface of the ring gear. The ring gear typically includes first and second portions that provide teeth facing in opposite directions, which mesh with complimentary oppositely facing teeth of the star gears.

An epicyclic gear train must share the load between the gears within the system. As a result, the splined connection between the ring gear and spline ring is subject to wear under high loads and deflection. Since the spline connection requires radial clearance, it is difficult to get a repeatable balance of the turbo fan assembly. Balance can also deteriorate over time with spline wear.

SUMMARY

In one exemplary embodiment, a gas turbine engine includes a bypass ratio greater than about ten (10). A fan is supported on a fan shaft and has a plurality of fan blades. There is a gutter with an annular channel. A gear system is connected to the fan shaft. There is a plurality of planetary gears and a ring gear with an aperture that is axially aligned with the annular channel. The ring gear includes a first portion with a first set of opposed angled teeth separated by a trough from a second portion with a second set of opposed angled teeth. A torque frame at least partially supports the gear system. A low pressure turbine has an inlet, an outlet,

and a low pressure turbine pressure ratio greater than 5:1 and a low fan pressure ratio of less than 1.45 across the fan blade alone.

In a further embodiment of any of the above, a support relative to a fixed housing facilitates segregation of vibrations.

In a further embodiment of any of the above, there is an input to the gear system that facilitates segregation of vibrations.

In a further embodiment of any of the above, the gear system includes a sun gear that has a sun gear splined connection.

In a further embodiment of any of the above, the input includes an input splined connection complementary to the sun gear splined connection. The gear system includes a gear reduction ratio of greater than 2.5.

In a further embodiment of any of the above, the fan shaft is supported by at least one tapered roller bearing.

In a further embodiment of any of the above, a fan tip speed less than 1150 ft/second.

In a further embodiment of any of the above, a fan tip speed is less than 1150 ft/second. A fan is on a fan shaft and has a plurality of fan blades and a low fan pressure ratio of less than 1.45 across the fan blades alone.

In a further embodiment of any of the above, the first portion and the second portion of the ring gear each include a radially extending flange that extends radially outward away from a corresponding set of opposed angled teeth. The fan shaft includes a radially extending flange connected to the radially extending flange on the first portion of the ring gear and the radially extending flange on the second portion of the ring gear.

In a further embodiment of any of the above, a seal is attached to at least one of the radially extending flanges on the ring gear or the radially extending flange on the fan shaft.

In a further embodiment of any of the above, the seal includes an oil return passage.

In a further embodiment of any of the above, the oil return passage includes a slot.

In a further embodiment of any of the above, the slot is located in the seal.

In a further embodiment of any of the above, the slot is located in the radially extending flange on the fan shaft.

In a further embodiment of any of the above, the gutter is for collecting oil expelled from the gear system.

In a further embodiment of any of the above, a fan tip speed less than 1150 ft/second.

In a further embodiment of any of the above, the gutter is formed from a soft material.

In a further embodiment of any of the above, the soft material is aluminum. In another exemplary embodiment, a gas turbine engine includes a fan supported on a fan shaft by at least one roller bearing and has a plurality of fan blades.

A bypass ratio is greater than about ten (10). There is a gutter with an annular channel. A planetary gear system is connected to the fan shaft. The gear system has a gear reduction ratio of greater than 2.5 and a plurality of intermediate gears. A ring gear with an aperture is axially aligned with the annular channel. The ring gear includes a first portion separated from a second portion. The first portion and the second portion each include a radially extending flange that extends radially outward away from a corresponding set of opposed angled teeth. A torque frame is at least partially supporting the gear system with respect to the housing which facilitates the segregation of vibrations and other transients.

3

In a further embodiment of any of the above, there is an input to the gear system which facilitates segregation of vibrations.

In a further embodiment of any of the above, the gear system includes a sun gear that has a sun gear splined connection. The input includes an input splined connection complementary to the sun gear splined connection.

In a further embodiment of any of the above, the roller bearing is a tapered roller bearing.

In a further embodiment of any of the above, the gutter is for collecting oil expelled from the gear system.

In a further embodiment of any of the above, the gutter is formed from a soft material.

In a further embodiment of any of the above, the soft material is aluminum.

In a further embodiment of any of the above, a low pressure turbine has an inlet, an outlet, and a low pressure turbine pressure ratio greater than 5:1. A low fan pressure ratio of less than 1.45 which is measured across the fan blades alone.

In a further embodiment of any of the above, the fan shaft includes a radially extending flange which is connected to the radially extending flange on the first portion of the ring gear and the radially extending flange on the second portion of the ring gear.

In a further embodiment of any of the above, a seal is attached to at least one of the radially extending flanges on the ring gear or the radially extending flange on the fan shaft.

In a further embodiment of any of the above, the seal includes an oil return passage.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a partial cross-sectional view of a front portion of a gas turbine engine illustrating a turbo fan, epicyclic gear train and a compressor section.

FIG. 2 is an enlarged cross-sectional view of the epicyclic gear train shown in FIG. 1.

FIG. 3 is an enlarged cross-sectional view of an example ring gear similar to the arrangement shown in FIG. 2.

FIG. 4 is a view of the ring gear shown in FIG. 3 viewed in a direction that faces the teeth of the ring gear in FIG. 3.

FIG. 5 shows another embodiment.

FIG. 6 shows yet another embodiment.

DETAILED DESCRIPTION

A portion of a gas turbine engine 10 is shown schematically in FIG. 1. The turbine engine 10 includes a fixed housing 12 that is constructed from numerous pieces secured to one another. A compressor section 14 having compressor hubs 16 with blades are driven by a turbine shaft 25 about an axis A. A turbo fan 18 is supported on a turbo fan shaft 20 that is driven by a compressor shaft 24, which supports the compressor hubs 16, through an epicyclic gear train 22. The engine 10 is a high-bypass geared architecture aircraft engine. In one disclosed, non-limiting embodiment, the engine 10 bypass ratio is greater than about six (6) to ten (10), the gear train 22 is an epicyclic gear train such as a planetary gear system or other gear system with a gear reduction ratio of greater than about 2.3 and the low pressure turbine 18 has a pressure ratio that is greater than about 5. The engine 10 in one non-limiting embodiment is a high-bypass geared architecture aircraft engine. In one disclosed embodiment, the engine 10 bypass ratio is greater than ten (10:1), the turbofan diameter is significantly larger than that of the low pressure compressor 16, and the low pressure

4

turbine 27a (shown schematically) has a pressure ratio that is greater than 5:1. As understood, the low pressure turbine 27a is downstream of at least one upstream, or high pressure turbine. The gear train 22 may be an epicyclic gear train such as a planetary gear system or other gear system with a gear reduction ratio of greater than 2.5:1. It should be understood, however, that the above parameters are only exemplary of one embodiment of a geared architecture engine and that the present invention is applicable to other gas turbine engines including direct drive turbofans.

A significant amount of thrust is provided by the bypass flow B due to the high bypass ratio. The fan 18 of the engine 10 is designed for a particular flight condition—typically cruise at about 0.8 M and about 35,000 feet. The flight condition of 0.8 M and 35,000 ft, with the engine at its best fuel consumption—also known as “bucket cruise TSFC”—is the industry standard parameter of lbf of fuel being burned divided by lbf of thrust the engine produces at that minimum point. “Low fan pressure ratio” is the pressure ratio across the fan blade alone, without the FEGV system 36. The low fan pressure ratio as disclosed herein according to one non-limiting embodiment is less than 1.45. “Low corrected fan tip speed” is the actual fan tip speed in ft/sec divided by an industry standard temperature correction of $[(T_{\text{ambient}} \text{ deg R})/518.7]^{0.5}$. The “Low corrected fan tip speed” as disclosed herein according to one non-limiting embodiment is less than 1150 ft/second.

The gear train 22 generally includes a fan drive gear system (FDGS) 100 driven by the compressor shaft 24 through an input coupling 102. The input coupling 102 both transfers torque from the compressor shaft 24 to the gear train 22 and facilitates the segregation of vibrations and other transients therebetween.

The input coupling 102 may include an interface spline 102 joined, by a gear spline 106, to the sun gear 30. The sun gear 30 is in meshed engagement with multiple star gears 32. Each star gear 32 is also in meshed engagement with rotating ring gear 38 that is mechanically connected to the fan shaft 20. Since the star gears 32 mesh with both the rotating ring gear 38 as well as the rotating sun gear 30, the star gears 32 rotate about their own axes to drive the ring gear 38. The rotation of the ring gear 38 is conveyed to the fan 20 through the fan shaft 20 to thereby drive the fan 18 at a lower speed than the turbine shaft 25.

In the example arrangement shown, the epicyclic gear train 22 is a star gear train. Referring to FIG. 2, the epicyclic gear train 22 includes the sun gear 30 that is connected to the compressor shaft 24, which provides rotational input, by the splined connection. A carrier 26 is fixed to the housing 12 by a torque frame 28 using fingers (not shown) known in the art. The carrier 26 supports star gears 32 using journal bearings 34 that are coupled to the sun gear 30 by meshed interfaces between the teeth of sun and star gears 30, 32. Multiple star gears 32 are arranged circumferentially about the sun gear 30. Retainers 36 retain the journal bearings 34 to the carrier 26. A ring gear 38 surrounds the carrier 26 and is coupled to the star gears 32 by meshed interfaces. The ring gear 38, which provides rotational output, is secured to the turbo fan shaft 20 by circumferentially arranged fastening elements, which are described in more detail below.

The torque frame 28 supports the carrier 26 with respect to the housing 12 such as a front center body which facilitates the segregation of vibrations and other transients therebetween. It should be understood that various gas turbine engine case structures may alternatively or additionally be provided.

5

The fixed housing **12** may further include a number 1 and 1.5 bearing support frame **108** which is commonly referred to as a "K-frame" which supports the number 1 and number 1.5 bearing systems **110A**, **110B** to support the fan shaft **20** (FIG. 1). The number 1 and number 1.5 bearing systems **110A**, **110B** may include tapered roller bearings which provide a line contact.

Referring to FIGS. 3 and 4, the ring gear **38** is a two-piece construction having first and second portions **40**, **42**. The first and second portions **40**, **42** abut one another at a radial interface **45**. A trough **41** separates oppositely angled teeth **43** (best shown in FIG. 4) on each of the first and second portions **40**, **42**. The arrangement of teeth **43** forces the first and second portions **40**, **42** toward one another at the radial interface **45**. The back side of the first and second portions **40**, **42** includes a generally S-shaped outer circumferential surface **47** that, coupled with a change in thickness, provides structural rigidity and resistance to overturning moments. The first and second portions **40**, **42** have a first thickness **T1** that is less than a second thickness **T2** arranged axially inwardly from the first thickness **T1**. The first and second portions **40**, **42** include facing recesses **44** that form an internal annular cavity **46**.

The first and second portions **40**, **42** include flanges **51** that extend radially outward away from the teeth **43**. The turbo fan shaft **20** includes a radially outwardly extending flange **70** that is secured to the flanges **51** by circumferentially arranged bolts **52** and nuts **54**, which axially constrain and affix the turbo fan shaft **20** and ring gear **38** relative to one another. Thus, the spline ring is eliminated, which also reduces heat generated from windage and churning that resulted from the sharp edges and surface area of the splines. The turbo fan shaft **20** and ring gear **38** can be rotationally balanced with one another since radial movement resulting from the use of splines is eliminated. An oil baffle **68** is also secured to the flanges **51**, **70** and balanced with the assembly.

Seals **56** having knife edges **58** are secured to the flanges **51**, **70**. The first and second portions **40**, **42** have grooves **48** at the radial interface **45** that form a hole **50**, which expels oil through the ring gear **38** to a gutter **60** that is secured to the carrier **26** with fasteners **61** (FIG. 2). The direct radial flow path provided by the grooves **48** reduces windage and churning by avoiding the axial flow path change that existed with splines. That is, the oil had to flow radially and then axially to exit through the spline interface. The gutter **60** is constructed from a soft material such as aluminum so that the knife edges **58**, which are constructed from steel, can cut into the aluminum if they interfere. Referring to FIG. 3, the seals **56** also include oil return passages **62** provided by first and second slots **64** in the seals **56**, which permit oil on either side of the ring gear **38** to drain into the gutter **60**. In the example shown in FIG. 2, the first and second slots **64**, **66** are instead provided in the flange **70** and oil baffle **68**, respectively.

FIG. 5 shows an embodiment **200**, wherein there is a fan drive turbine **208** driving a shaft **206** to in turn drive a fan rotor **202**. A gear reduction **204** may be positioned between the fan drive turbine **208** and the fan rotor **202**. This gear reduction **204** may be structured and operate like the gear reduction disclosed above. A compressor rotor **210** is driven by an intermediate pressure turbine **212**, and a second stage compressor rotor **214** is driven by a turbine rotor **216**. A combustion section **218** is positioned intermediate the compressor rotor **214** and the turbine section **216**.

FIG. 6 shows yet another embodiment **300** wherein a fan rotor **302** and a first stage compressor **304** rotate at a

6

common speed. The gear reduction **306** (which may be structured as disclosed above) is intermediate the compressor rotor **304** and a shaft **308** which is driven by a low pressure turbine section.

Although a preferred embodiment of this invention has been disclosed, a worker of ordinary skill in this art would recognize that certain modifications would come within the scope of this invention. For that reason, the following claims should be studied to determine the true scope and content of this invention.

What is claimed is:

1. A gas turbine engine comprising:

a bypass ratio greater than about ten (10);

a fan supported on a fan shaft and having a plurality of fan blades;

a gear system connected to the fan shaft, a plurality of planetary gears, a first set of opposed angled ring gear teeth separated from a second set of opposed angled ring gear teeth, wherein a lubricant flow path is located axially between the first set of opposed angled ring gear teeth and the second set of opposed angled ring gear teeth;

a gear system support relative to a fixed housing facilitating segregation of vibrations;

an annular channel axially aligned with the lubricant flow path; and

a low pressure turbine with an inlet, an outlet, and a low pressure turbine pressure ratio greater than 5:1.

2. The gas turbine engine of claim 1, further comprising a torque frame at least partially supporting the gear system, wherein the torque frame facilitates segregation of vibrations.

3. The gas turbine engine of claim 2, wherein the gear system includes a sun gear having a sun gear splined connection.

4. The gas turbine engine of claim 3, wherein said gear system includes a gear reduction ratio of greater than 2.5.

5. The gas turbine engine of claim 4, wherein the annular channel is at least partially defined by a gutter.

6. The gas turbine engine of claim 5, wherein the fan shaft is supported by at least one tapered roller bearing.

7. The gas turbine engine of claim 5, further comprising a fan tip speed less than 1150 ft/second.

8. The gas turbine engine of claim 7, further comprising a low fan pressure ratio of less than 1.45 across the fan blades alone.

9. The gas turbine engine of claim 5, wherein said gutter is for collecting oil expelled from the gear system.

10. The gas turbine engine of claim 9, further comprising a fan tip speed less than 1150 ft/second.

11. The gas turbine engine of claim 10, further comprising a low fan pressure ratio of less than 1.45 across the fan blades alone.

12. The gas turbine engine of claim 11, wherein the gutter is formed from a soft material.

13. The gas turbine engine of claim 12, wherein the soft material is aluminum.

14. The gas turbine engine of claim 8, wherein the first set of opposed angled ring gear teeth and the second set of opposed angled ring gear teeth each include a radially extending flange that extends radially outward away from a corresponding set of opposed angled ring gear teeth, and the fan shaft includes a radially extending flange connected to the radially extending flange on the first set of opposed angled ring gear teeth and the radially extending flange on the second set of opposed angled ring gear teeth.

7

15. The gas turbine engine of claim 14, further comprising a seal attached to at least one of the radially extending flanges on the first and second set of opposed angled ring gear teeth or the radially extending flange on the fan shaft.

16. The gas turbine engine of claim 15, wherein the seal includes an oil return passage.

17. The gas turbine engine of claim 16, wherein the oil return passage includes a slot.

18. The gas turbine engine of claim 17, wherein the slot is located in the seal.

19. The gas turbine engine of claim 17, wherein the slot is located in the radially extending flange on the fan shaft.

20. The gas turbine engine of claim 3, further comprising an input to the gear system, wherein the input facilitates segregation of vibrations and includes an input connection complementary to the sun gear connection.

21. A gas turbine engine comprising:

a fan supported on a fan shaft by at least one roller bearing and having a plurality of fan blades;

a bypass ratio greater than about ten (10);

an epicyclic gear system connected to the fan shaft, the epicyclic gear system having a gear reduction ratio of greater than 2.5, a plurality of intermediate gears, and a ring gear with an aperture that is, wherein the ring gear includes a first portion separated from a second portion, the first portion and the second portion each include a radially extending flange that extends radially outward away from a corresponding set of opposed angled teeth;

a torque frame as least partially supporting the gear system with respect to a housing to facilitate segregation of vibrations; and

an annular channel axially aligned with the aperture and located radially outward from the aperture.

8

22. The gas turbine engine of claim 21, wherein the gear system includes a sun gear having a sun gear connection.

23. The gas turbine engine of claim 22, wherein the annular channel includes a gutter for collecting oil expelled from the gear system.

24. The gas turbine engine of claim 23, wherein the gutter is formed from aluminum.

25. The gas turbine of claim 24, further comprising a low pressure turbine with an inlet, an outlet, and a low pressure turbine pressure ratio greater than 5:1, and a low fan pressure ratio of less than 1.45 and the low fan pressure ratio is measured across the fan blades alone.

26. The gas turbine of claim 24, further comprising a low pressure turbine with an inlet, an outlet, and a low pressure turbine pressure ratio greater than 5:1, a low fan pressure ratio of less than 1.45 and the low fan pressure ratio is measured across the fan blades alone, and a gear system support relative to a fixed housing facilitating segregation of vibrations.

27. The gas turbine engine of claim 26, wherein the fan shaft includes a radially extending flange connected to the radially extending flange on the first portion of the ring gear and the radially extending flange on the second portion of the ring gear.

28. The gas turbine engine of claim 27, further comprising a seal attached to at least one of the radially extending flanges on the ring gear or the radially extending flange on the fan shaft, wherein the seal includes an oil return passage.

29. The gas turbine engine of claim 28, further comprising a fan tip speed less than 1150 ft/second.

30. The gas turbine engine of claim 29, further comprising an input to the gear system wherein the input facilitates segregation of vibrations and includes an input connection complementary to the sun gear connection.

* * * * *