



US011400502B2

(12) **United States Patent**  
**Aldrich et al.**

(10) **Patent No.:** **US 11,400,502 B2**  
(45) **Date of Patent:** **Aug. 2, 2022**

(54) **EDGE LEVELER WITH OFFSET ROLLERS**

(56) **References Cited**

(71) Applicant: **FuelCell Energy, Inc.**, Danbury, CT (US)  
(72) Inventors: **Benjamin Aldrich**, Bethlehem, CT (US); **Carson Payne**, Canton, CT (US); **Steve Rulli**, Winsted, CT (US); **Marc Gizzie**, Winsted, CT (US); **Steve Ayres**, Waterbury, CT (US)  
(73) Assignee: **FuelCell Energy, Inc.**, Danbury, CT (US)  
(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 184 days.

U.S. PATENT DOCUMENTS

3,006,401	A *	10/1961	Jamesn .....	B21D 1/02 72/162
3,032,245	A	5/1962	George et al.	
3,545,243	A *	12/1970	Fritz .....	B21D 1/05 72/160
3,595,277	A	7/1971	Lefever	
4,033,165	A *	7/1977	Arimura .....	B21B 37/28 72/205
4,635,458	A *	1/1987	Bradlee .....	B21D 1/02 72/163
4,918,797	A *	4/1990	Watkins .....	E04D 3/364 29/243.5
5,554,235	A	9/1996	Noe et al.	
6,892,561	B2 *	5/2005	Grell .....	B21D 1/05 72/160

(Continued)

(21) Appl. No.: **16/564,730**

(22) Filed: **Sep. 9, 2019**

(65) **Prior Publication Data**

US 2020/0086370 A1 Mar. 19, 2020

**Related U.S. Application Data**

(60) Provisional application No. 62/730,870, filed on Sep. 13, 2018.

(51) **Int. Cl.**  
**B21D 1/02** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **B21D 1/02** (2013.01)

(58) **Field of Classification Search**  
CPC ... B21D 1/02; B21D 3/02; B21D 3/05; B21D 3/04; B21D 5/14; B21D 1/06  
USPC ..... 72/160, 162-165  
See application file for complete search history.

FOREIGN PATENT DOCUMENTS

CN	104668313	A *	6/2015 .....	B21D 1/02
CN	108262376	A *	7/2018 .....	B21D 3/12

(Continued)

*Primary Examiner* — Gregory D Swiatocha


*Assistant Examiner* — Bobby Yeonjin Kim

(74) *Attorney, Agent, or Firm* — Foley & Lardner LLP

(57) **ABSTRACT**

An edge leveler for leveling an edge of a plate includes a first frame, a plurality of first rollers rotatably mounted along the first frame; a second frame, and a plurality of second rollers rotatably mounted along the second frame. The second rollers are offset relative to the first rollers. A width of a gap between an adjacent pair of first and second rollers on a first end portion of the edge leveler is greater than a width of a gap between an adjacent pair of first and second rollers in a middle portion of the edge leveler.

**19 Claims, 12 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

2001/0008719 A1\* 7/2001 Ikeda ..... H01M 8/0228  
72/196  
2007/0044531 A1\* 3/2007 Liefer ..... B21D 1/02  
72/160  
2015/0013418 A1\* 1/2015 Abe ..... B21D 1/06  
72/163  
2015/0128675 A1\* 5/2015 Abe ..... B21B 35/00  
72/160

FOREIGN PATENT DOCUMENTS

DE 202007013550 U1 \* 12/2007 ..... B21D 1/02  
JP 55130338 A \* 10/1980  
JP 62187523 A \* 8/1987  
KR 20100096899 A \* 9/2010 ..... B21D 1/02

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4





FIG. 5










FIG. 7





**FIG. 9**

1100

PROVIDING AN EDGE LEVELER INCLUDING A FIRST FRAME, A PLURALITY OF FIRST ROLLERS ROTATABLY MOUNTED ALONG THE FIRST FRAME, A SECOND FRAME, AND A PLURALITY OF SECOND ROLLERS ROTATABLY MOUNTED ALONG THE SECOND FRAME.

1101

LEVELING AN EDGE OF THE BIPOLAR PLATE USING THE EDGE LEVELER

1103

**FIG. 10**




FIG. 11




FIG. 12




FIG. 13




FIG. 14

**EDGE LEVELER WITH OFFSET ROLLERS****CROSS REFERENCE TO RELATED PATENT APPLICATION**

The present application claims the benefit of and priority to U.S. Provisional Application No. 62/730,870, filed Sep. 13, 2018, the entire disclosure of which is hereby incorporated by reference herein.

**BACKGROUND**

The present disclosure relates generally to the field of shaping devices, and more specifically to an edge leveler for removing bows in bipolar plates used in fuel cell stack assemblies.

Bipolar plates serve as the anode plate and the cathode plate in a fuel cell. Bipolar plates can account for a significant portion of a fuel cell stack's weight and cost. Functions performed by bipolar plates include inhibiting leakage of reactant gases or coolant from a fuel cell, distributing reaction gases uniformly over active areas of a fuel cell, removing heat from the active areas, and carrying current across multiple cells in a fuel cell stack.

**SUMMARY**

According to an exemplary embodiment of the present disclosure, an edge leveler for leveling an edge of a plate includes a first frame; a plurality of first rollers rotatably mounted along the first frame; a second frame; and a plurality of second rollers rotatably mounted along the second frame. The second rollers are offset relative to the first rollers. A width of a gap between an adjacent pair of first and second rollers on a first end portion of the edge leveler is greater than a width of a gap between an adjacent pair of first and second rollers in a middle portion of the edge leveler.

According to one aspect, a width of a gap between an adjacent pair of first and second rollers on a second end portion of the edge leveler is greater than the width of the gap between the adjacent pair of first and second rollers in the middle portion of the edge leveler.

According to another aspect, the width of the gap between the adjacent pair of first and second rollers on the second end portion of the edge leveler is adjustable.

According to another aspect, the width of the gap between the adjacent pair of first and second rollers on the second end portion of the edge leveler is adjustable via a set screw.

According to another aspect, the width of the gap between the adjacent pair of first and second rollers on the first end portion of the edge leveler is adjustable.

According to another aspect, the width of the gap between the adjacent pair of first and second rollers on the first end portion of the edge leveler is adjustable via a set screw.

According to another aspect, the edge leveler is configured to be mounted on a track.

According to another aspects, at least one of the first rollers and the second rollers is free spinning (i.e., not driven).

According to another aspect, a rotational speed of at least one of the first rollers and second rollers is controllable by a controller.

According to another exemplary embodiment of the present disclosure, a system for leveling an edge of a plate includes a track; and an edge leveler mounted on the track. The edge leveler includes a first frame; a plurality of first

rollers rotatably mounted along the first frame; a second frame; and a plurality of second rollers rotatably mounted along the second frame. The second rollers are offset relative to the first rollers. A width of a gap between an adjacent pair of first and second rollers on a first end portion of the edge leveler is greater than a width of a gap between an adjacent pair of first and second rollers in a middle portion of the edge leveler.

According to one aspect of the system, a width of a gap between an adjacent pair of first and second rollers on a second end portion of the edge leveler is greater than the width of the gap between the adjacent pair of first and second rollers in the middle portion of the edge leveler.

According to another aspect of the system, the width of the gap between the adjacent pair of first and second rollers on the second end portion of the edge leveler is adjustable.

According to another aspect of the system, the width of the gap between the adjacent pair of first and second rollers on the second end portion of the edge leveler is adjustable via a set screw.

According to another aspect of the system, the width of the gap between the adjacent pair of first and second rollers on the first end portion of the edge leveler is adjustable.

According to another aspect of the system, the width of the gap between the adjacent pair of first and second rollers on the first end portion of the edge leveler is adjustable via a set screw.

According to another exemplary embodiment of the present disclosure, a method of shaping a bipolar plate for a fuel cell includes the steps of providing an edge leveler and leveling an edge of the bipolar plate using the edge leveler. The edge leveler includes a first frame; a plurality of first rollers rotatably mounted along the first frame; a second frame; and a plurality of second rollers rotatably mounted along the second frame. The second rollers are offset relative to the first rollers. A width of a gap between an adjacent pair of first and second rollers on a first end portion of the edge leveler is greater than a width of a gap between an adjacent pair of first and second rollers in a middle portion of the edge leveler.

According to one aspect of the method, a width of a gap between an adjacent pair of first and second rollers on a second end portion of the edge leveler is greater than the width of the gap between the adjacent pair of first and second rollers in the middle portion of the edge leveler.

According to another aspect of the method, the width of the gap between the adjacent pair of first and second rollers on the second end portion of the edge leveler is adjustable.

According to another aspect of the method, the width of the gap between the adjacent pair of first and second rollers on the second end portion of the edge leveler is adjustable via a set screw.

According to another aspect of the method, the width of the gap between the adjacent pair of first and second rollers on the first end portion of the edge leveler is adjustable.

According to another aspect of the method, the width of the gap between the adjacent pair of first and second rollers on the first end portion of the edge leveler is adjustable via a set screw.

According to another aspect of the method, the edge leveler is mounted on a track, and is moved along a length of the track during the step of leveling the edge of the bipolar plate.

According to another aspect of the method, the edge leveler is controlled by a controller to be automatically moved along a length of the track during the step of leveling the edge of the bipolar plate.

## BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings are not intended to be drawn to scale. Like reference numbers and designations in the various drawings indicate like elements. For purposes of clarity, not every component may be labeled in every drawing. In the drawings:

FIG. 1 is a side top perspective view of a warped bipolar plate.

FIG. 2 is a side perspective showing the warped bipolar plate shown in FIG. 1.

FIG. 3 is a side perspective of an edge leveler including offset rollers according to one exemplary embodiment of the present disclosure.

FIG. 4 is a side perspective view of the edge leveler including offset rollers shown in FIG. 3.

FIG. 5 is a side perspective view of a system for leveling edges of a plate including an edge leveler including offset rollers, according to another exemplary embodiment of the present disclosure.

FIG. 6 is front perspective view of the system shown in FIG. 5.

FIG. 7 is a side top perspective view of a flattened bipolar plate.

FIG. 8 is a side perspective showing the flattened bipolar plate shown in FIG. 7.

FIG. 9 is a block diagram illustrating a system for leveling edges of a plate, according to another exemplary embodiment of the present disclosure.

FIG. 10 is a process flowchart illustrating a method of flattening a bipolar plate for a fuel cell according to another exemplary embodiment of the present disclosure.

FIG. 11 is an example of an edge leveler having eleven rollers.

FIGS. 12-14 illustrate examples of various configurations of rollers that may be used in an edge leveler, where the rollers have different shapes, sizes, and heights with respect to a frame of the edge leveler.

## DETAILED DESCRIPTION

Bipolar plates are generally made of an inexpensive, lightweight material so as to minimize a cost or weight of the fuel cell and/or fuel cell stack. Because of the relatively light weight of the material, current processes for making bipolar plates, such as stamping and welding, tend to create a bow or warp in the plate which persists throughout the cell manufacturing process. Specifically, the bows or warps may be due to differential rates of cooling of a weld between two materials of dissimilar or variable thickness. Bowed or warped bipolar cells (e.g., non-flat bipolar cell packages and/or cambered stamped parts popping up into waves along the sealing surfaces) may result in stack gaps (e.g., stack corner gaps) within a fuel cell stack and in poorly distributed, non-uniform cell-to-cell contact surface area, which may cause an undesirable increase in cell resistance. Additionally, the bow or warps in the bipolar plates may make accurate application of various adhesives or other components difficult to achieve, especially in an automated assembly line environment.

Current approaches to controlling or preventing bows or warps in the bipolar plates include attempts to control a flatness of the stamped parts which are used to assemble a bipolar plate. Other approaches include balancing a material thickness of a bipolar plate to reduce welding-induced warping. Yet other approaches include performing a hemming operation to partially control the flatness of a bipolar

plate. All of these prior approaches achieve only marginal flattening of the assembled bipolar plate and do not necessarily correct the bowing or warping that occurs before final assembly of the bipolar plate. Additionally, the prior approaches can result in increased material and/or assembly costs.

There is therefore a need for devices and processes which can achieve better flatness of an assembled bipolar plate and decrease the likelihood that the final bipolar plate includes bows or warps that impede fuel cell performance. Furthermore, there is a need for devices and processes that reduce manufacturing and material costs.

FIGS. 1 and 2 show a warped bipolar plate 50. The bipolar plate includes edge 55 and edge 60. The warps and/or bends in the bipolar plate are evident relative to reference line 56, which is a straight line, parallel to the ground, extending along a length of the edge 55 of the bipolar plate 50. The warp and/or bend is measured in terms of a magnitude of angle 57 defined by line 56 and the edge 55 of the bipolar plate 50.

Referring generally to the FIGURES, the present disclosure relates to a shaping device, in particular an edge leveler 100 configured to flatten a bipolar plate for a fuel cell. The edge leveler 100 is useable to eliminate warps and/or bends of the bipolar plate, such as bipolar plate 50. The edge leveler 100 includes sets (e.g., banks, series, etc.) of rollers which are spaced in relation to each other in an offset configuration. The edge leveler 100 is adjustable such that a gap between different sets of offset rollers is adjustable based on a thickness of the bipolar plate 50. The present disclosure also relates to systems including the edge leveler 100 as described, as well as methods of using the edge leveler 100 disclosed herein. The edge leveler 100 as disclosed herein achieves a predetermined flatness in a bipolar plate which allows for desired material costs and manufacturing costs reductions. Furthermore, the edge leveler 100 ensures that a bipolar plate maintains the predetermined flatness when the bipolar plate is assembled in a fuel cell.

As shown in FIG. 3-4, an exemplary embodiment of an edge leveler 100 includes a first frame 110 and a second frame 120. The first frame 110 and the second frame 120 are formed of any suitable material. For example, the first frame 110 and the second frame 120 are formed of steel, such as stainless steel. Although a length of the first frame 110 and a length of the second frame 120 are shown to be the same in FIGS. 3-4, the edge leveler 100 is not particularly limited to this implementation. For example, the length of the second frame 120 may be longer than the length of the first frame 110. As an alternative example, the length of the first frame 110 may be longer than the length of the second frame 120.

The first frame 110 and the second frame 120 are securably coupled to each other using fasteners. For example, as shown in FIG. 3, the first frame 110 and the second frame 120 include fastener holes 132 which are configured to hold and/or house fasteners 142 (shown in FIG. 4). As shown in FIG. 4, the fasteners 142 are threaded bolts 142a secured by nuts 142b. The threaded bolts 142a have a suitable stiffness and/or firmness required to hold the first frame 110 and the second frame 120 together even when the edge leveler 100 is subject to loads caused when the bipolar plate 50 is run through the edge leveler 100. However, the edge leveler 100 is not particularly limited to this implementation. For example, the edge leveler 100 may include any suitable fasteners which may be used to securely couple the first frame 110 to the second frame 120. Additionally, although the first frame 110 and the second frame 120 are shown



5

having two fastener holes **132**, the first frame **110** and the second frame **120** may include any suitable number of fastener holes **132**. For example, the number of fastener holes **132** may be one, two, three, four, five, six, or more.

The first frame **110** and the second frame **120** are configured to be separated by an adjustable gap **135**, shown in FIG. **3**. The adjustable gap **135** is configured to be adjustable based on a thickness of a bipolar plate (such as bipolar plate **50**, shown in FIGS. **1-2**) fed into the edge leveler **100**. As shown in FIG. **3**, the gap **135** may exist only at an end **102** of the edge leveler **100** but not at an end **101** of the edge leveler. In this implementation, the gap **135** exists only at the end **102** to facilitate progressively less bending of the edge **55** of the bipolar plate **50** as the edge **55** of the bipolar plate **50** is run through the edge leveler **100**. However, the edge leveler **100** is not particularly limited to the implementation shown in FIG. **3**. For example, FIG. **4** shows an edge leveler **100** with an adjustable gap **135** which extends along an entire length of the edge leveler **100**, from the end **102** of the edge leveler **100** to the end **101** of the edge leveler **100**.

The gap **135** is adjustable using set screws **141** and/or set screws **144** (shown in FIG. **4**). The set screws **141** are mounted to the first frame **110** in set screw holes **131**, shown in FIG. **3**. The set screws **144** are mounted to the end **101** and/or the end **102** of the edge leveler in set screw holes **134**, shown in FIG. **3**. By adjusting the set screws **141** and/or the set screws **144**, the gap **135** is adjustable to accommodate the thickness of the bipolar plate **50**. The set screws **141** and **144** are any commercially available set screws. Although, as shown in FIG. **4**, the number of set screws **141** is two and the number of set screws **144** is two, the edge leveler **100** is not particularly limited to this implementation. For example, the number of set screws **141** may be one, two, three, four, five, six, or more, and the number of set screws **144** may be one, two, three, four, five, six, or more. Although, as shown in FIGS. **3** and **4**, the set screw holes **131** are provided in the first frame **110** and the set screw holes **134** are provided in the second frame **120**, the edge leveler **100** is not particularly limited to this implementation. For example, the set screw holes **131** may be provided in the second frame **120** or in both the first frame **110** and the second frame **120**, and the set screw holes **134** may be provided in the first frame **110** or in both the first frame **110** and the second frame **120**.

As shown in FIG. **3**, the second frame **120** also includes mounting holes **133** which are configured to hold and/or house fasteners **143** (shown in FIG. **4**). The fasteners **143** are configured to mount the edge leveler **100** to an external device (such as a table) such that the edge leveler **100** is configured to be used in a stationary position. The fasteners **143** are any commercially available suitable fasteners; for example, mounting screws. Although, as shown in FIGS. **3** and **4**, the mounting holes **133** are provided in the second frame **120**, the edge leveler **100** is not particularly limited to this implementation. For example, the mounting holes **133** may be provided in the first frame **110** or in both the first frame **110** and the second frame **120**.

As shown in FIGS. **3-4**, the first frame **110** of the edge leveler **100** includes opposing surface **111** and opposing surface **112**. The first frame **110** also includes a front surface **113** which is configured to support a plurality of rollers **115** (e.g., by rotatably mounting the plurality of rollers **115** along the front surface **113** of the first frame **110**). According to one aspect, the plurality of rollers **115** are arranged in series in a straight line along a length of the first frame **110**. The plurality of rollers **115** are rotatably mounted to the front surface **113** of the first frame **110**. The plurality of rollers **115** are mounted only on one side of the first frame **110** (namely

6

on the surface **113** of the first frame **110**) such that the bipolar plate **50** is rolled into one side of the edge leveler **100**. Each of the rollers **115** are configured to rotate about an axis of rotation **116**. Each of the rollers **115** includes an inner diameter **117** and an outer diameter **118**. The diameters **117** and **118** are sized based on a thickness of the bipolar plate **50** which is run through the edge leveler **100**. According to some aspects, the plurality of rollers **115** are configured to be feed rollers. According to other aspects, the plurality of rollers **115** are configured to be idle rollers.

Still referring to FIGS. **3-4**, the number of the plurality of rollers **115** shown is three, but the edge leveler **100** is not particularly limited to this implementation. For example, the number of the plurality of rollers **115** may be one, two, three, four, five, six, or more. The rollers **115** are any suitable rollers, such as commercially available rollers. The rollers **115** are made of any suitable material, for example stainless steel or plastic. Stainless steel rollers **115** provide for a longer operating life for the rollers **115**, compared to plastic rollers **115**. However, plastic rollers **115** minimize scratching of the bipolar plate **50** when the bipolar plate **50** is rolled by the rollers **115**.

Referring to FIG. **4**, according to one aspect, the gap between the roller **115a** and the roller **125a** (which are adjacent first and second rollers on a first end portion of the edge leveler **100** closest to the end **101**) is greater than the gap between the roller **115b** and roller **125b** and/or roller **125c** (which are adjacent first and second rollers on a middle portion of the edge leveler **100**, between the ends **101** and **102**). Accordingly, in this aspect, the gap between a set of rollers (e.g., roller **115a** and roller **125a**) on a first end of the edge leveler **100** is greater than a gap between rollers in a middle portion (e.g., roller **115b** and roller **125b** and/or roller **125c**) of the edge leveler **100**. According to another aspect, the gap between the roller **115c** and the roller **125d** (which are adjacent first and second rollers on a first end portion of the edge leveler **100** closest to the end **102**) is greater than the gap between the roller **115b** and roller **125b** and/or roller **125c**. Accordingly, in this aspect, the gap between a set of rollers (e.g., roller **115c** and roller **125d**) on a second end of the edge leveler **100** is greater than the gap between rollers in the middle portion (e.g., roller **115b** and roller **125b** and/or roller **125c**) of the edge leveler **100**. According to another aspect, the gap between the sets of rollers on both sides of the edge leveler **100** is greater than the gap between rollers in the middle portion of the edge leveler **100**.

The second frame **120** of the edge leveler **100** includes opposing surface **121** and opposing surface **122**. The second frame **120** also includes a front surface **123** which is configured to support a plurality of rollers **125** (e.g., by rotatably mounting the plurality of rollers **125** along the front surface **123** of the second frame **120**). According to one aspect, the plurality of rollers **125** are arranged in series in a straight line along a length of the second frame **120**. The plurality of rollers **125** are mounted only on one side of the first frame **120** (namely on the surface **123** of the first frame **120**) such that the bipolar plate **50** is rolled into one side of the edge leveler **100**. The second frame **120** is oriented relative to the first frame **110** such that the front surface **123** of the second frame **120** lies within a same plane as the front surface **113** of the first frame **110**. In this configuration, the bipolar plate **50** can be rolled between the rollers **115** and the rollers **125**.

Each of the plurality of rollers **125** are configured to rotate about an axis of rotation **126**. Each of the rollers **125** includes an inner diameter **127** and an outer diameter **128**. The diameters **127** and **128** are sized based on a thickness of

the bipolar plate **50** which is run through the edge leveler **100**. According to some aspects, the diameter **127** of each of the rollers **125** is of a same size as diameter **117** of each of the rollers **115**. According to other aspects, the diameter **127** of each of the rollers **125** is of a different size as diameter **117** of each of the rollers **115**. According to some aspects, the diameter **128** of each of the rollers **125** is of a same size as diameter **118** of each of the rollers **115**. According to other aspects, the diameter **128** of each of the rollers **125** is of a different size as diameter **118** of each of the rollers **115**. According to some aspects, the plurality of rollers **125** are configured to be feed rollers. According to other aspects, the plurality of rollers **125** are configured to be idle rollers.

As shown in FIGS. 3-4, the number of the plurality of rollers **125** shown is four, but the edge leveler **100** is not particularly limited to this implementation. For example, the number of the plurality of rollers **125** may be one, two, three, four, five, six, seven, eight or more. According to one aspect, the number of rollers **125** is one more than the number of rollers **115**. The rollers **125** are any suitable rollers, such as commercially available rollers. The rollers **125** are made of any suitable material, for example stainless steel or plastic. Stainless steel rollers **125** provide for a longer operating life for the rollers **125**, compared to plastic rollers **125**. However, plastic rollers **125** minimize scratching of the bipolar plate **50** when the bipolar plate **50** is rolled by the rollers **125**.

The axes of rotation **126** of each of the rollers **125** is offset from the axes of rotation **116** of each of the rollers **115**. For any given roller **125**, a distance **126a** from the end **101** of the edge leveler **100** to the axis of rotation **126** of the roller **125** is different than a distance **116a** from the end **101** of the edge leveler **100** to the axis of rotation **116** of a roller **115** which is immediately adjacent to the roller **125**. The distance between one roller **115** and one roller **125** is shown as distance **150**. According to one aspect, the difference between the distance **126a** and the distance **116a** is a function of the outer diameter **118** of the roller **115** and/or the outer diameter **128** of the roller **125**. For example, the difference between the distance **126a** and the distance **116a** is equal to about half of the diameter **117** and/or diameter **118**.

In FIGS. 3-4, a total number of rollers (rollers **115**, **125**) is seven. However, the edge leveler **100** is not limited to this implementation. In another example, as shown in FIG. 11, an edge leveler **100'** may include eleven rollers (rollers **115**, **125**). In each of the examples, a number of rollers **115** on the first frame **110** is different from the number of rollers **125** on the second frame **120**. However, the edge levelers **100**, **100'** are not limited to this implementation. In some examples, there may be an equal number of rollers **115** and rollers **125**. In other examples, there may be more rollers **125** than rollers **115**. In even further examples, there may be more rollers **115** than rollers **125**.

FIGS. 12-14 illustrate different examples of an edge leveler (i.e., edge leveler **100A** shown in FIG. 12, edge leveler **100B** shown in FIG. 13, and edge leveler **100C** shown in FIG. 14). As shown in FIGS. 12-14, the rollers (e.g., the rollers **115**, **125**) of the edge levelers can be any shape (e.g., the rollers **115**, **125** may have different diameters  $D_1$  and  $D_2$ , as shown in FIG. 14, etc.) and may be mounted higher or lower (i.e., further or closer) to a respective first frame **110** or second frame **120** to accommodate different objects having varying shapes and sizes, while still directing de-stressing forces to the object. For example, the rollers **115**, **125** of edge leveler **100B** are disposed at a height **HB** above the respective first frame **110** and second frame **120**

that is higher than the relative heights **HA** and **Hc** of rollers **115**, **125** on edge levelers **100A** and **100C**, respectively.

In some aspects, a plurality of edge levelers **100** may be provided in series.

According to some aspects, the edge leveler **100** is operated manually. According to other aspects, the edge leveler **100** is operated in an automatic configuration and is configured to operate and/or move in an automatic configuration. For example, when the edge leveler **100** is operated in an automatic configuration, the edge leveler **100** is mounted to a track, such as track **220** (described below) and the edge leveler **100** is connected, using any suitable connection (e.g., mechanical, electrical, etc.) to a controller **300**, as shown in FIG. 9. According to one aspect, the controller **300** includes a memory **310** and a processor **305**. According to some aspects, the controller **300** is configured to control a speed and/or direction of the rotational movement of the rollers **115** and/or the rollers **125**. According to other aspects, such as the case in which the edge leveler **100** is mounted on a track (as described below with reference to the edge leveler **100'**), the controller **300** is configured to automatically control a movement of the edge leveler **100** or the edge leveler **100'** along a length of the track (such as along the length of the track **220** described below). In examples including such an automatic control, the whole frame may be pushed with a linear drive system (e.g., an air cylinder, a ball screw, etc.). However, the rollers may remain free spinning (i.e., are not driven).

Referring now to FIGS. 5-6, according to one embodiment of the present disclosure, an edge leveling system **200** is shown. The system **200** includes a table **210** on which a bipolar plate **50** to be flattened is placed. The system **200** also includes a vice **205** which is configured to hold the bipolar plate **50** in place on the table **210**. The system also includes a track **220** on which the edge leveler **100'** is mountable. When mounted on the track **220**, the edge leveler **100'** may be stationary or slidable (i.e., configured to translate). Although in the example of FIG. 6, the system **200** is only provided at one side of the table **210**, the system **200** is not limited to this implementation. For example, a plurality of systems **200** (e.g., two, three, four, etc.) may be provided at a plurality of sides of the table **210** (e.g., one system on each side of the table **210**, one system provided at each of two opposing sides of the table **210**, two systems provided on one side of the table **210**, etc.).

The system **200** includes an edge leveler **100'**, which is the same as the edge leveler **100** described above, except for any differences herein described. The edge leveler **100'** shown in FIGS. 5-6 includes five rollers **115** and six rollers **125**. The edge leveler **100'** also includes four set screws **141**, two each disposed on opposing ends of the edge levelers **100'**. The four set screws **141** are configured to adjust a gap between the rollers **115** and the rollers **125**. The edge leveler **100'** also includes fastener **153** which is configured to mount the edge leveler **100'** to the track **220**. In particular, the fastener **153** may be configured to attach the frame of the edge leveler **100'** to a carriage on the track **220**. The edge leveler **100'** also includes elements mounting holes **154** (which may not be used in this configuration) and a horizontal mounted roller **155**. The horizontal mounted roller **155** may be used as a guide to prevent the edge of the bipolar plate from moving too far into the edge leveler rollers **115**, **125** and causing damage to the wet seals (part of the bipolar plate assembly).

The edge leveler **100'** is configured to be mounted onto a track **220** such that the edge leveler **100'** moves along the track **220** in a line **221** along a length of the track **220**. This configuration of the track **220** allows the edge leveler **100'** to

be run in two directions along the line 221 along an edge (such as edge 55) of the bipolar plate 50. Handles 201 which are mounted to the edge leveler 100' allow a user to move the edge leveler 100' along the track 220.

Referring to FIGS. 7-8, a flattened bipolar plate 50 is shown after the bipolar plate 50 is rolled through the edge leveler 100 or the edge leveler 100' as described herein. As shown in FIGS. 7-8, the bipolar plate 50 includes flattened edge 55 which has been flattened to a predetermined flatness. The predetermined flatness may be, for example, less than 1/4" of displacement of the leveled edge. In other examples, the predetermined flatness may be measured in terms of the angle between the line 56 and the edge 55. For example, the edge 55 of the bipolar plate has been flattened so that the angle between line 56 and the edge 55 is zero.

Another exemplary embodiment of the present disclosure relates to a method of shaping a bipolar plate for a fuel cell. As shown in FIG. 10, the method 1100 of shaping a bipolar plate for a fuel cell includes the step 1101 of providing an edge leveler, such as the edge leveler 100 or the edge leveler 100', both described herein. The edge leveler includes a first frame; a plurality of first rollers rotatably mounted along the first frame; a second frame; and a plurality of second rollers rotatably mounted along the second frame; and leveling an edge of the bipolar plate using the edge leveler. The second rollers are offset relative to the first rollers. A width of a gap between an adjacent pair of first and second rollers on a first end portion of the edge leveler is greater than a width of a gap between an adjacent pair of first and second rollers in a middle portion of the edge leveler. The method 1100 also includes step 1103 of leveling an edge of the bipolar plate using the edge leveler. The method 1100 may also include the step of flattening the plate to a predetermined flatness.

According to one aspect of the method 1100, a width of a gap between an adjacent pair of first and second rollers on a second end portion of the edge leveler is greater than the width of the gap between the adjacent pair of first and second rollers in the middle portion of the edge leveler. According to another aspect of the method 1100, the width of the gap between the adjacent pair of first and second rollers on the second end portion of the edge leveler is adjustable. According to another aspect of the method 1100, the width of the gap between the adjacent pair of first and second rollers on the second end portion of the edge leveler is adjustable via a set screw. According to another aspect of the method 1100, the width of the gap between the adjacent pair of first and second rollers on the first end portion of the edge leveler is adjustable. According to another aspect of the method 1100, the width of the gap between the adjacent pair of first and second rollers on the first end portion of the edge leveler is adjustable via a set screw. According to another aspect of the method 1100, the edge leveler is configured to be mounted on a track, such as the track 220 described herein. According to another aspect of the method 1100, the edge leveler is configured to be automatically moveable along a length of the track. A movement of the edge leveler along the length of the track is controllable by a controller, such as the controller 300 herein described.

Any of the edge levelers described above may be used to create a camber-free wet seal (e.g., an edge component that overlaps/seals an interface of two pieces, for example, two solid planar pieces). For example, an edge leveler may receive a cambered stamped part or wet seal. The rollers of the edge levelers relax the internal differential stretched metal stresses, thereby straightening out the cambered stamped part or resulting in a camber-free wet seal.

The edge levelers described above are tools used to remove and/or straighten the bow in bipolar plates used in fuel cell stack assemblies by using a series of opposing offset interfering roller bearings at an adjustable angle and engagement depth. The edge levelers gradually bend the bowed edges of the bipolar plates straight. The edge levelers are specifically designed to allow a set of opposing offset interfering rollers to run over and manipulate the welded edge wing portion of the bipolar plate and straighten the stamped in stress and induced weld warp in the bipolar plate edge. The offset rollers are only mounted on one side, leaving the other side open. This configuration allows two sets of rollers to run along both sides of the stationary bipolar plate at the same time. The edge levelers are also configured to adjust the gap interference and taper of the rollers to adjust the edge levelers to take the cambered stress out of the warped parts and to achieve the desired flatness of the bipolar plate welded assembly and wing. In particular, the edge levelers may be adjustable for taper and for gap setting to be able to accommodate any bow amount that results from the bipolar plate edge welding assembly process.

As discussed above, the edge leveler can be used by hand or in various automated configurations. In one example, an edge leveler system includes a track-mounted, linear cylinder driven, offset roller bearing set edge leveler that eliminates ergonomic issues and variable quality that may result from hand operation (manual operation).

As utilized herein, the terms "approximately," "about," "substantially", and similar terms are intended to have a broad meaning in harmony with the common and accepted usage by those of ordinary skill in the art to which the subject matter of this disclosure pertains. It should be understood by those of skill in the art who review this disclosure that these terms are intended to allow a description of certain features described and claimed without restricting the scope of these features to the precise numerical ranges provided. Accordingly, these terms should be interpreted as indicating that insubstantial or inconsequential modifications or alterations of the subject matter described and claimed are considered to be within the scope of the disclosure as recited in the appended claims.

The terms "coupled," "connected," and the like, as used herein, mean the joining of two members directly or indirectly to one another. Such joining may be stationary (e.g., permanent) or moveable (e.g., removable or releasable). Such joining may be achieved with the two members or the two members and any additional intermediate members being integrally formed as a single unitary body with one another or with the two members or the two members and any additional intermediate members being attached to one another.

References herein to the positions of elements (e.g., "top," "bottom," "above," "below," etc.) are merely used to describe the orientation of various elements in the FIGURES. It should be noted that the orientation of various elements may differ according to other exemplary embodiments, and that such variations are intended to be encompassed by the present disclosure.

The construction and arrangement of the elements of the edge leveler with offset rollers as shown in the exemplary embodiments are illustrative only. Although only a few embodiments of the present disclosure have been described in detail, those skilled in the art who review this disclosure will readily appreciate that many modifications are possible (e.g., variations in sizes, dimensions, structures, shapes and proportions of the various elements, values of parameters, mounting arrangements, use of materials, colors, orienta-

## 11

tions, etc.) without materially departing from the novel teachings and advantages of the subject matter recited. For example, elements shown as integrally formed may be constructed of multiple parts or elements, the position of elements may be reversed or otherwise varied, and the nature or number of discrete elements or positions may be altered or varied.

Additionally, the word “exemplary” is used to mean serving as an example, instance, or illustration. Any embodiment or design described herein as “exemplary” is not necessarily to be construed as preferred or advantageous over other embodiments or designs (and such term is not intended to connote that such embodiments are necessarily extraordinary or superlative examples). Rather, use of the word “exemplary” is intended to present concepts in a concrete manner. Accordingly, all such modifications are intended to be included within the scope of the present disclosure. Other substitutions, modifications, changes, and omissions may be made in the design, operating conditions, and arrangement of the preferred and other exemplary embodiments without departing from the scope of the appended claims.

Other substitutions, modifications, changes and omissions may also be made in the design, operating conditions and arrangement of the various exemplary embodiments without departing from the scope of the present disclosure. For example, any element (e.g., the offset rollers, etc.) disclosed in one embodiment may be incorporated or utilized with any other embodiment disclosed herein. Also, for example, the order or sequence of any process or method steps may be varied or re-sequenced according to alternative embodiments. Any means-plus-function clause is intended to cover the structures described herein as performing the recited function and not only structural equivalents but also equivalent structures. Other substitutions, modifications, changes and omissions may be made in the design, operating configuration, and arrangement of the preferred and other exemplary embodiments without departing from the scope of the appended claims.

What is claimed is:

1. An edge leveler for leveling an edge of a plate, the edge leveler comprising:

a first frame;

a plurality of first rollers rotatably mounted along the first frame;

a second frame; and

a plurality of second rollers rotatably mounted along the second frame;

wherein the plurality of second rollers are offset relative to the first rollers;

wherein a width of a gap between an adjacent pair of first and second rollers on a first end portion of the edge leveler is greater than a width of a gap between an adjacent pair of first and second rollers in a middle portion of the edge leveler; and

wherein the plurality of first rollers and the plurality of second rollers are configured to receive only a first edge of the plate therebetween to straighten the first edge of the plate relative to the rest of the plate;

and wherein the edge leveler is configured to slidably couple to a track and to slide along the track to level the first edge of the plate while the plate is stationary.

2. The edge leveler according to claim 1, wherein a width of a gap between an adjacent pair of first and second rollers on a second end portion of the edge leveler is greater than the width of the gap between the adjacent pair of first and second rollers in the middle portion of the edge leveler.

## 12

3. The edge leveler according to claim 2, wherein the width of the gap between the adjacent pair of first and second rollers on the second end portion of the edge leveler is adjustable.

4. The edge leveler according to claim 3, wherein the width of the gap between the adjacent pair of first and second rollers on the second end portion of the edge leveler is adjustable via a set screw.

5. The edge leveler according to claim 1, wherein the width of the gap between the adjacent pair of first and second rollers on the first end portion of the edge leveler is adjustable.

6. The edge leveler according to claim 5, wherein the width of the gap between the adjacent pair of first and second rollers on the first end portion of the edge leveler is adjustable via a set screw.

7. The edge leveler according to claim 1, wherein a rotational speed of at least one of the first rollers or the second rollers is controllable by a controller.

8. The edge leveler of claim 1, further comprising a plurality of handles configured to allow a user to move the edge leveler along the track.

9. A system for leveling an edge of a stationary plate, the system comprising:

a track; and

an edge leveler slidably coupled to the track, the edge leveler comprising:

a first frame;

a plurality of first rollers rotatably mounted along the first frame;

a second frame; and

a plurality of second rollers rotatably mounted along the second frame; and

a vertically mounted roller arranged perpendicularly to the plurality of first rollers;

wherein the edge leveler is configured to slide along the track to level one edge of the stationary plate, and the plurality of first rollers and the plurality of second rollers are configured to receive one edge of the plate therebetween while an opposite edge of the plate is not received therebetween, with the vertically mounted roller acting to prevent the one edge of the plate from moving too far into the plurality of first and second rollers;

wherein the second rollers are offset relative to the first rollers; and

wherein a width of a gap between an adjacent pair of first and second rollers on a first end portion of the edge leveler is greater than a width of a gap between an adjacent pair of first and second rollers in a middle portion of the edge leveler.

10. The system according to claim 9, wherein a width of a gap between an adjacent pair of first and second rollers on a second end portion of the edge leveler is greater than the width of the gap between the adjacent pair of first and second rollers in the middle portion of the edge leveler.

11. The system according to claim 10, wherein the width of the gap between the adjacent pair of first and second rollers on the second end portion of the edge leveler is adjustable.

12. The system according to claim 11, wherein the width of the gap between the adjacent pair of first and second rollers on the second end portion of the edge leveler is adjustable via a set screw.

13. The system according to claim 9, wherein the width of the gap between the adjacent pair of first and second rollers on the first end portion of the edge leveler is adjustable.

**13**

**14.** A method of shaping a bipolar plate for a fuel cell, the method comprising:

providing an edge leveler comprising:

a first frame coupled to a track;

a plurality of first rollers rotatably mounted along the first frame;

a second frame; and

a plurality of second rollers rotatably mounted along the second frame;

wherein the second rollers are offset relative to the first rollers;

wherein a width of a gap between an adjacent pair of first and second rollers on a first end portion of the edge leveler is greater than a width of a gap between an adjacent pair of first and second rollers in a middle portion of the edge leveler; and

wherein the plurality of first rollers and the plurality of second rollers are configured to receive only a first edge of the bipolar plate therebetween; and

sliding the edge leveler along the track to level the first edge of the bipolar plate relative to the rest of the plate while the plate is stationary.

**14**

**15.** The method according to claim **14**, wherein a width of a gap between an adjacent pair of first and second rollers on a second end portion of the edge leveler is greater than the width of the gap between the adjacent pair of first and second rollers in the middle portion of the edge leveler.

**16.** The method according to claim **15**, wherein the width of the gap between the adjacent pair of first and second rollers on the second end portion of the edge leveler is adjustable.

**17.** The method according to claim **14**, wherein the width of the gap between the adjacent pair of first and second rollers on the first end portion of the edge leveler is adjustable.

**18.** The method according to claim **17**, wherein the width of the gap between the adjacent pair of first and second rollers on the first end portion of the edge leveler is adjustable via a set screw.

**19.** The method according to claim **14**, wherein the edge leveler is controlled by a controller to be automatically moved along a length of the track during the step of leveling the first edge of the bipolar plate.

\* \* \* \* \*