

US011423800B2

(12) **United States Patent**
Batzler et al.

(10) **Patent No.:** **US 11,423,800 B2**
(45) **Date of Patent:** **Aug. 23, 2022**

(54) **WELDING TRAINING SYSTEM**

(71) Applicant: **Illinois Tool Works Inc.**, Glenview, IL (US)

(72) Inventors: **Todd Gerald Batzler**, Hortonville, WI (US); **Bruce Patrick Albrecht**, Neenah, WI (US); **William Joshua Becker**, Manitowoc, WI (US)

(73) Assignee: **Illinois Tool Works Inc.**, Glenview, IL (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 67 days.

(21) Appl. No.: **16/996,494**

(22) Filed: **Aug. 18, 2020**

(65) **Prior Publication Data**

US 2020/0380885 A1 Dec. 3, 2020

Related U.S. Application Data

(63) Continuation of application No. 15/167,496, filed on May 27, 2016, now Pat. No. 10,748,442, which is a (Continued)

(51) **Int. Cl.**

G09B 19/24 (2006.01)
G09B 19/00 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **G09B 19/003** (2013.01); **B23K 9/095** (2013.01); **B23K 9/32** (2013.01); **B23K 37/00** (2013.01); **G09B 5/00** (2013.01); **G09B 19/24** (2013.01); **G05B 2219/37396** (2013.01); **G09B 9/00** (2013.01)

(58) **Field of Classification Search**

CPC G09B 19/24; B23K 9/09; B23K 9/095; B23K 9/0953

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,340,270 A 5/1920 Emil
2,045,800 A 6/1936 Walther
(Continued)

FOREIGN PATENT DOCUMENTS

CA 2311685 12/2001
CA 2517874 12/2001

(Continued)

OTHER PUBLICATIONS

Hillers et al. "TEREBES: Welding helmet with AR capabilities". In: Proceedings / Virtual and Augmented Reality Status Conference 2004 : [Leipzig, Feb. 19-20, 2004] / Federal Ministry of Education and Research (Year: 2004).*

(Continued)


Primary Examiner — Robert J Utama

(74) *Attorney, Agent, or Firm* — McAndrews, Held & Malloy, Ltd.

(57) **ABSTRACT**

A welding training system includes one or more welding operator device which provides positional feedback relevant to a quality weld. The positional feedback is analyzed and, when the positional feedback is outside of a predetermined range, a signal is provided to the welding operator. In one embodiment, tactile feedback is provided in a welding gun.

19 Claims, 9 Drawing Sheets



Related U.S. Application Data					
	continuation of application No. 12/473,392, filed on May 25, 2009, now Pat. No. 9,352,411.		4,943,702 A	7/1990	Richardson
			4,954,690 A	9/1990	Kensrue
			4,992,881 A	2/1991	Tomasek
			4,996,409 A	2/1991	Paton
			5,061,841 A	10/1991	Richardson
(60)	Provisional application No. 61/056,696, filed on May 28, 2008.		5,103,376 A	4/1992	Blonder
			5,185,561 A	2/1993	Good
			5,208,436 A	5/1993	Blankenship
			5,211,564 A	8/1993	Martinez
(51)	Int. Cl.		5,231,928 A	8/1993	Phillips
	<i>B23K 9/32</i> (2006.01)		5,243,265 A	9/1993	Matsuura
	<i>B23K 9/095</i> (2006.01)		5,281,921 A	1/1994	Novak
	<i>B23K 37/00</i> (2006.01)		5,283,418 A	2/1994	Bellows
	<i>G09B 5/00</i> (2006.01)		5,302,799 A	4/1994	Kennedy
	<i>G09B 9/00</i> (2006.01)		5,304,774 A	4/1994	Durheim
			5,306,893 A	4/1994	Morris
			5,320,538 A	6/1994	Baum
(56)	References Cited		5,343,011 A	8/1994	Fujii
	U.S. PATENT DOCUMENTS		5,380,978 A	1/1995	Pryor
			5,397,872 A	3/1995	Baker
			5,404,181 A	4/1995	Hung
			5,426,732 A	6/1995	Boies
			5,430,643 A	7/1995	Seraji
			5,448,405 A	9/1995	Clausen
			5,464,957 A	11/1995	Kidwell
			5,508,757 A	4/1996	Chen
			5,514,846 A	5/1996	Cecil
			5,517,420 A	5/1996	Kinsman
			5,521,843 A	5/1996	Hashima
			5,533,146 A	7/1996	Iwai
			5,543,863 A	8/1996	Lin
			5,546,476 A	8/1996	Mitaka
			5,571,431 A	11/1996	Lantieri
			5,592,241 A	1/1997	Kita
			5,617,335 A	4/1997	Hashima
			5,659,479 A	8/1997	Duley
			5,668,612 A	9/1997	Hung
			5,674,415 A	10/1997	Leong
			5,675,229 A	10/1997	Thorne
			5,681,490 A	10/1997	Chang
			5,708,253 A	1/1998	Bloch
			5,709,219 A	1/1998	Chen
			5,747,042 A	5/1998	Choquet
			5,823,785 A	10/1998	Matherne, Jr.
			5,832,139 A	11/1998	Batterman
			5,845,053 A	12/1998	Watanabe
			5,846,086 A *	12/1998	Bizzi A63B 69/0026 434/247
			5,856,844 A	1/1999	Batterman
			5,930,093 A	7/1999	Morrissett
			5,961,859 A	10/1999	Chou
			5,973,677 A	10/1999	Gibbons
			5,999,909 A	12/1999	Rakshit
			6,003,052 A	12/1999	Yamagata
			6,018,729 A	1/2000	Zacharia
			6,019,359 A	2/2000	Fly
			6,024,273 A	2/2000	Ludewig
			6,033,226 A	3/2000	Bullen
			6,039,494 A	3/2000	Pearce
			6,046,431 A	4/2000	Beattie
			6,046,754 A	4/2000	Stanek
			6,049,059 A	4/2000	Kim
			6,051,805 A	4/2000	Vaidya
			6,101,455 A	8/2000	Davis
			6,107,601 A	8/2000	Shimagama
			6,115,025 A	9/2000	Buxton
			6,130,407 A	10/2000	Villafuerte
			6,136,946 A	10/2000	Yao
			6,153,848 A	11/2000	Nagae
			6,155,475 A	12/2000	Ekelof
			6,163,946 A	12/2000	Pryor
			6,226,395 B1	5/2001	Gilliland
			6,236,017 B1	5/2001	Smartt et al.
			6,242,711 B1	6/2001	Cooper
			6,271,500 B1	8/2001	Hirayama
			6,288,359 B1	9/2001	Koch
			6,290,740 B1	9/2001	Schaefer
			6,301,763 B1	10/2001	Pryor
			6,315,186 B1	11/2001	Friedl

(56)

References Cited

U.S. PATENT DOCUMENTS

6,329,635 B1	12/2001	Leong	8,046,178 B2	10/2011	Dai
6,337,458 B1	1/2002	Lepeltier	8,100,694 B2	1/2012	Portoghese
6,371,765 B1	4/2002	Wall	8,110,774 B2	2/2012	Huonker
6,417,894 B1	7/2002	Goff	8,235,588 B2	8/2012	Louban
6,441,342 B1	8/2002	Hsu	8,248,324 B2	8/2012	Nangle
6,445,964 B1	9/2002	White	8,274,013 B2	9/2012	Wallace
6,469,752 B1	10/2002	Ishikawa	8,393,519 B2	3/2013	Allehaux
6,476,354 B1	11/2002	Jank	8,406,682 B2	3/2013	Elesseily
6,479,793 B1	11/2002	Wittmann	8,431,862 B2	4/2013	Kachline
6,506,997 B2	1/2003	Matsuyama	8,432,476 B2	4/2013	Ashforth
6,516,300 B1	2/2003	Rakshit	8,502,866 B2	8/2013	Becker
6,572,379 B1	6/2003	Sears	8,512,043 B2	8/2013	Choquet
6,583,386 B1	6/2003	Ivkovich	8,541,746 B2	9/2013	Andres
6,596,972 B1	7/2003	Di Novo	8,657,605 B2	2/2014	Wallace
6,614,002 B2	9/2003	Weber	8,681,178 B1	3/2014	Tseng
6,621,049 B2	9/2003	Suzuki	8,686,318 B2	4/2014	Albrecht et al.
6,622,906 B1	9/2003	Kushibe	8,692,157 B2	4/2014	Daniel
6,647,288 B2	11/2003	Madill	8,698,843 B2	4/2014	Tseng
6,670,574 B1	12/2003	Bates	8,747,116 B2	6/2014	Zboray et al.
6,697,761 B2	2/2004	Akatsuka	8,777,629 B2	7/2014	Kreindl
6,703,585 B2	3/2004	Suzuki	8,803,908 B2	8/2014	Van Osten
6,710,298 B2	3/2004	Eriksson	8,834,168 B2	9/2014	Peters
6,728,582 B1	4/2004	Wallack	8,851,896 B2	10/2014	Wallace
6,734,393 B1	5/2004	Friedl	8,860,760 B2	10/2014	Chen
6,744,011 B1	6/2004	Hu	8,911,237 B2	12/2014	Postlethwaite
6,748,249 B1	6/2004	Eromaki	8,915,740 B2	12/2014	Zboray
6,750,428 B2	6/2004	Okamoto	8,946,595 B2	2/2015	Ishida
6,753,909 B1	6/2004	Westerman	8,953,033 B2	2/2015	Yamane
6,768,974 B1	7/2004	Nanjundan	8,953,909 B2	2/2015	Guckenberger
6,795,068 B1	9/2004	Marks	RE45,398 E	3/2015	Wallace
6,839,049 B1	1/2005	Koizumi	8,987,628 B2	3/2015	Daniel et al.
6,857,553 B1	2/2005	Hartman	8,990,842 B2	3/2015	Rowley
6,868,726 B2	3/2005	Lemkin	8,992,226 B1	3/2015	Leach
6,910,971 B2	6/2005	Alsenz	9,011,154 B2	4/2015	Kindig
6,927,360 B2	8/2005	Artelsmair	9,012,802 B2	4/2015	Daniel
6,937,329 B2	8/2005	Esmiller	9,050,678 B2	6/2015	Daniel
6,967,635 B2	11/2005	Hung	9,050,679 B2	6/2015	Daniel
6,977,357 B2	12/2005	Hsu	9,089,921 B2	7/2015	Daniel
6,995,536 B2	2/2006	Challoner	9,101,994 B2	8/2015	Albrecht
7,015,419 B2	3/2006	Hackl	9,196,169 B2	11/2015	Wallace
7,025,053 B1	4/2006	Altamirano	9,218,745 B2	12/2015	Choquet
7,032,814 B2	4/2006	Blankenship	9,230,449 B2	1/2016	Conrardy
7,045,742 B2	5/2006	Feichtinger	9,269,279 B2	2/2016	Penrod et al.
7,081,888 B2	7/2006	Cok	9,293,056 B2	3/2016	Zboray
7,120,473 B1	10/2006	Hawkins	9,293,057 B2	3/2016	Zboray
7,132,617 B2	11/2006	Lee	9,318,026 B2	4/2016	Peters
7,132,623 B2	11/2006	Demiranda	9,330,575 B2	5/2016	Peters
7,150,047 B2	12/2006	Ferguson	9,336,686 B2	5/2016	Peters
7,173,215 B1	2/2007	Kapoor	9,384,675 B2	7/2016	Zboray
7,181,413 B2	2/2007	Hadden	9,402,122 B2	7/2016	Richardson
7,226,176 B1	6/2007	Huang	9,573,215 B2	2/2017	Pfeifer
7,261,261 B2	8/2007	Ligertwood	9,685,099 B2	6/2017	Boulware
7,342,210 B2	3/2008	Ferguson	9,724,787 B2	8/2017	Becker et al.
7,358,458 B2	4/2008	Daniel	9,789,603 B2	10/2017	Jacobsen
7,465,230 B2	12/2008	Lemay	10,748,442 B2 *	8/2020	Batzler G09B 19/24
7,474,760 B2	1/2009	Hertzman	2001/0026445 A1	10/2001	Naghi
7,523,069 B1	4/2009	Friedl et al.	2001/0032508 A1	10/2001	Lemkin
7,564,005 B2	7/2009	Cabanaw	2002/0043607 A1	4/2002	Tajima
7,574,172 B2	8/2009	Clark et al.	2002/0071550 A1	6/2002	Pletikosa
7,577,285 B2	8/2009	Schwarz	2002/0105797 A1	8/2002	Navid
D614,217 S	4/2010	Peters	2002/0114653 A1	8/2002	Gatta
7,698,094 B2	4/2010	Aratani	2002/0148745 A1	10/2002	Chang
D615,573 S	5/2010	Peters	2002/0153354 A1	10/2002	Norby
7,766,213 B2	8/2010	Henrikson	2003/0011673 A1	1/2003	Eriksson
7,789,811 B2	9/2010	Cooper	2003/0092496 A1	5/2003	Alsenz
7,813,830 B2	10/2010	Summers	2003/0172032 A1	9/2003	Choquet
7,826,984 B2	11/2010	Sjostrand	2004/0058703 A1	3/2004	Eromaki
7,831,098 B2	11/2010	Melikian	2004/0068335 A1	4/2004	Ferla
7,839,416 B2	11/2010	Ebensberger	2004/0069754 A1	4/2004	Bates
7,845,560 B2	12/2010	Emanuel	2004/0099648 A1	5/2004	Hu
D631,074 S	1/2011	Peters	2004/0175684 A1	9/2004	Kaasa
7,899,618 B2	3/2011	Ledet	2004/0223148 A1	11/2004	Takemura
7,962,967 B2	6/2011	Becker	2004/0227730 A1	11/2004	Sugihara
8,019,144 B2	9/2011	Sugihara	2004/0251910 A1	12/2004	Smith
8,044,942 B1	10/2011	Leonhard	2005/0006363 A1	1/2005	Hsu
			2005/0012598 A1	1/2005	Berquist
			2005/0016979 A1	1/2005	Stein
			2005/0017152 A1	1/2005	Ferguson
			2005/0073506 A1	4/2005	Durso

(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0127052	A1	6/2005	Spencer	2010/0133247	A1	6/2010	Mazumder
2005/0133488	A1	6/2005	Blankenship	2010/0145520	A1	6/2010	Gerio
2005/0135682	A1	6/2005	Abrams	2010/0201803	A1	8/2010	Melikian
2005/0179654	A1	8/2005	Hawkins	2010/0207620	A1	8/2010	Gies
2005/0197115	A1	9/2005	Clark et al.	2010/0224610	A1	9/2010	Wallace
2005/0207102	A1	9/2005	Russo	2010/0238119	A1	9/2010	Dubrovsky
2005/0219206	A1	10/2005	Schena	2010/0245273	A1	9/2010	Hwang
2005/0227635	A1	10/2005	Hawkins	2010/0283588	A1	11/2010	Gomez
2005/0256611	A1	11/2005	Pretlove	2010/0291313	A1	11/2010	Ling
2006/0010551	A1	1/2006	Bishop	2010/0314362	A1	12/2010	Albrecht
2006/0081740	A1	4/2006	Bellavance	2011/0000892	A1	1/2011	Mueller
2006/0136183	A1	6/2006	Choquet	2011/0006047	A1	1/2011	Penrod
2006/0151446	A1	7/2006	Schneider	2011/0091846	A1	4/2011	Kreindl
2006/0163228	A1	7/2006	Daniel	2011/0092828	A1	4/2011	Spohn
2006/0173619	A1	8/2006	Brant	2011/0117527	A1	5/2011	Conrardy
2006/0212169	A1	9/2006	Luthardt	2011/0176720	A1	7/2011	Vanosten
2006/0241432	A1	10/2006	Herline	2011/0183304	A1	7/2011	Wallace
2007/0038400	A1	2/2007	Lee	2011/0198329	A1	8/2011	Davidson
2007/0051711	A1	3/2007	Kachline	2011/0220616	A1	9/2011	Mehn
2007/0056942	A1	3/2007	Daniel et al.	2011/0220619	A1	9/2011	Mehn
2007/0114215	A1	5/2007	Bill	2011/0240605	A1	10/2011	Takayama
2007/0115202	A1	5/2007	Kiesenhofer	2011/0249090	A1	10/2011	Moore
2007/0164006	A1	7/2007	Burgstaller	2011/0284508	A1	11/2011	Miura
2007/0187378	A1	8/2007	Karakas	2011/0285290	A1	11/2011	Griffin
2007/0188606	A1	8/2007	Atkinson	2011/0286005	A1	11/2011	Yamamoto
2007/0209586	A1	9/2007	Ebensberger	2011/0290765	A1	12/2011	Albrecht
2007/0221636	A1	9/2007	Monzyk	2011/0313731	A1	12/2011	Vock
2007/0242065	A1*	10/2007	O'Flynn	2012/0007748	A1	1/2012	Forgues
		 G09B 9/003	2012/0037600	A1	2/2012	Katoh
			345/419	2012/0048838	A1	3/2012	Ishida
				2012/0072021	A1	3/2012	Walser
				2012/0077174	A1	3/2012	Depaul
				2012/0105476	A1	5/2012	Tseng
				2012/0113512	A1	5/2012	Tsanev
2007/0247793	A1	10/2007	Carnevali	2012/0122062	A1	5/2012	Yang et al.
2007/0248261	A1	10/2007	Zhou	2012/0175834	A1	7/2012	Hamm
2007/0264620	A1	11/2007	Maddix	2012/0180180	A1	7/2012	Steve
2007/0278196	A1	12/2007	James	2012/0188365	A1	7/2012	Stork
2007/0291166	A1	12/2007	Misawa	2012/0189993	A1	7/2012	Kindig
2008/0030631	A1	2/2008	Gallagher	2012/0205359	A1	8/2012	Daniel
2008/0038702	A1*	2/2008	Choquet	2012/0231894	A1	9/2012	Nicora
		 G09B 19/0038	2012/0248080	A1	10/2012	Hutchison
			434/260	2012/0248083	A1	10/2012	Garvey
				2012/0291172	A1	11/2012	Wills
2008/0061113	A9	3/2008	Seki	2012/0298640	A1	11/2012	Conrardy
2008/0077422	A1	3/2008	Dooley	2012/0323496	A1	12/2012	Burroughs
2008/0124698	A1	5/2008	Ebensberger	2013/0040270	A1	2/2013	Albrecht
2008/0128395	A1	6/2008	Aigner	2013/0064427	A1	3/2013	Picard et al.
2008/0128400	A1	6/2008	Michels	2013/0081293	A1	4/2013	Delin
2008/0149602	A1	6/2008	Lenzner	2013/0119037	A1	5/2013	Daniel
2008/0149608	A1	6/2008	Albrecht	2013/0178952	A1	7/2013	Wersborg
2008/0158502	A1	7/2008	Becker	2013/0182070	A1	7/2013	Peters
2008/0168290	A1	7/2008	Jobs	2013/0183645	A1	7/2013	Wallace
2008/0169277	A1	7/2008	Achtner	2013/0189656	A1	7/2013	Zboray
2008/0234960	A1	9/2008	Byington	2013/0189657	A1	7/2013	Wallace
2008/0314887	A1	12/2008	Stoger	2013/0189658	A1	7/2013	Peters
2009/0005728	A1	1/2009	Weinert	2013/0200882	A1	8/2013	Almalki
2009/0057285	A1	3/2009	Bashore	2013/0203029	A1	8/2013	Choquet
2009/0057286	A1	3/2009	Ihara	2013/0206741	A1	8/2013	Pfeifer et al.
2009/0109128	A1	4/2009	Nangle	2013/0209976	A1	8/2013	Postlethwaite
2009/0146359	A1	6/2009	Canfield	2013/0230832	A1	9/2013	Peters
2009/0152251	A1	6/2009	Dantinne	2013/0252214	A1	9/2013	Choquet
2009/0161212	A1	6/2009	Gough	2013/0256289	A1	10/2013	Knoener
2009/0173726	A1	7/2009	Davidson et al.	2013/0262000	A1	10/2013	Hutchison et al.
2009/0189974	A1	7/2009	Deering	2013/0264315	A1	10/2013	Hung
2009/0190826	A1	7/2009	Tate et al.	2013/0264322	A1	10/2013	Bornemann
2009/0200281	A1	8/2009	Hampton	2013/0265416	A1	10/2013	Enyedy
2009/0200282	A1	8/2009	Hampton	2013/0288211	A1	10/2013	Patterson
2009/0230107	A1	9/2009	Ertmer	2013/0323695	A1	12/2013	Zboray
2009/0231423	A1	9/2009	Becker et al.	2013/0326842	A1	12/2013	Pearson
2009/0236325	A1	9/2009	Gozalbo	2014/0008088	A1	1/2014	Chellew
2009/0249606	A1	10/2009	Diez	2014/0017642	A1	1/2014	Postlethwaite
2009/0283021	A1	11/2009	Wong	2014/0042135	A1	2/2014	Daniel et al.
2009/0298024	A1	12/2009	Batzler	2014/0042137	A1	2/2014	Daniel et al.
2009/0313549	A1	12/2009	Casner et al.	2014/0069899	A1	3/2014	Mehn
2009/0323121	A1	12/2009	Valkenburg	2014/0131337	A1	5/2014	Williams
2010/0020483	A1	1/2010	Ma	2014/0134579	A1	5/2014	Becker
2010/0048273	A1	2/2010	Wallace	2014/0134580	A1	5/2014	Becker
2010/0062405	A1	3/2010	Zboray	2014/0184496	A1	7/2014	Gribetz
2010/0062406	A1	3/2010	Zboray				
2010/0088793	A1	4/2010	Ghisleni				
2010/0123664	A1	5/2010	Shin				

(56)

References Cited

U.S. PATENT DOCUMENTS

2014/0220522 A1 8/2014 Peters
 2014/0234813 A1 8/2014 Peters
 2014/0263224 A1 9/2014 Becker
 2014/0263227 A1 9/2014 Daniel et al.
 2014/0267773 A1 9/2014 Jeung
 2014/0272835 A1 9/2014 Becker
 2014/0272836 A1 9/2014 Becker
 2014/0272837 A1 9/2014 Becker
 2014/0272838 A1 9/2014 Becker
 2014/0315167 A1 10/2014 Kreindl
 2014/0322684 A1 10/2014 Wallace
 2014/0346158 A1 11/2014 Matthews
 2014/0346163 A1 11/2014 Rajagopalan
 2014/0346793 A1 11/2014 Destories
 2014/0374396 A1 12/2014 Luo et al.
 2015/0056584 A1 2/2015 Boulware
 2015/0056585 A1 2/2015 Boulware
 2015/0072323 A1 3/2015 Postlethwaite
 2015/0122781 A1 5/2015 Albrecht
 2015/0154884 A1 6/2015 Salsich
 2015/0170539 A1 6/2015 Barrera
 2015/0190875 A1 7/2015 Becker
 2015/0190876 A1 7/2015 Becker
 2015/0190887 A1 7/2015 Becker
 2015/0190888 A1 7/2015 Becker
 2015/0194072 A1 7/2015 Becker
 2015/0194073 A1 7/2015 Becker
 2015/0209887 A1 7/2015 Delisio
 2015/0235565 A1 8/2015 Postlethwaite
 2015/0248845 A1 9/2015 Postlethwaite
 2015/0325153 A1 11/2015 Albrecht
 2015/0328710 A1 11/2015 Kachline
 2015/0352653 A1 12/2015 Albrecht
 2015/0375323 A1 12/2015 Becker
 2015/0375324 A1 12/2015 Becker
 2015/0375327 A1 12/2015 Becker
 2015/0379894 A1 12/2015 Becker
 2016/0039034 A1 2/2016 Becker
 2016/0039053 A1 2/2016 Becker
 2016/0049085 A1 2/2016 Beeson
 2016/0093233 A1 3/2016 Boulware
 2016/0125592 A1 5/2016 Becker et al.
 2016/0125593 A1 5/2016 Becker
 2016/0125594 A1 5/2016 Becker
 2016/0125653 A1 5/2016 Denis
 2016/0125761 A1 5/2016 Becker
 2016/0125762 A1 5/2016 Becker
 2016/0125763 A1 5/2016 Becker
 2016/0125764 A1 5/2016 Becker
 2016/0203734 A1 7/2016 Boulware
 2016/0203735 A1 7/2016 Boulware
 2016/0236303 A1 8/2016 Matthews
 2016/0260261 A1 9/2016 Hsu
 2016/0267806 A1 9/2016 Hsu
 2016/0288236 A1 10/2016 Becker
 2016/0358503 A1 12/2016 Batzler
 2017/0046974 A1 2/2017 Becker
 2017/0046975 A1 2/2017 Becker et al.
 2017/0046976 A1 2/2017 Becker et al.
 2017/0046977 A1 2/2017 Becker
 2017/0148352 A1 5/2017 Becker
 2017/0165776 A1 6/2017 Becker
 2017/0169729 A1 6/2017 Becker

FOREIGN PATENT DOCUMENTS

CA 2549553 7/2004
 CA 2554498 4/2006
 CN 1264822 8/2000
 CN 100371672 12/2004
 CN 1841321 10/2006
 CN 1866317 11/2006
 CN 1909020 2/2007
 CN 101218060 7/2008
 CN 201181527 1/2009

CN 101502906 8/2009
 CN 101770710 7/2010
 CN 102049595 5/2011
 CN 102083580 6/2011
 CN 102165504 A 8/2011
 CN 102165505 8/2011
 CN 102298858 12/2011
 CN 202200202 4/2012
 CN 102441737 5/2012
 CN 103038804 A 4/2013
 CN 202877704 4/2013
 CN 103071909 5/2013
 CN 103143810 6/2013
 CN 103392089 11/2013
 CN 203276641 11/2013
 CN 103831553 6/2014
 CN 203778997 8/2014
 DE 202010011064 10/2010
 DE 102010038902 2/2012
 EP 0323277 7/1989
 EP 0878263 11/1998
 EP 0963744 12/1999
 EP 1029306 8/2000
 EP 1295195 6/2001
 EP 1573699 9/2005
 EP 1797545 6/2007
 EP 1864744 12/2007
 EP 2022592 2/2009
 EP 2415560 2/2014
 ES 2438440 1/2014
 FR 1456780 7/1966
 FR 2827066 1/2003
 GB 2454232 A 5/2009
 JP H11146387 5/1999
 JP 2000298427 10/2000
 JP 2002317557 10/2002
 JP 2004181493 7/2004
 JP 2007021542 2/2007
 JP 2009125790 6/2009
 KR 100876425 12/2008
 KR 20110000152 1/2011
 SU 846203 7/1981
 SU 972552 11/1982
 SU 1324050 7/1987
 SU 1354234 11/1987
 SU 1489933 6/1989
 SU 1638145 3/1991
 WO 9958286 11/1999
 WO 03019349 1/2003
 WO 2004057554 7/2004
 WO 2005102230 11/2005
 WO 2005110658 11/2005
 WO 2006004427 1/2006
 WO 2006034571 4/2006
 WO 2007009131 1/2007
 WO 2007044135 4/2007
 WO 2008076777 6/2008
 WO 2009022443 2/2009
 WO 2009053829 4/2009
 WO 2009060231 A1 5/2009
 WO 2009092944 7/2009
 WO 2009146359 A1 12/2009
 WO 2010000003 1/2010
 WO 2010020867 2/2010
 WO 2010020869 2/2010
 WO 2010020870 2/2010
 WO 2010111722 10/2010
 WO 2011112493 9/2011
 WO 2011150165 12/2011
 WO 2012036710 3/2012
 WO 2012137060 10/2012
 WO 2013023012 2/2013
 WO 2013061518 5/2013
 WO 2013138831 9/2013
 WO 2013186413 12/2013
 WO 2014007830 1/2014
 WO 2014074296 5/2014

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	2014074297	5/2014
WO	2014140719	9/2014

OTHER PUBLICATIONS

“Low Cost Virtual Reality Welding Training System,” NSRP Joint Panel Meeting, Apr. 21, 2010, http://www.nsrp.org/6-Presentations/Joint/042110_Low_Cost_Virtual_Reality_Welder_Training_System_Fast.pdf.

“NJC Technology Displayed at ShipTech 2005”, *Welding Journal*, vol. 84, No. 3, Mar. 2005, p. 54, https://app.aws.org/w/r/www/wj/2005/03/WJ_2005_03.pdf.

“Sheet Metal Conference XXII,” Conference Program, American Welding Society, May 2006, Detroit.

“SOLDAMATIC: Augmented Training Technology for Welding,” Seabery Augmented Training Technology, Seabery Soluciones, 2011.

“Virtual Reality Program to Train Welders for Shipbuilding”, American Welding Society, Navy Joining Center, <https://app.aws.org/wj/2004/04/052/>.

“Virtual Reality Welder Training Initiatives: Virtual Welding Lab Pilot,” Paul D. Camp Community College, Advanced Science & Automation Corporation, Northrop Grumman Newport News, Nov. 22, 2006, http://www.nsrp.org/6-Presentations/WD/103106_Virtual_Reality_Welder.pdf.

“Virtual Welding—A Low Cost Virtual Reality Welder Training System”, Interim Status Report # 4, Technology Investment Agreement 2008-600, Feb. 18, 2009, http://www.nsrp.org/3-Key_Deliverables/FY08_Low-Cost_Virtual_Reality_Welder_Trainer/FY08_Low-Cost_Virtual_Reality_Welder_Trainer-Interim2.pdf.

“Virtual Welding: A Low Cost Virtual Reality Welder Training System,” NSRP ASE, Feb. 19, 2009, http://www.nsrp.org/6-presentations/WD/020409_Virtual_Welding_Wilbur.pdf.

“Vision for Welding Industry,” American Welding Society, Apr. 22, 1999, <http://www.aws.org/library/doclib/vision.pdf>.

“Welding in Defense Industry,” American Welding Society conference schedule, 2004. https://app.aws.org/conferences/defense/live_index.html.

“Welding Technology Roadmap,” prepared by Energetics, Inc., Columbia, MD, in cooperation with the American Welding Society and The Edison Welding Institute, Sep. 2000.

[IMTS Preview] Lincoln Electric for Welding Simulator, Environmental Push Pull System, Robotic Technology, Aug. 9, 2010. 123arc.com—“Weld into the future”; 2000.

Advance Program of American Welding Society Programs and Events, Nov. 11-14, 2007, Chicago.

Aiteanu, Dorin, “Virtual and Augmented Reality Supervisor for a New Welding Helmet” Nov. 15, 2005, pp. 1-150.

Aiteanu, Dorin, and Axel Graser, “Computer-Aided Manual Welding Using an Augmented Reality Supervisor,” Sheet Metal Welding Conference XII, Livonia, MI, May 9-12, 2006, pp. 1-14.

Aiteanu, Dorin, et al., “A Step Forward in Manual Welding: Demonstration of Augmented Reality Helmet,” Institute of Automation, University of Bremen, Germany, 2003.

Aiteanu et al., Generation and Rendering of a Virtual Welding Seam in an Augmented Reality Training Environment, Proceedings of the Sixth IASTED International Conference Visualization, Imaging, and Image Proceeding, Aug. 28-30, 2006, Palma de Mallorca, Spain ISBN Hardcopy: 0-88986-598-1 /CD: 0-88986-600-7 (8 pages).

American Welding Society Forms: typical Procedure Qualification Record and Welding Procedure Specification forms.

American Welding Society’s Virtual Welding Trailer to Debut at FABTECH Careers in Welding Trailer Appeals to New Generation of Welders, Miami, Florida, Nov. 3, 2011.

ArcSentry Weld Monitoring System, Version 3, Users Manual, Native American Technologies, Golden, CO, Dec. 10, 1999.

ARVIKA Forum Vorstellung Projekt PAARA, BMW Group Virtual Reality Center, Nuernberg, 2003.

Ascension Technology Corporation: Tracking 3D Worlds: <http://ascension-tech.com/>, Dec. 1996.

Barckhoff, J.R.; “Total Welding Management,” American Welding Society, 2005.

Bender Shipbuilding and Repair, Co., “Virtual Welding—A Low Cost Virtual Reality Welder Training System”, Technical Proposal, Jan. 23, 2008.

Byrd, Alex Preston, “Identifying the effects of human factors and training methods on a weld training program” (2014). Graduate Theses and Dissertations. Paper 13991.

California Department of Corrections and Rehabilitation Uses SimWelder From SGI and VRsim for Vocational Training—VRsim, Jun. 18, 2008.

Canadian Metalworking, Lincoln Electric launches family of virtual reality welding tools, Nov. 21, 2012.

Canadian Office Action Appln No. 2,961,093 dated Mar. 5, 2018 (4 pgs).

Canadian Office Action Appln No. 2,961,806 dated Jan. 8, 2018 (3 pgs).

Central Welding Supply <http://www.welders-direct.com/> Feb. 29, 2000.

Cho, Min Hyn, Numerical Simulation F Arc Welding Process and its Application Dissertation for Ohio State University by Min Hyun Cho, M.S. 2006: See Internet as this document is security protected) https://etd.ohiolink.edu/ap:0:0:APPLICATION_PROCESS=DOWNLOAD_ETD_SUB_DOC_ACCNUM:::F1501_ID:osu1155741113, attachment.

Choquet, Claude, ARC+ & ARC PC Welding Simulators: Teach Welders with Virtual Interactive 3D Technologies; Jul. 2010.

Choquet, Claude, ARC+: Today’s Virtual Reality Solution for Welders, Jun. 1, 2008.

Cybernetics: Enhancing Human Performance found in the DTIC Review dated Mar. 2001, p. 186/19. See <http://www.dtic.mil/dtic/tr/fulltext/u2/a385219.pdf>.

Echtler, Florian, Fabian Stuurm, Kay Kindermann, Gudrun Klinker, Joachim Stilla, Jorn Trilk, Hesam Najafi, “The Intelligent Welding Gun: Augmented Reality for Experimental Vehicle Construction,” Virtual and Augmented Reality Applications in Manufacturing, Ong S.K and Nee A.Y.C., eds., Springer Verlag, 2003, pp. 1-27.

Evaluating Two Novel Tactile Feedback Devices, by Thomas Hulin, Phillipp Kremer, Robert Scheibe, Simon Schaeztle and Carsten Preusche presented at the 4th International Conference on Enactive Interfaces, Grenoble, France, Nov. 19-22, 2007.

EWI, “EWI ArcCheck,” marketing brochure, Columbus, Ohio, 1 page.

EWI, “EWI SkillBuilder,” marketing brochure, Columbus, Ohio, 1 page.

Fast et al., Virtual Training for Welding, Proceedings of the Third IEEE and ACM International Symposium on Mixed and Augmented Reality (ISMAR 2004); 0-7695-2191-6/04; 2004.

Fast, Kenneth, Jerry Jones, and Valerie Rhoades; “Virtual Welding—A Low Cost Virtual Reality Welder Training System Phase II,” National Shipbuilding Research Program (Nsrp), NSRP ASE Technology Investment Agreement No. 2010-357, Feb. 29, 2012, http://www.nsrp.org/3-RA-Panel_Final_Reports/FY08_Virtual_Welder_Final_Report.pdf.

Fite-Georgel, Pierre; “Is there a Reality in Industrial Augmented Reality?” 10th IEEE International Symposium on Mixed and Augmented Reality (ISMAR), 2011.

Fridenfolk et al., Design and Validation of a Universal 6D Seam Tracking System in Robotic Welding Based on Laser Scanning, Industrial Robotics: Programming, Simulation, and Application, ISBN 3-86611-286-6, pp. 702, ARS/pIV, Germany, Dec. 2006, edited by Kin Huat.

Fronius “The Ghost”: http://www.fronius.com/cps/rde/xchg/SID-3202EAB7-AE082518/fronius_international/hs.xsl/79_15490_ENG_HTML.htm; 2006.

Fronius International GmbH—Focus on Welding—Fronius Virtual Welding; http://www.fronius.com/cps/rde/xchg/SID-99869147-0110E322/fronius_international/hs.xsl/79_15490_ENG_HML.htm; 2006.

Fronius Perfect Welding; 06,3082, EN v01 2010 aw05; Virtual Welding—The training method of the future; Feb. 20, 2012.

(56)

References Cited

OTHER PUBLICATIONS

<ftp://www.hitl.washington.edu/pub/scivw/publications/IDS-pdf/HAPTIC1.PDF>, (University of Washington): Table 11, Tactile Feedback Actuator Technologies, p. 119, below the table is a. Based on Hasser (1995, 1996).

Gawda—Welding & Gases Today Online GAWDA Media Blog; Will Games Turn Welding into a Virtual Market? Friday, Dec. 2, 2011; <http://www.weldingandgases.com/blogs/Devin-OToole/index.php/ta> . . .

Gundersen, O., et al. "The Use of an Integrated Multiple Neural Network Structure for Simultaneous Prediction of Weld Shape, Mechanical Properties, and Distortion in 6063-T6 and 6082-T6 Aluminum Assemblies", *Mathematical Modelling of Weld Phenomena*, vol. 5, Maney Publishing, 2001.

Haptic Feedback for Virtual Reality by Grigore C. Burdea dated 1996.

Hashimoto, Nobuyoshi et al., "Training System for Manual Arc Welding by Using Mixed Reality: Reduction of Position-Perception Error of Electrode Tip," *Journal of the Japan Society for Precision Engineering*, vol. 72, pp. 249-253, 2006.

Hemez, Francois M., Scott W. Doebeling, "Uncertainty, Validation of Computer Models and the Myth of Numerical Predictability," *Engineering Analysis Group (ESA-EA)*, Los Alamos National Laboratory, dated 2004.

Hillers, B. and Axel Graeser, "Direct welding arc observation without harsh flicker," *FABTECH International and AWS Welding Show*, 2007.

Hillers, B. and Axel Graeser, "Real time Arc-Welding Video Observation System," 62nd International Conference of IIW, Jul. 12-17, 2009, Singapore, 2009.

Hillers, B., et al.; "TEREBES: Welding Helmet with AR Capabilities," Institute of Automation, University of Bremen, and Institute of Industrial Engineering and Ergonomics, RWTH Aachen University, 2004.

Hillers, Bernd, Dorin Aiteanu, Axel Graser, "Augmented Reality—Helmet for the Manual Welding Process," *Virtual and Augmented Reality Applications in Manufacturing*, Institute of Automation, University of Bremen, 2004.

Himperich, Frederick, "Applications in Augmented Reality in the Automotive Industry," *Fachgebiet Augmented Reality*, Department of Informatics, Jul. 4, 2007, p. 1-21.

Hodgson, et al. "Virtual Reality in the Wild: A Self-Contained and Wearable Simulation System." *IEEE Virtual Reality*, Mar. 4-8, 2012, Orange County, CA USA.

<http://www.123arc.com> "Simulation and Certification"; 2000.

Image from [Sim Welder.com](http://www.simwelder.com)—R-V's Welder Training Goes Virtual, www.rvii.com/PDF/simwelder.pdf; Jan. 2010.

Impact Spring 2012 vol. 12, No. 2, Undergraduate Research in Information Technology Engineering, University of Virginia School of Engineering & Applied Science; 2012.

Impact Welding: miscellaneous examples from current and archived website, trade shows, etc. See, e.g., <http://www.impactwelding.com>. Integrated Microelectromechanical Gyroscopes; *Journal of Aerospace Engineering*, Apr. 2003 pp. 65-75 (p. 65) by Huikai Xie and Garry K. Fedder.

International Search Report for PCT application No. PCT/US2013/066040 dated Mar. 11, 2014, 12 pgs.

International Search Report for PCT application No. PCT/US2009/045436, dated Nov. 9, 2009, 3 pgs.

International Search Report for PCT application No. PCT/US2012/050059, dated Nov. 27, 2012, 16 pgs.

International Search Report for PCT application No. PCT/US2013/038371, dated Jul. 31, 2013, 8 pgs.

International Search Report for PCT application No. PCT/US2013/066037, dated Mar. 11, 2014, 10 pgs.

International Search Report for PCT application No. PCT/US2014/018107, dated Jun. 2, 2014, 3 pgs.

International Search Report for PCT application No. PCT/US2014/018109, dated Jun. 2, 2014, 4 pgs.

International Search Report for PCT application No. PCT/US2014/018113, dated Jun. 2, 2014, 3 pgs.

International Search Report for PCT application No. PCT/US2014/018114, dated Jun. 2, 2014, 4 pgs.

International Search Report for PCT application No. PCT/US2014/065498, dated May 11, 2015, 13 pgs.

International Search Report for PCT application No. PCT/US2014/065506, dated Jun. 26, 2015, 16 pgs.

International Search Report for PCT application No. PCT/US2014/065512, dated Jun. 8, 2015, 17 pgs.

International Search Report for PCT application No. PCT/US2014/065525, dated Jul. 23, 2015, 16 pgs.

International Search Report for PCT application No. PCT/US2014/067951, dated Feb. 24, 2015, 10 pgs.

International Search Report for PCT application No. PCT/US2015/037410, dated Nov. 6, 2015, 10 pgs.

International Search Report for PCT application No. PCT/US2015/037439, dated Nov. 3, 2015, 12 pgs.

International Search Report for PCT application No. PCT/US2015/037440, dated Nov. 3, 2015, 12 pgs.

International Search Report for PCT application No. PCT/US2015/039680, dated Sep. 23, 2015, 12 pgs.

International Search Report from PCT application No. PCT/US2014/018103, dated Jun. 30, 2014, 13 pgs.

International Search Report from PCT application No. PCT/US2015/043370, dated Dec. 4, 2015, 12 pgs.

International Search Report from PCT application No. PCT/US2015/058563, dated Jan. 29, 2016, 13 pgs.

International Search Report from PCT application No. PCT/US2015/058567, dated May 6, 2016, 15 pgs.

International Search Report from PCT application No. PCT/US2015/058569, dated Feb. 10, 2016, 12 pgs.

International Search Report from PCT application No. PCT/US2015/058660, dated Feb. 2, 2016, 14 pgs.

International Search Report from PCT application No. PCT/US2015/058664, dated Apr. 25, 2016, 17 pgs.

International Search Report from PCT application No. PCT/US2015/058666, dated Feb. 1, 2016, 11 pgs.

International Search Report from PCT application No. PCT/US2015/058667, dated Feb. 5, 2016, 14 pgs.

International Search Report from PCT application No. PCT/US2016/023612, dated Jul. 18, 2016, 11 pgs.

Jo et al., Visualization of Virtual Weld Beads, VRST 2009, Kyoto, Japan, Nov. 18-20, 2009; Electronics and Telecommunications Research Institute (ETRI) ACM 978-1 60558-869-8/09/0011.

Kiwinakiful; Holographic TV coming 2012 (as seen on BBC); <http://www.youtube.com/watch?v=Ux6aD6vE9sk&feature=related>, Jul. 2, 2011.

Kobayashi, Kazuhiko et al., "Modified Training System for Manual Arc Welding by Using Mixed Reality and Investigation of Its Effectiveness," *Journal of the Japan Society for Precision Engineering*, vol. 70, pp. 941-945, 2004.

Kobayashi, Kazuhiko et al., "Simulator of Manual Metal Arc Welding with Haptic Display," *Chiba University, ICAT 2001*, Dec. 2001.

Kobayashi, Kazuhiko et al., "Skill Training System of Manual Arc Welding by Means of Face-Shield HMD and Virtual Electrode," Chiba University, Japan, R. Nakatsu et al. (eds.), *Entertainment Computing*, Springer Science+Business Media, New York, 2003.

Kooima, Robert; Kinect +3D TV=Virtual Reality; <http://www.youtube.com/watch?v=2MX1RinEXUM&feature=related>, Feb. 26, 2011.

Leap Motion; <https://www.leapmotion.com/>, May 2012.

Lincoln Electric VRTEX Virtual Reality Arc Welding Trainer; <http://www.lincolnelectric.com/en-us/equipment/training-equipment/pages/vrtex360.aspx>; 1999.

MacCormick, John; How does the Kinect work?; <http://users.dickinson.edu/~jmac/selected-talks/kinect.pdf>, Dec. 1, 2011.

NAMEs Users Guide, NA Tech Neural Applications, Copyright 1997, 1998, 1999, 2000 Golden, CO (123 pages).

NAMEs, Native American Technologies Weld Measuring Software, Users Guide, 2000.

(56)

References Cited

OTHER PUBLICATIONS

National Science Foundation—Where Discoveries Begin—Science and Engineering’s Most Powerful Statements Are Not Made From Words Alone—Entry Details for NSF International Science & Engineering Visualization Challenge, Public Voting ended on Mar. 9, 2012; Velu the welder by Muralitharan Vengadasalam—Sep. 30, 2011; <https://nsf-scivis.skild.com/skild2/NationalScienceFoundation/viewEntryDetail.action?pid> . . .

Native American Technologies, “ArcDirector Weld Controller” web page, <http://web.archive.org/web/20020608125127/http://www.natech-inc.com/arcdirector/index.html>, published Jun. 8, 2002.

Native American Technologies, “ArcSentry Weld Quality Monitoring System” web page, <http://web.archive.org/web/20020608124903/http://www.natech-inc.com/arcsentry1/index.html>, published Jun. 8, 2002.

Native American Technologies, “P/NA.3 Process Modelling and Optimization” web pages, <http://web.archive.org/web/20020608125619/http://www.natech-inc.com/pna3/index.html>, published Jun. 8, 2002.

Native American Technologies, “Process Improvement Products” web page, <http://web.archive.org/web/20020608050736/http://www.natech-inc.com/products.html>, published Jun. 8, 2002.

Natural Point, Trackir; <http://www.naturalpoint.com/trackir/>, Dec. 2003.

NZ Manufacturer Game promotes welding trade careers; <http://nzmanufacturer.co.nz/2011/11/gme-promotes-welding-trade-careers/> . . . Compentenz Industry Training; www.competenz.org.nz; Game promotes welding trade careers, Nov. 7, 2011.

OptiTrack: Motion Capture Systems: <http://www.naturalpoint.com/optitrack/>, Mar. 2005.

Penrod, Matt; “New Welder Training Tools,” EWI PowerPoint presentation, 2008.

PhaseSpace: Optical Motion Capture: <http://phasespace.com/>, 2009.
Playstation; Move Motion Controller: <http://us.playstation.com/ps3/playstation-move/>, Mar. 2010.

Polhemus: Innovation in Motion: <http://polhemus.com/?page=researchandtechnology>, 1992.

Porter et al., EWI-CRP Summary Report SR0512, Jul. 2005—Virtual Reality Welder Training.

Porter, N., et al. Virtual Reality Welder Training, Paper No. 2005-P19.

Porter, Nancy C., Edison Welding Institute; J. Allan Cote, General Dynamics Electric Boat; Timothy D. Gifford, VRSim; and Wim Lam, FCS Controls—Virtual Reality Welder Training—Project No. S1051 Navy Man Tech Program; Project Review for Ship Tech 2005,—Mar. 1, 2005, Biloxi, MS, http://www.nsrp.org/6-Presentations/WD/Virtual_Welder.pdf.

Porter, Nancy C., Edison Welding Institute; J. Allan Cote, General Dynamics Electric Boat; Timoty D. Gifford, VRSim; and Wim Lam, FCS Controls—Virtual Reality Welder Training—Session 5; Joining Technologies for Naval Applications; 2007.

Quebec International, May 28, 2008 ‘Video Game’ Technology to Fill Growing Need; http://www.mri.gouv.qc.ca/portail/_scripts/actualities/viewnew.sap?NewID=5516.

Ryu, Jonghyun, Jaehoon Jung, Sejoon Kim, and Seungmoon Choi, “Perceptually Transparent Vibration Rendering Using a Vibration Motor for Haptic Interaction,” 16 IEEE International Conference on Robot & Human Interactive Communication, Jeju, Korea, Aug. 26-29, 2007.

Sandor, Christian, Gudrun Klinker, “PAARTI: Development of an Intelligent Welding Gun for BMW,” PIA 2003, Tokyo, Japan, Technical University of Munich Department of Informatics, Oct. 7, 2003.

Sandor, Christian, Gudrun Klinker; “Lessons Learned in Designing Ubiquitous Augmented Reality User Interfaces,” Emerging Technologies of Augmented Reality Interfaces, Eds. Haller, M, Billinghurst, M., and Thomas, B., Idea Group Inc., 2006.

ShotOfFuel; Wii Head Tracking for 3D, <http://www.youtube.com/watch?v=1x5ffF-0Wr4>, Mar. 19, 2008.

Stone, R. T., K. Watts, and P. Zhong, “Virtual Reality Integrated Welder Training, Welding Research,” *Welding Journal*, vol. 90, Jul. 2011, pp. 136-s-141-s, https://app.aws.org/wj/supplement/wj201107_s136.pdf.

TCS News & Events: Press Release: TCS wins the “People Choice” award from National Science Foundation, USA, pp. 1-6; Press Release May 21, 2012; http://www.tsc.com/news_events/press_releases/Pages/TCS_People_Choice_award_Natio . . .

TeachWELD: Welding Simulator/Hands-on Learning for Welding: <http://realityworks.com/products/teachweld-welding-simulator>; 2012.
Terebes; miscellaneous examples from <http://www.terebes.uni-bremen.de>.

The Rutgers Master II—New Design Force-Feedback Glove by Mourad Bouzit, Member, IEEE, Grigore Burdea, Senior Member, IEEE, George Popescu, Member, IEEE, and Rares Bolan, Student Member, found in *IEEE/ASME Transactions on Mechatronics*, vol. 7, No. 2, Jun. 2002.

Thefabricator.com—Arc Welding Article; Heston, Tim, Virtual welding—Training in a virtual environment gives welding students a leg up—Mar. 11, 2008.

Tschirner, Petra, Hillers, Bernd, and Graeser, Axel; “A Concept for the Application of Augmented Reality in Manual Gas Metal Arc Welding,” *Proceedings of the International Symposium on Mixed and Augmented Reality*, 2002.

Vicon: Motion Capture Systems: <http://vicon.com/>, Dec. 1998.

Virtual Reality Training Manual Module 1—Training Overview—A Guide for Gas Metal Arc Welding—EWI 2006.

VRSim™, virtual training for welding.

VRTEX 360 Operator’s Manual, Lincoln Electric, Oct. 2012.

VRTEX 360, Lincoln Electric, Dec. 2009.

VRTEX™ 360 Training Solution Publication MC09-98 | Issue Date Dec. 2009, Lincoln Global, Inc©.

Weld Training Solutions, Realweld, The Lincoln Electric Company, Jul. 2015.

Welding Journal, American Welding Society, Nov. 2007, https://app.aws.org/wj/2007/11/WJ_2007_11.pdf.

White, S., et al., “Low-Cost Simulated MIG Welding for Advancement in Technical Training,” *Virtual Reality*, 15, 1, 69-81, Mar. 2011. ISSN:13594338 [Retrieved from EBSCOhost, Jun. 15, 2015].

* cited by examiner




FIG. 1





FIG. 2






FIG. 4




FIG. 5




FIG. 6




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 7D




FIG. 7




FIG. 8




FIG. 9

WELDING TRAINING SYSTEM**CROSS-REFERENCE TO RELATED
APPLICATIONS/INCORPORATION BY
REFERENCE**

This application is a continuation of U.S. application Ser. No. 15/167,496 filed May 27, 2016, which is a continuation of U.S. application Ser. No. 12/473,392 filed May 28, 2009 (now U.S. Pat. No. 9,352,411), which claims the benefit of U.S. provisional application 61/056,696 filed May 28, 2008, which is hereby incorporated by reference in their entirety.

BACKGROUND

The mechanical quality of an arc weld is a function of many complex variables, and can vary significantly depending on the skill of the operator. It is, therefore, very important for welding operators to be trained in welding processes and control. Training welders to provide a quality weld, however, can be a very time consuming process. Typical training programs are long, expensive, and inefficient. These programs, moreover, require personal hands-on instruction, and the number of instructor necessary is also problematic.

Due to the need to simplify and improve training, virtual reality (VR) trainers have been developed. In these systems, the operator does not strike an arc, but rather receives guidance from an instructor or the welding system in a “virtual” system, of the type typically found in the PC gaming industry. These systems can be either “virtual reality” and/or “augmented reality” systems. In ‘virtual reality’, the reality of the operator is completely replaced, typically through the use of helmet or other enclosure, with a computer-generated environment that visually represents the new environment. This can be extended with additional sensors and actuators to coordinated forces applied in conjunction with the visual reality to enhance the virtual experience. In ‘augmented reality’, portions of the operator’s senses may be overridden with computer-generated data, which can include, for example, graphic images. The technology to create sensation, or constrain movement also falls into this category.

SUMMARY OF THE INVENTION

The present invention uses real welding and feedback to the operator to train an operator, or a combination of real and simulated welding experiences, as opposed to solely simulated or virtual training.

In this invention, a ‘closed-loop’ feedback mechanism is provided with the welding trainee ‘in the loop’. By measuring the movements of trainee and then feeding back a signal in such a way as to encourage the trainee to compensate in the proper direction, an environment can be created where proper hand-eye coordination and muscle-memory is learned, both in a simulated and real-arc scenario.

This invention gives the operator the ability to learn faster in a real arc situation, but also tries to help the operator as if the teacher is with the student, when, in reality, the teacher is not. Therefore, fewer instructors are required.

In one aspect of the invention, a device for use by a welding operator while performing a weld is provided. The welding operator device includes a controller, a position sensor providing position feedback data to the controller, and a position feedback indicator operatively coupled to the controller. The controller is programmed to receive position data from the position sensor, to determine a position of at

least one of a welding operator performing a weld and an angle of the weld, and to activate the position indicator to provide feedback to the welding operator to correct a welding parameter during a weld. In some applications, the welding operator device can include a communications device for communicating position feedback data to at least one of a welding power source and a welding network.

In another aspect of the invention, the position sensor can be an angle sensor or an altimeter. The position sensor can be, for example, a global positioning sensor, a gyroscopic sensor, an accelerometer, and a micro-electromechanical gyroscope. The position indicator can be a visual feedback device, an audio feedback device, and a tactile feedback device. A visual feedback device can include, for example, an LCD, LED, or OLED display. The tactile feedback device can comprise a vibrational motor, a piezo-electric device, weighted rotating cam, an air bladder, and an exoskeleton. A plurality of tactile feedback devices can be located on the welding operator device to provide a directional feedback signal to the operator.

In another aspect of the invention, the welding operator device can be a welding gun, a welding glove, or a wristband worn by the welding operator. Alternatively, the welding operator device can comprise an eye shield for shielding the operator’s eyes during a weld, such as a welding helmet or eye goggles.

In yet another aspect of the invention, a welding system is provided including a welding power source for providing welding power to the weld, which includes a power source controller and a power source communications device. A welding operator device is in communication with the power source communications device in the welding power source, and includes a position feedback sensor, an operator indicator, and a communications device operatively coupled to the position feedback sensor and the operator indicator. The communications device in the welding operator device provides position feedback data to the welding power source controller, and the welding power source controller is programmed to evaluate the position feedback and to activate the operator indicator when the position feedback is outside of a predetermined range.

In another aspect of the invention, the welding system can include at least one weld position locator device. The weld position locator device comprises a position sensor operatively coupled to a weld position communications device, that is positionable adjacent a part to be welded. The communications device provides weld position feedback data from the position sensor to the welding power source for use in evaluating the position of the weld.

In another aspect of the invention, the welding operator device can be a protective eye shielding device, a welding gun, a glove, and or wrist band. The system can also include a second welding operator device that provides position feedback data to the welding power source, and the second welding operator device can be a protective eye shielding device, a welding gun, a glove, or a wrist band.

In still another aspect of the invention, a welding gun is provided including a position sensor, a controller, and a tactile feedback device. The controller is programmed to receive feedback from the position sensor, and to activate the tactile feedback device when the feedback indicates that the position of the welding operator device is outside of a predetermined range. The position sensor can be at least one of an angle sensor and an altimeter. The tactile feedback device can be one or more of a vibrational motor, a piezo-electric device, and an air bladder. The welding gun can include a plurality of tactile feedback devices located at a

3

corresponding plurality of positions around the gun or a handle of the welding gun, and the controller can be programmed to selectively activate one or more of the plurality of tactile devices to provide a directional feedback signal to a welding operator during a weld.

In still another aspect of the invention, a welding glove is provided including a position sensor, a controller, and a tactile feedback device. The controller is programmed to receive feedback from the position sensor, and to activate the tactile feedback device when the feedback indicates that the position of the welding operator device is outside of a predetermined range. The position sensor can be at least one of an angle sensor and an altimeter. The tactile feedback device can be one or more of a vibrational motor, a piezoelectric device, and an air bladder. The gun can include a plurality of tactile feedback devices located at a corresponding plurality of positions around the welding glove, and the controller can be programmed to selectively activate one or more of the plurality of tactile devices to provide a directional feedback signal to a welding operator during a weld.

In another aspect of the invention, a welding system is provided including a welding power source for providing welding power to a weld, and including a power source controller and a power source communications device. The system also includes a first welding operator device in communications with the power source communications device in the welding power source, and including a position feedback sensor, and a communications device operatively coupled to the position feedback sensor. A second welding operator device is also provided in communication with the welding power source, and including an operator indicator, and a communications device operatively coupled to the operator indicator. The communications device in the first welding operator device provides position feedback data to the welding power source controller, and the welding power source controller is programmed to evaluate the position feedback and to communicate a signal to the communications device in the second welding operator device to activate the operator indicator when the position feedback is outside of a predetermined range. In another aspect of the invention, the first welding operator device is at least one of a welding gun and a welding glove. The second welding operator device can be or include a protective eye shield.

In still another aspect of the invention, a welding power source is provided comprising a welding power supply for conditioning raw power for a welding-type process, a controller, and a communications device in communication with the controller and one or more peripheral devices configured to provide position feedback relevant to a quality of the welding-type process, wherein the controller is programmed to receive the position feedback, compare the position feedback to stored data, and to provide a signal to a weld operator when the position feedback is outside of a predetermined range. The controller can further be programmed to selectively provide an actual weld where the position data is monitored and stored data during a weld and a simulated welding-type process where the position feedback is monitored and compared to stored data without starting an arc.

These and still other advantages of the invention will be apparent from the description which follows. In the detailed description below, the preferred embodiment of the invention will be described in reference to the accompanying drawings. This embodiment does not represent the full scope of the invention. Rather the invention may be employed in other embodiments. Reference should therefore be made to the claims herein for interpreting the breadth of the invention.

4

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a view of a welding power source and associated components for performing a welding operation in accordance with the present invention;

FIG. 2 is a perspective view of the welding gun of FIG. 1;

FIG. 3 is an exploded view of the helmet of FIG. 1;

FIG. 4 is a front view of the helmet of FIG. 3, and illustrating a bullseye display;

FIG. 5 is a front view of the helmet of FIG. 3 illustrating a ghost image of a gun on the helmet display;

FIG. 6 is a front view of the helmet of FIG. 3 illustrating a weld travel speed gauge on the helmet display;

FIGS. 7 and 7A-7D illustrate a front view of the helmet of FIG. 3 illustrating a torch angle position correction images on the helmet display;

FIG. 8 is a simplified block diagram of the electronic components of FIG. 1;

FIG. 9 is a flow chart illustrating the steps in a training process in accordance with the present invention.

DETAILED DESCRIPTION OF THE INVENTION

The present invention will be described with respect to a power source for a MIG or Gas Metal Arc Welding (GMAW) system, and with reference to a gun feeding weld wire. One skilled in the art will appreciate however, that the present invention is applicable with power sources for other types of welding systems such as stick welding and TIG welding systems, and could also be applied to other welding-type systems such as induction heaters and plasma cutters. Furthermore, the term gun as used herein is intended to include both wire feed guns and other types of welding and plasma cutting torches.

Referring now to FIG. 1, a welding power source 10 designed to supply raw power that, when conditioned, is usable for a welding-type process is shown. For MIG welding applications, power source 10 is connected to a wire feeder 28 designed to present a consumable wire electrode 33 to the weld via a MIG gun 38. The power source 10 is connected to the wire feeder 28 via a weld cable 30 and to a work piece 32 via negative weld cable 34. A clamp 36 electrically connects an end of negative weld cable 34 to the work piece 32. Gun 38 is connected to the wire feeder via a connecting plug 40, and the wire feeder 28 is connected to a connector 12 on the control panel 24 of the power source 10 through a control cable 31. A gas cylinder 44 provides shielding gas to the wire feeder for use during the welding process through gas hose 46. The wire feeder 28 can include controls 26 for controlling, for example, wire feed speed and voltage. Similar controls (not shown) can be provided on the control panel 24 of the welding power source 10. A welding helmet 50 including a protective mask and a welding glove 80 are worn by the operator, and can be in communication with any of the components in the welding system to provide feedback to the weld operator, as described below.

Referring still to FIG. 1 and now also to FIG. 8, a block diagram of the components of the welding system described above is shown. In the block diagram, position feedback devices, including weld position sensors and height sensors are shown as associated with one or more of the welding power source 10, and welding operator devices including the gun 38, glove 80, and helmet 50. The components of the system are also shown as including individual controllers and communication devices. It will be apparent to one of

5

ordinary skill, however, that all of the sensor, controller and communication devices shown here will not be necessary in all applications, and that duplicative sensors and devices can be positioned in one or more of the welding power source and associated external components. In addition, where a separate memory component is not shown below, it is assumed that a memory component is available, either as part of a controller or as a separate component in the device.

Referring now specifically to FIG. 8, the welding power source 10 includes a controller 102 for controlling a welding power supply 100 that conditions raw power for a welding-type process. The controller 102 is in further communication with a memory component 108, and a communications device 106 which can be either a wired or wireless communications system, and that communicates with at least one of the gun 38, helmet 50, and glove 80. The controller 102 can also be connected to a user interface, here shown as an input/output device 104, which can include a series of switches, a keyboard, an interactive display, or a combination of such devices. Optionally, the controller 102 controls an integrated wire feeder 28. Although, for simplicity, the wire feeder 28 is shown here as integral with the power supply 10, as described and shown above, the wire feeder 28 can be a separate component, and can include a separate controller and a communications device that can be in communications with the other components of the system. Furthermore, although the user interface 104 is shown as part of the power supply 10, the user interface could also be provided on the power source 10, wire feeder 28, gun 38, helmet 50 or in an external device in communication with any of these weld system components. Although not shown here, additional feedback devices including visual and audio alert or alarm devices, can also be provided on the welding power source, or in an external wire feeder.

Referring still to FIG. 8, weld position locator devices 82 and 84 can be coupled at opposing ends of a weld or spaced along the weld to provide linear position feedback to the operator/trainee. The weld position locator devices 82 and 84 can include, for example, transmitters 140 and 144, respectively, that transmits an RF or other signal that is read by a receiver, which can be in the gun 38 (receiver 136), in the glove 80 (receiver 114), or associated elsewhere in the system. The strength of the received signal can be used to determine at least a linear position of the weld, and to calculate a weld travel speed, as described below. The weld position locator devices 82 and 84 can include power sources 142 and 146, such as batteries, or can be connected to and powered from the welding power source 10, and also height sensors 141 and 143, although height sensing can also be determined from the transmitters 140 and 144 in some applications, and a separate sensor is not necessary. Although two weld position locator devices 82 and 84 are shown here, it will be apparent that one, or a plurality of weld position locator devices, can also be used. In particular, the number of weld locator devices can be selected based on the expected length of the weld and the strength of the transmitted signal.

Referring still to FIG. 8 and also to FIG. 1, the welding operator devices, including the welding helmet 50, glove 80, and gun 38, can be in communication with each other and with the power source 10, such that feedback regarding the weld can be transmitted to the operator/trainee during the weld, as described below. Communications between the helmet 50, glove 80, gun 38 and other components in the welding system are preferably wireless, although these devices can communicate through conventional wired com-

6

munications systems, by transmitting signals through the weld cables, or in other methods known in the art.

Referring still to FIGS. 1 and 8, the gun 38 includes a trigger 52 which, when activated, provides a signal to the wire feeder 28 to drive the consumable wire electrode to the work piece 32, and a signal to the power source 10 to activate a contactor providing welding power to the weld cables 30. The gun 38 can optionally include one or more sensors for locating the position of the gun during a weld, including an angle sensor 138, a receiver 136 for determining a linear position of the gun 38 as it moves along a weld, and a height sensor 139 to provide feedback regarding the height of the weld. The gun 38 can also include at least one stimulation device 134 for providing feedback to a weld operator or trainee. The stimulation device 134 can be driven directly by the controller 102 in the power source 10, or by a controller 132 in the gun. The gun 38 can also include a communications device 130 for communicating with the power source 10, glove 80 or other components in the system.

Referring still to FIGS. 1 and 8 and now also to FIG. 2, as described above, the gun 38 includes an angle sensor device 138 for sensing an angle of the tip of the gun 38 relative to the work piece 32, which can be provided, for example, inside the handle 56 of the gun 38, coupled to the handle 56, or closely spaced near the handle 56. The angle sensor device 138 can be, for example, a global positioning sensor, a gyroscopic sensor, a WAAS sensor, one or more accelerometers, a micro-electromechanical (MEMS) gyroscope or angular rate sensor, particularly of the type that senses motion in response to a Coriolis effect, or other devices. The gun 38 can communicate positional data to other components in the system through the connector 40, or through wireless communications as discussed above. When an angle sensor device 138 or any other weld position sensor is used, the trigger 52 can also provide a signal to acquire a "weld start" position based on data acquired from the GPS, positional network, or other sensor device, and store this position in memory in the gun 38, in the wire feeder 28, in the power source 10, or in all three locations. Alternatively, a mechanical alignment device could be provided at the start of the weld to align the gun in a "start position", which could then be stored in memory.

In another embodiment, the sensor device 138 can comprise multi-axis accelerometers which are used to determine the position of the torch and/or a glove. Multi-axis accelerometers sense angles such as the welding torch push or pull angle, and the angle of the torch with respect to the work being welded (the "torch angle"). The push, pull, and torch angles are determined and measured in multiple dimensions by comparing the orientation of the accelerometer with 'gravity vector' or acceleration due to the earth's gravity. As described above, the acquired angle data can be transmitted to other welding components in the welding system.

In an alternate embodiment, reflective material and corresponding light can be used to determine the position of the torch and the torch angle. In this application, the light used should be selected to be in a different light band that does not interfere with the welding arc to avoid interference. Another embodiment may include LEDs of various wavelengths on the gun or glove to show position independent of radiated light from the weld.

Referring still to FIGS. 2 and 8, to alert the operator to welding conditions, as described above, one or more stimulation device 134 can also be provided in the gun 38. The stimulation devices 134 can provide a pressure, vibration, or other signals to the operator. In one embodiment, a vibra-

tional motor can also be provided inside a handle of the gun **38**, or connected externally to a handle of the gun, to provide directional, tactile feedback to the operator during a weld to correct angle or motion due to vibration in an appropriate location communicating the type of correction needed. A suitable device is part number C1234B016F, available from Vibramotor.com. The position of the torch during welding can be compared to stored data, and the vibrational motor provided in or connected to the gun **38** can be activated to provide directional feedback to the operator indicating the appropriate direction to move the gun. Directional data could be provided, for example, by using a plurality of spaced vibrational motors within the gun handle, or by adjusting the frequency of the vibration to indicate different angle, directional, or travel speed changes. The intensity of the stimulation could also be correlated with a magnitude of error between a preferred or predetermined position and the actual position of the gun **38**. Here, for example, the vibration of the motor would increase with the error, vibrating a little if the angle is slightly off, and more if the angle is significantly off. Vibration may also remain until the correction occurs.

Referring still to FIG. **8**, the glove **80** can optionally include sensors for determining a position of the hand of the operator, distance from the weld, or other positional data, and a stimulation device **112** for providing feedback to the operator. A receiver **114**, for example, can be in communications with weld position locator devices **82** and **84** positioned adjacent a weld associated with work piece **32** to determine the position of the gun **38** and glove **80** along an expected weld line. The glove **80** can also include a power supply **110**, for powering the electronics associated with the glove **80**. The power supply can be, for example, a battery, a solar-powered supply that is charged by light produced by the weld, an inductive power supply, or other types of power supplies. The power can also be drawn from the welding power source **10** and through a cable tethered to the gun **38**. To provide control functions and communications to the welding power source **10** or other components in the weld system, a controller **116** or communications device **118** can also be provided in the glove **80**. The communication device **118** can, for example, transmit acquired data from the receiver **114** to the power source **10**, and receive signals from the welding power supply **10** to control the stimulation devices **112**. Although a feedback receiver **114** is shown here, it will be apparent that other types of angle sensors, height sensors, and other types of position sensors can also be incorporated in the glove **80** to provide positional feedback.

Referring again to FIGS. **1** and **8**, the stimulation devices **112** in welding glove **80** can include a vibrational motor that vibrates or applies pressure to the hand of the operator in selected locations to tell the operator to tip, push or pull the gun differently. The stimulation can alternatively come from the vibration of piezo-electric devices positioned in the glove to provide a ‘feel’ sensation, from small air bladders that are pumped up, or from an exoskeleton that can apply pressure to the operator’s hand in the glove. Although a welding glove **80** is shown here, as an alternative, the stimulation device or devices could also be provided in a wristband or in a specialized device coupled to the hand of a trainee weld operator.

Referring still to FIG. **8**, the helmet **50** can include both sensors and feedback devices for providing feedback to an operator. Sensors in the helmet **50** can include, for example, an altimeter or height sensor **128** for providing feedback regarding the position of an operator’s head while welding,

or a series of position location sensors, such as global positioning sensors (GPS) that provide three dimensional feedback as the location of the helmet **50**. Feedback can be provided to the operator using a display **54**, audio device **126**, or both. To provide communications to and from the welding power source **10** or other components in the weld system, the helmet **50** can include an internal controller **122** and a communications device **120**. Although a welding helmet is shown, it will be apparent that welding goggles or other types of shielding devices could also be used.

Referring now also to FIG. **3**, the communication device **120** in helmet **50** can receive torch angle and position feedback from the weld power source **10**, gun **38**, or glove **80** and helmet height feedback from the internal sensor **128**. Based on this feedback, the controller **122** optionally drives a heads-up display **54** and audio device **126**. The display **54** can be an LCD, LED, OLED laser projection, or other type of display, but is preferably a transparent organic light emitting diode (TOLED) display, and capable of providing graphic feedback indicating gun angle and gun travel speed feedback data to the operator. Since it is difficult to focus on a display placed close to the eyes, the display **54** can also include optics to create the appearance that the display information is projected at a work distance (typically about eighteen inches) over the welder’s view of the work area. To account for variations in operator height and head position, the helmet can be calibrated relative to the work piece to appropriately position weld feedback (such as a “ghost image” or “shadow”) on the display. Calibration may be provided through a manual input to the user interface **104** on the power source **10**, based on head height to work or automatically via height sensor **128** which can be an altimeter device or radar. Alternatively field strength from an RF transmitter or other device may determine the distance from head to work and intelligence in the control of the ghost signal will compensate from instructor to student or even from weld to weld for a given student as they move their head. During calibration, height of the helmet **50** can also be compared to height parameters associated with height sensors **139** in the gun or height sensors **141** and **143** associated with the weld position sensors **82** and **84**. Although a helmet is shown and described here, it will be apparent that welding goggles, glasses, safety glasses or other types of shields could also be used.

To provide additional feedback to the operator, the helmet **50** can also include audio generation devices **126**. For example, a headphone can be provided in the helmet, and audio feedback produced in response to the weld, or audio signals from an instructor, can be transmitted directly to the operator.

Referring again to FIG. **8**, the torch position and weld travel speed sensor devices described above can be used during actual operation of a welding power source, and also to train the welder when not welding. For example, in one embodiment of the invention, a user can choose a “training mode” of operation through user interface **104** of power source **10**. In the “training mode,” activating the trigger **52** of gun **38** activates collection of gun or torch position and weld travel speed and position data, but does not activate wire feed, a weld contactor supplying weld power to the weld cables, gas, or coolants. Positional feedback is collected, and the appropriate stimulation device can be activated to provide feedback to the operator when necessary. When the operator is sufficiently proficient with movement of the weld gun, the power source **10** can be returned to a “weld” mode. A weld operator or trainee, therefore, can get guidance from an “instructor” without the instructor’s con-

tinual presence, practice torch positioning without using expensive materials, and switch to an actual welding application when a predetermined level of proficiency is achieved.

Referring again to FIGS. 1, and 8 in one exemplary method of operation, an instructor or trainer initially performs a weld to be taught to student welders. The instructor begins by pulling the trigger 52 on gun 38, activating a weld. Upon receipt of the trigger signal, positional data is acquired from the angle sensor device 138 and position sensor devices 114 and 136 in the gun 38 or glove 80. As the instructor performs the weld, gun positional data and gun travel data is sampled or calculated at selected time periods, and stored in memory 108 of the power source 10. Other feedback data, such as voltage feedback, current feedback, wire stick out, travel speed, and wire feed speed feedback can also be saved. When the instructor is satisfied with the weld, the instructor can save these parameters as a “good weld” and activate feedback alarms for comparison to the feedback data in subsequent welds. The weld data can be stored, for example, in memory 108 of the power source 10, or elsewhere in the system, and later recalled as, for example, a weld program. Similar instructor guidance for proper motion may be saved in the simulation mode.

In alternative methods, “canned” programs could be stored in the memory 108 in the welding power source 10 or elsewhere in the weld system, and these programs could be recalled from memory by the instructor. These programs could, for example, be based on American Welding Society standards for specific weld types and joint configurations, which define gun angles, including a work angle, a push angle, and a pull or drag angle. The canned programs could, for example, be selectable between a butt weld, a tee weld, a lap joint, or other types of weld configurations for determining the position of the gun for a specific weld, specified by an operator from a user interface 104, as discussed above.

Referring now also to FIG. 9, to train a weld operator, a student welder selects a stored weld to be performed as, for example, from the user interface 104 in the welding power source 10, and retrieves weld data from memory (step 200). The operator then begins a weld by activating the trigger 52 on the gun 38 (step 202). Preferably, as described above, the student has the option of selecting a “simulated” or an “actual” weld (step 204). The “simulated” or “actual” option may be stored in memory 108 as part of the program, or be individually selected from the user interface 104. When a weld is “actual”, weld feedback data is acquired only after a weld is detected as a function of current feedback, or a combination of current and voltage feedback, as shown in FIG. 10 (steps 206 and 207).

Referring still to FIG. 9, as a weld is performed, weld feedback data is acquired (step 208) from the gun, glove, and weld position sensors described above, as well as from height sensors, to determine the position of the gun 38 or glove 80 (particularly, push, pull, and torch angles), and to determine a level of the helmet 50 as compared to the weld. Weld travel speed data can be calculated from the acquired data. Weld parameters, such as voltage, current, and wire feed speed, can also be monitored.

The acquired weld feedback data is compared to the stored data (step 210), and, when the gun position (push, pull, and torch angles), weld travel speed, or other parameters are out of a selected range (step 212), the operator receives feedback to reposition the gun or adjust the travel speed (step 214). The operator feedback can be visual or audio feedback provided through the helmet 50, or tactile feedback through the stimulation devices in the gun 38 or

glove 80, and can be continued until the trigger is dropped (step 216) and the real or simulated weld is ended. The feedback can also be associated with a selected tolerance, such that a visual, tactile, or audio alarm is activated when the feedback parameters exceed the tolerance. The selected tolerance could be a pre-determined fixed value, a percentage, or a user-adjustable parameter. Hysteresis can also be provided in the tolerance to prevent the stimulation from flickering during borderline conditions. Here, the threshold would be adjusted based on the current status of the stimulation.

As described above, the sensors, controllers, and communications devices shown in the block diagram of FIG. 8 can be provided in various components in the weld system, and the configuration of the system can be varied based on application. In one embodiment, for example, the gun 38 includes a controller 132, communications device 130, angle sensor 138, receiver 136, and height sensor 139. In operation, the controller 132 compares acquired data to an ideal or expected position, and transmits operator feedback through the communications device 130 to one or more stimulation device 112 in the glove 80. Alternatively, data can be collected from one or more of sensor 138, receiver 136, and height sensor 140, and transmitted to the welding power source communications device 106. Here, the controller 102 in welding power source 10 compares the acquired data to data stored in memory 108, and communicates instructions to a stimulation device 112 (in glove 80) or 134 (in gun 38), providing operator feedback. Various other configurations will be apparent to those of ordinary skill in the art.

Referring now to FIG. 4, in one embodiment of the invention, feedback to the user is provided through positional coordinate axes 10 on the lens of the welding helmet 50, welding goggles or glasses. These axes can be, as shown here, provided in a “bulls-eye” configuration. A series of latitudinal and longitudinal graphing lines, x/y coordinate axes or other symbols could also be used. The center of the coordinate system indicates the “desired position” of the gun. An actual location of the gun 62 can be displayed on the coordinate system. Based on this feedback, the operator can re-position the gun to an appropriate position. As described above, the height of the helmet is preferably calibrated for a specific operator, and the position of the gun or other “ghost image” provided on the display is appropriately positioned based on the height of the welder.

Referring now to FIG. 5, in another embodiment of the invention, a “ghost” or “shadow” graphic of a weld gun 64 indicating the appropriate position and travel speed of the gun 38 as viewed from the helmet 50, or, in the alternative, welding goggles or glasses, can be provided. The “shadow” allows the operator to view both the actual position of the gun, and a desired position of the gun, enabling the operator to move the gun into alignment with the shadow when adjustment is necessary. Although a representation of the gun is shown here, it will be apparent that alignment lines and other directional indicators could also be used. Furthermore, to provide proper alignment of the viewing area of the helmet, angle and position sensors can also be integrated into the helmet. Using feedback from these sensors, the relative position of the helmet with respect to the torch can be calculated to appropriately position the “shadow”.

Referring now to FIG. 6, in another embodiment of the invention, a “travel speed” indicator 66 could be provided. As shown here, the travel speed indicator 66 could be a graphical speedometer extending between a “too slow” 68 (turtle) and a “too fast” 70 (hare) icon. A marker 72

11

indicating the actual speed is provided on the graphical speedometer as a comparator for the operator. The travel speed of the gun **38** can be calculated based on feedback from a sensor device in gun **38**, as described above. A reflective material or LED type device and optical tracking, for example, can be used to determine the position and speed of the gun. Alternatively, a vector coordinate system can be used to determine the speed of the welding gun by integrating the acceleration signals coming from the multi-axis accelerometers described above. In this way the sensor can provide both angle and speed. By integrating the signal again, the torch position can be estimated in the vector coordinate system using the same sensor. Alternate methods for determining weld travel speed, are described in U.S. Pat. Nos. 4,399,346, 6,476,354, and 7,015,419, each of which are hereby incorporated by reference for their description of travel speed calculation methods. RF signal strength could also be used.

Referring now to FIGS. **7** and **7A-7D**, in an alternate embodiment of the invention, a graphical representation of a gun **74**, indicating that the gun angle is too high (FIG. **7A**), too low (FIG. **7B**), or that the push (FIG. **7C**) or pull (FIG. **7D**) angle should be adjusted can also be provided on a display **54** in the helmet **50**, goggles, or glasses. The gun icon could, for example, be provided in a corner of the lens in helmet **50** as a signal to the operator.

As described above with reference to FIGS. **3** and **8**, the helmet can also include audio generation devices for providing feedback to the operator. For example, a constant tone could be provided to the operator to indicate a change in a first direction (e.g. if the weld speed is too slow, or the angle of the weld is offset in one particular direction), and a pulsed tone to indicate an alternate change (too fast, angle offset in the opposite directions). A series of varying tones could be provided to indicate different directional changes. Words may also be used. A combination of visual and audio tones could also be used to indicate alternate directions and speeds.

Referring again to FIG. **9**, although the feedback data is described above as gun position and travel speed feedback, it will be apparent that in an actual weld setting, other weld parameters could also be monitored. For example, expected voltage, current, wire stick out, arc length and wire feed speed could be stored with the welding program and feedback related to these parameters can be monitored during an actual weld. When the parameters fall outside of predetermined values, visual, tactile stimulation, or aural feedback can be provided to the operator as described above.

Referring again to FIG. **8**, in an alternative embodiment of the invention, a weld operator can selectively choose weld feedback parameters (torch angles, torch travel speed, voltage, current, stick out, etc.) and operator feedback notification methods (tactile feedback, helmet display, audio feedback) for monitoring through the user interface **104** on the welding power source. The operator could also correlate a specific weld parameter to a feedback notification, and this correlation can be stored in memory **108** in the welding power source. The selected parameters could also be correlated with a specific operator. Other data, such as an operator identifier, operator height, and skill level can also be stored with operator preferences to simplify set-up for training.

Although specific embodiments have been shown and described, it will be apparent that a number of variations could be made within the scope of the invention. It should be understood therefore that the methods and apparatuses described above are only exemplary and do not limit the scope of the invention, and that various modifications could

12

be made by those skilled in the art that would fall under the scope of the invention. It is also contemplated that headphones or ear buds could provide audio tones, and, as discussed above, that visual feedback could be provided on goggles or glasses.

Furthermore, although a number of different types of visual, audio and tactile feedback devices are described above for various applications, it will be apparent to those of ordinary skill in the art that these devices can be used in various combinations, and on a number of peripheral devices used by welding operators. For example, the tactile feedback devices described above can be applied to the handles of torches or guns, and to welding gloves, wristbands, and other devices, either alone or in combination. Audio devices and visual devices, such as light emitting diodes, can also be provided on gloves and torches, or on helmets and goggles. Indicator devices can also be provided on other peripheral devices, including wire feeders.

Additionally, the components of a welding system as described above with reference to FIG. **8** can be provided with various levels of functionality, and the analysis components in the system can be varied. For example, in some applications, the position analysis can be provided in the welding power source, and in other applications the position analysis can be provided in peripheral components such as a welding torch, welding glove, or welding helmet. In some applications, a positional feedback sensor and communications device can be provided in a welding operator device such as a torch, gun, or glove, and the positional feedback data can be transmitted to the power source, which analyzes the data. In some applications, the position feedback can be provided in a first welding operator device, such as a wristband, and an operator feedback device, such as a visual indicator, tactile feedback device, or audio device in a second welding operator device, such as a helmet or eye goggles. Feedback position data, moreover, could be gathered from various different devices and transmitted to a central controller, such as in the power source. Various combinations can be provided.

Furthermore, although operator feedback devices have been described mainly as associated with welding operator devices such as welding torches, gloves, and helmets, it will be apparent that feedback can also be provided in a welding power source, wire feeder, or other peripheral device. Therefore, the invention should not be limited to the embodiment described. To apprise the public of the scope of this invention, the following claims are made:

We claim:

1. A welding system, comprising:

a helmet;

a display device;

a first weld position locator configured to determine position feedback of a welding torch; and

a controller configured to:

determine a position of the welding torch based on the position feedback; and

generate and output feedback of the torch position, based on the determined position of the welding torch, via the display device, wherein the feedback comprises visual feedback including both a first representation of the actual torch position of the welding torch and a second representation of a ghost or shadow version of the welding torch representative of a desired position and travel speed of the gun.

13

2. The welding system as defined in claim 1, wherein the weld position locator comprises:

a first transmitter configured to transmit a first signal; and
a first receiver configured to receive the first signal,
wherein at least one of the first transmitter or the first
receiver are positioned on the welding torch. 5

3. The welding system as defined in claim 2, wherein the controller is configured to determine the position of the welding torch based on a strength of the first signal received at the first receiver. 10

4. A welding system, comprising:

a helmet;

an audio generation device;

a first weld position locator configured to determine position feedback of a welding torch, the first weld position locator comprising: 15

a first transmitter configured to transmit a first signal;
and

a first receiver configured to receive the first signal,
wherein at least one of the first transmitter or the first
receiver are positioned on the welding torch; 20

a second weld position locator, comprising:

a second transmitter configured to transmit a second
signal; and

a second receiver configured to receive the second
signal, wherein at least one of the second transmitter
or the second receiver are positioned on the welding
torch; and

a controller configured to:

determine a position of the welding torch based on the
position feedback; and

generate and output audio feedback of the torch posi-
tion, based on the determined position of the welding
torch, via the audio generation device, wherein the
audio feedback comprises word-based feedback, 25
wherein the controller is configured to determine the
position of the welding torch based on a strength of
the second signal received at the second receiver.

5. The welding system as defined in claim 1, wherein the helmet further comprises optics configured to create an appearance that information on the display, including the graphic feedback, is projected at a work distance over a view of a work area. 30

6. A welding system, comprising:

a helmet;

an audio generation device;

a first weld position locator configured to determine position feedback of a welding torch; and

a controller configured to:

determine a position of the welding torch based on the
position feedback; and

generate and output audio feedback of the torch posi-
tion, based on the determined position of the welding
torch, via the audio generation device, wherein the 35

14

audio feedback comprises word-based feedback, wherein the helmet comprises a display, and the controller is configured to:

display visual feedback via the display based on the
determined position of the welding torch; and
calibrate the display of the graphic feedback based
on at least one of an operator height or a head
position of the operator.

7. The welding system as defined in claim 6, wherein the display is at least one of an LCD display, an LED display, or an OLED display. 10

8. The welding system as defined in claim 6, wherein the display is transparent.

9. The welding system as defined in claim 6, wherein the helmet has a viewing area and the controller is configured to display the graphic feedback over the viewing area via the display. 15

10. The welding system as defined in claim 6, wherein the weld position locator comprises an angle sensor configured to determine torch angle data, the controller configured to generate and display graphic feedback of the torch angle, based on the determined torch angle data, via the display of the helmet. 20

11. The welding system as defined in claim 6, wherein the controller is configured to generate and display the graphic feedback during a training mode of operation. 25

12. The welding system as defined in claim 6, wherein the controller is configured to generate and display the graphic feedback during a live welding operation.

13. The welding system as defined in claim 1, wherein the helmet includes the display, and the controller is configured to calibrate the display of the feedback based on at least one of an operator height or a head position of the operator. 30

14. The welding system as defined in claim 1, wherein the helmet includes the display, and the display is at least one of an LCD display, an LED display, or an OLED display. 35

15. The welding system as defined in claim 1, wherein the display is transparent.

16. The welding system as defined in claim 1, wherein the helmet has a viewing area and the controller is configured to display the feedback as graphic feedback over the viewing area via the display. 40

17. The welding system as defined in claim 1, wherein the weld position locator comprises an angle sensor configured to determine torch angle data, the controller configured to generate and display graphic feedback of the torch angle, based on the determined torch angle data, via the display. 45

18. The welding system as defined in claim 1, wherein the controller is configured to generate and display the feedback during a training mode of operation. 50

19. The welding system as defined in claim 1, wherein the controller is configured to generate and display the feedback during a live welding operation.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 11,423,800 B2
APPLICATION NO. : 16/996494
DATED : August 23, 2022
INVENTOR(S) : Todd Gerald Batzler, Bruce Patrick Albrecht and William Joshua Becker

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

On the Title Page

Page 2, Item (63):

Please delete:

“May 25, 2009”

And insert:

-- May 28, 2009 --

Signed and Sealed this
Eighteenth Day of October, 2022



Katherine Kelly Vidal
Director of the United States Patent and Trademark Office