

US011464120B2

(12) **United States Patent**
Han

(10) **Patent No.:** **US 11,464,120 B2**
(45) **Date of Patent:** ***Oct. 4, 2022**

(54) **MEMORY CARD AND MEMORY CARD SOCKET**

(71) Applicant: **Samsung Electronics Co., Ltd.**,
Suwon-si (KR)

(72) Inventor: **Seok-jae Han**, Seongnam-si (KR)

(73) Assignee: **Samsung Electronics Co., Ltd.**,
Gyeonggi-do (KR)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **17/218,232**

(22) Filed: **Mar. 31, 2021**

(65) **Prior Publication Data**

US 2021/0219441 A1 Jul. 15, 2021

Related U.S. Application Data

(63) Continuation of application No. 16/504,548, filed on
Jul. 8, 2019, now Pat. No. 10,980,138.

(30) **Foreign Application Priority Data**

Jul. 13, 2018 (KR) 10-2018-0081758

(51) **Int. Cl.**

H05K 1/18 (2006.01)

H05K 5/00 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **H05K 5/0069** (2013.01); **G06K 7/0047**
(2013.01); **H05K 1/144** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC H01L 25/043; H01L 25/0657; H01L
25/0756; H01L 25/117; H01L 21/8829;

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,376,904 B1 4/2002 Haba et al.

7,185,426 B1 * 3/2007 Hiner H01L 24/73
29/841

(Continued)

FOREIGN PATENT DOCUMENTS

JP 2004-172157 A 6/2004

Primary Examiner — Hoa C Nguyen


(74) *Attorney, Agent, or Firm* — Harness, Dickey &
Pierce, P.L.C.

(57) **ABSTRACT**

A memory card comprising a first main surface and a second
main surface opposing each other, and including a printed
circuit board (PCB) constituting the first main surface, the
PCB including a plurality of first external connection ter-
minals, the plurality of first external connection terminals
exposed on the first main surface, a plurality of memory
devices stacked on the PCB, a memory controller configured
to control the plurality of memory devices, a molding layer
encapsulating the plurality of memory devices and the
memory controller, the molding layer constituting the sec-
ond main surface, and one or more second external connec-
tion terminals electrically connected to the memory control-
ler, the one or more second external connection terminals
embedded in the molding layer and exposed by the molding
layer on the second main surface may be provided.

19 Claims, 17 Drawing Sheets

100



(51) Int. Cl. <i>G06K 7/00</i> (2006.01) <i>H05K 3/42</i> (2006.01) <i>H05K 3/40</i> (2006.01) <i>H05K 1/14</i> (2006.01)	(56) References Cited
(52) U.S. Cl. CPC <i>H05K 1/181</i> (2013.01); <i>H05K 3/4007</i> (2013.01); <i>H05K 3/425</i> (2013.01); <i>H05K</i> <i>2201/10159</i> (2013.01); <i>H05K 2201/10515</i> (2013.01)	U.S. PATENT DOCUMENTS 8,053,881 B2 11/2011 Kim et al. 8,059,421 B2 11/2011 Park 8,765,525 B2 7/2014 Yoon et al. 9,377,825 B2 6/2016 Shinohara et al. 9,514,832 B2 12/2016 Cao et al. 2008/0049392 A1 2/2008 Takiar 2008/0156884 A1 7/2008 Choi et al. 2009/0206461 A1* 8/2009 Yoon H01L 23/3128 257/737
(58) Field of Classification Search CPC H01L 21/82393; H01L 21/8221; H01L 23/4012; G06K 19/077; H05K 2201/10159; H05K 2201/10515; H05K 1/144; H05K 7/023; H05K 7/1422; H05K 7/1424; H05K 1/181 See application file for complete search history.	2009/0290274 A1 11/2009 Suenaga et al. 2010/0072593 A1 3/2010 Kim et al. 2015/0200187 A1 7/2015 Park et al. 2015/0319843 A1 11/2015 Lim et al. 2017/0278833 A1 9/2017 Park et al. 2018/0005974 A1 1/2018 Chiu et al. * cited by examiner

FIG. 1A




FIG. 1B




FIG. 2




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B




FIG. 5




FIG. 6A




FIG. 6B




FIG. 7A




FIG. 7B




FIG. 8




FIG. 9A




FIG. 9B




FIG. 10




FIG. 11A




FIG. 11B




FIG. 11C




FIG. 11D





FIG. 11E



1

**MEMORY CARD AND MEMORY CARD
SOCKET****CROSS-REFERENCE TO RELATED
APPLICATION**

This application is a continuation of U.S. application Ser. No. 16/504,548, filed on Jul. 8, 2019, which claims priority under 35 U.S.C. § 119 to Korean Patent Application No. 10-2018-0081758, filed on Jul. 13, 2018, in the Korean Intellectual Property Office, the disclosure of each of which is incorporated herein in its entirety by reference.

BACKGROUND

The inventive concepts relate to memory cards and/or memory card sockets, and more particularly, to memory cards operating at a high speed and having improved reliability and stability, and/or to memory card sockets accommodating the same.

Memory cards have become useful devices for conveniently storing and moving a large amount of information. There is a need for memory cards which not only perform high-speed input/output operations of processing a large amount of information, but also provide improved stability and reliability without errors in input/output operations of processing data. Further, manufacturing methods capable of easily and stably manufacturing such memory cards is desired.

SUMMARY

The inventive concepts provide memory cards having improved reliability and stability while operating at a high speed.

The inventive concepts provide memory card sockets capable of accommodating the memory card.

The inventive concepts provide electronic systems including the memory card socket.

According to an example embodiment of the inventive concepts, a memory card comprising a first main surface and a second main surface opposing each other includes a printed circuit board (PCB) establishing the first main surface, the PCB including a plurality of first external connection terminals, the plurality of first external connection terminals exposed on the first main surface, a plurality of memory devices stacked on the PCB, a memory controller configured to control the plurality of memory devices, a molding layer encapsulating the plurality of memory devices and the memory controller, the molding layer establishing the second main surface, and one or more second external connection terminals electrically connected to the memory controller, the one or more second external connection terminals embedded in the molding layer and exposed by the molding layer at the second main surface.

According to an example embodiment of the inventive concepts, a memory card includes a printed circuit board (PCB) including a plurality of first external connection terminals, the plurality of first external connection terminals configured to be connected to an external device, a plurality of memory devices stacked on the PCB, a memory controller on an uppermost memory device among the plurality of memory devices, an interposer on the uppermost memory device, one or more second external connection terminals on the interposer, the one or more second external connection terminals configured to be connected to the external device,

2

and a molding layer encapsulating the plurality of memory devices and the memory controller.

According to an example embodiment of the inventive concepts, a memory card socket configured to accommodate a memory card that including a first main surface and a second main surface opposing each other includes first external connection terminals configured to contact the first main surface, the first external connection terminals including at least one power supply terminal from among power supply terminals configured to provide power supply in a range between about 3.3V and about 1.8V, second external connection terminals configured to contact the second main surface, the second external connection terminals including one or more of (i) a power supply terminal of about 1.2 V or less, (ii) a pair of data input/output terminals, or (iii) a set of data input/output terminals having a one-lane structure in which a set of data input terminals and a set of data output terminals each comprise a differential signal pair, and a housing configured to accommodate the first external connection terminals and the second external connection terminals, the housing configured to accommodate the memory card

According to an example embodiment of the inventive concepts, an electronic system includes a controller, an input/output device configured to input or output data, a memory device configured to store data, the memory device including the aforementioned memory card socket, an interface configured to transmit data to an external device, and a bus configured to connect the controller, the input/output device, the memory device, and the interface for communications therebetween.

BRIEF DESCRIPTION OF THE DRAWINGS

Example embodiments of the inventive concepts will be more clearly understood from the following detailed description taken in conjunction with the accompanying drawings in which:

FIG. 1A is a plan view illustrating a first main surface of a memory card according to an example embodiment;

FIG. 1B is a plan view illustrating a second main surface of a memory card according to an example embodiment;

FIG. 2 is a cross-sectional view illustrating a cross-section taken along line II-IT in FIG. 1B;

FIG. 3A is a plan view illustrating a second main surface of a memory card according to an example embodiment;

FIG. 3B is a cross-sectional view illustrating a cross-section taken along line IIIB-IIIB' in FIG. 3A;

FIG. 4A is a plan view illustrating a second main surface of a memory card according to an example embodiment;

FIG. 4B is a cross-sectional view illustrating a cross-section taken along line IVB-IVB' in FIG. 4A;

FIG. 5 is a cross-sectional view illustrating a memory card according to an example embodiment;

FIGS. 6A and 6B are plan views illustrating a first main surface and a second main surface of a memory card, respectively, according to an example embodiment;

FIGS. 7A and 7B are schematic plan views illustrating second main surfaces of memory cards, respectively, according to some example embodiments;

FIG. 8 is a schematic diagram of a system including a memory socket configured to accommodate a memory card, according to an example embodiment;

FIG. 9A is a schematic diagram illustrating the memory card socket of FIG. 8 in more detail in consideration of an electrical connection to a memory card;

3

FIG. 9B is a side view schematically illustrating a state in which the memory card socket and the memory card of FIG. 9A are connected to each other;

FIG. 10 is a block diagram of an example of an electronic system including a memory card, according to an example embodiment; and

FIGS. 11A through 11E are cross-sectional views sequentially illustrating a method of manufacturing a memory card, according to an example embodiment.

DETAILED DESCRIPTION

While the term “same” is used in description of example embodiments, it should be understood that some imprecisions may exist. Thus, when one element is referred to as being the same as another element, it should be understood that the one element is the same as another element within a desired manufacturing tolerance range (e.g., $\pm 10\%$).

When the terms “about,” “approximately,” or “substantially” are used in this specification in connection with a numerical value, it is intended that the associated numerical value include a manufacturing tolerance (e.g., $\pm 10\%$) around the stated numerical value. Moreover, when the words “generally” and “substantially” are used in connection with geometric shapes, it is intended that precision of the geometric shape is not required but that latitude for the shape is within the scope of the disclosure.

Hereinafter, some example embodiments of the inventive concepts will be described in detail with reference to the accompanying drawings.

FIG. 1A is a plan view illustrating a first main surface 110 of a memory card 100 according to an example embodiment. FIG. 1B is a plan view illustrating a second main surface 112 of the memory card 100 according to an example embodiment. FIG. 2 is a cross-sectional view illustrating a section taken along the line II-II' in FIG. 1B.

Referring to FIGS. 1A, 1B, and 2, the memory card 100 may include the first main surface 110 and the second main surface 112 opposing each other. Here, a ‘main surface’ may denote each of two opposing surfaces extending to have the largest area among respective surfaces of the memory card 100.

The first main surface 110 may be one main surface of a substrate 101 (e.g., a printed circuit board (PCB)). On the substrate 101, a plurality of memory devices 194 and a memory controller 192 configured to control the plurality of memory devices 194 may be provided. Further, first external connection terminals (which include a first row terminal (or first row terminals) 130 and a second row terminal (or second row terminals) 140) may be provided on (while being exposed outwardly at) the first main surface 110.

The second main surface 112 may be defined by a molding layer 162 surrounding the memory controller 192 and the plurality of memory devices 194. Second external connection terminals 150 connectable to external devices may be provided on (while being exposed outwardly at) the second main surface 112.

The plurality of memory devices 194 may include, for example, NAND flash memory devices. The plurality of memory devices 194 may be stacked to be offset from each other in any one direction. In the present example embodiment, the plurality of memory devices 194 are illustrated to include four memory devices (e.g., a first memory device 194a, a second memory device 194b, a third memory device 194c, and a fourth memory device 194d). However, the inventive concepts are not limited thereto.

4

The memory controller 192 may be provided on the first memory device 194a, which is an uppermost one of the plurality of memory devices 194. The memory controller 192 may be configured to control the memory devices 194. The memory controller 192 may be electrically connected to the first external connection terminals (130 and 140) exposed outwardly at the first main surface. Further, the memory controller 192 may be electrically connected to the second external connection terminal 150 exposed outwardly at the second main surface 112. In some example embodiments, the memory controller 192 may be electrically connected to the substrate 101 via bonding wires, and further electrically connected to the first external connection terminals (130 and 140) via wirings (not shown) provided in the substrate 101.

In some example embodiments, an interposer 180 may be provided on the first memory device 194a, which is the uppermost one of the plurality of memory devices 194. The interposer 180 may be provided in a lateral direction with respect to the memory controller 192. In other words, the interposer 180 may be spaced apart from the memory controller 192 in a lateral direction. In some example embodiments, the interposer 180 may be attached directly onto the first memory device 194a. In some embodiments, the memory controller 192 may be attached directly onto the first memory device 194a. The interposer 180 and the memory controller 192 may be attached directly onto the first memory device 194a by using, for example, a die attach film (DAF), an adhesive, or a non-conductive film (NCF).

The interposer 180 may include an interposer substrate and a conductor line 182 and interposer terminals (not shown) provided thereon. The interposer substrate may include an insulator substrate (e.g., a silicon substrate or a glass substrate). The conductor line 182 may include a wire of gold (Au), aluminum (Al), and/or copper (Cu), and may include an embossed or damascened wire.

The second external connection terminals 150 may be electrically connected to the conductor line 182 on the interposer 180 via a conductor via CV. The conductor via CV may include one of copper (Cu), tungsten (W), titanium (Ti), tantalum (Ta), tin (Sn), Au, Al, nickel (Ni), cobalt (Co), or an alloy thereof. In some example embodiments, the conductor via CV may be formed integrally with the second external connection terminal 150. In some example embodiments, there may be an interface between the conductor via CV and the second external connection terminal 150.

In some example embodiments, the conductor via CV may extend in a direction substantially perpendicular (e.g., vertical) to the first main surface 110 and/or the second main surface 112.

Side surfaces of the second external connection terminals 150 may be surrounded by the molding layer 162. Top surfaces of the second external connection terminals 150 may be at least partially exposed by the molding layer 162. Portions of bottom surfaces of the second external connection terminals 150 that are not in contact with the conductor via CV may be covered by the molding layer 162.

In FIG. 1B, the second external connection terminals 150 are illustrated to include three terminals 151, 153, and 154, but the inventive concepts are not limited thereto. The second external connection terminal 150 may include one or two terminals, or four or more terminals.

In some embodiments, the second external connection terminals 150 may include a power supply terminal having a voltage of about 1.2 V or less (e.g., a voltage of about 1.2 V or a voltage of about 0.4 V) as a supply voltage. In some example embodiments, the second external connection ter-

5

minals **150** may include a ground terminal. In some example embodiments, the second external connection terminals **150** may include at least a pair of data input/output terminals.

The memory controller **192** may be electrically connected to the conductor line **182** on the interposer **180** via a bonding wire BW. In other words, the memory controller **192** may be electrically connected to the second external connection terminal **150** via the conductor line **182** provided on the interposer **180**.

The conductor line **182** on a top surface of the interposer **180** may not be electrically connected to active elements such as semiconductor devices (including, but not limited to, transistors, diodes, and operational amplifiers), and inactive elements (including, but not limited to, resistors, inductors, and capacitors), all of which are provided in the first memory device **194a**. Accordingly, the conductor line **182** may not be directly related to an operation of the first memory device **194a**, and may be directly related to signal transceiving and/or power supply between the memory controller **192** and the second external connection terminal **150**.

The memory card **100** may have two pairs of opposing edges (or alternatively, sides). The two pairs of opposing edges may include an insertion side edge **121** in a direction in which the memory card **100** is inserted into a memory card socket, a second edge **127** opposing the insertion side edge **121**. The insertion side edge **121** and the third edge **127** may be parallel to each other. The memory card **100** also includes a second edge **123** connecting an end of the insertion side edge **121** and an end of the second edge **127** and a third edge **125** connecting an opposite second end of the insertion side edge **121** and an opposite end of the second edge **127**.

The third edge **125** may extend in a direction substantially perpendicular (e.g., vertical) to a direction in which the insertion side edge **121** extends. In the present example embodiment, the third edge **125** is illustrated to extend only in one direction, and the first edge **123** is illustrated to include both a portion parallel to the third edge **125** and a portion not parallel to the third edge **125**.

Between each of the edges (**121**, **123**, **125**, and **127**), there may be one or more corners **128** having a certain radius of curvature. In some example embodiments, the edges (**121**, **123**, **125**, and **127**) may have the same radius of curvature.

The insertion side edge **121** may be an edge of the memory card socket into which the memory card **100** is inserted. When the memory card **100** is inserted into the memory card socket, the insertion side edge **121** may be inserted first among the edges (**121**, **123**, **135**, and **127**), and when the memory card **100** is released from the memory card socket, the insertion side edge **121** may be released last among the edges (**121**, **123**, **135**, and **127**). A width of the insertion side edge **121** may be determined in consideration of a certain clearance space such that the memory card **100** smoothly enters the memory card socket.

Terminals may be arranged adjacent to the insertion side edge **121** for electrically connecting the semiconductor devices in the memory card **100** to a host. The host may be, for example, a mobile phone, a desktop computer, a notebook computer, a tablet personal computer (PC), a game machine, a navigation device, and a digital camera, but the inventive concepts are not limited thereto. In some example embodiments, an adapter for interfacing may be arranged between the memory card **100** and the host.

The first external connection terminals (**130** and **140**) may be arranged in two rows on the first main surface **110** as illustrated in FIG. 1A. In other words, a plurality of first row

6

terminals **130** and a plurality of second row terminals **140** may be arranged adjacent to the insertion side edge **121** of the substrate **101**.

The first row terminals **130** may include the power supply terminal **131** configured to provide a first voltage as a supply voltage, and the first voltage may have a value between about 3.0 V and about 3.5 V (e.g., about 3.3 V). The first voltage may be supplied to the semiconductor devices operating at a relatively low speed among the semiconductor devices in the memory card **100**. For example, the first voltage may be supplied to the memory devices **194** in the memory card **100**. The memory devices **194** may be non-volatile memory devices.

The second row terminals **140** may include a power supply terminal **141** configured to provide a second voltage as a supply voltage, and the second voltage may have a value between about 1.5 V and about 2.2 V (e.g., about 1.8 V). The second voltage may be supplied to the semiconductor devices operating at a relatively high speed among the semiconductor devices in the memory card **100**. For example, the second voltage may be supplied to the memory controller **192** in the memory card **100**.

The first row terminals **130** may be arranged closer to the insertion side edge **121** compared with the second row terminals **140**. In other words, the second row terminals **140** may be arranged farther apart from the insertion side edge **121** compared with the first row terminals **130**.

In FIG. 1A, two of the first row terminals **130** and ten of the second row terminals **140** are illustrated, but the numbers, positions, shapes, and sizes of the first and second row terminals **130** and **140** are not limited thereto. In some example embodiments, some terminals of the first and second row terminals **130** and **140** may be covered by a solder resist (SR) layer, and thus may not be exposed to the outside. The unexposed some terminals may be, for example, test terminals.

The first row terminals **130** and the second row terminals **140** each may include one or more ground terminals. For example, the first row terminals **130** may include a ground terminal **133**. Further, the second row terminals **140** may include ground terminals **144**.

The second row terminals **140** may include a pair of data input terminals **145in** and a pair of data output terminals **145out**. Although the data input terminals **145in** are illustrated to be arranged closer to the center of the memory card **100** compared with the pair of data output terminals **145out** in FIG. 1A, arrangements thereof may be changed.

The pair of data input terminals **145in** may constitute a pair of differential signals, and the pair of data output terminals **145out** may also constitute a pair of differential signals. The pair of data input terminals **145in** and the pair of data output terminals **145out** using the pair of differential signals may be relatively insensitive to noise or interference, thereby enabling stable transmission of high-speed data. The pair of data input terminals **145in** and the pair of data output terminals **145out** may constitute data input/output terminals of a one-lane structure.

The data input terminals **145in** may be electrically shielded by a pair of ground terminals **144a** and **144b**. Further, the data output terminals **145out** may be electrically shielded by a pair of ground terminals **144b** and **144c**. The pair of data input terminals **145in** and the pair of data output terminals **145out** may more reliably input and output data due to the shields, respectively.

The pair of data input terminals **145in** may have the same dimension. Further, the pair of data output terminals **145out**

may have the same dimension. Further, the data input terminals **145_{in}** and the data output terminals **145_{out}** may have the same dimension.

The second row terminals **140** may further include a card detection terminal **143** and a reference clock terminal **147**.

The first external connection terminals (**130** and **140**) may include an external connection terminal according to one standard of a secure digital (SD) card, a micro SD card, a mini SD card, a universal flash storage (UFS) card, or a multimedia card (MMC).

In a side direction of the second row terminals **140**, a lateral protrusion that looks like a shark's fin may be provided. A passive element **170** may be provided in the lateral protrusion. The passive element **170** may include one or more of a resistor, a capacitor, an inductor, a thermistor, an oscillator, a ferrite bead, an antenna, a varistor, and/or a crystal. However, example embodiments of the present inventive concepts are not limited thereto. According to some example embodiments, the lateral protrusion may include any other passive element(s).

The memory card **100** may further include a withdrawal assisting portion **160** at the second main surface **112**. The withdrawal assisting portion **160** may allow easy withdrawal of the memory card **100** from a memory card socket after the memory card **100** has been inserted into the socket. The withdrawal assisting portion **160** may be protruded from the second main surface **112** of the memory card **100**. Further, the withdrawal assisting portion **160** may be formed adjacent to the second edge **127**.

FIG. 3A is a plan view illustrating the second main surface **112** of a memory card **100a** according to an example embodiment. FIG. 3B is a cross-sectional view illustrating a section taken along the line IIIB-IIIB' in FIG. 3A.

The embodiment illustrated in FIGS. 3A and 3B differs from the example embodiment illustrated in FIGS. 1A and 2 in that the memory controller **192** is arranged on the interposer **180a**. Thus, duplicate descriptions are omitted and the following descriptions focus on differences.

Referring to FIGS. 3A and 3B, the interposer **180a** may be arranged directly on the first memory device **194a**. In some example embodiments, the interposer **180a** may be attached directly onto the first memory device **194a** by using a die attach film, an adhesive, or a nonconductive film.

Further, the memory controller **192** may be arranged directly on the interposer **180a**. The memory controller **192** may be attached directly onto the interposer **180a** by using a die attach film, an adhesive, or a nonconductive film. The conductor line **182** may be provided on the interposer **180a** (e.g., on a portion of a top surface of the interposer **180a**), and the memory controller **192** may be electrically connected directly to the conductor line **182** via the bonding wire BW. Here, the fact that the conductor line **182** and the memory controller **192** are electrically connected directly to each other may denote that no other electrical element except for an element dedicated to flow current therethrough is arranged between the conductor line **182** and the memory controller **192**.

The conductor line **182** may be connected to the conductor via CV, and the conductor via CV may be connected to the second external connection terminal **150**. In other words, the memory controller **192** may be connected to the second external connection terminal **150** via the bonding wire BW, the conductor line **182**, and the conductor via CV.

The conductor line **182** on the top surface of the interposer **180a** may not be electrically connected to active elements such as semiconductor devices (including, but not limited to, transistors, diodes, and operational amplifiers), and inactive

elements (including, but not limited to, resistors, inductors, and capacitors), all of which are provided in the first memory device **194a**. Accordingly, the conductor line **182** may not be directly related to an operation of the first memory device **194a** and may be directly related to signal transceiving and/or power supply between the memory controller **192** and the second external connection terminal **150**.

A plane area of the memory controller **192** may be sufficiently less than that of the interposer **180a**.

FIG. 4A is a plan view illustrating the second main surface **112** of a memory card **100b** according to an example embodiment. FIG. 4B is a cross-sectional view illustrating a section taken along the line IVB-IVB' in FIG. 4A.

The example embodiment illustrated in FIGS. 4A and 4B differs from the example embodiment illustrated in FIGS. 1A through 2 in that the interposer **180** is omitted. Thus, duplicate descriptions are omitted and the following descriptions focus on differences.

Referring to FIGS. 4A and 4B, a conductor line (or a plurality of conductive lines) **182a** may be provided on the first memory device **194a** (e.g., on a top surface of the first memory device **194a**).

In some example embodiments, the conductor lines **182a** may be provided on a top surface of each of the first memory device **194a**, the second memory device **194b**, the third memory device **194c**, and the fourth memory device **194d**. In this case, the conductor lines **182a** on the top surfaces of the second memory device **194b**, the third memory device **194c**, and the fourth memory device **194d** may be dummy conductor lines which do not participate in the operation of the memory card **100b**.

The conductor vias CV that are connected to the second external connection terminals **150** (which includes terminals **151**, **153**, and **154**), respectively, may be connected directly to the conductor lines **182a**, respectively. The conductor vias CV may extend in a direction vertical or substantially perpendicular to the second main surface **112**.

One or more of the conductor lines **182a** may be electrically connected to the memory controller **192** via the bonding wire BW. In other words, the conductor line **182a** may be electrically and directly connected to the memory controller **192**. Here, the fact that the conductor line **182a** and the memory controller **192** are electrically and directly connected to each other may denote that no other electrical element except for an element dedicated to flow current therethrough is arranged between the conductor line **182a** and the memory controller **192**.

Accordingly, the memory controller **192** may be electrically connected to one or more the second external connection terminals **150** via the bonding wire(s) BW, the conductor line(s) **182a**, and the conductor via(s) CV.

One or more of the conductor lines **182a** on a top surface of the first memory device **194a** may not be electrically connected to active elements such as semiconductor devices (including, but not limited to, transistors, diodes, and operational amplifiers), and inactive elements (including, but not limited to, resistors, inductors, and capacitors), all of which are provided in the first memory device **194a**. Accordingly, one or more of the conductor line **182a** may not be directly related to an operation of the first memory device **194a**, and may be directly related to signal transceiving and/or power supply between the memory controller **192** and the second external connection terminal **150**.

The top surface of the first memory device **194a** may be passivated, and the conductor line(s) **182a** may be provided in or on a passivation layer.

FIG. 5 is a cross-sectional view illustrating a memory card **100c** according to an example embodiment.

The memory card **100c** of FIG. 5 may be different from the memory cards **100**, **100a**, or **100b** of FIGS. 1A-4B in that, instead of a plurality of memory devices **194** being offset to each other and being interconnected to each other via the bonding wires BW, a plurality of memory devices **195** may be laminated without forming an offset to each other. Thus, duplicate descriptions are omitted and the following descriptions focus on differences.

Referring to FIG. 5, the plurality of memory devices **195** may include a first memory device **195a**, a second memory device **195b**, a third memory device **195c**, and a fourth memory device **195d**. Although this example illustrates the plurality of memory devices **195** to include four memory devices (**195a**, **195b**, **195c**, and **195d**), the inventive concepts are not limited thereto.

The memory controller **192** and the interposer **180** may be provided on the first memory device **195a**, which is the uppermost one of the plurality of memory devices **195**. FIG. 5 illustrates an example in which the interposer **180** is arranged in a lateral direction of the memory controller **192**. In other words, FIG. 5 illustrates an example in which the interposer **180** is laterally spaced apart from the memory controller **192**. However, it may be understood by those of ordinary skill in the art that it is possible to arrange the memory controller **192** on a top of the interposer **180** on the first memory device **195a**, as illustrated in FIGS. 3A and 3B.

FIGS. 6A and 6B are plan views illustrating the first main surface **110** and the second main surface **112** of a memory card **100d**, respectively, according to an example embodiment.

Referring to FIGS. 6A and 6B, as described above, the first external connection terminals (**130** and **140**) provided on the first main surface **110** may include the pair of first data input terminals **145in** and the pair of first data output terminals **145out**. The pair of first data input terminals **145in** and the pair of first data output terminals **145out** each may constitute a pair of differential signals.

Signals input through the pair of first data input terminals **145in** may be transmitted to the memory controller **192** via a first signal input path **261in**. Further, a signal output from the memory controller **192** may be transmitted to the pair of first data output terminals **145out** via a first signal output path **261out**. As described above with reference to FIG. 1A, the pair of first data input terminals **145in** and the pair of first data output terminals **145out** may constitute the first data input/output terminals of a one-lane structure.

The second external connection terminals **150** provided on the second main surface **112** may include a pair of second data input terminals **155in** and a pair of second data output terminals **155out**. Although the pair of second data input terminals **155in** are illustrated to be arranged to the right side of the pair of second data output terminals **155out** in FIG. 6B, their positions may be mutually exchanged.

The second data input terminals **155in** may be electrically shielded by a pair of ground terminals **244a** and **244b**. Further, the second data output terminals **155out** may be electrically shielded by a pair of ground terminals **244b** and **244c**. The pair of second data input terminals **155in** and the pair of second data output terminals **155out** may more reliably input and output data due to the shields, respectively.

The pair of second data input terminals **155in** may constitute a pair of differential signals, and the pair of second data output terminals **155out** may also constitute a pair of differential signals. Signals input through the pair of second

data input terminals **155in** may be transmitted to the memory controller **192** via a second signal input path **263in**. Further, a signal output from the memory controller **192** may be transmitted to the pair of second data output terminals **155out** via a second signal output path **263out**.

The pair of second data input terminals **155in** and the pair of second data output terminals **155out** may constitute the second data input/output terminals of a one-lane structure.

Accordingly, the pair of data input terminals **155in** and the pair of data output terminals **155out** on the second main surface **112**, and the pair of data input terminals **145in** and the pair of data output terminals **145out** on the first main surface **110** may constitute a set of data input/output terminals of two-lane structure when viewed in a plan view. Because the number of paths through which data is input/output is doubled, a data input/output speed may be theoretically doubled.

Such an arrangement of terminals (e.g., the second data input/output terminals and ground terminals used for an operation of a memory card) on the second main surface **112** may allow a higher degree of freedom for a design of wire-routing in the substrate **101**, and thus, a memory card having higher reliability and stability may be obtained.

FIG. 7A is a plan view illustrating the second main surface **112** of a memory card **100e** according to an example embodiment. FIG. 7A is the same as FIG. 1B except that a capacitor **184a** is connected to the conductor line **182**. Thus, duplicate descriptions are omitted and the following descriptions focus on differences.

Referring to FIG. 7A, the capacitor **184a** may be further provided on the interposer **180**. The capacitor **184a** may be connected to the conductor line **182** which is connected to any one (e.g., the terminal **154**) of the second external connection terminals **150**. When the terminal **154** is a power supply terminal (e.g., a terminal supplying a voltage of about 1.2 V, about 0.4 V, or about 0.2 V) as a supply voltage, it may be helpful to improve the electrical characteristics of the memory card **100e** may be improved by connecting the terminal **154** to a capacitor. The capacitor **184a** may be mounted on the interposer **180** and may be electrically connected to the terminal **154**.

One end of the capacitor **184a** may be connected to a conductor line **182** that is connected to the terminal **154**. Further, the other end of the capacitor **184a** may be grounded.

The capacitor **184a** may be a separate element that is mounted on the interposer **180** or may be an element embedded within the interposer **180** formed while embedding the conductor line **182** in the interposer **180**.

FIG. 7B is a plan view illustrating the second main surface **112** of a memory card **100f** according to an example embodiment.

The memory card **100f** of FIG. 7B differs from the memory card **100e** of FIG. 7A in that a capacitor **184b** is provided in an area other than the interposer **180**. Thus, duplicate descriptions are omitted and the following descriptions focus on differences.

Referring to FIG. 7B, the capacitor **184b** may be provided at a position outside the interposer **180** (e.g., directly on the substrate **101** (refer to FIG. 2)). In some example embodiments, the capacitor **184b** may be the passive element **170** as illustrated in FIG. 2.

According to the inventive concepts, memory cards having improved reliability and stability while operating at a relatively high speed and memory card sockets capable of accommodating the memory card may be obtained.

11

According to the example embodiments, memory cards may include external connection terminals on a first main surface as well as a second main surface. Thus, a degree of freedom of wire-routing of the PCB of the memory card may be improved, and thus, memory cards having improved reliability and stability may be obtained.

Further, the data input/output speed may be improved by providing the second external connection terminals arranged on the second main surface and arranged to have a one-lane arrangement.

FIG. 8 is a schematic diagram of a system 200 including a memory socket 220 configured to accommodate the memory card 100 according to an example embodiment.

Referring to FIG. 8, the system 200 may include the memory card socket 220, the memory card 100 described with reference to the above example embodiments, a card interface controller 230, and a host (or an external device) 240. The memory card socket 220 may be configured to accommodate insertion and contact of the memory card 100. The memory card socket 220 may be configured to be electrically connected to, for example, the first external connection terminals (that is, the first row terminals 130 and the second row terminals 140) and the second external connection terminals 150 of the memory cards 100, 100a, 100b, 100c, 100d, 100e, or 100f illustrated in FIGS. 1A through 6B. The card interface controller 230 may control data exchange with the memory card 100 via the memory card socket 220. The card interface controller 230 may also be used to store data in the memory card 100. The host 240 may control the card interface controller 230.

FIG. 9A is a schematic diagram of the memory card socket 220 in FIG. 8 in more detail in consideration of an electrical connection to the memory card 100. FIG. 9B is a side view schematically illustrating a state in which the memory card socket 220 and the memory card 100 are connected to each other.

Referring to FIGS. 9A and 9B, the memory card socket 220 is configured to accommodate the above-described memory card 100, 100a, 100b, 100c, 100d, 100e, or 100f. A portion indicated by 220A in FIG. 9A may illustrate a bottom portion of the memory card socket 220 and pins which contact a bottom surface of the memory card 100, and a portion indicated by 220B may illustrate a top portion of the memory card socket 220 and pins which contact a top surface of the memory card 100.

The memory card socket 220 may include first row corresponding socket terminals 221a corresponding to the first row terminals 130 of the memory card 100, 100a, 100b, 100c, 100d, 100e, or 100f, second row corresponding socket terminals 221b corresponding to the second row terminals 140 of the memory card 100, 100a, 100b, 100c, 100d, 100e, or 100f, the memory cards 100, 100a, 100b, third row corresponding socket terminals 221c corresponding to the second external connection terminals 150 of the memory card 100, 100a, 100b, 100c, 100d, 100e, or 100f, and a housing capable of accommodating the socket terminals (221a, 221b, and 221c).

The memory card 100, 100a, 100b, 100c, 100d, 100e, or 100f may operate by being inserted into the housing 223 to contact the first row corresponding socket terminals 221a, the second row corresponding socket terminals 221b, and the third row corresponding socket terminals 221c.

As described above with reference to FIG. 8, the memory card socket 220 may be electrically connected to a card interface controller 230 which is configured to control inputting/outputting of power, signals, and/or data to/from the first row corresponding socket terminals 221a, the sec-

12

ond row corresponding socket terminals 221b, and the third row corresponding socket terminals 221c.

Among the first row corresponding socket terminals 221a, the second row corresponding socket terminals 221b, and the third row corresponding socket terminals 221c, there may be a socket terminal which is configured to identify the inserted memory card 100, 100a, 100b, 100c, 100d, 100e, or 100f as first-type card when a particular terminal corresponding to the inserted memory cards 100, 100a, 100b, 100c, 100d, 100e, or 100f is a ground terminal, and identify the inserted memory card 100, 100a, 100b, 100c, 100d, 100e, or 100f as second-type card when the particular terminal is not a ground terminal.

Although the first row terminals 130 of the memory card 100, 100a, 100b, 100c, 100d, 100e, or 100f illustrated in the embodiments are two, more than three socket terminals may be provided such that the first row corresponding socket terminals 221a recognize and use the second-type memory cards. In some example embodiments, the number of socket terminals may be greater than the number of the second row terminals 140 and/or the number of the second external connection terminals 150 such that the second row corresponding socket terminals 221b and/or the third row corresponding socket terminals 221c may recognize and use different types of memory cards. It will be understood by those of ordinary skill in the art that the memory card socket according to example embodiments of the inventive concepts are not limited to the numbers of socket terminals illustrated in FIGS. 9A and 9B.

FIG. 10 is a block diagram of an example of an electronic system 4100 including a memory card according to an example embodiment of the inventive concepts.

Referring to FIG. 10, the electronic system 4100 according to an example embodiment may include a controller 4110, an input/output (I/O) device 4120, a memory device 4130, an interface 4140, and a bus 4150. The controller 4110, the I/O device 4120, the memory device 4130, and/or the interface 4140 may be connected to each other via the bus 4150. The bus 4150 may correspond to a path through which data is moved.

The controller 4110 may include at least one of a microprocessor, a digital signal process, a microcontroller, and/or logic elements capable of performing similar functions. The I/O device 4120 may include a keypad, a keyboard, a display device, etc. The memory device 4130 may store data and/or commands, etc. The memory device 4130 may include at least one of the memory cards disclosed in the example embodiments described above. The memory device 4130 may include the memory card socket 220 described with reference to FIGS. 8, 9A, and 9B. In addition, the memory device 4130 may further include other types of semiconductor memory devices (for example, nonvolatile memory devices and/or static random-access memory (RAM) (SRAM) devices). The interface 4140 may transmit data to or receive data from a communication network. The interface 4140 may be in a wired or wireless form. For example, the interface 4140 may include an antenna, or a wired or wireless transceiver, etc. Although not illustrated, the electronic system 4100 may include an operation memory element for improving an operation of the controller 4110 and may further include a high-speed dynamic RAM (DRAM) device, and/or an SRAM device, etc.

The electronic system 4100 may be applied to a cellular phone, a desktop computer, a notebook computer, a tablet personal computer (PC), a game machine, a navigation device, a digital camera, a personal digital assistant (PDA),

13

a wireless phone, digital music player, or any electronic product capable of transmitting and/or receiving information in a wireless environment.

FIG. 11A through 11E are cross-sectional views sequentially illustrating a method of manufacturing the memory card 100 according to an example embodiment. Particularly, the cross-sectional views of FIGS. 11A through 11E may be cross-sectional views along line II-II' in FIG. 1B.

Referring to FIG. 11A, the memory device 194 may be mounted on the substrate 101.

For example, the substrate 101 may be a PCB. The memory device 194 may be mounted on a top surface of the substrate 101, and a first row terminal 130 and a second row terminal 140 may be arranged on a bottom surface of the substrate that is opposite to the top surface thereof. The memory devices 194 may include a plurality of memory devices (e.g., the first memory device 194a, the second memory device 194b, the third memory device 194c, and the fourth memory device 194d). The memory devices 194 may be mounted on the substrate 101 by using a die attach film, an adhesive, or a nonconductive film, etc. Further, the memory devices 194 may be electrically connected to the substrate 101 via the bonding wire(s) BW.

The memory controller 192 may be arranged on the first memory device 194a (e.g., the uppermost one of the memory devices 194). Further, the interposer 180 may be arranged on the first memory device 194a. The memory devices 194, the memory controller 192, and the interposer 180 have been described in detail with reference to FIGS. 1A through 2, and thus detailed descriptions thereof are omitted here.

In some example embodiments, the memory controller 192 and the interposer 180 may be electrically connected to each other by using bonding wire(s) BW. In some example embodiments, the memory controller 192 may be electrically connected to the substrate 101 by using the bonding wire(s) BW. However, the bonding wire(s) BW may interfere with a film subsequently laminated thereon. In FIG. 11A, first bonding wires including bonding wires BW between the plurality of memory devices 194 and a bonding wire BW between the fourth memory device 194d and the substrate 101 are formed. The remaining bonding wire(s) may be formed later. However, the inventive concepts are not limited thereto.

Further, although the interposer 180 and the memory controller 192 are illustrated to be arranged side by side in FIG. 11A, the memory controller 192 may be mounted on the interposer 180 (e.g., on a top surface of the interposer 180) as illustrated in FIGS. 3A and 3B. Further, the memory controller 192 may be arranged such that the memory controller 192 is connected to the conductor line 182a formed on the first memory device 194a (e.g., on the top surface of the first memory device 194a), without providing the interposer 180.

Referring to FIG. 11B, a photosensitive film F may be attached to the top surfaces of the memory controller 192 and the interposer 180.

An adhesive property of the photosensitive film F may be changed through, for example, an exposure process. For example, when the photosensitive film F is exposed to ultraviolet rays UV by using an exposure mask M, the photosensitive film F may have a property that an adhesive force of a portion of the photosensitive film F exposed to the ultraviolet rays UV is decreased or removed, while the adhesive force of a portion of the photosensitive film F not exposed to the ultraviolet rays UV is maintained. Here, the exposure mask M may have a pattern of a transparent

14

portion T and an opaque portion B, and the photosensitive film F may be irradiated with the ultraviolet rays UV through the exposure mask M.

Then, the portion of the photosensitive film F corresponding to the opaque portion B blocking the ultraviolet rays UV may maintain the original adhesive force of the photosensitive film F as is. In addition, the adhesive force of the portion of the photosensitive film F corresponding to the portion T transmitting the ultraviolet rays UV may be reduced or eliminated by the ultraviolet rays UV.

Referring to FIG. 11C, a film pattern FP may be obtained by peeling off and removing a denatured portion (e.g., a portion where the adhesive force is reduced or eliminated) of the photosensitive film F.

Further, the memory controller 192 may be electrically connected to the interposer 180 by using second bonding wire(s) BW. Further, the memory controller 192 may be electrically connected to the substrate 101 by using third bonding wire(s) BW. According to some example embodiments, in the case that the bonding wire(s) BW does not interfere with a film laminated thereon (e.g., the photosensitive film F in FIG. 11B and/or a molding layer 162 in FIG. 11D to be explained below), an entirety of the bonding wires (e.g., the first, second, and third bonding wires) may be formed in a process illustrated in FIG. 11A.

Referring to FIG. 11D, a molding layer 162 may encapsulate the memory controller 192 and the memory devices 194. At this time, after the substrate 101 is fixed in a mold C, the molding layer 162 having fluidity may be injected. For example, the mold C may prevent the molding layer 162 from entering a portion where the conductor via CV is to be formed later. In other words, the mold C may be configured to directly contact the film pattern FP to define a shape of the conductor via CV to be formed later.

Referring to FIG. 11E, after the mold C is removed, the exposed film pattern FP may be removed. The film pattern FP may be removed by a wet or dry method. In some example embodiments, the film pattern FP may be wet removed by using a chemical agent. In some example embodiments, the film pattern FP may be dry removed through dry-ashing in a hot oxidizing atmosphere.

A portion of the conductor line 182 may be exposed by removing the film pattern FP. The conductor via CV and the second external connection terminals 150 may be formed with respect to the exposed conductor line 182 by a method such as plating (refer to FIG. 2).

When the conductor via CV and the second external connection terminals 150 are simultaneously formed by plating, the interface between the conductor vias CV and the second external connection terminals 150 may not exist.

In some example embodiments, after the conductor via CV is formed by using solder paste, the second external connection terminals 150 may be formed by plating a conductive layer on the conductor via CV. When the conductor via CV and the second external connection terminals 150 are formed as described above, the interface between the conductor via CV and the second external connection terminals 150 may exist.

While the inventive concepts have been particularly shown and described with reference to some example embodiments thereof, it will be understood by those of ordinary skill in the art that various changes in form and details may be made therein without departing from the spirit and scope of the inventive concepts as defined in the appended claims. Accordingly, modifications of the disclosed example embodiments of the inventive concepts will not depart from the scope of the appended claims.

15

What is claimed is:

1. A memory card comprising a first main surface and a second main surface opposing each other, the memory card comprising:

a printed circuit board (PCB) establishing the first main surface, the PCB including a plurality of first external connection terminals, the plurality of first external connection terminals exposed on the first main surface; a plurality of memory devices stacked on the PCB; a memory controller configured to control the plurality of memory devices; a molding layer encapsulating the plurality of memory devices and the memory controller, the molding layer establishing the second main surface; and

one or more second external connection terminals electrically connected to the memory controller, the one or more second external connection terminals embedded in the molding layer and exposed by the molding layer at the second main surface,

wherein a surface of the one or more second external connection terminals is coplanar with the second main surface,

wherein the plurality of first external connection terminals comprise,

a first set of the first external connection terminals in a first row, the first row being adjacent to an insertion-side edge of the memory card, the first set of the first external connection terminals including a power supply terminal of a first voltage and a ground terminal, and

a second set of the first external connection terminals in a second row, the second row being farther apart from the insertion-side edge than the first row, the second set of the first external connection terminals including a power supply terminal of a second voltage and data terminals.

2. The memory card of claim 1, wherein at least one of the one or more second external connection terminals is connected to a conductive via penetrating the molding layer.

3. The memory card of claim 2, wherein the conductive via extends in a direction perpendicular to the second main surface.

4. The memory card of claim 3, wherein the conductive via is electrically connected to a conductor line extending in a direction parallel to the second main surface.

5. The memory card of claim 4, wherein an end of the conductor line is connected to the conductive via and the other end of the conductor line is connected to the memory controller.

6. The memory card of claim 5, wherein the conductor line is connected to the memory controller via a bonding wire.

7. The memory card of claim 5, wherein the conductive line is provided on a surface of an uppermost one of the plurality of memory devices.

8. The memory card of claim 4, further comprising: an interposer between the memory controller and the plurality of memory devices.

9. The memory card of claim 8, wherein a planar area of the interposer is greater than that of the memory controller, and the conductor line is provided on a surface of the interposer.

10. The memory card of claim 1, wherein the one or more second external connection terminals comprises:

one or more of (i) a pair of data input/output terminals; or (ii) a data input/output terminal having a one-lane

16

structure in which a set of data input terminals and a set of data output terminals each comprise a differential signal pair.

11. A memory card comprising a first main surface and a second main surface opposing each other, the memory card comprising:

a printed circuit board (PCB) establishing the first main surface, the PCB including a plurality of first external connection terminals, the plurality of first external connection terminals on the first main surface;

a plurality of memory devices stacked on the PCB;

a memory controller on an uppermost memory device among the plurality of memory devices;

a molding layer encapsulating the plurality of memory devices and the memory controller, the molding layer establishing the second main surface;

one or more second external connection terminals electrically connected to the memory controller, the one or more second external connection terminals embedded in the molding layer and exposed by the molding layer at the second main surface, wherein a surface of the one or more second external connection terminals is coplanar with the second main surface;

a conductive via penetrating the molding layer, the conductive via being connected to one of the second external connection terminals; and

a conductor line extending in a direction parallel to the second main surface, an end of the conductor line being connected to the conductive via and the other end of the conductor line being connected to the memory controller via a bonding wire,

wherein the plurality of first external connection terminals comprise,

a first set of the first external connection terminals in a first row, the first row being adjacent to an insertion-side edge of the memory card, the first set of the first external connection terminals including a power supply terminal of a first voltage and a ground terminal, and

a second set of the first external connection terminals in a second row, the second row being farther apart from the insertion-side edge than the first row, the second set of the first external connection terminals including a power supply terminal of a second voltage and data terminals.

12. The memory card of claim 11, further comprising: a capacitor, an end of the capacitor being electrically connected to the conductor line and the other end of the capacitor being grounded.

13. The memory card of claim 12, wherein the capacitor is provided in a lateral protrusion provided in a side direction of the second set of the first external connection terminals.

14. The memory card of claim 11, wherein the one or more second external connection terminals comprise a power supply terminal configured to supply a supply voltage of about 1.2 V or less, and the plurality of first external connection terminals comprise a power supply terminal configured to supply a supply voltage between about 3.3V and about 1.8V.

15. The memory card of claim 11, wherein the plurality of first external connection terminals comprise external connection terminals according to any one standard among a secure digital (SD) card, a micro SD card, a mini SD card, a universal flash storage (UFS) card, or a multimedia card (MMC).

17

16. The memory card of claim **11**, wherein the plurality of first external connection terminals include test terminals covered by a solder resist (SR) layer.

17. A memory card comprising a first main surface and a second main surface opposing each other, the memory card comprising:

- a printed circuit board (PCB) establishing the first main surface, the PCB including a plurality of first external connection terminals, the plurality of first external connection terminals exposed on the first main surface;
- a plurality of memory devices stacked on the PCB;
- a memory controller on an uppermost memory device among the plurality of memory devices;
- a molding layer encapsulating the plurality of memory devices and the memory controller, the molding layer establishing the second main surface;
- one or more second external connection terminals electrically connected to the memory controller, the one or more second external connection terminals embedded in the molding layer and exposed by the molding layer at the second main surface, wherein a surface of the one or more second external connection terminals is coplanar with the second main surface;
- a conductive via extending in a direction perpendicular to the second main surface; and

18

a conductor line extending in a direction parallel to the second main surface, an end of the conductor line being connected to the conductive via and the other end of the conductive line being connected to the memory controller via a bonding wire,

wherein the plurality of first external connection terminals comprise,

- a first set of the first external connection terminals in a first row, the first row being adjacent to an insertion-side edge of the memory card, the first set of the first external connection terminals including a power supply terminal of a first voltage and a ground terminal, and
- a second set of the first external connection terminals in a second row, the second row being farther apart from the insertion-side edge than the first row, the second set of the first external connection terminals including a power supply terminal of a second voltage and data terminals.

18. The memory card of claim **17**, wherein the conductor line is not electrically connected to a semiconductor device provided in the plurality of memory devices stacked on the PCB.

19. The memory card of claim **18**, wherein the conductor line is provided on a surface of an uppermost one of the plurality of memory devices.

* * * * *