



US011467609B2

(12) **United States Patent**  
**Gessler et al.**

(10) **Patent No.: US 11,467,609 B2**  
(45) **Date of Patent: Oct. 11, 2022**

(54) **PRESSURE-REGULATING DEVICE, SYSTEMS INCLUDING THE PRESSURE-REGULATING DEVICE, AND RELATED METHODS**

(58) **Field of Classification Search**  
CPC ..... Y10T 137/7795; Y10T 137/7808; Y10T 137/7825; Y10T 137/7826  
See application file for complete search history.

(71) Applicant: **Mobile I.V. Systems, LLC**, Chugiak, AK (US)

(56) **References Cited**

(72) Inventors: **Ryan Gessler**, Camas, WA (US); **Fred Vreeman**, Fairbanks, AK (US)

U.S. PATENT DOCUMENTS

(73) Assignee: **MOBILE I.V. SYSTEMS, LLC**, Chugiak, AK (US)

1,465,654 A \* 8/1923 Radtke ..... F25B 41/31  
137/454.2  
1,561,367 A \* 11/1925 Spreen ..... F16K 29/00  
137/454.5  
1,703,531 A \* 2/1929 Hyde ..... F25B 41/31  
137/505.42

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(Continued)

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **16/995,723**

CA 2256776 A1 7/2000  
CA 2256776 A1 ‡ 7/2000

(22) Filed: **Aug. 17, 2020**

(Continued)

(65) **Prior Publication Data**

US 2020/0379490 A1 Dec. 3, 2020

**Related U.S. Application Data**

OTHER PUBLICATIONS

International Search Report and Written Opinion dated Aug. 16, 2017 for PCT application No. PCT/US2017/027217.‡

(Continued)

(63) Continuation of application No. 16/093,552, filed as application No. PCT/US2017/027217 on Apr. 12, 2017, now Pat. No. 10,747,241.

*Primary Examiner* — Robert K Arundale

(74) *Attorney, Agent, or Firm* — Dorsey & Whitney LLP

(60) Provisional application No. 62/321,667, filed on Apr. 12, 2016.


(57) **ABSTRACT**

(51) **Int. Cl.**  
**F16K 31/12** (2006.01)  
**G05D 16/10** (2006.01)  
**G05D 16/04** (2006.01)

Embodiments described herein relate to a pressure-regulating device, systems that include the device, and related methods. For example, the pressure-regulating device may receive gas from a gas supply at a first pressure (e.g., on a supply side of the pressure-regulating device) and may regulate or reduce the pressure of the received gas to a selected or suitable second, different pressure.

(52) **U.S. Cl.**  
CPC ..... **G05D 16/107** (2019.01); **G05D 16/0402** (2019.01); **G05D 16/103** (2013.01); **Y10T 137/7795** (2015.04); **Y10T 137/7808** (2015.04)

**15 Claims, 24 Drawing Sheets**



(56)

## References Cited

## U.S. PATENT DOCUMENTS

2,057,150 A ‡ 10/1936 Kehl ..... G05D 16/0402  
137/505.12  
2,160,025 A \* 5/1939 Erle ..... B64C 11/42  
416/139  
2,313,149 A ‡ 3/1943 Jacobsson ..... A62B 9/022  
137/81.1  
2,343,146 A \* 2/1944 Jenkins ..... G05D 16/0663  
137/316  
2,618,908 A ‡ 11/1952 Salter ..... G05D 16/10  
137/454.5  
2,666,278 A \* 1/1954 Matasovic ..... G05D 16/0663  
137/454.5  
2,770,252 A ‡ 11/1956 Bass, Sr. .... G05D 16/0402  
137/505.12  
3,153,424 A \* 10/1964 Acker ..... G05D 16/0663  
137/505.41  
3,407,841 A \* 10/1968 Semon ..... G05D 16/0658  
137/505.15  
3,825,008 A ‡ 7/1974 Shook ..... A61B 17/135  
606/202  
3,890,999 A \* 6/1975 Moskow ..... G05D 16/103  
137/505.25  
4,446,859 A ‡ 5/1984 Pedersen ..... A62B 9/022  
128/20  
4,450,858 A \* 5/1984 Acomb ..... G05D 16/0663  
137/484.8  
4,657,160 A ‡ 4/1987 Woods ..... A61M 5/1483  
4,862,884 A ‡ 9/1989 Christianson ..... B63C 11/18  
128/20  
5,307,834 A ‡ 5/1994 Tatarek-Gintowt .... G05D 16/10  
137/11  
5,346,477 A ‡ 9/1994 Edwards ..... A61M 5/1483  
604/11  
5,749,854 A ‡ 5/1998 Shen ..... A61M 5/1486  
604/11  
5,894,869 A ‡ 4/1999 Mussack ..... B67D 1/0418  
141/19  
5,911,220 A ‡ 6/1999 Morgan ..... A62B 9/02  
128/20  
5,921,275 A \* 7/1999 Knop ..... F16K 31/404  
137/498  
6,026,849 A ‡ 2/2000 Thordarson ..... G05D 7/0106  
137/50  
6,488,046 B2 ‡ 12/2002 Parietti ..... G05D 16/0672  
137/50  
6,843,388 B1 ‡ 1/2005 Hollars ..... F17C 13/06  
222/18  
6,948,520 B2 ‡ 9/2005 Carroll ..... G05D 16/103  
137/50  
7,080,655 B2 ‡ 7/2006 Jacksier ..... G05D 16/103  
137/14  
7,140,387 B2 ‡ 11/2006 Wilson, Jr. .... F41A 33/06  
137/50  
7,290,563 B2 ‡ 11/2007 Nakamura ..... F16K 7/075  
137/61  
7,334,598 B1 ‡ 2/2008 Hollars ..... F17C 13/04  
137/11  
7,635,005 B2 ‡ 12/2009 Blankevoort ..... G01N 30/32  
137/50  
7,757,710 B2 ‡ 7/2010 Larsen ..... G05D 16/103  
137/50  
8,087,428 B1 ‡ 1/2012 Beswick ..... F16K 17/085  
137/50  
8,167,001 B2 ‡ 5/2012 Larsen ..... G05D 16/0404  
137/88  
8,327,871 B1 ‡ 12/2012 Franklin ..... G05D 16/0655  
137/27  
8,375,983 B2 ‡ 2/2013 Niebel ..... G05D 16/0402  
137/50  
9,310,812 B2 ‡ 4/2016 Costle ..... G05D 16/103  
9,739,388 B2 ‡ 8/2017 Rider ..... B67D 1/0412  
10,126,758 B2 ‡ 11/2018 Ottestad ..... G05D 16/10

10,747,241 B2 8/2020 Gessler et al.  
2003/0164190 A1 \* 9/2003 Ellero ..... G05D 16/0663  
137/505.42  
2004/0173267 A1 9/2004 Jacksier et al.  
2004/0187929 A1 ‡ 9/2004 Carroll ..... G05D 16/103  
137/50  
2004/0231733 A1 ‡ 11/2004 Nakamura ..... G05D 16/0404  
137/61  
2004/0256008 A1 \* 12/2004 Huang ..... G05D 16/103  
137/505.25  
2005/0152796 A1 \* 7/2005 Morrison ..... G05D 16/103  
417/440  
2006/0157122 A1 ‡ 7/2006 Kawamura ..... G05D 16/103  
137/613  
2006/0185736 A1 ‡ 8/2006 Cavagna ..... G05D 16/0683  
137/50  
2007/0017524 A1 ‡ 1/2007 Wilson ..... A61M 16/207  
128/20  
2007/0272313 A1 ‡ 11/2007 Olds ..... G05D 16/0663  
137/61  
2008/0011361 A1 ‡ 1/2008 Larsen ..... G05D 16/103  
137/52  
2009/0020169 A1 \* 1/2009 Lo ..... G05D 16/103  
137/484.2  
2009/0071548 A1 ‡ 3/2009 Patterson ..... G05D 16/103  
137/49  
2009/0071550 A1 ‡ 3/2009 Patterson ..... G05D 16/103  
137/52  
2010/0206401 A1 ‡ 8/2010 Niebel ..... G05D 16/185  
137/505.11  
2011/0155267 A1 ‡ 6/2011 Nicolini ..... F17C 13/04  
137/511  
2012/0181287 A1 \* 7/2012 Holbeche ..... F16K 17/16  
220/582  
2012/0234407 A1 ‡ 9/2012 Edwards ..... G05D 16/0655  
137/505  
2014/0102560 A1 \* 4/2014 Costle ..... G05D 16/0402  
137/505.12  
2017/0123439 A1 ‡ 5/2017 Koenig ..... G05D 16/0402  
2019/0070362 A1 ‡ 3/2019 Lynch ..... A61M 5/19  
2019/0179348 A1 6/2019 Gessler et al.

## FOREIGN PATENT DOCUMENTS

CN 1573188 A 2/2005  
CN 1720491 A 1/2006  
CN 1985122 A 6/2007  
CN 201218424 Y 4/2009  
CN 201218424 Y ‡ 4/2009  
CN 101966975 A 2/2011  
CN 102758943 A 10/2012  
CN 102758943 A ‡ 10/2012  
CN 202545919 U 11/2012  
CN 202545919 U ‡ 11/2012  
DE 19821292 A1 11/1999  
DE 19821292 A1 ‡ 11/1999  
DE 102017113055 A1 12/2018  
DE 102017113055 A1 ‡ 12/2018  
EP 2275037 A1 ‡ 1/2011  
EP 2275037 A1 1/2011  
EP 2191178 B1 ‡ 11/2012 ..... G05D 16/0402  
EP 2191178 B1 11/2012  
EP 2720105 A2 4/2014  
JP 2004360893 A 12/2004  
KR 20090116689 A 11/2009  
KR 101244377 B1 ‡ 3/2013  
KR 101244377 B1 3/2013  
RU 152440 U1 ‡ 5/2015  
RU 152440 U1 5/2015  
WO 2017180750 A1 10/2017  
WO WO-2017180750 A1 ‡ 10/2017  
WO 2018041820 A1 3/2018  
WO WO-2018041820 A1 ‡ 3/2018

## OTHER PUBLICATIONS

(56)

**References Cited**

OTHER PUBLICATIONS

English translation of Office Action for IN Application No. 201817042374, dated Jan. 18, 2021.

English translation of Office Action for JP Application No. 2019-505128, dated Feb. 8, 2021.

English translation of Office Action for KR Application No. 10-2018-7032761, dated Jan. 28, 2021.

First office action received in CN App. No. 201780036611.3 dated Jun. 1, 2020.

Extended European Search Report for Application No. 17783060.1, dated Feb. 19, 2020.

Partial Supplementary European Search Report for Application No. 17783060.1, dated Nov. 5, 2019.

\* cited by examiner

‡ imported from a related application




FIG. 1A




FIG. 1B





Fig. 2A



**FIG. 2B**




FIG. 3B

FIG. 3A




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 5






FIG. 6






FIG. 7C




FIG. 7D




FIG. 7E




FIG. 8A




FIG. 8B




FIG. 9A




FIG. 9B




FIG. 9C




FIG. 10A

FIG. 10B




FIG. 11




FIG. 12A




FIG. 12B




FIG. 12C




FIG. 12D




FIG. 12E




FIG. 13




FIG. 14




FIG. 15

# **PRESSURE-REGULATING DEVICE, SYSTEMS INCLUDING THE PRESSURE-REGULATING DEVICE, AND RELATED METHODS**

## **CROSS-REFERENCE TO RELATED APPLICATIONS**

This application is a continuation of U.S. patent application Ser. No. 16/093,552 filed on Oct. 12, 2018, and issued as U.S. Pat. No. 10,747,241 on Aug. 18, 2020, which is a U.S. National Stage filing under 35 U.S.C. § 371 of PCT Application No. PCT/US2017/027217, filed on Apr. 12, 2017, which claims the benefit of priority to U.S. Provisional Application No. 62/321,667 filed on Apr. 12, 2016, the contents of which are incorporated herein by this reference.

## **BACKGROUND**

Commonly, compressing gas facilitates storage and transportation thereof. For example, compressed gas may require smaller storage containers (e.g., compared to uncompressed gas), which may enhance convenience of storage, transportation, or use of the gas. Moreover, compressed gas may be used as propellant or pneumatic power supply. For example, one or more mechanisms may be pneumatically powered by the expansion and/or application of pressure of the compressed gas.

In some circumstances, the gas may be stored at pressures that exceed the pressure required during one or more applications thereof. A pressure regulation device may be used to reduce the pressure of the source gas to a suitable or selected pressure for one or more devices that receive the source gas.

## **SUMMARY**

Generally, the embodiments described herein relate to a pressure-regulating device, systems that include the device, and related methods. For example, the pressure-regulating device may receive gas from a gas supply at a first pressure (e.g., on a supply side of the pressure-regulating device) and may regulate or reduce the pressure of the received gas to a selected or suitable second, different pressure. In an embodiment, the gas at the second pressure may exit from gas outlet of the pressure-regulating device.

An embodiment includes a pressure-regulating device that includes a gas inlet, an expansion body defining an expansion chamber that is in fluid communication with the gas inlet, a first stage pressure regulator configured to decrease gas pressure of a gas flowing therethrough, the first stage pressure regulator being in fluid communication with the expansion chamber, an intermediate regulator body threadedly connected to the expansion body and securing at least a portion of the first stage pressure regulator therebetween in a manner that changing distance between the expansion body and the intermediate regulator body changes an amount of pressure decrease produced by the first stage regulator, a second stage pressure regulator positioned downstream from first stage pressure regulator and in fluid communication therewith, the second stage pressure regulator being configured to decrease gas pressure of a gas flowing therethrough, and a gas outlet positioned downstream from the second stage pressure regulator.

Embodiments also include a pressure-regulating device that includes a gas inlet, an expansion body defining an expansion chamber that is in fluid communication with the gas inlet, and a first stage pressure regulator configured to

decrease gas pressure of a gas flowing therethrough, the first stage pressure regulator being in fluid communication with the expansion chamber. The first stage pressure regulator includes a first valve including a first sealing member configured to open and close gas flow through the first valve, a first piston movable in an upstream and downstream directions relative to the gas inlet and configured to move the sealing member in the manner that opens the first valve, a first biasing member positioned to apply a force the first piston in the upstream direction, and a first adjustment mechanism including opposing first and second threaded protrusions, threadedly engaged together and enclosing the first valve and the first biasing member therebetween. The pressure-regulating device also includes a second stage pressure regulator positioned downstream from first stage pressure regulator and in fluid communication therewith. The second stage pressure regulator is configured to decrease gas pressure of a gas flowing therethrough. The pressure-regulating device further includes a gas outlet positioned downstream from the second stage pressure regulator.

An embodiment includes a system that includes a pressure cuff and a pressure-regulating device. The pressure-regulating device includes a gas inlet, an expansion body defining an expansion chamber that is in fluid communication with the gas inlet, a first stage pressure regulator configured to decrease gas pressure of a gas flowing therethrough, the first stage pressure regulator being in fluid communication with the expansion chamber, an intermediate regulator body threadedly connected to the expansion body and securing at least a portion of the first stage pressure regulator therebetween in a manner that changing distance between the expansion body and the intermediate regulator body changes an amount of pressure decrease produced by the first stage regulator, a second stage pressure regulator positioned downstream from first stage pressure regulator and in fluid communication therewith, the second stage pressure regulator being configured to decrease gas pressure of a gas flowing therethrough, and a gas outlet positioned downstream from the second stage pressure regulator and operably connected to the pressure cuff.

Features from any of the disclosed embodiments may be used in combination with one another, without limitation. In addition, other features and advantages of the present disclosure will become apparent to those of ordinary skill in the art through consideration of the following detailed description and the accompanying drawings.

## **BRIEF DESCRIPTION OF THE DRAWINGS**

For better understanding, the like elements are referenced by like reference numbers. The drawings are not necessarily to scale, with the emphasis instead placed upon the principles of the present disclosure. Understanding that these drawings depict only typical embodiments of the invention and are not therefore to be considered to be limiting of its scope, the invention will be described and explained with additional specificity and detail through the use of the accompanying drawings in which:

FIG. 1A is a perspective view of a pressure-regulating device according to an embodiment;

FIG. 1B is a cross-sectional view of the pressure-regulating device of FIG. 1A;

FIG. 2A is an enlarged, partial cross-sectional view of the pressure-regulating device of FIG. 1A in an open configuration;

FIG. 2B is an enlarged, partial cross-sectional view of the pressure-regulating device of FIG. 1A in a closed configuration

FIG. 3A is an enlarged, partial cross-sectional view of the pressure-regulating device of FIG. 1A in an unlocked configuration;

FIG. 3B is an enlarged, partial cross-sectional view of the pressure-regulating device of FIG. 1A in a locked configuration;

FIG. 4A is a front perspective view of an expansion body of a pressure-regulating device according to an embodiment;

FIG. 4B is a side perspective view of the expansion body of FIG. 4A;

FIG. 4C is a back perspective view of the expansion body of FIG. 4A;

FIG. 5 is an enlarged, partial cross-sectional view of the pressure-regulating device of FIG. 1A;

FIG. 6 is another enlarged, partial cross-sectional view of the pressure-regulating device of FIG. 1A, showing a pressurized cylinder and a portion of an expansion chamber of the pressure-regulating device;

FIG. 7A is a top, perspective view of a piston of a pressure-regulating device according to an embodiment;

FIG. 7B is an enlarged, partial perspective view of the piston of FIG. 7A;

FIG. 7C is a back, perspective view of the piston of FIG. 7A;

FIG. 7D is an enlarged, partial perspective view of the piston of FIG. 7C;

FIG. 7E is a cross-sectional view of the piston of FIG. 7A;

FIG. 8A is a top view of a piston of a pressure-regulating device according to an embodiment;

FIG. 8B is a cross-sectional view of the piston of FIG. 8A;

FIG. 9A is a side view of a pressure gauge of a pressure-regulating device according to an embodiment;

FIG. 9B is a cross-sectional view of the pressure gauge of FIG. 9A exposed to a first pressure;

FIG. 9C is a cross-sectional view of the pressure gauge of FIG. 9A exposed to a second pressure;

FIG. 10A is a top view of a pressure-regulating device connected to a pressure cuff according to an embodiment;

FIG. 10B is a side view of the pressure-regulating device connected to the pressure cuff of FIG. 10A.

FIG. 11 is a cross-sectional view of an expansion body of a pressure-regulating device according to an embodiment;

FIG. 12A is a perspective view of an outer ring of a lock mechanism according to an embodiment;

FIG. 12B is a top view of the outer ring of FIG. 12A;

FIG. 12C is a perspective view of one half of the outer ring of FIG. 12A;

FIG. 12D is a perspective view of an inner ring of a lock mechanism according to an embodiment;

FIG. 12E is a side view of the inner ring of FIG. 12D;

FIG. 13 is a cross-sectional view of a regulator-inflow member of a pressure-regulating device according to an embodiment;

FIG. 14 is a cross-sectional view of a regulator-inflow member of a pressure-regulating device according to another embodiment; and

FIG. 15 is a perspective view of an inlet deflector of a pressure-regulating device according to an embodiment.

#### DETAILED DESCRIPTION

Generally, the embodiments described herein relate to a pressure-regulating device, systems that include the device, and related methods. For example, the pressure-regulating

device may receive gas from a gas supply at a first pressure (e.g., on a supply side of the pressure-regulating device) and may regulate or reduce the pressure of the received gas to a selected or suitable second, different pressure. In an embodiment, the gas at the second pressure may exit from gas outlet of the pressure-regulating device.

In some embodiments, the outlet pressure of pressure-regulating device may be adjusted or calibrated to a suitable pressure. For example, the pressure-regulating device may include and/or may be connected to a pressure gauge that may provide an indication of the gas outlet pressure. Moreover, the pressure-regulating device may include one or more pressure-adjustment mechanisms. In some embodiments, the pressure-regulating device includes at least two pressure-adjustment mechanisms. The pressure-regulating device may include a first stage regulator that may be adjusted to reduce gas pressure from the supply pressure to a lower pressure that is within a selected pressure range, and may further include a second stage regulator that may further adjust the outlet pressure (e.g., decrease the gas pressure) to be in a narrower or more precise pressure range. For example, the first stage regulator may be used for coarse adjustment of the outlet pressure, and the second stage regulator may be used for finer or more precise pressure adjustment of the outlet pressure.

FIGS. 1A-1B illustrate a pressure-regulating device 100 according to an embodiment. Specifically, FIG. 1A is a perspective view of the pressure-regulating device 100; and FIG. 1B is a cross-sectional view of the pressure-regulating device 100. In the illustrated embodiment, the pressure-regulating device 100 includes a gas inlet 110 and a gas outlet 120. As mentioned above, the pressure at the gas inlet 110 may be higher than at the gas outlet 120. Moreover, the pressure-regulating device 100 may be adjusted or calibrated to produce a suitable or selected pressure reduction from the gas inlet 110 to the gas outlet 120 and/or to produce a suitable or selected pressure at the gas outlet 120.

Generally, the pressure-regulating device 100 may receive gas from any number of suitable gas sources or supplies. In the illustrated embodiment, as described below in more detail, the pressure-regulating device 100 may be configured to accept a gas cartridge 130 that includes compressed gas (e.g., a standard CO<sub>2</sub> gas cartridge). In additional or alternative embodiments, the pressure-regulating device 100 may receive compressed gas from a centralized supply (e.g., a supply line) or any other suitable source. In any event, compressed gas from a suitable supply may flow into the gas inlet 110. For ease of description, the direction of the gas flow in the pressure-regulating device 100 is referred to as downstream or distal, and a direction that is opposite to the downstream direction is referred to as upstream or proximal.

Compressed gas, at first pressure, may enter the pressure-regulating device 100 at the gas inlet 110 and exit the pressure-regulating device 100 at the gas outlet 120, at a second, lower pressure. For example, the ratio of the first pressure to second pressure may be in one or more of the following ranges: from 2:1 to 5:1, from 4:1 to 10:1, from 8:1 to 20:1, from 15:1 to 50:1, from 40:1, to 100:1. For example, the pressure-regulating device 100 may reduce pressure from 800 psi to 10 psi or less (e.g., to 5 psi, 1 psi). Moreover, in some embodiments, the pressure-regulating device 100 may be configured to reduce or adjust pressure in a manner that produces the pressure ratio between the gas inlet 110 and gas outlet 120 that is outside the above-noted ranges. It should be appreciated that the pressure values expressed herein are described in terms of pressure above atmospheric

## 5

pressure (e.g., a reference to the pressure of 5 psi refers to absolute pressure of about 19.7 psi).

In the illustrated embodiment, the pressure-regulating device **100** includes an expansion body **200** that may be operably connected to the gas inlet **110**. For example, the expansion body **200** may have an expansion chamber **210** (e.g., defined by one or more walls of the expansion body **200**) that may be in fluid communication with the gas inlet **110**. Hence, for example, gas may flow from the gas inlet **110** into the expansion chamber **210**. In some embodiments, as the gas enters the expansion chamber **210**, the gas may expand in the expansion chamber **210** (e.g., the amount of the gas entering the expansion chamber **210** may have or occupy a greater volume than before entering the expansion chamber **210**), such that the pressure of the gas in the expansion chamber **210** is lower than the pressure of the gas before entering the expansion chamber **210**.

It should be appreciated, however, that in some embodiments, the expansion chamber **210** may be in continuous fluid communication with the gas inlet **110**. Hence, for example, the pressure of the gas in the expansion chamber **210** may be the same as the pressure of the gas in the gas cartridge **130** or at the gas source that is otherwise connected to gas inlet **110**. For example, expansion of the gas from the gas cartridge **130** into the expansion chamber **210** may reduce the pressure of the gas in the gas cartridge **130**, such that the gas in the expansion chamber **210** and in the gas cartridge **130** is at a lower pressure than the pressure of the gas that was in the gas cartridge **130**, before entry into the expansion chamber **210**.

In an embodiment, the pressure-regulating device **100** includes a pressure regulator **300** that is in fluid communication with the gas inlet **110** and gas outlet **120**. Specifically, for example, the pressure regulator **300** may reduce and/or regulate the pressure of the gas to produce a suitable or selected pressure at the gas outlet **120**. In the illustrated embodiment, the pressure regulator **300** is a two-stage pressure regulator. For example, at a first stage regulator **301**, the pressure regulator **300** may be adjusted or calibrated to produce a selected pressure output to the gas outlet **120** at a first degree of accuracy or precision, and at a subsequent, second stage regulator **302**, the pressure regulator **300** may be adjusted or calibrated to produce a selected pressure output at a second, higher degree of accuracy or precision (e.g., the first and second stage regulators **301**, **302** may facilitate fine-tuning or calibration of the pressure regulator **300** to a selected or suitable degree of precision). The second stage regulator **302** may be positioned downstream from the first stage regulator **301** and in fluid communication therewith. Moreover, it should be appreciated that the pressure-regulating device may include any suitable number of stages.

As mentioned above, the pressure-regulating device **100** may be operably coupled to or may include a gauge or a pressure indicator that may be configured to determine and/or provide a measurement or indication of the gas pressure at the gas outlet **120**. In the illustrated embodiment, the pressure-regulating device **100** includes a pressure gauge **400**. For example, the pressure gauge **400** may be operably connected to the pressure regulator **300** (e.g., the pressure gauge **400** may be in fluid communication with the pressure regulator **300** and/or with the gas outlet **120** of the pressure-regulating device **100**). Under some operating conditions, the pressure gauge **400** may facilitate or assist with calibration of the pressure regulator **300**. For example, the pressure regulator **300** may be calibrated to produce a suitable or

## 6

selected pressure at the gas outlet **120** based on the pressure readings at the pressure gauge **400**.

Generally, the pressure gauge **400** may have any number of suitable configurations (e.g., the pressure gauge **400** may be mechanical and/or analogue gauge or may be a digital gauge). In the illustrated embodiment, the pressure gauge **400** includes an indicator piston that may move out of a regulator cap in response to a pressure experienced by the indicator piston. The indicator piston may include one or more markings that correspond to a pressure required to move the indicator piston out of the regulator cap to expose the marking. That is, as the indicator piston moves out of the regulator cap (due to the pressure experienced by the indicator piston), the markings corresponding to the pressure experience by the indicator piston are exposed and/or may align with a stationary indicator to provide a reading or indication of the pressure. In any event, a pressure gauge that may be connected to or incorporated into the pressure-regulating device **100** may provide a pressure reading that indicates the gas pressure at the gas outlet **120** of the pressure-regulating device **100**.

As mentioned above, the pressure regulator **300** may control the gas pressure at the gas outlet **120**. FIGS. 2A-2B are partial, cross-sectional views of the pressure-regulating device **100** (FIGS. 1A-1B), showing the pressure regulator **300** of the pressure-regulating device **100**. Specifically, in FIG. 2A, the pressure regulator **300** is shown in an open configuration, and in FIG. 2B, the pressure regulator **300** is shown in a closed configuration, during its operation. As described below in more detail, continuously reconfiguring the pressure regulator **300** between open and closed configurations may control the output pressure or produce the selected pressure at the gas outlet **120**.

For example, the gas outlet **120** may be operably connected to a device (e.g., as described below, the gas outlet **120** may be connected to a pressure cuff). Under some operating conditions, the pressure-regulating device **100** and a device connected thereto may define or form a closed system or semi-closed system, where the gas outlet **120** may be in fluid communication with an inlet of the device connected to the pressure-regulating device **100** and/or with a chamber of the connected device, such that the pressure at the gas outlet **120** may be generally or approximately the same as the pressure in the connected device.

Under some operating conditions, the pressure at the gas outlet **120** may be approximately 0 psi (e.g., the pressure at the gas outlet **120** and/or in the device connected to the pressure-regulating device **100** may be approximately atmospheric pressure). In some embodiments, when the gas outlet **120** is below a selected pressure (e.g., a cut-off pressure for which the pressure regulator **300** is calibrated), the pressure regulator **300** may be in the open configuration (shown in FIG. 2A), such that the gas can flow to the gas outlet **120**, to increase the pressure at the gas outlet **120** to the selected pressure, at which the pressure regulator **300** may assume the closed configuration, to prevent further gas flow to the gas outlet **120** (as described below). Moreover, as the pressure at the gas outlet **120** drops below the selected pressure, the pressure regulator **300** may again assume the open configuration to allow more gas to pass to the gas outlet **120**, thereby increasing the pressure at the gas outlet **120** to the selected pressure, and again, at which the pressure regulator **300** may assume the closed configuration. As such, the pressure regulator **300** may cycle between open and closed configurations to selectively and/or intermittently permit gas to flow to the gas outlet **120** (e.g., from the gas

inlet 110), to maintain a selected pressure at the gas outlet 120 and/or in the device connected to the gas outlet 120.

For example, the first stage regulator 301 of the pressure regulator 300 may include a first piston 310 that is movable in a proximal direction (e.g., toward the gas inlet) open the first stage regulator 301 of the pressure regulator 300 and allow the gas to flow through the first stage regulator 301 (e.g., as indicated with the arrows in FIG. 2A). The first piston 310 also may move distally to close or prevent gas flow through the first stage regulator 301. For example, the first stage regulator 301 may include a chamber 320 (described below in more detail). When the pressure in the chamber 320 is below a selected pressure (e.g., below the output pressure at the gas outlet 120), the first piston 310 moves in the proximal direction, which allows pressurized gas to enter the chamber 320 and move the first piston 310 in the distal direction (e.g., when the pressure in the chamber 320 is at the selected pressure) and stop further entry of gas into the chamber 320, thereby closing or preventing gas flow through the first stage regulator 301.

In the illustrated embodiment, the first stage regulator 301 includes a first valve 330 that may be operated by the first piston 310 to open and close gas flow through the first stage regulator 301. For example, the first valve 330 may have a sealing member 331, a seal 332 (e.g., an O-ring), and a spring 333 that may press or bias the sealing member 331 toward and into engagement with the seal 332. Specifically, when the sealing member 331 is pressed against the seal 332, the sealing member 331 may seal against the seal 332, thereby preventing gas flow through the first valve 330 (i.e., the first valve 330 may be in closed configuration). Conversely, moving the sealing member 331 off the seal 332 (e.g., moving the ball in the proximal direction and compressing the spring 333) may form a suitable gap between the sealing member 331 and the seal 332 to allow gas to flow through the gap and through the first valve 330. It should be appreciated that the sealing member, described above as the sealing member 331, may have any number of suitable shapes and/or sizes.

In an embodiment, the expansion body 200 may define at least portion of the first valve 330. For example, the expansion body 200 may include a hollow protrusion 201 (e.g., extending in the proximal direction into the expansion chamber 210 of the expansion body 200), which forms a cavity that houses the sealing member 331, seal 332, and spring 333. For example, the spring 333 may be pressed against the sealing member 331 and together therewith enclosed in the cavity formed by a retention member 334, such that the spring 333 may force the sealing member 331 against the seal 332. The retention member 334 may have an opening therethrough, such that compressed gas may pass through the retention member 334, into the cavity defined by the hollow protrusion 201, through an orifice 202 (when the first valve 330 is open), and into the chamber 320 (e.g., the opening in the retention member 334 may define an inlet of the first valve 330).

The first valve 330 also may include orifice 202 (e.g., which may be defined by one or more portions of the expansion body 200). When the first valve 330 is in the open configuration, gas may flow through the orifice 202 into the chamber 320. Furthermore, in some embodiments, as described below in more detail, the first piston 310 includes one or more passageways therethrough. For example, the gas may flow through the orifice 202 and through one or more passageways of the first piston 310 and out of the first stage regulator 301 (as indicated with the arrows). After

exiting the first stage regulator 301, the gas may flow into the second stage regulator 302, as described below.

The first stage regulator 301 may include a biasing member, such as a spring 340 that may press or bias the first piston 310 in the proximal direction. For example, the strength of the spring 340 and/or the compression of the spring 340 may be suitable to move the first piston 310 in the proximal direction when the pressure in the chamber 320 is below a selected pressure. Moreover, a portion of the first piston 310 may be sized to extend or pass through the orifice 202 and contact the sealing member 331 of the first valve 330.

For example, the spring 340 may push the first piston 310 in the proximal direction and thereby push the sealing member 331 in the proximal direction (e.g., overcoming the force applied by the spring 333 onto the sealing member 331), thereby opening the first valve 330 to allow the gas to flow through the orifice 202 into the chamber 320 and out of the first stage regulator 301 (e.g., downstream toward the gas outlet 120). Conversely, when the pressure in the chamber 320 is at least equal to the selected pressure, the pressure in the chamber 320 together with the force of the spring 333 applied onto the sealing member 331 and thereby applied onto the first piston 310 in the distal direction is sufficient to move the first piston 310 in the distal direction (and to compress the spring 340), thereby allowing the sealing member 331 to close the first valve 330 and stop gas flow through the first valve 330.

In the illustrated embodiment, the chamber 320 is partially defined by and between the expansion body 200 and an intermediate regulator body 220. Moreover, the expansion body 200 may connect to the intermediate regulator body 220. For example, connecting together the expansion body 200 and the intermediate regulator body 220 may define the chamber 320 therebetween. For example, at a distal end, the expansion body 200 may include a protrusion 203 that may define a portion of the chamber 320 (e.g., the protrusion 203 may be a tubular cylinder extending distally or away from the inlet of the pressure-regulating device 100). The intermediate regulator body 220 may include a protrusion 221 that may extend proximally or generally toward the protrusion 203. The first piston 310 is movable relative to the protrusions 203 and 221 and may seal against the inner walls of the protrusions 203 and 221. For example, suitable seals, such as O-rings, may form a seal between the first piston 310 and the inner surfaces of the protrusions 203 and 221, while allowing the first piston 310 to move in the proximal and distal directions relative to the protrusions 203 and 221.

The first piston 310 may include one or more passageways. For example, sealing the first piston 310 between the protrusions 203 and 221 also seals the passageways therebetween. In particular, the passageways of the first piston 310 together with the space defined by the protrusions 203 and 221 define the chamber 320. That is, for example, the pressurized gas in the chamber 320 acts onto the first piston 310 to apply a net force onto the first piston 310 in the distal direction (e.g., the surface area of the first piston 310 on the proximal side thereof, measured along one or more planes perpendicular to the downstream direction, may be greater than on the distal side, such that applying the same pressure on both sides results in net force applied onto the first piston 310 in the distal direction).

In some embodiments, the gas in the passageways of the first piston 310 is in fluid communication with the second stage regulator 302 (as described below) and is substantially prevented from exiting the chamber 320. Hence, for example, the pressure in the chamber 320 may be similar to

or the same as the pressure at the inlet of the second stage regulator **302**, in one or more portions of the second stage regulator **302**, at the gas outlet **120**, or combinations thereof.

For example, as mentioned above, the gas in the chamber **320** may apply pressure onto the first piston **310**. In particular, inside the chamber **320**, the first piston **310** may be configured to have a greater surface area on the proximal side (measured along one or more planes perpendicular to the downstream direction) than on the distal side. Hence, the pressurized gas in the chamber **320** may apply more force in the distal direction than in the proximal direction. Specifically, when the gas pressure in the chamber **320** is at least at a selected pressure (e.g., at a calibrated pressure), the force applied onto the first piston **310** by the pressurized gas together with the spring **333** biasing the sealing member **331** in the distal direction is sufficient to move the first piston **310** in the distal direction to a location that allows the sealing member **331** to seal against the seal **332**. In other words, the combined force produced by the pressurized gas together with the force of the first valve **330** suitably compress the spring **340** to close the first valve **330**.

Generally, any number of suitable mechanisms or connections may connect or secure together the expansion body **200** and the intermediate regulator body **220**. In the illustrated embodiment, the expansion body **200** includes an outer threaded wall **204** that encloses the protrusion **203** and defines a male thread. Furthermore, the intermediate regulator body **220** may include a threaded wall **221** that defines a female thread, which is configured to mate with the male thread of the threaded wall **204** of the expansion body **200**. Hence, the expansion body **200** and the intermediate regulator body **220** may be threadedly connected together.

In an embodiment, the spring **340** may be located in the space defined by and between the threaded walls **204** and **221** (e.g., as shown in FIG. 2A). Hence, for example, moving the expansion body **200** and the intermediate regulator body **220** closer together (e.g., by tightening together the threaded walls **204** and **221**) may compress the spring **340**, thereby increasing the force applied thereby onto the first piston **310**. Conversely, loosening the threaded walls **204** and **221** (i.e., moving the expansion body **200** and intermediate regulator body **220** farther apart from each other) reduces compression of the spring **340**, such that the spring **340** applies less force onto the first piston **310**.

The first stage regulator **301** may be calibrated to produce a selected pressure in the chamber **320** (which may be similar to the pressure produced at the gas outlet **120**). For example, when the gas in the chamber **320** is at the selected pressure, the pressurized gas together with the first valve **330** push the first piston **310** in the distal direction, such as to close the first valve **330** (and stop further flow of gas into the chamber **320**). By contrast, when the gas pressure in the chamber **320** is below the selected pressure, the spring **340** moves the first piston **310** in the proximal direction to move the sealing member **331** off the seal **332** and open the first valve **330**, to allow the gas to enter the chamber **320**, until the pressure in the chamber **320** is increased to the selected pressure, which would close the first valve **330**.

The selected pressure is based on and/or related to the force applied by the spring **340** onto the first piston **310**. Hence, for example, changing the compression of the spring **340** may change the amount of force applied by the spring **340** onto the first piston **310**, thereby changing the pressure required to close the first valve **330** (i.e., changing the selected pressure for moving the first piston **310** distally in the manner that closes the first valve **330**). In some embodiments, the first stage regulator **301** may be calibrated to

produce a selected output pressure by changing the compression of the spring **340** (e.g., by changing the distance between the expansion body **200** and the intermediate regulator body **220**). That is, the amount of pressure decrease or reduction produced by the first stage regulator **301** may be changed by changing the compression of the spring **340**.

It should be appreciated that the first stage regulator **301** may have any number of suitable biasing mechanisms that may force the first piston **310** in the proximal direction. Moreover, the biasing mechanisms may be adjustable to facilitate calibration of the output pressure of the first stage regulator. For example, the first piston **310** may be pneumatically biased (e.g., by a pneumatic cylinder) and the pressure in the pneumatic cylinder may be adjusted, such that the selected pressure in the chamber **320** may force the first piston **310** distally to close the first valve **330**.

As mentioned above, the pressure regulator **300** may include the first stage regulator **301** and the second stage regulator **302**. For example, after passing through the first stage regulator **301** (e.g., when the first valve **330** is open), the gas may enter the second stage regulator **302**. Moreover, after passing through the second stage regulator **302**, the gas may flow to the gas outlet **120** and to a device connected thereto. In the illustrated embodiment, the pressure regulator **300** includes a second valve **350** and a second piston **360** that is movable in proximal and distal directions to operate the second valve **350** (e.g., to open and close the second valve **350**).

The gas that exits the first stage regulator **301** may flow to the second valve **350**. Similar to the first valve **330**, the second valve **350** may include a sealing member **351**, a seal **352**, and a spring **353** that may press the sealing member **351** against the seal **352**, thereby producing a suitable seal therebetween to prevent or close gas flow through the second valve **350**. In particular, the second stage regulator **302** may include an orifice **223**, and the second valve **350** may control gas flow through the orifice **223**.

In the illustrated embodiment, the intermediate regulator body **220** may define at least a portion of the second valve **350**. For example, the intermediate regulator body **220** may have a cavity **224** that may house the sealing member **351**, seal **352**, and the spring **353**. Furthermore, the second valve **350** may include a retention member **354** that may secure the spring **353** in the cavity **224**, such that the spring **353** presses the sealing member **351** toward and/or against the seal **352** in the manner that may form a seal therebetween. The retention member **354** may include an opening therethrough.

The opening in the retention member **354** may define the inlet of the second valve **350**. After exiting the first stage regulator **301**, the gas may enter the second valve **350** of the second stage regulator **302**. If the second valve **350** is in the open configuration (e.g., as shown in FIG. 2A) the gas may flow through the second valve **350** and through the second stage regulator **302** to the gas outlet **120**. Conversely, if the second valve **350** is in the closed configuration, the gas in the cavity **224** of the second valve **350** is prevented from flowing through the second valve **350** (e.g., the pressure at the gas outlet **120** is not increased by the gas flow through the second valve **350**).

As described above, the second piston **360** may move in the proximal direction to open the second valve **350** (e.g., to allow gas flow through the second valve **350** to the gas outlet **120**, such as to increase the pressure at the gas outlet **120**) and/or may move in the distal direction to close the second valve **350** (or to allow the second valve **350** to close) in the manner that the pressure at the gas outlet **120** is not increased from gas flow through the second valve **350** to the

## 11

gas outlet 120. For example, the second piston 360 may include a portion that is sized to fit into and/or pass through the orifice 223 and contact the sealing member 351 of the second valve 350. Hence, similar to the chamber 320 of the first stage regulator 301, the second piston 360 may move in the proximal direction to press against the sealing member 351 (compressing the spring 353) to open the second valve 350 and allow the air to pass therethrough (e.g., as shown in FIG. 2A). Conversely, the second piston 360 may move in the distal direction to close the second valve 350 or to allow the second valve 350 to close (e.g., as shown in FIG. 2B).

In the illustrated embodiment, the second stage regulator 302 includes a biasing member, such as a spring 370 that is positioned and configured to press or bias the second piston 360 in the proximal direction. For example, when the pressure in the chamber 380 is below a selected pressure (e.g., as described below), the spring 370 generates sufficient force to move the second piston 360 in the proximal direction and push the sealing member 351 off the seal 352, thereby producing a gap between the sealing member 351 and seal 352 (or opening the second valve 350) and allowing gas to enter the chamber 380.

The chamber 380 may be in fluid communication with the gas outlet 120. Hence, for example, the gas pressure at the chamber 380 and at the gas outlet 120 may be similar or the same. For example, when the gas pressure at the gas outlet 120 is below the selected output pressure (e.g., at 0, 2 psi, etc.), the force applied by the spring onto the second piston 360 is sufficient to move the second piston 360 in the proximal direction and open the second valve 350. Conversely, when the pressure at the gas outlet 120 is at least at the selected pressure (and the pressure in the chamber 380 is generally the same as at the gas outlet 120), the pressurized gas forces the second piston 360 to move distally and allow the second valve 350 to close.

In the illustrated embodiment, the intermediate regulator body 220 includes a generally tubular section 225 (e.g., tubular section 225 may have a generally circular cross-section). Moreover, the intermediate regulator body 220 may connect to a regulator cap 230 and may collectively therewith define a cavity within which the second piston 360 may be located. In some embodiments, the regulator cap 230 may include an outer wall 231 that extends in the proximal direction and connects to the tubular section 225 of the intermediate regulator body 220 (e.g., the tubular section 225 may define an external thread, and the wall 231 of the regulator cap 230 may define an internal thread which may threadedly connect together). Additionally or alternatively, the regulator cap 230 may include a protrusion 232.

For example, the second piston 360 may seal against the inner surfaces of the tubular section 225 and protrusion 232 (e.g., by suitable seals, such as O-rings), such that the second piston 360 is movable relative to the tubular section 225 and protrusion 232 in proximal and distal directions. Sealing the second piston 360 against the tubular section 225 and the protrusion 232 forms the chamber 380 that is defined by the passageways in the second piston 360 and by the cavities formed by the seals. In an embodiment, the chamber 380 is defined by the passageways in the second piston 360 and the cavities formed by the seals between the second piston 360 and the tubular section 225 and protrusion 232. For example, when the pressure in the chamber 380 is below the selected pressure, the spring 370 may overcome the force applied by the pressurized gas onto the second piston 360, to move the second piston 360 in the proximal direction and open the second valve 350. When the pressure in the chamber 380 is at least at the selected pressure (e.g., at the pressure cali-

## 12

brated for the gas outlet 120), the force applied onto the second piston 360 in the distal direction (due to the larger surface area of the proximal side of the second piston 360 than on the distal side thereof) compresses the spring 370 and moves the second piston 360 in the distal direction, allowing the second valve 350 to close and prevent further pressure increase in the chamber 380 and at the gas outlet 120.

As such, for example, the pressure at the gas outlet 120, at which the second piston 360 may open the second valve 350 (i.e., the pressure at which the second piston 360 moves in the proximal), is related to or based on the force applied by the spring 370 onto the second piston 360 in the proximal direction. Hence, for example, increasing the force applied onto the second piston 360 in the proximal direction will increase the output pressure at the gas outlet 120 (i.e., the pressure required to close the second valve 350), and decreasing the force applied onto the second piston 360 will decrease the output pressure at the gas outlet 120.

In the illustrated embodiment, the spring 370 is located between the intermediate regulator body 220 and the regulator cap 230 (e.g., in the cavity formed by and between the wall 231 of the regulator cap 230 and the 225 of the intermediate regulator body 220). Hence, for example, changing the distance between the intermediate regulator body 220 and the regulator cap 230 may change the compression of the spring 370, thereby changing the amount of force applied thereby onto the second piston 360 in the proximal direction. Again, it should be appreciated that any number of suitable devices or mechanisms may be included in the second stage regulator 302 to apply a selected and/or changeable amount of force onto the second piston 360 in the proximal direction (e.g., the second stage regulator 302 may include a pneumatic piston that may apply a selected amount of force onto the second piston 360).

As mentioned above, the first stage regulator 301 and the second stage regulator 302 may be adjusted and/or calibrated to produce a selected outlet pressure at the gas outlet 120. Specifically, configuring the first stage regulator 301 and/or the second stage regulator 302 to produce the selected pressure may involve adjusting the amount of force applied onto the respective first piston 310 and second piston 360 thereof. For example, the distance between the expansion body 200 and the intermediate regulator body 220 may be adjusted to adjust or calibrate the amount of compression in the spring 340 and the amount of force applied thereby onto the first piston 310. Similarly, the distance between the intermediate regulator body 220 and the regulator cap 230 may be adjusted to adjust or calibrate the amount of compression in the spring 370 and the amount of force applied thereby onto the second piston 360 (e.g., to change the amount of pressure decrease or reduction produced by the second stage regulator 302).

Adjusting the distances between the expansion body 200 and the intermediate regulator body 220 and/or between the intermediate regulator body 220 and the regulator cap 230 adjusts or calibrates the pressure in the respective chamber 320 and chamber 380 of the first stage regulator 301 and second stage regulator 302, which is required to close first valve 330 and second valve 350. Under some operating conditions, the first piston 310 and the second piston 360 may move in proximal and distal directions, as pressure at the gas outlet 120 and at the respective chamber 320 and chamber 380 changes, such as to operate or open and close the first valve 330 and second valve 350 to increase the pressure in the chamber 320 and chamber 380 (and at the gas outlet 120) to the calibrated or selected pressure.

## 13

Again, the pressure in the chamber 320 and/or in the chamber 380 may be similar to or the same as the outlet pressure at the gas outlet 120. Hence, adjusting the forces applied onto the first piston 310 and/or second piston 360 (e.g., as described above) calibrates the pressure at the gas outlet 120. In an embodiment, a pressure gauge may be included in the pressure-regulating device 100 and/or connected thereto. For example, one or more portions of the pressure gauge may be in fluid communication with the outlet of the second stage regulator 302 and/or with the gas outlet 120. Hence, for example, the pressure-regulating device 100 may be calibrated to produce a selected outlet pressure at the gas outlet 120 by adjusting the forces applied onto the first piston 310 and/or second piston 360 (e.g., by changing compression of the spring 340 and/or spring 370, as described above).

In some embodiments, the pressure-regulating device 100 may include one or more locks that may lock the pressure-regulating device 100 (e.g., preventing gas flow through the first valve 330 and/or second valve 350). For example, the pressure-regulating device 100 may include a lock mechanism 600 that has an outer ring 610 and an inner ring 620 operably connected to the outer ring 610. As described below in more detail, the outer ring 610 may move the inner ring 620 in the distal direction, to engage and move the first piston 310 in the distal direction, such that the first valve 330 is allowed close and remain closed. Moreover, the inner ring 620 may retain the first piston 310 at a distal position, such that the first piston 310 is prevented from engaging and opening the first valve 330. With the first valve 330 closed, gas flow to the gas outlet 120 is stopped.

In the illustrated embodiment, the lock mechanism 600 includes an exterior portion (i.e., the outer ring 610) and an interior portion (i.e., the inner ring 620), which is separated from the exterior portion by a portion of the expansion body 200. Specifically, the outer ring 610 may be positioned near and/or in contact with the first piston 310. It should be appreciated, however, that the interior portion of the lock mechanism 600 (i.e., the inner ring 620) is located outside of an airtight or sealed environment (e.g., outside of the chamber 320). Hence, the connection between the outer ring 610 and the inner ring 620 does not have to be airtight, to maintain the pressure in the sealed environment, such as in the chamber 320.

FIGS. 3A and 3B illustrate the lock mechanism 600 at unlocked and locked positions, respectively. Generally, the inner ring 620 may be moved distally to engage the first piston 310 with any number of suitable mechanisms. In an embodiment, the expansion body 200 may include channels 205a, 205b that may guide and secure the outer ring 610 and inner ring 620 in the locked and unlocked positions. Specifically, the inner ring 620 may be connected to the outer ring 610 with connection posts 630a, 630b that may pass through the channels 205a, 205b.

As described below in more detail, the channels 402a, 204b may be slanted or angled along the length of the expansion body 200. For example, rotating the outer ring 610 relative to the expansion body 200, moves the connection posts 603a, 603b along the corresponding channels 205a, 205b; since the channels 205a, 205b are tilted, as the post 603a, 603b move radially about the expansion body 200, due to the tilt of the channels 205a, 205b, the posts also move axially. In an embodiment, the channels 205a, 205b may be tilted such that clockwise rotation advances the connection posts 603a, 603b together with the inner ring 620 in the distal direction (as shown in FIGS. 3A-3B), thereby locking or securing the first piston 310 in the locked posi-

## 14

tion, to prevent gas flow through the first valve 330. Conversely, rotating the outer ring 610 in the counterclockwise direction may advance the connection posts 603, 603b together with the inner ring 620 in the proximal direction, thereby unlocking the first piston 310, and allowing the gas to flow through the first valve 330, as may be regulated by the first piston 310 (as described above).

It should be appreciated that the channels may have suitable orientations, such that rotating the outer ring 610 clockwise would unlock the first piston 310 and rotating the outer ring 610 counterclockwise would lock the first piston 310. Moreover, additional or alternative suitable lock mechanisms may be included in the pressure-regulating device. Suitable lock mechanisms include threaded mechanism with slidable connectors, toggle locks, etc.

FIGS. 4A-4C illustrate the expansion body 200. For example, FIG. 4A is a side, perspective view of the expansion body 200, oriented such that the channel 205a is visible; FIG. 4B is a distal perspective view of the expansion body 200; and FIG. 4C is a proximal perspective view of the expansion body 200. As shown in FIGS. 4A-4B, the channels 205a, 205b are slanted axially. Moreover, the slant of the channel 205a is such that the connection posts 630a, 630b (FIGS. 3A-3B) may travel a suitable distance, such that the inner ring of the lock mechanism moves between locked and unlocked positions (as described above).

For ease of description, the following describes only a single channel, the channel 205a. It should be appreciated, however, that the channel 205b (FIG. 4B) may be located on an opposite side to the channel 205a and may be the same as the channel 205b. Moreover, channels 205a, 205b may have the orientation such that the radial movement of the opposing connection posts (as the outer ring rotates) produces the same axial movement thereof.

In the illustrated embodiment, the expansion body 200 may have protrusions 205a', 205a" that extend into the channel 205a. For example, the protrusion 205a' may be positioned near an upper end of the channel 205a, such that the connecting post may pass the protrusion 205a' and may be prevented thereby from moving along the channel 205a (e.g., the protrusion 205a' may selectively retain the lock mechanism in the unlocked position). Similarly, the protrusion 205a" may be positioned near the lower end of the channel 205a, such that the connecting post may pass the protrusion 205a" and may be selectively secured thereby (e.g., such that the lock mechanism is selectively secured in the locked position). It should be appreciated that any number of suitable elements and/or mechanisms may secure the lock mechanism in the locked and/or unlocked position (e.g., notches, set screws, detent mechanisms, etc.).

Generally, the lock mechanism may be located at any suitable location on the pressure-regulating device. In an embodiment, the lock mechanism may be positioned near the first valve (e.g., near the distal end of the expansion body 200). For example, the channel 205a may be located near the threaded wall 204 and/or orifice 202 of the expansion body 200. In additional or alternative embodiments, the lock mechanism may be positioned farther from the distal end of the expansion body 200.

The expansion body 200 defines the expansion chamber 210 (FIG. 4C). For example, the expansion body 200 may include at least one wall 206 (e.g., generally cylindrical, tubular wall) that partially defines the expansion chamber 210. Moreover, the expansion body 200 may include an end wall 202a, closing off the expansion chamber 210 on a distal end thereof. Moreover, the end wall 202a may define the orifice 202. At the proximal end, the expansion body 200

## 15

may include a connection location (e.g., a thread **207** (FIG. 4C) for connecting a cap, thereby enclosing the expansion chamber **210** on the proximal side thereof.

In some embodiments, the pressure-regulating device may include a baffle or deflector to facilitate gas flow. FIG. **5** is a cross-sectional view of a portion of the pressure-regulating device **100**. As shown in FIG. **5**, the pressure-regulating device **100** includes an inlet deflector **700** secured at the proximal end of the expansion body **200** and enclosing the expansion chamber **210**. For example, the inlet deflector **700** may include a thread that corresponds to and mates with the thread **207**, thereby securing the inlet deflector **700** to the expansion body **200**.

Generally, the inlet deflector **700** may include a solid body **710** that defines the inlet gas inlet **110**. Gas flow through the inlet deflector **700** is shown schematically with the arrows. In the illustrated embodiment, the inlet deflector **700** includes a baffle **720** positioned downstream from the inlet gas inlet **110**. For example, a mounting **721** may secure the baffle **720** to the solid body **710**. The mounting **721** may be operably connected to and/or integrated with the solid body **710**. For example, the mounting **721** may define one or more openings **722** that are operably connected to or in fluid communication with the gas inlet **110** (e.g., gas may flow through the gas inlet **110**, through the openings **722**, about the baffle **720**, and into the expansion chamber **210**). In an embodiment, the openings **722** may be oriented substantially perpendicularly to the flow of gas at the gas inlet **110** (e.g., perpendicularly to the axis of the pressure-regulating device **100**).

Generally, the baffle **720** may have any number of suitable shapes and/or sizes. In an embodiment, the baffle **720** may be disc-shaped. Moreover, the size of the baffle **720** may be such as to leave a suitable space between the edges or periphery thereof and the inner surface of the wall **206** that defines the expansion chamber **210** (e.g., such as to produce suitable gas flow in the gap defined by and between the peripheral shape of the baffle **720** and the inner surface of the expansion chamber **210**).

In an embodiment, the baffle **720** may have an angled or semi-spherical proximal surface **723** (e.g., surface closer to the gas inlet **110**). For example, the proximal surface **723** of the baffle **720** may be oriented at a non-perpendicular angle relative to the direction of flow of the gas at the gas inlet **110** of the pressure-regulating device **100**. Moreover, the solid body **710** may have a distal surface **711** opposite to the proximal surface of the baffle **720**, such as to define a space between the proximal surface of the baffle **720**, through which the gas may flow after exiting the opening **722**. The proximal surface **723** of the baffle **720** may be spaced from the distal surface **711** of the solid body **710** by a suitable distance to facilitate the flow of gas into the expansion chamber **210**.

Generally, the inlet deflector **700** may be sealed against the expansion body **200** on the proximal side thereof (e.g., such that the gas in the expansion chamber **210** is prevented from leaking out on the proximal side of the expansion chamber **210**). In the illustrated embodiment, O-rings form a seal between the outer surface of the inlet deflector **700** and the inner surface of the wall **206**, in the manner that prevents gas from leaking or exiting the expansion chamber **210** on the proximal side of the expansion chamber **210**. It should be appreciated that any number of suitable seals may be formed between the inlet deflector **700** and the expansion body **200** (e.g., the inlet deflector **700** and the expansion body **200** may have tapered pipe thread that may be suitable

## 16

to seal the expansion chamber **210** in the manner that prevents gas from exiting the expansion chamber **210** on the proximal side thereof.

In an embodiment, the gas source may be a gas cartridge (e.g., a CO<sub>2</sub> gas cartridge). Under some operating conditions, the gas cartridge may require penetration to allow the gas contained therein to exit and flow into the pressure-regulating device **100**. For example, the inlet deflector **700** may include a penetrator **730** that may be operably secured thereto and/or integrated therewith. The penetrator **730** may penetrate the gas cartridge seal to allow the gas in the gas cartridge to flow into the gas inlet **110**. The penetrator **730** may be hollow and may be fluidly connected to and/or define at least a portion of the gas inlet **110**.

Moreover, the inlet deflector **700** may include a seal located near and/or around the penetrator. For example, an O-ring **740** may surround the penetrator **730** and may seal about the gas cartridge, thereby preventing or limiting gas leakage between the gas cartridge and the penetrator **730** (e.g., such that the gas is forced to flow into the gas inlet **110**).

As mentioned above, the gas may flow from the expansion chamber **210** into the hollow protrusion **201** of the first valve **330**. In an embodiment, the pressure-regulating device **100** may include a regulator-inflow member **800** operably connected to the hollow protrusion **201**. Generally, the regulator-inflow member **800** may extend outward from the protrusion **201** and from the first valve **330**, in the proximal direction, into the expansion chamber **210**.

For example, the regulator-inflow member **800** may have a wall **801** that defines a passageway **802**, through which gas in the expansion chamber **210** may flow toward and/or into the first valve **330**. The regulator-inflow member **800** may have any number of suitable shapes. For example, the regulator-inflow member **800** may be a tapered tube (e.g., a conical tapered tube), such that at a proximal end (i.e., at the location for entry of the gas from the expansion chamber **210**), the regulator-inflow member **800** and the opening therein is narrower than at locations distally therefrom.

The regulator-inflow member **800** may be connected and/or secured to the hollow protrusion **201** with any number of suitable mechanisms. In the illustrated embodiment, the regulator-inflow member **800** includes a socket **803** that may wrap about at least a portion of the hollow protrusion **201**. For example, the hollow protrusion **201** may have a generally cylindrical outer surface; the socket **803** may have a complementary shape to the hollow protrusion **201** and may at least partially seal thereabout, such as to direct the gas in the expansion chamber **210** into the pressure regulator (e.g., into the first valve **330**).

Generally, any gas source may be operably connected to the pressure-regulating device **100**, to supply the gas into the expansion chamber **210**. As described above, in at least one embodiment, a gas cartridge may be connected to the pressure-regulating device **100**. FIG. **6** is a cross-sectional view of a portion of the pressure-regulating device **100**, near the proximal end thereof. In the illustrated embodiment, the pressure-regulating device **100** includes the gas cartridge cap **500** that is generally shaped and sized to house a complementary-shaped gas cartridge. For example, the gas cartridge cap **500** may be secured to the expansion body **200** of the pressure-regulating device **100**, thereby securing the gas cartridge to the pressure-regulating device **100** (e.g., such as to maintain the seal with the O-ring **840**).

In an embodiment, the gas cartridge cap **500** includes a threaded section **501**, and the expansion body **200** includes a correspondingly threaded section **208** (e.g., the threaded

17

section **501** of the gas cartridge cap **500** may have a male thread, and the threaded section **208** of the expansion body **200** may have a female thread). For example, screwing together and/or tightening the gas cartridge cap **500** and the expansion body **200** may secure the gas cartridge to and/or in the pressure-regulating device **100**. Moreover, screwing together and/or tightening the gas cartridge cap **500** and the expansion body **200** may press the gas cartridge against the penetrator **730**, thereby puncturing the seal of the gas cartridge and sealing the gas cartridge against the O-ring **840**.

Referring back to FIGS. 2A-2B, as described above, the pressure-regulating device **100** may include the first stage regulator **301** and second stage regulator **302**. Generally, the pressure-regulating device **100** may have any number of stages. Moreover, the pistons for one or more of the stage regulators of the pressure-regulating device **100** may have any number of suitable shapes and/or configurations. For example, the pistons of the first and/or second stage regulators of the pressure-regulating device **100** may have greater surface area on the proximal side thereof than on the distal side thereof. Additionally or alternatively, the pistons may have one or more passageways therethrough, to allow or facilitate gas flow through the piston and to the next stage or to the gas outlet **120** of the pressure-regulating device **100**.

FIGS. 7A-7E illustrate the first piston **310** of the first stage regulator, according to an embodiment. FIG. 7A is a view of the proximal side **311a** of the first piston **310**; FIG. 7B is a view of an enlarged portion of the proximal side **311a** of the first piston **310**. FIG. 7C is a view of the distal side **311b** of the first piston **310**; FIG. 7D is a view of an enlarged portion of the distal side **311b** of the first piston **310**. FIG. 7E is a cross-sectional view of the first piston **310**.

In an embodiment, the first piston **310** includes multiple passages **312** defined between a center stem **313** and alternating recessed surfaces **314** and raised surfaces **315**. The recessed surfaces **314** and raised surfaces **315** may be recessed from a top surface **318** of the first piston **310** on the proximal side **311a** thereof. Moreover, the recessed surfaces **314** and raised surfaces may define a bottom (e.g., an uneven bottom) of a recess **319** (e.g., the recessed surfaces **314** and the raised surfaces **315** may be recessed from the top surface by different distances).

In the illustrated embodiment, the first piston **310** includes three passageways **312**. The passageways **312** may be formed between the recessed surfaces **314** and the center stem **313**. Moreover, the passageways **312** may connect to an outlet passageway **316** (e.g., after exiting from the outlet passageway **316**, the gas may flow to the subsequent stage). It should be also appreciated that the first piston **310** may have any number of passageways. In the illustrated embodiment, the total surface area of the proximal side **311a**, which is oriented generally perpendicularly to the movement of the first piston **310**, lies inside the outer circumference **311a'** (FIG. 7E). The total surface area of the distal side **311b**, which is oriented generally perpendicularly to the movement of the first piston **310**, lies inside the outer circumference of the **311b'** (FIG. 7E).

As described above, a portion of the first piston **310** may be sized and configured to fit into the orifice **202** (FIGS. 2A-2B). For example, at least part of the center stem **313** may be sized and configured to fit into the orifice. In the illustrated embodiment, an upper portion **313a** of the center stem **313** is smaller than the lower portion **313b** thereof, and the upper portion **313a** of the center stem **313** is sized and shaped to fit into the orifice.

18

As described above, the first piston **310** may be biased in the proximal direction by a compressed spring. As shown in the illustrated embodiment, the first piston **310** may include a flange **317** that may support the spring. For example, the flange **317** may be suitably sized to support the spring, such that the spring may press against the flange **317** and bias the first piston **310** in the proximal direction.

FIGS. 8A-8B illustrate the second piston **360** of the second stage regulator. FIG. 8A is a top view of the second piston **360**; FIG. 8B is a cross-sectional view of the second piston **360**. Similar to the first piston **310** (FIGS. 7A-7E), the second piston **360** may have a larger surface area on a proximal side **361** of the second piston **360** than on distal side **362**. Moreover, the second piston **360** may include one or more passageways **363** connected to and/or in fluid communication with an outlet passageway **364**. As described above, gas flowing out of the outlet passageway **364** may flow to the gas outlet of the pressure-regulating device (e.g., when the second piston **360** is included in the second stage regulator of the two stage regulator pressure regulator).

In the illustrated embodiment, the total surface area of the proximal side **361**, which is oriented generally perpendicularly to the movement of the second piston **360**, lies inside the outer circumference **361a** (FIG. 8B). The total surface area of the distal side **362**, which is oriented generally perpendicularly to the movement of the second piston **360** lies inside the outer circumference **362a** (FIG. 7E) of the second piston **360**.

In an embodiment, the second piston **360** includes a generally annular recess **365** (e.g., the recess may be defined between top surface **366** and a recessed surface **365a**). Moreover, the second piston **360** may include further recesses that define the passageways **363**, which may be formed by recesses from or in the recessed surface **365a** to lower recessed surface **363a**. Hence, the gas may flow into the recess **366**, into the passageways **363**, and out of the outlet passageway **364** of the second piston **360**.

The second piston **360** may include a center stem **367**; the passageways **363** may be located about the **367**. In the illustrated embodiment, the second piston **360** has three passageways **363**. It should be appreciated that the second piston **360** may have fewer or more than three passageways, in additional or alternative embodiments.

As described above, a portion of the second piston **360** may be sized and configured to fit into the orifice **223** (FIGS. 2A-2B). For example, at least part of the center stem **367** may be sized and configured to fit into the orifice. In the illustrated embodiment, an upper portion **367a** of the center stem **367** is smaller than the lower portion **367b** thereof, and the upper portion of the **367a** is sized and shaped to fit into the orifice.

As described above, the pressure-regulating device may include and/or may be operably coupled to a pressure gauge, such as the pressure gauge **400**, to facilitate calibration of the device. FIGS. 9A-9C illustrate the pressure gauge **400**, according to an embodiment. FIG. 9A is a front view of the pressure gauge **400**; FIG. 9B is a cross-sectional view of the pressure gauge **400** at a first pressure  $P_1$ ; and FIG. 9C is a cross-sectional view of the pressure gauge **400** at a second pressure  $P_2$  that is greater than the first pressure  $P_1$ .

As described above, a portion of the pressure gauge **400** may be defined by the regulator cap **230** (e.g., which may connect to the intermediate regulator body **220** (FIGS. 2A-2B)). An end cap **410** may be connected to the regulator cap **230**, and together, the end cap **410** and regulator cap **230** may enclose and/or secure an indicator piston **420**. Specifi-

19

cally, the gas pressure experienced at the gas outlet **120** may be approximately the same as the pressure experience by the indicator piston **420**.

In the illustrated embodiment, the pressure gauge **400** includes a spring **430** that biases the indicator piston **420** in the proximal direction. The spring **430** may be selected and/or calibrated (e.g., shortened, pre-compressed, etc.) such that the indicator piston **420** moves in the distal direction (or outward relative to the end cap **410**) by a selected amount or distance that corresponds to a selected pressure (e.g., the distance by which indicator piston **420** moves distally in response to application of pressure may be proportional to the applied pressure).

The indicator piston **420** may include a scale **440** thereon (e.g., printed, attached, etc.). As the indicator piston **420** moves outward relative to the end cap **410**, graduations or indications on the scale **440** become visible and may be identified as corresponding to the detected or determined pressure. For example, in FIG. 9B the pressure gauge **400** indicates the first pressure  $P_1$ , and the scale **440** is exposed in the manner that identifies the first pressure  $P_1$  (e.g., to user or operator of the pressure-regulating device); in FIG. 9B the pressure gauge **400** indicates the second pressure  $P_2$ , and the scale **440** is exposed in the manner that identifies the second pressure  $P_2$  ( $P_2 > P_1$ ).

In an embodiment, the pressure gauge **400** includes a pressure seal **450** that may be located at a proximal end of the indicator piston **420** (e.g., near the gas outlet **120**). For example, the pressure seal **450** may seal against the inside wall of the regulator cap **230**, which defines the chamber within which the indicator piston **420** and pressure seal **450** are positioned. For example, the pressurized gas may apply pressure onto the pressure seal **450**, and the pressure seal **450** may apply a force onto the indicator piston **420** in the distal direction (e.g., proportional to the area of the pressure seal **450**). In an embodiment, the indicator piston **420** may be at least partially hollow and one or more portions of the pressure seal **450** may be fitted inside at least a portion of the hollow space or cavity of the pressure seal **450** (thereby connecting together the pressure seal **450** and the indicator piston **420**). In any event the pressure seal **450** may be advanced in the distal direction together with indicator piston **420**, thereby move the indicator piston **420** and exposing the scale **440** thereof, in the manner that indicates the applied pressure (e.g., the pressure at or near the gas outlet **120**).

As described above, the pressure-regulating device may be operably coupled to any number of suitable additional or alternative devices. FIGS. 10A-10B illustrate the pressure-regulating device **100** operably coupled to a pressure cuff pressure-regulating device **1000**. Specifically, any pressure-regulating device described herein, such as the pressure-regulating device **100** may provide compressed gas at a suitable pressure to the pressure cuff pressure-regulating device **1000**. In an embodiment, the pressure cuff pressure-regulating device **1000** may be used to compress one or more elements or devices with a specific or selected pressure (as controlled by the pressure-regulating device **100**). For example, an IV bag of fluid or solution (e.g., for intravenous injection) may be placed inside the pressure cuff pressure-regulating device **1000**, and the pressure cuff pressure-regulating device **1000** may compress the IV bag to produce a suitable flow of the fluid out of the IV bag and to a patient. Hence, for example, instead of a gravity-fed flow of the fluid out of the IV bag, which may require vertically suspending the IV bag, the flow out of the IV bag may be produced by the pressure applied thereon by the pressure-regulating

20

device **1000**, which may be controlled by the pressure-regulating device **100**, as described above.

As described above, the interior surface of expansion body, which defines the expansion chamber, may be generally smooth. Alternatively, the expansion body may have any number of suitable features on the internal surface thereof. FIG. 11 is a cross-sectional view of an expansion body **200c** according to an embodiment. Except as otherwise described herein, elements and features of the expansion body **200c** may be similar to or the same as elements and features of the expansion body **200** (FIGS. 2A-2C).

The expansion body **200c** may have an expansion chamber **210c** defined by a wall **206c**. For example, the wall **206c** may have an inner surface that includes means for increasing thermal equilibrium within fluid of the chamber as the gas flows in the expansion chamber **210c**. The means may include a groove or rib **209c** disposed on the inner surface of the wall **206c**.

The expansion chamber **210c** may further include one or more safety features, such as one or more blow-out ports **205c**. The blow-out ports **205c** are in an orientation to relieve expansion chamber pressure to an intermediate cavity that is open to atmospheric pressure while obstructing the direct path of the relieved pressure stream for human protection in the event of an over pressurization of the expansion chamber.

Generally, the blow-out ports **205c** may be configured to rupture at a selected pressure, to prevent uncontrolled failure of the wall **206c** of the expansion body **200c**. In an embodiment, the blow-out ports **205c** may include one or more stress-concentration or crack-initiation points (e.g., sharp corners), at which the blow-out ports **205c** may start fail (e.g., such that the failure of the blow-out ports **205c** initiates at selected locations or portions thereof).

The spiral rib **209c** may increase the contact time of fluid with the inner surface of the wall **206c** and may increase heat transfer with the gas flowing in the expansion chamber **210c**. While the device illustrated in FIG. 11 includes a spiral rib **209c**, any suitable or similar structure may be disposed on or at least partially define the inner surface of the wall **206c**.

As described above, the pressure-regulating device may include a lock mechanism that has inner and outer rings. FIGS. 12A-12C illustrate outer ring **610**, and FIGS. 12D-12E illustrate inner ring **620** according to an embodiment.

As described above, the lock mechanism may include the outer ring **610**, the inner ring **620**, and the connection posts **630a**, **630b** connecting together the outer ring **610** and inner ring **620**. As shown in FIGS. 12D-12E, the inner ring **620** may include openings **625a**, **625b** that correspond to the connection posts **630a**, **630b**. For example, the connection posts **630a**, **630b** may be integrated with the outer ring **610** and may align with and may be sized and shaped to fit into the corresponding ones of the openings **625a**, **625b**. After positioning the inner ring **620** at the suitable position in the pressure-regulating device, the outer ring **610** may be positioned over the inner ring **620** (as described above), and the connection posts **630a**, **630b** may enter the openings **625a**, **625b**, thereby securing together the outer ring **610** and inner ring **620**.

In an embodiment, the outer ring **610** may include two portions, first portion **610a** and a second portion **610b**, as shown in FIGS. 12A-12C. For example, the first and second portions **610a**, **610b** may snap together (e.g., to facilitate assembly of the lock mechanism). As shown in FIG. 12C, the first portion **610a** may include a catch **611a** and a snap-hook outer ring **612a**. The second portion **610b** may have complementary snap-hook that snaps over the catch

## 21

611a and a complementary catch that receives the snap-hook 612a of the first portion outer ring 610a. For example, the connection posts 630a, 630b may be aligned with and/or inserted into the corresponding openings 625a, 625b, and thereafter the first and second portions 610a, 610b may be snapped and secured together. It should be also appreciated that the first and second portions 610a, 610b may be connected together with any number of suitable connection mechanisms.

In an embodiment, the inner ring 620 may include two or more peaks, such as peaks 621a-621c at an edge thereof. The peaks 621a-621c may engage the first stage regulator piston (as described above). For example, recessing edge portions adjacent to the peaks 621a-621c (e.g., such as to form or define the peaks 621a-621c) may provide a reduce area of contact with the piston (as compared with a continuous edge without recesses, which may reduce frictional forces between the inner ring 620 and the piston, thereby facilitating ease of rotating the outer ring 610 relative to the piston.

As described above, a regulator-inflow member may be mounted upstream from the first valve. FIG. 13 is a cross-sectional view of a regulator-inflow member 800a according to an embodiment. Except as otherwise described herein, elements and features of the regulator-inflow member 800a may be similar to or the same as elements and features of the regulator-inflow member 800 (FIG. 5). For example, the regulator-inflow member 800a may include a socket 803a that may be similar to the socket 803 (FIG. 5).

In the illustrated embodiment, the regulator-inflow member 800a includes a passageway 802a that is capped at the proximal end thereof (e.g., upstream end). Moreover, the regulator-inflow member 800a may include side ports 804a extending through the wall of the regulator-inflow member 800a to the passageway 802a, such that gas may flow through the side ports 804a and into the passageway 802a. Generally, the side ports 804a and/or the passageway 802a may have any number of suitable shapes and/or sizes, which may vary from one embodiment to the next.

Furthermore, the regulator-inflow member 800a may include a front baffle 805a. Generally, the baffle 805a may have any number of suitable shapes and sizes. In an embodiment, the baffle 805a may be generally disk-shaped. In additional or alternative embodiments, the baffle 805a may be square, oval, etc.

In the illustrated embodiment, the baffle 805a is positioned proximally or upstream from the side ports 804a. In some embodiments, the regulator-inflow member may have multiple baffles. FIG. 14 is a cross-sectional view of a regulator-inflow member 800b according to an embodiment. Except as otherwise described herein, elements and features of the regulator-inflow member 800b may be similar to or the same as elements and features of the regulator-inflow member 800a (FIG. 13). For example, the regulator-inflow member 800b may include a passageway 802b, side ports 804b in fluid communication with the passageway 802b, and may further include a front baffle 805b. In the illustrated embodiment, the regulator-inflow member 800b includes a back or secondary baffle 806b that may be positioned downstream or in the distal direction from the baffle 805b. In some embodiments, the baffles 805b and 806b may be positioned such that the side ports 804b are located therebetween (e.g., the centers of the side ports 804b may be equidistantly spaced from opposing surfaces of the baffles 805b, 806b).

As described above, the inlet deflector may have any number of suitable shapes and/or configurations. FIG. 15 is

## 22

a perspective view of an inlet deflector 700a according to an embodiment. Except as otherwise described herein, elements and features of the inlet deflector 700a may be similar to or the same as the elements and features of the inlet deflector 700 (FIG. 5). For example, the inlet deflector 700a includes a baffle 720a (similar to the baffle 720 of the inlet deflector 700 (FIG. 5)).

In the illustrated embodiment, the baffle 720 includes cutouts 725a. Generally, the cutouts 725a may have any number of suitable shapes and/or sizes. Moreover, the baffle 720a may have any number of cutouts 725a thereon. For example, increasing the size and/or the number of cutouts 725a may decrease the gas flow velocity relative to the baffle 720a.

The present invention may be embodied in other specific forms without departing from its spirit or essential characteristics. The described embodiments are to be considered in all respects only as illustrative and not restrictive. The scope of the invention is, therefore, indicated by the appended claims rather than by the foregoing description. All changes that come within the meaning and range of equivalency of the claims are to be embraced within their scope.

We claim:

1. A pressure-regulating device comprising:

a gas inlet;

an expansion body defining an expansion chamber that is in fluid communication with the gas inlet, the expansion body comprising a hollow protrusion extending, from a distal wall of the expansion body, upstream into the expansion chamber;

at least one pressure regulation stage in fluid communication with the expansion chamber and configured to decrease gas pressure of a gas passing through the at least one pressure regulation stage, wherein the at least one pressure regulation stage includes a valve, wherein an upstream opening of the hollow protrusion located within an interior of the expansion chamber communicates gas from the interior of the expansion chamber to the valve; and

a gas outlet positioned downstream from and in fluid communication with the at least one pressure regulation stage, and wherein the at least one pressure regulation stage comprises a first pressure regulation stage, wherein the valve is a first valve, which is part of the first pressure regulation stage, the first pressure regulation stage further comprising a first piston configured to actuate the first valve between an open position and a closed position and a first biasing member biasing the first piston toward an open position of the first valve, wherein the first piston and the first biasing member are secured between a distal end of the expansion body and a proximal end of an intermediate regulator body, and wherein the expansion body and the intermediate regulator body are threadedly coupled such that changing a distance between the distal end of the expansion body and the proximal end of the intermediate regulator body changes an amount of pressure decrease produced by the first pressure regulation stage.

2. The pressure-regulating device of claim 1, wherein hollow protrusion defines a cavity, and wherein the first valve comprises a seal and a sealing member located in the cavity.

3. The pressure-regulating device of claim 2 wherein the seal and sealing member of the first valve are retained within the cavity at least in part by a retainer received in the proximal opening and having a through passage for communicating the gas through the retainer to the first valve.

23

4. The pressure-regulating device of claim 1 further comprising a second pressure regulation stage including a second valve arranged in series with the first valve such that gas flowing out of the first valve is communicated to an inlet of the second valve.

5. The pressure-regulating device of claim 4, wherein the first valve and the second valve are substantially coaxially arranged, with a gas flow path through the pressure-regulating device extending subtile along a longitudinal direction of the pressure-regulating device.

6. The pressure-regulating device of claim 4, wherein the second pressure regulation stage comprising a second piston configured to actuate the second valve between an open position and a closed position, and a second biasing member biasing the second piston toward an open position of the second valve.

7. The pressure-regulating device of claim 4, wherein the second piston and the second biasing element are secured between a distal end of the intermediate regulator body and a cap of the pressure-regulating device.

8. The pressure-regulating device of claim 1, further comprising an inflow member coupled to and extending proximally from the hollow protrusion, the inflow member comprising a passageway for communicating gas from the expansion chamber to the valve.

9. A pressure-regulating device, comprising:

a gas inlet;

an expansion body defining an expansion chamber that is in fluid communication with the gas inlet;

at least one pressure regulation stage configured to decrease gas pressure of a gas flowing therethrough, the at least one pressure regulation stage being in fluid communication with the expansion chamber and comprising:

a valve including a sealing member configured to open and close gas flow through the valve;

a piston movable in upstream and downstream directions relative to the gas inlet and configured to move the sealing member in the manner that opens the valve;

a first biasing member positioned to apply a force onto the piston in the upstream direction; and

an adjustment mechanism including opposing first and second threaded walls, threadedly engaged together to enclose the biasing member therebetween, wherein the piston seals against an inner surface of a first protrusion extending distally from the expansion body and is offset radially inward from the first threaded wall, and wherein the piston further seals against an inner surface of a second protrusion opposite the first protrusion and offset radially inward from the second threaded wall; and

24

a gas outlet positioned downstream from the at least one pressure regulation stage.

10. The pressure-regulating device of claim 9, wherein the first threaded wall extends distally from the expansion body.

11. The pressure-regulating device of claim 9, wherein the expansion body includes a hollow protrusion that extends into the expansion chamber and defines a passage for communicating the gas from the expansion chamber to the valve, and wherein the sealing member is located in the passage.

12. A pressure-regulating device comprising:

an inlet body defining a gas inlet, the inlet body comprising a baffle downstream from the gas inlet;

an expansion body defining an expansion chamber that is in fluid communication with the gas inlet, the expansion body comprising a hollow protrusion extending proximally into the expansion chamber;

a first pressure regulation stage in fluid communication with the expansion chamber and configured to decrease gas pressure of a gas passing through the first pressure regulation stage, wherein the first pressure regulation stage includes a first valve, wherein a proximal opening of the hollow protrusion located within an interior of the expansion chamber communicates gas from the interior of the expansion chamber to the first valve, the first pressure regulation stage further comprising a first piston configured to actuate the first valve between an open position and a closed position and a first biasing member biasing the first piston toward an open position of the first valve;

a second pressure regulation stage including a second valve arranged in series with the first valve such that gas flowing out of the first valve is communicated to an inlet of the second valve; and

a gas outlet positioned downstream from and in fluid communication with the second valve of the second pressure regulation stage.

13. The pressure-regulating device of claim 12, wherein hollow protrusion defines a cavity, and wherein the first valve comprises a seal and a sealing member located in the cavity.

14. The pressure-regulating device of claim 12, wherein the first valve and the second valve are substantially coaxially arranged, with a gas flow path through the pressure-regulating device extending subtile along a longitudinal direction of the pressure-regulating device.

15. The pressure-regulating device of claim 12, wherein the baffle extending radially outward from the gas inlet into a portion of the expansion chamber which is wider than the gas inlet.

\* \* \* \* \*