



US011499489B2

(12) **United States Patent**
Kurtz et al.

(10) **Patent No.:** **US 11,499,489 B2**
(45) **Date of Patent:** **Nov. 15, 2022**

(54) **ANNULAR RING MIXER WITH VANES**

B01F 35/718051 (2022.01); *F02D 9/08* (2013.01); *F02M 26/14* (2016.02); *F02M 26/17* (2016.02); *F02M 26/19* (2016.02); *B01F 2101/501* (2022.01)

(71) Applicant: **Ford Global Technologies, LLC**, Dearborn, MI (US)

(72) Inventors: **Eric Matthew Kurtz**, Dearborn, MI (US); **Liangjun Hu**, Bloomfield Hills, MI (US); **Daniel Joseph Styles**, Canton, MI (US); **Daniel William Kantrow**, Ann Arbor, MI (US); **Darrell Sparks**, Howell, MI (US)

(58) **Field of Classification Search**

CPC *B01F 3/026*; *B01F 5/0403*; *B01F 5/0473*; *B01F 5/0611*; *B01F 15/0261*; *B01F 2215/0085*; *F02D 9/08*; *F02D 41/0077*; *F02M 26/14*; *F02M 26/17*; *F02M 26/19*
See application file for complete search history.

(73) Assignee: **Ford Global Technologies, LLC**, Dearborn, MI (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

4,461,150 A * 7/1984 Grohn *F02M 26/19*
123/568.17
8,056,340 B2 * 11/2011 Vaught *F02B 33/44*
60/605.2

(21) Appl. No.: **17/212,207**

(Continued)

(22) Filed: **Mar. 25, 2021**

FOREIGN PATENT DOCUMENTS

(65) **Prior Publication Data**

US 2022/0307436 A1 Sep. 29, 2022

CN 2050478 U * 1/1990 *F02M 17/14*
JP 6177604 B2 8/2017

(51) **Int. Cl.**

F02D 41/00 (2006.01)
F02M 26/17 (2016.01)
F02M 26/14 (2016.01)
F02D 9/08 (2006.01)
F02M 26/19 (2016.01)
B01F 25/31 (2022.01)
B01F 25/43 (2022.01)
B01F 35/71 (2022.01)
B01F 23/10 (2022.01)
B01F 25/314 (2022.01)
B01F 25/431 (2022.01)
B01F 101/00 (2022.01)

Primary Examiner — Audrey B. Walter

(74) *Attorney, Agent, or Firm* — Vincent Mastrogiamomo; Brooks Kushman, P.C.

(52) **U.S. Cl.**


CPC *F02D 41/0077* (2013.01); *B01F 23/19* (2022.01); *B01F 25/31* (2022.01); *B01F 25/3141* (2022.01); *B01F 25/4311* (2022.01);

(57)

ABSTRACT

An exhaust gas recirculation system for an engine includes a conduit, and a mixer. The conduit is configured to direct to direct exhaust gas away from an exhaust manifold. The mixer is configured to direct exhaust gas from the conduit, into an engine air intake system. The mixer is arranged with an exhaust gas mixing volute chamber having a plurality of mixing vanes configured to direct the exhaust gas into a central intake airflow upstream of an intake manifold.

11 Claims, 7 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

10,012,184 B2 * 7/2018 Guidi F02M 26/06
10,428,711 B2 10/2019 Zhang
2016/0201610 A1 * 7/2016 Dahl F02M 26/19
123/568.17
2019/0017426 A1 1/2019 Zhang et al.
2020/0256266 A1 * 8/2020 Mastbergen F02M 35/10052
2020/0408173 A1 * 12/2020 Zhong F02M 26/70

* cited by examiner




FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 3C






FIG. 3D






FIG. 8




FIG. 9




FIG. 10




FIG. 11

1

ANNULAR RING MIXER WITH VANES

TECHNICAL FIELD

The present disclosure relates to exhaust gas recirculation systems for internal combustion engines.

BACKGROUND

Internal combustion engines may include exhaust gas recirculation systems that are configured to redirect exhaust gas into the air intake system of the engine to reduce emissions.

SUMMARY

A vehicle includes an internal combustion, an air intake system, an exhaust system, and an exhaust gas recirculation system. The internal combustion engine has at least one cylinder. The air intake system is configured to deliver air to the at least one cylinder. The exhaust system has a set of conduits configured to direct exhaust gas away from the at least one cylinder. The exhaust gas recirculation system has a at least one tube, and a mixer. The at least one tube is configured to direct the exhaust gas away from the set of conduits. The mixer is configured to direct the exhaust gas from the at least one tube, into the air intake system. The mixer forms an annular tube or ring that is disposed about an intake tube. The mixer includes at least one vane extending into a flow path of at least one of the exhaust gas and the air intake system. The mixer is configured to blend the exhaust gas and the air prior to introduction into the internal combustion engine.

An exhaust gas recirculation system for an engine includes a conduit, and a mixer. The conduit is configured to direct exhaust gas away from an exhaust manifold. The mixer is configured to direct exhaust gas from the conduit, into an engine air intake system. The mixer is arranged with an exhaust gas mixing volute chamber having a plurality of mixing vanes configured to direct the exhaust gas into a central intake airflow upstream of an intake manifold.

An exhaust gas recirculation mixer for an engine exhaust system includes a housing, an exhaust gas inlet, and at least one mixing vane. The housing forms an annular tube or ring that defines a central opening. The housing further defines an exhaust gas inlet and at least one mixing vane. The at least one mixing vane is configured between the exhaust gas inlet and the annular tube or ring. The at least one mixing vane includes a twist or slope to swirl an exhaust gas exiting the engine.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic illustration of an exemplary vehicle having an internal combustion engine;

FIG. 2 is a perspective view of an exemplary intake system having an air intake tube with a planar throttle body plate and an exemplary mixer for an exhaust gas recirculation system;

FIG. 3A is a side view of an exemplary single twist throttle plate configured in an intake tube;

FIG. 3B is a front view of the exemplary single twist throttle plate of FIG. 3A, configured in an intake tube;

FIG. 3C is a side view of an exemplary double twist throttle plate configured in an intake tube;

FIG. 3D is a front view of the exemplary double twist throttle plate of FIG. 3C, configured in an intake tube;

2

FIG. 4 is a cross-sectional view of the mixer for the exhaust gas recirculation system including fixed twist vanes of FIG. 2 taken along a central vertical plane;

FIG. 5 is a cross-sectional view of the mixer for the exhaust gas recirculation system including fixed twist vanes of FIG. 2 taken along a horizontal plane;

FIG. 6 is a cross-sectional view of the mixer for the exhaust gas recirculation system including fixed straight vanes of FIG. 2 taken along the central vertical plane;

FIG. 7 is a cross-sectional view of the mixer for the exhaust gas recirculation system including fixed straight vanes of FIG. 2 taken along the horizontal plane;

FIG. 8 is a cross-sectional view of the mixer for the exhaust gas recirculation system including fixed inverted vanes of FIG. 2 taken along the central vertical plane;

FIG. 9 is a cross-sectional view of the mixer for the exhaust gas recirculation system including fixed inverted vanes of FIG. 2 taken along the horizontal plane;

FIG. 10 is a cross-sectional view of the mixer for the exhaust gas recirculation system including fixed dynamic vanes of FIG. 2 taken along the central vertical plane; and

FIG. 11 is a cross-sectional view of the mixer for the exhaust gas recirculation system including fixed dynamic vanes of FIG. 2 taken along the horizontal plane.

DETAILED DESCRIPTION

Embodiments of the present disclosure are described herein. It is to be understood, however, that the disclosed embodiments are merely examples and other embodiments may take various and alternative forms. The figures are not necessarily to scale; some features could be exaggerated or minimized to show details of specific components. Therefore, specific structural and functional details disclosed herein are not to be interpreted as limiting, but merely as a representative basis for teaching one skilled in the art to variously employ the embodiments. As those of ordinary skill in the art will understand, various features illustrated and described with reference to any one of the figures may be combined with features illustrated in one or more other figures to produce embodiments that are not explicitly illustrated or described. The combinations of features illustrated provide representative embodiments for typical applications. Various combinations and modifications of the features consistent with the teachings of this disclosure, however, could be desired for specific applications or implementations.

Exhaust gas recirculation is an important method to reduce NOx emissions of an internal combustion engine. With the more stringent emission criteria being established, especially with low NOx emission requirements, there is a strong need to improve the engine exhaust gas recirculation distribution uniformity. To meet the low NOx emission, an annular ring mixer can enable exhaust gas recirculation mixing while minimizing the pressure drop in the main flow of an engine intake. However, since current annular ring mixer devices distribute the exhaust gas over its outer periphery and the exhaust gas is well distributed over the circumference of the duct, it tends to enter the main flow at a primarily tangential velocity, thereby limiting the penetration of the exhaust gas into the main flow of the intake. One method to increase the exhaust gas recirculation drivability is to provide an annular ring mixer that includes a volute having a gradually reducing section area along the azimuthal direction to uniformly distribute and direct the exhaust gas to the main flow. The annular ring mixer may also break up the flow of the exhaust gas through the use of vanes or fins

extending into the flow path of either the exhaust gas or the main intake flow thereby creating a mixing of the exhaust gas at a central path in the main flow.

In the current disclosure, an annular ring mixer design having a volute that may include a gradually reducing section area along the azimuthal direction to uniformly distribute and direct an exhaust gas to a main intake air flow is proposed. The annular ring mixer may include at least one vane or fin configured internally that may direct or guide the exhaust gas flowing through the volute toward a center of the main intake air flow is also proposed. The main goal is to enable improved exhaust gas mixing while maintaining the use of an annular ring mixer for reduced intake air pressure loss. The exhaust gas recirculation flow is diverted from the engine and cooled in an exhaust gas recirculation cooler. Then the cooled exhaust gas recirculation flows are introduced into the annular ring exhaust gas recirculation mixer. The exhaust gas recirculation flows do not mix with each other before mixing with the main air flow of the air intake system of the engine. Introducing the exhaust gas recirculation flows into the main air flow reduces the mixing losses and helps to maintain the pulsation energy, which increases the exhaust gas recirculation drivability and the penetration of the exhaust gas recirculation flow into the main air flow of the air intake system.

Referring to FIG. 1, a schematic illustration of an exemplary vehicle **10** having an internal combustion engine **12** is illustrated. The engine **12** may be configured to provide power and torque to wheels to propel the vehicle **10**. The engine **12** may include any known configuration of cylinders such as, but not limited to a single cylinder bank engine having a single or a plurality of cylinders or a double cylinder bank engine having a plurality of cylinders, each bank of the double bank having an equal number of cylinders. The engine **12** may include any known configuration of two cylinders, three cylinders, four cylinders, six cylinders or other known vehicle engine configurations. As illustrated in the exemplary vehicle **10**, the engine **12** includes a first bank of cylinders **14** and a second bank of cylinders **16**.

The engine **12** includes an air intake system **18**. The air intake system **18** includes a set of pipes, tubes, or conduits **20** that are configured to deliver an air supply to each cylinder to provide the oxygen required for the combustion of fuel. The set of pipes, tubes, or conduits **20** may include one or more first intake pipes tubes or conduits **25** housing a throttle valve **28**, one or more second air intake pipes tubes or conduits **26** directly connected to one or more air intake manifolds **22**, the intake manifolds **22** directly deliver the air into each cylinder. The first intake pipe, tube, or conduit **25** of the set of pipes, tubes, or conduits **20** may draw air directly from an ambient environment or may receive air from a compressor **21** of a turbocharger **24** or supercharger. If a turbocharger **24** or supercharger is delivering air the air intake system **18**, the air may first be sent to a charge air cooler **60**. From the charge air cooler **60**, the air may then pass by the throttle valve **28**, through the air intake manifolds **22** and into the cylinders of the first bank of cylinders **14** and of the second bank of cylinders **16**. The throttle valve **28** is adjusted by an operator of the vehicle **10** by depressing an accelerator pedal (not shown) in conjunction with an adjustment to the amount of fuel being delivered into the cylinders based on a power or torque demand of the engine **12** or the wheels of the vehicle **10**, which is interpreted by a controller (not shown) based on a position of the accelerator pedal.

The controller may be a powertrain control unit (PCU), may be part of a larger control system, and may be con-

trolled by various other controllers throughout the vehicle **10**, such as a vehicle system controller (VSC). It should therefore be understood that the controller and one or more other controllers can collectively be referred to as a “controller” that controls various actuators in response to signals from various sensors to control functions such as starting/stopping the engine **12**, operating the engine **12** to provide wheel torque, select or schedule shifts of a transmission of the vehicle **10**, etc.

The controller may include a microprocessor or central processing unit (CPU) in communication with various types of computer readable storage devices or media. Computer readable storage devices or media may include volatile and nonvolatile storage in read-only memory (ROM), random-access memory (RAM), and keep-alive memory (KAM), for example. KAM is a persistent or non-volatile memory that may be used to store various operating variables while the CPU is powered down. Computer-readable storage devices or media may be implemented using any of a number of known memory devices such as PROMs (programmable read-only memory), EPROMs (electrically PROM), EEPROMs (electrically erasable PROM), flash memory, or any other electric, magnetic, optical, or combination memory devices capable of storing data, some of which represent executable instructions, used by the controller in controlling the engine **12** or vehicle **10**.

As illustrated, the engine **12** also includes an exhaust system **30**. The exhaust system **30** is configured to direct exhaust gas away from the cylinders of the engine **12**. The exhaust system **30** includes a first set of exhaust gas pipes, tubes, or conduits **32** that are configured to direct exhaust gas away from the first bank of cylinders **14**. The first set of exhaust pipes, tubes, or conduits **32** may include a first exhaust manifold **34** that directly receives the exhaust gas from the first bank of cylinders **14**. The exhaust system **30** may include a second set of exhaust pipes, tubes, or conduits **36** that are configured to direct exhaust gas away from the second bank of cylinders **16**. The second set of exhaust pipes, tubes, or conduits **36** may include a second exhaust manifold **38** that directly receives the exhaust from the second bank of cylinders **16**. The exhaust gas is channeled to one or more tail pipes (not shown), via the first set of exhaust pipes, tubes, or conduits **32** and the second set of exhaust pipes, tubes, or conduits **36**, wherein the exhaust gas is dumped into the ambient environment outside the vehicle **10**. At least one intermediate component of the exhaust system **30** may be disposed between the exhaust manifolds **34**, **38** and the one or more tailpipes (not shown). Such intermediate component may include one or more mufflers, one or more catalytic converters, and a turbine **40** if the vehicle **10** includes the turbocharger **24**, etc.

The engine **12** also include an exhaust gas recirculation system **42**. The exhaust gas recirculation system **42** may include a first exhaust gas recirculation pipe, tube, or conduit **44** that is configured to direct a first portion of the exhaust gas away from the first set of exhaust pipes, tubes, or conduits **32** of the exhaust system **30**. More specifically, the first exhaust gas recirculation pipe, tube, or conduit **44** may be configured to direct the first portion of the exhaust gas away from the first exhaust manifold **34**, thereby directing the first portion of exhaust gas away from the first bank of cylinders **14**. The first exhaust gas recirculation pipe, tube, or conduit **44** may be comprised of one or more pipes, tubes, or conduits. A first exhaust gas recirculation valve **46** may be disposed along the first exhaust gas recirculation pipe, tube, or conduit **44** to control the amount of exhaust flowing through the first exhaust gas recirculation pipe, tube, or

5

conduit **44**. The first exhaust gas recirculation pipe, tube, or conduit **44** directs the first portion of the exhaust gas into an exhaust gas recirculation cooler **48**. The first portion of the exhaust gas is then directed toward a mixer **50** via a second pipe, tube, or conduit **45**.

The exhaust gas recirculation system **42** may include a third exhaust gas recirculation pipe, tube, or conduit **52** that is configured to direct a second portion of the exhaust gas away from the second set of pipes, tubes, or conduits **36** of the exhaust system **30**. More specifically, the third exhaust gas recirculation pipe, tube, or conduit **52** may be configured to direct the second portion of the exhaust gas away from the second exhaust manifold **38**, thereby directing the second portion of exhaust gas away from the second bank of cylinders **16**. The third exhaust gas recirculation pipe, tube, or conduit **52** may be comprised of one or more pipes, tubes, or conduits. A second exhaust gas recirculation valve **53** may be disposed along the third exhaust gas recirculation pipe, tube, or conduit **52** to control the amount of exhaust flowing through the third exhaust gas recirculation pipe, tube, or conduit **52**. The third exhaust gas recirculation pipe, tube, or conduit **52** directs the second portion of the exhaust gas into the exhaust gas recirculation cooler **48**. The first and second portions of the exhaust gas may be combined into a single flow path in the exhaust gas recirculation cooler **48** or the first and second portions of exhaust gas may be segregated from each other when passing through the exhaust gas recirculation cooler **48**. The second portion of the exhaust gas is then directed toward the mixer **50** via a fourth pipe, tube, or conduit **54**. The fourth pipe, tube, or conduit **54** may be comprised of one or more pipes, tubes, or conduits.

It should be understood that the second pipe, tube, or conduit **45** and the fourth pipe, tube, or conduit **54** may be directly connected to the mixer **50** or alternatively the second and fourth conduits may be connected to the mixer **50** through a Y-pipe, Y-tube or Y-conduit **58** as the mixer **50** may include a single inlet port **62**. The mixer **50** then delivers the first and second portion of the exhaust gas into the pipes, tubes, or conduits **26** of the air intake system **18** as a homogenous exhaust gas. The mixer **50** then delivers the homogenous exhaust gas into the pipes, tubes, or conduits **26** of the air intake system **18**.

Referring to FIGS. **2** through **5**, an exemplary embodiment of a mixer **100** for an exhaust gas recirculation system is illustrated. The embodiment of the mixer **100** may correspond to mixer **50** in FIG. **1**. The mixer **100** is configured to direct and homogenize the exhaust gas from the second pipe, tube, or conduit **44**, the fourth pipe, tube, or conduit **54**, or the Y-pipe, Y-tube, or Y-conduit **58**, with the intake air coming from the ambient environment or the charge air cooler **60**. As discussed previously, the intake air or a central airflow **64** enters the mixer **100** from the first intake pipes tubes or conduits **25**, exiting the central airflow **64** past at least one exhaust gas outlet **112** configured about an annular tube or ring **104** to introduce the exhaust gas into the air intake pipes, tubes, or conduits **26** of the air intake system **18** enabling better mixing efficiency of the exhaust gases while minimizing any pressure drop across the system.

The mixer **100** includes a housing **102** defining a mixer volute **106** extending between an exhaust gas inlet **110** and the at least one exhaust gas outlet **112**. The mixer volute **106** may include a first end **118** having a first circumference and a gradually reducing section area along an azimuthal direction extending to a second end **130** having a second circumference, the second end **130** second circumference being smaller than the first end **118** first circumference. The mixer volute **106** includes the two different sized first end **118** and

6

second end **130** to uniformly distribute and direct the exhaust gas to the main intake air flow **64** to promote turbulence allowing for a more thorough mixing of the exhaust gas with the main intake air flow **64**. The annular tube **104** may comprise one of the pipes, tubes, or conduits **20** and the air intake pipes, tubes, or conduits **26** of the air intake system **18** configured downstream of the throttle valve **28** and upstream of the intake manifolds **22**. As specifically illustrated in FIGS. **2-3D**, the throttle valve **28** may include at least one of a substantially planar disc throttle plate **72**, a single side twist disc throttle plate **82** and a double side twist disc throttle plate **92**. With specific reference to FIG. **2**, the substantially planar disc throttle plate **72** is shown. The substantially planar disc throttle plate **72** is attached to a pivot shaft **74**, the substantially planar disc throttle plate **72** may be removably attached with a threaded fastener **70** or permanently attached via a rivet or other known mechanical attachment method. The pivot shaft **74** may be configured to extend through a side wall of the intake tube **25** or an aperture (not illustrated) may be used to gain access to an end of the pivot shaft **74**.

As illustrated in FIG. **2**, the pivot shaft **74** is extending through and support by the intake tube **25** along a central plane (not shown) of the intake tube **25** such that the pivot shaft **74** and the attached substantially planar disc throttle plate **72** are centered in the intake tube **25**. The exposed end of the pivot shaft **74** may be connected to any known rotational actuation device to rotate the pivot shaft **76** thereby opening and closing the throttle valve **28** allowing the throttle plate **72** to vary the volume of the central airflow **64** flowing into the mixer **50**, such that when the substantially planar disc throttle plate **72** is rotated to a vertical position the central air flow **64** is blocked and when the substantially planar disc throttle plate **72** transitioned from the vertical position the central air flow **64** can flow across the substantially planar disc throttle plate **72** and through the mixer **50**, as discussed above.

Turning to FIGS. **3A** and **3B**, a single twist throttle plate **82** is illustrated. The single twist throttle plate **82** includes a substantially planar side and a sloped/twisted side **86**, the sloped/twisted side allows the central air flow **64** to be lifted or interrupted as the central air flow **64** moves from the intake tube **25** and into the central opening **116**, **216** and **316** of the mixer **50**. This lift may create turbulence within the air intake tube **25** and ultimately promote additional blending of the exhaust gas as the central air flow **64** passes through the mixer **50**. The sloped/twisted side **86** may transition upward or downward from the substantially planar side at about a midsection of the single twist throttle plate **82** adjacent the mechanical fasteners **70**, which attach the single twist throttle plate **82** to the pivot shaft **84**.

FIGS. **3C** and **3D** illustrate the double side twist disc throttle plate **92**. The double side twist disc throttle plate **92** may include a substantially planar midsection where the pivot shaft **94** is attached. A first sloped/twisted side **96** may transition upward or downward from substantially planar midsection while the second sloped/twisted side **98** is positioned at an opposite side of the pivot shaft **94** and may transition upward or downward from the substantially planar midsection. Further, when the first sloped/twisted side **96** is transition upward the second sloped/twisted side **98** will be positioned downward and when the first sloped/twisted side **96** is transition downward the second sloped/twisted side **98** will be positioned upward such that the two sides **96**, **98** may transition in opposite directions. However, it is contemplated that the upward and downward positions may be in any configuration including in the same direction that allows

the central air **64** to flow across the two sides **96, 98** and creates an interrupted air flow to promote swirling within the mixer **50** to blend the exhaust gases with the central air flow **64**.

The annular tube **104** may include an inner diameter **114** defining a central opening **116** and encompassing the central airflow **64**. Additionally, an at least one vane or fin **120** may extend out from the annular tube **104** protruding inwardly and away from the inner diameter **114** of the central opening **116** toward the central airflow **64**. The at least one exhaust gas outlet **112** may be a single aperture or a plurality of apertures divided by at least one vane or fin **120** extending across the at least one gas outlet **112**. The exhaust gas outlet **112** allows the exhaust gas to exit the mixer volute **106** flowing into the central airflow **64** of the air intake system **18** while flowing over and around a vane or fin outer surface **122**.

The vane or fin **120** is an obstruction that may extend into the flow path of the exhaust gas and the central airflow **64**. The exhaust gas may flow over and around the vane or fin outer surface **122** allowing the vane or fin outer surface **122** to project and disrupt the flow of the exhaust gas thereby providing further mixing and stirring of the entrained exhaust gas with the central airflow **64** to homogenize the intake air entering the intake manifold **22** of the combustion engine **12**. The at least one vane or fin **120** may be a single vane or fin or a plurality of vanes or fins configured radially about the annular tube **104**. The vane or fin **120** may be configured linearly extending across the exhaust gas outlet **112** along an axis of the annular tube **104** or the vane or fin **120** may be positioned at an angle or twist as illustrated at least in FIGS. **4** and **5** or it may be configured as a straight vane or fine **124** as illustrated in FIGS. **6** and **7**. Additionally, it should be understood that the angle of the twist may and a slope of the vane or fins **120, 124** may affect the velocity of the exhaust gas or the central airflow **64** by increasing or decreasing as desired for a specific application.

Referring to FIGS. **8** and **9**, a second embodiment of a mixer **200** for an exhaust gas recirculation system is illustrated. The mixer **200** may correspond to mixer **50** in FIG. **1**. The mixer **200** is configured to direct and homogenize the exhaust gas from the second pipe, tube, or conduit **44**, the fourth pipe, tube, or conduit **54**, or the Y-pipe, Y-tube, or Y-conduit **58**, with the intake air coming from the ambient environment or the charge air cooler **60**. Similarly as discussed previously, the intake air or the central airflow **64** enters the mixer **200** from the set of pipes, tubes, or conduits **20**, exiting the central airflow **64** through at least one exhaust gas outlet **212** configured about and annular tube **204** to introduce the exhaust gas into the air intake pipes, tubes, or conduits **26** of the air intake system **18** enabling better mixing efficiency of the exhaust gases with minimized pressure drop across the system.

The mixer **200** includes a housing **202** defining a mixer volute **206** extending between an exhaust gas inlet **210** and the at least one exhaust gas outlet **212**. The annular tube **204** may comprise one of the pipes, tubes, or conduits **20** and the air intake pipes, tubes, or conduits **26** of the air intake system **18** configured downstream of the throttle valve **28** and upstream of the intake manifolds **22**. The annular tube **204** may include an inner diameter **214** defining a central opening **216** and encompassing the central airflow **64**. Additionally, an at least one vane or fin **220** may extend from the annular tube **204** protruding inwardly into the mixer volute **206** from the inner diameter **214** of the central opening **216**. The at least one exhaust gas outlet **212** may be a single aperture or a plurality of apertures divided by the at least one

vane or fin **220** extending across the at least one gas outlet **212**. The exhaust gas outlet **212** allows the exhaust gas to exit the mixer volute **206** flowing into the central airflow **64** of the air intake system **18** while flowing over and around a vane or fin outer surface **222**.

The vane or fin **220** is an obstruction that may extend outward toward the housing **202** extending into the flow path of the exhaust gas in the mixer volute **206**. As the exhaust gas flows through the mixer volute **206** and over the vane or fin outer surface **222** the exhaust gas flow may be disrupted and directed radially inward of the mixer **200** and into the central airflow **64**. The vane or fin **220** further providing homogenization through turbulence of the exhaust gas as it enters the central airflow **64** to promote mixing between the entrained exhaust gas and the intake air entering the intake manifold **22** of the combustion engine **12**. The at least one vane or fin **220** may be a single vane or fin or a plurality of vanes or fins configured radially about the annular tube **204**. The vane or fin **220** may be configured linearly extending straight across the exhaust gas outlet **212** along an axis of the annular tube **204** or the vane or fin **220** may be positioned at an angle or twist. Additionally, it should be understood that the angle of the twist and a slope of the vane or fine **220** may affect the velocity of the exhaust gas or the central airflow **64** by increasing or decreasing as desired for a specific application.

Referring to FIGS. **10** and **11**, a third embodiment of a mixer **300** for an exhaust gas recirculation system is illustrated. The mixer **300** may correspond to mixer **50** in FIG. **1**. The mixer **300** is configured to direct and homogenize the exhaust gas from the second pipe, tube, or conduit **44**, the fourth pipe, tube, or conduit **54**, or the Y-pipe, Y-tube, or Y-conduit **58**, with the intake air coming from the ambient environment or the charge air cooler **60**. Similarly as discussed previously, the intake air or the central airflow **64** enters the mixer **300** from the set of pipes, tubes, or conduits **20**, exiting the central airflow **64** through at least one exhaust gas outlet **312** configured about and annular tube **304** to introduce the exhaust gas into the air intake pipes, tubes, or conduits **26** of the air intake system **18** enabling better mixing efficiency of the exhaust gases with minimized pressure drop across the system.

The mixer **300** includes a housing **302** defining a mixer volute **306** extending between an exhaust gas inlet **310** and the at least one exhaust gas outlet **312**. The annular tube **304** may comprise one of the pipes, tubes, or conduits **20** and the air intake pipes, tubes, or conduits **26** of the air intake system **18** configured downstream of the throttle valve **28** and upstream of the intake manifolds **22**. The annular tube **304** may include an inner diameter **314** defining a central opening **316** and encompassing the central airflow **64**. Turning specifically to FIG. **10**, an exemplary at least one dynamic vane or fin **320** is illustrated. The at least one dynamic vane or fin **320** may be a plurality of at least one dynamic vane or fins **320** that may rotatably extend out from the annular tube **304**. The at least one dynamic vane or fin **320** may be configured radially about the annular tube **304** in a rotatable and overlapping configuration to at least partially or fully close of the flow of exhaust gas. The at least one dynamic vane or fin **320** may be manually adjustable and set to a preconfigured and fixed angle. Alternatively, the at least one dynamic vane or fin **320** may be configured to rotate and adjust the angle of the at least one dynamic vane or fin **320** relative to the exhaust gas outlet **312**. Thus, in order to rotate, the at least one dynamic vane or fin **320** may be pinned or rotatably affixed to the annular tube **304** at a first end **324** with a movable second end **326** allowing the at least

one dynamic vane or fin **320** to rotate about an arc **328** and control the exhaust gas flow by opening and closing, at least partially the at least one exhaust gas outlet **312**. This pivoting or rotation of the at least one dynamic vane or fin **320** may thereby alter the flow area of exhaust gas out of the mixer volute **306** prior to and during introduction of the exhaust gas into the central airflow **62** in the air intake **25**. In this configuration the at least one dynamic vane or fin **320** may include an activation device (not illustrated) connected to the first end **324** to rotate and or transition the at least one dynamic vane or fin **320** to vary the angle of the fin or the size of the exhaust gas outlet **312** to project and disrupt the exhaust gas to further promote the mixing and homogenization of the exhaust gas with the central airflow **64** prior to introduction into the intake manifold **22** of the combustion engine **12**.

Additionally, when the at least one dynamic vanes and fins **320** are configured to rotate to adjust the angle relative to a tangential, the exhaust gas velocity will increase or decrease to a desired exhaust gas velocity depending on the predetermined angle. The angle of rotation relative to the tangential may be in a range of 0 to 90 degrees. During a low speed condition of the vehicle **10** the exhaust gas velocity may be low and the angle may be increased to a range of about 20 degrees to about 80 degrees and when the vehicle **10** is under a high speed/load condition the angle could be set to a range of about 0 degrees to about 20 degrees thereby reducing any potential flow loss in the central airflow **64**. Thus, the exhaust gas may be balanced depending on the load conditions of the combustion engine **12**.

It should be understood that mixers **100**, **200**, and **300** may be interchangeable and may be include any one of the features discussed herein either individually or in combination. Specifically, the mixers **100**, **200**, and **300** may be configured with the volute **106** alone without any vanes, they may be configured with a combination of the volute **106** and the vanes, and they may be configured with a combination of the different vanes illustrated in the various mixer embodiments **100**, **200**, and **300**. It should be understood that the designations of first, second, third, fourth, etc. for any component, state, or condition described herein may be rearranged in the claims so that they are in chronological order with respect to the claims. Additionally, the different embodiments disclosed herein may be implemented individually or in any combination, the specific arrangements are examples and do not limit any combination.

The words used in the specification are words of description rather than limitation, and it is understood that various changes may be made without departing from the spirit and scope of the disclosure. As previously described, the features of various embodiments may be combined to form further embodiments that may not be explicitly described or illustrated. While various embodiments could have been described as providing advantages or being preferred over other embodiments or prior art implementations with respect to one or more desired characteristics, those of ordinary skill in the art recognize that one or more features or characteristics may be compromised to achieve desired overall system attributes, which depend on the specific application and implementation. As such, embodiments described as less desirable than other embodiments or prior art implementations with respect to one or more characteristics are not outside the scope of the disclosure and may be desirable for particular applications.

What is claimed is:

1. A vehicle comprising:
 - an internal combustion engine having at least one cylinder;
 - an air intake system configured to deliver air to the at least one cylinder; and
 - an exhaust system having;
 - a set of conduits configured to direct an exhaust gas away from the at least one cylinder, and
 - an exhaust gas recirculation system having,
 - at least one tube configured to direct the exhaust gas away from the set of conduits, and
 - a mixer configured to direct the exhaust gas from the at least one tube into the air intake system, wherein the mixer forms an annular ring having a continuous volute chamber exhaust gas opening disposed radially around an inner diameter of the annular ring and attached to an intake tube, the annular ring is a portion of the air intake system that is configured downstream of a throttle valve and upstream of an intake manifold, the throttle valve includes at least one of a single twist throttle plate or a double twist throttle plate, the mixer includes at least one vane extending across the volute chamber opening and into a flow path of at least one of the exhaust gas and the air intake system, and the at least one vane has an outer surface and is configured to blend the exhaust gas and the air flowing over the outer surface and prior to introduction into the internal combustion engine.
2. The vehicle of claim 1, wherein the at least one vane is at least one of a fixed position and a moveable position, the fixed position is configured at a predetermined angle to provide a predetermined velocity of the exhaust gas, and the moveable position is a dynamic position configured to adjust the angle of the at least one vane automatically as determined by a load of the internal combustion engine and a throttle valve position.
3. The vehicle of claim 1, wherein the annular ring includes at least one exhaust gas outlet or aperture configured radially around the annular ring at the volute chamber exhaust gas opening.
4. The vehicle of claim 3, wherein the at least one vane is at least one of a straight vane, a dynamic vane, an inverted vane and a twist vane, the dynamic vane is at least one of a straight vane, a twist vane and an inverted vane, and the dynamic vane is configured to rotate to at least one of an open position, a partially open position and a closed position.
5. The vehicle of claim 1, wherein the annular ring defines a volute chamber having a gradually reducing section area along an azimuthal direction, and the volute chamber is configured to direct the exhaust gas from an exhaust gas intake conduit to the continuous volute chamber exhaust gas opening.
6. The vehicle of claim 5, wherein the at least one vane is a plurality of vanes configured radially around the annular ring, and each vane divides the continuous volute chamber exhaust gas opening into a plurality of exhaust gas outlets extending around the annular ring.
7. The vehicle of claim 5, wherein the at least one vane is configured to extend at least one of into the volute chamber and into the intake tube.

- 8.** An engine exhaust gas mixer comprising:
 a housing forming an annular ring that defines a central
 opening extending radially around an inner diameter of
 the annular ring, the housing further defining,
 an exhaust gas inlet, 5
 an air intake including a twist throttle plate, the twist
 throttle plate having at least one curved end, the curved
 end directing an intake air in a non-laminar flow path,
 and
 at least one mixing vane configured between the exhaust 10
 gas inlet and the annular ring, the at least one mixing
 vane extending across the central opening and includ-
 ing at least one of a twist or slope to swirl an exhaust
 gas of the engine as the exhaust gas flows over an outer
 surface of the at least one mixing vane. 15
- 9.** The engine exhaust gas mixer of claim **8**, further
 comprising an exhaust gas mixing volute configured
 between the exhaust gas inlet and the central opening.
- 10.** The mixer of claim **9**, wherein the at least one mixing
 vane is fixed at an angle relative to a flow path of an intake 20
 air.
- 11.** The mixer of claim **9**, wherein the at least one mixing
 vane is configured at least partially extending into at least
 one of the central opening and the exhaust gas mixing
 volute. 25

* * * * *