



US011530994B2

(12) **United States Patent**
Kitamura et al.

(10) **Patent No.:** **US 11,530,994 B2**
(45) **Date of Patent:** ***Dec. 20, 2022**

(54) **X-RAY IMAGING SYSTEM CONTAINING X-RAY APPARATUS HAVING GRATINGS AND OBJECT HOUSING FOR SETTING ENVIRONMENTAL CONDITION INDEPENDENT OF EXTERNAL ENVIRONMENT**

(58) **Field of Classification Search**
CPC A61B 6/484; A61B 6/04; A61B 6/0407; A61B 6/44; A61B 6/4435; A61B 6/4441;
(Continued)

(71) Applicant: **Konica Minolta, Inc.**, Tokyo (JP)

(56) **References Cited**

(72) Inventors: **Mitsuharu Kitamura**, Tokyo (JP);
Yasunori Tsuboi, Hino (JP)

U.S. PATENT DOCUMENTS

(73) Assignee: **KONICA MINOLTA, INC.**, Tokyo (JP)

6,859,516 B2 * 2/2005 Schneider G01N 23/041
378/43
6,937,695 B2 * 8/2005 Hoshino G01N 23/201
378/86

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 127 days.

FOREIGN PATENT DOCUMENTS

This patent is subject to a terminal disclaimer.

JP S63-67855 U 5/1988
JP H03-74351 U 7/1991

(Continued)

(21) Appl. No.: **16/910,990**

OTHER PUBLICATIONS

(22) Filed: **Jun. 24, 2020**

An English translation of JP2009-074800A by Patent Translate.
(Year: 2022).*

(Continued)

(65) **Prior Publication Data**

US 2020/0319120 A1 Oct. 8, 2020

Related U.S. Application Data

(63) Continuation of application No. 16/194,928, filed on Nov. 19, 2018, now Pat. No. 10,732,133.

Primary Examiner — Allen C. Ho

(74) *Attorney, Agent, or Firm* — Lucas & Mercanti, LLP

(30) **Foreign Application Priority Data**

Dec. 4, 2017 (JP) JP2017-232242


(57) **ABSTRACT**

(51) **Int. Cl.**
G01N 23/041 (2018.01)
G06T 11/00 (2006.01)
A61B 6/00 (2006.01)

An X-ray imaging system including: an X-ray Talbot imaging apparatus which is provided with an object table, an X-ray source, a plurality of gratings, and an X-ray detector side by side in a direction of an X-ray radiation axis, and irradiates the X-ray detector with an X-ray from the X-ray source through an object and the plurality of gratings to obtain a moire image required for forming a reconstruction image of the object; and an object housing inside which the object is housed and an environmental condition independent of an external environment is set, wherein the object housing is provided detachably with respect to the object table.

(52) **U.S. Cl.**
CPC **G01N 23/041** (2018.02); **A61B 6/484** (2013.01); **G06T 11/003** (2013.01);
(Continued)

18 Claims, 6 Drawing Sheets



(52) **U.S. Cl.**
 CPC . *G01N 2223/31* (2013.01); *G01N 2223/3103*
 (2013.01); *G01N 2223/3106* (2013.01); *G01N*
2223/401 (2013.01)

(58) **Field of Classification Search**
 CPC A61B 6/508; A61B 6/4035; A61B 6/4291;
 A61B 6/4429; A61B 6/4447; A61B 6/54;
 A61B 6/542; A61B 6/545; G01N 23/041
 USPC 378/36, 62, 204, 208, 209
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,993,113 B2 * 1/2006 Hoshino G01N 23/207
 378/86
 7,400,705 B2 * 7/2008 Hoshino G01N 23/201
 378/86
 8,041,004 B2 10/2011 David et al.
 8,602,648 B1 12/2013 Jacobsen et al.
 8,855,265 B2 10/2014 Engel et al.
 9,044,154 B2 * 6/2015 Hoshino A61B 6/04
 9,084,528 B2 7/2015 Geller et al.
 9,107,638 B2 8/2015 Hoshino
 9,330,456 B2 5/2016 Sperl et al.
 9,494,534 B2 * 11/2016 Baturin A61B 6/4291
 9,538,970 B2 1/2017 Koehler et al.
 9,572,541 B2 2/2017 Hoshino
 9,629,600 B2 4/2017 Hoshino et al.
 9,642,581 B2 * 5/2017 Lowe A61B 6/4452
 9,719,947 B2 8/2017 Yun et al.
 9,775,575 B2 10/2017 Proksa
 9,855,018 B2 1/2018 Hamano et al.
 9,872,660 B2 1/2018 Hamano et al.

9,874,531 B2 1/2018 Yun et al.
 9,916,655 B2 3/2018 Stampanoni et al.
 10,076,297 B2 * 9/2018 Bauer A61B 6/484
 10,172,580 B2 1/2019 Roessl et al.
 10,349,908 B2 7/2019 Yun et al.
 10,359,375 B2 7/2019 Cao et al.
 10,365,235 B2 7/2019 Tanabe et al.
 10,371,649 B2 * 8/2019 Yasui G21K 1/067
 10,488,351 B2 * 11/2019 Butani G01N 23/046
 10,514,342 B2 12/2019 Kagias et al.
 10,652,990 B2 * 5/2020 Butani A61B 6/467
 10,695,019 B2 * 6/2020 Kitamura G01N 23/041
 10,732,133 B2 * 8/2020 Kitamura G01N 23/20075
 10,830,712 B2 * 11/2020 Butani A61B 6/42
 10,852,255 B2 * 12/2020 Tsuboi G21K 1/06
 11,058,388 B2 * 7/2021 Rempel A61B 6/4452

FOREIGN PATENT DOCUMENTS

JP 2009-074800 A 4/2009
 JP 4445397 B2 4/2010
 JP 2011232029 A 11/2011
 JP 2013535785 A 9/2013
 JP 2014095640 A 5/2014
 JP 2016004722 A 1/2016
 JP 2017072399 A 4/2017
 JP 2017198600 A 11/2017

OTHER PUBLICATIONS

Office Action dated May 11, 2021 issued in related Japanese Application No. 2017-232242 and English translation.
 JPO, Office Action for the related Japanese Application No. 2017-232242, dated Dec. 7, 2021, with English translation.

* cited by examiner

FIG. 1




FIG. 2




FIG. 3




FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B




FIG. 6




FIG. 7




FIG. 8





FIG. 9



1

**X-RAY IMAGING SYSTEM CONTAINING
X-RAY APPARATUS HAVING GRATINGS
AND OBJECT HOUSING FOR SETTING
ENVIRONMENTAL CONDITION
INDEPENDENT OF EXTERNAL
ENVIRONMENT**

CROSS REFERENCE TO RELATED
APPLICATION

This application is a continuation of U.S. patent application Ser. No. 16/194,928 filed Nov. 19, 2018 (issued on Aug. 4, 2020 as U.S. Pat. No. 10,732,133), which in turn claimed priority of Japanese Patent Application No. 2017-232242, filed on Dec. 4, 2017, the contents of both applications are incorporated herein by reference.

BACKGROUND

Technological Field

The present invention relates to an X-ray imaging system provided with an X-ray Talbot imaging apparatus.

Description of the Related Art

As a conventional X-ray imaging apparatus, one that includes a Talbot interferometer or a Talbot-Lau interferometer having a plurality of gratings (hereinafter referred to as "X-ray Talbot imaging apparatus") is known. In order to obtain a high-resolution reconstruction image by an X-ray Talbot imaging apparatus, a fringe scanning technique is employed (for example, refer to JP 4445397 B1). In the fringe scanning technique, one of the plurality of gratings is shifted in a direction of a slit pitch in increments of $1/M$ (M is a positive integer, where $M > 2$ in an absorption image, and $M > 3$ in a differential phase image and a small-angle scattering image) of the slit pitch of the grating, whereby performing reconstruction with an image (moire image) imaged M times. The Fourier transform may also be employed. In the Fourier transform, with the presence of an object, one moire image is imaged by an X-ray Talbot imaging apparatus, and in the image processing, the moire image is subjected to the Fourier transform or the like, whereby reconstructing a differential phase image or the like.

In recent years, such an X-ray Talbot imaging apparatus is required for observing an internal mechanism of a test object (or an object).

If an internal mechanism of an object is observed while the object is placed under any environmental conditions, it is possible to check changes in the object under a predetermined environmental condition. Especially, observing the progress in normal times and under stringent environmental conditions makes it possible to see the changing mechanism of the object as a substance. Simultaneously capturing such conditions in a differential phase image or a small-angle scattering image specifically imaged by an X-ray Talbot imaging apparatus and in an ordinary absorption image offers an advantage in explaining a phenomenon which is not observed in a test or inspection in the related art.

However, a plurality of gratings, a main part of the X-ray Talbot imaging apparatus, has a grating structure with a pitch of several μm , and significant environmental changes cause minute deformation in the gratings, parts that hold the gratings or the like. This may cause noise or the like in a reconstruction image to be formed. In the meantime, many

2

objects to be subjected to non-destructive testing require, for example, imaging of states under a special temperature and humidity and imaging of states associated with environmental changes. Therefore, a change in environment of an object without changing an installation environment of only an X-ray Talbot imaging apparatus brings a great advantage to the X-ray Talbot imaging apparatus.

SUMMARY

An object of the present invention is to prevent troubles in an X-ray Talbot imaging apparatus attributed to an installation environment and to clarify an internal mechanism of an object which is not observed in a test or inspection in the related art.

To achieve at least one of the abovementioned objects, according to an aspect of the present invention, an X-ray imaging system reflecting one aspect of the present invention includes: an X-ray Talbot imaging apparatus which is provided with an object table, an X-ray source, a plurality of gratings, and an X-ray detector side by side in a direction of an X-ray radiation axis, and irradiates the X-ray detector with an X-ray from the X-ray source through an object and the plurality of gratings to obtain a moire image required for forming a reconstruction image of the object; and an object housing inside which the object is housed and an environmental condition independent of an external environment is set, wherein the object housing is provided detachably with respect to the object table.

BRIEF DESCRIPTION OF THE DRAWINGS

The advantages and features provided by one or more embodiments of the invention will become more fully understood from the detailed description given hereinafter and the appended drawings which are given by way of illustration only, and thus are not intended as a definition of the limits of the present invention, and wherein:

FIG. 1 is a schematic view showing an overall picture of an X-ray Talbot imaging apparatus and an object housing;

FIG. 2 is a view for explaining the principle of a Talbot interferometer;

FIG. 3 is a schematic plan view of a source grating, a first grating, and a second grating;

FIGS. 4A and 4B are cross-sectional perspective views each showing a configuration of the object housing;

FIGS. 5A and 5B are schematic views each showing a configuration of a moving system that moves the object housing;

FIG. 6 is a schematic view of the object housing including a rotator;

FIG. 7 is a schematic view of the object housing including a laser radiator;

FIG. 8 is a schematic view of the object housing including a nail inserter; and

FIG. 9 is a schematic view of the object housing including a heat generator.

DETAILED DESCRIPTION OF THE
EMBODIMENTS

Hereinafter, one or more embodiments of the present invention will be described in detail with reference to the drawings. The following embodiment includes various technically preferable limitations in order to carry out the present

invention. However, the technical scope of the present invention is not limited to the following embodiment and illustrated examples.

In an X-ray imaging system described in this embodiment, the interior of an object housing **30** that houses an object H is set to an environmental condition independent of an external environment, and the object H is imaged with an X-ray Talbot imaging apparatus **1**. Accordingly, the X-ray imaging system herein enables imaging of the object H under environmental conditions different from normal times.

The object H in this embodiment represents all kinds of samples such as metals, resin, composite materials, and woven fabric, and includes all kinds of subjects that required examination of internal properties. Imaging with the X-ray Talbot imaging apparatus **1** enables observation of an internal mechanism of the object H.

In this embodiment, as the X-ray Talbot imaging apparatus **1**, one that includes a Talbot-Lau interferometer provided with a source grating (also referred to as “multi-grating”, “multi-slit”, “G0 grating”, or the like) **12** is employed. An X-ray Talbot imaging apparatus **1** including a Talbot interferometer provided with only a first grating (also referred to as “G1 grating”) **14** and a second grating (also referred to as “G2 grating”) **15** instead of the source grating **12** may also be employed.

[X-ray Talbot Imaging Apparatus]

FIG. **1** is a schematic view showing an overall picture of the X-ray Talbot imaging apparatus **1** and the object housing **30**.

The X-ray Talbot imaging apparatus **1** according to this embodiment includes an X-ray generator **11**, the source grating **12**, an object table **13**, the first grating **14**, the second grating **15**, an X-ray detector **16**, a support **17**, and a base **18**.

According to such an X-ray Talbot imaging apparatus **1**, a moire image of the object H disposed at a predetermined position with respect to the object table **13** is imaged by a method based on the principle of a fringe scanning technique, or the moire image is analyzed by the Fourier transform, so that at least three types of images are reconstructed (referred to as “reconstruction images”). The three types of images are an absorption image (the same as an ordinary X-ray absorption image) obtained by imaging an average component of moire fringes in the moire image, a differential phase image obtained by imaging phase information of the moire fringes, and a small-angle scattering image obtained by imaging visibility of the moire fringes. Resynthesis or the like of these three types of reconstruction images may form more kinds of images.

The fringe scanning technique is a method to obtain a high-resolution reconstruction image by shifting one of a plurality of gratings in a direction of a slit pitch in increments of $1/M$ (M is a positive integer, where $M > 2$ in an absorption image, and $M > 3$ in a differential phase image and a small-angle scattering image) of the slit pitch of the grating, and by performing reconstruction with a moire image imaged M times.

The Fourier transform is a method to reconstruct and form a differential phase image or the like by imaging one moire image with an X-ray Talbot imaging apparatus **1**, with the presence of an object H, and by performing the Fourier transform or the like on the moire image during the image processing.

First, the principle common to a Talbot interferometer and a Talbot-Lau interferometer will be described with reference to FIG. **2**.

FIG. **2** shows a case where a Talbot interferometer is employed. Note that a case where a Talbot-Lau interferom-

eter is employed is described basically similarly. The z direction in FIG. **2** corresponds to the vertical direction in the X-ray Talbot imaging apparatus **1** of FIG. **1**, the x and y directions in FIG. **2** correspond to the horizontal directions (front-back, right-left directions) in the X-ray Talbot imaging apparatus **1** of FIG. **1**.

As shown in FIG. **3**, the first grating **14** and the second grating **15** (as well as the source grating **12** in a Talbot-Lau interferometer) include a plurality of slits S arranged at a predetermined pitch d in the x direction perpendicular to the z direction which is a direction of X-ray radiation.

As shown in FIG. **2**, an X-ray emitted from an X-ray generator **11** is transmitted through the first grating **14** (in a Talbot-Lau interferometer, the X-ray emitted from the X-ray generator **11** is converted to multiple light by the source grating **12** (not shown in FIG. **2**)). The transmitted X-ray forms an image at a constant interval in the z direction. This image is called “self-image” (also referred to as “grating image” or the like), and a phenomenon in which a self-image is formed at a constant interval in the z direction is called “Talbot effect”.

In other words, the Talbot effect indicates a phenomenon in which coherent light penetrates the first grating **14** provided with the slits S at the constant pitch d , as shown in FIG. **3**, causing the light to form a self-image at a constant interval in a light traveling direction.

As shown in FIG. **2**, the second grating **15** provided with slits S , as in the first grating **14**, is disposed at a position where a self-image of the first grating **14** is formed. When the second grating **15** is arranged in such a manner that an extending direction of the slits S of the second grating **15** (that is, the x -axial direction in FIG. **2**) becomes substantially parallel to an extending direction of the slits S of the first grating **14**, a moire image M_0 is obtained on the second grating **15**.

In FIG. **2**, if the moire image M_0 is drawn on the second grating **15**, moire fringes and the slits S are mixed up, making the drawing complicated. Therefore, the moire image M_0 is drawn as being separated from the second grating **15**. However, actually, the moire image M_0 is formed on the second grating **15** and downstream of the second grating **15**. The moire image M_0 is imaged by the X-ray detector **16** disposed immediately below the second grating **15**.

As shown in FIGS. **1** and **2**, when the object H is present between the X-ray source **11a** and the first grating **14**, the phase of the X-ray is shifted due to the object H. This phase shift wobbles the moire fringes of the moire image M_0 from the edge of the object H. On the other hand, if the object H is not present between the X-ray source **11a** and the first grating **14**, which is not shown in the drawing, the moire image M_0 with only the moire fringes shows up. This is the principle of a Talbot interferometer and a Talbot-Lau interferometer.

Based on this principle, in the X-ray Talbot imaging apparatus **1** according to this embodiment, as shown in FIG. **1**, for example, the second grating **15** is disposed at a position inside a second cover unit **130** where the self-image of the first grating **14** is formed. As described above, separating the second grating **15** and the X-ray detector **16** blurs the moire image M_0 (see FIG. **2**). Therefore, in this embodiment, the X-ray detector **16** is disposed immediately below the second grating **15**. The second grating **15** may be formed of an emitting material such as a scintillator or amorphous selenium, and the second grating **15** may be formed in an integrated manner with the X-ray detector **16**.

5

The second cover unit **130** is provided to protect the first grating **14**, the second grating **15**, the X-ray detector **16**, and the like so that somebody or something does not hit or touch the X-ray detector **16** and the like.

Although not shown in the drawing, the X-ray detector **16** includes conversion elements that generate electric signals depending on emitted X-rays. The conversion elements are arranged two-dimensionally (in matrix form), and the electric signals generated by the conversion elements are read as image signals. In this embodiment, the X-ray detector **16** is configured to image the moire image Mo, or the X-ray image formed on the second grating **15**, as an image signal for each conversion element. The pixel size of the X-ray detector **16** is 10 to 300 (μm), and preferably, 50 to 200 (μm).

An example of the X-ray detector **16** may include a flat panel detector (FPD). There are an indirect conversion FPD that converts a detected X-ray into an electric signal through a photoelectric conversion element; and a direct conversion FPD that directly converts a detected X-ray into an electric signal. Either FPD is employable.

In an indirect conversion FPD, photoelectric conversion elements that form a pixel are two-dimensionally arranged together with a thin film transistor (TFT) under a scintillator plate made of CsI, Gd₂O₂S, or the like. When an X-ray incident on the X-ray detector **16** is absorbed by the scintillator plate, the scintillator plate emits light. This emitted light leads to accumulation of charges in each photoelectric conversion element, and the accumulated charges are read out as image signals.

In a direct conversion FPD, an amorphous selenium film having a film thickness of 100 to 1000 (μm) is formed on glass by thermal evaporation of amorphous selenium, and the amorphous selenium film and electrodes are evaporated on an array of the two-dimensionally arranged TFT. When the amorphous selenium film absorbs an X-ray, a voltage is liberated in the substance in the form of electron-hole pairs, and a voltage signal between the electrodes is read by the TFT.

Imaging units such as a charge coupled device (CCD) and an X-ray camera may also be used as the X-ray detector **16**.

In this embodiment, the X-ray Talbot imaging apparatus **1** images a plurality of moire images Mo by what is called a fringe scanning technique. In other words, the X-ray Talbot imaging apparatus **1** according to this embodiment images the plurality of moire images Mo by shifting relative positions of the first grating **14** and the second grating **15** in the x-axial direction in FIGS. **1** to **3** (that is, a direction perpendicular to the extending direction of the slits S (y-axial direction)).

An image processing device (not shown) which has received image signals of the plurality of moire images Mo from the X-ray Talbot imaging apparatus **1** executes image processing and reconstructs an absorption image, a differential phase image, a small-angle scattering image, and the like based on the plurality of moire images Mo.

Therefore, in order to image the plurality of moire images Mo by the fringe scanning technique, the X-ray Talbot imaging apparatus **1** according to this embodiment may move the first grating **14** in the x-axial direction in increments of a predetermined amount. The X-ray Talbot imaging apparatus **1** may move the second grating **15**, instead of the first grating **14**, or may move both gratings in the x-axial direction.

While fixing the relative positions of the first grating **14** and the second grating **15**, the X-ray Talbot imaging apparatus **1** may image one moire image Mo, and this moire image Mo may be analyzed by the Fourier transform in the

6

image processing executed by the image processing device to reconstruct an absorption image, a differential phase image, and the like.

Hereinafter described is configurations of other parts in the X-ray Talbot imaging apparatus **1** according to this embodiment. The X-ray Talbot imaging apparatus **1** in this embodiment is of what is called vertical type and includes the X-ray generator **11**, the source grating **12**, the object table **13**, the first grating **14**, the second grating **15**, and the X-ray detector **16** arranged in this order in the z direction or the gravity direction. In other words, in this embodiment, the z direction is the direction of X-ray radiation from the X-ray generator **11**.

As the X-ray source **11a**, the X-ray generator **11** includes, for example, a Coolidge X-ray source, a rotating anode X-ray source or the like, either of which is widely and generally used in a medical field. Other X-ray sources may also be employed herein. The X-ray generator **11** in this embodiment emits an X-ray in a cone-beam shape from a focal point. In other words, as shown in FIG. **1**, the X-ray is emitted in such a manner that the X-ray spreads out as it separates from the X-ray generator **11**, centering on an X-ray radiation axis Ca that coincides with the z direction (that is, an X-ray radiation range).

In this embodiment, the source grating **12** is provided below the X-ray generator **11**. In regard to vibration of the X-ray generator **11** caused by rotation of an anode in the X-ray source **11a**, in order not to transmit the vibration to the source grating **12**, the source grating **12** in this embodiment is not attached to the X-ray generator **11** but to a fixing member **12a** that is attached to the base **18** provided on the support **17**.

In this embodiment, in order to prevent propagation of the vibration of the X-ray generator **11** to other parts of the X-ray Talbot imaging apparatus **1** such as the support **17** (or to reduce the vibration to be propagated), a cushioning member **17a** is provided between the X-ray generator **11** and the support **17**.

In this embodiment, in addition to the source grating **12**, to the fixing member **12a**, attached are a filter (also referred to as "additional filter") **112** that changes the quality of an X-ray transmitted through the source grating **12**, a beam limiting device **113** that limits an irradiation field of an X-ray to be emitted, and an irradiation field lamp **114** that irradiates an object with visible light instead of an X-ray before X-ray radiation so as to adjust a position of the X-ray.

The source grating **12**, the filter **112**, and the beam limiting device **113** are not necessarily disposed in this order. Furthermore, in this embodiment, a first cover unit **120** that protects the source grating **12** and the like is disposed around those members.

In this embodiment, the hardware processor **19** (see FIG. **1**) includes a computer in which a central processing unit (CPU), a read only memory (ROM), a random access memory (RAM), an input/output interface, and the like are connected to each other by a bus (those members are not shown in the drawing). Instead of a general-purpose computer as in this embodiment, the hardware processor **19** may include a dedicated control device. Although not shown in the drawing, the hardware processor **19** is provided with appropriate units and devices such as an input unit and an output unit including an operation unit, a storage unit, and a communication unit.

The output unit includes a display unit (not shown) that displays information necessary for performing various operations of the X-ray Talbot imaging apparatus **1** and displays a formed reconstruction image.

The hardware processor **19** performs overall control of the X-ray Talbot imaging apparatus **1**. In other words, for example, the hardware processor **19** is connected to the X-ray generator **11** and may set a tube voltage, a tube current, an irradiation time, and the like in the X-ray source **11a**. The hardware processor **19**, for example, may also be configured to relay transmission and reception of signals and data between the X-ray detector **16** and an external image processing device (not shown).

In other words, the hardware processor **19** in this embodiment functions as a controller that causes a series of imaging to acquire the plurality of moire images Mo (one moire image in the Fourier transform) necessary for forming a reconstruction image of the object H.

[Object Housing]

As shown in FIG. **1**, the object housing **30** is a box-like body that internally houses the object H, and the interior of the object housing **30** may be set to an environmental condition independent of an external environment.

As shown in FIGS. **4A** and **4B**, the object housing **30** includes a box-shaped main body **31** provided with a bottom **31a** and a peripheral wall **31b**, and a cover **32** that covers an opening of the main body **31**.

With the opening of the main body **31** being covered with the cover **32**, the interior of the object housing **30** is hermetically sealed.

Using such an object housing **30**, the periphery of the object H may be set to the environmental condition independent of the external environment.

The cover **32** is provided detachably with respect to an upper end of the main body **31**.

A structure for attaching or detaching the cover **32** to or from the upper end of the main body **31** is not particularly limited. It is preferable to employ, for example, a connecting fitting (not shown) called a toggle latch or a patch fitting, or a fixing screw (not shown) that fixes the cover **32** to the upper end of the main body **31**.

With the cover **32** being attached to the upper end of the main body **31**, the object housing **30** functions as a pressure-resistant (or explosion-proof) box-shaped body.

Each of the main body **31** and the cover **32** includes an X-ray transmitter **33** on the X-ray radiation axis Ca and in the X-ray radiation range around the X-ray radiation axis Ca. The X-ray transmitter **33** is less likely to hinder transmission of X-rays compared to peripheral parts. The X-ray transmitter **33** includes a material having high X-ray transmissivity (for example, resin or resin mixed with carbon fiber or glass fiber).

The X-ray transmitter **33** of the main body **31** is provided in the bottom **31a**. Since the X-ray from the X-ray generator **11** is emitted in a cone-beam shape as described above, the X-ray transmitter **33** in the main body **31** may be provided in an area wider than the X-ray transmitter **33** in the cover **32**.

In this embodiment, the main body **31** and the cover **32**, excluding the X-ray transmitter **33**, are mainly made of metal, but those members may be made of a material with high X-ray transmissivity.

Examples of environmental conditions independent of an external environment inside the object housing **30** include conditions related to temperature and/or humidity inside the object housing **30**. In other words, in this embodiment, temperature and/or humidity are examples of environmental conditions independent of an external environment inside the object housing **30**, and the temperature and/or humidity inside the object housing **30** are adjustable.

In order to adjust the temperature inside the object housing **30**, the object housing **30** further includes a heater unit **34** as shown in FIGS. **4A** and **4B**. Accordingly, the temperature inside the object housing **30** may be set to any temperature.

The adjustment of the temperature in the heater unit **34** may be automatically controlled by the hardware processor **19** (controller) of the X-ray Talbot imaging apparatus **1** in conjunction with the X-ray Talbot imaging apparatus **1**.

In other words, the hardware processor **19** controls the series of imaging performed by the X-ray Talbot imaging apparatus **1** to acquire the plurality of moire images Mo, and at the time of the series of imaging, the hardware processor **19** may also adjust the temperature inside the object housing **30**. That is, the hardware processor **19** and the heater unit **34** are communicably connected to each other.

As shown in FIGS. **4A** and **4B**, the heater unit **34** in this embodiment may be put in and out from the object housing **30**.

In the peripheral wall **31b** of the main body **31**, the object housing **30** includes an inlet/outlet port **31c** that allows the heater unit **34** to be put in and out of the object housing **30**.

In this embodiment, the operation of putting in and out the heater unit **34** may be automatically controlled by the hardware processor **19** (controller) of the X-ray Talbot imaging apparatus **1** in conjunction with the X-ray Talbot imaging apparatus **1**.

In other words, in the series of imaging by the X-ray Talbot imaging apparatus **1**, the heater unit **34** may be put in and out by the hardware processor **19**. That is, the hardware processor **19** and a drive unit that drives the heater unit **34** are communicably connected to each other.

Humidity inside the object housing **30** is adjusted by, for example, a humidity adjustment unit (not shown) having functions of humidification and dehumidification. The operation of this humidity adjustment unit may be also automatically controlled by the hardware processor **19** (controller) of the X-ray Talbot imaging apparatus **1** in conjunction with the X-ray Talbot imaging apparatus **1**.

The object housing **30** and the X-ray Talbot imaging apparatus **1** are mechanically independent from each other, and the object housing **30** is detachably disposed in the object table **13** in the X-ray Talbot imaging apparatus **1**. More specifically, the main body **31** of the object housing **30** is attached to the object table **13**. However, the present invention is not limited to this configuration, and both the main body **31** and the cover **32** may be attached to any part of the X-ray Talbot imaging apparatus **1**.

In this embodiment, although not shown in the drawing, an engagement unit is provided between a lower end of the main body **31** and the object table **13**. Example of such an engagement unit includes a simple structure that facilitates attachment and detachment such as the aforementioned connecting fitting and fixing screw. In addition, the object housing **30** may include a holding unit that holds the edge of the object table **13**. Alternatively, the object table **13** may include a holding unit that holds the object housing **30**. The object housing **30** is desirably attached to or detached from the object table **13** by a simple operation such as sliding or lifting in the x direction, the y direction, or a rotation direction.

If the interior of the object housing **30** is set to a high temperature, for example, the object housing **30** itself may be heated. Even in such a case, detaching the object housing **30** from the object table **13** reduces an influence of environmental changes on the X-ray Talbot imaging apparatus **1**. As needed, X-ray Talbot imaging is carried out with the

object housing **30** being attached to the object table **13**. Accordingly, it is possible to clarify an internal mechanism of an object which is not observed in a test or inspection in the related art.

In X-ray Talbot imaging using the object housing **30**, for example, the object H may be housed in the object housing **30**, and then, an environmental condition inside the object housing **30** may be gradually changed to another condition different from an external environment. Alternatively, an environmental condition inside the object housing **30** may be changed to another condition different from an external environment, and then, the object H may be housed in the object housing **30** to see changes over time. Furthermore, environmental conditions inside the object housing **30** may be changed at some interval.

Configuration Example 1 of Object Housing

The object housing **30** is not necessarily used for each imaging. When ordinary X-ray Talbot imaging and X-ray Talbot imaging in a state where the interior of the object housing **30** is set to an environmental condition independent of an external environment are simultaneously performed, it is possible to acquire highly accurate information on the object H. The ordinary X-ray Talbot imaging and the X-ray Talbot imaging in a state where the interior of the object housing **30** is set to an independent environmental condition are frequently performed by turns in some cases.

Therefore, as shown in FIGS. **5A** and **5B**, the object housing **30** is provided on the object table **13** of the X-ray Talbot imaging apparatus **1**, being movable back and forth with respect to the X-ray radiation range. In other words, the object housing **30** is provided on the object table **13** of the X-ray Talbot imaging apparatus **1** so as to be able to advance and retreat with respect to the X-ray radiation range.

The object table **13** is provided with a moving system **40** that moves the object housing **30** so that the object housing **30** moves away from or closer to the X-ray radiation range.

The moving system **40** includes a stand **41** attached to the object table **13** and a guide rail **42** elongated along a length direction of the stand **41**.

The stand **41** is formed in a rectangular plate shape and is set to have a length protruding outward beyond the upper surface of the object table **13**. In addition, an opening **41a** corresponding to the X-ray radiation range is formed at a portion of the stand **41** placed on the upper surface of the object table **13**, so that the stand **41** is less likely to hinder transmission of X-rays.

The guide rail **42** is provided on the stand **41** in pairs and elongated along the length direction of the stand **41**. The guide rail **42** includes a movable body (not shown) that is movable along the guide rail and a drive unit (not shown) that causes the movable body to operate.

The object housing **30** is attached to the movable body of the guide rail **42** and moves (advances and retreats) from a position corresponding to the X-ray radiation range of the object table **13** to the outside of the object table **13**.

Imaging is performed in a state shown in FIG. **5A** when the object housing **30** is used, and imaging is performed in a state shown in FIG. **5B** when the ordinary X-ray Talbot imaging is performed.

The operation of the movable body in the moving system **40** may be automatically controlled by the hardware processor **19** (controller) of the X-ray Talbot imaging apparatus **1** in conjunction with the X-ray Talbot imaging apparatus **1**.

That is, the hardware processor **19** and a drive unit that drives the movable body are communicably connected to each other.

Configuration Example 2 of Object Housing

Each of the plurality of gratings **12**, **14**, and **15** is a one-dimensional grating. Accordingly, a direction shows up in a moire image M_0 acquired by the X-ray Talbot imaging apparatus **1**. In other words, depending on an imaging direction of the object H, for example, a fiber direction and a scratch direction are visible in some portions and invisible in some portions.

Therefore, as shown in FIG. **6**, one of the object table **13** and the object housing **30** of the X-ray Talbot imaging apparatus **1** includes a rotator **35** that rotates the object H about the X-ray radiation axis C_a . When the object housing **30** that houses the object H is rotated at any angle by the rotator **35**, an image of the object H imaged before the rotation and an image of the object H imaged after the rotation are viewed differently, and a predetermined portion of the object H which is not viewed before the rotation becomes visible in the image that is imaged after the rotation.

Example of the rotator **35** in this embodiment includes a rotation member which has a circular or frame shape with an opening (not shown) formed at the center and of which a rotation center corresponds to the X-ray radiation axis C_a . The opening formed in the center corresponds to the X-ray transmitter **33** and easily transmits X-rays.

Similarly to the X-ray transmitter **33**, the rotator **35** may include a material having high X-ray transmissivity. In this case, it is not necessary to form an opening in the center.

The rotator **35** is positioned between the object table **13** and the bottom **31a** of the main body **31** in the object housing **30**. A lower end face of the rotator **35** is attached to the object table **13**, and an upper end face thereof is attached to the bottom **31a**. The upper end face of the rotator **35** is provided with a rotating body (not shown) which is rotatable and to which the bottom **31a** of the main body **31** in the object housing **30** is attached, and the lower end face of the rotator **35** is provided with a drive unit that rotates the rotating body.

In this embodiment, the object housing **30** is provided with the rotator **35**, but the object table **13** of the X-ray Talbot imaging apparatus **1** may be provided with the rotator **35**. Furthermore, the main body **31** of the object housing **30** may be provided with the rotator **35**.

The rotation of the rotator **35** may be automatically controlled by the hardware processor **19** (controller) of the X-ray Talbot imaging apparatus **1** in conjunction with the X-ray Talbot imaging apparatus **1**. That is, the hardware processor **19** and a drive unit that drives the rotating body are communicably connected to each other.

Another Configuration Example of Object Housing

The case where examples of environmental conditions independent of an external environment inside the object housing **30** include conditions related to temperature and/or humidity inside the object housing **30** has been described, but the environmental conditions are not limited thereto and may be modified appropriately.

In other words, for example, the interior of the object housing **30** may be made vacuum, pressurized, or depressurized. Alternatively, the object H may be immersed in water, or the object H may be vibrated. Furthermore, various

11

environmental conditions as described above including the conditions related to temperature and/or humidity may be used in combination.

Although not shown in the drawing, the object housing **30** is provided with appropriate equipment, devices, and the like for preparing various environmental conditions as described above.

In other words, in a case where the interior of the object housing **30** is made vacuum, pressurized, or depressurized, the object housing **30** is provided with a pump, a valve mechanism, or the like.

In a case where the object H is immersed in water, the object housing **30** is provided with a water storage tank and a water supply and drainage mechanism.

In a case where the object H is vibrated, the object housing **30** is provided with a vibrator together with a vibration isolating mechanism that prevents transmission of the vibration to the X-ray Talbot imaging apparatus **1**.

Various equipment, devices, and the like for setting the interior of the object housing **30** to an environmental condition independent of an external environment may be automatically controlled by the hardware processor **19** (controller) of the X-ray Talbot imaging apparatus **1** in conjunction with the X-ray Talbot imaging apparatus **1**.

As described above, according to this embodiment, it is possible to observe an internal mechanism of the object H when the object H is housed in the object housing **30** under any environmental condition, which enables observation of changes in a substance in each environment. Especially, observation of an environment in consideration with the usual usage environment and observation of the progress under stringent environmental conditions make it possible to observe the changing mechanism of the substance. In other words, simultaneously capturing any environmental condition of the object H in a differential phase image or a small-angle scattering image specific to a Talbot image and in an ordinary absorption image leads to clarification of the internal mechanism of the object H which is not observed in a test or inspection in the related art.

Furthermore, as described above, the plurality of gratings **12**, **14** and **15** or a main member of the X-ray Talbot imaging apparatus **1** has a grating structure with a pitch of several μm . Therefore, with a significant environmental change, the gratings, parts that hold the gratings or the like are slightly deformed, which may cause noise or the like in a reconstruction image to be formed. In the meantime, many objects to be subjected to non-destructive testing require, for example, imaging of states under a special temperature and humidity and imaging of states associated with environmental changes. Since the object housing **30** is detachably attached to the object table **13**, the object housing **30** may be attached to the object table **13** as necessary.

Therefore, it is possible to image the object H by the X-ray Talbot imaging apparatus **1** under an environmental condition independent of an external environment without changing an installation environment of the X-ray Talbot imaging apparatus **1**, and to prevent troubles in the X-ray Talbot imaging apparatus **1** attributed to the installation environment, and to clarify the internal mechanism of the object H which is not observed in a test or inspection in the related art.

The X-ray Talbot imaging apparatus **1** includes the hardware processor (hardware processor **19**) that causes the series of imaging for acquiring the plurality of moire images Mo necessary for forming a reconstruction image of the object H. The hardware processor of the X-ray Talbot imaging apparatus **1** may automatically control setting of

12

independent environmental conditions inside the object housing **30** in conjunction with the X-ray Talbot imaging apparatus **1**. Therefore, while controlling the imaging by the X-ray Talbot imaging apparatus **1**, the hardware processor may appropriately control the interior of the object housing **30** to be set to an environmental condition independent of an external environment or to an environmental condition similar to the external environment. Such a configuration makes it easier to clarify the internal mechanism of the object H.

Since independent environmental conditions include conditions related to temperature and/or humidity inside the object housing **30**, the interior of the object housing **30** may be set to a high temperature and high humidity, or to a low temperature and low humidity. Accordingly, the internal mechanism of the object H is observed while the object H is housed in the object housing **30** under such conditions.

On the X-ray radiation axis Ca and in the X-ray radiation range around the X-ray radiation axis Ca, the object housing **30** includes the X-ray transmitter **33** which is less likely to hinder transmission of X-rays compared to the peripheral parts. Therefore, by housing the object H at the position of the X-ray transmitter **33**, it is easy to transmit X-rays at the time of imaging compared to a case where the object housing **30** does not house the object H at the position of the X-ray transmitter **33**.

Each of the plurality of gratings **12**, **14**, and **15** is a one-dimensional grating. Therefore, by moving one of the plurality of gratings **12**, **14**, and **15** relative to other gratings to perform the fringe scanning technique, and by repeating imaging in which the X-ray detector **16** reads image signals in accordance with emitted X-rays, it is possible to acquire the plurality of moire images Mo necessary for forming a reconstruction image of the object H.

Furthermore, in consideration of the fact that each of the plurality of gratings **12**, **14**, **15** is a one-dimensional grating, one of the object table **13** and the object housing **30** of the X-ray Talbot imaging apparatus **1** includes the rotator that rotates the object H about the X-ray radiation axis Ca. Therefore, an image of the object H imaged before the rotation and an image of the object H imaged after the rotation are viewed differently, and a portion (for example, scratches, defects and the like) of the object H which is not viewed in the image before the rotation is observed in the image that is imaged after the rotation. Accordingly, the object H may be inspected in detail.

The X-ray Talbot imaging apparatus **1** and the object housing **30** are mechanically independent from each other. Therefore, the object housing **30** is easily attached to and detached from the object table **13**. Accordingly, it is easy to attach the object housing **30** to the object table **13** as needed and to detach it from the object table **13**.

The object housing **30** is disposed on the object table **13** of the X-ray Talbot imaging apparatus **1**, being movable back and forth with respect to the X-ray radiation range. Therefore, it is possible to appropriately change conditions between the imaging carried out by the X-ray Talbot imaging apparatus **1** with the object housing **30** and the ordinary imaging carried out by the X-ray Talbot imaging apparatus **1** without the object housing **30**.

[Modification]

The aforementioned embodiment illustrates the configuration in which the interior of the object housing **30** is set to an environmental condition independent of an external environment. The following modification illustrates a configuration that changes physical properties of the object H itself. The following modifications may be combined to the extent possible.

Similarly to the embodiment, the X-ray Talbot imaging apparatus **1** in the following modifications is configured to image a plurality of moire images Mo by what is called the fringe scanning technique. However, the X-ray Talbot imaging apparatus **1** herein may employ the Fourier transform in which one moire image is subjected to the Fourier transform and the like to reconstruct an image such as a differential phase image.

[Modification 1]

As shown in FIG. 7, the object housing **30** in this modification has a laser radiator **36** that irradiates the object H with a laser beam.

Laser beams are excellent in directivity and convergence. Raising an output of a laser beam enables intensive heating of a minute portion in the object H.

The laser radiator **36** is provided inside the object housing **30**, having an angle adjustable relative to the object H.

In regard to the adjustment of the angle and the radiation of a laser beam and/or operation of stopping the radiation of a laser beam, the laser radiator **36** may be automatically controlled by the hardware processor **19** (controller) of the X-ray Talbot imaging apparatus **1** in conjunction with the X-ray Talbot imaging apparatus **1**.

In other words, the hardware processor **19** controls the series of imaging performed by the X-ray Talbot imaging apparatus **1** to acquire the plurality of moire images Mo, and at the time of the series of imaging, the hardware processor **19** also control each operation of the laser radiator **36**. That is, the hardware processor **19** and the laser radiator **36** are communicably connected to each other.

A laser beam of the laser radiator **36** in this modification intensively heats the minute portion of the object H. Therefore, performing the X-ray Talbot imaging leads to clarification of the mechanism of partial changes in physical properties of the object H due to heating.

The output of the emitted laser beam may be considerably increased to partially destroy the object H, and the mechanism of changes in physical properties of the destroyed object H may be imaged by the X-ray Talbot imaging apparatus **1**.

In order not to hinder X-ray irradiation of the X-ray generator **11** with respect to the object H, in this modification, a laser beam is emitted while the X-ray radiation is stopped.

When laser beam radiation is performed during the X-ray Talbot imaging, a laser beam is to be emitted toward a position not to hinder the X-ray irradiation with respect to the object H.

According to this modification, the object housing **30** includes the laser radiator **36** that irradiates the object H with a laser beam. Therefore, performing the X-ray Talbot imaging leads to clarification of the mechanism of partial changes in physical properties of the object H irradiated with the laser beam. Since such X-ray Talbot imaging is performed without changing an installation environment of the X-ray Talbot imaging apparatus **1**, it is possible to prevent troubles in the X-ray Talbot imaging apparatus **1** attributed to the installation environment.

Furthermore, as described in the embodiment, the X-ray Talbot imaging apparatus **1** is preferable in that the X-ray Talbot imaging is performed while the interior of the object housing **30** is set to an environmental condition independent of an external environment and that the object H is imaged under various conditions.

[Modification 2]

As shown in FIG. 8, the object housing **30** in this modification includes a nail inserter **37** that performs a nailing test on the object H.

In the nailing test, an internal short circuit is simulated by piercing a nail in a thickness direction of an electrode body such as a lithium ion battery, and the degree of heat generation is studied to check the safeness of the battery. In the nailing test, when the nail penetrates a battery cell, an internal short circuit occurs between a positive electrode current collector and a negative electrode current collector in the battery cell through the nail, leading to a phenomenon of local heating of contact portions between these current collectors and the nail and the periphery of the contact portions.

The object housing **30** in this modification includes the nail inserter **37**, so that it is possible to clarify an internal mechanism of a nailed portion in the object H.

The nail inserter **37** includes a nail body **37a**, a through hole (not shown) for the nail body **37a** formed in the cover **32** of the object housing **30**, and a packing material (not shown) provided on the inner periphery of the through hole.

The packing material includes an elastically deformable material which ensures hermeticity of the object housing **30** when the nail body **37a** is not penetrated through the through hole.

The nail body **37a** may have a built-in temperature sensor for measuring the temperature inside the object H.

In this modification, the nail body **37a** is inserted or removed by a user such as a radiological technician or an inspector, but the present invention is not limited thereto. The nail body **37a** may be inserted or removed by a drive unit (not shown). In a case where the nail body **37a** is inserted or removed by such a drive unit, the drive unit may be automatically controlled by the hardware processor **19** (controller) of the X-ray Talbot imaging apparatus **1** in conjunction with the X-ray Talbot imaging apparatus **1**.

In the illustrated example, the nail body **37a** is provided in a central portion of the object housing **30**, but the invention is not limited thereto. The nail body **37a** may be inserted or removed obliquely relative to the object H. Alternatively, the nail body **37a** may be inserted or removed from the peripheral wall **31b** side of the main body **31**.

According to this modification, the object housing **30** includes the nail inserter **37** for performing the nailing test on the object H. Therefore, performing the X-ray Talbot imaging leads to clarification of the mechanism of changes in physical properties of the object H subjected to the nailing test. Since such X-ray Talbot imaging is performed without changing an installation environment of the X-ray Talbot imaging apparatus **1**, it is possible to prevent troubles in the X-ray Talbot imaging apparatus **1** attributed to the installation environment.

Furthermore, as described in the embodiment, the X-ray Talbot imaging apparatus **1** is preferable in that the X-ray Talbot imaging is performed while the interior of the object housing **30** is set to an environmental condition independent of an external environment and that the object H is imaged under various conditions.

[Modification 3]

As shown in FIG. 9, the object housing **30** in this modification includes a temperature controllable heat generator **38** which is brought into contact with the object H.

The heat generator **38** heats to a high temperature by itself. Being brought into contact with the surface of the object H, the heat generator **38** may heat the surface of the object H or singe the surface depending on the material of the object H.

The heat generator **38** is provided with an arm **38a** that holds the heat generator **38**, being disposed inside the object H. An angle and distance of the arm **38a** relative to the object H is adjustable.

The adjustment of the angle and distance of the arm **38a** and the adjustment of the temperature in the heat generator **38** may be automatically controlled by the hardware processor **19** (controller) of the X-ray Talbot imaging apparatus **1** in conjunction with the X-ray Talbot imaging apparatus **1**.

In other words, the hardware processor **19** controls the series of imaging performed by the X-ray Talbot imaging apparatus **1** to acquire the plurality of moire images Mo, and at the time of the series of imaging, the hardware processor **19** also may control each operation of the heat generator **38** and the arm **38a**.

The heat generator **38** may interfere with X-ray radiation. Therefore, in the X-ray Talbot imaging, it is desirable that the angle and distance of the arm **38a** be appropriately adjusted to make the heat generator **38** shifted from the X-ray radiation range. Note that imaging is performed while at least the heat generator **38** is separated from the object H.

According to this modification, the object housing **30** includes the temperature controllable heat generator **38** which is brought into contact with the object H. Therefore, performing the X-ray Talbot imaging leads to clarification of the mechanism of partial changes in physical properties of the object H brought into contact with the heat generator **38**. Since such X-ray Talbot imaging is performed without changing an installation environment of the X-ray Talbot imaging apparatus **1**, it is possible to prevent troubles in the X-ray Talbot imaging apparatus **1** attributed to the installation environment.

Furthermore, as described in the embodiment, the X-ray Talbot imaging apparatus **1** is preferable in that the X-ray Talbot imaging is performed while the interior of the object housing **30** is set to an environmental condition independent of an external environment and that the object H is imaged under various conditions.

Although embodiments of the present invention have been described and illustrated in detail, the disclosed embodiments are made for purposes of illustration and example only and not limitation. The scope of the present invention should be interpreted by terms of the appended claims.

What is claimed is:

1. An X-ray imaging system comprising:

an X-ray Talbot imaging apparatus comprising an X-ray source, an X-ray detector, a plurality of gratings, and a support on which the X-ray source, the X-ray detector, and the plurality of gratings are mounted,

wherein the X-ray detector is irradiated with an X-ray from the X-ray source through an object and the plurality of gratings to obtain a moire image required for forming a reconstruction image of the object; and an object housing in which the object is housed, the object housing being capable of setting an internal environmental condition therein independent of an external environment,

wherein the object housing is detachably provided on the support.

2. The X-ray imaging system according to claim **1**, wherein the X-ray Talbot imaging apparatus further includes a hardware processor that causes a series of imaging to obtain the moire image required for forming the reconstruction image of the object, and

wherein the hardware processor automatically controls a setting of the internal environmental condition inside the object housing in conjunction with the X-ray Talbot imaging apparatus.

3. The X-ray imaging system according to claim **1**, wherein the internal environmental condition includes a condition related to a temperature and/or a humidity inside the object housing.

4. The X-ray imaging system according to claim **1**, wherein the object housing includes an X-ray transmitter on an X-ray radiation axis and in an X-ray radiation range around the X-ray radiation axis, the X-ray transmitter being less likely to hinder a transmission of an X-ray than a peripheral part.

5. The X-ray imaging system according to claim **4**, wherein the object housing includes a rotator that rotates the object about the X-ray radiation axis.

6. The X-ray imaging system according to claim **1**, wherein each grating of the plurality of gratings comprises a one-dimensional grating.

7. The X-ray imaging system according to claim **1**, wherein the X-ray Talbot imaging apparatus and the object housing are provided mechanically independently from each other.

8. The X-ray imaging system according to claim **7**, wherein the object housing detachably provided on the support is removable from an X-ray radiation range of the X-ray from the X-ray source.

9. The X-ray imaging system according to claim **7**, wherein the object housing detachably provided on the support is movable between positions inside and outside of an X-ray radiation range of the X-ray from the X-ray source.

10. The X-ray imaging system according to claim **1**, wherein the object housing includes a laser radiator that irradiates the object with a laser beam.

11. The X-ray imaging system according to claim **1**, wherein the object housing includes a nail inserter for performing a nailing test on the object.

12. The X-ray imaging system according to claim **1**, wherein the object housing includes a temperature controllable heat generator that is made to contact the object.

13. An X-ray Talbot imaging apparatus, comprising: an X-ray source, an X-ray detector, and a support on which the X-ray source and the X-ray detector are mounted,

wherein the X-ray detector is irradiated with an X-ray from the X-ray source through an object; and

an object housing in which the object is housed, the object housing being capable of setting an internal environmental condition therein independent of an external environment,

wherein the object housing is detachably provided on the support,

the object housing being movable from a position in an X-ray radiation range of the X-ray from the X-ray source to a position outside of the X-ray radiation range.

14. An X-ray imaging method, comprising the steps of: providing an X-ray Talbot imaging apparatus comprising an X-ray source, an X-ray detector, a plurality of gratings, and a support on which the X-ray source, the X-ray detector, and the plurality of gratings are mounted,

irradiating the X-ray detector with an X-ray from the X-ray source through an object and the plurality of gratings to obtain a moire image required for forming a reconstruction image of the object;

housing the object in an object housing that is detachably provided on the support; and setting an internal environmental condition in the object housing independent of an external environment.

15. The X-ray imaging method according to claim **14**,⁵ wherein the step of irradiating the X-ray detector with an X-ray from the X-ray source through an object and the plurality of gratings to obtain a moire image required for forming a reconstruction image of the object includes causing a series of imaging to acquire the moire image required¹⁰ for forming the reconstruction image of the object.

16. The X-ray imaging method according to claim **14**, wherein the step of setting an internal environmental condition in the object housing independent of an external environment includes setting a temperature and/or a humid-¹⁵ity inside the object housing.

17. The X-ray imaging method according to claim **14**, further comprising a step of removing the object housing from an X-ray radiation range of the X-ray from the X-ray²⁰ source.

18. The X-ray imaging method according to claim **14**, further comprising a step of moving the object housing from a position in an X-ray radiation range of the X-ray from the X-ray source to a position outside of the X-ray radiation²⁵ range.

* * * * *