

US011543542B2

(12) **United States Patent**
Talley et al.

(10) **Patent No.:** **US 11,543,542 B2**
(45) **Date of Patent:** **Jan. 3, 2023**

(54) **OCCLUSION-BASED DIRECTIONALITY AND LOCALIZATION OF RADIATION SOURCES WITH MODULAR DETECTION SYSTEMS AND METHODS**

(58) **Field of Classification Search**
CPC G01T 1/2907; G01T 3/00; G01T 1/2008;
G01T 1/208; G01V 5/0075
See application file for complete search history.

(71) Applicant: **FLIR Detection, inc.**, Stillwater, OK (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(72) Inventors: **Kemper Talley**, Oak Ridge, TN (US);
Felix J. Liang, Oak Ridge, TN (US);
William T. Milam, Maryville, TN (US);
Leslie Hoy, Knoxville, TN (US);
Kyle Hawes, Knoxville, TN (US);
Hartmut Brands, Oak Ridge, TN (US);
Steve W. Fleetwood, Knoxville, TN (US)

9,599,727 B2 3/2017 Ouspenski et al.
10,416,322 B1* 9/2019 Newman G01V 5/00
(Continued)

FOREIGN PATENT DOCUMENTS

WO WO 2011/012155 A1 2/2011

OTHER PUBLICATIONS

(73) Assignee: **Teledyne FLIR Detection, Inc.**, Stillwater, OK (US)

Osovizky, A, et al., "SENTIRAD—An Innovative Personal Radiation Detector Based on a Scintillation Detector and a Silicon Photomultiplier", Nuclear Instruments and Methods in Physics Research A, vol. 652, Jan. 12, 2011, pp. 41-44.

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(Continued)

(21) Appl. No.: **17/319,005**

Primary Examiner — David P Porta

(22) Filed: **May 12, 2021**

Assistant Examiner — Fani Polyzos Boosalis

(65) **Prior Publication Data**

US 2021/0278552 A1 Sep. 9, 2021

(74) *Attorney, Agent, or Firm* — Haynes and Boone, LLP

Related U.S. Application Data

(63) Continuation of application No. PCT/US2019/056797, filed on Oct. 17, 2019.
(Continued)


(57) **ABSTRACT**

(51) **Int. Cl.**
G01T 1/208 (2006.01)
G01T 1/20 (2006.01)

(52) **U.S. Cl.**
CPC **G01T 1/2008** (2013.01); **G01T 1/208** (2013.01)

Various techniques are provided to detect the direction and location of one or more radiation sources. In one example, a system includes a plurality of radiation detectors configured to receive radiation from a radiation source. A first one of the radiation detectors is positioned to at least partially occlude a second one of the radiation detectors to attenuate the radiation received by the second radiation detector. The system also includes a processor configured to receive detection information provided by the first and second radiation detectors in response to the radiation, and determine a direction of the radiation source using the detection information. A modular system including gamma radiation detectors and neutron radiation detectors and related methods are also provided. In some cases, radiation source type

(Continued)



may be determined in addition to or separate from radiation source direction.

20 Claims, 6 Drawing Sheets

Related U.S. Application Data

(60) Provisional application No. 62/760,146, filed on Nov. 13, 2018.

(56) **References Cited**

U.S. PATENT DOCUMENTS

10,605,932	B1 *	3/2020	Newman	G01V 5/0091
11,010,852	B2 *	5/2021	Hansell	B64C 39/024
2005/0121618	A1 *	6/2005	Fowler, Jr.	G01T 1/169 250/361 R
2007/0029493	A1	2/2007	Kniss et al.	
2009/0236538	A1	9/2009	Frank	
2009/0294678	A1	12/2009	Frank	

OTHER PUBLICATIONS

Ayaz-Maierhafer, B., et al., "Design Optimization for a Wearable, Gamma-Ray and Neutron Sensitive, Detector Array with Directionality Estimation", Nuclear Instruments and Methods in Physics Research, A, vol. 870, Jul. 27, 2017, pp. 131-139.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

**OCCLUSION-BASED DIRECTIONALITY
AND LOCALIZATION OF RADIATION
SOURCES WITH MODULAR DETECTION
SYSTEMS AND METHODS**

CROSS-REFERENCE TO RELATED
APPLICATIONS

This patent application is a continuation of International Patent Application No. PCT/US2019/056797 filed Oct. 17, 2019 and entitled “OCCLUSION-BASED DIRECTIONALITY AND LOCALIZATION OF RADIATION SOURCES WITH MODULAR DETECTION SYSTEMS AND METHODS”, which is hereby incorporated by reference in its entirety.

International Patent Application No. PCT/US2019/056797 claims the benefit of and priority to U.S. Provisional Patent Application No. 62/760,146 filed Nov. 13, 2018 and entitled “OCCLUSION-BASED DIRECTIONALITY AND LOCALIZATION OF RADIATION SOURCES WITH MODULAR DETECTION SYSTEMS AND METHODS,” which is hereby incorporated by reference in its entirety.

TECHNICAL FIELD

The present invention relates generally to the detection of radiation sources and, more particularly, to the determination of the direction and location of such sources.

BACKGROUND

Radiation detection systems are important tools used to discover and interdict nuclear threats. As such, they are frequently used in support of homeland security, nuclear nonproliferation, and nuclear treaty verification.

Certain existing radiation detection systems are non-directional. In this regard, such systems may detect the presence of a radiation source, but may not be able to discern the actual direction and position of the radiation source. Indeed, such systems may rely on human trial and error until the human user can ascertain a detection pattern and determine the direction and location of the radiation source. Accordingly, such systems can be relatively inefficient and imprecise.

In addition, certain radiation sources may emit multiple types of radiation, for example, both gamma radiation and neutron radiation. However, detecting both types of radiation is often more difficult. For example, many existing radiation detection systems are dedicated to detecting only one type of radiation. As a result, multiple detection devices may be required which can be cumbersome for users.

Although certain lithium-doped scintillators may be used to detect both gamma radiation and neutron radiation using a single detector, such dual-mode detectors have significant limitations. For example, in order to discriminate between gamma radiation and neutron radiation, such detectors may attempt to identify different detected pulse heights and pulse shapes. However, in strong radiation fields, pulse pileup can degrade the detector’s ability to accurately discriminate between gamma radiation and neutron radiation. In addition, such dual-mode detectors typically exhibit low yields during manufacture which increases costs and reduces manufacturing efficiencies.

SUMMARY

In accordance with embodiments discussed herein, techniques are provided to detect the direction and location of

one or more radiation sources. By determining the locations of multiple radiation sources, a radiation map may be provided. A modular system including gamma radiation detectors and neutron radiation detectors and related methods are also provided.

In one embodiment, a system includes a plurality of radiation detectors configured to receive radiation from a radiation source, wherein a first one of the radiation detectors is positioned to at least partially occlude a second one of the radiation detectors to attenuate the radiation received by the second radiation detector; and a processor configured to: receive detection information provided by the first and second radiation detectors in response to the radiation, and determine a direction of the radiation source using the detection information.

In another embodiment, a method includes receiving radiation at a plurality of radiation detectors from a radiation source, wherein a first one of the radiation detectors is positioned to at least partially occlude a second one of the radiation detectors to attenuate the radiation received by the second radiation detector; receiving detection information provided by the first and second radiation detectors in response to the radiation; and determining a direction of the radiation source using the detection information.

In another embodiment, a system includes a plurality of radiation detectors configured to receive radiation from a radiation source, wherein a first one of the radiation detectors is positioned to at least partially occlude a second one of the radiation detectors to attenuate the radiation received by the second radiation detector; and a processor configured to: receive detection information provided by the first and second radiation detectors in response to the radiation, and identify the radiation source using the detection information.

The scope of the invention is defined by the claims, which are incorporated into this section by reference. A more complete understanding of embodiments of the present invention will be afforded to those skilled in the art, as well as a realization of additional advantages thereof, by a consideration of the following detailed description of one or more embodiments. Reference will be made to the appended sheets of drawings that will first be described briefly.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a block diagram of a detection system in accordance with an embodiment of the disclosure.

FIG. 2 illustrates an implementation of a detection system in accordance with an embodiment of the disclosure.

FIG. 3 illustrates radiation detectors receiving radiation from a radiation source positioned at various angles in accordance with an embodiment of the disclosure.

FIG. 4 illustrates ratios of radiation counts detected by radiation detectors from different radiation sources at various angles in accordance with an embodiment of the disclosure.

FIGS. 5 and 6 illustrate radiation counts detected by radiation detectors from different radiation sources at an angle of maximum occlusion in accordance with embodiments of the disclosure.

FIG. 7 illustrates a process of operating a detection system in accordance with an embodiment of the disclosure.

Embodiments of the present invention and their advantages are best understood by referring to the detailed description that follows. It should be appreciated that like

reference numerals are used to identify like elements illustrated in one or more of the figures.

DETAILED DESCRIPTION

In accordance with various embodiments discussed herein, a detection system and related methods are provided to detect the direction and location of one or more radiation sources. For example, by providing multiple radiation detectors (e.g., gamma detectors) that are adjacent to each other, the detectors may at least partially or fully occlude (e.g., shield) each other such that the detectors may detect different radiation counts in response to the same external radiation source.

In this regard, when two gamma detectors placed adjacent to each other, the direction of a radiation source can be determined within 180 degrees (e.g., left or right) in some embodiments and within significantly smaller ranges of angles as further discussed herein. This is due to the absorption of radiation by the occluding detector. By comparing the different radiation counts and/or energy spectra to predetermined radiation counts and/or energy spectra associated with known radiation sources at known directions, the direction (e.g., angles or angle ranges) of a detected radiation source can be determined.

Direction determination can be further enhanced by repositioning (e.g., moving) the detection system along any direction and/or by rotation of the detection system to detect radiation at different known locations within a detection environment. A histogram of data associated with the movement of the detection system can be used to determine the direction of the radiation source within a very small angular cone. For example, in some embodiments, the highest radiation counts may be correlated with a location or orientation provided by a navigation system and/or inertial measurement unit.

In addition, by making multiple direction determinations for different known locations of the detection system, the position of the radiation source may be determined and mapped. Also, detected radiation counts and/or energy spectra may be used to discriminate between multiple radiation sources in a detection environment and determine the types of radiation sources detected.

Thus, by using the occlusion properties of multiple adjacent detectors, the detection system is not required to provide or manipulate complex masks or shielding systems to discern the distribution or direction of radiation sources. Moreover, the use of multiple adjacent detectors as discussed herein improves upon conventional Compton cameras and imagers that typically require long count times and high cost, or Bayesian localization and machine learning techniques that may be computationally complex.

Also in accordance with embodiments discussed herein, a detection system and related methods are provided to include gamma detectors and neutron detectors together in a compact modular form factor. For example, by implementing neutron detectors in the form of elongate (e.g., flat) panels, multiple neutron detectors may be disposed around multiple gamma detectors to perform both neutron and gamma detection while also detecting the direction and location of one or more radiation sources using the gamma detector occlusion principles discussed herein.

FIG. 1 illustrates a block diagram of a detection system **100** in accordance with an embodiment of the disclosure. Detection system **100** may be implemented with different form factors for use with different physical platforms in various environments. For example, in some embodiments,

detection system **100** may be implemented in a modular form that is ruggedized and scalable for deployment as a personal radiation detector (PRD), a spectroscopic personal radiation detector (SPRD), a man-portable radiation detector system (MRDS), a radioisotope identifying detector (RIID), an unmanned aerial vehicle (UAV), an unmanned ground vehicle (UGV), an unmanned surface vehicle (USV), an unmanned underwater vehicle (UUV), an unmanned spacecraft, a portal monitor, and/or an imaging device.

Detection system **100** includes a plurality of radiation detectors **110** and **120**. In particular, gamma detectors **110** are configured to detect gamma radiation. Although two gamma detectors **110** are explicitly shown, any desired number of gamma detectors may be provided. As further discussed herein, gamma detectors **110** may be positioned adjacent to each other such that at one or more of gamma detectors **110** at least partially occludes one or more other gamma detectors **110** in relation to a radiation source.

Gamma detectors **110** include scintillators **112** configured to emit photons in response to incident gamma radiation. In some embodiments, scintillators **112** may be implemented by various types of scintillating materials such as sodium iodide (NaI), cesium iodide (CsI), lanthanum bromide (LaBr), cerium bromide (CeBr), and/or other materials.

Gamma detectors **110** also include sensors **116** configured to receive the photons provided by scintillators **112** and convert them into electric pulses to detect gamma radiation counts and energy spectra associated with the photons. In various embodiments, sensors **116** may be implemented as photosensors (e.g., silicon photomultipliers and/or others) and/or semiconductors (e.g., germanium (Ge) and/or others).

In some embodiments, gamma detectors **110** may be implemented with semiconductors using, for example, cadmium zinc telluride (CdZnTe), thallium bromide (TlBr), and/or other materials that convert gamma radiation into electrons and holes and output electrical pulses.

Gamma detection information (e.g., signals comprising analog or digital data and also referred to as sensor information) from sensors **116** may be provided to processor **130**. Such gamma detection information may include, for example, gamma radiation counts, gamma radiation count rates, energy spectra associated with the gamma radiation counts, and/or data to be used by processor **130** to determine the counts, count rates, and/or energy spectra.

Detection system **100** also includes a plurality of neutron detectors **120** configured to detect neutron radiation. Although two neutron detectors **120** are explicitly shown, any desired number of neutron detectors may be provided. As further discussed herein, neutron detectors **120** may be implemented as panels positioned in a manner that surrounds (e.g., encircles) gamma detectors **110** to provide a compact modular implementation of detection system **100**.

Neutron detectors **120** include scintillators **122** configured to emit photons in response to incident neutron radiation. In some embodiments, scintillators **122** may be implemented by various types of scintillating materials (e.g., neutron conversion materials) such as lithium compounds, boron compounds, and/or other materials.

Neutron detectors **120** also include light guides **124** configured to pass photons (e.g., fluorescence) from scintillators **122** to sensors **126**. Neutron detectors **120** also include sensors **126** configured to receive the photons provided by scintillators **122** and convert them into electric pulses. Sensors **126** which may be implemented, for example as photosensors and/or semiconductors as previously discussed

with regard to sensors **116**. In some embodiments, neutron detectors **120** may further include wavelength shifters.

Neutron detection information (e.g., signals comprising analog or digital data and also referred to as sensor information) from sensors **126** may be provided to processor **130**. Such neutron radiation detection information may include, for example, neutron radiation counts, neutron radiation count rates, and/or data to be used by processor **130** to determine the counts and/or count rates.

Detection system **100** also includes a neutron moderator **128** which may surround (e.g., encircle) neutron detectors **120**. In this regard, neutron moderator **128** operates to reduce the speed of incident neutrons to increase the probability of detection. As further discussed herein, neutron moderator **128** may surround neutron detectors **120** and gamma detectors **110** in a modular implementation of detection system **100**. In some embodiments, neutron moderator **128** may be implemented using one or more hydrogen-rich materials (e.g., high-density polyethylene) to perform neutron moderation while also providing a protective shell.

As discussed, processor **130** receives detection information from sensors **116** and **126** to determine overall numbers of radiation counts, radiation count rates, and energy spectra. In addition, processor **130** may be used to cause detection system **100** to perform any of the operations discussed herein. In various embodiments, processor **130** may be implemented as one or more microprocessors, microcontrollers, application specific integrated circuits (ASICs), programmable logic devices (PLDs) (e.g., field programmable gate arrays (FPGAs), complex programmable logic devices (CPLDs), field programmable systems on a chip (FPSCs), or other types of programmable devices), or other processing devices. In this regard, processor **130** may execute machine readable instructions (e.g., software, firmware, or other instructions) stored in memory **132**.

In various embodiments, processor **130** may process the detection information received from sensors **116** and **126** to build an energy histogram and perform radiation source identification. Such data may be integrated with data received from any other portions of detection system **100** for additional situational awareness.

Memory **132** may be implemented as a machine readable medium storing various machine readable instructions and data. For example, in some embodiments, memory **132** may store an operating system and one or more applications as machine readable instructions that may be read and executed by processor **130** to perform various operations described herein. Memory **132** may also store various types of data discussed herein, such as radiation counts, count rates, count ratios, energy spectra, position information, radiation maps, and/or other information associated with various radiation sources. For example, in some embodiments, memory **132** may store the ratio of gamma radiation counts received by at least two gamma detectors **110** in response to a known radiation source at various angles of incidence. These predetermined count ratios may be compared with newly determined count ratios to identify the type and direction of a new radiation source. In some embodiments, memory **132** may be implemented as non-transitory non-volatile memory (e.g., flash memory, hard drive, solid state drive, or others), volatile memory, or combinations thereof.

Navigation system **134** may be used to detect the location of detection system **100** in accordance with various navigation signals, such as global positioning signals and/or other types of navigation signals as appropriate. In some embodiments, navigation system **134** may include a compass or other appropriate directional devices.

Inertial measurement unit **136** may be used to detect and trace the relative movement of detection system **100**, for example, as a user or a vehicle moves through space in relation to various radiation sources. This can permit detection system **100** to ascertain the relative location of radiation sources detected by gamma detectors **110**. Moreover, by using the location information provided by navigation system **134**, the relative location information provided by inertial measurement unit **136**, and the radiation detection information provided by gamma detectors **110**, detection system **100** may further determine the absolute location of radiation sources. In various embodiments, inertial measurement unit **136** may be implemented using an accelerometer, gyroscope, magnetometer, and/or other devices.

Temperature sensor **138** detects the temperature of the environment and/or detectors **110/120** to operate detectors **110/120** in a stabilized manner in accordance with pre-calibrated gain settings. Other sensors **140** may be provided for measuring additional information as appropriate for particular implementations of detection system **100**.

One or more preamplifiers **142** operate to amplify signals provided by gamma detectors **110** and neutron detectors **120** for further use by processor **130**. Power supply **144** provides electrical power to operate the various components of detection system **100**. For example, in the case of a mobile implementation of detection system **100**, power supply may be a battery. Bias circuitry **146** receives electrical power from power supply **144** and provides appropriate voltage and/or current bias signals to sensors **116** and **126** to operate gamma detectors **110** and neutron detectors **120**.

Communication interface **148** may be implemented as one or more wireless interfaces (e.g., WiFi, Bluetooth, cellular, infrared, radio, and/or other types) and/or wired interfaces (e.g., Universal Serial Bus (USB), Ethernet, and/or other types). In this regard, communication interface **148** may send and/or receive communication signals **192** to and/or from a remote device **190**. In some embodiments, remote device **190** may be implemented as a smart phone or tablet running one or more applications (e.g., using a processor and memory in a similar manner as discussed with regard to processor **130** and memory **132**). For example, in some embodiments, detection system **100** may provide information to remote device **190** (e.g., radiation detection results and/or radiation maps) and may receive commands therefrom. In some embodiments, the processing performed by processor **130** may be performed by remote device **190** and vice versa.

Display **150** presents information to a user of detection system **100**. In various embodiments, display **150** may be implemented as a liquid crystal display (LCD), an organic light emitting diode (OLED) display, and/or any other appropriate display.

User controls **152** receive user input to operate detection system **100**. In various embodiments, user controls **152** may be implemented by one or more buttons, keyboards, levers, joysticks, and/or other controls. In some embodiments, user controls **152** may be integrated with display **150** as a touchscreen.

Other components **154** may also be provided as appropriate to support, for example, particular implementations of detection system **100**. For example, in some embodiments, other components **154** may include one or more propulsion systems, actuators, attachment mechanisms, and/or other features to move detection system **100** and/or secure detection system **100** to a user or other platform (e.g., a vehicle).

FIG. 2 illustrates an implementation of detection system **100** in accordance with an embodiment of the disclosure. In

the particular embodiment shown in FIG. 2, detection system 100 is implemented as a modular system with two gamma detectors 110 and six neutron detectors 120. However, any desired number of each type of detector may be provided in various geometries.

In this embodiment, the two gamma detectors 110 include circuit boards that also include connectors 111 for attaching any of the various components of FIG. 1 to the gamma detectors 110. Also in this embodiment, the six neutron detectors 120 are each implemented by an elongate panel such that they surround the two gamma detectors 110 as shown. By implementing neutron detectors 120 as elongate panels as shown, they can be positioned to closely wrap around gamma detectors 110 more efficiently than would be possible using conventional neutron detectors they typically rely on helium-3 tubes.

In addition, neutron moderator 128 is provided as an outer shell that surrounds the neutron detectors 120 to reduce the speed of incident neutrons received from the outside environment before they pass to neutron detectors 120. Also, this embodiment includes a support structure 160 which may be used, for example, as a mounting platform to receive any of the components of FIG. 1.

Thus, it will be understood that detection system 100 may be implemented in a modular system with gamma detectors 110, neutron detectors 120, and neutron moderator 128 provided in an efficient and compact manner. In particular, by implementing neutron detectors 120 as elongate panels, they can be conveniently positioned around the gamma detectors to save space while still being further surrounded by neutron moderator 128 which effectively acts as a protective shell around the gamma detectors 110 and neutron detectors 120 while still providing neutron moderation.

Although two gamma detectors 110 are shown in a 2x1 array in FIG. 2, other configurations are contemplated. For example, any desired number of gamma detectors 110 may be provided in various arrays such as 3x1, 2x2, and so on. Similarly, the number of neutron detectors 120 can be increased or decreased as to surround the gamma detectors 110 as appropriate.

Moreover, although a rectangular arrangement of gamma detectors 110 is illustrated in FIG. 2, other arrangements may be provided (e.g., non-rectangular and/or irregular arrangements) while still providing the benefits discussed herein.

FIG. 3 illustrates two gamma detectors 110 of detection system 100 receiving radiation from a radiation source 300 (e.g., isotope) selectively positioned at various angles in accordance with an embodiment of the disclosure. For ease of discussion, the two gamma detectors 110 are individually identified as gamma detector 110A and gamma detector 110B and are illustrated alone without the remaining components of detection system 100. Radiation source 300 emits gamma radiation 310 and, in some embodiments may also emit neutron radiation as further discussed herein.

As shown, gamma detectors 110A and 110B are positioned adjacent to each other and are aligned along an axis 301. A radiation source 300 is shown at different positions 302A to 302G, each of which causes radiation source 300 to emit gamma radiation 310 toward gamma detectors 110A and 110B at a different angle of incidence (e.g., measured in relation to axis 301) for each position. For example, at position 302A, radiation source 300 emits gamma radiation 310 at an angle of 0 degrees parallel to axis 301. At position 302G, radiation source 300 emits gamma radiation 310 at an angle of 90 degrees perpendicular to axis 301. At intermediate positions 302B-F, radiation source 300 emits gamma

radiation 310 at 15 degrees, 30 degrees, 45 degrees, 60 degrees, and 75 degrees relative to axis 301, respectively. Although different angles of 15 degree increments are shown distributed along a horizontal plane, any desired positions may be used in other directions as desired.

As a result of the adjacent positioning of gamma detectors 110A and 110B, gamma detector 110A may occlude gamma detector 110B with regard to gamma radiation 310 received from certain angles (e.g., directions). In this regard, gamma detector 110A may at least partially shield gamma detector 110B relative to radiation source 300. For example, when radiation source 300 is at position 302A, gamma detector 110A fully occludes gamma detector 110B. In this case, gamma detector 110A will receive gamma radiation 310 directly from radiation source 300. Meanwhile, gamma detector 110B will receive at least some of gamma radiation 310 only after it has already passed through and become attenuated by gamma detector 110A. As a result, gamma detector 110A will receive higher numbers of radiation counts than gamma detector 110B when radiation source 300 is at position 302A.

Similarly, for each of positions 300B-300F, gamma detector 110A will continue to at least partially occlude gamma detector 110B, thus causing gamma detector 110A to continue receiving higher numbers of radiation counts than gamma detector 110B. However, as radiation source 300 transitions through positions 300B to 300E, the amount of occlusion diminishes as gamma detector 110B receives a higher proportion of gamma radiation 310 directly from radiation source 300 rather than passed through gamma detector 110A. As a result, the ratio of radiation counts received by gamma detector 110A in relation to gamma detector 110B will vary based on the particular location of radiation source 300.

Finally, for position 300G (e.g., 90 degrees), gamma detector 110A no longer occludes gamma detector 110B. In this case, gamma detectors 110A and 110B may receive substantially the same number of radiation counts in response to gamma radiation 310. As a result, the ratio of radiation counts received by gamma detector 110A in relation to gamma detector 110B will be approximately equal to 1.

These principles can be further understood with reference to FIG. 4 which illustrates ratios of radiation counts received by gamma detectors 110A and 110B from different types of radiation sources at various angles in accordance with an embodiment of the disclosure. In particular, FIG. 4 identifies plots 410 to 440 corresponding to the ratios of total radiation counts received for different configurations of gamma detectors 110A and 110B and different types of radiation sources 300.

To provide plots 410 to 440, gamma detectors 110A and 110B were implemented with different sizes (e.g., both implemented as 35 mm³ detectors or both implemented as 18 mm³ detectors) and tested to observe the angular dependence on their radiation count ratios in relation to radiation source 300. By examining the ratio of counts observed between gamma detectors 110A and 110B, it is possible to discern whether or not radiation source 300 is within a cone of varying degrees based on the counting time and spectral data. In this regard, the raw counts in a low background environment are sufficient to distinguish a 48 μCi 137Cs or 10 μCi 60Co radiation source 300 placed 50 cm away for both detector sizes. It is also possible to further determine if the 48 μCi 137Cs radiation source 300 is within a 30 degree cone for 35 mm³ gamma detectors 110A and 110B at a distance of 200 cm.

Plot **410** was obtained using gamma detectors **110A** and **110B** provided with scintillators **112** implemented by CsI cubes of 35 mm lengths coupled to sensors **116** implemented with silicon photomultipliers (SiPMs) with four quads in a 2x2 configuration where a quad is made-up of four 6x6 mm² SiPMs in a 2x2 configuration (e.g., effectively 16 SiPMs). In addition, plot **410** utilized radiation source **300** implemented by 48 μ Ci ¹³⁷Cs positioned at a distance of 200 cm from gamma detectors **110A** and **110B**.

Plot **420** was obtained using gamma detectors **110A** and **110B** implemented in the manner of plot **410** and with radiation source **300** implemented by 10 μ Ci ⁶⁰Co positioned at a distance of 50 cm from gamma detectors **110A** and **110B**.

Plot **430** was obtained using gamma detectors **110A** and **110B** provided with scintillators **112** implemented by CsI cubes of 18 mm lengths coupled to sensors **116** implemented with four 6x6 mm² SiPMs in a 2x2 configuration. In addition, plot **430** utilized radiation source **300** implemented by 48 μ Ci ¹³⁷Cs positioned at a distance of 50 cm from gamma detectors **110A** and **110B**.

Plot **440** was obtained using gamma detectors **110A** and **110B** implemented in the manner of plot **430** and with radiation source **300** implemented by 10 μ Ci ⁶⁰Co positioned at a distance of 50 cm from gamma detectors **110A** and **110B**.

For each of plots **410-440**, radiation source **300** was moved in 15 degree increments relative to gamma detectors **110A** and **110B** in a horizontal plane through positions **302A** to **302G** (e.g., from 0 degrees to 90 degrees). Each measurement was taken for five minutes to provide a baseline measurement was achieved.

As shown in FIG. 4, the ratio of total counts observed by gamma detectors **110A** and **110B** varies based on the angle of incidence for all of plots **410** to **440** regardless of the particular detector implementation or type of radiation source **300**. As a result of this angular dependence, processor **130** may be used to determine the direction of radiation source **300** relative to detection system **100** using the ratio of counts between gamma detectors **110A** and **110B**.

For example, as shown in FIG. 4, significant changes in the ratio of counts are exhibited from position **302A** through position **302B**. As a result, by determining the ratio between radiation counts, processor **130** may be able to determine the direction of radiation source **300** within a cone of 30 degrees (e.g., corresponding to ± 15 degrees centered on axis **301**).

Indeed, changes in the ratio of counts continue to be exhibited through position **302C** where the ratio still remains above 1.1. As a result, processor **130** may be able to determine the direction of radiation source **300** within a cone of 60 degrees (e.g., corresponding to ± 30 degrees centered on axis **301**).

Moreover, in some embodiments, the direction of radiation source **300** may be determined to a desired degree of accuracy depending on various factors including, for example, the configuration of the various detectors **110**, the count rate incident upon the detectors **110**, the counting time, and/or the position of the radiation source **300** relative to the detectors. For example, if the radiation source **300** is positioned at location **302G** (e.g. 90 degrees where no occlusion is occurring), then detection system **100** may be moved as appropriate to introduce occlusion to resolve which side (e.g., left or right) the radiation source **300** is positioned.

As also shown in FIG. 4, larger gamma detectors **110A/110B** may result in higher count ratios due to the larger amount of shielding and radiation absorption afforded by

their larger volume. For example, plot **420** (corresponding to the larger 35 mm³ size) exhibits a significantly higher count ratio in comparison to plot **440** (corresponding to the smaller 18 mm³ size) at positions **302A** and **302B**. This is particularly clear with regard to position **302A** which is incident along axis **301** at an angle of 0 degrees.

For plots **410** and **420**, the average background gamma radiation was 29.3 counts per second and 30.7 counts per second for gamma detectors **110A** and **110B**, respectively. Also for plot **410**, the combined average background gamma radiation was 151 counts per second including both gamma detectors **110A** and **110B**, while for plot **420** it was 60 counts per second. For plots **430** and **440**, the average background gamma radiation was 7.3 counts per second and 7.0 counts per second for gamma detectors **110A** and **110B**, respectively. The increased background radiation associated with plot **410** results in its count ratio being closer to 1 than the other plots where the background radiation was less than 20% of the count rate with radiation source **300** present at 50 cm.

Also in FIG. 4, the effect of detector size on linear attenuation can be seen by comparing the ratios of the total counts of plots **420** and **440** corresponding to 35 mm³ and 18 mm³ gamma detectors **110A/110B**. Although the larger 35 mm³ gamma detectors **110A/110B** exhibit a larger solid angle to receive gamma radiation, the 35 mm³ size causes more absorption than the 18 mm³ and thus results in a larger count ratio as demonstrated by plots **420** and **440** at position **302A**.

Also in FIG. 4, the effect of detector size on absorption efficiency is evident by comparing the ratios of plots **430** and **440** using 18 mm³ detectors with different 48 μ Ci ¹³⁷Cs and 10 μ Ci ⁶⁰Co radiation sources **300**, respectively. In this regard, the total counts observed for the 10 μ Ci ⁶⁰Co radiation source **300** was much lower owing to its higher energy peaks. Although the count ratios begin to converge past position **302C** (e.g., 30 degrees), there is nevertheless a large difference between the count ratios from position **302A** through position **302C** (e.g., from 0 degrees through 30 degrees). In some embodiments, the convergence of the count ratios beyond position **302C** may be caused by faces of gamma detectors **110A** and **110B** exhibiting reduced occlusion in relation to each other. Accordingly, various adjustments may be made to provide a desired detector configuration in accordance with various design considerations of detection system **100** including, for example, count time, efficiency, cost, form factor, and other factors.

In some cases, the ratio of counts may be increased by considering only the counts near peak positions (e.g., peak energy spectra corresponding to particular energy bands) for radiation source **300**. In particular, by isolating the dependence of directionality on radiation counts located around the peaks while ignoring the background radiation, the count ratios may be increased for more accurate processing and location determination. For example, FIGS. 5 and 6 illustrate radiation counts detected by gamma detectors **110A** and **110B** from different radiation sources **300** at an angle of maximum occlusion (e.g., at position **302A** along axis **301**) in accordance with embodiments of the disclosure.

In particular, FIG. 5 illustrates the radiation counts and corresponding energy spectra detected by 35 mm³ gamma detectors **110A** and **110B** from a 10 μ Ci ⁶⁰Co radiation source **300** at position **302A** at a distance of 50 cm (e.g., corresponding to position **302A** of plot **420**). In this case, a total of 61811 counts were detected by gamma detector **110A** and a total of 39502 counts were detected by gamma detector **110B**. As shown in FIG. 5, energy bands **520** and

11

530 exhibit substantial differences in the counts detected by gamma detectors 110A and 110B.

FIG. 6 illustrates the radiation counts and corresponding energy spectra detected by 35 mm³ gamma detectors 110A and 110B from a 48 μCi 137Cs radiation source 300 at position 302A at a distance of 200 cm (e.g., corresponding to position 302A of plot 410). In this case, a total of 25591 counts were detected by gamma detector 110A and a total of 19024 counts were detected by gamma detector 110B. As shown in FIG. 6, energy bands 620 exhibits substantial differences in the counts detected by gamma detectors 110A and 110B. In particular, the ratio of counts near the 662 keV peak at energy band 620 is 2.89 which is significantly larger than the overall ratio of 1.35 for the total counts (e.g., see plot 410 at position 302A in FIG. 4).

Thus, by using the ratio of counts corresponding to particular energy bands (e.g., energy bands 520, 530, and 620 in FIGS. 5 and 6), processor 130 may more effectively isolate radiation source 300 from background radiation. In some embodiments, processor 130 may determine the directions of multiple radiation sources 300 using each isotope's unique peak count ratios. In this regard, count times may be extended as appropriate and additional sensor fusion processing such as a Kalman filter may be used.

FIG. 7 illustrates a process of operating detection system 100 in accordance with an embodiment of the disclosure. In block 710, detection system 100 is initially positioned in proximity to radiation source 300 which may be an unknown radiation source 300 at an unknown distance and unknown direction. For example, in the case of a user-mounted implementation of detection system 100 (e.g., a PRD, SPRD, MRDS, or other system) the user may position themselves in proximity to radiation source 300 while wearing (e.g., attached to the user's person, clothing, in a backpack, and/or any appropriate location), holding, and/or otherwise supporting detection system 100. In other cases, detection system 100 may be positioned manually and/or remotely (e.g., by maneuvering any of the various vehicles and/or platforms discussed herein into position).

In block 715, the two or more gamma detectors 110 (e.g., gamma detectors 110A and 110B as discussed) receive gamma radiation from radiation source 300. In block 720, the two or more gamma detectors 110 detect the gamma radiation counts and energy spectra associated with the received gamma radiation. For example, gamma detection information from sensors 116 of gamma detectors 110 may be provided to processor 130 to count the number of gamma emissions received over time and record the number of counts, the count rate, and the energy level associated with each count. In various embodiments, blocks 715 and 720 may be performed simultaneously during a predetermined length of time (e.g., a predetermined detection period) and/or until a sufficient number of gamma radiation counts have been received.

In block 725, one or more neutron detectors 120 receive neutron radiation from radiation source 300. In this regard, radiation source 300 may emit both gamma radiation and neutron radiation to be detected by gamma detectors 110 and neutron detectors 120, respectively. In block 730, the neutron detectors 120 detect neutron radiation counts associated with the received neutron radiation. For example, neutron detection information from sensors 126 may be provided to processor 130 to count the number of neutron radiation emissions received over time and thus record the number of counts and the count rate. In various embodiments, blocks 725 and 730 may be performed simultaneously during a predetermined length of time (e.g., a predetermined detec-

12

tion period) and/or until a sufficient number of neutron radiation counts have been received.

Also, in some embodiments, blocks 715 through 730 may be performed simultaneously such that gamma radiation and neutron radiation may be simultaneously detected by detection system 100 using gamma detectors 110 and neutron detectors 120, respectively. In this regard, the compact modular implementation of detection system 100 (e.g., discussed with regard to FIG. 2) may be advantageously used to permit both gamma radiation and neutron radiation to be simultaneously detected in an efficient manner even in high radiation fields.

In block 735, processor 130 compares the gamma detection information (e.g. gamma radiation counts and gamma radiation energy spectra) and neutron detection information (e.g., neutron radiation counts) with predetermined gamma detection information and predetermined neutron detection information stored in memory 132 which are associated with known radiation sources at known directions. For example, processor 130 may compare the gamma radiation counts provided by gamma detectors 110A and 110B with known gamma radiation counts associated with different directions that have been previously determined by prior testing using known radiation sources at known directions.

In some embodiments, the comparisons performed in block 735 may include determining the ratio of gamma detector counts associated with gamma detectors 110A and 110B and comparing the determined count ratio to predetermined count ratios. Other types of calculations are also contemplated for the comparisons.

Also, in some embodiments, the comparisons performed in block 735 may be limited to certain energy bands that exhibit significant differences in the gamma radiation counts determined by gamma detectors 110A and 110B. For example, as discussed with regard to FIGS. 5 and 6, certain energy bands (e.g., energy bands 520, 530, and 620) may exhibit substantial differences in counts for particular radiation sources 300. By limiting the comparisons to these or other selected energy bands, higher count ratios may be determined and utilized for more accurate analysis.

In block 740, processor 130 determines the direction of radiation source 300 using the comparisons performed in block 735. As discussed with regard to FIGS. 3-6, the direction of radiation source 300 may correlate to the gamma radiation counts detected by gamma detectors 110A and 110B when positioned adjacent to each other such that gamma detector 110A at least partially occludes gamma detector 110B. Thus, by comparing the counts detected by gamma detectors 110A and 110B with known gamma radiation counts associated with known directions, processor 130 may determine a correlation (e.g., through comparison, interpolation, and/or other processing techniques) between the gamma radiation counts detected by gamma detectors 110A and 110B and predetermined gamma radiation counts associated with a predetermined direction. Thus, processor 130 may determine the direction (e.g., angular location) of radiation source 300 with high confidence.

In block 745, processor 130 determines the type of radiation source 300 (e.g., a particular isotope) using the comparisons performed in block 735. For example, certain radiation sources may exhibit gamma radiation in particular energy bands and/or known relationships between detected gamma radiation and detected neutron radiation. Accordingly, by comparing the detected gamma radiation counts, detected gamma radiation energy spectra, and detected neutron radiation counts to known values stored in memory 132, processor 130 may correlate the detected values with known

13

values associated with a known radiation source to identify the particular type of radiation source **300** being detected (e.g., a 48 μCi ^{137}Cs radiation source, a 10 μCi ^{60}Co radiation source, and/or others).

Although FIG. 7 identifies that the direction of radiation source **300** may be determined (block **740**) and the type of radiation source **300** may be determined (block **745**), both determinations are not required to be performed. For example, in various embodiments, the direction, the type, and/or both may be determined as appropriate for particular implementations.

In block **750**, processor **130** associates the direction determined in block **740** and the radiation source type determined in block **745** with the current position of detection system **100**. As discussed, navigation system **134** may be used to detect the location of detection system **100**. In addition, inertial measurement unit **136** may be used to further refine this location as detection system **100** moves. Accordingly, processor may store an association between the direction, radiation source type, and current position in memory **132** to provide a record of radiation source **300** for further use in generating a radiation map.

In block **755**, processor **130** and/or a user determines whether further detection operations should be performed at another location. In this regard, detection system **100** may be selectively repositioned (e.g., translated and/or rotated) to other locations to again receive radiation and determine the direction and type of the same radiation source **300** or additional radiation sources **300**.

If additional locations are to be detected, then the process returns to block **710** where detection system **100** is repositioned and the process repeats. Otherwise, the process continues to block **760**.

By repeating the process of FIG. 7 for different positions of detection system **100**, processor **130** may generate and store in memory **132** multiple associations between the direction, radiation source type, and position of one or more radiation sources **300**. For example, by determining the directions of a radiation source relative to multiple positions of detection system **100**, processor **130** may determine a location of the radiation source based on an intersection of the determined directions (e.g., through triangulation, interpolation, and/or other techniques).

Accordingly, in block **760**, processor **130** generates a map of radiation sources **300** identifying their locations and radiation source type. In various embodiments, the radiation map may be provided to a user for review (e.g., presented on display **150** and/or remote device **190**) and/or to appropriate systems for further processing and analysis.

Where applicable, various embodiments provided by the present disclosure can be implemented using hardware, software, or combinations of hardware and software. Also where applicable, the various hardware components and/or software components set forth herein can be combined into composite components comprising software, hardware, and/or both without departing from the spirit of the present disclosure. Where applicable, the various hardware components and/or software components set forth herein can be separated into sub-components comprising software, hardware, or both without departing from the spirit of the present disclosure. In addition, where applicable, it is contemplated that software components can be implemented as hardware components, and vice-versa.

Software in accordance with the present disclosure, such as program code and/or data, can be stored on one or more non-transitory machine readable mediums. It is also contemplated that software identified herein can be imple-

14

mented using one or more general purpose or specific purpose computers and/or computer systems, networked and/or otherwise. Where applicable, the ordering of various steps described herein can be changed, combined into composite steps, and/or separated into sub-steps to provide features described herein.

Embodiments described above illustrate but do not limit the invention. It should also be understood that numerous modifications and variations are possible in accordance with the principles of the present invention. Accordingly, the scope of the invention is defined only by the following claims.

What is claimed is:

1. A system comprising:
 - a plurality of gamma radiation detectors configured to receive gamma radiation from a radiation source, wherein a first one of the gamma radiation detectors is positioned to at least partially occlude a second one of the gamma radiation detectors to attenuate the gamma radiation received by the second gamma radiation detector;
 - a neutron moderator shell;
 - a plurality of neutron radiation detectors implemented as panels surrounding the first and second gamma radiation detectors and configured to receive neutron radiation from the radiation source passed by the neutron moderator shell; and
 - a processor configured to:
 - receive gamma detection information provided by the first and second gamma radiation detectors in response to the gamma radiation,
 - receive neutron detection information provided by the neutron radiation detectors in response to the neutron radiation, and
 - determine a direction of the radiation source using the detection information.
2. The system of claim 1, wherein the processor is configured to:
 - compare the received gamma and neutron detection information with predetermined detection information associated with a predetermined direction;
 - determine a correlation between the received gamma and neutron detection information and the predetermined detection information associated with the predetermined direction; and
 - wherein the direction of the radiation source is determined using the correlation.
3. The system of claim 2, wherein the gamma detection information comprises a ratio of radiation counts detected by the first and second gamma radiation detectors.
4. The system of claim 1, wherein the direction comprises a range of angles.
5. The system of claim 1, wherein:
 - the system is configured to be moved to receive the gamma radiation at the first and second gamma radiation detectors at a plurality of positions; and
 - the processor is configured to:
 - receive additional gamma detection information provided by the first and second gamma radiation detectors in response to the radiation received for each of the positions,
 - determine a direction of the radiation source for each of the positions using the additional gamma detection information, and
 - determine a location of the radiation source using the determined directions.

15

6. The system of claim 5, wherein:
the processor is configured to:
determine locations for a plurality of radiation sources;
and
generate a radiation map comprising the determined 5
locations of the radiation sources; and
the system further comprises a communication interface
configured to transmit the radiation map to a remote
device.
7. The system of claim 1, wherein: 10
the gamma detection information comprises gamma
radiation counts and gamma radiation energy spectra;
the neutron detection information comprises neutron
radiation counts; and
the processor is configured to identify the radiation source 15
using the gamma radiation counts, the gamma radiation
energy spectra, and the neutron radiation counts.
8. The system of claim 1, wherein the system is config-
ured to be provided on a user and/or on a vehicle. 20
9. The system of claim 1, further comprising:
an inertial measurement unit configured to detect relative
movement of the radiation detectors in relation to the
radiation source; and
wherein the processor is configured to: 25
receive location information provided by a navigation
system,
receive relative location information provided by the
inertial measurement unit, and
determine an absolute location of the radiation source 30
using the location information, the relative location
information, and the detection information.
10. A method comprising:
receiving gamma radiation at a plurality of gamma radia- 35
tion detectors from a radiation source, wherein a first
one of the gamma radiation detectors is positioned to at
least partially occlude a second one of the gamma
radiation detectors to attenuate the gamma radiation
received by the second gamma radiation detector, 40
wherein a plurality of neutron radiation detectors
implemented as panels surround the first and second
gamma radiation detectors and are configured to
receive neutron radiation from the radiation source
passed by a neutron moderator shell; 45
receiving gamma detection information provided by the
first and second gamma radiation detectors in response
to the radiation;
receiving neutron detection information provided by the
neutron radiation detectors in response to the neutron 50
radiation; and
determining a direction of the radiation source using the
detection information.
11. The method of claim 10, further comprising:
comparing the received gamma and neutron detection 55
information with predetermined detection information
associated with a predetermined direction;
determining a correlation between the received gamma
and neutron detection information and the predeter-
mined detection information associated with the pre- 60
determined direction; and
wherein the direction of the radiation source is determined
using the correlation.
12. The method of claim 11, wherein the gamma detection
information comprises a ratio of radiation counts detected by 65
the first and second gamma radiation detectors, wherein the
direction comprises a range of angles.

16

13. The method of claim 10, further comprising:
moving the first and second gamma radiation detectors to
receive the gamma radiation at a plurality of positions;
receiving additional gamma detection information pro-
vided by the first and second gamma radiation detectors
in response to the gamma radiation received for each of
the positions;
determining a direction of the radiation source for each of
the positions using the additional gamma detection
information; and
determining a location of the radiation source using the
determined directions.
14. The method of claim 13, further comprising:
determining locations for a plurality of radiation sources;
generating a radiation map comprising the determined
locations of the radiation sources; and
transmitting the radiation map to a remote device.
15. The method of claim 10, wherein:
the gamma detection information comprises gamma
radiation counts and gamma radiation energy spectra;
the neutron detection information comprises neutron
radiation counts; and
the method further comprises identifying the radiation
source using the gamma radiation counts, the gamma
radiation energy spectra, and the neutron radiation
counts.
16. The method of claim 10, wherein the method is
performed by a detection system provided on a user and/or
on a vehicle.
17. The method of claim 10, further comprising:
receiving location information provided by a navigation
system;
receiving relative location information provided by an
inertial measurement unit configured to detect relative
movement of the radiation detectors in relation to the
radiation source; and
determining an absolute location of the radiation source
using the location information, the relative location
information, and the detection information.
18. A system comprising:
a plurality of radiation detectors configured to receive
radiation from a radiation source, wherein a first one of
the radiation detectors is positioned to at least partially
occlude a second one of the radiation detectors to
attenuate the radiation received by the second radiation
detector;
a plurality of neutron detectors implemented as panels
surrounding the first and second radiation detectors;
an inertial measurement unit configured to detect relative
movement of the radiation detectors in relation to the
radiation source; and
a processor configured to:
receive detection information provided by the first and
second radiation detectors in response to the radia-
tion,
identify the radiation source using the detection infor-
mation,
receive location information provided by a navigation
system,
receive relative location information provided by the
inertial measurement unit, and
determine an absolute location of the radiation source
using the location information, the relative location
information, and the detection information.
19. The system of claim 18, wherein:
the radiation detectors are gamma radiation detectors
configured to detect gamma radiation from the radia-
tion source;

the detection information is gamma detection information provided in response to the gamma radiation; the system further comprises a neutron moderator shell; and the plurality of neutron radiation detectors are configured 5 to receive neutron radiation from the radiation source passed by the neutron moderator shell and provide neutron detection information in response to the neutron radiation.

20. A method of operating the system of claim **18**, the 10 method comprising operating the processor to:
receive the detection information provided by the first and second radiation detectors;
identify the radiation source using the detection informa- 15 tion;
receive the location information provided by the navigation system;
receive the relative location information provided by the inertial measurement unit; and
determine the absolute location of the radiation source 20 using the location information, the relative location information, and the detection information.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 11,543,542 B2
APPLICATION NO. : 17/319005
DATED : January 3, 2023
INVENTOR(S) : Kemper Talley et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

On the Title Page

Item [71], delete "Applicant: FLIR Detection, inc.," and insert -- Applicant: Teledyne FLIR Detection, Inc., --.

Signed and Sealed this
Fourteenth Day of February, 2023



Katherine Kelly Vidal
Director of the United States Patent and Trademark Office