



US011543633B2

(12) **United States Patent**
Shabtay et al.

(10) **Patent No.:** **US 11,543,633 B2**
(45) **Date of Patent:** ***Jan. 3, 2023**

(54) **ZOOM DUAL-APERTURE CAMERA WITH FOLDED LENS**

(71) Applicant: **Corephotonics Ltd.**, Tel Aviv (IL)

(72) Inventors: **Gal Shabtay**, Tel Aviv (IL); **Ephraim Goldenberg**, Tel Aviv (IL); **Gal Avivi**, Tel Aviv (IL); **Gil Bachar**, Tel Aviv (IL)

(73) Assignee: **Corephotonics Ltd.**, Tel Aviv (IL)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **17/577,430**

(22) Filed: **Jan. 18, 2022**

(65) **Prior Publication Data**

US 2022/0137377 A1 May 5, 2022

Related U.S. Application Data

(63) Continuation of application No. 17/126,266, filed on Dec. 18, 2020, now Pat. No. 11,262,559, which is a (Continued)

(51) **Int. Cl.**
H04N 5/225 (2006.01)
G02B 13/00 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **G02B 13/0065** (2013.01); **G02B 7/09** (2013.01); **G02B 7/102** (2013.01); **G02B 13/009** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC G02B 13/0065; G02B 7/09; G02B 7/102; G02B 13/009; G02B 13/02; G02B 13/04;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,106,752 A 2/1938 Land
2,354,503 A 7/1944 Arthur
(Continued)

FOREIGN PATENT DOCUMENTS

CN 101276415 A 10/2008
CN 201514511 U 6/2010
(Continued)

OTHER PUBLICATIONS

A compact and cost effective design for cell phone zoom lens, Chang et al., Sep. 2007, 8 pages.
(Continued)


Primary Examiner — Mekonnen D Dagnew

(74) *Attorney, Agent, or Firm* — Nathan & Associates; Menachem Nathan

(57) **ABSTRACT**

Zoom digital cameras comprising a Wide sub-camera and a folded fixed Tele sub-camera. The folded Tele sub-camera may be auto-focused by moving either its lens or a reflecting element inserted in an optical path between its lens and a respective image sensor. The folded Tele sub-camera is configured to have a low profile to enable its integration within a portable electronic device.

7 Claims, 15 Drawing Sheets



Related U.S. Application Data

continuation of application No. 16/664,841, filed on Oct. 26, 2019, now Pat. No. 10,976,527, which is a continuation of application No. 16/402,412, filed on May 3, 2019, now Pat. No. 10,509,209, which is a continuation of application No. 16/172,761, filed on Oct. 27, 2018, now Pat. No. 10,571,665, which is a continuation of application No. 15/820,917, filed on Nov. 22, 2017, now Pat. No. 10,156,706, which is a continuation of application No. 15/177,688, filed on Jun. 9, 2016, now Pat. No. 9,829,684, which is a continuation of application No. 14/717,258, filed on May 20, 2015, now Pat. No. 9,392,188, which is a continuation-in-part of application No. 14/455,906, filed on Aug. 10, 2014, now abandoned.

(51) **Int. Cl.**

H04N 5/247 (2006.01)
G02B 13/02 (2006.01)
G02B 7/09 (2021.01)
G02B 7/10 (2021.01)
H04N 5/232 (2006.01)
G02B 13/04 (2006.01)

(52) **U.S. Cl.**

CPC *G02B 13/02* (2013.01); *G02B 13/04* (2013.01); *H04N 5/2253* (2013.01); *H04N 5/2254* (2013.01); *H04N 5/2257* (2013.01); *H04N 5/2258* (2013.01); *H04N 5/23212* (2013.01); *H04N 5/247* (2013.01)

(58) **Field of Classification Search**

CPC .. *H04N 5/2253*; *H04N 5/2254*; *H04N 5/2257*; *H04N 5/2258*; *H04N 5/23212*; *H04N 5/247*

See application file for complete search history.

(56)

References Cited

U.S. PATENT DOCUMENTS

2,378,170 A 6/1945 Aklin
 2,441,093 A 5/1948 Aklin
 3,388,956 A 6/1968 Eggert et al.
 3,524,700 A 8/1970 Eggert et al.
 3,558,218 A 1/1971 Grey
 3,864,027 A 2/1975 Harada
 3,942,876 A 3/1976 Betensky
 4,134,645 A 1/1979 Sugiyama et al.
 4,199,785 A 4/1980 McCullough et al.
 4,338,001 A 7/1982 Matsui
 4,465,345 A 8/1984 Yazawa
 5,000,551 A 3/1991 Shibayama
 5,005,083 A 4/1991 Grage et al.
 5,032,917 A 7/1991 Aschwanden
 5,041,852 A 8/1991 Misawa et al.
 5,051,830 A 9/1991 von Hoessle
 5,099,263 A 3/1992 Matsumoto et al.
 5,248,971 A 9/1993 Mandi
 5,287,093 A 2/1994 Amano et al.
 5,394,520 A 2/1995 Hall
 5,436,660 A 7/1995 Sakamoto
 5,444,478 A 8/1995 Lelong et al.
 5,459,520 A 10/1995 Sasaki
 5,657,402 A 8/1997 Bender et al.
 5,682,198 A 10/1997 Katayama et al.
 5,768,443 A 6/1998 Michael et al.
 5,926,190 A 7/1999 Turkowski et al.
 5,940,641 A 8/1999 McIntyre et al.
 5,969,869 A 10/1999 Hirai et al.
 5,982,951 A 11/1999 Katayama et al.
 6,101,334 A 8/2000 Fantone
 6,128,416 A 10/2000 Oura

6,147,702 A 11/2000 Smith
 6,148,120 A 11/2000 Sussman
 6,169,636 B1 1/2001 Kreitzer
 6,208,765 B1 3/2001 Bergen
 6,268,611 B1 7/2001 Pettersson et al.
 6,549,215 B2 4/2003 Jouppi
 6,611,289 B1 8/2003 Yu et al.
 6,643,416 B1 11/2003 Daniels et al.
 6,650,368 B1 11/2003 Doron
 6,654,180 B2 11/2003 Ori
 6,680,748 B1 1/2004 Monti
 6,714,665 B1 3/2004 Hanna et al.
 6,724,421 B1 4/2004 Glatt
 6,738,073 B2 5/2004 Park et al.
 6,741,250 B1 5/2004 Furlan et al.
 6,750,903 B1 6/2004 Miyatake et al.
 6,778,207 B1 8/2004 Lee et al.
 7,002,583 B2 2/2006 Rabb, III
 7,015,954 B1 3/2006 Foote et al.
 7,038,716 B2 5/2006 Klein et al.
 7,187,504 B2 3/2007 Horiuchi
 7,199,348 B2 4/2007 Olsen et al.
 7,206,136 B2 4/2007 Labaziewicz et al.
 7,248,294 B2 7/2007 Slatter
 7,256,944 B2 8/2007 Labaziewicz et al.
 7,305,180 B2 12/2007 Labaziewicz et al.
 7,339,621 B2 3/2008 Fortier
 7,346,217 B1 3/2008 Gold, Jr.
 7,365,793 B2 4/2008 Cheatle et al.
 7,411,610 B2 8/2008 Doyle
 7,424,218 B2 9/2008 Baudisch et al.
 7,509,041 B2 3/2009 Hosono
 7,515,351 B2 4/2009 Chen et al.
 7,533,819 B2 5/2009 Barkan et al.
 7,564,635 B1 7/2009 Tang
 7,619,683 B2 11/2009 Davis
 7,643,225 B1 1/2010 Tsai
 7,660,049 B2 2/2010 Tang
 7,684,128 B2 3/2010 Tang
 7,688,523 B2 3/2010 Sano
 7,692,877 B2 4/2010 Tang et al.
 7,697,220 B2 4/2010 Iyama
 7,738,016 B2 6/2010 Toyofuku
 7,738,186 B2 6/2010 Chen et al.
 7,773,121 B1 8/2010 Huntsberger et al.
 7,777,972 B1 8/2010 Chen et al.
 7,809,256 B2 10/2010 Kuroda et al.
 7,813,057 B2 10/2010 Lin
 7,821,724 B2 10/2010 Tang et al.
 7,826,149 B2 11/2010 Tang et al.
 7,826,151 B2 11/2010 Tsai
 7,869,142 B2 1/2011 Chen et al.
 7,880,776 B2 2/2011 LeGall et al.
 7,898,747 B2 3/2011 Tang
 7,916,401 B2 3/2011 Chen et al.
 7,918,398 B2 4/2011 Li et al.
 7,957,075 B2 6/2011 Tang
 7,957,076 B2 6/2011 Tang
 7,957,079 B2 6/2011 Tang
 7,961,406 B2 6/2011 Tang et al.
 7,964,835 B2 6/2011 Olsen et al.
 7,978,239 B2 7/2011 Deever et al.
 3,004,777 A1 8/2011 Souma
 8,000,031 B1 8/2011 Tsai
 8,077,400 B2 12/2011 Tang
 8,115,825 B2 2/2012 Culbert et al.
 8,149,327 B2 4/2012 Lin et al.
 8,149,523 B2 4/2012 Ozaki
 8,154,610 B2 4/2012 Jo et al.
 8,218,253 B2 7/2012 Tang
 8,228,622 B2 7/2012 Tang
 8,233,224 B2 7/2012 Chen
 8,238,695 B1 8/2012 Davey et al.
 8,253,843 B2 8/2012 Lin
 8,274,552 B2 9/2012 Dahi et al.
 8,279,537 B2 10/2012 Sato
 8,363,337 B2 1/2013 Tang et al.
 8,390,729 B2 3/2013 Long et al.
 8,391,697 B2 3/2013 Cho et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,395,851 B2	3/2013	Tang et al.	2004/0061788 A1	4/2004	Bateman
8,400,555 B1	3/2013	Georgiev et al.	2004/0141065 A1	7/2004	Hara et al.
8,400,717 B2	3/2013	Chen et al.	2004/0141086 A1	7/2004	Mihara
8,439,265 B2	5/2013	Ferren et al.	2004/0240052 A1	12/2004	Minefuji et al.
8,446,484 B2	5/2013	Muukki et al.	2005/0013509 A1	1/2005	Samadani
8,451,549 B2	5/2013	Yamanaka et al.	2005/0041300 A1	2/2005	Oshima et al.
8,483,452 B2	7/2013	Ueda et al.	2005/0046740 A1	3/2005	Davis
8,503,107 B2	8/2013	Chen et al.	2005/0062346 A1	3/2005	Sasaki
8,514,491 B2	8/2013	Duparre	2005/0128604 A1	6/2005	Kuba
8,514,502 B2	8/2013	Chen	2005/0141103 A1	6/2005	Nishina
8,547,389 B2	10/2013	Hoppe et al.	2005/0157184 A1	7/2005	Nakanishi et al.
8,553,106 B2	10/2013	Scarff	2005/0168834 A1	8/2005	Matsumoto et al.
8,570,668 B2	10/2013	Takakubo et al.	2005/0168840 A1	8/2005	Kobayashi et al.
8,587,691 B2	11/2013	Takane	2005/0185049 A1	8/2005	Iwai et al.
8,619,148 B1	12/2013	Watts et al.	2005/0200718 A1	9/2005	Lee
8,718,458 B2	5/2014	Okuda	2005/0270667 A1	12/2005	Gurevich et al.
8,780,465 B2	7/2014	Chae	2006/0054782 A1	3/2006	Olsen et al.
8,803,990 B2	8/2014	Smith	2006/0056056 A1	3/2006	Ahiska et al.
8,810,923 B2	8/2014	Shinohara	2006/0067672 A1	3/2006	Washisu et al.
8,854,745 B1	10/2014	Chen	2006/0102907 A1	5/2006	Lee et al.
8,896,655 B2	11/2014	Mauchly et al.	2006/0125937 A1	6/2006	LeGall et al.
8,958,164 B2	2/2015	Kwon et al.	2006/0170793 A1	8/2006	Pasquarette et al.
8,976,255 B2	3/2015	Matsuoto et al.	2006/0175549 A1	8/2006	Miller et al.
9,019,387 B2	4/2015	Nakano	2006/0187310 A1	8/2006	Janson et al.
9,025,073 B2	5/2015	Attar et al.	2006/0187322 A1	8/2006	Janson et al.
9,025,077 B2	5/2015	Honda	2006/0187338 A1	8/2006	May et al.
9,041,835 B2	5/2015	Shibuno	2006/0227236 A1	10/2006	Pak
9,137,447 B2	9/2015	Shabtay et al.	2007/0024737 A1	2/2007	Nakamura et al.
9,185,291 B1	11/2015	Sokeila et al.	2007/0126911 A1	6/2007	Nanjo
9,215,377 B2	12/2015	Luo	2007/0177025 A1	8/2007	Kopet et al.
9,215,385 B2	12/2015	Yoneyama et al.	2007/0188653 A1	8/2007	Pollock et al.
9,229,194 B2	1/2016	Kato et al.	2007/0189386 A1	8/2007	Imagawa et al.
9,235,036 B2	1/2016	Brisedoux et al.	2007/0229983 A1	10/2007	Saori
9,270,875 B2	2/2016	Kanda et al.	2007/0257184 A1	11/2007	Olsen et al.
9,279,957 B2	3/2016	Jiang et al.	2007/0285550 A1	12/2007	Son
9,286,680 B1	3/2016	Silverstein et al.	2008/0017557 A1	1/2008	Witdouck
9,344,626 B2	5/2016	Zhou	2008/0024614 A1	1/2008	Li et al.
9,360,671 B1	6/2016	Malone et al.	2008/0025634 A1	1/2008	Border et al.
9,369,621 B2	6/2016	Geerds	2008/0030592 A1	2/2008	Border et al.
9,413,930 B2	8/2016	Attar et al.	2008/0030611 A1	2/2008	Jenkins
9,413,984 B2	8/2016	Jin	2008/0056698 A1	3/2008	Lee et al.
9,420,180 B2	8/2016	Nakada et al.	2008/0084484 A1	4/2008	Ochi et al.
9,438,792 B2	9/2016	Medasani et al.	2008/0106629 A1	5/2008	Kurtz et al.
9,485,432 B1	11/2016	Chen et al.	2008/0117316 A1	5/2008	Orimoto
9,488,802 B2	11/2016	Dror et al.	2008/0129831 A1	6/2008	Cho et al.
9,568,712 B2	2/2017	Attar et al.	2008/0218611 A1	9/2008	Parulski et al.
9,578,257 B2	2/2017	Munger et al.	2008/0218612 A1	9/2008	Border et al.
9,618,748 B2	4/2017	Iwasaki et al.	2008/0218613 A1	9/2008	Janson et al.
9,678,310 B2	6/2017	Attar et al.	2008/0219654 A1	9/2008	Border et al.
9,681,057 B2	6/2017	Sugie	2008/0304161 A1	12/2008	Souma
9,723,220 B2	8/2017	Laroya	2009/0002839 A1	1/2009	Sato
9,736,365 B2	8/2017	Du et al.	2009/0086074 A1	4/2009	Li et al.
9,736,391 B2	8/2017	Ahn et al.	2009/0109556 A1	4/2009	Shimizu et al.
9,768,310 B2	9/2017	Ravirala et al.	2009/0122195 A1	5/2009	Van Baar et al.
9,800,798 B2	10/2017	Mercado	2009/0122406 A1	5/2009	Rouvinen et al.
9,817,213 B2	11/2017	Fisher et al.	2009/0122423 A1	5/2009	Park et al.
9,851,803 B2	12/2017	Qian et al.	2009/0128644 A1	5/2009	Camp et al.
9,894,287 B2	2/2018	Lu	2009/0141365 A1	6/2009	Jannard et al.
9,900,522 B2	2/2018	Goldenberg et al.	2009/0219547 A1	9/2009	Kauhanen et al.
9,927,600 B2	3/2018	Yuen	2009/0225438 A1	9/2009	Kubota
2002/0005902 A1	1/2002	Zhang	2009/0252484 A1	10/2009	Hasuda et al.
2002/0030163 A1	3/2002	Park et al.	2009/0295949 A1	12/2009	Ojala
2002/0063711 A1	5/2002	Park et al.	2009/0324135 A1	12/2009	Kondo et al.
2002/0075258 A1	6/2002	Imoto	2010/0013906 A1	1/2010	Border et al.
2002/0118471 A1	8/2002	Footo	2010/0020221 A1	1/2010	Tupman et al.
2002/0122113 A1	9/2002	Koiwai et al.	2010/0060746 A9	3/2010	Olsen et al.
2002/0167741 A1	11/2002	Prentice et al.	2010/0097444 A1	4/2010	Lablans
2003/0030729 A1	2/2003	Gin	2010/0103194 A1	4/2010	Chen et al.
2003/0093805 A1	5/2003	Misawa et al.	2010/0165131 A1	7/2010	Makimoto et al.
2003/0160886 A1	8/2003	Yoshikawa	2010/0165476 A1	7/2010	Eguchi
2003/0202113 A1	10/2003	Itokawa	2010/0196001 A1	8/2010	Ryynänen et al.
2004/0008773 A1	1/2004	Yamasaki et al.	2010/0238327 A1	9/2010	Griffith et al.
2004/0012683 A1	1/2004	Liu et al.	2010/0259836 A1	10/2010	Kang et al.
2004/0017386 A1	1/2004	Pilu	2010/0277813 A1	11/2010	Ito
2004/0027367 A1	2/2004		2010/0283842 A1	11/2010	Guissin et al.
			2010/0321494 A1	12/2010	Peterson et al.
			2011/0001838 A1	1/2011	Lee
			2011/0058320 A1	3/2011	Kim et al.
			2011/0063417 A1	3/2011	Peters et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2011/0063446 A1	3/2011	McMordie et al.	2014/0313316 A1	10/2014	Olsson et al.
2011/0064327 A1	3/2011	Dagher et al.	2014/0362242 A1	12/2014	Takizawa
2011/0080487 A1	4/2011	Venkataraman et al.	2014/0362274 A1	12/2014	Christie et al.
2011/0115965 A1	5/2011	Engelhardt et al.	2015/0002683 A1	1/2015	Hu et al.
2011/0128288 A1	6/2011	Petrou et al.	2015/0042870 A1	2/2015	Chan et al.
2011/0149119 A1	6/2011	Matsui	2015/0070781 A1	3/2015	Cheng et al.
2011/0157430 A1	6/2011	Hosoya et al.	2015/0070783 A1*	3/2015	Hashimoto G06T 5/002
2011/0164172 A1	7/2011	Shintani et al.			359/708
2011/0188121 A1	8/2011	Goring et al.	2015/0092066 A1	4/2015	Geiss et al.
2011/0229054 A1	9/2011	Weston et al.	2015/0103147 A1	4/2015	Ho et al.
2011/0234798 A1	9/2011	Chou	2015/0116569 A1	4/2015	Mercado
2011/0234853 A1	9/2011	Hayashi et al.	2015/0138381 A1	5/2015	Ahn
2011/0234881 A1	9/2011	Wakabayashi et al.	2015/0154776 A1	6/2015	Zhang et al.
2011/0242286 A1	10/2011	Pace et al.	2015/0162048 A1	6/2015	Hirata et al.
2011/0242355 A1	10/2011	Goma et al.	2015/0195458 A1	7/2015	Nakayama et al.
2011/0249347 A1	10/2011	Kubota	2015/0215516 A1	7/2015	Dolgin
2011/0298966 A1	12/2011	Kirschstein et al.	2015/0237280 A1	8/2015	Choi et al.
2012/0026366 A1	2/2012	Golan et al.	2015/0242994 A1	8/2015	Shen
2012/0044372 A1	2/2012	Cote et al.	2015/0244906 A1	8/2015	Wu et al.
2012/0062780 A1	3/2012	Moriyama	2015/0244942 A1	8/2015	Shabtay et al.
2012/0069235 A1	3/2012	Imai	2015/0253532 A1	9/2015	Lin
2012/0069455 A1	3/2012	Lin et al.	2015/0253543 A1	9/2015	Mercado
2012/0075489 A1	3/2012	Nishihara	2015/0253647 A1	9/2015	Mercado
2012/0092777 A1	4/2012	Tochigi et al.	2015/0261299 A1	9/2015	Wajs
2012/0105579 A1	5/2012	Jeon et al.	2015/0271471 A1	9/2015	Hsieh et al.
2012/0105708 A1	5/2012	Hagiwara	2015/0281678 A1	10/2015	Park et al.
2012/0124525 A1	5/2012	Kang	2015/0286033 A1	10/2015	Osborne
2012/0154547 A1	6/2012	Aizawa	2015/0316744 A1	11/2015	Chen
2012/0154614 A1	6/2012	Moriya et al.	2015/0334309 A1	11/2015	Peng et al.
2012/0154929 A1	6/2012	Tsai et al.	2015/0373252 A1	12/2015	Georgiev
2012/0196648 A1	8/2012	Havens et al.	2015/0373263 A1	12/2015	Georgiev et al.
2012/0229663 A1	9/2012	Nelson et al.	2016/0044250 A1	2/2016	Shabtay et al.
2012/0229920 A1	9/2012	Otsu et al.	2016/0062084 A1	3/2016	Chen et al.
2012/0249815 A1	10/2012	Bohn et al.	2016/0070088 A1	3/2016	Koguchi
2012/0262806 A1	10/2012	Lin et al.	2016/0085089 A1	3/2016	Mercado
2012/0287315 A1	11/2012	Huang et al.	2016/0154202 A1	6/2016	Wippermann et al.
2012/0320467 A1	12/2012	Baik et al.	2016/0154204 A1	6/2016	Lim et al.
2013/0002928 A1	1/2013	Imai	2016/0187631 A1	6/2016	Choi et al.
2013/0016427 A1	1/2013	Sugawara	2016/0212358 A1	7/2016	Shikata
2013/0057971 A1	3/2013	Zhao et al.	2016/0212418 A1	7/2016	Demirdjian et al.
2013/0063629 A1	3/2013	Webster et al.	2016/0241751 A1	8/2016	Park
2013/0076922 A1	3/2013	Shihoh et al.	2016/0291295 A1	10/2016	Shabtay et al.
2013/0088788 A1	4/2013	You	2016/0295112 A1	10/2016	Georgiev et al.
2013/0093842 A1	4/2013	Yahata	2016/0301840 A1	10/2016	Du et al.
2013/0094126 A1	4/2013	Rappoport et al.	2016/0306161 A1	10/2016	Harada et al.
2013/0113894 A1	5/2013	Miralay	2016/0313537 A1	10/2016	Mercado
2013/0135445 A1	5/2013	Dahi et al.	2016/0341931 A1	11/2016	Liu et al.
2013/0155176 A1	6/2013	Paripally et al.	2016/0353008 A1	12/2016	Osborne
2013/0182150 A1	7/2013	Asakura	2016/0353012 A1	12/2016	Kao et al.
2013/0201360 A1	8/2013	Song	2016/0381260 A1*	12/2016	Narayanswamy G03B 19/22
2013/0202273 A1	8/2013	Ouedraogo et al.			348/360
2013/0208178 A1	8/2013	Park	2017/0019616 A1	1/2017	Zhu et al.
2013/0235224 A1	9/2013	Park et al.	2017/0070731 A1	3/2017	Darling et al.
2013/0250150 A1	9/2013	Malone et al.	2017/0102522 A1	4/2017	Jo
2013/0258044 A1	10/2013	Betts-LaCroix	2017/0115471 A1	4/2017	Shinohara
2013/0270419 A1	10/2013	Singh et al.	2017/0160511 A1	6/2017	Kim et al.
2013/0278785 A1	10/2013	Nomura et al.	2017/0187962 A1	6/2017	Lee et al.
2013/0279032 A1	10/2013	Suigetsu et al.	2017/0214846 A1	7/2017	Du et al.
2013/0286488 A1	10/2013	Chae	2017/0214866 A1	7/2017	Zhu et al.
2013/0321668 A1	12/2013	Kamath	2017/0242225 A1	8/2017	Fiske
2014/0009631 A1	1/2014	Topliss	2017/0289458 A1	10/2017	Song et al.
2014/0022436 A1	1/2014	Kim et al.	2018/0013944 A1	1/2018	Evans, V et al.
2014/0049615 A1	2/2014	Uwagawa	2018/0017844 A1	1/2018	Yu et al.
2014/0092487 A1	4/2014	Chen et al.	2018/0024329 A1	1/2018	Goldenberg et al.
2014/0118584 A1	5/2014	Lee et al.	2018/0059365 A1	3/2018	Bone et al.
2014/0146216 A1	5/2014	Okumura	2018/0059379 A1	3/2018	Chou
2014/0160311 A1	6/2014	Hwang et al.	2018/0120674 A1	5/2018	Avivi et al.
2014/0192238 A1	7/2014	Attar et al.	2018/0150973 A1	5/2018	Tang et al.
2014/0192253 A1	7/2014	Laroia	2018/0176426 A1	6/2018	Wei et al.
2014/0204480 A1	7/2014	Jo et al.	2018/0198897 A1	7/2018	Tang et al.
2014/0218587 A1	8/2014	Shah	2018/0217475 A1	8/2018	Goldenberg et al.
2014/0285907 A1	9/2014	Tang et al.	2018/0224630 A1	8/2018	Lee et al.
2014/0293453 A1	10/2014	Ogino et al.	2018/0241922 A1	8/2018	Baldwin et al.
2014/0300799 A1*	10/2014	Yoshino H04N 5/23212	2018/0295292 A1	10/2018	Lee et al.
		348/347	2018/0300901 A1	10/2018	Wakai et al.
			2019/0121103 A1	4/2019	Bachar et al.
			2019/0170965 A1	6/2019	Shabtay et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

FOREIGN PATENT DOCUMENTS

CN	102193162	A	9/2011
CN	102739949	A	10/2012
CN	102147519	B	1/2013
CN	103024272	A	4/2013
CN	103841404	A	6/2014
CN	104297906	A	1/2015
CN	105467563	A	4/2016
EP	1536633	A1	6/2005
EP	1780567	A1	5/2007
EP	2523450	A1	11/2012
JP	S54157620	A	12/1979
JP	S59121015	A	7/1984
JP	S59191146	A	10/1984
JP	6165212	A	4/1986
JP	S6370211	A	3/1988
JP	04211230	A	8/1992
JP	406059195	A	3/1994
JP	H07318864	A	12/1995
JP	08271976	A	10/1996
JP	2002010276	A	1/2002
JP	2003298920	A	10/2003
JP	2004133054	A	4/2004
JP	2004245982	A	9/2004
JP	2005099265	A	4/2005
JP	2006238325	A	9/2006
JP	2007133096	A	5/2007
JP	2007219199	A	8/2007
JP	2007228006	A	9/2007
JP	2007306282	A	11/2007
JP	2008076485	A	4/2008
JP	2010164841	A	7/2010
JP	2010204341	A	9/2010
JP	2011085666	A	4/2011
JP	2012203234	A	10/2012
JP	2013105049	A	5/2013
JP	2013106289	A	5/2013
JP	2014142542	A	8/2014
KR	20070005946	A	1/2007
KR	20090058229	A	6/2009
KR	20090131805	A	12/2009
KR	20100008936	A	1/2010
KR	20140135909	A	5/2013
KR	20140014787	A	2/2014
KR	20140023552	A	2/2014
KR	101477178	B1	12/2014
KR	20140144126	A	12/2014
KR	20150118012	A	10/2015
WO	2000027131	A2	5/2000
WO	2004084542	A1	9/2004
WO	2006008805	A1	1/2006
WO	2010122841	A1	10/2010
WO	2013058111	A1	4/2013
WO	2013063097	A1	5/2013
WO	2014072818	A2	5/2014

WO	2017025822	A1	2/2017
WO	2017037688	A1	3/2017
WO	2018130898	A1	7/2018

OTHER PUBLICATIONS

Consumer Electronic Optics: How small a lens can be? The case of panomorph lenses, Thibault et al., Sep. 2014, 7 pages.

Optical design of camera optics for mobile phones, Steinich et al., 2012, pp. 51-58 (8 pages).

The Optics of Miniature Digital Camera Modules, Bareau et al., 2006, 11 pages.

Modeling and measuring liquid crystal tunable lenses, Peter P. Clark, 2014, 7 pages.

Mobile Platform Optical Design, Peter P. Clark, 2014, 7 pages.

Boye et al., "Ultrathin Optics for Low-Profile Innocuous Imager", Sandia Report, 2009, pp. 56-56.

"Cheat sheet: how to understand f-stops", Internet article, Digital Camera World, 2017.

Statistical Modeling and Performance Characterization of a Real-Time Dual Camera Surveillance System, Greienhagen et al., Publisher: IEEE, 2000, 8 pages.

A 3MPixel Multi-Aperture Image Sensor with 0.7 μ m Pixels in 0.11 μ m CMOS, Fife et al., Stanford University, 2008, 3 pages.

Dual camera intelligent sensor for high definition 360 degrees surveillance, Scotti et al., Publisher: IET, May 9, 2000, 8 pages.

Dual-sensor foveated imaging system, Hua et al., Publisher: Optical Society of America, Jan. 14, 2008, 11 pages.

Defocus Video Matting, McGuire et al., Publisher: ACM SIGGRAPH, Jul. 31, 2005, 11 pages.

Compact multi-aperture imaging with high angular resolution, Santacana et al., Publisher: Optical Society of America, 2015, 10 pages.

Multi-Aperture Photography, Green et al., Publisher: Mitsubishi Electric Research Laboratories, Inc., Jul. 2007, 10 pages.

Multispectral Bilateral Video Fusion, Bennett et al., Publisher: IEEE, May 2007, 10 pages.

Super-resolution imaging using a camera array, Santacana et al., Publisher: Optical Society of America, 2014, 6 pages.

Optical Splitting Trees for High-Precision Monocular Imaging, McGuire et al., Publisher: IEEE, 2007, 11 pages.

High Performance Imaging Using Large Camera Arrays, Wilburn et al., Publisher: Association for Computing Machinery, Inc., 2005, 12 pages.

Real-time Edge-Aware Image Processing with the Bilateral Grid, Chen et al., Publisher: ACM SIGGRAPH, 2007, 9 pages.


Superimposed multi-resolution imaging, Carles et al., Publisher: Optical Society of America, 2017, 13 pages.

Viewfinder Alignment, Adams et al., Publisher: EUROGRAPHICS, 2008, 10 pages.

Dual-Camera System for Multi-Level Activity Recognition, Bodor et al., Publisher: IEEE, Oct. 2014, 6 pages.

Engineered to the task: Why camera-phone cameras are different, Giles Humpston, Publisher: Solid State Technology, Jun. 2009, 3 pages.

* cited by examiner






FIG. 2A




FIG. 2B




FIG. 2C




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B




FIG. 5A






FIG. 5B






FIG. 6C




FIG. 7




FIG. 8




FIG. 9A




FIG. 9B




FIG. 9C




FIG. 10A




FIG. 10B




FIG. 10C




FIG. 11A




FIG. 11B




FIG. 12A




FIG. 12B

1300




FIG. 13A




FIG. 13B




Fig. 14

ZOOM DUAL-APERTURE CAMERA WITH FOLDED LENS

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 17/126,266 filed Dec. 18, 2020 (now allowed), which was a continuation of U.S. patent application Ser. No. 16/664,841 filed Oct. 26, 2019 (now U.S. Pat. No. 10,976,527), which was a continuation of U.S. patent application Ser. No. 16/402,412 filed May 3, 2019 (now U.S. Pat. No. 10,509,209), which was a continuation of U.S. patent application Ser. No. 16/172,761 filed Oct. 27, 2018 (now U.S. Pat. No. 10,571,665), which was a continuation of U.S. patent application Ser. No. 15/820,917 filed Nov. 22, 2017 (now U.S. Pat. No. 10,156,706), which was a continuation of U.S. patent application Ser. No. 15/177,688 filed Jun. 9, 2016 (now U.S. Pat. No. 9,829,684), which was a continuation of U.S. patent application Ser. No. 14/717,258 filed May 20, 2015 (now U.S. Pat. No. 9,392,188), which was a continuation-in-part of U.S. patent application Ser. No. 14/455,906 filed Aug. 10, 2014 (abandoned).

FIELD

The presently disclosed subject matter is generally related to the field of digital cameras, and in particular to multiple-aperture digital cameras.

BACKGROUND

In recent years, mobile devices such as cell-phones (and in particular Smartphones), tablets and laptops have become ubiquitous. Such devices commonly include one or two compact digital cameras e.g. a main rear-facing camera (i.e. a camera on the back side of the device, facing away from the user and often used for casual photography) and a secondary front-facing camera (i.e. a camera located on the front side of the device and often used for video conferencing).

The design of many of these cameras is similar to the traditional structure of a digital still camera, i.e. they comprise an optical component (or a train of several optical elements and a main aperture) placed on top of an image sensor (also referred to henceforth simply as “sensor”). The optical component (also referred to as “optics”) refracts the incoming light rays and bends them to create an image of a scene on the sensor.

The dimensions of these cameras are largely determined by the size of the sensor and by the height of the optics. These are usually tied together through the focal length (f) of the lens and its field of view (FOV)—a lens that has to image a certain FOV on a sensor of a certain size has a specific focal length. Keeping the FOV constant, the larger the sensor dimensions (e.g. in an X-Y plane), the larger the focal length and the optics height.

As the dimensions of mobile devices (and in particular the thickness of devices such as Smartphones) are constantly being diminished, compact camera dimensions are becoming an increasingly limiting factor on device thickness. Several approaches have been proposed to reduce compact camera thickness in order to alleviate this constraint. Recently, multi-aperture systems have been proposed for this purpose. In such systems, instead of having one aperture with one train of optical elements, the camera is divided into several apertures, each with dedicated optical elements, and

all sharing a similar field of view. Hereinafter, each such aperture, together with the optics and the sensor area on which the image is formed, is defined as a “sub-camera”. Images from the sub-cameras are fused together to create a single output image.

In some multi-aperture camera designs, each sub-camera creates a smaller image on the image sensor compared with the image created by a reference single-aperture camera. Therefore, the height of each sub-camera can be smaller than the height of a single-aperture camera, reducing the total height of the camera and allowing for slimmer designs of mobile devices.

Dual-aperture zoom cameras in which one sub-camera has a wide FOV (“Wide sub-camera”) and the other has a narrow FOV (“Tele sub-camera”) are known. One problem with dual-aperture zoom cameras relates to the height of the zoom Tele sub-camera. There is a significant difference in the height (also known as “total track length” or “TTL”) of Tele (“T”) and Wide (“W”) sub-cameras. The TTL is typically defined as the maximal distance between the object-side surface of a first lens element and a camera image sensor plane. In most miniature lenses, the TTL is larger than the lens effective focal length (EFL). A typical TTL/EFL ratio for a given lens (or lens unit) is around 1.3. In a single-aperture Smartphone camera with a $\frac{1}{3}$ - $\frac{1}{4}$ " sensor, EFL is typically between 3.5 and 4.5 mm, respectively, leading to a FOV of 70-80°.

Assuming, for example, one wishes to achieve a dual-aperture $\times 2$ optical zoom in a Smartphone, it would be natural to use $EFL_W=3.5$ mm and $EFL_T=2 \times EFL_W=7$ mm. However, without spatial restrictions, the Wide lens will have an $EFL_W=3.5$ mm and a TTL_W of $3.5 \times 1.3=4.55$ mm, while the Tele lens will have $EFL_T=7$ mm and TTL_T of $7 \times 1.3=9.1$ mm. The incorporation of a 9.1 mm lens in a Smartphone camera would lead to a camera height of around 10 mm, which is unacceptable for many Smartphone manufacturers.

An example of a solution to the aforementioned problem is described in co-invented and co-owned PCT patent application PCT/IB2014/062180 titled “Dual-aperture zoom digital camera” (published as WO2014/199338). Some of the principles of this solution are shown in FIGS. 1A and 1B hereof schematically illustrating an embodiment of a dual-aperture zoom camera with auto-focus (AF) and numbered **100**, in FIG. 1A, a general isometric view, and, in FIG. 1B, a sectioned isometric view. Camera **100** comprises two sub-cameras, labeled **102** and **104**, each sub-camera having its own optics. Thus, sub-camera **102** includes an optics bloc **106** with an aperture **108** and an optical lens module **110**, as well as a sensor **112**. Similarly, sub-camera **104** includes an optics bloc **114** with an aperture **116** and an optical lens module **118**, as well as a sensor **120**. Each optical lens module may include several lens elements as well as an Infra-Red (IR) filter **122a** and **122b**. Optionally, some or all of the lens elements belonging to different apertures may be formed on the same substrate. The two sub-cameras are positioned next to each other, with a small baseline in the **124** between the center of the two apertures **108** and **116**. Each sub-camera can further include an AF mechanism, respectively **126** and **128**, controlled by a controller (not shown). Camera **100** is “thin” as expressed by $TTL_W/EFL_W > 1.1$ and $TTL_T/EFL_T < 1.0$ (e.g. 0.85).

While the zoom range in camera **100** is about $\times 2$, it would be advantageous to further increase this range. However, this requires increasing further the Tele lens EFL (EFL_T), which will cause an increase in the camera height. An increase of

EFL_T to exemplarily 12 mm will result in an undesirable camera height of for example $0.85 \times 12 + 0.9 = 11.1$ mm

General Description

As noted above, the requirements for digital cameras for use in portable electronic devices are related to the dimensions and image quality of the camera. Moreover, these requirements become more essential when the camera is to be installed within the portable device, unlike other external camera units attachable to the portable device.

In the case of an internal (integral) camera unit, a camera is required to have dimensions as small as possible in order to fit the thickness of the device in which the camera is installed (preferably without protruding from the device's casing), while being suitable to operate with commonly used image sensors. This problem is even more crucial when using a Tele lens with a long effective focal length (EFL) to obtain a relatively high zooming effect.

Thus, according to one aspect of the presently disclosed subject matter, there is provided a zoom digital camera comprising a Wide sub-camera and a Tele sub-camera. The Wide sub-camera comprises a Wide lens module and a Wide image sensor, the Wide lens module having a Wide lens symmetry axis along a first optical path between an object side and the Wide image sensor. The Wide sub-camera is configured to provide a Wide image.

The Tele sub-camera comprises a Tele lens module and a Tele image sensor and a first reflecting element. The Tele lens module has a Tele lens symmetry axis along a second optical path, the Tele lens symmetry axis positioned substantially perpendicular to the Wide lens symmetry axis. The Tele sub-camera is configured to provide a Tele image.

The first reflecting element has a first reflecting element symmetry axis inclined substantially at 45 degrees to both the Wide lens symmetry axis and the Tele lens symmetry axis and is operative to provide a folded optical path between the object and the Tele image sensor. Accordingly, the Tele sub-camera is considered to be folded and is referred to herein as "folded Tele sub-camera".

The Wide lens has a Wide field of view (FOV_W) and the Tele lens has a Tele field of view (FOV_T) narrower than FOV_W. According to one non-limiting example, the Tele sub-camera provides an $\times 5$ zooming effect, compared to the Wide sub-camera.

The digital camera is operatively connected to at least one image processor configured to process the Tele image and the Wide image into an output image. Methods of fusing images received through different optical paths into a single output image are provided for example in co-invented and co-owned PCT patent application, publication no. WO2014/083489 titled "HIGH-RESOLUTION THIN MULTI-APERTURE IMAGING SYSTEMS", and co-invented and co-owned U.S. patent application Ser. No. 14/365,711 titled "DUAL APERTURE ZOOM DIGITAL CAMERA" which are incorporated herein by reference and discloses a multi-aperture imaging system comprising a first camera with a first sensor that captures a first image, and a second camera with a second sensor that captures a second image. Either image may be chosen to be a primary or an auxiliary image, based on a zoom factor. An output image with a point of view determined by the primary image is obtained by registering the auxiliary image to the primary image.

In order to further adapt the dimensions of the folded Tele sub-camera to the trend in electronic portable devices, seeking to reduce their thickness as much as possible, various features of the folded Tele sub-camera were specifically configured to enable to achieve a folded Tele sub-camera with reduced height. Reduction of the Tele-sub-

camera height enables to reduce the overall height of a dual aperture camera. Furthermore, reduction of the folded Tele sub-camera height was achieved while maintaining a desirable image quality.

Thus, in addition to the above features, according to various examples of the presently disclosed subject matter, the zoom digital camera can comprise one or more of features (1) to (32) below, in any desired combination and permutation.

1) wherein the Tele lens module of the folded Tele sub-camera comprises a group of at least 3 lens elements and wherein the lens elements in the group are designed to have a diameter substantially not exceeding the diameter of an aperture of the Tele sub-camera. As explained below, this is different than conventional lens modules where the diameters of the lenses are designed to be increasingly wider towards the sensor.

2) wherein the Tele lens module of the folded Tele sub-camera comprises a group of 3 to 5 lens elements.

3) wherein the Tele sub-camera further comprises a substrate, a structure for holding the lens elements in place, and a camera casing.

4) wherein the aperture of the Tele sub-camera is designed to provide a sufficiently low F # (e.g. equal or smaller than 3) to increase light falling on the Tele image sensor.

5) wherein the Tele lens module is designed to enable to generate an image on an entire area of the Tele image sensor. The Tele image sensor can be for example a $\frac{1}{3}$ " image sensor or a $\frac{1}{4}$ " image sensor.

6) wherein the lens elements in the group are designed such that blocked light does not exceed a certain percentage of the light entering the Tele lens module (e.g. not more than 25% of light entering the Tele lens module is blocked).

7) wherein according to one example the Tele sub-camera is configured to have the following technical parameters: an EFL > 9 mm, an F # ≤ 3 and light blockage does not exceed more than 25% of light entering the Tele sub-camera aperture for all viewing angles.

8) wherein the Tele sub-camera is characterized by a height not exceeding 6.5 mm.

9) wherein the Tele sub-camera is characterized by a height not exceeding 5.7 mm.

10) wherein the Tele image sensor lies in a plane substantially perpendicular to the Tele lens symmetry axis.

11) wherein the Tele sub-camera comprises a Tele auto-focus (AF) mechanism configured to move the Tele lens along the Tele symmetry axis; the AF mechanism is designed such that its height substantially does not exceed the height of a Tele lens module.

12) wherein the AF mechanism comprises one or more magnets coupled to respective coils, positioned laterally on one or two sides of the Tele lens module, the magnets having a height substantially not exceeding the height of the Tele lens module.

13) wherein the AF mechanism comprises only one magnet coupled to a respective coil.

14) wherein the camera further comprises a second reflecting element positioned in the second optical path between the Tele lens module and the Tele image sensor, the second reflecting element being configured to direct light that propagates parallel to the second optical path to the first optical path, wherein the Tele image sensor lies in a plane substantially perpendicular to the Wide lens symmetry axis.

15) wherein the camera further comprises a Tele auto-focus (AF) mechanism configured to move the second reflecting element along a second reflecting element symmetry axis.

5

16) wherein the Wide and Tele image sensors are mounted on a single printed circuit board.

17) wherein at least one processor operatively connected to the camera is configured to use a zoom factor (ZF) to determine a respective output field of view.

18) wherein the Wide lens module has a Wide field of view FOV_W and the Tele lens module has a Tele field of view FOV_T narrower than FOV_W ; the camera further comprises a Mid sub-camera that includes a Mid lens module with a field of view FOV_M that fulfills $FOV_W > FOV_M > FOV_T$ and a Mid image sensor, the Mid lens having a Mid lens symmetry axis; the Mid camera is configured to provide a Mid image.

19) wherein the Mid sub-camera is configured with an EFL which equals to a geometric average of an EFL of the Wide sub-camera and an EFL of the Tele sub-camera.

20) wherein at least one processor operatively connected to the camera is configured to process the Mid image together with the Tele image or the Wide image into an output image.

21) wherein the Mid lens symmetry axis is substantially perpendicular to the Wide lens symmetry axis and the Mid image sensor lies in a plane substantially perpendicular to the Mid lens symmetry axis; and wherein the Tele image sensor lies in a plane substantially perpendicular to the Tele lens symmetry axis.

22) wherein the camera further comprises a Mid auto-focus (AF) mechanism configured to move the Mid lens module along the Mid symmetry axis, which is substantially perpendicular to the Wide lens symmetry axis; and a Tele AF mechanism configured to move the Tele lens module along the Tele symmetry axis; either of the Mid AF mechanism and Tele AF mechanism have a height substantially not exceeding the height of the Tele lens module.

23) wherein the Mid AF mechanism comprises one or more magnets coupled to respective coils, positioned laterally on one or two sides of the Tele lens module, the magnets having a height substantially not exceeding the height of the Tele lens module.

24) wherein the Mid AF mechanism comprises only one magnet coupled to a respective coil.

25) wherein the camera further comprises a third reflecting element inclined substantially at 45 degrees to both the Wide lens symmetry axis and the Mid lens symmetry axis; the third reflecting element is configured to provide a folded optical path between the object side and the Mid image sensor.

26) wherein the camera further comprises a fourth reflecting element positioned in a fourth optical path between the Mid lens and the Mid image sensor, the fourth reflecting element configured to direct light that propagates parallel to the second optical path to the first optical path, wherein the Mid image sensor lies in a plane substantially parallel to the Mid lens symmetry axis.

27) wherein the camera further comprises a Mid auto-focus (AF) mechanism configured to move the fourth reflecting element along a fourth reflecting element symmetry axis.

28) wherein a Mid lens symmetry axis of the Mid sub-camera is substantially parallel to the Wide lens symmetry axis and the Wide and Mid image sensors are mounted on a single printed circuit board.

29) wherein a Mid lens symmetry axis of the Mid sub-camera is substantially perpendicular to the Wide lens symmetry axis and the Wide and Mid image sensors are mounted on a single printed circuit board.

6

30) wherein at least one processor operatively connected to the camera is configured to use a zoom factor (ZF) to determine a respective output field of view.

31) wherein at least one processor operatively connected to the camera is configured to output an output image formed by using Wide and Mid images for a ZF that sets a FOV between FOV_W and FOV_M .

32) wherein at least one processor operatively connected to the camera is configured to output an output image formed by using Mid and Tele images for a ZF that sets a FOV between FOV_M and FOV_T .

According to one example, the presently disclosed subject matter includes a digital camera configured to be integrated within a casing of an electronic device, the camera comprising: a Wide sub-camera, a Tele sub-camera and a Tele auto-focus (AF) mechanism;

the Wide sub-camera comprising, a Wide lens module and a Wide image sensor, the Wide lens module having a Wide lens symmetry axis along a first optical path between an object side and the Wide image sensor; the Wide sub-camera configured to provide a Wide image; a Tele sub-camera comprising, a Tele lens module and a Tele image sensor and a first mirror; the Tele lens module having a Tele lens symmetry axis along a second optical path, the Tele lens symmetry axis positioned substantially perpendicular to the Wide lens symmetry axis; the Tele camera is configured to provide a Tele image; the first mirror has a first mirror symmetry axis inclined substantially at 45 degrees to both the Wide lens symmetry axis and the Tele lens symmetry axis and is operative to provide a folded optical path between the object and the Tele image sensor;

wherein the Tele lens module comprises a group of 3 to 5 lens elements and wherein the lens elements in the group are designed to have a diameter substantially not exceeding the diameter of an aperture of the Tele sub-camera, to enable the generation of an image on an entire area of the Tele image sensor, and to enable passage of at least 75% of light entering the Tele lens module, towards the Tele image sensor;

wherein the Tele AF mechanism is configured to move the Tele lens along the Tele symmetry axis; the AF mechanism comprises one or more magnets coupled to respective coils, positioned laterally on one or two sides of the Tele lens module, the magnets having a height substantially not exceeding the height of the Tele lens module.

The presently disclosed subject matter further contemplates a mobile electronic device such as a cell phone (e.g. Smartphone), portable computer, notepad, tablet, watch, any type of electronic wearable device (e.g. bracelet, watch, helmet, glasses, etc.), or the like, which is equipped with a digital camera as disclosed herein. According to some examples, the digital camera is fully integrated within the electronic device (i.e. without protruding from the casing of the electronic device).

The presently disclosed subject matter further contemplates a Folded Tele sub-camera having a low camera profile as disclosed above.

BRIEF DESCRIPTION OF THE DRAWINGS

Non-limiting examples of embodiments disclosed herein are described below with reference to figures attached hereto that are listed following this paragraph. The drawings and descriptions are meant to illuminate and clarify embodiments disclosed herein, and should not be considered limiting in any way. Like elements in different drawings may be indicated by the same numerals.

FIG. 1A shows schematically a general isometric view of the design of a dual-aperture camera with zoom and AF;

FIG. 1B shows schematically a sectioned isometric view of the design of a dual-aperture camera with zoom and AF;

FIGS. 2A and 2B show schematically a zoom and auto-focus dual-aperture camera with folded Tele lens module in (FIG. 2A) a general isometric view, and (FIG. 2B) a side view, according to an example of the presently disclosed subject matter;

FIG. 2C shows schematically in a general isometric view a zoom and auto-focus dual-aperture camera with folded Tele lens module, according to an example of the presently disclosed subject matter;

FIGS. 3A and 3B show schematically a zoom and auto-focus dual-aperture camera with folded Tele lens module disclosed herein in (FIG. 3A) a general isometric view, and (FIG. 3B) a side view, according to an example of the presently disclosed subject matter;

FIGS. 4A and 4B show schematically a zoom and auto-focus dual-aperture camera with folded Tele lens module disclosed herein in (FIG. 4A) a general isometric view, and (FIG. 4B) a side view, according to an example of the presently disclosed subject matter;

FIGS. 5A and 5B show schematically details of the auto-focus mechanism for moving the second mirror in the example shown in FIGS. 4A and 4B in (FIG. 5A) a general isometric view, and (FIG. 5B) a cross sectional view through section A-A;

FIG. 6A shows schematically in a general isometric view a zoom and auto-focus triple-aperture camera with one folded Tele lens according to an example of the presently disclosed subject matter;

FIG. 6B shows schematically in a general isometric view a zoom and auto-focus triple-aperture camera with one folded Tele lens, according to an example of the presently disclosed subject matter;

FIG. 6C shows schematically in a general isometric view a zoom and auto-focus triple-aperture camera with one folded Tele lens according to an example of the presently disclosed subject matter;

FIG. 7 shows schematically in a general isometric view a zoom and auto-focus triple-aperture camera with two folded lenses, according to an example of the presently disclosed subject matter;

FIG. 8 shows schematically in a general isometric view a zoom and auto-focus triple-aperture camera with two folded Tele lenses, according to an example of the presently disclosed subject matter;

FIGS. 9A, 9B and 9C show graphs illustrating in: (FIG. 9A) user experience of resolution gain vs. zoom factor in an ideal continuous zoom; (FIG. 9B) user experience of resolution gain vs. zoom factor with a camera that includes two, Wide and Tele sub-cameras with 13 Mega pixel sensors and a 2 Mega pixel viewer; and (FIG. 9C) user experience of resolution gain vs. zoom factor with a camera that includes three, Wide, Mid and Tele sub-cameras with 13 Mega pixel sensors and a 2 Mega pixel viewer, according to an example of the presently disclosed subject matter;

FIG. 10A shows a Tele lens module with a five-element Tele lens unit that can be used in a camera, according to an example of the presently disclosed subject matter;

FIG. 10B shows an embodiment of a Tele lens module with a four-element Tele lens unit that can be used in a camera disclosed herein, according to an example of the presently disclosed subject matter;

FIG. 10C shows a Tele lens module with a three-element Tele lens unit that can be used in a camera, according to an example of the presently disclosed subject matter;

FIG. 11A illustrates the term “lens optical height” $H/2$ for each lens element of a four-element lens unit, according to an example of the presently disclosed subject matter;

FIG. 11B illustrates the effect of blocked light according to an example of the presently disclosed subject matter;

FIGS. 12A and 12B show schematically in (FIG. 12A) an isometric view and in (FIG. 12B) an external view of a camera module, according to an example of the presently disclosed subject matter;

FIGS. 13A and 13B show schematically in (FIG. 13A) an isometric view and in (FIG. 13B) an external view of another camera module, according to an example of the presently disclosed subject matter; and

FIG. 14 shows schematically a portable electronic device with an integrated dual-aperture camera with folded Tele lens module, according to an example of the presently disclosed subject matter.

DETAILED DESCRIPTION

It is to be understood that when specific direction and/or angle values are given herein, they are meant to include a range of values acceptable within practical tolerances known in the pertinent field.

Furthermore, for the sake of clarity the term “substantially” is used herein to imply the possibility of variations in values within an acceptable range. According to one example, the term “substantially” used herein should be interpreted to imply possible variation of up to 10% over or under any specified value. According to another example, the term “substantially” used herein should be interpreted to imply possible variation of up to 5% over or under any specified value. According to a further example, the term “substantially” used herein should be interpreted to imply possible variation of up to 2.5% over or under any specified value. The specified value can be absolute value (e.g. substantially not exceeding 45° , substantially perpendicular, etc.) or relative (e.g. substantially not exceeding the height of x, etc.).

It is noted, that in the current discussion “aperture diameter” refers to diameter of an aperture in a camera with a constant aperture size or to the maximal aperture diameter in a camera with a variable aperture size.

As used herein, the phrase “for example,” “such as,” “for instance,” “in an embodiment” and variants thereof describe non-limiting examples of the presently disclosed subject matter. It is appreciated that certain features of the presently disclosed subject matter, which are, for clarity, described in the context of separate embodiments, may also be provided in combination in a single embodiment. Conversely, various features of the presently disclosed subject matter, which are, for brevity, described in the context of a single embodiment, may also be provided separately or in any suitable sub-combination.

It is noted that the term “optic bloc” as used herein refers to the lens module together with the auto focus mechanism.

Turning now to FIGS. 2A and 2B, it shows schematically an embodiment of a zoom and auto-focus dual-aperture camera 200 with folded Tele lens disclosed herein in (FIG. 2A) a general isometric view and (FIG. 2B) a sectioned isometric view. The isometric view is shown related to a XYZ coordinate system. Camera 200 comprises two sub-cameras, a regular Wide sub-camera 202 and a Tele sub-camera 204.

Wide camera **202** includes a Wide optics bloc with a respective aperture **208** (indicating object side of the camera) and an optical lens module **210** (or “lens module” in short) with a symmetry (and optical) axis **212** in the Y direction, as well as a Wide image sensor **214**. Tele camera **204** includes a Tele optics bloc with a respective aperture **218** and an optical lens module **220** with a Tele lens symmetry (and optical) axis **222a**, as well as a Tele image sensor **224**.

Camera **200** further comprises a first flat reflecting element (e.g. mirror or prism) **226** inserted in a “Tele” optical path. The Tele optical path is extended from an object (not shown) through the Tele lens module (or simply “Tele lens”) to the Tele sensor and marked by arrows **222b** and **222a**. Arrow **222b** indicates the direction from the object side of the camera and is substantially parallel to symmetry axis **212** of the Wide sub-camera. For simplicity, hereinafter the reflective element is referred to as “mirror”, however, this is by way of example only and should not be construed as limiting in any way.

According to one example, the Wide image sensor **214** lies in the X-Z plane, while the Tele image sensor lies a X-Y

example between 100-500 μm . Camera **200** can further include (or be otherwise operatively connected to) a processing unit comprising one or more suitably configured processors (not shown) for processing the Tele image and the Wide image into an output image.

The processing unit may include hardware (HW) and software (SW) specifically dedicated for operating with the digital camera. Alternatively, a processor of an electronic device (e.g. its native CPU) in which the camera is installed can be adapted for executing various processing operations related to the digital camera (including, but not limited to, processing the Tele image and the Wide image into an output image).

Camera **200** (as well as other cameras mentioned below) may have, according to some non-limiting examples, dimensions and/or parameters as shown in Table 1. These dimensions (given in millimeters) and parameters include a camera width W , a camera length L , a camera height H , a Wide sub-camera effective focal length EFL_W , a Wide F-number $F\#_W$, a Tele sub-camera effective focal length EFL_T and a Tele F-number $F\#_T$.

TABLE 1

FIG.	W	L	H	EFL_W	EFL_M	EFL_T	$F\#_W$	$F\#_M$	$F\#_T$
2A&B	5-12	20-50	4-8	2-8		5-25	2-3		2-5
2C	10-25	10-40	4-8	2-8		5-25	2-3		2-5
3A&B	5-12	20-50	4-8	2-8		5-25	2-3		2-5
4A&B	5-12	20-50	4-8	2-8		5-25	2-3		2-5
6A	5-12	25-60	4-8	2-5	4-10	8-30	2-3	2-3	2-5
6B	5-12	20-50	4-8	2-5	4-10	8-30	2-3	2-3	2-5
6C	10-25	10-40	4-8	2-5	4-10	8-30	2-3	2-3	2-5
7	5-12	25-60	4-8	2-5	4-10	8-30	2-3	2-3	2-5
8	10-25	20-50	4-8	2-8	4-20	8-30	2-3	2-5	2-5

35

plane substantially perpendicular to the Tele lens symmetry axis **222a**. Various camera elements may be mounted on a substrate **232**, e.g. a printed circuit board (PCB). It may be said that the Tele sensor is “upright” as it lies in a plane substantially perpendicular to that of Wide sensor **214** and substrate **232**.

Notably, using a Tele sub-camera with a Tele sensor in an upright position helps to reduce the length of the Tele sub camera and therefore reduces the overall camera footprint, as compared to a Tele sensor positioned in the X-Z plane, as described below with reference to FIGS. **3A** and **3B**.

According to one example, mirror **226** is inclined at substantially 45° to the Tele lens symmetry axis (**222a**) and to arrow **222b**. The Tele optical path is thus “folded”. Hereinafter, a Tele lens having a folded optical path passing therethrough is referred to as a “folded Tele lens” and a Tele sub-camera with such a folded lens is referred to as a “folded Tele sub-camera”.

Both Wide and Tele sub-cameras may be fixed focus (FF) or auto focus (AF). When present, an AF mechanism for the Wide camera is indicated generally by numeral **206**, and in one example it can be similar to the mechanism shown in FIGS. **1A** and **1B**. A new, low profile AF mechanism is described below with reference to FIGS. **12A** and **12B** and FIGS. **13A** and **13B**.

If an AF mechanism is included in the Tele sub-camera, it is applied such that the auto-focus movement is along the Z axis. An AF mechanism may be coupled to and may be operative to move the Tele lens along the Z axis in a direction shown by an arrow **230**, i.e. parallel to its symmetry axis **222a**. The Tele lens movement range may be for

For example, the folding of the Tele lens module in camera **200** (as well as in cameras **300-600** below) enables the use of a Tele lens module with an EFL_T of 12 mm while maintaining the overall camera height significantly lower than the height of a camera utilizing a normal upright Tele lens with the same EFL_T (e.g. 11.1 mm mentioned in the background section above).

In order to provide more clarity and avoid clutter in the following drawings, some elements similar to or identical to elements in camera **200** may be mentioned, but shown without reference numerals.

FIG. **2C** shows schematically, in a general isometric view, another embodiment of a zoom and auto-focus dual-aperture camera (**200'**) with folded Tele lens module disclosed herein. Camera **200'** includes essentially the same elements as camera **200**, and such elements (when numbered) are numbered accordingly with the same numerals. The two cameras differ mainly in the relative positioning (e.g. on substrate **232'**) of the Tele and Wide sub-cameras and mirror **226**.

As shown, these elements are arranged such that camera **200'** has a “squarer” footprint than camera **200**. In particular, a width W in camera **200'** is larger than width W in camera **200**, while a length L in camera **200'** is smaller than L in camera **200**. Note that the configuration shown, in which the Wide sub-camera’s sides are parallel to respectively the X and Z axes while the Tele lens is essentially aligned along the Z axis, is shown by way of example only, and that in other embodiments each sub-camera may be positioned differently. For example, the Wide sub-camera may have sides not parallel to the X, Y axes and the Tele lens may be aligned in a different direction than Z, as long as the optical

65

11

axis, before the folding, is parallel to the Wide camera symmetry axis. Camera 200' may have exemplary dimensions and/or parameters shown in Table 1.

FIGS. 3A and 3B show schematically yet another embodiment of a zoom and auto-focus dual-aperture camera with folded Tele lens disclosed herein and numbered 300 in (FIG. 3A) a general isometric view and (FIG. 3B) a sectioned isometric view. Camera 300 is substantially identical to camera 200, except that camera 300 includes a second mirror 302 inserted in the optical path between the Tele lens and Tele sensor 224, the path marked here by arrows 304a and 304b. In addition, and unlike in cameras 200 and 200' (but as in camera 100), Tele sensor 224 lies in the X-Z plane (same as the Wide sensor). According to one example, the Wide and Tele sensors may be placed on the same substrate, e.g. a PCB. Alternatively, each sensor may be mounted on a separate PCB. Both mirrors can be inclined at substantially 45° to the Tele lens symmetry axis 222a.

As in camera 200, both Wide and Tele sub-cameras may be fixed focus (FF) or auto focus (AF). As in camera 200, an AF mechanism (not shown) is coupled to and operative to move the Tele lens along the Z axis in a direction shown by an arrow 230, i.e. parallel to symmetry axis 222a. Camera 300 may have for example, the same dimensions and/or parameters as camera 200 or be larger (e.g. by about 5-10 mm) along the Z axis.

Camera 300 requires that the Tele lens module is designed such that its back focal length (BFL), i.e. the distance along the optical path from the left hand side of the Tele lens barrel to the mirror, and from there to the Tele image sensor (the combined lengths of arrow 304a and 304b), is large enough to enable the inclusion of the second mirror. In addition, the folded Tele geometry in camera 300 allows direct mounting of the Wide and Tele image sensors on a single common PCB. Alternatively, each sensor may be mounted on a separate PCB. Camera 300 can have for example dimensions and/or parameters shown in Table 1.

FIGS. 4A and 4B show, schematically, an embodiment of a zoom and auto-focus dual-aperture camera with folded Tele lens disclosed herein and numbered 400 in (FIG. 4A) a general isometric view and (FIG. 4B) a sectioned isometric view. Camera 400 is substantially identical to camera 300, except that the Tele sub-camera is auto-focused by means of moving the second mirror using an AF mechanism (see FIGS. 5A and 5B) 402 coupled thereto. Mechanism 402 moves second mirror 302 in a direction perpendicular to its flat plane (e.g. at 45° to the X-Y and X-Z planes) shown by an arrow 430. The mirror movement range may for example, between 100-500 μm. Alternatively, the second mirror 302 can be moved in other directions to focus the Tele image that is captured by the Tele sensor, for example, along the Z axis or the Y axis. Camera 400 may have for example, dimensions and/or parameters shown in Table 1.

FIGS. 5A and 5B show, schematically, details of mechanism 402 in (FIG. 5A) a general isometric view, and (FIG. 5B) a cross sectional view through section A-A. Mechanism 402 includes an electromagnetic actuator comprising a stationary member 404 and a moving member 406. Stationary member 404 includes four permanent magnets 408a-d. Moving member 406, shown here generally to have a cylindrical shape with a symmetry axis 410 includes a core 412 surrounded at least partially by a coil 414. Moving member 406 is mechanically coupled at one end 416 to mirror 302 and at an opposite end 418 to four springs 420a-d, which in turn are rigidly coupled to a stationary frame 422. The number of springs shown is provided by way of example only, and fewer (e.g. one) or more than four

12

springs can be used. In use, a current passing through coil 414 leads to a magnetic force that causes moving member 406 and mirror 302 to move along symmetry axis 410 as indicated by arrow 430.

FIG. 6A shows schematically, in a general isometric view, an embodiment of a zoom and auto-focus triple-aperture camera with one folded Tele lens 600 disclosed herein. Camera 600 includes for example, elements and functionalities of camera 200. That is, camera 600 includes a Wide sub-camera 202 with a Wide lens 210 and a Wide sensor 214, a Tele sub-camera 204 with a folded Tele lens 220, a mirror 226 and an "upright" Tele sensor 224.

In this example, the three sub-cameras are substantially aligned in the Z direction along a common axis. As in camera 200, Tele lens auto-focus is achieved by moving the Tele lens along the Z axis in a direction shown by arrow 230. However, in addition to the elements of camera 200, camera 600 further includes a second Tele (referred to as "Mid" or "M") sub-camera 602 with a Mid lens 604 and a Mid sensor 606. Mid sub-camera 602 has an EFL_M and a FOV_M intermediate to those of the Wide and Tele sub-cameras, (see examples in Table 1). A symmetry (and optical) axis 612 of the Mid sub-camera is substantially parallel to axis 212 of Wide sub-camera 202 and direction 222b in Tele sub-camera 204. Note that while the Wide and Mid sub-cameras are shown in a particular arrangement (with Mid sub-camera 602 closer to Tele sub-camera 204), this order may be changed such that the Wide and Mid sub-cameras exchange places. Camera 600 may have for example, dimensions and/or parameters shown in Table 1.

In use, an output FOV of camera 600 (as well as camera 600', 600", 700 and 800) is defined by a zoom factor ZF. Such an FOV may be marked "FOV_{ZF}". For example, in zoom-in up to a $ZF=ZF_M$ the camera output is the same as the output of a dual-aperture zoom camera with only Wide and Mid sub-cameras, where the Mid sub-camera replaces the Tele sub-camera. When zooming in from ZF_M to ZF_T the camera output is the same as the output of a dual-aperture zoom camera with only Mid and Tele sub-cameras, where the Mid sub-camera replaces the Wide sub-camera. This provides a "continuous zoom" (i.e. resolution gain vs. ZF) experience. A more detailed explanation of the term "continuous zoom" as used herein, and an example of a continuous zoom experience obtained with a camera disclosed herein, are provided with respect to FIG. 8.

FIG. 6B shows schematically, in a general isometric view, another embodiment of a zoom and auto-focus triple-aperture camera with one folded Tele lens disclosed herein and numbered 600'. Camera 600' includes essentially the same elements as camera 600, but the Wide and Mid sub-cameras are aligned along the Z direction, while the Tele sub-camera has the Z direction as its symmetry axis. As in camera 600, the positions of the Wide and Mid sub-cameras are interchangeable. Camera 600' may have for example dimensions and/or parameters shown in Table 1.

FIG. 6C shows schematically, in a general isometric view, yet another embodiment of a zoom and auto-focus triple-aperture camera with one folded Tele lens disclosed herein and numbered 600". Camera 600" includes essentially the same elements as cameras 600 and 600', but the positioning of the three sub-cameras is changed such that the folded Tele lens is adjacent to and parallel to a side 608 of Wide sub-camera 202 and a side 610 of Mid sub-camera 602. As in cameras 600 and 600', the positions of the Wide and Mid sub-cameras are interchangeable. Camera 600" may have, for example, dimensions and/or parameters shown in Table 1.

Note that while the triple-aperture camera with one folded Tele lens embodiments of FIGS. 6A-C are shown as including an “upright” Tele sensor 224, other triple-aperture cameras with one folded Tele lens embodiments may include a second mirror and a Tele sensor positioned in the X-Z plane as in camera 300. One such embodiment is shown in FIG. 7. FIG. 7 shows schematically, in a general isometric view, yet another embodiment of a zoom and auto-focus triple-aperture camera with one folded Tele lens disclosed herein and numbered 700. Camera 700 may be seen essentially as a camera in which a Mid sub-camera 602 is added to the elements of camera 300. Alternatively, it can be seen as a camera in which a second mirror 302 is inserted in the optical path between folded Tele lens 220 and Tele sensor 224. Tele auto-focus may be achieved by (as shown by arrow 430) moving second mirror 302 (as in camera 400), or, alternatively, by moving the Tele lens (as in camera 300). Camera 700 may have for example, dimensions and/or parameters shown in Table 1.

FIG. 8 shows schematically, in a general isometric view, an embodiment of a zoom and auto-focus triple-aperture camera with two folded lenses disclosed herein and numbered 800. Camera 800 may be seen as combining elements existing in camera 200 with an added “folded” Mid sub-camera 802. Thus, as in camera 200, camera 800 may include a Wide sub-camera 202 with a Wide lens and Wide sensor, a Tele sub-camera 204 with a folded Tele lens, an upright Tele sensor 224, and a mirror 226. Folded Mid sub-camera 802 includes a Mid lens 804 and an upright Mid sensor 806. An added mirror 808 reflects radiation arriving from the object side in a direction 810 which is parallel to direction 222b and axis 212, through Mid lens 804 to the Mid sensor along a Mid lens symmetry axis 812, thus providing Mid image data which may be combined with Wide and Tele sub-cameras image data. In some examples, mid lens 804 may be moved by an AF mechanism (not shown) along its axis 812 in the Z direction (the movement illustrated by an arrow 830) to provide Mid autofocus, similar to the Tele autofocus movement illustrated above by arrow 230.

Alternative embodiments (not shown) of a camera with folded Mid and Tele lenses may include additional mirrors and “flat” Mid and Tele sensors (similar to embodiments shown in FIGS. 3A and 3B, 4A and 4B and 7 for the Tele lens). Furthermore, according to this example, autofocus may be achieved by moving these mirrors instead of the lenses. Camera 800 may have for example, dimensions and/or parameters shown in Table 1. This configuration of camera 800 enables for example $EFL_M=3 \cdot EFL_W$ and $EFL_T=9 \cdot EFL_W$ while maintaining a camera height of less than 7 mm.

FIG. 9A illustrates the user experience of resolution gain vs ZF in an ideal optical zoom case. FIG. 9B illustrates the actual user experience of resolution gain vs ZF in a common case of two 13 Mega (13 M) pixel sub-cameras (one Wide and one Tele) and a 2 Mega (2 M) pixel viewer (e.g. display).

For example, assume the Wide and Tele sub-cameras have EFL_S fulfilling $EFL_T=5 \cdot EFL_W$. In this case, the starting resolution ($ZF=1$) will be the 2 M of the viewer. As ZF increases by sub-camera digital zoom, the viewer 2 M pixels will sample a smaller “new” FOV (contributing to higher resolution). This new FOV is a function of ZF i.e. $FOV_{ZF}=FOV_W/ZF$. The new FOV_{ZF} is sampled by a smaller number of pixels (PXC) in the Wide sub-camera (contributing to lower resolution) according to $PXC=13 M/(ZF)^2$. As long as $PXC>2 M$ (or $ZF<(13/2)^{0.5}=DZC$), the perceived resolution will increase with ZF. For ZF close to 1, the

resolution increase will be similar to the resolution increase of an optical zoom. For a digital ZF close to DZC, the resolution increase will be much lower. For a digital $ZF>DZC$, the resolution will remain constant. A formula describing the resolution gain (RG) achieved by digital zoom of the Wide sub-camera as a function of ZF can be written as:

$$RG=RG(W) \cdot (1+CQ \cdot (ZFC-1) \cdot \sqrt{\tan h(((ZF-1)/CQ \cdot (ZFC-1))^2)})$$

where CQ (typically between 0.7-0.8) represents the camera quality at maximum resolution and $RG(W)$ is the perceived object resolution of a Wide sub-camera image without any digital zoom.

In FIG. 9B, RG follows this formula for $1<ZF<5$. At $ZF=5$ (defined as “transition ZF” or ZF_T), the output switches to the T sub-camera with a corresponding $RG(T)=5$, where $RG(T)$ is the perceived object resolution of a T sub-camera image without any digital zoom. In a similar way, the continued resolution gain with ZF after the sub-camera switch follows:

$$RG=RG(T) \cdot (1+CQ \cdot (DZC-1) \cdot \sqrt{\tan h(((ZF/ZF_T-1)/CQ \cdot (DZC-0))^2)})$$

As can be seen from FIG. 9B, the user experience of resolution gain with ZF is very different than in an ideal optical zoom case.

FIG. 9C illustrates a user experience of resolution gain vs. ZF in a common case of 13 M sub cameras and 2 M viewer with a three-aperture camera that includes a Wide sub-camera with EFL_W , an intermediate Mid sub-camera with $EFL_M=2.35 \cdot EFL_W$ and a Tele sub-camera with $EFL_T=5 \cdot EFL_W$. In this case there are two sub-camera transitions $ZF_{T1}=2.35$ and $ZF_{T2}=5$. Correspondingly, there are three resolution gains $RG(W)=1$, $RG(M)=2.35$ and $RG(T)=5$. The figure illustrates the following RG behavior:

$$\text{From } ZF=1 \text{ up to } ZF=2.35, RG=RG(W) \cdot (1+CQ \cdot (DZC-1) \cdot \sqrt{\tan h(((ZF-1)/CQ \cdot (DZC-1))^2)});$$

$$\text{From } ZF=2.35 \text{ up to } ZF=5, RG=RG(M) \cdot (1+CQ \cdot (DZC-1) \cdot \sqrt{\tan h(((ZF/ZF_{T1}-1)/CQ \cdot (DZC-1))^2)});$$

$$\text{From } ZF=5 \text{ onwards, } RG=RG(T) \cdot (1+CQ \cdot (DZC-1) \cdot \sqrt{\tan h(((ZF/ZF_{T2}-1)/CQ \cdot (DZC-0))^2)}).$$

As can be seen, in this case the user experience of resolution gain vs. ZF is very close to the user experience in an ideal optical zoom.

Thus, according to an example of the presently disclosed subject matter, given an EFL_W and an EFL_T , a Mid sub-camera with respective EFL_M can be selected based on the geometric mean of the EFL_W value and an EFL_T value. According to this example, EFL_M is selected based on the equation $=>\sqrt{EFL_T \cdot EFL_W}$, where in some cases EFL_M equals $\sqrt{EFL_T \cdot EFL_W}$.

As mentioned above, it is desirable to design a camera having dimensions which are as small as possible in order to be suitable to operate with commonly used image sensors and to fit the thickness of an electronic device (e.g. a Smartphone), in which the camera is installed (preferably without protruding from the device’s casing). Accordingly, in a multiple-aperture (e.g. dual-aperture) camera as disclosed herein it is desirable to maintain the height of a folded Tele sub-camera as low as possible. Unlike common cameras (e.g. upright sub-cameras), in a folded Tele sub-camera as disclosed herein the height of the camera is related to the dimension of the module in the y axis as shown for example

in FIGS. 2A-C and is largely dependent on the diameter of the largest lens among the lenses in the respective lens module.

At the same time, it is also desirable to achieve good image resolution while providing high zooming effect (e.g. $ZF=\times 5$ or greater) and therefore the aperture diameter in the folded Tele sub-camera must be maintained sufficiently large to enable to achieve a sufficiently small F # (e.g. F # = 3 or smaller). Notably, the larger the EFL of the Tele sub-camera, the larger the aperture must be to maintain a given F #.

Furthermore, in many conventional lens modules (e.g. upright Wide or Tele lens modules) with a sensor being larger than the aperture, the diameter of the lenses is designed to be increasingly wider towards the sensor so it is adapted to the field angle of light entering the camera aperture, which is intended to fall on the entire area of the sensor. In a folded lens unit, this conventional design of increasing lens diameter would result in a greater camera height and is therefore undesirable.

Thus, a new folded Tele sub-camera is disclosed herein having a lens module with a group of lens elements designed with reduced height while maintaining light blockage below a certain value and allowing projection of incoming light on the entire area of the image sensor.

According to examples of the presently disclosed subject matter, the lens elements in the lens module are not designed with an increasingly larger diameter towards the sensor. Rather, the diameter of each lens element in the lens module of the folded Tele sub-camera is reduced in size. The diameter of each lens is determined to be as small as possible while maintaining sufficient light passage through the lens towards the sensor for obtaining desired camera properties (e.g. resolution and SNR) and enabling to continue and provide an image on the entire area (i.e. active pixel area of the sensor) of the image sensor. The image sensors can be for example, a $\frac{1}{3}$ " image sensor and a $\frac{1}{4}$ " image sensor.

According to certain examples, the diameter of the largest lens element in the Tele lens module (comprising at least 3 lens elements) substantially does not exceed the diameter of the aperture (218) for allowing light to enter the Tele sub-camera (i.e. Tele sub-camera aperture). Thus, the diameter of the Tele sub-camera aperture can assist to define maximal diameter of the lens elements in the Tele lens module.

According to one example, the diameter of the largest lens element in the Tele lens module is lower than or equal to the diameter of the Tele-sub camera aperture. According to another example, the diameter of the largest lens element in the Tele lens module does not exceed the diameter of the Tele sub-camera aperture by more than 10%. According to another example, the diameter of the largest lens element in the Tele lens module does not exceed the diameter of the Tele sub-camera aperture by more than 5%. According to yet another example, the diameter of the largest lens element in the Tele lens module does not exceed the diameter of the Tele sub-camera aperture by more than 2.5%. Examples of folded Tele sub-camera design parameters according to these principles are described below with reference to FIGS. 10 and 11 and Tables 2-7.

FIGS. 10A-10C show various exemplary Tele lens modules (numbered 220a, 220b or 220c) that can be used in a

zoom dual-aperture camera disclosed herein, including as a folded Tele lens. Each module includes a respective group of lens elements. Also shown in FIG. 10A are aperture stop 218, symmetry axis 222a in a "z" direction, Tele sensor 224 and an additional cover plate 223.

Lens modules 220a, 220b or 220c include, respectively, 5, 4 and 3 lens elements (or simply "elements"). The lens elements are marked L1, L2, L3, L4 and L5 (in lens module 220a), L1, L2, L3 and L4 (in lens module 220b) and L1, L2 and L3 (in lens module 220c). Notably, the examples described herein include at least 3 lens elements which can provide sufficient imaging quality.

Detailed optical data and aspheric surface data is given in Tables 2 and 3 for lens module 220a, in Tables 4 and 5 for lens module 220b, and in Tables 6 and 7 for lens module 220c. The units of the radius of curvature (R), the lens element thickness and/or distances between elements along the symmetry axis, and the diameter are expressed in mm "N_d" is the refraction index. "V_d" is a parameter indicating lens material color disparity. A large V_d indicates a small color disparity and vice-versa. "BKZ" is a known glass with a known N_d and V_d. The equation of the aspheric surface profiles is expressed by:

$$z = \frac{cr^2}{1 + \sqrt{1 - (1+k)c^2r^2}} + \alpha_1 r^2 + \alpha_2 r^4 + \alpha_3 r^6 + \alpha_4 r^8 + \alpha_5 r^{10} + \alpha_6 r^{12} + \alpha_7 r^{14} + \alpha_8 r^{16}.$$

where "r" is distance from (and perpendicular to) the symmetry axis, k is the conic coefficient, $c=1/R$ where R is the radius of curvature, and a are coefficients given in Tables 3, 5 and 7. Note that the maximum value of r, "max r"=Diameter/2. Also note that in Table 2 (and in Tables 4 and 6 below), the distances between various elements (and/or surfaces) are measured on the symmetry axis Z, wherein the stop is at Z=0. Each number is measured from the previous surface.

TABLE 2

#	Radius (R)	Distance	N _d /V _d	Diameter	Conic coefficient k
1	Infinite	-0.324		4.0	0
2	4.938499	0.779	1.544921/55.9149	4.0	2.2402
3	53.73119	0.074		4.0	28
4	4.310708	1.217	1.635517/23.9718	4.0	1.2159
5	2.127431	0.509		3.5	-0.9831
6	7.374006	0.678	1.544921/55.9149	3.6	10.8851
7	-147.731	0.604		3.5	-12.2
8	-2.28889	0.742	1.635517/23.9718	3.5	-7.6686
9	-2.97793	0.082		3.9	-5.7863
10	2.411553	0.6	1.544921/55.9149	4.1	-6.0953
11	3.111521	6.982		4.0	-8.4191
12	Infinite	0.21	BK7	6.0	0
13	Infinite	0.187		6.0	0
14	Infinite	0		6.1	0

TABLE 3

#	α ₁	α ₂	α ₃	α ₄	α ₅	α ₆	α ₇	α ₈
2	0	-2.5699E-03	-6.5546E-04	-2.4933E-05	-1.9717E-05	9.1450E-07	1.8986E-08	0.0000E+00

TABLE 3-continued

#	α_1	α_2	α_3	α_4	α_5	α_6	α_7	α_8
3	0	4.7508E-04	-4.3516E-04	-6.5166E-05	-4.2148E-07	1.0572E-06	4.4021E-08	0.0000E+00
4	0	-9.1395E-03	2.5655E-04	-4.5210E-05	7.4472E-06	-1.1011E-06	2.8410E-07	0.0000E+00
5	0	-1.0827E-02	1.0372E-03	5.0554E-05	-9.5710E-06	1.1448E-05	-2.2474E-06	0.0000E+00
6	0	-9.5074E-03	1.0268E-03	2.4209E-04	1.1234E-04	3.9355E-06	-9.7194E-06	7.9430E-07
7	0	-3.6269E-03	8.7662E-04	7.0010E-04	6.5578E-05	-2.0053E-05	-4.1923E-06	0.0000E+00
8	0	-1.2355E-02	1.8611E-03	1.5007E-04	-9.4899E-05	-8.0223E-06	-3.1794E-06	0.0000E+00
9	0	-7.3112E-03	9.3354E-04	2.5951E-06	-4.0614E-06	-8.8752E-06	-1.6836E-06	6.2706E-07
10	0	-2.7777E-03	7.1318E-04	3.0673E-05	-2.3126E-06	-2.9513E-06	5.1524E-07	0.0000E+00
11	0	-3.8232E-03	4.8687E-04	4.8505E-05	2.2064E-06	-4.0755E-06	5.8813E-07	0.0000E+00

TABLE 4

#	Radius	Distance	N_d/V_d	Diameter	Conic coefficient k
1	Infinite	-0.420		4.0	
2	4.114235	1.674	1.544921/55.9149	4.0	-0.6679
3	-14.5561	0.073		4.0	15.3789
4	76.19695	1.314	1.635517/23.9718	3.9	-10.0000
5	3.726602	1.130		3.6	-0.3699
6	5.336503	1.407	1.635517/23.9718	3.8	-9.4625
7	9.356809	0.839		3.6	-12.2000
8	2.76767	0.512	1.544921/55.9149	3.8	-3.0862
9	2.342	3.457		4.0	-2.3717
10	Infinite	0.210	BK7	8.0	
11	Infinite	0.894		8.0	
12	Infinite	0.000		8.0	

TABLE 5

#	α_1	α_2	α_3	α_4	α_5	α_6	α_7
2	0	3.1365E-04	-2.4756E-04	-3.2950E-05	-3.1474E-06	-6.6837E-07	-9.3198E-08
3	0	1.1887E-03	-5.1479E-04	-7.0886E-06	-6.6567E-06	7.3082E-07	-2.1508E-07
4	0	-6.7467E-03	1.6492E-03	-1.7937E-04	2.4668E-05	-6.1495E-08	-5.8827E-07
5	0	-1.8460E-02	3.8467E-03	-5.0388E-04	9.0675E-05	6.3951E-06	-4.2041E-06
6	0	-1.0557E-03	5.4851E-04	-1.1124E-04	1.2112E-04	-1.4549E-05	-1.0474E-06
7	0	-1.3355E-02	7.1465E-03	-1.8536E-03	4.1411E-04	-8.4044E-06	-6.4049E-06
8	0	-5.9360E-02	6.4070E-03	4.1503E-04	-2.5533E-04	4.3694E-05	-5.0293E-06
9	0	-5.6451E-02	9.0603E-03	-5.9225E-04	-1.1000E-04	2.2464E-05	-1.5043E-06

TABLE 6

#	Radius	Distance	N_d/V_d	Diameter	Conic coefficient k
1	Infinite	0.060		5.0	0.00
2	7.942	1.682	1.534809/55.6639	5.0	-7.2579
3	-15.778	2.040		5.0	17.1752
4	-2.644	2.143	1.639078/23.2529	5.0	-5.3812
5	-7.001	0.063		5.0	-8.3079
6	2.300	1.193	1.534809/55.6639	5.0	-0.5654
7	3.373	7.787		5.0	-0.1016
8	Infinite	0.210	BK7	8.0	
9	Infinite	0.200		8.0	

TABLE 7

#	α_1	α_2	α_3	α_4	α_5	α_6	α_7
2	0	-3.4545E-04	-2.6977E-04	-6.3091E-06	-7.6965E-07	0.0000E+00	0.0000E+00
3	0	-1.2414E-03	-3.0118E-04	1.6812E-05	-1.6865E-06	1.9446E-07	-1.1391E-08
4	0	3.0073E-03	-4.8811E-04	9.4948E-05	-5.7587E-06	1.0543E-07	0.0000E+00
5	0	3.6847E-03	-4.8608E-04	7.2121E-05	-2.9304E-06	0.0000E+00	0.0000E+00
6	0	-1.5774E-02	1.4580E-03	-2.6302E-04	2.3905E-05	-1.1017E-06	0.0000E+00
7	0	-8.6658E-03	1.2548E-03	-3.6145E-04	5.0797E-05	-3.8486E-06	1.1039E-07

The following terms are defined: “Lens optical height”
 15 “H” is the maximal diameter of the optically used area of each lens element, i.e. the area through which light passes directly from the camera aperture to the sensor to form an image. The term is illustrated in FIG. 11A for a four-element lens module. Each element L_n has a respective optical height
 20 “ H_n ”. The figure shows $H/2$ as the distance between the symmetry axis and the tip of marked arrows. The “camera optical height” is the largest optical height out of all lens elements, in this case H_i .

A “blocked light percentage” (per viewing angle) is
 25 defined as the percentage of light arriving at the camera from a very far object at a certain viewing angle (horizontal and vertical) and which enters the camera aperture but does not reach the image sensor. Notably, the relative light blockage increases with a decrease in the diameter of the lens ele-

ments. FIG. 11B illustrates a blockage 240 of part of the
 light caused by a light stop 250 inserted (by way of example)
 45 between elements L3 and L4 of a four-element Tele lens. Light stop, also known simply as “stop”, is configured to prevent light from reaching the lens edge and being scattered in all directions.

According to the presently disclosed subject matter, the
 50 diameter of the lens elements in the Tele lens module are determined such that light which is blocked by light stops does not prevent more than a predefined percentage of the incoming light from reaching the image sensor.

The Tele lenses disclosed above allow the use of a large
 55 Tele sensor (>4.5 mm×3.35 mm) enabling high pixel count (e.g. 13 Mega pixels). They provide a low camera optical

height that enables a low camera module height (e.g. $<1.25 \times (1 + \text{EFL}/F \#) = 1.25 \times (1 + \text{camera aperture})$), see also FIGS. 12A and 12B and FIGS. 13A and 13B.

The folded Tele lenses disclosed herein allow a long EFL (e.g. >10 mm) for high zoom, a low F # (e.g. <3) to obtain more light and optical resolution, and a low percentage of blocked light ($<25\%$) for all viewing angles. As shown above, a folded Tele lens module may include, for example, 3-5 lens elements. This combination of lens elements enables to obtain a high image quality at a low price.

It is noted that the lens elements of the Tele lens module are held in place by a special structure (e.g. barrel), for example by a plastic tub (cold barrel). Thus, the Tele lens module discussed herein is considered to include the structure holding the lens elements in place (barrel) as well as a substrate (e.g. one or more PCBs). The one or two magnets can be positioned on the substrate as illustrated in FIGS. 12A and 12B and FIGS. 13A and 13B or on the sides of the substrates. In any case their height substantially does not exceed the height of the Tele lens module.

FIGS. 12A and 12B show in (FIG. 12A) an isometric view and in (FIG. 12B) an external view of a camera disclosed herein and numbered 1200. Camera 1200 includes a two-magnet (1202 and 1204), two-coil (1206 and 1208) AF mechanism for the folded Tele lens. Each pair of magnet-coils is disposed so as to provide a force that moves a Tele lens 1210 along its symmetry axis. The force (and movement) are countered (and reversed) by a spring 1212.

FIGS. 13A and 13B show in (FIG. 13A) an isometric view and in (FIG. 13B) an external view of a camera disclosed herein and numbered 1300. In contrast with camera 1200, camera 1300 includes a one-magnet (1302), one-coil (1306) and spring (1312) AF mechanism for the folded Tele lens. AF mechanisms illustrated in FIGS. 12A and 12B and FIGS. 13A and 13B are configured to operate according to the principles of voice coil actuator (VCA, commonly known as "magnetic actuators").

This AF mechanism is specifically designed to maintain a low camera profile. According to one example, the AF mechanism is designed to fit laterally on one or two faces of the Tele lens module, while the other faces remain clear of the AF mechanism parts.

Specifically, one or two magnets (coupled magnetically to respective coils) are designed with a height substantially not exceeding the height of the Tele lens module in order to avoid any significant contribution to the overall height of the Folded Tele sub-camera.

This design is illustrated in FIGS. 12A and 12B (showing an AF design with two magnets) and FIGS. 13A and 13B (showing an AF design with one magnet). Note that while the magnets are positioned upright on one or two sides of the Tele lens module, the two other plains (on the object side, marked by arrow OS, and substrate side, marked by arrow SS), located perpendicular to the magnets, remain clear of the magnets. This design of the AF mechanism in general and the magnets, specifically significantly reduces (or, in some configurations, completely avoids) an increase in the overall height of the Tele sub-camera which may have been otherwise induced by the AF mechanism.

According to one example, the height of the magnets is lower than or equal to the height of the Tele lens module (defined for example by the highest lens). According to another example, the height of the magnets does not exceed the height of the Tele lens module by more than 10%. According to another example, the height of the magnets does not exceed the height of the Tele lens module by more

than 5%. According to another example, the height of the magnets does not exceed the height of the Tele lens module by more than 2.5%.

The entire camera (including the AF mechanism) may be packaged in a low profile mechanical packaging (casing) 1250 with height H_T (height total), see FIG. 12B, enabling inclusion of a zoom dual or triple aperture camera disclosed herein in a low profile cell-phone, such that H_T is equal to or smaller than 6.5 mm and in some examples equal to or smaller than 5.7.

FIG. 14 shows a schematic illustration of an example of a portable electronic device with an integrated dual-aperture camera with folded Tele lens module, according to an example of the presently disclosed subject matter. As illustrated in the image, the camera 1450 (including dual aperture camera with folded Tele lens module and the camera casing) is fully integrated in the portable electronic device 1400 and does not protrude from the device casing. The camera is oriented within the portable device such that its longitudinal dimension is positioned horizontally with respect to the device. Due to the folded optical path of the Tele sub-camera it can provide a high zooming effect (e.g. $\times 5$ or greater) while having a structure not protruding from the casing of the electronic device (e.g. Smartphone).

While this disclosure has been described in terms of certain embodiments and generally associated methods, alterations and permutations of the embodiments and methods will be apparent to those skilled in the art. The disclosure is to be understood as not limited by the specific embodiments described herein, but only by the scope of the appended claims.

What is claimed is:

1. An auto-focus (AF) mechanism capable of being integrated in a folded Tele sub-camera configured to accommodate for a Tele lens module having a Tele lens module height, wherein the Tele lens has a Tele lens symmetry axis, wherein the AF mechanism is configured to move the Tele lens along the Tele lens symmetry axis and wherein the AF mechanism has a height not exceeding the Tele lens module height.
2. The AF mechanism of claim 1, wherein a Tele lens module plane facing an object side and a Tele lens module plane facing a substrate side do not touch AF mechanism parts.
3. The AF mechanism of claim 1, wherein the AF mechanism includes a plurality of magnets and associated coils, and wherein a Tele lens module plane facing an object side and a Tele lens module plane facing a substrate side do not have magnets and coils.
4. The AF mechanism of claim 2, wherein the Tele lens module plane facing the object side and the Tele lens module plane facing the substrate side do not have magnets.
5. The AF mechanism of claim 4, wherein the coils are positioned laterally on one or two sides of the Tele lens module that are perpendicular to the Tele lens module plane facing an object side and the Tele lens module plane facing a substrate side.

6. A lens module having an aperture diameter (AD) and a height (H) and carrying a lens, the lens module capable of being integrated in a folded sub-camera module having a camera module height (CMH) together with an image sensor and a reflecting element receiving light along a first optical path from an object side, the lens including a group of N lens elements L_1 to L_N in order from an object side to an image side and having a lens symmetry axis along a second optical path positioned substantially perpendicular to the first optical path, the N lens elements designed to have a diameter substantially not exceeding AD, wherein $CMH < (1.25 \times (1$

21

mm+AD)) in millimeters, and wherein an auto-focus (AF) mechanism with an AF mechanism height not exceeding H is configured to move the lens along the lens symmetry axis.

7. The lens module of claim 6, wherein the image sensor has a sensor size S, fulfilling the condition $\frac{1}{3} \text{ inch} \geq S \geq \frac{1}{4} \text{ inch}$.

* * * * *

22