
W. MANGOLD. CONTAINER. APPLICATION FILED MAR. 8, 1915.

1,154,710.

Patented Sept. 28, 1915.



WILLIAM MANGOLD

Witnesses Nobert M. Lutylieut. a. J. Hind.

By Watson E Coleman

UNITED STATES PATENT OFFICE.

WILLIAM MANGOLD, OF BALTIMORE, MARYLAND.

CONTAINER.

1,154,710.

Specification of Letters Patent. Patented Sept. 28, 1915.

Application filed March 8, 1915. Serial No. 12,895.

To all whom it may concern:

Be it known that I, WILLIAM MANGOLD, a citizen of the United States, residing at Baltimore, State of Maryland, have in-5 vented certain new and useful Improvements in Containers, of which the following is a specification, reference being had to the accompanying drawings.

This invention relates to certain improve-10 ments in containers, and more particularly to a device of this general character especially designed and adapted for use in connection with liquids such as milk; and it is an object of the invention to provide 15 a device of this general character which can be produced with a minimum of expense and at the same time possesses a maximum of efficiency.

Furthermore, it is an object of the inven-20 tion to provide a device of this general character including a removable closure member and having novel and improved means whereby said closure member may be removed from operative position with

25 convenience and facility. The invention consists in the details of construction and in the combination and arrangement of the several parts of my improved container whereby certain impor-30 tant advantages are attained and the device is rendered simpler, less expensive and otherwise more convenient and advantageous for use, all as will be hereinafter more

fully set forth. The novel features of the invention will be carefully defined in the appended claim. In order that the invention may be the

better understood, I will now proceed to describe the same with reference to the ac-

40 companying drawings, wherein-Figure 1 is an elevational view, with a portion broken away, of a container constructed in accordance with an embodiment of my invention; and Fig. 2 is a sectional 45 view taken substantially on the line 2-2

of Fig. 1.

As disclosed in the accompanying drawings, 1 denotes the body of my container of cylindrical form and having one end 50 closed, said container being preferably produced from paper pulp and impregnated with and exteriorly coated with paraffin, whereby the same is rendered imper-

vious to moisture. It is also to be observed that the body 1 is disposed on a slight taper 55 in order to facilitate the packing and ship-

ping thereof.

2 denotes a removable closure member for the open end of the container, said closure member being also produced from paper 60 pulp and saturated with and exteriorly coated with paraffin, and provided with an annular flange 3 adapted to overlie the body 1 and snugly engage the same, whereby it will be observed that an effective closure for 65 the container is afforded.

In order that the closure member 2 may be readily and conveniently removed, I interpose between the flange 3 and body 1 the segmental metallic member 4 provided 70 intermediate its length with an elongated tongue 5 projecting beyond the flange 3 and which may be readily grasped by the digits of the hand. The member 4 is frictionally held in applied position, yet is also 75 free to move around the body 1 whereby the flange 3 may be readily and conveniently loosened or disengaged from the body 1 and the closure member 2 removed from opera-

tive position. From the foregoing description it will be obvious that a container constructed in accordance with my invention is of an extremely simple and comparatively inexpensive nature and is particularly well adapted 85 for use by reason of the convenience and facility with which it may be assembled, and it will also be obvious that my invention is susceptible of some change and modification without material departure from 90 the principles and spirit thereof and for this reason I do not wish to be understood as limiting myself to the precise arrangement and formation of the several parts herein shown in carrying out my invention 95 in practice.

Having described my invention, what I

claim is: A container comprising a body having one end open and having an exterior coat- 100 ing of material yieldable to pressure, a movable closure member for the open end of said body provided with an annuar flange overlying the body, and a substantially T-shape member, the head of said 105 member being positioned between the annular flange and the adjacent portion of the body and frictionally held in said position, the stem of said member being of a length to project beyond the flange, the edges of the head serving to separate the flange of the cover from the body upon movement of the member around the body.

In testimony whereof I hereunto affix my signature in the presence of two witnesses.

WILLIAM MANGOLD.

Witnesses:

J. R. Jones, Harvey C. Jones.

Copies of this patent may be obtained for five cents each, by addressing the "Commissioner of Patents, Washington, D. C."