



US011555574B2

(12) **United States Patent**
Dowd et al.

(10) **Patent No.:** **US 11,555,574 B2**
(45) **Date of Patent:** **Jan. 17, 2023**

(54) **HEIGHT ADJUSTABLE MONITOR ARM MOUNTING ASSEMBLY**

(71) Applicant: **OmniMax USA, LLC**, Anna, TX (US)

(72) Inventors: **Paul Dowd**, Scarsdale, NY (US);
Bennet O. Poepping, Tuckahoe, NY (US)

(73) Assignee: **OmniMax USA, LLC**, Anna, TX (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/879,043**

(22) Filed: **May 20, 2020**

(65) **Prior Publication Data**

US 2021/0364122 A1 Nov. 25, 2021

(51) **Int. Cl.**

F16M 11/04 (2006.01)
F16M 11/16 (2006.01)
F16M 11/18 (2006.01)

(52) **U.S. Cl.**

CPC **F16M 11/046** (2013.01); **F16M 11/041** (2013.01); **F16M 11/045** (2013.01); **F16M 11/16** (2013.01); **F16M 11/18** (2013.01)

(58) **Field of Classification Search**

CPC .. **F16M 11/046**; **F16M 11/041**; **F16M 11/045**; **F16M 11/16**; **F16M 11/18**
USPC **248/243**, **407-409**, **125.3**, **245**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

90,344 A *	5/1869	Dare	B65B 67/12
				248/125.3
1,732,081 A *	10/1929	Clement	B25H 1/0007
				269/84
6,017,009 A *	1/2000	Swartz	A47B 57/10
				248/245
6,863,252 B2 *	3/2005	Bosson	F16M 11/041
				248/278.1
8,398,049 B2 *	3/2013	Lategan	F16M 11/08
				248/125.7
RE44,727 E *	1/2014	Bosson	F16M 11/2014
				248/278.1
2002/0011544 A1 *	1/2002	Bosson	F16M 11/041
				248/274.1
2002/0113180 A1 *	8/2002	Wiebe	F16M 11/16
				248/188
2015/0342351 A1 *	12/2015	Hung	G09F 15/0087
				211/26
2017/0261030 A1 *	9/2017	Hung	F16M 11/08
2018/0094768 A1 *	4/2018	Burke	F16M 11/2014
2020/0386367 A1 *	12/2020	Hung	F16M 13/022

* cited by examiner


Primary Examiner — Christopher Garft

(74) *Attorney, Agent, or Firm* — Frank M. Scutch, III

(57) **ABSTRACT**

A height adjustable monitor arm assembly includes a monitor arm having a latch mechanism where a post arm includes indented rings therein for engaging the latch mechanism. The monitor arm includes an aperture for positioning the at least one monitor arm over the post arm so that the latching mechanism engages with one of the plurality of indented rings to vertically adjust the at least one monitor arm along the length of the post arm. Further, a dual adapter arm also includes its own latching mechanism and mounts over the vertical post arm for use where monitor displays can be mounted on both ends thereof. In one embodiment, a four monitor configuration can be held in position allowing for enhanced user utility in their workspace.

9 Claims, 4 Drawing Sheets






FIG. 1




FIG. 2







FIG. 3



1

HEIGHT ADJUSTABLE MONITOR ARM MOUNTING ASSEMBLY

FIELD OF THE INVENTION

The present invention relates generally to electronic displays and monitors and more particular to a height adjustable monitor arm mounting assembly.

BACKGROUND OF THE INVENTION

Arms fastened to computer monitors and displays are well known in the art. These devices typically hold a monitor above a desk top and provide some angular adjustment so the user can better see the display. In order to prevent fatigue, user's typically want to view a monitor at eye level. One problem with current monitor arms is it that they are not easily vertically adjusted. The user can view the monitor only by tilting their head by looking up or down. This causes muscle strain over long periods of time.

Although some monitor mounts allow a vertical adjustment with a 4-bar linkage and gas spring, the gas spring is difficult adjust correctly. Moreover the gas spring is often unable to reliably support the monitor after some amount of time. Other systems are vertically fixed with a clamp or set screw, and require a tool loosen and tighten the device. This makes it difficult to adjust height due to the weight hanging off the arm and typically requires a great deal of force and/or friction to prevent slippage.

Accordingly, new solutions are required to adjust monitor viewing angle and height allowing the user a great comfort and ease of use.

SUMMARY OF THE INVENTION

A height adjustable monitor arm assembly includes a vertical post arm having at least one indented ring formed thereon. At least one monitor arm has an aperture for mounting over the post arm. The at least one monitor arm includes a latch mechanism therein for engaging with the at least one indented ring to hold the at least one monitor arm in a fixed position along the length of the vertical post arm. The assembly includes an actuator configured within the at least one monitor arm for operating a resilient member allowing the at least one monitor arm to be disengaged from the at least one indented ring. The at least one monitor arm is comprised with a proximal arm for attachment to the vertical arm post and a distal arm for connecting to a monitor where the distal arm includes at least one hinge for allowing the monitor to be horizontally adjusted.

The assembly may also include a dual adapter arm having an aperture for mounting to the vertical post arm where the dual adapter arm includes a latch mechanism therein for engaging with the at least one indented ring to hold the dual adapter arm in a fixed position along the length of the vertical post arm. The dual adapter arm includes at least one actuator configured within the dual adapter arm for operating a resistant member allowing the dual adapter arm to be disengaged from the at least one indented ring.

BRIEF DESCRIPTION OF THE FIGURES

The accompanying figures, where like reference numerals refer to identical or functionally similar elements throughout the separate views and which together with the detailed description below are incorporated in and form part of the specification, serve to further illustrate various embodiments

2

and to explain various principles and advantages all in accordance with the present invention.

FIG. 1 is a perspective view of a height adjustable monitor arm mounting assembly for holding three monitors each having adjustable height.

FIG. 2 is an exploded view of a single monitor arm according to an embodiment of the invention.

FIG. 3 is an exploded view of a dual adapter allowing the arm to hold two-monitors.

FIG. 4A, FIG. 4B and FIG. 4C are illustrations of the monitor arm moving between a raised and lowered position.

Skilled artisans will appreciate that elements in the figures are illustrated for simplicity and clarity and have not necessarily been drawn to scale. For example, the dimensions of some of the elements in the figures may be exaggerated relative to other elements to help to improve understanding of embodiments of the present invention.

DETAILED DESCRIPTION

Before describing in detail embodiments that are in accordance with the present invention, it should be observed that the embodiments reside primarily in combinations of method steps and apparatus components related to a height adjustable monitor arm. Those skilled in the art will recognize that a monitor arm may be used with a computer, television and/or other video apparatus. Accordingly, the apparatus components and method steps have been represented where appropriate by conventional symbols in the drawings, showing only those specific details that are pertinent to understanding the embodiments of the present invention so as not to obscure the disclosure with details that will be readily apparent to those of ordinary skill in the art having the benefit of the description herein.

In this document, relational terms such as first and second, top and bottom, and the like may be used solely to distinguish one entity or action from another entity or action without necessarily requiring or implying any actual such relationship or order between such entities or actions. The terms "comprises," "comprising," or any other variation thereof, are intended to cover a non-exclusive inclusion, such that a process, method, article, or apparatus that comprises a list of elements does not include only those elements but may include other elements not expressly listed or inherent to such process, method, article, or apparatus. An element preceded by "comprises . . . a" does not, without more constraints, preclude the existence of additional identical elements in the process, method, article, or apparatus that comprises the element.

FIG. 1 is a perspective view of a height adjustable monitor arm mounting assembly for holding three monitors each having adjustable height. Those skilled in the art will recognize the term "monitor" to mean an electronic visual display device that includes a screen and operational circuitry. The monitor may include but is not limited to a computer monitor display, television monitor or other electronic display device. As seen in FIG. 1, the monitor arm assembly **100** includes a post arm **101** that is cylindrical in shape having a plurality of indented rings formed at predetermined positions along the entire length of its body. Each indented ring is smaller in diameter than the body of the post arm **101**. Hence, each ring has an inner diameter that is smaller in size than the outer diameter of the post arm **101**. Although indented rings are used in this embodiment to secure the monitor arm(s), other mounting structures and methods are also possible e.g. rings or other protrusions having a diameter greater than that of the post arm **101**. At

3

one end, the post arm **101** uses a mounting clamp for securing the post arm **101** to the surface of a desk, table or other flat surface. As seen in FIG. 1, this embodiment uses two different types of monitor arms attached to the post arm **101** for example, one using a distal arm and one without a distal arm.

In order to hold a single monitor to the post arm **101**, a single monitor arm **105** is formed using a proximal arm **107** jointed to a distal arm **109**. As will be described herein, a hole, opening or aperture is formed in the proximal arm **107** slides over and end of the post arm **101** so that it be adjustably positioned along the length of the post arm **101** at any desired location. In an alternative, embodiment, the aperture can be opened and clipped on from the side of the post arm. The distal arm **109** is adjustably fastened at one end to the proximal arm **107** where its opposite end has a monitor mount **111** for attachment to the rear housing of a video monitor. Although the monitor mount **111** is shown here having a standardized star-like configuration, those skilled in the art will recognize that other configurations of monitor mount are also possible. As will be described herein, the monitor arm **105** is vertically adjustable allowing the user to easily adjust its height on the post arm **101** above a desk or table top.

Further, other configurations allow two or more monitors to be attached along the post arm **101**. More specifically a dual adapter arm **113** has an aperture centrally located in its body. The aperture slides over one end of the post arm **101** where the sides of the dual adapter arm **113** are both accessible. In one embodiment, a left monitor arm **115** is attached to the left side of the dual adapter arm **113** while a right monitor arm **117** attaches to the right side of the dual adapter arm **113**. As noted with regard to the monitor arm **105**, the dual adapter arm **113** slides over the top of the post arm **101** at one end, where its height can be adjusted anywhere along the length of the post arm **101**. The dual adapter arm **113** includes a left proximal arm **119**, left distal arm **121** and monitor mount **123**. Similarly, the dual monitor arm **117** is comprised of a right proximal arm **125**, right distal arm **127** and monitor mount **129**. The pivotal nature of each of the monitor arms allows a monitor screen to be easily adjusted for desired viewing angles. Those skilled in the art will further recognize that in order to reduce cost, the dual adapter arm **113** can use the same components as the single monitor arm **105**.

Finally, in situations where multiple monitors are required, a triple-add arm **131** can be used. The triple-add arm **131** is comprised of a proximal arm **133** mounted directly to a monitor mount **135**. The triple-add arm **131** is short having no distal arm attached thereto. The triple-add arm **131** also slides over the top of the post arm **101** at one end where it can be positioned directly above the dual adapter arm **113**. The triple-add arm **131** derives its name from situations where three monitors are required to be positioned together laterally, in a row, across the body of the dual adapter arm **113**.

FIG. 2 is an exploded view of a single monitor arm according to an embodiment of the invention. The single monitor arm **200** is comprised of an upper housing **201** and a lower housing **203**. The combination of the upper housing **201** and lower housing **203**, when joined together, form the proximal arm **205**. Mounted within the lower housing **203**, is a latch mechanism **207**. The latch mechanism **207** uses a spring lever **209** that provides a resilient force. An aperture in the lower housing exposes an actuator such as a button **211** that uses a resilient member such as a spring **213** to release the latch **215**. Those skilled in the art will recognize

4

that the latch mechanism **207** pivots by engaging one of the indented rings in the post arm to hold the proximal arm **205** in a fixed position. When the upper housing **201** and the lower housing **203** are joined, an upper spacer **213** and lower spacer **215** are joined through aperture **217** using a screw or other fastener **219**. An upper grommet **221** and lower grommet **223** are also joined together allowing wire and/or cable to pass through the interior of the proximal arm **205**. The distal arm **227** connects to the proximal arm **205** using the upper spacer **213** and/or lower spacer **215**. A monitor mount **229** connects to the distal arm **227** using a hinge **231**. Finally, cable fasteners **233**, **235** are attached under the lower housing **203** allowing wires and cables to be routed to an attached monitor. Thus the single monitor arm can be adjusted both vertically and horizontally allowing the user to position a monitor in practically any desired position.

FIG. 3 is an exploded view of a dual adapter arm allowing the arm to hold two-monitors or other display devices. The dual adapter arm **300** includes an upper adapter housing **301** and lower adapter housing **303**. The upper adapter housing **301** includes a first spacer **305** and second spacer **307** that is engaged with respective threaded studs **309**, **311** extending upwardly from the upper adapter housing **301**. The spacers **305**, **307** each have end caps **313**, **315** for covering the interior of the respective spacer. As seen in FIG. 1, the first spacer **305** and second spacer **307** fit within a respective aperture in the proximal arm. A bushing or grommet **317** fits within the aperture **319** that is used for routing cable and wire through the dual adapter arm **300**.

The lower adapter housing **303** uses a plurality of latch mechanisms for engaging the indented rings in the post arm. Two latch mechanisms are provided to provide a greater hold when the dual adapter arm **300** is supporting two or three monitors. A first latch mechanism **321** is provided to the left of an aperture **323** while a second latch mechanism **325** is provided to the right the aperture **323**. The first latch mechanism **321** and second latch mechanism **325** both include respective spring levers **327**, **329** that use a latch **331**, **333** to engage the post arm. The spring levers **327**, **329** must be pushed or engaged with force to overcome their resilient members therein. Apertures **335**, **337** in the lower adapter housing **303** expose buttons **339**, **341** that use the respective spring levers **327**, **329** to release the respective latch **331**, **333**. Those skilled in the art will recognize that the first latch mechanism **321** and second latch mechanism **325** both independently pivot and hold the dual adapter arm in a fixed position by engaging the indented rings in the post arm. Finally, a grommet **335** partially fills the aperture **323** for use in routing wire and cable where cable fasteners **337** and **338** hold the cable securely under the lower adapter housing **303**.

FIG. 4A, FIG. 4B and FIG. 4C are illustrations of the monitor arm moving between raised and lowered positions along the length of the post arm. FIG. 4A illustrates a monitor arm **401** positioned substantially low on the a post arm **403**. When the user wishes to raise monitor arm **401** to a higher level, the user will engage an actuator such as a button **405** with their finger **407**. As described with regard to both FIG. 2 and FIG. 3, the button disengages the latch from the indented ring in the post arm **403** allowing the monitor arm to move freely. FIG. 4B illustrates the monitor arm **401** being raised upwardly along the post arm **403** so a monitor can be adjusted to a higher viewing level. Finally, FIG. 4C illustrates the monitor arm **401** at a final raised position along the post arm **403** where the user can release the button **405** to reengage the latch to an indented ring.

5

Thus, the present invention is directed to a height adjustable video monitor arm mounting assembly that includes one or more single monitor arms as well as a dual adapter arm whose height is adjustable along the length of a post arm that is fastened vertically to a desk or table top. In one embodiment, the mounting assembly can hold four monitors that are all vertically and horizontally adjustable offering a user a high degree utility in viewing multiple monitors in their workspace.

In the foregoing specification, specific embodiments of the present invention have been described. However, one of ordinary skill in the art appreciates that various modifications and changes can be made without departing from the scope of the present invention as set forth in the claims below. Accordingly, the specification and figures are to be regarded in an illustrative rather than a restrictive sense, and all such modifications are intended to be included within the scope of present invention. The benefits, advantages, solutions to problems, and any element(s) that may cause any benefit, advantage, or solution to occur or become more pronounced are not to be construed as a critical, required, or essential features or elements of any or all the claims. The invention is defined solely by the appended claims including any amendments made during the pendency of this application and all equivalents of those claims as issued.

We claim:

1. A height adjustable monitor arm assembly comprising: a vertical post arm having at least one indented ring formed thereon; a proximal monitor arm formed using an upper housing and lower housing and having an aperture configured therein for mounting over the post arm; a distal monitor arm attached to the proximal monitor arm for attaching to a display monitor; an actuator having a user operable button extending under the proximal monitor arm for operating a latch mechanism, such that the latch mechanism includes a levered arm having a tab at one end, where the user operable button is pressed to push the tab of the levered arm causing the latch mechanism to move away from the post arm, the latch member having an arc shaped tooth at one end; and wherein the arc shaped tooth engages within the at least one indented ring to hold the proximal monitor arm in a fixed position along the length of the vertical post arm.
2. A height adjustable monitor arm assembly as in claim 1, wherein the distal monitor arm includes at least one hinge for allowing the monitor display to horizontally adjusted.
3. A height adjustable monitor arm assembly comprising: at least one monitor arm formed from a proximal monitor arm and a distal monitor arm such that the proximal monitor arm is pivotably connected to the distal monitor arm; a post arm having a plurality of indented rings therein; an actuator having a button extending under the proximal monitor arm for operating a latch mechanism, the latch mechanism having a levered arm with a tab at one end, where the the button is pressed to push the tab causing the latch mechanism to move away from the post arm,

6

the latch member biased by a resilient member and having an arc shaped tooth at one end for allowing the at least one monitor arm to be disengaged from one of the plurality of indented rings; and

- wherein the proximal monitor arm includes an aperture for positioning the proximal monitor arm over the post arm so that the arch shaped tooth engages with one of the plurality of indented rings to vertically adjust the at least one monitor arm along the length of the post arm.
4. A height adjustable monitor arm assembly as in claim 3, wherein the distal monitor arm includes at least one hinge for allowing a monitor display to horizontally adjusted.
 5. A height adjustable monitor arm assembly as in claim 3, further comprising: a dual adapter arm having an aperture for mounting over the post arm for use in mounting monitors on both ends thereof, where the dual adapter arm includes at least one latch mechanism therein for engaging with one of the plurality of indented rings to hold the dual adapter arm in a fixed position along the length of the post arm.
 6. A height adjustable video monitor arm assembly comprising: a post arm having a plurality of indented rings and mounted vertically from a table surface; a first monitor arm having an aperture for mounting the first monitor arm over the post arm; a second monitor arm having an aperture for mounting the second monitor arm over the post arm; a dual monitor arm having an aperture for mounting the second monitor arm over the post arm; and wherein each of the first monitor arm, second monitor arm and dual monitor arm includes at least one latch mechanism for engaging with one of the plurality of indented rings for holding the first monitor arm, second monitor arm and dual monitor arm in a fixed position along the length of the post arm, and where an actuator includes a button configured under each of the first monitor arm, second monitor arm and dual monitor arm for operating the at least one latch mechanism, the at least one latch mechanism includes a levered arm having a tab at one end, where the button is pressed to push the tab causing the at least one latch mechanism to move away from the post arm, the latch mechanism is moveable and is biased by a resilient member, the latch mechanism having an arc shaped tooth at one end for allowing the first monitor arm, second monitor arm and dual monitor arm to be disengaged from the at least one indented ring to adjust its position on the post arm.
 7. A height adjustable video monitor arm assembly as in claim 6, wherein the first monitor arm is comprised with a proximal arm for attachment to the vertical arm post and a distal arm for connecting to a monitor.
 8. A height adjustable video monitor arm assembly as in claim 7, wherein the distal arm includes at least one hinge for allowing the computer monitor to horizontally adjusted.
 9. A height adjustable video monitor arm assembly as in claim 8, wherein the distal arm includes a monitor mount for use in mounting to the back of a monitor housing.

* * * * *