



US011562785B1

(12) **United States Patent**
Tanaka et al.

(10) **Patent No.:** **US 11,562,785 B1**
(45) **Date of Patent:** **Jan. 24, 2023**

(54) **MICROELECTRONIC DEVICES, AND RELATED MEMORY DEVICES AND ELECTRONIC SYSTEMS**

(71) Applicant: **Micron Technology, Inc.**, Boise, ID (US)

(72) Inventors: **Tomoharu Tanaka**, Kanagawa (JP); **Yoshiaki Fukuzumi**, Kanagawa (JP)

(73) Assignee: **Micron Technology, Inc.**, Boise, ID (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **17/446,340**

(22) Filed: **Aug. 30, 2021**

(51) **Int. Cl.**

- G11C 11/4097** (2006.01)
- H01L 27/11551** (2017.01)
- H01L 27/11529** (2017.01)
- H01L 27/11573** (2017.01)
- G11C 11/4091** (2006.01)
- B81B 7/00** (2006.01)
- H01L 27/11578** (2017.01)

(52) **U.S. Cl.**

CPC **G11C 11/4097** (2013.01); **B81B 7/008** (2013.01); **G11C 11/4091** (2013.01); **H01L 27/11529** (2013.01); **H01L 27/11551** (2013.01); **H01L 27/11573** (2013.01); **H01L 27/11578** (2013.01); **B81B 2201/07** (2013.01)

(58) **Field of Classification Search**

CPC . G11C 11/4097; G11C 11/4091; B81B 7/008; B81B 2201/07; H01L 27/11529; H01L 27/11551; H01L 27/11573; H01L 27/11578

USPC 365/63
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,400,604	B2	6/2002	Noda
8,456,920	B2	6/2013	Arizono
8,611,153	B2	12/2013	Tanzawa
8,656,092	B2	2/2014	Ha
8,958,228	B2	2/2015	Samachisa et al.
8,971,112	B2	3/2015	Crippa et al.
9,299,442	B2	3/2016	Ha
9,305,660	B2	4/2016	Moschiano et al.
9,343,169	B2	5/2016	Vali et al.
9,672,156	B2	6/2017	Ha
9,679,913	B1 *	6/2017	Hu H01L 27/11565
10,468,116	B2	11/2019	Ha
10,510,397	B2	12/2019	Shigekazu

(Continued)



Primary Examiner — Fernando Hidalgo

(74) *Attorney, Agent, or Firm* — TraskBritt

(57) **ABSTRACT**

A microelectronic device comprises local digit line structures, global digit line structures, source line structures, sense transistors, read transistors, and write transistors. The local digit line structures are coupled to strings of memory cells. The global digit line structures overlie the local digit line structures. The source line structures are interposed between the local digit line structures and the global digit line structures. The sense transistors are interposed between the source line structures and the global digit line structures, and are coupled to the local digit line structures and the source line structures. The read transistors are interposed between and are coupled to the sense transistors and the global digit line structures. The write transistors are interposed between and are coupled to the global digit line structures and the local digit line structures. Additional microelectronic devices, memory devices, and electronic systems are also described.

27 Claims, 6 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2009/0268537 A1 10/2009 Kajigaya
2011/0233644 A1* 9/2011 Fukuzumi H01L 29/42344
257/324
2012/0182804 A1* 7/2012 Hung G11C 16/0483
365/185.13
2013/0176781 A1* 7/2013 Hung G11C 16/04
365/185.05
2015/0194380 A1* 7/2015 Takaki H01L 27/11551
438/666
2018/0364908 A1 12/2018 Lea et al.
2018/0365293 A1 12/2018 De Santis et al.
2020/0118615 A1 4/2020 Shigekazu
2020/0258897 A1* 8/2020 Yan H01L 27/11573
2021/0210506 A1* 7/2021 Yan H01L 23/5226
2022/0020761 A1* 1/2022 Yeh H01L 27/11573
2022/0068957 A1* 3/2022 Yeh H01L 27/11565

* cited by examiner




FIG. 1A




FIG. 1C




FIG. 2A




FIG. 2B




FIG. 3

1

**MICROELECTRONIC DEVICES, AND
RELATED MEMORY DEVICES AND
ELECTRONIC SYSTEMS**

TECHNICAL FIELD

The disclosure, in various embodiments, relates generally to the field of microelectronic device design and fabrication. More specifically, the disclosure relates to microelectronic devices including local digit line structures and global digit line structures, and to related memory devices, and electronic systems.

BACKGROUND

Microelectronic device designers often desire to increase the level of integration or density of features within a microelectronic device by reducing the dimensions of the individual features and by reducing the separation distance between neighboring features. In addition, microelectronic device designers often desire to design architectures that are not only compact, but offer performance advantages, as well as simplified, easier and less expensive to fabricate designs.

One example of a microelectronic device is a memory device. Memory devices are generally provided as internal integrated circuits in computers or other electronic devices. There are many types of memory devices including, but not limited to, non-volatile memory devices (e.g., NAND Flash memory devices). One way of increasing memory density in non-volatile memory devices is to utilize vertical memory array (also referred to as a “three-dimensional (3D) memory array”) architectures. A conventional vertical memory array includes strings of memory cells vertically extending through a stack structure including tiers of conductive structures and insulative materials. Each string of memory cells may include at least one select device coupled in series to a serial combination of vertically stacked memory cells. Such a configuration permits a greater number of switching devices (e.g., transistors) to be located in a unit of die area (e.g., length and width of active surface consumed) by building the array upwards (e.g., vertically) on a die, as compared to structures with conventional planar (e.g., two-dimensional (2D)) arrangements of transistors.

In a conventional non-volatile memory device (e.g., a conventional 3D NAND Flash memory device) including a vertical memory array, digit lines (e.g., bit lines, data lines) are coupled to the strings of memory cells of the vertical memory array, and openings are provided next to edges of the vertical memory array to accommodate digit line contacts for each of the digit lines. The digit line contacts electrically connect the digit lines to logic circuitry to facilitate operations (e.g., read operations, program operations, erase operations) on the strings of memory cells of the vertical memory array. However, conventional configurations of digit lines and logic circuitry can hamper improvements in the performance (e.g., data transfer rates, power consumption) of the non-volatile memory device, and/or can impede reductions to the sizes (e.g., horizontal footprints) of features of the non-volatile memory device.

**BRIEF DESCRIPTION OF THE SEVERAL
VIEWS OF THE DRAWINGS**

FIG. 1A is simplified, partial perspective view of a microelectronic device structure for a microelectronic device, in accordance with embodiments of the disclosure.

2

FIG. 1B is simplified, partial cross-sectional view of the microelectronic device structure shown in FIG. 1A.

FIG. 1C is a schematic diagram of circuitry of the section of the microelectronic device structure shown in FIG. 1B.

FIG. 2A is simplified, partial schematic perspective view of a microelectronic device structure for a microelectronic device, in accordance with additional embodiments of the disclosure.

FIG. 2B is a schematic diagram of circuitry of a section of the microelectronic device structure shown in FIG. 2A.

FIG. 3 is a schematic block diagram of an electronic system, in accordance with embodiments of the disclosure.

DETAILED DESCRIPTION

The following description provides specific details, such as material compositions, shapes, and sizes, in order to provide a thorough description of embodiments of the disclosure. However, a person of ordinary skill in the art would understand that the embodiments of the disclosure may be practiced without employing these specific details. Indeed, the embodiments of the disclosure may be practiced in conjunction with conventional microelectronic device fabrication techniques employed in the industry. In addition, the description provided below does not form a complete process flow for manufacturing a microelectronic device (e.g., a memory device, such as 3D NAND Flash memory device). The structures described below do not form a complete microelectronic device. Only those process acts and structures necessary to understand the embodiments of the disclosure are described in detail below. Additional acts to form a complete microelectronic device from the structures may be performed by conventional fabrication techniques.

Drawings presented herein are for illustrative purposes only, and are not meant to be actual views of any particular material, component, structure, device, or system. Variations from the shapes depicted in the drawings as a result, for example, of manufacturing techniques and/or tolerances, are to be expected. Thus, embodiments described herein are not to be construed as being limited to the particular shapes or regions as illustrated, but include deviations in shapes that result, for example, from manufacturing. For example, a region illustrated or described as box-shaped may have rough and/or nonlinear features, and a region illustrated or described as round may include some rough and/or linear features. Moreover, sharp angles that are illustrated may be rounded, and vice versa. Thus, the regions illustrated in the figures are schematic in nature, and their shapes are not intended to illustrate the precise shape of a region and do not limit the scope of the present claims. The drawings are not necessarily to scale. Additionally, elements common between figures may retain the same numerical designation.

As used herein, a “memory device” means and includes microelectronic devices exhibiting memory functionality, but not necessary limited to memory functionality. Stated another way, and by way of non-limiting example only, the term “memory device” includes not only conventional memory (e.g., conventional non-volatile memory, such as conventional NAND memory; conventional volatile memory, such as conventional DRAM), but also includes an application specific integrated circuit (ASIC) (e.g., a system on a chip (SoC)), a microelectronic device combining logic and memory, and a graphics processing unit (GPU) incorporating memory.

As used herein, the term “configured” refers to a size, shape, material composition, orientation, and arrangement

of one or more of at least one structure and at least one apparatus facilitating operation of one or more of the structure and the apparatus in a pre-determined way.

As used herein, the terms “vertical,” “longitudinal,” “horizontal,” and “lateral” are in reference to a major plane of a structure and are not necessarily defined by earth’s gravitational field. A “horizontal” or “lateral” direction is a direction that is substantially parallel to the major plane of the structure, while a “vertical” or “longitudinal” direction is a direction that is substantially perpendicular to the major plane of the structure. The major plane of the structure is defined by a surface of the structure having a relatively large area compared to other surfaces of the structure. With reference to the figures, a “horizontal” or “lateral” direction may be perpendicular to an indicated “Z” axis, and may be parallel to an indicated “X” axis and/or parallel to an indicated “Y” axis; and a “vertical” or “longitudinal” direction may be parallel to an indicated “Z” axis, may be perpendicular to an indicated “X” axis, and may be perpendicular to an indicated “Y” axis.

As used herein, features (e.g., regions, structures, devices) described as “neighboring” one another means and includes features of the disclosed identity (or identities) that are located most proximate (e.g., closest to) one another. Additional features (e.g., additional regions, additional structures, additional devices) not matching the disclosed identity (or identities) of the “neighboring” features may be disposed between the “neighboring” features. Put another way, the “neighboring” features may be positioned directly adjacent one another, such that no other feature intervenes between the “neighboring” features; or the “neighboring” features may be positioned indirectly adjacent one another, such that at least one feature having an identity other than that associated with at least one of the “neighboring” features is positioned between the “neighboring” features. Accordingly, features described as “vertically neighboring” one another means and includes features of the disclosed identity (or identities) that are located most vertically proximate (e.g., vertically closest to) one another. Moreover, features described as “horizontally neighboring” one another means and includes features of the disclosed identity (or identities) that are located most horizontally proximate (e.g., horizontally closest to) one another.

As used herein, the term “intersection” means and includes a location at which two or more features (e.g., regions, structures, materials, devices) or, alternatively, two or more portions of a single feature meet. For example, an intersection between a first feature extending in a first direction (e.g., an X-direction) and a second feature extending in a second direction (e.g., a Y-direction) different than the first direction may be the location at which the first feature and the second feature meet.

As used herein, spatially relative terms, such as “beneath,” “below,” “lower,” “bottom,” “above,” “upper,” “top,” “front,” “rear,” “left,” “right,” and the like, may be used for ease of description to describe one element’s or feature’s relationship to another element(s) or feature(s) as illustrated in the figures. Unless otherwise specified, the spatially relative terms are intended to encompass different orientations of the materials in addition to the orientation depicted in the figures. For example, if materials in the figures are inverted, elements described as “below” or “beneath” or “under” or “on bottom of” other elements or features would then be oriented “above” or “on top of” the other elements or features. Thus, the term “below” can encompass both an orientation of above and below, depending on the context in which the term is used, which will be

evident to one of ordinary skill in the art. The materials may be otherwise oriented (e.g., rotated 90 degrees, inverted, flipped) and the spatially relative descriptors used herein interpreted accordingly.

As used herein, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise.

As used herein, “and/or” includes any and all combinations of one or more of the associated listed items.

As used herein, the phrase “coupled to” refers to structures operatively connected with each other, such as electrically connected through a direct Ohmic connection or through an indirect connection (e.g., by way of another structure).

As used herein, the term “substantially” in reference to a given parameter, property, or condition means and includes to a degree that one of ordinary skill in the art would understand that the given parameter, property, or condition is met with a degree of variance, such as within acceptable tolerances. By way of example, depending on the particular parameter, property, or condition that is substantially met, the parameter, property, or condition may be at least 90.0 percent met, at least 95.0 percent met, at least 99.0 percent met, at least 99.9 percent met, or even 100.0 percent met.

As used herein, “about” or “approximately” in reference to a numerical value for a particular parameter is inclusive of the numerical value and a degree of variance from the numerical value that one of ordinary skill in the art would understand is within acceptable tolerances for the particular parameter. For example, “about” or “approximately” in reference to a numerical value may include additional numerical values within a range of from 90.0 percent to 110.0 percent of the numerical value, such as within a range of from 95.0 percent to 105.0 percent of the numerical value, within a range of from 97.5 percent to 102.5 percent of the numerical value, within a range of from 99.0 percent to 101.0 percent of the numerical value, within a range of from 99.5 percent to 100.5 percent of the numerical value, or within a range of from 99.9 percent to 100.1 percent of the numerical value.

As used herein, “conductive material” means and includes electrically conductive material such as one or more of a metal (e.g., tungsten (W), titanium (Ti), molybdenum (Mo), niobium (Nb), vanadium (V), hafnium (Hf), tantalum (Ta), chromium (Cr), zirconium (Zr), iron (Fe), ruthenium (Ru), osmium (Os), cobalt (Co), rhodium (Rh), iridium (Ir), nickel (Ni), palladium (Pd), platinum (Pt), copper (Cu), silver (Ag), gold (Au), aluminum (Al)), an alloy (e.g., a Co-based alloy, an Fe-based alloy, an Ni-based alloy, an Fe- and Ni-based alloy, a Co- and Ni-based alloy, an Fe- and Co-based alloy, a Co- and Ni- and Fe-based alloy, an Al-based alloy, a Cu-based alloy, a magnesium (Mg)-based alloy, a Ti-based alloy, a steel, a low-carbon steel, a stainless steel), a conductive metal-containing material (e.g., a conductive metal nitride, a conductive metal silicide, a conductive metal carbide, a conductive metal oxide), and a conductively-doped semiconductor material (e.g., conductively-doped polysilicon, conductively-doped germanium (Ge), conductively-doped silicon germanium (SiGe)). In addition, a “conductive structure” means and includes a structure formed of and including conductive material.

As used herein, “insulative material” means and includes electrically insulative material, such one or more of at least one dielectric oxide material (e.g., one or more of a silicon oxide (SiO_x), phosphosilicate glass, borosilicate glass, borophosphosilicate glass, fluorosilicate glass, an aluminum oxide (AlO_x), a hafnium oxide (HfO_x), a niobium oxide

(NbO_x), a titanium oxide (TiO_x), a zirconium oxide (ZrO_x), a tantalum oxide (TaO_x), and a magnesium oxide (MgO_x), at least one dielectric nitride material (e.g., a silicon nitride (SiN_y)), at least one dielectric oxynitride material (e.g., a silicon oxynitride (SiO_xN_y)), at least one dielectric oxycarbide material (e.g., silicon oxycarbide (SiO_xC_y)), at least one hydrogenated dielectric oxycarbide material (e.g., hydrogenated silicon oxycarbide ($\text{SiC}_x\text{O}_y\text{H}_z$)), and at least one dielectric carboxynitride material (e.g., a silicon carboxynitride ($\text{SiO}_x\text{C}_z\text{N}_y$)). Formulae including one or more of “x,” “y,” and “z” herein (e.g., SiO_x , AlO_x , HfO_x , NbO_x , TiO_x , SiN_y , SiO_xN_y , SiO_xC_y , $\text{SiC}_x\text{O}_y\text{H}_z$, $\text{SiO}_x\text{C}_z\text{N}_y$) represent a material that contains an average ratio of “x” atoms of one element, “y” atoms of another element, and “z” atoms of an additional element (if any) for every one atom of another element (e.g., Si, Al, Hf, Nb, Ti). As the formulae are representative of relative atomic ratios and not strict chemical structure, an insulative material may comprise one or more stoichiometric compounds and/or one or more non-stoichiometric compounds, and values of “x,” “y,” and “z” (if any) may be integers or may be non-integers. As used herein, the term “non-stoichiometric compound” means and includes a chemical compound with an elemental composition that cannot be represented by a ratio of well-defined natural numbers and is in violation of the law of definite proportions. In addition, an “insulative structure” means and includes a structure formed of and including insulative material.

As used herein, the term “homogeneous” means relative amounts of elements included in a feature (e.g., a region, a structure, a material) do not vary throughout different portions (e.g., different horizontal portions, different vertical portions) of the feature. Conversely, as used herein, the term “heterogeneous” means relative amounts of elements included in a feature (e.g., a material, a structure) vary throughout different portions of the feature. If a feature is heterogeneous, amounts of one or more elements included in the feature may vary stepwise (e.g., change abruptly), or may vary continuously (e.g., change progressively, such as linearly, parabolically) throughout different portions of the feature. The feature may, for example, be formed of and include a stack of at least two different materials.

Unless the context indicates otherwise, the materials described herein may be formed by any suitable technique including, but not limited to, spin coating, blanket coating, chemical vapor deposition (CVD), plasma enhanced CVD (PECVD), atomic layer deposition (ALD), plasma enhanced ALD (PEALD), physical vapor deposition (PVD) (e.g., sputtering), or epitaxial growth. Depending on the specific material to be formed, the technique for depositing or growing the material may be selected by a person of ordinary skill in the art. In addition, unless the context indicates otherwise, removal of materials described herein may be accomplished by any suitable technique including, but not limited to, etching (e.g., dry etching, wet etching, vapor etching), ion milling, abrasive planarization (e.g., chemical-mechanical planarization (CMP)), or other known methods.

FIG. 1A is a simplified, partial perspective view of a microelectronic device structure **100** (e.g., a memory device structure, such as a 3D NAND Flash memory device structure) for a microelectronic device (e.g., a memory device, such as a 3D NAND Flash memory device), in accordance with embodiments of the disclosure. FIG. 1B is simplified, partial cross-sectional view of the microelectronic device structure **100** about dashed line A-A depicted in FIG. 1A. FIG. 1C is a schematic diagram of circuitry of the section of

the microelectronic device structure **100** shown in FIG. 1B. For clarity and ease of understanding of the drawings and related description, not all features (e.g., regions, structures, materials, devices) of the microelectronic device structure **100** depicted in one or more of FIGS. 1A through 1C are depicted in one of more others of FIGS. 1A through 1C. With the description provided below, it will be readily apparent to one of ordinary skill in the art that the structures and devices described herein may be included in relatively larger structures, devices, and systems.

Referring collectively to FIGS. 1A and 1B, the microelectronic device structure **100** may be formed to include a source tier **101**; a stack structure **104** vertically overlying (e.g., in the Z-direction) the source tier **101**; a local digit line tier **126** vertically overlying the stack structure **104**; a global digit line tier **134** vertically overlying the local digit line tier **126**; a read/write electrode tier **138** vertically interposed between the local digit line tier **126** and the global digit line tier **134**; a source line tier **144** vertically interposed between the local digit line tier **126** and the read/write electrode tier **138**; and a routing tier **148** vertical interposed between the source line tier **144** and the read/write electrode tier **138**. As described in further detail below, the microelectronic device structure **100** includes various features (e.g., regions, structures, materials, devices) individually operatively associated with (e.g., within; extending to, into, through, and/or between; physically and/or electrically connected to additional features of) one or more of the source tier **101**, the stack structure **104**, the local digit line tier **126**, the global digit line tier **134**, the read/write electrode tier **138**, the source line tier **144**, and the routing tier **148**.

The source tier **101** may include at least one source structure **102** (e.g., a source plate) at least partially positioned with a horizontal area of the stack structure **104** vertically overlying the source tier **101**. The source structure **102** may be formed and include conductive material, such as one or more of a metal, an alloy, and a conductive metal-containing material (e.g., a conductive metal nitride, a conductive metal silicide, a conductive metal carbide, a conductive metal oxide). As a non-limiting example, the source structure **102** may be formed of and include W.

The stack structure **104** of the microelectronic device structure **100** may be formed to include a vertically alternating (e.g., in the Z-direction) sequence of conductive structures **106** and insulative structures **108** arranged in tiers **110**. The conductive structures **106** may be vertically interleaved with the insulative structures **108**. Each of the tiers **110** of the stack structure **104** may include at least one of the conductive structures **106** vertically neighboring at least one of the insulative structures **108**. The stack structure **104** may be formed to include any desired number of the tiers **110**, such as greater than or equal to sixteen (16) of the tiers **110**, greater than or equal to thirty-two (32) of the tiers **110**, greater than or equal to sixty-four (64) of the tiers **110**, greater than or equal to one hundred and twenty-eight (128) of the tiers **110**, or greater than or equal to two hundred and fifty-six (256) of the tiers **110**.

The conductive structures **106** of the tiers **110** of the stack structure **104** may be formed of and include conductive material. By way of non-limiting example, the conductive structures **106** may each individually be formed of and include a metallic material comprising one or more of at least one metal, at least one alloy, and at least one conductive metal-containing material (e.g., a conductive metal nitride, a conductive metal silicide, a conductive metal carbide, a conductive metal oxide). In some embodiments, the conductive structures **106** are formed of and include W. Each of

the conductive structures **106** may individually be substantially homogeneous, or one or more of the conductive structures **106** may individually be substantially heterogeneous. In some embodiments, each of the conductive structures **106** is formed to be substantially homogeneous.

Optionally, one or more liner material(s) (e.g., insulative liner material(s), conductive wirer material(s)) may also be formed around the conductive structures **106**. The liner material(s) may, for example, be formed of and include one or more a metal (e.g., titanium, tantalum), an alloy, a metal nitride (e.g., tungsten nitride, titanium nitride, tantalum nitride), and a metal oxide (e.g., aluminum oxide). In some embodiments, the liner material(s) comprise at least one conductive material employed as a seed material for the formation of the conductive structures **106**. In some embodiments, the liner material(s) comprise titanium nitride. In further embodiments, the liner material(s) further include aluminum oxide. As a non-limiting example, aluminum oxide may be formed directly adjacent the insulative structures **108**, titanium nitride may be formed directly adjacent the aluminum oxide, and tungsten may be formed directly adjacent the titanium nitride. For clarity and ease of understanding the description, the liner material(s) are not illustrated in FIGS. **1A** and **1B**, but it will be understood that the liner material(s) may be disposed around the conductive structures **106**.

The insulative structures **108** of the tiers **110** of the stack structure **104** may be formed of and include insulative material, such one or more of at least one dielectric oxide material (e.g., one or more of SiO_x , phosphosilicate glass, borosilicate glass, borophosphosilicate glass, fluorosilicate glass, AlO_x , HfO_x , NbO_x , TiO_x , ZrO_x , TaO_x , and MgO_x), at least one dielectric nitride material (e.g., SiN_y), at least one dielectric oxynitride material (e.g., SiO_xN_y), and at least one dielectric carboxynitride material (e.g., $\text{SiO}_x\text{C}_z\text{N}_y$). In some embodiments, each of the insulative structures **108** is formed of and includes a dielectric oxide material, such as SiO_x (e.g., SiO_2). Each of the insulative structures **108** may individually be substantially homogeneous, may be substantially heterogeneous. In some embodiments, each of the insulative structures **108** is substantially homogeneous.

As shown in FIGS. **1A** and **1B**, the tiers **110** of the stack structure **104** may be sub-divided into access line tiers **112**, at least one select gate tier **114** (e.g., a lower select gate tier), and at least one additional select gate tier **116** (e.g., an upper select gate tier). The access line tiers **112** may be vertically interposed between the select gate tier **114** and the additional select gate tier **116**. At least some of the conductive structures **106** within the access line tiers **112** may be employed as local access line structures (e.g., local word line structures) for the microelectronic device structure **100**. At least one of the conductive structures **106** within the select gate tier **114** may employed as at least one first select gate structure (e.g., at least one source side select gate (SGS) structure) for the microelectronic device structure **100**. At least one of the conductive structures **106** within the additional select gate tier **116** may employed as at least one second select gate structure (e.g., at least one drain side select gate (SGD) structure) for the microelectronic device structure **100**. In some embodiments, horizontally neighboring (e.g., in the X-direction) conductive structures **106** within the additional select gate tier **116** are employed as additional select gate structures (e.g., SGD structures) for the microelectronic device structure **100**.

As depicted in FIGS. **1A** and **1B**, in some embodiments the stack structure **104** includes four (4) access line tiers **112** (e.g., a first access line tier **112A**, a second access line tier

112B, a third access line tier **112C**, and a fourth access line tier **112D**), one select gate tier **114**, and one additional select gate tier **116**. However, the stack structure **104** may be formed to include a different quantity of access line tiers **112** (e.g., greater than four (4) access line tiers **112**), a different quantity of select gate tiers **114** (e.g., greater than one select gate tier **114**, such as two or more select gate tiers **114**), and/or a different quantity of additional select gate tiers **116** (e.g., greater than one additional select gate tier **116**, such as two or more additional select gate tiers **116**, three or more additional select gate tiers **116**, or four or more additional select gate tiers **116**).

Referring to FIG. **1B**, the first pillar structures **118** may vertically extend through the tiers **110** of the stack structure **104**. The first pillar structures **118** may each individually be formed of and include a stack of materials. By way of non-limiting example, each of the first pillar structures **118** may be formed to include a charge-blocking material, such as first dielectric oxide material (e.g., SiO_x , such as SiO_2 ; AlO_x , such as Al_2O_3); a charge-trapping material, such as a dielectric nitride material (e.g., SiN_y , such as Si_3N_4); a tunnel dielectric material, such as a second dielectric oxide material (e.g., SiO_x , such as SiO_2); a channel material, such as a semiconductor material (e.g., silicon, such as polycrystalline silicon); and a dielectric fill material (e.g., a dielectric oxide, a dielectric nitride, air). The charge-blocking material may be formed on or over surfaces of the conductive structures **106** and the insulative structures **108** of the tiers **110** of stack structure **104** at least partially defining horizontal boundaries of the first pillar structures **118**; the charge-trapping material may be horizontally surrounded by the charge-blocking material; the tunnel dielectric material may be horizontally surrounded by the charge-trapping material; the channel material may be horizontally surrounded by the tunnel dielectric material; and the dielectric fill material may be horizontally surrounded by the channel material.

Intersections of the first pillar structures **118** and the conductive structures **106** within the access line tiers **112** of the stack structure **104** may define vertically extending strings of memory cells **120** coupled in series with one another within the stack structure **104**. In some embodiments, the memory cells **120** formed at the intersections of the conductive structures **106** and the first pillar structures **118** within access line tiers **112** of the stack structure **104** comprise so-called "MONOS" (metal-oxide-nitride-oxide-semiconductor) memory cells. In additional embodiments, the memory cells **120** comprise so-called "TANOS" (tantalum nitride-aluminum oxide-nitride-oxide-semiconductor) memory cells, or so-called "BETANOS" (band/barrier engineered TANOS) memory cells, each of which are subsets of MONOS memory cells. In further embodiments, the memory cells **120** comprise so-called "floating gate" memory cells including floating gates (e.g., metallic floating gates) as charge storage structures. The floating gates may horizontally intervene between central structures of the first pillar structures **118** and the conductive structures **106** of the different access line tiers **112** of the stack structure **104**. The vertically extending strings of memory cells **120** together form at least one memory array within the stack structure **104**.

Still referring to FIG. **1B**, intersections of the first pillar structures **118** and the conductive structures **106** within the select gate tier **114** of the stack structure **104** may define select transistors **122** coupled in series with the vertically extending strings of memory cells **120**. Portions of the first pillar structures **118** within vertical boundaries of the select

gate tier **114** of the stack structure **104** may include the tunnel dielectric material (e.g., SiO_x , such as SiO_2), the channel material (e.g., silicon, such as polycrystalline silicon), and the dielectric fill (e.g., SiO_x , such as SiO_2 ; SiN_y , such as Si_3N_4 ; air), but may be at least partially (e.g., substantially) free of the charge-blocking material and the charge-trapping material present within additional portions of the first pillar structures **118** within vertical boundaries of the access line tiers **112** of the stack structure **104**. In some embodiments, the select transistors **122** comprise metal-oxide-semiconductor (MOS) transistors. If the conductive structures **106** within the select gate tier **114** of the stack structure **104** are employed as SGS structures for the microelectronic device structure **100**, the select transistors **122** may comprise MOS-SGS transistors.

In addition, intersections of the first pillar structures **118** and the conductive structures **106** within the additional select gate tier **116** of the stack structure **104** may define additional select transistors **124** coupled in series with the vertically extending strings of memory cells **120**. Further portions of the first pillar structures **118** within vertical boundaries of the additional select gate tier **116** of the stack structure **104** may include the tunnel dielectric material (e.g., SiO_x , such as SiO_2), the channel material (e.g., silicon, such as polycrystalline silicon), and the dielectric fill (e.g., SiO_x , such as SiO_2 ; SiN_y , such as Si_3N_4 ; air), but may be at least partially (e.g., substantially) free of the charge-blocking material and the charge-trapping material included within the additional portions of the first pillar structures **118** within the vertical boundaries of the access line tiers **112** of the stack structure **104**. In some embodiments, the additional select transistors **124** comprise MOS transistors. If the conductive structures **106** within the additional select gate tier **116** of the stack structure **104** are employed as SGD structures for the microelectronic device structure **100**, the additional select transistors **124** may comprise MOS-SGD transistors.

Collectively referring to FIGS. **1A** and **1B**, the local digit line tier **126** may include multiple (e.g., more than one, a plurality of) local digit line structures **128**. The local digit line structures **128** may vertically overlie the first pillar structures **118** (FIG. **1B**), and may individually horizontally extend in the X-direction (e.g., a first horizontal direction). The local digit line tier **126** may include rows of the local digit line structures **128** extending in the X-direction, and columns of the local digit line structures **128** extending in the Y-direction (e.g., a second horizontal direction) orthogonal to the X-direction. A group of the local digit line structures **128** provided within an individual row of the local digit line structures **128** may be substantially horizontally aligned with one another in the Y-direction, may be horizontally separated from one another in the X-direction, and may horizontally extend in series with one another in the X-direction. As described in further detail below, those local digit line structures **128** provided within the same row of the local digit line structures **128** as one another may be operatively associated with the same global digit line structure as one another. In addition, a group of the local digit line structures **128** provided within an individual column of the local digit line structures **128** may be substantially horizontally aligned with one another in the X-direction, may be horizontally separated from one another in the Y-direction, and may extend in parallel with one another in the X-direction. By way of non-limiting example, as depicted in FIG. **1A**, an individual column of the local digit line structures **128** may include a first local digit line structure **128A** and a second local digit line structure **128B** spaced apart from the

first local digit line structure **128A**. As described in further detail below, those local digit line structures **128** provided within the same column of the local digit line structures **128** as one another may be operatively associated with the different global digit line structures than one another.

The local digit line structures **128** may each individually be formed of and include conductive material. By way of non-limiting example, the local digit line structures **128** may each individually be formed of and include one or more of at least one metal, at least one alloy, and at least one conductive metal-containing material (e.g., a conductive metal nitride, a conductive metal silicide, a conductive metal carbide, a conductive metal oxide). In some embodiments, the local digit line structures **128** are each individually formed of and include one or more of W, Ru, Mo, and titanium nitride (TiN_y). Each of the local digit line structures **128** may individually be substantially homogeneous, or one or more of the local digit line structures **128** may individually be substantially heterogeneous. In some embodiments, each of the local digit line structures **128** are formed to be substantially homogeneous.

Still referring to FIGS. **1A** and **1B**, the microelectronic device structure **100** further includes first conductive contact structures **132** vertically intervening between and electrically connecting at least some of the local digit line structures **128** and at least some of first pillar structures **118** (FIG. **1B**). The first conductive contact structures **132** may each individually be formed of and include conductive material. By way of non-limiting example, the first conductive contact structures **132** may each individually be formed of and include one or more of at least one metal, at least one alloy, and at least one conductive metal-containing material (e.g., a conductive metal nitride, a conductive metal silicide, a conductive metal carbide, a conductive metal oxide). In some embodiments, the first conductive contact structures **132** are each individually formed of and include one or more of W, Ru, Mo, and TiN_y .

The global digit line tier **134** may include multiple (e.g., more than one, a plurality of) global digit line structures **136**. The global digit line structures **136** may vertically overlie the local digit line structures **128**, and may individually horizontally extend in the X-direction. The global digit line structures **136** may be horizontally separated from one another in the Y-direction, and may extend in parallel with one another in the X-direction. As non-limiting example, as depicted in FIG. **1A**, the global digit line tier **134** may include a first global digit line structure **136A** and a second global digit line structure **136B** spaced apart from the first global digit line structure **136A**. Different global digit line structures **136** may be operatively associated with different local digit line structures **128** than one another. Each of the global digit line structures **136** may be operatively associated with an individual row of the local digit line structures **128**, with different global digit line structures **136** (e.g., the first global digit line structure **136A**, the second global digit line structure **136B**) operatively associated with different rows of the local digit line structures **128** than one another. For example, the first global digit line structure **136A** may be operatively associated with the first local digit line structure **128A** and at least one additional local digit line structure **128** within the same row (e.g., a first row) of the local digit line structures **128** as the first local digit line structure **128A**; and the second global digit line structure **136B** (FIG. **1A**) may be operatively associated with the second local digit line structure **128B** (FIG. **1A**) and at least one further local digit line structure **128** within the same row (e.g., a second row) of the local digit line structures **128** as

the second local digit line structure **128B**. In addition, each column the local digit line structures **128** may be operatively associated with multiple global digit line structures **136**. For example, the first local digit line structure **128A** and the second local digit line structure **128B** within the same column (e.g., a first column) of the local digit line structures **128** as one another may be operatively associated with the first global digit line structure **136A** and the second global digit line structure **136B**, respectively. The global digit line structures **136** may be operatively associated with the local digit line structures **128**, at least in part, by way of additional features of the microelectronic device structure **100** individually operatively associated with one or more of the read/write electrode tier **138**, the source line tier **144**, and the routing tier **148**, as described in further detail below. Horizontal dimensions (e.g., lengths) in the X-direction of the global digit line structures **136** may be greater than (e.g., longer than) horizontal dimensions (e.g., lengths) in the X-direction of the local digit line structures **128** operatively associated therewith.

The global digit line structures **136** may each individually be formed of and include conductive material. By way of non-limiting example, the global digit line structures **136** may each individually be formed of and include one or more of at least one metal, at least one alloy, and at least one conductive metal-containing material (e.g., a conductive metal nitride, a conductive metal silicide, a conductive metal carbide, a conductive metal oxide). In some embodiments, the global digit line structures **136** are each individually formed of and include one or more of W, Ru, Mo, and TiN. Each of the global digit line structures **136** may individually be substantially homogeneous, or one or more of the global digit line structures **136** may individually be substantially heterogeneous. In some embodiments, each of the global digit line structures **136** is formed to be substantially homogeneous.

The global digit line structures **136** may be coupled to logic circuitry (e.g., page buffer circuitry) of a microelectronic device including the microelectronic device structure **100**. The logic circuitry may, for example, be included within a base structure vertically underlying the microelectronic device structure **100**. In some embodiments, the global digit line structures **136** are coupled to page buffer devices each individually including an arrangement of data cache circuitry (e.g., dynamic data cache (DDC) circuitry, primary data cache (PDC) circuitry, secondary data cache (SDC) circuitry, temporary data cache (TDC) circuitry), sense amplifier (SA) circuitry, and digit line pre-charge circuitry. Optionally, isolation devices (e.g., isolation transistors) may be interposed between the global digit line structures **136** and the page buffer devices at desirable locations along conductive paths extending from and between the global digit line structures **136** and the page buffer devices. In some embodiments, the isolation devices comprise high-voltage-isolation (HVISO) transistors configured and operated to pass voltages greater than or equal to about 18V, such as within a range of from about 18V to about 25V. In additional embodiments, the isolation devices comprise low-voltage-isolation (LVISO) transistors configured and operated to substantially block applied voltages less than about 18 V while in an OFF state (e.g., an inactive state, a depletion state, a deselected state).

Still referring to FIGS. **1A** and **1B**, the read/write electrode tier **138** may include read electrode structures **140** and write electrode structures **142**. The read electrode structures **140** and the write electrode structures **142** may vertically interposed between the local digit line structures **128** and the

global digit line structures **136**, and may individually horizontally extend the Y-direction orthogonal to the X-direction in which the local digit line structures **128** and the global digit line structures **136** horizontally extend. Each of the local digit line structures **128** may be operatively associated with one of the read electrode structures **140** and one of the write electrode structures **142**, as described in further detail below. In addition, each of the global digit line structures **136** may be operatively associated multiple (e.g., more than one) of the read electrode structures **140** and multiple (e.g., more than one) of the write electrode structures **142**, as also described in further detail below.

The read electrode structures **140** are spaced apart from the write electrode structures **142** in the X-direction, and may horizontally extend in parallel with one another and the write electrode structures **142** in the Y-direction. As described in further detail below, the read electrode structures **140** may be employed as gate structures for switching transistors (e.g., read transistors) of the microelectronic device structure **100**. Each of the read electrode structures **140** may be operatively associated with a group of the local digit line structures **128** within an individual column of the local digit line structures **128**. For example, as shown in FIG. **1A**, the first local digit line structure **128A** and the second local digit line structure **128B** within the same column of the local digit line structures **128** as one another may each be operatively associated with a single (e.g., only one) read electrode structure **140** of the read/write electrode tier **138**. Different groups of the local digit line structures **128** within different columns of the local digit line structures **128** than one another may be operatively associated with different read electrode structures **140** than one another. In addition, each of the read electrode structures **140** may be operatively associated with multiple (e.g., more than one) of the global digit line structures **136**. For example, as shown in FIG. **1A**, an individual read electrode structure **140** may be operatively associated with each of the first global digit line structure **136A** and the second global digit line structure **136B**. Moreover, each of the global digit line structures **136** may be operatively associated with multiple (e.g., more than one) read electrode structures **140** of the read/write electrode tier **138**. For example, the first global digit line structure **136A** and the second global digit line structure **136B** may each be operatively associated with more than one of the read electrode structures **140** (e.g., the read electrode structure **140** shown in FIG. **1A**, and at least one additional read electrode structure **140** operatively associated with at least one additional column of the local digit line structures **128**).

Still referring to FIG. **1A**, the write electrode structures **142** may horizontally alternate with the read electrode structures **140** in the X-direction. As described in further detail below, the write electrode structures **142** may be employed as gate structures for additional switching transistors (e.g., write transistors) of the microelectronic device structure **100**. Each of the write electrode structures **142** may be operatively associated with a group of the local digit line structures **128** within an individual column of the local digit line structures **128**. Each column of the local digit line structures **128** may be operatively associated with a single (e.g., only one) write electrode structure **142** and a single read electrode structure **140** horizontally neighboring (e.g., in the X-direction) the single write electrode structure **142**. For example, the first local digit line structure **128A** and the second local digit line structure **128B** within the same column of the local digit line structures **128** as one another may each be operatively associated with a single write electrode structure **142** of the read/write electrode tier **138**.

13

Different groups of the local digit line structures **128** within different columns of the local digit line structures **128** than one another may be operatively associated with different write electrode structures **142** than one another. In addition, each of the write electrode structures **142** may be operatively associated with multiple (e.g., more than one) of the global digit line structures **136**. For example, as shown in FIG. 1A, an individual write electrode structure **142** may be operatively associated with each of the first global digit line structure **136A** and the second global digit line structure **136B**. Moreover, each of the global digit line structures **136** may be operatively associated with multiple (e.g., more than one) write electrode structures **142** of the read/write electrode tier **138**. For example, the first global digit line structure **136A** and the second global digit line structure **136B** may each be operatively associated with more than one of the write electrode structures **142** (e.g., the write electrode structure **142** shown in FIG. 1A, and at least one additional write electrode structure **142** operatively associated with at least one additional column of the local digit line structures **128**).

The read electrode structures **140** and the write electrode structures **142** may each individually be formed of and include conductive material. By way of non-limiting example, the read electrode structures **140** and the write electrode structures **142** may each individually be formed of and include one or more of at least one metal, at least one alloy, and at least one conductive metal-containing material (e.g., a conductive metal nitride, a conductive metal silicide, a conductive metal carbide, a conductive metal oxide). In some embodiments, the read electrode structures **140** and the write electrode structures **142** are each individually formed of and include one or more of W, Ru, Mo, and TiN_y. Each of the read electrode structures **140** and the write electrode structures **142** may individually be substantially homogeneous, or one or more of the read electrode structures **140** and/or one or more of the write electrode structures **142** may individually be substantially heterogeneous. In some embodiments, each of the read electrode structures **140** and each of the write electrode structures **142** is formed to be substantially homogeneous.

Referring collectively to FIGS. 1A and 1B, the source line tier **144** includes source line structures **146**. The source line structures **146** may vertically interposed between the local digit line structures **128** of the local digit line tier **126** and the read electrode structures **140** of the read/write electrode tier **138**. The source line structures **146** may individually horizontally extend the Y-direction orthogonal to the X-direction in which the local digit line structures **128** and the global digit line structures **136** horizontally extend. As described in further detail below, each of the local digit line structures **128** may individually be operatively associated with one of the source line structures **146**, and each of the read electrode structures **140** may individually be operatively associated with one of the source line structures **146**. In addition, as also described in further detail below, each of the global digit line structures **136** may individually be operatively associated multiple (e.g., more than one) of the source line structures **146**.

As shown in FIG. 1A, each of the source line structures **146** may individually be operatively associated with one of the read electrode structures **140** and a group of the local digit line structures **128** within an individual column of the local digit line structures **128**. For example, the first local digit line structure **128A** and the second local digit line structure **128B** within the same column of the local digit line structures **128** as one another, and a single (e.g., only one)

14

read electrode structure **140** operatively associated therewith, may each be operatively associated with a single (e.g., only one) source line structure **146** of the source line tier **144**. Different groups of the local digit line structures **128** within different columns of the local digit line structures **128** than one another, and different read electrode structures **140** operatively associated with the different columns of the local digit line structures **128**, may be operatively associated with different source line structures **146** than one another. In addition, each of the source line structures **146** may be operatively associated with multiple (e.g., more than one) of the global digit line structures **136**. For example, as shown in FIG. 1A, an individual source line structure **146** may be operatively associated with each of the first global digit line structure **136A** and the second global digit line structure **136B**. Moreover, each of the global digit line structures **136** may be operatively associated with multiple (e.g., more than one) source line structures **146** of the source line tier **144**. For example, the first global digit line structure **136A** and the second global digit line structure **136B** may each be operatively associated with more than one of the source line structures **146** (e.g., the source line structure **146** shown in FIG. 1A, and at least one additional source line structure **146** operatively associated with at least one additional column of the local digit line structures **128**).

The source line structures **146** may each individually be formed of and include conductive material. By way of non-limiting example, the source line structures **146** may each individually be formed of and include one or more of at least one metal, at least one alloy, and at least one conductive metal-containing material (e.g., a conductive metal nitride, a conductive metal silicide, a conductive metal carbide, a conductive metal oxide). In some embodiments, the source line structures **146** are each individually formed of and include one or more of W, Ru, Mo, and TiN_y. Each of the source line structures **146** may individually be substantially homogeneous, or one or more of the source line structures **146** may individually be substantially heterogeneous. In some embodiments, each of the source line structures **146** is formed to be substantially homogeneous.

Referring to FIGS. 1A and 1B, the routing tier **148** includes routing structures **150**. The routing structures **150** may be vertically interposed between the source line structures **146** of the source line tier **144** and the read electrode structures **140** of the read/write electrode tier **138**. The routing structures **150** may individually horizontally extend the X-direction. As described in further detail below, each of the routing structures **150** may be operatively associated with one of the local digit line structures **128**, one of the source line structures **146**, one of the read electrode structures **140**, and one of the global digit line structures **136**. In addition, as also described in further detail below, each of the global digit line structures **136** may be operatively associated multiple (e.g., more than one, a plurality) of the routing structures **150**.

As shown in FIG. 1A, each of the routing structures **150** may individually be operatively associated with one of the local digit line structures **128**. For example, the first local digit line structure **128A** may be operatively associated with one of the routing structures **150**, and the second local digit line structure **128B** may be operatively associated with another one of the routing structures **150**. The routing structures **150** may be coupled to the local digit line structures **128**. As described in further detail below, routing structures **150** may be employed as gate structures for sense transistors interposed between and operatively associated with the source line structures **146** and the read electrode

structures 140. Different groups of the local digit line structures 128 within different columns of the local digit line structures 128, and different read electrode structures 140 operatively associated with the different columns of the local digit line structures 128, may be operatively associated with different groups of the routing structures 150 than one another. In addition, each of the routing structures 150 may individually be operatively associated with one of the global digit line structures 136. For example, as shown in FIG. 1A, the first global digit line structure 136A may be operatively associated with one of the routing structures 150 operatively associated with the first local digit line structure 128A; and the second global digit line structure 136B may be operatively associated with another one of the routing structures 150 operatively associated with the second local digit line structure 128B. Moreover, each of the global digit line structures 136 may be operatively associated with multiple (e.g., more than one) routing structures 150 of the routing tier 148. For example, the first global digit line structure 136A may be operatively associated with different routing structures 150 operatively associated with different local digit line structures 128 within an individual row of the local digit line structures 128 extending in the X-direction; and the second global digit line structure 136B may be operatively associated with other different routing structures 150 operatively associated with other different local digit line structures 128 within another individual row of the local digit line structures 128 extending in the X-direction.

The routing structures 150 may each individually be formed of and include conductive material. By way of non-limiting example, the routing structures 150 may each individually be formed of and include one or more of at least one metal, at least one alloy, and at least one conductive metal-containing material (e.g., a conductive metal nitride, a conductive metal silicide, a conductive metal carbide, a conductive metal oxide). In some embodiments, the routing structures 150 are each individually formed of and include one or more of W, Ru, Mo, and TiN_x. Each of the routing structures 150 may individually be substantially homogeneous, or one or more of the routing structures 150 may individually be substantially heterogeneous. In some embodiments, each of the routing structures 150 is formed to be substantially homogeneous.

Still referring to FIGS. 1A and 1B, the microelectronic device structure 100 further includes second pillar structures 152 operatively associated with the local digit line structures 128, the source line structures 146, the routing structures 150, the read electrode structures 140, and the global digit line structures 136. The second pillar structures 152 may individually vertically extend from one of the global digit line structures 136 (e.g., the first global digit line structure 136A, the second global digit line structure 136B), through each of one of the read electrode structures 140 and one of the routing structures 150, and at least to (e.g., to, into, beyond) one of the source line structures 146.

The second pillar structures 152 may at least be formed of and include semiconductor material (e.g., silicon, such as polycrystalline silicon; an oxide semiconductor material). One or more vertical regions of the semiconductor material of the second pillar structures 152 may be doped, or the semiconductor material of the second pillar structures 152 may be substantially undoped. If doped, the semiconductor material of the second pillar structures 152 may be doped with one or more conductivity-enhancing species (e.g., one or more N-type dopants, such as one or more of phosphorus, arsenic, antimony, and bismuth; one or more P-type dopants, such as one or more of boron, aluminum, and gallium)

facilitating desired vertical transistors at intersections of the read electrode structures 140 and the routing structures 150, as described in further detail below. In some embodiments, the second pillar structures 152 are each individually formed of and include a stack of materials. For example, each of the second pillar structures 152 may at least include the semiconductor material, and a tunnel dielectric material (e.g., a dielectric oxide material, such as SiO_x) horizontally surrounding and covering at least portions of the second pillar structure 152 at intersections of the second pillar structure 152 and one of the read electrode structures 140 and one of the routing structures 150. In addition, each of the second pillar structures 152 may, optionally, include one or more conductive materials vertically interposed between the semiconductor material thereof and at least one (e.g., each) of the global digit line structure 136 operatively associated therewith and the source line structure 146 operatively associated therewith.

Still referring to FIGS. 1A and 1B, intersections of the second pillar structures 152 and the read electrode structures 140 may define read transistors 158 (e.g., first switching transistors) of the microelectronic device structure 100. The read transistors 158 may comprise vertical transistors including a channel region vertically offset from source/drain regions. In some embodiments, the read transistors 158 comprise MOS transistors. Channel regions of the read transistors 158 may be positioned within vertical boundaries of the read electrode structures 140; and source/drain regions of the read transistors 158 may vertically neighbor the channel regions, and may be vertically offset from the read electrode structures 140. Tunnel dielectric material of the second pillar structures 152 may be horizontally interposed between the semiconductor material of the second pillar structures 152 and the read electrode structures 140 within vertical boundaries of the read electrode structures 140, and may serve as gate dielectric structures for the read transistors 158.

In addition, intersections of the second pillar structures 152 and the routing structures 150 may define sense transistors 160 of the microelectronic device structure 100. The sense transistors 160 may comprise vertical transistors including a channel region vertically offset from source/drain regions. For each second pillar structure 152, the sense transistor 160 defined thereby may be provided in series with the read transistor 158 defined thereby. As a non-limiting example, for an individual sense transistor 160 defined by an individual second pillar structure 152, a drain region of the sense transistor 160 may be coupled to a source region of an individual read transistor 158 vertically overlying the sense transistor 160 and defined by the second pillar structure 152. The sense transistor 160 defined by the second pillar structure 152 may be physically and electrically interposed between the read transistor 158 defined by the second pillar structure 152 and each of the source line structure 146 and the local digit line structure 128 operatively associated with the second pillar structure 152. In some embodiments, the sense transistors 160 comprise MOS transistors. In some such embodiments, the sense transistors 160 comprise PMOS transistors, so that conductive structures 106 (e.g., employed as local access line structures) of the stack structure 104 may be driven from LOW to HIGH. Channel regions of the sense transistors 160 may be positioned within vertical boundaries of the routing structures 150; and source/drain regions of the sense transistors 160 may vertically neighbor the channel regions, and may be vertically offset from the routing structures 150. Tunnel dielectric material of the second pillar structures 152 may be

horizontally interposed between the semiconductor material of the second pillar structures **152** and the routing structures **150** within vertical boundaries of the routing structures **150**, and may serve as gate dielectric structures for the sense transistors **160**.

Still referring to FIGS. **1A** and **1B**, the microelectronic device structure **100** further includes third pillar structures **154** operatively associated with the local digit line structures **128**, the write electrode structures **142**, and the global digit line structures **136**. The third pillar structures **154** may individually vertically extend from one of the global digit line structures **136** (e.g., the first global digit line structure **136A**, the second global digit line structure **136B**), through one of the write electrode structures **142**, and at least to (e.g., to, into) one of the local digit line structures **128** (e.g., the first local digit line structure **128A**, the second local digit line structure **128B**).

The third pillar structures **154** may at least be formed of and include semiconductor material (e.g., silicon, such as polycrystalline silicon; oxide semiconductor material). One or more vertical regions of the semiconductor material of the third pillar structures **154** may be doped, or the semiconductor material of the third pillar structures **154** may be substantially undoped. If doped, the semiconductor material of the third pillar structures **154** may be doped with one or more conductivity-enhancing species (e.g., one or more N-type dopants, such as one or more of phosphorus, arsenic, antimony, and bismuth; one or more P-type dopants, such as one or more of boron, aluminum, and gallium) facilitating desired vertical transistors at intersections of the write electrode structures **142**, as described in further detail below. In some embodiments, the third pillar structures **154** are each individually formed of and include a stack of materials. For example, each of the third pillar structures **154** may at least include the semiconductor material, and a tunnel dielectric material (e.g., a dielectric oxide material, such as SiO_x) horizontally surrounding and covering at least portions of the third pillar structure **154** at intersections of the third pillar structure **154** and one of the write electrode structures **142**. In addition, each of the third pillar structures **154** may, optionally, include one or more conductive materials vertically interposed between the semiconductor material thereof and at least one (e.g., each) of the global digit line structure **136** operatively associated therewith and the local digit line structure **128** operatively associated therewith.

Intersections of the third pillar structures **154** and the write electrode structures **142** may define write transistors **162** (e.g., second switching transistors) of the microelectronic device structure **100**. In some embodiments, the write transistors **162** comprise MOS transistors. Channel regions of the write transistors **162** may be positioned within vertical boundaries of the write electrode structures **142**; and source/drain regions of the write transistors **162** may vertically neighbor the channel regions, and may be vertically offset from the write electrode structures **142**. Tunnel dielectric material of the third pillar structures **154** may be horizontally interposed between the semiconductor material of the third pillar structures **154** and the write electrode structures **142** within vertical boundaries of the write electrode structures **142**, and may serve as gate dielectric structures for the write transistors **162**.

Still referring to FIGS. **1A** and **1B**, the microelectronic device structure **100** further includes second conductive contact structures **156** operatively associated with the local digit line structures **128** and the routing structures **150**. The second conductive contact structures **156** may individually

vertically extend from one of the routing structures **150**, and at least to (e.g., to, into) one of the local digit line structures **128** (e.g., the first local digit line structure **128A**, the second local digit line structure **128B**). Each second conductive contact structure **156** may facilitate electrical communication between the local digit line structure **128** and the routing structure **150** (and, hence, the sense transistor **160**, the read transistor **158**, and the global digit line structure **136**) operatively associated therewith.

The second conductive contact structures **156** may each individually be formed of and include conductive material. By way of non-limiting example, the second conductive contact structures **156** may each individually be formed of and include one or more of at least one metal, at least one alloy, and at least one conductive metal-containing material (e.g., a conductive metal nitride, a conductive metal silicide, a conductive metal carbide, a conductive metal oxide). In some embodiments, the second conductive contact structures **156** are each individually formed of and include one or more of W, Ru, Mo, and TiN_x . Each of the second conductive contact structures **156** may individually be substantially homogeneous, or one or more of the second conductive contact structures **156** may individually be substantially heterogeneous.

Referring collectively to FIGS. **1A** through **1C**, the source line structures **146**, the sense transistors **160**, the read transistors **158**, and the write transistors **162** may form portions of read/write circuits interposed between the local digit line structures **128** and the global digit line structures **136**. The sense transistors **160** are coupled with the local digit line structures **128**, are in electrical communication with the source line structures **146**, and are also in electrical communication with the global digit line structures **136** through the read transistors **158**. The write transistors **162** are in electrical communication with the local digit line structures **128** and the global digit line structures **136**.

During read operations for a microelectronic device (e.g., a memory device, such as a 3D NAND Flash memory device) including the microelectronic device structure **100**, a local digit line structure **128** and an operatively associated global digit line structure **136** may be pre-charged by way of an operatively associated write transistor **162** and made floating. Thereafter, an operatively associated read electrode structure **140** may be activated. If a read cell current (I_{cell}) flows, a potential level of the local digit line structure **128** drops, an operatively associated sense transistor **160** is in an OFF state, and a potential level of the global digit line structure **136** remains at the pre-charged level. Conversely, if a read cell current (I_{cell}) does not flow, the potential level of the local digit line structure **128** remains at the pre-charged level, the operatively associated sense transistor **160** is in an ON state, and the potential level of the global digit line structure **136** drops. The potential level of the global digit line structure **136** may be detected by a sense amplifier of a page buffer device operatively associated with the global digit line structure **136**. Since each local digit line structure **128** is relatively shorter (e.g., in the X-direction) than the global digit line structure **136** operatively associated therewith, sensing functions may be carried out in a shorter period time relative to sensing functions facilitated through conventional microelectronic device structure configurations. In addition, since parasitic capacitance associated with the local digit line structures **128** is smaller than that associated with the global digit line structures **136**, read performance (e.g., sensing speed) may be maintained or improved relative to conventional read performance facili-

tated by conventional microelectronic device structure configurations, even with relatively smaller read cell currents (I_{cell}).

In additional embodiments, the microelectronic device structure **100** may be formed to have a different configuration than that previously described with reference to FIGS. **1A** through **1C**. The microelectronic device structure **100** may, for example, be formed to exhibit a shielded digit line configuration wherein local digit line structures and global digit lines structures horizontally neighboring one another (e.g., in the Y-direction) are operatively associated with different read electrodes and different write electrodes than one another. The shielded digit line configuration may, for example, mitigate undesirable parasitic capacitance between horizontally neighboring digit line structures (e.g., horizontally neighboring local digit line structures, horizontally neighboring global digit line structures) during read operations. By way of non-limiting example, FIG. **2A** is simplified, partial schematic perspective view of a microelectronic device structure **200** for a microelectronic device (e.g., a memory device, such as a NAND Flash memory device), in accordance with additional embodiments of the disclosure. FIG. **2B** is a schematic diagram of circuitry of a section of the microelectronic device structure **200** shown in FIG. **2A**. With the description provided below, it will be readily apparent to one of ordinary skill in the art that the structures and devices described herein may be included in relatively larger structures, devices, and systems.

Throughout FIGS. **2A** and **2B** and the associated description, features (e.g., regions, materials, structures, devices) functionally similar previously described features (e.g., previously described materials, structures, devices) are referred to with similar reference numerals incremented by 100. To avoid repetition, not all features shown in FIGS. **2A** and **2B** are described in detail herein. Rather, unless described otherwise below, a feature in one or more of FIGS. **2A** and **2B** designated by a reference numeral that is a 100 increment of the reference numeral of a feature previously described with reference to one or more of FIGS. **1A** through **1C** will be understood to be substantially similar to the previously described feature. As a non-limiting example, unless described otherwise below, features designated by the reference numerals **236A** and **236B** in FIGS. **2A** and **2B** will be understood to respectively be substantially similar to the first global digit line structure **136A** and the second global digit line structure **136B** previously described herein with reference to FIGS. **1A** through **1C**. As another non-limiting example, unless described otherwise below, features designated by the reference numerals **228A** and **228B** in FIGS. **2A** and **2B** will be understood to be respectively substantially similar to the first local digit line structure **128A** and the second local digit line structure **128B** previously described herein with reference to FIGS. **1A** through **1C**.

Furthermore, unless described otherwise below, it will be understood that a feature designated with an alphanumeric reference numeral (e.g., a reference numeral including a combination of alphabetical and numerical characters) is considered to be part of a relatively larger group of functionally similar features collectively identified by a reference numeral only including the numeric portion of the alphanumeric reference numeral. As a non-limiting example, unless described otherwise below, the feature designated by the alphanumeric reference numeral **260A** in FIGS. **2A** and **2B** is considered to be one sense transistor **260** (e.g., a first sense transistor) of a relatively larger group of sense transistors **260**, wherein such sense transistors **260** are functionally similar to the sense transistors **160** previously described

herein with reference to FIGS. **1A** through **1C**. As another non-limiting example, unless described otherwise below, the feature designated by the alphanumeric reference numeral **260B** in FIGS. **2A** and **2B** is considered to be another sense transistor **260** (e.g., a second sense transistor) of the relatively larger group of sense transistors **260** that are functionally similar to the sense transistors **160** previously described herein with reference to FIGS. **1A** through **1C**.

In addition, unless described otherwise below, features of the microelectronic device structure **100** previously described with reference to FIGS. **1A** through **1C** may also be included, in substantially the same manner (e.g., so as to exhibit substantially similar configurations and positions), within the microelectronic device structure **200** described herein with reference to FIGS. **2A** through **2B**. For clarity and ease of understanding of the drawings and related description, not all components (e.g., features, structures, devices) of the microelectronic device structure **200** depicted in one of FIGS. **2A** through **2B** are depicted in the other of FIGS. **2A** and **2B**.

As shown in FIG. **2A**, the microelectronic device structure **200** may be formed to exhibit a shielded digit line configuration wherein local digit line structures **228** (e.g., a first local digit line structure **228A**, a second local digit line structure **228B**) horizontally neighboring one another in the Y-direction are operatively associated with different read electrodes **240** and different write electrodes **242** than one another, as are global digit line structures **236** (e.g., a first global digit line structure **236A**, a second global digit line structure **236B**) and additional features (described in further detail below) of the microelectronic device structure **200** operatively associated with the local digit line structures **228**. The microelectronic device structure **200** may include pairs of read electrodes **240** (e.g., a first read electrode **240A**, a second read electrode **240B**) horizontally neighboring one another in the X-direction and extending in parallel in the Y-direction; and pairs of write electrodes **242** (e.g., a first write electrode **242A**, a second write electrode **242B**) horizontally neighboring one another in the X-direction and extending in parallel in the Y-direction. The pairs of read electrodes **240** are horizontally offset from (e.g., may horizontally alternate with) the pairs of write electrodes **242** in the X-direction. For an individual pair of read electrodes **240**, one of the read electrodes **240** (e.g., a first read electrode **240A**) may be operatively associated with one local digit line structure **228** (e.g., a first local digit line structure **228A**), and the other of the read electrodes **240** (e.g., a second read electrode **240B**) may be operatively associated with an additional local digit line structure **228** (e.g., a second local digit line structure **228B**) horizontally neighboring the local digit line structure **228** (e.g., the first local digit line structure **228A**). In addition, for an individual pair of write electrodes **242** horizontally neighbor the pair of read electrodes **240**, one of the write electrodes **242** (e.g., a first write electrode **242A**) may be operatively associated with the local digit line structure **228** (e.g., the first local digit line structure **228A**), and the other of the read electrodes **240** (e.g., a second write electrode **242B**) may be operatively associated with the additional local digit line structure **228** (e.g., the second local digit line structure **228B**).

In some embodiments, so-called “odd” local digit line structures **228** and so-called “odd” global digit line structures **236** are operatively associated with different read electrodes **240** and different write electrodes **242** than so-called “even” local digit line structures **228** and so-called “even” global digit line structures **236** horizontally neigh-

boring (e.g., in the Y-direction) the “odd” local digit line structures **228** and the “odd” global digit line structures **236**. As a non-limiting example, the first local digit line structure **228A** may be considered an “odd” local digit line structure **228**, and the first global digit line structure **236A** operatively associated with the first local digit line structure **228A** may be considered an “odd” global digit line structure **236**; and the second local digit line structure **228B** may be considered an “even” local digit line structure **228**, and the second global digit line structure **236B** operatively associated with the second local digit line structure **228B** may be considered an “even” global digit line structure **236**. As shown in FIG. 2A, the first local digit line structure **228A** and the first global digit line structure **236A** may both be operatively associated with the first read electrode **240A** and the first write electrode **242A**; and the second local digit line structure **228B** and the second global digit line structure **236B** may both be operatively associated with the second read electrode **240B** horizontally neighboring the first read electrode **240A** and the second write electrode **242B** horizontally neighboring the first write electrode **242A**. Furthermore, additional features of the microelectronic device structure **200** operatively associated with the first local digit line structure **228A** and the first global digit line structure **236A** (e.g., in the manners previously described herein with reference to one or more of FIGS. 1A through 1C) may be operatively associated with the first read electrode **240A** and the first write electrode **242A**; and further features of the microelectronic device structure **200** operatively associated with the second local digit line structure **228B** and the second global digit line structure **236B** (e.g., in the manners previously described herein with reference to one or more of FIGS. 1A through 1C) may be operatively associated with the second read electrode **240B** and the second write electrode **242B**. By way of non-limiting example, a first source line structure **246A**, a first read transistor **258A**, a first sense transistor **260A**, and a first write transistor **262A** may be operatively associated with (e.g., in the manners previously described herein with reference to one or more of FIGS. 1A through 1C) the first read electrode **240A** and the first write electrode **242A**; and a second source line structure **246B**, a second read transistor **258B**, a second sense transistor **260B**, and a second write transistor **262B** may be operatively associated with (e.g., in the manners previously described herein with reference to one or more of FIGS. 1A through 1C) the second read electrode **240B** and the second write electrode **242B**.

Referring to FIG. 2B, the microelectronic device structure **200** may be formed to include multiple (e.g., more than one, a plurality of) additional select gate tiers **216** (e.g., upper select gate tiers), such as a first additional select gate tier **216A** and a second additional select gate tier **216B** vertically overlying the first additional select gate tier **216A**. The multiple additional select gate tiers **216** may partially define (e.g., in the manner previously described herein with reference to one or more of FIGS. 1A through 1C) multiple additional select transistors **224** operatively associated with individual vertically extending strings of memory cells **220** of the microelectronic device structure **200**. For example, for an individual vertically extending string of memory cells **120**, a first additional select transistor **224A** and a second additional select transistor **224B** may be coupled in series with the vertically extending string of memory cells **120**. During read operations for a microelectronic device including the microelectronic device structure **200**, states (e.g., ON states, OFF states; active states, inactive states; enhancement states, depletion states; selected states, deselected states) of

the first additional select transistor **224A** and the second additional select transistor **224B** coupled in series with a vertically extending string of memory cells **220** operatively associated with one local digit line structure **228** (e.g., the first local digit line structure **228A**) may be controlled relative to states (e.g., ON states, OFF states; active states, inactive states; enhancement states, depletion states; selected states, deselected states) of the first additional select transistor **224A** and the second additional select transistor **224B** coupled in series with another vertically extending string of memory cells **220** operatively associated with another local digit line structure **228** (e.g., the second local digit line structure **228B**). For example, the first additional select transistor **224A** and the second additional select transistor **224B** coupled in series with an individual vertically extending string of memory cells **220** operatively associated with the first local digit line structure **228A** may respectively be provided in an OFF state (e.g., an inactive state, a depletion state, deselected state) and an ON state (e.g., an active state, an enhancement state, a selected state), while the first additional select transistor **224A** and the second additional select transistor **224B** coupled in series with another individual vertically extending string of memory cells **220** operatively associated with the second local digit line structure **228B** may respectively be provided in an ON state and an OFF state; or vice versa.

Thus, a microelectronic device in accordance with embodiments of the disclosure comprises local digit line structures, global digit line structures, source line structures, sense transistors, read transistors, and write transistors. The local digit line structures are coupled to strings of memory cells. The global digit line structures overlie the local digit line structures. The source line structures are interposed between the local digit line structures and the global digit line structures. The sense transistors are interposed between the source line structures and the global digit line structures, and are coupled to the local digit line structures and the source line structures. The read transistors are interposed between and are coupled to the sense transistors and the global digit line structures. The write transistors are interposed between and are coupled to the global digit line structures and the local digit line structures.

Furthermore, a microelectronic device in accordance with additional embodiments of the disclosure comprises a stack structure, a local digit line tier, a global digit line tier, a source line tier, a read/write electrode tier, a routing tier, first pillar structures, and second pillar structures. The stack structure comprises conductive structures and insulative structures vertically interleaved with the conductive structures. The local digit line tier vertically overlies the stack structure and comprises local digit line structures coupled to strings of memory cells vertically extending through the stack structure. The global digit line tier vertically overlies the local digit line tier and comprises global digit line structures. The source line tier is vertically interposed between the local digit line tier and the global digit line tier and comprises source line structures. The read/write electrode tier is vertically interposed between the source line tier and the global digit line tier and comprises read electrode structures and write electrode structures. The routing tier is vertically interposed between the source line tier and the read/write electrode tier and comprises routing structures coupled to the local digit line structures. The first pillar structures comprise semiconductor material. The first pillar structures vertically extend from the global digit line structures, through the read electrode structures and the routing structures, and at least to the source line structures. The

second pillar structures comprise additional semiconductor material. The second pillar structures vertically extend from the global digit line structures, through the write electrode structures, and at least to the local digit line structures.

Moreover, a memory device in accordance with embodiments of the disclosure comprises a source plate, a stack structure, local digit lines, strings of memory cells, global digit lines, sense transistors, read transistors, and write transistors. The stack structure overlies the source plate and comprises an access line region comprising local access line structures; a select gate region underlying the access line region and comprising source side select gate (SGS) structures; and an additional select gate region overlying the access line region and comprising drain side select gate (SGD) structures. The local digit lines overlie the stack structure. The strings of memory cells extend through the stack structure and are in electrical communication with the source plate and the local digit lines. The global digit lines overlie the local digit lines and are in electrical communication with page buffer circuitry. Horizontal dimensions of the global digit lines are greater than horizontal dimensions of the local digit lines. The sense transistors overlie and are in electrical communication with the local digit lines. The read transistors overlie the sense transistors and are in electrical communication with the sense transistors and the global digit lines. The write transistors overlie the local digit lines and are in electrical communication with the local digit lines and the global digit lines.

Microelectronic devices structures (e.g., the microelectronic device structure **100**, the microelectronic device structure **200**) and microelectronic devices in accordance with embodiments of the disclosure may be used in embodiments of electronic systems of the disclosure. For example, FIG. **3** is a schematic block diagram of an illustrative electronic system **300** according to embodiments of disclosure. The electronic system **300** may comprise, for example, a computer or computer hardware component, a server or other networking hardware component, a cellular telephone, a digital camera, a personal digital assistant (PDA), portable media (e.g., music) player, a Wi-Fi or cellular-enabled tablet such as, for example, an iPad® or SURFACE® tablet, an electronic book, a navigation device, etc. The electronic system **300** includes at least one memory device **302**. The memory device **302** may comprise, for example, one or more of a microelectronic device structure (e.g., the microelectronic device structure **100**, the microelectronic device structure **200**) and a microelectronic device previously described herein. The electronic system **300** may further include at least one electronic signal processor device **304** (often referred to as a “microprocessor”). The electronic signal processor device **304** may, optionally, include one or more of a microelectronic device structure (e.g., the microelectronic device structure **100**, the microelectronic device structure **200**) and a microelectronic device previously described herein. While the memory device **302** and the electronic signal processor device **304** are depicted as two (2) separate devices in FIG. **3**, in additional embodiments, a single (e.g., only one) memory/processor device having the functionalities of the memory device **302** and the electronic signal processor device **304** is included in the electronic system **300**. In such embodiments, the memory/processor device may include one or more of a microelectronic device structure (e.g., the microelectronic device structure **100**, the microelectronic device structure **200**) and a microelectronic device previously described herein. The electronic system **300** may further include one or more input devices **306** for inputting information into the electronic system **300** by a

user, such as, for example, a mouse or other pointing device, a keyboard, a touchpad, a button, or a control panel. The electronic system **300** may further include one or more output devices **308** for outputting information (e.g., visual or audio output) to a user such as, for example, one or more of a monitor, a display, a printer, an audio output jack, and a speaker. In some embodiments, the input device **306** and the output device **308** may comprise a single touchscreen device that can be used both to input information to the electronic system **300** and to output visual information to a user. The input device **306** and the output device **308** may communicate electrically with one or more of the memory device **302** and the electronic signal processor device **304**.

Thus, an electronic system in accordance with embodiments of the disclosure comprises an input device, an output device, a processor device operably connected to the input device and the output device, and a memory device operably connected to the processor device. The memory device comprises strings of memory cells, a source plate, local digit lines, global digit lines, source lines, first vertical transistors, second vertical transistors, and third vertical transistors. The strings of memory cells vertically extend through a stack structure comprising conductive material vertically alternating with insulative material. The source plate vertically underlies the stack structure and is in electrical communication with the strings of memory cells. The local digit lines vertically overlie the stack structure and are in electrical communication with the strings of memory cells. The global digit lines vertically overlie the local digit lines and are have greater horizontal lengths than the local digit lines. The source lines are vertically between the local digit lines and the global digit lines. The first vertical transistors are vertically between the source lines and the global digit lines. The first vertical transistors are in electrical communication with the local digit lines and the source lines. The second vertical transistors are vertically between and are in electrical communication with the first vertical transistors and the global digit lines. The third vertical transistors are vertically between and are in electrical communication with the global digit lines and the local digit lines.

The structures and devices of the disclosure advantageously facilitate one or more of improved microelectronic device performance, reduced costs (e.g., manufacturing costs, material costs), increased miniaturization of components, and greater packaging density as compared to conventional structures, conventional devices, and conventional methods. The structures and devices of the disclosure may also improve scalability, efficiency, and simplicity as compared to conventional structures and conventional devices.

While the disclosure is susceptible to various modifications and alternative forms, specific embodiments have been shown by way of example in the drawings and have been described in detail herein. However, the disclosure is not limited to the particular forms disclosed. Rather, the disclosure is to cover all modifications, equivalents, and alternatives falling within the scope of the following appended claims and their legal equivalent. For example, elements and features disclosed in relation to one embodiment may be combined with elements and features disclosed in relation to other embodiments of the disclosure.

What is claimed is:

1. A microelectronic device, comprising:
 - local digit line structures coupled to strings of memory cells;
 - global digit line structures overlying the local digit line structures;

25

source line structures interposed between the local digit line structures and the global digit line structures; sense transistors interposed between the source line structures and the global digit line structures, the sense transistors coupled to the local digit line structures and the source line structures;

read transistors interposed between and coupled to the sense transistors and the global digit line structures; and write transistors interposed between and coupled to the global digit line structures and the local digit line structures.

2. The microelectronic device of claim 1, wherein the local digit line structures comprise:

rows of the local digit line structures extending in a first horizontal direction, each of the rows of the local digit line structures comprising a group of the local digit line structures substantially aligned with one another in a second horizontal direction orthogonal to the first horizontal direction; and

columns of the local digit line structures extending in the second horizontal direction, each of the columns of the local digit line structures comprising an additional group of the local digit line structures substantially aligned with one another in the first horizontal direction.

3. The microelectronic device of claim 2, wherein each local digit line structure of the additional group of the local digit line structures of one of the columns of the local digit line structures is operatively associated with a different one of the global digit line structures than each other local digit line structure of the additional group of the local digit line structures of the one of the columns of the local digit line structures.

4. The microelectronic device of claim 3, wherein: each read transistor of a group of the read transistors operatively associated the additional group of the local digit line structures of the one of the columns of the local digit line structures shares a gate electrode with each other read transistor of the group of the read transistors; and

each write transistor of a group of the write transistors operatively associated the additional group of the local digit line structures of the one of the columns of the local digit line structures shares an additional gate electrode with each other write transistor of the group of the write transistors.

5. The microelectronic device of claim 3, wherein: at least one read transistor of a group of the read transistors operatively associated the additional group of the local digit line structures of the one of the columns of the local digit line structures is operatively associated with a different gate electrode than at least one other read transistor of the group of the read transistors; and at least one write transistor of a group of the write transistors operatively associated the additional group of the local digit line structures of the one of the columns of the local digit line structures is operatively associated with a different additional gate electrode than at least one other write transistor of the group of the write transistors.

6. The microelectronic device of claim 5, wherein: at least one read transistor neighbors the at least one other read transistor in the second horizontal direction; and at least one write transistor neighbors the at least one other write transistor in the second horizontal direction.

7. The microelectronic device of claim 3, wherein each local digit line structure of the group of the local digit line

26

structures of one of the rows of the local digit line structures is operatively associated with the same one of the global digit line structures as each other local digit line structure of the group of the local digit line structures of the one of the rows of the local digit line structures.

8. The microelectronic device of claim 1, wherein the local digit line structures and the global digit line structures each extend in a first horizontal direction, and horizontal dimensions of the local digit line structures in the first horizontal direction are less than horizontal dimensions of the global digit line structures in the first horizontal direction.

9. The microelectronic device of claim 1, wherein: the sense transistors comprise first vertical transistors vertically interposed between the source line structures and the global digit line structures; the read transistors comprise second vertical transistors vertically interposed between the sense transistors and the global digit line structures; and the write transistors comprise third vertical transistors vertically interposed between the global digit line structures and the local digit line structures.

10. The microelectronic device of claim 9, wherein: gate structures of the sense transistors vertically overlie and are coupled to the local digit line structures; source regions of the sense transistors vertically overlie and are coupled to the source line structures; and drain regions of the sense transistors vertically underlie and are coupled to source regions of the read transistors.

11. The microelectronic device of claim 1, wherein the sense transistors comprise PMOS transistors.

12. The microelectronic device of claim 1, wherein the read transistors are located at substantially the same vertical position as the write transistors.

13. A microelectronic device, comprising: a stack structure comprising conductive structures and insulative structures vertically interleaved with the conductive structures;

a local digit line tier vertically overlying the stack structure and comprising local digit line structures coupled to strings of memory cells vertically extending through the stack structure;

a global digit line tier vertically overlying the local digit line tier and comprising global digit line structures; a source line tier vertically interposed between the local digit line tier and the global digit line tier and comprising source line structures;

a read/write electrode tier vertically interposed between the source line tier and the global digit line tier and comprising read electrode structures and write electrode structures;

a routing tier vertically interposed between the source line tier and the read/write electrode tier and comprising routing structures coupled to the local digit line structures;

first pillar structures comprising semiconductor material, the first pillar structures vertically extending from the global digit line structures, through the read electrode structures and the routing structures, and at least to the source line structures; and

second pillar structures comprising additional semiconductor material, the second pillar structures vertically extending from the global digit line structures, through the write electrode structures, and at least to the local digit line structures.

27

14. The microelectronic device of claim 13, further comprising:

- first vertical transistors at intersections of the first pillar structures and the source line structures;
- second vertical transistors at intersections of the first pillar structures and the read electrode structures; and
- third vertical transistors at intersections of the second pillar structures and the write electrode structures.

15. The microelectronic device of claim 14, further comprising conductive contact structures vertically extending from the routing structures to the local digit line structures.

16. The microelectronic device of claim 13, wherein: the local digit line structures, the global digit line structures, and the routing structures each horizontally extend in a first direction; and

the source line structures, the read electrode structures, and the write electrode structures each horizontally extend in a second direction orthogonal to the first direction.

17. The microelectronic device of claim 13, wherein at least one of the local digit line structures has a length in a first horizontal direction shorter than a length of at least one of the global digit line structures in the first horizontal direction.

18. The microelectronic device of claim 13, wherein:

- the read/write electrode tier comprises a pair of the read electrode structures horizontally neighboring a pair of the write electrode structures in a first direction; and
- at least one of the local digit line structures is operatively associated with a different read electrode structure of the pair of the read electrode structures and a different write electrode structure of the pair of the write electrode structures than at least one other of the local digit line structures horizontally neighboring the at least one of the local digit line structures in a second direction orthogonal to the first direction.

19. The microelectronic device of claim 13, further comprising a source tier vertically underlying the stack structure and comprising a source structure coupled to the strings of memory cells.

20. A memory device, comprising:

- a source plate;
- a stack structure overlying the source plate and comprising:
 - an access line region comprising local access line structures;
 - a select gate region underlying the access line region and comprising source side select gate (SGS) structures; and
 - an additional select gate region overlying the access line region and comprising drain side select gate (SGD) structures;

local digit lines overlying the stack structure;

strings of memory cells extending through the stack structure and in electrical communication with the source plate and the local digit lines;

global digit lines overlying the local digit lines and in electrical communication with page buffer circuitry, horizontal dimensions of the global digit lines greater than horizontal dimensions of the local digit lines;

sense transistors overlying and in electrical communication with the local digit lines;

read transistors overlying the sense transistors and in electrical communication with the sense transistors and the global digit lines; and

28

write transistors overlying the local digit lines and in electrical communication with the local digit lines and the global digit lines.

21. The memory device of claim 20, wherein each of the global digit lines is operatively associated with more than one of the local digit lines.

22. The memory device of claim 20, wherein further comprising source lines overlying the local digit lines and in electrical communication with the sense transistors.

23. The memory device of claim 20, wherein the sense transistors, the read transistors, and the write transistors each comprise vertical metal-oxide-semiconductor (MOS) transistors.

24. The memory device of claim 20, wherein:

- at least one of the read transistors operatively associated with a column of the local digit lines is in electrical communication with a different gate electrode than at least one other of the read transistors operatively associated with the column of the local digit lines; and

- at least one of the write transistors operatively associated with the column of the local digit lines is in electrical communication with a different additional gate electrode than at least one other of the write transistors operatively associated with the column of the local digit lines.

25. The memory device of claim 20, wherein each local digit line within a column of the local digit lines is in electrical communication with a different one of the global digit lines than each other local digit line within the column of the local digit lines.

26. An electronic system, comprising:

- an input device;
- an output device;
- a processor device operably connected to the input device and the output device; and

- a memory device operably connected to the processor device and comprising:

- strings of memory cells vertically extending through a stack structure comprising conductive material vertically alternating with insulative material;

- a source plate vertically underlying the stack structure and in electrical communication with the strings of memory cells;

- local digit lines vertically overlying the stack structure and in electrical communication with the strings of memory cells;

- global digit lines vertically overlying the local digit lines and having greater horizontal lengths than the local digit lines;

- source lines vertically between the local digit lines and the global digit lines;

- first vertical transistors vertically between the source lines and the global digit lines, the first vertical transistors in electrical communication with the local digit lines and the source lines;

- second vertical transistors vertically between and in electrical communication with the first vertical transistors and the global digit lines; and

- third vertical transistors vertically between and in electrical communication with the global digit lines and the local digit lines.

27. The electronic system of claim 26, wherein the memory device comprises a 3D NAND Flash memory device.

* * * * *