

US011564387B2

(12) **United States Patent**  
**Haakenson et al.**

(10) **Patent No.:** **US 11,564,387 B2**  
(45) **Date of Patent:** **Jan. 31, 2023**

(54) **LADDER STAND**

(71) Applicant: **ARDISAM, INC.**, Cumberland, WI (US)

(72) Inventors: **Bryant Haakenson**, Amery, WI (US); **Michael Furseth**, Cumberland, WI (US); **Scott Nickell**, Cumberland, WI (US); **Blake Otto**, Gladwin, MI (US)

(73) Assignee: **ARDISAM, INC.**, Cumberland, WI (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 522 days.

(21) Appl. No.: **16/724,095**

(22) Filed: **Dec. 20, 2019**

(65) **Prior Publication Data**

US 2021/0186000 A1 Jun. 24, 2021

(51) **Int. Cl.**  
**A01M 31/02** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **A01M 31/02** (2013.01)

(58) **Field of Classification Search**  
CPC ..... A01M 31/02; A01M 31/025; E06C 1/34; E06C 7/06; E06C 7/182; E06C 7/16; E06C 7/188  
USPC ..... 182/116  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

5,310,019 A \* 5/1994 Paul ..... A01M 31/02 182/135  
5,580,129 A 12/1996 Findlay

5,975,389 A \* 11/1999 Braun ..... A45F 4/02 224/916  
6,053,278 A \* 4/2000 Myers ..... A01M 31/02 182/20  
6,890,033 B1 \* 5/2005 Casella ..... A47C 4/42 297/344.21  
8,167,374 B2 \* 5/2012 Findlay ..... A47C 1/0265 297/344.21  
8,973,708 B1 \* 3/2015 Fenner ..... A01M 31/02 182/12  
8,991,555 B2 \* 3/2015 Furseth ..... E06C 7/48 182/187

(Continued)

**OTHER PUBLICATIONS**

“U.S. Appl. No. 16/946,299”, Nonfinal Office Action, dated Jul. 8, 2022, 17 pages.

(Continued)


*Primary Examiner* — Muhammad Ijaz

(74) *Attorney, Agent, or Firm* — Perkins Coie LLP

(57) **ABSTRACT**

A ladder stand includes a ladder portion, a platform on the ladder portion, and a plurality of support straps to hold the ladder stand against a support structure. The plurality of support straps may include upper support straps that are each connected to the ladder stand, wrap partially around the tree, and connect to each other with a connecting device, to position the tree between the ladder stand and the straps. The platform may include a blade element positioned to press against the tree when the support straps are tightened against the tree. A method of installing a ladder stand may include connecting ends of the upper support straps to each other after passing the ends around an obstruction on the tree. A user may pull on other ends of the straps to draw the straps upward along the tree until they are approximately level with the blade element.

**15 Claims, 6 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

2008/0105490 A1\* 5/2008 Butcher ..... A01M 31/02  
182/116  
2009/0229917 A1\* 9/2009 Berkbuegler ..... A01M 31/02  
182/187  
2013/0248287 A1\* 9/2013 Furseth ..... A01M 31/02  
182/115  
2015/0129360 A1\* 5/2015 Shiver ..... E06C 1/06  
182/116  
2017/0142959 A1 5/2017 Berkbuegler  
2017/0211904 A1\* 7/2017 Matthews ..... F41A 23/02  
2019/0281812 A1\* 9/2019 Lee ..... E06C 7/14  
2020/0000084 A1\* 1/2020 McGucken, III ..... A47C 3/18  
2020/0336581 A1\* 10/2020 Allen ..... F16M 11/16  
2020/0344997 A1\* 11/2020 Berkbuegler ..... A01M 31/02  
2020/0383315 A1\* 12/2020 Overbaugh ..... E04G 1/30  
2021/0186001 A1 6/2021 Haakenson et al.

OTHER PUBLICATIONS

Hawk Hunting, Hercules Cross Grip Safety System Ladder Stand, URL: A <https://www.hawkhunting.com/hawk-upgrades-ladder-stands-hercules/>, Jan. 10, 2018.  
Leverage, 5100 Tree Stand Review—Outdoorfreaks.net, YouTube, URL <https://www.youtube.com/watch?v=3SJ2QjMFGdw>, Sep. 13, 2012.

Leverage, Outcast Telescoping Ladder Stand, YouTube, URL <https://www.youtube.com/watch?v=WK-jllUUQao>, Jun. 6, 2012.  
Leverage, Outcast Model 5300, Telescoping Ladder Stand, 2013.  
Lock Jaws, Lockjawz Tree Stands, Facebook Video, URL: <https://www.facebook.com/lockjawztreestands/>, exact publication date unknown, web page visited Sep. 21, 2020.  
Primal Vantage, Grip Jaw & Backbone Stabilizer Truss System, Web Video, URL <https://www.primaltreestands.com/press/hp2-introducing-the-new-innovative-emergency-descent-device-3>, Jul. 23, 2018.  
River's Edge Treestands, Lockdown Ladder Stands from River Edge, YouTube, URL <https://www.youtube.com/watch?v=H2timkvMeTU&t=2s>, Dec. 20, 2017.  
Trophy Treestands, Draw Tight Demo, YouTube, URL <https://www.youtube.com/watch?v=kcbsSHFETjc>, Dec. 6, 2019.  
Trophy Treestands, Jaw Safety System Demo 1, YouTube, URL <https://www.youtube.com/watch?v=zv2nOgResSw>, Aug. 26, 2019.  
Trophy Treestands, Single Person Ladderstand, URL <https://www.trophytreestands.com/product-page/f-15>, exact publication date unknown, web page visited Sep. 16, 2020.  
X-STAND Jaw Safety System, YouTube, URL <https://www.youtube.com/watch?v=tkP61J1FFeg>, Aug. 18, 2016.  
Rock West Composites, "Telescoping Clamps", URL: <https://www.rockwestcomposites.com/shop/connector-accessories/locking-telescoping-mechanisms/telescoping-clamps>, website visited Feb. 3, 2021.

\* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6



**1****LADDER STAND**

## BACKGROUND

Hunters, wildlife observers, and others use portable ladder stands (also called tree stands) to conceal themselves from wildlife or to have an elevated perspective for observing wildlife. Such a ladder stand may be permanently or temporarily attached to a structure, such as a tree. A ladder stand advantageously allows a user to carry minimal structure into a remote area and to rely on natural features to support the stand.

Existing ladder stands have several drawbacks. For example, existing stands may not work on trees with branches because installation requires positioning support straps over or around branches. Existing stands that rely on movable jaws to hold a tree may work only on a limited range of tree sizes. Such movable-jaw systems may also be difficult to install or uninstall because the jaws may need to be operated (such as opening or closing) while a user is on an upper platform of the stand, meaning a user may need to climb the stand before it is safely secured to the tree. Existing stands also tend to apply a downward force on the upper attachment point to the tree, which can cause the stand to shift down the tree and become unstable while climbing. Further, existing stands may have only one strap to tighten a tree blade against a tree. Because trees are typically not uniform, having only one strap to tighten the blade against a tree can result in an uneven or twisted contact with the tree.

## SUMMARY

Representative embodiments of the present technology include a ladder stand having a blade element that is drawn toward a support structure, such as a tree, by two straps that extend from the ladder stand, wrap partially around the tree, and connect to each other at the backside of the tree or otherwise adjacent to the tree to position the tree between the blade element and the straps. The straps may be connected to each other by a connecting device so that a user or installer may pass each strap around the tree individually. By connecting the straps together after passing them around the tree, a user may position the straps to avoid obstructions on the tree before tightening the straps to draw the blade element into the tree. The straps may be positioned to be generally level or horizontal with the blade element to provide a primarily horizontal or perpendicular force to draw the blade element against or into the tree. In some embodiments, a stabilizer bar may be positioned below a platform of the ladder stand, between a ladder portion of the ladder stand and the tree, to further stabilize the ladder stand against the tree.

Other features and advantages will appear hereinafter. The features described above can be used separately or together, or in various combinations of one or more of them.

## BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings, wherein the same reference number indicates the same element throughout the several views:

FIG. 1 illustrates a ladder stand configured in accordance with embodiments of the present technology, in a deployed position and attached to a support structure.

FIG. 2 illustrates a detailed view of a portion of the ladder stand shown in FIG. 1, including an upper connection between the support structure and the ladder stand.

**2**

FIG. 3 illustrates a detailed view of a portion of the ladder stand shown in FIG. 1, including a tensioning device attached to the ladder portion and operable to tension an upper support strap, in accordance with embodiments of the present technology.

FIG. 4 illustrates the ladder stand shown in FIGS. 1-3 in a pre-climb and pre-installation configuration, in order to illustrate an installation procedure in accordance with embodiments of the present technology.

FIG. 5 is a detailed view of a portion of the ladder stand shown in FIG. 4.

FIG. 6 is a detailed view of another portion of the ladder stand shown in FIG. 4.

## DETAILED DESCRIPTION

The present technology is directed to ladder stands, and associated systems and methods. Various embodiments of the technology will now be described. The following description provides specific details for a thorough understanding and enabling description of these embodiments. One skilled in the art will understand, however, that the invention may be practiced without many of these details. Additionally, some well-known structures or functions, such as those common to ladder stands, chairs, or ladders, may not be shown or described in detail so as to avoid unnecessarily obscuring the relevant description of the various embodiments. Accordingly, embodiments of the present technology may include additional elements or exclude some of the elements described below with reference to FIGS. 1-6, which illustrate examples of the technology.

The terminology used in this description is intended to be interpreted in its broadest reasonable manner, even though it is being used in conjunction with a detailed description of certain specific embodiments of the invention. Certain terms may even be emphasized below; however, any terminology intended to be interpreted in any restricted manner will be overtly and specifically defined as such in this detailed description section.

Where the context permits, singular or plural terms may also include the plural or singular term, respectively. Moreover, unless the word “or” is expressly limited to mean only a single item exclusive from the other items in a list of two or more items, then the use of “or” in such a list is to be interpreted as including (a) any single item in the list, (b) all the items in the list, or (c) any combination of items in the list. Further, unless otherwise specified, terms such as “attached” or “connected” are intended to include integral connections, as well as connections between physically separate components.

FIG. 1 illustrates a ladder stand **100** configured in accordance with embodiments of the present technology, in a deployed position and attached to a support structure **105**, which may include a tree, a pole, or another sturdy structure. The ladder stand **100** includes a ladder portion **110** (having a plurality of rungs or steps), a seating portion **115** (which may include a chair **116** supported on a platform **117**) supported by the ladder portion **110**, and a plurality of support straps (such as four support straps) **120a**, **120b**, **120c**, **120d** for securing the ladder stand **100** on the support structure **105**.

In some embodiments, the ladder stand **100** includes a stabilizer bar **125**, which may be a single bar, a multiple piece bar, or a telescoping bar. The stabilizer bar **125** may be oriented generally horizontally and may be pivotally connected, releasably connected, or otherwise suitably connected to the ladder portion **110** at a first end **130**, and

engaged with the support structure **105** at a second end **135**. In some embodiments, the second end **135** includes one or more spikes **140** for pressing into the support structure **105** (for example, to dig or stab into a tree for a secure connection with the tree). In other embodiments, spikes **140** may be omitted and the second end **135** may frictionally engage the support structure **105**. The ladder portion **110** may be collapsible, telescoping, one integral ladder, or another suitable configuration for forming a ladder structure.

FIG. **2** illustrates a detailed view of a portion of the ladder stand **100**, showing an upper connection **200** between the support structure **105** and the ladder stand **100**. In some embodiments, a first upper support strap **120a** is connected to the ladder stand **100** and wraps partially around the support structure **105**, and a second upper support strap **120b** is connected to the ladder stand **100** and wraps partially around the support structure **105**. The first upper support strap **120a** and the second upper support strap **120b** may be connected to each other with a connecting device **210**.

The ladder stand **100** may be positioned on a first side **212** (such as the front) of the support structure **105**, and the connecting device **210** may be positioned on a second side **214** (such as the back) of the support structure **105**, opposite the first side **212**, or the connecting device **210** may be positioned elsewhere as long as it connects the first and second upper support straps **120a**, **120b** such that they together wrap around the support structure **105**. The connecting device **210** joins the first and second upper support straps **120a**, **120b** such that they together wrap around the support structure **105** to secure the ladder stand **100** to the support structure **105**.

The ladder stand **100** may include one or more blade elements (such as two blade elements, or more blade elements) **215a**, **215b**. In some embodiments, the blade elements are carried by the seating portion **115** (for example, attached to the chair **116** or the platform **117**, or otherwise supported by the platform **117**). The blade elements **215a**, **215b** may include teeth **217** (such as serrations or spikes) for digging or stabbing into the support structure **105**. For example, as described in additional detail below, the upper support straps **120a**, **120b** may be tightened against the support structure **105** to cause a primary blade element **215a** (such as a lowermost blade element attached to the platform **117**) to press against or into the support structure **105**.

Embodiments of the present technology advantageously allow the upper support straps **120a**, **120b** to create a force that is generally perpendicular to the support structure **105** (such as a horizontal force), as opposed to a force that is oriented at a generally oblique angle relative to the support structure **105**. In other words, in some embodiments, the primary blade element **215a** and the upper support straps **120a**, **120b** are positioned to be generally parallel when one or more tensioning devices **300** (described below) apply tension to the upper support straps **120a**, **120b** so that the primary blade element **215a** is positioned and configured to apply a generally horizontal force against or into the support structure **105**. Such a perpendicular or horizontal force aids the primary blade element **215a** in gripping the support structure **105** and avoids an undesirable upward or downward force on the remainder of the ladder stand **100**. This provides improved stability and reliability in the connection between the ladder stand **100** (specifically, the primary blade element **215a**) and the support structure **105**. Such improved stability and reliability facilitates a safe pre-climb installation process and provides a stable ladder stand **100** that a

user can safely climb to complete installation (such as fastening additional straps), as explained in additional detail below.

FIG. **3** illustrates a detailed view of a portion of the ladder stand **100**, showing a tensioning device **300** attached to the ladder portion **110** (or otherwise supported by the ladder portion **110**) and operable to tighten the second upper support strap **120b**, in accordance with embodiments of the present technology. FIG. **3** shows only one side of the ladder portion **110**, the second upper support strap (**120b**), and one tensioning device **300**, but FIG. **1** illustrates another tensioning device **300** attached to the other side of the ladder portion **110** and operable to tighten the first upper support strap **120a**. In some embodiments, the tensioning devices **300** may include a ratchet device for applying tension to the upper support straps **120a**, **120b**. Although two tensioning devices **300** are shown in the figures, in some embodiments, more or fewer tensioning devices may be used. For example, one single tensioning device **300** may be implemented to tighten both upper support straps **120a**, **120b**. The one or more tensioning devices **300** are operable to tighten the upper support straps **120a**, **120b** to draw the blade elements (such as the primary blade element **215a**) against or into the support structure **105**.

With reference to FIG. **1**, the upper support straps **120a**, **120b**, which are connected together by the connecting device **210**, extend along the platform **117**, down the ladder portion **110**, to the tensioning devices **300** for a user to tighten the support straps **120a**, **120b** from a user's position on the ground. In some embodiments, the upper support straps **120a**, **120b** may be supported by one or more strap supports **118** (such as hooks or loops) attached to the platform **117**. In some embodiments, the upper support straps **120a**, **120b** may be supported by one or more additional strap supports **118** attached to the ladder portion **110**. In some embodiments, the straps **120a**, **120b** may be partially concealed by passing them through or within one or more ladder rails **119** or one or more platform rails **121**.

With reference to FIGS. **1** and **2**, in some embodiments, the ladder stand **100** may include one or more additional straps and tensioning devices to tighten the ladder stand **100** against the support structure **105**, such as one or more additional straps and tensioning devices adjacent to a secondary blade element **215b**. Such additional straps may be installed or tightened after the upper support straps **120a**, **120b** are tightened against the support structure **105**. A user may climb the ladder stand **100** after the upper support straps **120a**, **120b** are tightened, and then a user may install or tighten additional straps.

Although the blade elements **215a**, **215b** are described as including teeth **217**, in some embodiments, the blade elements **215a**, **215b** may be replaced with, or may include, another suitable structure configured to grip the ladder stand **100** against the support structure **105** when the upper support straps **120a**, **120b** are tightened against the support structure **105**. For example, a gripping structure may include a surface that does not include teeth or spikes but instead is a smooth blade or broad surface that relies on friction against the support structure **105**.

With reference to FIG. **1**, and as described in additional detail below with regard to FIG. **6**, lower support straps **120c**, **120d** may be connected to the second end **135** of the stabilizer bar **125**, wrapped around the support structure **105**, and connected together with a tensioning device **300**. The tensioning device **300** is operable to tighten the lower support straps **120c**, **120d** to pull the one or more spikes **140**

5

into the support structure **105** or to otherwise pull the second end **135** against the support structure **105**.

FIG. **4** illustrates the ladder stand **100** in a pre-climb and pre-installation configuration, in order to illustrate an installation procedure in accordance with embodiments of the present technology. FIG. **5** is a detailed view of a portion of the ladder stand **100** shown in FIG. **4**. FIG. **6** is a detailed view of another portion of the ladder stand **100** shown in FIG. **4**. With reference to FIGS. **4-6**, embodiments of the present technology include methods of installing a ladder stand against a support structure.

In some embodiments, a user raises the ladder portion **110** and the seating portion **115** to lean against the support structure **105**. The user may pass a first end **400** of the first upper support strap **120a** and a first end **405** of the second upper support strap **120b** around the support structure **105**. The user may then connect the first end **400** of the first upper support strap **120a** to the first end **405** of the second upper support strap **120b** using the connecting device **210**. In some embodiments, the connecting device **210** may be a carabiner, a hook, a knot tying the first ends **400, 405** together (directly or with an intermediate tying element), or another suitable device to join the first ends **400, 405**. It is preferable that the connecting device **210** is a releasable device, but in other embodiments, it may be permanent (for example, if installation of the ladder stand **100** is intended to be permanent). When the first end **400** of the first upper support strap **120a** is connected to the first end **405** of the second upper support strap **120b**, the support structure **105** is positioned between the first upper support strap **120a**, the second upper support strap **120b**, and the primary blade element **215a**.

To tighten the connected upper support straps **120a, 120b** against the support structure **105**, a user may pull a second end **410** of the first upper support strap **120a** and a second end **415** of the second upper support strap **120b**. By pulling the second ends **410, 415** of the upper support straps **120a, 120b**, the upper support straps **120a, 120b** are put under tension, the connecting device **210** moves upward along the support structure **105**, and eventually becomes generally level with the primary blade element **215a** (for example, the connecting device **210** and the first ends **400, 405** move from a position shown in FIGS. **4** and **6**, to a position shown in FIGS. **1** and **2**). Continued tension on the upper support straps **120a, 120b** draws the primary blade element **215a** against or into the support structure **105** to provide a secure connection between the ladder stand **100** and the support structure **105**.

In some embodiments, to assist a user in pulling down on the second ends **410, 415** of the upper support straps **120a, 120b** to apply tension, the second ends **410, 415** may be connected to each other using a connecting device **420**, which may be a connecting device such as a carabiner, a hook, a knot tying the second ends **410, 415** together (directly or with an intermediate tying element), or another suitable device to join the second ends **410, 415**. It is preferable that the connecting device **420** is a releasable device, but in some embodiments, it may be permanent. In some embodiments, a cord **425** may be connected to the second ends **410, 415** of the upper support straps **120a, 120b** such that it hangs near the ground (at a lower height, below the platform **117**). Such a cord **425** may be positioned and configured to allow a user to reach the cord **425** to aid in pulling the upper support straps **120a, 120b** while tensioning the upper support straps **120a, 120b** (for example, by pulling the cord **425** downward). In some embodiments, when the upper support straps **120a, 120b** are in a tensioned configuration, or the connecting device **210** attached to the first ends

6

**400, 405** of the upper support straps **120a, 120b** has generally reached the height of the primary blade element **215a**, a user may disconnect the connecting device **420** to remove the cord **425** and separate the second ends **410, 415** of the upper support straps **120a, 120b**. Each of the second ends **410, 415** of the upper support straps **120a, 120b** may be passed through or into a corresponding tensioning device **300** on the ladder portion **110**, and the upper support straps **120a, 120b** may be further tensioned using the tensioning devices **300**. In some embodiments, the second ends **410, 415** of the upper support straps **120a, 120b** may be passed into the same tensioning device **300** to tension the upper support straps **120a, 120b**.

Returning to FIG. **1**, which illustrates the upper support straps **120a, 120b** in a tensioned configuration, the upper support straps **120a, 120b** may be tensioned individually and to different levels of tension (for example, when each upper support strap **120a, 120b** is tightened by its own corresponding tensioning device **300**, as illustrated in FIG. **1**). Preferably, the upper support straps **120a, 120b** do not cross each other on the second side **214** (the back side) of the support structure **105**, opposite the remainder of the ladder stand **100**. An advantage of embodiments of the present technology is that the separate upper support straps **120a, 120b** (which may only be connected to each other on the second side **214** (the back side) of the support structure **105** opposite the remainder of the ladder stand **100** via the connecting device **210** at the first ends **400, 405**) can be tensioned individually to adapt to support structures **105** (such as trees) that have uneven shapes. A user may tighten each support strap **120a, 120b** independently from the other to ensure a desired level of contact between the primary blade element **215a** and the support structure **105**. More specifically, trees are not uniform, and embodiments of the present technology avoid problems with existing tree stands that often have uneven contact with support structures.

Another advantage of ladder stands configured in accordance with embodiments of the present technology is the ability to pass over or around obstructions extending from support structures **105**, such as tree branches. For example, FIG. **1** shows an obstruction **430** extending from the support structure **105**. Because the upper support straps **120a, 120b** are separable from each other and connectable using the connecting device **210**, a user may toss (or otherwise pass) one or both first ends **400, 405** of the upper support straps **120a, 120b** over the obstruction **430** to position both first ends **400, 405** on the same side of the obstruction. In some embodiments, a user may hoist one or both first ends **400, 405** over the obstruction using the stabilizer bar **125** as a tool. When the first ends **400, 405** are on the same side of the obstruction **430**, the first ends **400, 405** may be connected to each other using the connecting device **210**, after which a user may tension the upper support straps **120a, 120b** to pull the connecting device **210** and the first ends **400, 405** into position (such as the position illustrated in FIG. **1**), bypassing the obstruction **430**.

With reference to FIG. **6**, a tensioning device **300** may connect first ends **600, 605** of the lower support straps **120c, 120d** such that the lower support straps **120c, 120d** wrap around the support structure **105**. The tensioning device **300**, which may be similar to other tensioning devices described herein, may tighten the lower support straps **120c, 120d** to draw the stabilizer bar **125** toward the support structure **105**. With reference to FIGS. **1** and **4**, the stabilizer bar **125** passes from the ladder portion **110** to the support structure **105** to further stabilize the ladder stand **100**.

Some embodiments of the present technology include a kit of parts for assembling or installing a ladder stand. Kits of parts in accordance with embodiments of the present technology include some or all of a variety of the elements of a ladder stand described herein. For example, a kit of parts may include a ladder portion, a seating portion, a plurality of straps, one or more connecting devices, one or more tensioning devices, one or more cords, a stabilizer bar, or other components.

Ladder stands configured in accordance with embodiments of the present technology improve safety by facilitating a stable attachment to support structures before a user climbs the ladder stand to complete assembly (completing assembly may include adding further support straps to draw a secondary blade element **215b** against or into the support structure). Ladder stands configured in accordance with embodiments of the present technology further facilitate stability in the installation process by applying a generally horizontal force against or into the support structure, rather than a generally downward force.

From the foregoing, it will be appreciated that specific embodiments of the presently disclosed technology have been described herein for purposes of illustration, but that various modifications may be made without deviating from the scope of the technology. For example, ladder stands configured in accordance with embodiments of the present technology may include more or fewer support straps, they may omit a chair (instead having a generally bare platform supported on the ladder portion), they may have another seating, standing, or housing structure on the platform instead of (or in addition to) a chair portion, they may be foldable, collapsible, or able to be disassembled, they may be made of various materials (metals, plastics, composites, or other materials), they may include additional support structure, or they may include steps or stairs instead of ladder rungs. Although a chair with arms and a back is illustrated in the figures, the term “chair” is understood to include a bench without arms or a back, or another suitable seating surface. Although preferred embodiments of the present technology include upper support straps **120a**, **120b** that are separable from each other and connectable using the connecting device **210** (in order to avoid obstructions, for example), in some embodiments, the upper support straps **120a**, **120b** may be combined in a single integral support strap. For example, a single integral support strap may extend between free ends that correspond to the first ends **400**, **405**, which may be connected together using a connecting device **210**, and then the strap may be tightened in a manner similar to the separable upper support straps **120a**, **120b** (e.g., by passing the single support strap through one or more tightening devices **300**). In some embodiments, a single integral support strap may extend between free ends that correspond to the second ends **410**, **415** (such that the strap may be continuous as it wraps around the tree), although such a single integral support strap may not provide the advantages of separate upper support straps **120a**, **120b** (such as the ability to pass over or around an obstruction).

Certain aspects of the technology described in the context of particular embodiments may be combined or eliminated in other embodiments. Further, while advantages associated with certain embodiments of the presently disclosed technology have been described in the context of those embodiments, other embodiments may also exhibit such advantages, and not all embodiments need necessarily exhibit such advantages to fall within the scope of the technology.

Accordingly, the disclosure and associated technology can encompass other embodiments not expressly shown or described herein.

What is claimed is:

1. A ladder stand comprising:

a ladder portion;

a platform supported on the ladder portion;

a plurality of support straps configured to hold the ladder stand against a support structure, the plurality of support straps comprising a first upper support strap having a first end and a second end, and a second upper support strap having a first end and a second end, wherein each of the first upper support strap and the second upper support strap is connected to the ladder stand and configured to wrap partially around the support structure;

a connecting device configured to connect the first end of the first upper support strap to the first end of the second upper support strap, wherein when the connecting device connects the first end of the first upper support strap to the first end of the second upper support strap, the first upper support strap and the second upper support strap together are configured to wrap around the support structure;

a first tensioning device supported by the ladder portion and configured to receive the second end of the first upper support strap;

a second tensioning device supported by the ladder portion and configured to receive the second end of the second upper support strap; and

a blade element supported by the platform, wherein when the ladder stand is positioned against the support structure, the blade element is positioned to press against or into the support structure;

wherein the first tensioning device is operable to tighten the first upper support strap and the second tensioning device is operable to tighten the second upper support strap to draw the blade element against or into the support structure.

2. The ladder stand of claim 1, further comprising a stabilizer bar having a first end and a second end, wherein the first end is connected to the ladder portion and the second end is configured to be pressed against the support structure.

3. The ladder stand of claim 2, wherein the second end of the stabilizer bar comprises one or more spikes configured to press into the support structure.

4. The ladder stand of claim 2, further comprising a third tensioning device, wherein:

the plurality of support straps comprises two lower support straps;

each lower support strap is connected to the second end of the stabilizer bar;

the lower support straps are configured to wrap at least partially around the support structure to be connected to each other; and

the lower support straps are connected to each other with a ratchet device configured to tighten the lower support straps around the support structure to pull the second end of the stabilizer bar against the support structure or into the support structure.

5. The ladder stand of claim 1, wherein each of the first upper support strap and the second upper support strap passes through one or more strap supports attached to the ladder portion or through a rail of the ladder portion.

9

6. The ladder stand of claim 5, wherein each of the first upper support strap and the second upper support strap passes through one or more strap supports attached to the platform.

7. The ladder stand of claim 1, wherein the blade element, the first upper support strap, and the second upper support strap are positioned to be generally parallel when the tensioning devices apply tension to the first upper support strap and the second upper support strap, and wherein the blade element is positioned and configured to apply a generally horizontal force to the support structure.

8. The ladder stand of claim 1, wherein the first upper support strap and the second upper support strap do not cross over each other.

9. The ladder stand of claim 1, wherein the connecting device is releasable, and wherein the connecting device comprises a carabiner or directly tying the first end of the first upper support strap to the first end of the second upper support strap.

10. The ladder stand of claim 1, wherein the blade element is a first blade element and the ladder stand further comprises a chair supported on the platform and a second blade element attached to the chair.

11. A kit of parts for assembling or installing a ladder stand, comprising:

- a ladder portion;
- a platform configured to be supported on the ladder portion;
- a chair configured to be supported on the platform;
- a blade element configured to be attached to the platform;

10

a first strap having a first end and a second end, the first strap configured to extend along the platform and configured to wrap around a support structure;

a second strap having a first end and a second end, the second strap configured to extend along the platform and configured to wrap around the support structure; and

a releasable connecting device configured to connect the first end of the first strap to the first end of the second strap.

12. The kit of claim 11 wherein the first and second straps are configured to extend along the ladder portion and the ladder portion is configured to receive the first and second straps with one or more strap supports.

13. The kit of claim 11, further comprising a stabilizer bar having a first end and a second end, wherein the first end is configured to be connected to the ladder portion and the second end is configured to be pressed against the support structure.

14. The kit of claim 11, further comprising a first tensioning device configured to apply tension to the first strap, and a second tensioning device configured to apply tension to the second strap, wherein the first and second tensioning devices comprise ratchet devices.

15. The kit of claim 11, wherein the releasable connecting device is a first releasable connecting device, the kit further comprising a cord and a second releasable connecting device, wherein the second releasable connecting device is configured to connect the cord to the second end of the first strap and the second end of the second strap.

\* \* \* \* \*