



US011612390B2

(12) **United States Patent**
Favreau et al.

(10) **Patent No.:** **US 11,612,390 B2**
(45) **Date of Patent:** **Mar. 28, 2023**

(54) **SUTURING CLOSURE SCOPE WITH ALTERNATIVE NEEDLE ORIENTATION**

(71) Applicant: **Boston Scientific Scimed, Inc.**, Maple Grove, MN (US)

(72) Inventors: **John T. Favreau**, Spencer, MA (US);
Ethan Miller, Ashland, MA (US);
Peter L. Dayton, Brookline, MA (US);
Shawn Ryan, Littleton, MA (US);
Morgan Zhu, Somerville, MA (US);
Shaun D. Comee, Fiskdale, MA (US);
James J. Scutti, Arlington, MA (US)

(73) Assignee: **Boston Scientific Scimed, Inc.**, Maple Grove, MN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 392 days.

(21) Appl. No.: **17/010,075**

(22) Filed: **Sep. 2, 2020**

(65) **Prior Publication Data**

US 2021/0068812 A1 Mar. 11, 2021

Related U.S. Application Data

(60) Provisional application No. 62/896,998, filed on Sep. 6, 2019.

(51) **Int. Cl.**

A61B 17/04 (2006.01)
A61B 1/05 (2006.01)
A61B 1/06 (2006.01)
A61B 17/00 (2006.01)

(52) **U.S. Cl.**

CPC **A61B 17/0469** (2013.01); **A61B 1/05** (2013.01); **A61B 1/0661** (2013.01); **A61B 2017/0023** (2013.01)

(58) **Field of Classification Search**

CPC **A61B 17/0469**; **A61B 2017/0023**; **A61B 1/05**; **A61B 1/0661**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,709,694 A * 1/1998 Greenberg A61B 17/0483
606/147
5,954,733 A * 9/1999 Yoon A61B 18/1445
606/147
5,984,932 A * 11/1999 Yoon A61B 17/0469
606/147
5,993,466 A * 11/1999 Yoon A61B 18/1445
606/147
6,086,601 A * 7/2000 Yoon A61B 17/062
606/147
6,159,224 A * 12/2000 Yoon A61B 18/1445
606/147

(Continued)

FOREIGN PATENT DOCUMENTS

WO 2018046822 A1 3/2018

OTHER PUBLICATIONS

International Search Report and Written Opinion for the International Patent Application No. PCT/US2020/048995, dated Dec. 10, 2020, 16 pages.


Primary Examiner — Phong Son H Dang

(74) *Attorney, Agent, or Firm* — Seager, Tufte & Wickhem, LLP

(57) **ABSTRACT**

The present disclosure relates generally to the field of medical devices. In particular, the present disclosure relates to single-use endoscopic medical devices with integrated and purpose-built functionality.

7 Claims, 6 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

9,427,226	B2 *	8/2016	Martin	A61B 17/0482
9,649,107	B2 *	5/2017	Brecher	A61B 17/06066
9,675,339	B2 *	6/2017	Brecher	A61B 17/0469
9,867,608	B1 *	1/2018	Shelton, IV	A61B 17/0469
10,595,855	B2 *	3/2020	Malkowski	A61B 17/0469
10,939,909	B2 *	3/2021	Zeiner	A61B 17/06114
2002/0120290	A1	8/2002	Green	
2010/0081875	A1	4/2010	Fowler et al.	
2011/0152891	A1	6/2011	McLawhorn et al.	
2011/0313433	A1 *	12/2011	Woodard, Jr.	A61B 17/0469 606/145

* cited by examiner




FIG. 1A








FIG. 1B








FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 6A




FIG. 6B




FIG. 6C

1

SUTURING CLOSURE SCOPE WITH ALTERNATIVE NEEDLE ORIENTATION

PRIORITY

This application claims the benefit of priority under 35 USC § 119 to U.S. Provisional Patent Application Ser. No. 62/896,998, filed Sep. 6, 2019, which is incorporated by reference herein in its entirety and for all purposes.

FIELD

The present disclosure relates generally to the field of medical devices. In particular, the present disclosure relates to endoscopic medical devices with integrated and purpose-built functionality.

BACKGROUND

Multi-purpose endoscopes include one or more working channels to support a variety of medical instruments designed to perform a specific/dedicated function under direct visualization. Due at least in part to their multi-purpose functionality, these endoscopes tend to be somewhat large/bulky and lack an intrinsic (e.g., purpose-built) ability to treat and/or manipulate tissues independent of the specific medical instrument inserted through their working channel(s). For example, the functionality (e.g., visibility, maneuverability, etc.) of some currently available endoscopic suturing devices designed for use with multi-purpose endoscopes is inherently limited by the requirement that they fit within the limited/standard dimensions of the working channel(s).

A variety of advantageous medical outcomes may therefore be realized by the endoscopic medical devices of the present disclosure.

SUMMARY

In one aspect, the present disclosure relates to an endoscopic medical device comprising an elongate member. The elongate member may define a suture channel and a working channel therethrough. An elongate sheath may be rotatably disposed about the elongate member. A needle passer may extend from a distal end of the elongate sheath. A needle grasper may extend from a distal end of the elongate member. The elongate sheath may be configured to rotate about the elongate member between a first position, a second position and a third position. In the first position, the needle passer may be disposed substantially opposite the needle grasper. In the second position, a first side of the needle passer may be substantially adjacent to a first side of the needle grasper. In the third position, a second side of the needle passer may be substantially adjacent to a second side of the needle grasper.

In the above-described and other embodiments, a suture may be movably disposed within the suture channel and a medical accessory device may be movably disposed within the working channel. A distal end of the suture may be attached to a curved needle. A distal end of the medical accessory device may be configured to extend beyond the distal end of the elongate member to engage a target tissue. In the first position the curved needle may be releasably attached to the needle passer. In the second position the curved needle may be transferred from the needle passer to the needle grasper. In the third position the curved needle may be transferred from the needle grasper to the needle

2

passer. A camera may be disposed on the distal end of the elongate member. A light source may be disposed on the distal end of the elongate member.

In another aspect, the present disclosure relates to a medical device comprising an endoscope. The endoscope may define a suture channel and a working channel therethrough. A working space may be formed within a distal portion of the endoscope. A distal end of the suture channel may open into a first side of the working space. A distal end of the working channel may open into a third side of the working space. A needle passer may be movably disposed within the distal portion of the endoscope. The needle passer may be configured to move between a first position on the first side of the working space and a second position on a second side of the working space.

In the above-described and other embodiments, a suture may be movably disposed within the suture channel and a medical accessory device may be movably disposed within the working channel. A distal end of the suture may be attached to a needle. A distal end of the medical accessory device may be configured to extend into the working space to engage a target tissue. A needle receiver may be disposed within the second side of the working space and configured to receive the needle passer. A camera may be disposed on the third side of the working space. A light source may be disposed on the third side of the working space.

In yet another aspect, the present disclosure relates to an endoscopic medical device comprising an elongate member. A suturing arm may extend from a distal end of the elongate member. The suturing arm may include first and second projections defining a working space therebetween. A suture channel may extend through the elongate member and through a first projection of the suturing arm. A working channel may extend through the elongate member and through a portion of the suturing arm between the first and second projections. A curved needle passer may be movably disposed within the suturing arm. The curved needle passer may be configured to rotate within the suturing arm between a first position and a second position.

In the above-described and other embodiments, a suture may be movably disposed within the suture channel and a medical accessory device may be movably disposed within the working channel. A distal end of the suture may be attached to a curved needle. A distal end of the medical accessory device may be configured to extend beyond a distal end of the first and second projections to engage a target tissue. The curved needle passer may be disposed within the first projection of the suturing arm when in the first position. The curved needle passer may be disposed within the second projection of the suturing arm when in the second position. A camera may be disposed on the distal end of the elongate member.

In yet another aspect, the present disclosure relates to an endoscopic medical device comprising an elongate member. The elongate member may define a suture channel and a working channel therethrough. A needle passer may extend from a distal end of the elongate member. The needle passer may be pivotally attached to a distal end of the elongate member. A needle grasper may extend from a distal end of the elongate member. The needle passer may be configured to pivot between a first position in which a distal end of the needle passer and a distal end of the needle grasper are separated by a first distance and a second position in which the distal end of the needle passer and the distal end of the needle grasper are separated by a second distance, wherein the first distance is greater than the second distance.

In the above-described and other embodiments, a suture may be movably disposed through the suture channel and a medical accessory device may be movably disposed within the working channel. A distal end of the suture may be attached to a needle. A distal end of the medical accessory device may be configured to extend beyond a distal end of the needle passer and the needle grasper to engage a target tissue.

In yet another aspect, the present disclosure relates to an endoscopic medical device comprising an elongate member. The elongate member may define a suture channel and a working channel therethrough. A suturing arm may extend from a distal end of the elongate member. The distal end of the elongate member may define a first side of a working space. A distal portion of the suturing arm may extend distally of a distal end of the elongate member to define a second side of the working space. The working space may extend between the first and second sides. A needle passer may be movably disposed within a distal portion of the elongate member. The needle passer may be configured to move between a first position on the first side of the working space and a second position on the second side of the working space.

In the above-described and other embodiments, a suture may extend through the suture channel and a medical accessory device may be movably disposed within the working channel. A distal end of the suture may be attached to a needle. A distal end of the medical accessory device may be configured to extend beyond the distal end of the elongate member to engage a target tissue. A needle receiver may be disposed within the portion of the suturing arm extending distally of the distal end of the elongate member.

BRIEF DESCRIPTION OF THE DRAWINGS

Non-limiting embodiments of the present disclosure are described by way of example with reference to the accompanying figures, which are schematic and not intended to be drawn to scale. In the figures, each identical or nearly identical component illustrated is typically represented by a single numeral. For purposes of clarity, not every component is labeled in every figure, nor is every component of each embodiment shown where illustration is not necessary to allow those of ordinary skill in the art to understand the disclosure. In the figures:

FIGS. 1A-1B provide perspective views of an endoscopic medical device, according to one embodiment of the present disclosure.

FIGS. 2A-2B provide perspective views of the endoscopic medical device of FIGS. 1A-1B in use, according to one embodiment of the present disclosure.

FIGS. 3A-3B provide perspective views of an endoscopic medical device, according to one embodiment of the present disclosure.

FIGS. 4A-4B provide perspective views of an endoscopic medical device, according to one embodiment of the present disclosure.

FIGS. 5A-5C provide perspective views of an endoscopic medical device, according to one embodiment of the present disclosure.

FIGS. 6A-6C provide perspective views of an endoscopic medical device, according to one embodiment of the present disclosure.

DETAILED DESCRIPTION

The present disclosure is not limited to the particular embodiments described herein. The terminology used herein

is for the purpose of describing particular embodiments only, and is not intended to be limiting beyond the scope of the appended claims. Unless otherwise defined, all technical terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which the disclosure belongs.

Although embodiments of the present disclosure are described with specific reference to single-use endoscopic medical devices with an integrated and purpose-built tissue needle assembly for suturing tissues, it should be appreciated that such endoscopic medical devices may include a variety of end effectors (e.g., scissors, scalpels, clip deployment members, graspers, biopsy needles, injecting needles, staplers, etc.) configured to manipulate tissues in a variety of body lumens, body passageways, organs and the like.

As used herein, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “comprises” and/or “comprising,” or “includes” and/or “including” when used herein, specify the presence of stated features, regions, steps, elements and/or components, but do not preclude the presence or addition of one or more other features, regions, integers, steps, operations, elements, components and/or groups thereof.

As used herein, the term “distal” refers to the end farthest away from the medical professional or physician when introducing a device into a patient, while the term “proximal” refers to the end closest to the medical professional or physician when introducing a device into a patient.

Referring to FIGS. 1A-1B, in one embodiment, a distal end of an endoscopic medical device **100** (e.g., suture device, single-use purpose-built suturing device, etc.) of the present disclosure may include an elongate member **110** (e.g., elongate tubular member, flexible elongate tubular member, endoscope, etc.) and an elongate sheath **116** (e.g., flexible elongate sheath, outer sheath, over-tube, etc.) rotatably disposed about (e.g., around) an outer surface of the elongate member **110**. The disclosure pertains to medical devices, e.g., endoscopes, gastroscopes, bronchoscopes, colonoscopes, ureteroscopes, and the like, having integrated features for acquiring, manipulating, and closing openings in target tissue. Although single-use endoscopes are described herein, it is understood that embodiments of the present disclosure may be included in reusable medical devices such as endoscopes as well.

In various embodiments, as discussed below, the elongate sheath **116** may be sufficiently rigid (e.g., include sufficient columnar strength and/or torsional rigidity) that rotational forces exerted on a proximal portion thereof (e.g., a portion of the elongate sheath extending outside a patient) may be efficiently and effectively translated to the distal end of the elongate sheath **116** to support a rotational (e.g., side-to-side, clockwise and counterclockwise) suturing motion within a body passage or lumen. A first channel **112** (e.g., suture channel, dedicated suture channel, etc.) and a second channel **114** (e.g., working channel, dedicated working channel, etc.) may extend through a longitudinal axis of the elongate member **110**. A needle passer **118** (e.g., shuttle, etc.) may extend from a distal end of the elongate sheath **116** and a needle grasper **120** may extend from a distal end of the elongate member **110**. In various embodiments, the needle passer **118** may be attached to or integrally formed with a distal end of the elongate sheath **116** and the needle grasper **120** may be attached to or integrally formed with a distal end of the elongate member **110**. The elongate sheath **116** may be configured to rotate about a full/complete or nearly full/complete outer dimension (e.g., outer circumference) of

the elongate member **110** between a first position, a second position and a third position. In the first position, the needle passer **118** may be disposed/positioned substantially opposite the needle grasper **120**, e.g., the needle passer **118** and needle grasper **120** may be separated by up to approximately 180 degrees relative to an outer dimension of a distal end of the respective elongate member **110** and elongate sheath **116**. In the second position, a first side **118a** (e.g., first edge) of the needle passer **118** may be substantially adjacent to (e.g., abutting or in close proximity to) a corresponding first side **120a** (e.g., first edge) of the needle grasper **120**. In the second position, a second side **118b** (e.g., second edge) of the needle passer **118** may be substantially adjacent to (e.g., abutting or in close proximity to) a corresponding second side **120b** (e.g., second edge) of the needle grasper **120**.

In one embodiment, a suture **122** (e.g., filament, thread, etc.) may extend through the suture channel **112** and a medical accessory device **124** may extend through the working channel **114**. A distal end of the suture **122** may be attached to (e.g., glued, tied, etc.) a curved needle **126** releasably attached to the needle passer **118**. For example, the curved needle **126** may be releasably housed/held within an aperture **119** extending through the first and second sides **118a**, **118b** of the needle passer **118**. As discussed below, the needle grasper **120** may be configured to receive the curved needle **126** from the needle passer **118** (e.g., when the elongate sheath **116** is rotated in a first direction about the elongate member **110**) and to return the curved needle **126** to the needle passer **118** (e.g., when the elongate sheath **116** is rotated in a second direction about the elongate member **110**). For example, the curved needle **126** may be releasably received within an aperture **121** extending through the first and second sides **120a**, **120b** of the needle grasper **120** when the first sides **118a**, **120a** of the respective needle passer **118** and needle grasper **120** are in the second position. The needle passer **118** may be slightly offset (e.g., bent, angled, etc.), so that the curved needle **126** aligns with the aperture **121** of the needle grasper **120**.

In one embodiment, the medical accessory device **124** may be movably (e.g., slidably and/or rotatably, etc.) disposed within the working channel **114** of the elongate member **110** such that a tissue engaging element **125** attached to or integrally formed with a distal end of the medical accessory device **124** may extend beyond a distal end of the elongate member **110**. By way of non-limiting example, the tissue engaging element **125** may include a spiral shape (e.g., helical, corkscrew, grasper, etc.) configured to penetrate (e.g., embed, engage, etc.) and reversibly immobilize a portion of a target tissue relative to the distal ends of the elongate member **110** and the elongate sheath **116**. The medical accessory device **124**, with the tissue engaging element **125** reversibly engaged with the target tissue, may be proximally retracted to pull a portion of the target tissue into a space (e.g., working space) between the needle passer **118** and needle grasper **120**, e.g., with the elongate sheath **116** in the first position relative to the elongate member **110**. It is understood that the distal end of the medical device **100** may be operable via one or more mechanisms at a proximal end of the medical device, for example, at a handle. A medical professional may articulate the elongate sheath **116**, medical accessory device **124**, needle passer **118**, or needle grasper **120**, or combinations thereof, to acquire and suture, or otherwise manipulate tissue via endoscope handle knobs or additional articulation elements.

Referring to FIGS. 2A-2B, in use and by way of example, the distal end of an endoscopic medical device **100** of the

present disclosure may be advanced through a body lumen or passage and the distal ends of the elongate member **110** and elongate sheath **116** positioned adjacent to a target tissue (e.g., a tissue which may include a portion to be sutured). The medical accessory device **124** may then be distally advanced through the working channel **114** to position the tissue engaging element **125** in contact with a portion of the target tissue. The medical accessory device **124** may then be rotated within the working channel **114** (e.g., in a clockwise or counterclockwise direction) to reversibly embed/engage the tissue engaging element **125** with the target tissue. The medical accessory device **124** may then be proximally retracted within the working channel **114** to pull/draw a portion of the target tissue into the space between the needle passer **118** and the needle grasper **120**. The elongate sheath **116** may then be rotated (e.g., by a medical professional rotating a proximal end of the elongate sheath) in a first direction (e.g., clockwise) about the outer surface of the elongate member **110** from the first position to the second position. In various embodiments, as the needle passer **118** moves to the second position (e.g., the first side of the needle passer is adjacent to or substantially abutting or adjacent to the corresponding first side of the needle grasper), a sharpened end of the curved needle **126** and a portion of the suture **122** attached thereto may pass through the target tissue and be received within (e.g., grasped) by the needle grasper (e.g., the curved needle **126** may extend into/through the aperture **121**). The elongate sheath **116** may then be rotated in the second direction (e.g., counterclockwise) about the outer surface of the elongate member **110** to return the elongate sheath **116** to the first position, thereby transferring the curved needle **126** to (e.g., releasing the curved needle within) the needle grasper **120**. From the first position, the elongate sheath **116** may then be further rotated in the second direction (e.g., counterclockwise) such that the second side of the needle passer **118** is substantially abutting or adjacent to the second side of the needle grasper **120**. The sharpened end of the curved needle **126** may be received within (e.g., grasped) by the needle passer **118** (e.g., the curved needle may extend into/through aperture **119**), thereby transferring (e.g., releasing, returning) the curved needle **126** to the needle passer **118**. The elongate sheath **116** may then be rotated in the first direction (e.g., clockwise) about the outer surface of the elongate member **110** to return to the first position and the tissue engaging element **125** disengaged from the target tissue (e.g., by rotating the medical accessory device in a direction opposite the direction used to engage the target tissue).

In various embodiments, with a first section/length of the suture **122** extending through the target tissue, the distal end of the endoscopic medical device **100** may be repositioned within the body lumen or passage (e.g., proximally retracted or distally advanced) to reposition the needle passer **118** and needle grasper **120** adjacent to a different portion/section of the target tissue. The steps outlined above may then be repeated to suture a second portion of the target tissue. These steps may be performed as many times as necessary to suture (e.g., close) an entire portion/length of the target tissue and the endoscopic medical device **100** removed from within the patient.

In various embodiments, one or more imaging devices, or cameras **128** and one or more illumination devices, or light sources **130** may be disposed on or within the distal end of the elongate member **110** to allow the medical professional to visualize the target tissue and properly manipulate the elongate sheath (e.g., needle passer), elongate member (e.g., needle grasper), curved needle and medical accessory

device. It should be appreciated that the peripheral location of the needle passer **118** and needle grasper **120** relative to the respective distal ends of the elongate sheath **116** and elongate member **110** may optimize/maximize visibility of the target tissue as well as the working area within the body lumen or passage. In various embodiments, the elongate member **110** may include one or more additional working channels (not shown) configured to receive additional medical devices, end effectors and/or accessories within the working area. In addition, or alternatively, an elevator (not shown) may be disposed within a distal portion of any of the disclosed working channels to control placement/positioning of the endoscopic medical devices (including the tissue engaging element **125**) within the body lumen or passage.

Referring to FIGS. 3A-3B, in one embodiment, a distal end of an endoscopic medical device **200** (e.g., suture device, single-use purpose-built suturing device, etc.) of the present disclosure may include an elongate member **210** (e.g., elongate tubular member, flexible elongate tubular member, endoscope, etc.). A working space **216** (e.g., working area, etc.) may be defined by a distal portion of the elongate member **210**, e.g., along one side of a longitudinal axis of the elongate member. In various embodiments, the side of the elongate member **210** within which the working space **216** is formed may be referred to as a “bottom” side of the elongate member **210**. The working space **216** may include a first side **216a** (e.g., a proximal side defining a proximal surface/wall, etc.), a second side **216b** (e.g., a distal side defining a distal surface/wall) and a third side **216c** (e.g., a top side defining an upper surface/wall). A first channel **212** (e.g., suture channel, dedicated suture channel, etc.) and a second channel **214** (e.g., working channel, dedicated working channel, etc.) may extend through the elongate member **210**, e.g., through the longitudinal axis of the elongate member. A distal end of the first channel **212** may be coextensive with the first side **216a** of the working space **216** (e.g., the first channel may open into the working space through the proximal surface/wall) and a distal end of the second channel **214** may be coextensive with the third side **216c** of the working space (e.g., the second channel **214** may open into the working space through the upper surface/wall).

A needle passer **218** (e.g., shuttle, etc.) may be movably disposed within the distal portion of the elongate member **210** and configured to move proximally and distally (e.g., back-and-forth) across the working space **216**. In various embodiments, the needle passer **218** may be configured to move distally from a first position on the first side **216a** of the working space **216** to a second position on the second side **216b** of the working space and proximally from the second side **216b** of the working space **216** to the first side **216a** of the working space **216**.

A needle receiver **220** may be disposed on or within the second side **216b** (e.g., distal wall) of the working space **216** and configured to receive the needle passer **218**, e.g., when the needle passer **218** is in the second position. In various embodiments, the needle receiver **220** may include a slot or recessed portion formed within the second side **216b** of the working space **216** and substantially aligned with the opening of the first channel **212**, e.g., the slot or recessed portion and the distal end/opening of the first channel **212** may be disposed on substantially opposite sides of the working space **216**.

In one embodiment, a suture **222** (e.g., filament, thread, etc.) may extend through the first channel **212** and a medical accessory device **224** may extend through the second channel **214**. A distal end of the suture **222** may be attached to

(e.g., glued, tied, etc.) a needle **226** engaged by (e.g., attached to) the needle passer **218**.

In one embodiment, the medical accessory device **224** may be movably (e.g., slidably and/or rotatably, etc.) disposed within the second channel **214** of the elongate member **210** such that a tissue engaging element **225** (e.g., attached to or integrally formed with a distal end of the medical accessory device **224**) may extend into and beyond an opening of the working space **216**. By way of non-limiting example, the tissue engaging element **225** may include a spiral (e.g., helical, corkscrew, grasper, etc.) shape configured to penetrate (e.g., embed, engage, etc.) and reversibly immobilize a portion of a target tissue. The medical accessory device **224**, with the tissue engaging element **225** reversibly engaged with the target tissue, may be proximally retracted to pull a portion of the target tissue into the working space **216** and between the needle passer **218** and needle receiver **220**, e.g., with the needle passer **218** in the first position. It is understood that the distal end of the medical device **200** may be operable via one or more mechanisms at a proximal end of the medical device, for example, at a handle. A medical professional may articulate the elongate member **210**, medical accessory device **224**, needle passer **218**, or needle receiver **220**, or combinations thereof, to acquire and suture, or otherwise manipulate tissue via endoscope handle knobs or additional articulation elements.

In use, and by way of example, an endoscopic medical device **200** of the present disclosure may be advanced through a body lumen or passage and the working space **216** positioned adjacent to (e.g., over, above, etc.) a target tissue (e.g., a tissue which may include a portion to be sutured). The medical accessory device **224** may then be distally advanced through the second channel **214** to position the tissue engaging element **225** beyond an opening of the working space **216** and in contact with a portion of the target tissue. The medical accessory device **224** may then be rotated within the second channel **214** (e.g., in a clockwise or counterclockwise direction) to reversibly embed/engage the tissue engaging element **225** with the target tissue. The medical accessory device **224** may then be proximally retracted within the second channel **214** to pull/draw a portion of the target tissue into the working space **216** and between the needle passer **118** (e.g., in the first position) and the needle receiver **220**. The needle passer **218**, with a needle **226** attached thereto, may then be moved from the first position to the second position such that the needle passer **218** moves distally across the working space **216** and is received within (e.g., extends into) the needle receiver **220**. In various embodiments, as the needle passer **218** moves to the second position, a sharpened end of the needle **226** and a portion of the suture **222** attached thereto may pass through the target tissue immobilized by the tissue engaging element **225** within the working space **216**. The tissue engaging element **225** may then be disengaged from the target tissue (e.g., by rotating the medical accessory device in a direction opposite the direction used to engage the target tissue). The needle passer **218**, with the needle **226** attached thereto, may then be moved from the second position to the first position such that the needle passer **218** moves proximally across the working space **216** and returns to the first position, e.g., the initial/starting position.

In various embodiments, with a first section/length of the suture **222** extending through the target tissue, the endoscopic medical device **200** may be repositioned within the body lumen or passage (e.g., proximally retracted or distally advanced) to position the working space **216** adjacent to a

different portion/section of the target tissue. The steps outlined above may then be repeated to suture a second portion of the target tissue. These steps may be performed as many times as necessary to suture (e.g., close) an entire portion of the target tissue and the endoscopic medical device **200** removed from within the patient.

Referring again to FIG. 3A, in one embodiment, the second channel **214** may include a first portion (e.g., first branch) which extends into the working space **216** (as discussed above) and a second portion (e.g., second branch) that extends through the remaining longitudinal portion of the elongate member **210**, e.g., such that an opening of the second portion of the second channel is coextensive with a distal end of the elongate member **210**. In various embodiments, an elevator **227** may be disposed at or near a junction of the first and second portions of the second channel **214**. A medical professional may move/actuate the elevator **227** as necessary to direct the medical accessory device **224** through the desired portion of the second channel **214**. For example, the elevator **227** may be moved to a first position in which the second portion of the second channel **214** remains accessible (e.g., not blocked or obstructed) to allow the medical accessory device **224** to extend beyond the distal end of the elongate member **210**, e.g., to examine or manipulate a target tissue beyond a distal end of the endoscopic medical device **200**. Alternatively, the elevator **227** may move to a second position within the second channel **214** to direct/deflect the medical accessory device **224** into the working space **216** (as discussed above). As above, in addition to directing the medical accessory device **224** through the desired portion of the second channel **214**, the elevator **227** may control placement/positioning of the medical accessory device (including the tissue engaging element **225**) within the working space **216** and/or beyond an opening of the working space **216**.

In various embodiments, one or more imaging devices, or cameras **228** and one or more illumination devices, or light sources **230** may be disposed on or within the distal end of the elongate member **210** to allow the medical professional to visualize the body lumen and/or target tissue, e.g., to navigate through the body lumen and/or properly position the working space **216** relative to the target tissue. In various additional embodiments, one or more additional cameras **229** and one or more additional light sources **231** may be disposed on or within the second side **216b** or third side **216c** (e.g., upper surface) of the working space **216** and/or adjacent to the needle receiver **220**, e.g., to properly position the working space relative to the target tissue and manipulate the target tissue. It should be appreciated that the peripheral location the needle passer **218** and needle receiver **220** on the first and second sides of the working space **216** may optimize/maximize visibility of the target tissue within the working space. In various additional embodiments, the elongate member **210** may include one or more additional working channels (not shown) configured to receive additional medical devices, end effectors and/or accessories into the working space **216** and/or beyond the distal end of the elongate member **210**.

Referring to FIGS. 4A-4B, in one embodiment, an endoscopic medical device **300** (e.g., suture device, single-use purpose-built suturing device, etc.) of the present disclosure may include an elongate member **310** (e.g., elongate tubular member, flexible elongate tubular member, endoscope, etc.). A suturing arm **316** may extend from a distal end of the elongate member **310**. In various embodiments, the suturing arm **316** may be attached to or integrally formed with a distal end of the elongate member **310**. The suturing arm **316** may

include first and second projections **316a**, **316b** (e.g., first and second fingers or tabs) defining a space or opening (e.g., working space, etc.) therebetween. A first channel **312** (e.g., suture channel, dedicated suture channel, etc.) may extend through a longitudinal axis of the elongate member and through the first projection **316a** of the suturing arm **316**. A second channel **314** (e.g., working channel, dedicated working channel, etc.) may extend through the longitudinal axis of the elongate member **310** and through a portion of the suturing arm **316** between the first and second projections **316a**, **316b**. A distal end of the first channel **312** may be coextensive with (e.g., open into) a first side of the working space (e.g., the suture channel may open into the working space through an end of the first projection **316a**) and a distal end of the second channel **314** may be coextensive with (e.g., open into) the working space between the first and second projections **316a**, **316b**.

A curved needle passer **318** (e.g., shuttle, etc.) may be movably disposed within a third channel **313** of the suturing arm **316** and configured to move along a 360-degree path (e.g., rotate, revolve, etc.) within the suturing arm **316**. In various embodiments, the curved needle passer **318** may be configured to move along the curved path from a first position (e.g., housed within the first projection **316a**), across or through the working space between the first and second projections **316a**, **316b**, to a second position (e.g., housed within the second projection **316b**).

In one embodiment, a suture **322** (e.g., filament, thread, etc.) may extend through the first channel **312** and a medical accessory device **324** may extend through the second channel **314**. A distal end of the suture **322** may be attached to (e.g., glued, tied, etc.) a curved needle **326** attached to the curved needle passer **318**.

In one embodiment, the medical accessory device **324** may be movably (e.g., slidably and/or rotatably, etc.) disposed within the second channel **314** of the elongate member **310** and suturing arm **316** such that a tissue engaging element **325** attached to or integrally formed with a distal end of the medical accessory device **324** may extend beyond a distal end of the suturing arm **316**. By way of non-limiting example, the tissue engaging element **325** may include a spiral (e.g., helical, corkscrew, grasper, etc.) shape configured to penetrate (e.g., embed, engage, etc.) a target tissue and reversibly immobilize a portion of a target tissue relative to a distal end of the suturing arm **316**. The medical accessory device **324**, with the tissue engaging element **325** reversibly engaged with the target tissue, may be proximally retracted to pull a portion of the target tissue into the working space between the first and second projections **316a**, **316b** of the suturing arm **316**. It is understood that the distal end of the medical device **300** may be operable via one or more mechanisms at a proximal end of the medical device, for example, at a handle. A medical professional may articulate the elongate member **310**, medical accessory device **324** or needle passer **318**, or combinations thereof, to acquire and suture, or otherwise manipulate tissue via endoscope handle knobs or additional articulation elements.

In use and by way of example, an endoscopic medical device **300** of the present disclosure may be advanced through a body lumen or passage and the distal ends of the first and second projections **316a**, **316b** of the suturing arm **316** positioned adjacent to a target tissue (e.g., a tissue which may include a portion to be sutured). The medical accessory device **324** may then be distally advanced through the second channel **314**, and through the working space defined by the first and second projections **316a**, **316b**, to position the tissue engaging element **325** in contact with a portion of

the target tissue beyond a distal end of the suturing arm 316. The medical accessory device 324 may then be rotated within the second channel (e.g., in a clockwise or counter-clockwise direction) to reversibly embed/engage the tissue engaging element 325 with the target tissue. The medical accessory device 324 may then be proximally retracted within the second channel 314 to pull/draw a portion of the target tissue into the working space between the first and second projections 316a, 316b. The curved needle passer 318, with a curved needle 326 attached thereto, may then be moved (e.g., rotated) along a curved path from a first position housed within the first projection 316a, across/through the working space between the first and second projection 316a, 316b, to a second position housed within the second projection 316b. In various embodiments, as the curved needle passer 318 moves to the second position, a sharpened end of the curved needle 326 and a portion of the suture 322 attached thereto may pass through the target tissue immobilized by the tissue engaging element 325 within the working space. The tissue engaging element 325 may then be disengaged from the target tissue (e.g., by rotating the medical accessory device in a direction opposite the direction used to engage the target tissue). The curved needle passer 318, and curved needle 326 attached thereto, may then be further moved (e.g., rotated, revolved, etc.) through third channel 313 of the suturing arm 316 to return to the first position (e.g., initial/starting position) housed within the first projection 316a.

In various embodiments, with a first section/length of the suture 322 extending through the target tissue, the endoscopic medical device 300 may be repositioned within the body lumen or passage (e.g., proximally retracted or distally advanced) to position the first and second projections 316a, 316b of the suturing arm 316 adjacent to a different portion/section of the target tissue. The steps outlined above may then be repeated to suture a second portion of the target tissue. These steps may be performed as many times as necessary to suture (e.g., close) an entire portion of the target tissue and the endoscopic medical device 300 removed from within the patient.

In various embodiments, one or more imaging devices, or cameras 328 and one or more illumination devices, or light sources 330 may be disposed on or within the distal end of the elongate member 310, and/or the distal ends of the first and second projections 316a, 316b of the suturing arm 316, to allow the medical professional to visualize the target tissue and properly manipulate the curved needle passer 318 and medical accessory device 324. In various embodiments, the elongate member 310 and/or suturing arm 316 may include one or more additional working channels (not shown) configured to receive additional medical devices, end effectors and/or accessories beyond the distal end of thereof. In addition, or alternatively, an elevator (not shown) may be disposed within a distal portion of any of the disclosed working channels to control placement/positioning of the endoscopic medical devices (including the tissue engaging element 325) within the body lumen or passage.

Referring to FIGS. 5A-5C, in one embodiment, a distal end of an endoscopic medical device 400 (e.g., suture device, single-use purpose-built suturing device, etc.) of the present disclosure may include an elongate member 410 (e.g., elongate tubular member, flexible elongate tubular member, endoscope, etc.). A needle passer 418 (e.g., shuttle, etc.) and a needle grasper 420 may extend from a distal end of the elongate member 410. A first channel 412 (e.g., suture channel, dedicated suture channel, etc.) and a second channel 414 (e.g., working channel, dedicated working channel,

etc.) may extend through a longitudinal axis of the elongate member 410. The first channel 412 may extend along one side of the elongate member 410 such that a distal end of the first channel 412 may be coextensive with (e.g., open into) a distal end of the elongate member 410 adjacent to (e.g., above) the needle passer 418. The second channel 414 may extend along a central portion of the elongate member 410 such that a distal end of the second channel 414 may be coextensive with (e.g., open into) the distal end of the elongate member between 410 the needle passer 418 and the needle grasper 420. In various embodiments, the needle passer 418 may be pivotally attached to the distal end of the elongate member 410 and the needle grasper 420 may be fixedly (e.g., immovably) attached to or integrally formed with the distal end of the elongate member 410. The needle passer 418 may be configured to move (e.g., pivot back-and-forth) between a first position (FIG. 5B) and a second position (FIG. 5C) relative to the stationary needle grasper 420. For example, in the first position, the needle grasper 420 may extend from the distal end of the elongate member 410 substantially parallel to a longitudinal axis of the elongate member 410, and the needle passer 418 may be disposed at an angle relative to the longitudinal axis of the elongate member 410 and/or the needle grasper 420. In the second position, the needle passer 418 may extend from the distal end of the elongate member 410 substantially parallel to a longitudinal axis of the elongate member 410 and parallel to (e.g., alongside) the needle grasper 420. In the first position a distal end of the needle passer 418 may be separated from a distal end of the needle grasper 420 by a first distance and in the second position the distal end of the needle passer 418 may be separated from the distal end of the needle grasper 420 by a second distance, the second distance being less than the first distance.

Alternatively, in one embodiment, both the needle passer 418 and the needle grasper 420 may be pivotally attached to the distal end of the elongate member 410 and configured to move (e.g., pivot back-and-forth) between a first position and a second position. For example, in the first position, the needle grasper 420 and the needle passer 418 may be disposed at an angle relative to the longitudinal axis of the elongate member 410. In the second position, the needle passer 418 and needle grasper 420 may extend from the distal end of the elongate member 410 substantially parallel to a longitudinal axis of the elongate member 410 and parallel to (e.g., alongside) to each other. In the first position a distal end of the needle passer 418 may be separated from a distal end of the needle grasper 420 by a first distance and in the second position the distal end of the needle passer 418 may be separated from the distal end of the needle grasper 420 by a second distance, the second distance being less than the first distance.

In one embodiment, a suture 422 (e.g., filament, thread, etc.) may extend through the first channel 412 and a medical accessory device 424 may extend through the second channel 414. A distal end of the suture 422 may be attached to (e.g., glued, tied, etc.) a needle 426 releasably attached to the needle passer 418. For example, the needle 426 may be releasably held/maintained within an aperture 419 extending through the needle passer 418. As discussed below, the needle grasper 420 may be configured to receive the needle 426 from the needle passer 418 (e.g., within an aperture 421 extending through the needle grasper 420) following a first actuation (e.g., when the needle passer 418 moves/pivots from the first position to the second position a first time) and return the needle to 426 to the needle passer 418 following

a second actuation (e.g., when the needle passer **418** moves/pivot from the first to second position a second/subsequent time).

In one embodiment, the medical accessory device **424** may be movably (e.g., slidably and/or rotatably, etc.) disposed within the second channel **414** of the elongate member such that a tissue engaging element **425** attached to or integrally formed with a distal end of the medical accessory device **424** may extend beyond a distal end of the elongate member **410** between the needle passer **418** and needle grasper **420**. By way of non-limiting example, the tissue engaging element **425** may include a spiral (e.g., helical, corkscrew, grasper, etc.) shape configured to penetrate (e.g., embed, engage, etc.) a target tissue and reversibly immobilize a portion of a target tissue relative to the distal end of the elongate member **410**. The medical accessory device **424**, with the tissue engaging element **425** reversibly engaged with the target tissue, may be proximally retracted to pull a portion of the target tissue into a space (e.g., working space) between the needle passer **418** and needle grasper **420**, e.g., with the needle passer **418** in the first position relative to the needle grasper **420**.

In use and by way of example, an endoscopic medical device **400** of the present disclosure may be advanced through a body lumen or passage and the distal ends of the needle passer **418** and needle grasper **420** positioned adjacent to a target tissue (e.g., a tissue which may include a portion to be sutured). The medical accessory device **424** may then be distally advanced through the second channel **414**, and through the working space between the needle passer **418** and needle grasper **420**, to position the tissue engaging element **425** in contact with a portion of the target tissue beyond a distal end of the needle passer **418** and needle grasper **420**. The medical accessory device **424** may then be rotated within the second channel (e.g., in a clockwise or counterclockwise direction) to reversibly embed/engage the tissue engaging element **425** with the target tissue. The medical accessory device **424** may then be proximally retracted within the second channel **414** to pull/draw a portion of the target tissue into the working space between the needle passer **416** and the needle grasper **420**. The needle passer **418**, with a needle **426** releasably attached thereto (e.g., extending perpendicular to the needle passer), may then be moved (e.g., pivoted) from the first position to the second position and the needle released from the needle passer **418** and transferred to the needle grasper **420**. In various embodiments, as the needle passer **418** moves to the second position, a sharpened end of the needle **426** and a portion of the suture **422** attached thereto may pass through the target tissue immobilized by the tissue engaging element **425** between the needle passer **418** and needle grasper. The needle passer **418** may then move from the second position to the first position and the tissue engaging element **425** may be disengaged from the target tissue (e.g., by rotating the medical accessory device in a direction opposite the direction used to engage the target tissue). The needle passer **418** may then be moved (e.g., pivoted) from the first position to the second position to transfer (e.g., return) the needle **426** from the needle grasper **420** back to the needle passer **418**. The needle passer **418**, with the needle **426** releasably attached thereto, may then be moved from the second position to the first position.

In various embodiments, with a first section/length of the suture **422** extending through the target tissue, and the needle passer **418** returned to the first position, the endoscopic medical device **400** may be repositioned within the

advanced) to position the distal ends of the needle passer **418** and needle grasper **420** adjacent to a different portion/section of the target tissue. The steps outlined above may then be repeated to suture a second portion of the target tissue. These steps may be performed as many times as necessary to suture (e.g., close) an entire portion of the target tissue and the endoscopic medical device **400** removed from within the patient.

In various embodiments, one or more imaging devices, or cameras **428** and one or more illumination devices, or light sources **430** may be disposed on or within the distal end of the elongate member **410** to allow the medical professional to visualize the target tissue and properly manipulate the needle passer **418** and medical accessory device **424**. In various embodiments, the elongate member **410** may include one or more additional working channels (not shown) configured to receive additional medical devices, end effectors and/or accessories beyond the distal end of thereof. In addition, or alternatively, an elevator (not shown) may be disposed within a distal portion of any of the disclosed working channels to control placement/positioning of the endoscopic medical devices (including the tissue engaging element **425**) within the body lumen or passage.

Referring to FIGS. **6A-6C**, in one embodiment, a distal end of an endoscopic medical device **500** (e.g., suture device, single-use purpose-built suturing device, etc.) of the present disclosure may include an elongate member **510** (e.g., elongate tubular member, flexible elongate tubular member, endoscope, etc.). A suturing arm **516** may extend from a distal end of the elongate member **510**. A distal portion **516a** of the suturing arm **516** may extend distally beyond (e.g., in front of) a distal end of the elongate member **510** to define a working space therebetween (e.g., a working space between the distal end of the elongate member **510** and a proximal surface of the distal portion **516a** of the suturing arm **516**). A first channel **512** (e.g., suture channel, dedicated suture channel, etc.) and a second channel **514** (e.g., working channel, dedicated working channel, etc.) may extend through a longitudinal axis of the elongate member **510**. A distal end of the suture channel **512** and a distal end of the working channel **514** may be coextensive with the working space (e.g., the suture channel **512** and working channel **514** may open into the working space at the distal end of the elongate member **510**).

A needle passer **518** (e.g., shuttle, etc.) may be movably disposed within the distal portion of the elongate member **510** and configured to move proximally and distally (e.g., back-and-forth) across the working space (e.g., between the distal end of the elongate member **510** and the proximal surface of the distal portion **516a** of the suturing arm **516**). In various embodiments, the needle passer **518** may be configured to move distally from a first position on a first side of the working space to a second position on a second side of the working space and proximally from the second side of the working space to the first side of the working space.

A needle receiver **520** may be disposed on or within the distal portion **516a** of the suturing arm **516** and configured to receive the needle passer **518**, e.g., when the needle passer **518** is in the second position. In various embodiments, the needle receiver **520** may include a slot or recessed portion formed within the proximal surface of the distal portion **516** and substantially aligned with the opening of the suture channel **512**, e.g., the slot or recessed portion and the distal end/opening of the suture channel **512** may be disposed on substantially opposite sides of the working space.

In one embodiment, a suture **522** (e.g., filament, thread, etc.) may extend through the suture channel **512** and a medical accessory device **524** may extend through the working channel **514**. A distal end of the suture **522** may be attached to (e.g., glued, tied, etc.) a needle **526** engaged by (e.g., attached to) the needle passer **518**.

In one embodiment, the medical accessory device **524** may be movably (e.g., slidably and/or rotatably, etc.) disposed within the working channel **514** of the elongate member **510** such that a tissue engaging element **525** (e.g., attached to or integrally formed with a distal end of the medical accessory device **524**) may extend into and beyond an opening of the working space. By way of non-limiting example, the tissue engaging element **525** may include a spiral (e.g., helical, corkscrew, grasper, etc.) shape configured to penetrate (e.g., embed, engage, etc.) and reversibly immobilize a portion of a target tissue. The medical accessory device **524**, with the tissue engaging element **525** reversibly engaged with the target tissue, may be proximally retracted to pull a portion of the target tissue into the working space and between the needle passer **518** and the distal portion **516a** of the suturing arm **56**, e.g., with the needle passer **518** in the first position.

In use, and by way of example, a distal end of an endoscopic medical device **500** of the present disclosure may be advanced through a body lumen or passage and the working space positioned adjacent to (e.g., over, above, etc.) a target tissue (e.g., a tissue which may include a portion to be sutured). The medical accessory device **524** may then be distally advanced through the working channel **514** to position the tissue engaging element **525** beyond an opening of the working space and in contact with a portion of the target tissue. The medical accessory device **524** may then be rotated within the working channel **514** (e.g., in a clockwise or counterclockwise direction) to reversibly embed/engage the tissue engaging element **525** with the target tissue. The medical accessory device **524** may then be proximally retracted within the working channel **514** to pull/draw a portion of the target tissue into the working space and between the needle passer **518** (e.g., in the first position) and the distal portion **516a** of the suturing arm **516**. The needle passer **518**, with a needle **526** attached thereto, may then be moved from the first position to the second position such that the needle passer **518** moves distally across the working space and is received within (e.g., extends into) the needle receiver **520** of the distal portion **516a** of the suturing arm **516**. In various embodiments, as the needle passer **518** moves to the second position, a sharpened end of the needle **526** and a portion of the suture **522** attached thereto may pass through the target tissue immobilized by the tissue engaging element **525** within the working space. The tissue engaging element **525** may then be disengaged from the target tissue (e.g., by rotating the medical accessory device in a direction opposite the direction used to engage the target tissue). The needle passer **518**, with the needle **526** attached thereto, may then be moved from the second position to the first position such that the needle passer **518** moves proximally across the working space and returns to the first position, e.g., the initial/starting position.

In various embodiments, with a first section/length of the suture **522** extending through the target tissue, the endoscopic medical device **500** may be repositioned within the body lumen or passage (e.g., proximally retracted or distally advanced) to position the working space adjacent to a different portion/section of the target tissue. The steps outlined above may then be repeated to suture a second portion of the target tissue. These steps may be performed as many

times as necessary to suture (e.g., close) an entire portion of the target tissue and the endoscopic medical device **500** removed from within the patient.

In various embodiments, the endoscopic medical devices **100, 200, 300, 400, 500** which may be single-use and include integrated and purpose-built functionality, may provide a variety of advantages as compared to reusable multipurpose endoscopes. For example, the single-use endoscopic medical devices **100, 200, 300, 400, 500** may mitigate the risk of patient infection associated with more complex reusable endoscopes and associated medical tools, which require sterilization between each use. In addition, the built-in functionality may allow for the disclosed endoscopic medical devices **100, 200, 300, 400, 500** to be smaller and more maneuverable than reusable endoscopes, which must accommodate a wide range of medical devices for a variety of different/unrelated medical procedures.

All of the devices and/or methods disclosed and claimed herein can be made and executed without undue experimentation in light of the present disclosure. While the devices and methods of this disclosure have been described in terms of preferred embodiments, it may be apparent to those of skill in the art that variations can be applied to the devices and/or methods and in the steps or in the sequence of steps of the method described herein without departing from the concept, spirit and scope of the disclosure. All such similar substitutes and modifications apparent to those skilled in the art are deemed to be within the spirit, scope and concept of the disclosure as defined by the appended claims.

What is claimed is:

1. A medical device, comprising:

an endoscope, wherein the endoscope defines a suture channel and a working channel therethrough;

an elongate sheath rotatably disposed about the endoscope, the elongated sheath including a lumen, wherein the endoscope is disposed within the lumen of the elongated sheath;

a needle passer extending from a distal end of the elongate sheath; and

a needle grasper extending from a distal end of the endoscope;

wherein the elongate sheath is configured to rotate about the endoscope between a first position, a second position and a third position;

wherein, in the first position, the needle passer is disposed substantially opposite the needle grasper;

wherein, in the second position, a first side of the needle passer is substantially adjacent to a first side of the needle grasper; and

wherein, in the third position, a second side of the needle passer is substantially adjacent to a second side of the needle grasper.

2. The medical device of claim **1**, further comprising a suture movably disposed within the suture channel and a medical accessory device movably disposed within the working channel.

3. The medical device of claim **2**, wherein a distal end of the suture is attached to a curved needle.

4. The medical device of claim **3**, wherein in the first position the curved needle is releasably attached to the needle passer;

wherein in the second position the curved needle is transferred from the needle passer to the needle grasper; and

wherein in the third position the curved needle is transferred from the needle grasper to the needle passer.

5. The medical device of claim 2, wherein a distal end of the medical accessory device is configured to extend beyond the distal end of the endoscope to engage a target tissue.

6. The medical device of claim 1, further comprising a camera disposed on the distal end of the elongate member. 5

7. The medical device of claim 1, further comprising a light source disposed on the distal end of the elongate member.

* * * * *