



US011633312B2

(12) **United States Patent**
Munakata et al.

(10) **Patent No.:** **US 11,633,312 B2**
(45) **Date of Patent:** ***Apr. 25, 2023**

(54) **ABSORBENT ARTICLE HAVING
OUTWARDLY CONVEX LONGITUDINAL
CENTRAL CHANNELS FOR IMPROVED
PROTECTION**

(58) **Field of Classification Search**
CPC .. A61F 13/532; A61F 13/15203; A61F 13/47;
A61F 13/4702; A61F 13/4704;
(Continued)

(71) Applicant: **The Procter & Gamble Company,**
Cincinnati, OH (US)

(56) **References Cited**

(72) Inventors: **Yoko Munakata,** Hyogo (JP); **Kiyoe
Ohba,** Osaka (JP)

U.S. PATENT DOCUMENTS

(73) Assignee: **THE PROCTER & GAMBLE
COMPANY,** Cincinnati, OH (US)

3,677,249 A 7/1972 Kokx
4,045,833 A 9/1977 Mesek et al.
(Continued)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 386 days.

FOREIGN PATENT DOCUMENTS

This patent is subject to a terminal dis-
claimer.

CN 1189999 A 8/1998
DE 29703589 U1 6/1997
(Continued)

(21) Appl. No.: **16/852,861**

OTHER PUBLICATIONS

(22) Filed: **Apr. 20, 2020**

All Office Actions, U.S. Appl. No. 14/550,172.
(Continued)

(65) **Prior Publication Data**

US 2020/0246201 A1 Aug. 6, 2020

Related U.S. Application Data

Primary Examiner — Jacqueline F Stephens

(63) Continuation of application No. 14/552,921, filed on
Nov. 25, 2014, now Pat. No. 10,912,684, which is a
(Continued)

(74) *Attorney, Agent, or Firm* — William E. Gallagher

(51) **Int. Cl.**
A61F 13/15 (2006.01)
A61F 13/532 (2006.01)


(Continued)

(57) **ABSTRACT**

(52) **U.S. Cl.**
CPC *A61F 13/532* (2013.01); *A61F 13/15203*
(2013.01); *A61F 13/47* (2013.01);
(Continued)

An absorbent article having a pair of longitudinal edges,
front and rear transverse edges, a front end region, a rear end
region, and a central region disposed between the front and
rear end regions. The absorbent article has a liquid pervious
topsheet, a liquid impervious backsheet, an absorbent core
disposed between the topsheet and the backsheet, a pair of
outwardly convex longitudinal central channels formed at
least in the central region. The traversal distance of the pair
of outwardly convex longitudinal central channels decreases
towards both ends of the channels to define a central closed
area. The absorbent article has a rear channel defining a rear
closed area in the rear end region.

18 Claims, 4 Drawing Sheets



Related U.S. Application Data					
	continuation of application No. 14/221,943, filed on Mar. 21, 2014, now Pat. No. 9,925,094, which is a continuation of application No. 11/289,844, filed on Nov. 30, 2005, now Pat. No. 8,715,258.	5,713,886 A	2/1998	Sturino	
		5,746,729 A	5/1998	Wada	
		5,795,345 A	8/1998	Mizutani	
		5,797,894 A	8/1998	Cadieux	
		5,830,296 A	11/1998	Emenaker	
		5,855,572 A	1/1999	Schmidt	
		5,891,118 A	4/1999	Toyoshima et al.	
		5,941,861 A	8/1999	Ng	
(60)	Provisional application No. 60/631,759, filed on Nov. 30, 2004.	5,954,705 A	9/1999	Sawaki	
		6,042,575 A	3/2000	Osborn, III	
(51)	Int. Cl.	6,049,023 A	4/2000	Blenke et al.	
	<i>A61F 13/47</i> (2006.01)	6,074,376 A	6/2000	Mills	
	<i>A61F 13/475</i> (2006.01)	6,152,904 A	11/2000	Matthews	
	<i>A61F 13/533</i> (2006.01)	6,159,190 A	12/2000	Tanaka	
	<i>A61F 13/45</i> (2006.01)	6,210,385 B1	4/2001	Mizutani	
(52)	U.S. Cl.	6,217,563 B1	4/2001	Gompel	
	CPC <i>A61F 13/4702</i> (2013.01); <i>A61F 13/4704</i> (2013.01); <i>A61F 13/4756</i> (2013.01); <i>A61F 13/533</i> (2013.01); <i>A61F 2013/15373</i> (2013.01); <i>A61F 2013/4587</i> (2013.01)	6,231,556 B1	5/2001	Osborn, III	
		6,284,943 B1	9/2001	Osborn, III	
(58)	Field of Classification Search	6,293,931 B1	9/2001	Romare	
	CPC A61F 13/4756; A61F 13/05; A61F 2013/15373; A61F 2013/4587	6,300,538 B1	10/2001	Lindquist	
	USPC 604/378, 379, 380, 385.01	6,326,525 B1	12/2001	Hamajima	
	See application file for complete search history.	6,348,047 B1	2/2002	Harper	
(56)	References Cited	6,371,948 B1	4/2002	Mizutani	
	U.S. PATENT DOCUMENTS	6,394,989 B2	5/2002	Mizutani	
		6,395,956 B1	5/2002	Glasgow	
		6,425,889 B1	7/2002	Kitaoka	
		6,425,890 B1	7/2002	Samuelsson	
		6,475,199 B1	11/2002	Gann	
		6,482,193 B1	11/2002	Samuelsson	
		6,486,379 B1	11/2002	Chen	
		6,492,574 B1	12/2002	Chen	
		6,503,233 B1	1/2003	Chen	
		6,506,961 B1	1/2003	Levy	
		6,515,195 B1	2/2003	Lariviere	
		6,517,525 B1	2/2003	Berthou	
		6,547,772 B1	4/2003	Suekane et al.	
		6,563,013 B1	5/2003	Murota	
		6,613,955 B1	9/2003	Lindsay	
		6,617,490 B1	9/2003	Chen	
		6,652,503 B1	11/2003	Bradley	
		6,667,424 B1	12/2003	Hamilton	
		6,673,982 B1	1/2004	Chen	
		6,692,603 B1	2/2004	Lindsay	
		6,740,069 B2 *	5/2004	Drevik A61F 13/47263 604/385.01	
		6,746,436 B1	6/2004	Sierri et al.	
		6,824,534 B2	11/2004	Mishima	
		6,858,771 B2	2/2005	Yoshimasa	
		6,965,058 B1	11/2005	Raidel	
		6,986,761 B1	1/2006	Hines	
		7,056,311 B2	6/2006	Kinoshita	
		7,078,583 B2	7/2006	Kudo	
		7,122,023 B1	10/2006	Hinoki	
		7,279,613 B2	10/2007	Nozaki	
		7,312,372 B2	12/2007	Miyama	
		7,368,627 B1	5/2008	Widlund	
		7,754,940 B2	7/2010	Brisebois	
		8,715,258 B2	5/2014	Munakata	
		8,920,398 B2	12/2014	Miura	
		9,730,844 B2	8/2017	Miura et al.	
		9,925,094 B2	3/2018	Munakata	
		10,912,684 B2 *	2/2021	Munakata A61F 13/533	
		2001/0009992 A1	7/2001	Boulanger et al.	
		2001/0031956 A1	10/2001	Drevik	
		2001/0039406 A1	11/2001	Hamajima	
		2001/0047159 A1	11/2001	Mizutani	
		2002/0013567 A1	1/2002	Mishima et al.	
		2002/0052587 A1	5/2002	Magnusson	
		2002/0052589 A1	5/2002	Strand	
		2002/0065497 A1	5/2002	Kölby-falk	
		2002/0082579 A1	6/2002	Helmfridsson	
		2002/0087133 A1	7/2002	Osterdahl	
		2002/0128622 A1	9/2002	Carvalho	
		2002/0156450 A1	10/2002	Drevik	
		2003/0018314 A1	1/2003	Nozaki	
		2003/0023221 A1	1/2003	Kashiwagi et al.	
		2003/0050617 A1	3/2003	Chen	
		2003/0055392 A1	3/2003	Tagami	
		2003/0078554 A1	4/2003	Drevik	

(56)

References Cited

U.S. PATENT DOCUMENTS

2003/0088222	A1	5/2003	Yoshimasa	
2003/0088231	A1	5/2003	Yoshimasa	
2003/0093054	A1	5/2003	Sierra et al.	
2003/0120235	A1	6/2003	Boulanger	
2003/0125700	A1	7/2003	Drevik	
2003/0135177	A1	7/2003	Baker	
2003/0153890	A1	8/2003	Rosenfeld	
2003/0187419	A1	10/2003	Bissah et al.	
2004/0068244	A1	4/2004	Salone	
2004/0147893	A1	7/2004	Mizutani et al.	
2004/0176734	A1	9/2004	Rasmussen	
2004/0243082	A1	12/2004	Kinoshita et al.	
2004/0243084	A1	12/2004	Yoshimasa	
2004/0243087	A1	12/2004	Kinoshita	
2004/0260262	A1	12/2004	Nishitani	
2004/0267220	A1	12/2004	Hull	
2004/0267224	A1	12/2004	Ulman	
2005/0124951	A1*	6/2005	Kudo	A61F 13/47218 604/380
2005/0137556	A1	6/2005	Brisebois	
2005/0148972	A1	7/2005	Miyama et al.	
2005/0182374	A1	8/2005	Zander	
2005/0256472	A1	11/2005	Tsutsui	
2006/0116652	A1	6/2006	Miura	
2006/0116653	A1	6/2006	Munakata	
2007/0055212	A1	3/2007	Kameo	
2015/0080831	A1	3/2015	Munakata	
2015/0080833	A1	3/2015	Miura	
2015/0265474	A1	9/2015	Munakata	
2018/0028374	A1	2/2018	Miura et al.	

FOREIGN PATENT DOCUMENTS

EP	1016393	A1	7/2000
EP	1208824		5/2002

EP	200858791	B1	8/2002
EP	1269950	A2	1/2003
JP	2000051269	A	2/2000
JP	2001095842	A	4/2001
JP	2001314445	A	11/2001
JP	2002253612	A	9/2002
JP	2002345888	A	12/2002
JP	2003052743	A	2/2003
JP	2003180733	A	7/2003
WO	WO9515139		6/1995
WO	9817218	A1	4/1998
WO	WO0145610	A1	6/2001
WO	WO0241817	A1	5/2002
WO	WO2004049997	A1	6/2004

OTHER PUBLICATIONS

All Office Actions, U.S. Appl. No. 14/552,921.
 All Office Actions, U.S. Appl. No. 15/648,712.
 Brady et al., "Definition of nonwovens", In The Materials Handbook Thirteenth Edition, Retrieved on: May 22, 2008, 3 Pages.
 Definition of "envelope", Webster's Third New International Dictionary, Unabridged.
 Hatch, Kathryn L., "Dry-Laid Nonwoven Fabrics", In the Book of Introduction to Textile Technology, 2006, 3 Pages.
 All Office Actions, Responses, and Notice of Allowance, if applicable, U.S. Appl. No. 14/221,943, filed Mar. 21, 2014, P&G Case AA668C, Munakata, et al.
 All Office Actions, Responses, and Notice of Allowance, U.S. Appl. No. 11/289,812, filed Nov. 30, 2005, P&G Case AA671, Miura, et al.
 All Office Actions, Responses, and Notice of Allowance, U.S. Appl. No. 11/289,844, filed Nov. 30, 2005, P&G Case AA668, Munakata, et al.
 PCT International Search Report dated Apr. 6, 2006, 11 pages.

* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9

1

**ABSORBENT ARTICLE HAVING
OUTWARDLY CONVEX LONGITUDINAL
CENTRAL CHANNELS FOR IMPROVED
PROTECTION**

FIELD OF THE INVENTION

The present invention relates to absorbent articles such as sanitary napkins, pantliners, and incontinence pads. More particularly, the present invention relates to a sanitary napkin having a pair of outwardly convex longitudinal central channels.

BACKGROUND OF THE INVENTION

Absorbent articles, such as sanitary napkins, pantliners, and incontinence pads, are typically worn in the crotch region of an undergarment. These devices are designed to absorb and retain liquids and other discharges from the human body to prevent body and garment soiling. The aforementioned types of absorbent articles are typically placed in a garment such as the wearer's panty and worn between the wearer's legs, adjacent to the genital (or fluids discharge source) area of the body.

Conventional relatively thick, overnight, or extra protection sanitary napkin products currently marketed in Japan provide some protection from soiling by utilizing a combination of increased product length and thickness (which may include a profiled or varied caliper). These products, however, are not believed to conform or fit to the body of the wearer as closely as possible, particularly at the portions that are adjacent to the discharge portion of body fluids in use. Thus, leakage is possible, particularly at both the central region, the rear region and/or the side edges of these products. This issue is seen not only in conventional relatively thick, overnight, or extra protection sanitary napkin products but also other conventional relatively thinner and smaller sanitary napkin products in the market.

Thus, there is a need for an absorbent article that provides improved protection from soiling. There is another need for a sanitary napkin that fits closer to the wearer's body in the areas where menses and other body fluids originate.

SUMMARY OF THE INVENTION

In one aspect of the invention, the invention is directed to an absorbent article having a pair of longitudinal edges, front and rear transverse edges, a front end region, a rear end region, and a central region disposed between the front and rear end regions. The absorbent article comprises: a liquid pervious topsheet; a liquid impervious backsheet; an absorbent core disposed between the topsheet and the backsheet; a pair of outwardly convex longitudinal central channels formed at least in the central region. The traversal distance of the pair of outwardly convex longitudinal central channels decreases towards the both ends of the channels to define a central closed area which has a maximum length of 80-220 mm and a maximum width of 25-70 mm. The absorbent article further comprises a rear channel defining a rear closed area in the rear end region.

In another aspect of the invention, the absorbent article has a pair of longitudinal edges, front and rear transverse edges, a front end region, a rear end region, and a central region disposed between the front and rear end regions. The absorbent article comprises: a liquid pervious topsheet; a liquid impervious backsheet; an absorbent core disposed between the topsheet and the backsheet. The absorbent

2

article further comprises a pair of longitudinal channels formed in the front end region, the central region and the rear end region; and a pair of central side flaps each extending laterally outward in the central region. The pair of longitudinal channels has (1) an outwardly convex channel portion in the central region, (2) a front inwardly concave channel portion at the transition area between the front end region and the central region, and (3) a rear inwardly concave channel portion at the transition area between the rear end region and the central region.

BRIEF DESCRIPTION OF THE DRAWINGS

While the specification concludes with claims particularly pointing out and distinctly claiming the subject matter which is regarded as forming the present invention, it is believed that the invention will be better understood from the following description which is taken in conjunction with the accompanying drawings in which:

FIG. 1 is a top plane view of a preferred embodiment of the absorbent article of the present invention;

FIG. 2 is a side view of the absorbent article shown in FIG. 1;

FIG. 3 is a schematic cross-sectional view of the absorbent article shown in FIG. 1 taken along line 3-3 of FIG. 1;

FIG. 4 is a schematic cross-sectional view of the absorbent article shown in FIG. 1 taken along line 4-4 of FIG. 1;

FIG. 5 is a perspective view of an emboss channel formed in the absorbent article shown in FIG. 1;

FIG. 6 is a plane view of the pair of outwardly convex longitudinal channels shown in FIG. 1;

FIG. 7 is a bottom plane view of the absorbent article shown in FIG. 1;

FIG. 8 is a top plane view of another preferred embodiment of the absorbent article of the present invention; and

FIG. 9 is a top plane view of yet another preferred embodiment of the absorbent article of the present invention.

DETAILED DESCRIPTION OF THE
INVENTION

Herein, "comprise" and "include" mean that other elements and/or other steps which do not affect the end result can be added. Each of these terms encompasses the terms "consisting of" and "consisting essentially of".

Herein, "absorbent article" refers to articles which absorb and contain body exudates or discharges such as body fluids, and is intended to include sanitary napkins, pantliners, diapers, and incontinence pads (and other articles worn in the crotch region of a garment).

Herein, "disposable" refers to articles which are intended to be discarded after a single use, composted, or otherwise disposed of in an environmentally compatible manner. (That is, they are not intended to be laundered or otherwise restored or reused as an absorbent article.)

Herein, "sanitary napkin" refers to articles which are worn by females adjacent to the pudendal region which are intended to absorb and contain the various exudates which are discharged from the body (e.g., blood, menses, and urine). It should be understood, however, that the present invention is also applicable to other feminine hygiene or catamenial pads such as pantliners, diapers, and incontinence pads (and other articles worn in the crotch region of a garment).

Herein, "joined" encompasses configurations in which an element is directly secured to another element by affixing the

element directly to the other element; configurations in which the element is indirectly secured to the other element by affixing the element to intermediate member(s) which in turn are affixed to the other element; and configurations in which one element is integral with another element, i.e., one element is essentially part of the other element.

Herein, "body surface" refers to surfaces of absorbent articles and/or their component members which face the body of the wearer, while "garment surface" refers to the opposite surfaces of the absorbent articles and/or their component members that face away from the wearer when the absorbent articles are worn. Absorbent articles and components thereof, including the topsheet, backsheet, absorbent core, and any individual layers of their components, have a body surface and a garment surface.

FIG. 1 is a top plane view of a preferred embodiment of the absorbent article of the present invention. In preferred embodiments shown in FIGS. 1-8, the absorbent article is a relatively thick, overnight, extra protection, disposable sanitary napkin 20.

The sanitary napkin 20 has two surfaces, a liquid pervious body-contacting surface or body surface 20A and a liquid impervious garment surface 20B. FIG. 2 is a side view of the sanitary napkin 20 shown in FIG. 1. The body surface 20A is intended to be worn adjacent to the body of the wearer. The garment surface 20B of the sanitary napkin 20 is on the opposite side and is intended to be placed adjacent to the wearer's undergarments when the sanitary napkin 20 is worn.

Referring to FIG. 1, the sanitary napkin 20 has two centerlines, a longitudinal centerline L and a transverse centerline T. Herein, "longitudinal" refers to a line, axis or direction in the plane of the sanitary napkin 20 that is generally aligned with (e.g., approximately parallel to) a vertical plane which bisects a standing wearer into left and right body halves when the sanitary napkin 20 is worn. Herein, "transverse" or "lateral" refers to a line, axis or direction which lies within the plane of the sanitary napkin 20 that is generally perpendicular to the longitudinal direction.

The sanitary napkin 20 has two spaced apart longitudinal edges 22 and two spaced apart transverse or end edges (or "ends") 24, which together form the periphery 26 of the sanitary napkin 20. The sanitary napkin 20 also has two end regions, i.e., a front end region 28 and a rear end region 30. A central region 32 is disposed between the end regions 28 and 30. The sanitary napkin 20 includes a pair of central side flaps 52 in the central region 32 and a pair of rear side flaps 54 in the rear end region 30. Each pair of central and rear side flaps 52 and 54 extends laterally outward from a main body portion 25 in the central region 32 and the rear end region 30, respectively.

The front end region 28 is defined as the area that is placed to the front of the wearer's body when the sanitary napkin 20 is worn. The rear end region 30 is defined as the area that is placed to the rear of the wearer's body. The central region 32 is defined as the area that is generally located directly below the perineum of the wearer and which receives the greatest amount of menses.

In a preferred embodiment, each region can be defined with respect to the positions of the side flaps 52 and 54. The front end region 28 ends at the transition area where the traversal distance between the two longitudinal edges 22 starts to increase towards the central region 32 as shown in FIG. 1. Similarly, the rear end region 30 ends at the transition area where the traversal distance between the two

longitudinal edges 22 starts to increase towards the central region 32 as shown in FIG. 1.

In other words, each region can be defined with respect to the curve of the longitudinal edge 22. The front end region 28 ends at the transition area where the curve of the longitudinal edge 22 starts to extend laterally outward at a higher rate than before as shown in FIG. 1. Similarly, the rear end region 30 ends at the transition area where the curve of the longitudinal edge 22 starts to extend laterally outward at a higher rate than before as shown in FIG. 1.

FIG. 3 is a cross-sectional view of the sanitary napkin 20 taken along the section line 3-3 in FIG. 1, which shows the individual components of the sanitary napkin 20 shown in FIG. 1. The sanitary napkin 20 shown in FIG. 3 generally comprises at least three primary components, i.e., a liquid pervious topsheet 38; a liquid impervious backsheet 40; an absorbent core 42 having longitudinal edges 48 disposed between the topsheet 38 and the backsheet 40. The central side flaps 52 extend laterally outward from the corresponding longitudinal edge 48 of the absorbent core 42 in the central region 32. The topsheet 38, backsheet 40, and absorbent core 42 can comprise any types of materials known in the art as being suitable for such components of an absorbent article or a sanitary napkin.

The topsheet 38 is preferably compliant, soft feeling, and non-irritating to the wearer's skin. Further, the topsheet 38 is liquid permeable or pervious, permitting body fluids (e.g., menses and/or urine) to readily penetrate through its thickness. A suitable liquid permeable material for the topsheet 38 may be manufactured from a wide range of materials such as woven and nonwoven materials (e.g., a nonwoven web of fibers); polymeric materials such as apertured formed thermoplastic films, apertured plastic films, and hydroformed thermoplastic films; porous foams; reticulated foams; reticulated thermoplastic films; and thermoplastic scrims. Suitable woven and nonwoven materials can be comprised of natural fibers (e.g., wood or cotton fibers), synthetic fibers (e.g., polymeric fibers such as polyester, polypropylene, or polyethylene fibers) or from a combination of natural and synthetic fibers. When the topsheet 38 includes a nonwoven web, the web may be manufactured by a wide number of known techniques. For example, the web may be spunbonded, carded, wet-laid, melt-blown, hydroentangled, combinations of the above, or the like.

A particularly suitable material for the topsheet 38 includes an apertured formed film. Apertured formed films are preferred for the topsheet 38 because they are pervious to body fluids and, if properly apertured, have a reduced tendency to allow liquids to pass back through and rewet the wearer's skin. Thus, the body surface of the formed film (i.e., the body surface 22 of the sanitary napkin 20) remains dry, thereby reducing body soiling and creating a more comfortable feel for the wearer. A preferred material for the topsheet 38 is a macroscopically expanded, three-dimensional formed polyethylene film. One preferred material for the topsheet 38 is available from Tredegar Film Products, Ind., USA, under Code No. X-27121.

The backsheet 40 is impervious to body fluids and is preferably manufactured from a thin plastic film, although other flexible liquid impervious materials may also be used. Herein, "flexible" refers to materials which are compliant and will readily conform to the general shape and contours of the human body. The backsheet 40 prevents the body fluids absorbed and contained in the absorbent core 42 from wetting articles which contact the absorbent article such as bed sheets, pants, pajamas and undergarments. The backsheet 40 may thus include a woven or nonwoven material,

polymeric films such as thermoplastic films of polyethylene or polypropylene, or composite materials such as a film-coated nonwoven material. The backsheet **40** can include a single layer material, or two or more layers of materials. The backsheet **40** preferably has a thickness of from about 0.012 mm (0.5 mil) to about 0.081 mm (3.4 mils). In a preferred embodiment, the backsheet **40** is a single layer polyethylene film. Such a preferred polyethylene film is available from Daedong Co. Ltd., KyungBuk-Do, Korea, under Code No. DNF-040712VL.

The backsheet **40** preferably has a microporous structure which can permit vapors to escape from the absorbent core **42** (often called “breathable backsheet”) while still preventing body fluids from passing through the backsheet **40**. A preferred microporous polyethylene film is available from Mitsubishi Chemical Corporation, Tokyo, Japan, under Code No. NPP2. The backsheet **40** can be embossed to provide a clothlike appearance.

The absorbent core **42** is capable of receiving, absorbing or retaining body fluids discharged. The absorbent core **42** is preferably compressible, conformable, and non-irritating to the wearer’s skin. The absorbent core **42** can be formed by a single layer material or a plurality layers of materials. The absorbent core may include any of a wide variety of liquid-absorbent materials commonly used in absorbent articles, such as comminuted wood pulp, which is generally referred to as airfelt. A particularly preferred absorbent core material is an airfelt material which is available from Weyerhaeuser Company, Wash., USA, under Code No. NB416.

Examples of other suitable absorbent materials for use in the absorbent core include creped cellulose wadding; melt-blown polymers including coform; chemically stiffened, modified or cross-linked cellulosic fibers; synthetic fibers such as crimped polyester fibers; peat moss; tissue including tissue wraps and tissue laminates; absorbent foams; absorbent sponges; absorbent gelling materials; or any equivalent material or combinations of materials, or mixtures of these.

The absorbent core **42** may be manufactured in a wide variety of sizes and shapes. The periphery of the absorbent core **42** thus can take any shape in its top plane view. Preferred shapes for the core periphery include an oval, a rectangle, an hourglass, and a combination of the oval and rectangle such as the one shown in FIG. 1.

In a preferred embodiment for a relatively thick, overnight, extra protection sanitary napkin, the sanitary napkin **20** has a total core length ranging between about 200 and 450 mm. A length shorter than about 200 mm typically does not extend far enough into the gluteal area to provide improved protection. A length longer than about 400 mm generally extends too far beyond the gluteal groove for all of the rear end region to conform to the wearer’s buttocks leading to poor gluteal fit.

FIG. 4 is a schematic cross-sectional view of the sanitary napkin **20** shown in FIG. 1 taken along line 4-4 of FIG. 1. The rear side flaps **54** extend laterally outward from the corresponding longitudinal edge **48** of the absorbent core **42** in the rear end region **30**. Preferably, the sanitary napkin **20** further includes a continuous support layer **44** which is disposed between the absorbent core **42** and the backsheet **40** in (at least a part of) the rear end region **30** (and the front region **28** and the central region **32** if desired). The continuous support layer **44** extends laterally into the rear side flaps **54** in the rear end region **30**. Herein, “continuous layer” means a layer (or member) that does not include two (or more) component materials physically separated (or spaced apart) within the layer. For example, if a layer (or member) includes two component materials which are not directly

bonded or connected one another, that layer is not a continuous layer but a discontinuous layer. The continuous support layer **44** should have sufficient thickness, rigidity and resiliency to prevent the rear side flaps **54** from bunching (i.e., deforming or twisting) which tends to be caused by a stress generated between the rear side flaps **54** and the undergarment during use.

The continuous support layer **44** can be formed by a wide variety of materials (preferably hydrophilic), preferably fibrous materials. Preferred fibrous materials include nonwoven materials. The fibers or other components of such nonwoven materials may be synthetic or natural, or partially synthetic and partially natural. Suitable synthetic fibers include polyester, polypropylene, polyethylene, nylon, viscous rayon, or cellulose acetate fibers. Suitable natural fibers include cotton, cellulose, or other natural fibers.

In one preferred embodiment, the continuous support layer **44** is an air laid nonwoven material which is available from Kang Na Hsiung Enterprise Co., Ltd., Taipei, Taiwan, under Code No. AL080-BL01-10. This nonwoven material has basis weight of 80 g/m², density of 0.07 g/cm³, and thickness of 1.16 mm. This nonwoven material is formed by a mixture of chemical pulp (or cellulose) fibers and polyethylene/polypropylene bi-component fibers through an air through process. In order to provide the desired support effect for the rear side flaps **54** under in-use conditions, it is desirable that the nonwoven material for the continuous support layer **44** preferably has basis weight of 30-180 g/m², density of 0.05-0.20 g/cm³, and thickness of 0.3-1.5 mm.

Referring again to FIG. 4, the sanitary napkin **20** preferably includes an adhesive layer (not shown in FIGs.) disposed between the continuous support layer **44** and the backsheet **40** in the rear end region **30**. Preferably, the adhesive layer is applied uniformly between the continuous support layer **44** and the backsheet **40**. Thus, the uniform adhesive layer uniformly bonds the continuous support layer **44** to the backsheet **40** in the rear end region **30**. The uniform adhesive layer is preferred since it can help provide a uniform thickness, rigidity and/or resiliency to the rear side flaps **54** which can also prevent the rear side flaps **54** from bunching which may be caused by a stress generated between the rear side flaps **54** and the undergarment during use.

The topsheet **38**, the backsheet **40**, the absorbent core **42** may be assembled in a variety of configurations known in the art. Preferred configurations are described in U.S. Pat. Nos. 4,950,264; 5,009,653 issued to Osborn; U.S. Pat. No. 4,425,130 issued to DesMarais; U.S. Pat. Nos. 4,589,876 and 4,687,478 issued to Van Tilburg, and U.S. Pat. No. 5,234,422 issued to Sneller, et al.

Referring again to FIG. 1, the sanitary napkin **20** has a pair of outwardly convex longitudinal central channels **62** formed at least in the central region **32**. Herein, “channel” refers to a generally elongated depression formed in at least a portion of an absorbent article. The channel can be formed by, for example, reducing the amount of the absorbent core at the channel portion, and/or compressing or embossing the absorbent core at the channel portion.

Typically, the channel is formed by applying a compressive force to both the topsheet and the absorbent core toward the backsheet. The topsheet at the channel portion is pushed down into the absorbent core, and the materials of the topsheet and the absorbent core are compressed at and below the bottom of the channel portion. By this operation (which is often called “embossing process”), the channel portion of the absorbent article has relatively higher density than the other portion(s) or the surrounding portion(s) of the channel

portion. The channels of the present invention can be formed by any structures and processes known in the art.

The channel tends to preferentially diffuse or lead body fluids flow along the direction in which the channel extends. Therefore, the channel is useful to control body fluids flow within the absorbent article thereby preventing body fluids leakage from the absorbent article. The channel also tends to work as a preferential bending axis of the absorbent article. Therefore, the absorbent article may bend at the channel portion such that it provides an improved fit of the absorbent article to the wearer's body. It should be noted that such an improved fit of the absorbent article can also contribute to an improvement in preventing body fluids leakage from the absorbent article.

The channel of the present invention can be either continuous or discontinuous. Herein, "discontinuous" means the channel can be separated by a non-channel portion (i.e., a portion where no channel is formed) such that the channel includes 2 or more elongated channel portions which are separated by a non-channel portion. The distance between the two succeeding channel portions (i.e., the length of the no channel portion) may be changed depending on the product design. Preferably, the length of the no channel portion is 0-20 mm, more preferably 2-10 mm, and yet more preferably 3-6 mm.

In one preferred embodiment, channels are formed by applying a uniform (or a single level of) compressive force to the topsheet and the absorbent core toward the backsheet. Alternatively, channels can be formed by applying two or more levels of compressive forces to the topsheet and the absorbent core toward the backsheet thereby forming a "two (or more) stage channel structure".

In the preferred embodiment shown in FIG. 1, the channels **62**, **64**, **65** and **66** are formed by applying two levels of compressive forces to the topsheet **38** and the absorbent core **42** toward the backsheet **40**. The application of the two levels of compressive forces (i.e., higher compression and lower compression) produces two stage depth portions (i.e., "two stage channel structure") in the resulting channels, i.e., first portion and second portion.

FIG. 5 is a perspective view of one channel formed in the sanitary napkin **20** shown in FIG. 1. In this embodiment, the channel **62** has two side walls (or channel walls) **83** and **84**. The first portions **81** are formed by a higher compression, while the second portion **82** is formed by a lower compression. The absorbent core **42** is more compressed at the portions **81** of higher compression than the portion **82** of lower compression. In the embodiment shown in FIG. 5 (and also FIG. 3), the portions **81** of higher compression form the lowest portions of the channel **62**, while the portion **82** of lower compression forms the higher portion in the channel **62**. The first portions **81** of higher compression have a higher density than the portion **82** of lower compression as a result of compression force differences. Such a two stage channel structure is preferred since it can provide a better comfort to the wearer's body in use compared with the channel structure which has no stage difference (formed by no compression force differences applied). In addition, since the compression force is more concentrated at the portions **81** of higher compression, the two stage channel structure can also increase the bonding strength between the topsheet **38** and the absorbent core **42** at the portions **81**.

The first portions **81** formed by a higher compression extend from one channel wall **83** but does not reach the other channel wall **84**. In the embodiment shown in FIG. 5, the shape of the first portions **81** formed by a higher compression is about a rectangular. However, the shape of the first

portions **81** can vary depending on the channel design in the sanitary napkin **20**. The length, width and depth of the first portions **81** can also vary depending on the channel design in the sanitary napkin **20**. Similarly, the shape, the length, width and depth of the second portion **82** can also vary depending on the channel design in the sanitary napkin **20**.

The first portions **81** formed by a higher compression are spaced one another. The distance or interval of two adjacent portions **81** can be either consistent or inconsistent. In the embodiment shown in FIG. 5, the distance of two adjacent portions **81** is consistent.

In an alternative embodiment (not shown in FIGs.), the first portions **81** may be formed by lower compression, and the second portion **82** may be formed by higher compression. This produces an opposite geographic shape of the channels.

A variety of preferred channel structures which are applicable to the present invention are disclosed in, for example, U.S. Pat. No. 6,563,013 issued to Murota on May 13, 2003. This publication discloses examples of "two stage channel structure" which are preferably applicable to the embodiments of the present invention.

In the embodiment shown in FIG. 5, the first portion **81** formed by a higher compression extends from one channel wall **83** but does not reach the other channel wall **84**. This channel structure is referred to as a "stitched channel structure".

However, this is not always necessary. Alternatively to such a stitched channel structure, the first portion **81** formed by a higher compression can extend from one channel wall **83** to the other channel wall **84**. Such a structure can be produced by an application of higher and lower compressions alternatively applied along the longitudinal direction of the channel **62**. Such channel structures are disclosed in, for example, U.S. Pat. No. 5,795,345 issued to Mizutani et al. on Aug. 18, 1998.

FIG. 6 is a plane view of the pair of outwardly convex longitudinal central channels **62** shown in FIG. 1. Herein, "outwardly convex" means the longitudinal channels have a curved line shape (including a polygonal lines shape and a curved line shape) which is outwardly extended when looking from the longitudinal centerline L. The longitudinal central channels **62** shown in FIG. 1 have a circular arc shape which is outwardly curved when looking from the longitudinal centerline L of the sanitary napkin **20**. The traversal distance TD of the pair of outwardly convex longitudinal central channels **62** decreases towards the both ends of the central channels **62** to define a central closed area **72**.

Herein, "closed area" is an area that is disposed between the inside channel wall(s) of the outwardly convex longitudinal channels. When the traversal distance between the inside channel walls of the outwardly convex longitudinal channels reaches 60% of the maximum traversal distance, a closed area is defined at least at that position. However, the closed area can extend within the inside channel walls of the outwardly convex longitudinal channels until they stop at their ends (before they intersect).

In one preferred embodiment, the closed area is defined at least at the position where the traversal distance between the inside channel walls of the outwardly convex longitudinal channels reaches 20% (or less than 5% or about 0% if desired) of the maximum traversal distance. Thus, it should be noted that the "closed area" does not require an area that is physically "closed" by the outwardly convex longitudinal channels. The closed area has a maximum length (ML) and a maximum width (MW). The maximum length is defined as

the longitudinal distance between the outermost walls at the both ends of the outwardly convex longitudinal channels. The maximum width is defined as the maximum traversal distance between the inside channel walls of the outwardly convex longitudinal channels. (These maximum length and width ML and MW of the closed area are shown in FIG. 6.)

In the embodiment shown in FIG. 6, the central closed area 72 is defined at least at the position P where the traversal distance TD between the outwardly convex longitudinal central channels 62 reaches 60% of the maximum traversal distance. However, the closed area 72 extends within the inside channel walls of the outwardly convex longitudinal channels 62 until they stop at their ends.

The closed area preferably has a periphery wherein 70-100% in length of the periphery is surrounded by the outwardly convex longitudinal channels. In other words, the rest (i.e., 0-30% in length) of the periphery may be surrounded by other channel(s). Preferably, 80-98% in length of the periphery of the closed area is defined by the outwardly convex longitudinal channels.

The closed area generally tries to maintain the body fluids absorbed underneath the closed area (e.g., an absorbent core). In addition, the closed area also works to prevent the material of the absorbent core from moving when it becomes wet by the absorbed body fluids.

The central closed area 72 shown in FIG. 6 has a periphery 70 defined by the inside channel walls of the two central channels 62. Preferably, 70-100% in length of the periphery 70 is surrounded by the outwardly convex longitudinal channels 62. In the embodiment shown in FIG. 6, since there is about 2% in length of the periphery 70 of the closed area having no channel portion 63, about 98% in length of the periphery 70 of the closed area 72 is defined by the outwardly convex longitudinal channels 62.

The pair of outwardly convex longitudinal central channels 62 can take any shape that defines a central closed area 72. Preferably, the central channels 62 takes an oval like shape. Preferred oval like shapes include, for example, an actual oval shape defined by mathematics and an eye shape (i.e., a shape formed by two arc like lines), and the like. In the preferred embodiment shown in FIG. 1, the central channels 62 has an eye shape consisting of two arc like lines, each of which is formed by five (5) circular arcs which are connected in series. Such oval like shapes have a maximum length ML and a maximum width MW. The central closed area 72 shown in FIG. 6 has a maximum length ML and a maximum width MW.

Preferably, the central closed area 72 has a maximum length ML of 80-220 mm and a maximum width MW of 25-70 mm. More preferably, the central closed area 72 has a maximum length ML of 130-190 mm and a maximum width MW of 35-55 mm. In the preferred embodiment shown in FIG. 1, the central closed area 72 has a maximum length ML of 160 mm and a maximum width MW of 46 mm.

Referring again to FIG. 1, the sanitary napkin 20 preferably has a rear channel 64 defining a rear closed area 74 in the rear end region 30. The rear closed area 74 can be formed not only within the rear end region 30 but both or either the central region 32 and/or the rear end region 30. For example, in the embodiment shown in FIG. 1, the rear closed area 74 is formed within the rear end region 30. On the other hand, in the embodiment shown in FIG. 9 (which is discussed in later), the rear closed area 74 is formed within both the central region 32 and the rear end region 30.

Preferably, the maximum width of the rear closed area 74 is no greater than that of the maximum width of the central closed area 72. By limiting the width of the rear closed area

74 within the maximum width of the central closed area 72, the discharged body fluids are led along the longitudinal direction more than the traversal direction by the fluids control function of the rear channels 64. Therefore, this configuration is useful to prevent the body fluids leakage from the longitudinal edges 22 of the sanitary napkin 20 in the rear end region 30. In preferred embodiment shown in FIG. 1, the maximum width of the rear closed area 74 is about same as that of the maximum width of the central closed area 72.

The rear channel 64 can take any shape that forms a closed area. The rear channel 64 preferably takes an oval like shape or an elongated U-character shape. Preferred oval like shapes include, for example, an actual oval shape defined by mathematics and an elongated U-character shape. A preferred elongated U-character shape has the traversal distance between the two arms of the elongated U-character shape decreases towards the central closed area 72 as shown in FIG. 1.

In a preferred embodiment, the sanitary napkin 20 further has an additional (or secondary) rear channel 65 within the rear closed area 74 in the rear end region 30 as shown in FIG. 1. The additional rear channel 65 does not need to form a closed area. The additional rear channel 65 is used to control the rigidity of the sanitary napkin 20 at the rear end region 30. In addition, the additional rear channel 65 also can work to maintain the absorbed body fluids in the inside area of the channel 65. The additional rear channel 65 can take any shape but it preferably takes an elongated U-character shape as shown in FIG. 1.

Referring again to FIG. 1, the sanitary napkin 20 preferably has a front channel 66 forming a front closed area 76 in the front end region 30.

The front closed area 76 can be formed not only within the front end region 28 but both the central region 32 and the front end region 28. For example, in the embodiment shown in FIG. 1, the front closed area 76 is formed within the front end region 30. On the other hand, in the embodiment shown in FIG. 9 (which is discussed in later), the front closed area 76 is formed within both the central region 32 and the front end region 30.

Preferably, the maximum width of the front closed area 76 is no greater than that of the maximum width of the central closed area 72. By limiting the width of the front closed area 76 within the maximum width of the central closed area 72, the discharged body fluids are led along the longitudinal direction more than the traversal direction by the fluids control function of the front channels 66. Therefore, this configuration is also useful to prevent the body fluids leakage from the longitudinal edges 22 of the sanitary napkin 20 in the front end region 28. In preferred embodiment shown in FIG. 1, the maximum width of the front closed area 76 is about same as that of the maximum width of the central closed area 72.

The front channel 66 can also take any shape that forms a closed area. The front channel 66 preferably takes a horseshoe like shape, an oval or circle like shape or a U-character shape. One example of preferred horseshoe like shape is shown in FIG. 1.

In one embodiment, the absorbent core 42 is non-profiled within the central closed area 72 so that the central region 32 has the same caliper as the outside of the central closed area 72. Preferably, the absorbent core 42 is profiled within the central closed area 72 so that the central region 32 has a caliper that is greater than the caliper of the outside of the central closed area 72 (i.e., a non-profiled portion) as shown in FIGS. 2 and 3. Herein, "profiled" means that one specified

portion of a material has a caliper that is greater than that of the other portion to be compared. Herein, calipers are measured under a pressure of 0.5 psi using a circular comparator foot with a 1 inch diameter area. Typically, a profiled portion is formed by increasing the amount of material(s) at the profiled portion of the absorbent core than the other adjacent portion such that the profiled portion shows an expanded shape (or appearance) on the body surface **20A** compared to the other portion. In the embodiment of FIG. 1, the absorbent core **42** contains an increased amount of material(s) within the central closed area **72** than the outside of the central closed area **72** such that the sanitary napkin **20** is profiled at the central closed area **72** as shown in FIG. 2.

Preferably, the front end region **28** and the rear end region **30** have the same or similar caliper, while the central region **32** comprises the greatest caliper portion of the sanitary napkin **20** as a result of the profiled structure. The caliper ratio of the profiled portion to the non-profiled portion preferably ranges from about 1.1:1 to about 3:1, and more preferably from about 2:1 to about 2.6:1. In the sanitary napkin **20** shown in FIG. 1, the caliper ratio of the profiled portion to the non-profiled portion is about 2.2:1.

The sanitary napkin **20** can be of any caliper, including relatively thick, relatively thin, or even very thin. The embodiment of the sanitary napkin **20** shown in FIG. 1 is intended to be an example of a relatively thick, overnight, extra protection sanitary napkin having a caliper of about 5 mm in the end regions **28** and **30** and a caliper of about 14 mm in the central region **32**. It should be understood, however, when viewing these figures the number of layers of material shown may cause the sanitary napkin **20** to appear much thicker than it actually is, particularly in cross-section.

As shown in FIG. 1, the sanitary napkin **20** is asymmetrically shaped so that the rear end region **30** is larger than the front end region **28**. In the preferred embodiment shown in FIG. 1, the sanitary napkin **20** is asymmetrically shaped such that the rear end region **30** has both a larger width and a longer length than the front end region **28**. The widths of the front and rear end regions are defined by the traversal distance between the longitudinal edges **22** of the sanitary napkin **20**. The ratio of the widths of the rear end region **30** to the front end region **28** preferably ranges from between about 1:1 and about 2.5:1. More preferably, the ratio of the widths of the rear end region **30** to the front end region **28** is about 1.4:1. The ratio of the longitudinal lengths of the front end region **28** to the central region **32** is from about 1:1 to about 1:4, and the ratio of the longitudinal lengths of the central region **32** to the rear end region **30** is from about 1:0.5 to about 1:3. In the preferred embodiment shown in FIG. 1, the ratio of the longitudinal lengths of the front end region **28** to the central region **32** and the rear end region **30** is about 1:1.7:2.5.

The topsheet **38** and the backsheet **40** typically have length and width dimensions generally larger than those of the absorbent core **42**. The topsheet **38** and backsheet **40** extend beyond the edges of the absorbent core **42**, and are joined together to form a pair of central side flaps **52** and a pair of rear side flaps **54**. These topsheet **38** and backsheet **40** can be joined any means (e.g., an adhesive) known in the art.

The central side flaps **52** can be in any suitable configuration and shape known in the art. Suitable flaps are described in U.S. Pat. No. 5,389,094 issued to Lavash, et al. on Feb. 14, 1995; and U.S. Pat. No. 5,558,663 issued to Weinberger, et al. on Sep. 24, 1996.

In the embodiment shown in FIG. 1, the central side flaps **52** and the rear side flaps **54** are integral with the main body portion **25** of the sanitary napkin **20** (i.e., these flaps comprise integral extensions of the topsheet **38** and the backsheet **40** from the main body portion **25**). Alternatively, these flaps can be formed by separate materials from the topsheet **38** and the backsheet **40**, which are joined to the main body portion **25** of the sanitary napkin **20** in any suitable manner. In that event, the flaps are each joined to (or associated with) the main body portion **25** along a juncture, typically a longitudinally-oriented (or "longitudinal") juncture (not shown in Figs.).

The central side flaps **52** and the rear side flaps **54** are used to attach the sanitary napkin **20** to the wearer's panties or undergarment through adhesive fasteners as known in the art. The fasteners comprise a plurality of patches of adhesive adhered to the garment surface **20B** of the backsheet **40** of the sanitary napkin **20**.

FIG. 7 is a bottom plane view of the sanitary napkin **20** shown in FIG. 1. Typically one or two (or more if desired) adhesive patches (i.e., panty fastening adhesive **55**) are disposed on the main body portion **25** of the sanitary napkin **20** such that the sanitary napkin **20** can adhere to the crotch area of the wearer's undergarment to keep the sanitary napkin **20** in place.

The panty fastening adhesive **55** is preferably at least about 50% as long as the absorbent core **42**, but is preferably no greater than about 100% of the length of the core **42**. The preferred length of the panty fastening adhesive **55** is between about 75% and about 90% the length of the absorbent core **42**. The width of the panty fastening adhesive **55** is preferably at least about 25% of the width of the portion of the absorbent core **42** lying in the front end region **28**, but should be no wider than about 100% the width of the portion of the core **42** in the front end region **28**. The preferred width of the panty fastening adhesive **55** is between about 70% and about 88% of the width of the first end region core width.

In addition, a pair of additional adhesive patches (i.e., central flap adhesives **56**) are disposed on the garment surface **20B** of the central side flaps **52** of the sanitary napkin **20** to adhere to the undersides of the wearer's undergarment during use and to keep the napkin **20** in place to improve fit.

Preferably, another pair of additional adhesive patches (i.e., rear flap adhesives **57**) are disposed on the garment surface **20B** of the rear side flaps **54** of the sanitary napkin **20** to additionally help keep the sanitary napkin **20** in place. The rear flap adhesives **57** adheres to the undersides of the wearer's undergarment during use and to keep the napkin **20** in place to improve fit. The rear flap adhesives **57** jointly work with the continuous support layer **44** in the rear side flaps **54** to prevent the rear side flaps **54** from undesirable bunching during the use of the sanitary napkin **20**.

The central side flaps **52**, which have panty fasteners thereon, adhere to the underside of the wearer's undergarment. The central side flaps **52** serve to keep the sanitary napkin **20** in place during wear. Keeping the sanitary napkin **20** in place prevents skewing of the napkin **20** in the panty, and undesirable bunching. The central side flaps **52** may also assist the central region **32** in forming into the desired W-shaped configuration, and the rear end region **30** in forming the desired inverted V-shaped configuration.

These adhesive patches are preferably covered by release strips before use as known in the art. Preferably, the central side flaps **52** are folded over the topsheet **38** and they are bridged by a single (or unitary) release strip through the central flap adhesives **56**. Similarly, the rear side flaps **54** are

also folded over the topsheet and they are also bridged by a single (or unitary) release strip through the rear flap adhesives 57. In a particularly preferred embodiment, both the central side flaps 52 and the rear side flaps 54 are bridged by a single (or unitary) release strip. Herein, "unitary" means the release strip member can be formed by either a single material or two (or more) joined materials.

The panty fastening adhesive 55 is also covered by a release strip. If desired, the panty fastening adhesive 55 is covered by a releasable wrapper that also serves as an individual wrapper package for the sanitary napkin 20. A preferred structure is described in U.S. Pat. No. 6,074,376 issued to Mills on Jun. 13, 2000.

The sanitary napkin 20 is worn by the wearer so that the rear end region 30 is placed to the rear of the wearer's body to provide the best gluteal fit. The outwardly convex longitudinal central channels 62 assist the central region 32 of the sanitary napkin 20 in assuming a W-shaped cross-sectional configuration when the napkin 20 is laterally compressed by the wearer's thighs, thereby allowing improved contact with the wearer's genital area. This W-shaped configuration is formed by the sides compressing upwards and inwards and the center buckling upward into a convex upward configuration, with the densified region provided by the channels forming the fold lines.

In addition, due to the profiled configuration in the central region 32, the central closed area 72 is brought more closely to the source area of body fluids thereby contributing to a further better fit to the wearer's body. The profiled configuration of the central closed area 72 cooperates with the W-shaped cross-sectional configuration thereby allowing the central closed area 72 to closely fit to the wearer's genital area. This cooperative function enables an improved leakage protection at the central region 32.

The W-shape configuration of the central region 32 is transformed into an inverted V-shape configuration in the rear end region 30. The inverted V-shape configuration retains the profiled central portion of the W-shape configuration to improve gluteal fit. The rear end region 30 is thus also able to closely fit into the crevice between the wearer's buttocks (that is, in the gluteal groove) for improved protection from end soiling. This occurs while the rear end region 30 maintains its area coverage due to the size of the same and the panty fastening adhesive.

As a result, in the embodiment shown in FIG. 1, all the asymmetrical shape of the sanitary napkin 20, the embossed channels 62, 64 and 66, the central and rear side flaps 52 and 54, and the profiled configuration in the central closed area 72 cooperatively work together thereby providing an improved fit and leakage protection.

FIG. 8 is a top plane view of another preferred embodiment of the absorbent article of the present invention. In this embodiment, the absorbent article is also a relatively thick, overnight, extra protection, disposable sanitary napkin 21. It should be noted that except the channels arrangements the sanitary napkin 21 is similar to the sanitary napkin 20 which is discussed hereinabove. Referring to FIG. 8, the sanitary napkin 21 has a pair of longitudinal channels 90 formed in the front end region 28, the central region 32 and the rear end region 30; and a pair of central side flaps 52 each extending laterally outward from the central region 32. Each of the longitudinal channel 90 includes (or divided into) an outwardly convex central channel 92, an outwardly convex rear channel 94 and an outwardly convex front channel 96. The longitudinal channel 90 has (1) an outwardly convex channel portion 97 in the central region, (2) a front inwardly concave channel portion 98 at the transition area between

the front end region 28 and the central region 32, and (3) a rear inwardly concave channel portion 99 at the transition area between the rear end region 30 and the central region 32.

Herein, "inwardly concave" means the longitudinal channels have a curved line shape (including a polygonal lines shape and a curved line shape) which is inwardly curved when looking from the longitudinal centerline L. The longitudinal channels 90 shown in FIG. 8 have a circular arc shape which is inwardly concave at the portions 98 and 99 when looking from the longitudinal centerline L of the sanitary napkin 20.

In one embodiment, the absorbent core 42 can be non-profiled within the central closed area 72. However, similarly to the sanitary napkin 20 shown in FIG. 1, the absorbent core 42 of the sanitary napkin 21 is preferably profiled in the central area 93 between the front inwardly concave channel portion 98 and the rear inwardly concave channel portion 99 so that the central region 32 has a caliper that is greater than the caliper of the outside of the central area 93 (i.e., a non-profiled portion).

Due to the profiled configuration in the central region 32, the central area 93 is brought more closely to the source area of body fluids thereby contributing to a further better fit to the wearer's body. The profiled configuration of the central area 93 cooperates with the W-shaped cross-sectional configuration formed by the outwardly convex central channels 92 thereby allowing the central area 93 to closely fit to the wearer's genital area. This cooperative function enables an improved leakage protection at the central region 32.

FIG. 9 is a top plane view of yet another preferred embodiment of the absorbent article of the present invention. In this preferred embodiment, the absorbent article is a thick disposable sanitary napkin 23 which is designed for a user who tends to have heavy discharge of body fluids in daytime. It should be noted, however, that this sanitary napkin 23 is relatively thinner and smaller compared with the sanitary napkin 20 shown in FIG. 1.

Referring to FIG. 9, the sanitary napkin 23 has two centerlines, a longitudinal centerline L and a transverse centerline T. The sanitary napkin 23 has two spaced apart longitudinal edges 22 and two spaced apart transverse or end edges (or "ends") 24, which together form the periphery 26 of the sanitary napkin 23. The sanitary napkin 23 also has two end regions, i.e., a front end region 28 and a rear end region 30. A central region 32 is disposed between the end regions 28 and 30. The sanitary napkin 23 includes a pair of side flaps 50 in the central region 32. Similarly to the central side flaps 52 in FIG. 1, the side flaps 50 can be also in any suitable configuration or shape known in the art.

As shown in FIG. 9, the sanitary napkin 23 is symmetrically shaped so that the shapes, areas, lengths and widths of the rear end region 30 and the front end region 28 are same. The ratio of the lengths of the end region 28 or 30 to the central region 32 can vary from about 1:5 to about 1:1, preferably from about 1:4 to about 1:3. In the sanitary napkin 23 shown in FIG. 9, this ratio is about 1:3.4.

Similarly to the sanitary napkin 20 shown in FIG. 1, the sanitary napkin 23 shown in FIG. 9 generally comprises a liquid pervious topsheet 38; a liquid impervious backsheetsheet 40; an absorbent core 42 disposed between the topsheet 38 and the backsheetsheet 40. The topsheet 38, backsheetsheet 40, and absorbent core 42 can comprise any types of materials and structures known in the art as being suitable for such components of an absorbent article or a sanitary napkin.

The sanitary napkin 23 shown in FIG. 9 has a pair of outwardly convex longitudinal central channels 62 formed at

least in the central region 32. The traversal distance TD of the pair of outwardly convex longitudinal central channels 62 decreases towards the both ends of the central channels 62 to define a central closed area 72. In the embodiment shown in FIG. 9, the central closed area 72 is defined at least at the position P where the traversal distance TD between the outwardly convex longitudinal central channels 62 reaches 60% of the maximum traversal distance TD. However, the closed area 72 extends within the inside channel walls of the outwardly convex longitudinal channels 62 until they stop at their ends.

Preferably, the central closed area 72 has a maximum length ML of 105-165 mm and a maximum width MW of 20-60 mm. More preferably, the central closed area 72 has a maximum length ML of 120-150 mm and a maximum width MW of 30-50 mm. In the preferred embodiment shown in FIG. 9, the central closed area 72 has a maximum length ML of 135 mm and a maximum width MW of 38 mm.

The sanitary napkin 23 preferably has a rear channel 64 defining a rear closed area 74 in the rear end region 30. The rear closed area 74 is formed within the central region 32 and the rear end region 30. The sanitary napkin 23 preferably has a front channel 66 forming a front closed area 76 in the front end region 30. The front closed area 76 is formed within the central region 32 and the front end region 28. The front and rear channels 66 and 64 can take any shape that form a closed area. The front and rear channels 66 and 64 preferably take a horseshoe like shape, an oval or circle like shape or a U-character shape. One example of preferred horseshoe like shape is shown in FIG. 9.

In one embodiment, the absorbent core 42 can be non-profiled within the central closed area 72. However, the absorbent core 42 is preferably profiled within the central closed area 72 so that the central region 32 has a caliper that is greater than the caliper of the outside of the central closed area 72 (i.e., a non-profiled portion). Preferably, the front end region 28 and the rear end region 30 have the same or similar caliper, while the central region 32 comprises the greatest caliper portion of the sanitary napkin 20 as a result of the profiled structure. The caliper ratio of the profiled portion to the non-profiled portion preferably ranges from about 1.1:1 to about 3:1, and more preferably is from about 2:1 to about 2.6:1. In the sanitary napkin 23 shown in FIG. 9, the caliper ratio of the profiled portion to the non-profiled portion is about 2.4:1.

In the embodiment shown in FIG. 9, the sanitary napkin 23 has a caliper of about 3.5 mm in the end regions 28 and 30 and a caliper of about 8.5 mm in the central region 32.

The sanitary napkin 23 is worn by the wearer so that the rear end region 30 is placed to the rear of the wearer's body. The outwardly convex longitudinal central channels 62 assist the central region 32 of the sanitary napkin 23 in assuming a W-shaped cross-sectional configuration when the napkin 23 is compressed by the wearer's thighs. This W-shaped configuration is formed by the sides compressing upwards and inwards and the center buckling upward into a convex upward configuration, with the densified region provided by the channels forming the fold lines.

In addition, due to the profiled configuration in the central region 32, the central closed area 72 is brought more closely to the source area of body fluids or the wearer's genital area thereby contributing to a further better fit to the wearer's body. The profiled configuration of the central closed area 72 cooperates with the W-shaped cross-sectional configuration thereby allowing the central closed area 72 to closely fit to the wearer's genital area. This cooperative function enables an improved leakage protection at the central region 32.

The dimensions and values disclosed herein are not to be understood as being strictly limited to the exact numerical values recited. Instead, unless otherwise specified, each such dimension is intended to mean both the recited value and a functionally equivalent range surrounding that value. For example, a dimension disclosed as "40 mm" is intended to mean "about 40 mm."

Every document cited herein, including any cross referenced or related patent or application, is hereby incorporated herein by reference in its entirety unless expressly excluded or otherwise limited. The citation of any document is not an admission that it is prior art with respect to any invention disclosed or claimed herein or that it alone, or in any combination with any other reference or references, teaches, suggests or discloses any such invention. Further, to the extent that any meaning or definition of a term in this document conflicts with any meaning or definition of the same term in a document incorporated by reference, the meaning or definition assigned to that term in this document shall govern.

While particular embodiments of the present invention have been illustrated and described, it would be obvious to those skilled in the art that various other changes and modifications can be made without departing from the spirit and scope of the invention. It is therefore intended to cover in the appended claims all such changes and modifications that are within the scope of this invention.

What is claimed is:

1. A sanitary napkin, comprising:
 - a) a topsheet comprising an apertured formed film;
 - b) a backsheet;
 - c) an absorbent core disposed between the topsheet and the backsheet, the absorbent core comprising a plurality of layers of material;
 - d) a transverse centerline;
 - e) a longitudinal centerline, and a pair of side edges extending generally parallel to the longitudinal centerline;
 - f) a central region;
 - g) a first end region positioned on one side of the central region along the longitudinal centerline, wherein a first boundary between the central region and the first end region is in a first transition area where a transversal distance between the pair of side edges increases from the first end region to the central region;
 - h) a second end region positioned on an opposite side of the central region along the longitudinal centerline, wherein a second boundary between the central region and the second end region is in a second transition area where a transversal distance between the pair of side edges increases from the second end region to the central region; and
 - i) a pair of side flaps comprising a material that is an extension of a material comprised by at least one of the topsheet and the backsheet;
 - j) wherein the sanitary napkin is asymmetric about the transverse centerline so that at least one of a width and a length of the first end region is different than that of the second end region;
 - k) wherein the sanitary napkin is profiled in that the central region comprises additional material such that a central closed area of the central region has a central region caliper that is greater than an end region caliper of the first end region and/or the second end region and wherein a ratio of the central region caliper to the end region caliper is from about 1.1:1 to about 3:1; and

17

- 1) wherein the central closed area is circumscribed by longitudinally-oriented areas of lesser caliper that impart outwardly convex longitudinal side profiles of the area of the central region; and the central closed area does not extend substantially into either of the first or second end regions.
2. The sanitary napkin of claim 1, wherein the area of the central region having a greater caliper has a maximum length of 80-220 millimeters and a maximum width of 25-70 millimeters.
3. The sanitary napkin of claim 1, wherein a layer of the absorbent core has a rectangular shape.
4. The sanitary napkin of claim 3, wherein the layer comprises a combination of cellulosic fibers and absorbent gelling material.
5. The sanitary napkin of claim 1, wherein the area of the central region having a greater caliper entirely overlies the absorbent core.
6. The sanitary napkin of claim 1, wherein: the area of the central region having a greater caliper has a maximum length of 80-220 millimeters and a maximum width of 25-70 millimeters; a layer of the absorbent core has a rectangular shape; the layer comprises a combination of cellulosic fibers and absorbent gelling material; and the area of the central region having a greater caliper entirely overlies the absorbent core.
7. A sanitary napkin, comprising:
- a topsheet;
 - a backsheet;
 - an absorbent core disposed between the topsheet and the backsheet, the absorbent core comprising a plurality of layers of material;
 - a transverse centerline;
 - a longitudinal centerline, and a pair of side edges extending generally parallel to the longitudinal centerline;
 - a central region;
 - a first end region positioned on one side of the central region along the longitudinal centerline, wherein a first boundary between the central region and the first end region is in a first transition area where a transversal distance between the pair of side edges increases from the first end region to the central region;
 - a second end region positioned on an opposite side of the central region along the longitudinal centerline, wherein a second boundary between the central region and the second end region is in a second transition area where a transversal distance between the pair of side edges increases from the second end region to the central region; and
 - a pair of side flaps comprising a material that is separate from a material of at least one of the topsheet and the backsheet;
 - wherein the sanitary napkin is asymmetric about the transverse centerline so that at least one of a width and a length of the first end region is different than that of the second end region;
 - wherein the sanitary napkin is profiled in that the central region comprises additional material such that a central closed area of the central region has a central region caliper that is greater than an end region caliper of the first end region and/or the second end region and wherein a ratio of the central region caliper to the end region caliper is from about 1.1:1 to about 3:1; and
 - wherein the central closed area is circumscribed by longitudinally-oriented areas of lesser caliper that impart outwardly convex longitudinal side profiles of

18

- the area of the central region; and the central closed area does not extend substantially into either of the first or second end regions.
8. The sanitary napkin of claim 7, wherein the area of the central region having a greater caliper has a maximum length of 80-220 millimeters and a maximum width of 25-70 millimeters.
9. The sanitary napkin of claim 7, wherein a layer of the absorbent core has a rectangular shape.
10. The sanitary napkin of claim 9, wherein the layer comprises a combination of cellulosic fibers and absorbent gelling material.
11. The sanitary napkin of claim 7, wherein the area of the central region having a greater caliper entirely overlies the absorbent core.
12. The sanitary napkin of claim 7, wherein: the area of the central region having a greater caliper has a maximum length of 80-220 millimeters and a maximum width of 25-70 millimeters; a layer of the absorbent core has a rectangular shape; the layer comprises a combination of cellulosic fibers and absorbent gelling material; and the area of the central region having a greater caliper entirely overlies the absorbent core.
13. A sanitary napkin, comprising:
- a topsheet;
 - a backsheet;
 - an absorbent core disposed between the topsheet and the backsheet, the absorbent core comprising a plurality of layers of material;
 - a transverse centerline;
 - a longitudinal centerline, and a pair of side edges extending generally parallel to the longitudinal centerline;
 - a central region;
 - a first end region positioned on one side of the central region along the longitudinal centerline, wherein a first boundary between the central region and the first end region is in a first transition area where a transversal distance between the pair of side edges increases from the first end region to the central region;
 - a second end region positioned on an opposite side of the central region along the longitudinal centerline, wherein a second boundary between the central region and the second end region is in a second transition area where a transversal distance between the pair of side edges increases from the second end region to the central region; and
 - a pair of side flaps comprising a material that is an extension of a material comprised by at least one of the topsheet and the backsheet;
 - wherein the sanitary napkin is asymmetric about the transverse centerline so that at least one of a width and a length of the first end region is different than that of the second end region;
 - wherein the sanitary napkin is profiled in that the central region comprises additional material such that a central closed area of the central region has a central region caliper that is greater than an end region caliper of the first end region and/or the second end region and wherein a ratio of the central region caliper to the end region caliper is from about 1.1:1 to about 3:1; and
 - wherein the central closed area is circumscribed by longitudinally-oriented areas of lesser caliper that impart outwardly convex longitudinal side profiles of the area of the central region; and the central closed area does not extend substantially into either of the first or second end regions.

14. The sanitary napkin of claim 13, wherein the area of the central region having a greater caliper has a maximum length of 80-220 millimeters and a maximum width of 25-70 millimeters.

15. The sanitary napkin of claim 13, wherein a layer of the absorbent core has a rectangular shape. 5

16. The sanitary napkin of claim 15, wherein the layer comprises a combination of cellulosic fibers and absorbent gelling material.

17. The sanitary napkin of claim 13, wherein the area of the central region having a greater caliper entirely overlies the absorbent core. 10

18. The sanitary napkin of claim 13, wherein: the area of the central region having a greater caliper has a maximum length of 80-220 millimeters and a maximum width of 25-70 millimeters; a layer of the absorbent core has a rectangular shape; the layer comprises a combination of cellulosic fibers and absorbent gelling material; and the area of the central region having a greater caliper entirely overlies the absorbent core. 15 20

* * * * *