



US011638643B1

(12) **United States Patent**
Askegaard et al.

(10) **Patent No.:** **US 11,638,643 B1**
(45) **Date of Patent:** **May 2, 2023**

- (54) **PROSTHETIC HEART VALVES**
- (71) Applicant: **Laplace Interventional Inc.**, Plymouth, MN (US)
- (72) Inventors: **Gunnar Paul Askegaard**, Brainerd, MN (US); **Lucas Tradd Schneider**, Champlin, MN (US); **Ramji Iyer**, Plymouth, MN (US)
- (73) Assignee: **Laplace Interventional Inc.**, Plymouth, MN (US)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

8,728,155 B2	5/2014	Montorfano et al.
9,393,110 B2	7/2016	Levi et al.
9,579,196 B2	2/2017	Morriss
9,681,951 B2	6/2017	Ratz et al.
10,213,307 B2	2/2019	Dwork
10,321,995 B1	6/2019	Christianson
10,583,000 B2	3/2020	Ratz
10,653,522 B1	5/2020	Vidlund et al.
10,779,936 B2	9/2020	Pollak
10,813,779 B2	10/2020	Fleming, III et al.
10,898,328 B2 *	1/2021	Starksen A61F 2/2466
11,109,965 B2 *	9/2021	Iyer A61F 2/2436
11,337,801 B2 *	5/2022	Iyer A61F 2/2418
11,510,777 B1 *	11/2022	Iyer A61F 2/2436
11,602,433 B2 *	3/2023	Ratz A61F 2/2436

(Continued)

- (21) Appl. No.: **17/986,607**
- (22) Filed: **Nov. 14, 2022**

Related U.S. Application Data

- (60) Provisional application No. 63/390,810, filed on Jul. 20, 2022.
- (51) **Int. Cl.**
A61F 2/24 (2006.01)
- (52) **U.S. Cl.**
CPC *A61F 2/2403* (2013.01); *A61F 2/2436* (2013.01)
- (58) **Field of Classification Search**
CPC A61F 2/2403; A61F 2/2436
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,824,069 A	10/1998	Lemole
6,312,464 B1	11/2001	Navia
6,458,153 B1	10/2002	Bailey et al.


FOREIGN PATENT DOCUMENTS

WO WO 2015/052570 4/2015
Primary Examiner — Suzette J Gherbi
 (74) *Attorney, Agent, or Firm* — Fish & Richardson P.C.

(57) **ABSTRACT**

Prosthetic heart valves may be delivered to a targeted native heart valve site via one or more delivery catheters. In some embodiments, the prosthetic heart valve includes structural features that securely anchor the prosthetic heart valve to the anatomy at the site of the native heart valve. Such structural features can provide robust migration resistance. In addition, the prosthetic heart valves can include structural features that improve sealing between the prosthetic valve and native valve anatomy to mitigate paravalvular leakage. In particular implementations, the prosthetic heart valves occupy a small delivery profile, thereby facilitating a smaller delivery catheter system for advancement to the heart. Some delivery catheter systems can include a curved inner catheter to facilitate deployment of the prosthetic heart valve to a native tricuspid valve site via a superior vena cava or inferior vena cava.

7 Claims, 24 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0149181	A1	7/2005	Eberhardt	2015/0327994	A1	11/2015	Morriss et al.
2007/0055356	A1	3/2007	Eidenschink	2016/0158003	A1	6/2016	Wallace et al.
2010/0023046	A1	1/2010	Heidner et al.	2016/0278922	A1	9/2016	Braido et al.
2010/0161045	A1	6/2010	Righini	2017/0056166	A1	3/2017	Ratz et al.
2010/0217382	A1	8/2010	Chau et al.	2017/0071733	A1	3/2017	Ghione et al.
2010/0316830	A1	12/2010	Hartley et al.	2017/0128199	A1	5/2017	Gurovich et al.
2011/0137397	A1	6/2011	Chau et al.	2017/0128208	A1	5/2017	Christianson et al.
2012/0083832	A1	4/2012	Delaloye et al.	2017/0216023	A1	8/2017	Lane et al.
2013/0211508	A1	8/2013	Lane et al.	2017/0216026	A1	8/2017	Quill et al.
2014/0207231	A1	7/2014	Hacohen et al.	2017/0325945	A1	11/2017	Dale et al.
2014/0222142	A1	8/2014	Kovalsky et al.	2018/0000586	A1	1/2018	Ganesan
2014/0257467	A1	9/2014	Lane et al.	2019/0008636	A1	1/2019	Francis et al.
2014/0277390	A1	9/2014	Ratz	2019/0029811	A1	1/2019	Bishop et al.
2014/0296969	A1	10/2014	Tegels et al.	2019/0183639	A1	6/2019	Moore
2014/0296975	A1	10/2014	Tegels et al.	2020/0179109	A1	6/2020	Reimer
2014/0350669	A1	11/2014	Gillespie et al.	2020/0268512	A1	8/2020	Mohl
2015/0119981	A1	4/2015	Khairkhahan et al.	2021/0244535	A1*	8/2021	Iyer A61F 2/2436
2015/0196390	A1	7/2015	Ma et al.	2021/0346153	A1	11/2021	Vietmeier et al.
2015/0216653	A1	8/2015	Freudenthal	2021/0393401	A1*	12/2021	Iyer A61F 2/2418
				2022/0273427	A1*	9/2022	Iyer A61F 2/2418
				2022/0409369	A1*	12/2022	Christianson A61F 2/2436

* cited by examiner




FIG. 1





FIG. 2



- RA – Right Atrium
- LA – Left Atrium
- RV – Right Ventricle
- LV – Left Ventricle
- Ao – Aorta
- MPA – Main Pulmonary Artery
- SVC – Superior Vena Cava
- IVC – Inferior Vena Cava
- RVOT – Right Ventricular Outflow Tract

FIG. 3




FIG. 5




FIG. 4




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10






FIG. 11






FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40




FIG. 41




FIG. 42




FIG. 43

PROSTHETIC HEART VALVES**CROSS-REFERENCE TO RELATED APPLICATIONS**

This application claims the benefit of U.S. Provisional Application Ser. No. 63/390,810, filed Jul. 20, 2022. The disclosure of the prior application is considered part of (and is incorporated by reference in) the disclosure of this application.

FIELD OF INVENTION

This disclosure generally relates to prosthetic heart valve systems. For example, this disclosure relates to transcatheter deliverable prosthetic heart valves that are adapted to be used to replace a sub-optimally functioning native heart valve, including but not limited to a tricuspid valve.

BACKGROUND

A human heart includes four types of heart valves that are arranged to ensure blood flow in specific directions: mitral, tricuspid, aortic and pulmonary valves. The aortic and pulmonary valves are semilunar valves, which are in the arteries leaving the heart, and prevent blood from flowing back into left ventricle and right ventricle respectively when closed. The mitral and tricuspid valves are atrio-ventricular valves, which are between the atria and the ventricles, and prevent blood from flowing back into left atrium and right atrium respectively when closed. Conditions of stenosis (when valve does not open fully) as well as regurgitation/insufficiency (when valve does not close properly resulting in leaks) are recognized as significant contributors to mortality and morbidity.

Some valve replacement systems include valve prostheses that are compressed into a delivery catheter, also referred to as transcatheter valves, so as to avoid open-heart surgery. Many transcatheter valve prostheses have a tubular frame that may or may not be axisymmetric, and include two or more leaflets. While these transcatheter valve prostheses can be compressed into a catheter, they may still require a large delivery system (for example, a required catheter size of 45 French). This is especially true in case of mitral valve replacement systems and tricuspid valve replacement systems, which often require valve prostheses with a larger profile.

SUMMARY

Some embodiments described herein include a prosthetic heart valve that may be delivered to a targeted native heart valve site via one or more delivery catheters. In some embodiments, a prosthetic heart valve includes structural features that securely anchor the prosthetic heart valve to the anatomy at the site of the native heart valve. Such structural features can provide robust migration resistance. In addition, the prosthetic heart valves can include structural features that improve sealing between the prosthetic valve and native valve anatomy to mitigate paravalvular leakage. In particular implementations, the prosthetic heart valves occupy a small delivery profile, thereby facilitating a smaller delivery catheter system for advancement to the heart. Some delivery catheter systems can include a curved inner catheter to facilitate deployment of the prosthetic heart valve to a native tricuspid valve site via a superior vena cava or inferior vena cava.

In one aspect, this disclosure is directed to a prosthetic heart valve that includes a main body comprising an inflow end portion and an outflow end portion, and an occluder extending between the inflow end and outflow end portions and comprising valve leaflets attached to the main body in an arrangement that: (i) allows blood flow through the occluder in a direction from the inflow end portion toward the outflow end portion along a central axis of the occluder and (ii) prevents blood flow through the occluder in a direction from the outflow end portion toward the inflow end portion. The prosthetic heart valve also includes a first anterior flap extending from the outflow end portion in a first direction that is transverse to the central axis; a posterior flap extending from the outflow end portion in a second direction that is opposite of the first direction; and a posterior arm extending from the inflow end portion in the second direction.

Such a prosthetic heart valve may optionally include one or more of the following features. The prosthetic heart valve may also include an anterior arm extending from the inflow end portion in the first direction. The prosthetic heart valve may also include a second anterior flap extending from the outflow end portion in the first direction. The first and second anterior flaps may overlap each other. A cross-sectional shape of the first and second anterior flaps taken perpendicularly to the first direction may be arcuate.

In another aspect, this disclosure is directed to another prosthetic heart valve. The prosthetic heart valve includes a main body comprising an inflow end portion and an outflow end portion, and an occluder extending between the inflow end and outflow end portions and comprising valve leaflets attached to the main body in an arrangement that: (i) allows blood flow through the occluder in a direction from the inflow end portion toward the outflow end portion along a central axis of the occluder and (ii) prevents blood flow through the occluder in a direction from the outflow end portion toward the inflow end portion. The prosthetic heart valve also includes an anterior flap extending from the outflow end portion in a first direction that is transverse to the central axis; a posterior flap extending from the outflow end portion in a second direction that is opposite of the first direction; and an anterior arm extending from the inflow end portion in the first direction.

In another aspect, this disclosure is directed to another prosthetic heart valve. The prosthetic heart valve includes a main body comprising an inflow end portion and an outflow end portion, and an occluder extending between the inflow end and outflow end portions and comprising valve leaflets attached to the main body in an arrangement that: (i) allows blood flow through the occluder in a direction from the inflow end portion toward the outflow end portion along a central axis of the occluder and (ii) prevents blood flow through the occluder in a direction from the outflow end portion toward the inflow end portion. The prosthetic heart valve also includes a first anterior flap extending from the outflow end portion in a first direction that is transverse to the central axis; and a second anterior flap extending from the outflow end portion in the first direction. A cross-sectional shape of the first and second anterior flaps taken perpendicularly to the first direction is arcuate from an outer edge of the first anterior flap to an outer edge of the second anterior flap.

In another aspect, this disclosure is directed to another prosthetic heart valve. The prosthetic heart valve includes a main body comprising an inflow end portion and an outflow end portion, and an occluder extending between the inflow end and outflow end portions and comprising valve leaflets

attached to the main body in an arrangement that: (i) allows blood flow through the occluder in a direction from the inflow end portion toward the outflow end portion along a central axis of the occluder and (ii) prevents blood flow through the occluder in a direction from the outflow end portion toward the inflow end portion. The prosthetic heart valve also includes a first anterior flap extending from the outflow end portion in a first direction that is transverse to the central axis; a second anterior flap extending from the outflow end portion in the first direction; a first posterior flap extending from the outflow end portion in a second direction that is opposite of the first direction; and a second posterior flap extending from the outflow end portion in the second direction. A passageway is defined between the first and second posterior flaps. The first and second posterior flaps extend from the outflow end portion farther than the first and second anterior flaps.

In another aspect, this disclosure is directed to a method of deploying a prosthetic heart valve. The method includes engaging any of the prosthetic heart valves described herein with anatomical structures of a native tricuspid valve. The lateral anterior flap extends into a right ventricular outflow tract (RVOT) and engages with a lateral wall of the RVOT to provide anchoring during diastole.

In another aspect, this disclosure is directed to another method of deploying a prosthetic heart valve. The method includes engaging any of the prosthetic heart valves described herein with anatomical structures of a native tricuspid valve. A distal end portion of the posterior arm rests against an interior wall of an inferior vena cava, or coronary sinus, or a right atrium.

In another aspect, this disclosure is directed to another method of deploying a prosthetic heart valve. The method includes engaging any of the prosthetic heart valves described herein with anatomical structures of a native tricuspid valve. A distal end portion of the anterior arm rests against an interior wall of a right atrial appendage.

Various types of deployment systems may be used in combination with the prosthetic tricuspid valves described herein. In some embodiments described herein, such a deployment system may include an outer sheath catheter defining a first lumen; a middle deflectable catheter slidably disposed in the first lumen and defining a second lumen, the middle deflectable catheter comprising a selectively deflectable distal end portion with at least one plane of deflection; and an inner control catheter slidably disposed in the second lumen and including one or more control wires that configure the inner control catheter to releasably couple with a prosthetic heart valve. The inner control catheter includes a distal end portion that elastically transitions to a naturally curved configuration when the inner control catheter converts from being radially constrained to being radially unconstrained. In some embodiments, the distal end portion defines an interior angle of less than 135 degrees when in the naturally curved configuration.

In another aspect, this disclosure is directed to another method of deploying a prosthetic heart valve. The method includes advancing the prosthetic heart valve toward a native tricuspid valve, via a jugular vein and a superior vena cava, while the prosthetic heart valve is releasably coupled to a prosthetic heart valve deployment system and diametrically constrained in a low profile delivery configuration. The prosthetic heart valve deployment system includes an outer sheath catheter defining a first lumen; a middle deflectable catheter slidably disposed in the first lumen and defining a second lumen, the middle deflectable catheter comprising a selectively deflectable distal end portion; and an inner

control catheter slidably disposed in the second lumen and including one or more control wires that are releasably coupled with the prosthetic heart valve. The inner control catheter includes a distal end portion constrained in the first lumen. The method also includes retracting the outer sheath relative to the inner control catheter to allow the distal end portion of the inner control catheter to become radially unconstrained and to elastically transition to a curved configuration; and deflecting the selectively deflectable distal end portion of the middle deflectable catheter so that the inner control catheter and the middle deflectable catheter in combination are curved by at least 90° relative to the outer sheath.

In another aspect, this disclosure is directed to a prosthetic heart valve deployment system that includes: an outer sheath catheter defining a first lumen; a middle deflectable catheter slidably disposed in the first lumen and defining a second lumen, the middle deflectable catheter comprising a selectively deflectable distal end portion with at least one plane of deflection; and an inner control catheter slidably disposed in the second lumen and including one or more control wires that configure the inner control catheter to releasably couple with a prosthetic heart valve. The inner control catheter includes a distal end portion that elastically transitions to a naturally curved configuration when the inner control catheter converts from being radially constrained to being radially unconstrained.

In another aspect, this disclosure is directed to another method of deploying a prosthetic heart valve. The method includes advancing the prosthetic heart valve toward a native tricuspid valve, via a femoral vein and an inferior vena cava, while the prosthetic heart valve is releasably coupled to a prosthetic heart valve deployment system and diametrically constrained in a low profile delivery configuration. The prosthetic heart valve deployment system includes an outer sheath catheter defining a first lumen; a middle deflectable catheter slidably disposed in the first lumen and defining a second lumen, the middle deflectable catheter comprising a selectively deflectable distal end portion; and an inner control catheter slidably disposed in the second lumen and including one or more control wires that are releasably coupled with the prosthetic heart valve. The inner control catheter includes a curved distal end portion that is curved by less than 20° when constrained in the first lumen. The method also includes advancing the inner control catheter relative to the outer sheath to allow the curved distal end portion to become unconstrained and to elastically transition to a curved configuration that is curved by at least 45° relative to the outer sheath; and deflecting the selectively deflectable distal end portion of the middle deflectable catheter so that the inner control catheter and the middle deflectable catheter in combination are curved by at least 90° relative to the outer sheath.

Any of the prosthetic heart valves described herein may optionally include one or more of the following additional features. In some embodiments, portions of the first anterior flap and the second anterior flap overlap each other. The prosthetic tricuspid valve may also include a posterior flap extending laterally from the end of the main body in an opposite direction as the first and second anterior flaps. In some embodiments, the first and second anterior flaps extend farther laterally than the posterior flap. In particular embodiments, the first and second anterior flaps in combination are wider (in the septal to lateral direction) than the posterior flap. A framework of the prosthetic tricuspid valve (that comprises the main body, the first and second anterior flaps, and the posterior flap) may be made of a single, unitary

5

material that was cut and expanded. In some embodiments, a distal tip portion of the posterior flap extends along an axis that is at a non-zero angle relative to a portion of the posterior flap that extends directly from the main body. In some examples, having the portions of the first anterior flap and the second anterior flap that overlap each other increases a bending resistance of the first anterior flap and the second anterior flap in combination as compared to the first anterior flap and the second anterior flap individually. Having the portions of the first anterior flap and the second anterior flap as separate members can configure the prosthetic tricuspid valve to have a pacemaker lead pass through the prosthetic tricuspid valve between the first and second anterior flaps. The prosthetic tricuspid valve may also include one or more additional anterior flaps extending laterally from the end of the main body in the same direction as the first and second anterior flaps. The prosthetic tricuspid valve may also include two or more posterior flaps extending laterally from the end of the main body in an opposite direction as the first and second anterior flaps. Having the portions of the first posterior flap and the second posterior flap as separate members can configure the prosthetic tricuspid valve to have a pacemaker lead pass through the prosthetic tricuspid valve between the first and second posterior flaps. In some embodiments, a transverse cross-section of the main body has an oval shaped outer profile that defines a major diameter and a minor diameter. The minor diameter is shorter than the major diameter. The occluder may have a circular cross-sectional shape, and the anterior and posterior flaps may extend transversely to the major diameter. The prosthetic heart valve may also include a leaflet engagement member extending from the main body, a portion of the leaflet engagement member extending toward the inflow end portion and terminating at a free end. The leaflet engagement member may extend in the second direction. The posterior flap may extend farther away from the main body than the leaflet engagement member.

BRIEF DESCRIPTION OF FIGURES

FIG. 1 shows a sectional view of a human heart including four heart valves (mitral valve, tricuspid valve, aortic valve, and pulmonary valve) that allow blood flow through specific pathways. The mitral and tricuspid valve are arranged to prevent backflow of blood into left atrium and right atrium respectively when the left and right ventricle contract respectively.

FIG. 2 shows a top view of the tricuspid valve of FIG. 1 and including three native leaflets: anterior, posterior and septal.

FIG. 3 shows another sectional view of a human heart including the four chambers (right atrium, right ventricle, left atrium, and left ventricle) and major conduits that deliver blood to the heart and transport blood away from the heart.

FIG. 4 shows a schematic view of the right side of the heart of FIG. 3, including the right atrium ("RA"), right ventricle ("RV"), and right ventricle outflow tract ("RVOT"), in accordance with some native anatomies.

FIG. 5 shows another schematic view of the right side of the heart of FIG. 3, including the RA, RV, and RVOT, in accordance with some native anatomies.

FIG. 6 shows a side view of an example prosthetic heart valve in accordance with some embodiments described herein.

FIG. 7 shows a side view of the prosthetic heart valve of FIG. 6 engaged within a native tricuspid valve.

6

FIG. 8 shows a top view of the prosthetic heart valve of FIG. 6.

FIG. 9 shows a top view of a frame of another example prosthetic heart valve in accordance with some embodiments described herein.

FIG. 10 schematically illustrates a transverse plane view of a native tricuspid valve annulus and RVOT.

FIG. 11 schematically illustrates a top view of the prosthetic heart valve of FIG. 6.

FIG. 12 schematically illustrates the prosthetic heart valve of FIG. 11 engaged with the native tricuspid valve annulus and RVOT of FIG. 10.

FIG. 13 schematically illustrates a cross-section view taken along the cutting plane 13-13 of FIG. 12 and including the anterior flaps of the prosthetic heart valve and the RVOT.

FIG. 14 schematically shows a longitudinal plane cross-section view of an anterior portion of a native tricuspid valve annulus and the anterior flaps of prosthetic heart valves described herein.

FIG. 15 is an anterior side view of the prosthetic heart valves described herein showing a cross-sectional shape of the anterior flaps.

FIG. 16 shows a top view of some prosthetic heart valves described herein.

FIG. 17 shows a plan view of an example prosthetic heart valve deployment system in accordance with some embodiments.

FIG. 18 shows an expanded view of a distal end portion of the prosthetic heart valve deployment system of FIG. 17.

FIG. 19 schematically illustrates a side view of the prosthetic tricuspid valves described herein.

FIG. 20 schematically shows the prosthetic tricuspid valve of FIG. 19 coupled with the prosthetic heart valve deployment system of FIG. 17.

FIGS. 21 through 30 show an example trans-jugular method of deploying the prosthetic tricuspid valves described herein using the prosthetic heart valve deployment system of FIG. 17.

FIG. 31 schematically shows a top view of another example prosthetic heart valve in accordance with some embodiments described herein.

FIGS. 32-37 schematically depict an example trans-femoral method of deploying the prosthetic heart valve of FIG. 31 using the prosthetic heart valve deployment system of FIG. 17.

FIG. 38 is a perspective view of an example frame that can be used for the prosthetic heart valves described herein.

FIG. 39 is a top view of the frame of FIG. 38.

FIG. 40 is a side view of the frame of FIG. 38.

FIG. 41 is a perspective view of another example frame that can be used for the prosthetic heart valves described herein.

FIG. 42 is a top view of the frame of FIG. 41.

FIG. 43 is a side view of the frame of FIG. 41.

DETAILED DESCRIPTION

Some embodiments described herein include a prosthetic heart valve that may be delivered to a targeted native heart valve site via one or more delivery catheters. In some embodiments, a prosthetic heart valve includes structural features that securely anchor the prosthetic heart valve to the anatomy at the site of the native heart valve. Such structural features can provide robust migration resistance during diastole and systole. In addition, the prosthetic heart valves can include structural features that improve sealing between the prosthetic valve and native valve anatomy to mitigate

paravalvular leakage. In particular implementations, the prosthetic heart valves occupy a small delivery profile, thereby facilitating a smaller delivery catheter system for advancement to the heart. Some catheter-based prosthetic heart valve deployment systems can include a curved inner catheter to facilitate deployment of the prosthetic heart valve to a native tricuspid valve site via a superior vena cava or inferior vena cava.

Referring to FIG. 1, certain aspects of the concepts described herein regarding the heart valve replacement systems can be implemented in prosthetic valve designs that are intended for use at any of the four heart valves that allow blood flow through a specific pathway: mitral valve, tricuspid valve, aortic valve and the pulmonary valve. FIG. 2 depicts, for example, a targeted site at a tricuspid valve of the heart. The tricuspid valve 10 includes an anterior leaflet 11a, a posterior leaflet 11p, and a septal leaflet 11s, and an annulus 12. In some circumstances, the tricuspid valve 10 may undergo stenosis or anatomical changes that cause tricuspid regurgitation, such as instances in which the distance between the anterio-septal commissure and the anterio-posterior commissure of the native tricuspid valve increases with the progression of a diseased state due to dilation of the annulus 12 of the tricuspid valve 10.

FIG. 3 illustrates a longitudinal sectional view of a human heart 1 that shows the four chambers (right atrium, right ventricle, left atrium, and left ventricle) and the major conduits that deliver blood to the heart 1 and transport blood away from the heart 1. The tricuspid valve 10 is located between the right atrium and the right ventricle. Blood enters the right atrium from the superior vena cava and the inferior vena cava. Blood flows from the right atrium to the right ventricle through the tricuspid valve 10. The blood exits the right ventricle and enters the main pulmonary artery (“MPA”) via the RVOT that is adjacent to the tricuspid valve 10.

FIGS. 4 and 5 schematically illustrate the right side of the heart 1, including the right atrium, right ventricle, and tricuspid valve 10 therebetween. Naturally, there is anatomical variability among the human population. FIGS. 4 and 5 depict some of the anatomical variability. In particular, FIG. 4 shows a heart 1a that includes the presence of a posterior shelf 11. In contrast, FIG. 5 shows a heart 1b with a lack of any such posterior shelf. Some human hearts (such as the heart 1a) have a posterior shelf 11, but some human hearts (such as the heart 1b) do not have a distinct posterior shelf. The prosthetic tricuspid valves disclosed herein are designed to be implantable in the native tricuspid valve 10 of both types of anatomies (e.g., both the heart 1a with the posterior shelf 11, and the heart 1b without the posterior shelf).

The posterior shelf 11, when present, provides an anatomical structure that can be used advantageously for the anchorage of a prosthetic tricuspid valve (as described further herein). When no such posterior shelf is present (e.g., as shown in FIG. 5), robust anchorage of a prosthetic tricuspid valve at the site of the native tricuspid valve 10 is more challenging. Nevertheless, and as described in U.S. patent application Ser. No. 17/747,507 filed on May 18, 2022) which is hereby incorporated by reference in its entirety and for all purposes), the prosthetic tricuspid valves described herein can be successfully used in such a case.

FIGS. 6-8 illustrate an example prosthetic tricuspid valve 100 (or simply “valve 100”) in accordance with some example embodiments of this disclosure. The valve 100 includes a frame 102 and a covering 104 attached to the

frame 102. FIG. 7 shows the valve 100 engaged with a native tricuspid valve 10 between the right atrium and the right ventricle.

The frame 102 comprises a cellular structure that provides mechanical support for the shape and structures of the valve 100. In some embodiments, the frame 102 is made from nitinol (NiTi), stainless steel, cobalt chromium, MP35N, titanium, polymeric materials, other biocompatible materials, or any combination thereof. Some or all parts of the frame 102 may be covered by the covering 104.

The frame 102 can be made of a laser cut, expanded, and shape-set material in some embodiments. The frame 102 is self-expanding in some embodiments. In some embodiments, the precursor material is tubular NiTi, a NiTi sheet, or other suitable types of precursor materials.

The covering 104 may be made of a biocompatible polymer material (e.g., expanded polytetrafluoroethylene (ePTFE), UHMWPE (ultra-high molecular weight polyethylene), nylon, polyester (e.g., DACRON), or another synthetic material), natural tissues (e.g., bovine, porcine, ovine, or equine pericardium), or any combination thereof. The covering 104 can be attached to the frame 102 by suturing, using clips, adhesives, and/or any other suitable attachment process.

The valve 100 includes a main body 106. The main body 106 includes an occluder 110 (e.g., a one-way valve) that defines a central axis 101. The occluder 110 has flexible leaflets 111a, 111b, and 111c (collectively 111a-c) that cause the occluder 110 to function as a one-way valve (in a manner like a native tricuspid valve). The occluder 110 defines a circular inlet where the edges of leaflets 111a-c are attached to the frame 102. Other side edges of the leaflets 111a-c are attached to posts 112a, 112b, and 112c of the frame 102. The leaflets 111a-c also have distal free edges that are coaptable with each other to facilitate the opening and sealing of the occluder 110.

The main body 106 of the valve 100 includes an inflow end portion 102i, a mid-body portion 102m, and an outflow end portion 102o. The inflow end portion 102i includes a series of arch shapes in the frame 102, circumscribing the axis 101 of the occluder 110. The occluder leaflets 111a-c allow blood to directionally flow through the occluder 110 from the inflow end portion 102i to the outflow end portion 102o. The leaflets 111a-c of the occluder 110 close against each other (e.g., coapt) to prevent blood flow in the other direction (to prevent blood flow from the outflow end portion 102o to the inflow end portion 102i).

The embodiments of the valve 100 depicted in this disclosure employ three occluder leaflets 111a-c, which is referred to as tri-leaflet occluder. The occluder 110 of the valve 100 can optionally employ configurations other than a tri-leaflet occluder. For example, bi-leaflet, quad-leaflet, or mechanical valve constructs can be used in some embodiments. In particular implementations described herein, the flexible leaflets 111a-c are made of natural tissues such as porcine or bovine or equine or ovine pericardium. In such embodiments, the tissues are chemically cross-linked using glutaraldehyde or formaldehyde, or other aldehydes commonly used as crosslinking agents. In other embodiments, the flexible leaflets 111a-c are made of polymers such as polyurethane, polyester (DACRON) or expanded polytetrafluoroethylene (ePTFE). In some embodiments, the flexible leaflets 111a-c are attached to structural frame 102 using sutures that could be made of materials including but not limited to UHMWPE, nylon, or polyester (e.g., DACRON).

The valve 100 also includes a first anterior flap 120a (or septal anterior flap 120a), a second anterior flap 120b (or

lateral anterior flap **120b**), and at least one posterior flap **130**. The frame **102** and the covering **104** combine to form the anterior flaps **120a-b** and the posterior flap **130**. The frame **102** provides the structure of the anterior flaps **120a-b** and the posterior flap **130**, and the covering **104** provides occlusion. While the depicted embodiment includes two anterior flaps **120a-b**, in some embodiments one, three, four, or more than four anterior flaps can be included. While the depicted embodiment includes a single posterior flap **130**, in some embodiments two, three, four, or more than four posterior flaps can be included. For instance, FIG. **31** refers to an embodiment with two posterior flaps **330a** and **330b**.

The anterior flaps **120a-b** and the posterior flap **130** extend away from the outflow end portion **102o** of the main body **106** in opposite directions away from the axis **101**. That is, the posterior flap **130** extends directionally opposite from the extension direction of the first and second anterior flaps **120a-b**. In some embodiments, the posterior flap **130** extends 180° opposite from the extension direction of the first and second anterior flaps **120a-b**. In particular embodiments, the anterior flaps **120a-b** and the posterior flap **130** extend away from the outflow end portion **102o** of the main body **106** transverse to the axis **101** of the occluder **110**.

In the depicted embodiment, the first anterior flap **120a** and the second anterior flap **120b** each include a mid-body portion **124** (FIG. **6**) that is bent at an angle so as to direct terminal end portions of the anterior flaps **120a-b** toward the inlet end of the main body **106**. In some embodiments, the anterior flaps **120a-b** initially extend away from the main body **106** substantially perpendicularly (e.g., within about 80° to 100°) to the central axis **101**. Then, at the mid-body portion **124**, the anterior flaps **120a-b** have a bend that defines an angle θ in a range of between 20° to 60°, or 30° to 60°, or 30° to 70°, or 40° to 60°, or 40° to 70°, or 40° to 50°, without limitation.

The bends in the mid-body **106** of the anterior flaps **120a-b** can allow the anterior flaps **120a-b** to conform to the contours of the wall that defines the RVOT (as shown in FIG. **7**). Accordingly, the bent anterior flaps **120a-b** can reduce the potential of the anterior flaps **120a-b** to restrict blood flow through the RVOT in some cases.

As shown in FIG. **8**, the depicted embodiment includes an opening **126a** that is defined by the covering **104** located at a terminal end portion of the first anterior flap **120a**. Additionally, the covering **104** on the second anterior flap **120b** defines an opening **126b** at a terminal end portion of the second anterior flap **120b**.

The openings **126a-b** in the end portions of the anterior flaps **120a-b** allow blood to flow through the anterior flaps **120a-b** (via the openings **126a-b**). This can be beneficial because in some implementations the anterior flaps **120a-b** extend into the RVOT. Accordingly, such openings **126a-b** may in some cases reduce the potential of the anterior flaps **120a-b** to restrict blood flow through the RVOT.

In the depicted embodiment, the posterior flap **130** includes a first portion **130a** and a second portion **130b** that are arranged at an angle in relation to each other. The first portion **130a** extends away from the outflow end portion **102o** of the main body **106** generally transverse to the axis **101** of the occluder **110**. The second portion **130b** of the posterior flap **130** extends from the first portion **130a**. In the depicted embodiment, the second portion **130b** extends generally parallel to the axis **101** of the occluder **110**. The angle defined between the first portion **130a** and the second portion **130b** can be in a range of 80° to 100°, or 70° to 110°, or 60° to 120°, or 50° to 130°, or 40° to 140°, without limitation.

The first anterior flap **120a** and the second anterior flap **120b** each extend in the same direction, which is opposite of the direction that the posterior flap **130** extends. In the depicted embodiment, portions of the first anterior flap **120a** and the second anterior flap **120b** overlap each other. An advantage of having the two separate anterior flaps **120a-b** (rather than a single larger anterior flap) is that the anterior flap portion of the valve **100** can be radially compressed to a smaller profile for transcatheter delivery by the virtue of having the two separate anterior flaps **120a-b** (as compared to having a single larger anterior flap).

In some embodiments, as shown in FIG. **7**, the first and second anterior flaps **120a-b** extend into the RVOT and overlap one axially on top of the other. This arrangement is functionally akin to a cantilevered beam arrangement. With the first and second anterior flaps **120a-b** overlapping on each other, the bending resistance of the first and second anterior flaps **120a-b** is increased (as compared to a single flap or non-overlapping flaps). This arrangement enables an advantageous extent of rigidity, without having to use framework members that are larger in cross-section. That is, the overlapping arrangement of the first and second anterior flaps **120a-b** allow for the use of smaller framework members, which in turn importantly allows for a smaller collapsed delivery size (diameter). In other words, overlapping arrangement of the first and second anterior flaps **120a-b** provides a support structure that is thicker without having to use a material with higher wall thickness (from which the framework is created); ultimately providing the bending stiffness or rigidity that keeps the valve **100** stable when RV pressure acts on the valve **100**.

In the depicted embodiment, an open passage **122** (e.g., see FIG. **16**) is defined between the first anterior flap **120a** and the second anterior flap **120b**. The open passage **122** can be used, for example, for passing a pacemaker lead through the valve **100**, without disturbing the functioning of the occluder **110**.

Accordingly, the valve **100** can facilitate the pass-through of the pacemaker lead while still providing sealing to prevent tricuspid valve regurgitation from the RV to the RA. In some cases, the pacemaker lead is pre-existing and the valve **100** is implanted subsequently (with the open passage **122** being used to receive the pacemaker lead). In other cases, the valve **100** can be pre-existing and the pacemaker lead can be subsequently passed through the open passage **122**. This could take place both during the same implant procedure, or as a subsequent procedure.

FIG. **31** illustrates another example prosthetic valve **300**. The valve **300** defines an open passage **332** between the posterior flaps **330a** and **330b** that can be used, for example, for passing a pacemaker lead through the valve **300**, without disturbing the functioning of the occluder **310**. In some cases, the pacemaker lead is pre-existing and the valve **300** is implanted subsequently (with the open passage **322** being used to receive the pacemaker lead). In other cases, the valve **300** can be pre-existing and the pacemaker lead can be subsequently passed through the open passage **322**.

Still referring to FIGS. **6-8**, the valve **100** also includes one or more leaflet engagement members **140**. In the depicted embodiment, the valve **100** includes two leaflet engagement members: a first leaflet engagement member **140a** and a second engagement member **140b**. In the depicted embodiment, the leaflet engagement members **140a-b** extend from the outflow end portion **102o** of the main body **106**. In some embodiments, the leaflet engagement members **140a-b** extend from the mid-body portion **102m** of the main body **106**.

11

The leaflet engagement members **140a-b** extend from the frame **102** and bend toward the inflow end portion **102i** of the main body **106**. In other words, a portion of each leaflet engagement member **140a-b** extends toward the inflow end portion **102i** of the main body **106**. A space, groove, or slot is defined between the leaflet engagement members **140a-b** and the outer surface of the frame **102** (with the covering **104** being present on the frame **102** and leaflet engagement members **140a-b**). As described further below, the space, groove, or slot receives and mechanically captures/holds a portion of a native leaflet (e.g., the posterior leaflet **11p** and/or the septal leaflet **11s**) to provide migration resistance for the valve **100**.

In the depicted embodiment, the leaflet engagement members **140a-b** extend from the frame **102** of the main body **106** in the same direction as the posterior flap **130**. The posterior flap **130** extends away from the main body **106** farther than the leaflet engagement members **140a-b**. Various other arrangements of the leaflet engagement members **140a-b** and the posterior flap **130** are also envisioned and within the scope of this disclosure.

The leaflet engagement members **140a-b** may be U-shaped wire loops, as in the depicted embodiment. The wire loops that make up the leaflet engagement members **140a-b** can be continuous with the wire members of the frame **102**.

In the depicted embodiment, the leaflet engagement members **140a-b** terminate at free ends. Accordingly, the leaflet engagement members **140a-b** point toward the inflow end portion **102i** of the main body **106**, with the free ends of the leaflet engagement members **140a-b** being the closest to the inflow end portion **102i**. This arrangement defines the space, groove, or slot receives and mechanically captures/holds a portion of a native leaflet to provide migration resistance for the valve **100**.

The depicted embodiment of the valve **100** includes an optional posterior arm **150**. The posterior arm **150** comprises a wire member (e.g., an elongated loop) that extends from the frame **102** and includes a free end **150e** (which can also be said to be located at a distal end portion of the posterior arm **150**). In some embodiments, the posterior arm **150** is a wire member that is constructed unitarily with wire members of the frame **120**. Hence, it can be said that the posterior arm **150** is a portion of the frame **120**. In the depicted embodiment, the covering **104** is attached to the posterior arm **150**, including the free end **150e**.

In the depicted embodiment, the posterior arm **150** extends from the inflow end portion **102i** of the frame **102**. The posterior arm **150** extends in a direction that is the same as, or that is generally (e.g., $\pm 20^\circ$) parallel to, the direction in which the posterior flap **130** extends. In some embodiments, the posterior arm **150** extends from the mid-body portion **102m** of the frame **102**. The location of the free end **150e** is within a transverse plane (e.g., taken perpendicular to the axis **101**) that intersects the mid-body portion **102m** of the frame **102** or the inflow end portion **102i** of the frame **102**.

The posterior arm **150** provides additional anchorage and migration resistance for the valve **100**. As depicted in FIG. 7, the free end **150e** of the posterior arm **150** abuts against an anatomical structure when the valve **100** is engaged in a native tricuspid valve **10**. In some cases, the free end **150e** of the posterior arm **150** abuts against an interior wall of an inferior vena cava, or coronary sinus, or the right atrium, or another anatomical structure. Where it abuts can be largely a function of the variable anatomy from patient to patient. The migration resistance provided by the posterior arm **150**

12

can be particularly advantageous during diastole when the occluder **110** is open to allow blood flow from the right atrium to the right ventricle via the occluder **110**.

Referring also to FIG. 9, in some embodiments the frame **102** can include an anterior arm **160**. The anterior arm **160** may also be covered similarly to the posterior arm **150**. The anterior arm **160** comprises a wire member (e.g., an elongated loop) that extends from the frame **102** and includes a free end **160e** (which can also be said to be located at a distal end portion of the posterior arm **160**). In some embodiments, the anterior arm **160** is a wire member that is constructed unitarily with wire members of the frame **120**. Hence, it can be said that the anterior arm **160** is a portion of the frame **120**. In the depicted embodiment, the covering **104** is attached to the anterior arm **160**, including the free end **160e**.

In the depicted embodiment, the anterior arm **160** extends from the inflow end portion **102i** of the frame **102**. The anterior arm **160** extends in an anterior direction away from the axis **101** (e.g., a direction that is generally the same as the direction in which the anterior flaps **120a-b** extend). In some embodiments, the anterior arm **160** extends from the mid-body portion **102m** of the frame **102**. The location of the free end **160e** is within a transverse plane (e.g., taken perpendicular to the axis **101**) that intersects the mid-body portion **102m** of the frame **102** or the inflow end portion **102i** of the frame **102**.

The anterior arm **160** provides additional anchorage and migration resistance for the valve **100**. The free end **160e** of the anterior arm **160** abuts against an anatomical structure when the valve **100** is engaged in a native tricuspid valve **10**. In some cases, the free end **160e** of the anterior arm **160** abuts against an interior wall of a right atrial appendage or another anatomical structure. Where the anterior arm **160** lands relative to the anatomy can vary based on patient to patient variability. The migration resistance provided by the anterior arm **160** can be particularly advantageous during diastole when the occluder **110** is open to allow blood flow from the right atrium to the right ventricle via the occluder **110**.

Some embodiments of the valve **100** include the posterior arm **150**, but not the anterior arm **160**. Other embodiments of the valve **100** include the anterior arm **160**, but not the posterior arm **150**. Still other embodiments of the valve **100** include both the posterior arm **150** and the anterior arm **160**.

FIG. 10 schematically illustrates a transverse plane view of a native tricuspid valve **10**. The native tricuspid valve **10** includes the annulus **12**. The RVOT extends away from the native tricuspid valve **10** along an arcuate path.

FIG. 11 schematically illustrates a top view of the valve **100**. The valve **100** includes the main body **106**, the occluder **110**, the septal anterior flap **120a**, the lateral anterior flap **120b**, the posterior flap **130**, and the posterior arm **150**.

FIG. 12 schematically illustrates the valve **100** engaged in the anatomy of the native tricuspid valve **10** (that is also illustrated in FIG. 10). In this illustration, it can be seen how the septal anterior flap **120a** and the lateral anterior flap **120b** extend into the RVOT. Moreover, it can be seen that an edge of the lateral anterior flap **120b** abuts against and extends along a lateral wall **14** of the RVOT.

FIG. 13 schematically illustrates a cross-sectional view of the RVOT and distal end portions of the anterior flaps **120a-b**. This cross-sectional view is taken along the cutting plane **13-13** shown in FIG. 12. It can be seen that the edge of the lateral anterior flap **120b** abuts against and engages with the anatomical topography of the lateral wall **14** of the RVOT. The interfacing relationship between the lateral anterior flap **120b** and the lateral wall **14** of the RVOT

13

provides anchorage and migration resistance of the valve **100** relative to the native tricuspid valve **10**. For example, there is a frictional migration resistance aspect provided by the normal forces exerted by the edge of the lateral anterior flap **120b** against the lateral wall **14** of the RVOT. In addition, in some embodiments there is supplementary migration resistance provided because the edge of the lateral anterior flap **120b** can seat against certain anatomical topographical features of the lateral wall **14** of the RVOT. In such a case, the lateral wall **14** physically supports the lateral anterior flap **120b** and resists movement of the valve **100** relative to the anatomy of the native tricuspid valve **10** and RVOT. The interfacing relationship between the lateral anterior flap **120b** and the lateral wall **14** of the RVOT provides anchorage and migration resistance of the valve **100** relative to the native tricuspid valve **10** that is particularly beneficial during diastole when the occluder **110** is open to allow blood flow from the right atrium to the right ventricle via the occluder **110**.

Referring again to FIG. **10**, the shape of the annulus **12** of many tricuspid valves is not circular. Often, as depicted here, shape of the annulus **12** is oblong or ovoidal (oval shaped). That is, the distance between the posterior and anterior regions of the annulus **12** is longer than the distance between the septal and lateral regions of the annulus **12**. Accordingly, it can be said that the annulus **12** defines a major diameter **16** between the posterior and anterior regions, and a minor diameter **18** between the septal and lateral regions of the annulus **12**.

Also referring again to FIG. **12**, in this embodiment of the valve **100**, the main body **106** has an oval outer cross-sectional shape. In contrast, the occluder **110** within the main body **106** has a circular cross-sectional shape. The oval shaped main body **106** of the valve **100** has a major diameter **108** and a minor diameter **109**. The anterior flaps **120a-b** and the posterior flap **130** extend from the main body **106** along a direction that is transverse to the major diameter **108** of the oval shaped main body **106**. In some embodiments, the anterior flaps **120a-b** and/or the posterior flap **130** extend from the main body **106** substantially orthogonally or perpendicularly (e.g., $90^\circ \pm 5^\circ$, $90^\circ \pm 10^\circ$, $90^\circ \pm 15^\circ$, or $90^\circ \pm 20^\circ$,) to the major diameter **108** of the oval shaped main body **106**.

In some embodiments, as depicted in FIG. **12**, the main body **106** is smaller than the full size/area of the annulus **12**. Accordingly, the anterior flaps **120a-b** can be used to fill up the internal area defined the annulus **12** that is not occupied by the main body **106**. The occluder **110** occupies a circular cross-sectional area that is smaller than the cross-sectional area main body **106**, which is adequate for the hemodynamics of the blood flow between the atrium and the ventricle. In some embodiments, the percentage of the internal area defined by the annulus **12** that is occupied by the main body **106** is about 50% (with the remaining about 50% of the area of the annulus **12** being covered by the anterior flaps **120a-b**). In some embodiments, the percentage of the area of the annulus **12** that is occupied by the main body **106** is in a range of about 50% to 60%, or 55% to 65%, or 60%, to 70%, or 65% to 75%, or 70% to 80%, or 75% to 85%, or 60% to 80%, without limitation, with the anterior flaps **120a-b** covering the remainder of the area of the annulus **12**. In some embodiments, the anterior flaps **120a-b** cover at least 50%, or at least 40%, or at least 30%, or at least 20%, or at least 10%, or at least 5% of the internal area defined by the annulus **12**.

The fact that the anterior flaps **120a-b** cover at least a portion of the area defined within the annulus **12** can be

14

beneficial for additional reasons. For example, if, at some point in the future after the valve **100** has been implanted in the annulus **12**, a pacemaker lead needs to be passed through the annulus **12**, then a location on the anterior flaps **120a-b** can be punctured to allow the pacemaker lead to pass through the anterior flaps **120a-b**. The puncture can be at the open passage **122**, or at another location of the anterior flaps **120a-b**. The ability to pass a pacemaker lead through the anterior flaps **120a-b** is advantageous because doing so does not affect the functionality of the occluder **110**. This is advantage is made possible by the fact that the anterior flaps **120a-b** cover at least a portion of the area of the annulus **12**.

Since, as depicted in the example of FIG. **12**, in some cases a portion of the oval shaped annulus **12** is covered by the anterior flaps **120a-b**, the main body **106** need not be circular, and can be constructed to have various types of cross-sectional shapes. An oval shape (as shown) may be preferable in some cases, as it can be radially compressed well for fitting in a low-profile delivery catheter because it can have a smaller perimeter due to the minor diameter **109** of the main body **106** being shorter than the major diameter **108**. If, for example, the main body **106** had a circular cross-sectional shape with a diameter equal to the major diameter **108**, the main body **106** could not be radially crushed/compressed to as small of a size as the depicted oval shaped main body **106**. Hence, a larger delivery sheath would be required if the main body **106** was circular (as compared to oval as shown).

Interestingly, in the example depicted in FIG. **12**, while both the annulus **12** of the tricuspid valve **10** and the main body **106** of the valve **100** are oblong or oval shaped, the orientations of their major and minor diameters are about 90° (e.g., $90^\circ \pm 10^\circ$) offset in relation to each other when the valve **100** is implanted in the tricuspid valve **10**. That is, the major diameter **108** of the oval shaped main body **106** is substantially parallel (e.g., $\pm 10^\circ$) relative to the minor diameter **18** of the annulus **12**. Moreover, the minor diameter **109** of the oval shaped main body **106** is substantially parallel (e.g., $\pm 10^\circ$) relative to the major diameter **16** of the annulus **12**. These geometric relationships are beneficial because the annulus **12** is fully occluded by the valve **100** and the diameter of the radially compressed delivery configuration of the valve **100** can be reduced (as compared to having the main body **106** filling a larger area of the annulus **12**).

Again, it is evident in FIG. **12** that the opening defined by the native annulus **12** is not completely filled by the main body **106**. Instead, the laterally-extending first and second anterior flaps **120a-b** help to cover and fluidly seal the native tricuspid valve opening which is not circular in this example (e.g., with the native valve opening being oblong, or irregularly shaped). In other words, in combination with the main body **106** of the valve **100**, the first and second anterior flaps **120a-b** (and the laterally-extending posterior anchoring flap **130** in some cases) help to cover and fluidly seal the native tricuspid valve opening which is not circular in some cases. In addition, terminal end portions of the first and second anterior flaps **120a-b** extend into the RVOT to provide anchoring and migration resistance. Accordingly, the first and second anterior flaps **120a-b** perform both sealing and anchorage.

In some cases, the shape of a patient's native annulus **12** is generally circular. In such a case, the valve **100** can still provide much of the benefits described above. For example, the main body **106** can still have an oblong or oval-shaped outer cross-sectional shape that occupies less than the full circular area of the native annulus **12** (with the first and

second anterior flaps **120a-b** occupying the remainder). In that case, the valve **100** is implanted in the native annulus **12** such that the central axis **101** of the occluder **110** is laterally offset (e.g., in the posterior direction) from the geometric center of the generally circular native annulus **12**. In addition, the major diameter **108** of the main body **106** can be shorter than the diameter of the native annulus **12**. For example, in some embodiments the length of the major diameter **108** of the main body **106** is about 60% to 80% of the diameter of the native annulus **12**, or about 70% to 90% of the diameter of the native annulus **12**, or about 80% to 95% of the diameter of the native annulus **12**, without limitation.

FIG. **14** illustrates a longitudinal plane cross-section view (e.g., approximately parallel to the central axis of the annulus **12**) near an anterior portion of the native tricuspid valve annulus **12**. This view is from the interface between the RVOT and the native tricuspid valve annulus **12**, looking toward the right atrium and right ventricle. In this view, it can be seen that the anterior annulus **12** is curved.

FIG. **15** shows an anterior end view of the frame **102** of the valve **100** (without the covering **104** in this example). The first and second anterior flaps **120a-b** are in the foreground in this view, and the main body **106** is in the background.

A heavy line **121** has been superimposed on FIG. **15** to represent the cross-sectional shape of the first and second anterior flaps **120a-b** (when the covering **104** is attached to the frame **102**). It can be seen that the cross-sectional shape of the first and second anterior flaps **120a-b** (taken perpendicularly to the direction in which the first and second anterior flaps **120a-b** extend from the main body **106**) is curved or arcuate. The arc extends from the outflow end portion **102o** of the frame **102** toward the inflow end portion **102i**, with the middle of the arc being the closest point of the arc to the inflow end portion **102i**.

The curved or arcuate cross-sectional shape of the first and second anterior flaps **120a-b** is beneficial because, as described in reference to FIG. **14**, the anterior portion of the native tricuspid valve annulus **12** with which the first and second anterior flaps **120a-b** interface is also curved. Accordingly, a good sealing interface between the arced first and second anterior flaps **120a-b** and the arced anterior portion of the native tricuspid valve annulus **12** is created by these complimentary curved shapes. This sealing arrangement between the arced first and second anterior flaps **120a-b** and the native tricuspid valve annulus **12** can be beneficial for mitigating paravalvular leaks when the valve **100** is engaged with the native tricuspid valve **10**.

As shown in FIG. **15**, in the depicted embodiment the arcuate cross-sectional shape of the first and second anterior flaps **120a-b** is at least partially facilitated by the configuration of frame portions **128a** and **128b** (also visible in FIG. **9**). The frame portions **128a** and **128b** constitute interior parts of the outer edges of the first and second anterior flaps **120a-b**. The frame portions **128a** and **128b** are arranged at a non-zero angle in relation to the central axis **101** so as to help define the arcuate cross-sectional shape of the first and second anterior flaps **120a-b** that is represented by the heavy line **121**. In some embodiments, the angle between the frame portions **128a** and **128b** and the central axis **101** is between 20° to 50°, or between 30° to 60°, or between 40° to 70°, without limitation. The frame portions **128a** and **128b** near the outer edges of the first and second anterior flaps **120a-b** perform particularly advantageously to create good seals between the first and second anterior flaps **120a-b** and the

anterior portion of the native tricuspid valve annulus **12**, because paravalvular leaks are particularly prone to occur in those edge areas.

FIGS. **17** and **18** illustrate an example prosthetic heart valve deployment system **200** (or simply “deployment system **200**”). The deployment system **200** includes a control handle **210**, an outer sheath catheter **220**, a middle deflectable catheter **230**, and an inner control catheter **240**. The outer sheath catheter **220** defines a first lumen. The middle deflectable catheter **230** is slidably disposed in the first lumen and defines a second lumen. The inner control catheter **240** is slidably disposed in the second lumen.

The inner control catheter **240** includes a curved portion **242**. The curved portion **242** is elastically deformable. That is, while the curved portion **242** is located within the confines of the first lumen of the outer sheath catheter **220**, the curved portion **242** is essentially linear (or at least more linear than when the curved portion **242** is radially unconstrained). When the curved portion **242** of the inner control catheter **240** is distally expressed out (either by pushing the inner control catheter **240** distally or by pulling the outer sheath catheter **220** proximally) from the confines of the first lumen of the outer sheath catheter **220**, the curved portion **242** then naturally elastically reconfigures to exhibit a pronounced curve (e.g., as shown in FIG. **18**). Thus, it can be said that the natural shape of the inner control catheter **240** includes the curved portion **242** that defines an interior angle θ . In some embodiments, the interior angle θ can be between 130° and 160°, or between 120° and 150°, or between 110° and 140°, or between 100° and 130°, or between 90° and 120°, or between 80° and 110°, or between 80° and 100°, without limitation. In some embodiments, the interior angle θ can be less than 160°, or less than 150°, or less than 140°, or less than 135°, or less than 130°, or less than 120°, or less than 110°, or less than 100°, or less than 90° without limitation.

The middle deflectable catheter **230** includes a selectively deflectable distal end portion **232** with at least one plane of deflection. In some embodiments, the selectively deflectable distal end portion **232** is deflectable in two planes. In some embodiments, the middle deflectable catheter **230** includes two or more separate selectively deflectable portions that are in same planes or in different planes.

In the depicted embodiment, the selectively deflectable distal end portion **232** is deflectable in a same plane as the plane of the curved portion **242** of the inner control catheter **240**. Accordingly, when the selectively deflectable distal end portion **232** of the middle deflectable catheter **230** is deflected, the curvature of the combination of the middle deflectable catheter **230** and the inner control catheter **240** in relation to the axis of the outer sheath catheter **220** is increased beyond that of the interior angle θ alone. In some embodiments, the combined curvature of the middle deflectable catheter **230** and the inner control catheter **240** in relation to the axis of the outer sheath catheter **220** can define an interior angle between 90° and 110°, or between 80° and 100°, or between 70° and 90°, or between 60° and 80°, or between 50° and 70°, or between 30° and 60°, or between 0° and 30°, without limitation. This high degree of curvature can be beneficial during deployment of a prosthetic valve (such as the valve **100**) using the deployment system **200**, as described further below.

The inner control catheter **240** can also include mechanical features for releasably coupling with a prosthetic valve (such as the valve **100**). For example, in the depicted embodiment, the inner control catheter **240** includes one or more control wires and/or release pins **244** that can releas-

ably couple the valve **100** to the inner control catheter **240** in a low profile delivery configuration.

FIG. **19** shows a schematic illustration of the valve **100**. FIG. **20** schematically shows the valve **100** coupled to the inner control catheter **240** and located within the first lumen defined by the outer sheath catheter **220**. The distal tip of the middle deflectable catheter **230** is also visible. In this arrangement, the valve **100** is radially compressed to a low-profile delivery configuration while within the outer sheath catheter **220**. In some embodiments, the valve **100** (or portions thereof are wrapped or folded around the inner control catheter **240**. For example, in some embodiments the anterior flaps **120a-b** are wrapped around the inner control catheter **240**. The valve **100** can self-expand as its emergence from the outer sheath catheter **220** takes place (e.g., by the manual retraction of the outer sheath catheter **220** relative to the middle deflectable catheter **230** and the inner control catheter **240**).

In some embodiments, when the valve **100** is in its collapsed delivery configuration within the outer sheath catheter **220**, the portions of the valve **100** are arranged relative to each other as follows. The first and second anterior flaps **120a-b** (which can be wrapped on each other) are distal-most. The occluder portion (or valve core) **110** with the flexible leaflets is proximal-most within the outer sheath catheter **220**. The posterior anchoring flap **130** is arranged between the distal-most first and second anterior flaps **120a-b** and the proximal-most occluder portion **110**.

The valve **100** can be releasably coupled to the inner control catheter **240** using the one or more control wires and/or release pins **244** (FIG. **18**). In some embodiments, a first control wire is releasably coupled to a proximal end portion of the main body **106**, a second control wire is releasably coupled to a distal end portion of the main body **106**, and a third control wire is releasably coupled to the posterior flaps **120a-b**. The control wires can be tensioned to draw and maintain the associated portion of the valve **100** radially inward to be snug against the inner control catheter **240**. During deployment of the valve **100**, the control wires can be individually relaxed to allow the associated portion of the valve **100** to expand elastically toward its natural expanded shape.

Still referring to FIG. **20**, in this delivery configuration the curved portion **242** of the inner control catheter **240** is being constrained in an essentially linear configuration by the outer sheath catheter **220**. However, when the inner control catheter **240** is expressed from the outer sheath catheter **220** (or as the outer sheath catheter **220** is pulled proximally relative to the inner control catheter **240**), the curved portion **242** will become unconstrained and will elastically deflect to its natural curved configuration (e.g., as shown in FIG. **18**). The curved configuration of the curved portion **242** is beneficial for the deployment process of the valve **100** into engagement with a native tricuspid valve **10**, as described further below.

FIGS. **21-30** illustrate a series of steps for deploying a prosthetic heart valve (such as the heart valve **100** described herein in any of its variations) using the heart valve deployment system **200**. These figures illustrate a trans-jugular vein approach to the native tricuspid valve **10** (via the superior vena cava).

FIG. **21** shows a distal end portion of the deployment system **200** emerging into the right atrium via the superior vena cava. The deployment system **200** is being advanced over a guidewire that was installed previously. The valve **100** (not visible) is within the outer sheath catheter **220**.

FIG. **22** illustrates the valve **100** (while the valve **100** is releasably coupled to the inner control catheter **240**) after the withdrawal of the outer sheath catheter **220** and/or the advancement of the inner control catheter **240** and the middle deflectable catheter **230**. At this stage, the curved portion **242** (not visible under the valve **100**) has become unconstrained and has elastically deflected to its natural curved configuration. The natural curved configuration of the curved portion **242** facilitates the inner control catheter **240** to make a relatively tight turn within the right atrium to advance from the vena cava and through the annulus **12** of the native tricuspid valve **10** as depicted.

FIGS. **23** and **24** illustrate further advancement of the valve **100** (while the valve **100** is still releasably coupled to the inner control catheter **240**). In these images, the middle deflectable catheter **230** is being deflected (by a first amount in FIG. **23** and a greater amount in FIG. **24**). The deflection of the middle deflectable catheter **230** adds to the curvature of the inner control catheter **240** to enable the distal end portion of the inner control catheter **240** to become directed toward the RVOT after passing through the annulus **12** (as shown in FIG. **24**).

FIGS. **25** through **27** illustrate the release process of the portions of the valve **100** from the inner control catheter **240**. As the portions of the valve **100** are released, those portions become engaged in the targeted native anatomical locations. The control wires and/or release pins for the anterior flaps **120a-b** and the posterior flap **130** are released (as best seen in FIG. **26**). In response, the anterior flaps **120a-b** deploy into the RVOT and the posterior flap **130** deploys to the posterior area of the tricuspid valve **10** just inferior to the annulus **12**. In addition, as the posterior flap **130** deploys, the one or more leaflet engagement members **140** engage with and capture/hold a portion of the native leaflet (e.g., the posterior leaflet **11p** and/or the septal leaflet **11s**) to provide migration resistance for the valve **100**. At this stage, the posterior arm **150** and/or the anterior arm **160** (FIGS. **6-9**) can also be deployed if the valve **100** includes a posterior arm **150** and/or an anterior arm **160**. FIG. **27** shows the release of control wires that are coupled to the main body **106**. In response, the main body **106** radially expands into contact and engagement with the annulus **12**.

FIGS. **28** through **30** illustrate withdrawal of the deployment system **200**. When the control wires are disengaged from the valve **100**, the inner control catheter **240** and the middle deflectable catheter **230** can then be withdrawn, leaving the valve **100** engaged with the anatomy in and around the native tricuspid valve **100**.

FIG. **31** illustrates another example prosthetic heart valve **300**. The valve **300** is similar to the valve **100** described above, but is modified to be better suited for trans-femoral delivery (via the inferior vena cava) to the native tricuspid valve **10**.

The valve **300** includes an ovalar main body **306** that contains a circular occluder **310** that defines a central axis **301**. The occluder **310** extends between an inflow end and an outflow end portion of the main body **306**, and includes valve leaflets in an arrangement that: (i) allows blood flow through the occluder **310** in a direction from the inflow end portion toward the outflow end portion along a central axis **301** of the occluder **310** and (ii) prevents blood flow through the occluder **310** in a direction from the outflow end portion toward the inflow end portion. The valve **300** also includes a first anterior flap **320a** extending from the outflow end portion of the main body **306** in a first direction that is transverse to the central axis **301**, and a second anterior flap **320b** also extending from the outflow end portion in the first

direction. The valve **300** also includes a first posterior flap **330a** extending from the outflow end portion of the main body **306** in a second direction that is opposite of the first direction, and a second posterior flap **330b** also extending from the outflow end portion in the second direction. A passageway **332** (e.g., for a pacemaker lead as described above) is defined between the first and second posterior flaps **330a-b**. In contrast to the valve **100**, the first and second posterior flaps **330a-b** of the valve **300** extend from the outflow end portion of the main body **306** farther (a greater distance) than the first and second anterior flaps **320a-b**. This arrangement biases the main body **306** toward the anterior portion of the annulus **12** (refer to FIG. **10**), which is different from the valve **100** which is biased toward the posterior portion of the annulus **12** (refer to FIG. **12**).

FIGS. **32-37** schematically illustrate a series of steps for deploying the heart valve **300** (as described herein in any of its variations) into the heart **1** using the heart valve deployment system **200** (e.g., refer to FIGS. **17** and **18**). These figures illustrate a trans-femoral vein approach to the native tricuspid valve **10** (via the inferior vena cava; “IVC”).

FIG. **32** illustrates the advancement of the deployment system **200** toward the right atrium (“RA”) via the IVC. The outer sheath catheter **220** (containing the heart valve **300** in its low-profile delivery configuration) can be advanced over a previously placed guidewire that extends into the right ventricle (“RV”) via the native tricuspid valve **10**.

FIG. **33** illustrates the emergence in the RA of the heart valve **300** from the outer sheath catheter **220** (e.g., by pulling the outer sheath catheter **220** proximally and/or by distally advancing the middle deflectable catheter **230** and inner control catheter **240**).

FIGS. **34** and **35** illustrate the advancement of the heart valve **300** into position for engagement with the native tricuspid valve **10**. To accomplish this, the middle deflectable catheter **230** and inner control catheter **240** are both curved. That is, the inner control catheter **240** is naturally curved because of its curved portion **242**, and the middle deflectable catheter **230** is selectively deflected by a clinician operator who is performing the procedure.

FIG. **36** illustrates the release of the heart valve **300** from the inner control catheter **240**, and the resulting expansion/deployment of the heart valve **300** into engagement at the location of the native tricuspid valve **10**. The release of the various components/regions of the heart valve **300** can be performed in a controlled manner by manual manipulation of the one or more control wires and/or release pins **244** (FIG. **18**) by the clinician operator. The release of the heart valve **300** from the inner control catheter **240** results in the expansion of the main body **306**, the anterior flaps **320a-b**, and the posterior flaps **330a-b** into engagement with the anatomy of the native tricuspid valve **10**, the RV, and the RVOT.

Lastly, FIG. **37** illustrates the implanted heart valve **300** in engagement with the heart **1** and functioning as a prosthetic tricuspid valve between the RA and the RV. The deployment system **200** and guidewire have been withdrawn. It can be seen here (and in the top view of FIG. **31**) that the heart valve **300** is positioned such that the main body **306** is positionally biased toward the anterior portion of the annulus **12** (refer to FIG. **10**), which is adjacent the RVOT. Accordingly (and as shown in FIG. **31**), the laterally-extending first and second posterior flaps **330a-b** help to cover and fluidly seal the native tricuspid valve opening within the annulus **12**, which is not circular in this example (e.g., with the native valve opening being oblong, oval, or irregularly shaped). In other words, in combination with the main body **306** of the valve

300, the first and second posterior flaps **330a-b** (and, in some cases, the laterally-extending anterior anchoring flaps **320a-b** to a lesser extent) help to cover/occlude and fluidly seal the native tricuspid valve opening which is not circular in some cases. In addition, the end portions of the first and second posterior flaps **330a-b** extend into engagement with the posterior shelf **11** (FIG. **4**) and/or with the wall of the RV just inferior to the annulus **12** to provide anchoring and migration resistance. Accordingly, the first and second posterior flaps **330a-b** perform both sealing and anchorage.

FIGS. **38-40** illustrate the frame **102** that can be used in some embodiments of the prosthetic heart valves described herein. The frame **102** has a cellular construction that provides mechanical support for the shape and structures of the prosthetic heart valves. In some embodiments, the frame **102** is made from nitinol (NiTi), stainless steel, cobalt chromium, MP35N, titanium, polymeric materials, other biocompatible materials, or any combination thereof. Some or all parts of the frame **102** may be covered (e.g., by the covering **104** described above). In some embodiments, the frame **102** can be made of a laser cut, expanded, and shape-set material. The frame **102** is self-expanding in some embodiments. In some embodiments, the precursor material is tubular NiTi, a NiTi sheet, or other suitable types of precursor materials.

In this example, the frame **102** includes the optional posterior arm **150** with the free end **150e**. The posterior arm **150** can also be referred to as a “diastolic anchoring tab,” because the posterior arm **150** helps to prevent migration of the prosthetic heart valve toward the right ventricle during diastole. In this example, the frame **102** does not include the anterior arm **160** (e.g., see FIG. **9**). However, in some embodiments the anterior arm **160** is included as part of the frame **102**.

In this example, the frame **102** does not include the frame portions **128a** and **128b** (e.g., see FIG. **9**). However, in some embodiments the frame portions **128a** and **128b** are included as part of the frame **102**.

As best seen in FIG. **40**, the frame **102** includes an inflow end portion **102i** and an outflow end portion **102o**. In the depicted embodiment, the cellular structure of the inflow end portion **102i** and an outflow end portion **102o** differ from each other. In particular, the size of the cells that make up the inflow end portion **102i** are smaller than the size of the cells that make up the outflow end portion **102o**. For example, the cells of the inflow end portion **102i** have a shorter longitudinal length (e.g., measured longitudinally parallel to the longitudinal axis **101**) than the cells of the outflow end portion **102o**. Said another way, the cells of the outflow end portion **102o** are longer when measured along the longitudinal direction of the frame **102** than the cells of the inflow end portion **102i**.

The differences in the sizes of the cells of the inflow end portion **102i** as compared to the cells of the outflow end portion **102o** causes the frame **102** to advantageously have different structural characteristics along the longitudinal length of the frame **102**. For example, the inflow end portion **102i** of the frame **102** is structurally stiffer than the outflow end portion **102o**, particularly as related to radially directed forces. Conversely, the outflow end portion **102o** of the frame **102** is structurally more flexible than the inflow end portion **102i**. Moreover, the structures of the anterior flaps **120a-b** are very flexible because of the anterior flaps **120a-b** are primarily made of large open areas within peripheral frame members (e.g., see FIG. **39**).

It can be advantageous for the inflow end portion **102i** of the frame **102** to be structurally stiff. For example, such

stiffness can help to maintain the circular cross-sectional shape of the occluder of the prosthetic valve (e.g., the occluder **110** shown in FIGS. **6-8**) while the heart muscle contracts to pump blood. Keeping such a circular cross-sectional shape of the occluder can serve to ensure that the leaflets of the occluder maintain their relative orientations in a predictable way. This can beneficially provide robust coaptation between the leaflets to mitigate the occurrence of regurgitation through the occluder, for example.

It can be advantageous for the outflow end portion **102o** of the frame **102** and the anterior flaps **120a-b** to be structurally flexible. For example, such flexibility can beneficially mitigate the amount of force from the frame **102** that is exerted onto the anatomy of the heart. In particular, having a flexible outflow end portion **102o** and flexible anterior flaps **120a-b** reduces or eliminates forces from the frame **102** from being applied to certain sensitive anatomical areas such as the AV node, the right coronary artery, and the annulus of the heart valve, to provide a few examples.

FIGS. **41-43** illustrate another example frame **102'** that can be used in some embodiments of the prosthetic heart valves described herein. This embodiment is different from the frame **102** in that the frame **102'** includes the frame portions **128a** and **128b** and does not include the posterior arm **150** (and also does not include an anterior arm **160**). It should be understood that such features can be mixed and matched in any desired combination.

The frame **102'** shares the cell-size characteristics of the frame **102** as described above. That is, the cells that make up the inflow end portion **102i** are smaller and stiffer than the cells that make up the outflow end portion **102o**. The cells of the anterior flaps **120a-b** have the largest size (making them the most flexible portion of the frame **102'**).

Alternative methods of achieving the variable stiffness characteristics described above are also contemplated. For example, the strut widths and/or thicknesses of different portions of the frame **102** could be different.

While this specification contains many specific implementation details, these should not be construed as limitations on the scope of any invention or of what may be claimed, but rather as descriptions of features that may be specific to particular embodiments of particular inventions. Certain features that are described in this specification in the context of separate embodiments can also be implemented in combination in a single embodiment in part or in whole. Conversely, various features that are described in the context of a single embodiment can also be implemented in multiple embodiments separately or in any suitable subcombination. Moreover, although features may be described herein as acting in certain combinations and/or initially claimed as such, one or more features from a claimed combination can in some cases be excised from the combination, and the claimed combination may be directed to a subcombination or variation of a subcombination.

Similarly, while operations are depicted in the drawings in a particular order, this should not be understood as requiring that such operations be performed in the particular order shown or in sequential order, or that all illustrated operations be performed, to achieve desirable results. Although a number of implementations have been described in detail above, other modifications are possible. For example, the steps depicted in the figures do not require the particular order shown, or sequential order, to achieve desirable results. In addition, other steps may be provided, or steps may be eliminated, from the described flows, and other components may be added to, or removed from, the

described systems. Accordingly, other implementations are within the scope of the following claims.

What is claimed is:

1. A method of deploying a prosthetic heart valve, the method comprising:

advancing the prosthetic heart valve toward a native tricuspid valve, via a jugular vein and a superior vena cava, while the prosthetic heart valve is releasably coupled to a prosthetic heart valve deployment system and diametrically constrained in a low profile delivery configuration, wherein the prosthetic heart valve deployment system comprises:

an outer sheath catheter defining a first lumen;

a middle deflectable catheter slidably disposed in the first lumen and defining a second lumen, the middle deflectable catheter comprising a selectively deflectable distal end portion; and

an inner control catheter slidably disposed in the second lumen and including one or more control wires that are releasably coupled with the prosthetic heart valve,

wherein the inner control catheter includes a distal end portion that is radially constrained in the first lumen; retracting the outer sheath relative to the inner control catheter to allow the distal end portion of the inner control catheter to become radially unconstrained and to elastically transition to a curved configuration; and deflecting the selectively deflectable distal end portion of the middle deflectable catheter so that the inner control catheter and the middle deflectable catheter in combination are curved by at least 90° relative to the outer sheath.

2. The method of claim **1**, wherein the distal end portion of the inner control catheter is curved by less than 20° when radially constrained in the first lumen.

3. The method of claim **1**, the distal end portion to elastically transitions to a curved configuration that is curved by at least 45° relative to the outer sheath when radially unconstrained.

4. The method of claim **1**, wherein the prosthetic heart valve comprises:

a main body comprising an inflow end portion and an outflow end portion;

an occluder extending between the inflow end and outflow end portions and comprising valve leaflets attached to the main body in an arrangement that: (i) allows blood flow through the occluder in a direction from the inflow end portion toward the outflow end portion along a central axis of the occluder and (ii) prevents blood flow through the occluder in a direction from the outflow end portion toward the inflow end portion;

a first anterior flap extending from the outflow end portion in a first direction that is transverse to the central axis;

a posterior flap extending from the outflow end portion in a second direction that is opposite of the first direction; and

a posterior arm extending from the inflow end portion in the second direction; and

a leaflet engagement member extending from the main body, a portion of the leaflet engagement member extending toward the inflow end portion and terminating at a free end.

5. The method of claim **4**, wherein, as the posterior flap is released from the prosthetic heart valve deployment system, a portion of a native leaflet of the native tricuspid valve becomes captured and held between the leaflet engagement member and the main body.

6. The method of claim 4, wherein, when the posterior arm is released from the prosthetic heart valve deployment system, an end of the posterior arm rests against an interior wall of an inferior vena cave, or coronary sinus, or a right atrium.

5

7. The method of claim 4, further comprising an anterior arm extending from the inflow end portion in the first direction, and wherein, when the anterior arm is released from the prosthetic heart valve deployment system, a distal end portion of the anterior arm rests against an interior wall of a right atrial appendage.

10

* * * * *