

US011660927B2

(12) **United States Patent**
Hollman et al.

(10) **Patent No.:** **US 11,660,927 B2**
(45) **Date of Patent:** **May 30, 2023**

(54) **SIDE-BY-SIDE VEHICLE**

21/183 (2013.01); *B62D 29/00* (2013.01);
B62D 33/0625 (2013.01); *B60G 2200/144*
(2013.01);

(71) Applicant: **Polaris Industries Inc.**, Medina, MN
(US)

(Continued)

(72) Inventors: **Keith A. Hollman**, Osceola, WI (US);
Anthony J. Komarek, Taylors Falls,
MN (US); **Aaron D. Deckard**,
Zionsville, IN (US); **Shawn D.**
Peterson, East Bethel, MN (US);
Daniel L. Goffman, Cocolalla, ID (US)

(58) **Field of Classification Search**

None
See application file for complete search history.

(73) Assignee: **Polaris Industries Inc.**, Medina, MN
(US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,476,200 A 11/1969 Schoepe et al.
3,600,768 A 8/1971 Romanzi et al.

(Continued)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

FOREIGN PATENT DOCUMENTS

CN 1603146 A 4/2005
CN 2837126 Y 11/2006

(Continued)

(21) Appl. No.: **17/323,597**

(22) Filed: **May 18, 2021**

OTHER PUBLICATIONS

(65) **Prior Publication Data**

US 2021/0268863 A1 Sep. 2, 2021

Examination Report issued by the European Patent Office, dated
Jan. 12, 2018, for European Patent Application v/o. 14771458.8; 6
pages.

(Continued)

Related U.S. Application Data

(63) Continuation of application No. 16/924,695, filed on
Jul. 9, 2020, now Pat. No. 11,091,003, which is a
(Continued)

Primary Examiner — Faye M Fleming

(74) *Attorney, Agent, or Firm* — Faegre Drinker Biddle &
Reath LLP

(51) **Int. Cl.**

B60G 21/055 (2006.01)
B60K 13/04 (2006.01)

(Continued)


(57) **ABSTRACT**

A utility vehicle includes a plurality of ground-engaging
members, a frame assembly, a cab frame assembly, a front
suspension assembly, a rear suspension assembly, a power
steering assembly, and a powertrain assembly, all of which
may be configured to lower the center of gravity of the
vehicle.

(52) **U.S. Cl.**

CPC *B60G 21/055* (2013.01); *B60G 3/20*
(2013.01); *B60K 13/04* (2013.01); *B60K 17/22*
(2013.01); *B60R 19/48* (2013.01); *B62D 3/12*
(2013.01); *B62D 7/18* (2013.01); *B62D*

15 Claims, 49 Drawing Sheets



Related U.S. Application Data

continuation of application No. 16/531,960, filed on Aug. 5, 2019, now Pat. No. 10,737,547, which is a continuation of application No. 14/477,589, filed on Sep. 4, 2014, now Pat. No. 10,369,861.

(60) Provisional application No. 61/873,726, filed on Sep. 4, 2013.

(51) **Int. Cl.**

- B60G 3/20* (2006.01)
- B62D 3/12* (2006.01)
- B60K 17/22* (2006.01)
- B62D 7/18* (2006.01)
- B62D 21/18* (2006.01)
- B60R 19/48* (2006.01)
- B62D 33/06* (2006.01)
- B62D 29/00* (2006.01)
- B60K 13/02* (2006.01)
- B60K 5/00* (2006.01)

(52) **U.S. Cl.**

CPC *B60G 2200/44* (2013.01); *B60G 2300/124* (2013.01); *B60G 2300/13* (2013.01); *B60K 13/02* (2013.01); *B60K 2005/003* (2013.01); *B60Y 2200/20* (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,306,044	A	4/1994	Tucker
6,003,898	A	12/1999	Teply et al.
6,293,588	B1	9/2001	Clune
6,309,024	B1	10/2001	Busch
6,976,550	B2	12/2005	Vaisanen
7,000,978	B1	2/2006	Messano
7,625,048	B2	12/2009	Rouhana et al.
7,648,170	B2	1/2010	Geslin et al.
7,819,220	B2	10/2010	Sunsdahl et al.
7,950,486	B2	5/2011	Van et al.
8,079,602	B2	12/2011	Kinsman et al.
8,215,694	B2	7/2012	Smith et al.
8,225,896	B2	7/2012	Eichenberger et al.
8,302,711	B2	11/2012	Kinsman et al.
8,328,235	B2	12/2012	Schneider et al.
8,414,082	B2	4/2013	Nakamura et al.
8,464,824	B1	6/2013	Reisenberger
8,465,050	B1	6/2013	Spindler et al.
8,548,710	B1	10/2013	Reisenberger
8,613,335	B2	12/2013	Deckard et al.
8,613,337	B2	12/2013	Kinsman et al.
8,640,814	B2	2/2014	Deckard et al.
D703,102	S	4/2014	Eck et al.
8,684,410	B2	4/2014	Kwon et al.
8,781,705	B1	7/2014	Reisenberger
8,827,025	B2	9/2014	Hapka
8,827,028	B2	9/2014	Sunsdahl et al.
8,979,123	B1	3/2015	Takahashi et al.
9,441,526	B2 *	9/2016	Noguchi E02F 9/2066
9,776,481	B2	10/2017	Deckard et al.
10,246,153	B2	4/2019	Deckard et al.
10,369,861	B2	8/2019	Deckard et al.

11,091,003	B2	8/2021	Deckard et al.
2002/0135175	A1	9/2002	Schroth
2005/0073126	A1	4/2005	Seki
2005/0073187	A1	4/2005	Frank et al.
2007/0090621	A1	4/2007	Vigen
2008/0023249	A1	1/2008	Sunsdahl et al.
2009/0184531	A1	7/2009	Yamamura et al.
2010/0090797	A1	4/2010	Koenig et al.
2010/0276990	A1	11/2010	Zuchoski et al.
2010/0314191	A1	12/2010	Deckard et al.
2011/0297462	A1	12/2011	Grajkowski et al.
2012/0223500	A1	9/2012	Kinsman et al.
2013/0033070	A1	2/2013	Kinsman et al.
2013/0049318	A1	2/2013	Kwon et al.
2013/0199097	A1	8/2013	Spindler et al.
2014/0090917	A1	4/2014	Despres-Nadeau
2014/0110893	A1	4/2014	Kinsman et al.
2014/0125018	A1	5/2014	Brady et al.
2016/0305313	A1 *	10/2016	Kumar F02D 41/30
2019/0351728	A1	11/2019	Deckard et al.
2020/0338948	A1	10/2020	Deckard et al.
2021/0215093	A1 *	7/2021	Buchwitz B62J 50/21

FOREIGN PATENT DOCUMENTS

CN	101171149	A	4/2008
CN	101177110	A	5/2008
CN	201597405	U	10/2010
CN	101878146	A	11/2010
CN	201729195	U	2/2011
CN	202986930	U	6/2013
EP	1510452	A2	3/2005
FR	2944497	A3	10/2010
JP	2010083275	A *	4/2010 B60K 13/02
WO	2008/016377	A2	2/2008
WO	2014/059258	A1	4/2014
WO	2014/074711	A1	5/2014

OTHER PUBLICATIONS

Examination Report No. 1 issued by the Australian Government IP Australia, dated Apr. 27, 2017, for Australian Patent Application No. 2014315278, 3 pages.

Examination Report No. 1 issued by the Australian Government IP Australia, dated Nov. 29, 2018, for Australian Patent Application No. 2018204263; 4 pages.

International Preliminary Report on Patentability issued by the European Patent Office, dated Apr. 14, 2015 for International Patent Application No. PCT/US2013/064516; 18 pages.

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2014/054041, dated Nov. 26, 2015, 30 pages.

International Search Report and Written Opinion issued by the European Patent Office, dated Jan. 14, 2014, for International Application No. PCT/US2013/064516; 24 pages.

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2014/054041, dated Mar. 3, 2015, 16 pages.

Office Action dated Apr. 7, 2016 issued by the Australian Patent Office in Australian Patent Application No. 2013329090; 3 pages.

Office Action issued by the European Patent Office for European Patent Application No. 14771458.8, dated May 3, 2017; 6 pages.

* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9A




Fig. 9B




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18




Fig. 19




Fig. 20




Fig. 21




Fig. 22




Fig. 23





Fig. 25




Fig. 26




Fig. 27




Fig. 28




Fig. 28A




Fig. 28B




Fig. 28C




Fig. 29A




Fig. 298B




Fig. 29C




Fig. 30




Fig. 31A




Fig. 31B




Fig. 32




Fig. 32A




Fig. 32B




Fig. 32C




Fig. 32D




Fig. 32E




Fig. 33




Fig. 33A




Fig. 34




Fig. 35




Fig. 37




Fig. 38

SIDE-BY-SIDE VEHICLE**CROSS-REFERENCE TO RELATED APPLICATIONS**

The present application is a continuation of U.S. patent application Ser. No. 16/924,695, filed on Jul. 9, 2020, which is a continuation of U.S. patent application Ser. No. 16/531,960, filed on Aug. 5, 2019, which is a continuation of U.S. patent application Ser. No. 14/477,589, filed on Sep. 4, 2014, which claims priority to U.S. Provisional Patent Application Ser. No. 61/873,726, filed on Sep. 4, 2013, the complete disclosures of which are expressly incorporated by reference herein.

BACKGROUND OF THE DISCLOSURE

The present disclosure generally relates to all-terrain and utility vehicles and, more particularly, to side-by-side utility vehicles configured to carry at least an operator, a passenger, and cargo.

Generally, all-terrain vehicles (“ATVs”) and utility vehicles (“UVs”) are configured to carry one or two passengers and cargo over a variety of terrains. Side-by-side vehicles, in which the driver and passenger are seated beside each other on laterally spaced apart seats, have become popular because of the ability to allow the passenger to share the driver’s viewpoint and riding experience instead of being positioned behind the driver.

ATVs and UVs are configured for various types of terrain and performances, and as such, it may be desirable for the vehicle to have a low center of gravity. A lower center of gravity may provide the ATVs and UVs with more stability on rugged terrain.

SUMMARY OF THE DISCLOSURE

In one embodiment of the present disclosure a utility vehicle comprises a plurality of front ground engaging members, a plurality of rear ground engaging members positioned rearward of the front ground engaging members, and a frame assembly supported by the front and rear ground engaging members. The utility vehicle further comprises a powertrain assembly operably coupled to the front and rear ground engaging members and a front suspension assembly operably coupled to the front ground engaging members. The front suspension assembly includes upper alignment arms, lower alignment arms, shock absorbers, and a torsion bar. The utility vehicle also comprises a steering assembly operably coupled to the front ground engaging members. The steering assembly includes a steering wheel, a steering rack, and steering arms. The torsion bar is positioned intermediate the upper alignment arms and the lower alignment arms.

A further embodiment of the present disclosure includes a utility vehicle comprising a plurality of front ground engaging members, a plurality of rear ground engaging members, and a frame supported by the front and rear ground engaging members. The frame includes a front frame portion and a rear frame portion. The front frame portion includes upstanding members defining a front plane of the utility vehicle. The utility vehicle further comprises a powertrain assembly operably coupled to the front and rear ground engaging members, a front suspension assembly operably coupled to the front ground engaging members, and a rear suspension assembly operably coupled to the rear

ground engaging members. The front ground engaging members extend forward beyond the front plane of the utility vehicle.

Another illustrative embodiment of the present disclosure includes a utility vehicle comprising a plurality of ground engaging members and a frame assembly supported by the ground engaging members. The frame assembly is comprised of a first material. The utility vehicle further comprises a powertrain assembly operably coupled to the ground engaging members and supported on the frame assembly, and a cab frame assembly coupled to the frame assembly. The cab frame assembly is comprised of a second material. A weight of the first material is greater than that of the second material.

In one embodiment of the present disclosure, a cab frame assembly comprises a front upstanding member, a rear upstanding member positioned rearward of the front upstanding member, and a longitudinal member coupled to front and rear upstanding members. At least one of the front upstanding member, the rear upstanding member, and the longitudinal member includes a plurality of internal ribs and an internal channel.

Another illustrative embodiment of the present disclosure includes a utility vehicle comprising a plurality of ground engaging members, a frame assembly supported by the ground engaging members, and a powertrain assembly supported by the frame assembly. The powertrain assembly includes an engine, a transmission operably coupled to the engine, an air intake assembly fluidly coupled to the engine, and an exhaust assembly fluidly coupled to the engine. The exhaust assembly is configured to selectively regulate a flow of exhaust from the engine in response to at least one of a drive mode, an operator input, and a throttle position.

In a further illustrative embodiment of the present disclosure, a cab frame assembly comprises a front upstanding member, a rear upstanding member positioned rearward of the front upstanding member, and a longitudinal member coupled to the front and rear upstanding members. At least one of the front upstanding member, the rear upstanding member, and the longitudinal member is extruded.

In another illustrative embodiment of the present disclosure, a utility vehicle, comprises a plurality of ground-engaging members and a frame assembly supported by the plurality of ground-engaging members. The frame assembly includes a front end and a rear end. The utility vehicle further comprises a cab frame assembly coupled to the frame assembly and extending above the frame assembly to define an operator area. At least one seat is positioned within the operator area and includes a seat bottom and a seat back. The utility vehicle further comprises a front suspension assembly coupled to the front end of the frame assembly. The front suspension includes a shock absorber, an alignment arm, and a torsion bar. The utility vehicle also comprises a rear suspension assembly coupled to the rear end of the frame assembly. The rear suspension assembly includes a shock absorber, an alignment arm, and a torsion bar. A center of gravity of the utility vehicle is configured to be lowered by at least one of including a recess on the seat back, extruding the cab frame assembly, positioning the torsion bar of the front suspension assembly approximately 5 inches from a bottom of the frame assembly, and positioning the torsion bar of the rear suspension assembly approximately 6 inches from a bottom of the frame assembly.

The above mentioned and other features of the invention, and the manner of attaining them, will become more apparent and the invention itself will be better understood by

3

reference to the following description of embodiments of the invention taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a left front perspective view of the vehicle of the present disclosure;

FIG. 2 is a right rear perspective view of the vehicle of FIG. 1;

FIG. 3 is a left side view of the vehicle of FIG. 1;

FIG. 4 is right side view of the vehicle of FIG. 1;

FIG. 5 is a top view of the vehicle of FIG. 1;

FIG. 6 is a bottom view of the vehicle of FIG. 1;

FIG. 7 is a front view of the vehicle of FIG. 1;

FIG. 8 is a rear view of the vehicle of FIG. 1;

FIG. 9A is a left front perspective view of a frame of the vehicle of FIG. 1;

FIG. 9B is a left rear perspective view of a portion of the frame of FIG. 9A;

FIG. 10 is a right rear perspective view of the frame of FIG. 9A;

FIG. 11 is a left front perspective view of a front frame portion of the frame of FIG. 9A;

FIG. 12 is an exploded view of a bumper and the front frame portion of FIG. 11;

FIG. 13 is a cross-sectional view of a coupler assembly of the bumper of FIG. 12, taken along line 13-13 of FIG. 12;

FIG. 14 is a left rear perspective view of a rear frame portion of the frame of FIG. 9A;

FIG. 15 is a further left rear perspective view of the rear frame portion of FIG. 14;

FIG. 16 is a left rear perspective view of a coupler assembly of the rear frame portion of FIG. 15;

FIG. 17 is left front perspective view of a cab frame assembly of the vehicle of FIG. 1;

FIG. 18 is an exploded view of the cab frame assembly of FIG. 17;

FIG. 19 is a cross-sectional view of the cab frame assembly of FIG. 17, taken along line 19-19 of FIG. 17;

FIG. 20 is a further cross-sectional view of the cab frame assembly, taken along line 20-20 of FIG. 17;

FIG. 21 is a right front perspective view of an inner surface of a retainer bar of the cab frame assembly of FIG. 17;

FIG. 22 is a left side view of a front end of the vehicle of FIG. 1;

FIG. 23 is an exploded view of a grille of a cooling assembly of the vehicle of FIG. 1;

FIG. 24 is a left rear perspective view of the grille of FIG. 23;

FIG. 25 is an exploded view of an access panel of the vehicle of FIG. 1 configured to enclose a portion of an engine compartment;

FIG. 26 is a left rear perspective view of a seat of the vehicle of FIG. 1;

FIG. 27 is a rear view of a display screen within a dashboard assembly of the vehicle of FIG. 1;

FIG. 28 is a left rear perspective view of a front suspension assembly and a rear suspension assembly of the vehicle of FIG. 1;

FIG. 28A is a left rear perspective view of the rear suspension assembly of FIG. 28;

FIG. 28B is a front view of the rear suspension assembly of FIG. 28A;

FIG. 28C is a top view of the rear suspension assembly of FIG. 28B;

4

FIG. 29A is a left front perspective view of the front suspension assembly of FIG. 28;

FIG. 29B is a left side view of a hub assembly of the front suspension assembly of FIG. 29A;

FIG. 29C is a front view of a portion of the front suspension assembly of FIG. 29A;

FIG. 30 is an exploded view of the front suspension assembly of FIG. 29A;

FIG. 31A is a left side view of the front suspension assembly of FIG. 29A and a steering assembly;

FIG. 31B is a left rear perspective view of an alternative embodiment steering arm of the steering assembly of FIG. 31A;

FIG. 32 is a left rear perspective view of an air intake assembly of the vehicle of FIG. 1;

FIG. 32A is a right rear perspective view of an alternative embodiment air intake assembly of the vehicle of FIG. 1;

FIG. 32B is a left rear perspective view of the air intake assembly of FIG. 32A positioned within a portion of a cargo box of the vehicle of FIG. 1;

FIG. 32C is a rear view of a portion of the air intake assembly of FIG. 32B;

FIG. 32D is a top view of the portion of the air intake assembly of FIG. 32C;

FIG. 32E is a left rear perspective view of the portion of the air intake assembly of FIG. 32D positioned within a portion of the cargo box;

FIG. 33 is a left rear perspective view of an exhaust assembly of the vehicle of FIG. 1;

FIG. 33A is a left rear perspective view of an alternative embodiment exhaust assembly of the vehicle of FIG. 1;

FIG. 34 is a rear view of an alternative embodiment of the exhaust assembly of FIG. 33;

FIG. 35 is a left front perspective view of doors of the vehicle of FIG. 1;

FIG. 36 is a left front perspective view of an alternative embodiment vehicle of the vehicle of FIG. 1;

FIG. 37 is a left rear perspective view of a front suspension assembly and a rear suspension assembly of the alternative embodiment vehicle of FIG. 36; and

FIG. 38 is a left rear perspective view of a powertrain assembly of the vehicle of FIG. 1.

DETAILED DESCRIPTION OF THE DRAWINGS

Corresponding reference characters indicate corresponding parts throughout the several views. Unless stated otherwise the drawings are proportional.

The embodiments disclosed below are not intended to be exhaustive or to limit the invention to the precise forms disclosed in the following detailed description. Rather, the embodiments are chosen and described so that others skilled in the art may utilize their teachings. While the present disclosure is primarily directed to a utility vehicle, it should be understood that the features disclosed herein may have application to other types of vehicles such as all-terrain vehicles, motorcycles, watercraft, snowmobiles, people movers, and golf carts.

With reference to FIGS. 1-8, a utility vehicle 2 is shown. Vehicle 2 may include light-weight components and/or may position heavier components lower on vehicle 2 in order to lower the center of gravity of vehicle 2.

Vehicle 2 includes a front end 4 and a rear end 6. A plurality of ground engaging members, including front wheels 8 and rear wheels 10, support utility vehicle 2 on a ground surface. In one embodiment, front and rear wheels 8 and 10 may include tires having an outer diameter of

5

approximately 26-32 inches. When including 26-inch tires on front and rear wheels **8**, **10**, the center of gravity of vehicle **2** may be lowered. Illustratively, the width between the centers of the hubs of rear wheels **10** defines a width of vehicle **2**, which may be approximately 45-55 inches. Illustratively, the width of vehicle **2** at ride height and without any payload (e.g., cargo, driver, and/or passenger) may be approximately 50 inches.

Rear end **6** of utility vehicle **2** supports portions of a powertrain assembly **250**, which, as shown in FIG. **38**, includes at least an engine **252**, a variable clutch assembly **254**, illustratively a continuously variable transmission (“CVT”), a transmission **255**, front final drive unit **256**, rear final drive unit **258**, an exhaust assembly **280**, and an air intake assembly **260**. Portions of powertrain assembly **250**, such as engine **252**, transmission **255**, and variable clutch assembly **254**, may be positioned on vehicle **2** such that the weight distribution of vehicle **2** may be approximately 40/60 or approximately 35/65, as measured from front end **4** to rear end **6** along longitudinal axis L. Additionally, powertrain assembly **250** may be configured to lower the center of gravity of vehicle **2**. For example, the position of engine **252** may be lowered in order to lower the center of gravity of vehicle **2**. In one embodiment, engine **252** may be lowered by approximately 5-10 mm, and more particularly, by approximately 7 mm, in order to lower the center of gravity of vehicle **2**. Also, the position of variable clutch assembly **254** and/or transmission **255** may be lowered by approximately 5-10 mm, and more particularly, by approximately 7 mm in order to lower the center of gravity of vehicle **2**.

In one embodiment, engine **252** is configured for at least approximately 60-75 hp. Additionally, front final drive unit **256** may be configured as a close-ratio drive unit. By configuring front final drive unit **256** as a close-ratio drive unit, less slip is needed to engage front wheels **8** when vehicle **2** operates in an all-wheel drive and/or four-wheel drive mode. Furthermore, by configuring front final drive unit **256** as a close-ratio drive unit, vehicle **2** may include active descent control.

A frame assembly **20** extends between front end **4** and rear end **6** of utility vehicle **2** and is supported on front wheels **8** and rear wheels **10**. Frame assembly **20** supports a cargo box **12** at rear end **6** and an operator area **14** between front end **4** and rear end **6**. As shown in FIG. **5**, in one embodiment, cargo box **12** includes a first side wall **12a**, a second side wall **12b**, and a removable panel **13**, which provides access to an engine compartment for powertrain assembly **250** and other components of vehicle **2** positioned below cargo box **12**. As shown in FIGS. **1-4**, side wall **12a** supports an engine intake port **502** and side wall **12b** supports a clutch intake port **500** for an air intake assembly **260** or **260'**, as detailed further herein. In one embodiment, intake ports **500** and **502** include filters therein.

Cargo box **12** may be comprised of a polymeric material. In one embodiment, cargo box **12** is comprised of a light-weight polymeric material, which decreases the weight of vehicle **2**. As such, the center of gravity of vehicle **2** may be lowered when cargo box **12** is comprised of a light-weight material.

Operator area **14** includes seating for at least an operator and a passenger in a side-by-side arrangement. Illustratively, operator area **14** includes a plurality of bucket-type seats **15**, each having a seat bottom **16** and a seat back **18**. Seat bottom **16** and seat back **18** may be coupled to each other or may be separate therefrom. Alternative embodiments of seats **15** may include a bench-type seat, in which one seat bottom **16** and one seat back **18** support both the operator and the

6

passenger. In one embodiment, the height of seat back **18** may be vertically adjustable to accommodate different heights of operators and passengers. Additionally, in one embodiment of seats **15**, seat bottom **16** may be configured to slide or otherwise move in a longitudinal direction to further increase the comfort of the operator and passenger. Further details about seats **15** of vehicle **2** may be disclosed in U.S. Provisional Patent Application Ser. No. 61/829,743, filed on May 31, 2013, the complete disclosure of which is expressly incorporated by reference herein.

As shown in FIG. **2**, vehicle **2** includes a dashboard assembly **200** and a floorboard assembly **210**. Floorboard assembly **210** extends forward of seats **15** and is coupled to dashboard assembly **200**. Floorboard assembly **210** includes a plurality of horizontal boards **212** and a plurality of dead pedals **214**. Illustratively, one horizontal board **212** supports the operator’s feet and another horizontal board **212** supports the passenger’s feet. Additionally, as shown in FIG. **5**, horizontal boards **212** may include at least one drain **216**. Horizontal boards **212** may include a cap configured to fit within an opening in horizontal boards **212**. The cap is removably coupled to horizontal boards **212** and may be opened or removed in order to allow fluids, dirt, and debris to flow out of operator area **14** when cleaning operator area **14**.

Referring back to FIG. **2**, dead pedals **214** are angled upwardly from horizontal boards **212** in order to also support the operator’s feet and the passenger’s feet. Illustrative dead pedals **214** may be integral with horizontal boards **212**, or alternatively, may be separate therefrom and coupled thereto with conventional fasteners. Further details about floorboard assembly **210** of vehicle **2** may be disclosed in U.S. Provisional Patent Application Ser. No. 61/829,743, filed on May 31, 2013, the complete disclosure of which is expressly incorporated by reference herein.

Referring to FIGS. **9A-11**, frame assembly **20** extends along a longitudinal axis L of utility vehicle **2** (FIG. **6**) and includes a front frame portion **22**, a mid-frame portion **24**, and a rear frame portion **26**. Frame assembly **20** includes forward longitudinally-extending members **28** extending between front frame portion **22** and rear frame portion **26**. A plurality of cross-members **30**, **32**, and **34** extend transversely to longitudinal axis L and are coupled to both forward longitudinally-extending members **28**. Additionally, a skid plate **86** may be coupled to forward longitudinally-extending members **28** and/or cross-members **30**, **32**, and **34**. Skid plate **86** also extends between front frame portion **22** and rear frame portion **26** and is positioned below forward longitudinally-extending members **28** and cross-members **30**, **32**, and **34**.

At front frame portion **22**, forward longitudinally-extending members **28** are coupled to alignment arm brackets **36** for a front suspension assembly **170**, as detailed further herein. Illustratively, front frame portion **22** includes at least four alignment arm brackets **36**. Additionally, forward longitudinally-extending members **28** are coupled to a lower plate member **38**, which is spaced apart from and positioned below an upper plate member **39**. Upper plate member **39** includes brackets **40**, which may be integrally formed with upper plate member **39** or, alternatively, welded or otherwise coupled thereto.

As shown in FIG. **11**, upper plate member **38** includes an opening, which may be configured to cooperate with a winch assembly (not shown). Lower plate member **39** includes a plurality of accessory mounts, illustratively openings **37**, which may be configured to couple with accessories and/or cargo. Additionally, some of openings **37** are configured as

tie-downs for receiving a hook or other coupling device for coupling cargo to vehicle 2. As such, frame assembly 20 integrally includes mounts for accessories and cargo. Referring to FIG. 12, lower and upper plate members 38, 39 may support an accessory 110, such as a bumper, brush guard, or other similar member configured to protect front end 4 of vehicle 2 from damage. For example, accessory 110 may be coupled to lower plate member 38 and brackets 40 of upper plate member 39 with coupling assemblies 112.

Referring to FIGS. 12 and 13, coupling assemblies 112 may be configured as expansion members, such as expansion bolts, configured to extend through openings in bracket 40 and openings 37 in lower plate member 39 in order to secure accessory 110 to front frame portion 22. Coupling assemblies 112 include a support member 122, a washer 124, a sleeve 116, and a bolt 118. Support member 122 is coupled to a frame member 114 of accessory 110. Washer 124 is positioned against the front surface of support member 122. Bolt 118 is inserted through washer 124 and support member 122 until a flange 120 of bolt 118 contacts washer 124. Bolt 118 is received within a cylindrical opening of sleeve 116.

In order to couple accessory 110 with front frame portion 22, sleeve 116 extends through integral openings 37 in lower plate member 39 and brackets 40 of upper plate member 38. A lip 126 of sleeve 116 engages an inner surface of lower plate member 38 and/or brackets 40. Bolt 118 is received within sleeve 116 such that sleeve 116 expands when bolt 118 is tightened in order to secure accessory 110 to front frame portion 22. As such, frame assembly 20 integrally includes various mounting points for accessories, such as accessory 110. Additionally, the configuration of coupling assemblies 112 is such that it is not necessary for accessory 110 to be held in place at front end 4 of vehicle 2 while assembling accessory 110 on vehicle 2.

Referring again to FIGS. 9A-10, a forward powertrain support member 42 is coupled to forward longitudinally-extending members 28 and is positioned rearward of lower plate member 38. Forward powertrain support member 42 may be configured to support a portion of a powertrain assembly 250, for example front final drive unit 256 (FIG. 38).

Additionally, as shown in FIGS. 9A-10, forward longitudinally-extending members 28 are coupled to first upstanding members 44 and second upstanding member 45 at front frame portion 22. Illustratively, front frame portion 22 includes two first upstanding members 44 and two second upstanding members 45. First upstanding members 44 include generally vertical portions 44a, generally angled portions 44b, and generally rearward portions 44c. Vertical portions 44a are coupled to upper plate member 39 and lower plate member 38. Rearward portions 44c of first upstanding members 44 of front frame portion 22 are angled upwardly. In one embodiment, rearward portions 44c are at an angle α of approximately 30-32 degrees from horizontal and are approximately 8-12 inches above the top surface of the front tires along a line C, as shown in FIG. 9B. Illustratively, angle α is approximately 31.3 degrees and the distance along line C is approximately 10.1 inches. As such, first upstanding members 44 are sufficiently spaced apart from front wheels 8 to provide sufficient space in the wheel well area for maximum turning radius. In other words, the geometry of front frame portion 22 does not interfere with or limit the turning radius of front wheels 8. In one embodiment, the front tires have a diameter of approximately 30

inches and the configuration of front end 4 of vehicle 2 does not interfere with or limit the turning radius of front wheels 8.

First upstanding members 44 also support a generally U-shaped frame member 54 coupled to the upper ends thereof. More particularly, vertical portions 44a of first upstanding members 44 are coupled to forward longitudinally-extending members 28 and rearward portions 44c of first upstanding members 44 are coupled to U-shaped frame member 54, such that U-shaped frame member 54 is positioned above forward longitudinally-extending members 28. U-shaped frame member 54 includes a cross-member 56 and a support member 58.

Second upstanding members 45 support a brace 46 extending therebetween. Brace 46 is coupled to U-shaped frame member 54. Additionally, second upstanding members 45 are coupled to braces 60, which are angled forwardly. The lower ends of braces 60 are coupled to forward longitudinally-extending members 28 and the upper ends of braces 60 are coupled to second upstanding members 45.

Referring to FIGS. 9A-10, mid-frame portion 24 includes lower longitudinally-extending members 62 and upper longitudinally-extending members 64. Lower longitudinally-extending members 62 are coupled to forward longitudinally-extending member 28 with frame members 66. Lower longitudinally-extending members 62 include front portions 62a, which are coupled to U-shaped frame member 54, horizontal portions 62b, which are coupled to frame members 66, and rear portions 62c, which are coupled to a cab frame assembly 150, as detailed further herein. Front portions 62a may be approximately 4-8 inches from the outer surface of the tire of front wheel 8 along a line D, as shown in FIG. 9B. Illustratively, the distance along line D is approximately 6.0 inches. Additionally, frame members 66 may be approximately 6-10 inches from the outer surface of the tire of front wheel 8 along a line E, as shown in FIG. 9B. Illustratively, the distance along line E is approximately 8.3 inches. The distance from front wheel 8 to frame members 66 and front portions 62a provides sufficient space within the wheel well of front wheels 8 such that the turning radius of front wheels 8 is not compromised.

Illustratively, horizontal portions 62b may be coupled to front and rear portions 62a, 62c with coupler assemblies 68. Alternatively, horizontal portions 62b may be integrally formed with front and rear portions 62a, 62c, or may be coupled thereto with conventional fasteners (e.g., welds, rivets, bolts, and/or adhesive). Lower longitudinally-extending members 62 may be coupled to upper longitudinally-extending members 64 with brackets 65.

Upper longitudinally-extending members 64 include horizontal portions 64a and angled portions 64b. Horizontal portions 64a are coupled to front portions 62a of lower longitudinally-extending members 62. Additionally, horizontal portions 64a may be coupled to U-shaped frame member 54 with frame members 70. Horizontal portions 64a may be integrally formed with angled portions 64b, or alternatively, may be separate therefrom and coupled thereto with conventional fasteners (e.g., welds, rivets, bolts, and/or adhesive). Angled portions 64b extend rearwardly from horizontal portions 64a and are coupled to rear portions 62c of lower longitudinally-extending members 62.

Referring to FIG. 10, mid-frame portion 24 also includes a dashboard support member 72 coupled to cross-member 56 with an arm member 74 and a steering support member 76. Additionally, dashboard support member 72 is coupled to front portions 62a of lower longitudinally-extending members 62 with members 78 and brackets 79. In one

embodiment, dashboard support member **72** and members **78** may be comprised of a light-weight material. In one embodiment, members **72**, **78** are comprised of polymeric material, a carbon fiber material, and/or an aluminum material to lower the center of gravity of vehicle **2**.

Mid-frame portion **24** also includes a seat frame assembly **80**. Seat frame assembly **80** includes a front cross-member **82** and a rear cross-member **84** generally parallel to front cross-member **82**. Seats **15** are configured to be removably coupled to seat frame assembly **80**.

Referring to FIGS. **9A-10**, and **14-16**, rear frame portion **26** includes upper rearward longitudinally-extending members **88** which have upper portions **88a** and lower portions **88b**. Illustratively, upper portions **88a** and lower portions **88b** may be integrally formed with each other. Alternatively, upper portions **88a** and lower portions **88b** may be separate from each other and coupled thereto with conventional fasteners (e.g., welds, rivets, bolts, and/or adhesive). Upper portions **88a** may be coupled to rear portions **62a** of lower longitudinally-extending members **62** and/or a rear cross-member **90**. Additionally, braces **92** may be coupled to upper portions **88a** and rear cross-member **90**. Rear cross-member **90** and braces **92** may be removably coupled to rear frame portion **26** with bolts in order to provide access to powertrain assembly **250**.

Rear frame portion **26** also includes lower rearward longitudinally-extending members **128**, which are coupled to forward longitudinally-extending members **28**. More particularly, as shown best in FIGS. **14-16**, the outer diameter (od) of lower rearward longitudinally-extending members **128** is smaller than the inner diameter (id) of forward longitudinally-extending members **28**. Illustratively, the outer diameter (od) of lower rearward longitudinally-extending members **128** may be approximately 36-40 mm and the inner diameter (id) of forward longitudinally-extending members **28** may be approximately 38-42 mm. In one embodiment, the outer diameter (od) of lower rearward longitudinally-extending members **128** may be approximately 38 mm and the inner diameter (id) of the forward longitudinally-extending members **28** may be approximately 40 mm. As such, lower rearward longitudinally-extending members **128** are received within a portion of forward longitudinally-extending members **28**. Conventional fasteners, such as welds, rivets, bolts, and/or adhesive may be used to secure lower rearward longitudinally-extending members **128** within forward longitudinally-extending members **28**. Illustratively, lower rearward longitudinally-extending members **128** are welded to forward longitudinally-extending members **28**.

Rear frame portion **26** further includes a plurality of angled members **94**, **96**, and **98**. Angled members **94** may be coupled to rear portions **62c** of lower longitudinally-extending members **62** and forward longitudinally-extending members **28**. Angled members **96** and **96** are coupled to lower rearward longitudinally-extending members **128**. Angled members **96** and **98** may be coupled to alignment arm brackets **100** for a rear suspension assembly **300**. A bracket **104** may be coupled to upper rearward longitudinally-extending members **88**. A plate member **102** is coupled to lower portions **88b** of upper rearward longitudinally-extending members **88** and is positioned rearward of angled members **94**, **96**, and **98**. Further details about frame assembly **20** of vehicle **2** may be disclosed in U.S. Provisional Patent Application Ser. No. 61/829,743, filed on May 31, 2013, the complete disclosure of which is expressly incorporated by reference herein.

Referring to FIGS. **17-21**, a cab frame assembly **150** is coupled to frame assembly **20** and includes front upstanding members **152**, rear upstanding members **154**, and longitudinal members **156** extending therebetween. Additionally, cab frame assembly **150** includes a front cross-member **158**, a rear upper cross-member **160**, and a rear lower cross-member **162**. Front cross-member **158** is coupled to an upper end of front upstanding members **152** and/or longitudinal members **156**. In one embodiment, front upstanding members **152** are integrally formed with longitudinal members **156**. The lower end of front upstanding members **152** may be coupled to frame assembly **20** with couplers **151**. Couplers **151** may be bolted, adhered, or otherwise coupled to frame assembly **20** and/or front upstanding members **152**.

Rear upper cross-member **160** is coupled to an upper end of rear upstanding members **154** and/or longitudinal members **156**. Rear lower cross-member **162** is also coupled to rear upstanding members **154**. In one embodiment, rear upstanding members **154** are integrally formed with rear upper cross-member **160**. The lower end of rear upstanding members **154** may be coupled to frame assembly **20** with couplers **151**, which may be bolted, adhered, or otherwise coupled to frame assembly **20** and/or rear upstanding members **154**.

As shown in FIGS. **18** and **19**, front cross-member **158** may be coupled to front upstanding members **152** and/or longitudinal members **156** with a coupler assembly **130**. Similarly, longitudinal members **156** are coupled to rear upper cross-member **160** and rear upstanding members **154** with coupler assemblies **130**. Additionally, rear lower cross-member **162** is coupled to rear upstanding members **154** with coupler assemblies **130**. Coupler assemblies **130** include an outer bracket **132**, an inner bracket **134**, and a fastener **136**. More particularly, front upstanding members **152** and longitudinal members **156** are received within opposing ends of outer and inner brackets **132**, **134** and may be coupled thereto with conventional fasteners (e.g., adhesive). Front cross-member **158** is received within an inner end of inner bracket **134** and may be coupled thereto with adhesive or other conventional fasteners. As such, front upstanding members **152**, longitudinal members **156**, and front cross-member **158** are brought together in a T-configuration by coupler assemblies **130**. Fastener **136** is received within an opening of outer bracket **132** and extends into an inner channel **166** of front cross-member **158** in order to couple together front upstanding members **152**, longitudinal members **156**, and front cross-member **158**. Fastener **136** may be threadedly coupled or otherwise secured within inner channel **166**. In a similar way, upper rear cross-member **160** is coupled to rear upstanding members **154** and longitudinal members **156**. Additionally, lower rear cross-member **162** is coupled to rear upstanding members **154** with coupler assemblies **130**.

Cab frame assembly **150** may be at least partially comprised of a metallic material. For example, illustrative cab frame assembly **150** is comprised of a material that weighs less, or has a lower density, than the material of frame assembly **20**. Illustrative cab frame assembly **150** may be comprised of aluminum, whereas illustrative frame assembly **20** may be at least partially comprised of steel. More particularly, at least some of front upstanding members **152**, rear upstanding members **154**, longitudinal members **156**, front cross-member **158**, rear upper cross-member **160**, and rear lower cross-member **162** are comprised of aluminum. Alternative embodiments of cab frame assembly **150** may be comprised of other light-weight materials, such as polymeric materials and/or carbon fiber materials. By using aluminum,

polymeric materials, and/or carbon fiber materials, cab frame assembly 150 may be light-weight and decrease the overall weight of vehicle 2. As such, the center of gravity of vehicle 2 may be lowered. For example, when cab frame assembly 150 is comprised of aluminum, the weight of cab frame assembly 150 may be reduced by approximately 40% compared to a cab frame assembly 150 comprised of steel. Alternatively, members 152, 154, 156, 158, 160, and/or 162 of cab frame assembly 150 may be comprised of 16-gauge tubes, rather than 14-gauge tubes, and the decreased size of members 152, 154, 156, 158, 160, and/or 162 may decrease the weight of cab frame assembly 150 and, therefore, lower the center of gravity of vehicle 2.

When cab frame assembly 150 is comprised of aluminum, the bending stiffness or strength of at least some of front upstanding members 152, rear upstanding members 154, longitudinal members 156, front cross-member 158, rear upper cross-member 160, and rear lower cross-member 162 may be increased by including at least one structural reinforcement member. Illustratively, the at least one structural reinforcement member defines a plurality of internal ribs 164 and inner channel 166. Internal ribs 164 and inner channel 166 may be extruded with members 152, 154, 156, 158, 160, and 162. As shown in FIG. 20, front upstanding members 152, rear upstanding members 154, longitudinal members 156, front cross-member 158, rear upper cross-member 160, and/or rear lower cross-member 162 may include at least four internal ribs 164. Internal ribs 164 extend inwardly from the inner surface of front upstanding members 152, rear upstanding members 154, longitudinal members 156, front cross-member 158, rear upper cross-member 160, and/or rear lower cross-member 162 and engage with inner channel 166. By including at least four internal ribs 164, the bending stiffness of each member 152, 154, 156, 158, 160, and/or 162 is increased in two directions—both direction B_1 and direction B_2 . As shown in FIGS. 19 and 20, inner channel 166 extends along the length of front upstanding members 152, rear upstanding members 154, longitudinal members 156, front cross-member 158, rear upper cross-member 160, and/or rear lower cross-member 162 and is generally hollow in order to receive fastener 136 of coupler assemblies 130. Additionally, electrical wires may be routed through inner channel 166 and/or the channels defined between internal ribs 164 in order to conceal and protect the wires.

At least some of front upstanding members 152, rear upstanding members 154, longitudinal members 156, front cross-member 158, rear upper cross-member 160, and rear lower cross-member 162 may be extruded and profiled. For example, front upstanding members 152, rear upstanding members 154, longitudinal members 156, front cross-member 158, rear upper cross-member 160, and/or rear lower cross-member 162 may be extruded with a generally hour-glass or FIG. 8 profile to allow accessories, such as doors 222 (FIG. 35), a roof (not shown), a front windshield (not shown), and/or a rear windshield (not shown) to be coupled to cab frame assembly 150. Additional details about the profile of cab frame assembly 150 may be disclosed in U.S. patent application Ser. No. 13/429,589, filed on Jun. 8, 2012, the complete disclosure of which is expressly incorporated by reference herein.

Additionally, cab frame assembly 150 also includes a retainer or bolster bar 140, which may be coupled to rear upstanding members 154. More particularly, rear upstanding members 154 may include tabs 142 for coupling with bolster bars 140. A fastener 144 may be received within openings of bolster bars 140 and corresponding openings in tabs 142 in

order to couple bolster bars 140 to rear upstanding members 154. Bolster bar 140 includes tabs 141, which are configured to support a door 222 (FIG. 35), as detailed further herein. Illustrative bolster bars 140 may be comprised of a light-weight or low-density metallic material, polymeric material, and/or carbon fiber material. For example, bolster bar 140 may be comprised of aluminum. With the use of aluminum or other light-weight materials, the center of gravity of vehicle 2 may be lowered.

Referring to FIG. 22, frame assembly 20 may be coupled to a body of vehicle 2. For example, the body of vehicle 2 may include a hood 220 at front end 4, as well as dashboard assembly 200 and floorboard assembly 210 with operator area 14 (FIG. 2). As shown in FIG. 22, the forward-most portion of vehicle 2 is defined by upstanding members 44 along line F. However, the forward-most portion of front wheels 8 are forward of the line F. As such, if vehicle 2 contacts an obstacle (e.g., rock or tree) at a position along line O, only front wheels 8 will contact the obstacle. The remainder of vehicle 2 is rearward of line O and, therefore, does not contact the obstacle. In this way, the approach angle at front frame portion 22 of frame assembly 20 minimizes damage to vehicle 2 by ensuring that front wheels 8 will contact an obstacle before any other portion of vehicle 2. For example, angle α of first upstanding members 44 defines the approach angle, which allows front wheels 8 to be configured to contact an obstacle at line O before the remainder of vehicle 2 reaches the obstacle. Further details about the body of vehicle 2 may be disclosed in U.S. Provisional Patent Application Ser. No. 61/829,743, filed on May 31, 2013, the complete disclosure of which is expressly incorporated by reference herein.

Referring to FIGS. 23 and 24, a cooling system 230 is positioned at front end 4 of vehicle 2 and, therefore, the approach angle of frame assembly 20 also protects cooling system 230 from damage if front end 4 vehicle 2 contacts an obstacle. Cooling system 230 includes a main grille 232, at least one heat exchanger 234, and secondary grilles 236, 238. Main grille 232 is positioned forward of heat exchanger 234 and above secondary grilles 236, 238. Main grille 232 is removably coupled to the body of vehicle 2, for example hood 220, with tabs 233 and 235. As shown in FIG. 24, tabs 233 are positioned along the top edge of main grille 232 and tabs 235 are positioned along the bottom edge of main grille 232. Tabs 233 are configured to compress when main grille 232 is assembled at front end 4 of vehicle 2; however, tabs 233 are biased to an expanded position in order to secure main grille 232 against hood 220 and other components at front end 4 of vehicle 2.

Main grille 232 includes a plurality of louvers 237 to allow air to flow therethrough in order to provide cooling air to heat exchanger 234. In one embodiment, louvers 237 may be angled in order to deflect dirt, mud, and other debris away from heat exchanger 234. Additionally, the angled configuration of louvers 237 may be such that the flow of air therethrough is laminar. Also, by keeping main grille 232 clean and free of dirt and mud, air flow through louvers 237 is more efficient. Additionally, a removable deflector 239 may be coupled to heat exchanger 234 in order to further deflect dirt, mud, and debris away from heat exchanger 234. Illustratively, deflector 239 may extend around the perimeter of heat exchanger 234.

Referring to FIG. 25, the body of vehicle 2 also includes a plurality of panels within operator area 14. For example, an access panel 240 may be included within operator area 14, which is positioned between seats 15, as shown in FIG. 5. In this way, access panel 240 may be positioned generally

rearward of seats **15** and encloses an engine compartment for powertrain assembly **250** from operator area **14**. More particularly, an engine **252** of powertrain assembly **250** may be positioned rearward of access panel **240**. As such, access panel **240** prevents the operator or passenger from accidentally contacting components of powertrain assembly **250** within the engine compartment and also prevents transfer of noise, heat, fluids, dirt, and/or debris from the engine compartment into operator area **14**. Access panel **240** is removably coupled to the body, which also provides access to the engine compartment for repairing, changing, and/or monitoring components of engine **252** or other portions of powertrain assembly **250**. For example, engine **252** may be oriented such that the oil dipstick and/or engine filter is adjacent access panel **240**. In this way, the operator is able to monitor or change the oil level and/or filter of engine **252** without removing seats **15**.

As shown in FIG. **26**, operator area **14** includes seats **15**, which include seat bottoms **16** and seat backs **18**. The rearward surface of seat backs **18** may include a recessed portion **244** rearward of a head rest **246** of seats **15**. By including recessed portion **244** on seats **15**, the weight of seats **15** may be reduced. For example, the weight of seats **15** may be reduced by approximately 15%. As such, the overall weight of vehicle **2** may be reduced, which may lower the center of gravity of vehicle **2**.

Referring to FIG. **27**, operator area **14** also includes dashboard assembly **200** positioned generally forward of seats **15** and generally above floorboard assembly **210** (FIG. **2**). Dashboard assembly **200** includes an upper dashboard member **202**, which may include at least one opening for a multi-functional display screen or gauge **204**. Illustratively, screen **204** may be configured with to output information about navigation, radio, cellular telephones, and/or data about vehicle **2**. For example, display screen **204** may be configured to output GPS coordinates, information about the terrain, and data received from sensors about the fuel levels, output of powertrain assembly **250**, and other similar data from vehicle **2**. Additionally, upper dashboard member **202** may support integrated accessories **206**, such as integrated speakers and/or heating and cooling vents.

Additionally, upper dashboard member **202** may support a passenger grab bar **208** (FIG. **2**). The passenger may hold on to grab bar **208** during operation of vehicle **2** to stabilize himself or herself in seat **15**. Grab bar **208** may be comprised of a metallic material generally surrounded by a polymeric cover. In one embodiment, grab bar **208** may be at least partially comprised of aluminum. As such, grab bar **208** may weigh less and/or have a lower density than a grab bar comprised of other materials, for example steel and, and therefore, may lower the center of gravity of vehicle **2**.

As shown in FIGS. **28-28C**, vehicle **2** includes front suspension assembly **170** and rear suspension assembly **300**. In one embodiment, rear suspension assembly **300** is configured for approximately 8-12 inches of travel. Illustratively, rear suspension assembly **300** is configured for approximately 10 inches of travel. Rear suspension assembly **300** is positioned generally rearward of engine **252** at rear end **6** of utility vehicle **2**. Referring to FIGS. **28-28C**, rear suspension assembly **300** may be configured as a dual alignment arm-type suspension assembly and includes upper alignment arms **302**, lower alignment arms **304**, shock absorbers **306**, and a torsion bar **308**. An inner end of upper and lower alignment arms **302**, **304** are coupled to alignment arms brackets **100** of rear frame portion **26**, and an outer end of upper and lower alignment arms **302**, **304** are coupled to hub assemblies **310** of rear wheels **10**.

A lower end of shock absorber **306** is coupled to lower alignment arm **304**, and an upper end of shock absorber **306** is coupled to brackets **104** on upper rearward longitudinally-extending members **88**. In one embodiment, brackets **104** are approximately 15-20 inches above skid plate **86**, and illustratively, are approximately 17.8 inches above skid plate **86**.

Shock absorbers **306** may be self-leveling or load-leveling shocks, for example Nivomat® shocks available from ZF Sachs AG Corporation of Germany. In one embodiment, shocks **306** include an incompressible fluid, such as oil, and a coil-over spring. When cargo and passengers are supported within vehicle **2**, the ground clearance of vehicle **2** (i.e., the distance between the bottom of frame assembly **20** and the ground surface) may be affected such that the ground clearance is reduced and vehicle **2** sits lower to the ground. As such, the bottom surface of vehicle **2** may scrape against the ground, obstacles, or other objects, during operation. However, shocks **306** are configured to selectively or automatically adjust the ride height of vehicle **2** to accommodate a load on vehicle **2** in order to maintain a consistent ground clearance. In other words, shocks **306** are configured to maintain the same ground clearance when vehicle **2** supports cargo and passengers as when vehicle **2** does not include any passengers or cargo. Additional details about shocks **306** may be disclosed in U.S. Pat. No. 8,079,602, issued on Dec. 20, 2011, the complete disclosure of which is expressly incorporated by reference herein.

In one embodiment, shocks **306** are configured to automatically adjust the ride height in response to a load on vehicle **2** in order to maintain a predetermined ground clearance. In another embodiment, the operator may be able to selectively adjust the ride height, either by manually adjusting a portion of shocks **306** or by activating an operator input from operator area **14**. For example, if the terrain suddenly changes and includes large obstacles, the operator may selectively adjust shocks **306** to increase the ground clearance to accommodate the terrain.

Also, in a further embodiment, shocks **306** may be configured for continuous damping control, as detailed further in U.S. Provisional Patent Application Ser. No. 61/723,623, filed on Nov. 7, 2012, the complete disclosure of which is expressly incorporated by reference herein.

Torsion bar **308** of rear suspension assembly **300** extends generally in a U-shape and is generally positioned along the inner sides of shock absorbers **306**. Torsion bar **308** is coupled to upper alignment arms **302** through rods **309**, as shown in FIG. **28B**. Illustratively, an upper end of rod **308** is coupled to a front surface of upper alignment arms **302** and a lower end of rod **308** extends below upper alignment arm **302** in order to couple with torsion bar **308**. Torsion bar **308** is positioned vertically intermediate upper and lower alignment arms **302**, **304**. As shown in FIG. **28C**, forwardly-extending portions **308a** of torsion bar **308** may be positioned below upper alignment arms **302** and half shafts **311** of rear final drive unit **258** (FIG. **38**). More particularly, as shown in FIG. **28B**, forwardly-extending portions **308a** of torsion bar **308** may be bent and angled downwardly relative to a center portion **308b** of torsion bar **308** in order to extend below half shafts **311** and couple with the lower ends of rods **309**. In one embodiment, center portion **308b** of torsion bar **308** may be approximately 4-7 inches above skid plate **86**, and illustratively is approximately 5.9 inches above skid plate **86**. As such, torsion bar **308** occupies a lower position on vehicle **2**, which may lower the center of gravity of vehicle **2**. Torsion bar **308** includes isolators **312**. Torsion bar **308** is positioned below an exhaust assembly **280** of pow-

15

ertrain assembly 250 and isolators 312 may be configured to couple with frame assembly 20 and contact exhaust assembly 280, as shown in FIG. 8.

As shown in FIGS. 29-31, front suspension assembly 170 is configured as a dual alignment arm-type suspension and includes upper alignment arms 172, lower alignment arms 174, shock absorbers 176, and a torsion bar 178. In one embodiment, front suspension assembly 170 is configured for approximately 8-12 inches of travel. Illustrative front suspension assembly 170 is configured for approximately 10 inches of travel. An inner end of lower alignment arms 174 is coupled to alignment arm brackets 36 and an outer end of lower alignment arms 174 is coupled to a hub assembly 180 of front wheels 8. Illustrative lower alignment arms 174 include a rearward arm 174a and a forward arm 174b which are angled toward each other in order to couple with hub assembly 180. Additionally, forward arm 174b includes a bend 175 to further position the outer end of forward arm 174b inward. By bending and angling forward arm 174b inward, forward arm 174b does not contact an obstacle before front wheels 8.

Upper alignment arms 172 include a rearward arm 172a and a forward arm 172b. As with forward arm 174b, forward arm 172b is angled inwardly toward rearward arm 172a and, as such, does not contact an obstacle before front wheels 8. An inner end of upper alignment arms 172 is coupled to upper plate member 39 and brackets at front frame portion 22. An outer end of upper alignment arms 172 is coupled to hub assembly 180 of front wheels 8. More particularly, upper and lower alignment arms 172, 174 are coupled to hub assemblies 180 via a knuckle 181. Knuckle 181 has a steering axis of rotation, also called a king pin axis, 182. As shown in FIG. 29B, steering axis of rotation or king pin axis 182 is angled rearwardly relative to a vertical axis V. Illustratively, steering axis of rotation 182 is at a rearward angle β of approximately 5-10 degrees, and more particularly, 7.5 degrees, from vertical axis V. Additionally, as shown in FIG. 29C, front wheels 8 are angled inwardly such that knuckle 181 is angled inwardly relative to vertical axis V. Illustratively, knuckle 181 is angled inwardly at an angle θ of approximately 2-8 degrees, and more particularly, 5.0 degrees, from vertical axis V.

Rearward arm 172a of upper alignment arms 172 may bend upwardly in order to accommodate steering arms 192 of a power steering assembly 190 and/or the half shafts of front final drive unit 256. More particularly, steering arms 192 are positioned intermediate upper alignment arms 172 and lower alignment arms 174. Additionally, steering arms 192 are coupled to hub assemblies 180 at a joint 184, which is rearward of knuckle 181. As shown in FIGS. 29A-C and 31, joint 184 of steering arms 192 is rearward of steering axis of rotation 182.

As shown in FIG. 31B, alternative steering arms 192' may be included with power steering assembly 190. For example, steering arms 192' may include a cast component 193 for coupling steering arms 192' to joint 184. Illustratively, cast component 193 may be comprised of aluminum. When power steering assembly 190 includes steering arms 192' with cast component 193, the weight of steering arms 192' may be reduced by approximately 40% compared to steering arms 192, which may include steel. As such, the center of gravity of vehicle 2 may be lowered by including steering arms 192' on vehicle 2.

Referring to FIGS. 28-31, the upper end of shock absorbers 176 is coupled to brace 46 at front frame portion 22. In one embodiment, brace 46 and the upper end of shock absorbers 176 may be approximately 18-23 inches above

16

skid plate 86, and illustratively, is 21.6 inches above skid plate 86. The lower end of shock absorbers 176 are coupled to upper alignment arms 172 through a bracket 177. Additionally, referring to FIG. 29C, bracket 177 and the lower end of shock absorbers 176 may be approximately 2-6 inches from the steering axis of rotation 182 along line M, and illustratively, is approximately 4 inches from the steering axis of rotation 182. Bracket 177 is also coupled to rods 186, which extend generally vertically and also couple with torsion bar 178. Illustratively, shock absorbers 176 are operably coupled to torsion bar 178 with rods 186. As such, movement may be transmitted between torsion bar 178 and shock absorbers 176.

Shock absorbers 176 may be self-leveling or load-leveling shocks, for example Nivomat® shocks available from ZF Sachs AG Corporation of Germany. In one embodiment, shocks 176 include an incompressible fluid, such as oil, and a coil-over spring. When cargo and passengers are supported within vehicle 2, the ground clearance of vehicle 2 may be affected such that the ground clearance is reduced and vehicle 2 sits lower to the ground. As such, the bottom surface of vehicle 2 may scrape against the ground, obstacles, or other objects, during operation. However, shocks 176 are configured to selectively or automatically adjust the ride height of vehicle 2 to accommodate a load on vehicle 2 in order to maintain a consistent ground clearance. In other words, shocks 176 are configured to maintain the same ground clearance when vehicle 2 supports cargo and passengers as when vehicle 2 does not include any passengers or cargo.

In one embodiment, shocks 176 are configured to automatically adjust the ride height in response to a load on vehicle 2 in order to maintain a predetermined ground clearance. In another embodiment, the operator may be able to selectively adjust the ride height, either by manually adjusting a portion of shocks 176 or by activating an operator input from operator area 14. For example, if the terrain suddenly changes and includes large obstacles, the operator may selectively adjust shocks 176 to increase the ground clearance to accommodate the terrain.

In this way, because both shocks 176 of front suspension assembly 170 and shocks 306 of rear suspension assembly 300 include load-leveling shocks, vehicle 2 includes load-leveling shocks on all four corners thereof. Additionally, because shocks 176 and/or 306 are configured to adjust the ride height or ground clearance of vehicle 2, shocks 176 and/or shocks 306 are able to affect the center of gravity of vehicle 2. In one embodiment, the ride height of vehicle 2 may be lowered by approximately 1 inch in order to lower the center of gravity of vehicle 2.

Also, in a further embodiment, shocks 176 may be configured for continuous damping control, as detailed further in U.S. Provisional Patent Application Ser. No. 61/723,623, filed on Nov. 7, 2012, and U.S. Pat. No. 8,079,602, issued on Dec. 20, 2011, the complete disclosures of which are expressly incorporated by reference herein.

Torsion bar 178 is supported on frame assembly 20 with a bracket 188. More particularly, bracket 188 is coupled to second upstanding members 45 of front frame portion 22. Torsion bar 178 is positioned vertically intermediate upper alignment arm 172 and lower alignment arm 174. In one embodiment, a center portion 178a of torsion bar 178 (FIG. 30) is approximately 3-7 inches above skid plate 86, and illustratively, is approximately 4.9 inches above skid plate 86. Illustratively, torsion bar 178 extends rearwardly around a rear surface of a steering rack 194 of power steering assembly 190. Additionally, torsion bar 178 is positioned

directly rearward of front final drive unit **256** such that steering rack **194** is positioned intermediate torsion bar **178** and front final drive unit **256**. Illustratively, torsion bar **178** may be approximately 8-12 inches, and more particularly, 9.2 inches, rearward of front final drive unit **256** along a line F, as shown in FIG. 9B.

As with joint **184**, steering rack **194** also is positioned rearward of steering axis of rotation **182** of knuckle **181**. Additionally, steering rack **194** is positioned vertically intermediate upper alignment arm **172** and lower alignment arm **174**, and is positioned longitudinally intermediate lower alignment arm brackets **36**, as shown best in FIG. 31. In one embodiment, the center of steering rack **194** is positioned approximately 4-8 inches above skid plate **86**, and illustratively, is approximately 5.6 inches above skid plate **86**. By positioning steering rack **194** and torsion bar **178** intermediate upper and lower alignment arms **172** and **174**, steering rack **194** and torsion bar **178** are at a low position on vehicle **2**, which may lower the center of gravity of vehicle **2**. Additional components of power steering assembly **190**, for example an electric power steering unit (not shown), also may be positioned adjacent upper and lower alignment arms **172**, **174** of front suspension assembly **170** to further lower the center of gravity of vehicle **2**. In one embodiment, the electric power steering unit may be adjacent or incorporated into a top portion of steering rack **194** in order to lower the center of gravity of vehicle **2**.

As shown in FIG. 29C, steering arms **192** are angled downwardly from steering rack **194** in order to couple with hub assemblies **180** at joint **184**. In one embodiment, steering arms **192** may be at an angle Ω of approximately 6-10 degrees, and more particularly 8.6 degrees, from horizontal. By angling steering arms **192** downwardly, the suspension travel of front suspension assembly **170** may be increased without compromising the turning radius of front wheels **8**. Additionally, half shafts **257** are operably coupled to hub assemblies **180** and front final drive unit **256** and also may be angled downwardly from front final drive unit **256** in order to couple with hub assemblies **180**. For example, in one embodiment, half shafts **257** may be at an angle Ψ of approximately 5-8 degrees, and more particularly 6.9 degrees, from horizontal. By angling the half shafts downwardly, the suspension travel also may be increased without compromising the steering angle or turning radius for front wheels **8**.

Additional details of front suspension assembly **170** may be disclosed in U.S. Pat. No. 8,302,711, filed on Dec. 8, 2011, and issued on Nov. 6, 2012, the complete disclosure of which is expressly incorporated by reference herein.

Referring to FIG. 32, an air intake assembly **260** of vehicle **2** is shown. Air intake assembly **260** includes a filter housing **262** for supporting a filter (not shown) therein, a lid **264** removably coupled to filter housing **262**, an intake tube **266**, an outlet tube **268**, a breather inlet tube **272**, and a resonator tube, illustratively a quarter-wave tube **274**. In one embodiment, the position of filter housing **262** may be adjusted to lower the center of gravity of vehicle **2**. As shown, intake tube **266** pulls air from the right or passenger side of vehicle **2** and the air flows into filter housing **262** in order to flow through the filter therein. The filter removes particles, dust, dirt, and/or other debris from the air. Once cleaned, the air flows out of filter housing **262** and into outlet tube **268**. Outlet tube **268** directs air toward engine **252** of powertrain assembly. More particularly, a port **270** of outlet tube **268** is fluidly coupled to the throttle bodies of engine.

Additionally, a smaller portion of air in outlet tube **268** may flow through breather inlet tube **272**, which directs air to the breather of engine **252**.

Quarter-wave tube **274** is also fluidly coupled to outlet tube **268** in order to decrease the noise of air intake assembly **260**. More particularly, air intake assembly **260** is positioned rearward of seats **15** and, therefore, noise from air intake assembly **260** may be heard within operator area **14**. However, by providing a resonator, such as quarter-wave tube **274**, the noise from air intake assembly **260** may be reduced. As shown in FIG. 32, quarter-wave tube **274** is positioned on the "clean" side of filter housing **262** (i.e., is fluidly coupled to outlet tube **268**). Alternatively, as shown in FIG. 32A, an alternative embodiment quarter-wave tube **274'** may be positioned on the "dirty" side of filter housing **262** such that quarter-wave tube **274'** may be fluidly coupled to an intake tube **266'**.

An alternative embodiment of air intake assembly **260** is shown as air intake assembly **260'** in FIGS. 32A-32E. Air intake assembly **260'** includes filter housing **262**, intake tube **266'**, an outlet tube **268'**, breather inlet tube **272**, and quarter-wave tube **274'**. The configuration and operation of illustrative air intake assembly **260'** is described herein. It should be understood that the configuration and operation of air intake assembly **260** may be the same as that for air intake assembly **260'**. As shown in FIG. 32A, air intake assembly **260'** is positioned within a forward portion of cargo box **12**. More particularly, air intake assembly **260'** is positioned between side walls **12a** and **12b** of cargo box **12**, such that intake tube **266'** is positioned adjacent or generally in proximity to side wall **12a**, and outlet tube **268'** is adjacent or generally in proximity to side wall **12b**. Additionally, air intake assembly **260'** is positioned forward of removable panel **13** (FIG. 5). A cover **450** of cargo box **12** is positioned generally around air intake assembly **260'**, as shown in FIGS. 32C and 32E. Illustratively, air intake assembly **260'** is positioned with a chamber **452** defined by cover **450** and a top surface **458** of cargo box **12**.

As shown in FIGS. 32C and 32D, intake tube **266'** is spaced apart from side wall **12a** of cargo box. As such, intake tube **266'** also is spaced apart from engine intake port **502**. In this way, intake tube **266'** is not in direct contact with side wall **12a** of cargo box **12** or engine intake port **502**. With intake tube **266'** spaced apart from side wall **12a**, intake tube **266'** can pull air into filter housing **262** from multiple locations. For example, as shown in FIGS. 32C-32E, air may flow in the direction of arrow **456** in order to flow into intake tube **266'** through engine intake port **502**. Additionally, air may flow in the direction of arrow **454** in order to flow into intake tube **266'** through chamber **452**. As such, if engine intake port **502** becomes clogged with dirt, debris, snow, mud, or is otherwise blocked, air can continue to flow into air intake assembly **260'** through chamber **452**. In one embodiment, a primary air volume for air intake assembly **260'** is defined by the volume of air flowing in direction **456**, and a secondary air volume for air intake assembly **260'** is defined by the volume of air flowing in direction **454**. In other embodiments, the balance of air flowing into intake tube **266'** through engine intake port **502** and chamber **452** may be balanced, regulated, or otherwise. In a further embodiment, air may be pulled into variable clutch assembly **254** (FIG. 38) in the same manner described herein for engine **252**.

As shown in FIG. 33, exhaust assembly **280** of powertrain assembly **250** includes an inlet body **282**, an inlet tube **284**, an outlet tube or tailpipe **288**, and an exhaust body or muffler **286**. In one embodiment, inlet tube **284** may be configured

with multiple tube portions, which are coupled together with a coupler 285. Exhaust body 286 may include a plurality of baffle plates 290 and a filter tube 292. Exhaust assembly 280 is supported by rear frame portion 26 at rear end 6 of vehicle 2. As shown in FIG. 8, exhaust body 286 may be further supported on isolators 312 of rear suspension assembly 300.

The outer surface of exhaust assembly 280 may be wrapped or otherwise surrounded by an insulation material, for example a fiberglass insulation wrap available from The 3M Company. In assembly, the wrap may be wound around exhaust assembly 280, heated, and then allowed to cool such that the wrap ultimately forms a hard cast-type material around exhaust assembly 280. In one embodiment, at least exhaust body 286 may be perforated such that when the insulation wrap is applied thereto and heated, the insulation may expand and a portion of the insulation will penetrate the perforations and generally extend into the interior of exhaust body 286. Alternative embodiments of insulation material also may be used. By using the insulation wrap, rather than a rigid shield, the thickness of the wrap and, therefore, the insulation provided to exhaust assembly 280, may be customized and adjusted.

As shown in FIG. 33A, an alternative embodiment exhaust assembly 280' includes inlet body 282, inlet tube 284, outlet tube or tailpipe 288, and exhaust body 286. Additionally, exhaust assembly 280' includes a heat shield 281, rather than a fiberglass insulation wrap or other insulating material or object, to insulate exhaust body 286. Illustratively, heat shield 281 is coupled to exhaust body 286 with conventional fasteners, for example bolts, screws, welds, rivets, and/or adhesive.

In operation, exhaust from engine 252 flows through ports 298 and into inlet body 282. The exhaust in inlet body 282 flows into inlet tube 284, into exhaust body 286 through an inlet port 294, and exits vehicle 2 through port 296 of outlet tube 288.

The internal geometry of exhaust body 286 may affect the sound emanating from exhaust assembly 280. More particularly, the internal geometry of exhaust body 286 may be configured to reduce or eliminate the effects of acoustical standing waves therein. It is known that mufflers may include parallel baffle walls to define an expansion chamber volume within the muffler. The baffle plates are typically oriented in a generally vertical configuration such that the baffle plates may be generally perpendicular to the flow of air and sound within the muffler. As such, the muffler may include a plurality of parallel surfaces. However, as sound reflects off of these parallel surfaces within the muffler, it can create standing waves in the expansion chamber, which may create frequencies at which the muffler is less effective.

In order to reduce or eliminate the amplification effects due to reflections, baffle plates 290 within exhaust body 286 are angled and oriented in a diagonal configuration therein. Additionally, by positioning filter tube 292 between baffle plates 290, amplification effects due to the reflections may be further reduced or eliminated altogether.

In operation, as sound enters exhaust body 286 through inlet port 294, the sound may reflect off of diagonal baffle plates 290. As such, the sound is reflected at an angle away from inlet port 294 and bounces around a first chamber A, which is defined by a first baffle plate 290A, a first wall 295A of exhaust body 286, and the corresponding inner surface of exhaust body 286. Illustratively, first chamber A is generally triangularly shaped. By reflecting the sound in an angled manner about triangularly-shaped chamber A, the sound does not reinforce on itself because the sound does not bounce off of parallel walls. The sound is then transferred

through filter tube 292 and a filter therein dampens the sound before the sound exits into a second chamber B. Despite the generally parallel configuration of baffle plates 290, the sound flowing between baffle plates 290 is negligible because filter tube 292 dampens the sound. Furthermore, an alternative embodiment of baffle plates 290 may include curved surfaces such that the surfaces of baffle plates 290 are not parallel to each other.

Second chamber B is similar to first chamber A in that second chamber B also is generally triangularly shaped and is defined by a second wall 295B of exhaust body 286, a second baffle plate 290B, and the corresponding inner surface of exhaust body 286. By reflecting the sound in an angled manner about triangularly-shaped chamber B, the sound does not reinforce on itself because the sound does not bounce off of parallel walls. As such, the sound exiting exhaust body 286 through port 296 and outlet tube 288 is not reinforced, but rather, is reduced or generally eliminated.

Referring to FIG. 34, an alternative embodiment of exhaust assembly 280 is shown as exhaust assembly 280', with like reference numerals indicating like parts having like structure and functionality. Exhaust assembly 280' may be configured as an active exhaust assembly and includes a first exhaust body 297, a second exhaust body 286', an inlet tube 284', an outlet tube or tailpipe 288', an inlet tube 291, a second tube 293, and a valve assembly 299. Exhaust assembly 280' is configured to operate in a high-flow mode and a low-flow mode. In the high-flow mode, a substantial amount or all of the exhaust flowing from engine 252 flows through exhaust assembly 280' along an unrestricted path and exits from outlet tube 288'. As a result of the unrestricted flow path, little backpressure builds within exhaust assembly 280' and a loud sound emanates from exhaust assembly 280' such that vehicle 2 operates in a high-performance, sport mode. Conversely, when vehicle 2 is in the low-flow mode, the exhaust from engine 252 is reduced when flowing through exhaust assembly 280'. Additionally, the exhaust may flow through a restricted path. As a result, the backpressure increases within exhaust assembly 280' and a quieter sound emanates from exhaust assembly 280' such that vehicle 2 operates in a restrained and muted or quiet mode.

Exhaust assembly 280' may be configured to toggle only between the high-flow mode and the low-flow mode. Alternatively, exhaust assembly 280' may be configured for an infinite number of flow options between the two modes. For example, the operator may be able to switch between the high-flow mode and the low-flow mode with a mechanical valve system, which may include a lever and a pulley to regulate the flow of exhaust through exhaust assembly 280'. Additionally, the operator may switch between the high-flow mode and the low-flow mode with an electrical system, which may include an electrical switch to toggle between the high-flow mode and the low-flow mode. Alternatively, the electrical system may include a solenoid-operated butterfly valve, which may be configured to open and close in an infinite number of positions to regulate the flow of exhaust through exhaust assembly 280. Further still, exhaust assembly 280' may include an electrical valve operably coupled to the engine control unit ("ECU") of vehicle 2 in order to regulate the flow of exhaust based on the throttle position.

In one embodiment, exhaust assembly 280' operates by coupling a butterfly valve 299a and a solenoid 299b of valve assembly 299 to first tube 291. First tube 291 is fluidly coupled to outlet tube 288' and provides an unrestricted flow path for the exhaust between inlet tube 284' and outlet tube 188'. Second tube 293 is positioned below first tube 291 and is fluidly coupled to first exhaust body 297 and second

exhaust body **286'**. The flow of exhaust through second tube **293** and second exhaust body **286'** may be restricted. For example, a plurality of baffle plates/walls or a series of cross-over tubes may be positioned within second exhaust body **286'** in order to restrict the flow of exhaust there-through.

In operation, when the operator desires to operate vehicle **2** in the high-flow, loud, sport mode, for example when the operator drives vehicle **2** in sparsely-populated areas or at open throttle, solenoid **299b** will receive a signal to open valve **299a** to allow a substantial portion or all of the exhaust entering first exhaust body **297** from inlet tube **284'** to flow into first tube **291** and into outlet tube **288'** through an unrestricted path. As such, the exhaust bypasses the restricted flow path through second tube **293** and, therefore, little backpressure builds within exhaust assembly **280'**. As a result, a loud and sportier sound is produced. The high-flow mode may correspond to an open throttle position such that the high-flow mode may be engaged when vehicle **2** is accelerating, operating at high speeds, and/or in a sport or high-performance drive mode. Exhaust assembly **280'** may be configured to allow the operator to selectively engage the high-flow mode when it is desirable to operate vehicle **2** in the sport drive mode. Alternatively, the ECU may automatically operate exhaust assembly **280'** in the high-flow mode when vehicle **2** is in the high-performance, sport drive mode or at open throttle.

Conversely, when the operator desires to operate vehicle **2** in the low-flow, quiet, restrained mode, for example when the operator drives vehicle **2** in cruise control or in a densely-populated area, such as a neighborhood, solenoid **299b** will receive a signal to at least partially close valve **299a** to restrict the amount of exhaust entering first exhaust body **297** from inlet tube **284'** to flow into first tube **291** and outlet tube **288'**. Rather, a substantial portion or all of the exhaust entering first exhaust body **297** from inlet tube **284'** is diverted to second tube **293**, where the exhaust flows into second tube **293** and through a restricted flow path in second exhaust body **286'**. As such, backpressure builds within exhaust assembly **280'** and only a quiet, muted noise is produced. The low-flow mode may correspond to a partially-closed throttle position such that low-flow mode may be engaged when vehicle **2** is decelerating, operating in cruise control, operating at low speeds, and/or in non-sport drive mode. Exhaust assembly **280'** may be configured to allow the operator to selectively engage the low-flow mode when it is desirable to operate vehicle **2** in the non-sport drive mode, for example when driving in a neighborhood. Alternatively, the ECU may automatically operate exhaust assembly **280'** in the low-flow mode, at specific throttle positions, or when vehicle **2** is in the non-sport drive mode.

In one embodiment, the position of exhaust assembly **280** or **280'** may be lowered in order to lower the center of gravity of vehicle **2**.

As shown in FIG. **35**, utility vehicle **2** may include doors **222**. Doors **222** include a recessed outer portion **224**. The recessed outer portion **224** decreases the weight of doors **222**, which may decrease the overall weight of vehicle **2** and, therefore, lower the center of gravity of vehicle **2**.

The inner surface of doors **222** is generally flat and smooth. In one embodiment, the inner surface of doors **222** may be angled or curved outwardly to increase the space within operator area **14** for the operator and passenger. Alternatively, doors **222** may include a living hinge which allows at least a portion of doors **222** to extend outwardly to further increase the space within operator area **14**. With the curved or outwardly-extending configuration of doors **222**,

the comfort of the operator and the passenger within operator area **14** may be improved.

Doors **222** are coupled to bolster bars **140** with hinges **228**. Hinges **228** are coupled to tabs **141** of bolster bars **140**. Additionally, doors **222** include a latch assembly **226**, which operably couples to frame assembly **20**. In one embodiment, doors **222** may be at least partially comprised of aluminum and plastic, thereby making doors **222** light-weight. As such, doors **222** may decrease the weight of vehicle **2** and lower the center of gravity of vehicle **2**. In one embodiment, vehicle **2** may include side nets, rather than doors **222**. The side nets may be configured to latch in a similar manner to latch assembly **226**. Further details about doors **222** of vehicle **2** may be disclosed in U.S. Provisional Patent Application Ser. No. 61/829,743, filed on May 31, 2013, the complete disclosure of which is expressly incorporated by reference herein.

Referring to FIGS. **36** and **37**, an alternative embodiment of utility vehicle **2** is shown as utility vehicle **2'**. Utility vehicle **2'** of FIGS. **36** and **37** is similar to utility vehicle **2** of FIGS. **1-35**, with like reference numerals indicating like parts having like structure and functionality, except as detailed herein. As shown in FIG. **36**, utility vehicle **2'** has front end **4** and rear end **6**. A plurality of ground engaging members, including front wheels **8'** and rear wheels **10'**, support utility vehicle **2'** on the ground surface. Illustratively, the width between the outer sides of rear wheels **10'** defines a width of vehicle **2'**, which may be approximately 50-65 inches. Illustratively, the width between the centers of the hubs of rear wheels **10** is approximately 60 inches, when measured at ride height without any payload.

Referring to FIG. **36**, a cab frame assembly **150'** is coupled to frame assembly **20** and includes front upstanding members **152**, rear upstanding members **154**, longitudinal members **156**, front cross-member **158**, rear upper cross-member **160**, rear lower cross-member **162**, and diagonal members **400**. An upper end of diagonal members **400** is coupled to rear upper cross-member **160** with coupler assemblies **130** and a lower end of diagonal members **400** is coupled to rear frame portion **26**. Illustratively, diagonal members **400** are angled downwardly over cargo box **12**.

Additionally, vehicle **2'** may include doors **222'**. Doors **222'** are coupled to bolster bars **140** and partially enclose operator area **14**. Further details about doors **222'** of vehicle **2'** may be disclosed in U.S. Provisional Patent Application Ser. No. 61/829,743, filed on May 31, 2013, the complete disclosure of which is expressly incorporated by reference herein.

Referring to FIG. **37**, vehicle **2'** includes a front suspension assembly **170'** and a rear suspension assembly **300'**. Rear suspension assembly **300'** is positioned generally rearward of powertrain assembly **250** at rear end **6** of utility vehicle **2'**. Similar to rear suspension assembly **300** of FIG. **28**, rear suspension assembly **300'** of FIG. **37** includes upper alignment arms **302'**, lower alignment arms **304'**, shock absorbers **306'**, and a torsion bar **308'**. In one embodiment, rear suspension assembly **300'** is configured for approximately 12-14 inches of travel. Illustratively, rear suspension assembly **300'** may be configured for approximately 13.2 inches of travel.

An outer end of upper and lower alignment arms **302'**, **304'** is coupled to hub assemblies **310'** of rear wheels **10'**. A lower end of shock absorber **306'** is coupled to lower alignment arm **304**. Torsion bar **308'** extends generally in a U-shape and is positioned along the inner sides of shock absorbers **306'**. Torsion bar **308** is coupled to upper alignment arms **302'**. Illustrative rear suspension assembly **300'** of

23

vehicle 2' may be approximately 10 inches wider than rear suspension assembly 300 of vehicle 2 (FIG. 28).

As shown in FIG. 37, front suspension assembly 170' includes upper alignment arms 172', lower alignment arms 174', shock absorbers 176', and a torsion bar 178'. Upper and lower alignment arms 172', 174' are coupled to a hub assembly 180' of front wheels 8'. Steering arms 192' are positioned intermediate upper alignment arms 172' and lower alignment arms 174'. Additionally, steering arms 192' are coupled to hub assemblies 180'. In one embodiment, front suspension assembly 170' is configured for approximately 10-13 inches of travel. Illustratively, front suspension assembly 170' may be configured for approximately 12.3 inches of travel.

The lower end of shock absorbers 176' is coupled to upper alignment arms 172' through a bracket 177'. Bracket 177' is also coupled to rods 186', which extend generally vertically and also couple with torsion bar 178'. Illustratively, shock absorbers 176' are operably coupled to torsion bar 178' with rods 186'. As such, movement may be transmitted between torsion bar 178' and shock absorbers 176'. Illustrative front suspension assembly 170' of vehicle 2' may be approximately 10 inches wider than front suspension assembly 170 of vehicle 2 (FIG. 28).

As with vehicle 2 of FIGS. 1-35, the center of gravity of vehicle 2' may be lowered by positioning various components of powertrain assembly 250, power steering assembly 190, front suspension assembly 170', and/or rear suspension assembly 300' lower on vehicle 2'. Additionally, the center of gravity of vehicle 2' may be lowered by comprising portions of frame assembly 20 and cab frame assembly 150' of light-weight materials, such as aluminum, carbon fiber, and/or polymeric materials, rather than steel. As such, portions of vehicle 2' may be adhered or otherwise bonded together, rather than welded.

While this invention has been described as having an exemplary design, the present invention may be further modified within the spirit and scope of this disclosure. This application is therefore intended to cover any variations, uses, or adaptations of the invention using its general principles. Further, this application is intended to cover such departures from the present disclosure as come within known or customary practices in the art to which this invention pertains.

What is claimed is:

1. A utility vehicle, comprising:
 - a plurality of ground engaging members;
 - a frame assembly supported by the ground engaging members; and
 - a powertrain assembly supported by the frame assembly and including:
 - an engine;
 - a continuously variable transmission operably coupled to the engine;
 - an air intake assembly fluidly coupled to the engine; and
 - an exhaust assembly fluidly coupled to the engine, the exhaust assembly being configured to selectively regulate a flow of exhaust from the engine in response to at least one of a drive mode, an operator input, and a throttle position.
2. The utility vehicle of claim 1, wherein the exhaust assembly includes a first exhaust body, a second exhaust body, a first passageway, a second passageway, and a valve assembly, the valve assembly being configured to direct exhaust from the engine through one of the first and second

24

passageways in response to at least one of the drive modes, the operator input, and the throttle position.

3. The utility vehicle of claim 2, wherein the valve assembly is open when the utility vehicle is operating in a high-flow mode, and the valve assembly is at least partially closed when the utility vehicle is operating in a low-flow mode.

4. The utility vehicle of claim 3, wherein a sound emanating from the exhaust assembly is greater when in the high-flow mode than in the low-flow mode.

5. The utility vehicle of claim 2, further comprising an engine control unit operably coupled to the engine and the exhaust assembly, wherein the engine control unit is configured to control a position of the valve assembly in response to the throttle position.

6. A utility vehicle, comprising:

- a plurality of ground engaging members;
- a frame assembly supported by the ground engaging members; and
- a powertrain assembly supported by the frame assembly and including:
 - an engine;
 - a transmission operably coupled to the engine;
 - an air intake assembly fluidly coupled to the engine; and
 - an exhaust assembly fluidly coupled to the engine, the exhaust assembly being configured to selectively regulate a flow of exhaust from the engine in response to at least one of a drive mode, an operator input, and a throttle position, wherein the exhaust assembly includes a first exhaust body, a second exhaust body, a first passageway, a second passageway, and a valve assembly, the valve assembly being configured to direct exhaust from the engine through one of the first and second passageways in response to at least one of the drive modes, the operator input, and the throttle position.

7. The utility vehicle of claim 6, wherein the valve assembly is open when the utility vehicle is operating in a high-flow mode, and the valve assembly is at least partially closed when the utility vehicle is operating in a low-flow mode.

8. The utility vehicle of claim 7, wherein a sound emanating from the exhaust assembly is greater when in the high-flow mode than in the low-flow mode.

9. The utility vehicle of claim 6, further comprising an engine control unit operably coupled to the engine and the exhaust assembly, wherein the engine control unit is configured to control a position of the valve assembly in response to the throttle position.

10. A utility vehicle, comprising:

- a plurality of ground engaging members;
- a frame assembly supported by the ground engaging members; and
- a powertrain assembly supported by the frame assembly and including:
 - an engine;
 - a transmission operably coupled to the engine;
 - an air intake assembly fluidly coupled to the engine; and
 - an exhaust assembly fluidly coupled to the engine, the exhaust assembly being configured to selectively regulate a flow of exhaust from the engine in response to at least one of a drive mode and an operator input.

11. The utility vehicle of claim 10, wherein the exhaust assembly includes a first exhaust body, a second exhaust

body, a first passageway, a second passageway, and a valve assembly, the valve assembly being configured to direct exhaust from the engine through one of the first and second passageways in response to at least one of the drive modes, the operator input, and the throttle position. 5

12. The utility vehicle of claim **11**, wherein the valve assembly is open when the utility vehicle is operating in a high-flow mode, and the valve assembly is at least partially closed when the utility vehicle is operating in a low-flow mode. 10

13. The utility vehicle of claim **12**, wherein a sound emanating from the exhaust assembly is greater when in the high-flow mode than in the low-flow mode.

14. The utility vehicle of claim **11**, further comprising an engine control unit operably coupled to the engine and the exhaust assembly, wherein the engine control unit is configured to control a position of the valve assembly in response to the throttle position. 15

15. The utility vehicle of claim **14**, further comprising:
 a body coupled to the frame, the body having a forward-most portion; 20
 a rear suspension assembly operably coupled to the rear ground engaging members, wherein the forward-most portion of the front ground engaging members is forward of the forward most portion of the body. 25

* * * * *