



US011668922B2

(12) **United States Patent**
Otterstrom et al.

(10) **Patent No.:** **US 11,668,922 B2**
(45) **Date of Patent:** **Jun. 6, 2023**

(54) **MULTIPLE IMAGING MODALITY LIGHT SOURCE**

(58) **Field of Classification Search**
None
See application file for complete search history.

(71) Applicant: **Stryker Corporation**, Kalamazoo, MI (US)

(56) **References Cited**

(72) Inventors: **Gregory G. Otterstrom**, Morgan Hill, CA (US); **Ajay Ramesh**, Pleasanton, CA (US); **Hannah Lawrence**, San Jose, CA (US); **Candice Pack**, Campbell, CA (US); **Richard I. Palmisano**, San Martin, CA (US)

U.S. PATENT DOCUMENTS

4,538,062 A 8/1985 Shishido
5,084,612 A 1/1992 Iwasaki et al.
(Continued)

(73) Assignee: **Stryker Corporation**, Kalamazoo, MI (US)

FOREIGN PATENT DOCUMENTS
CN 1870932 A 11/2006
CN 101295102 A 10/2008
(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

OTHER PUBLICATIONS

First Office Action dated Aug. 13, 2013, directed to CN Application No. 200920145842.3; 21 pages.

(21) Appl. No.: **17/454,055**

(Continued)

(22) Filed: **Nov. 8, 2021**

Primary Examiner — Elmito Breval

(65) **Prior Publication Data**

(74) *Attorney, Agent, or Firm* — Morrison & Foerster LLP

US 2022/0057622 A1 Feb. 24, 2022

(57) **ABSTRACT**

Related U.S. Application Data


A light source includes a first LED to provide light of a first light wavelength spectrum along a first light path; a second LED to provide light of a second light wavelength spectrum along a second light path; a dichroic filter for passing light emitted from at least one of the first LED and the second LED and reflecting light emitted from at least one of the first LED and the second LED; an optical filter movable between a first position in which the optical filter receives light from the first light path and a second position of which the optical filter does not receive light from the first light path; a light output; a controller which is capable of switching the light source between a first mode for providing a first light to the light output and a second mode for providing a second light to the light output.

(60) Continuation of application No. 16/908,648, filed on Jun. 22, 2020, now Pat. No. 11,169,370, which is a (Continued)

(51) **Int. Cl.**
G02B 23/24 (2006.01)
G02B 27/10 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **G02B 23/2461** (2013.01); **A61B 1/00105** (2013.01); **A61B 1/00126** (2013.01);
(Continued)

15 Claims, 27 Drawing Sheets



Related U.S. Application Data

division of application No. 15/458,137, filed on Mar. 14, 2017, now Pat. No. 10,690,904.

(60) Provisional application No. 62/321,414, filed on Apr. 12, 2016.

(51) **Int. Cl.**

G02B 27/14 (2006.01)
A61B 1/06 (2006.01)
A61B 1/00 (2006.01)
H04N 23/56 (2023.01)
A61B 90/00 (2016.01)
G02B 23/26 (2006.01)
H04N 23/50 (2023.01)

(52) **U.S. Cl.**

CPC **A61B 1/0638** (2013.01); **A61B 1/0646** (2013.01); **A61B 1/0669** (2013.01); **A61B 1/0684** (2013.01); **G02B 27/1006** (2013.01); **G02B 27/141** (2013.01); **H04N 23/56** (2023.01); **A61B 2090/3937** (2016.02); **G02B 23/26** (2013.01); **H04N 23/555** (2023.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,093,769 A 3/1992 Luntsford
 5,132,526 A 7/1992 Iwasaki
 5,269,289 A 12/1993 Takehana et al.
 5,636,259 A 6/1997 Khutoryansky et al.
 5,717,605 A 2/1998 Komiya et al.
 5,842,765 A 12/1998 Cassarly et al.
 5,917,883 A 6/1999 Khutoryansky et al.
 5,957,834 A 9/1999 Mochida
 6,040,940 A 3/2000 Kawasaki
 6,193,401 B1 2/2001 Girkin et al.
 6,195,154 B1 2/2001 Imai
 6,485,414 B1 11/2002 Neuberger
 6,549,239 B1 4/2003 Tao
 6,563,632 B1 5/2003 Schoeppe et al.
 6,663,560 B2 12/2003 Macaulay et al.
 6,730,019 B2 5/2004 Irion
 6,876,494 B2 4/2005 Ishikawa et al.
 6,924,490 B2 8/2005 Natori
 7,015,444 B2 3/2006 Kawano et al.
 7,016,053 B2 3/2006 Moriuchi et al.
 7,176,428 B2 2/2007 Kawano et al.
 7,223,986 B2 5/2007 Natori
 7,239,384 B2 7/2007 Kawano
 7,258,663 B2 8/2007 Doguchi et al.
 7,268,938 B2 9/2007 Kawano et al.
 7,304,789 B2 12/2007 Hirata et al.
 7,448,995 B2 11/2008 Wiklof et al.
 7,583,389 B2 9/2009 Neal et al.
 7,609,440 B2 10/2009 Tanikawa et al.
 7,616,330 B2 11/2009 Neal et al.
 7,623,251 B2 11/2009 Neal et al.
 7,661,862 B2 2/2010 Lee et al.
 8,408,704 B2 4/2013 Tomidokoro et al.
 8,892,190 B2 11/2014 Docherty et al.
 9,459,415 B2 10/2016 Feingold et al.
 10,690,904 B2 6/2020 Otterstrom et al.
 11,169,370 B2 11/2021 Otterstrom et al.
 2002/0014595 A1 2/2002 Sendai et al.
 2002/0043636 A1 4/2002 Kimura
 2002/0101643 A1 8/2002 Kobayashi
 2002/0120181 A1 8/2002 Irion
 2002/0168096 A1 11/2002 Hakamata et al.
 2003/0007087 A1 1/2003 Hakamata et al.
 2003/0042493 A1 3/2003 Kazakevich
 2003/0067645 A1 4/2003 Ibsen et al.
 2003/0147254 A1 8/2003 Yoneda et al.
 2003/0169431 A1 9/2003 Moriuchi et al.

2003/0184661 A1 10/2003 Yubata et al.
 2003/0202090 A1 10/2003 Ota et al.
 2004/0061673 A1 4/2004 Ishikawa et al.
 2004/0105095 A1 6/2004 Stobrawa et al.
 2004/0105482 A1 6/2004 Sugiyama et al.
 2004/0147806 A1 7/2004 Adler
 2004/0228373 A1 11/2004 Tatsuno et al.
 2005/0020926 A1 1/2005 Wiklof et al.
 2005/0099824 A1 5/2005 Dowling et al.
 2005/0187441 A1 8/2005 Kawasaki et al.
 2005/0200947 A1 9/2005 Hirata et al.
 2005/0203423 A1 9/2005 Zeng et al.
 2005/0211872 A1 9/2005 Kawano et al.
 2005/0224692 A1 10/2005 Tsuchiya et al.
 2005/0228231 A1 10/2005 Mackinnon et al.
 2005/0237604 A1 10/2005 Kawano et al.
 2005/0251230 A1 11/2005 Mackinnon et al.
 2005/0253056 A1 11/2005 Nakata
 2005/0270641 A1 12/2005 Hirata et al.
 2005/0276553 A1 12/2005 Kazakevich
 2005/0279950 A1 12/2005 Kawano et al.
 2006/0009682 A1 1/2006 Nagasawa et al.
 2006/0017920 A1 1/2006 Tsuchiya et al.
 2006/0103922 A1 5/2006 Tsuyuki
 2006/0146125 A1 7/2006 Yamada
 2006/0175546 A1 8/2006 Asai
 2006/0187499 A1 8/2006 Natori et al.
 2007/0028918 A1 2/2007 Tsuyuki et al.
 2007/0051869 A1 3/2007 Knebel
 2007/0091425 A1 4/2007 Kawano
 2007/0097369 A1 5/2007 Shimada
 2007/0100241 A1 5/2007 Adler
 2007/0104417 A1 5/2007 Tanaka et al.
 2007/0120070 A1 5/2007 Kawano et al.
 2007/0153367 A1 7/2007 Kawasaki
 2007/0159682 A1 7/2007 Tanaka et al.
 2007/0188707 A1 8/2007 Nanjo
 2007/0213588 A1 9/2007 Morishita et al.
 2007/0213593 A1 9/2007 Nakaoka
 2007/0236701 A1 10/2007 Neal et al.
 2007/0236702 A1 10/2007 Neal et al.
 2007/0236703 A1 10/2007 Neal et al.
 2007/0270652 A1 11/2007 Morishita et al.
 2007/0274649 A1 11/2007 Takahashi et al.
 2007/0299309 A1 12/2007 Seibel et al.
 2008/0039695 A1 2/2008 Takaoka et al.
 2008/0043244 A1 2/2008 Hatori et al.
 2008/0137328 A1 6/2008 Lee et al.
 2008/0186388 A1 8/2008 Yamagata et al.
 2008/0198448 A1 8/2008 Ganser et al.
 2008/0225388 A1 9/2008 Hirata
 2008/0232131 A1 9/2008 Suda
 2008/0246920 A1 10/2008 Buczek et al.
 2008/0252900 A1 10/2008 Hatori
 2008/0283770 A1 11/2008 Takahashi
 2009/0032732 A1 2/2009 Konishi
 2009/0067042 A1 3/2009 Tanikawa
 2009/0073553 A1 3/2009 Hirata
 2009/0201577 A1 8/2009 Laplante
 2009/0244521 A1 10/2009 Yazdanfar et al.
 2009/0251704 A1 10/2009 Masuda
 2010/0245552 A1 9/2010 Higuchi
 2011/0063427 A1 3/2011 Fengler
 2011/0208004 A1 8/2011 Feingold
 2012/0004508 A1 1/2012 McDowall et al.
 2012/0230024 A1 9/2012 Moore
 2012/0248333 A1 10/2012 Fallert et al.
 2012/0257030 A1 10/2012 Lim et al.
 2014/0031623 A1* 1/2014 Kagaya A61B 1/0638
 2015/0098065 A1 4/2015 Tanaka
 2015/0112192 A1 4/2015 Docherty et al.
 2015/0112193 A1 4/2015 Docherty et al.
 2015/0238127 A1 8/2015 Saito
 2015/0253653 A1 9/2015 Fujita
 2016/0022126 A1 1/2016 Ramesh et al.
 2016/0029874 A1 2/2016 Usami
 2016/0231494 A1 8/2016 Feingold et al.

A61B 1/0638
600/109

(56)

References Cited

U.S. PATENT DOCUMENTS

2017/0188853 A1 7/2017 Nakao
 2017/0293134 A1 10/2017 Otterstrom et al.
 2021/0011274 A1 1/2021 Otterstrom et al.

FOREIGN PATENT DOCUMENTS

EP 1930751 A2 6/2008
 JP S54-10237 Y2 5/1979
 JP H7-67832 A 3/1995
 JP H7-275192 A 10/1995
 JP H11-253384 A 9/1999
 JP 2001-224015 A 8/2001
 JP 2006-87764 A 4/2006
 WO 2005/000110 A2 1/2005
 WO 2010/059197 A2 5/2010
 WO WO-2014152757 A2 * 9/2014 A61B 1/00006

OTHER PUBLICATIONS

International Preliminary Report on Patentability dated Jun. 3, 2011, directed to International Application No. PCT/US2009/006155; 10 pages.

International Search Report and Written Opinion dated Jun. 7, 2010, directed to International Application No. PCT/US2009/006155; 14 pages.

International Search Report dated Nov. 3, 2014, directed to International Application No. PCT/US2014/027700; 6 pages.

Office Action dated Feb. 28, 2014, directed to JP Application No. 2011-536337; 6 pages.

Office Action dated Jul. 19, 2013, directed to JP Application No. 2011-536337; 7 pages.

Office Action dated Nov. 5, 2020, directed to JP Application No. 2011-536337; 5 pages.

Otterstrom et al., U.S. Office Action dated Sep. 26, 2019, directed to U.S. Appl. No. 15/458,137; 6 pages.

Otterstrom et al., U.S. Office Action dated Feb. 19, 2019, directed to U.S. Appl. No. 15/458,137; 6 pages.

Otterstrom et al., U.S. Notice of Allowance and Fee(s) due dated Feb. 13, 2020, directed to U.S. Appl. No. 15/458,137; 7 pages.

Otterstrom et al., U.S. Restriction Requirement dated Nov. 5, 2018, directed to U.S. Appl. No. 15/458,137; 5 pages.

International Written Opinion dated Nov. 3, 2014, directed to international Application No. PCT/US2014/027700; 7 pages.

Otterstrom et al., U.S. Office Action dated Oct. 28, 2020, directed to U.S. Appl. No. 16/908,648; 8 pages.

Otterstrom et al., U.S. Notice of Allowance and Fee(s) Due dated Jul. 2, 2021, directed to U.S. Appl. No. 16/908,648; 8 pages.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3B

FIG. 3A




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13A




FIG. 13B




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26

1**MULTIPLE IMAGING MODALITY LIGHT SOURCE****CROSS-REFERENCE TO RELATED APPLICATIONS**

This application is a continuation of U.S. patent application Ser. No. 16/908,648, filed Jun. 22, 2020, which is a divisional of U.S. patent application Ser. No. 15/458,137, filed Mar. 14, 2017, now U.S. Pat. No. 10,690,904, which claims the benefit of U.S. Provisional Application No. 62/321,414, filed Apr. 12, 2016, the entire contents of each of which are incorporated by reference herein.

FIELD OF THE INVENTION

The present invention relates generally to a solid state system for providing illumination from an external light source through an instrument to an object, such as a patient surgical site. The external light source includes components for providing light in the visible spectrum as well as light in the ultraviolet and/or infrared spectrums.

BACKGROUND OF THE INVENTION

Endoscopic systems are used to inspect regions within a body during surgery. Endoscopic systems typically include an endoscope, a light source, and an imaging device such as a camera head. Typically, an endoscope includes a rigid or flexible elongated insertion tube equipped with a set of optical fibers that extend from a proximal handle through the endoscope body to a distal viewing tip. An external light source provides light to the optic fibers via a cable that attaches to a post or other structure on the endoscope. The endoscope also receives images and transmits them to the imaging device for providing an image to a monitor or other display apparatus for viewing by a surgeon.

In one commercial embodiment, an endoscopic system includes a solid state light source that generates white light which is conveyed to a distal end of the endoscope via a light guide. The light guide includes multiple fibers and is connected between an output connector of the light source and a light post of the endoscope. The white light illuminates a working area at the distal end of the endoscope. The camera, connected to a handle of the endoscope, generates video signals representative of images at the working area for display on a video monitor.

The light source includes an optical system and a lens array used to collimate light from an LED array. A focusing lens focuses the light onto the light guide. The lenses collect light emitted by LEDs. The lenses may be single lenses, such as single or double aspherics, compound lenses, radiant index type lenses, or combinations of each of these. Other arrangements have lens arrays that are implemented as part of an LED array by adhesion, fusion, or other means. Some arrangements have a rectangular-shaped LED and lens array.

The focal length of the lens and the diameter of the lens are chosen on the order of a few millimeters. The actual values are selected based on the size of the LED emitting surface which determines the field of view of the lens.

The collected light from the lens array travels to a focusing lens. The focusing lens projects the light image of each LED emitting surface onto an entrance face of the light guide. The image is magnified so that the size is approximately equal to the size of the entrance face of the light guide. The light guide transports the light to the endoscope. The light passes through the endoscope to illuminate a

2

surgical site. Light is reflected off of the surgical site which is received by the endoscope and transmitted to the camera head. The camera head provides images of the surgical site for display on the monitor.

Another endoscopic system that has been designed is described in commonly-owned PCT Application No. WO 2010/059197 A2.

The above-described endoscopic systems do not concern themselves with the ability of providing specific wavelengths of light or excitation of fluorescent markers in an object, such as a body part at a surgical site. While there are systems on the market that do provide excitation light for fluorescent markers, these systems typically use incandescent light and/or multiple light sources and multiple components to transmit light to the surgical site, and multiple components to separate the light emitted.

SUMMARY OF THE INVENTION

One embodiment of the present invention includes a single light source which is capable of providing white light, and providing ultraviolet light. The embodiment includes one or more movable light filters to provide a variety of illumination modes.

Another embodiment of the invention employs a light source to provide light in the red, blue, green, ultraviolet and infrared wavelength spectra to an endoscope which transports the light to a surgical site. Reflected light and fluorescent light from fluorescent markers at the surgical site are then transmitted through the endoscope, through a notch filter, for separation of light in the desired spectra, then to the imaging device.

Yet another embodiment of the invention includes two or more infrared laser diodes in the same light engine slot. The two or more infrared laser diodes are each connected to the same heat sink.

Still another embodiment of the invention employs a modular light engine which may be replaced with other modular light engines and/or may provide additional illumination modes to an existing light source.

Other advantages, objects and/or purposes of the invention will be apparent to persons familiar with constructions of this general type upon reading the following specification and inspecting the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an illustration of an endoscopic camera arrangement which is an embodiment of the present invention.

FIG. 2 is a diagram of a portion of the endoscopic camera arrangement of FIG. 1 and an object with fluorescent markers in it.

FIG. 3A is an enlarged, longitudinal and fragmentary cross-sectional view of the distal end of a preferred endoscope.

FIG. 3B is an enlarged end view of the distal end of the endoscope as seen generally along line IIIB-IIIB in FIG. 3A.

FIG. 4 is a block diagram of a light source of the endoscopic system of FIG. 1.

FIG. 5 is a diagrammatic view of the light and filter portion of the light source of FIG. 4 with movable filters out of the light paths, and showing a light emission first mode.

FIG. 6 is a diagrammatic view of the LED and filter portion of FIG. 5 with movable filters in the light paths of an ultraviolet light and a green light, and showing a light emission second mode.

3

FIG. 7 is a diagrammatic view of the LED and filter portion of FIG. 5, and showing a light emission third mode.

FIG. 8 is a diagrammatic view of the LED and filter portion of FIG. 5, and showing a light emission fourth mode.

FIG. 9 is a diagrammatic view of the LED and filter portion of FIG. 5, and showing a light emission fifth mode.

FIG. 10 is a diagrammatic view of a second embodiment of the light and filter portion of the light source of the endoscopic system of FIG. 1, and having LEDs for ultra-violet light, blue light, green light, and red light, and a laser diode for infrared light.

FIG. 11 is a diagrammatic view of a third embodiment of the light and filter portion of the light source of the endoscopic system of FIG. 1, and having LEDs for blue light, green light, and red light, multiple laser diodes for infrared light, and optionally an LED for ultraviolet light.

FIG. 12 is a perspective view of a single light source slot in a light engine having two infrared laser diodes, both connected to a single heat sink.

FIG. 13A is a perspective view of a light source stack which includes a plurality of laser diodes.

FIG. 13B is an elevational side view of the light source stack, including infrared laser diodes, and a heat sink, of FIG. 12.

FIG. 14 is a diagrammatic view of a fourth embodiment of the light and filter portion of the light source of the endoscopic system of FIG. 1, and having LEDs for white light and UV light and multiple laser diodes for infrared light.

FIG. 15 is a perspective view of a light source with a modular light engine.

FIG. 16 is a rear perspective view of the light source with modular light engine of FIG. 15, with the housing of the light source removed.

FIG. 17 is a perspective view of the modular light engine of FIG. 15 with the housing removed.

FIG. 18 is a perspective view of a light source with a modular upgrade to the light engine.

FIG. 19 is a perspective view of the modular upgrade of FIG. 18 with a portion of the housing removed.

FIG. 20 is an elevational view of the modular upgrade of FIG. 18 with a portion of the housing removed, and showing the light paths therein.

FIG. 21 is a top perspective view of a light module receiving base of a light source.

FIG. 22 is a perspective view of a portion of the light module receiving base of FIG. 21.

FIG. 23 is a top plan view of an embodiment of a light module.

FIG. 24 is a top perspective view of the light module of FIG. 23.

FIG. 25 is a top perspective view of the light module of FIG. 23 engaging with the base of FIG. 21.

FIG. 26 is a partially exploded view of an embodiment of a light module and a movable filter.

DETAILED DESCRIPTION

Certain terminology will be used in the following description for convenience and reference only, and will not be limiting. For example, the words “upwardly,” “downwardly,” “rightwardly,” and “leftwardly” will refer to directions in the drawings to which reference is made. The words “inwardly” and “outwardly” will refer to directions toward and away from, respectively, the geometric center of the arrangement,

4

and designated parts thereof. This terminology includes the words specifically mentioned, derivatives thereof, and words of similar import.

FIG. 1 shows an endoscopic camera arrangement 10, including a scope assembly 11 which may be utilized in endoscopic procedures. The scope assembly 11 incorporates an endoscope or scope 12 which is coupled to a camera head 16 by a coupler 13 located at the distal end of the camera head 16. Light is provided to the scope by a light source 14 via a light guide 26, such as a fiber optic cable. The camera head 16 is coupled to a camera control unit (CCU) 18 by an electrical cable 15. The CCU 18 is preferably connected to, and communicates with, the light source 14. Operation of the camera 16 is controlled, in part, by the CCU 18. The cable 15 conveys video image data from the camera head 16 to the CCU 18 and conveys various control signals bi-directionally between the camera head 16 and the CCU 18. In one embodiment, the image data output by the camera head 16 is digital.

A control or switch arrangement 17 is provided on the camera head 16 and allows a user to manually control various functions of the arrangement 10. Voice commands are input into a microphone 25 mounted on a headset 27 worn by the surgeon and coupled to a voice-control unit 23. A hand-held control device 21, such as a tablet with a touch screen user interface or a PDA, may be coupled to the voice control unit 23 as a further control interface. In the illustrated embodiment, a recorder 31 and a printer 33 are also coupled to the CCU 18. Additional devices, such as an image capture and archiving device, may be included in the arrangement 10 and coupled to the CCU 18. Video image data acquired by the camera head 16 and processed by the CCU 18 is converted to images, which can be displayed on a monitor 20, recorded by the recorder 31, and/or used to generate static images, hard copies of which can be produced by the printer 33.

FIG. 2 shows an embodiment of part of the endoscopic system 10 used to illuminate and receive light from an object 1, such as a surgical site of a patient. The object 1, depending on the procedure, may include fluorescent or other imaging markers 2 therein. The markers 2 are preferably comprised of indocyanine green (ICG) which is an FDA-approved fluorescent dye for bile duct identification and sentinel lymph node (SLN) identification; a hexaminolevulinate hydrochloride imaging agent for locating cancerous tissues such as tumors, also known as UV fluorescent imaging or more specifically, 5-ALA imaging; or a fluorophore such as fluorescein, which is an FDA-approved fluorescent dye for cerebrospinal fluid identification.

FIGS. 3A and 3B illustrate the structure of a preferred embodiment of the endoscope 12 in greater detail at the distal end 38 thereof. A shaft 36 of the endoscope 12 is defined by a substantially cylindrical and tubular outer housing 40 and an inner tubular housing 42 located within the outer housing 40. The outer and inner housings 40, 42 are sized such that an annular space 44 is defined therebetween which extends along a substantial portion of the longitudinal extent of the shaft 36. A cylindrical optical fiber 46 is located within the annular space 44 and extends from the distal end 38 rearwardly to the proximal end of the endoscope 12 to receive electromagnetic radiation transmitted into the endoscope 12 via the light guide 26.

In the illustrated example, the inner tubular housing 42 encloses the innermost functional components of the endoscope 12, such as an optical train 48. The optical train 48 can comprise an image lens 50 at the distal end 38 suitably fixed or connected to the inner surface of the inner tubular housing

42 with a corresponding generally annular image lens casing 52. A distal window 54 is located at the distal terminus of the tubular outer housing 40, the inner tubular housing 42 and the optical fiber 46. In one embodiment, the otherwise empty spaces in the optical train 48, for instance the space between the image lens 50 and the distal window 54, are hermetically sealed against the exterior of the endoscope 12 and filled with a specified fluid such as low-humidity nitrogen gas. Alternatively, one or more such spaces may be hermetically sealed with respect to the exterior of the endoscope 12 and substantially devoid of fluid. The components and workings of the endoscopic system as described above are conventional and further description is accordingly not provided herein.

The illustrated endoscope 12 includes the distal window 54 on the distal end 38 thereof. The distal window 54 allows the imaging light coming from the optical fiber 46 to pass therethrough for illuminating the surgical field. After passing through the distal window 54, the imaging light reflects off of matter in the surgical field, for example, object 1, and reflects back through and into the endoscope 12 through a center area of the distal window 54 to be passed to an eyepiece. The distal window 54, however, typically does not allow heating light to pass therethrough in order to absorb energy of the heating light to heat the distal window 54. Heating of the distal window 54 prevents moisture from condensating on an exterior surface 56 of the distal window 54, thereby preventing fogging of the endoscope 12. The distal window 54 can comprise an optical absorbing element or an optical absorbing element in combination with another optical element (e.g., a fully transparent window). This endoscope and its anti-fogging features are described in detail in U.S. Ser. No. 14/155,480, that published as U.S. Pub. Pat. App. No. 2014/0200406, and which is hereby incorporated by reference in its entirety.

The light source 14 depicted in FIG. 4 may generate light in five modes: (1) white light (a combination of red, green, and blue light), (2) a limited band imaging mode using the UV LED with a 415-nm filter and the green LED with a 540-nm filter, (3) a UV fluorescent mode using only the UV LED (and preferably no filter), which includes, but is not limited to, a 5-ALA fluorescence mode, (4) a fluorescein mode using the UV LED and the blue LED, preferably without filters, and (5) an endoscope defogging mode in which all of the UV LED, the blue LED, the green LED, and the red LED are used.

In all five modes, the light is transmitted to and through an optic lens output system 22 (see FIG. 2) which focuses light onto a light pipe 24. The light pipe 24 preferably has a diameter substantially similar to the diameter of the fiber bundle of the endoscope and creates a homogeneous light, which is then transmitted to the fiber optic light guide 26. The light guide 26 includes multiple optic fibers and is connected to a light post 28, which is part of the endoscope 12. As described above, the endoscope 12 has an illumination pathway and an optical channel pathway.

The endoscope 12 may include a notch filter 8, which allows at least 80% of infrared light in a wavelength range of 830 nm to 870 nm to pass therethrough and allows at least 80% of visible light in the wavelength range of 400 nm to 700 nm to pass therethrough, but blocks light having a wavelength of 808 nm, and other similar wavelengths, if desired or more practical. The notch filter 8 should have an optical density of OD5 or higher. Alternatively, the notch filter 8 can be located in the coupler 13.

The basic components of the light source 14 are shown in FIG. 4. The light source 14 includes an LED and filter

section 129, which has a first LED 130, a second LED 132, a third LED 134, and a fourth LED 136. Preferably, the first LED 130 emits light in the ultraviolet spectrum (preferably 400-440 nm and more preferably 405-420 nm) and includes light having a wavelength range of 407-409 nm, the second LED 132 emits light in the blue wavelength spectrum, the third LED 134 emits light in the green wavelength spectrum, and the fourth LED 136 emits light in the red wavelength spectrum. The first LED 130 is activated by a first LED driver 138, the second LED 132 is activated by a second LED driver 140, the third LED 134 is activated by a third LED driver 142, and the fourth LED 136 is activated by a fourth LED driver 144. The drivers 138, 140, 142, 144 are each powered by an external power supply 148.

The electrical currents supplied to the LEDs 130, 132, 134, 136, are adjusted using a Digital-to-Analog Converter (DAC) 130a for the UV LED 130, a DAC 132a for the blue LED 132, a DAC 134a for the green LED 134, and a DAC 136a for the red LED 136.

Adjacent the first LED 130 is a first optical component 130', adjacent the second LED 132 is a second optical component 132', adjacent the third LED 134 is a third optical component 134', and adjacent the fourth LED 136 is a fourth optical component 136'. The optical components 130', 132', 134', 136' are for the purpose of decreasing the angles of the paths of the light emitted from the LEDs 130, 132, 134, 136, respectively. The optical components 130', 132', 134', 136' may be any component that is capable of achieving the desired purpose, but preferably are lenses or light pipes.

Adjacent the first optical component 130' is a first motorized movable filter 141, and adjacent the third optical component 134' is a second motorized movable filter 145. The movable filters 141, 145 may be used to filter light from the first and third LEDs 130, 134, respectively, or not used depending on the desired imaging mode, as discussed below.

The first motorized movable filter 141 includes an optical filter 141' and a motor 141" (see FIGS. 5-9). Activation of the motor 141" allows the optical filter 141' to be moved into or out of the pathway along which light emitted by the first LED 130 travels. The second motorized movable filter 145 includes an optical filter 145' and a motor 145". Activation of the motor 145" allows the optical filter 145' to be moved into or out of the pathway along which light emitted by the third LED 134 travels.

Adjacent the first movable filter 141 is a first dichroic filter 150, adjacent the second optical component 132' is a second dichroic filter 152, and adjacent both the second movable filter 145 and the fourth optical component 136' is a third dichroic filter 154. The dichroic filters 150, 152, 154 are each designed to reflect certain light and allow passage of other light therethrough, as described in more detail below.

A color sensor 160 is positioned adjacent the second dichroic filter 152, at a location opposite the second LED 132. The color sensor 160 detects light in the visible light wavelength spectrum, and when visible light is detected, it provides a signal to a color balance circuit/logic device 162. The amount of visible light detected is used by the color balance circuit/logic device 162 to provide signals to the LED drivers 140, 142, 144 to adjust the intensity of one or more of the LEDs 132, 134, 136, such that the preferred balance of light in the visible spectrum is achieved. A switching logic device 164 is provided which switches the light source 14 among the various modes of the light source 14.

FIGS. 5-9 show a more detailed view of the LED and filter section 129 of the first embodiment. In this arrangement, the

first dichroic filter **150** allows all visible light (i.e. light in the blue, green, and red wavelength spectra) to pass, while reflecting ultraviolet light. The second dichroic filter **152** allows light in the red and green wavelength spectra to pass while reflecting light in the blue wavelength spectrum. The third dichroic filter **154** allows light in the red wavelength spectrum to pass, while reflecting light in the green wavelength spectrum. A first optical lens **166** is located between the first dichroic filter **150** and the second dichroic filter **152**, and is for focusing light received from the second dichroic filter **152** to be passed to the first dichroic filter **150**. A second optical lens **168** is located between the second dichroic filter **152** and the third dichroic filter **154**, and is for focusing light received from the third dichroic filter **154** to be passed to the second dichroic filter **152**.

In operation in the first mode, shown in FIG. **5**, power is not supplied to the first LED driver **138**, but is supplied to the second LED driver **140**, the third LED driver **142**, and the fourth LED driver **144**. Thus, in this mode, no light is provided by the first LED **130**, but light is provided by the second LED **132**, the third LED **134**, and the fourth LED **136**. Also, the movable filters **141'**, **145'** are positioned outside of the light paths. Light in the red wavelength spectrum is emitted from the fourth LED **136** in the direction of the pathway **170** toward the fourth optical component **136'** and the third dichroic filter **154**, as shown in FIG. **5**. Light in the green wavelength spectrum is emitted from the third LED **134** in the direction of the pathway **172** toward the third optical component **134'** and the third dichroic filter **154**. Because the third dichroic filter **154** allows red light to pass and reflects green light, the light along the pathway **174** is a mixture of light in the red and green wavelength spectra. This mixture of light from the pathway **174** is focused by the second optical lens **168** and transmitted along the pathway **176** to the second dichroic filter **152**. Light in the blue wavelength spectrum is emitted by the second LED **132** along the pathway **178** toward the second optical component **132'** and the second dichroic filter **152**. Because the second dichroic filter **152** allows red and green light to pass and reflects blue light, the light along the pathway **180** is a mixture of blue, green, and red light. This light is transmitted along the pathway **180** and through optical lens **166**, which focuses the light. The focused blue, green, and red light mixture is transmitted along the pathway **182** toward the first dichroic filter **150**, which allows blue light, green light, and red light to pass. Thus, all of the light transmitted along the pathway **182** passes through the first dichroic filter **150** to an exit pathway **184**. The mixture of blue light, green light, and red light, i.e. white light, is transmitted along the exit pathway **184** to the lens system **22**, as shown in FIG. **2**.

In the second mode, shown in FIG. **6**, power is provided to the first LED driver **138** and to the third LED driver **142**, but is not provided to the second LED driver **140** or the fourth LED driver **144**. Thus, the light source **14** provides ultraviolet light and light in the green wavelength spectrum. Because the second LED **132** and the fourth LED **136** provide no light in this mode, there is no light transmitted along the pathways **178** and **170** (see FIG. **5**). In this mode, the movable filters **141'**, **145'** are positioned in the pathways **186**, **172**, respectively, for filtering of the light emissions of the first LED **130** and the third LED **134**. The third LED **134** emits light in the green wavelength spectrum along pathway **172** in the direction of the third optical component **134'**, the movable filter **145'**, and the third dichroic filter **154**, which reflects the green light. The movable filter **145'** filters the light from the LED **134** such that light reaching the dichroic filter **154** along pathway **172** is only visible light having a

wavelength of approximately 540 nm. As a result, the 540-nm light is transmitted along the pathway **174**, to and through the optical lens **168**, along the pathway **176** to the second dichroic filter **152**, along the pathway **180** to and through the lens **166**, and along pathway **182** to the dichroic filter **150**. The first LED **130** emits ultraviolet light along the pathway **186** in the direction of the first optical component **130'**, the movable filter **141'**, and the first dichroic filter **150**. The light reaching the movable filter **141'** is filtered such that light reaching the dichroic filter **150** along pathway **186** is only ultraviolet light having a wavelength of approximately 415 nm. Because the first dichroic filter **150** passes light in the visible wavelength spectrum, and reflects ultraviolet light, the result of light transmitted along the exit pathway **184** is a mixture of 540-nm visible light, and 415-nm ultraviolet light, as shown in FIG. **6**. This mixture of light is transmitted to the lens system **22**.

As shown in FIG. **7**, operation in the third mode involves supplying power to only the first LED **130**. Power is not supplied to the second LED **132**, the third LED **134**, or the fourth LED **136**. The movable filter **141'** is positioned outside of the light pathway **186** such that light from the first LED **130** travels along pathway **186** to and through the optical component **130'**, and to the dichroic filter **150**. The UV light emitted by the first LED **130** is reflected by the first dichroic filter **150**, and thus the light from the first LED **130** moves along the exit pathway **184** to the lens system **22**.

In the fourth mode, shown in FIG. **8**, power is supplied to the first LED driver **138** and the second LED driver **140**, but is not supplied to the third LED driver **142** and the fourth LED driver **144**. Thus, in this mode, light is provided only by the first LED **130** and the second LED **132**. Also, the movable filters **141'**, **145'** are positioned outside of the light paths. Light in the blue wavelength spectrum is emitted by the second LED **132** along the pathway **178** toward the second optical component **132'** and the second dichroic filter **152**. This light is reflected by the second dichroic filter **152** and transmitted along the pathway **180** and through optical lens **166**, which focuses the light. The focused blue light is transmitted along the pathway **182** toward the first dichroic filter **150**, which allows blue light to pass. Light in the UV wavelength spectrum is emitted from the first LED **130** in the direction of pathway **186** toward the first optical component **130'**, and to the dichroic filter **150**. The UV light emitted by the first LED **130** is reflected by the first dichroic filter **150**. The mixture of UV and blue light is transmitted along the exit pathway **184** to the lens system **22**, as shown in FIG. **2**.

In the fifth mode, shown in FIG. **9**, power is supplied to the first LED driver **138**, the second LED driver **140**, the third LED driver **142**, and the fourth LED driver **144**. Thus, in this mode, light is provided by the first LED **130**, the second LED **132**, the third LED **134**, and the fourth LED **136**. Also, the movable filters **141'**, **145'** are positioned outside of the light paths. Light in the red wavelength spectrum is emitted from the fourth LED **136** in the direction of the pathway **170** toward the fourth optical component **136'** and the third dichroic filter **154**, as shown in FIG. **9**. Light in the green wavelength spectrum is emitted from the third LED **134** in the direction of the pathway **172** toward the third optical component **134'** and the third dichroic filter **154**. Because the third dichroic filter **154** allows red light to pass and reflects green light, the light along the pathway **174** is a mixture of light in the red and green wavelength spectra. This mixture of light from the pathway **174** is focused by the second optical lens **168** and transmitted along the pathway **176** to the second dichroic filter **152**. Light in the blue

wavelength spectrum is emitted by the second LED **132** along the pathway **178** toward the second optical component **132'** and the second dichroic filter **152**. Because the second dichroic filter **152** allows red and green light to pass and reflects blue light, the light along the pathway **180** is a mixture of blue, green, and red light. This light is transmitted along the pathway **180** and through optical lens **166**, which focuses the light. The focused blue, green, and red light mixture is transmitted along the pathway **182** toward the first dichroic filter **150**, which allows blue light, green light, and red light to pass. Light in the UV wavelength spectrum is emitted from the first LED **130** in the direction of pathway **186** toward the first optical component **130'**, and to the dichroic filter **150**. The UV light emitted by the first LED **130** is reflected by the first dichroic filter **150**. The mixture of UV light, blue light, green light, and red light is transmitted along the exit pathway **184** to the lens system **22**, as shown in FIG. **2**.

After the light, in the first mode, the second mode, the third mode, fourth mode, or fifth mode passes through the lens system **22**, it is transmitted through the light pipe **24**, through the fiber optic light guide **26**, and to the endoscope **12** via the light post **28**. The light transmits through the illumination pathway of the endoscope to the object **1**.

In the first mode, visible light is reflected off of the object **1**, a portion of which is received by the endoscope **12**, and which is transmitted to the camera head **16** via the optical channel pathway. In the second mode, 415-nm UV light, as well as 540-nm visible light, are transmitted to the object **1**. The light is reflected or absorbed by the object **1**, and a portion of the reflected light is received by the endoscope **12**. In the third mode, UV light is transmitted to the object **1**, and excites the fluorescent markers **2** in the object. The excitation of the fluorescent markers **2** causes the markers **2** to emit their own light, which is approximately 633-nm red/pink light. This 633-nm light, along with some reflected light, is transmitted to the camera head **16** via the optical channel pathway. A filter may be used in the endoscope **12** to block excitation light so as to prevent excitation light from washing out the fluorescent emission. In the fourth mode, 415-nm UV light, as well as blue visible light, are transmitted to the object **1**. The light in the 465 nm to 490 nm range excites fluorescein markers in the object **1**. The excitation of the fluorescent markers causes the markers **2** to emit their own light in the 520 nm to 530 nm range. A filter may be used in the endoscope **12** or in the coupler **13** to prevent reflected blue light from washing out the received light emission. In the fifth mode, UV light, blue light, green light, and red light are all transmitted to and through the endoscope **12**. The light emitted can be used to defog the endoscope by reducing or eliminating moisture on the exterior surface **56** of the distal window via absorption of radiation from the light.

The light, in the first mode, the second mode, the third mode, or the fourth mode, returns along a path to the camera head **16** as shown and described in WO 2014/152757 which is hereby incorporated by reference in its entirety. The camera head **16** may include a trichroic prism or other filters.

The reference numeral **229** (FIG. **10**) generally designates another embodiment of the present invention, being a second embodiment of an LED and filter section of a light source. Since the LED and filter section **229** is similar to the previously-described LED and filter section **129**, similar parts and light pathways appearing in FIGS. **1-9** are represented by the same corresponding reference number, except for adding 100 to the previous part numeral of those in FIGS. **1-9**.

The LED and filter section **229** includes not only the four LEDs described above for the LED and filter section **129**, but also includes an infrared laser diode **243**. In front of the laser diode **243** is an optical component **243'**. Infrared light emitted from the laser diode **243** travels along light pathway **288** through the optical component **243'** and to a dichroic filter **250** which reflects infrared light, and passes blue, green, and red light emitted from LEDs **232**, **234**, and **236**. The infrared and/or blue, green, and red light from the dichroic filter **250** travels along light pathway **284** to and through a lens **269**, and then along light pathway **290** to another dichroic filter **251**. The dichroic filter **251** passes infrared light, as well as blue, green, and red visible light, while reflecting light in the ultraviolet spectrum. Thus, light emitted from the LED **230** in the ultraviolet spectrum travels along light pathway **286**, through an optical component **230'** (and optionally a movable filter **241'**) and is reflected by the dichroic filter **251**. Any light from the LEDs **230**, **232**, **234**, **236** and/or light from the laser diode **243** then travels along an exit light pathway **292** to the light output and to and through the optical lens output system **22**. The LED and filter portion **229** includes two movable filters **241**, **245**, which may be moved into or out of the light paths **286**, **272**, respectively, in similar fashion to that described above with respect to the LED and filter section **129**. The laser diode **243** is preferably an infrared diode (denoted by the letters IR) which emits light having a wavelength in the range of about 805 nm to about 810 nm, and more preferably having a wavelength of about 808 nm.

Accordingly, the LED and filter section **229** may function in at least six modes, those being the five modes discussed above, as well as an infrared mode for light emission in a wavelength range of about 805 nm to about 810 nm. This mode is especially useful for using ICG markers which reflect a fluorescence. An additional mode may use the IR light for defogging as described in U.S. Pat. Pub. No. 2014/0200406.

An infrared sensor may be positioned adjacent the first dichroic filter **250**, at a location opposite the laser diode **243**. The infrared sensor detects the presence of infrared light, and when the presence of infrared light is detected, it provides a signal to a laser diode intensity control circuit. The laser diode intensity control circuit is connected to the laser diode driver and controls the intensity of the light emitted from the laser diode **243**.

The reference numeral **329** (FIG. **11**) generally designates another embodiment of the present invention, being a third embodiment of an LED and filter section of a light source. Since the LED and filter section **329** is similar to the previously-described LED and filter section **229**, similar parts and light pathways appearing in FIG. **10** are represented by the same corresponding reference number, except for adding 100 to the previous part numeral of those in FIG. **10**.

The LED and filter section **329** includes a blue LED **332**, a green LED **334**, a red LED **336**, and optionally a UV LED **330**. The LED and filter section **329** also includes an infrared laser configuration **343**. Due to space constraints in some light source systems, and the desire to have a heat sink available for each LED/laser, the laser configuration **343** includes two infrared laser diodes as shown in FIGS. **12-13**.

FIG. **12** depicts the infrared laser configuration **343**, that includes a first infrared laser diode **400**, which preferably emits an 808-nm infrared laser, and a second infrared laser diode **402**, which preferably emits a 780-nm infrared laser. Each of the laser diodes **400**, **402** are connected to a heat sink **404**. The heat sink **404** is capable of absorbing the heat

11

from each of the laser diodes **400**, **402**, especially since the laser diodes **400**, **402** are typically used separately from one another.

As shown in FIG. **13A**, the laser configuration **343** may include more than two laser diodes. The laser configuration **343** depicted in FIG. **13B** has four laser diodes **400**, **401**, **402**, **403**, while only using one light source slot/heat sink.

In FIGS. **12**, **13A**, and **13B** the laser diodes **400**, **401**, **402**, **403** are shown to be one above the other vertically, however other configurations are contemplated. Preferably though, an optical prism **406** is placed between/among the laser diodes **400**, **402** and is capable of receiving an emission from each of the laser diodes, such as laser diodes **400**, **402**, as shown in FIG. **13B**. A laser emission is received by the optical prism **406** from the laser diode **400** via light path **408** and receives a laser emission from laser diode **402** via light path **410**. The optical prism **406** is capable of redirecting the emissions from laser diodes **400**, **402** along light path **388** toward and through an optical component **343'** and to a dichroic filter **350**. The emissions from the laser diodes **400**, **402** are directed out of the optical prism **406** along concentric optical pathways **388a** and **388b**, respectively.

Another embodiment is depicted in FIG. **14**. This embodiment is one that typically would have a small size where space limitations are at a premium. The light source **500** includes four different light emission components. Those light source components are a white light LED **502**, a UV LED **504**, an infrared 808 nm laser diode **506**, and an infrared 780 nm laser diode **508**. The infrared 808 nm laser diode **506** and the infrared 780 nm laser diode **508** preferably both use the same "slot" and thus the same heat sink as depicted in FIGS. **12-13**.

The white light LED **502** is preferably a powerful LED and can be used during normal endoscopic illumination. The white light emitted from the LED **502** could be filtered and separated into individual color components and used for other imaging modalities. The light emitted from the LED **502** travels along a light path **510** to and through an optical component **512** and to a dichroic filter **514** which allows visible light to pass therethrough.

The LED **504** emits ultraviolet light along a light pathway **516** to and through an optical component **518** and to the dichroic filter **514**. The dichroic filter **514** reflects the ultraviolet light from the LED **504** and thus both visible light and ultraviolet light move along light path **520** to a second dichroic filter **522** which allows both visible light and ultraviolet light to pass therethrough.

Infrared light from either laser diode **506** or laser diode **508** is emitted from the slot **509** along a light path **524** to and through an optical component **526** and to the second dichroic filter **522**. The second dichroic filter **522** reflects infrared light. Light reflected by or passing through the dichroic filter **522** moves along a light path **528**.

The light along light path **528** is directed to a filter mechanism **530**, such as a filter wheel, which can change optical filters, depending on the mode desired. It is contemplated that other types of filters could also be used with the light engine **500**.

The light engine **500** is capable of multiple imaging modalities, while having a smaller overall footprint size than a typical light engine because it requires fewer heat sinks and slots. The light engine **500** is capable of at least the following imaging modalities: white light, ICG, on target drug (780 nm), UV fluorescent, limited band imaging, fluorescein, and a backlight for laser modes.

FIGS. **15-17** depict a first embodiment of a modular light engine system for a light source **614**. The light source **614**

12

has a port or opening **614a** which is shaped and sized to receive a modular light engine **614b**. The light source **614** therefore may use interchangeable light engines, such as light engine **614b**, which is essentially an LED and filter section similar to that of the LED and filter sections **129**, **229**, **329**, **500** discussed above. Accordingly, the user may select a particular modular light engine for the particular surgical procedure to be performed. Therefore, the modular light engine **614b** may include a variety of different filters and lights. An example of such a modular light engine is shown in FIG. **17**, which has components similar to the second embodiment of the LED and filter section **229**, discussed above. Specifically, the modular light engine **614b** depicted in FIG. **17** include LEDs **630**, **632**, **634**, and **636**, with corresponding optical components **630'**, **632'**, **634'**, and **636'**. In addition, included is an infrared laser diode **643** with corresponding optical component **643'**. Four dichroic filters **650**, **651**, **652**, and **654** are included for proper reflection and/or passing of light for a particular mode, and lenses **666**, **668**, **669** are included for focusing of light.

Another embodiment of a light source **714** with a modular light engine **714b** is depicted in FIGS. **18-20**. The light source **714** includes an opening or port **714a** which is shaped and sized to receive the modular light engine **714b**.

The modular light engine **714b** is different from that of **614b** in that the modular light engine **714b** does not include LED lights, but uses light from LEDs or other light sources in the light source **714** for light in the visible spectrum and/or infrared spectrum.

As depicted in FIGS. **19-20**, the modular light engine **714b** includes a housing **1100**, a light input **1102**, and a light output **1104**. Inside the housing **1100** are a battery pack **1106**, which may be of the rechargeable type, a UV LED chip board **1108** which is capable of providing UV light via an LED, and a microcontroller **1110** for controlling the UV LED chip board **1108**. Also included within the housing **1100** are a color filter wheel **1112**, a motor **1114** for turning the color filter wheel **1112** when desired, and a variety of optical prism blocks **1116** for providing light paths for the various light inputted into and generated by the modular light engine **714b**.

FIG. **20** shows the various light paths for the light which may be emitted by the modular light engine **714b**. Specifically, as shown, red, blue, and green light may be inputted via light input **1102** and follow along the light path **1117** as shown in FIG. **20**, including through one or more of the prism blocks **1116**, and to and through a portion of the filter wheel **1112**. In addition, the light path **1118** for UV light generated by the UV LED chip board **1108** is depicted in FIG. **20**. As shown, the UV light travels from the chip board **1108**, to and through a portion of the filter wheel **1112**, and to and through one or more of the prism blocks **1116** before exiting via the light output **1104**.

FIGS. **21-22** depict a light engine port **1200** which may be part of a light engine such as light source **614** and is configured to receive and connect to a light module such as light module **614b**. The port **1200** includes a floor **1202** which has two slots **1204**, **1206** therein for easy centering and alignment of a light module. The port **1200** also includes a substantially vertically oriented receiving member **1208** which has a groove **1210** therein that is sized to receive a portion of a front panel of a light module.

The port **1200** also includes multiple heat sinks **1212**, **1214**, **1216**, **1218**, **1220** which are sized and positioned to contact a thermal interface of an LED chip board on a light module. The heat sinks **1212**, **1214**, **1216**, **1218**, **1220** allow

13

thermal management of the light source, including a light module via forced air cooling, while allowing the light module to be removable.

The port **1200** also preferably includes multiple high current power supply connectors, such as banana plugs **1222**, for connection to a light module. In addition, an electrical pinout block **1224** is included to provide power and electronic communication to any sensors, motors, or other components that are part of the light module.

The groove **1210** in the receiving member **1208** is generally semicircular in shape with a circular indentation and is therefore shaped and sized to receive a circular portion of the end plate of a light module.

The reference numeral **1300** (FIGS. **23-24**) generally designates another embodiment of a light module of the present invention. Since light module **1300** is similar to previously described light module **614b**, similar parts appearing in FIGS. **17** and **23-24**, respectively, are represented by the same, corresponding number, except for the addition of 700 in the numerals of the latter. The light module **1300** includes a front panel **1370** which has a light port therein defined by a round outer lip **1372**. The outer lip **1372** is sized and shaped to fit within and be received by the groove **1210** in the receiving member **1208**. The LEDs and laser diode **1330**, **1332**, **1334**, **1336**, and **1343** each have preferably two power receiving ports **1374** configured to receive and engage with banana plug connectors such as the banana plug connectors **1222** of the port **1200**. In addition, each of the LEDs and the laser diode has a thermal interface for conveying heat to a heat sink for that particular LED or laser diode. The LED **1330** has a thermal interface **1376** which is sized and configured to engage with the heat sink **1212** of the base **1200**, the LED **1343** includes a thermal interface **1378** which is sized and configured to engage with the heat sink **1214**, the LED **1332** has a thermal interface **1380** which is sized and configured to engage with the heat sink **1216**, the LED **1334** has a thermal interface **1382** which is sized and configured to engage with the heat sink **1218**, and the LED **1336** has a thermal interface **1384** which is sized and configured to engage with the heat sink **1220**. The thermal interface **1384** is at an angle "A" with respect to the longitudinal axis of the LED **1336**, as shown in FIG. **23**. Angling of the thermal interface **1384**, as well as the face of its respective heat sink **1220** creates an increased compression between the two to maintain heat transfer away from the LED light source. Angle A is preferably between about 20° and about 30°, and more preferably is about 25°. A wedge **1386** is placed between the thermal interface **1384** and the LED **1336** and is preferably of a material that is a good heat conductor, such as copper.

The light module **1300** also includes a pinout block (female) receiver **1388** for receiving electrical power from the port **1200**, which may be used for a variety of purposes, including movement of one or more filters during the operation of the light source.

As depicted in FIG. **24**, the light module **1300** preferably has a base **1387** with two feet **1388**, **1390** depending therefrom. The feet **1388**, **1390** are spaced apart from each other and are sized and shaped to fit within grooves **1204** and **1206**, respectively.

FIG. **25** depicts the beginning of engagement between the light module **1300** and the port **1200**. The straight arrows in FIG. **25** show the direction of movement of the light module **1300**, once feet **1388**, **1390** are aligned with and guided into the grooves **1204**, **1206**, respectively, for the light module **1300** to be fully connected and engaged with the port **1200**.

14

The light source, including the port **1200**, the light module **1300**, or preferably a combination of the two, may include a motorized magnetically driven optical filter, which is shown in FIGS. **24** and **26**. The magnetically driven optical filter device **1400** includes a movable driven filter **1402** which includes a filter arm **1404**. The filter arm **1404** is attached at its distal end to a front panel **1406** and a magnet **1408**.

The front panel **1406** includes a frame **1410** and an inner member **1412** attached to the frame **1410**. The inner member **1412** has an aperture **1414** therein which may or may not include a lens.

On the side of the front panel **1406** opposite the filter **1402** is a motor **1416**. The motor **1416** may receive electrical power from the pin **1224** of the base **1200** via the pin receiving **1388**. The motor **1416** drives a lever arm **1418** which is attached to a magnet **1420**.

In operation, the motor **1416** may be used to move the lever arm **1418** in a counterclockwise or clockwise direction, thereby moving the magnet **1420** with it. Due to magnetic forces, the magnet **1408** is moved along with magnet **1420**, which in turn moves the filter arm **1404** and the filter **1402** in a clockwise or counterclockwise direction to move the filter **1402** into or out of the light path of the light exiting the light module **1300**.

The above-described light sources and light source engines provide a flexible system by which various modes of light output can be achieved for a variety of different medical procedures. The modularity of the modular light engines gives the potential of using a variety of different modular pieces without having to purchase a whole new light source system, while providing increased capability as well as the potential for future modular components which may be used with existing light sources.

Although particular preferred embodiments of the invention have been disclosed in detail for illustrative purposes, it will be recognized that variations or modifications of the disclosed apparatus, including the rearrangement of parts, lie within the scope of the present invention.

What is claimed is:

1. A multi-mode medical light source comprising:

- (a) a first LED to provide light of a first light wavelength spectrum along a first light path;
- (b) a second LED to provide light of a second light wavelength spectrum along a second light path;
- (c) a dichroic filter for passing light emitted from at least one of the first LED and the second LED and reflecting light emitted from at least one of the first LED and the second LED;
- (d) an optical filter movable between a first position in which the optical filter receives light from the first light path and a second position of which the optical filter does not receive light from the first light path;
- (e) a light output;
- (f) a controller which is capable of switching the light source between a first mode and a second mode, the first mode for providing a first imaging light to the light output and the second mode for providing a second imaging light to the light output.

2. The medical light source of claim 1, wherein the light source comprises a third LED to provide light in a third wavelength spectrum.

3. The medical light source of claim 2, wherein the light source comprises a fourth LED to provide light in a fourth wavelength spectrum.

4. The medical light source of claim 1, wherein the optical filter is a first optical filter and the light source further

15

comprises a second optical filter movable between a third position and a fourth position.

5 **5.** The medical light source of claim **4**, wherein the controller is capable of switching the light source to a third mode for providing a third imaging light to the light output.

6. The medical light source of claim **4**, wherein the first optical filter isolates and emits light having a wavelength of approximately 415 nm, and the second optical filter isolates and emits light having a wavelength of approximately 540 nm.

10 **7.** The medical light source of claim **1**, wherein when the optical filter is in the first position, the optical filter is at a location of the light path and when the optical filter is in the second position, the first light path is unfiltered at the location.

15 **8.** The medical light source of claim **1**, wherein the optical filter is movable between the first position and the second position via at least one motor.

9. The medical light source of claim **1**, wherein the optical filter isolates and emits light having a wavelength of approximately 415 nm.

20 **10.** The medical light source of claim **1**, wherein the optical filter isolates and emits light having a wavelength of approximately 540 nm.

11. The medical light source of claim **1**, wherein the light source is configured for providing light to an endoscopic camera.

25 **12.** The medical light source of claim **1**, wherein when the optical filter is in the second position, the first light path is unobstructed.

16

13. A medical imaging system comprising:
an endoscopic imager; and

a multi-mode medical light source for providing light to the endoscopic imager, the light source comprising:

(a) a first LED to provide light of a first light wavelength spectrum along a first light path;

(b) a second LED to provide light of a second light wavelength spectrum along a second light path;

(c) a dichroic filter for passing light emitted from at least one of the first LED and the second LED and reflecting light emitted from at least one of the first LED and the second LED;

(d) an optical filter movable between a first position in which the optical filter receives light from the first light path and a second position of which the optical filter does not receive light from the first light path;

(e) a light output; and

(f) a controller which is capable of switching the light source between a first mode and a second mode, the first mode for providing a first imaging light to the light output and the second mode for providing a second imaging light to the light output.

14. The system of claim **13**, further comprising a camera control unit coupled to the endoscopic imager.

15. The system of claim **14**, wherein the camera control unit is communicatively connected to the light source.

* * * * *