

US011670977B2

(12) **United States Patent**
Fogle et al.

(10) **Patent No.:** **US 11,670,977 B2**
(45) **Date of Patent:** **Jun. 6, 2023**

(54) **OUTER ROTOR BRUSHLESS MOTOR STATOR MOUNT**

(52) **U.S. Cl.**
CPC **H02K 1/2786** (2013.01); **B25F 5/02** (2013.01); **H02K 1/28** (2013.01); **H02K 3/522** (2013.01);

(71) Applicant: **Black & Decker Inc.**, New Britain, CT (US)

(Continued)

(72) Inventors: **John B. Fogle**, White Hall, MD (US); **Dustin Jeffries**, Baltimore, MD (US); **Michael R. Marjomaa**, Mount Wolfe, PA (US); **Kevin L. Pulley**, White Marsh, MD (US); **Vincent W. Zou**, Lutherville-Timonium, MD (US); **Jarrett A. Dunston**, Bel Air, MD (US); **David J. Smith**, Columbia, MD (US); **Rene Thieme**, Riesa (DE); **Tim Heimrich**, Bad Camberg (DE); **Tobias Heep**, Hadamar-Steinbach (DE); **Daniel Bernhart**, Bad Camberg (DE); **Dieter Schmidfrerick**, Idstein (DE)

(58) **Field of Classification Search**
CPC H02K 5/207; H02K 5/00; H02K 5/04; H02K 29/08

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,592,566 A 7/1971 Beardslee
4,890,049 A 12/1989 Auinger
(Continued)

FOREIGN PATENT DOCUMENTS

CN 2640110 Y 9/2004
DE 19954962 B4 11/2004
(Continued)

(73) Assignee: **Black & Decker Inc.**, New Britain, CT (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 158 days.

OTHER PUBLICATIONS

EPEESR , dated Jul. 16, 2020 in corresponding EP Application 20171177.7.

(Continued)

(21) Appl. No.: **16/856,762**

(22) Filed: **Apr. 23, 2020**

Primary Examiner — Jose A Gonzalez Quinones
(74) *Attorney, Agent, or Firm* — Amir R. Rohani

(65) **Prior Publication Data**

US 2020/0343780 A1 Oct. 29, 2020

(57) **ABSTRACT**


A brushless direct-current motor is provided includes an inner stator and an outer rotor. A rotor shaft extends through a stator core of the inner stator. A first end cap includes a radial back plate disposed on a first side of the stator and a front center opening through which the rotor shaft is supported via a front bearing. A second end cap includes an inner annular body extending axially inwardly and forming a rear center opening, an outer annular body, and a main body extending on a second side of the stator. The inner annular body includes a first portion that extends at least

(Continued)

Related U.S. Application Data

(60) Provisional application No. 62/837,935, filed on Apr. 24, 2019, provisional application No. 62/881,105, filed on Jul. 31, 2019.

(51) **Int. Cl.**
H02K 5/16 (2006.01)
H02K 5/15 (2006.01)
(Continued)



partially into an opening of the stator core and supports the rotor shaft via a rear bearing, and a second portion rearward of the first portion that received a rear end of the rotor shaft therein and houses a sensor board therein.

15 Claims, 24 Drawing Sheets

(51) Int. Cl.

- H02K 1/2786* (2022.01)
- H02K 11/33* (2016.01)
- B25F 5/02* (2006.01)
- H02K 7/14* (2006.01)
- H02K 29/08* (2006.01)
- H02K 1/28* (2006.01)
- H02K 3/52* (2006.01)
- H02K 9/06* (2006.01)
- H02K 15/03* (2006.01)
- H02K 21/22* (2006.01)

(52) U.S. Cl.

- CPC *H02K 5/15* (2013.01); *H02K 5/16* (2013.01); *H02K 5/161* (2013.01); *H02K 7/14* (2013.01); *H02K 7/145* (2013.01); *H02K 9/06* (2013.01); *H02K 11/33* (2016.01); *H02K 15/03* (2013.01); *H02K 21/22* (2013.01); *H02K 29/08* (2013.01)

(58) Field of Classification Search

USPC 310/47, 50, 60 B, 89
See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

5,229,674 A	7/1993	Best
5,497,040 A	3/1996	Sato
5,536,986 A	7/1996	Fukuyama et al.
5,698,915 A	12/1997	Fukuyama et al.
5,714,819 A	2/1998	Gilliland et al.
5,734,214 A	3/1998	Gilliland et al.
5,915,643 A	6/1999	Dolgas
5,931,403 A	8/1999	Rieff
6,023,113 A	2/2000	Otsuka
6,037,688 A	3/2000	Gilliland et al.
6,169,383 B1	1/2001	Johnson
6,309,180 B1	10/2001	Gilliland et al.
6,555,943 B2	4/2003	Walther et al.
6,617,747 B1	9/2003	Petersen
6,707,224 B1	3/2004	Petersen
6,768,243 B1	7/2004	Yamazaki et al.
6,798,094 B2	9/2004	Hirsou et al.
6,891,456 B2	5/2005	Byram
7,034,417 B1	4/2006	Liu
7,064,462 B2	6/2006	Hempe et al.
7,064,464 B2	6/2006	Ickinger
7,076,830 B2	7/2006	Conner et al.
7,109,615 B2	9/2006	Doemen et al.
7,122,923 B2	10/2006	Lafontaine et al.
7,342,333 B2	3/2008	Umezu
7,350,283 B2	4/2008	Won et al.
7,557,478 B2	7/2009	Hoshika
7,588,444 B2	9/2009	Kataoka et al.
7,602,137 B2	10/2009	Du et al.
7,736,062 B2	6/2010	Hagshenas et al.
7,746,372 B2	6/2010	Yoo
7,768,166 B2	8/2010	Lafontaine et al.
7,812,488 B2	10/2010	Cosco et al.
7,872,383 B2	1/2011	Dubuc et al.
7,893,579 B2	2/2011	Rudel et al.
7,915,772 B2	3/2011	Wong
7,923,879 B2	4/2011	Nitta

7,944,074 B2	5/2011	Longtin et al.
8,011,442 B2	9/2011	Lennartz
8,018,108 B2	9/2011	Lafontaine et al.
8,132,702 B2	3/2012	Kunz et al.
8,193,748 B2	6/2012	Deller et al.
8,207,642 B2	6/2012	Lafontaine et al.
8,278,803 B2	10/2012	Lin et al.
8,283,831 B1	10/2012	Kaminsky et al.
8,283,841 B2	10/2012	Lin et al.
8,354,766 B2	1/2013	Maekawa
8,424,625 B2	4/2013	Ishii
8,471,419 B2	6/2013	Shimomura et al.
8,546,986 B2	10/2013	Marchitto et al.
8,550,323 B2	10/2013	Fujimoto
8,552,675 B2	10/2013	Asahi et al.
8,659,251 B2	2/2014	Amagasa
8,786,151 B1	7/2014	Cole et al.
8,866,353 B2	10/2014	Miyama et al.
8,916,997 B2	12/2014	Kirkley, Jr. et al.
8,963,384 B2	2/2015	Kirkley, Jr. et al.
9,093,882 B2	7/2015	Mayer et al.
9,143,021 B2	9/2015	Haruno et al.
9,375,531 B1	6/2016	Lee et al.
9,393,483 B2	7/2016	Tan et al.
9,577,497 B2	2/2017	Taniguchi
9,583,994 B2	2/2017	Jang
9,627,936 B2	4/2017	Nakano et al.
9,627,944 B2	4/2017	Nakano et al.
9,675,219 B1	6/2017	Chaffin
9,685,840 B2	6/2017	Germann et al.
9,724,814 B2	8/2017	Yoshikane et al.
9,731,410 B2	8/2017	Hirabayashi et al.
9,742,234 B2	8/2017	Hashimoto et al.
9,762,102 B2	9/2017	Kanda et al.
9,800,116 B2	10/2017	Iwai et al.
9,812,931 B2	11/2017	Lankin et al.
9,819,240 B2	11/2017	Hashimoto et al.
9,885,370 B2	2/2018	Fang et al.
9,917,486 B2	3/2018	Kirkley, Jr. et al.
9,929,620 B2	3/2018	Nakamura et al.
10,014,746 B2	7/2018	Kanda et al.
10,075,037 B2	9/2018	Ichikawa et al.
10,193,416 B2	1/2019	Germann et al.
10,263,481 B2	4/2019	Roberts
2002/0101122 A1	8/2002	Haines et al.
2006/0076842 A1	4/2006	Park
2006/0119204 A1	6/2006	Awazu et al.
2006/0237234 A1	10/2006	Dennis et al.
2007/0035192 A1	2/2007	Jeon et al.
2008/0042503 A1	2/2008	Hartkorn et al.
2009/0133894 A1	5/2009	Mizuhara
2010/0038985 A1	2/2010	Shim et al.
2011/0056716 A1	3/2011	Jönsson et al.
2011/0241457 A1	10/2011	Müller et al.
2012/0031215 A1	2/2012	Feier
2012/0066916 A1	3/2012	Heinzelmann et al.
2012/0076672 A1	3/2012	Binder
2012/0262021 A1	10/2012	Lafontaine et al.
2012/0313464 A1	12/2012	Fukuoka et al.
2013/0009494 A1	1/2013	Oguma
2013/0076176 A1	3/2013	Edrington et al.
2013/0284475 A1	10/2013	Hirabayashi et al.
2014/0008092 A1	1/2014	Yanagihara
2014/0076953 A1	3/2014	Ekstrom et al.
2014/0175915 A1	6/2014	Park
2014/0288750 A1	9/2014	Lankin et al.
2015/0014007 A1	1/2015	Ukai et al.
2015/0333600 A1*	11/2015	Nakano H02K 11/33 310/68 B
2016/0079822 A1	3/2016	Noguchi
2016/0181891 A1	6/2016	Fogle et al.
2016/0268876 A1	9/2016	Goto
2016/0301276 A1	10/2016	Saki et al.
2016/0352190 A1	12/2016	Hieda et al.
2017/0033720 A1	2/2017	Zeyn et al.
2017/0106522 A1	4/2017	Coates et al.
2017/0110925 A1	4/2017	Fu et al.
2017/0110935 A1	4/2017	Oktavec et al.
2017/0113319 A1	4/2017	Boeck et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2017/0194847 A1 7/2017 Nuzzo et al.
 2017/0201150 A1 7/2017 Haga et al.
 2017/0238773 A1 8/2017 Chaffin
 2017/0310193 A1 10/2017 Ryu
 2018/0013329 A1 1/2018 Aoyama
 2018/0013334 A1 1/2018 Ishikura et al.
 2018/0031628 A1 2/2018 Ahrens et al.
 2018/0109164 A1 4/2018 Holman
 2018/0123416 A1 5/2018 Yamasaki et al.
 2018/0198351 A1 7/2018 Akutsu et al.
 2018/0241268 A1 8/2018 Asahi et al.
 2018/0245597 A1 8/2018 Takarai et al.
 2018/0278113 A1 9/2018 Asahi et al.
 2018/0316238 A1 11/2018 Kong
 2019/0028003 A1 1/2019 Seith et al.
 2019/0193255 A1 6/2019 Valentini
 2019/0252945 A1 8/2019 Kviberg et al.

FOREIGN PATENT DOCUMENTS

DE 10393564 T5 10/2005
 DE 102004049630 A1 4/2006
 DE 202007004491 U1 8/2007
 DE 102007000468 A1 3/2008
 DE 102008059884 A1 2/2010
 DE 102009026202 A1 6/2010
 DE 102009001808 A1 9/2010
 DE 102009022815 B3 11/2010
 DE 202010015072 U1 4/2011
 DE 102011008385 A1 9/2011
 DE 112010001944 T5 9/2012
 DE 202012103438 U1 11/2012
 DE 102011105345 A1 12/2012
 DE 102012107793 A1 2/2013
 DE 112011102148 T5 5/2013
 DE 112011102756 T5 9/2013
 DE 112012004272 T5 7/2014
 DE 102013218829 A1 3/2015
 DE 202014100199 U1 5/2015
 DE 202015100353 * 5/2015
 DE 102015200093 A1 7/2016
 DE 102015200095 A1 7/2016
 DE 202016103204 U1 1/2017
 DE 102017210019 A1 12/2017
 DE 102017213675 A1 2/2018
 DE 102017003865 A1 10/2018
 DE 102017223519 B3 10/2018
 EP 270935 A2 6/1988
 EP 1542340 A2 6/2005
 EP 1481458 B1 7/2005

EP 1298772 B1 1/2006
 EP 1173917 B1 5/2006
 EP 1255928 B1 10/2006
 EP 1622241 B1 2/2007
 EP 1797234 A1 6/2007
 EP 1564869 B1 1/2008
 EP 1580311 B1 7/2008
 EP 1045504 B1 12/2008
 EP 1923173 B1 5/2009
 EP 1515414 B1 1/2011
 EP 1897209 B1 8/2011
 EP 2597189 A1 5/2013
 EP 2606556 A1 6/2013
 EP 2860857 A2 4/2015
 EP 1816729 B1 10/2015
 EP 2936659 A1 10/2015
 EP 2946887 B1 8/2017
 EP 3211760 A1 8/2017
 EP 3007330 B1 9/2017
 EP 3322071 A1 5/2018
 EP 3208917 B1 3/2019
 GB 1432322 A 4/1976
 JP H0252527 U 4/1990
 JP 3738966 B * 1/2006
 JP 2007252097 A * 9/2007
 JP 2007252097 A 9/2007
 JP 20102145987 A * 9/2010
 JP 202121474 A * 1/2012
 JP 2016111738 A * 6/2016
 JP 2016111738 A 6/2016
 WO 14038805 A1 3/2014
 WO 14084553 A1 6/2014
 WO 14098625 A1 6/2014
 WO WO-2014117881 A1 * 8/2014 H02K 1/2786
 WO 14184518 A2 11/2014
 WO 15073658 A1 5/2015
 WO 16004042 A1 1/2016
 WO 18066109 A1 4/2018
 WO 18074944 A1 4/2018
 WO WO-2018150448 A1 * 8/2018 H02K 15/0068
 WO 18166144 A1 9/2018
 WO 18193095 A1 10/2018
 WO 18196003 A1 11/2018
 WO 19084568 A1 5/2019

OTHER PUBLICATIONS

EPEESR, dated Jul. 20, 2020 in EP Application 20171178.5.
 EP Communication Article 94(3), dated Aug. 5, 2021 in EP Application 20171177.7.
 EP Communication Article 94(3), dated Aug. 13, 2021 in corresponding EP Application 20171178.5.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 4B




FIG. 5




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D




FIG. 6E




FIG. 6F




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 8A




FIG. 8B




FIG. 8C



FIG. 8D




FIG. 9A




FIG. 9B




FIG. 10A




FIG. 10B




FIG. 11A




FIG. 11B




FIG. 12A




FIG. 12B




FIG. 13A




FIG. 13B




FIG. 14A




FIG. 14B




FIG. 15




FIG. 16




FIG. 17




FIG. 18

1

OUTER ROTOR BRUSHLESS MOTOR STATOR MOUNT

RELATED APPLICATION

This application claims the benefit of U.S. Provisional Application No. 62/837,935 filed Apr. 24, 2019 and U.S. Provisional Application No. 62/881,105 filed Jul. 31, 2019, both of which are incorporated herein by reference in their entireties.

FIELD

This disclosure relates to an outer-rotor brushless motor, and more particularly to a high-power outer-rotor brushless motor for use in power tools and outdoor products.

BACKGROUND

Conventional brushless direct-current (BLDC) motors are provided with a permanent magnet rotor supported within a stator. The stator includes a ring-shaped stator core, a series of stator teeth that extend radially inwardly from the stator core, and a series of stator windings wound in various patterns on the stator teeth. The rotor includes a rotor core that supports a number of magnets and is mounted on a rotor shaft. The shaft is supported relative to the stator via one or more bearings.

Another type of BLDC motor, referred to as an outer-rotor or external rotor motor, is provided with the rotor on the outside of the stator. In an outer-rotor motor, the rotor magnets are provided on an outer cup that is rotatable around a stator core. The outer cup includes a plate on one side of the stator that is secured to a rotor shaft. US Patent Publication No. 2019/0058373, which is incorporated herein by reference in its entirety, provides an example of an outer-rotor motor in a nailer, where the outer rotor includes an integrated flywheel for driving a driver of the nailer. Outer-rotor motors provides some performance advantages over comparable inner-rotor motors. Namely, since an outer rotor is by necessity larger than an inner rotor, it creates higher inertia and reduces the torque ripple effect and lower vibration. An outer rotor also provides higher magnetic flux and is also capable of producing more torque than a comparable inner rotor motor.

Use of electric motors in battery-operated cordless outdoor products such as lawn mowers has gained popularity in recent years. Electric motors, particularly brushless motors as described above, are capable of producing high amount of output power at a high degree of efficiency suitable for such applications. Despite its advantages, use of electric brushless motor in such products presents challenges relating to placement and assembly of the motor in a compact and efficient manner. Moreover, as outdoor products are used in environments with high amount of debris, dust, and grass particulate, protection of the motor against entry of debris and contamination is of great importance.

An impact tool such as a demolition tool or a hammer typically includes a tool holder in which a cutting tool can be supported and driven by an impact mechanism. The impact tool typically includes an electric motor that converts electrical energy to a rotary motion and an impact mechanism by which the rotary output of the electric motor is converter to a linear motion. The impact mechanism repetitively strikes the end of a cutting tool to impart axial impacts onto the cutting tool. The U.S. Pat. No. 10,328,558, which is incorporated herein by reference in its entirety, describes

2

an example of such a hammer drill that can operate in a hammer mode to perform this operation. In an impact tool, the motor is typically housed within a motor housing below the transmission mechanism in a direction perpendicular to the longitudinal axis of the transmission mechanism. A handle is typically attached at one end to the end of the motor housing and at the other end to the transmission housing. A battery receptacle may be located below the handle adjacent the motor housing.

Once again, while outer-rotor brushless electric motors are capable of producing high amount of output power at a high degree of efficiency suitable for impact power tools, placement of the motor in a compact and efficient manner and without significantly increasing the overall length and/or diameter of the tool housing presents challenges.

SUMMARY

According to an aspect of this disclosure, a brushless direct-current (BLDC) motor is provided. The motor includes a stator having a stator core, teeth extending radially outwardly from the stator core, and windings wound around the stator teeth; a rotor shaft extending along a center axis; and a rotor having a rotor core disposed around the stator. The rotor includes permanent magnets secured to the rotor core, an inner annular member mounted on the rotor shaft, and a plurality of radial blades extending angularly from the rotor core to the inner annular member forming a fan adjacent the stator that generates an airflow with rotation of the rotor shaft. A first end cap is provided including a radial back plate proximate the fan and a center opening in the radial back plate through which the rotor shaft extends. A second end cap is provided including a main body disposed adjacent the stator opposite the fan. The radial back plate of the first end cap includes at least one sloped surface forming at least one air gap such that the airflow generated by the fan is centrifugally guided within the first end cap by the sloped surface and caused to exit the first end cap through the air gap.

In an embodiment, first end cap further includes an annular body formed at least partially around the fan and the radial back plate extends from the annular body. In an embodiment, the annular body includes at least one exhaust port in fluid communication with the at least one air gap and through which the airflow is expelled from the first end cap in a substantially radial direction.

In an embodiment, two sloped surfaces are provided on two sides of the center opening of the first end cap, and two air gaps are formed between respective ends of the two sloped surfaces. The two air gaps extend from the annular body of the first end cap towards the center opening to intersect a centrifugal path of the airflow within the first end cap.

In an embodiment, the first end cap includes a side plate projecting outwardly around the annular body and a lower surface arranged to be mounted on a housing of a tool.

In an embodiment, the center opening of the end cap supports a front bearing of the rotor shaft.

In an embodiment, the second end cap includes an annular body extending from the main body around at least a portion of the rotor core, the annular body of the second end cap coming into contact and being secured to the first end cap.

In an embodiment, the second end cap includes a first set of openings for passage of airflow and a second set of openings for passage of a set of motor terminals arranged to electrically couple to the stator windings of the stator.

In an embodiment, a stator collar is mounted on the stator core and the terminals are mounted on the stator collar in a direction parallel to the rotor shaft.

In an embodiment, the second end cap includes a center opening within which a sensor board is secured. The sensor board accommodates positional sensors facing the rotor shaft. A sense magnet is mounted on the rotor shaft facing the positional sensors.

According to another aspect of this disclosure, a brushless direct-current (BLDC) motor is provided including: a stator having a stator core, teeth extending radially outwardly from the stator core, and windings wound around the stator teeth; a rotor shaft extending along a center axis; and a rotor having a rotor core disposed around the stator, permanent magnets secured to the rotor core, and an inner annular member mounted on the rotor shaft. A first end cap is provided including a radial back plate disposed on a first side of the stator and having a front center opening through which the rotor shaft is supported via a front bearing. A second end cap is provided having an inner annular body, an outer annular body, and a main body extending on a second side of the stator from the inner annular body to the outer annular body. The inner annular body extends axially inwardly and forms a rear center opening. The inner annular body includes a first portion that extends at least partially into an opening of the stator core and supports the rotor shaft via a rear bearing, and a second portion rearward of the first portion that received a rear end of the rotor shaft therein and houses a sensor board therein, where the sensor board accommodates positional sensors facing the end of the rotor shaft.

In an embodiment, the rotor includes radial blades extending angularly from the rotor core to the inner annular member forming a fan adjacent the stator that generates an airflow with rotation of the rotor shaft.

In an embodiment, the radial back plate of the first end cap includes at least one sloped surface forming at least one air gap. The airflow generated by the fan is centrifugally guided within the first end cap by the at least one sloped surface and caused to exit the first end cap through the at least one air gap. The first end cap includes an annular outer body having at least one exhaust port in fluid communication with the at least one air gap and through which the airflow is expelled from the first end cap in a substantially radial direction.

In an embodiment, the annular body of the second end cap extends from the main body around at least a portion of the rotor core and comes into contact with the first end cap to secure the second end cap to the first end cap around the rotor.

In an embodiment, the second end cap includes a first set of openings for passage of airflow and a second set of openings for passage of a set of motor terminals arranged to electrically couple to the windings of the stator.

In an embodiment, a stator collar is mounted on the stator core and the terminals are mounted on the stator collar in a direction parallel to the rotor shaft.

In an embodiment, the first portion of the inner annular body has a larger diameter at the first portion than at the second portion.

In an embodiment, a sense magnet is mounted on the rear end of the rotor shaft in close proximity to the sensor board.

In an embodiment, the inner annular body further includes a third portion disposed between the first portion and the second portion and having a diameter that is greater than that of the second portion but smaller than that of the first portion. In an embodiment, the sense magnet is located within the third portion of the inner annular body.

In an embodiment, the inner annular body further includes a radial rim formed at a rear end of the second portion and the sensor board is secured to the radial rim. In an embodiment, an impact absorbing member or a spring is disposed between the sensor board and the radial rim.

In an embodiment, the second end cap is provided with one or more deflection limiting members near meeting boundaries of the outer annular body and the main body. The deflection limiting member(s) face the rotor core to absorb an impact of the rotor core in an event of a pivoting movement of the rotor shaft away from the center axis.

According to another aspect of this disclosure a brushless direct-current (BLDC) motor is provided including a stator having a stator core, teeth extending radially outwardly from the stator core, and windings wound around the stator teeth; a rotor shaft extending along a center axis; and a rotor having a rotor core disposed around the stator, permanent magnets secured to the rotor core, and an inner annular member mounted on the rotor shaft. A first end cap including a radial back plate is disposed on a first side of the stator and having a front center opening through which the rotor shaft extends. A second end cap is provided having an inner annular body, an outer annular body, and a main body extending on a second side of the stator from the inner annular body to the outer annular body, where the second end cap includes openings for passage of motor terminals electrically coupled to the windings. A stator collar is mounted on the stator core and the terminals are mounted on the stator collar in a direction parallel to the rotor shaft.

In an embodiment, three terminals are provided equidistantly around the stator collar.

In an embodiment, each of the plurality of terminals includes a main body and two side guide portions together having a curved contour, the two side guide portions configured to be received within axial guide channels of the stator collar.

In an embodiment, each of the plurality of terminals includes two tang portions on one end proximate the stator extending angularly from the main body for connection to a respective one of the windings.

In an embodiment, the stator further includes an end insulator mounted on an end of the stator core and the teeth to electrically insulate the teeth from the stator windings.

In an embodiment, the end insulator includes an annular inner mounting platform on which the stator collar is mounted and an annular rim projecting from the mounting platform and disposed around the stator collar.

In an embodiment, the stator collar has approximately the same diameter as the stator core. In an embodiment, the stator collar is sized such that the motor terminals are disposed along a circumference that is smaller than a circumference formed by the windings.

According to an aspect of this disclosure, a lawn mower is provided including a main deck defining a lower cavity within which a cutting blade is received, wheels supporting the main deck, and a brushless direct-current (BLDC) motor mounted on the main deck for driving the cutting blade. The motor may be configured according to any of the above-described embodiments, with the rotor shaft driving the cutting blade. In an embodiment, airflow generated by the motor fan is caused to exit the motor above the main deck so as to substantially separate the motor airflow from the lawn mower cavity. In an embodiment, the lawn mower further includes a motor housing disposed above the main deck to house the motor, and a battery cage disposed above the motor housing for receiving a removeable battery pack therein.

According to another aspect of this disclosure, a power tool is provided including a housing, a battery receptacle formed on the housing for receiving a power tool battery pack, a control module disposed within the housing to control supply of power from the battery pack, and a brushless direct-current (BLDC) motor mounted within or on the housing. The motor is configured according to any of the above-described embodiments. In an embodiment, the first end cap of the motor is integrally formed with the housing.

According to yet another aspect of this disclosure, a power tool is provided including a housing; a tubular cylinder housed within the housing defining a longitudinal axis; a piston reciprocatingly disposed within the tubular cylinder; a crank mechanism disposed within the housing configured to convert a rotary motion to a reciprocating motion for driving the piston; and a tool holder mounted on the housing forward of the tubular cylinder. A battery receptacle is provided on the housing for receiving a removable power tool battery pack, the battery pack being provided on a first side of a plane intersecting the longitudinal axis when received within the battery receptacle. A brushless direct-current (BLDC) motor is mounted on the housing on a second side of the plane intersecting the longitudinal axis. The motor includes a stator having a stator core, teeth extending radially outwardly from the stator core, and windings wound around the stator teeth; a rotor shaft extending along a center axis oriented perpendicularly to the longitudinal axis; and a rotor having a rotor core disposed around the stator, permanent magnets secured to the rotor core, and an inner annular member mounted on the rotor shaft. A first end cap of the motor is mounted on the housing, the first end cap including a radial back plate disposed on a first side of the stator and having a front center opening through which the rotor shaft is supported via a front bearing. A second end cap provided outside the housing, the second end cap including a main body disposed adjacent the stator.

In an embodiment, the motor counterbalances a weight of the battery pack such that a distance between the longitudinal axis and a center of gravity of the power tool with the battery pack received within the battery receptacle is less than or equal to approximately 20% of a full height of the power tool.

In an embodiment, a handle is mounted on the housing, the handle having a first end disposed adjacent the motor and a second end forming the battery receptacle. In an embodiment, at least a portion of the second end cap intersects a longitudinal axis of the first end of the handle.

In an embodiment, the first end cap supports the rotor shaft via a front bearing and the second end cap supports the rotor shaft via a second bearing. In an embodiment, the second end cap includes an inner annular body that projects into the stator core to support the second bearing within the stator core. In an embodiment, at least a portion of the first end cap intersects a longitudinal axis of an upper wall of the tubular cylinder.

In an embodiment, the crank mechanism includes a crank wheel mounted on an end of the rotor shaft adjacent the first bearing, a pivoting pin mounted on the crank wheel offset from the rotor shaft, and a piston arm extending from the piston and coupled to the pivoting pin.

In an embodiment, the first end cap is formed integrally with the housing.

In an embodiment, the rotor includes radial blades extending angularly from the rotor core to the inner annular

member forming a fan adjacent the stator that generates an airflow with rotation of the rotor shaft.

In an embodiment, the radial back plate of the first end cap includes at least one sloped surface forming at least one air gap, wherein the airflow generated by the fan is centrifugally guided within the first end cap by the sloped surface and caused to exit the first end cap through the air gap. The first end cap includes an annular outer body having at least one exhaust port in fluid communication with the air gap and through which the airflow is expelled from the first end cap in a substantially radial direction such that the airflow is substantially prevented from entering into the housing of the power tool.

In an embodiment, the radial back plate of the first end cap includes air vents that allow the airflow generated by the fan to enter the main housing in a direction of the center axis.

Additional features and advantages of various embodiments will be set forth, in part, in the description that follows, and will, in part, be apparent from the description, or may be learned by the practice of various embodiments. The objectives and other advantages of various embodiments will be realized and attained by means of the elements and combinations particularly pointed out in the description herein.

BRIEF DESCRIPTION OF THE DRAWINGS

The drawings described herein are for illustration purposes only and are not intended to limit the scope of this disclosure in any way.

FIG. 1 depicts a perspective view of an electric mower, according to an embodiment;

FIG. 2 depicts a side view of an electric mower with a translucent main body, according to an embodiment;

FIGS. 3A and 3B depict front and rear perspective views of an outer-rotor brushless motor, according to an embodiment;

FIGS. 4A and 4B depict front and rear exploded views showing the inner components of the outer-rotor brushless motor, including rotor and stator assemblies and first and second end caps, according to an embodiment;

FIG. 5 depicts a side cross-sectional view of the outer-rotor brushless motor, according to an embodiment;

FIGS. 6A-6F depict perspective views of the outer rotor assembly components through the course of the manufacturing assembly, according to an embodiment;

FIGS. 7A and 7B depict front and rear perspective views of the second end cap, according to an embodiment;

FIG. 7C depicts a partial cross-sectional view of the motor showing a bearing pocket of the second end cap receiving a bearing and a sensor arrangement, according to an embodiment;

FIG. 8A depicts a perspective view of the second end cap including deflection limiting members, according to an embodiment;

FIG. 8B depicts a partial cross-sectional view of the motor including an impact absorbing member behind the positional sensor board within the bearing pocket, according to an embodiment;

FIG. 8C depicts a partial cross-sectional view of the motor including a spring member behind the positional sensor board within the bearing pocket, according to an embodiment;

FIG. 8D depicts a wave spring used as the spring member of FIG. 8C, according to an embodiment;

FIGS. 9A and 9B depict front and rear perspective views of the first end cap, according to an embodiment;

FIG. 10A depicts a top view of the first end cap, according to an embodiment;

FIG. 10B depicts a top horizontal cross-sectional view of the first end cap, according to an embodiment;

FIG. 11A depicts a side view of the first end cap, according to an embodiment;

FIG. 11B depicts a side vertical cross-sectional view of the first end cap, according to an embodiment;

FIG. 12A depicts a perspective view of the stator assembly including a stator core and a stator collar prior to assembly, according to an embodiment;

FIG. 12B depicts a perspective view of the stator assembly and the stator collar after assembly, according to an embodiment;

FIG. 13A depicts a perspective view of the stator assembly including stator windings and the stator collar mounted on the stator core, according to an embodiment;

FIG. 13B depict a partial zoomed-in perspective view of the stator assembly including the stator collar, according to an embodiment;

FIGS. 14A and 14B depict side and top views of the stator assembly, according to an embodiment;

FIG. 15 depicts a perspective view of a cordless electric hammer having an outer-rotor brushless motor, according to an embodiment;

FIG. 16 depicts a side cross-sectional view of the hammer;

FIG. 17 depicts a partial zoom-in cross-sectional view of the hammer; and

FIG. 18 depicts a partial exploded view of the motor 500 relative to the main housing 602.

Throughout this specification and figures like reference numbers identify like elements.

DETAILED DESCRIPTION

It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory only and are intended to provide an explanation of various embodiments of the present teachings.

FIG. 1 depicts a perspective view of an electric mower 10, according to an embodiment. FIG. 2 depicts a side view of an electric mower 10 with a translucent main body 12, according to an embodiment. As shown in FIGS. 1 and 2, the electric mower 10 includes a main body 12 having a main deck 52 and a motor housing 50. The electric mower 10 further includes one or more blades 14 rotatably supported in a cavity 16 defined below the main deck 52, a pair of front wheels 18 supported by the main body 12, a pair of rear wheels 20 supported by the main body 12, and a handle 22 extending rearwardly from the main body 12. A grass collection bag 54 is supported on a rear side of the main body 12 below the handle 22.

In an embodiment, an outer-rotor brushless DC (BLDC) motor 500 coupled to a rotor shaft 340 is mounted in the motor housing 50 of the main body 12 above the main deck 52 for rotatably driving the one or more blades 14. The motor 500 may be arranged to drive the blades 14 by a direct drive mechanism (i.e., connecting the blade 14 directly to the rotor shaft 340). Alternatively, motor 400 may drive the blades 14 via a transmission mechanism including transfer gears, a transfer belt, and/or other speed and/or torque reduction and transmission components.

The handle 22 is provided with a pair of side rods 24 extending from either side end of the rear part of the main body 12 on two sides of the grass collection bag 54, and a

cross rod 26 extending between the rear ends of the side rods 24. The cross rod 26 of the handle 22 is provided with a lever 28 for operating the BLDC motor 500.

In an embodiment, a battery cage 30 is disposed above the motor housing 50 for receiving a removable tool battery pack 32 therein. In an embodiment, the battery pack 32 may be a sliding power tool type battery pack having a 60V, 80V, 100V, or 120V maximum voltage. U.S. Pat. No. 8,573,324, which is hereby incorporated by reference in its entirety, provides an example of a sliding power tool battery pack that slidably couples to a power tool. The battery cage 30 includes an angular opening sized to receive the battery pack 32 therein at an angle of, for example, 15 to 45 degrees relative to a plane of the main deck 52. In an embodiment, the battery pack 32 is positioned so as to intersect an axis of the rotor shaft 340.

In an embodiment, a power module 40 is disposed in the main body 12 within or adjacent the motor housing 50. The power module 40 includes a series of power switches configured as a three-phase inverter circuit for regulating supply of power from the battery pack to the motor 500. In an embodiment, a controller (not shown) is also disposed within the main body, as a part of the power module 40 or separately thereof, for controlling the switching operation of the power switches. Controller controls the power switches based on the position of the lever 28 to control the average voltage supplied from the battery pack to the motor 500.

In an embodiment, the motor 500 is supported within the motor housing 50 in a way that all components of the motor 500 are positioned above the plane of the main deck 52. Additionally, motor housing 50 is provided with two oppositely arranged exhaust vents 56 disposed above the main deck 52 arranged to expel air away from the motor 500 in a direction radial to the motor shaft 340 above the main deck 52.

The motor 500 features are described here in detail.

FIGS. 3A and 3B depict front and back perspective views of the BLDC motor 500, according to an embodiment. In an embodiment, motor 500 includes a first end cap 100, also referred to herein as a deck plate or a motor plate, and a second end cap 200, also referred to herein as a motor cup or stator mount. In an embodiment, the first end cap 100 is secured to the main deck 52 of the main body 12 by any method known to one skilled in the art. Similarly, the first end cap 100 and the second end cap 200 are coupled to one another by any method known to one skilled in the art. Such known methods include, but are not limited to, fasteners, adhesive, a tongue and groove assembly, friction-fitting, press-fitting, etc.

In an embodiment, the first end cap 100 includes a center opening 126 through which the rotor shaft 340 extends outwardly and one or more radial exhaust ports 124A and 124B arranged circumferentially on opposite sides of the first end cap 100. The second end cap 200 similarly includes a center opening 210 through which one or more control signal cables (not shown) are received, and a series of openings 220 and 222 disposed at a distance around the center opening 210. In an embodiment, stator terminals 440 to the power module 40 pass through one or more of the openings 220. These features will be described later in detail.

In an embodiment, inlet openings 222 are air inlets align with one or more air inlets (not shown) of the motor housing 50 that receive incoming cooling air from the outside environment. In an embodiment, radial exhaust ports 124A and 124B align with exhaust vents 56 of the motor housing 50 to allow expulsion of hot air away from the motor 500

above the main deck **52** and in a radial direction parallel to the plane of the main deck **52**. This arrangement substantially isolates airflow for cooling the motor **500** components from the cavity **16** below the main deck **52**. This reduces ingress of contaminated air including dust and grass into the motor **500**. This also ensures that the airflow generated by the blade **14** within the cavity **16** is unimpeded by the airflow for cooling the motor **400**.

FIGS. **4A** and **4B** depict front and back exploded views showing the components of BLDC motor **500**, according to an embodiment. FIG. **5** depicts a cross-sectional view of the outer-rotor brushless motor **500**, according to an embodiment. As shown in these figures, in addition to the first end cap **100** and the second end cap **200**, the BLDC motor **500** includes a rotor assembly **300**, a stator assembly **400**, and the rotor shaft **340**. In an embodiment, the first and second end caps **100** and **200** are secured to one another via fasteners **110** or other means to substantially contain and encapsulate the rotor assembly **300** and stator assembly **400** components. These features are described herein in detail.

In an embodiment, stator assembly **400** is provided as an inner stator including a stator lamination stack **410** having a ring-shaped stator core **402** and a plurality of stator teeth radially projecting outwardly from the stator core with slots formed therebetween. Stator windings **420** are wound around the stator teeth defining the phases of the BLDC motor **500**. In an embodiment, where the BLDC motor **500** is a three-phase motor includes 12 stator windings **420**, the stator will constitute three groups of four stator windings **420** connected together on or around the stator core. The stator windings **420** within each group of stator windings **420** may be electrically coupled together in a series of a parallel connection, and the three groups of windings may be electrically wired together in a wye or a delta configuration. In an embodiment, stator assembly **400** can further include one or more end insulators covering end surfaces of the stator lamination stack **410** to electrically insulate the stator windings **420** from the stator lamination stack **410**.

In an embodiment, stator lamination stack **410** has a thickness of approximately 8-14 mm, preferably approximately 10-12 mm, and a diameter of approximately 100-130 mm, preferably approximately 110-115 mm. Thus, in an embodiment, the stator lamination stack has a diameter to thickness ratio of approximately 8-12, preferably approximately 9-11, in an example approximately 10. In an embodiment, this ratio optimizes the motor for high power/high torque applications such as a lawn mower. In an exemplary embodiment, the motor **500** has a maximum output speed of approximately 3,000 rpm, but a maximum power output of at least 1,100 watts, more preferably at least 1,200 watts, in an example approximately 1300 watts, suitable for high power/high torque applications.

In an embodiment, stator assembly **400** is secured, axially and radially, to the second end cap **200**. The second end cap **200** is thus also referred to in this disclose as a stator mount. In an embodiment, ring-shaped stator core **402** of the stator assembly **400** is mounted and secured to an inner annular portion of the second end cap **200**, as discussed later in detail.

In an embodiment, rotor assembly **300** is provided as an outer rotor including an inner annular member **322** and an outer annular core **320**. Inner annular member **322** includes an inner through-hole that is securely mounted over the rotor shaft **340** by press-fitting or other known means. Outer annular core **320** is provided with a larger diameter than the stator assembly **400** so as to circumferentially surround the stator assembly **400** with a small airgap therebetween. Outer

annular core **320** supports one or more permeant magnets (discussed below) that magnetically interact with the stator windings **420**, causing rotation of the rotor assembly **300** around the stator assembly **400** when the stator windings are sequentially energized. Extending substantially radially or angularly between the inner annular member **322** and the outer annular core **320** are a series of radial blades **326** that form a fan arranged to generate airflow for cooling the motor **500** components, particularly the stator windings **440**, as the rotor assembly **300** rotates. In particular, radial blades **326** are contained on their outer periphery by the annular core **320**, thus forming an axial fan that directs air parallel to the axis of the rotor shaft **340**. As will be described later in detail, first end cap **100** is provided with features to redirect the air generated by the axial fan in a radial direction.

In an embodiment, rotation of the rotor assembly **300** causes rotation of the rotor shaft **340** around its center longitudinal axis. In an embodiment, rotor shaft **340** is axially secured to the first and second end caps **100** and **200** via front and rear bearings **130** and **230**, respectively. Front and rear bearing **130** and **230** provide axial and radial support for the rotor shaft **340**, and subsequently for the entire rotor assembly **300**, with respect to the first and second end caps **100** and **200**, and subsequently with respect to the stator assembly **400**. This arrangement ensures that the rotor outer annular core **320** is securely positioned around the stator assembly **400** with an airgap in between.

Referring now to FIGS. **6A-6E**, and with continued reference to FIGS. **4A-5**, details of the outer rotor assembly **300** and its assembly process are described herein, according to an embodiment.

FIG. **6A** depicts a partial perspective view of the rotor assembly **300** including inner annular member **322**, outer annular core **320**, and radial blades **326**. In an embodiment, between approximately four to sixteen radial blades **326**, more preferably between six to fourteen radial blades, and even more preferably between eight to twelve radial blades, are provided. Each radial blade **326** can extend from an exterior portion of the inner annular member **322** to an interior portion **324** of the outer annular core **320**. Interior portion **324** of the outer annular core **320** may include an inwardly-projecting rim having curved portions that mate with radial ends of the radial blades **326**. The radial blades **326** can be placed at angles relative to a plane defined by the outer annular core **320** and the inner annular member **322**. The angular arrangement of the radial blades **326** forms openings **328** between adjacent radial blades **326**, through which airflow is generated and passed towards the first end cap **100**. The geometry of the radial blades **326** can be in an airfoil shape to improve an overall efficiency of the moving air.

FIG. **6B** depicts a perspective view of a laminated back iron ring **310**, according to an embodiment. FIG. **6C** depicts a perspective view of the laminated back iron ring **310**, with permanent magnets **314** mounted on an inner surface thereof. In an embodiment, laminated back iron ring **310** is a ring-shaped lamination stack made of steel or other conductive material mounted within the outer annular core **320** of the rotor assembly **300** to support permanent magnets **314**. The laminated back iron ring **310** can include magnet pockets **312** for holding the permanent magnets **314**. In an embodiment, the number of the magnet pockets **312** can correspond to the number of the permanent magnets **314**. In an embodiment, there may be between four to sixteen permanent magnets **314**, more preferably between six to twelve permanent magnets **314**, and even more preferably

between eight to ten permanent magnets **314**. The number of permanent magnets **314** is determined as number of poles and slots of the motor **500**.

In an embodiment, each magnet pocket **312** can be formed into a peripherally elongated rectangular shape. In an example, each magnet pocket **312** may also be curved to match the curvature of the laminated back iron ring **310**. Each of the permanent magnets **314** inserted into the corresponding magnet pocket **312** can be a sintered neodymium magnet, which is formed into a shape corresponding to the magnet pocket **312**. Furthermore, the permanent magnets **314** are magnetized so that the magnets adjacent to each other have poles reverse to each other.

As shown in FIGS. **6A-6C**, the inner surface of the outer circular member **324** can include a design to receive the laminated back iron ring **310**. To this end, in an embodiment, the inner surface of the outer circular member **324** can include protrusions **332** that can correspond to grooves **319** on the laminated back iron ring **310**. The interior portion **324** of the outer annular core **320** provides a platform for mounting and placement of the lamination back iron ring **310**.

In an embodiment, as shown in FIG. **6D**, the laminated back iron ring **310** and the permanent magnets **314** are at least partially encapsulated by an overmold layer **316** including resin or plastic material via an overmold or insert-mold process. In an embodiment, the overmold layer **316** substantially covers the permanent magnets **314** and forms molded-in airflow reliefs **318** between the respective magnets **314**.

FIG. **6E** depicts a perspective view of the outer rotor assembly **300** including the overmolded laminated back iron ring **310** of FIG. **6D**, according to an embodiment. In an embodiment, the laminated back iron ring **310** having the permanent magnets **314** and being, at least, partially encapsulated by overmold layer **316** is slip-fitted to the outer annular core **320**. In an embodiment, the protrusions **332** of the outer annular core **320** are aligned with the grooves **319** of the laminated back iron ring **310** and the laminated back iron ring **310** is received into the outer annular core **320**.

In an embodiment, the laminated back iron ring **310** is secured to the outer annular core **320** by any known methods, such as by an adhesive to form the rotor assembly **300**. In an embodiment, the laminated back iron ring **310** is first inserted into the outer annular core **320** and then the permanent magnets **314** are secured into the magnet pockets **312** by any known methods, such as by an adhesive. The overmold layer **316** may then be applied to the laminated back iron ring **310** having the permanent magnets **314** to form the rotor assembly **300**.

FIG. **6F** depicts a perspective view of the rotor assembly **300** mounted on the rotor shaft **340**, according to an embodiment. As previously discussed, in an embodiment, inner through-hole **330** formed within the inner annular member **322** of the rotor assembly **300** is press-fitted on the rotor shaft **340**. The rotor shaft **340** is thus axially, radially, and rotationally secured to the rotor assembly **300**. As also previously discussed, rotor shaft **340** is further secured, axially and radially but not rotationally, to first end cap **100** and the second end cap **200** via front and rear bearings **130** and **230**, respectively.

This arrangement provides an outer-rotor assembly having permanent magnets disposed around the outer circumference of a stator assembly, but also coupled to a central rotor shaft rotatably received within the stator assembly. This arrangement also integrates fan blades forming an axial

fan for cooling the motor into the outer rotor assembly structure, ridding the motor of a separate fan structure.

In an embodiment, the rotor laminated back iron ring **310** has a diameter of approximately 120-150 mm, preferably approximately 130-140 mm, in an example approximately 136 mm. The entire rotor assembly **300** including the outer annular core **320** has a diameter of approximately 130-160 mm, preferably approximately 140-150 mm, in an example approximately 145 mm. In an embodiment, the rotor laminated back iron ring **310** has approximately the same thickness as the stator lamination stack **410**.

Referring now to FIGS. **7A, 7B** and **7C**, and with continued reference to FIGS. **4A-5**, the second end cap **200** is described herein in detail.

FIGS. **7A** and **7B** depict front and back perspective views of second end cap **200**, according to an embodiment. FIG. **7C** depicts a zoom-in cross-sectional view of the second end cap **200**.

In an embodiment, second end cap **200** includes an outer annular body **202**, an inner annular body **206** forming the center opening **210**, and a conical or dome shaped main body **204** extending between the inner annular body **206** and the outer annular body **202**. In an embodiment, front peripheral edge **208** of the outer annular body **202** is disposed to mate with the first end cap **200**, as discussed later.

In an embodiment, center opening **210** of the inner annular body **206** forms a pocket **240** facing the first end cap **200** that securely supports the rear bearing **230** of the rotor shaft **340** therein to axially and radially support the rotor shaft **340** with respect to the second end cap **200**. Additionally, pocket **240** houses a sense magnet ring **250** including a series of magnets is mounted on a distal end of the rotor shaft **340** rearwardly of the rear bearing **230**. Moreover, pocket **240** houses and supports a positional sensor board **260** including a series of positional sensors (e.g., Hall sensors) in close proximity to and facing the sense magnet ring **250**. The positional sensor board **260** is oriented on a plane substantially parallel to the longitudinal axis of the rotor shaft **340**.

In an embodiment, pocket **240** includes a bearing pocket **242** at an end of the pocket **240** closest to the second end cap **200**. The bearing pocket **242** (i.e., first portion of the inner annular body **206**) has a first diameter sized to form-fittingly receive the rear bearing **230** of the rotor shaft **340** therein.

In an embodiment, the pocket **240** further includes a sense magnet pocket **244** disposed rearward of the bearing pocket **242** with respect to the second end cap **200**. The sense magnet pocket **244** (i.e., third portion of the inner annular body **206**) has a second diameter smaller than the first diameter, sized to freely receive and house the sense magnet ring **250** therein. In an embodiment, radial rim **246** formed between the bearing pocket **242** and the sense magnet pocket **244** forms as an axial stop for the rear bearing **230**.

In an embodiment, the pocket **240** further includes a positional sensor board pocket **248** (i.e., second portion of the inner annular body **206**) disposed rearward of the sense magnet pocket **244** with a third diameter smaller than the first and second diameters. In an embodiment, positional sensor board pocket **248** is sized to form-fittingly receive the positional sensor board **260** therein, with magnetic (hall) sensors **262** in close proximity to the sense magnet ring **250** at a distance of, for example, 0.5 to 3 mm, preferably 0.2-2 mm, and approximately 1 mm. The magnetic sensors **262** detect a magnetic field generated by the sense magnet ring **250** magnets to detect a rotatory position of the rotor shaft **340**. In an embodiment, a radial rim **247** formed between the positional sensor board pocket **248** and an inner wall **249** of

center opening 210 forms an axial stop for the positional sensor board 260. In an embodiment, positional sensor board 260 may be fastened to the radial rim 247 or the side walls of the positional sensor board pocket 248 via, for example, screws or other fastening means. Communication signals from the positional sensor board 260 may be passed through the center opening 210 for communication with the controller (not shown).

In an embodiment, the bearing pocket 240 protrudes inwardly towards the stator assembly 400 from the second end cap 200, with at least the bearing pocket 242 protruding axially into the inner opening of the ring-shaped stator core 402 of the stator assembly 400. This arrangement allows the rear bearing 230 to sit within the inner opening of the ring-shaped stator core 402 in-line with the stator lamination stack 410 along the same radial plane. Further, the sense magnet ring 250 is in-line with at least a portion of the stator windings 420 along the same radial plane. The arrangement according to this embodiment reduces the axial length of the BLDC motor 500 and flattens the overall envelope.

In an embodiment, one or more openings 220 are disposed in the main body 204 at a first radius around the center opening 210 through which the stator terminals 440 (i.e., for receiving U, V, W phase power lines from the power module 40) are received. In an embodiment, the stator terminals 440 project slightly out of the openings 220 to ease wrapping or fusing of power lines to the terminals 440. In an embodiment, air inlets 222 are disposed in the main body 204 along a second radius greater than the first radius around the center opening 210 for receiving incoming cooling air into the second end cap 200 for airflow generated by the motor fan.

In an embodiment, as briefly discussed above, the inner annular portion 206 of the second end cap 200 structurally, i.e., radially and axially, supports the stator assembly 400. In an embodiment, the ring-shaped stator core 402 is sized to be mounted around the inner annular portion 206 of the second end cap 200, with the stator lamination stack 410 being disposed circumferentially around the bearing pocket 242. This structure ensures that the stator assembly 400 is securely piloted within the second end cap 200 with high precision.

In power appliances such electric mower 10 utilizing the motor 500 described herein, the rotor assembly 300 can be seen deflecting drastically upon high impact resulting from contact between the mower blades 14 and a hard object such as a rock or metal object, particularly ingress of such hard object within the blades 14. In some instances, rotor assembly 300 can be seen pivoting around an axis that is perpendicular to the general axis of the motor 500 to deflect upwardly in the direction of the second end cap 200. In an embodiment, the deviation of the rotor shaft 340 from the longitudinal axis of the motor 500 causes the rotor assembly 300 to pivot around an axis perpendicular to the axis of the motor 500, one side of the rotor assembly 300 making contact with the stator assembly 400 and the second end cap 200. Any contact between the rotor assembly 300 in its rotating state and the non-rotating parts of the motor 500 including the stator assembly 400 and the second end cap 200 can cause severe damage to the motor 500 components.

To limit the deflection of the rotor assembly 300 in the event of such contact or ingress of hard objects with or into the mower blades 14, according to an embodiment of the invention, the second end cap 200 is provided with one or more deflection limiting members 270, as shown in the perspective view of FIG. 8A. In an embodiment, deflection limiting members 270 may be made of flexible and/or elastically resilient material such as plastic, rubber, etc. In an

embodiment, deflection limiting members 270 may be secured to an inner surface of the main body 204 of the second end cap 200 bordering the outer annular body 202. In an embodiment, deflection limiting members 270 may be provided as a series of discrete segments provided at a distance from one another, as shown in FIG. 8A, or as a one-piece ring sized to be received within the outer annular body 202. In an embodiment, deflection limiting members 270 may be provided as integral ribs projecting from the main body 204 and/or the outer annular body 202 of the second end cap 200, or as separate pieces assembled into the second end cap 200.

In an embodiment, deflection limiting members 270 are provided with a height 272 (in the axis direction of the motor 500) that is smaller than the distance between the rotor assembly 300 and the main body 204 of the second end cap 200. In an embodiment, the height 272 of deflection limiting members 270 is sized so that the rotor assembly 300 does not contact the deflection limiting members 270 during normal operation and with a normal level of vibration and movement, but is prevented by deflection limiting members 270 from pivoting drastically so as to come into contact with the stator assembly 400.

In an embodiment, a thickness 272 (in the radial direction of the motor 500) of the deflection limiting members 270 is sized to come into contact with the rotor assembly 300, i.e., peripheral end of the laminated back iron ring 310 or the overmold layer 316, but not with the stator assembly 400. In an embodiment, deflection limiting members 270 are disposed along a ring having a diameter that is greater than the diameter of the stator assembly 400 but approximately corresponds to the diameter of the laminated back iron ring 310 of the rotor assembly 300.

In the event of high impact resulting from contact or ingress of hard objects described above, the upward deflection of the rotor assembly 300 may also at times make contact with and damage the positional sensor board 260. This is particularly due to the small air gap that is maintained between the positional sensor board 260 and the sense magnet ring 250 for accurate sensing of the angular position of the rotor assembly 300.

To absorb this impact and protect the positional sensor board 260 from damage, according to embodiment, an impact absorbing member 280 is provided, as depicted in the partial cross-sectional view of FIG. 8B. In an embodiment, impact absorbing member 280 is received within sensor board pocket 248. Impact absorbing member 280 may be fastened to the radial rim 247 or the side walls of the positional sensor board pocket 248 via, for example, adhesive, screws or other fastening mechanism. In an embodiment, positional sensor board 260 is in turn secured to the impact absorbing member 280 via, for example, an adhesive, screws, or other fastening mechanism. In an embodiment, impact absorbing member 280 may be made of flexible or resiliently elastic material such as dense foam, rubber, etc. In an embodiment, impact absorbing member 280 may be provided with the sufficient thickness to effectively absorb the force of an impact upon the positional sensor board 260 by the rotor shaft 340 and/or the sense magnet ring 250, while maintaining proper airgap between the sense magnet ring 250 and the positional sensor board 260. In an embodiment, impact absorbing member 280 may be 1-3 mm in thickness. In an embodiment, impact absorbing member 280 may be disc-shaped or ring-shaped with an outer diameter that is substantially equivalent to or greater than the positional sensor board 260.

In an embodiment, the impact absorbing member may be a spring element **282** provided to absorb the impact on the positional sensor board **260**, as depicted in the partial cross-sectional view of FIG. **8C**. In an embodiment, spring member **282** may be a wave spring, though other types of spring such as a Belleville washer, disc spring, compression spring, torsion spring, etc. may alternatively be utilized. In an embodiment, spring member **282** is sized to be received within the sensor board pocket **248** and secured to the radial rim **247** or the side walls of the positional sensor board pocket **248** via, for example, adhesive, screws or other fastening mechanism. In an embodiment, positional sensor board **260** is in turn secured to the impact absorbing member **280** via, for example, an adhesive, screws, or other fastening mechanism. In an embodiment, spring member **282** may be provided with the sufficient thickness to effectively absorb the force of an impact upon the positional sensor board **260** by the rotor shaft **340** and/or the sense magnet ring **250**, while maintaining proper airgap between the sense magnet ring **250** and the positional sensor board **260**. In an embodiment, spring member **280** may have a thickness of 1-3 mm.

FIG. **8D** depicts a perspective view of a wave spring used as the spring member **282**, according to an embodiment.

The first end cap **100** is described herein in detail with reference to FIGS. **9A-11B**, and with continued reference to FIGS. **4A-5**, according to an embodiment.

FIGS. **9A** and **9B** depict front and back perspective views of the first end cap **100**, according to an embodiment. FIG. **10A** respectively depict a top perspective view and a top horizontal cross-sectional view of the first end cap **100** along the y-z plane, according to an embodiment. FIGS. **11A** and **11B** respectively depict a side perspective view and a side vertical cross-sectional view of the first end cap **100**, according to an embodiment.

In an embodiment, as previously discussed, rotor shaft **340** passes through central opening **126** of the first end cap **100** to protrude into the main deck **52** of the electric mower **10** for driving the blades **14**. Moreover, the central opening **126** includes a bearing pocket **128** sized to form-fittingly and securely receive the front bearing **130** of the rotor shaft **340**. The front bearing **130** secures the rotor assembly **300** with respect to the first end cap **100** axially and radially, while allowing free rotation of the rotor assembly **300** within the first end cap **100**.

Additionally, the first end cap **100** includes a radial back plate **120** facing the rotor assembly **300**, an annular body **118** formed around the radial back plate **120**, and a donut-shaped side plate **116** projecting outwardly around the annular body **118** along substantially the same plate as the radial back plate **120**. A rear peripheral edge **117** of the annular body **118** comes to contact with front peripheral edge **208** of the second end cap **200** to substantially circumferentially enclose the rotor and stator assemblies **300** and **400**.

In an embodiment, radial back plate **120** is disposed adjacent radial blades **326** that form the fan of the rotor assembly **300**. The back plate **120** acts as a baffle for the fan, redirecting airflow generated by the fan to be expelled out of the exhaust ports **124A** and **124B** in a direction radial to the rotor shaft **340**. In an embodiment, back plate **120** includes at least one sloped surface, for example, two sloped surfaces **120A** and **120B**, as shown in FIGS. **9B**, **10B** and **11B**. The two sloped surfaces **120A** and **120B** of the back plate **120** are each sloped with respect to a radial plane of the back plate **120** such that adjacent ends of the two slopes surfaces **120A** and **120B** are axially offset with respect to one another, forming two air gaps **123A** and **123B** therebetween. Each of the air gaps **123A** and **123B** extends from approximately the

outer portion of the bearing pocket **128** to approximately an inner portion of the rear peripheral edge **117** of the annular body **118**. The air gaps **123A** and **123B** are formed parallel to the x-y plane in FIG. **9B**, where the x axis designates the longitudinal axis of the motor shaft **340**. The air gaps **123A** and **123B** extend laterally into the annular body **118**, forming air channels that are in fluid communication with the radial exhaust ports **124A** and **124B**. Radial exhaust ports **124A** and **124B** are formed over the side plate **116**. As airflow generated by the fan comes into contact with the back plate **120**, the sloped surfaces **120A** and **120B** cause centrifugal circulation of the airflow within the first end cap **100**. Air gaps **123A** and **123B** intercept the centrifugal circulation path of the airflow within the first end cap **100**, causing the air to exit the first end cap **100** in a radial and/or lateral direction through the exhaust ports **124A** and **124B**. Arrangement of the exhaust ports **124A** and **124B** above the main deck **52** of the electric mower **10** ensures that hot air existing the motor **500** does not enter the cavity **16** of the mower **10**. The two sloped surfaces **120A** and **120B** of the back plate **120** can form baffles that can provide a cyclonic path for the airflow generated by the radial blades **326** to be directed towards the two radial exhaust ports **124A** and **124B**.

In an embodiment, each of the sloped surfaces **120A** and **120B** is an inclined surface, which has a starting end adjacent to the radial blades **326** of the rotor assembly **300** and a terminal end adjacent to the each of the corresponding exhaust ports **124A** and **124B**.

In an embodiment, each of the sloped surfaces **120A** and **120B** extend from the starting end to the terminating end along the circumferential direction with a substantially constant width from the starting end to the terminal end. Two connecting walls **122A** and **122B** connect the outer edge of each of the sloped surfaces **120A** and **120B** to the first end cap body. Each of the connecting walls **122A** and **122B** can extend from the starting end of its corresponding sloped surfaces **120A** and **120B** and to the terminating end of each of its corresponding sloped surfaces **120A** and **120B**.

In an embodiment, main deck **52** includes a corresponding through-hole that aligns with the central opening **126** for receiving the rotor shaft **340**. In an embodiment, a series of screws are received through the cavity **16** of the main deck **52** through corresponding through-holes of the main deck **52** (not shown) and peripheral receptacles **125** of the first end cap **100**. A series of slugs or threaded nuts **112** are provided on the side plate **116** of the first end cap **100** to securely receive the screws and fasten the first end cap **100** on top of the main deck **52**. For this reason, the first end cap **100** is also referred to as the deck mount in this disclosure.

In an embodiment, the overall motor assembly **500** includes an envelope of approximately 140-180 mm, preferably approximately 150-170 mm, in an example approximately 160 mm, as defined by the diameter of the annular body **118** of the first end cap **110** and the diameter of the second end cap **200**. Furthermore, the length of the more, as defined between the lower end of the first end cap **100** and the upper end of the second end cap **200**, is approximately 60-100 mm, preferably approximately 70-90 mm, in an example approximately 80 mm. This approximately 2:1 ratio of the motor diameter to height provides for a high torque, high power, planar-shaped motor that can be flatly mounted on top of the main deck **52** of the mower **10**.

Aspects of the stator assembly **400** are described herein in detail with reference to FIGS. **12A-14B**, and with continued reference to FIGS. **4A-5**, according to an embodiment.

FIGS. 12A and 12B depict perspective views stator assembly 400 with a stator collar 430 prior and after assembly onto the ring-shaped stator core 402 of the stator assembly 400, according to an embodiment. FIG. 13A depicts a perspective view of the stator assembly 400 including the stator windings 420, with the stator collar 430 mounted thereon, according to an embodiment. FIG. 13B depicts a perspective zoomed-in view of the stator assembly 400 showing a single stator terminal 440 of the stator collar 430, according to an embodiment. Additionally, FIGS. 14A and 14B depict side and top views of the stator assembly 400, respectively, according to an embodiment.

In an embodiment, stator teeth 406 extend radially from the stator core 402. Each of the stator teeth 406 is wound by a stator coil to form the stator windings 420. The stator coils can be separately wound on the stator teeth 406 or continuous wound on the stator teeth 406, in a series or parallel and delta or wye configuration, as discussed above. In an embodiment, each of the stator teeth 406 is substantially T-shaped.

In order to electrically isolate the stator coils from the stator lamination stack 410, the end insulators 412 may be provided. In an embodiment, end insulators are discrete components mounted on the ends of the stator lamination stack 410, or at least partially encapsulate the stator lamination stack 410 by a process, such as an over-mold process. The end insulators 412 can be made from a material such as plastic or resin.

In an embodiment, stator collar 430 can include a substantially-cylindrical insulation carrier 432, which may be formed from plastic material. Additionally, the stator collar 430 can include a series of stator terminals 440, such as three stator terminals 440, mounted on the insulation carrier 432 and electrically insulated from each other by the insulation carrier 432. In an embodiment, each of the stator terminals 440 can be pressed into the stator collar 430. In an embodiment, the stator collar 430 includes a series of side openings with railings or channels 444 arranged parallel to the center axis of the stator collar 430 (and center axis of the motor 500) along the side openings. The stator terminals 440 include two side guides 446 that are slidingly received within the railings or channels 444 to affix the stator terminals 440 within the side openings of the stator collar 430.

In an embodiment, at least one of the end insulators 412 of the stator assembly 400 includes an inner annular rim 404 that supports mounting the stator collar 430 on the stator assembly 300. The insulating carrier 432 of the stator collar 430 is annular and can be fixed to or be placed inside or on the inner annular rim 404 of the end insulator 412. In an embodiment, end insulator 412 includes a central opening formed within the annular rim 404 with a larger diameter than central opening 411 of the stator lamination stack 410. This arrangement exposes a donut-shaped mounting platform 414 of the end surface of the stator lamination stack 410 facing the stator collar 430. A lower portion 434 of the insulating carrier 432 includes an outer diameter that is smaller than the outer diameter of the insulating carrier 432, sized to fit within the annular rim 404 and rest on top of the mounting platform 414 of the end surface of the stator lamination stack 410.

In an embodiment, end insulator 412 can also be provided with a series of tabs 416 projecting axially (in parallel to the longitudinal axis of the motor 500) from or adjacent to the annular rim 404. Stator collar 430 similarly includes recessed surfaces 448 that removably receive the tabs 416 for positioning and retention of the stator collar 430 over the end insulator 412. In an embodiment, the tabs 416 or the

recessed surfaces 448 may include snaps 449 for improved retention of the stator collar 430 over the end insulator 412.

In an embodiment, end insulator 412 further includes a series of recessed surfaces 417 that extend radially through the annular rim 404 into the outer surface of the teeth of the end insulator 412. Stator collar 430 is similarly provided with a series of radial protrusions 447 that are removably received within the recessed surfaces 417. The recessed surfaces 417 and radial protrusions 447 may be provided with snaps or other known retention features for securing the stator collar 430 over the end insulator 412.

In an embodiment, this configuration of the stator assembly 300 and stator collar 430 allows the stator collar 430 to be interchangeable with another one that has different types and/or quantities of stator terminals. The stator collar 430 may include different solder points for the terminals, different junctions for the terminals, different weld connections for the terminals, or a different number of terminals (e.g., for a 6-phase controlled motor v. a 3-phase controlled motor). Different stator collars 430 may be chosen by a motor designer based on, for example, the thickness of stator winding wires and/or the number of turns of windings around each stator tooth, the series or parallel connections between stator windings in the same phase, the delta or wye connections between stator windings of different phases, etc. For example, the dual-tang configuration described above may be more suited for a motor design with relatively thick stator windings. Interchangeability of the stator collar 430 allows a motor designer to adapt the same stator assembly 300 for different applications by only.

In an embodiment, stator collar 430 is provided with terminals 440 a main body 452 of which includes a curved contour when viewed in the axial direction of the motor 500 to form a uniform profile on the stator collar 430. In an embodiment, referring to FIG. 13B, each of the stator terminals 440 is a monolithic member, which includes at least two tangs 442 integrally extending radially-outwardly from the main body 452 of the stator terminal 440. This arrangement allows multiple sets of stator wires to be wound on the same terminal, increasing the capacity of each of the stator terminals 440. The two tangs 442 may be arranged at an angle from each other in the radial direction to simplify the fusing of the stator wires and aid in the winding of a coil. In this case, the stator terminals 440 may be arcuately shaped.

An alternative application of the outer-rotor BLDC motor 500 is described herein with reference to FIGS. 15-17, according to an embodiment.

FIG. 15 depicts a perspective view of a cordless electric hammer 600, according to an embodiment. FIG. 16 depicts a side cross-sectional view of the hammer 600.

Referring to these figures, hammer 600 comprises a main housing 602. In an embodiment, a handle 604 having two ends is attached to the main housing 602 via an upper mounting assembly 606 having vibration-absorbing features and a lower mounting assembly 608 having a pivoting member that allows slight pivoting of the handle 604 relative to the main housing 602. U.S. Pat. No. 10,137,562 titled "Rear Handle," which is incorporated herein by reference in its entirety, describes an example of the rear handle 604 and its mounting assemblies.

In an embodiment, a battery receptacle 610 is provided below the handle 604 rear of the lower mounting assembly 608. The battery receptacle 610 is configured to removably receive and lock in a power tool battery pack 612. Battery pack 612 may be, for example, a power tool 60V MAX battery pack configured to be slidingly received and secured

within the battery receptacle **610**. In an embodiment, the battery receptacle **610** includes a series of battery terminals **614** supported by the lower end of the handle **604** that engage and receive power from corresponding terminals of the battery pack **612**.

In an embodiment, a control module **616** is further provided within the handle **604** for controlling the operation of the hammer **600**. A trigger switch **618** may be supported by the handle **604** for engagement by a user forward of the control module **616**. Control module **616** controls flow of power from the battery pack **612** based on an input from the trigger switch **618**.

In an embodiment, hammer **600** further includes a cylindrical housing **620** disposed forward of the main housing **602**. A tool holder **622** is provided forward of the cylindrical housing **620** for holding tools such as a chisel (not shown). Cylindrical housing **620** houses a tubular cylinder **624** and includes a pneumatic hammer mechanism for driving the chisel in a reciprocating motion. The pneumatic hammer mechanism includes a piston **626** located within tubular cylinder **624** and arranged for reciprocating motion, a ram **628** also arranged within the tubular cylinder **624** forward of the piston **626** for reciprocating motion, an air chamber **630** located within the tubular cylinder **624** between the piston **626** and the ram **628** to transfer reciprocating motion of the piston **626** to the ram **628**, and a beat piece **632** located forward of the ram **628** for transferring the reciprocating motion of the ram **628** to a striking force on the chisel. Details related to the hammer mechanism and its components can be found in, for example, U.S. Pat. No. 9,925,653 titled "Hammer Drill," and U.S. Pat. No. 7,331,407 titled "Vibration Reduction Apparatus for Power Tool and Power Tool Incorporating Such Apparatus," both of which are incorporated herein by reference in their entireties.

In an embodiment, a brushless outer-rotor motor **500**, as described above with reference to FIGS. **3A** through **14B**, is mounted on the main housing **602** of the hammer **600**. In an embodiment, first end cap **100** of the motor **500** is mounted on the main housing **602** such that the motor **500** components are positioned substantially outside an extension envelope defined by the cylindrical housing **620**. In an embodiment, motor **500** is fully positioned above a horizontal plane formed by longitudinal axis 'A' of the hammer **500**, whereas battery receptacle **610** is fully positioned below the same plane. In an embodiment, a portion of the first end cap **100** intersects a longitudinal axis 'B' of the upper wall of cylindrical housing **620** and/or an upper wall of the tubular cylinder **624**. In an embodiment, a portion of the second end cap **200** intersects a longitudinal axis 'C' of the upper mounting assembly **606** of the rear handle **616**. In an embodiment, the upper end of the main body **602** near the upper mounting assembly **606** is secured to the second end cap **200** for added structural support of the motor **500** relative to the hammer **600**.

FIG. **17** depicts a partial zoom-in view of the hammer **600**. FIG. **18** depicts a partial exploded view of the motor **500** relative to the main housing **602**. As shown here, and with continued reference to FIGS. **15** and **16**, in an embodiment, motor **500** includes the same stator **400**, rotor **300**, first end cap **100**, and second end cap **200** as described above, with first end cap **100** shaped to be suitably mounted on top of the main housing **602** or disposed within a cavity provided on the main housing **602**.

In an embodiment, rotor shaft **340** extends perpendicularly to the longitudinal axis 'A' of the hammer **600** from the motor **500** and through the main housing **602**. Rotor shaft **340** is supported relative to the stator assembly **400** via rear

bearing **230**, as described above in detail. In an embodiment, rear bearing **230** is fully located outside the main housing **602** as well as the extension envelope defined by the cylindrical housing **620**. Rotor shaft **340** is further supported relative to the first end cap **100** via front bearing **130**. In an embodiment, front bearing **130** intersects the longitudinal axis 'B' of the upper wall of cylindrical housing **620** and/or an upper wall of the tubular cylinder **624**.

In an embodiment, a lower end of the rotor shaft **340** is coupled to a crank wheel **642** within the main housing **602**. The crank wheel **642** is caused to rotate about the axis of the rotor shaft **340** by rotation of the rotor shaft **340**. In an embodiment, a piston arm **644** extends rearwardly from the piston **626** and penetrates into the main housing **602**. The crank wheel **642** is coupled to end of the piston arm **644** via a pivoting pin **646**. Rotary motion of the crank wheel **642** is transferred to a reciprocating motion of the piston arm **644** via the pivoting pin **646**.

In an embodiment, crank wheel **642** may be mounted on the rotor shaft **340** by, for example, press-fitting or alternative mounting means. Direct mounting of the crank wheel **642** on the rotor shaft **340** provides for a direct-drive mechanism without any reduction gears, which reduces heat loss and increases efficiency. Electronic commutation of the motor **500** by control unit **616** allows for optimization of motor speed and power output as required without a need for gear reduction system. In an embodiment, motor **500** may be controlled to output a maximum power of 1300 W to 1700 W, preferably approximately 1500 W, at a rotational speed of 2000 to 3000 RPM, suitable for direct drive of the hammer **600**. Alternatively, the crank wheel **642** may include gears that mesh with corresponding gears on the rotor shaft **340**.

In an embodiment, 60V Max battery packs having capacity rating of 3 Ah to 12 Ah may be utilized to power the hammer **600**. These battery packs may have a weight range of 2.5 to 4.5 lbs. One advantage of disposition of the motor **500** above the main housing **602** and opposite the battery receptacle **610**, as described above, is more efficient balancing of the hammer **600**. In an embodiment, the above-described configuration ensures that the hammer **600**, when provided with a 60V Max battery pack, has a center of gravity that is significantly close to the central longitudinal axis 'A' of the hammer **600**. In an embodiment, a distance between said center of gravity and the longitudinal axis 'A' of the hammer **600** is less than approximately 20%, more preferably less than approximately 10%, of the full height of the hammer **600** as measured from the top of the handle **604** to the bottom of the battery pack **612**.

In an embodiment, as discussed above, the first end cap **100** may be mounted over the main housing **602**. The first end cap **100** may be secured to the main housing **602** by any known means such as screws. Alternatively, as shown in FIG. **18**, the first end cap **100** may be formed integrally as part of the main housing **602** as a single piece.

In an embodiment, first end cap **100** may be provided with radial exhaust ports as previously described in order to substantially isolate the airflow through the motor **500** from the main housing **602**. In an embodiment, while some leakage of air from the first end cap **100** to the main housing **602** is possible, the air is substantially prevented from entering the main housing **602**. In this embodiment, an additional fan (not shown) may be provided on the motor shaft **340** above the crank wheel **642** to cool the internal components of the hammer **600**. Alternatively, as shown in FIG. **18**, the first end caps **100** may be provided with a series of air vents **640** that allow flow of air from the motor **500**

into the main housing 602 in a direction along the axis of the rotor shaft 340 for cooling of the internal components of the hammer 600.

The foregoing description of the embodiments has been provided for purposes of illustration and description. It is not intended to be exhaustive or to limit the disclosure. Individual elements or features of a particular embodiment are generally not limited to that particular embodiment, but, where applicable, are interchangeable and can be used in a selected embodiment, even if not specifically shown or described. The same may also be varied in many ways. Such variations are not to be regarded as a departure from the disclosure, and all such modifications are intended to be included within the scope of the disclosure.

Example embodiments are provided so that this disclosure will be thorough and will fully convey the scope to those who are skilled in the art. Numerous specific details are set forth such as examples of specific components, devices, and methods, to provide a thorough understanding of embodiments of the present disclosure. It will be apparent to those skilled in the art that specific details need not be employed, that example embodiments may be embodied in many different forms and that neither should be construed to limit the scope of the disclosure. In some example embodiments, well-known processes, well-known device structures, and well-known technologies are not described in detail.

The terminology used herein is for the purpose of describing particular example embodiments only and is not intended to be limiting. As used herein, the singular forms “a,” “an,” and “the” may be intended to include the plural forms as well, unless the context clearly indicates otherwise. The terms “comprises,” “comprising,” “including,” and “having,” are inclusive and therefore specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof. The method steps, processes, and operations described herein are not to be construed as necessarily requiring their performance in the particular order discussed or illustrated, unless specifically identified as an order of performance. It is also to be understood that additional or alternative steps may be employed.

The invention claimed is:

1. A brushless direct-current (BLDC) motor comprising:
 - a rotor shaft extending along a center axis;
 - a stator having a stator core, a plurality of teeth extending radially outwardly from the stator core, a plurality of windings wound around the stator teeth, a stator collar mounted on the stator core, and a plurality of terminals mounted on the stator collar in a direction parallel to the longitudinal axis and electrically coupled to the plurality of windings;
 - a rotor having a rotor core disposed around the stator, a plurality of permanent magnets secured to the rotor core, and an inner annular member mounted on the rotor shaft;
 - a first end cap including a radial back plate disposed on a first side of the stator and having a front center opening through which the rotor shaft is supported via a front bearing; and
 - a second end cap having an inner annular body, an outer annular body, and a main body extending on a second side of the stator from the inner annular body to the outer annular body, the inner annular body extending axially inwardly and forming a rear center opening, wherein the inner annular body includes a first portion

that extends at least partially into an opening of the stator core and supports the rotor shaft via a rear bearing radially intersecting at least a portion of the stator, and a second portion rearward of the first portion that receives a rear end of the rotor shaft therein and houses a sensor board therein, the sensor board accommodating at least one positional sensor facing the end of the rotor shaft,

wherein the second end cap further comprises a plurality of openings formed in the main body around the inner annular body for passage of the plurality of terminals so distal ends of the plurality of terminals project outside the second end cap, wherein a radial plane passing through the sensor board intersects the plurality of terminals.

2. The motor of claim 1, wherein the rotor comprises a plurality of radial blades extending angularly from the rotor core to the inner annular member forming a fan adjacent the stator that generates an airflow with rotation of the rotor shaft.

3. The motor of claim 2, wherein the radial back plate of the first end cap includes at least one sloped surface forming at least one air gap, wherein the airflow generated by the fan is centrifugally guided within the first end cap by the at least one sloped surface and caused to exit the first end cap through the at least one air gap, and wherein the first end cap includes an annular outer body having at least one exhaust port in fluid communication with the at least one air gap and through which the airflow is expelled from the first end cap in a substantially radial direction.

4. The motor of claim 1, wherein the annular body of the second end cap extends from the main body around at least a portion of the rotor core and comes into contact with the first end cap to secure the second end cap to the first end cap around the rotor.

5. The motor of claim 2, wherein the second end cap comprises a plurality of air passage openings for passage of the airflow, wherein the plurality of air passage openings is radially inward of the plurality of openings.

6. The motor of claim 1, wherein the first portion of the inner annular body has a larger diameter at the first portion than at the second portion.

7. The motor of claim 6, further comprising a sense magnet mounted on the rear end of the rotor shaft in close proximity to the sensor board.

8. The motor of claim 7, wherein the inner annular body further includes a third portion disposed between the first portion and the second portion and having a diameter that is greater than that of the second portion but smaller than that of the first portion, the sense magnet being located within the third portion of the inner annular body.

9. The motor of claim 1, wherein the inner annular body further comprises a radial rim formed at a rear end of the second portion, wherein the sensor board is secured to the radial rim.

10. The motor of claim 1, further comprising at least one of an impact absorbing member or a spring disposed between the sensor board and the radial rim.

11. The motor of claim 1, wherein the second end cap is provided with one or more deflection limiting members near meeting boundaries of the outer annular body and the main body, the one or more deflection limiting member facing the rotor core to absorb an impact of the rotor core in an event of a pivoting movement of the rotor shaft away from the center axis.

23

12. A power tool comprising:
 a housing;
 a battery receptacle formed on the housing for receiving
 a power tool battery pack;
 a control module disposed within the housing to control 5
 supply of power from the battery pack; and
 a brushless direct-current (BLDC) motor mounted within
 or on the housing, the motor comprising:
 a rotor shaft extending along a center axis;
 a stator having a stator core, a plurality of teeth extending 10
 radially outwardly from the stator core, a plurality of
 windings wound around the stator teeth, a stator collar
 mounted on the stator core, and a plurality of terminals
 mounted on the stator collar in a direction parallel to the
 longitudinal axis and electrically coupled to the plural- 15
 ity of windings;
 a rotor having a rotor core disposed around the stator, a
 plurality of permanent magnets secured to the rotor
 core, and an inner annular member mounted on the
 rotor shaft; 20
 a first end cap including a radial back plate disposed on a
 first side of the stator and having a front center opening
 through which the rotor shaft is supported via a front
 bearing; and
 a second end cap having an inner annular body, an outer 25
 annular body, and a main body extending on a second
 side of the stator from the inner annular body to the
 outer annular body, the inner annular body extending
 axially inwardly and forming a rear center opening,
 wherein the inner annular body includes a first portion 30
 that extends at least partially into an opening of the
 stator core and supports the rotor shaft via a rear
 bearing radially intersecting at least a portion of the
 stator, and a second portion rearward of the first portion
 that receives a rear end of the rotor shaft therein and 35
 houses a sensor board therein, the sensor board accom-
 modating at least one positional sensor facing the end
 of the rotor shaft,
 wherein the second end cap further comprises a plurality
 of openings formed in the main body around the inner 40
 annular body for passage of the plurality of terminals so
 distal ends of the plurality of terminals project outside
 the second end cap, wherein a radial plane passing
 through the sensor board intersects the plurality of
 terminals. 45
13. The power tool of claim 12, wherein the power tool
 further comprises:
 a tubular cylinder housed within the housing defining a
 longitudinal axis;
 a piston reciprocatingly disposed within the tubular cyl- 50
 nder;
 a crank mechanism disposed within the housing config-
 ured to convert a rotary motion to a reciprocating
 motion for driving the piston;
 a tool holder mounted on the housing forward of the 55
 tubular cylinder; and
 a battery receptacle provided on the housing for receiving
 a removable power tool battery pack, the battery pack
 being provided on a first side of a plane that intersects
 the longitudinal axis when received within the battery 60
 receptacle,

24

- wherein the motor is mounted on the housing on a second
 side of the plane that intersects the longitudinal axis
 such that a distance between the longitudinal axis and
 a center of gravity of the power tool with the battery
 pack received within the battery receptacle is less than
 or equal to approximately 20% of a full height of the
 power tool.
14. A lawn mower comprising:
 a main deck defining a lower cavity within which a cutting
 blade is received;
 a plurality of wheels supporting the main deck; and
 a brushless direct-current (BLDC) motor mounted on the
 main deck for driving the cutting blade, the motor
 comprising:
 a rotor shaft extending along a center axis through an
 opening of the main deck to rotationally drive the
 cutting blade;
 a stator having a stator core, a plurality of teeth
 extending radially outwardly from the stator core, a
 plurality of windings wound around the stator teeth,
 a stator collar mounted on the stator core, and a
 plurality of terminals mounted on the stator collar in
 a direction parallel to the longitudinal axis and
 electrically coupled to the plurality of windings;
 a rotor having a rotor core disposed around the stator,
 a plurality of permanent magnets secured to the rotor
 core, and an inner annular member mounted on the
 rotor shaft;
 a first end cap mounted on the main deck, the first end
 cap including a radial back plate disposed on a first
 side of the stator and having a front center opening
 through which the rotor shaft is supported via a front
 bearing; and
 a second end cap having an inner annular body, an outer
 annular body, and a main body extending on a
 second side of the stator from the inner annular body
 to the outer annular body, the inner annular body
 extending axially inwardly and forming a rear center
 opening, wherein the inner annular body includes a
 first portion that extends at least partially into an
 opening of the stator core and supports the rotor shaft
 via a rear bearing radially intersecting at least a
 portion of the stator, and a second portion rearward
 of the first portion that receives a rear end of the rotor
 shaft therein and houses a sensor board therein, the
 sensor board accommodating at least one positional
 sensor facing the end of the rotor shaft,
 wherein the second end cap further comprises a plu-
 rality of openings formed in the main body around
 the inner annular body for passage of the plurality of
 terminals so distal ends of the plurality of terminals
 project outside the second end cap, wherein a radial
 plane passing through the sensor board intersects the
 plurality of terminals.
15. The lawn mower of claim 14, further comprising a
 motor housing disposed above the main deck to house the
 motor, and a battery cage disposed above the motor housing
 for receiving a removable battery pack therein.