



US011671441B2

(12) **United States Patent**
Gouveia

(10) **Patent No.:** **US 11,671,441 B2**
(45) **Date of Patent:** ***Jun. 6, 2023**

(54) **SYSTEMS AND METHODS FOR EXTERNAL
DETECTION OF MISCONFIGURED
SYSTEMS**

(71) Applicant: **BitSight Technologies, Inc.**, Boston,
MA (US)

(72) Inventor: **Joao Gouveia**, Bejos de Azeitao (PT)

(73) Assignee: **BitSight Technologies, Inc.**, Boston,
MA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 200 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **17/014,495**

(22) Filed: **Sep. 8, 2020**

(65) **Prior Publication Data**

US 2020/0404017 A1 Dec. 24, 2020

Related U.S. Application Data

(63) Continuation of application No. 15/954,921, filed on
Apr. 17, 2018, now Pat. No. 10,812,520.

(51) **Int. Cl.**
H04L 9/40 (2022.01)
H04L 61/3015 (2022.01)

(52) **U.S. Cl.**
CPC **H04L 63/1433** (2013.01); **H04L 61/302**
(2013.01)

(58) **Field of Classification Search**
CPC H04L 63/1433; H04L 61/302
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,867,799 A 2/1999 Lang et al.
6,016,475 A 1/2000 Miller et al.
6,745,150 B1 6/2004 Breiman
6,792,401 B1 9/2004 Nigro et al.
7,062,572 B1 6/2006 Hampton
D525,264 S 7/2006 Chotai et al.
D525,629 S 7/2006 Chotai et al.

(Continued)

FOREIGN PATENT DOCUMENTS

WO WO-2017/142694 A1 8/2017
WO WO-2019/023045 A1 1/2019

OTHER PUBLICATIONS

U.S. Appl. No. 15/271,655 Published as: US2018/0083999, filed
Sep. 21, 2016, Self-Published Security Risk Management.

(Continued)


Primary Examiner — Oleg Korsak

(74) *Attorney, Agent, or Firm* — Goodwin Procter LLP

(57) **ABSTRACT**

A computer-implemented method is provided for external
detection of a vulnerable system coupled to a communica-
tion network. The method can include measuring commu-
nication traffic on the communication network to identify
one or more domain names, which in turn can originate from
server systems in the communication network. The method
can further include identifying the domain names based on
metadata from the domain names and/or the measured
communication traffic, where each domain name has an
associated property indicative of its vulnerability. The
method can further include determining whether any one (or
more) of the domain names is registered at a domain name
registry and, if the domain name is not registered, registering
the domain name.

21 Claims, 4 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2014/0244317 A1 8/2014 Roberts et al.
 2014/0282261 A1 9/2014 Ranz et al.
 2014/0283068 A1 9/2014 Call et al.
 2014/0288996 A1 9/2014 Rence et al.
 2014/0304816 A1 10/2014 Klein et al.
 2014/0330616 A1 11/2014 Lyras
 2014/0334336 A1 11/2014 Chen et al.
 2014/0337086 A1 11/2014 Asenjo et al.
 2014/0337633 A1 11/2014 Yang et al.
 2014/0344332 A1 11/2014 Giebler
 2015/0033331 A1 1/2015 Stern et al.
 2015/0033341 A1 1/2015 Schmidtler et al.
 2015/0052607 A1 2/2015 Al Hamami
 2015/0074579 A1 3/2015 Gladstone et al.
 2015/0081860 A1 3/2015 Kuehnel et al.
 2015/0156084 A1 6/2015 Kaminsky et al.
 2015/0180883 A1 6/2015 Aktas et al.
 2015/0195299 A1 7/2015 Zoldi et al.
 2015/0207776 A1 7/2015 Morin et al.
 2015/0248280 A1 9/2015 Pillay et al.
 2015/0261955 A1 9/2015 Huang et al.
 2015/0264061 A1 9/2015 Ibatullin et al.
 2015/0288706 A1 10/2015 Marshall
 2015/0288709 A1 10/2015 Singhal et al.
 2015/0310188 A1 10/2015 Ford et al.
 2015/0310213 A1 10/2015 Ronen et al.
 2015/0317672 A1 11/2015 Espinoza et al.
 2015/0331932 A1 11/2015 Georges et al.
 2015/0347756 A1 12/2015 Hidayat et al.
 2015/0350229 A1 12/2015 Mitchell
 2015/0381649 A1 12/2015 Schultz et al.
 2016/0014081 A1 1/2016 Don, Jr. et al.
 2016/0023639 A1 1/2016 Cajiga et al.
 2016/0036849 A1 2/2016 Zakian
 2016/0065613 A1 3/2016 Cho et al.
 2016/0078382 A1 3/2016 Watkins et al.
 2016/0088015 A1 3/2016 Sivan et al.
 2016/0119373 A1 4/2016 Fausto et al.
 2016/0140466 A1 5/2016 Sidebottom et al.
 2016/0147992 A1 5/2016 Zhao et al.
 2016/0162602 A1 6/2016 Bradish et al.
 2016/0171415 A1 6/2016 Yampolskiy et al.
 2016/0173520 A1 6/2016 Foster et al.
 2016/0173522 A1 6/2016 Yampolskiy et al.
 2016/0182537 A1 6/2016 Tatourian et al.
 2016/0189301 A1 6/2016 Ng et al.
 2016/0191554 A1 6/2016 Kaminsky
 2016/0205126 A1 7/2016 Boyer et al.
 2016/0212101 A1 7/2016 Reshadi et al.
 2016/0241560 A1 8/2016 Reshadi et al.
 2016/0248797 A1 8/2016 Yampolskiy et al.
 2016/0253500 A1 9/2016 Alme et al.
 2016/0259945 A1 9/2016 Yampolskiy et al.
 2016/0337387 A1 11/2016 Hu et al.
 2016/0344769 A1 11/2016 Li
 2016/0344801 A1 11/2016 Akkarawittayapoom
 2016/0364496 A1 12/2016 Li
 2016/0373485 A1 12/2016 Kamble
 2016/0378978 A1 12/2016 Singla et al.
 2017/0048267 A1 2/2017 Yampolskiy et al.
 2017/0063901 A1 3/2017 Muddu et al.
 2017/0104783 A1 4/2017 Vanunu et al.
 2017/0142148 A1 5/2017 Bußber et al.
 2017/0161253 A1 6/2017 Silver
 2017/0161409 A1 6/2017 Martin
 2017/0213292 A1 7/2017 Sweeney et al.
 2017/0221072 A1 8/2017 AthuluruThrumala et al.
 2017/0223002 A1 8/2017 Sabin et al.
 2017/0236078 A1 8/2017 Rasumov
 2017/0237764 A1 8/2017 Rasumov
 2017/0264623 A1 9/2017 Ficarra et al.
 2017/0279843 A1 9/2017 Schultz et al.
 2017/0300911 A1 10/2017 Alnajem
 2017/0316324 A1 11/2017 Barrett et al.
 2017/0318045 A1 11/2017 Johns et al.

2017/0324555 A1 11/2017 Wu et al.
 2017/0324766 A1 11/2017 Gonzalez
 2017/0337487 A1 11/2017 Nock et al.
 2018/0013716 A1 1/2018 Connell et al.
 2018/0088968 A1 3/2018 Myhre et al.
 2018/0103043 A1 4/2018 Kupreev et al.
 2018/0121659 A1 5/2018 Sawhney et al.
 2018/0123934 A1 5/2018 Gissing et al.
 2018/0124091 A1 5/2018 Sweeney et al.
 2018/0124110 A1 5/2018 Hunt et al.
 2018/0139180 A1 5/2018 Napchi et al.
 2018/0146004 A1 5/2018 Belfiore, Jr. et al.
 2018/0157468 A1 6/2018 Stachura
 2018/0191768 A1 7/2018 Broda et al.
 2018/0285414 A1 10/2018 Kondiles et al.
 2018/0322584 A1 11/2018 Crabtree et al.
 2018/0336348 A1 11/2018 Ng et al.
 2018/0337938 A1 11/2018 Kneib et al.
 2018/0337941 A1 11/2018 Kraning et al.
 2018/0349641 A1 12/2018 Barday et al.
 2018/0365519 A1 12/2018 Pollard et al.
 2018/0375896 A1 12/2018 Wang et al.
 2019/0034845 A1 1/2019 Mo et al.
 2019/0065545 A1 2/2019 Hazel et al.
 2019/0079869 A1 3/2019 Baldi et al.
 2019/0089711 A1 3/2019 Faulkner
 2019/0098025 A1 3/2019 Lim
 2019/0124091 A1 4/2019 Ujiie et al.
 2019/0140925 A1 5/2019 Pon et al.
 2019/0141060 A1 5/2019 Lim
 2019/0147378 A1 5/2019 Mo et al.
 2019/0166152 A1 5/2019 Steele et al.
 2019/0179490 A1 6/2019 Barday et al.
 2019/0215331 A1 7/2019 Anakata et al.
 2019/0238439 A1 8/2019 Pugh et al.
 2019/0297106 A1 9/2019 Geil et al.
 2019/0303574 A1 10/2019 Lamay et al.
 2019/0362280 A1 11/2019 Vescio
 2019/0379632 A1 12/2019 Dahlberg et al.
 2019/0391707 A1 12/2019 Ristow et al.
 2019/0392252 A1 12/2019 Fighel et al.
 2020/0053127 A1 2/2020 Brotherton et al.
 2020/0065213 A1 2/2020 Poghosyan et al.
 2020/0074084 A1 3/2020 Dorrans et al.
 2020/0092172 A1 3/2020 Kumaran et al.
 2020/0097845 A1 3/2020 Shaikh et al.
 2020/0106798 A1 4/2020 Lin
 2020/0125734 A1 4/2020 Light et al.
 2020/0183655 A1 6/2020 Barday et al.
 2020/0272763 A1 8/2020 Brannon et al.
 2020/0285737 A1 9/2020 Kraus et al.
 2020/0356689 A1 11/2020 McEnroe et al.
 2020/0356695 A1 11/2020 Brannon et al.

OTHER PUBLICATIONS

U.S. Appl. No. 17/069,151, filed Oct. 13, 2020, Information Technology Security Assessment System.
 U.S. Appl. No. 29/598,298, D835,631, filed Mar. 24, 2017, Computer Display Screen With Graphical User Interface.
 U.S. Appl. No. 29/599,622, filed Apr. 5, 2017, Computer Display With Security Ratings Graphical User Interface.
 U.S. Appl. No. 29/599,620, filed Apr. 5, 2017, Computer Display With Security Ratings Graphical User Interface.
 U.S. Appl. No. 16/015,686, filed Jun. 22, 2018, Methods for Mapping IP Addresses and Domains to Organizations Using User Activity Data.
 U.S. Appl. No. 16/543,075, filed Aug. 16, 2019, Methods for Mapping IP Addresses and Domains to Organizations Using User Activity Data.
 U.S. Appl. No. 16/738,825, filed Jan. 9, 2020, Methods for Mapping IP Addresses and Domains to Organizations Using User Activity Data.
 U.S. Appl. No. 17/146,064, filed Jan. 11, 2021, Methods for Mapping IP Addresses and Domains to Organizations Using User Activity Data.

(56)

References Cited

OTHER PUBLICATIONS

- U.S. Appl. No. 15/918,286, filed Mar. 12, 2018, Correlated Risk in Cybersecurity.
- U.S. Appl. No. 16/292,956, filed May 5, 2019, Correlated Risk in Cybersecurity.
- U.S. Appl. No. 16/795,056, filed Feb. 19, 2020, Correlated Risk in Cybersecurity.
- U.S. Appl. No. 17/179,630, filed Feb. 19, 2021, Correlated Risk in Cybersecurity.
- U.S. Appl. No. 16/170,680, filed Oct. 25, 2018, Systems and Methods for Remote Detection of Software Through Browser Webinjects.
- U.S. Appl. No. 16/688,647, filed Nov. 19, 2019, Systems and Methods for Remote Detection of Software Through Browser Webinjects.
- U.S. Appl. No. 17/000,135, filed Aug. 21, 2020, Systems and Methods for Remote Detection of Software Through Browser Webinjects.
- U.S. Appl. No. 17/401,683, filed Aug. 13, 2021, Systems and Methods for Remote Detection of Software Through Browser Webinjects.
- U.S. Appl. No. 15/954,921, filed Apr. 17, 2018, Systems and Methods for External Detection of Misconfigured Systems.
- U.S. Appl. No. 16/549,764, filed Aug. 23, 2019, Systems and Methods for Inferring Entity Relationships Via Network Communications of Users or User Devices.
- U.S. Appl. No. 16/787,650, filed Feb. 11, 2020, Systems and Methods for Inferring Entity Relationships Via Network Communications of Users or User Devices.
- U.S. Appl. No. 16/583,991, filed Sep. 26, 2019, Systems and Methods for Network Asset Discovery and Association Therefor With Entities.
- U.S. Appl. No. 17/085,550, filed Oct. 30, 2020, Systems and Methods for Network Asset Discovery and Association Therefor With Entities.
- U.S. Appl. No. 29/666,942, filed Oct. 17, 2018, Computer Display With Graphical User Interface.
- U.S. Appl. No. 16/360,641, filed Mar. 21, 2019, Systems and Methods for Forecasting Cybersecurity Ratings Based on Event-Rate Scenarios.
- U.S. Appl. No. 16/514,771, filed Jul. 17, 2019, Systems and Methods for Generating Security Improvement Plans for.
- U.S. Appl. No. 16/922,672, filed Jul. 7, 2020, Systems and Methods for Generating Security Improvement Plans for Entities.
- U.S. Appl. No. 17/307,577, filed May 4, 2021, Systems and Methods for Generating Security Improvement Plans for Entities.
- U.S. Appl. No. 29/677,306, filed Jan. 18, 2019, Computer Display With Corporate Hierarchy Graphical User Interface Computer Display With Corporate Hierarchy Graphical User Interface.
- U.S. Appl. No. 16/775,840, filed Jan. 29, 2020, Systems and Methods for Assessing Cybersecurity State of Entities Based on Computer Network Characterization.
- U.S. Appl. No. 17/018,587, filed Sep. 11, 2020, Systems and Methods for Assessing Cybersecurity State of Entities Based on Computer Network Characterization.
- U.S. Appl. No. 17/346,970, filed Jun. 14, 2021, Systems and Methods for Assessing Cybersecurity State of Entities Based on Computer Network Characterization.
- U.S. Appl. No. 17/132,512, filed Dec. 23, 2020, Systems and Methods for Rapidly Generating Security Ratings.
- U.S. Appl. No. 16/779,437, filed Jan. 31, 2020, Systems and Methods for Rapidly Generating Security Ratings.
- U.S. Appl. No. 17/119,822, filed Dec. 11, 2020, Systems and Methods for Cybersecurity Risk Mitigation and Management.
- U.S. Appl. No. 17/392,521, filed Aug. 3, 2021, Systems and Methods for Cybersecurity Risk Mitigation and Management.
- U.S. Appl. No. 16/802,232, filed Feb. 26, 2020, Systems and Methods for Improving a Security Profile of an Entity Based on Peer Security Profiles.
- U.S. Appl. No. 16/942,452, filed Jul. 29, 2020, Systems and Methods for Improving a Security Profile of an Entity Based on Peer Security Profiles.
- U.S. Appl. No. 29/736,641, filed Jun. 2, 2020, Computer Display With Peer Analytics Graphical User Interface.
- U.S. Appl. No. 17/039,675, filed Sep. 30, 2020, Systems and Methods for Determining Asset Importance in Security Risk Management.
- U.S. Appl. No. 17/320,997, filed May 14, 2021, Systems and Methods for Determining Asset Importance in Security Risk Management.
- U.S. Appl. No. 16/884,607, filed Apr. 21, 2021, Systems and Methods for Managing Cybersecurity Alerts.
- U.S. Appl. No. 17/236,594, filed Apr. 21, 2021, Systems and Methods for Managing Cybersecurity Alerts.
- Azman, Mohamed et al. Wireless Daisy Chain and Tree Topology Networks for Smart Cities. 2019 IEEE International Conference on Electrical, Computer and Communication Technologies (ICECCT). <https://ieeexplore.ieee.org/stamp/stamp.jsp?tp=&arnumber=8869252> (Year: 2019).
- Basinya, Evgeny A.; Yushmanov, Anton A. Development of a Comprehensive Security System. 2019 Dynamics of Systems, Mechanisms and Machines (Dynamics). <https://ieeexplore.ieee.org/stamp/stamp.jsp?tp=&arnumber=8944700> (Year: 2019).
- Camelo, "Botnet Cluster Identification," Sep. 2014, 90 pages.
- Camelo, "Condenser: A Graph-based Approach for Detecting Botnets," AnubisNetworks R&D, Amadora, Portugal and CENTRIA, Universidade NOVA de Lisboa, Portugal (pp. 8) Oct. 31, 2014.
- Luo, Hui; Henry, Paul. A Secure Public Wireless LAN Access Technique That Supports Walk-Up Users. GLOBECOM '03. IEEE Global Telecommunications Conference. <https://ieeexplore.ieee.org/stamp/stamp.jsp?tp=&arnumber=1258471> (Year: 2003).
- McNab, "Network Security Assessment," copyright 2004, 13 pages. Morningstar Direct, dated to 11/12/202, morningstardirect.com [online]. Retrieved Feb. 26, 2021 from internet <URL:<https://web.archive.org/web/20201112021943/https://www.morningstar.com/products/direct>> (Year: 2020).
- Rees, L. P. et al., "Decision support for cybersecurity risk planning." Decision Support Systems 51.3 (2011):pp. 493-505.
- Santos, J. R. et al., "A framework for linking cybersecurity metrics to the modeling of macroeconomic interdependencies." Risk Analysis: An International Journal (2007) 27.5, pp. 1283-1297.
- Search Query Report form IP.com (performed Apr. 27, 2020).
- Seigneur et al., A Survey of Trust and Risk Metrics for a BYOD Mobile Worker World: Third International Conference on Social Eco-Informatics, 2013, 11 pages.
- Seneviratne et al., "SSIDs in the Wild: Extracting Semantic Information from WiFi SSIDs" HAL archives-ouvertes.fr, HAL Id: hal-01181254, Jul. 29, 2015, 5 pages.
- The Dun & Bradstreet Corp. Stock Report, Standard & Poor's, Jun. 6, 2009, 8 pages.
- Winship, C., "Models for sample selection bias", Annual review of sociology, 18(1) (Aug. 1992), pp. 327-350.
- "About Neo4j," 1 page.
- "Agreed Upon Procedures," Version 4.0, BITS, The Financial Institution Shared Assessments Program, Assessment Guide, Sep. 2008, 56 pages.
- "Amazon Mechanical Turk," accessed on the internet at <https://www.mturk.com/>; 7 pages.
- "An Executive View of IT Governance," IT Governance Institute, 2009, 32 pages.
- "Assessing Risk in Turbulent Times," A Workshop for Information Security Executives, Glassmeyer/McNamee Center for Digital Strategies, Tuck School of Business at Dartmouth, Institute for Information Infrastructure Protection, 2009, 17 pages.
- "Assuring a Trusted and Resilient Information and Communications Infrastructure," Cyberspace Policy Review, May 2009, 76 pages.
- "Computer Network Graph," <http://www.opte.org>; 1 page.
- "Creating Transparency with Palantir," accessed on the internet at <https://www.youtube.com/watch?v=8cbGChfagUA>; Jul. 5, 2012; 1 page.
- "Gephi (gephi.org)," accessed on the internet at <https://web.archive.org/web/20151216223216/https://gephi.org/>; Dec. 16, 2015; 1 page.

(56)

References Cited

OTHER PUBLICATIONS

- “Master Security Criteria,” Version 3.0, BITS Financial Services Security Laboratory, Oct. 2001, 47 pages.
- “Mile 2 CPTe Maltego Demo,” accessed on the internet at <https://www.youtube.com/watch?v=o2oNKOUzP0U>; Jul. 12, 2012; 1 page.
- “Neo4j (neo4j.com),” accessed on the internet at <https://web.archive.org/web/20151220150341/http://neo4j.com:80/developer/guide-data-visualization/>; Dec. 20, 2015; 1 page.
- “Palantir Cyber: Uncovering malicious behavior at petabyte scale,” accessed on the internet at https://www.youtube.com/watch?v=_EhYezVO6EE; Dec. 21, 2012; 1 page.
- “Palantir.com,” accessed on the internet at <http://www.palantir.com/>; Dec. 2015; 2 pages.
- Gilgur et al., “Percentile-Based Approach to Forecasting Workload Growth,” Proceedings of CMG’15 Performance and Capacity International Conference by the Computer Measurement Group. No. 2015 (Year:2015).
- “Plugging the Right Holes,” Lab Notes, MIT Lincoln Library, Posted Jul. 2008, retrieved Sep. 14, 2010 from <http://www.ll.mit.edu/publications/labnotes/pluggingtherightholes/>, 2 pages.
- “Rapid7 Nexpose Vulnerability Scanner,” accessed on the internet at <https://www.rapid7.com/products/nexpose/download/>, 5 pages.
- “Report on Controls Placed in Operation and Test of Operating Effectiveness,” EasCorp, Jan. 1-Dec. 31, 2008, prepared by Crowe Horwath, 58 pages.
- “Shared Assessments: Getting Started,” BITS, 2008, 4 pages.
- “Tenable Nessus Network Vulnerability Scanner,” accessed on the internet at <https://www.tenable.com/products/nessus/nessus-professional/>; 13 pages.
- “Twenty Critical Controls for Effective Cyber Defense: Consensus Audit,” Version 2.3, Nov. 13, 2009, retrieved on Apr. 9, 2010 from <http://www.sans.org/critical-security-controls/print.php>, 52 pages.
- 2009 Data Breach Investigations Report, study conducted by Verizon Business RISK Team, 52 pages.
- Application as filed, PAIR transaction history and pending claims of U.S. Appl. No. 13/240,572 as of Nov. 18, 2015, 45 pages.
- Artz, Michael Lyle, “NetSPA: A Network Security Planning Architecture,” Massachusetts Institute of Technology, May 24, 2002, 97 pages.
- Bhilare et al., “Protecting Intellectual Property and Sensitive Information in Academic Campuses from Trusted Insiders: Leveraging Active Directory,” SIGUCC, Oct. 2009 (5 pages).
- Bitsight, “Cyber Security Myths Versus Reality: How Optimism Bias Contributes to Inaccurate Perceptions of Risk,” Jun. 2015, Dimensional Research, pp. 1-9.
- Borgatti, et al., “On Social Network Analysis in a Supply Chain Context,” *Journal of Supply Chain Management*; 45(2): 5-22; Apr. 2009, 18 pages.
- Boyer, Stephen, et al., “Playing with Blocks: SCAP-Enable Higher-Level Analyses,” MIT Lincoln Laboratory, 5th Annual IT Security Automation Conference, Oct. 26-29, 2009, 35 pages.
- Browne, Niall, et al., “Shared Assessments Program AUP and SAS70 Frequently Asked Questions,” BITS, 4 pages.
- Buckshaw, Donald L., “Use of Decision Support Techniques for Information System Risk Management,” submitted for publication in Wiley’s *Encyclopedia of Quantitative Risk Assessment* in Jan. 2007, 11 pages.
- Buehler, Kevin S., et al., “Running with risk,” *The McKinsey Quarterly*, No. 4, 2003, pp. 40-49.
- Camelo, “Botnet Cluster Identification,” *Faculdade de Ciências e Tecnologia, Universidade Nova de Lisboa*, pp. 1-88, Sep. 2014.
- Camelo et al., “Condenser: A Graph-based Approach for Detecting Botnets,” *AnubisNetworks R&D, Amadora, Portugal and CENTRIA, Universidade NOVA de Lisboa, Portugal* (pp. 8) Oct. 31, 2014.
- Carstens, et al., “Modeling Company Risk and Importance in Supply Graphs,” *European Semantic Web Conference 2017: The Semantic Web* pp. 18-31.
- Chu, Matthew, et al., “Visualizing Attack Graphs, Reachability, and Trust Relationships with Navigator,” MIT Lincoln Library, *VizSEC ’10, Ontario, Canada*, Sep. 14, 2010, 12 pages.
- Chuvakin, “SIEM: Moving beyond compliance”, RSA White Paper, 2010, 16 pages.
- Computer Network Graph-Bees, http://bioteams.com/2007/04/30/visualizing_complex_networks.html, date accessed Sep. 28, 2016, 2 pages.
- Computer Network Graph-Univ. of Michigan, <http://people.cst.cmich.edu/liao1q/research.shtml>, date accessed Sep. 28, 2016, 5 pages.
- Crowther, Kenneth G., et al., “Principles for Better Information Security through More Accurate, Transparent Risk Scoring,” *Journal of Homeland Security and Emergency Management*, vol. 7, Issue 1, Article 37, 2010, 20 pages.
- Davis, Lois M., et al., “The National Computer Security Survey (NCSS) Final Methodology,” Technical report prepared for the Bureau of Justice Statistics, Safety and Justice Program, RAND Infrastructure, Safety and Environment (ISE), 2008, 91 pages.
- Dillon-Merrill, PhD., Robin L, et al., “Logic Trees: Fault, Success, Attack, Event, Probability, and Decision Trees,” *Wiley Handbook of Science and Technology for Homeland Security*, 13 pages.
- Dun & Bradstreet Corp. Stock Report, Standard & Poor’s, Jun. 6, 2009, 8 pages.
- Dun & Bradstreet, *The DUNSRight Quality Process: Power Behind Quality Information*, 24 pages.
- Edmonds, Robert, “ISC Passive DNS Architecture”, Internet Systems Consortium, Inc., Mar. 2012, 18 pages.
- Equifax Inc. Stock Report, Standard & Poor’s, Jun. 6, 2009, 8 pages.
- Gundert, Levi, “Big Data in Security—Part III: Graph Analytics,” accessed on the Internet at <https://blogs.cisco.com/security/big-data-in-security-part-iii-graph-analytics>; Cisco Blog, Dec. 2013, 8 pages.
- Hachem, Sara; Toninelli, Alessandra; Pathak, Animesh; Issany, Valerie. “Policy-Based Access Control in Mobile Social Ecosystems,” 2011 IEEE International Symposium on Policies for Distributed Systems and Networks (POLICY). <http://ieeexplore.ieee.org/stamp/stamp.jsp?arnumber=5976796>. 8 pages.
- Hacking Exposed 6, S. McClure et al., copyright 2009, 37 pages.
- Ingols, Kyle, et al., “Modeling Modern Network Attacks and Countermeasures Using Attack Graphs,” MIT Lincoln Laboratory, 16 pages.
- Ingols, Kyle, et al., “Practical Attack Graph Generation for Network Defense,” MIT Lincoln Library, IEEE Computer Society, Proceedings of the 22nd Annual Computer Security Applications Conference (ACSAC’06), 2006, 10 pages.
- Ingols, Kyle, et al., “Practical Experiences Using SCAP to Aggregate CND Data,” MIT Lincoln Library, Presentation to NIST SCAP Conference, Sep. 24, 2008, 59 pages.
- Jean, “Cyber Security: How to use graphs to do an attack analysis,” accessed on the internet at <https://linkurio.us/blog/cyber-security-use-graphs-attack-analysis/>; Aug. 2014, 11 pages.
- Jin et al., “Identifying and tracking suspicious activities through IP gray space analysis”, *MineNet*, Jun. 12, 2007, 6 pages.
- Johnson, Eric, et al., “Information Risk and the Evolution of the Security Rating Industry,” Mar. 24, 2009, 27 pages.
- Joslyn, et al., “Massive Scale Cyber Traffic Analysis: A Driver for Graph Database Research,” Proceedings of the First International Workshop on Graph Data Management Experience and Systems (GRADES 2013), 6 pages.
- KC Claffy, “Internet measurement and data analysis: topology, workload, performance and routing statistics,” accessed on the Internet at <http://www.caida.org/publications/papers/1999/Nae/Nae.html>, NAE ’99 workshop, 1999, 22 pages.
- Li et al., “Finding the Linchpins of the Dark Web: a Study on Topologically Dedicated Hosts on Malicious Web Infrastructures”, IEEE, 2013, 15 pages.
- Lippmann, Rich, et al., “NetSPA: a Network Security Planning Architecture,” MIT Lincoln Laboratory, 11 pages.
- Lippmann, Richard, et al., “Validating and Restoring Defense in Depth Using Attack Graphs,” MIT Lincoln Laboratory, 10 pages.
- Lippmann, RP, et al., “An Annotated Review of Papers on Attack Graphs,” Project Report IA-1, Lincoln Laboratory, Massachusetts Institute of Technology, Mar. 31, 2005, 39 pages.
- Lippmann, RP, et al., “Evaluating and Strengthening Enterprise Network Security Using Attack Graphs,” Project Report IA-2, MIT Lincoln Laboratory, Oct. 5, 2005, 96 pages.

(56)

References Cited

OTHER PUBLICATIONS

- Maltego XL, accessed on the Internet at <https://www.paterva.com/web7/buy/maltego-clients/maltego-xl.php>, 5 pages.
- Massimo Candela, "Real-time BGP Visualisation with BGPlay," accessed on the Internet at https://labs.ripe.net/Members/massimo_candela/real-time-bgp-visualisation-with-bgplay, Sep. 30, 2015, 8 pages.
- Maxmind, <https://www.maxmind.com/en/about-maxmind>, <https://www.maxmind.com/en/geoip2-isp-database>, date accessed Sep. 28, 2016, 3 pages.
- McNab, "Network Security Assessment," copyright 2004, 55 pages.
- Method Documentation, CNSS Risk Assessment Tool Version 1.1, Mar. 31, 2009, 24 pages.
- Moradi, et al., "Quantitative Models for Supply Chain Management," IGI Global, 2012, 29 pages.
- Netcraft, www.netcraft.com, date accessed Sep. 28, 2016, 2 pages.
- NetScanTools Pro, <http://www.netscantools.com/nstpromain.html>, date accessed Sep. 28, 2016, 2 pages.
- Network Security Assessment, C. McNab, copyright 2004, 13 pages.
- Noel, et al., "Big-Data Architecture for Cyber Attack Graphs, Representing Security Relationships in NoSQL Graph Databases," The MITRE Corporation, 2014, 6 pages.
- Nye, John, "Avoiding Audit Overlap," Moody's Risk Services, Presentation, Source Boston, Mar. 14, 2008, 19 pages.
- Pending claims for U.S. Appl. No. 14/021,585.
- U.S. Appl. No. 13/240,572.
- U.S. Appl. No. 14/021,585.
- U.S. Appl. No. 14/944,484.
- U.S. Appl. No. 61/386,156.
- Paxson, Vern, "How The Pursuit of Truth Led Me To Selling Viagra," EECS Department, University of California, International Computer Science Institute, Lawrence Berkeley National Laboratory, Aug. 13, 2009, 68 pages.
- Proposal and Award Policies and Procedures Guide, Part I—Proposal Preparation & Submission Guidelines GPG, The National Science Foundation, Feb. 2009, 68 pages.
- Provos et al., "The Ghost In the Browser Analysis of Web-based Malware", 2007 (9 pages).
- Rare Events, Oct. 2009, JASON, The MITRE Corporation, Oct. 2009, 104 pages.
- "Report to the Congress on Credit Scoring and Its Effects on the Availability and Affordability of Credit," Board of Governors of the Federal Reserve System, Aug. 2007, 304 pages.
- RFC 1834, <https://tools.ietf.org/html/rfc1834>, date accessed Sep. 28, 2016, 7 pages.
- RFC 781, <https://tools.ietf.org/html/rfc781>, date accessed Sep. 28, 2016, 3 pages.
- RFC 950, <https://tools.ietf.org/html/rfc950>, date accessed Sep. 28, 2016, 19 pages.
- RFC 954, <https://tools.ietf.org/html/rfc954>, date accessed Sep. 28, 2016, 5 pages.
- SamSpade Network Inquiry Utility, <https://www.sans.org/reading-room/whitepapers/tools/sam-spade-934>, date accessed Sep. 28, 2016, 19 pages.
- SBIR Phase I: Enterprise Cyber Security Scoring, CyberAnalytix, LLC, <http://www.nsf.gov/awardsearch/showAward.do?AwardNumber=I013603>, Apr. 28, 2010, 2 pages.
- Security Warrior, Cyrus Peikari, Anton, Chapter 8: Reconnaissance, 6 pages.
- Snort Intrusion Monitoring System, <http://archive.oreilly.com/pub/h/1393>, date accessed Sep. 28, 2016, 3 pages.
- Srivastava, Divesh; Velegrakis, Yannis. "Using Queries to Associate Metadata with Data," IEEE 23rd International Conference on Data Engineering. Pub. Date: 2007. <http://ieeexplore.ieee.org/stamp/stamp.jsp?arnumber=4221823>, 3 pages.
- Stone-Gross, Brett, et al., "FIRE: Finding Rogue Networks," 10 pages.
- Taleb, Nassim N., et al., "The Six Mistakes Executives Make in Risk Management," Harvard Business Review, Oct. 2009, 5 pages.
- The CIS Security Metrics v1.0.0, The Center for Internet Security, May 11, 2009, 90 pages.
- The Fair Credit Reporting Act (FCRA) of the Federal Trade Commission (FTC), Jul. 30, 2004, 86 pages.
- The Financial Institution Shared Assessments Program, Industry Positioning and Mapping Document, BITS, Oct. 2007, 44 pages.
- Wagner, et al., "Assessing the vulnerability of supply chains using graph theory," Int. J. Production Economics 126 (2010) 121-129.
- Wikipedia, <https://en.wikipedia.org/wiki/Crowdsourcing>, date accessed Sep. 28, 2016, 25 pages.
- Williams, Leevar, et al., "An Interactive Attack Graph Cascade and Reachability Display," MIT Lincoln Laboratory, 17 pages.
- Williams, Leevar, et al., "Garnet: A Graphical Attack Graph and Reachability Network Evaluation Tool," MIT Lincoln Library, VizSEC 2009, pp. 44-59.
- U.S. Appl. No. 15/377,574 9,705,932, filed Dec. 13, 2016, Methods and Systems for Creating, De-Duplicating, and Accessing Data Using an Object Storage System.
- U.S. Appl. No. 14/021,585 9,438,615, Published as: US2015/0074579, filed Sep. 9, 2013, Security Risk Management.
- U.S. Appl. No. 15/216,955 Published as: US2016/0330231, filed Jul. 22, 2016, Methods for Using Organizational Behavior for Risk Ratings.
- U.S. Appl. No. 15/239,063 Published as: US2017/0093901, filed Aug. 17, 2016, Security Risk Management.
- U.S. Appl. No. 16/405,121 Published as: US2019/0260791, filed May 7, 2019, Methods for Using Organizational Behavior for Risk Ratings.
- U.S. Appl. No. 17/025,930, filed Sep. 18, 2020, Methods for Using Organizational Behavior for Risk Ratings.
- U.S. Appl. No. 13/240,572 Published as: US2016/0205126, filed Sep. 22, 2011, Information Technology Security Assessment System.
- U.S. Appl. No. 14/944,484 9,973,524 Published as: US2016/0323308, filed Nov. 18, 2015, Information Technology Security Assessment System.
- U.S. Appl. No. 15/142,677 9,830,569 Published as: US/2016/0239772, filed Apr. 29, 2016, Security Assessment Using Service Provider Digital Asset Information.
- U.S. Appl. No. 17/069,151 Published as: US/2021/0211454, filed Oct. 13, 2020, Information Technology Security Assessment System.
- U.S. Appl. No. 15/134,845 9,680,858, filed Apr. 21, 2016, Annotation Platform for a Security Risk System.
- U.S. Appl. No. 15/044,952 Published as: US2017/0236077, filed Feb. 16, 2016, Relationships Among Technology Assets and Services and the Entities Responsible for Them.
- U.S. Appl. No. 15/089,375 10,176,445 Published as: US2017/0236079, filed Apr. 1, 2016, Relationships Among Technology Assets and Services and the Entities Responsible for Them.
- U.S. Appl. No. 29/598,298 D835,631, filed Mar. 24, 2017, Computer Display Screen With Graphical User Interface.
- U.S. Appl. No. 29/598,299 D818,475, filed Mar. 24, 2017, Computer Display With Security Ratings Graphical User Interface.
- U.S. Appl. No. 29/599,622 D847169, filed Apr. 5, 2017, Computer Display With Security Ratings Graphical User Interface.
- U.S. Appl. No. 29/599,620 D846,562, filed Apr. 5, 2017, Computer Display With Security Ratings Graphical User Interface.
- U.S. Appl. No. 16/015,686 10,425,380, filed Jun. 22, 2018, Methods for Mapping IP Addresses and Domains to Organizations Using User Activity Data.
- U.S. Appl. No. 16/543,075 10,554,619, filed Aug. 16, 2019, Methods for Mapping IP Addresses and Domains to Organizations Using User Activity Data.
- U.S. Appl. No. 16/738,825 10,893,021, filed Aug. 16, 2019, Methods for Mapping IP Addresses and Domains to Organizations Using User Activity Data.
- U.S. Appl. No. 17/146,064 Published as: US2021/0218702, filed Jan. 11, 2021, Methods for Mapping IP Addresses and Domains to Organizations Using User Activity Data.
- U.S. Appl. No. 15/918,286 10,257,219, filed Mar. 12, 2018, Correlated Risk in Cybersecurity.

(56)

References Cited

OTHER PUBLICATIONS

U.S. Appl. No. 16/292,956 10,594,723, filed Mar. 5, 2019, Correlated Risk in Cybersecurity.

U.S. Appl. No. 16/795,056 10,931,705, filed Feb. 19, 2020, Correlated Risk in Cybersecurity.

U.S. Appl. No. 17/179,630 Published as US 2021/0176269, filed Feb. 19, 2021, Correlated Risk in Cybersecurity.

U.S. Appl. No. 16/170,680 10,521,583, filed Oct. 25, 2018, Systems and Methods for Remote Detection of Software Through Browser Webinjects.

U.S. Appl. No. 16/688,647, 10,776,483, filed Nov. 19, 2019, Systems and Methods for Remote Detection of Software Through Browser Webinjects.

U.S. Appl. No. 17/000,135 11,126,723, filed Nov. 19, 2019, Systems and Methods for Remote Detection of Software Through Browser Webinjects.

U.S. Appl. No. 17/401,683 Published as US 2021/0374243, filed Aug. 13, 2021, Systems and Methods for Remote Detection of Software Through Browser Webinjects.

U.S. Appl. No. 15/954,921 10812520, filed Apr. 17, 2018, Systems and Methods for External Detection of Misconfigured Systems.

U.S. Appl. No. 16/549,764, Published as: US2021/0058421, filed Aug. 23, 2019, Systems and Methods for Inferring Entity Relationships Via Network Communications of Users or User Devices.

U.S. Appl. No. 16/787,650 10,749,893, filed Feb. 11, 2020, Systems and Methods for Inferring Entity Relationships Via Network Communications of Users or User Devices.

U.S. Appl. No. 16/583,991 10,848,382, filed Sep. 26, 2019, Systems and Methods for Network Asset Discovery and Association Thereof With Entities.

U.S. Appl. No. 17/085,550 11,329,878 Published as: US2021/0099347, filed Oct. 30, 2020, Systems and Methods for Network Asset Discovery and Association Thereof With Entities.

U.S. Appl. No. 29/666,942 D892135, filed Oct. 17, 2018, Computer Display With Graphical User Interface.

U.S. Appl. No. 16/360,641 11,200,323, filed Mar. 21, 2019, Systems and Methods for Forecasting Cybersecurity Ratings Based on Event-Rate Scenarios.

U.S. Appl. No. 17/523,166 Published as US 2022/0121753, Systems and Methods for Forecasting Cybersecurity Ratings Based On Event-Rate Scenarios.

U.S. Appl. No. 16/514,771 10,726,136, filed Jul. 17, 2019, Systems and Methods for Generating Security Improvement Plans for Entities.

U.S. Appl. No. 16/922,673, 11,030,325, filed Jul. 7, 2020, Systems and Methods for Generating Security Improvement Plans for Entities.

U.S. Appl. No. 17/307,577 Published as: US2021/0326449, filed May 4, 2021, Systems and Methods for Generating Security Improvement Plans for Entities.

U.S. Appl. No. 29/677,306 D905702, filed Jan. 18, 2019, Computer Display Screen With Corporate Hierarchy Graphical User Interface.

U.S. Appl. No. 16/775,840 10,791,140, filed Jan. 29, 2020, Systems and Methods Assessing Cybersecurity State of Entities Based on Computer Network Characterization.

U.S. Appl. No. 17/018,587 11,050,779, filed Sep. 11, 2020, Systems and Methods for Assessing Cybersecurity State of Entities Based on Computer Network Characterization.

U.S. Appl. No. 16/779,437 10,893,067 Published as: US2021/0243221, filed Jan. 31, 2020, Systems and Methods for Rapidly Generating Security Ratings.

U.S. Appl. No. 17/132,512 Published as US 2021/0243221, Systems and Methods for Rapidly Generating Security Ratings.

U.S. Appl. No. 17/119,822 11,122,073, filed Dec. 11, 2020, Systems and Methods for Cybersecurity Risk Mitigation and Management.

U.S. Appl. No. 29/815,855, filed Nov. 17, 2021, Computer Display With A Graphical User Interface for Cybersecurity Risk Management.

U.S. Appl. No. 17/392,521 Published as US 2022/0191232, filed Aug. 3, 2021, Systems and Methods for Cybersecurity Risk Mitigation and Management.

U.S. Appl. No. 16/802,232 10,764,298, filed Feb. 26, 2020, Systems and Methods for Improving a Security Profile of an Entity Based on Peer Security Profiles.

U.S. Appl. No. 19/942,452 11,265,330, filed Jul. 29, 2020, Systems and Methods for Improving a Security Profile of an Entity Based on Peer Security Profiles.

U.S. Appl. No. 29/725,724, filed Feb. 26, 2020, Computer Display With Risk Vectors Graphical User Interface.

U.S. Appl. No. 29/736,641 D937870, filed Jun. 2, 2020, Computer Display With Peer Analytics Graphical User Interface.

U.S. Appl. No. 17/039,675 11,032,244 Published as US 2021/0099428, filed Sep. 30, 2020, Systems and Methods for Determining Asset Importance in Security Risk Management.

U.S. Appl. No. 17/320,997 Published as US 2021/0344647, filed May 14, 2021, Systems and Methods for Determining Asset Importance in Security Risk Management.

U.S. Appl. No. 16/884,607 11,023,585, filed May 27, 2020, Systems and Methods for Managing Cybersecurity Alerts.

U.S. Appl. No. 17/236,594 Published as US 2021/0374246, filed Apr. 21, 2021, Systems and Methods for Managing Cybersecurity Alerts.

U.S. Appl. No. 17/710,168, filed Mar. 31, 2022, Systems and Methods for Assessing Cybersecurity Risk in a Work From Home Environment.

U.S. Appl. No. 17/945,337, filed Sep. 15, 2022, Systems and Methods for Precomputation of Digital Asset Inventories.

U.S. Appl. No. 17/856,217, filed Jul. 1, 2022, Systems and Methods for Accelerating Cybersecurity Assessments.

Chernyshev, M. et al., "On 802.11 Access Point Locatability and Named Entity Recognition in Service Set Identifiers", IEEE Trans. on Info. and Sec., vol. 11 No. 3 (Mar. 2016).




FIG. 1A




FIG. 1B




FIG. 2




FIG. 3

SYSTEMS AND METHODS FOR EXTERNAL DETECTION OF MISCONFIGURED SYSTEMS

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of and claims priority to and the benefit of U.S. patent application Ser. No. 15/954,921, titled "SYSTEMS AND METHODS FOR EXTERNAL DETECTION OF MISCONFIGURED SYSTEMS," filed on Apr. 17, 2018, the disclosure of which is incorporated herein by reference in its entirety.

TECHNICAL FIELD

The following disclosure is directed to methods and systems for detecting vulnerable systems, and, more specifically, methods and systems for detecting vulnerable systems based on domain name properties.

BACKGROUND

In an age of increased cybercrime and varied cybersecurity efforts, detecting vulnerabilities before, or within real-time, a security flaw is exploited can be a true business advantage to companies, governments, institutions, and individuals. In many instances, there are benign but misconfigured systems having these security flaws that become targets for parties with nefarious intentions. Every day, seemingly endless types and numbers of malignant actors exploit security flaws for the purpose of theft (both monetary and of data), espionage, frustration (e.g., denial of service attacks and mass spamming), terrorism, and more. However, the resources necessary to get ahead of these potential threats can be astounding and unfeasible.

SUMMARY

Domain names on the Internet can be a specific source of security flaws and, often, speed in detecting exploitation of domain names becomes crucial to overcoming attacks. To track and detect security flaws in real time, or near real time, systems and methods can monitor communication traffic and extract metadata related to the traffic and/or domain names to detect vulnerable systems.

In accordance with an embodiment of the disclosure, a computer-implemented method is provided for external detection of a vulnerable system coupled to a communication network. The method can include measuring communication traffic on the communication network to identify one or more domain names, which in turn can originate from server systems in the communication network. The method can further include identifying the domain names based on metadata from the domain names and/or the measured communication traffic, where each domain name has an associated property indicative of its vulnerability. The method can further include determining whether any one (or more) of the domain names is registered at a domain name registry and, if the domain name is not registered, registering the domain name.

Embodiments of the methods can include one or more of the following features. Domain names having the property indicative of vulnerability can be: (i) an unregistered domain name, (ii) a malfunctioning domain name, (iii) an abandoned domain name, and/or (iv) an algorithm-generated domain

name. The vulnerable system can be a malware-infected server system and/or, a misconfigured server system.

In some embodiments, the metadata can include a geographical location associated with each domain name. If so, the registration of the domain name based on the extracted metadata includes registering the domain name based on a high frequency of domain names having a property indicative of vulnerability in a particular geographical location. The method can further include associating the registered domain name with a server system configured to monitor communication traffic to the registered domain name, and, in some instances, detecting the vulnerable system associated with the registered domain name. Measuring communication traffic to each of the plurality of domain names can further include receiving communication traffic data from one or more Internet service providers (ISP), comparing relative magnitude of communication traffic to an expected amount of traffic, and/or measuring a frequency of communication traffic to the domain name.

In accordance with another embodiment of the disclosure, a system including one or more computer systems programmed to perform operations is provided. The operations include measuring communication traffic in the communication network to identify one or more domain names, where the communication traffic originates from server systems in the communication network. The domain names are based on metadata from (i) the domain names and/or (ii) the measured communication traffic, where each domain name has an associated property indicative of its vulnerability. The operations further include determining whether any one (or more) of the domain names is registered at a domain name registry, and if the domain name is not registered, registering the domain name.

Embodiments of the systems can include one or more of the following features. Domain names having the property indicative of vulnerability can be: (i) an unregistered domain name, (ii) a malfunctioning domain name, (iii) an abandoned domain name, and/or (iv) an algorithm-generated domain name. The vulnerable system can be a malware-infected server system and/or, a misconfigured server system.

In some embodiments, the metadata can include a geographical location associated with each domain name. If so, the registration of the domain name based on the extracted metadata includes registering the domain name based on a high frequency of domain names having a property indicative of vulnerability in a particular geographical location. The method can further include associating the registered domain name with a server system configured to monitor communication traffic to the registered domain name, and, in some instances, detecting the vulnerable system associated with the registered domain name. Measuring communication traffic to each of the plurality of domain names can further include receiving communication traffic data from one or more Internet service providers (ISP), comparing relative magnitude of communication traffic to an expected amount of traffic, and/or measuring a frequency of communication traffic to the domain name.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGS. 1A-1B are flowcharts of exemplary embodiments of methods for detecting vulnerable systems coupled to a communication network.

FIG. 2 is a diagram of an exemplary embodiment of a system for detecting vulnerable systems coupled to a communication network.

FIG. 3 is a block diagram of an example computer system that may be used in implementing the systems and methods described herein.

DETAILED DESCRIPTION

Disclosed herein are exemplary embodiments of systems and methods for detecting vulnerable systems in communication networks. These vulnerable systems can include one or more computing systems, one or more server systems, or other networked systems. In many instances, vulnerable systems are associated with domain names on the Internet. “Domain names,” as used herein, may refer to registered or unregistered names, addresses, and/or links to a resource on the Internet.

Some domain names may be associated with vulnerable resources. In some embodiments, an algorithm may generate links to domain names that are not registered or generated in error. For example, an algorithm that links to “google.com” may incorrectly generate links such as “goooooogle.com” or “goggle.com.” In another embodiment, an application developer may register a domain name for a legitimate service or business. If the business associated with the domain name closes, and the domain name is abandoned, the domain name may become expired or “dropped” from the registry. If so, the registry may delete the domain name (de-register) and the domain name may become available to another party. In another embodiment, a registered domain name may be associated with a misconfigured system. For example, the misconfigured system may be operating with security flaws that open the system to security risks. In another embodiment, parties acting with nefarious intentions (criminals or criminal groups, malignant state-sponsored actors, etc.) may register domain names for their own purposes (e.g., malware, botnets, etc.). In another embodiment, an anti-virus software program may try to contact domain names repeatedly based on some acquired misinformation. If so, that domain name will have repeat incoming traffic. Examples of detection of botnets is discussed in *CONDENSER: A Graph-Based Approach for Detecting Botnets*, by Camelo et al., and in *Botnet Cluster Identification* (Master Thesis), by Pedro Camelo, each of which are incorporated herein by reference.

The below described exemplary systems and methods are configured to identify such domain names, and in some embodiments, identify one or more vulnerable systems associated with such domain names. For the purpose of clarity and conciseness, the methods and systems of FIGS. 1A-3 are discussed below together.

Detection Systems and Methods

FIGS. 1A-1B are flowcharts of exemplary embodiments of methods for detecting vulnerable systems coupled to a communication network. FIG. 2 is a diagram of an exemplary embodiment of an environment 200 in which a system for detecting vulnerable systems coupled to, or part of, a communication network operates.

In step 102, the detection system 202 measures communication traffic in the communication network to identify a plurality of domain names of interest. The communication traffic can be originating from one or more external (separate from the system 200) server systems 204 in the communication network. External server systems can include company servers, desktop computers, Internet of things (IoT) devices, mobile devices, or any other device on external networks. In some embodiments, the communication traffic can be provided by one or more Internet service providers

(ISPs). Many ISPs track communication traffic to domain names for standard business purposes. However, the monitoring and/or measuring of communication traffic is typically associated with large amounts of data. Thus, in some embodiments, metadata related to the measured communication traffic may be extracted from the communication traffic in the interest of efficiency. Meta data can include geographical location of the communication traffic, frequency of the communication traffic, magnitude of the communication traffic, aggregated counters of a number of unique Internet Protocol (IP) addresses per country, a number of events observed per period (e.g., every hour), a ratio between unique IPs versus a sum of a portion or all communication traffic. Efficiency may be crucial in some instances where a domain name may be associated with a flawed, but important Internet resource that is vulnerable to malware. In some embodiments, the ISPs can provide a list of domain names that are the subject of network traffic. This list of domain names can be analyzed to identify those that may be addresses for vulnerable systems. In some embodiments, the detection of nonexistent domain names being contacted by a group of devices does not necessarily map to malicious behavior. In some cases, the behavior can be mapped to a control failure associated with a software or service dependent on those domains. When that control failure occurs, the affected devices can become vulnerable to malicious actors that can potentially acquire the nonexistent domains and gain control over the associated devices.

In step 104, the detection system 202 identifies one or more domain names (1 through N) that each are vulnerable with regard to some property or attribute. For example, the domain name can have the following conditions associated therewith: (i) an unregistered domain name, (ii) a malfunctioning domain name, (iii) an abandoned domain name, and/or (iv) an algorithm-generated domain name. In some embodiments, the domain names can be identified based on the metadata extracted from the measured communication traffic and/or the domain names themselves. For example, a domain name may be identified based on statistical anomalies regarding traffic emanating from or directed to the domain name, or suspicious IP header information extracted from packets directed to the domain name. Examples include identification of a group of systems or devices attempting to contact nonexistent domain names at a given frequency, from a given set of geographies, and/or using specific protocols and/or payloads. This group of devices interacting with one or more domains, using a similar pattern and/or frequency, may be associated with automated traffic generated by malware, or may be caused by mis-configurations of machine-to-machine communication.

One important advantage to extracting metadata of the communication traffic is that much (or all) of the data from the traffic and associated parameters do not have to be stored. Instead, a detection system 202 can include a streaming server 206 that executes queries on the data in real time or near real time. In some embodiments, the extracted metadata can include geographical information related to the communication traffic. If so, for example, the detection system 202 can detect a group of domain names associated with a particular geography (such a city or region of a country) with significant incoming traffic. In some embodiments, the relative magnitude of traffic (or “cluster” of traffic) may be measured to identify domain names. For example, if one or a handful of parties are pinging “gogle.com,” it is likely a mistake (such as mistyping). However, if thousands of parties are pinging the same domain name “gogle.com,” the detection system 202 may identify that

5

domain name as a candidate for registration. Thus, the measured traffic may be compared against an expected amount of traffic for the purpose of detection. Measures of expected amounts of traffic may be available from the ISPs themselves or other services. In another embodiment, the frequency of the traffic may be measured. An anomalous pattern of contacting a domain name may signify a vulnerability. For example, if the system **202** detects a group of devices periodically attempting to contact a domain, or group of domains, at a given frequency (for example, each hour), such a detection can be indicative of automated malicious traffic.

In some embodiments, the traffic data and/or data regarding the domain names may be stored and analyzed by accessing the storage **208**. By determining one or more domain names having a vulnerable property or attribute, the detection system can ultimately detect and/or identify one or more vulnerable systems **210** associated with the domain name.

In step **106**, the detection system **202** is configured to determine whether each domain name is registered at a domain name registry. In step **108**, if the domain name is not registered, then the system **202** is configured to register the domain name. Once registered, in step **110**, the system **202** can associate the registered domain name with a server system **212** configured to monitor communication traffic to the registered domain name. The server system **212** may be controlled by the detection system **202**. In step **112**, the detection system **202** can identify and/or detect one or more vulnerable systems associated with the registered domain name. Once the domain name (e.g., domain name **2** of FIG. **2**) has been acquired and configured on the server system **212**, the vulnerable system(s) **210** will typically contact the domain on the server system **212** using a specific network protocol and payload. Inspecting the network request by the vulnerable system **210** allows the detection system **202** to associate the vulnerable system(s) with malicious or other anomalous behavior that triggered the domain communication.

Computer-Based Implementations

In some examples, some or all of the processing described above can be carried out on a personal computing device, on one or more centralized computing devices, or via cloud-based processing by one or more servers. In some examples, some types of processing occur on one device and other types of processing occur on another device. In some examples, some or all of the data described above can be stored on a personal computing device, in data storage hosted on one or more centralized computing devices, or via cloud-based storage. In some examples, some data are stored in one location and other data are stored in another location. In some examples, quantum computing can be used. In some examples, functional programming languages can be used. In some examples, electrical memory, such as flash-based memory, can be used.

FIG. **3** is a block diagram of an example computer system **300** that may be used in implementing the technology described in this document. General-purpose computers, network appliances, mobile devices, or other electronic systems may also include at least portions of the system **300**. The system **300** includes a processor **310**, a memory **320**, a storage device **330**, and an input/output device **340**. Each of the components **310**, **320**, **330**, and **340** may be interconnected, for example, using a system bus **350**. The processor **310** is capable of processing instructions for execution

6

within the system **300**. In some implementations, the processor **310** is a single-threaded processor. In some implementations, the processor **310** is a multi-threaded processor. The processor **310** is capable of processing instructions stored in the memory **320** or on the storage device **330**.

The memory **320** stores information within the system **300**. In some implementations, the memory **320** is a non-transitory computer-readable medium. In some implementations, the memory **320** is a volatile memory unit. In some implementations, the memory **320** is a nonvolatile memory unit.

The storage device **330** is capable of providing mass storage for the system **300**. In some implementations, the storage device **330** is a non-transitory computer-readable medium. In various different implementations, the storage device **330** may include, for example, a hard disk device, an optical disk device, a solid-state drive, a flash drive, or some other large capacity storage device. For example, the storage device may store long-term data (e.g., database data, file system data, etc.). The input/output device **340** provides input/output operations for the system **300**. In some implementations, the input/output device **340** may include one or more of a network interface devices, e.g., an Ethernet card, a serial communication device, e.g., an RS-232 port, and/or a wireless interface device, e.g., an 802.11 card, a 3G wireless modem, or a 4G wireless modem. In some implementations, the input/output device may include driver devices configured to receive input data and send output data to other input/output devices, e.g., keyboard, printer and display devices **360**. In some examples, mobile computing devices, mobile communication devices, and other devices may be used.

In some implementations, at least a portion of the approaches described above may be realized by instructions that upon execution cause one or more processing devices to carry out the processes and functions described above. Such instructions may include, for example, interpreted instructions such as script instructions, or executable code, or other instructions stored in a non-transitory computer readable medium. The storage device **330** may be implemented in a distributed way over a network, such as a server farm or a set of widely distributed servers, or may be implemented in a single computing device.

Although an example processing system has been described in FIG. **3**, embodiments of the subject matter, functional operations and processes described in this specification can be implemented in other types of digital electronic circuitry, in tangibly-embodied computer software or firmware, in computer hardware, including the structures disclosed in this specification and their structural equivalents, or in combinations of one or more of them. Embodiments of the subject matter described in this specification can be implemented as one or more computer programs, i.e., one or more modules of computer program instructions encoded on a tangible nonvolatile program carrier for execution by, or to control the operation of, data processing apparatus. Alternatively or in addition, the program instructions can be encoded on an artificially generated propagated signal, e.g., a machine-generated electrical, optical, or electromagnetic signal that is generated to encode information for transmission to suitable receiver apparatus for execution by a data processing apparatus. The computer storage medium can be a machine-readable storage device, a machine-readable storage substrate, a random or serial access memory device, or a combination of one or more of them.

The term “system” may encompass all kinds of apparatus, devices, and machines for processing data, including by way of example a programmable processor, a computer, or multiple processors or computers. A processing system may include special purpose logic circuitry, e.g., an FPGA (field programmable gate array) or an ASIC (application specific integrated circuit). A processing system may include, in addition to hardware, code that creates an execution environment for the computer program in question, e.g., code that constitutes processor firmware, a protocol stack, a database management system, an operating system, or a combination of one or more of them.

A computer program (which may also be referred to or described as a program, software, a software application, a module, a software module, a script, or code) can be written in any form of programming language, including compiled or interpreted languages, or declarative or procedural languages, and it can be deployed in any form, including as a standalone program or as a module, component, subroutine, or other unit suitable for use in a computing environment. A computer program may, but need not, correspond to a file in a file system. A program can be stored in a portion of a file that holds other programs or data (e.g., one or more scripts stored in a markup language document), in a single file dedicated to the program in question, or in multiple coordinated files (e.g., files that store one or more modules, sub programs, or portions of code). A computer program can be deployed to be executed on one computer or on multiple computers that are located at one site or distributed across multiple sites and interconnected by a communication network.

The processes and logic flows described in this specification can be performed by one or more programmable computers executing one or more computer programs to perform functions by operating on input data and generating output. The processes and logic flows can also be performed by, and apparatus can also be implemented as, special purpose logic circuitry, e.g., an FPGA (field programmable gate array) or an ASIC (application specific integrated circuit).

Computers suitable for the execution of a computer program can include, by way of example, general or special purpose microprocessors or both, or any other kind of central processing unit. Generally, a central processing unit will receive instructions and data from a read-only memory or a random access memory or both. A computer generally includes a central processing unit for performing or executing instructions and one or more memory devices for storing instructions and data. Generally, a computer will also include, or be operatively coupled to receive data from or transfer data to, or both, one or more mass storage devices for storing data, e.g., magnetic, magneto optical disks, or optical disks. However, a computer need not have such devices. Moreover, a computer can be embedded in another device, e.g., a mobile telephone, a personal digital assistant (PDA), a mobile audio or video player, a game console, a Global Positioning System (GPS) receiver, or a portable storage device (e.g., a universal serial bus (USB) flash drive), to name just a few.

Computer readable media suitable for storing computer program instructions and data include all forms of nonvolatile memory, media and memory devices, including by way of example semiconductor memory devices, e.g., EPROM, EEPROM, and flash memory devices; magnetic disks, e.g., internal hard disks or removable disks; magneto optical disks; and CD-ROM and DVD-ROM disks. The processor

and the memory can be supplemented by, or incorporated in, special purpose logic circuitry.

To provide for interaction with a user, embodiments of the subject matter described in this specification can be implemented on a computer having a display device, e.g., a CRT (cathode ray tube) or LCD (liquid crystal display) monitor, for displaying information to the user and a keyboard and a pointing device, e.g., a mouse or a trackball, by which the user can provide input to the computer. Other kinds of devices can be used to provide for interaction with a user as well; for example, feedback provided to the user can be any form of sensory feedback, e.g., visual feedback, auditory feedback, or tactile feedback; and input from the user can be received in any form, including acoustic, speech, or tactile input. In addition, a computer can interact with a user by sending documents to and receiving documents from a device that is used by the user; for example, by sending web pages to a web browser on a user’s user device in response to requests received from the web browser.

Embodiments of the subject matter described in this specification can be implemented in a computing system that includes a back end component, e.g., as a data server, or that includes a middleware component, e.g., an application server, or that includes a front end component, e.g., a client computer having a graphical user interface or a Web browser through which a user can interact with an implementation of the subject matter described in this specification, or any combination of one or more such back end, middleware, or front end components. The components of the system can be interconnected by any form or medium of digital data communication, e.g., a communication network. Examples of communication networks include a local area network (“LAN”) and a wide area network (“WAN”), e.g., the Internet. The computing system can include clients and servers. A client and server are generally remote from each other and typically interact through a communication network. The relationship of client and server arises by virtue of computer programs running on the respective computers and having a client-server relationship to each other.

While this specification contains many specific implementation details, these should not be construed as limitations on the scope of what may be claimed, but rather as descriptions of features that may be specific to particular embodiments. Certain features that are described in this specification in the context of separate embodiments can also be implemented in combination in a single embodiment. Conversely, various features that are described in the context of a single embodiment can also be implemented in multiple embodiments separately or in any suitable sub-combination. Moreover, although features may be described above as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination can in some cases be excised from the combination, and the claimed combination may be directed to a sub-combination or variation of a sub-combination.

Similarly, while operations are depicted in the drawings in a particular order, this should not be understood as requiring that such operations be performed in the particular order shown or in sequential order, or that all illustrated operations be performed, to achieve desirable results. In certain circumstances, multitasking and parallel processing may be advantageous. Moreover, the separation of various system components in the embodiments described above should not be understood as requiring such separation in all embodiments, and it should be understood that the described

program components and systems can generally be integrated together in a single software product or packaged into multiple software products.

Particular embodiments of the subject matter have been described. Other embodiments are within the scope of the following claims. For example, the actions recited in the claims can be performed in a different order and still achieve desirable results. As one example, the processes depicted in the accompanying figures do not necessarily require the particular order shown, or sequential order, to achieve desirable results. In certain implementations, multitasking and parallel processing may be advantageous. Other steps or stages may be provided, or steps or stages may be eliminated, from the described processes. Accordingly, other implementations are within the scope of the following claims.

Terminology

The phraseology and terminology used herein is for the purpose of description and should not be regarded as limiting.

The term “approximately”, the phrase “approximately equal to”, and other similar phrases, as used in the specification and the claims (e.g., “X has a value of approximately Y” or “X is approximately equal to Y”), should be understood to mean that one value (X) is within a predetermined range of another value (Y). The predetermined range may be plus or minus 20%, 10%, 5%, 3%, 1%, 0.1%, or less than 0.1%, unless otherwise indicated.

The indefinite articles “a” and “an,” as used in the specification and in the claims, unless clearly indicated to the contrary, should be understood to mean “at least one.” The phrase “and/or,” as used in the specification and in the claims, should be understood to mean “either or both” of the elements so conjoined, i.e., elements that are conjunctively present in some cases and disjunctively present in other cases. Multiple elements listed with “and/or” should be construed in the same fashion, i.e., “one or more” of the elements so conjoined. Other elements may optionally be present other than the elements specifically identified by the “and/or” clause, whether related or unrelated to those elements specifically identified. Thus, as a non-limiting example, a reference to “A and/or B”, when used in conjunction with open-ended language such as “comprising” can refer, in one embodiment, to A only (optionally including elements other than B); in another embodiment, to B only (optionally including elements other than A); in yet another embodiment, to both A and B (optionally including other elements); etc.

As used in the specification and in the claims, “or” should be understood to have the same meaning as “and/or” as defined above. For example, when separating items in a list, “or” or “and/or” shall be interpreted as being inclusive, i.e., the inclusion of at least one, but also including more than one, of a number or list of elements, and, optionally, additional unlisted items. Only terms clearly indicated to the contrary, such as “only one of” or “exactly one of,” or, when used in the claims, “consisting of,” will refer to the inclusion of exactly one element of a number or list of elements. In general, the term “or” as used shall only be interpreted as indicating exclusive alternatives (i.e. “one or the other but not both”) when preceded by terms of exclusivity, such as “either,” “one of,” “only one of,” or “exactly one of.” “Consisting essentially of,” when used in the claims, shall have its ordinary meaning as used in the field of patent law.

As used in the specification and in the claims, the phrase “at least one,” in reference to a list of one or more elements, should be understood to mean at least one element selected from any one or more of the elements in the list of elements, but not necessarily including at least one of each and every element specifically listed within the list of elements and not excluding any combinations of elements in the list of elements. This definition also allows that elements may optionally be present other than the elements specifically identified within the list of elements to which the phrase “at least one” refers, whether related or unrelated to those elements specifically identified. Thus, as a non-limiting example, “at least one of A and B” (or, equivalently, “at least one of A or B,” or, equivalently “at least one of A and/or B”) can refer, in one embodiment, to at least one, optionally including more than one, A, with no B present (and optionally including elements other than B); in another embodiment, to at least one, optionally including more than one, B, with no A present (and optionally including elements other than A); in yet another embodiment, to at least one, optionally including more than one, A, and at least one, optionally including more than one, B (and optionally including other elements); etc.

The use of “including,” “comprising,” “having,” “containing,” “involving,” and variations thereof, is meant to encompass the items listed thereafter and additional items.

Use of ordinal terms such as “first,” “second,” “third,” etc., in the claims to modify a claim element does not by itself connote any priority, precedence, or order of one claim element over another or the temporal order in which acts of a method are performed. Ordinal terms are used merely as labels to distinguish one claim element having a certain name from another element having a same name (but for use of the ordinal term), to distinguish the claim elements.

What is claimed is:

1. A computer-implemented method for external detection of a vulnerable system, the vulnerable system coupled to a communication network based on domain name properties, the method comprising:

receiving communication traffic in the communication network to identify at least one domain name associated with a vulnerable system, the communication traffic originating from at least one server system in the communication network;

executing queries on the communication traffic to extract metadata while monitoring the communication traffic; identifying the domain name having an associated property indicative of vulnerability of the domain name based on the metadata, wherein the domain name having the associated property indicative of vulnerability comprises a misconfigured domain name;

determining whether the misconfigured domain name is registered at a domain name registry;

if the misconfigured domain name is not registered, registering the misconfigured domain name based on a high frequency of domain names; and

detecting the vulnerable system associated with the registered misconfigured domain name.

2. The method of claim 1, wherein the vulnerable system is a malware-infected server system.

3. The method of claim 1, wherein the vulnerable system is a misconfigured server system.

4. The method of claim 1, wherein the metadata further comprises a geographical location associated with each domain name.

11

5. The method of claim 1, further comprising:
 associating the registered misconfigured domain name
 with a server system configured to monitor communi-
 cation traffic to the registered misconfigured domain
 name.

6. The method of claim 1 further comprising detecting the
 vulnerable system associated with the registered misconfig-
 ured domain name.

7. The method of claim 1, wherein receiving communi-
 cation traffic comprises:
 receiving communication traffic from at least one Internet
 Service Provider (ISP).

8. The method of claim 1 further comprising comparing a
 relative magnitude of communication traffic to an expected
 amount of communication traffic.

9. The method of claim 1, wherein receiving communi-
 cation traffic comprises measuring a frequency of commu-
 nication traffic to the misconfigured domain name.

10. The method of claim 1, wherein the metadata com-
 prises at least one of the group consisting of: (a) geographi-
 cal location of the communication traffic, (b) frequency of
 the communication traffic, (c) magnitude of the communi-
 cation traffic, (d) aggregated counters of a number of unique
 Internet Protocol (IP) addresses per country, (e) a number of
 events observed per period, and (f) a ratio of unique IP
 addresses to a sum of a portion of the communication traffic.

11. A system for external detection of a vulnerable system
 coupled to a communication network, the system compris-
 ing:

at least one computer systems programmed to perform
 operations comprising:

receiving communication traffic in the communication
 network to identify at least one domain name asso-
 ciated with a vulnerable system, the communication
 traffic originating from at least one server system in
 the communication network;

executing queries on the communication traffic to
 extract metadata while monitoring the communi-
 cation traffic;

identifying the domain name having an associated
 property indicative of vulnerability of the domain
 name based on the metadata, wherein the domain
 name having the associated property indicative of
 vulnerability comprises a misconfigured domain
 name;

determining whether the misconfigured domain name
 is registered at a domain name registry;

if the misconfigured domain name is not registered,
 registering the misconfigured domain name based on
 a high frequency of domain names; and

detecting the vulnerable system associated with the
 registered misconfigured domain name.

12. The system of claim 11, wherein the vulnerable
 system is a malware-infected server system.

13. The system of claim 11, wherein the vulnerable
 system is a misconfigured server system.

14. The system of claim 11, wherein the operations further
 comprise:

associating the registered domain name with a server
 system configured to monitor communication traffic to
 the registered domain name.

15. The system of claim 11, wherein the operations further
 comprise detecting the vulnerable system associated with
 the registered misconfigured domain name.

12

16. The system of claim 11, wherein receiving commu-
 nication traffic comprises:

receiving communication traffic from at least one Internet
 Service Provider (ISP).

17. The system of claim 11, wherein the operations further
 comprise comparing a relative magnitude of communication
 traffic to an expected amount of communication traffic.

18. The system of claim 11, wherein receiving commu-
 nication traffic comprises measuring a frequency of com-
 munication traffic to the misconfigured domain name.

19. The system of claim 11, wherein the metadata com-
 prises at least one of the group consisting of: (a) geographi-
 cal location of the communication traffic, (b) frequency of
 the communication traffic, (c) magnitude of the communi-
 cation traffic, (d) aggregated counters of a number of unique
 Internet Protocol (IP) addresses per country, (e) a number of
 events observed per period, and (f) a ratio of unique IP
 addresses to a sum of a portion of the communication traffic.

20. A computer-implemented method for external detec-
 tion of a vulnerable system, the vulnerable system coupled
 to a communication network based on domain name prop-
 erties, the method comprising:

receiving communication traffic in the communication
 network to identify at least one domain name asso-
 ciated with a vulnerable system, the communication
 traffic originating from at least one server system in the
 communication network;

executing queries on the communication traffic to extract
 metadata while monitoring the communication traffic;

identifying the domain name having an associated prop-
 erty indicative of vulnerability of the domain name
 based on the metadata, wherein the domain name
 having the associated property indicative of vulnerabil-
 ity comprises an abandoned domain name;

determining whether the abandoned domain name is
 registered at a domain name registry;

if the abandoned domain name is not registered, register-
 ing the abandoned domain name based on a high
 frequency of domain names; and

detecting the vulnerable system associated with the reg-
 istered abandoned domain name.

21. A computer-implemented method for external detec-
 tion of a vulnerable system, the vulnerable system coupled
 to a communication network based on domain name prop-
 erties, the method comprising:

receiving communication traffic in the communication
 network to identify at least one domain name asso-
 ciated with a vulnerable system, the communication
 traffic originating from at least one server system in the
 communication network;

executing queries on the communication traffic to extract
 metadata while monitoring the communication traffic;

identifying the domain name having an associated prop-
 erty indicative of vulnerability of the domain name
 based on the metadata, wherein the domain name
 having the associated property indicative of vulnerabil-
 ity comprises an algorithm-generated domain name;

determining whether the algorithm-generated domain
 name is registered at a domain name registry;

if the algorithm-generated domain name is not registered,
 registering the algorithm-generated domain name
 based on a high frequency of domain names; and

detecting the vulnerable system associated with the reg-
 istered algorithm-generated domain name.