



(12) **United States Patent**
Waldern et al.

(10) **Patent No.:** US 11,681,143 B2
(45) **Date of Patent:** Jun. 20, 2023

(54) **METHODS AND APPARATUS FOR MULTIPLYING THE IMAGE RESOLUTION AND FIELD-OF-VIEW OF A PIXELATED DISPLAY**

(71) Applicant: **DigiLens Inc.**, Sunnyvale, CA (US)

(72) Inventors: **Jonathan David Waldern**, Los Altos Hills, CA (US); **Alastair John Grant**, San Jose, CA (US); **Milan Momcilo Popovich**, Leicester (GB)

(73) Assignee: **DigiLens Inc.**, Sunnyvale, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 236 days.

(21) Appl. No.: **16/942,418**

(22) Filed: **Jul. 29, 2020**

(65) **Prior Publication Data**

US 2021/0033857 A1 Feb. 4, 2021

Related U.S. Application Data

(60) Provisional application No. 62/880,033, filed on Jul. 29, 2019.

(51) **Int. Cl.**
G02B 27/00 (2006.01)
G02F 1/295 (2006.01)
F21V 8/00 (2006.01)

(52) **U.S. Cl.**
CPC **G02B 27/0081** (2013.01); **G02B 6/005** (2013.01); **G02B 6/0026** (2013.01); **G02F 1/2955** (2013.01); **G02F 2203/24** (2013.01)

(58) **Field of Classification Search**
CPC .. G02B 27/0081; G02B 6/0026; G02B 6/005; G02F 1/2955; G02F 2203/24
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,043,938 A 11/1912 Huttenlocher
2,141,884 A 12/1938 Sonnefeld

(Continued)

FOREIGN PATENT DOCUMENTS

BR PI0720469 A2 1/2014
CA 2889727 A1 6/2014

(Continued)

OTHER PUBLICATIONS

Trisnadi, "Hadamard Speckle Contrast Reduction", Optics Letters, Jan. 1, 2004, vol. 29, No. 1, pp. 11-13.

(Continued)


Primary Examiner — Collin X Beatty

(74) *Attorney, Agent, or Firm* — KPPB LLP

(57) **ABSTRACT**

Systems and methods for multiplying the resolution and field-of-view of pixelated displays in accordance with various embodiments of the invention are illustrated. One embodiment includes an apparatus having an image projector for directing light from a pixelated image source into unique angular directions, an image processor electrically connected to the image projector for computing native images of the image source corresponding to first and second field-of-view portions and for computing shifted images in a predefined direction corresponding to the first and second field-of-view portions for sequential display by the image projector, a first set of gratings having a native configuration for propagating the light of the native image and at least one shifted configuration for propagating the light of at least one shifted image, and a second set of gratings having a first configuration for projecting the first field-of-view portion and a second configuration for projecting the second field-of-view portion.

20 Claims, 11 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

3,482,498 A	12/1969	Becker	5,117,302 A	5/1992	Lipton
3,620,601 A	11/1971	Leonard et al.	5,119,454 A	6/1992	McMahon et al.
3,741,716 A	6/1973	Johne et al.	5,124,821 A	6/1992	Antier et al.
3,843,231 A	10/1974	Borel et al.	5,139,192 A	8/1992	Simmonds et al.
3,851,303 A	11/1974	Muller	5,142,357 A	8/1992	Lipton et al.
3,885,095 A	5/1975	Wolfson et al.	5,142,644 A	8/1992	Vansteenkiste et al.
3,940,204 A	2/1976	Withrington	5,148,302 A	9/1992	Nagano et al.
3,965,029 A	6/1976	Arora	5,150,234 A	9/1992	Takahashi et al.
3,975,711 A	8/1976	McMahon	5,151,958 A	9/1992	Honkanen
4,035,068 A	7/1977	Rawson	5,153,751 A	10/1992	Ishikawa et al.
4,066,334 A	1/1978	Fray et al.	5,159,445 A	10/1992	Gitlin et al.
4,082,432 A	4/1978	Kirschner	5,160,523 A	11/1992	Honkanen et al.
4,099,841 A	7/1978	Ellis	5,181,133 A	1/1993	Lipton
4,133,152 A	1/1979	Penrose	5,183,545 A	2/1993	Branca et al.
4,178,074 A	12/1979	Heller	5,187,597 A	2/1993	Kato et al.
4,218,111 A	8/1980	Withrington et al.	5,193,000 A	3/1993	Lipton et al.
4,232,943 A	11/1980	Rogers	5,198,912 A	3/1993	Ingwall et al.
4,248,093 A	2/1981	Andersson et al.	5,200,861 A	4/1993	Moskovich et al.
4,251,137 A	2/1981	Knop et al.	5,210,624 A	5/1993	Matsumoto et al.
4,309,070 A	1/1982	St. Leger Searle	5,218,360 A	6/1993	Goetz et al.
4,322,163 A	3/1982	Schiller	5,218,480 A	6/1993	Moskovich et al.
4,386,361 A	5/1983	Simmonds	5,224,198 A	6/1993	Jachimowicz et al.
4,389,612 A	6/1983	Simmonds et al.	5,239,372 A	8/1993	Lipton
4,403,189 A	9/1983	Simmonds	5,240,636 A	8/1993	Doane et al.
4,418,993 A	12/1983	Lipton	5,241,337 A	8/1993	Betensky et al.
4,472,037 A	9/1984	Lipton	5,242,476 A	9/1993	Bartel et al.
4,523,226 A	6/1985	Lipton et al.	5,243,413 A	9/1993	Gitlin et al.
4,544,267 A	10/1985	Schiller	5,251,048 A	10/1993	Doane et al.
4,562,463 A	12/1985	Lipton	5,264,950 A	11/1993	West et al.
4,566,758 A	1/1986	Bos et al.	5,268,792 A	12/1993	Kreitzer et al.
4,583,117 A	4/1986	Lipton et al.	5,284,499 A	2/1994	Harvey et al.
4,643,515 A	2/1987	Upatnieks	5,289,315 A	2/1994	Makita et al.
4,647,967 A	3/1987	Kirschner et al.	5,295,208 A	3/1994	Caulfield et al.
4,688,900 A	8/1987	Doane et al.	5,296,967 A	3/1994	Moskovich et al.
4,711,512 A	12/1987	Upatnieks	5,299,289 A	3/1994	Omae et al.
4,714,320 A	12/1987	Banbury	5,303,085 A	4/1994	Rallison
4,728,547 A	3/1988	Vaz et al.	5,309,283 A	5/1994	Kreitzer et al.
4,729,640 A	3/1988	Sakata et al.	5,313,330 A	5/1994	Betensky
4,743,083 A	5/1988	Schimpe	5,315,324 A	5/1994	Kubelik et al.
4,749,256 A	6/1988	Bell et al.	5,315,419 A	5/1994	Saupe et al.
4,765,703 A	8/1988	Suzuki et al.	5,315,440 A	5/1994	Betensky et al.
4,775,218 A	10/1988	Wood et al.	5,317,405 A	5/1994	Kuriki et al.
4,791,788 A	12/1988	Simmonds et al.	5,327,269 A	7/1994	Tilton et al.
4,792,850 A	12/1988	Lipton et al.	5,329,363 A	7/1994	Moskovich et al.
4,799,765 A	1/1989	Ferrer	5,341,230 A	8/1994	Smith
4,811,414 A	3/1989	Fishbine et al.	5,343,147 A	8/1994	Sager et al.
4,848,093 A	7/1989	Simmonds et al.	5,351,151 A	9/1994	Levy
4,854,688 A	8/1989	Hayford et al.	5,359,362 A	10/1994	Lewis et al.
4,884,876 A	12/1989	Lipton et al.	5,363,220 A	11/1994	Kuwayama et al.
4,890,902 A	1/1990	Doane et al.	5,368,770 A	11/1994	Saupe et al.
4,928,301 A	5/1990	Smoot	5,369,511 A	11/1994	Amos
4,933,976 A	6/1990	Fishbine et al.	5,371,626 A	12/1994	Betensky
4,938,568 A	7/1990	Margerum et al.	5,400,069 A	3/1995	Braun et al.
4,946,245 A	8/1990	Chamberlin et al.	5,408,346 A	4/1995	Trissel et al.
4,960,311 A	10/1990	Moss et al.	5,410,370 A	4/1995	Janssen
4,964,701 A	10/1990	Dorschner et al.	5,416,510 A	5/1995	Lipton et al.
4,967,268 A	10/1990	Lipton et al.	5,416,514 A	5/1995	Janssen et al.
4,970,129 A	11/1990	Ingwall et al.	5,418,584 A	5/1995	Larson
4,971,719 A	11/1990	Vaz et al.	5,418,871 A	5/1995	Revelli et al.
4,994,204 A	2/1991	Doane et al.	5,428,480 A	6/1995	Betensky et al.
5,004,323 A	4/1991	West	5,437,811 A	8/1995	Doane et al.
5,007,711 A	4/1991	Wood et al.	5,438,357 A	8/1995	McNalley
5,009,483 A	4/1991	Rockwell et al.	5,452,385 A	9/1995	Izumi et al.
5,016,953 A	5/1991	Moss et al.	5,453,863 A	9/1995	West et al.
5,033,814 A	7/1991	Brown et al.	5,455,693 A	10/1995	Wreede et al.
5,035,734 A	7/1991	Honkanen et al.	5,455,713 A	10/1995	Kreitzer et al.
5,053,834 A	10/1991	Simmonds	5,463,428 A	10/1995	Lipton et al.
5,063,441 A	11/1991	Lipton et al.	5,465,311 A	11/1995	Caulfield et al.
5,076,664 A	12/1991	Migozzi	5,471,326 A	11/1995	Hall et al.
5,079,416 A	1/1992	Filipovich	5,473,222 A	12/1995	Thoeny et al.
5,096,282 A	3/1992	Margerum et al.	5,476,611 A	12/1995	Nolan et al.
5,099,343 A	3/1992	Margerum et al.	5,481,321 A	1/1996	Lipton
5,109,465 A	4/1992	Klopotek	5,485,313 A	1/1996	Betensky
5,110,034 A	5/1992	Simmonds et al.	5,493,430 A	2/1996	Lu et al.
5,117,285 A	5/1992	Nelson et al.	5,493,448 A	2/1996	Betensky et al.
			5,496,621 A	3/1996	Makita et al.
			5,499,140 A	3/1996	Betensky
			5,500,671 A	3/1996	Andersson et al.
			5,500,769 A	3/1996	Betensky

(56)

References Cited

U.S. PATENT DOCUMENTS

5,510,913 A	4/1996	Hashimoto et al.	5,831,700 A	11/1998	Li et al.
5,515,184 A	5/1996	Caulfield et al.	5,835,661 A	11/1998	Tai et al.
5,516,455 A	5/1996	Jacobine et al.	5,841,507 A	11/1998	Barnes
5,524,272 A	6/1996	Podowski et al.	5,841,587 A	11/1998	Moskovich et al.
5,530,566 A	6/1996	Kumar	5,847,787 A	12/1998	Fredley et al.
5,532,736 A	7/1996	Kuriki et al.	5,856,842 A	1/1999	Tedesco
5,532,875 A	7/1996	Betemsky	5,857,043 A	1/1999	Cook et al.
5,537,232 A	7/1996	Biles	5,867,238 A	2/1999	Miller et al.
RE35,310 E	8/1996	Moskovich	5,868,951 A	2/1999	Schuck, III et al.
5,543,950 A	8/1996	Lavrentovich et al.	5,870,228 A	2/1999	Kreitzer et al.
5,559,637 A	9/1996	Moskovich et al.	5,875,012 A	2/1999	Crawford et al.
5,572,248 A	11/1996	Allen et al.	5,877,826 A	3/1999	Yang et al.
5,572,250 A	11/1996	Lipton et al.	5,886,822 A	3/1999	Spitzer
5,576,888 A	11/1996	Betensky	5,892,598 A	4/1999	Asakawa et al.
5,579,026 A	11/1996	Tabata	5,892,599 A	4/1999	Bahuguna
5,583,795 A	12/1996	Smyth	5,898,511 A	4/1999	Mizutani et al.
5,585,035 A	12/1996	Nerad et al.	5,900,987 A	5/1999	Kreitzer et al.
5,593,615 A	1/1997	Nerad et al.	5,900,989 A	5/1999	Kreitzer
5,604,611 A	2/1997	Saburi et al.	5,903,395 A	5/1999	Rallison et al.
5,606,433 A	2/1997	Yin et al.	5,903,396 A	5/1999	Rallison
5,612,733 A	3/1997	Flohr	5,907,416 A	5/1999	Hegg et al.
5,612,734 A	3/1997	Nelson et al.	5,907,436 A	5/1999	Perry et al.
5,619,254 A	4/1997	McNelley	5,917,459 A	6/1999	Son et al.
5,619,586 A	4/1997	Sibbald et al.	5,926,147 A	7/1999	Sehm et al.
5,621,529 A	4/1997	Gordon et al.	5,929,946 A	7/1999	Sharp et al.
5,621,552 A	4/1997	Coates et al.	5,929,960 A	7/1999	West et al.
5,625,495 A	4/1997	Moskovich et al.	5,930,433 A	7/1999	Williamson et al.
5,629,259 A	5/1997	Akada et al.	5,936,776 A	8/1999	Kreitzer
5,631,107 A	5/1997	Tarumi et al.	5,937,115 A	8/1999	Domash
5,633,100 A	5/1997	Mickish et al.	5,942,157 A	8/1999	Sutherland et al.
5,646,785 A	7/1997	Gilboa et al.	5,945,893 A	8/1999	Plessky et al.
5,648,857 A	7/1997	Ando et al.	5,949,302 A	9/1999	Sarkka
5,661,577 A	8/1997	Jenkins et al.	5,949,508 A	9/1999	Kumar et al.
5,661,603 A	8/1997	Hanano et al.	5,956,113 A	9/1999	Crawford
5,665,494 A	9/1997	Kawabata et al.	5,962,147 A	10/1999	Shalhub et al.
5,668,614 A	9/1997	Chien et al.	5,963,375 A	10/1999	Kreitzer
5,668,907 A	9/1997	Veligidan	5,966,223 A	10/1999	Friesem et al.
5,677,797 A	10/1997	Betensky et al.	5,969,874 A	10/1999	Moskovich
5,680,231 A	10/1997	Grinberg et al.	5,969,876 A	10/1999	Kreitzer et al.
5,682,255 A	10/1997	Friesem et al.	5,973,727 A	10/1999	McGrew et al.
5,686,931 A	11/1997	Fuenfschilling et al.	5,974,162 A	10/1999	Metz et al.
5,686,975 A	11/1997	Lipton	5,985,422 A	11/1999	Krauter
5,691,795 A	11/1997	Doane et al.	5,986,746 A	11/1999	Metz et al.
5,694,230 A	12/1997	Welch	5,991,087 A	11/1999	Rallison
5,695,682 A	12/1997	Doane et al.	5,999,089 A	12/1999	Carlson et al.
5,701,132 A	12/1997	Kollin et al.	5,999,282 A	12/1999	Suzuki et al.
5,706,108 A	1/1998	Ando et al.	5,999,314 A	12/1999	Asakura et al.
5,706,136 A	1/1998	Okuyama et al.	6,014,187 A	1/2000	Taketomi et al.
5,707,925 A	1/1998	Akada et al.	6,023,375 A	2/2000	Kreitzer
5,710,645 A	1/1998	Phillips et al.	6,042,947 A	3/2000	Asakura et al.
5,724,189 A	3/1998	Ferrante	6,043,585 A	3/2000	Plessky et al.
5,724,463 A	3/1998	Deacon et al.	6,046,585 A	4/2000	Simmonds
5,726,782 A	3/1998	Kato et al.	6,052,540 A	4/2000	Koyama
5,727,098 A	3/1998	Jacobson	6,061,107 A	5/2000	Yang
5,729,242 A	3/1998	Margerum et al.	6,061,463 A	5/2000	Metz et al.
5,731,060 A	3/1998	Hirukawa et al.	6,069,728 A	5/2000	Huignard et al.
5,731,853 A	3/1998	Taketomi et al.	6,075,626 A	6/2000	Mizutani et al.
5,742,262 A	4/1998	Tabata et al.	6,078,427 A	6/2000	Fontaine et al.
5,745,266 A	4/1998	Smith et al.	6,094,311 A	7/2000	Moskovich
5,745,301 A	4/1998	Betensky et al.	6,097,551 A	8/2000	Kreitzer
5,748,272 A	5/1998	Tanaka et al.	6,104,448 A	8/2000	Doane et al.
5,748,277 A	5/1998	Huang et al.	6,107,943 A	8/2000	Schroeder
5,751,452 A	5/1998	Tanaka et al.	6,115,152 A	9/2000	Popovich et al.
5,757,546 A	5/1998	Lipton et al.	6,118,908 A	9/2000	Bischel et al.
5,760,931 A	6/1998	Saburi et al.	6,121,899 A	9/2000	Therault
5,764,414 A	6/1998	King et al.	6,127,066 A	10/2000	Ueda et al.
5,771,320 A	6/1998	Stone	6,128,058 A	10/2000	Walton et al.
5,790,288 A	8/1998	Jager et al.	6,133,971 A	10/2000	Silverstein et al.
5,790,314 A	8/1998	Duck et al.	6,133,975 A	10/2000	Li et al.
5,798,641 A	8/1998	Spagna et al.	6,137,630 A	10/2000	Tsou et al.
5,808,804 A	9/1998	Moskovich	6,141,074 A	10/2000	Bos et al.
5,812,608 A	9/1998	Valimaki et al.	6,141,154 A	10/2000	Kreitzer et al.
5,822,089 A	10/1998	Phillips et al.	6,151,142 A	11/2000	Phillips et al.
5,822,127 A	10/1998	Chen et al.	6,154,190 A	11/2000	Yang et al.
5,825,448 A	10/1998	Bos et al.	6,167,169 A	12/2000	Brinkman et al.
			6,169,594 B1	1/2001	Aye et al.
			6,169,613 B1	1/2001	Amitai et al.
			6,169,636 B1	1/2001	Kreitzer et al.
			6,176,837 B1	1/2001	Foxlin

(56)

References Cited

U.S. PATENT DOCUMENTS

6,185,016 B1	2/2001	Popovich	6,567,573 B1	5/2003	Domash et al.
6,188,462 B1	2/2001	Lavrentovich et al.	6,577,411 B1	6/2003	David et al.
6,191,887 B1	2/2001	Michaloski et al.	6,577,429 B1	6/2003	Kurtz et al.
6,195,206 B1	2/2001	Yona et al.	6,580,529 B1	6/2003	Amitai et al.
6,195,209 B1	2/2001	Kreitzer et al.	6,583,838 B1	6/2003	Hoke et al.
6,204,835 B1	3/2001	Yang et al.	6,583,873 B1	6/2003	Goncharov et al.
6,211,976 B1	4/2001	Popovich et al.	6,587,619 B1	7/2003	Kinoshita
6,222,297 B1	4/2001	Perdue	6,594,090 B2	7/2003	Kruschwitz et al.
6,222,675 B1	4/2001	Mall et al.	6,597,176 B2	7/2003	Simmonds et al.
6,222,971 B1	4/2001	Veligdan et al.	6,597,475 B1	7/2003	Shirakura et al.
6,249,386 B1	6/2001	Yona et al.	6,598,987 B1	7/2003	Parikka
6,259,423 B1	7/2001	Tokito et al.	6,600,590 B2	7/2003	Roddy et al.
6,259,559 B1	7/2001	Kobayashi et al.	6,608,720 B1	8/2003	Freeman
6,268,839 B1	7/2001	Yang et al.	6,611,253 B1	8/2003	Cohen
6,269,203 B1	7/2001	Davies et al.	6,618,104 B1	9/2003	Date et al.
6,275,031 B1	8/2001	Simmonds et al.	6,625,381 B2	9/2003	Roddy et al.
6,278,429 B1	8/2001	Ruth et al.	6,646,772 B1	11/2003	Popovich et al.
6,285,813 B1	9/2001	Schultz et al.	6,646,810 B2	11/2003	Harter, Jr. et al.
6,297,860 B1	10/2001	Moskovich et al.	6,661,578 B2	12/2003	Hedrick
6,301,056 B1	10/2001	Kreitzer et al.	6,667,134 B1	12/2003	Sutherland et al.
6,301,057 B1	10/2001	Kreitzer et al.	6,674,578 B2	1/2004	Sugiyama et al.
6,317,083 B1	11/2001	Johnson et al.	6,677,086 B1	1/2004	Sutehrland et al.
6,317,227 B1	11/2001	Mizutani et al.	6,686,815 B1	2/2004	Mirshekari-Syahkal et al.
6,317,228 B2	11/2001	Popovich et al.	6,690,516 B2	2/2004	Aritake et al.
6,320,563 B1	11/2001	Yang et al.	6,692,666 B2	2/2004	Sutherland et al.
6,321,069 B1	11/2001	Piirainen	6,699,407 B1	3/2004	Sutehrland et al.
6,323,970 B1	11/2001	Popovich	6,706,086 B2	3/2004	Emig et al.
6,323,989 B1	11/2001	Jacobson et al.	6,706,451 B1	3/2004	Sutherland et al.
6,324,014 B1	11/2001	Moskovich et al.	6,721,096 B2	4/2004	Bruzzzone et al.
6,327,089 B1	12/2001	Hosaki et al.	6,730,442 B1	5/2004	Sutherland et al.
6,330,109 B1	12/2001	Ishii et al.	6,731,434 B1	5/2004	Hua et al.
6,333,819 B1	12/2001	Svedenkrans	6,738,105 B1	5/2004	Hannah et al.
6,340,540 B1	1/2002	Ueda et al.	6,741,189 B1	5/2004	Gibbons, II et al.
6,351,333 B2	2/2002	Araki et al.	6,744,478 B1	6/2004	Asakura et al.
6,356,172 B1	3/2002	Koivisto et al.	6,747,781 B2	6/2004	Trisnadi et al.
6,356,674 B1	3/2002	Davis et al.	6,747,781 B2	6/2004	Dickhaus
6,359,730 B2	3/2002	Tervonen	6,748,342 B1	6/2004	Satoh et al.
6,359,737 B1	3/2002	Stringfellow	6,750,941 B2	6/2004	Satoh et al.
6,366,281 B1	4/2002	Lipton et al.	6,750,995 B2	6/2004	Dickson
6,366,369 B2	4/2002	Ichikawa et al.	6,757,105 B2	6/2004	Niv et al.
6,366,378 B1	4/2002	Tervonen et al.	6,771,403 B1	8/2004	Endo et al.
6,377,238 B1	4/2002	McPheters	6,776,339 B2	8/2004	Piikivi
6,377,321 B1	4/2002	Khan et al.	6,781,701 B1	8/2004	Sweetser et al.
6,388,797 B1	5/2002	Lipton et al.	6,791,629 B2	8/2004	Sweetser et al.
6,392,812 B1	5/2002	Howard	6,791,739 B2	9/2004	Moskovich et al.
6,407,724 B2	6/2002	Waldern et al.	6,804,066 B1	9/2004	Ramanujan et al.
6,409,687 B1	6/2002	Foxlin	6,805,490 B2	10/2004	Ha et al.
6,411,444 B1	6/2002	Moskovich et al.	6,821,457 B1	10/2004	Levola
6,414,760 B1	7/2002	Lopez et al.	6,822,713 B1	11/2004	Natarajan et al.
6,417,971 B1	7/2002	Moskovich et al.	6,822,713 B1	11/2004	Yaroshchuk et al.
6,437,563 B1	8/2002	Simmonds et al.	6,825,987 B2	11/2004	Repetto et al.
6,445,512 B1	9/2002	Moskovich et al.	6,829,095 B2	12/2004	Amitai
6,449,095 B1	9/2002	Ohtaki et al.	6,830,789 B2	12/2004	Doane et al.
6,470,132 B1	10/2002	Nousiainen et al.	6,833,955 B2	12/2004	Niv
6,473,209 B1	10/2002	Popovich	6,836,369 B2	12/2004	Fujikawa et al.
6,476,974 B1	11/2002	Kreitzer et al.	6,842,563 B2	1/2005	Zhang et al.
6,483,303 B2	11/2002	Simmonds et al.	6,844,212 B2	1/2005	Bond et al.
6,486,997 B1	11/2002	Bruzzzone et al.	6,844,980 B2	1/2005	He et al.
6,504,518 B1	1/2003	Kuwayama et al.	6,844,989 B1	1/2005	Jo et al.
6,504,629 B1	1/2003	Popovich et al.	6,847,274 B2	1/2005	Salmela et al.
6,509,937 B1	1/2003	Moskovich et al.	6,847,488 B2	1/2005	Travis
6,518,747 B2	2/2003	Sager et al.	6,850,210 B1	2/2005	Lipton et al.
6,519,088 B1	2/2003	Lipton	6,853,491 B1	2/2005	Ruhle et al.
6,522,794 B1	2/2003	Bischel et al.	6,853,493 B2	2/2005	Kreitzer et al.
6,524,771 B2	2/2003	Maeda et al.	6,864,861 B2	3/2005	Schehrer et al.
6,529,336 B1	3/2003	Kreitzer et al.	6,864,927 B1	3/2005	Cathey
6,534,977 B1	3/2003	Duncan et al.	6,864,931 B1	3/2005	Kumar et al.
6,545,778 B2	4/2003	Ono et al.	6,867,888 B2	3/2005	Sutherland et al.
6,550,949 B1	4/2003	Bauer et al.	6,873,443 B1	3/2005	Joubert et al.
6,552,789 B1	4/2003	Modro	6,878,494 B2	4/2005	Sutehrland et al.
6,557,413 B2	5/2003	Nieminen et al.	6,885,483 B2	4/2005	Takada
6,559,813 B1	5/2003	DeLuca et al.	6,903,872 B2	6/2005	Schrader
6,563,648 B2	5/2003	Gleckman et al.	6,909,345 B1	6/2005	Salmela et al.
6,563,650 B2	5/2003	Moskovich et al.	6,917,375 B2	7/2005	Akada et al.
6,567,014 B1	5/2003	Hansen et al.	6,922,267 B2	7/2005	Endo et al.
			6,926,429 B2	8/2005	Barlow et al.
			6,927,570 B2	8/2005	Simmonds et al.
			6,927,694 B1	8/2005	Smith et al.
			6,940,361 B1	9/2005	Jokio et al.
			6,943,788 B2	9/2005	Tomono
			6,950,173 B1	9/2005	Sutherland et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,950,227 B2	9/2005	Schrader	7,256,915 B2	8/2007	Sutherland et al.
6,951,393 B2	10/2005	Koide	7,259,906 B1	8/2007	Islam
6,952,312 B2	10/2005	Weber et al.	7,265,882 B2	9/2007	Sutherland et al.
6,952,435 B2	10/2005	Lai et al.	7,265,903 B2	9/2007	Sutherland et al.
6,958,662 B1	10/2005	Salmela et al.	7,268,946 B2	9/2007	Wang
6,958,868 B1	10/2005	Pender	7,285,903 B2	10/2007	Cull et al.
6,963,454 B1	11/2005	Martins et al.	7,286,272 B2	10/2007	Mukawa
6,972,788 B1	12/2005	Robertson et al.	7,289,069 B2	10/2007	Ranta
6,975,345 B1	12/2005	Lipton et al.	RE39,911 E	11/2007	Moskovich
6,980,365 B2	12/2005	Moskovich	7,299,983 B2	11/2007	Piikivi
6,985,296 B2	1/2006	Lipton et al.	7,301,601 B2	11/2007	Lin et al.
6,987,908 B2	1/2006	Bond et al.	7,312,906 B2	12/2007	Sutherland et al.
6,999,239 B1	2/2006	Martins et al.	7,313,291 B2	12/2007	Okhotnikov et al.
7,002,618 B2	2/2006	Lipton et al.	7,319,573 B2	1/2008	Nishiyama
7,002,753 B2	2/2006	Moskovich et al.	7,320,534 B2	1/2008	Sugikawa et al.
7,003,187 B2	2/2006	Frick et al.	7,323,275 B2	1/2008	Otaki et al.
7,006,732 B2	2/2006	Gunn, III et al.	7,333,685 B2	2/2008	Stone et al.
7,009,773 B2	3/2006	Chaoulov et al.	7,336,271 B2	2/2008	Ozeki et al.
7,018,563 B1	3/2006	Sutherland et al.	7,339,737 B2	3/2008	Urey et al.
7,018,686 B2	3/2006	Sutherland et al.	7,339,742 B2	3/2008	Amitai et al.
7,018,744 B2	3/2006	Otaki et al.	7,356,224 B2	4/2008	Levner et al.
7,019,793 B2	3/2006	Moskovich et al.	7,369,911 B1	5/2008	Volant et al.
7,021,777 B2	4/2006	Amitai	7,375,870 B2	5/2008	Schorpp
7,026,892 B2	4/2006	Kajiya	7,375,886 B2	5/2008	Lipton et al.
7,027,671 B2	4/2006	Huck et al.	7,391,573 B2	6/2008	Amitai
7,034,748 B2	4/2006	Kajiya	7,394,865 B2	7/2008	Borran et al.
7,046,439 B2	5/2006	Kaminsky et al.	7,395,181 B2	7/2008	Foxlin
7,053,735 B2	5/2006	Salmela et al.	7,397,606 B1	7/2008	Peng et al.
7,053,991 B2	5/2006	Sandusky	7,401,920 B1	7/2008	Kranz et al.
7,054,045 B2	5/2006	McPheters et al.	7,404,644 B2	7/2008	Evans et al.
7,058,434 B2	6/2006	Wang et al.	7,410,286 B2	8/2008	Travis
7,068,405 B2	6/2006	Sutherland et al.	7,411,637 B2	8/2008	Weiss
7,068,898 B2	6/2006	Buretea et al.	7,413,678 B1	8/2008	Natarajan et al.
7,072,020 B1	7/2006	Sutherland et al.	7,413,679 B1	8/2008	Sutherland et al.
7,075,273 B2	7/2006	O'Gorman et al.	7,415,173 B2	8/2008	Kassamakov et al.
7,077,984 B1	7/2006	Natarajan et al.	7,416,818 B2	8/2008	Sutherland et al.
7,081,215 B2	7/2006	Natarajan et al.	7,418,170 B2	8/2008	Mukawa et al.
7,088,457 B1	8/2006	Zou et al.	7,420,733 B1	9/2008	Natarajan et al.
7,088,515 B2	8/2006	Lipton	7,433,116 B1	10/2008	Islam
7,095,562 B1	8/2006	Peng et al.	7,436,568 B1	10/2008	Kuykendall, Jr.
7,099,080 B2	8/2006	Lipton et al.	7,447,967 B2	11/2008	Onggosanusi et al.
7,101,048 B2	9/2006	Travis	7,453,612 B2	11/2008	Mukawa
7,108,383 B1	9/2006	Mitchell et al.	7,454,103 B2	11/2008	Parriaux
7,110,184 B1	9/2006	Yona et al.	7,457,040 B2	11/2008	Amitai
7,119,965 B1	10/2006	Rolland et al.	7,466,994 B2	12/2008	Pihlaja et al.
7,123,418 B2	10/2006	Weber et al.	7,477,206 B2	1/2009	Cowan et al.
7,123,421 B1	10/2006	Moskovich et al.	7,479,354 B2	1/2009	Ueda et al.
7,126,418 B2	10/2006	Hunton et al.	7,480,215 B2	1/2009	Makela et al.
7,126,583 B1	10/2006	Breed	7,482,996 B2	1/2009	Larson et al.
7,132,200 B1	11/2006	Ueda et al.	7,483,604 B2	1/2009	Levola
7,133,084 B2	11/2006	Moskovich et al.	7,492,512 B2	2/2009	Niv et al.
7,139,109 B2	11/2006	Mukawa	7,496,293 B2	2/2009	Shamir et al.
RE39,424 E	12/2006	Moskovich	7,499,217 B2	3/2009	Cakmakci et al.
7,145,729 B2	12/2006	Kreitzer et al.	7,500,104 B2	3/2009	Goland
7,149,385 B2	12/2006	Parikka et al.	7,511,891 B2	3/2009	Messerschmidt
7,151,246 B2	12/2006	Fein et al.	7,513,668 B1	4/2009	Peng et al.
7,158,095 B2	1/2007	Jenson et al.	7,522,344 B1	4/2009	Curatu et al.
7,167,286 B2	1/2007	Anderson et al.	7,525,448 B1	4/2009	Wilson et al.
7,175,780 B1	2/2007	Sutherland et al.	7,528,385 B2	5/2009	Volodin et al.
7,181,105 B2	2/2007	Teramura et al.	7,545,429 B2	6/2009	Travis
7,181,108 B2	2/2007	Levola	7,550,234 B2	6/2009	Otaki et al.
7,184,002 B2	2/2007	Lipton et al.	7,567,372 B2	7/2009	Schorpp
7,184,615 B2	2/2007	Levola	7,570,322 B1	8/2009	Sutherland et al.
7,186,567 B1	3/2007	Sutherland et al.	7,570,405 B1	8/2009	Sutherland et al.
7,190,849 B2	3/2007	Katase	7,570,429 B2	8/2009	Maliah et al.
7,198,737 B2	4/2007	Natarajan et al.	7,572,555 B2	8/2009	Takizawa et al.
7,199,934 B2	4/2007	Yamasaki	7,573,640 B2	8/2009	Nivon et al.
7,205,960 B2	4/2007	David	7,576,916 B2	8/2009	Amitai
7,205,964 B1	4/2007	Yokoyama et al.	7,577,326 B2	8/2009	Amitai
7,206,107 B2	4/2007	Levola	7,579,119 B2	8/2009	Ueda et al.
7,212,175 B1	5/2007	Magee et al.	7,583,423 B2	9/2009	Sutherland et al.
7,230,767 B2	6/2007	Walck et al.	7,588,863 B2	9/2009	Takizawa et al.
7,230,770 B2	6/2007	Kreitzer et al.	7,589,900 B1	9/2009	Powell
7,242,527 B2	7/2007	Spitzer et al.	7,589,901 B2	9/2009	DeJong et al.
7,248,128 B2	7/2007	Mattila et al.	7,592,988 B2	9/2009	Katase
			7,593,575 B2	9/2009	Houle et al.
			7,597,447 B2	10/2009	Larson et al.
			7,599,012 B2	10/2009	Nakamura et al.
			7,600,893 B2	10/2009	Laino et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

7,602,552 B1	10/2009	Blumenfeld	8,107,023 B2	1/2012	Simmonds et al.
7,605,719 B1	10/2009	Wenger et al.	8,107,780 B2	1/2012	Simmonds
7,605,774 B1	10/2009	Brandt et al.	8,120,548 B1	2/2012	Barber
7,605,882 B1	10/2009	Sutherland et al.	8,132,948 B2	3/2012	Owen et al.
7,616,270 B2	11/2009	Hirabayashi et al.	8,132,976 B2	3/2012	Odell et al.
7,617,022 B1	11/2009	Wood et al.	8,134,434 B2	3/2012	Diederichs et al.
7,618,750 B2	11/2009	Ueda et al.	8,136,690 B2	3/2012	Fang et al.
7,619,739 B1	11/2009	Sutherland et al.	8,137,981 B2	3/2012	Andrew et al.
7,619,825 B1	11/2009	Peng et al.	8,142,016 B2	3/2012	Legerton et al.
7,629,086 B2	12/2009	Otaki et al.	8,149,086 B2	4/2012	Klein et al.
7,639,208 B1	12/2009	Ha et al.	8,152,315 B2	4/2012	Travis et al.
7,639,911 B2	12/2009	Lee et al.	8,155,489 B2	4/2012	Saarikko et al.
7,643,214 B2	1/2010	Amitai	8,159,752 B2	4/2012	Wertheim et al.
7,643,225 B1	1/2010	Tsai	8,160,409 B2	4/2012	Large
7,656,585 B1	2/2010	Powell et al.	8,160,411 B2	4/2012	Levola et al.
7,660,047 B1	2/2010	Travis et al.	8,167,173 B1	5/2012	Simmonds et al.
7,672,055 B2	3/2010	Amitai	8,186,874 B2	5/2012	Sinbar et al.
7,672,549 B2	3/2010	Ghosh et al.	8,188,925 B2	5/2012	DeJean
7,710,622 B2	5/2010	Takabayashi et al.	8,189,263 B1	5/2012	Wang et al.
7,710,654 B2	5/2010	Ashkenazi et al.	8,189,973 B2	5/2012	Travis et al.
7,724,441 B2	5/2010	Amitai	8,194,325 B2	6/2012	Levola et al.
7,724,442 B2	5/2010	Amitai	8,199,803 B2	6/2012	Hauske et al.
7,724,443 B2	5/2010	Amitai	8,213,065 B2	7/2012	Mukawa
7,733,571 B1	6/2010	Li	8,213,755 B2	7/2012	Mukawa et al.
7,733,572 B1	6/2010	Brown et al.	8,220,966 B2	7/2012	Mukawa
7,740,387 B2	6/2010	Schultz et al.	8,224,133 B2	7/2012	Popovich et al.
7,747,113 B2	6/2010	Mukawa et al.	8,233,204 B1	7/2012	Robbins et al.
7,751,122 B2	7/2010	Amitai	8,253,914 B2	8/2012	Kajiya et al.
7,751,662 B2	7/2010	Kleemann et al.	8,254,031 B2	8/2012	Levola
7,764,413 B2	7/2010	Levola	8,264,498 B1	9/2012	Vanderkamp et al.
7,777,819 B2	8/2010	Simmonds	8,294,749 B2	10/2012	Cable
7,778,305 B2	8/2010	Parriaux et al.	8,295,710 B2	10/2012	Marcus
7,778,508 B2	8/2010	Hirayama	8,301,031 B2	10/2012	Gentner et al.
7,843,642 B2	11/2010	Shaoulov et al.	8,305,577 B2	11/2012	Kivioja et al.
7,847,235 B2	12/2010	Krupkin et al.	8,306,423 B2	11/2012	Gottwald et al.
7,864,427 B2	1/2011	Korenaga et al.	8,310,327 B2	11/2012	Willers et al.
7,865,080 B2	1/2011	Hecker et al.	8,314,819 B2	11/2012	Kimmel et al.
7,866,869 B2	1/2011	Karakawa	8,314,993 B2	11/2012	Levola et al.
7,872,707 B1	1/2011	Sutherland et al.	8,320,032 B2	11/2012	Levola
7,872,804 B2	1/2011	Moon et al.	8,321,810 B2	11/2012	Heintze
7,884,593 B2	2/2011	Simmonds et al.	8,325,166 B2	12/2012	Akutsu et al.
7,884,985 B2	2/2011	Amitai et al.	8,329,773 B2	12/2012	Fäcke et al.
7,887,186 B2	2/2011	Watanabe	8,335,040 B2	12/2012	Mukawa et al.
7,903,921 B2	3/2011	Ostergard	8,351,744 B2	1/2013	Travis et al.
7,907,342 B2	3/2011	Simmonds et al.	8,354,640 B2	1/2013	Hamre et al.
7,920,787 B2	4/2011	Gentner et al.	8,354,806 B2	1/2013	Travis et al.
7,928,862 B1	4/2011	Matthews	8,355,610 B2	1/2013	Simmonds
7,936,519 B2	5/2011	Mukawa et al.	8,369,019 B2	2/2013	Baker et al.
7,944,428 B2	5/2011	Travis	8,376,548 B2	2/2013	Schultz
7,944,616 B2	5/2011	Mukawa	8,382,293 B2	2/2013	Phillips, III et al.
7,949,214 B2	5/2011	DeJong et al.	8,384,504 B2	2/2013	Diederichs et al.
7,961,117 B1	6/2011	Zimmerman et al.	8,384,694 B2	2/2013	Powell et al.
7,969,644 B2	6/2011	Tilleman et al.	8,384,730 B1	2/2013	Vanderkamp et al.
7,969,657 B2	6/2011	Cakmakci et al.	8,396,339 B2	3/2013	Mukawa et al.
7,970,246 B2	6/2011	Travis et al.	8,398,242 B2	3/2013	Yamamoto et al.
7,976,208 B2	7/2011	Travis	8,403,490 B2	3/2013	Sugiyama et al.
7,984,884 B1	7/2011	Iliev et al.	8,422,840 B2	4/2013	Large
7,999,982 B2	8/2011	Endo et al.	8,427,439 B2	4/2013	Larsen et al.
8,000,020 B2	8/2011	Amitai et al.	8,432,363 B2	4/2013	Saarikko et al.
8,000,491 B2	8/2011	Brodkin et al.	8,432,372 B2	4/2013	Butler et al.
8,004,765 B2	8/2011	Amitai	8,432,614 B2	4/2013	Amitai
8,014,050 B2	9/2011	McGrew	8,441,731 B2	5/2013	Sprague
8,016,475 B2	9/2011	Travis	8,447,365 B1	5/2013	Imanuel
8,018,579 B1	9/2011	Krah	8,466,953 B2	6/2013	Levola
8,022,942 B2	9/2011	Bathiche et al.	8,472,119 B1	6/2013	Kelly
8,023,783 B2	9/2011	Mukawa et al.	8,472,120 B2	6/2013	Border et al.
RE42,992 E	12/2011	David	8,477,261 B2	7/2013	Travis et al.
8,073,296 B2	12/2011	Mukawa et al.	8,481,130 B2	7/2013	Harding et al.
8,077,274 B2	12/2011	Sutherland et al.	8,482,858 B2	7/2013	Sprague
8,079,713 B2	12/2011	Ashkenazi	8,488,246 B2	7/2013	Border et al.
8,082,222 B2	12/2011	Rangarajan et al.	8,491,121 B2	7/2013	Tilleman et al.
8,086,030 B2	12/2011	Gordon et al.	8,491,136 B2	7/2013	Travis et al.
8,089,568 B1	1/2012	Brown et al.	8,493,366 B2	7/2013	Bathiche et al.
8,093,451 B2	1/2012	Spangenberg et al.	8,493,662 B2	7/2013	Noui
8,098,439 B2	1/2012	Amitai et al.	8,494,229 B2	7/2013	Jarvenpaa et al.
			8,508,848 B2	8/2013	Saarikko
			8,520,309 B2	8/2013	Sprague
			8,547,638 B2	10/2013	Levola
			8,548,290 B2	10/2013	Travers et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,565,560 B2	10/2013	Popovich et al.	9,274,338 B2	3/2016	Robbins et al.
8,578,038 B2	11/2013	Kaikuranta et al.	9,274,339 B1	3/2016	Brown et al.
8,581,831 B2	11/2013	Travis	9,274,349 B2	3/2016	Popovich et al.
8,582,206 B2	11/2013	Travis	9,310,566 B2	4/2016	Valera et al.
8,593,734 B2	11/2013	Laakkonen	9,329,325 B2	5/2016	Simmonds et al.
8,611,014 B2	12/2013	Valera et al.	9,335,604 B2	5/2016	Popovich et al.
8,619,062 B2	12/2013	Powell et al.	9,341,846 B2	5/2016	Popovich et al.
8,633,786 B2	1/2014	Ermolov et al.	9,354,366 B2	5/2016	Jain
8,634,120 B2	1/2014	Popovich et al.	9,366,862 B2	6/2016	Haddick et al.
8,634,139 B1	1/2014	Brown et al.	9,366,864 B1	6/2016	Brown et al.
8,639,072 B2	1/2014	Popovich et al.	9,372,347 B1	6/2016	Levola et al.
8,643,691 B2	2/2014	Rosenfeld et al.	9,377,623 B2	6/2016	Robbins et al.
8,643,948 B2	2/2014	Amitai et al.	9,377,852 B1	6/2016	Shapiro et al.
8,649,099 B2	2/2014	Schultz et al.	9,389,415 B2	7/2016	Fattal et al.
8,654,420 B2	2/2014	Simmonds	9,400,395 B2	7/2016	Travers et al.
8,659,826 B1	2/2014	Brown et al.	9,423,360 B1	8/2016	Kostamo et al.
D701,206 S	3/2014	Luckey et al.	9,429,692 B1	8/2016	Saarikko et al.
8,670,029 B2	3/2014	McEldowney	9,431,794 B2	8/2016	Jain
8,693,087 B2	4/2014	Nowatzyk et al.	9,456,744 B2	10/2016	Popovich et al.
8,698,705 B2	4/2014	Burke	9,459,451 B2	10/2016	Saarikko et al.
8,731,350 B1	5/2014	Lin et al.	9,464,779 B2	10/2016	Popovich et al.
8,736,802 B2	5/2014	Kajiya et al.	9,465,213 B2	10/2016	Simmonds
8,736,963 B2	5/2014	Robbins et al.	9,465,227 B2	10/2016	Popovich et al.
8,742,952 B1	6/2014	Bold	9,494,799 B2	11/2016	Robbins et al.
8,746,008 B1	6/2014	Mauritsen et al.	9,507,150 B1	11/2016	Stratton et al.
8,749,886 B2	6/2014	Gupta	9,513,480 B2	12/2016	Saarikko et al.
8,749,890 B1	6/2014	Wood et al.	9,519,089 B1	12/2016	Brown et al.
8,767,294 B2	7/2014	Chen et al.	9,523,852 B1	12/2016	Brown et al.
8,786,923 B2	7/2014	Chuang et al.	9,535,253 B2	1/2017	Levola et al.
8,810,600 B2	8/2014	Bohn et al.	9,541,383 B2	1/2017	Abovitz et al.
8,810,913 B2	8/2014	Simmonds et al.	9,541,763 B1	1/2017	Heberlein et al.
8,810,914 B2	8/2014	Amitai	9,547,174 B2	1/2017	Gao et al.
8,814,691 B2	8/2014	Haddick et al.	9,551,468 B2	1/2017	Jones
8,816,578 B1	8/2014	Peng et al.	9,551,874 B2	1/2017	Amitai
8,817,350 B1	8/2014	Robbins et al.	9,551,880 B2	1/2017	Amitai
8,824,836 B2	9/2014	Sugiyama	9,599,813 B1	3/2017	Stratton et al.
8,830,143 B1	9/2014	Pitchford et al.	9,612,403 B2	4/2017	Abovitz et al.
8,830,584 B2	9/2014	Saarikko et al.	9,632,226 B2	4/2017	Waldern et al.
8,830,588 B1	9/2014	Brown et al.	9,635,352 B1	4/2017	Henry et al.
8,842,368 B2	9/2014	Simmonds et al.	9,648,313 B1	5/2017	Henry et al.
8,859,412 B2	10/2014	Jain	9,651,368 B2	5/2017	Abovitz et al.
8,872,435 B2	10/2014	Kreitzer et al.	9,664,824 B2	5/2017	Simmonds et al.
8,873,149 B2	10/2014	Bohn et al.	9,664,910 B2	5/2017	Mansharof et al.
8,873,150 B2	10/2014	Amitai	9,674,413 B1	6/2017	Tiana et al.
8,885,112 B2	11/2014	Popovich et al.	9,678,345 B1	6/2017	Melzer et al.
8,885,997 B2	11/2014	Nguyen et al.	9,679,367 B1	6/2017	Wald
8,903,207 B1	12/2014	Brown et al.	9,715,067 B1	7/2017	Brown et al.
8,906,088 B2	12/2014	Pugh et al.	9,715,110 B1	7/2017	Brown et al.
8,913,324 B2	12/2014	Schrader	9,726,540 B2	8/2017	Popovich et al.
8,913,865 B1	12/2014	Bennett	9,727,772 B2	8/2017	Popovich et al.
8,917,453 B2	12/2014	Bohn	9,733,475 B1	8/2017	Brown et al.
8,937,771 B2	1/2015	Robbins et al.	9,746,688 B2	8/2017	Popovich et al.
8,937,772 B1	1/2015	Burns et al.	9,754,507 B1	9/2017	Wenger et al.
8,938,141 B2	1/2015	Magnusson	9,762,895 B1	9/2017	Henry et al.
8,950,867 B2	2/2015	Macnamara	9,766,465 B1	9/2017	Tiana et al.
8,964,298 B2	2/2015	Haddick et al.	9,785,231 B1	10/2017	Zimmerman
8,965,152 B2	2/2015	Simmonds	9,791,694 B1	10/2017	Haverkamp et al.
8,985,803 B2	3/2015	Bohn	9,791,696 B2	10/2017	Woltman et al.
8,989,535 B2	3/2015	Robbins	9,804,389 B2	10/2017	Popovich et al.
9,019,595 B2	4/2015	Jain	9,823,423 B2	11/2017	Waldern et al.
9,025,253 B2	5/2015	Hadad et al.	9,857,605 B2	1/2018	Popovich et al.
9,035,344 B2	5/2015	Jain	9,874,931 B1	1/2018	Koenck et al.
9,075,184 B2	7/2015	Popovich et al.	9,933,684 B2	4/2018	Brown et al.
9,081,178 B2	7/2015	Simmonds et al.	9,977,247 B1	5/2018	Brown et al.
9,097,890 B2	8/2015	Miller et al.	10,089,516 B2	10/2018	Popovich et al.
9,128,226 B2	9/2015	Fattal et al.	10,156,681 B2	12/2018	Waldern et al.
9,129,295 B2	9/2015	Border et al.	10,185,154 B2	1/2019	Popovich et al.
9,164,290 B2	10/2015	Robbins et al.	10,209,517 B2	2/2019	Popovich et al.
9,176,324 B1	11/2015	Scherer et al.	10,216,061 B2	2/2019	Popovich et al.
9,201,270 B2	12/2015	Fattal et al.	10,234,696 B2	3/2019	Popovich et al.
9,215,293 B2	12/2015	Miller	10,241,330 B2	3/2019	Popovich et al.
9,244,275 B1	1/2016	Li	10,330,777 B2	6/2019	Popovich et al.
9,244,280 B1	1/2016	Tiana et al.	10,359,736 B2	7/2019	Popovich et al.
9,244,281 B1	1/2016	Zimmerman et al.	10,409,144 B2	9/2019	Popovich et al.
9,269,854 B2	2/2016	Jain	10,423,813 B2	9/2019	Popovich et al.
			10,527,797 B2	1/2020	Waldern et al.
			10,545,346 B2	1/2020	Waldern et al.
			10,569,449 B1	2/2020	Curts et al.
			10,578,876 B1	3/2020	Lam et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

10,598,938	B1	3/2020	Huang et al.
10,613,268	B1	4/2020	Colburn et al.
10,649,119	B2	5/2020	Mohanty et al.
10,670,876	B2	6/2020	Popovich et al.
10,690,831	B2	6/2020	Calafiore
10,725,312	B2	7/2020	Popovich et al.
10,732,351	B2	8/2020	Colburn et al.
10,823,887	B1	11/2020	Calafiore et al.
10,942,430	B2	3/2021	Waldern et al.
10,983,257	B1	4/2021	Colburn et al.
11,103,892	B1	8/2021	Liao et al.
11,107,972	B2	8/2021	Diest et al.
11,137,603	B2	10/2021	Zhang
11,231,544	B2	1/2022	Lin et al.
11,243,333	B1	2/2022	Ouderkirk et al.
11,306,193	B1	4/2022	Lane et al.
11,307,357	B2	4/2022	Mohanty
11,340,386	B1	5/2022	Ouderkirk et al.
11,391,950	B2	7/2022	Calafiore
2001/0024177	A1	9/2001	Popovich
2001/0043163	A1	11/2001	Waldern et al.
2001/0050756	A1	12/2001	Lipton et al.
2002/0003509	A1	1/2002	Lipton et al.
2002/0009299	A1	1/2002	Lipton
2002/0011969	A1	1/2002	Lipton et al.
2002/0012064	A1	1/2002	Yamaguchi
2002/0021461	A1	2/2002	Ono et al.
2002/0036825	A1	3/2002	Lipton et al.
2002/0047837	A1	4/2002	Suyama et al.
2002/0075240	A1	6/2002	Lieberman et al.
2002/0093701	A1	7/2002	Zhang et al.
2002/0110077	A1	8/2002	Drobot et al.
2002/0126332	A1	9/2002	Popovich
2002/0127497	A1	9/2002	Brown et al.
2002/0131175	A1	9/2002	Yagi et al.
2002/0196332	A1	12/2002	Lipton et al.
2003/0007070	A1	1/2003	Lipton et al.
2003/0025881	A1	2/2003	Hwang
2003/0030912	A1	2/2003	Gleckman et al.
2003/0038912	A1	2/2003	Broer et al.
2003/0039442	A1	2/2003	Bond et al.
2003/0063042	A1	4/2003	Friesem et al.
2003/0063884	A1	4/2003	Smith et al.
2003/0067685	A1	4/2003	Niv
2003/0086670	A1	5/2003	Moridaira et al.
2003/0107809	A1	6/2003	Chen et al.
2003/0149346	A1	8/2003	Arnone et al.
2003/0175004	A1	9/2003	Garito et al.
2003/0197154	A1	10/2003	Manabe et al.
2003/0197157	A1	10/2003	Sutherland et al.
2003/0202247	A1	10/2003	Niv et al.
2003/0228019	A1	12/2003	Eichler et al.
2004/0004767	A1	1/2004	Song
2004/0012833	A1	1/2004	Newswanger et al.
2004/0089842	A1	5/2004	Sutehrland et al.
2004/0109234	A1	6/2004	Levola
2004/0112862	A1	6/2004	Willson et al.
2004/0130797	A1	7/2004	Leigh
2004/0141217	A1	7/2004	Endo et al.
2004/0156008	A1	8/2004	Reznikov et al.
2004/0174348	A1	9/2004	David
2004/0175627	A1	9/2004	Sutherland et al.
2004/0179764	A1	9/2004	Melikechi et al.
2004/0188617	A1	9/2004	Devitt et al.
2004/0208446	A1	10/2004	Bond et al.
2004/0208466	A1	10/2004	Mossberg et al.
2004/0225025	A1	11/2004	Sullivan et al.
2004/0263969	A1	12/2004	Lipton et al.
2004/0263971	A1	12/2004	Lipton et al.
2005/0018304	A1	1/2005	Lipton et al.
2005/0047705	A1	3/2005	Domash et al.
2005/0079663	A1	4/2005	Masutani et al.
2005/0105909	A1	5/2005	Stone
2005/0122395	A1	6/2005	Lipton et al.
2005/0134404	A1	6/2005	Kajiya et al.
2005/0135747	A1	6/2005	Greiner et al.
2005/0136260	A1	6/2005	Garcia
2005/0141066	A1	6/2005	Ouchi
2005/0180687	A1	8/2005	Amitai
2005/0195276	A1	9/2005	Lipton et al.
2005/0218377	A1	10/2005	Lawandy
2005/0231774	A1	10/2005	Hayashi et al.
2005/0232530	A1	10/2005	Kekas
2005/0254752	A1	11/2005	Domash et al.
2005/0259217	A1	11/2005	Lin et al.
2005/0259302	A9	11/2005	Metz et al.
2005/0259944	A1	11/2005	Anderson et al.
2005/0265585	A1	12/2005	Rowe
2005/0269481	A1	12/2005	David et al.
2005/0271258	A1	12/2005	Rowe
2005/0286133	A1	12/2005	Lipton
2006/0002274	A1	1/2006	Kihara et al.
2006/0012878	A1	1/2006	Lipton et al.
2006/0013977	A1	1/2006	Duke et al.
2006/0043938	A1	3/2006	O’Gorman et al.
2006/0055993	A1	3/2006	Kobayashi et al.
2006/0093793	A1	5/2006	Miyakawa et al.
2006/0114564	A1	6/2006	Sutherland et al.
2006/0119837	A1	6/2006	Raguin et al.
2006/0119916	A1	6/2006	Sutherland et al.
2006/0126179	A1	6/2006	Levola
2006/0132914	A1	6/2006	Weiss et al.
2006/0142455	A1	6/2006	Agarwal et al.
2006/0146422	A1	7/2006	Koike
2006/0159864	A1	7/2006	Natarajan et al.
2006/0164593	A1	7/2006	Peyghambarian et al.
2006/0171647	A1	8/2006	Ye et al.
2006/0177180	A1	8/2006	Tazawa et al.
2006/0181683	A1	8/2006	Bhowmik et al.
2006/0191293	A1	8/2006	Kuczma
2006/0215244	A1	9/2006	Yosha et al.
2006/0221063	A1	10/2006	Ishihara
2006/0221448	A1	10/2006	Nivon et al.
2006/0228073	A1	10/2006	Mukawa et al.
2006/0268104	A1	11/2006	Cowan et al.
2006/0268412	A1	11/2006	Downing et al.
2006/0279662	A1	12/2006	Kapellner et al.
2006/0284974	A1	12/2006	Lipton et al.
2006/0285205	A1	12/2006	Lipton et al.
2006/0291021	A1	12/2006	Mukawa
2006/0291052	A1	12/2006	Lipton et al.
2007/0012777	A1	1/2007	Tsikos et al.
2007/0019152	A1	1/2007	Caputo et al.
2007/0019297	A1	1/2007	Stewart et al.
2007/0041684	A1	2/2007	Popovich et al.
2007/0045596	A1	3/2007	King et al.
2007/0052929	A1	3/2007	Allman et al.
2007/0053032	A1	3/2007	Popovich
2007/0070476	A1	3/2007	Yamada et al.
2007/0070504	A1	3/2007	Akutsu et al.
2007/0089625	A1	4/2007	Grinberg et al.
2007/0097502	A1	5/2007	Lipton et al.
2007/0109400	A1	5/2007	Woodgate et al.
2007/0109401	A1	5/2007	Lipton et al.
2007/0116409	A1	5/2007	Bryan et al.
2007/0127348	A1	6/2007	Ooi et al.
2007/0133089	A1	6/2007	Lipton et al.
2007/0133920	A1	6/2007	Lee et al.
2007/0133983	A1	6/2007	Traff
2007/0146624	A1	6/2007	Duston et al.
2007/0146625	A1	6/2007	Ooi et al.
2007/0154153	A1	7/2007	Fomitchov et al.
2007/0160325	A1	7/2007	Son et al.
2007/0177007	A1	8/2007	Lipton et al.
2007/0182915	A1	8/2007	Osawa et al.
2007/0183650	A1	8/2007	Lipton et al.
2007/0188602	A1	8/2007	Cowan et al.
2007/0188837	A1	8/2007	Shimizu et al.
2007/0195409	A1	8/2007	Yun et al.
2007/0206155	A1	9/2007	Lipton
2007/0211164	A1	9/2007	Olsen et al.
2007/0236560	A1	10/2007	Lipton et al.
2007/0237456	A1	10/2007	Blauvelt et al.
2007/0247687	A1	10/2007	Handschy et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2007/0258138	A1	11/2007	Cowan et al.	2010/0092124	A1	4/2010	Magnusson et al.
2007/0263169	A1	11/2007	Lipton	2010/0096562	A1	4/2010	Klunder et al.
2008/0001909	A1	1/2008	Lim	2010/0097674	A1	4/2010	Kasazumi et al.
2008/0018851	A1	1/2008	Lipton et al.	2010/0097820	A1	4/2010	Owen et al.
2008/0024598	A1	1/2008	Perlin et al.	2010/0103078	A1	4/2010	Mukawa et al.
2008/0043334	A1	2/2008	Itzkovitch et al.	2010/0134534	A1	6/2010	Seesselberg et al.
2008/0049100	A1	2/2008	Lipton et al.	2010/0135615	A1	6/2010	Ho et al.
2008/0062259	A1	3/2008	Lipton et al.	2010/0136319	A1	6/2010	Imai et al.
2008/0089073	A1	4/2008	Hikmet	2010/0141555	A1	6/2010	Rorberg et al.
2008/0106775	A1	5/2008	Amitai et al.	2010/0149073	A1	6/2010	Chaum et al.
2008/0106779	A1	5/2008	Peterson et al.	2010/0165465	A1	7/2010	Levola
2008/0117289	A1	5/2008	Schowengerdt et al.	2010/0165660	A1	7/2010	Weber et al.
2008/0136916	A1	6/2008	Wolff	2010/0171680	A1	7/2010	Lapidot et al.
2008/0136923	A1	6/2008	Inbar et al.	2010/0177388	A1	7/2010	Cohen et al.
2008/0138013	A1	6/2008	Parriaux	2010/0202725	A1	8/2010	Popovich et al.
2008/0143964	A1	6/2008	Cowan et al.	2010/0214659	A1	8/2010	Levola
2008/0143965	A1	6/2008	Cowan et al.	2010/0220293	A1	9/2010	Mizushima et al.
2008/0149517	A1	6/2008	Lipton et al.	2010/0225834	A1	9/2010	Li
2008/0151370	A1	6/2008	Cook et al.	2010/0231532	A1	9/2010	Nho et al.
2008/0151379	A1	6/2008	Amitai	2010/0231693	A1	9/2010	Levola
2008/0186573	A1	8/2008	Lipton	2010/0231705	A1	9/2010	Yahav et al.
2008/0186574	A1	8/2008	Robinson et al.	2010/0232003	A1	9/2010	Baldy et al.
2008/0186604	A1	8/2008	Amitai	2010/0246003	A1	9/2010	Simmonds et al.
2008/0198471	A1	8/2008	Amitai	2010/0246004	A1	9/2010	Simmonds
2008/0225187	A1	9/2008	Yamanaka	2010/0246993	A1	9/2010	Rieger et al.
2008/0226281	A1	9/2008	Lipton	2010/0265117	A1	10/2010	Weiss
2008/0239067	A1	10/2008	Lipton	2010/0277803	A1	11/2010	Pockett et al.
2008/0239068	A1	10/2008	Lipton	2010/0284085	A1	11/2010	Laakkonen
2008/0273081	A1	11/2008	Lipton	2010/0284090	A1	11/2010	Simmonds
2008/0278812	A1	11/2008	Amitai	2010/0284180	A1	11/2010	Popovich et al.
2008/0285137	A1	11/2008	Simmonds et al.	2010/0296163	A1	11/2010	Saarikko
2008/0285140	A1	11/2008	Amitai	2010/0299814	A1	12/2010	Celona et al.
2008/0297731	A1	12/2008	Powell et al.	2010/0315719	A1	12/2010	Saarikko et al.
2008/0297807	A1	12/2008	Feldman et al.	2010/0321781	A1	12/2010	Levola et al.
2008/0298649	A1	12/2008	Ennis et al.	2010/0322555	A1	12/2010	Vermeulen et al.
2008/0303895	A1	12/2008	Akka et al.	2011/0001895	A1	1/2011	Dahl
2008/0303896	A1	12/2008	Lipton et al.	2011/0002143	A1	1/2011	Saarikko et al.
2008/0304111	A1	12/2008	Queenan et al.	2011/0013423	A1	1/2011	Selbrede et al.
2008/0309586	A1	12/2008	Vitale	2011/0019250	A1	1/2011	Aiki et al.
2008/0316303	A1	12/2008	Chiu et al.	2011/0019874	A1	1/2011	Jarvenpaa et al.
2008/0316375	A1	12/2008	Lipton et al.	2011/0026128	A1	2/2011	Baker et al.
2009/0017424	A1	1/2009	Yoeli et al.	2011/0026774	A1	2/2011	Flohr et al.
2009/0019222	A1	1/2009	Verma et al.	2011/0032602	A1	2/2011	Rothenberg et al.
2009/0052017	A1	2/2009	Sasaki	2011/0032618	A1	2/2011	Handerek et al.
2009/0052046	A1	2/2009	Amitai	2011/0032706	A1	2/2011	Mukawa
2009/0052047	A1	2/2009	Amitai	2011/0038024	A1	2/2011	Wang et al.
2009/0067774	A1	3/2009	Magnusson	2011/0050548	A1	3/2011	Blumenfeld et al.
2009/0074356	A1	3/2009	Sanchez et al.	2011/0063604	A1	3/2011	Hamre et al.
2009/0097122	A1	4/2009	Niv	2011/0096401	A1	4/2011	Levola
2009/0097127	A1	4/2009	Amitai	2011/0102711	A1	5/2011	Sutherland et al.
2009/0121301	A1	5/2009	Chang	2011/0109880	A1	5/2011	Nummela
2009/0122413	A1	5/2009	Hoffman et al.	2011/0157707	A1	6/2011	Tilleman et al.
2009/0122414	A1	5/2009	Amitai	2011/0164221	A1	7/2011	Tilleman et al.
2009/0128495	A1	5/2009	Kong et al.	2011/0187293	A1	8/2011	Travis et al.
2009/0128902	A1	5/2009	Niv et al.	2011/0211239	A1	9/2011	Mukawa et al.
2009/0128911	A1	5/2009	Itzkovitch et al.	2011/0235179	A1	9/2011	Simmonds
2009/0136246	A1	5/2009	Murakami	2011/0235365	A1	9/2011	McCollum et al.
2009/0141324	A1	6/2009	Mukawa	2011/0236803	A1	9/2011	Weiser et al.
2009/0153437	A1	6/2009	Aharoni	2011/0238399	A1	9/2011	Ophir et al.
2009/0169152	A1	7/2009	Oestergard	2011/0242349	A1	10/2011	Izuha et al.
2009/0190222	A1	7/2009	Simmonds et al.	2011/0242661	A1	10/2011	Simmonds
2009/0213208	A1	8/2009	Glatt	2011/0242670	A1	10/2011	Simmonds
2009/0237804	A1	9/2009	Amitai et al.	2011/0249309	A1	10/2011	McPheters et al.
2009/0242021	A1	10/2009	Petkie et al.	2011/0274435	A1	11/2011	Fini et al.
2009/0296218	A1	12/2009	Ryytty	2011/0299075	A1	12/2011	Meade et al.
2009/0303599	A1	12/2009	Levola	2011/0310356	A1	12/2011	Vallius
2009/0316246	A1	12/2009	Asai et al.	2012/0007979	A1	1/2012	Schneider et al.
2010/0014312	A1	1/2010	Travis et al.	2012/0027347	A1	2/2012	Mathal et al.
2010/0039796	A1	2/2010	Mukawa	2012/0033306	A1	2/2012	Valera et al.
2010/0053565	A1	3/2010	Mizushima et al.	2012/0044572	A1	2/2012	Simmonds et al.
2010/0060551	A1	3/2010	Sugiyama et al.	2012/0044573	A1	2/2012	Simmonds et al.
2010/0060990	A1	3/2010	Wertheim et al.	2012/0062850	A1	3/2012	Travis
2010/0065726	A1	3/2010	Zhong et al.	2012/0062998	A1	3/2012	Schultz et al.
2010/0079865	A1	4/2010	Saarikko et al.	2012/0075168	A1	3/2012	Osterhout et al.
2010/0086256	A1	4/2010	Ben Bakir et al.	2012/0081789	A1	4/2012	Mukawa et al.
				2012/0092632	A1	4/2012	McLeod et al.
				2012/0099203	A1	4/2012	Boubis et al.
				2012/0105634	A1	5/2012	Meidan et al.
				2012/0120493	A1	5/2012	Simmonds et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2012/0127577 A1	5/2012	Desserouer	2014/0024159 A1	1/2014	Jain
2012/0162549 A1	6/2012	Gao et al.	2014/0027006 A1	1/2014	Foley et al.
2012/0162764 A1	6/2012	Shimizu	2014/0037242 A1	2/2014	Popovich et al.
2012/0176665 A1	7/2012	Song et al.	2014/0043672 A1	2/2014	Clarke et al.
2012/0183888 A1	7/2012	Oliveira et al.	2014/0043689 A1	2/2014	Mason
2012/0194420 A1	8/2012	Osterhout et al.	2014/0055845 A1	2/2014	Jain
2012/0200532 A1	8/2012	Powell et al.	2014/0063055 A1	3/2014	Osterhout et al.
2012/0206811 A1	8/2012	Mukawa et al.	2014/0064655 A1	3/2014	Nguyen et al.
2012/0206937 A1	8/2012	Travis et al.	2014/0071538 A1	3/2014	Muller
2012/0207432 A1	8/2012	Travis et al.	2014/0098010 A1	4/2014	Travis
2012/0207434 A1	8/2012	Large	2014/0104665 A1	4/2014	Popovich et al.
2012/0214089 A1	8/2012	Hönel et al.	2014/0104685 A1	4/2014	Bohn et al.
2012/0214090 A1	8/2012	Weiser et al.	2014/0118647 A1	5/2014	Momonoï et al.
2012/0218481 A1	8/2012	Popovich et al.	2014/0130132 A1	5/2014	Cahill et al.
2012/0224062 A1	9/2012	Lacoste et al.	2014/0140653 A1	5/2014	Brown et al.
2012/0235884 A1	9/2012	Miller et al.	2014/0140654 A1	5/2014	Brown et al.
2012/0235886 A1	9/2012	Border et al.	2014/0146394 A1	5/2014	Tout et al.
2012/0235900 A1	9/2012	Border et al.	2014/0152778 A1	6/2014	Ihlenburg et al.
2012/0242661 A1	9/2012	Takagi et al.	2014/0160576 A1	6/2014	Robbins et al.
2012/0280956 A1	11/2012	Yamamoto et al.	2014/0168055 A1	6/2014	Smith
2012/0281943 A1	11/2012	Popovich et al.	2014/0168260 A1	6/2014	O'Brien et al.
2012/0290973 A1	11/2012	Robertson et al.	2014/0168735 A1	6/2014	Yuan et al.
2012/0294037 A1	11/2012	Holman et al.	2014/0168783 A1	6/2014	Luebke et al.
2012/0300311 A1	11/2012	Simmonds et al.	2014/0172296 A1	6/2014	Shtukater
2012/0320460 A1	12/2012	Levola	2014/0176528 A1	6/2014	Robbins
2012/0326950 A1	12/2012	Park et al.	2014/0177023 A1	6/2014	Gao et al.
2013/0016324 A1	1/2013	Travis	2014/0185286 A1	7/2014	Popovich et al.
2013/0016362 A1	1/2013	Gong et al.	2014/0198128 A1	7/2014	Hong et al.
2013/0021392 A1	1/2013	Travis	2014/0204455 A1	7/2014	Popovich et al.
2013/0021586 A1	1/2013	Lippey	2014/0211322 A1	7/2014	Bohn et al.
2013/0027006 A1	1/2013	Holloway et al.	2014/0218468 A1	8/2014	Gao et al.
2013/0033485 A1	2/2013	Kollin et al.	2014/0218801 A1	8/2014	Simmonds et al.
2013/0039619 A1	2/2013	Laughlin	2014/0232759 A1	8/2014	Simmonds et al.
2013/0044376 A1	2/2013	Valera et al.	2014/0240834 A1	8/2014	Mason
2013/0059233 A1	3/2013	Askham	2014/0240842 A1	8/2014	Nguyen et al.
2013/0069850 A1	3/2013	Mukawa et al.	2014/0267420 A1	9/2014	Schowengerdt et al.
2013/0077049 A1	3/2013	Bohn	2014/0268353 A1	9/2014	Fujimura et al.
2013/0088637 A1	4/2013	Duparre	2014/0300947 A1	10/2014	Fattal et al.
2013/0093893 A1	4/2013	Schofield et al.	2014/0300960 A1	10/2014	Santori et al.
2013/0101253 A1	4/2013	Popovich et al.	2014/0300966 A1	10/2014	Travers et al.
2013/0107186 A1	5/2013	Ando et al.	2014/0327970 A1	11/2014	Bohn et al.
2013/0117377 A1	5/2013	Miller	2014/0330159 A1	11/2014	Costa et al.
2013/0125027 A1	5/2013	Abovitz et al.	2014/0367719 A1	12/2014	Jain
2013/0128230 A1	5/2013	Macnamara	2014/0375542 A1	12/2014	Robbins et al.
2013/0138275 A1	5/2013	Nauman et al.	2014/0375789 A1	12/2014	Lou et al.
2013/0141937 A1	6/2013	Katsuta et al.	2014/0375790 A1	12/2014	Robbins et al.
2013/0143336 A1	6/2013	Jain	2015/0001677 A1	1/2015	Palumbo et al.
2013/0163089 A1	6/2013	Bohn	2015/0003796 A1	1/2015	Bennett
2013/0170031 A1	7/2013	Bohn et al.	2015/0010265 A1	1/2015	Popovich et al.
2013/0176704 A1	7/2013	Lanman et al.	2015/0015946 A1	1/2015	Muller
2013/0184904 A1	7/2013	Gadzinski	2015/0016777 A1	1/2015	Abovitz et al.
2013/0200710 A1	8/2013	Robbins	2015/0035744 A1	2/2015	Robbins et al.
2013/0207887 A1	8/2013	Raffle et al.	2015/0036068 A1	2/2015	Fattal et al.
2013/0224634 A1	8/2013	Berneth et al.	2015/0058791 A1	2/2015	Robertson et al.
2013/0229717 A1	9/2013	Amitai	2015/0062675 A1	3/2015	Ayres et al.
2013/0249895 A1	9/2013	Westerinen et al.	2015/0062707 A1	3/2015	Simmonds et al.
2013/0250207 A1	9/2013	Bohn	2015/0086163 A1	3/2015	Valera et al.
2013/0250430 A1	9/2013	Robbins et al.	2015/0086907 A1	3/2015	Mizuta et al.
2013/0250431 A1	9/2013	Robbins et al.	2015/0107671 A1	4/2015	Bodan et al.
2013/0257848 A1	10/2013	Westerinen et al.	2015/0109763 A1	4/2015	Shinkai et al.
2013/0258701 A1	10/2013	Westerinen et al.	2015/0125109 A1	5/2015	Robbins et al.
2013/0267309 A1	10/2013	Robbins et al.	2015/0148728 A1	5/2015	Sallum et al.
2013/0271731 A1	10/2013	Popovich et al.	2015/0160529 A1	6/2015	Popovich et al.
2013/0277890 A1	10/2013	Bowman et al.	2015/0167868 A1	6/2015	Boncha
2013/0300997 A1	11/2013	Popovich et al.	2015/0177443 A1	6/2015	Faecke et al.
2013/0305437 A1	11/2013	Weller et al.	2015/0177686 A1	6/2015	Lee et al.
2013/0312811 A1	11/2013	Aspnes et al.	2015/0177688 A1	6/2015	Popovich et al.
2013/0314789 A1	11/2013	Saarikko et al.	2015/0185475 A1	7/2015	Saarikko et al.
2013/0314793 A1	11/2013	Robbins et al.	2015/0219834 A1	8/2015	Nichol et al.
2013/0322810 A1	12/2013	Robbins	2015/0235447 A1	8/2015	Abovitz et al.
2013/0328948 A1	12/2013	Kunkel et al.	2015/0235448 A1	8/2015	Schowengerdt et al.
2013/0342525 A1	12/2013	Benko et al.	2015/0243068 A1	8/2015	Solomon
2014/0003762 A1	1/2014	Macnamara	2015/0247975 A1	9/2015	Abovitz et al.
2014/0009809 A1	1/2014	Pyun et al.	2015/0260994 A1	9/2015	Akutsu et al.
2014/0022616 A1	1/2014	Popovich et al.	2015/0268415 A1	9/2015	Schowengerdt et al.
			2015/0277375 A1	10/2015	Large et al.
			2015/0285682 A1	10/2015	Popovich et al.
			2015/0288129 A1	10/2015	Jain
			2015/0289762 A1	10/2015	Popovich et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2015/0309264 A1 10/2015 Abovitz et al.
 2015/0316768 A1 11/2015 Simmonds
 2015/0346490 A1 12/2015 Tekolste et al.
 2015/0346495 A1 12/2015 Welch et al.
 2015/0355394 A1 12/2015 Leighton et al.
 2016/0003847 A1 1/2016 Ryan et al.
 2016/0004090 A1 1/2016 Popovich et al.
 2016/0026253 A1 1/2016 Bradski et al.
 2016/0033705 A1 2/2016 Fattal
 2016/0033706 A1 2/2016 Fattal et al.
 2016/0038992 A1 2/2016 Arthur et al.
 2016/0041387 A1 2/2016 Valera et al.
 2016/0077338 A1 3/2016 Robbins et al.
 2016/0085300 A1 3/2016 Robbins et al.
 2016/0116739 A1 4/2016 TeKolste et al.
 2016/0124223 A1 5/2016 Shinbo et al.
 2016/0124241 A1 5/2016 Popovich et al.
 2016/0132025 A1 5/2016 Taff et al.
 2016/0170226 A1 6/2016 Popovich et al.
 2016/0178901 A1 6/2016 Ishikawa
 2016/0195664 A1 7/2016 Fattal et al.
 2016/0209648 A1 7/2016 Haddick et al.
 2016/0209657 A1 7/2016 Popovich et al.
 2016/0231568 A1 8/2016 Saarikko et al.
 2016/0231570 A1 8/2016 Levola et al.
 2016/0238772 A1 8/2016 Waldern et al.
 2016/0266398 A1 9/2016 Poon et al.
 2016/0274362 A1 9/2016 Tinch et al.
 2016/0283773 A1 9/2016 Popovich et al.
 2016/0291328 A1 10/2016 Popovich et al.
 2016/0299344 A1 10/2016 Dobschal et al.
 2016/0320536 A1 11/2016 Simmonds et al.
 2016/0327705 A1 11/2016 Simmonds et al.
 2016/0336033 A1 11/2016 Tanaka
 2016/0341964 A1 11/2016 Amitai
 2016/0363840 A1 12/2016 Mizoguchi et al.
 2016/0377879 A1 12/2016 Popovich et al.
 2017/0003505 A1 1/2017 Vallius et al.
 2017/0010466 A1 1/2017 Klug et al.
 2017/0010488 A1 1/2017 Klug et al.
 2017/0030550 A1 2/2017 Popovich et al.
 2017/0031160 A1 2/2017 Popovich et al.
 2017/0031171 A1 2/2017 Vallius et al.
 2017/0032166 A1 2/2017 Raguin et al.
 2017/0034435 A1 2/2017 Vallius
 2017/0038579 A1 2/2017 Yeoh et al.
 2017/0052374 A1 2/2017 Waldern et al.
 2017/0052376 A1 2/2017 Amitai et al.
 2017/0059759 A1 3/2017 Ayres et al.
 2017/0059775 A1 3/2017 Coles et al.
 2017/0102543 A1 4/2017 Vallius
 2017/0115487 A1 4/2017 Travis et al.
 2017/0123208 A1 5/2017 Vallius
 2017/0131460 A1 5/2017 Lin et al.
 2017/0131545 A1 5/2017 Wall et al.
 2017/0131546 A1 5/2017 Woltman et al.
 2017/0131551 A1 5/2017 Robbins et al.
 2017/0160546 A1 6/2017 Bull et al.
 2017/0180404 A1 6/2017 Bersch et al.
 2017/0180408 A1 6/2017 Yu et al.
 2017/0192246 A9 7/2017 Popovich et al.
 2017/0199333 A1 7/2017 Waldern et al.
 2017/0212295 A1 7/2017 Vasylyev
 2017/0219841 A1 8/2017 Popovich et al.
 2017/0255257 A1 9/2017 Tiana et al.
 2017/0270637 A1 9/2017 Perreault et al.
 2017/0276940 A1 9/2017 Popovich et al.
 2017/0299860 A1 10/2017 Wall et al.
 2017/0356801 A1 12/2017 Popovich et al.
 2017/0357841 A1 12/2017 Popovich et al.
 2018/0011324 A1 1/2018 Popovich et al.
 2018/0052277 A1 2/2018 Schowengerdt et al.
 2018/0059305 A1 3/2018 Popovich et al.
 2018/0074265 A1 3/2018 Waldern et al.
 2018/0074352 A1 3/2018 Popovich et al.

2018/0113303 A1 4/2018 Popovich et al.
 2018/0120669 A1 5/2018 Popovich et al.
 2018/0143449 A1 5/2018 Popovich et al.
 2018/0188542 A1 7/2018 Waldern et al.
 2018/0210198 A1 7/2018 Brown et al.
 2018/0210396 A1 7/2018 Popovich et al.
 2018/0232048 A1 8/2018 Popovich et al.
 2018/0246354 A1 8/2018 Popovich et al.
 2018/0252869 A1 9/2018 Ayres et al.
 2018/0275402 A1 9/2018 Popovich et al.
 2018/0284440 A1 10/2018 Popovich et al.
 2018/0373115 A1 12/2018 Brown et al.
 2019/0042827 A1 2/2019 Popovich et al.
 2019/0064735 A1 2/2019 Waldern et al.
 2019/0072723 A1 3/2019 Waldern et al.
 2019/0113751 A9 4/2019 Waldern et al.
 2019/0113829 A1 4/2019 Waldern et al.
 2019/0121027 A1 4/2019 Popovich et al.
 2019/0129085 A1 5/2019 Waldern et al.
 2019/0171031 A1 6/2019 Popovich et al.
 2019/0187538 A1 6/2019 Popovich et al.
 2019/0212195 A9 7/2019 Popovich et al.
 2019/0212573 A1 7/2019 Popovich et al.
 2019/0212588 A1 7/2019 Waldern et al.
 2019/0212589 A1 7/2019 Waldern et al.
 2019/0212596 A1 7/2019 Waldern et al.
 2019/0212597 A1 7/2019 Waldern et al.
 2019/0212698 A1 7/2019 Waldern et al.
 2019/0212699 A1 7/2019 Waldern et al.
 2019/0219822 A1 7/2019 Popovich et al.
 2019/0243209 A1* 8/2019 Perreault G09G 3/007
 2019/0265486 A1 8/2019 Hansotte et al.
 2019/0324202 A1 10/2019 Colburn et al.
 2020/0018875 A1 1/2020 Mohanty et al.
 2020/0026074 A1 1/2020 Waldern et al.
 2020/0033190 A1 1/2020 Popovich et al.
 2020/0057353 A1 2/2020 Popovich et al.
 2020/0158943 A1 5/2020 Calafiore
 2020/0183200 A1 6/2020 Diest et al.
 2020/0209483 A1 7/2020 Mohanty
 2020/0247016 A1 8/2020 Calafiore
 2020/0249568 A1 8/2020 Rao et al.
 2020/0271973 A1 8/2020 Waldern et al.
 2020/0400951 A1 12/2020 Zhang
 2020/0409151 A1 12/2020 Calafiore
 2021/0109285 A1 4/2021 Jiang et al.
 2021/0191122 A1 6/2021 Yaroshchuk et al.
 2021/0199873 A1 7/2021 Shi et al.
 2021/0199971 A1 7/2021 Lee et al.
 2021/0238374 A1 8/2021 Ye et al.
 2021/0405514 A1 12/2021 Waldern et al.
 2022/0019015 A1 1/2022 Calafiore et al.
 2022/0082739 A1 3/2022 Franke et al.
 2022/0091323 A1 3/2022 Yaroshchuk et al.
 2022/0204790 A1 6/2022 Zhang et al.
 2022/0206232 A1 6/2022 Zhang et al.

FOREIGN PATENT DOCUMENTS

CN 200944140 Y 9/2007
 CN 101103297 A 1/2008
 CN 101151562 A 3/2008
 CN 101263412 A 9/2008
 CN 100492099 C 5/2009
 CN 101589326 A 11/2009
 CN 101688977 A 3/2010
 CN 101793555 A 8/2010
 CN 101881936 A 11/2010
 CN 102314092 A 1/2012
 CN 103562802 A 2/2014
 CN 103777282 A 5/2014
 CN 103823267 A 5/2014
 CN 104040410 A 9/2014
 CN 104204901 A 12/2014
 CN 104956252 A 9/2015
 CN 10574539 A 11/2015
 CN 105074537 A 11/2015
 CN 105190407 A 12/2015
 CN 105229514 A 1/2016

(56)

References Cited

FOREIGN PATENT DOCUMENTS

CN	105393159	A	3/2016	JP	2001296503	A	10/2001
CN	105408801	A	3/2016	JP	2002090858	A	3/2002
CN	105408802	A	3/2016	JP	2002122906	A	4/2002
CN	105408803	A	3/2016	JP	2002156617	A	5/2002
CN	105531716	A	4/2016	JP	2002162598	A	6/2002
CN	105705981	A	6/2016	JP	2002523802	A	7/2002
CN	106125308	A	11/2016	JP	2002529790	A	9/2002
CN	106716223	A	5/2017	JP	2002311379	A	10/2002
CN	107466372	A	12/2017	JP	2003066428	A	3/2003
CN	108474945	A	8/2018	JP	2003270419	A	9/2003
CN	108780224	A	11/2018	JP	2004157245	A	6/2004
CN	109154717	A	1/2019	JP	2006350129	A	12/2006
CN	103823267	B	5/2019	JP	2007011057	A	1/2007
CN	110383117	A	10/2019	JP	2007094175	A	4/2007
CN	111386495	A	7/2020	JP	2007219106	A	8/2007
CN	114341729	A	4/2022	JP	2008112187	A	5/2008
DE	19751190	A1	5/1999	JP	2009036955	A	2/2009
DE	10221837	A1	12/2003	JP	2009133999	A	6/2009
DE	102006003785	A1	7/2007	JP	2009211091	A	9/2009
DE	102012108424	A1	3/2014	JP	4367775	B2	11/2009
DE	102013209436	A1	11/2014	JP	2012137616	A	7/2012
EP	0795775	A2	9/1997	JP	5303928	B2	10/2013
EP	0822441	A2	2/1998	JP	2013235256	A	11/2013
EP	1347641	A1	9/2003	JP	2014132328	A	7/2014
EP	1413972	A1	4/2004	JP	2015053163	A	3/2015
EP	1526709	A2	4/2005	JP	2015523586	A	8/2015
EP	1748305	A1	1/2007	JP	2015172713	A	10/2015
EP	1938152	A1	7/2008	JP	2016030503	A	3/2016
EP	1413972	B1	10/2008	JP	2018508037	A	3/2018
EP	2110701	A1	10/2009	JP	2018533069	A	11/2018
EP	2225592	A1	9/2010	JP	2019512745	A	5/2019
EP	2244114	A1	10/2010	JP	2019520595	A	7/2019
EP	2326983	A1	6/2011	JP	6598269	B2	10/2019
EP	2381290	A1	10/2011	JP	2020-537187	A	12/2020
EP	1828832	B1	5/2013	KR	20060132474	A	12/2006
EP	2733517	A1	5/2014	KR	20100092059	A	8/2010
EP	1573369	B1	7/2014	KR	20140140063	A	12/2014
EP	2748670	A1	7/2014	KR	20140142337	A	12/2014
EP	2929378	A1	10/2015	KR	1020220038452	A	3/2022
EP	2748670	B1	11/2015	TW	200535633	A	11/2005
EP	2995986	A1	3/2016	TW	200801583	A	1/2008
EP	2995986	B1	4/2017	TW	201314263	A	4/2013
EP	3256888	A1	12/2017	TW	201600943	A	1/2016
EP	3359999	A1	8/2018	TW	201604601	A	2/2016
EP	2494388	B1	11/2018	WO	1997001133	A1	1/1997
EP	3433658	A1	1/2019	WO	1997027519	A1	7/1997
EP	3433659	A1	1/2019	WO	1998004650	A1	2/1998
EP	2842003	B1	2/2019	WO	1999009440	A1	2/1999
EP	3548939	A2	10/2019	WO	1999052002	A1	10/1999
EP	3698214		8/2020	WO	2000016136	A1	3/2000
EP	4004646	A1	6/2022	WO	2000023830		4/2000
FR	2677463	A1	12/1992	WO	2000023832	A1	4/2000
GB	2115178	A	9/1983	WO	2000023847		4/2000
GB	2140935	A	12/1984	WO	2000028369	A2	5/2000
GB	2508661	A	6/2014	WO	2000028369	A3	10/2000
GB	2509536	A	7/2014	WO	2001050200	A2	7/2001
GB	2512077	A	9/2014	WO	2001090822	A1	11/2001
GB	2514658	A	12/2014	WO	2002082168	A1	10/2002
HK	1204684	A1	11/2015	WO	2003081320	A1	10/2003
HK	1205563	A1	12/2015	WO	200410226	A2	11/2004
HK	1205793	A1	12/2015	WO	2005001753	A1	1/2005
HK	1206101	A1	12/2015	WO	2005006065	A8	1/2005
JP	02186319	A	7/1990	WO	2005006065	A3	2/2005
JP	03239384	A	10/1991	WO	2005073798	A1	8/2005
JP	06294952	A	10/1994	WO	2006002870	A1	1/2006
JP	07098439	A	4/1995	WO	2006064301	A1	6/2006
JP	0990312	A	4/1997	WO	2006064325	A1	6/2006
JP	11109320	A	4/1999	WO	2006064334	A1	6/2006
JP	11142806	A	5/1999	WO	2006102073	A2	9/2006
JP	2953444	B2	9/1999	WO	2006132614	A1	12/2006
JP	2000056259	A	2/2000	WO	2006102073	A3	1/2007
JP	2000511306	A	8/2000	WO	2007015141	A2	2/2007
JP	2000261706	A	9/2000	WO	2007029032	A1	3/2007
JP	2000267042	A	9/2000	WO	2007085682	A1	8/2007
JP	2001027739	A	1/2001	WO	2007130130	A2	11/2007
				WO	2007141587	A1	12/2007
				WO	2007141589	A1	12/2007
				WO	2008011066	A2	1/2008
				WO	2008011066	A9	5/2008

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO 2008081070 A1 7/2008
 WO 2008100545 A2 8/2008
 WO 2008011066 A3 12/2008
 WO 2009013597 A2 1/2009
 WO 2009013597 A3 1/2009
 WO 2009077802 A1 6/2009
 WO 2009077803 A1 6/2009
 WO 2009101238 A1 8/2009
 WO 2007130130 A3 9/2009
 WO 2009155437 A1 12/2009
 WO 2009155437 A8 3/2010
 WO 2010023444 A1 3/2010
 WO 2010057219 A1 5/2010
 WO 2010067114 A1 6/2010
 WO 2010067117 A1 6/2010
 WO 2010078856 A1 7/2010
 WO 2010104692 A2 9/2010
 WO 2010122330 A1 10/2010
 WO 2010125337 A2 11/2010
 WO 2010125337 A3 11/2010
 WO 2011012825 A1 2/2011
 WO 2011032005 A2 3/2011
 WO 2011042711 A2 4/2011
 WO 2011051660 A1 5/2011
 WO 2011055109 A2 5/2011
 WO 2011042711 A3 6/2011
 WO 2011073673 A1 6/2011
 WO 2011107831 A1 9/2011
 WO 2011110821 A1 9/2011
 WO 2011131978 A1 10/2011
 WO 2012052352 A1 4/2012
 WO 2012062658 A1 5/2012
 WO 2012136970 A1 10/2012
 WO 2012158950 A1 11/2012
 WO 2012172295 A1 12/2012
 WO 2013027004 A1 2/2013
 WO 2013027006 A1 2/2013
 WO 2013033274 A1 3/2013
 WO 2013034879 A1 3/2013
 WO 2013049012 A1 4/2013
 WO 2013102759 A2 7/2013
 WO 2013163347 A1 10/2013
 WO 2013167864 A1 11/2013
 WO 2013190257 A1 12/2013
 WO 2014064427 A1 5/2014
 WO 2014080155 A1 5/2014
 WO 2014085734 A1 6/2014
 WO 2014090379 A1 6/2014
 WO 2014091200 A1 6/2014
 WO 2014093601 A1 6/2014
 WO 2014100182 A1 6/2014
 WO 2014113506 A1 7/2014
 WO 2014116615 A1 7/2014
 WO 2014130383 A1 8/2014
 WO 2014144526 A2 9/2014
 WO 2014159621 A1 10/2014
 WO 2014164901 A1 10/2014
 WO 2014176695 A1 11/2014
 WO 2014179632 A1 11/2014
 WO 2014188149 A1 11/2014
 WO 2014209733 A1 12/2014
 WO 2014209819 A1 12/2014
 WO 2014209820 A1 12/2014
 WO 2014209821 A1 12/2014
 WO 2014210349 A1 12/2014
 WO 2015006784 A2 1/2015
 WO 2015015138 A1 2/2015
 WO 2015017291 A1 2/2015
 WO 2015069553 A1 5/2015
 WO 2015081313 A2 6/2015
 WO 2015117039 A1 8/2015
 WO 2015145119 A1 10/2015
 WO 2016010289 A1 1/2016
 WO 2016020630 A2 2/2016
 WO 2016020643 A1 2/2016

WO 2016025350 A1 2/2016
 WO 2016020630 A3 3/2016
 WO 2016042283 A1 3/2016
 WO 2016044193 A1 3/2016
 WO 2016046514 A1 3/2016
 WO 2016103263 A1 6/2016
 WO 2016111706 A1 7/2016
 WO 2016111707 A1 7/2016
 WO 2016111708 A1 7/2016
 WO 2016111709 A1 7/2016
 WO 2016113534 A1 7/2016
 WO 2016116733 A1 7/2016
 WO 2016118107 A1 7/2016
 WO 2016122679 A1 8/2016
 WO 2016130509 A1 8/2016
 WO 2016135434 A1 9/2016
 WO 2016156776 A1 10/2016
 WO 2016181108 A1 11/2016
 WO 2017060665 A1 4/2017
 WO 2017094129 A1 6/2017
 WO 2017120320 A1 7/2017
 WO 2017134412 A1 8/2017
 WO 2017160367 A1 9/2017
 WO 2017162999 A1 9/2017
 WO 2017178781 A1 10/2017
 WO 2017180403 A1 10/2017
 WO 2017182771 A1 10/2017
 WO 2017203200 A1 11/2017
 WO 2017203201 A1 11/2017
 WO 2017207987 A1 12/2017
 WO 2018102834 A2 6/2018
 WO 2018102834 A3 6/2018
 WO 2018096359 A3 7/2018
 WO 2018129398 A1 7/2018
 WO 2017162999 A8 8/2018
 WO 2018150163 A1 8/2018
 WO 2019046649 A1 3/2019
 WO 2019077307 A1 4/2019
 WO 2019079350 A2 4/2019
 WO 2019079350 A3 4/2019
 WO 2019046649 A8 5/2019
 WO 2019122806 A1 6/2019
 WO 2019135784 A1 7/2019
 WO 2019135796 A1 7/2019
 WO 2019135837 A1 7/2019
 WO 2019136470 A 7/2019
 WO 2019136471 A1 7/2019
 WO 2019136473 A1 7/2019
 WO 2019171038 A1 9/2019
 WO 2020212682 A1 10/2020
 WO 2021021926 A1 2/2021
 WO 2021032982 A1 2/2021
 WO 2021032983 A1 2/2021
 WO 2021044121 A1 3/2021

OTHER PUBLICATIONS

Trisnadi, "Speckle contrast reduction in laser projection displays", Proc. SPIE 4657, 2002, 7 pgs.
 Tzeng et al., "Axially symmetric polarization converters based on photo-aligned liquid crystal films", Optics Express, Mar. 17, 2008, vol. 16, No. 6, pp. 3768-3775.
 Upatnieks et al., "Color Holograms for white light reconstruction", Applied Physics Letters, Jun. 1, 1996, vol. 8, No. 11, pp. 286-287.
 Urey, "Diffractive exit pupil expander for display applications", Applied Optics, Nov. 10, 2001, vol. 40, Issue 32, pp. 5840-5851.
 Ushenko, "The Vector Structure of Laser Biospeckle Fields and Polarization Diagnostics of Collagen Skin Structures", Laser Physics, 2000, vol. 10, No. 5, pp. 1143-1149.
 Valoriani, "Mixed Reality: Dalle demo a un prodotto", Disruptive Technologies Conference, Sep. 23, 2016, 67 pgs.
 Van Gerwen et al., "Nanoscaled interdigitated electrode arrays for biochemical sensors". Sensors and Actuators. Mar. 3, 1998, vol. B 49, pp. 73-80.
 Vecchi, "Studi Esr Di Sistemi Complessi Basati Su Cristalli Liquidi", Thesis, University of Bologna, Department of Physical and Inorganic Chemistry, 2004-2006, 110 pgs.

(56)

References Cited

OTHER PUBLICATIONS

- Veltri et al., "Model for the photoinduced formation of diffraction gratings in liquid-crystalline composite materials", *Applied Physics Letters*, May 3, 2004, vol. 84, No. 18, pp. 3492-3494.
- Vita, "Switchable Bragg Gratings", Thesis, Universita degli Studi di Napoli Federico II, Nov. 2005, 103 pgs.
- Vuzix, "M3000 Smart Glasses, Advanced Waveguide Optics", brochure, Jan. 1, 2017, 2 pgs.
- Wang et al., "Liquid-crystal blazed-grating beam deflector", *Applied Optics*, Dec. 10, 2000, vol. 39, No. 35, pp. 6545-6555.
- Wang et al., "Optical Design of Waveguide Holographic Binocular Display for Machine Vision", *Applied Mechanics and Materials*, Sep. 27, 2013, vols. 427-429, pp. 763-769.
- Wang et al., "Speckle reduction in laser projection systems by diffractive optical elements", *Applied Optics*, Apr. 1, 1998, vol. 37, No. 10, pp. 1770-1775.
- Weber et al., "Giant Birefringent Optics in Multilayer Polymer Mirrors", *Science*, Mar. 31, 2000, vol. 287, pp. 2451-2456.
- Wei An, "Industrial Applications of Speckle Techniques", Doctoral Thesis, Royal Institute of Technology, Department of Production Engineering, Chair of Industrial Metrology & Optics, Stockholm, Sweden 2002, 76 pgs.
- Welde et al., "Investigation of methods for speckle contrast reduction", Master of Science in Electronics, Jul. 2010, Norwegian University of Science and Technology, Department of Electronics and Telecommunications, 127 pgs.
- White, "Influence of thiol-ene polymer evolution on the formation and performance of holographic polymer dispersed liquid crystals", The 232nd ACS National Meeting, San Francisco, CA, Sep. 10-14, 2006, 1 pg.
- Wicht et al., "Nanoporous Films with Low Refractive Index for Large-Surface Broad-Band Anti-Reflection Coatings", *Macromol. Mater. Eng.*, 2010, 295, DOI: 10.1002/mame.201000045, 9 pgs.
- Wilderbeek et al., "Photoinitiated Bulk Polymerization of Liquid Crystalline Thiolene Monomers", *Macromolecules*, 2002, vol. 35, pp. 8962-8969.
- Wilderbeek et al., "Photo-Initiated Polymerization of Liquid Crystalline Thiol-Ene Monomers in Isotropic and Anisotropic Solvents", *J. Phys. Chem. B*, 2002, vol. 106, No. 50, pp. 12874-12883.
- Wisely, "Head up and head mounted display performance improvements through advanced techniques in the manipulation of light", *Proc. of SPIE*, 2009, 10 pages, vol. 7327.
- Wofford et al., "Liquid crystal bragg gratings: dynamic optical elements for spatial light modulators", Hardened Materials Branch, Survivability and Sensor Materials Division, AFRL-ML-WP-TP-2007-551, Air Force Research Laboratory, Jan. 2007, Wright-Patterson Air Force Base, OH, 17 pgs.
- Yang et al., "Robust and Accurate Surface Measurement Using Structured Light", *IEEE*, Apr. 30, 2008, vol. 57, Issue 6, pp. 1275-1280, DOI:10.1109/TIM.2007.915103.
- Yaqoob et al., "High-speed two-dimensional laser scanner based on Bragg grating stored in photothermally refractive glass", *Applied Optics*, Sep. 10, 2003, vol. 42, No. 26, pp. 5251-5262.
- Yaroschuk et al., "Stabilization of liquid crystal photoaligning layers by resistive mesogens", *Applied Physics Letters*, Jul. 14, 2009, vol. 95, pp. 021902-1-021902-3.
- Ye "Three-dimensional Gradient Index Optics Fabricated in Diffusive Photopolymers", Thesis, Department of Electrical, Computer and Energy Engineering, University of Colorado, 2012, 224 pgs.
- Yemtsova et al., "Determination of liquid crystal orientation in holographic polymer dispersed liquid crystals by linear and non-linear optics", *Journal of Applied Physics*, Oct. 13, 2008, vol. 104, pp. 073115-1-073115-4.
- Yeralan et al., "Switchable Bragg grating devices for telecommunications applications", *Opt. Eng.*, Aug. 2012, vol. 41, No. 8, pp. 1774-1779.
- Yokomori, "Dielectric surface-relief gratings with high diffraction efficiency", *Applied Optics*, Jul. 15, 1984, vol. 23; No. 14, pp. 2303-2310.
- Yoshida et al., "Nanoparticle-Dispersed Liquid Crystals Fabricated by Sputter Doping", *Adv. Mater.*, 2010, vol. 22, pp. 622-626.
- Zhang et al., "Dynamic Holographic Gratings Recorded by Photopolymerization of Liquid Crystalline Monomers", *J. Am. Chem. Soc.*, 1994, vol. 116, pp. 7055-7063.
- Zhang et al., "Switchable Liquid Crystalline Photopolymer Media for Holography", *J. Am. Chem. Soc.*, 1992, vol. 114, pp. 1506-1507.
- Zhao et al., "Designing Nanostructures by Glancing Angle Deposition", *Proc. of SPIE*, Oct. 27, 2003, vol. 5219, pp. 59-73.
- Ziębacz, "Dynamics of nano and micro objects in complex liquids", Ph.D. dissertation, Institute of Physical Chemistry of the Polish Academy of Sciences, Warsaw 2011, 133 pgs.
- Zou et al., "Functionalized nano interdigitated electrodes arrays on polymer with integrated microfluidics for direct bio-affinity sensing using impedimetric measurement", *Sensors and Actuators A*, Jan. 16, 2007, vol. 136, pp. 518-526, doi:10.1016/j.sna.2006.12.006.
- Zyga, "Liquid crystals controlled by magnetic fields may lead to new optical applications", *Nanotechnology, Nanophysics*, Retrieved from <http://phys.org/news/2014-07-liquid-crystals-magnetic-fields-optical.html>, Jul. 9, 2014, 3 pgs.
- Bourzac, "Magic Leap Needs to Engineer a Miracle", *Intelligent Machines*, Jun. 11, 2015, 7 pgs.
- Bowen et al., "Optimisation of interdigitated electrodes for piezoelectric actuators and active fibre composites", *J Electroceram*, Jul. 2006, vol. 16, pp. 263-269, DOI 10.1007/s10832-006-9862-8.
- Bowley et al., "Variable-wavelength switchable Bragg gratings formed in polymer-dispersed liquid crystals", *Applied Physics Letters*, Jul. 2, 2001, vol. 79, No. 1, pp. 9-11, DOI: 10.1063/1.1383566.
- Bronnikov et al., "Polymer-Dispersed Liquid Crystals: Progress in Preparation, Investigation and Application", *Journal of Macromolecular Science Part B*, published online Sep. 30, 2013, vol. 52, pp. 1718-1738, DOI: 10.1080/00222348.2013.808926.
- Brown, "Waveguide Displays", *Rockwell Collins*, 2015, 11 pgs.
- Bruzzone et al., "Compact, high-brightness LED illumination for projection systems", *Journal of the Society for Information Display*, vol. 17, No. 12, Dec. 2009, pp. 1043-1049, DOI: 10.1189/JSID17.12.1043.
- Buckley, "Colour holographic laser projection technology for heads-up and instrument cluster displays", *Conference: Proc. SID Conference 14th Annual Symposium on Vehicle Displays*, Jan. 2007, 5 pgs.
- Buckley, "Pixtronix DMS technology for head-up displays", *Pixtronix, Inc.*, Jan. 2011, 4 pgs.
- Buckley et al., "Full colour holographic laser projector HUD", *Light Blue Optics Ltd.*, Aug. 10, 2015, 5 pgs.
- Buckley et al., "Rear-view virtual image displays", in *Proc. SID Conference 16th Annual Symposium on Vehicle Displays*, Jan. 2009, 5 pgs.
- Bunning et al., "Effect of gel-point versus conversion on the real-time dynamics of holographic polymer-dispersed liquid crystal (HPDLC) formation", *Proceedings of SPIE—vol. 5213, Liquid Crystals VII*, Iam-Choon Khoo, Editor, Dec. 2003, pp. 123-129.
- Bunning et al., "Electro-optical photonic crystals formed in H-PDLCs by thiol-ene photopolymerization", *American Physical Society, Annual APS*, Mar. 3-7, 2003, abstract #R1.135.
- Bunning et al., "Holographic Polymer-Dispersed Liquid Crystals (H-PDLCs) I", *Annual Review of Material Science*, 2000, vol. 30, pp. 83-115.
- Bunning et al., "Morphology of Anisotropic Polymer Dispersed Liquid Crystals and the Effect of Monomer Functionality", *Journal of Polymer Science: Part B: Polymer Physics*, Jul. 30, 1997, vol. 35, pp. 2825-2833.
- Busbee et al., "SiO₂ Nanoparticle Sequestration via Reactive Functionalization in Holographic Polymer-Dispersed Liquid Crystals", *Advanced Materials*, Sep. 2009, vol. 21, pp. 3659-3662, DOI: 10.1002/adma.200900298.
- Butler et al., "Diffractive Properties of Highly Birefringent Volume Gratings: Investigation", *Journal of Optical Society of America*, Feb. 2002, vol. 19, No. 2, pp. 183-189.
- Cai et al., "Recent advances in antireflective surfaces based on nanostructure arrays", *Materials Horizons*, 2015, vol. 2, pp. 37-53, DOI: 10.1038/c4mh00140k.

(56)

References Cited

OTHER PUBLICATIONS

- Cameron, "Optical Waveguide Technology & Its Application in Head Mounted Displays", Proc. of SPIE, May 22, 2012, vol. 8383, pp. 83830E-1-83830E-11, doi: 10.1117/12.923660.
- Cameron, "The Application of Holographic Optical Waveguide Technology to Q-Sight™ Family of Helmet Mounted Displays", Proc. of SPIE, 2009, vol. 7326, 11 pages, doi:10.1117/12.818581.
- Caputo et al., "POLICRYPS Composite Materials: Features and Applications", Advances in Composite Materials—Analysis of Natural and Man-Made Materials, www.intechopen.com, Sep. 2011, pp. 93-118.
- Caputo et al., "POLICRYPS Switchable Holographic Grating: A Promising Grating Electro-Optical Pixel for High Resolution Display Application", Journal of Display Technology, Mar. 2006, vol. 2, No. 1, pp. 38-51, DOI: 10.1109/JDT.2005.864156.
- Carclo Optics, "Guide to choosing secondary optics", Carclo Optics, Dec. 15, 2014, www.carclo-optics.com, 48 pgs.
- Chen et al., "Polarization rotators fabricated by thermally-switched liquid crystal alignments based on rubbed poly(N-vinyl carbazole) films", Optics Express, Apr. 11, 2011, vol. 19, No. 8, pp. 7553-7558, first published Apr. 5, 2011.
- Cheng et al., "Design of an ultra-thin near-eye display with geometrical waveguide and freeform optics". Optics Express, Aug. 2014. 16 pgs., DOI:10.1364/OE.22.020705.
- Chi et al., "Ultralow-refractive-index optical thin films through nanoscale etching of ordered mesoporous silica films", Optic Letters, May 1, 2012, vol. 37, No. 9, pp. 1406-1408, first published Apr. 19, 2012.
- Chigrinov et al., "Photo-aligning by azo-dyes: Physics and applications", Liquid Crystals Today, Sep. 6, 2006, http://www.tandfonline.com/action/journalInformation?journalCode=tlcy20, 15 pgs.
- Cho et al., "Electro-optic Properties of CO₂ Fixed Polymer/Nematic LC Composite Films", Journal of Applied Polymer Science, Nov. 5, 2000, vol. 81, Issue 11, pp. 2744-2753.
- Cho et al., "Optimization of Holographic Polymer Dispersed Liquid Crystals for Ternary Monomers", Polymer International, Nov. 1999, vol. 48, pp. 1085-1090.
- Colegrove et al., "P-59: Technology of Stacking HPDLC for Higher Reflectance", SID 00 Digest, May 2000, pp. 770-773.
- Crawford, "Electrically Switchable Bragg Gratings", Optics & Photonics News, Apr. 2003, pp. 54-59.
- Cruz-Arreola et al., "Diffraction of beams by infinite or finite amplitude-phase gratings", Investigacio' N Revista Mexicana de Fi'sica, Feb. 2011, vol. 57, No. 1, pp. 6-16.
- Dabrowski, "High Birefringence Liquid Crystals", Crystals, Sep. 3, 2013, vol. 3, No. 3, pp. 443-482, doi:10.3390/cryst3030443.
- Dainty, "Some statistical properties of random speckle patterns in coherent and partially coherent illumination", Optica Acta, Mar. 12, 1970, vol. 17, No. 10, pp. 761-772.
- Date, "Alignment Control in Holographic Polymer Dispersed Liquid Crystal", Journal of Photopolymer Science and Technology, Nov. 2, 2000, vol. 13, No. 2, pp. 289-294.
- Date et al., "52.3: Direct-viewing Display Using Alignment-controlled PDLC and Holographic PDLC", Society for Information Display Digest, May 2000, pp. 1184-1187, DOI: 10.1889/1.1832877.
- Date et al., "Full-color reflective display device using holographically fabricated polymer-dispersed liquid crystal (HPDLC)", Journal of the SID, 1999, vol. 7, No. 1, pp. 17-22.
- De Bitetto, "White light viewing of surface holograms by simple dispersion compensation", Applied Physics Letters, Dec. 15, 1966, vol. 9, No. 12, pp. 417-418.
- Developer World, "Create customized augmented reality solutions", printed Oct. 19, 2017, LMX-001 holographic waveguide display, Sony Developer World, 3 pgs.
- Dhar et al., "Recording media that exhibit high dynamic range for digital holographic data storage", Optics Letters, Apr. 1, 1999, vol. 24, No. 7, pp. 487-489.
- Domash et al., "Applications of switchable Polaroid holograms", SPIE Proceedings, vol. 2152, Diffractive and Holographic Optics Technology, Jan. 23-29, 1994, Los Angeles, CA, pp. 127-138, ISBN: 0-8194-1447-6.
- Drake et al., "Waveguide Hologram Fingerprint Entry Device", Optical Engineering, Sep. 1996, vol. 35, No. 9, pp. 2499-2505.
- Drevensek-Olenik et al., "In-Plane Switching of Holographic Polymer-Dispersed Liquid Crystal Transmission Gratings", Mol. Cryst. Liq. Cryst., 2008, vol. 495, p. 177/[529]~185/[537], DOI: 10.1080/15421400802432584.
- Drevensek-Olenik et al., "Optical diffraction gratings from polymer-dispersed liquid crystals switched by interdigitated electrodes", Journal of Applied Physics, Dec. 1, 2004, vol. 96, No. 11, pp. 6207-6212, DOI: 10.1063/1.1807027.
- Ducharme, "Microlens diffusers for efficient laser speckle generation", Optics Express, Oct. 29, 2007, vol. 15, No. 22, pp. 14573-14579.
- Duong et al., "Centrifugal Deposition of Iron Oxide Magnetic Nanorods for Hyperthermia Application", Journal of Thermal Engineering, Yildiz Technical University Press, Istanbul, Turkey, Apr. 2015, vol. 1, No. 2, pp. 99-103.
- Fattal et al., "A multi directional backlight for a wide-angle glasses-free three-dimensional display", Nature, Mar. 21, 2012, vol. 495, pp. 348-351.
- Fontecchio et al., "Spatially Pixelated Reflective Arrays from Holographic Polymer Dispersed Liquid Crystals", SID 00 Digest, May 2000, pp. 774-776.
- Forman et al., "Materials development for PhotoINhibited Super-Resolution (PINSR) lithography". Proc. of SPIE, 2012, vol. 8249, pp. 824904-1-824904-9, doi: 10.1117/12.908512.
- Forman et al., "Radical diffusion limits to photoinhibited super-resolution lithography", Phys. Chem. Chem. Phys., May 31, 2013, vol. 15, pp. 14862-14867, DOI: 10.1039/c3cp51512.
- Friedrich-Schiller, "Spatial Noise and Speckle", Version 1.12.2011, Dec. 2011, Abbe School of Photonics, Jena, Germany, 27 pgs.
- Fries et al., "Real-time beam shaping without additional optical elements", Light Science & Applications, Jun. 20, 2018, vol. 7, No. 18, doi: 10.1038/S41377-018-0014-0.
- Fujii et al., "Nanoparticle-polymer-composite volume gratings incorporating chain-transfer agents for holography and slow-neutron optics", Optics Letters, Apr. 25, 2014, vol. 39, Issue 12, 5 pgs.
- Nordin et al., "Diffraction Properties of Stratified Volume Holographic Optical Elements", Journal of the Optical Society of America A., vol. 9, No. 12, Dec. 1992, pp. 2206-2217.
- Oh et al., "Achromatic diffraction from polarization gratings with high efficiency", Optic Letters, Oct. 15, 2008, vol. 33, No. 20, pp. 2287-2289.
- Olson et al., "Templating Nanoporous Polymers with Ordered Block Copolymers", Chemistry of Materials, Web publication Nov. 27, 2007, vol. 20, pp. 869-890.
- Ondax, Inc., "Volume Holographic Gratings (VHG)", 2005, 7 pgs.
- Orcutt, "Coming Soon: Smart Glasses That Look Like Regular Spectacles", Intelligent Machines, Jan. 9, 2014, 4 pgs.
- Osredkar, "A study of the limits of spin-on-glass planarization process", Informacije MIDEM, 2001, vol. 31, 2, ISSN0352-9045, pp. 102-105.
- Osredkar et al., "Planarization methods in IC fabrication technologies", Informacije MIDEM, 2002, vol. 32, 3, ISSN0352-9045, 5 pgs.
- Ou et al., "A Simple LCOS Optical System (Late News)", Industrial Technology Research Institute/OES Lab. Q100/Q200, SID 2002, Boston, USA, 2 pgs.
- Paolini et al., "High-Power LED Illuminators in Projection Displays", Lumileds, Aug. 7, 2001, 19 pgs.
- Park et al., "Aligned Single-Wall Carbon Nanotube Polymer Composites Using an Electric Field", Journal of Polymer Science: Part B: Polymer Physics, Mar. 24, 2006, DOI 10.1002/polb.20823, pp. 1751-1762.
- Park et al., "Fabrication of Reflective Holographic Gratings with Polyurethane Acrylates (PUA)", Current Applied Physics, Jun. 2002, vol. 2, pp. 249-252.
- Plawsky et al., "Engineered nanoporous and nanostructured films", MaterialsToday, Jun. 2009, vol. 12, No. 6, pp. 36-45.

(56)

References Cited

OTHER PUBLICATIONS

- Potenza, "These smart glasses automatically focus on what you're looking at", *The Verge*, Voc Media, Inc., Jan. 29, 2017, <https://www.theverge.com/2017/1/29/14403924/smart-glasses-automatic-focus-presbyopia-ces-2017>, 6 pgs.
- Presnyakov et al., "Electrically tunable polymer stabilized liquid-crystal lens". *Journal of Applied Physics*, Apr. 29, 2005, vol. 97, pp. 103101-1-103101-6.
- Qi et al., "P-111: Reflective Display Based on Total Internal Reflection and Grating-Gratina Coupling", *Society for Information Display Digest*, May 2003, pp. 648-651, DOI: 10.1889/1.1832359.
- Ramón, "Formation of 3D micro- and nanostructures using liquid crystals as a template", *Technische Universiteit Eindhoven*, Apr. 17, 2008, Thesis, 117 pgs., DOI:<http://dx.doi.org/10.6100/IR634422>.
- Ramsey, "Holographic Patterning of Polymer Dispersed Liquid Crystal Materials for Diffractive Optical Elements", Thesis, The University of Texas at Arlington, Dec. 2006, 166 pgs.
- Ramsey et al., "Holographically recorded reverse-mode transmission gratings in polymer-dispersed liquid crystal cells", *Applied Physics B: Laser and Optics*, Sep. 10, 2008, vol. 93, Nos. 2-3, pp. 481-489.
- Reid, "Thin film silica nanocomposites for anti-reflection coatings", *Oxford Advance Surfaces*, www.oxfordsurfaces.com, Oct. 18, 2012, 23 pgs.
- Riechert, "Speckle Reduction in Projection Systems", Dissertation, University Karlsruhe, 2009, 178 pgs.
- Rossi et al., "Diffractive Optical Elements for Passive Infrared Detectors", Submitted to OSA Topical Meeting "Diffractive Optics and Micro-Optics", Quebec, Jun. 18-22, 2000, 3 pgs.
- Sabel et al., "Simultaneous formation of holographic surface relief gratings and volume phase gratings in photosensitive polymer", *Materials Research Letters*, May 30, 2019, vol. 7, No. 10, pp. 405-411. doi: 10.1080/21663831.2019.1621956.
- Sagan et al., "Electrically Switchable Bragg Grating Technology for Projection Displays", *Proc. SPIE*, vol. 4294, Jan. 24, 2001, pp. 75-83.
- Sakhno et al., "Deep surface relief grating in azobenzene-containing materials using a low-intensity 532 nm laser", *Optical Materials: X*, Jan. 23, 2019, 100006, pp. 3-7, doi: 10.1016/j.omx.2019.100006.
- Saleh et al., "Fourier Optics: 4.1 Propagation of light in free space, 4.2 Optical Fourier Transform, 4.3 Diffraction of Light, 4.4 Image Formation, 4.5 Holography", *Fundamentals of Photonics 1991*, Chapter 4, pp. 108-143.
- Saraswat, "Deposition & Planarization", *EE 311 Notes*, Aug. 29, 2017, 28 pgs.
- Schechter et al., "Compact beam expander with linear gratings", *Applied Optics*, vol. 41, No. 7, Mar. 1, 2002, pp. 1236-1240.
- Schreiber et al., "Laser display with single-mirror MEMS scanner", *Journal of the SID* 17/7, 2009, pp. 591-595.
- Seiberle et al., "Photo-aligned anisotropic optical thin films", *Journal of the SID* 12/1, 2004, 6 pgs.
- Serebriakov et al., "Correction of the phase retardation caused by intrinsic birefringence in deep UV lithography", *Proc. of SPIE*, May 21, 2010, vol. 5754, pp. 1780-1791.
- Shi et al., "Design considerations for high efficiency liquid crystal decentered microlens arrays for steering light", *Applied Optics*, vol. 49, No. 3, Jan. 20, 2010, pp. 409-421.
- Shriyan et al., "Analysis of effects of oxidized multiwalled carbon nanotubes on electro-optic polymer/liquid crystal thin film gratings", *Optics Express*, Nov. 12, 2010, vol. 18, No. 24, pp. 24842-24852.
- Simonite, "How Magic Leap's Augmented Reality Works", *Intelligent Machines*, Oct. 23, 2014, 7 pgs.
- Smith et al., "RM-PLUS—Overview", *Licrivue*, Nov. 5, 2013, 16 pgs.
- Sony Global, "Sony Releases the Transparent Lens Eyewear 'SmartEyegiass Developer Edition'", printed Oct. 19, 2017, Sony Global—News Releases, 5 pgs.
- Steranka et al., "High-Power LEDs—Technology Status and Market Applications", *Lumileds*, Jul. 2002, 23 pgs.
- Stumpe et al., "Active and Passive LC Based Polarization Elements", *Mol. Cryst. Liq. Cryst.*, 2014, vol. 594, pp. 140-149.
- Stumpe et al., "New type of polymer-LC electrically switchable diffractive devices—POLIPHEN", May 19, 2015, p. 97.
- Subbarayappa et al., "Bistable Nematic Liquid Crystal Device", *Jul. 30, 2009*, 14 pgs.
- Sun et al., "Effects of multiwalled carbon nanotube on holographic polymer dispersed liquid crystal", *Polymers Advanced Technologies*, Feb. 19, 2010, DOI: 10.1002/pat.1708, 8 pgs.
- Sun et al., "Low-birefringence lens design for polarization sensitive optical systems". *Proceedings of SPIE*, 2006, vol. 6289, pp. 6289DH-1-6289DH-10, doi: 10.1117/12.679416.
- Sun et al., "Transflective multiplexing of holographic polymer dispersed liquid crystal using Si additives", *eXPRESS Polymer Letters*, 2011, vol. 5, No. 1, pp. 73-81.
- Sutherland et al., "Bragg Gratings in an Acrylate Polymer Consisting of Periodic Polymer-Dispersed Liquid-Crystal Planes", *Chem. Mater.*, 1993, vol. 5, pp. 1533-1538.
- Sutherland et al., "Electrically switchable volume gratings in polymer-dispersed liquid crystals", *Applied Physics Letters*, Feb. 28, 1994, volume 64, No. 9, pp. 1074-1076.
- Sutherland et al., "Enhancing the electro-optical properties of liquid crystal nanodroplets for switchable Bragg gratings", *Proc. of SPIE*, 2008, vol. 7050, pp. 705003-1-705003-9, doi: 10.1117/12.792629.
- Sutherland et al., "Liquid crystal bragg gratings: dynamic optical elements for spatial light modulators", *Hardened Materials Branch, Hardened Materials Branch, AFRL-ML-WP-TP-2007-514*, Jan. 2007, Wright-Patterson Air Force Base, OH, 18 pgs.
- Sutherland et al., "The physics of photopolymer liquid crystal composite holographic gratings", presented at SPIE: Diffractive and Holographic Optics Technology San Jose, CA, 1996, SPIE, vol. 2689, pp. 158-169.
- Sweatt, "Achromatic triplet using holographic optical elements", *Applied Optics*, May 1977, vol. 16, No. 5, pp. 1390-1391.
- Talukdar, "Technology Forecast: Augmented reality", *Changing the economics of Smartglasses*, Issue 2, 2016, 5 pgs.
- Tao et al., "TiO₂ nanocomposites with high refractive index and transparency", *J. Mater. Chem.*, Oct. 4, 2011, vol. 21, pp. 18623-18629.
- Titus et al., "Efficient, Accurate Liquid Crystal Digital Light Deflector", *Proc. SPIE 3633, Diffractive and Holographic Technologies, Systems, and Spatial Light Modulators VI*, 1 Jun. 1, 1999, doi: 10.1117/12.349334, 10 pgs.
- Tiziani, "Physical Properties of Speckles", *Speckle Metrology*, Chapter 2, Academic Press, Inc., 1978, pp. 5-9.
- Tominaga et al., "Fabrication of holographic polymer dispersed liquid crystals doped with gold nanoparticles", 2010 Japanese Liquid Crystal Society Annual Meeting, 2 pgs.
- Tomita, "Holographic assembly of nanoparticles in photopolymers for photonic applications", *The International Society for Optical Engineering, SPIE Newsroom*, 2006, 3 pgs., doi: 10.1117/2.1200612.0475.
- Extended European Search Report for EP Application No. 13192383.1, dated Apr. 2, 2014, 7 pgs.
- Extended European Search Report for European Application No. 13765610.4 dated Feb. 16, 2016, 6 pgs.
- Extended European Search Report for European Application No. 15187491.4, search completed Jan. 15, 2016, dated Jan. 28, 2016, 5 pgs.
- Extended European Search Report for European Application No. 18867522.7, Search completed Sep. 15, 2021, dated Sep. 24, 2021, 9 pgs.
- International Preliminary Report on Patentability for International Application No. PCT/GB2010/000835, dated Nov. 1, 2011, mailed Nov. 10, 2011, 9 pgs.
- International Preliminary Report on Patentability for International Application No. PCT/GB2010/001920, dated Apr. 11, 2012, mailed Apr. 19, 2012, 10 pgs.
- International Preliminary Report on Patentability for international Application No. PCT/GB2010/001982, dated May 1, 2012, mailed May 10, 2012, 7 pgs.

(56)

References Cited

OTHER PUBLICATIONS

International Preliminary Report on Patentability for International Application No. PCT/GB2013/000273, dated Dec. 23, 2014, mailed Dec. 31, 2014, 8 pgs.

International Preliminary Report on Patentability for international Application No. PCT/GB2015/000203, dated Mar. 21, 2017, mailed Mar. 30, 2017, 8 pgs.

International Preliminary Report on Patentability for International Application No. PCT/GB2016/000036, dated Aug. 29, 2017, mailed Sep. 8, 2017, 8 pgs.

International Preliminary Report on Patentability for International Application No. PCT/GB2016/000051, dated Sep. 19, 2017, Mailed Sep. 28, 2017, 7 Pgs.

International Preliminary Report on Patentability for International Application No. PCT/GB2016/000065, dated Oct. 3 2017, mailed Oct. 12, 2017, 8 pgs.

International Preliminary Report on Patentability for International Application No. PCT/IB2008/001909, dated Jan. 26, 2010, Mailed Jan. 26, 2010, 5 Pgs.

International Preliminary Report on Patentability for International Application No. PCT/US2018/012227, dated Jul. 30, 2019, Mailed Aug. 8, 2019, 7 Pgs.

International Preliminary Report on Patentability for International Application PCT /US2018/015553, dated Jun. 4, 2019, Mailed Jun. 13, 2019, 6 pgs.

International Preliminary Report on Patentability for international Application PCT/GB2009/051676, dated Jun. 14, 2011, mailed Jun. 23, 2011, 6 pgs.

International Preliminary Report on Patentability for International Application PCT/GB2011/000349, dated Sep. 18, 2012, mailed Sep. 27, 2012, 10 pgs.

International Preliminary Report on Patentability for International Application PCT/GB2012/000331, dated Oct 8, 2013, mailed Oct. 17, 2013, 8 pgs.

International Preliminary Report on Patentability for International Application PCT/GB2012/000677, dated Feb. 25, 2014, mailed Mar. 6, 2014, 5 pgs.

International Preliminary Report on Patentability for International Application PCT/GB2013/000005, dated July 8, 2014, mailed Jul. 17, 2014, 12 pgs.

International Preliminary Report on Patentability for International Application PCT/GB2014/000295, dated Feb. 2, 2016, mailed Feb. 11, 2016, 4 pgs.

International Preliminary Report on Patentability for International Application PCT/GB2015/000225, dated Feb. 14, 2017, mailed Feb. 23, 2017, 8 pgs.

International Preliminary Report on Patentability for International Application PCT/GB2015/000228, dated Feb. 14, 2017, mailed Feb. 23, 2017, 11 pgs.

International Preliminary Report on Patentability for International Application PCT/GB2015/000274, dated Mar. 28, 2017, mailed Apr. 6, 2017, 8 pgs.

International Preliminary Report on Patentability for International Application PCT/GB2016/000014, dated Jul. 25, 2017, mailed Aug. 3, 2017, 7 pgs.

International Preliminary Report on Patentability for International Application PCT/GB2017/000040, Report dated Sep. 25, 2018, Mailed Oct. 4, 2018, 7 pgs.

International Preliminary Report on Patentability for International Application PCT/GB2017/000055, dated Oct. 16, 2018, Mailed Oct. 25, 2018, 9 pgs.

International Preliminary Report on Patentability for International Application PCT/US2014/011736, dated Jul. 21, 2015, mailed Jul. 30, 2015, 9 pgs.

International Preliminary Report on Patentability for International Application PCT/US2016/017091, dated Aug. 15, 2017, mailed Aug. 24, 2017, 5 pgs.

International Preliminary Report on Patentability for International Application PCT/US2018/012691, dated Jul. 9, 2019, Mailed Jul. 18, 2019, 10 pgs.

International Preliminary Report on Patentability for International Application PCT/US2018/056150, Report issued on Apr. 21, 2020, dated Apr. 30, 2020, 6 pgs.

International Preliminary Report on Patentability for International Application PCT/US2020/044060, Report issued Feb. 1, 2022, dated Feb. 10, 2022, 7 Pgs.

International Preliminary Report on Patentability for PCT Application No. PCT/US2013/038070, dated Oct. 28, 2014, 6 pgs.

International Search Report and Written Opinion for International Application No. PCT/GB2010/000835, completed Oct. 26, 2010, dated Nov. 8, 2010, 12 pgs.

International Search Report and Written Opinion for International Application No. PCT/GB2010/001920, completed Mar. 29, 2011, dated Apr. 6, 2011, 15 pgs.

International Search Report and Written Opinion for International Application No. PCT/GB2015/000228, Search completed May 4, 2011, dated Jul. 15, 2011, 15 Pgs.

International Search Report and Written Opinion for International Application No. PCT/GB2016/000036, completed Jul. 4, 2016, dated Jul. 13, 2016, 10 pgs.

International Search Report and Written Opinion for International Application No. PCT/GB2016/000065, completed Jul. 14, 2016, dated Jul. 27, 2016, 10 pgs.

International Search Report and Written Opinion for International Application No. PCT/GB2017/000055, Search completed Jul. 19, 2017, dated Jul. 26, 2017, 12 pgs.

International Search Report and Written Opinion for International Application No. PCT/IB2008/001909, Search completed Feb. 4, 2009, dated Feb. 17, 2009, 6 Pgs.

International Search Report and Written Opinion for International Application No. PCT/US2013/038070, completed Aug. 12, 2013, dated Aug. 14, 2013, 12 pgs.

International Search Report and Written Opinion for International Application No. PCT/US2014/011736, completed Apr. 18, 2014, dated May 8, 2014, 10 pgs.

International Search Report and Written Opinion for International Application No. PCT/US2018/012227, Search completed Feb. 28, 2018, dated Mar. 14, 2018, 8 Pgs.

International Search Report and Written Opinion for International Application No. PCT/US2018/012691, completed Mar. 10, 2018, dated Mar. 28, 2018, 16 pgs.

International Search Report and Written Opinion for International Application No. PCT/US2018/015553, completed Aug. 6, 2018, dated Sep. 19, 2018, 12 pgs.

International Search Report and Written Opinion for International Application No. PCT/US2018/037410, Search completed Aug. 16, 2018, dated Aug. 30, 2018, 11 pgs.

International Search Report and Written Opinion for International Application No. PCT/US2018/048636, Search completed Nov. 1, 2018, dated Nov. 15, 2018, 16 pgs.

International Search Report and Written Opinion for International Application No. PCT/US2018/048960, Search completed Dec. 14, 2018, dated Jan. 8, 2019, 14 pgs.

International Search Report and Written Opinion for International Application No. PCT/US2018/056150, Search completed Dec. 4, 2018, dated Dec. 26, 2018, 10 pgs.

International Search Report and Written Opinion for International Application No. PCT/US2018/062835, Search completed Jan. 14, 2019, dated Jan. 31, 2019, 14 pgs.

“FLP Lens Series for LUXEON™ Rebel and Rebel ES LEDs”, Fraen Corporation, www.fraensrl.com, Aug. 7, 2015, 8 pgs.

“Head-up Displays, See-through display for military Aviation”, BAE Systems, 2016, 3 pgs.

“Holder for LUXEON Rebel—Part No. 180”, Polymer Optics Ltd., 2008, 12 pgs.

“LED 7-Segment Displays”, Lumex, uk.digikey.com, 2003, UK031, 36 pgs.

“LED325W UVTOP UV LED with Window”, Thorlabs, Specifications and Documentation, 21978-S01 Rev. A, Apr. 8, 2011, 5 pgs.

“Liquid Crystal Phases”, Phases of Liquid Crystals, <http://plc.cwru.edu/tutorial/enhanced/files/lc/phase>, Retrieved on Sep. 21, 2004, 6 pgs.

“LiteHUD Head-up display”, BAE Systems, 2016, 2 pgs.

(56)

References Cited

OTHER PUBLICATIONS

“LiteHUD Head-up display infographic”, BAE Systems, 2017, 2 pgs.

“Luxeon C: Power Light Source”, Philips Lumileds, www.philipslumileds.com, 2012, 18 pgs.

“Luxeon Rebel ES: Leading efficacy and light output, maximum design flexibility”, LUXEON Rebel ES Datasheet DS61 Feb. 21, 2023, www.philipslumileds.com, 2013, 33 pgs.

“Mobile Display Report”, Insight Media, LLC, Apr. 2012, vol. 7, No. 4, 72 pgs.

“Molecular Imprints Imprio 55”, Engineering at Illinois, Micro + Nanotechnology Lab, Retrieved from <https://mntl.illinois.edu/facilities/cleanrooms/equipment/Nano-Imprint.asp>, Dec. 28, 2015, 2 pgs.

“Navy awards SGB Labs a contract for HMDs for simulation and training”, Press releases, DigiLens, Oct. 2012, pp. 1-2.

“Optical measurements of retinal flow”, Industrial Research Limited, Feb. 2012, 18 pgs.

“Osterhout Design Group Develops Next-Generation, Fully-integrated Smart Glasses Using Qualcomm Technologies”, ODG, www.osterhoutgroup.com, Sep. 18, 2014, 2 pgs.

“Plastic has replaced glass in photochromic lens”, www.plastemart.com, 2003, 1 page.

“Range Finding Using Pulse Lasers”, OSRAM, Opto Semiconductors, Sep. 10, 2004, 7 pgs.

“Response time in Liquid-Crystal Variable Retarders”, Meadowlark Optics, Inc., 2005, 4 pgs.

“Secondary Optics Design Considerations for SuperFlux LEDs”, Lumileds, application brief AB20-5, Sep. 2002, 23 pgs.

“Solid-State Optical Mouse Sensor with Quadrature Outputs”, IC Datasheet, UniqueICs, Jul. 15, 2004, 11 pgs.

“SVGA TransparentVLSITM Microdisplay Evaluation Kit”, Radiant Images, Inc., Product Data Sheet, 2003, 3 pgs.

“Technical Data Sheet LPR1”, Luminus Devices, Inc., Luminus Projection Chipset, Release 1, Preliminary, Revision B, Sep. 21, 2004, 9 pgs.

“The Next Generation of TV”, SID Information Display, Nov./Dec. 2014, vol. 30, No. 6, 56 pgs.

“Thermal Management Considerations for SuperFlux LEDs”, Lumileds, application brief AB20-4, Sep. 2002, 14 pgs.

“USAF Awards SBG Labs an SBIR Contract for Wide Field of View HUD”, Press Release, SBG Labs DigiLens, Apr. 2014, 2 pgs.

“UVTOP240”, Roithner LaserTechnik GmbH, v 2.0, Jun. 24, 2013, 6 pgs.

“UVTOP310”, Roithner LaserTechnik GmbH, v 2.0, Jun. 24, 2013, 6 pgs.

“Velodyne’s HDL-64E: A High Definition Lidar Sensor for 3-D Applications”, High Definition Lidar, white paper, Oct. 2007, 7 pgs.

“VerLASE Gets Patent for Breakthrough Color Conversion Technology That Enables Full Color MicroLED Arrays for Near Eye Displays”, Cision PRweb, Apr. 28, 2015, Retrieved from the Internet <http://www.prweb.com/releases/2015/04/prweb12681038.htm>, 3 pgs.

“Webster’s Third New International Dictionary 433”, (1986), 3 pages.

“X-Cubes—Revisited for LCOS”, BASID, RAF Electronics Corp. Rawson Optics, Inc., Oct. 24, 2002, 16 pgs.

Aachen, “Design of plastic optics for LED applications”, Optics Colloquium 2009, Mar. 19, 2009, 30 pgs.

Abbate et al., “Characterization of LC-polymer composites for opto-electronic application”, Proceedings of OPTOEL’03, Leganes-Madrid, Spain, Jul. 14-16, 2003, 4 pgs.

Al-Kalbani et al., “Ocular Microtremor laser speckle metrology”, Proc. of SPIE, 2009, vol. 7176 717606-1, 12 pgs., doi:10.1117/12.808855.

Almanza-Workman et al., “Planarization coating for polyimide substrates used in roll-to-roll fabrication of active matrix backplanes for flexible displays”, HPL Laboratories, HPL-2012-23, Feb. 6, 2012, 12 pgs.

Amitai et al., “Visor-display design based on planar holographic optics”, Applied Optics, vol. 34, No. 8, Mar. 10, 1995, pp. 1352-1356.

Amundson et al., “Morphology and electro-optic properties of polymer-dispersed liquid-crystal films”, Physical Review E, Feb. 1997, vol. 55, No. 2, pp. 1646-1654.

An et al., “Speckle suppression in laser display using several partially coherent beams”, Optics Express, Jan. 5, 2009, vol. 17, No. 1, pp. 92-103, first published Dec. 22, 2008.

Apter et al., “Electrooptical Wide-Angle Beam Deflector Based on Fringing-Field-Induced Refractive Inhomogeneity in a Liquid Crystal Layer”, 23rd IEEE Convention of Electrical and Electronics Engineers in Israel, Sep. 6-7, 2004, pp. 240-243.

Arnold et al., “52.3: An Improved Polarizing Beamsplitter LCOS Projection Display Based on Wire-Grid Polarizers”, Society for Information Display, Jun. 2001, pp. 1282-1285.

Ayras et al., “Exit pupil expander with a large field of view based on diffractive optics”, Journal of the Society for Information Display, May 18, 2009, vol. 17, No. 8, pp. 659-664, DOI: 10.1889/JSID17.8.659.

Baets et al., “Resonant-Cavity Light-Emitting Diodes: a review”, Proceedings of SPIE, 2003, vol. 4996, pp. 74-86.

Bayer et al., “Introduction to Helmet-Mounted Displays”, 2016, pp. 47-108.

Beckel et al., “Electro-optic properties of thiol-ene polymer stabilized ferroelectric liquid crystals”. Liquid Crystals, vol. 30, No. 11, Nov. 2003, pp. 1343-1350, DOI: 10.1080/02678290310001605910.

Bergkvist, “Biospeckle-based Study of the Line Profile of Light Scattered in Strawberries”, Master Thesis, Lund Reports on Atomic Physics, LRAP-220, Lund 1997, pp. 1-62.

Bernards et al., “Nanoscale porosity in polymer films: fabrication and therapeutic applications”, Soft Matter, Jan. 1, 2010, vol. 6, No. 8, pp. 1621-1631, doi: 10.1039/B922303G.

Bleha et al., “Binocular Holographic Waveguide Visor Display”, SID Symposium Digest of Technical Papers, Holoeye Systems Inc., Jun. 2014, San Diego, CA, 4 pgs.

Bleha et al., “D-ILA Technology for High Resolution Projection Displays”, Sep. 10, 2003, Proceedings, vol. 5080, 11 pgs., doi: 10.1117/12.497532.

Bone, “Design Obstacles for LCOS Displays in Projection Applications ”Optics architectures for LCOS are still evolving“, Aurora Systems Inc., Bay Area SID Seminar, Mar. 27, 2001, 22 pgs.

Born et al., “Optics of Crystals”, Principles of Optics 5th Edition 1975, pp. 705-707.

Funayama et al., “Proposal of a new type thin film light-waveguide display device using”, The International Conference on Electrical Engineering, 2008, No. P-044, 5 pgs.

Gabor, “Laser Speckle and its Elimination”, BM Research and Development, Eliminating Speckle Noise, Sep. 1970, vol. 14, No. 5, pp. 509-514.

Gardiner et al., “Bistable liquid-crystals reduce power consumption for high-efficiency smart glazing”, SPIE, 2009, 10.1117/2.1200904. 1596, 2 pgs.

Gerritsen et al., “Application of Kogelnik’s two-wave theory to deep, slanted, highly efficient, relief transmission gratings”, Applied Optics, Mar. 1, 1991, vol. 30; No. 7, pp. 807-814.

Giancola, “Holographic Diffuser, Makes Light Work of Screen Tests”, Photonics Spectra, 1996, vol. 30, No. 8, pp. 121-122.

Golub et al., “Bragg properties of efficient surface relief gratings in the resonance domain”, Optics Communications, Feb. 24, 2004, vol. 235, pp. 261-267, doi: 10.1016/j.optcom.2004.02.069.

Goodman, “Introduction to Fourier Optics”, Second Edition, Jan. 1996, 457 pgs.

Goodman, “Some fundamental properties of speckle”, J. Opt. Soc. Am., Nov. 1976, vol. 66, No. 11, pp. 1145-1150.

Goodman, “Statistical Properties of Laser Speckle Patterns”, Applied Physics, 1975, vol. 9, Chapter 2, Laser Speckle and Related Phenomena, pp. 9-75.

Goodman et al., “Speckle Reduction by a Moving Diffuser in Laser Projection Displays”, The Optical Society of America, 2000, 15 pgs.

Guldin et al., “Self-Cleaning Antireflective Optical Coatings”, Nano Letters, Oct. 14, 2013, vol. 13, pp. 5329-5335.

(56)

References Cited

OTHER PUBLICATIONS

- Guo et al., "Review Article: A Review of the Optimisation of Photopolymer Materials for Holographic Data Storage", *Physics Research International*, vol. 2012, Article ID 803439, Academic Editor: Sergi Gallego, 16 pages, <http://dx.doi.org/10.1155/2012/803439>, May 4, 2012.
- Han et al., "Study of Holographic Waveguide Display System", *Advanced Photonics for Communications*, 2014, 4 pgs.
- Harbers et al., "I-15.3: LED Backlighting for LCD-HDTV", *Journal of the Society for Information Display*, 2002, vol. 10, No. 4, pp. 347-350.
- Harbers et al., "Performance of High Power LED Illuminators in Color Sequential Projection Displays", *Lumileds Lighting*, 2007, 4 pgs.
- Harbers et al., "Performance of High Power LED Illuminators in Color Sequential Projection Displays", *Lumileds*, Aug. 7, 2001, 11 pgs.
- Harbers et al., "Performance of High-Power LED illuminators in Projection Displays", *Proc. Int. Disp. Workshops, Japan*, vol. 10, 2003, pp. 1585-1588.
- Harding et al., "Reactive Liquid Crystal Materials for Optically Anisotropic Patterned Retarders", *Merck, licrivue*, 2008, ME-GR-RH-08-010, 20 pgs.
- Harding et al., "Reactive Liquid Crystal Materials for Optically Anisotropic Patterned Retarders", *SPIE Lithography Asia—Taiwan*, 2008, Proceedings vol. 7140, *Lithography Asia 2008*; 71402J, doi: 10.1117/12.805378.
- Hariharan, "Optical Holography: Principles, techniques and applications", *Cambridge University Press*, 1996, pp. 231-233.
- Harris, "Photonic Devices", *EE 216 Principals and Models of Semiconductor Devices*, Autumn 2002, 20 pgs.
- Harrold et al., "3D Display Systems Hardware Research at Sharp Laboratories of Europe: an update", *Sharp Laboratories of Europe, Ltd.*, received May 21, 1999, 7 pgs.
- Harthong et al., "Speckle phase averaging in high-resolution color holography", *J. Opt. Soc. Am. A*, vol. 14, No. 2, Feb. 1997, pp. 405-409.
- Hasan et al., "Tunable-focus lens for adaptive eyeglasses", *Optics Express*, Jan. 23, 2017, vol. 25, No. 2, 1221, 13 pgs.
- Hasman et al., "Diffractive Optics: Design, Realization, and Applications", *Fiber and Integrated Optics*, vol. 16, 1997, pp. 1-25.
- Hata et al., "Holographic nanoparticle-polymer composites based on step-growth thiol-ene photopolymerization", *Optical Materials Express*, vol. 1, No. 2, Jun. 1, 2011, pp. 207-222.
- He et al., "Dynamics of peristrophic multiplexing in holographic polymer-dispersed liquid crystal", *Liquid Crystals*, Mar. 26, 2014, vol. 41, No. 5, pp. 673-684.
- He et al., "Holographic 3D display based on polymer-dispersed liquid-crystal thin films", *Proceedings of China Display/Asia Display 2011*, pp. 158-160.
- He et al., "Properties of Volume Holograms Recording in Photopolymer Films with Various Pulse Exposures Repetition Frequencies", *Proceedings of SPIE* vol. 5636, Bellingham, WA, 2005, pp. 842-848, doi: 10.1117/12.580978.
- Herman et al., "Production and Uses of Driffractonless Beams", *J. Opt. Soc. Am. A*, Jun. 1991, vol. 8, No. 6, pp. 932-942.
- Hisano, "Alignment layer-free molecular ordering induced by masked photopolymerization and nonpolarized light", *Appl. Phys. Express* 9, Jun. 6, 2016, pp. 072601-1-072601-4.
- Hoepfner et al., "LED Front Projection Goes Mainstream", *Luminus Devices, Inc., Projection Summit*, 2008, 18 pgs.
- Holmes et al., "Controlling the Anisotropy of Holographic Polymer-Dispersed Liquid-Crystal Gratings", *Physical Review E*, Jun. 11, 2002, vol. 65, 066603-1-066603-4.
- Hoyle et al., "Advances in the Polymerization of Thiol-Ene Formulations", *Heraeus Noblelight Fusion UV Inc.*, 2003 Conference, 6 pgs.
- Hua, "Sunglass-like displays become a reality with free-form optical technology", *Illumination & Displays 3D Visualization and Imaging Systems Laboratory (3DVIS) College of Optical Sciences University of Arizona Tucson, AZ*, 2014, 3 pgs.
- Huang et al., "Diffraction properties of substrate guided-wave holograms", *Optical Engineering*, Oct. 1995, vol. 34, No. 10, pp. 2891-2899.
- Huang et al., "Theory and characteristics of holographic polymer dispersed liquid crystal transmission grating with scaffolding morphology", *Applied Optics*, Jun. 20, 2012, vol. 51, No. 18, pp. 4013-4020.
- Iannacchione et al., "Deuterium NMR and morphology study of copolymer-dispersed liquid-crystal Bragg gratings", *Europhysics Letters*, 1996, vol. 36, No. 6, pp. 425-430.
- Irie, "Photochromic diarylethenes for photonic devices", *Pure and Applied Chemistry*, 1996, pp. 1367-1371, vol. 68, No. 7, IUPAC.
- Jeng et al., "Aligning liquid crystal molecules", *SPIE*, 2012, 10.1117/2.1201203.004148, 2 pgs.
- Jo et al., "Control of Liquid Crystal Pretilt Angle using Polymerization of Reactive Mesogen", *IMID 2009 Digest*, P1-25, 2009, pp. 604-606.
- Juhl, "Interference Lithography for Optical Devices and Coatings", *Dissertation, University of Illinois at Urbana-Champaign*, 2010.
- Juhl et al., "Holographically Directed Assembly of Polymer Nanocomposites", *ACS Nano*, Oct. 7, 2010, vol. 4, No. 10, pp. 5953-5961.
- Jurbergs et al., "New recording materials for the holographic industry", *Proc. of SPIE*, 2009 vol. 7233, pp. 72330K-1-72330L-10, doi: 10.1117/12.809579.
- Kahn et al., "Private Line Report on Large Area Display", *Kahn International*, Jan. 7, 2003, vol. 8, No. 10, 9 pgs.
- Karasawa et al., "Effects of Material Systems on the Polarization Behavior of Holographic Polymer Dispersed Liquid Crystal Gratings", *Japanese Journal of Applied Physics*, Oct. 1997, vol. 36, No. 10, pp. 6388-6392.
- Karp et al., "Planar micro-optic solar concentration using multiple imaging lenses into a common slab waveguide", *Proc. of SPIE* vol. 7407, 2009 SPIE, pp. 74070D-1-74070D-11, CCC code: 0277-786X/09, doi 10.1117/12.826531.
- Karp et al., "Planar micro-optic solar concentrator". *Optics Express*, Jan. 18, 2010, vol. 18, No. 2, pp. 1122-1133.
- Kato et al., "Alignment-Controlled Holographic Polymer Dispersed Liquid Crystal (HPDLC) for Reflective Display Devices", *SPIE*, 1998, vol. 3297, pp. 52-57.
- Kessler, "Optics of Near to Eye Displays (NEDs)", *Oasis 2013*, Tel Aviv, Feb. 19, 2013, 37 pgs.
- Keuper et al., "26.1: RGB LED Illuminator for Pocket-Sized Projectors", *SID 04 Digest*, 2004, ISSN/0004-0966X/04/3502, pp. 943-945.
- Keuper et al., "P-126: Ultra-Compact LED based Image Projector for Portable Applications", *SID 03 Digest*, 2003, ISSN/0003-0966X/03/3401-0713, pp. 713-715.
- Kim et al., "Effect of Polymer Structure on the Morphology and Electro optic Properties of UV Curable PNLCs", *Polymer*, Feb. 2000, vol. 41, pp. 1325-1335.
- International Search Report and Written Opinion for International Application No. PCT/US2019/012758, completed Mar. 12, 2019, dated Mar. 27, 2019, 9 pgs.
- International Search Report and Written Opinion for International Application No. PCT/US2019/012764, completed Mar. 1, 2019, dated Mar. 18, 2019, 9 pgs.
- International Search Report and Written Opinion for International Application No. PCT/US2019/031163, Search completed Jul. 9, 2019, dated Jul. 29, 2019, 11 pgs.
- International Search Report and Written Opinion for International Application No. PCT/US2019/064765, Search completed Feb. 3, 2020, dated Mar. 18, 2020, 11 Pgs.
- International Search Report and Written Opinion for International Application No. PCT/US2019/065478, Search completed Jan. 29, 2020, dated Feb. 11, 2020, 14 pgs.
- International Search Report and Written Opinion for International Application No. PCT/US2020/018686, Search completed Apr. 25, 2020, dated May 22, 2020, 11 Pgs.

(56)

References Cited

OTHER PUBLICATIONS

International Search Report and Written Opinion for International Application No. PCT/US2020/044060, Search completed Oct. 9, 2020, dated Nov. 9, 2020, 12 pgs.

International Search Report and Written Opinion for International Application PCT/GB2009/051676, completed May 10, 2010, dated May 18, 2010, 7 pgs.

International Search Report and Written Opinion for International Application PCT/GB2016/000181, completed Dec. 21, 2016, dated Feb. 27, 2017, 21 pgs.

International Search Report and Written Opinion for International Application PCT/US2016/017091, completed by the European Patent Office dated Apr. 20, 2016, 7 pgs.

International Search Report and Written Opinion for International Application PCT/US2019/012759, completed Mar. 14, 2019, dated Apr. 15, 2019, 12 pgs.

International Search Report and Written Opinion for International Application PCT/US2019/047097, completed Nov. 22, 2015, dated Dec. 16, 2019, 10 pgs.

International Search Report for International Application No. PCT/GB2014/000295, completed Nov. 18, 2014, dated Jan. 5, 2015, 4 pgs.

International Search Report for International Application PCT/GB2017/000040, dated Jul. 18, 2017, completed Jul. 10, 2017, 3 pgs.

International Search Report for PCT/GB2010/001982, completed by the European Patent Office dated Feb. 24, 2011, 4 pgs.

International Search Report for PCT/GB2011/000349, completed by the European Patent Office dated Aug. 17, 2011, 4 pgs.

International Search Report for PCT/GB2012/000331, completed by the European Patent Office dated Aug. 29, 2012, 4 pgs.

International Search Report for PCT/GB2012/000677, completed by the European Patent Office dated Dec. 10, 2012, 4 pgs.

International Search Report for PCT/GB2013/000005, completed by the European Patent Office dated Jul. 16, 2013, 3 pgs.

International Search Report for PCT/GB2013/000273, completed by the European Patent Office dated Aug. 30, 2013, 4 pgs.

International Search Report for PCT/GB2015/000203, completed by the European Patent Office dated Oct. 9, 2015, 4 pgs.

International Search Report for PCT/GB2015/000225, completed by the European Patent Office on Nov. 10, 2015, dated Dec. 2, 2016, 5 pgs.

International Search Report for PCT/GB2015/000274, completed by the European Patent Office dated Jan. 7, 2016, 4 pgs.

International Search Report for PCT/GB2016/000014, completed by the European Patent Office dated Jun. 27, 2016, 4 pgs.

International Search Report for PCT/GB2016/000051, dated Aug. 11, 2016, 3 Pgs.

Written Opinion for International Application No. PCT/GB2010/001982, search completed Feb. 24, 2011, dated Mar. 8, 2011, 6 pgs.

Written Opinion for International Application No. PCT/GB2011/000349, completed Aug. 17, 2011, dated Aug. 25, 2011, 9 pgs.

Written Opinion for International Application No. PCT/GB2012/000331, completed Aug. 29, 2012, dated Sep. 6, 2012, 7 pgs.

Written Opinion for International Application No. PCT/GB2012/000677, completed Dec. 10, 2012, dated Dec. 17, 2012, 4 pgs.

Written Opinion for International Application No. PCT/GB2013/000005, search completed Jul. 16, 2013, dated Jul. 24, 2013, 11 pgs.

Written Opinion for International Application No. PCT/GB2013/000273, completed Aug. 30, 2013, dated Sep. 9, 2013, 7 pgs.

Written Opinion for International Application No. PCT/GB2014/000295, search completed Nov. 18, 2014, dated Jan. 5, 2015, 3 pgs.

Written Opinion for International Application No. PCT/GB2015/000203, completed Oct. 29, 2015, dated Nov. 16, 2015, 7 pgs.

Written Opinion for International Application No. PCT/GB2015/000225, search completed Nov. 10, 2015, dated Feb. 4, 2016, 7 pgs.

Written Opinion for International Application No. PCT/GB2015/000274, search completed Jan. 7, 2016, dated Jan. 19, 2016, 7 pgs.

Written Opinion for International Application No. PCT/GB2016/000014, search completed Jun. 27, 2016, dated Jul. 7, 2016, 6 pgs.

Written Opinion for International Application No. PCT/GB2016/000051, Search completed Aug. 11, 2016, dated Aug. 22, 2016, 6 Pgs.

Written Opinion for International Application No. PCT/GB2017/000040, search completed Jul. 10, 2017, dated Jul. 18, 2017, 6 pgs.

Written Opinion for International Application PCT/GB2016/000003, completed May 31, 2016, dated Aug. 12, 2016, 10 pgs.

“Agilent ADNS-2051 Optical Mouse Sensor: Data Sheet”, Agilent Technologies, Jan. 9, 2002, 40 pgs.

“Application Note-MOXTEK ProFlux Polarizer use with LCOS displays”, CRL Opto Limited, <http://www.crlopto.com>, 2003, 6 pgs.

“Application Note AN16: Optical Considerations for Bridgelux LED Arrays”, BridgeLux, Jul. 31, 2010, 23 pgs.

“Application Note: Variable Attenuator for Lasers”, Technology and Applications Center, Newport Corporation, www.newport.com, 2006, DS-08067, 6 pgs.

“Bae Systems to Unveil Q-Sight Family of Helmet-Mounted Display at AUSA Symposium”, Released on Tuesday, Oct. 9, 2007, 1 pg.

“Beam Steering Using Liquid Crystals”, Boulder Nonlinear Systems, Inc., info@bnonlinear.com, May 8, 2001, 4 pgs.

“BragGrate—Deflector: Transmitting Volume Bragg Grating for angular selection and magnification”, 2015, www.OptiGrate.com.

“Cree XLamp XP-E LEDs”, Cree, Inc., Retrieved from www.cree.com/XLamp, CLD-DS18 Rev 17, 2013, 17 pgs.

“Desmodur N 3900”, Bayer MaterialScience AG, Mar. 18, 2013, www.bayercoatings.com, 4 pgs.

“Digilens—Innovative Augmented Reality Display and Sensor Solutions for OEMs”, Jun. 6, 2017, 31 pgs.

“Exotic Optical Components”, Building Electro-Optical Systems, Making It All Work, Chapter 7, John Wiley & Sons, Inc., pp. 233-261.

“FHS Lenses Series”, Fraen Corporation, www.fraen.com, Jun. 16, 2003, 10 pgs.

Kim et al., “Enhancement of electro-optical properties in holographic polymer-dispersed liquid crystal films by incorporation of multiwalled carbon nanotubes into a polyurethane acrylate matrix”, *Polym. Int.*, Jun. 16, 2010, vol. 59, pp. 1289-1295.

Kim et al., “Fabrication of Reflective Holographic PDLC for Blue”, *Molecular Crystals and Liquid Crystals Science*, 2001, vol. 368, pp. 3845-3853.

Kim et al., “Optimization of Holographic PDLC for Green”, *Mol. Cryst. Liq. Cryst.*, vol. 368, 2001, pp. 3855-3864.

Klein, “Optical Efficiency for Different Liquid Crystal Colour Displays”, Digital Media Department, HPL-2000-83, Jun. 29, 2000, 18 pgs.

Kogelnik, “Coupled Wave Theory for Thick Hologram Gratings”, *The Bell System Technical Journal*, vol. 48, No. 9, Nov. 1969, pp. 2909-2945.

Kotakonda et al., “Electro-optical Switching of the Holographic Polymer-dispersed Liquid Crystal Diffraction Gratings”, *Journal of Optics A: Pure and Applied Optics*, Jan. 1, 2009, vol. 11, No. 2, 11 pgs.

Kress et al., “Diffractive and Holographic Optics as Optical Combiners in Head Mounted Displays”, *UbiComp '13*, Sep. 9-12, 2013, Session Wearable Systems for Industrial Augmented Reality Applications, pp. 1479-1482.

Lauret et al., “Solving the Optics Equation for Effective LED Applications”, Gaggione North America, LLFY System Design Workshop 2010, Oct. 28, 2010, 26 pgs.

Lee, “Patents Shows Widespread Augmented Reality Innovation”, *PatentVue* May 26, 2015, 5 pgs.

Levin et al., “A Closed Form Solution To Natural Image Matting”, *illumination & Displays 3D Visualization and imaging Systems Laboratory (3DVIS) College of Optical Sciences University of Arizona Tucson*, 2014, 8 pgs.

Levola, “Diffractive optics for virtual reality displays”, *Journal of the SID*, 2006, 14/5, pp. 467-475.

Levola et al., “Near-to-eye display with diffractive exit pupil expander having chevron design”, *Journal of the SID*, 2008, 16/8, pp. 857-862.

(56)

References Cited

OTHER PUBLICATIONS

- Levola et al., "Replicated slanted gratings with a high refractive index material for in and outcoupling of light", *Optics Express*, vol. 15, issue 5, 2007, pp. 2067-2074.
- Li et al., "Design and Optimization of Tapered Light Pipes", *Proceedings vol. 5529, Nonimaging Optics and Efficient Illumination Systems*, Sep. 29, 2004, doi: 10.1117/12.559844, 10 pgs.
- Li et al., "Dual Paraboloid Reflector and Polarization Recycling Systems for Projection Display", *Proceedings vol. 5002, Projection Displays IX*, Mar. 28, 2003, doi: 10.1117/12.479585, 12 pgs.
- Li et al., "Light Pipe Based Optical Train and its Applications", *Proceedings vol. 5524, Novel Optical Systems Design and Optimization VII*, Oct. 24, 2004, doi: 10.1117/12.559833, 10 pgs.
- Li et al., "Novel Projection Engine with Dual Paraboloid Reflector and Polarization Recovery Systems", *Wavien Inc., SPIE E1 5289-38*, Jan. 21, 2004, 49 pgs.
- Li et al., "Polymer crystallization/melting induced thermal switching in a series of holographically patterned Bragg reflectors", *Soft Matter*, Jul. 11, 2005, vol. 1, pp. 238-242.
- Lin et al., "Ionic Liquids in Photopolymerizable Holographic Materials", in book: *Holograms—Recording Materials and Applications*, Nov. 9, 2011, 21 pgs.
- Liu et al., "Holographic Polymer Dispersed Liquid Crystals" *Materials, Formation and Applications, Advances in OptoElectronics*, Nov. 30, 2008, vol. 2008, Article ID 684349, 52 pgs.
- Liu et al., "Realization and Optimization of Holographic Waveguide Display System", *Acta Optica Sinica*, vol. 37, Issue 5, Issuing date—May 10, 2017, pp. 310-317.
- Lorek, "Experts Say Mass Adoption of augmented and Virtual Reality is Many Years Away", *Siliconhills*, Sep. 9, 2017, 4 pgs.
- Lowenthal et al., "Speckle Removal by a Slowly Moving Diffuser Associated with a Motionless Diffuser", *Journal of the Optical Society of America*, Jul. 1971, vol. 61, No. 7, pp. 847-851.
- Lu et al., "Polarization switch using thick holographic polymer-dispersed liquid crystal grating", *Journal of Applied Physics*, vol. 95, No. 3, Feb. 1, 2004, pp. 810-815.
- Lu et al., "The Mechanism of electric-field-induced segregation of additives in a liquid-crystal host", *Phys Rev E Stat Nonlin Soft Matter Phys.*, Nov. 27, 2012, 14 pgs.
- Ma et al., "Holographic Reversed-Mode Polymer-Stabilized Liquid Crystal Grating", *Chinese Phys. Lett.*, 2005, vol. 22, No. 1, pp. 103-106.
- Mach et al., "Switchable Bragg diffraction from liquid crystal in colloid-templated structures", *Europhysics Letters*, Jun. 1, 2002, vol. 58, No. 5, pp. 679-685.
- Magarinos et al., "Wide Angle Color Holographic infinity optics display", *Air Force Systems Command, Brooks Air Force Base, Texas, AFHRL-TR-80-53*, Mar. 1981, 100 pgs.
- Marino et al., "Dynamical Behaviour of Poicryps Gratings", *Electronic-Liquid Crystal Communications*, Feb. 5, 2004, 10 pgs.
- Massenot et al., "Multiplexed holographic transmission gratings recorded in holographic polymer-dispersed liquid crystals: static and dynamic studies", *Applied Optics*, 2005, vol. 44, Issue 25, pp. 5273-5280.
- Matay et al., "Planarization of Microelectronic Structures by Using Polyimides", *Journal of Electrical Engineering*, 2002, vol. 53, No. 3-4, pp. 86-90.
- Mathews, "The LED FAQ Pages", Jan. 31, 2002, 23 pgs.
- Matic, "Blazed phase liquid crystal beam steering", *Proc. of the SPIE*, 1994, vol. 2120, pp. 194-205.
- McLeod, "Axicons and Their Uses", *Journal of the Optical Society of America*, Feb. 1960, vol. 50, No. 2, pp. 166-169.
- McManamon et al., "A Review of Phased Array Steering for Narrow-Band Electrooptical Systems", *Proceedings of the IEEE*, Jun. 2009, vol. 97, No. 6, pp. 1078-1096.
- McManamon et al., "Optical Phased Array Technology", *Proceedings of the IEEE*, Feb. 1996, vol. 84, Issue 2, pp. 268-298.
- Miller, "Coupled Wave Theory and Waveguide Applications", *The Bell System Technical Journal*, Short Hills, NJ, Feb. 2, 1954, 166 pgs.
- Moffitt, "Head-Mounted Display Image Configurations", retrieved from the internet on Dec. 19, 2014, dated May 2008, 25 pgs.
- Moharam et al., "Diffraction characteristics of photoresist surface-relief gratings", *Applied Optics*, Sep. 15, 1984, vol. 23, pp. 3214-3220.
- Nair et al., "Enhanced Two-Stage Reactive Polymer Network Forming Systems", *Polymer (Guildf)*, May 25, 2012, vol. 53, No. 12, pp. 2429-2434, doi: 10.1016/j.polymer.2012.04.007.
- Nair et al., "Two-Stage Reactive Polymer Network Forming Systems", *Advanced Functional Materials*, 2012, pp. 1-9, DOI: 10.1002/adfm.201102742.
- Naqvi et al., "Concentration-dependent toxicity of iron oxide nanoparticles mediated by increased oxidative stress", *International Journal of Nanomedicine*, Dovepress, Nov. 13, 2010, vol. 5, pp. 983-989.
- Natarajan et al., "Electro Optical Switching Characteristics of Volume Holograms in Polymer Dispersed Liquid Crystals", *Journal of Nonlinear Optical Physics and Materials*, 1997, vol. 5, No. 1, pp. 666-668.
- Natarajan et al., "Electro-Optical Switching Characteristics of Volume Holograms in Polymer Dispersed Liquid Crystals", *Journal of Nonlinear Optical Physics and Materials*, Jan. 1996, vol. 5, No. 1, pp. 89-98.
- Natarajan et al., "Holographic polymer dispersed liquid crystal reflection gratings formed by visible light initiated thiol-ene photopolymerization", *Polymer*, vol. 47, May 8, 2006, pp. 4411-4420.
- Naydenova et al., "Low-scattering Volume Holographic Material", *DIT PhD Project*, <http://www.dit.ie/ieo/>, Oct. 2017, 2 pgs.
- Neipp et al., "Non-local polymerization driven diffusion based model: general dependence of the polymerization rate to the exposure intensity", *Optics Express*, Aug. 11, 2003, vol. 11, No. 16, pp. 1876-1886.
- Nishikawa et al., "Mechanically and Light Induced Anchoring of Liquid Crystal on Polyimide Film", *Mol. Cryst. Liq. Cryst.*, Aug. 1999, vol. 329, 8 pgs.
- Nishikawa et al., "Mechanism of Unidirectional Liquid-Crystal Alignment on Polyimides with Linearly Polarized Ultraviolet Light Exposure", *Applied Physics Letters*, May 11, 1998, vol. 72, No. 19, 4 pgs.

* cited by examiner




FIG.1A




FIG.1B




FIG.2




FIG.3A




FIG.3B




FIG. 4A




FIG. 4B




FIG.4C




FIG.4D




FIG.5A




FIG.5B




FIG. 5C




FIG. 5D




FIG.6




FIG.7




FIG.8




FIG.9




FIG.10

**METHODS AND APPARATUS FOR
MULTIPLYING THE IMAGE RESOLUTION
AND FIELD-OF-VIEW OF A PIXELATED
DISPLAY**

CROSS-REFERENCE TO RELATED
APPLICATIONS

The current application claims the benefit of and priority under 35 U.S.C. § 119(e) to U.S. Provisional Patent Application No. 62/880,033 entitled “Methods and Apparatus for Multiplying the Image Resolution and Field-of-view of a Pixelated Display,” filed Jul. 29, 2019. The disclosure of U.S. Provisional Patent Application No. 62/880,033 is hereby incorporated by reference in its entirety for all purposes.

FIELD OF THE INVENTION

The present disclosure relates to displays and, more particular, to holographic devices for multiplying the resolution and field-of-view of pixelated displays.

BACKGROUND

Waveguides can be referred to as structures with the capability of confining and guiding waves (i.e., restricting the spatial region in which waves can propagate). One subclass includes optical waveguides, which are structures that can guide electromagnetic waves, typically those in the visible spectrum. Waveguide structures can be designed to control the propagation path of waves using a number of different mechanisms. For example, planar waveguides can be designed to utilize diffraction gratings to diffract and couple incident light into the waveguide structure such that the in-coupled light can proceed to travel within the planar structure via total internal reflection (TIR).

Fabrication of waveguides can include the use of material systems that allow for the recording of holographic optical elements within the waveguides. One class of such material includes polymer dispersed liquid crystal (PDLC) mixtures, which are mixtures containing photopolymerizable monomers and liquid crystals. A further subclass of such mixtures includes holographic polymer dispersed liquid crystal (HPDLC) mixtures. Holographic optical elements, such as volume phase gratings, can be recorded in such a liquid mixture by illuminating the material with two mutually coherent laser beams. During the recording process, the monomers polymerize, and the mixture undergoes a photopolymerization-induced phase separation, creating regions densely populated by liquid crystal micro-droplets, interspersed with regions of clear polymer. The alternating liquid crystal-rich and liquid crystal-depleted regions form the fringe planes of the grating. The resulting grating, which is commonly referred to as a switchable Bragg grating (SBG), has all the properties normally associated with volume or Bragg gratings but with much higher refractive index modulation ranges combined with the ability to electrically tune the grating over a continuous range of diffraction efficiency (the proportion of incident light diffracted into a desired direction). The latter can extend from non-diffracting (cleared) to diffracting with close to 100% efficiency.

Waveguide optics, such as those described above, can be considered for a range of display and sensor applications. In many applications, waveguides containing one or more grating layers encoding multiple optical functions can be realized using various waveguide architectures and material

systems, enabling new innovations in near-eye displays for augmented reality (AR) and virtual reality (VR), compact head-up displays (HUDs) and helmet-mounted displays or head-mounted displays (HMDs) for road transport, aviation, and military applications, and sensors for biometric and laser radar (LIDAR) applications. Waveguide displays have been proposed that use diffraction gratings to preserve eye box size while reducing lens size. Head-up displays where the pupil of a collimating optical system is effectively expanded by the waveguide structure can also be implemented.

SUMMARY OF THE INVENTION

Systems and methods for multiplying the resolution and field-of-view of pixelated displays in accordance with various embodiments of the invention are illustrated. One embodiment includes an apparatus for multiplying display resolution and field-of-view, the apparatus including an image projector for directing light from pixels of a pixelated image source into unique angular directions wherein the image projector includes a microdisplay panel optically connected to a projection lens, an image processor electrically connected to the image projector for computing native images of the image source corresponding to first and second field-of-view portions and for computing shifted images in a predefined direction corresponding to the first and second field-of-view portions for sequential display by the image projector, a first set of gratings including a first input grating optically coupled to the image projector and a first output grating, wherein the first set of gratings includes at least one switchable grating switchable between a diffracting state and a non-diffracting state, wherein the first set of gratings have a native configuration for propagating the light of the native image and at least one shifted configuration for propagating the light of at least one shifted image, each with an angular displacement corresponding to an image shift in the predefined direction, where the image shift is equal to $N+1/M$ times a pixel dimension, where N and M are integers and N includes zero, and a second set of gratings including a second input grating optically coupled to the first output grating of the first set of gratings, wherein the second set of gratings includes at least one switchable grating switchable between a diffracting state and a non-diffracting state, wherein the second set of gratings have a first configuration for projecting the first field-of-view portion and a second configuration for projecting the second field-of-view portion.

In another embodiment, the first set of gratings is disposed in a first waveguide and the second set of gratings is disposed in a second waveguide.

In a further embodiment, the second set of gratings includes first, second, third, and fourth gratings, wherein the first grating overlaps the third grating and the second grating overlaps the fourth grating, and wherein the first and third gratings act as input couplers and the second and fourth gratings act as output couplers.

In still another embodiment, at least one of the first and third gratings is a switchable grating.

In a still further embodiment, the first, second, third, and fourth gratings are switchable gratings, wherein the first configuration for projecting the first field-of-view portion is provided by one of the first or third switchable gratings and one of the second or fourth switchable gratings in their diffracting states.

In yet another embodiment, the second and fourth gratings are non-switchable gratings.

3

In a yet further embodiment, the first and second switchable gratings are disposed in a first layer within a waveguide and the third and fourth switchable gratings are disposed in a second layer within the waveguide.

In another additional embodiment, the first and second switchable gratings are disposed in a first waveguide and the third and fourth switchable gratings are disposed in a second waveguide.

In a further additional embodiment, M is equal to 2.

In another embodiment again, the native and the at least one shifted image are sequentially displayed within a human eye integration period.

In a further embodiment again, the image shift includes one of vertical or horizontal shifts.

In still yet another embodiment, the image shift includes vertical and horizontal shifts.

In a still yet further embodiment, the switchable gratings are recorded in a holographic polymer dispersed liquid crystal material.

In still another additional embodiment, the second set of gratings includes a non-switchable grating.

In a still further additional embodiment, the second set of gratings includes a fold grating.

In still another embodiment again, the second set of gratings includes at least one grating multiplexing at least one of wavelength or angular bandwidth.

In a still further embodiment again, the image projector is optically coupled to the first input grating of the first set of gratings by one of a prism or grating.

In yet another additional embodiment, the apparatus further includes an illumination homogenizer.

In a yet further additional embodiment, the second set of gratings includes a rolled k-vector grating.

A yet another embodiment again includes a method of multiplying the resolution and field-of-view of a waveguide display, the method including providing an image projector and an image processor, providing a waveguide display including first and second sets of gratings, wherein each of the first and second sets of gratings includes at least one switchable grating switchable between a diffracting state and a non-diffracting state, wherein the first set of gratings has a native switching configuration and a shifted switching configuration, wherein the second set of grating has a first switching configuration and a second switching configuration, and sequentially projecting at least four images, wherein the at least four images include a native image in a first field-of-view portion, a shifted image in a first field-of-view portion, a native image in a second field-of-view portion, and a shifted image in a second field-of-view portion, wherein the shifted image has an angular displacement with respect to a corresponding native image defined as an image shift that is equal to $N+1/M$ times a pixel dimension, where N and M are integers and N includes zero, wherein the native image in the first field-of-view portion is projected when the first set of gratings is in the native switching configuration and the second set of gratings is in the first switching configuration, the native image in the second field-of-view portion is projected when the first set of gratings is in the native switching configuration and the second set of gratings is in the second switching configuration, the shifted image in the first field-of-view portion is projected when the first set of gratings is in the shifted switching configuration and the second set of gratings is in the first switching configuration, and the shifted image in the second field-of-view portion is projected when the first set of

4

gratings is in the shifted switching configuration and the second set of gratings is in the second switching configuration.

Additional embodiments and features are set forth in part in the description that follows, and in part will become apparent to those skilled in the art upon examination of the specification or may be learned by the practice of the invention. A further understanding of the nature and advantages of the present invention may be realized by reference to the remaining portions of the specification and the drawings, which forms a part of this disclosure.

BRIEF DESCRIPTION OF THE DRAWINGS

The description will be more fully understood with reference to the following figures and data graphs, which are presented as exemplary embodiments of the invention and should not be construed as a complete recitation of the scope of the invention.

FIGS. 1A-1B conceptually illustrate schematic cross section views of a resolution multiplication waveguide device in accordance with an embodiment of the invention.

FIG. 2 conceptually illustrates a schematic cross section view of a resolution multiplication waveguide device with two switchable grating layers in accordance with an embodiment of the invention.

FIGS. 3A-3B conceptually illustrate schematic cross section views of a resolution multiplication waveguide device optically interfaced to a waveguide display in accordance with an embodiment of the invention.

FIGS. 4A-4D conceptually illustrate four pixel-shifting steps used to provide resolution quadrupling in accordance with an embodiment of the invention.

FIGS. 5A-5D conceptually illustrate a schematic cross section view of a resolution quadrupling waveguide device in accordance with an embodiment of the invention.

FIG. 6 is a flow chart illustrating a method of multiplying the resolution of a waveguide display in accordance with an embodiment of the invention.

FIG. 7 conceptually illustrates a schematic cross section view of a waveguide apparatus for multiplying the resolution and the field-of-view of a display in accordance with an embodiment of the invention.

FIG. 8 conceptually illustrates a schematic cross section view of a waveguide apparatus for multiplying the field-of-view of a display in accordance with an embodiment of the invention.

FIG. 9 conceptually illustrates a schematic cross section view of a single waveguide for multiplying the resolution and the field-of-view of a display in accordance with an embodiment of the invention.

FIG. 10 is a flow chart illustrating a method of multiplying the resolution and field-of-view of a waveguide display in accordance with an embodiment of the invention.

DETAILED DESCRIPTION

For the purposes of describing embodiments, some well-known features of optical technology known to those skilled in the art of optical design and visual displays have been omitted or simplified in order to not obscure the basic principles of the invention. Unless otherwise stated, the term "on-axis" in relation to a ray or a beam direction refers to propagation parallel to an axis normal to the surfaces of the optical components described in relation to the invention. In the following description the terms light, ray, beam, and direction may be used interchangeably and in association

with each other to indicate the direction of propagation of electromagnetic radiation along rectilinear trajectories. The term light and illumination may be used in relation to the visible and infrared bands of the electromagnetic spectrum. Parts of the following description will be presented using terminology commonly employed by those skilled in the art of optical design. As used herein, the term grating may encompass a grating comprised of a set of gratings in some embodiments. For illustrative purposes, it is to be understood that the drawings are not drawn to scale unless stated otherwise.

There is growing consensus that the prerequisite for a successful head mounted AR display is a small, low impact form factor, high brightness, wide field-of-view (FOV) display. A waveguide display can provide a wide FOV by tiling smaller FOVs, with each tile containing imagery formed on a microdisplay coupled to the waveguide. The image content for each FOV tile can be displayed time-sequentially. In general, as FOV increases, it is necessary to provide a high enough resolution to fill the FOV with image detail. To be successful in the market, a 50-degree FOV display should ideally be supported by a resolution of at least 1080p (1920×1080 pixels in 16:9 aspect ratio HD Wide-screen standard). U.S. patent application Ser. No. 16/162,280 entitled “Systems and Methods for Multiplying the Image Resolution of a Pixelated Display” filed Oct. 16, 2018 discusses FOV tiling in further detail. The disclosure of U.S. patent application Ser. No. 16/162,280 is hereby incorporated by reference in its entirety for all purposes.

To meet current wearable form factor demands, the microdisplay used to provide the input image should be not greater than 0.23-inches diagonal. However, current pixel sizes do not permit 1080p pixel resolution into a small display area. One way of overcoming the FOV/resolution bottleneck is to use image resolution multiplication. One well established technique pioneered by Texas Instruments (TI) in their rear projection TVs combines their fast switching DLP technology with a high-speed mechanical mirror to enable pixel doubling to 1080p resolution. Such solutions are unsuited for AR wearables, both in terms of form factor and industry resistance to mechanical complexity and cost. Alternative technologies such as organic LED are not mature enough to cost-effectively deliver 1080p resolution with high brightness. As such, there is a requirement for a compact, optically efficient, and cost-effective solution for display resolution multiplication and FOV multiplication. There is a further requirement for a compact, optically efficient, and cost-effective solution for display resolution multiplication and FOV multiplication integrated within a waveguide display architecture.

Referring generally to the drawings, systems and methods relating to near-eye display or head-up display systems in accordance with various embodiments of the invention are conceptually illustrated. Using the systems and methods disclosed herein, a single optical waveguide substrate can generate a wider field-of-view than found in current and conventional waveguide systems. In many embodiments, diffraction gratings may be used to split and diffract light rays into several beams that travel in different directions, thereby dispersing the light rays. In further embodiments, switchable Bragg gratings (SBGs) can be used in waveguides to eliminate extra layers and to reduce the thickness of current display systems, including HMDs, HUDs, and other near eye displays and to increase the field-of-view by tiling images presented sequentially on a microdisplay. Various types of grating architectures can be implemented for various purposes. In a number of embodiments, a larger

exit pupil may be created by using fold gratings in conjunction with conventional gratings (or other types of gratings disclosed herein) to provide pupil expansion on a single waveguide in both the horizontal and vertical directions. Grating structures, waveguide architectures, and display resolution multiplication and FOV multiplication techniques are discussed below in further detail.

Optical Waveguide and Grating Structures

Optical structures recorded in waveguides can include many different types of optical elements, such as but not limited to diffraction gratings. Gratings can be implemented to perform various optical functions, including but not limited to coupling light, directing light, and preventing the transmission of light. In many embodiments, the gratings are surface relief gratings that reside on the outer surface of the waveguide. In other embodiments, the grating implemented is a Bragg grating (also referred to as a volume grating), which are structures having a periodic refractive index modulation. Bragg gratings can be fabricated using a variety of different methods. One process includes interferential exposure of holographic photopolymer materials to form periodic structures. Bragg gratings can have high efficiency with little light being diffracted into higher orders. The relative amount of light in the diffracted and zero order can be varied by controlling the refractive index modulation of the grating, a property that can be used to make lossy waveguide gratings for extracting light over a large pupil.

One class of Bragg gratings used in holographic waveguide devices is the Switchable Bragg Grating (SBG). SBGs can be fabricated by first placing a thin film of a mixture of photopolymerizable monomers and liquid crystal material between substrates. The substrates can be made of various types of materials, such as glass and plastics. In many cases, the substrates are in a parallel configuration. In other embodiments, the substrates form a wedge shape. One or both substrates can support electrodes, typically transparent tin oxide films, for applying an electric field across the film. The grating structure in an SBG can be recorded in the liquid material (often referred to as the syrup) through photopolymerization-induced phase separation using interferential exposure with a spatially periodic intensity modulation. Factors such as but not limited to control of the irradiation intensity, component volume fractions of the materials in the mixture, and exposure temperature can determine the resulting grating morphology and performance. As can readily be appreciated, a wide variety of materials and mixtures can be used depending on the specific requirements of a given application. In many embodiments, HPDLC material is used. During the recording process, the monomers polymerize, and the mixture undergoes a phase separation. The LC molecules aggregate to form discrete or coalesced droplets that are periodically distributed in polymer networks on the scale of optical wavelengths. The alternating liquid crystal-rich and liquid crystal-depleted regions form the fringe planes of the grating, which can produce Bragg diffraction with a strong optical polarization resulting from the orientation ordering of the LC molecules in the droplets.

The resulting volume phase grating can exhibit very high diffraction efficiency, which can be controlled by the magnitude of the electric field applied across the film. When an electric field is applied to the grating via transparent electrodes, the natural orientation of the LC droplets can change, causing the refractive index modulation of the fringes to lower and the hologram diffraction efficiency to drop to very low levels. Typically, the electrodes are configured such that the applied electric field will be perpendicular to the substrates. In a number of embodiments, the electrodes are

fabricated from indium tin oxide (ITO). In the OFF state with no electric field applied, the extraordinary axis of the liquid crystals generally aligns normal to the fringes. The grating thus exhibits high refractive index modulation and high diffraction efficiency for P-polarized light. When an electric field is applied to the HPDLC, the grating switches to the ON state wherein the extraordinary axes of the liquid crystal molecules align parallel to the applied field and hence perpendicular to the substrate. In the ON state, the grating exhibits lower refractive index modulation and lower diffraction efficiency for both S- and P-polarized light. Thus, the grating region no longer diffracts light. Each grating region can be divided into a multiplicity of grating elements such as for example a pixel matrix according to the function of the HPDLC device. Typically, the electrode on one substrate surface is uniform and continuous, while electrodes on the opposing substrate surface are patterned in accordance with the multiplicity of selectively switchable grating elements.

Typically, the SBG elements are switched clear in 30 μ s with a longer relaxation time to switch ON. The diffraction efficiency of the device can be adjusted, by means of the applied voltage, over a continuous range. In many cases, the device exhibits near 100% efficiency with no voltage applied and essentially zero efficiency with a sufficiently high voltage applied. In certain types of HPDLC devices, magnetic fields can be used to control the LC orientation. In some HPDLC applications, phase separation of the LC material from the polymer can be accomplished to such a degree that no discernible droplet structure results. An SBG can also be used as a passive grating. In this mode, its chief benefit is a uniquely high refractive index modulation. SBGs can be used to provide transmission or reflection gratings for free space applications. SBGs can be implemented as waveguide devices in which the HPDLC forms either the waveguide core or an evanescently coupled layer in proximity to the waveguide. The substrates used to form the HPDLC cell provide a total internal reflection (TIR) light guiding structure. Light can be coupled out of the SBG when the switchable grating diffracts the light at an angle beyond the TIR condition.

In some embodiments, LC can be extracted or evacuated from the SBG to provide an evacuated Bragg grating (EBG). EBGs can be characterized as a surface relief grating (SRG) that has properties very similar to a Bragg grating due to the depth of the SRG structure (which is much greater than that practically achievable using surface etching and other conventional processes commonly used to fabricate SRGs). The LC can be extracted using a variety of different methods, including but not limited to flushing with isopropyl alcohol and solvents. In many embodiments, one of the transparent substrates of the SBG is removed, and the LC is extracted. In further embodiments, the removed substrate is replaced. The SRG can be at least partially backfilled with a material of higher or lower refractive index. Such gratings offer scope for tailoring the efficiency, angular/spectral response, polarization, and other properties to suit various waveguide applications.

Waveguides in accordance with various embodiments of the invention can include various grating configurations designed for specific purposes and functions. In many embodiments, the waveguide is designed to implement a grating configuration capable of preserving eyebox size while reducing lens size by effectively expanding the exit pupil of a collimating optical system. The exit pupil can be defined as a virtual aperture where only the light rays which pass through this virtual aperture can enter the eyes of a user.

In some embodiments, the waveguide includes an input grating optically coupled to a light source, a fold grating for providing a first direction beam expansion, and an output grating for providing beam expansion in a second direction, which is typically orthogonal to the first direction, and beam extraction towards the eyebox. Fold gratings can be configured to deflect incident light to continue traveling within a TIR path in the waveguide. As can readily be appreciated, the grating configuration implemented waveguide architectures can depend on the specific requirements of a given application. In some embodiments, the grating configuration includes multiple fold gratings. In several embodiments, the grating configuration includes an input grating and a second grating for performing beam expansion and beam extraction simultaneously. The second grating can include gratings of different prescriptions, for propagating different portions of the field-of-view, arranged in separate overlapping grating layers or multiplexed in a single grating layer. Furthermore, various types of gratings and waveguide architectures can also be utilized.

In several embodiments, the gratings within each layer are designed to have different spectral and/or angular responses. For example, in many embodiments, different gratings across different grating layers are overlapped, or multiplexed, to provide an increase in spectral bandwidth. In some embodiments, a full color waveguide is implemented using three grating layers, each designed to operate in a different spectral band (red, green, and blue). In other embodiments, a full color waveguide is implemented using two grating layers, a red-green grating layer and a green-blue grating layer. As can readily be appreciated, such techniques can be implemented similarly for increasing angular bandwidth operation of the waveguide. In addition to the multiplexing of gratings across different grating layers, multiple gratings can be multiplexed within a single grating layer—i.e., multiple gratings can be superimposed within the same volume. In several embodiments, the waveguide includes at least one grating layer having two or more grating prescriptions multiplexed in the same volume. In further embodiments, the waveguide includes two grating layers, each layer having two grating prescriptions multiplexed in the same volume. Multiplexing two or more grating prescriptions within the same volume can be achieved using various fabrication techniques. In a number of embodiments, a multiplexed master grating is utilized with an exposure configuration to form a multiplexed grating. In many embodiments, a multiplexed grating is fabricated by sequentially exposing an optical recording material layer with two or more configurations of exposure light, where each configuration is designed to form a grating prescription. In some embodiments, a multiplexed grating is fabricated by exposing an optical recording material layer by alternating between or among two or more configurations of exposure light, where each configuration is designed to form a grating prescription. As can readily be appreciated, various techniques, including those well known in the art, can be used as appropriate to fabricate multiplexed gratings.

In many embodiments, the waveguide can incorporate at least one of: angle multiplexed gratings, color multiplexed gratings, fold gratings, dual interaction gratings, rolled K-vector gratings, crossed fold gratings, tessellated gratings, chirped gratings, gratings with spatially varying refractive index modulation, gratings having spatially varying grating thickness, gratings having spatially varying average refractive index, gratings with spatially varying refractive index modulation tensors, and gratings having spatially varying average refractive index tensors. In some embodiments, the

waveguide can incorporate at least one of: a half wave plate, a quarter wave plate, an anti-reflection coating, a beam splitting layer, an alignment layer, a photochromic back layer for glare reduction, and louvre films for glare reduction. In several embodiments, the waveguide can support gratings providing separate optical paths for different polarizations. In various embodiments, the waveguide can support gratings providing separate optical paths for different spectral bandwidths. In a number of embodiments, the gratings can be HPDLC gratings, switching gratings recorded in HPDLC (such as switchable Bragg Gratings), Bragg gratings recorded in holographic photopolymer, or surface relief gratings. In many embodiments, the waveguide operates in a monochrome band. In some embodiments, the waveguide operates in the green band. In several embodiments, waveguide layers operating in different spectral bands such as red, green, and blue (RGB) can be stacked to provide a three-layer waveguiding structure. In further embodiments, the layers are stacked with air gaps between the waveguide layers. In various embodiments, the waveguide layers operate in broader bands such as blue-green and green-red to provide two-waveguide layer solutions. In other embodiments, the gratings are color multiplexed to reduce the number of grating layers. Various types of gratings can be implemented. In some embodiments, at least one grating in each layer is a switchable grating.

Waveguides incorporating optical structures such as those discussed above can be implemented in a variety of different applications, including but not limited to waveguide displays. In various embodiments, the waveguide display is implemented with an eyebox of greater than 10 mm with an eye relief greater than 25 mm. In some embodiments, the waveguide display includes a waveguide with a thickness between 2.0-5.0 mm. In many embodiments, the waveguide display can provide an image field-of-view of at least 50° diagonal. In further embodiments, the waveguide display can provide an image field-of-view of at least 70° diagonal. The waveguide display can employ many different types of picture generation units (PGUs). In several embodiments, the PGU can be a reflective or transmissive spatial light modulator such as a liquid crystal on Silicon (LCoS) panel or a micro electromechanical system (MEMS) panel. In a number of embodiments, the PGU can be an emissive device such as an organic light emitting diode (OLED) panel. In some embodiments, an OLED display can have a luminance greater than 4000 nits and a resolution of 4 kx4 k pixels. In several embodiments, the waveguide can have an optical efficiency greater than 10% such that a greater than 400 nit image luminance can be provided using an OLED display of luminance 4000 nits. Waveguides implementing P-diffracting gratings (i.e., gratings with high efficiency for P-polarized light) typically have a waveguide efficiency of 5%-6.2%. Since P-diffracting or S-diffracting gratings can waste half of the light from an unpolarized source such as an OLED panel, many embodiments are directed towards waveguides capable of providing both S-diffracting and P-diffracting gratings to allow for an increase in the efficiency of the waveguide by up to a factor of two. In some embodiments, the S-diffracting and P-diffracting gratings are implemented in separate overlapping grating layers. Alternatively, a single grating can, under certain conditions, provide high efficiency for both p-polarized and s-polarized light. In several embodiments, the waveguide includes Bragg-like gratings produced by extracting LC from HPDLC gratings, such as those described above, to enable high S and P diffraction efficiency over certain wavelength

and angle ranges for suitably chosen values of grating thickness (typically, in the range 2-5 μm).

Optical Recording Material Systems

Material systems in accordance with various embodiments of the invention can include photopolymer mixtures capable of forming holographic Bragg gratings. In a number of embodiments, the mixtures are able to form holographic gratings using interferential photolithography. In such cases, the index modulation is created by the varying exposure intensity of the interference pattern. Any of a variety of lithographic techniques, including those described in the sections above and those well-known in the art, can be used. Compared to conventional techniques relying on index changes through photo-reactivity, material systems and techniques in accordance with various embodiments of the invention utilize phase separation processes initiated through interferential exposure. In many embodiments, the photopolymer mixture includes different types of monomers, dyes, photoinitiators, and nanoparticles. Monomers can include but are not limited to vinyls, acrylates, methacrylates, thiols, epoxides, and other reactive groups. In some embodiments, the mixture can include monomers having different refractive indices. In several embodiments, the mixture can include reactive diluents and/or adhesion promoters. As can readily be appreciated, various types of mixtures and compositions can be implemented as appropriate depending on the specific requirements of a given application. In a number of embodiments, the mixture implemented is based on material systems described in U.S. application Ser. No. 16/242,943 entitled "Low Haze Liquid Crystal Materials" filed Jan. 8, 2019, U.S. application Ser. No. 16/242,954 entitled "Liquid Crystal Materials and Formulations" filed Jan. 8, 2019, U.S. application Ser. No. 16/007,932 entitled "Holographic Material Systems and Waveguides Incorporating Low Functionality Monomers" filed Jun. 13, 2018, and U.S. application Ser. No. 16/799,735 entitled "Holographic Polymer Dispersed Liquid Crystal Mixtures with High Diffraction Efficiency and Low Haze" filed Feb. 24, 2020. The disclosures of U.S. application Ser. Nos. 16/242,943, 16/242,954, 16/007,932, and 16/799,735 are hereby incorporated by reference in their entireties for all purposes.

To form holographic gratings, a master grating can be used to direct an exposure beam and to form an interferential pattern onto a layer of uncured photopolymer material to form gratings. The recording process can be performed on a waveguide cell that includes a layer of uncured photopolymer material sandwiched by two transparent substrates, which are typically made of plastic or glass plates. The waveguide cell with the layer of uncured photopolymer material can be formed in many different ways, including but not limited to vacuum filling and printing deposition processes. By exposing the master grating with a recording beam, a portion of the beam will diffract while a portion passes through as zero-order light. The diffracted portion and the zero-order portion can interfere to expose the photopolymer material. The monomers and nanoparticles phase separated to form alternating regions of monomers and nanoparticles corresponding to the interference pattern, effectively forming a volume Bragg grating. In a number of embodiments, two different exposure beams are utilized to form the interference pattern for the desired exposure.

Depending on the application, the type and size of the formed gratings can differ widely. In several embodiments, the nanoparticle-based photopolymer system is implemented to form isotropic gratings. Isotropic gratings can be advantageous in many different waveguide applications.

Anisotropic gratings, such as those formed from traditional HPDLC material systems, can produce a polarization rotation effect on light propagating within the waveguide, resulting in striations and other undesirable artefacts. Waveguides incorporating isotropic gratings can eliminate many of these artefacts, improving light uniformity. In many embodiments, the nanoparticle-based gratings have high diffraction efficiencies for both S- and P-polarized light, which enable more uniform and efficient waveguides compared to typical HPDLC gratings. In some embodiments, the gratings provide diffraction efficiencies of at least ~20% for at least one of S- and P-polarized light. In further embodiments, the gratings provide diffraction efficiencies of at least ~40% for at least one of S- and P-polarized light. As can readily be appreciated, such gratings can be configured with the appropriate polarized response depending on the specific requirements of a given application. For example, in a number of embodiments, the gratings provide at least ~40% diffraction efficiency for S-polarized light to implement a waveguide display with adequate brightness. In further embodiments, the gratings provide at least ~40% diffraction efficiency for S-polarized light and at least ~10% diffraction efficiency for P-polarized light.

Waveguide applications typically utilize subwavelength-sized gratings to enable the desired propagation and control of light within the waveguide. As such, several embodiments of the invention include the use of nanoparticle-based photopolymer material to form gratings having periods of less than ~500 nm. In further embodiments, the gratings have periods of ~300-500 nm. In a number of embodiments, the type of monomers and nanoparticles can be selected to provide a high rate of diffusion during the phase separation process of the grating formation. A high rate of diffusion can facilitate and can be required in some applications for the formation of small gratings. In many embodiments, the gratings are formed to have rolled K-vectors—i.e., the K-vectors of the gratings vary while maintaining a similar period. In addition to different periods and varying K-vectors, the gratings can also be formed to have a specific thickness, which is typically defined by the thickness of the layer of photopolymer material. As can readily be appreciated, the thickness at which the gratings are formed can depend on the specific application. In general, thinner gratings result in lower diffraction efficiencies but higher operating angular bandwidth. In contrast to other conventional material systems, photopolymer material systems in accordance with various embodiments of the invention are capable of providing thin gratings with sufficient diffraction efficiency values for many desired waveguide applications. In many embodiments, the gratings are formed to have a thickness of less than ~5 μm . In further embodiments, the gratings are formed to have a thickness of ~1-3 μm . In several embodiments, the gratings have a varying thickness profile.

The type of components utilized can depend on the specific requirements of a given application. For example, the type of nanoparticle can be selected to have low reactivity with the remaining components (i.e., the nanoparticles are chosen for their non-reactivity to the monomers, dyes, cointiators, etc. in the material system). In a number of embodiments, zirconium dioxide nanoparticles are utilized. In many applications, waveguide efficiency is of critical importance. In such cases, a nanoparticle having low-absorptive properties can be advantageous. Given the amount of grating interactions within a typical waveguide application, even absorption values considered low in conventional systems can still result in an unacceptable loss of efficiency.

For example, typical metallic nanoparticles having high absorptive properties would likely be undesirable for many waveguide applications. As such, in many embodiments, the type of nanoparticles is selected to provide less than 0.1% absorption. In some embodiments, the nanoparticles are non-metallic. In addition to low absorptive values, other characteristics affecting waveguide performance and grating-formation can also be considered.

Small gratings can be advantageous in many waveguide applications. Compared to traditional HPDLC material systems, phase-separated nanoparticle-based photopolymer material can allow for the formation of gratings with a much higher resolution due to the relatively small size of nanoparticles compared to LC droplets. In typical HPDLC material systems, the LC droplets are about 100 nm in size. This can lead to certain limitations in some applications. For instance, many waveguide applications implement a holographic exposure/recording process for forming gratings within a waveguide. Depending on the application, the resolution of feature sizes of the master grating can be limited. In several embodiments, the master grating has about ~125 nm resolution. As such, forming gratings using 100 nm LC droplets can be difficult and leaves little margin for error. Contrasted with photopolymer material systems described herein, the nanoparticles that form the gratings are at least an order of magnitude smaller. In some embodiments, the material system includes nanoparticles that have diameters of less than 15 nm. In further embodiments, the nanoparticles have diameters of ~4--10 nm. The relatively small sizes of the nanoparticles in comparison with the resolution of the feature sizes of the master grating allow for the formation of gratings with high fidelity. Furthermore, the physical characteristics of the nanoparticles can allow for the formation of gratings that result in relatively low haze compared to the large liquid crystal droplet sizes of traditional HPDLC material systems. In several embodiments, haze of less than ~1% can be achieved. In further embodiments, the system has haze of less than ~0.5%. Another important characteristic to consider in the selection of the type of nanoparticles to be used includes their refractive indices. In many applications, such as waveguide display applications, the refractive indices of the components and materials can have a large effect on waveguide performance and efficiency. For example, the refractive indices of the components within a grating can determine its diffraction efficiency. In some embodiments, nanoparticles having a high refractive index n are utilized to form gratings having high diffraction efficiencies. For example, in a number of embodiments, ZrO_2 nanoparticles having a refractive index of at least 1.7 are utilized. In some embodiments, nanoparticles having refractive indices of at least 1.9 are utilized. In further embodiments, nanoparticles having refractive indices of at least 2.1 are utilized. The nanoparticles and monomers within the photopolymer mixture are chosen to provide gratings having a high Δn . In several embodiments, the gratings have refractive index modulations of at least ~0.04 Δn . In further embodiments, gratings having refractive index modulations of ~0.05-0.06 Δn are utilized. Such materials can be advantageous in enabling the formation of thin gratings having sufficient diffraction efficiencies for certain waveguide applications. In a number of embodiments, the materials can form ~2 μm -thick gratings having diffraction efficiencies of above 30%. In further embodiments, the gratings can have diffraction efficiencies of above 40%. In certain cases, metallic nanoparticles can be implemented to provide a high refractive index, a typically characteristic of metallic components. However, metallic components typically have high

absorption and are unsuitable for use in many different waveguide applications. As such, many embodiments of the invention are directed towards material systems having non-metallic nanoparticles that are capable of forming thin, efficient gratings.

In many embodiments, the material system is an HPDLC mixture. HPDLC mixtures generally include LC, monomers, photoinitiator dyes, and cointiators. The mixture (often referred to as syrup) frequently also includes a surfactant. For the purposes of describing the invention, a surfactant is defined as any chemical agent that lowers the surface tension of the total liquid mixture. The use of surfactants in PDLC mixtures is known and dates back to the earliest investigations of PDLCs. For example, a paper by R. L. Sutherland et al., SPIE Vol. 2689, 158-169, 1996, the disclosure of which is incorporated herein by reference, describes a PDLC mixture including a monomer, photoinitiator, cointiator, chain extender, and LCs to which a surfactant can be added. Surfactants are also mentioned in a paper by Natarajan et al., Journal of Nonlinear Optical Physics and Materials, Vol. 5 No. 1 89-98, 1996, the disclosure of which is incorporated herein by reference. Furthermore, U.S. Pat. No. 7,018,563 by Sutherland; et al., discusses polymer-dispersed liquid crystal material for forming a polymer-dispersed liquid crystal optical element having: at least one acrylic acid monomer; at least one type of liquid crystal material; a photoinitiator dye; a cointiator; and a surfactant. The disclosure of U.S. Pat. No. 7,018,563 is hereby incorporated by reference in its entirety.

The patent and scientific literature contains many examples of material systems and processes that can be used to fabricate SBGs, including investigations into formulating such material systems for achieving high diffraction efficiency, fast response time, low drive voltage, and so forth. U.S. Pat. No. 5,942,157 by Sutherland, and U.S. Pat. No. 5,751,452 by Tanaka et al. both describe monomer and liquid crystal material combinations suitable for fabricating SBG devices. Examples of recipes can also be found in papers dating back to the early 1990s. Many of these materials use acrylate monomers, including:

R. L. Sutherland et al., Chem. Mater. 5, 1533 (1993), the disclosure of which is incorporated herein by reference, describes the use of acrylate polymers and surfactants. Specifically, the recipe comprises a crosslinking multifunctional acrylate monomer; a chain extender N-vinyl pyrrolidinone, LC E7, photoinitiator rose Bengal, and cointiator N-phenyl glycine. Surfactant octanoic acid was added in certain variants.

Fontecchio et al., SID 00 Digest 774-776, 2000, the disclosure of which is incorporated herein by reference, describes a UV curable HPDLC for reflective display applications including a multi-functional acrylate monomer, LC, a photoinitiator, a cointiators, and a chain terminator.

Y. H. Cho, et al., Polymer International, 48, 1085-1090, 1999, the disclosure of which is incorporated herein by reference, discloses HPDLC recipes including acrylates.

Karasawa et al., Japanese Journal of Applied Physics, Vol. 36, 6388-6392, 1997, the disclosure of which is incorporated herein by reference, describes acrylates of various functional orders.

T. J. Bunning et al., Polymer Science: Part B: Polymer Physics, Vol. 35, 2825-2833, 1997, the disclosure of which is incorporated herein by reference, also describes multifunctional acrylate monomers.

G. S. Iannacchione et al., Europhysics Letters Vol. 36 (6). 425-430, 1996, the disclosure of which is incorporated herein by reference, describes a PDLC mixture including a penta-acrylate monomer, LC, chain extender, cointiators, and photoinitiator.

Acrylates offer the benefits of fast kinetics, good mixing with other materials, and compatibility with film forming processes. Since acrylates are cross-linked, they tend to be mechanically robust and flexible. For example, urethane acrylates of functionality 2 (di) and 3 (tri) have been used extensively for HPDLC technology. Higher functionality materials such as penta and hex functional stems have also been used.

Waveguide Architectures for Resolution Multiplication and FOV Multiplication

In many embodiments, an apparatus for multiplying display resolution can include: an image projector for projecting image light from a microdisplay such that each light from a pixel is mapped into a unique angular direction; an image processor for computing a native image and at least one image shifted in a predefined direction for sequential display by the image projector; and at least one switchable grating switchable between diffracting and non-diffracting states optically coupled to the image processor, or generator, the switchable gratings having a first configuration for propagating the native image light and at least one configuration for propagating the shifted image light with an angular displacement corresponding to the image shift in the direction. In several embodiments, the switchable gratings may be configured in free space. In some embodiments, the switchable gratings are disposed within at least one waveguide.

The image shift can be implemented in several different ways. In a number of embodiments, the image shift is one of vertical or horizontal to provide resolution doubling. In several embodiments, the image shifts include vertical and horizontal shifts to provide doubling of both vertical and horizontal resolutions. In many embodiments, the image shift is equal to exactly half a pixel in the vertical or horizontal dimension. In some embodiments, the image shift is $N+1/2$ times a pixel dimension, where N is an integer (where 0 is assumed to be an integer). Such configurations can give more flexibility in the offset design, losing only N pixels in image size. As can readily be appreciated, the image shift can be implemented in a number of different ways. In some embodiments, the image shift can be of any sub-pixel size, such as but not limited to $1/3$ or $2/5$ times a pixel dimension. In a number of embodiments, the image shift is $N+$ any fraction of a pixel, where N is an integer. In many embodiments, integer vertical and half pixel horizontal offsets are provided. In some embodiments, integer horizontal and half pixel vertical offsets are provided. In several embodiments, vertical and horizontal offsets have different integer multiples of the pixel dimension to compensate for image offsets arising from non-orthogonal input, fold, and output grating vector (K -vector components) in the plane of a waveguide. In various embodiments, the native and shifted images are sequentially displayed within a human eye integration period.

In many embodiments, a resolution multiplication waveguide can include a set of switchable gratings. In further embodiments, the switchable gratings include first and second gratings disposed in a first waveguide and third and fourth gratings disposed in a second waveguide. In some embodiments, the first grating overlaps the third grating and the second grating overlaps the fourth grating. The gratings can overlap completely or partially depending on the appli-

15 cation. In the overlapping configurations, the first and third gratings can act as input couplers, and the second and further grating can act as output couplers. FIGS. 1A-1B conceptually illustrate side elevation views of a resolution multiplication waveguide device in accordance with an embodiment of the invention. The first configuration 100A, which is illustrated in FIG. 1A, is provided when the first and second switchable gratings are in their diffracting states. The second configuration 100B, which is illustrated in FIG. 1B, is provided when the first and second gratings are in their non-diffracting states. Referring first to FIG. 1A, the first configuration 100A includes an image projector 101 coupled to a resolution-multiplication waveguide that includes a first waveguide layer 102 containing a first input grating 103 and a first output grating 104. The resolution-multiplication waveguide further includes a second waveguide layer 105 containing a second input grating 106 and a second output grating 107. As shown, the second input grating 106 substantially overlaps the first input grating 103 and second output grating 107 substantially overlaps the first output grating 104. Voltages can be applied to the gratings in the first waveguide layer 102 by electrical connections indicated by the symbol V and referenced by the numerals 108A-108B.

In the illustrative embodiment of FIG. 1A, the image projector 101 includes a microdisplay panel 101A providing an array of pixels 101B and a projection lens 101C for projecting image light from the microdisplay 101A such that light from each pixel is mapped into a unique angular direction. In some embodiments, the projection lens 101C may be a multi-element refractive lens system. In several embodiments, the projection lens 101C may include diffractive elements or surfaces. An image projector of this basic configuration will be assumed for the purposes of explaining the invention. However, it should be apparent to those skilled in the art that the invention may be applied using any type of image projector. In some embodiments, the image projector 101 may use a large scanner to form a pixelated image. In a number of embodiments, the image projector 101 may contain more than one microdisplay or laser scanner for providing more than one pixelated image source.

Referring again to FIG. 1A, the device further includes an image processor 109, which is electrically connected to the image projector 101 via a data communications and control link 109A. The image processor 109 can be configured to compute a native (unshifted) image and at least one image shifted in a predefined direction for sequential display by the image projector 101. Image shifts can be implemented in any of the schemes described above, including but not limited to N+ any fraction of a pixel, where N is an integer including zero. Image light from the image projector 101 can be optically coupled into the resolution multiplication waveguide by a prism 110. In some embodiments, the prism 110 may be replaced by a grating.

When a native image frame is displayed on the microdisplay 101A, the light path from the image projector 101, or image generator, through the first waveguide layer 102 and into the light extraction path from the first waveguide layer 102, with the gratings 103, 104 of the first waveguide layer 102 in their diffracting states, is indicated in FIG. 1A by rays 111-115 with a native image frame pixel indicated by 116.

When a shifted image frame is displayed, the light path from the image projector 101, or image generator, into the second waveguide layer 105 and into the light extraction path from the second waveguide layer 105 and through the first waveguide layer 102 is indicated in FIG. 1B by rays

117-122. The shifted image frame pixel is indicated by 123 and the corresponding native image frame pixel is again indicated by 116. In the illustrative embodiment, zero-order light from the input gratings 103, 106 of each of the waveguide layers 102, 105 as indicated by ray 124 in FIG. 1A and ray 125 in FIG. 1B propagates substantially undeviated out of the waveguide layers 102, 105 onto a light trap 126. It should be apparent from the drawings that with minor modifications to the architecture shown in FIGS. 1A-1B, either of the waveguides can be used to propagate the native image frame.

In many embodiments, the gratings of the first waveguide layer are switchable while the gratings in the second waveguide layer do not require switching. In several embodiments, the gratings in the second waveguide layer are configured to always be in their diffracting states. In some embodiments, such as the one illustrated in FIG. 2, the gratings of both waveguide layers are switchable and configured to switch between diffracting and non-diffracting states. As shown, the configuration 200 of FIG. 2 includes a waveguide that can have similar components as shown in the embodiment of FIGS. 1A-1B, including a first waveguide layer 201 having a first input grating 202 and a first output grating 203 and a second waveguide layer 204 having a second input grating 205 and a second output grating 206. However, in the illustrative embodiment of FIG. 2, the gratings 205, 206 of the second waveguide layer 204 are switched into their non-diffracting states when the gratings 202, 203 of the first waveguide layer 201 are switched into their diffracting states. Voltages are applied to the gratings via electrical connections to a voltage source indicated by the symbol V and referenced by the numerals 207A-207D. By controlling the switching of the gratings 205, 206 in the second waveguide layer 204 when the gratings 202, 203 in the first waveguide layer 201 are diffracting, the risk of zero order light 208 coupling back into the first waveguide layer 201 can be minimized.

The gratings can be switched in coordination with the frame update of the microdisplay such that when the gratings of the first waveguide layer are in their diffracting states, the input image generator displays the native image and when the gratings of the first waveguide layer are in their non-diffracting states, the image generator displays an image recomputed with a half pixel horizontal shift. Since the switching of the native and shifted frames takes place within the human eye integration time, the display viewer can perceive a doubling of the displayed image resolution.

In many embodiments, the gratings in the first and second waveguide layers can be similarly configured but have slightly different grating prescriptions designed to produce a relative angular shift, which can be equivalent to half a pixel or any other predefined value, to the native image. In some embodiments, the required angular shift is produced by applying small tilts to the grating K-vectors. In several embodiments, the required angular shift is produced by small changes to the surface gratings formed by the input and output gratings. Since the angular separation of the native and shifted image frames is typically very small, when coupled into a display waveguide, the image light of the frames can be propagated with high efficiency before being extracted into the eye box of the waveguide display.

In some embodiments, the first and second waveguide layers are designed such that only a few total internal reflection (TIR) bounces take place before light extraction. This ensures that beam expansion is minimized for efficient coupling into a separate waveguide device.

In some embodiments, the first and second waveguide layers will be separated by a small air gap to ensure complete optical isolation. In several embodiments, a low index material such as a nanoporous material can be used for waveguide isolation.

In some embodiments, separate waveguide layers are provided for red, green, and blue light. In several embodiments, separate waveguide layers are provided for red and blue/green light. In many embodiments, the gratings multiplex more than one wavelength. In a number of embodiments, the gratings multiplex more than one angular bandwidth. In some embodiments, further resolution multiplication operations can be implemented. For example, to provide resolution quadrupling, waveguides can be further stacked to deflect light into different directions corresponding to pixel shifts in different directions. Such implementations can be based on similar principles and embodiments as those shown in FIGS. 1A-1B and FIG. 2.

In some embodiments, a resolution multiplication waveguide is optically coupled to a waveguide display. FIGS. 3A-3B conceptually illustrate schematic side elevation views illustrating two operational states 300A, 300B of one such embodiment. As shown, the resolution multiplication waveguide, which can be implemented based on embodiments similar to those illustrated in FIGS. 1A-1B and FIG. 2, is optically coupled to a waveguide display 301. In the illustrative embodiment, the waveguide display 301 contains an input grating 302 and an output grating 303. In some embodiments, the waveguide display 301 may further include a fold grating. In many embodiments, the waveguide display 301 may include separate layers for propagating light of different colors. In the illustrative embodiment of FIG. 3A, native image frame light 304 emerging from the first waveguide layer of the resolution multiplication waveguide is coupled into the waveguide display 301 along a TIR path represented by rays 305-306 before being coupled out of the waveguide 301 as represented by ray 307 to form an output image containing pixels such as the one indicated by 308. As shown in FIG. 3B, shifted image frame light 309 emerging from the second waveguide layer of the resolution multiplication waveguide is coupled into the waveguide display 301 along a TIR path represented by rays 310-311 before being coupled out of the waveguide as represented by ray 312 to form an output image containing pixels such as the one indicated by 313 which is shifted from the corresponding native pixel 308 by half a pixel width.

As described above, resolution multiplication applications can be implemented to provide quadrupling of the resolution of a display, that is, doubling both the vertical and horizontal resolutions. FIGS. 4A-4D provide illustrations of four different pixel-shifting steps used to provide resolution quadrupling in accordance with an embodiment of the invention. FIG. 4A shows a native image 400A, which is represented by a 4x4 pixel array contain pixels such as 401 separated by gaps 402. FIG. 4B illustrates a pixel array 400B in which each pixel, such as 403, has undergone a first half pixel horizontal shift relative to its corresponding native pixel 401. FIG. 4C illustrates a pixel array 400C in which each pixel, such as 404, has undergone a half pixel vertical and horizontal shift relative to its corresponding native pixel 401. FIG. 4D illustrates a pixel array 400D in which each pixel, such as 405, has undergone a half pixel vertical shift relative to its corresponding native pixel 401.

FIGS. 5A-5D illustrates the grating states 500A-500D of a waveguide display 501 capable of propagating the four-pixel arrays configurations illustrated in FIGS. 4A-4D. As shown, the waveguide display 501 includes first and second

input gratings for coupling light from an image projector 502 into a TIR path in the waveguide display 501. The waveguide display 501 further includes first and second output gratings for coupling light out of the waveguide display 501. Although the waveguide display 501 is illustrated as a single layer, such waveguide displays can be implemented with multiple waveguide layers, each containing a grating layer. Referring back to FIG. 5A, the waveguide display 501 further includes a common fold grating 503 disposed in the same grating layer as first input and output gratings, which can be used in both grating configurations 500A, 500B to provide two-dimensional beam expansion in association with the first and second output gratings. The fold grating 503 may be disposed in either of the two grating layers. In some embodiments, the fold grating 503 may not be required. Voltages are applied to the gratings via electrical connections to a voltage source indicated by the symbol V and referenced by the numerals 504A-504D.

FIG. 5A illustrates the grating configuration 500A for propagating the pixel configuration of FIG. 4A (native image) in which the second input grating and the second output grating are in their diffracting states 505A, 506A respectively and the first input grating and the first output grating are in their non-diffracting states 507B, 508B respectively. The ray path is indicated by rays 509A-512A. FIG. 5B illustrates the grating configuration 500B for propagating the pixel configuration of FIG. 4B in which the first input grating and the second output grating are in their diffracting states 507A, 506A respectively and the second input grating and the first output grating are in their non-diffracting states 505B, 508B respectively. The ray path is indicated by rays 509B-512B. FIG. 5C illustrates the grating configuration 500C for propagating the pixel configuration of FIG. 4C in which the first input grating and the first output grating are in their diffracting states 507A, 508A respectively and the second input grating and the second output grating are in their non-diffracting states 505B, 506B respectively. The ray path is indicated by rays 509C-512C. FIG. 5D illustrates the grating configuration 500D for propagating the pixel configuration of FIG. 4D in which the second input grating and the first output grating are in their diffracting states 505A, 508A respectively and the first input grating and the second output grating are in their non-diffracting states 507BA, 506B respectively. The diffracted ray path is indicated by the rays 510D-513D.

Achieving a 60 Hz 1080p image frame rate using the apparatus of FIGS. 5A-5D can require four video sub-frames to be generated at 240 Hz video frame rate. Each video sub-frame can require red, green, blue sub-frames, increasing the frame rate to 720 Hz. In some embodiments, the two-layer grating architecture illustrated in FIGS. 5A-5D is used to propagate monochromatic light with further similar waveguides being required for other colors. For example, in some embodiments, separate waveguides would be required for red, green, and blue. In several embodiments, color display is provided with one red waveguide and one blue/green waveguide. The switchable grating arrangement of FIGS. 5A-5D has several advantages including but not limited to: low cost and complexity; the input image from the projector passing through the minimum number of ITO layers; and the dual switchable grating offsets being switched separately thereby minimizing loss.

It should be apparent from consideration of FIGS. 5A-5D, in some embodiments, one of the first or second input gratings may be eliminated to provide a waveguide that propagates the native image and a shifted image sequen-

tially. Alternatively, by the same reasoning, one of the first or second output gratings may be eliminated to achieve the same effect. In some embodiments, one of the grating layers in FIGS. 5A-5D may be non-switching.

FIG. 6 is a flow diagram conceptually illustrating a method 600 of multiplying the resolution of a waveguide display in accordance with an embodiment of the invention. Referring to the flow diagram, the method 600 includes providing (601) an image projector and an image processor and providing (602) a waveguide containing first, second, third, and fourth switchable gratings with first and third gratings overlapping and the second and fourth gratings overlapping and each grating having an optical prescription for applying an angular shift to incident light. A pixel shift $(N+\frac{1}{2})$ multiplied by P can be performed (603), where N is an integer greater than or equal to zero and P is a pixel dimension. As described above, any fractional pixel shift can be implemented instead of $\frac{1}{2}$. A shifted image can be computed (604) using the image processor. A shifted image can be written (605) to the image projector. One of the first and third switchable gratings and one of the second and fourth switchable gratings can be switched (606) into their diffracting states. Shifted image light can be coupled (607) into the waveguide via the diffracting first or third switchable gratings. Image light can be coupled (608) out of the waveguide via the diffracting second or fourth switchable gratings with a pixel shift determined by the prescriptions of the diffracting switchable gratings. The pixel shift step can be repeated (608) until all required image pixel shifts have been completed.

In addition to resolution multiplication waveguide architectures, waveguides for multiplying resolution and field-of-view can also be implemented using related principles similar to those shown in FIGS. 1-6. FIG. 7 is a schematic illustration of an apparatus for multiplying the resolution and field-of-view in accordance with an embodiment of the invention. As shown, the apparatus 700 includes a first waveguide 701 for multiplying resolution (which can be implemented in accordance with any of the above described embodiments), an input image source 702 provide image modulated light 703, a second waveguide 704 for multiplying field-of-view supporting input gratings 705A,705B and output gratings 706A,706B. The first waveguide 701 provides resolution multiplied light 707A, which is coupled into the second waveguide 704. In some embodiments, the input gratings 705A, 705B are switchable gratings and the output gratings 706A, 706B are non-switching gratings. In many embodiments, the one of the input gratings 705A, 705B can be non-switching gratings and one or both of the output gratings can be non-switching gratings. In several embodiments, all of the gratings can be switching.

In the embodiments of FIG. 7, the input grating 705A and the output grating 706A provide a first waveguide path for a first field-of-view portion. The first waveguide path is illustrated by the total internal reflection rays 707B,707C which are coupled out of the waveguide 704 by the output grating 706A into a ray path 707D to the eyebox 708. The input grating 705B and the output grating 706B can provide a second waveguide path (not shown) for a second field-of-view portion. In many embodiments, the image source 702 provides first image modulated light for projection into the first field-of-view portion when the input grating 705A and the output grating 706A are in their diffracting states and the input grating 705B and the output grating 706B are in their non-diffracting states. In some embodiments, the image source provides second image modulated light for projection into the second field-of-view portion when the input grating

705A and the output grating 706A are in their non-diffracting states and the input grating 705B and the output grating 706B are in their diffracting states. As can be readily appreciated, various diffracting and non-diffracting configurations can be implemented for propagating the first and second image modulated light. From consideration of FIG. 7, it should be apparent that further input and output gratings can be added for the purposes of producing further field-of-view portions for viewing. In many embodiments, multiple fields of view portions can be tiled to provide a continuous and expanded field-of-view. In some embodiments, field-of-view portions do not need to abut.

FIG. 8 conceptually illustrates a waveguide 800 showing how in-coupling switchable diffractive elements and out-coupling diffractive elements can be paired up and switched in and out (on and off or vice versa) so that the output light does not suffer from image doubling and chromatic aberration, which could be present if non-switchable diffraction elements are utilized as discussed earlier. As shown, waveguide 800 includes input diffractive elements 801-803 (or input gratings) and output diffractive elements 804-806 (or output gratings). In some embodiments, the input diffractive elements 801-803 are switchable gratings and the output diffractive elements 804-806 are non-switching gratings. In many embodiments, the input diffractive elements 801-803 and the output diffractive elements 804-806 can include any combination of switching and non-switching gratings. In several embodiments, all of the diffractive elements can be switching. The diffractive elements can be formed in one or more layers of holographic recording medium. In the illustrative embodiment, the diffractive elements are formed in a holographic recording medium 807 sandwiched by substrates 808A, 808B. In other embodiments, each input diffractive element and its corresponding output diffractive element are formed in a holographic recording medium sandwiched by two transparent substrates. In several embodiments, the input diffractive elements 801-803 and corresponding output diffractive elements 804-806 have equal and opposite diffractive power. In the illustrative embodiment, input light is received from three different angles. The three angles can each correspond to the principal or center angles of incident rays contained within a portion of a field-of-view. In some embodiments, an input collimating lens (which is not illustrated) generates a field-of-view that is needed for the optical display system. According to some exemplary embodiments, the collimating lens may be integrated with the input diffractive elements, while in other exemplary embodiments, the collimating lens may be separate. At any point in time, only one of each input element 801, 802, 803 may be operational or switched on along with its corresponding output element 804, 805, 806 respectively and all elements may switch consecutively within the frame time of the system. In several embodiments, light does not couple into waveguide 800 until it hits a diffractive element (801, 802, or 803) that is operational. Therefore, only light from one angle range is coupled into waveguide at any one point in time. Further, in such embodiments, light does not couple out of the substrate until it hits the diffraction element (804, 805, or 806) that is operational. In some embodiments, using non-switching gratings for an input or output grating can result in incident light rays being off-Bragg (that is, not satisfying the Bragg equation) for a particular grating.

According to the illustrated example, a single parallel beam of light shown by dashed lines hits diffraction surface and is diffracted into waveguide until it hits complimentary diffractive surface and is diffracted out of waveguide at the same angle as it enters waveguide. Ray paths are indicated

by rays **809A-809C**. Because the input diffractive power is equal and opposite to the output diffractive power no chromatic aberration is induced in the system. It is noted that while FIG. **8** illustrates use of three input and output switchable diffractive elements, according to other exemplary embodiments, more or fewer than three switchable diffractive elements may be used. It is also noted that while the FIG. **8** illustrates reception and output of light at three different angles, the figure does not include the light in the range between the three field angles shown. The light incident on each of the diffractive surfaces are in a range limited by the diffraction efficiency angular bandwidths of the gratings.

While the waveguide of FIG. **8** has been illustrated as having single rows of diffractive elements, according to other exemplary embodiments, a waveguide can include in-coupling and out coupling gratings disposed in two dimensional arrays with correspond input and output elements paired up according to the principles illustrated in FIG. **8** with corresponding elements of the input and output arrays having equal and opposite grating vector components.

In some embodiments, the field-of-view multiplication waveguide can further include fold grating(s) for providing a first beam expansion with the output grating(s) providing a second expansion orthogonal to the first beam expansion. In such configurations, the input, output, and fold gratings can have gratings vectors summing to substantially zero. In some embodiments, the field-of-view multiplication waveguide support gratings for diffracting different wavelength bands. In several embodiments, the field-of-view multiplication waveguide support gratings for diffracting different incident light polarizations. In a number of embodiments, the field-of-view multiplication waveguide support can support at least one multiplexed grating for diffracting light of different wavelength bands, angular bandwidths, or polarization states. In many embodiments, the field-of-view multiplication waveguide can support at least one rolled k-vector grating. In some embodiments, the field-of-view multiplication waveguide can support at least one dual interaction grating.

FIG. **9** conceptually illustrates a waveguide for multiplying the resolution and field-of-view in accordance with an embodiment of the invention. The apparatus **900** includes a waveguide **901** supporting a first pair of input gratings **902A,902B**, a second pair of input gratings **903A,903B** and a first pair of output gratings **902C,902D** and a second pair of output gratings **903C,903D**. In the illustrative embodiment, the first pair of input gratings **902A,902B** and the first pair of output gratings **902C,902D** provide resolution multiplication for light to be projected in a first field-of-view portion with the gratings being switched to provide waveguide paths for native image and pixel shifted images according to the principles discussed in the preceding sections (such as those illustrated in FIGS. **1-6**). Ray paths from the image source **904** to the eye box **905** are represented by the rays **906-908**. The second pair of input gratings **903A,903B** and the second pair of output gratings **903C,903D** provide resolution multiplication for light to be projected in a second field-of-view portion with the gratings being switched to provide waveguide paths for native image and pixel shifted images. Providing the first and second field-of-view portion can be implemented in accordance with any of the principles described in the sections above. As can readily be appreciated, the input and output gratings can be disposed across several grating layers and/or waveguides that can be stacked to implement similar functions.

FIG. **10** is a flow diagram conceptually illustrating a method of multiplying the field-of-view and resolution of an image in accordance with an embodiment of the invention. As shown, the method **1000** of multiplying the field-of-view and resolution of an image is provided. Referring to the flow diagram, the method **1000** includes providing **(1001)** an image projector for directing light from pixels of a pixelated image display into unique angular directions, providing **(1002)** an image processor for computing native images corresponding to first and second field-of-view portions, at least one first field-of-view image shifted in a predefined direction and at least one second field-of-view image shifted in a predefined direction, providing **(1003)** a first waveguide supporting input gratings and output gratings for multiplying image resolution in at least one of two orthogonal directions, and providing **(1004)** a second waveguide supporting input gratings and output gratings for providing a first waveguide path for a first field-of-view portion and a second waveguide path for a second field-of-view portion. In some embodiments, the input gratings are switchable gratings and the output grating are non-switching gratings. In many embodiments, at least one of the input gratings can be non-switching gratings and at least one of the output gratings can be non-switching gratings. In several embodiments, all of the gratings can be switching.

Referring again to FIG. **10**, the method **1000** further includes computing **(1005)** a first image for projection into a first field-of-view. The resolution of the first field-of-view image can be multiplied **(1006)** using the first waveguide. The input grating and the output grating for propagating light for projection into the first field-of-view portion can be switched **(1007)** into their diffracting states at the same time as the input grating and output grating for propagating light for projection into the second field-of-view portion are switched into their non-diffracting states. The resolution multiplied first field-of-view portion can be projected **(1008)** for viewing. A second image for projection into the second field-of-view can be computed **(1009)** using the image processor. The resolution of the second field-of-view image can be multiplied **(1010)** using the first waveguide. The input grating and the output grating for propagating light for projection into the first field-of-view portion can be switched **(1011)** into their non-diffracting states at the same time as the input grating and output grating for propagating light for projection into the second field-of-view portion are switched into their diffracting states. The resolution multiplied second field-of-view portion can be projected **(1012)** for viewing.

Although FIGS. **7-10** illustrate specific configurations and methods, it should be readily apparent that various components and steps can be modified, removed, or included depending on the specific requirements of a given application. For example, FIG. **10** describe a method for multiplying the field-of-view and resolution using two separate waveguides. In other embodiments, the functions of the two waveguides can be implemented in a single waveguide.

Other Embodiments

The embodiments and techniques described in the sections above can be configured and modified in many different ways. For example, devices in accordance with various embodiments of the invention can incorporate the techniques and teachings disclosed in the U.S. patent application Ser. No. 16/162,280 filed Oct. 16, 2018, entitled "Systems and Methods for Multiplying the Resolution of a Pixelated Display;" U.S. Pat. No. 8,817,350 filed Jan. 20, 2012, entitled "Optical Displays;" and U.S. patent application Ser.

No. 13/869,866 filed Apr. 24, 2013, entitled "Holographic Wide Angle Display," the disclosures of which are hereby incorporated by reference in their entireties for all purposes. Furthermore, waveguide embodiments can include various grating configurations. In some embodiments, the switchable gratings are disposed in a waveguide further including a non-switching grating. In some embodiments, the non-switching grating is a fold grating (sometimes referred to as a turning grating) used for beam expansion as described in the references. In such embodiments, the invention provides a displays waveguide embodying resolution multiplication and two-axis beam expansion. In some embodiments, at least one of the gratings used for resolution multiplication is a rolled k-vector grating. The K-vector (more commonly referred to as the grating vector) is a vector-aligned normal to the grating planes (or fringes) which determines the optical efficiency for a given range of input and diffracted angles. Rolling the K-vectors allows the angular bandwidth of the grating to be expanded without the need to increase the waveguide thickness. In some embodiments, the switchable gratings include at least one grating multiplexing at least one of wavelength or angular bandwidth. It is well established in the literature of holography that more than one holographic prescription can be recorded into a single holographic layer. Methods for recording such multiplexed holograms are well known to those skilled in the art. In some embodiments, at least one of the switching gratings and other gratings used in association with them may combine two or more angular diffraction prescriptions to expand the angular bandwidth or to expand the spectral bandwidth. For example, color multiplexed gratings may be used to diffract two or more of the primary colors.

In any of the above described embodiments the image projector, which is referred to in some of the references an Input Image Node (IIN), may integrate a microdisplay panel, light source and other optical components commonly used to illuminate the display panel, separate the reflected light and collimate it into the required field-of-view. In some embodiments, the image projector may be based on the embodiments and teachings disclosed in U.S. patent application Ser. No. 13/869,866 entitled HOLOGRAPHIC WIDE-ANGLE DISPLAY, and U.S. patent application Ser. No. 13/844,456 entitled TRANSPARENT WAVEGUIDE DISPLAY. In some embodiments, the image projector contains a beam-splitter for directing light onto the microdisplay and transmitting the reflected light towards the waveguide. In some embodiments, the beamsplitter is a grating recorded in HPDLC and uses the intrinsic polarization selectivity of such gratings to separate the light illuminating the display and the image modulated light reflected off the display. In some embodiments, the beam splitter is a polarizing beam splitter cube. In some embodiment, the image projector incorporates an illumination homogenizer or a laser beam despeckler. Advantageously, the despeckler is holographic waveguide device based on the embodiments and teachings of U.S. Pat. No. 8,565,560 entitled LASER ILLUMINATION DEVICE.

In some embodiments, the light source is a laser. In some embodiments, the light source is a LED. In some embodiments, the image projector includes one or more lenses for modifying the illumination angular characteristics. LED will provide better uniformity than laser. If laser illumination is used, there is a risk of illumination banding occurring at the waveguide output. In some embodiments laser illumination banding in waveguides can be overcome using the techniques and teachings disclosed in U.S. patent application Ser. No. 15/512,500 entitled METHOD AND APPARATUS

FOR GENERATING INPUT IMAGES FOR HOLOGRAPHIC WAVEGUIDE DISPLAYS. In some embodiments, the light from the light source is polarized. In one or more embodiments, the image source is a liquid crystal display (LCD) micro display or liquid crystal on silicon (LCoS) micro display. In some embodiments, the image source is a MEMs device. In some embodiments, the image source is a display panel based on Texas Instruments' Digital Light Projector (DLP) technology.

In some embodiments, any of the gratings used to apply the invention may encoded optical power for adjusting the collimation of the output. In some embodiments, the output image is at infinity. In some embodiments, the output image may be formed at distances of several meters from the waveguide.

In some embodiments using fold gratings, the fold grating angular bandwidth is enhanced by designing the grating prescription provides dual interaction of the guided light with the grating. Exemplary embodiments of dual interaction fold gratings are disclosed in U.S. patent application Ser. No. 14/620,969 entitled WAVEGUIDE GRATING DEVICE.

In some embodiments, the waveguides used in the invention are formed by sandwiching the grating layers between glass or plastic substrates to form a stack within which total internal reflection occurs at the outer substrate and air interfaces. The stack may further comprise additional layers such as beam splitting coatings and environmental protection layers. In some embodiments, the cell substrates may be fabricated from glass. An exemplary glass substrate is standard Corning Willow glass substrate (index 1.51) which is available in thicknesses down to 50 microns. In other embodiments, the cell substrates may be optical plastics. In some embodiments, the gratings may be recorded in layers of material coated onto a transparent substrate and covered by a protective transparent layer after the holographic exposure process has been completed. In some embodiments, the grating layer may be broken up into separate layers. For example, in some embodiments, a first layer includes the fold grating while a second layer includes the output grating. In some embodiments, a third layer can include the input coupler or grating. The number of layers may then be laminated together into a single waveguide substrate. In some embodiments, the grating layer is comprised of a number of pieces including the input coupler, the fold grating and the output grating (or portions thereof) that are laminated together to form a single substrate waveguide. The pieces may be separated by optical glue or other transparent material of refractive index matching that of the pieces. In another embodiment, the grating layer may be formed via a cell making process by creating cells of the desired grating thickness and vacuum filling each cell with holographic recording material for each of the input coupler, the fold grating and the output grating. In one embodiment, the cell is formed by positioning multiple plates of glass with gaps between the plates of glass that define the desired grating thickness for the input coupler, the fold grating and the output grating. In one embodiment, one cell may be made with multiple apertures such that the separate apertures are filled with different pockets of holographic recording material. Any intervening spaces may then be separated by a separating material such as glue or oil to define separate areas. In one embodiment, the holographic material may be spin-coated onto a substrate and then covered by a second substrate after curing of the material. By using the fold grating, the waveguide display advantageously requires fewer layers than previous systems and methods of display-

ing information according to some embodiments. In addition, by using fold grating, light can travel by total internal reflection within the waveguide in a single rectangular prism defined by the waveguide outer surfaces while achieving dual pupil expansion. In another embodiment, the input coupler, the fold grating, and the output grating can be created by interfering two waves of light at an angle within the substrate to create a holographic wave front, thereby creating light and dark fringes that are set in the waveguide substrate at a desired angle. In some embodiments, the grating in a given layer is recorded in stepwise fashion by scanning or stepping the recording laser beams across the grating area. In some embodiments, the gratings are recorded using mastering and contact copying process currently used in the holographic printing industry.

In some embodiments, the gratings are recorded in a holographic polymer dispersed liquid crystal (HPDLC) (e.g., a matrix of liquid crystal droplets), although SBGs may also be recorded in other materials. In one embodiment, SBGs are recorded in a uniform modulation material, such as POLICRYPS or POLIPHEN having a matrix of solid liquid crystals dispersed in a liquid polymer. The SBGs can be switching or non-switching in nature. In its non-switching form, an SBG has the advantage over conventional holographic photopolymer materials of being capable of providing high refractive index modulation due to its liquid crystal component. Exemplary uniform modulation liquid crystal-polymer material systems are disclosed in United State Patent Application Publication No.: US2007/0019152 by Caputo et al and PCT Application No.: PCT/EP2005/006950 by Stumpe et al. both of which are incorporated herein by reference in their entireties. Uniform modulation gratings are characterized by high refractive index modulation (and hence high diffraction efficiency) and low scatter.

In some embodiments, at least one of the gratings is recorded a reverse mode HPDLC material. Reverse mode HPDLC differs from conventional HPDLC in that the grating is passive when no electric field is applied and becomes diffractive in the presence of an electric field. The reverse mode HPDLC may be based on any of the recipes and processes disclosed in PCT Application No.: PCT/GB2012/000680, entitled IMPROVEMENTS TO HOLOGRAPHIC POLYMER DISPERSED LIQUID CRYSTAL MATERIALS AND DEVICES. The grating may be recorded in any of the above material systems but used in a passive (non-switching) mode. The fabrication process is identical to that used for switched but with the electrode coating stage being omitted. LC polymer material systems are highly desirable in view of their high index modulation. In some embodiments, the gratings are recorded in HPDLC but are not switched.

In some embodiments of the invention, the resolution multiplication apparatus is used in an eye tracked display comprising a waveguide display according to the principles of the invention and an eye tracker. In one preferred embodiment, the eye tracker is a waveguide device based on the embodiments and teachings of PCT/GB2014/000197 entitled HOLOGRAPHIC WAVEGUIDE EYE TRACKER, PCT/GB2015/000274 entitled HOLOGRAPHIC WAVEGUIDE OPTICAL TRACKER, and PCT Application No. GB2013/000210 entitled APPARATUS FOR EYE TRACKING.

In some embodiments of the invention, the resolution multiplication apparatus is used in a waveguide display further comprises a dynamic focusing element. The dynamic focusing element may be based on the embodiments and teachings of U.S. Provisional Patent Application No.

62/176,572 entitled ELECTRICALLY FOCUS TUNABLE LENS. In some embodiments, a dual expansion waveguide display further comprising a dynamic focusing element and an eye tracker may provide a light field display based on the embodiments and teachings disclosed in U.S. Provisional Patent Application No. 62/125,089 entitled HOLOGRAPHIC WAVEGUIDE LIGHT FIELD DISPLAYS.

In some embodiments, a resolution multiplication apparatus according to the principles of the invention may be used in a waveguide display integrated within a window, for example, a windscreen-integrated HUD for road vehicle applications. In some embodiments, a window-integrated display may be based on the embodiments and teachings disclosed in U.S. Provisional Patent Application No. 62/125,064 entitled OPTICAL WAVEGUIDE DISPLAYS FOR INTEGRATION IN WINDOWS and U.S. Provisional Patent Application No. 62/125,066 entitled OPTICAL WAVEGUIDE DISPLAYS FOR INTEGRATION IN WINDOWS. In some embodiments, the resolution multiplication apparatus may include gradient index (GRIN) wave-guiding components for relaying image content between the image projector and the waveguide containing the resolution multiplication gratings. Exemplary embodiments are disclosed in U.S. Provisional Patent Application No. 62/123,282 entitled NEAR EYE DISPLAY USING GRADIENT INDEX OPTICS and U.S. Provisional Patent Application No. 62/124,550 entitled WAVEGUIDE DISPLAY USING GRADIENT INDEX OPTICS. In some embodiments, a resolution multiplication apparatus may be used in a dual expansion waveguide display incorporating a light pipe for providing beam expansion in one direction based on the embodiments disclosed in U.S. Provisional Patent Application No. 62/177,494 entitled WAVEGUIDE DEVICE INCORPORATING A LIGHT PIPE. In some embodiments, the input image source in the image projector may be a laser scanner as disclosed in U.S. Pat. No. 9,075,184 entitled COMPACT EDGE ILLUMINATED DIFFRACTIVE DISPLAY.

The embodiments of the invention may be used in wide range of displays including HMDs for AR and VR, helmet mounted displays, projection displays, heads up displays (HUDs), Heads Down Displays, (HDDs), autostereoscopic displays and other 3D displays. In some embodiments, a resolution multiplication apparatus according to the principles of the invention may be interfaced to an Augmented Reality (AR) waveguide display with a field-of-view of 50 degrees diagonal. Examples of waveguide displays that can be used in applications of the present invention are discussed in the reference documents. Applications of the invention are not necessarily confined to waveguide displays. In some embodiments, the resolution doubling waveguide may provide a compact image generator for use in any type of wearable or projection display. In some embodiments, the resolution multiplication apparatus may provide an image projector. In some embodiments, the apparatus is optically coupled to one of image display optics, an eyepiece, a projection lens, or a waveguide. In some embodiments, the apparatus forms part of a HMD, a HUD, an eye-slaved display, a dynamic focus display or a light field display. Some of the embodiments and teachings of this disclosure may be applied in waveguide sensors such as, for example, eye trackers, fingerprint scanners and LIDAR systems.

It should be emphasized that the drawings are exemplary and that the dimensions have been exaggerated. For example, thicknesses of the SBG layers have been greatly exaggerated. Optical devices based on any of the above-described embodiments may be implemented using plastic

substrates using the materials and processes disclosed in PCT Application No.: PCT/GB2012/000680, entitled IMPROVEMENTS TO HOLOGRAPHIC POLYMER DISPERSED LIQUID CRYSTAL MATERIALS AND DEVICES. In some embodiments, the waveguide embodi- 5 ments of the invention may be curved.

The construction and arrangement of the systems and methods as shown in the various exemplary embodiments are illustrative only. Although only a few embodiments have been described in detail in this disclosure, many modifica- 10 tions are possible (for example, variations in sizes, dimensions, structures, shapes and proportions of the various elements, values of parameters, mounting arrangements, use of materials, colors, orientations, etc.). For example, the position of elements may be reversed or otherwise varied 15 and the nature or number of discrete elements or positions may be altered or varied. Accordingly, all such modifications are intended to be included within the scope of the present disclosure. The order or sequence of any process or method steps may be varied or re-sequenced according to alternative 20 embodiments. Other substitutions, modifications, changes, and omissions may be made in the design, operating conditions, and arrangement of the exemplary embodiments without departing from the scope of the present disclosure.

DOCTRINE OF EQUIVALENTS

While the above description contains many specific embodiments of the invention, these should not be construed as limitations on the scope of the invention, but rather as an 30 example of one embodiment thereof. It is therefore to be understood that the present invention may be practiced in ways other than specifically described, without departing from the scope and spirit of the present invention. Thus, embodiments of the present invention should be considered 35 in all respects as illustrative and not restrictive. Accordingly, the scope of the invention should be determined not by the embodiments illustrated, but by the appended claims and their equivalents.

What is claimed is:

1. An apparatus for multiplying display resolution and field-of-view, the apparatus comprising:

an image projector for directing light from a plurality of pixels of a pixelated image source into unique angular directions wherein the image projector comprises a 45 microdisplay panel optically connected to a projection lens;

an image processor electrically connected to the image projector for computing native images of the image source corresponding to first and second field-of-view 50 portions and for computing shifted images in a predefined direction corresponding to the first and second field-of-view portions for sequential display by the image projector;

a first set of gratings comprising a first input grating 55 optically coupled to the image projector and a first output grating, wherein the first set of gratings comprises at least one switchable grating switchable between a diffracting state and a non-diffracting state, wherein the first set of gratings have a native configura- 60 tion for propagating the light of the native image and at least one shifted configuration for propagating the light of at least one shifted image, each with an angular displacement corresponding to an image shift in the predefined direction, where the image shift is equal to 65 $N+1/M$ times a pixel dimension, where N and M are integers and N includes zero; and

a second set of gratings comprising a second input grating optically coupled to the first output grating of the first set of gratings, wherein the second set of gratings comprises at least one switchable grating switchable between a diffracting state and a non-diffracting state, wherein the second set of gratings have a first configura- tion for projecting the first field-of-view portion and a second configuration for projecting the second field-of-view portion.

2. The apparatus of claim 1, wherein the first set of gratings is disposed in a first waveguide and the second set of gratings is disposed in a second waveguide.

3. The apparatus of claim 1, wherein the second set of gratings comprises first, second, third, and fourth gratings, wherein the first grating overlaps the third grating and the second grating overlaps the fourth grating, and wherein the first and third gratings act as input couplers and the second and fourth gratings act as output couplers.

4. The apparatus of claim 3, wherein at least one of the first and third gratings is a switchable grating.

5. The apparatus of claim 4, wherein the first, second, third, and fourth gratings are switchable gratings, wherein the first configuration for projecting the first field-of-view portion is provided by one of the first or third switchable gratings and one of the second or fourth switchable gratings in their diffracting states. 25

6. The apparatus of claim 3, wherein the second and fourth gratings are non-switchable gratings.

7. The apparatus of claim 3, wherein the first and second switchable gratings are disposed in a first layer within a waveguide and the third and fourth switchable gratings are disposed in a second layer within the waveguide. 30

8. The apparatus of claim 3, wherein the first and second switchable gratings are disposed in a first waveguide and the third and fourth switchable gratings are disposed in a second waveguide. 35

9. The apparatus of claim 1, wherein M is equal to 2.

10. The apparatus of claim 1, wherein the native and the at least one shifted image are sequentially displayed within a human eye integration period.

11. The apparatus of claim 1, wherein the image shift comprises one of vertical or horizontal shifts. 40

12. The apparatus of claim 1, wherein the image shift comprises vertical and horizontal shifts.

13. The apparatus of claim 1, wherein the switchable gratings are recorded in a holographic polymer dispersed liquid crystal material. 45

14. The apparatus of claim 1, wherein the second set of gratings comprises a non-switchable grating.

15. The apparatus of claim 1, wherein the second set of gratings comprises a fold grating.

16. The apparatus of claim 1 wherein the second set of gratings comprises at least one grating multiplexing at least one of wavelength or angular bandwidth. 50

17. The apparatus of claim 1, wherein the image projector is optically coupled to the first input grating of the first set of gratings by one of a prism or grating. 55

18. The apparatus of claim 1, further comprising an illumination homogenizer.

19. The apparatus of claim 1 wherein the second set of gratings comprises a rolled k-vector grating.

20. A method of multiplying the resolution and field-of-view of a waveguide display, the method comprising: 60

providing an image projector and an image processor; providing a waveguide display comprising first and second sets of gratings, wherein each of the first and second sets of gratings comprises at least one switchable grating switchable between a diffracting state and a non-diffracting state, wherein the first set of gratings has a native switching configuration and a shifted 65

switching configuration, wherein the second set of
 grating has a first switching configuration and a second
 switching configuration; and
 sequentially projecting at least four images, wherein the at
 least four images comprise a native image in a first 5
 field-of-view portion, a shifted image in a first field-
 of-view portion, a native image in a second field-of-
 view portion, and a shifted image in a second field-of-
 view portion, wherein the shifted image has an angular
 displacement with respect to a corresponding native 10
 image defined as an image shift that is equal to $N+1/M$
 times a pixel dimension, where N and M are integers
 and N includes zero;
 wherein:
 the native image in the first field-of-view portion is 15
 projected when the first set of gratings is in the native
 switching configuration and the second set of grat-
 ings is in the first switching configuration;
 the native image in the second field-of-view portion is
 projected when the first set of gratings is in the native 20
 switching configuration and the second set of grat-
 ings is in the second switching configuration;
 the shifted image in the first field-of-view portion is
 projected when the first set of gratings is in the
 shifted switching configuration and the second set of 25
 gratings is in the first switching configuration; and
 the shifted image in the second field-of-view portion is
 projected when the first set of gratings is in the
 shifted switching configuration and the second set of
 gratings is in the second switching configuration. 30

* * * * *