



US011686144B2

(12) **United States Patent**  
**Snider et al.**

(10) **Patent No.:** **US 11,686,144 B2**  
(45) **Date of Patent:** **Jun. 27, 2023**

(54) **SLIDER WINDOW ASSEMBLY WITH SWITCH DEVICE**

USPC ..... 49/413  
See application file for complete search history.

(71) Applicant: **Magna Mirrors of America, Inc.**,  
Holland, MI (US)

(56) **References Cited**

(72) Inventors: **Darin J. Snider**, Holland, MI (US);  
**David L. Guillozet**, Hamilton, MI (US)

U.S. PATENT DOCUMENTS

(73) Assignee: **Magna Mirrors of America, Inc.**,  
Holland, MI (US)

957,728 A	5/1910	Bliss
1,204,702 A	11/1916	Schupp
2,762,675 A	9/1956	Janows
2,858,408 A	10/1958	Barroero
2,912,714 A	11/1959	Rich
2,962,773 A	12/1960	Heller

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(Continued)

(21) Appl. No.: **17/652,295**

FOREIGN PATENT DOCUMENTS

(22) Filed: **Feb. 24, 2022**

CN	106401363 A	*	2/2017	
CN	109403803 A	*	3/2019	..... E05F 15/635

(65) **Prior Publication Data**

US 2022/0268078 A1 Aug. 25, 2022

*Primary Examiner* — Jerry E Redman

**Related U.S. Application Data**

(60) Provisional application No. 63/200,253, filed on Feb. 24, 2021.

(74) *Attorney, Agent, or Firm* — Honigman LLP

(51) **Int. Cl.**  
**B60J 1/18** (2006.01)  
**E05F 15/643** (2015.01)  
**E05F 15/655** (2015.01)


(57) **ABSTRACT**

A vehicular slider window assembly includes a frame having upper and lower rails. A fixed window has an opening and the rails are attached at the fixed window. A movable window is movable between a closed position and an opened position. A carrier disposed at a lower edge of the movable window moves with the movable window between the opened and closed positions. A sensing system determines when the movable window is in the closed position and includes a switch assembly that is actuated when the movable window is in the closed position. The switch assembly includes a switch device within a housing. A portion of the housing is an end stop configured to limit movement of the carrier when the movable window is in the closed position. The switch device includes a contact and, when the movable window is in the closed position, the contact actuates the switch device.

(52) **U.S. Cl.**  
CPC ..... **E05F 15/643** (2015.01); **B60J 1/1853** (2013.01); **E05F 15/655** (2015.01); **E05Y 2201/11** (2013.01); **E05Y 2201/654** (2013.01); **E05Y 2400/445** (2013.01); **E05Y 2400/822** (2013.01); **E05Y 2900/55** (2013.01)

(58) **Field of Classification Search**  
CPC ..... E05Y 2201/11; E05Y 2400/445; E05Y 2900/55; E05Y 15/643; E05Y 15/655; E05Y 2201/654; E05Y 2400/822; B60J 1/1863; B60J 1/16

**24 Claims, 21 Drawing Sheets**





(56)

References Cited

U.S. PATENT DOCUMENTS

3,177,989 A	4/1965	Di Chiaro	6,026,611 A	2/2000	Ralston et al.
3,237,250 A	3/1966	Scoville	6,086,138 A	7/2000	Xu et al.
3,379,859 A	4/1968	Marriott	6,112,462 A	9/2000	Kolar
3,508,361 A	4/1970	Ryder	6,119,401 A	9/2000	Lin et al.
3,715,707 A	2/1973	Anderson	6,119,402 A	9/2000	Wisner
3,893,260 A	7/1975	Cadiou	6,125,585 A	10/2000	Koneval et al.
3,898,427 A	8/1975	Levin et al.	6,161,894 A	12/2000	Chapman
3,911,245 A	10/1975	O'Shaughnessy	6,223,470 B1	5/2001	Millard et al.
3,964,068 A	6/1976	Torii et al.	6,225,904 B1	5/2001	Jaffe et al.
3,995,142 A	11/1976	Ciardelli et al.	6,293,609 B1	9/2001	Xu et al.
4,023,008 A	5/1977	Durussel	6,324,788 B1	12/2001	Koneval et al.
4,065,848 A	1/1978	Dery	6,328,243 B1	12/2001	Yamamoto
4,081,926 A	4/1978	Jardin	6,490,832 B1	12/2002	Fischbach et al.
4,124,054 A	11/1978	Spretnjak	6,525,659 B2	2/2003	Jaffe et al.
4,137,447 A	1/1979	Boaz	6,591,552 B1	7/2003	Rasmussen
4,158,270 A	6/1979	Cherbourg et al.	6,598,931 B2	7/2003	Tamura
4,171,594 A	10/1979	Colanzi	6,665,983 B1	12/2003	Zimmerman
4,244,774 A	1/1981	Dery	6,691,464 B2	2/2004	Nestell et al.
RE30,663 E	6/1981	Schnitzius	6,742,819 B2	6/2004	So et al.
4,388,522 A	6/1983	Boaz	6,766,617 B2	7/2004	Purcell
4,410,843 A	10/1983	Sauer et al.	6,955,009 B2	10/2005	Rasmussen
4,415,196 A	11/1983	Baum et al.	7,003,916 B2	2/2006	Nestell et al.
4,450,346 A	5/1984	Boaz	7,010,883 B2	3/2006	Jaerpsten et al.
4,458,445 A	7/1984	Sauer et al.	7,073,293 B2	7/2006	Galer
4,519,443 A	5/1985	Sutoh et al.	7,184,190 B2	2/2007	McCabe et al.
4,552,611 A	11/1985	Dery et al.	7,186,118 B2	3/2007	Hansen et al.
4,606,159 A	8/1986	Kunert	7,255,451 B2	8/2007	McCabe et al.
4,611,849 A	9/1986	Frenkler	7,259,359 B2	8/2007	Davey et al.
4,635,398 A	1/1987	Nakamura	7,400,435 B2	7/2008	Byers et al.
4,674,231 A	6/1987	Radek et al.	7,608,949 B2	10/2009	Busch
4,723,809 A	2/1988	Kida et al.	7,626,749 B2	12/2009	Baur et al.
4,738,052 A	4/1988	Koshida	7,871,272 B2	1/2011	Firman, II et al.
4,785,583 A	11/1988	Kawagoe et al.	7,900,863 B1	3/2011	Cheng
4,883,940 A	11/1989	Tokarz	8,042,664 B2	10/2011	Rutkowski et al.
4,920,698 A	5/1990	Friese et al.	8,151,519 B2	4/2012	Bello et al.
4,934,098 A	6/1990	Prouteau et al.	8,402,695 B2 *	3/2013	Smith ..... H01R 35/02 49/413
4,970,911 A	11/1990	Ujihara et al.	8,881,458 B2 *	11/2014	Snider ..... E05C 1/08 49/213
4,995,195 A	2/1991	Olberding et al.	8,915,018 B2	12/2014	Snider
5,046,283 A	9/1991	Compeau et al.	8,938,914 B2	1/2015	Hulst et al.
5,146,712 A	9/1992	Hlavaty	9,579,955 B2	2/2017	Snider
5,228,740 A	7/1993	Saltzman	9,642,187 B2 *	5/2017	Snider ..... H05B 1/0227
5,245,788 A	9/1993	Riegelman	9,688,122 B2 *	6/2017	Gipson ..... H05B 3/84
5,294,168 A	3/1994	Kronbetter	9,731,580 B2 *	8/2017	Snider ..... E05F 15/643
5,308,247 A	5/1994	Dyrdek	10,266,037 B2 *	4/2019	Hulst ..... E05D 15/0621
5,333,411 A	8/1994	Tschirschwitz et al.	10,501,977 B2	12/2019	Snider et al.
5,345,717 A	9/1994	Mori et al.	10,524,313 B2	12/2019	Snider et al.
5,363,596 A	11/1994	Kronbetter	10,843,644 B2	11/2020	Snider et al.
5,367,827 A	11/1994	Tajima et al.	11,013,069 B2 *	5/2021	Lahnala ..... E05F 11/535
5,442,880 A	8/1995	Gipson	11,425,798 B2 *	8/2022	Snider ..... B60J 1/007
5,466,911 A	11/1995	Spagnoli et al.	2003/0074842 A1	4/2003	Eckhardt et al.
5,467,560 A	11/1995	Camp et al.	2003/0140562 A1	7/2003	Staser et al.
5,473,840 A	12/1995	Gillen et al.	2003/0188490 A1	10/2003	Kraus et al.
5,505,023 A	4/1996	Gillen et al.	2003/0213179 A1	11/2003	Galer
5,522,191 A	6/1996	Wenner et al.	2004/0020131 A1	2/2004	Galer et al.
5,525,401 A	6/1996	Hirmer	2004/0065017 A1	4/2004	Priest et al.
5,531,046 A	7/1996	Kollar et al.	2004/0065018 A1	4/2004	Regnier et al.
5,542,214 A	8/1996	Buening	2006/0032140 A1 *	2/2006	Arimoto ..... E05F 15/646 49/413
5,572,376 A	11/1996	Pace	2006/0061008 A1	3/2006	Karner et al.
5,613,323 A	3/1997	Buening	2006/0107600 A1	5/2006	Nestell et al.
5,617,675 A	4/1997	Kobrehel	2006/0130405 A1	6/2006	Hemond et al.
5,711,112 A	1/1998	Barten et al.	2007/0075859 A1	4/2007	Garavuso
5,716,536 A	2/1998	Yokoto et al.	2007/0209283 A1	9/2007	Ostrowski et al.
5,724,769 A	3/1998	Cripe et al.	2007/0277443 A1	12/2007	Dery et al.
5,724,771 A	3/1998	Gipson	2008/0122262 A1	5/2008	Cicala
5,784,833 A	7/1998	Sponable et al.	2008/0127563 A1	6/2008	Tooker
5,799,444 A	9/1998	Freimark et al.	2008/0202032 A1	8/2008	Loidolt
5,799,449 A	9/1998	Lyons et al.	2009/0019778 A1	1/2009	Lahnala
5,822,922 A	10/1998	Grumm et al.	2009/0140858 A1	6/2009	Gore
5,836,110 A	11/1998	Buening	2009/0322705 A1	12/2009	Halsey, IV
5,853,895 A	12/1998	Lewno	2010/0146859 A1	6/2010	Gipson et al.
5,890,321 A	4/1999	Staser et al.	2010/0154312 A1 *	6/2010	Gipson ..... E05D 15/0621 49/413
5,953,887 A	9/1999	Lucas et al.	2010/0182143 A1	7/2010	Lynam
5,996,284 A	12/1999	Freimark et al.	2010/0194550 A1	8/2010	Suzuki
6,014,840 A *	1/2000	Ray ..... H05B 3/84 49/413	2010/0240229 A1 *	9/2010	Firman, II ..... H01R 13/6205 439/39

(56)

**References Cited**

U.S. PATENT DOCUMENTS

2011/0030276 A1\* 2/2011 Smith ..... B60J 1/1853  
49/70  
2012/0091113 A1\* 4/2012 Bennett ..... H05B 3/84  
49/70  
2013/0283693 A1\* 10/2013 Huizen ..... E05F 11/488  
49/123  
2014/0047772 A1 2/2014 Hulst  
2014/0062466 A1\* 3/2014 Thibault ..... G01B 7/14  
324/207.22  
2015/0167372 A1\* 6/2015 Hulst ..... B60J 1/1853  
49/123  
2015/0348385 A1 12/2015 Lamb  
2016/0121699 A1\* 5/2016 Snider ..... E05F 15/60  
49/13  
2019/0383084 A1 12/2019 Snider et al.  
2020/0240191 A1 7/2020 Gustafson  
2020/0355012 A1\* 11/2020 Kojima ..... E05F 15/695  
2022/0268078 A1\* 8/2022 Snider ..... E05F 15/643

\* cited by examiner




FIG. 1






FIG. 2




FIG. 3






FIG. 4




FIG. 5






FIG. 6




FIG. 7






FIG. 8




FIG. 9






FIG. 10




FIG. 11






FIG. 12




FIG. 13






FIG. 14




FIG. 15




FIG. 16






FIG. 17




FIG. 18




FIG. 19






FIG. 20



FIG. 21




FIG. 22



**1****SLIDER WINDOW ASSEMBLY WITH SWITCH DEVICE****CROSS REFERENCE TO RELATED APPLICATION**

The present application claims the filing benefits of U.S. provisional application Ser. No. 63/200,253, filed Feb. 24, 2021, which is hereby incorporated herein by reference in its entirety.

**FIELD OF THE INVENTION**

The present invention relates to a slider window assembly for a vehicle and, more particularly, a rear slider window assembly for a vehicle and, more particularly, a rear slider window assembly for a pickup truck or the like.

**BACKGROUND OF THE INVENTION**

It is known to provide a slider window assembly for an opening of a vehicle, such as a rear slider window assembly for a rear opening of a pickup truck. Conventional slider window assemblies for rear openings of trucks or the like typically include three or more panels, such as two fixed window panels and a slidable window panel. The slidable window panel is supported by rails and may be moved along the rails to open and close the window. The slidable window panel may be driven or moved by a cable drive system, such as described in U.S. Pat. No. 8,151,519, which is hereby incorporated herein by reference in its entirety.

**SUMMARY OF THE INVENTION**

A vehicular rear slider window assembly has a lower channel that slidably receives a movable window panel (and a carrier at the lower region of the movable window panel) therein, with a switch assembly that determines when the movable window panel is in its fully closed position. The carrier of the movable window panel is received in and moved along the lower channel via operation of a powered window drive system, which imparts movement of the carrier and movable window along the lower channel between its opened and closed positions, such as via moving or pulling at a drive cable attached at either end of the carrier, with a sheath of the cable engaged at the ends of the channel. The switch assembly comprises a housing portion that is molded as part of the end stop disposed at the end of the channel, and a switch device that is disposed within the housing and that has a movable contact element that extends along the channel toward an end of the carrier of the movable window panel. The housing and switch device are encased within an elastomeric (e.g., rubber) boot or cover that covers the movable contact element, such that, when the window is closed, the end of the carrier contacts the boot or cover at the movable contact element, which causes movement of the contact element to actuate the switch device to determine that the window is fully closed. When the movable window panel is not in its closed position, the movable contact element is biased towards its non-contacted or moved position or state and thus the switch device determines that the movable window panel is not fully closed.

Responsive to determination that the switch device is actuated, the system may control an indicator to indicate to the driver of the vehicle that the window is opened or closed. For example, the system may activate an indicator (such as a light or light emitting diode (LED) in the cabin of the

**2**

vehicle and viewable by the driver of the vehicle) when the window is at least partially opened (as determined by the contact element of the switch device not being contacted and moved by the carrier), and the system may deactivate the indicator when the switch device determines that the window is fully closed (as determined by the contact element of the switch device being contacted and moved by the carrier).

These and other objects, advantages, purposes and features of the present invention will become apparent upon review of the following specification in conjunction with the drawings.

**BRIEF DESCRIPTION OF THE DRAWINGS**

FIG. 1 is a rear perspective view of a pickup truck having a rear slider window assembly;

FIG. 2 is a perspective view of the rear slider window assembly, as viewed from the forward or interior side of the window assembly when the window assembly is normally mounted to a vehicle;

FIG. 3 is a plan view of the rear slider window assembly of FIG. 2;

FIG. 4 is a perspective view of a movable window panel and lower rail or channel element and drive system of the rear slider window assembly of FIGS. 2 and 3;

FIG. 5 is a perspective view of a switch assembly at an end stop of the lower channel element of the rear slider window assembly;

FIG. 6 is an exploded perspective view of the switch assembly;

FIG. 7 is a perspective view of the switch assembly, with the cover removed to show additional details;

FIG. 8 is a perspective view of the housing and end stop of the switch assembly;

FIG. 9 is a perspective view of the switch device of the switch assembly;

FIGS. 10 and 11 are perspective views of another switch assembly;

FIGS. 12 and 13 are exploded perspective views of the switch assembly;

FIG. 14 is a perspective view of the switch device as disposed in a housing portion of the switch assembly;

FIGS. 15 and 16 are perspective views of the housing portion of FIG. 14;

FIGS. 17 and 18 are perspective views of the base portion of the switch assembly;

FIG. 19 is an exploded view of another switch assembly;

FIG. 20 is a perspective view of the switch assembly of FIG. 19;

FIG. 21 is a perspective view of the switch assembly of FIG. 19 with an electrical connector extending therefrom; and

FIG. 22 is a perspective view of a rear slider window assembly with the switch assembly of FIG. 19.

**DESCRIPTION OF THE PREFERRED EMBODIMENTS**

Referring now to the drawings and the illustrative embodiments depicted therein, a rear slider window assembly 10 of a vehicle 12 (such as a pickup truck or the like) includes a window frame 14, a fixed window panel or panels having an aperture that separates side window panels or portions 16, 18 and a movable window panel 20 that is movable relative to the window frame 14 and the fixed window panel between a closed position, where the movable window panel 20 is disposed at the aperture of the fixed



window panel, and an opened position, where the movable window panel **20** is moved at least partially along the fixed window panel (FIGS. 1-4). The movable window panel **20** is movable along the frame **14** (such as along an upper rail or channel **22** and a lower rail or channel **24** of the frame) relative to the fixed window panel(s) via a drive system **26** that moves the movable panel in either direction to open and close the rear window, such as responsive to a user input or button or switch in the vehicle cabin.

The lower rail **24** comprises an elongated generally U-shaped channel portion disposed generally horizontally along the rear slider window and spanning at least part of each of the fixed window panels **16**, **18**. The lower edge region **20a** (FIG. 4) of the movable window panel **20** is received in or attached to a carrier, which is movably received in, the channel portion of the lower rail **24** and is movable or slidable along the channel portion as the movable window panel **20** is moved between its opened and closed positions via operation of the drive system **26**. The window assembly **10** includes a sensing system **30** for determining the position of the movable window panel, such as determining when the window panel is fully closed. The sensing system **30** comprises a switch assembly **32** disposed at an end of the channel portion of the lower rail **24**, such as at an end cap or cable guide **34**, and a bumper or stop element disposed at the respective end of the carrier. The switch assembly **32** detects the presence of the bumper and carrier to determine when the movable window panel is fully closed, as discussed below. In the illustrated embodiment, the switch device is embedded as a unit at the end stop or cable guide and is integrally formed with the end stop at the end of the channel of the lower rail, as also discussed below.

In the illustrated embodiment, window assembly **10** includes two fixed window panels or panel portions **16**, **18** that are spaced apart so as to define an opening therebetween. The fixed window panels may comprise two separate spaced apart fixed window panels that define the opening therebetween (and with upper and lower appliqués or trim or filler panels or elements disposed at the upper and lower regions of the opening and between the fixed window panels), while remaining within the spirit and scope of the present invention. Optionally, the window assembly may comprise a hole-in-glass window configuration, where a single fixed glass panel has an aperture or hole or opening established therethrough to define separate spaced apart fixed window panels or panel portions, such as in a similar manner as the window assemblies described in U.S. Pat. No. 8,881,458, which is hereby incorporated herein by reference in its entirety.

The slider or movable window panel **20** is movable along the lower rail **24** and the upper rail **22** of the frame portion **14** to open and close the aperture or opening, such as in a manner similar to known slider window assemblies. The slider window panel **20** is disposed at the lower carrier, which may receive the lower perimeter edge region **20a** of the slider window panel **20** therein and is slidably or movably received in the channel portion of the lower rail **24** of the frame portion **14**. The upper rail **22** may comprise any suitable channel or rail element configured to slidably receive an upper edge portion of the movable window panel **20**.

The movable or slider window panel **20** may be movable such as via manual pushing or pulling at the window panel and is movable in response to actuation of a drive motor **26a** of the drive motor assembly or system **26**, which may move cables or wires of cable assemblies **26b** relative to the sheath of the cable assemblies **26b** to impart horizontal movement

of the carrier and slider window panel **20** along the rails **22**, **24**. Although shown as a cable drive system, the carrier and movable window panel may be moved along the rails via any suitable drive system, such as by utilizing aspects of the drive systems described in U.S. Pat. Nos. 10,501,977; 8,938,914; 7,073,293 and/or 6,955,009, and/or U.S. Publication Nos. US-2019-0383084; US-2008-0127563 and/or US-2004-0020131, and/or U.S. patent application Ser. No. 17/305,818, filed Jul. 15, 2021 (Attorney Docket DON02 P4234), which are all hereby incorporated herein by reference in their entirety.

The lower rail includes end caps or cable guides or guide portions disposed at the ends of the channel portion at or near opposite end regions thereof, whereby the cable (or other drive means) of the drive system **26** attaches at or is guided and retained at the guide portions. The end guides may utilize aspects of the end guides described in U.S. Pat. No. 8,938,914, which is hereby incorporated herein by reference in its entirety. Optionally, the drive system **26** may utilize aspects of the drive assemblies of the types described in U.S. Pat. Nos. 4,920,698; 4,995,195; 5,146,712; 5,531,046; 5,572,376; 6,955,009 and/or 7,073,293, and/or U.S. Publication Nos. US-2004-0020131 and/or US-2008-0127563, which are all hereby incorporated herein by reference in their entirety.

Thus, the movable window panel **20** is movable along the upper and lower channels or rails between its opened and closed positions. The switch assembly **32** is part of the sensing system **30** that is operable to determine when the movable window panel **20** is at its fully closed position, so as to provide an indication to the driver of the vehicle equipped with the window assembly **10** to inform the driver that the window is fully closed. For example, when the window panel **20** is open, an indication light (such as a light emitting diode or LED or the like) at the instrument panel of the vehicle (or elsewhere in the vehicle cabin and viewable by the driver) will be activated to notify the driver that the window is opened (optionally, an audible indication device can also or otherwise be installed), and when the window is fully closed, the indicator (visual and/or audible) will be deactivated, thus indicating to the driver that the window is fully closed and latched.

As shown in FIGS. 5-9, the switch assembly **32** comprises the end stop **34** that is configured to be received at the end of the channel portion of the lower rail **24** at the end of the rail that corresponds generally to where the end of the carrier will be when the movable panel **20** is fully closed. The end stop **34** is received in the channel portion and includes a guide portion that guides and/or retains the cable or other drive element thereat. The end stop **34** includes a bumper or stop element **34a** that extends along the channel portion for contacting the carrier of the movable window panel **20** and stopping further movement of the movable window panel **20** when the panel reaches the fully closed position (which also generally coincides with a latch element being engaged to latch the movable window panel in the closed position).

As shown in FIGS. 6 and 7, the switch assembly **32** includes a housing portion **36** that extends upward from the end stop **34**, and that may be integrally formed (such as via the same injection molding process) with the end stop to provide a unitary end stop and housing construction. The housing portion **36** receives a switch device **38** therein, which is received at an opening of the housing **36** and that is pinned or secured at and within the housing **36**, such as via a fastener or pin **40** or the like. An elastomeric cover or boot **42** is disposed over the housing **36** and the switch device **38** to encase the housing **36** and switch device **38**, while



allowing for flexing or deforming of the cover **42** to allow for actuation of the switch device **38**.

The switch device **38** comprises an electronic switch device that has a movable contact element or switching element **39** that is movable relative to a housing portion **38a** and an electronic switch or circuit element **38b**. The contact element **39** is movably mounted at the housing portion **38a** (such as at an end portion **39a** of the contact element **39** that is attached at the housing portion) and includes an actuating portion **39b** that, when the contact element **39** is moved relative to the housing **38a**, presses the circuit element **38b** to actuate the switch (i.e., to close a circuit of the switch). The contact element **39** includes an outer or distal end **39c** that is distal from the end **39a** that attaches at the housing portion **38a**, with the distal end **39c** extending away from the housing portion **38a** along the lower rail **24** and optionally downwardly so as to be disposed partially within the lower rail **24** when the end stop portion **34** is attached at the channel portion of the lower rail **24**.

The contact element **39** may comprise any suitable element, such as a flexible metallic element or the like that flexes when the distal end **39c** is contacted by the carrier of the movable window panel **20** as the movable window panel **20** is moved to the closed position. Optionally, the contact element **39** may comprise a non-flexible element that is pivotally attached at the housing portion. The cover or boot **42** covers the switch device **38** to conceal and protect the switch device **38** and the contact element **39**, while allowing for flexing or moving of the contact element **39** when the movable window panel **20** is closed and presses against the contact element via engagement with the cover **42**.

The distal end **39c** of the contact element extends a predetermined amount beyond the stop element **34a** of the end stop, so that the contact element **39** is contacted and moved to actuate the switch device **38** slightly before the carrier contacts the stop element **34a**, which limits further movement of the movable window panel **20** in that direction. For example, the distal end **39c** of the contact element **39** may extend an amount so that when the portion of the carrier that contacts the cover **42** at the contact element **39** makes initial contact with the cover **42** at the distal end **39c** of the contact element **39**, the other portion of the carrier that contacts the stop element **34a** is spaced from the stop element **34a** by one millimeter or thereabouts (or any sufficient distance that allows for the contact element to sufficiently flex or move to actuate the switch device before the carrier is stopped by the stop element). The degree of extension of the distal end **39c** of the contact element **39** as compared to the stop element **34a** of the end stop **34** is selected based in part on the degree of movement of the contact element **39** that is required to actuate the switch **38** and based in part on the shape of the end of the carrier and relative locations of the portions of the carrier end that contact the cover **42** and the stop element **34a**.

The switch device **38** is electrically connected to a control device of the sensing system **32**, such as a control device disposed in the cabin of the vehicle. The control device determines when the switch device **38** is actuated (i.e., when the movable window panel is fully closed), and may provide an indication to the driver when the panel **20** is closed and/or may provide an indication to the driver when the panel **20** is opened. The switch device **38** may be electrically connected to the control device via electrical wires attached at the switch device **38** that electrically connect to a wire harness of the vehicle when the window assembly **10** is installed at the vehicle, or via electrically conductive traces along the fixed window panel **16**, **18**, which may extend to the

electrical connections of the window assembly for electrically connecting the heater grids of the window assembly and/or the drive system of the window assembly to one or more wire harnesses of the vehicle when the window assembly is installed at the vehicle.

In the illustrated embodiment, the lower rail **24** comprises a unitarily formed (such as via molding or injection molding or the like) rail having a generally U-shaped channel portion that is arranged generally horizontally across the rear slider window assembly **10**. The lower rail **24** may be formed via any suitable forming means and may comprise any suitable material or materials. For example, the lower rail **24** may comprise a rigid or substantially rigid molded polymeric channel (such as a polyvinylchloride material or PC—ABS or the like), and preferably a rigid polymeric material or engineered plastic material. The channel portion is an elongated generally U-shaped channel having a base or lower wall and a pair of spaced apart generally vertical walls extending upwardly from the base or lower wall. The end stop portion **34** of the switch assembly **32** is disposed at the end of the channel portion and extends upward from the base wall and spans between the spaced apart walls of the channel so as to close the end regions of the channel with the cable guide, with the housing portion **36** that houses the switch device **38** disposed above the channel portion.

Thus, the switch assembly **32** is part of the end stop (and integrally formed with the end stop) at the end of the channel portion of the lower rail **24**. The switch device **38** is disposed within a housing portion **36** that is integrally formed with the end stop **34** and has a contact element or switch element **39** that extends from the housing portion **36** and end stop **34** along the lower rail **24** toward the opening and toward the movable window panel **20**. The contact element **39** extends downward so as to be along the lower rail **24** and optionally within the channel portion of the lower rail **24**, with the housing portion **36** and switch device **38** and contact element **39** encased by the elastomeric or flexible cover or boot **42**. The end of the boot **42** at the distal end **39c** of the contact element **39** is contacted by the end of the carrier (such as by a bumper or cushioning element at the end of the carrier) when the movable window panel **20** is fully closed. When the boot **42** (at the contact element) is contacted by the carrier, the boot **42** flexes and the contact element **39** flexes or moves to actuate the switch or circuit element to indicate to the controller that the movable window panel **20** is fully closed.

Optionally, the switch device may have a two piece housing construction with one of the housing portions integrally formed with the end stop and with the switch device attached at one of the housing portions and encased at the housing when the housing portions are joined together (such as via snap attachment). For example, and such as shown in FIGS. **10-18**, a switch assembly **132** includes an end stop **134** that is configured to be received at the end of the channel portion of the lower rail at the end of the rail that corresponds generally to where the end of the carrier will be when the movable panel is fully closed. The end stop **134** is received in the channel portion and includes a guide portion that guides and/or retains the cable or other drive element thereat. The switch assembly **132** includes a housing portion **136** that extends upward from the end stop **134**, and that may be integrally formed (such as via the same injection molding process) with the end stop to provide a unitary end stop and housing portion construction. The housing portion **136** comprises a wall portion of the housing that receives the switch device **138** therein, whereby the switch device is housed or encased via attachment of a cover or second housing portion



**137** at the wall or housing portion **136**. In the illustrated embodiment, the wall housing portion **136** includes slots or apertures **136a**, guide or locating ribs **136b** and a guide hole **136c** (for locating the switch device **138**), while the cover or housing portion **137** includes flexible tabs **137a**, guide or locating ribs **137b** and a guide pin or locating pin **137c** (for locating the switch device **138**).

As shown in FIG. **14**, the switch device **138** is located at the cover portion **137** and positioned via the locating ribs **137b** and the guide pin **137c** (which is received in an aperture or hole **138a** at the switch device **138**). When the switch device **138** is located at the cover portion **137**, the contact element **139** protrudes from the cover portion **137**. The guide or locating elements of the cover portion **137** are formed to correspond with portions of the switch device **138** so that the switch device **138** is properly located at the cover portion **137** and retained thereat.

The cover portion **137** (with the switch device attached thereat) is then snap-attached at the wall housing portion **136** via engagement of the flexible tabs **137a** with the slots or apertures **136a** of the wall housing portion. When so attached, a locating pin **138b** of the switch device **138** is received at the locating hole **136c** of the wall portion **136**. The locating elements **136b**, **136c**, **137b**, **137c** of the wall portion **136** and the cover portion **137** function to hold the switch device in the housing, such that the contact element **139** protrudes through a slot or aperture formed by the housing portions **136**, **137**. The switch assembly **132** provides for enhanced assembly, since the switch device **138** may be readily positioned at the cover element **137** and the cover element **137** (with the switch positioned thereat) may be readily snap-attached at the wall portion **136** to position the switch device above the end stop portion. The switch device **138** may thus be disposed at and encased in the housing without use of fasteners, such as separate pins or screws or the like.

As discussed above, the movable contact element **139** of the switch device **138** is movable relative to the housing portion and an electronic switch or circuit element and includes an actuating portion that, when the contact element **139** is moved relative to the housing, presses the circuit element of the switch device to actuate the switch (i.e., to close a circuit of the switch). The contact element **139** includes an outer or distal end that is distal from the end that attaches at the housing portion of the switch device, with the distal end extending away from the housing along the lower rail and optionally downwardly so as to be disposed partially within the lower rail when the end stop portion **134** is attached at the channel portion of the lower rail.

Optionally, the wall portion of the housing of the switch assembly may include the guide pin and locating ribs for locating the switch within the housing. For example, and such as shown in FIGS. **19-22**, a switch assembly **232** includes an end stop **234** that is configured to be received at the end of the channel portion of the lower rail at the end of the rail that corresponds generally to where the end of the carrier will be when the movable panel is fully closed. The end stop **234** is received in the channel portion and includes a guide portion that guides and/or retains the cable or other drive element thereat. The switch assembly **232** includes a housing portion **236** that extends upward from the end stop **234**, and that may be integrally formed with the end stop (such as via the same injection molding process that forms the end stop) to provide a unitary end stop and housing portion construction. The housing portion **236** comprises a wall portion of the housing that receives the switch device **238** therein, whereby the switch device is housed or encased

via attachment of a cover or second housing portion **237** at the wall or housing portion **236**.

The wall portion **236** includes slots or apertures **236a** configured to receive corresponding flexible tabs **237a** of the cover portion **237**. The wall portion **236** further includes (i) guide or locating ribs **236b** configured to trace or at least partially circumscribe an outer edge of the switch device **238** and (ii) a guide hole **236c** configured to receive a guide pin of the switch device **238**. The wall portion also includes a guide pin **236d** configured to be received by a guide hole **238a** of the switch device **238** for locating the switch device within the housing.

Thus, the switch device **238** may be disposed at the wall portion **236** such that the guide pin **236d** is received at the guide hole **238a** of the switch device, the locating ribs **236b** circumscribe and/or engage the outer edge of the switch device **238**, and the guide hole **236c** receives the guide pin of the switch device **238**, to locate the switch device **238** at the housing. The cover portion **237** may then be snap attached at the wall portion via the flexible tabs **237a** received in the corresponding apertures **236a** to retain the switch device within the housing. The wall portion **236** and cover portion **237** cooperate to form an aperture through which a contact element **239** of the switch device **238** may protrude to sense or engage or receive the carrier element or movable window panel when the movable window panel is in the closed position.

As shown in FIG. **21**, the switch assembly **232** may include an electrical connector assembly **244** for electrically connecting the switch assembly at the vehicle when the window assembly is installed at the vehicle. The connector assembly **244** includes electrical wires or cables **244a** connected at the switch device **238** and a connector **244b** at a distal end of the wires **244a** distal from the switch device **238** for connecting to the vehicle wire harness. Thus, the switch assembly **232** may be electrically powered and communicate signals, such as to indicate that the movable window panel is in the closed position, via the electrical connector assembly **244**.

As shown in FIG. **22**, the movable window panel may comprise a two-piece movable window panel **220**, such that a first side window or window portion **220a** and a second side window or window portion **220b** may be movable relative to one another along respective sides **216**, **218b** of the fixed window panel when the movable window panels are moved between the closed and opened positions. For example, the first side **220a** may be movable along the first side **216** of the fixed window panel and the second side **220b** may be movable along the second side **218** of the fixed window panel. The two sides are configured to move in opposite directions from one another, such that movement of one side may result in corresponding opposite movement of the other side (such as by utilizing aspects of U.S. Pat. No. 10,501,977 and/or U.S. Publication No. US-2020-0240191, which are hereby incorporated herein by reference in their entireties). The sensor system **230** may have the switch assembly disposed at one side (FIG. **22**) for determining when the movable window panels are in the closed position. Optionally, the sensor system may include a switch assembly disposed at each side of the two-piece movable window panel.

In the illustrated embodiment, the fixed window panels each include an electrically conductive heater grid or other heating element or electrically operable element established at the window panels (such as at or on an interior surface of the window panels) and the movable window panel includes an electrically conductive heater grid or other heating ele-



ment or electrically operable element established at the window panel (such as at or on an interior surface of the movable window panel). The fixed window heater grids are electrically conductively connected to (or are otherwise in electrical conductive continuity with) a power source of the vehicle and may be powered (such as responsive to a user actuable input or switch or button of the vehicle or responsive to a sensor or accessory of the vehicle) to heat or defrost or defog the fixed window panels. The movable panel heater grid is electrically connected to the power source (and may be electrically connected to electrical terminals or elements at one of the fixed window heater grids of the fixed window panels) and may be electrically powered to heat or defrost or defog the movable window panel. The heater grids comprise a plurality of electrically conductive traces that extend across the respective window panels between respective busbars to provide enhanced and more uniform heating and defrosting/defogging of the window panel, as also discussed below. The heater grid of the movable window panel may be powered in a manner that allows for heating or defogging or defrosting of the movable window panel irrespective of whether the movable window panel is opened or partially opened or closed. For example, the electrical connections may be made via a flexible connector or wire or cable or the like, such as by utilizing aspects of the rear slider window assemblies described in U.S. Pat. Nos. 10,843,644; 10,524,313; 9,579,955; 8,938,914; 8,881,458 and/or 8,402,695, which are hereby incorporated herein by reference in their entireties. Optionally, the heater grid of the movable window panel may be powered only when in its closed position and/or via any suitable powering means.

The benefits of embodiments of the present invention may also be realized in sliding window constructions where an aperture is created in a fixed window panel and where a movable window panel can be made to open or close the aperture. Slider windows of this type are disclosed such as in U.S. Pat. Nos. 8,915,018 and/or 8,881,458 and/or U.S. Publication No. US-2003-0213179, which are hereby incorporated herein by reference in their entireties. The benefits of embodiments of the present invention may also be realized in vehicular movable window assemblies other than a rear slider window assembly for a pickup truck or the like, such as (for example) a slider window assembly suitable for use as a movable side window for a vehicle such as a van or a bus.

Optionally, the window assembly or assemblies of the present invention may utilize aspects of the window assemblies described in U.S. Pat. Nos. 9,731,580; 8,915,018; 8,881,458; 8,402,695; 7,073,293; 7,003,916; 6,119,401; 6,026,611; 5,996,284; 5,799,444 and/or 6,691,464, and/or U.S. Publication Nos. US-2014-0047772; US-2008-0127563; US-2006-0107600; US-2004-0020131 and/or US-2003-0213179, all of which are hereby incorporated herein by reference in their entireties.

Changes and modifications to the specifically described embodiments may be carried out without departing from the principles of the present invention, which is intended to be limited only by the scope of the appended claims, as interpreted according to the principles of patent law.

The invention claimed is:

1. A vehicular slider window assembly, the vehicular slider window assembly comprising:  
a frame portion having an upper rail and a lower rail;

a fixed window panel, the fixed window panel having an opening, wherein the upper and lower rails are fixedly attached to an interior surface of the fixed window panel;

a movable window panel that is movable along and between the upper rail and the lower rail, wherein the movable window panel is movable between a closed position, where the movable window panel closes the opening, and an opened position, where the movable window panel is located at least partially along the fixed window panel away from the opening;

a carrier disposed at a lower perimeter edge region of the movable window panel, wherein the carrier is received in a channel portion of the lower rail and moves along the channel portion of the lower rail with the movable window panel as the movable window panel is moved between the opened position and the closed position;

a sensing system operable to determine when the movable window panel is in the closed position and when the movable window panel is not in the closed position, wherein the sensing system comprises a switch assembly that is actuated when the movable window panel is in the closed position;

wherein the switch assembly comprises a switch device disposed within a housing, and wherein at least a first portion of the housing is part of an end stop;

wherein the end stop is disposed at an end of the channel portion of the lower rail, and wherein the end stop is configured to limit movement of the carrier along the channel portion when the movable window panel is moved to the closed position;

wherein the switch device comprises a contact element that extends along the channel portion of the lower rail, and wherein, when the movable window panel is moved to the closed position, the contact element moves to actuate the switch device;

wherein, when the movable window panel is not in the closed position, the contact element does not actuate the switch device; and

wherein, responsive to the switch device not being actuated and the sensing system determining that the movable window panel is not in the closed position, the sensing system generates a first output signal to alert a driver of a vehicle equipped with the vehicular slider window assembly that the movable window panel is not in the closed position.

2. The vehicular slider window assembly of claim 1, wherein the sensing system generates a second output signal different than the first output signal responsive to determining that the movable window panel is in the closed position.

3. The vehicular slider window assembly of claim 1, wherein the movable window panel is movable between the opened and closed positions by a cable drive system, and wherein cables of the cable drive system are guided by cable guides at opposite ends of the channel portion of the lower rail, and wherein the end stop of the switch assembly comprises one of the cable guides.

4. The vehicular slider window assembly of claim 1, wherein the end stop is configured to contact the carrier when the movable window panel is moved to the closed position, and wherein, when the movable window panel is moved to the closed position and the first portion contacts the carrier, the contact element is moved by the carrier to actuate the switch device.

5. The vehicular slider window assembly of claim 1, wherein the fixed window panel comprises first and second fixed window panels having the opening therebetween.



## 11

6. The vehicular slider window assembly of claim 1, wherein the fixed window panel comprises a single fixed window panel having the opening therethrough.

7. The vehicular slider window assembly of claim 1, wherein the switch device and associated circuitry are part of a unit, and wherein the unit is disposed in the first portion of the housing that is integrally formed with the end stop at the end of the channel portion of the lower rail.

8. The vehicular slider window assembly of claim 1, wherein the switch assembly comprises an elastomeric cover that is disposed at least partially over the housing and over the contact element, and wherein, when the movable window panel is moved to the closed position, the cover flexes to allow for movement of the contact element to actuate the switch device.

9. The vehicular slider window assembly of claim 1, wherein the first portion is integrally formed with the end stop, and wherein the housing comprises a second portion that is snap-attached to the first portion to encase the switch device in the housing.

10. The vehicular slider window assembly of claim 9, wherein the second portion comprises locating elements that locate the switch device at the second portion prior to snap-attaching the second portion to the first portion.

11. The vehicular slider window assembly of claim 1, wherein the first output signal causes activation of an indicator in a cabin of the vehicle to alert the driver of the vehicle that the movable window panel is not in the closed position, and wherein the indicator in the cabin of the vehicle is viewable by the driver of the vehicle.

12. A vehicular slider window assembly, the vehicular slider window assembly comprising:

- a frame portion having an upper rail and a lower rail;
- a fixed window panel, the fixed window panel having an opening, wherein the upper and lower rails are fixedly attached to an interior surface of the fixed window panel;

- a movable window panel that is movable along and between the upper rail and the lower rail, wherein the movable window panel is movable between a closed position, where the movable window panel closes the opening, and an opened position, where the movable window panel is located at least partially along the fixed window panel away from the opening;

- a carrier disposed at a lower perimeter edge region of the movable window panel, wherein the carrier is received in a channel portion of the lower rail and moves along the channel portion of the lower rail with the movable window panel as the movable window panel is moved between the opened position and the closed position;

- a sensing system operable to determine when the movable window panel is in the closed position and when the movable window panel is not in the closed position, wherein the sensing system comprises a switch assembly that is actuated when the movable window panel is in the closed position;

- wherein the switch assembly comprises a switch device disposed within a housing, and wherein at least a first portion of the housing is part of an end stop;

- wherein the end stop is disposed at an end of the channel portion of the lower rail, and wherein the end stop is configured to limit movement of the carrier along the channel portion when the movable window panel is moved to the closed position;

- wherein the movable window panel is movable between the opened and closed positions by a cable drive system, and wherein cables of the cable drive system

## 12

are guided by cable guides at opposite ends of the channel portion of the lower rail, and wherein the end stop of the switch assembly comprises one of the cable guides;

wherein the switch device comprises a contact element that extends along the channel portion of the lower rail, and wherein, when the movable window panel is moved to the closed position, the contact element moves to actuate the switch device;

wherein, when the movable window panel is not in the closed position, the contact element does not actuate the switch device;

wherein the end stop is configured to contact the carrier when the movable window panel is moved to the closed position, and wherein, when the movable window panel is moved to the closed position and the first portion contacts the carrier, the contact element is moved by the carrier to actuate the switch device; and

wherein, responsive to the switch device not being actuated and the sensing system determining that the movable window panel is not in the closed position, the sensing system generates a first output signal to alert a driver of a vehicle equipped with the vehicular slider window assembly that the movable window panel is not in the closed position.

13. The vehicular slider window assembly of claim 12, wherein the fixed window panel comprises first and second fixed window panels having the opening therebetween.

14. The vehicular slider window assembly of claim 12, wherein the fixed window panel comprises a single fixed window panel having the opening therethrough.

15. The vehicular slider window assembly of claim 12, wherein the switch device and associated circuitry are part of a unit, and wherein the unit is disposed in the first portion of the housing that is integrally formed with the end stop at the end of the channel portion of the lower rail.

16. The vehicular slider window assembly of claim 12, wherein the switch assembly comprises an elastomeric cover that is disposed at least partially over the housing and over the contact element, and wherein, when the movable window panel is moved to the closed position, the cover flexes to allow for movement of the contact element to actuate the switch device.

17. The vehicular slider window assembly of claim 12, wherein the first portion is integrally formed with the end stop, and wherein the housing comprises a second portion that is snap-attached to the first portion to encase the switch device in the housing.

18. A vehicular slider window assembly, the vehicular slider window assembly comprising:

- a frame portion having an upper rail and a lower rail;
- a fixed window panel, the fixed window panel having an opening, wherein the upper and lower rails are fixedly attached to an interior surface of the fixed window panel;

- a movable window panel that is movable along and between the upper rail and the lower rail, wherein the movable window panel is movable between a closed position, where the movable window panel closes the opening, and an opened position, where the movable window panel is located at least partially along the fixed window panel away from the opening;

- a carrier disposed at a lower perimeter edge region of the movable window panel, wherein the carrier is received in a channel portion of the lower rail and moves along the channel portion of the lower rail with the movable



## 13

window panel as the movable window panel is moved  
 between the opened position and the closed position;  
 a sensing system operable to determine when the movable  
 window panel is in the closed position and when the  
 movable window panel is not in the closed position,  
 wherein the sensing system comprises a switch assembly  
 that is actuated when the movable window panel is  
 in the closed position;  
 wherein the switch assembly comprises a switch device  
 disposed within a housing, and wherein at least a first  
 portion of the housing is part of an end stop;  
 wherein the end stop is disposed at an end of the channel  
 portion of the lower rail, and wherein the end stop is  
 configured to limit movement of the carrier along the  
 channel portion when the movable window panel is  
 moved to the closed position;  
 wherein the switch device comprises a contact element  
 that extends along the channel portion of the lower rail,  
 and wherein, when the movable window panel is  
 moved to the closed position, the contact element  
 moves to actuate the switch device;  
 wherein, when the movable window panel is not in the  
 closed position, the contact element does not actuate  
 the switch device;  
 wherein the switch device and associated circuitry are part  
 of a unit, and wherein the unit is disposed in the first  
 portion of the housing that is integrally formed with the  
 end stop at the end of the channel portion of the lower  
 rail;  
 wherein the first portion is integrally formed with the end  
 stop, and wherein the housing comprises a second  
 portion that is snap-attached to the first portion to  
 encase the switch device in the housing; and  
 wherein, responsive to the switch device not being actu-  
 ated and the sensing system determining that the mov-  
 able window panel is not in the closed position, the

## 14

sensing system generates a first output signal to alert a  
 driver of a vehicle equipped with the vehicular slider  
 window assembly that the movable window panel is  
 not in the closed position.

**19.** The vehicular slider window assembly of claim **18**,  
 wherein the movable window panel is movable between the  
 opened and closed positions by a cable drive system, and  
 wherein cables of the cable drive system are guided by cable  
 guides at opposite ends of the channel portion of the lower  
 rail, and wherein the end stop of the switch assembly  
 comprises one of the cable guides.

**20.** The vehicular slider window assembly of claim **18**,  
 wherein the end stop is configured to contact the carrier  
 when the movable window panel is moved to the closed  
 position, and wherein, when the movable window panel is  
 moved to the closed position and the first portion contacts  
 the carrier, the contact element is moved by the carrier to  
 actuate the switch device.

**21.** The vehicular slider window assembly of claim **18**,  
 wherein the fixed window panel comprises first and second  
 fixed window panels having the opening therebetween.

**22.** The vehicular slider window assembly of claim **18**,  
 wherein the fixed window panel comprises a single fixed  
 window panel having the opening therethrough.

**23.** The vehicular slider window assembly of claim **18**,  
 wherein the switch assembly comprises an elastomeric cover  
 that is disposed at least partially over the housing and over  
 the contact element, and wherein, when the movable win-  
 dow panel is moved to the closed position, the cover flexes  
 to allow for movement of the contact element to actuate the  
 switch device.

**24.** The vehicular slider window assembly of claim **18**,  
 wherein the second portion comprises locating elements that  
 locate the switch device at the second portion prior to  
 snap-attaching the second portion to the first portion.

\* \* \* \* \*