

US011703062B2

(12) **United States Patent**  
**Avedon**

(10) **Patent No.:** **US 11,703,062 B2**  
(45) **Date of Patent:** **Jul. 18, 2023**

(54) **TEMPERATURE DESTRATIFICATION SYSTEMS**

(71) Applicant: **AIRIUS IP HOLDINGS, LLC**,  
Longmont, CO (US)

(72) Inventor: **Raymond B. Avedon**, Boulder, CO  
(US)

(73) Assignee: **Airius IP Holdings, LLC**, Longmont,  
CO (US)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **17/807,500**

(22) Filed: **Jun. 17, 2022**

(65) **Prior Publication Data**  
US 2023/0055245 A1 Feb. 23, 2023

**Related U.S. Application Data**

(63) Continuation of application No. 17/303,592, filed on  
Jun. 2, 2021, now Pat. No. 11,365,743, which is a  
(Continued)

(51) **Int. Cl.**  
**F04D 25/08** (2006.01)  
**F04D 29/54** (2006.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **F04D 25/088** (2013.01); **B23P 19/00**  
(2013.01); **F04D 13/0613** (2013.01);  
(Continued)

(58) **Field of Classification Search**  
CPC ..... F21V 33/0096; F04D 13/0613; F04D  
19/002; F04D 25/12; F04D 25/088;  
(Continued)

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

651,637 A 6/1900 Nicol  
D33,522 S 11/1900 Brinkerhoff  
(Continued)

**FOREIGN PATENT DOCUMENTS**

AU 2013203632 11/2016  
CN 1426729 7/2003  
(Continued)

**OTHER PUBLICATIONS**

“Airius Model R20 EC ‘Eyeball’ Data Sheet”, [http://airius.com.au/products/new-retail-series-2/attachment/na\\_std\\_retailseries/](http://airius.com.au/products/new-retail-series-2/attachment/na_std_retailseries/) published Jun. 15, 2016 as printed May 23, 2017 in 1 page.


(Continued)

*Primary Examiner* — Igor Kershteyn  
(74) *Attorney, Agent, or Firm* — Knobbe, Martens, Olson & Bear, LLP

(57) **ABSTRACT**

A temperature destratification assembly can include an outer housing. An impeller can be positioned within the outer housing between the inlet and outlet of the outer housing. The impeller can have an impeller hub and a plurality of impeller blades extending radially outward from the impeller hub. The assembly can include an impeller motor configured to rotate the impeller blades about an axis of rotation. A stator can be positioned within the outer housing between the impeller and the outlet of the outer housing. The stator can include a plurality of vanes. The stator vanes can include an upstream edge at the upstream end of the stator, a first surface extending from the upstream edge to the downstream edge of the vane, and a second surface opposite the first surface and extending from the upstream edge to the downstream edge of vane. A plurality of the vanes can have a downstream edge at the outlet of the outer housing.

**15 Claims, 15 Drawing Sheets**



**Related U.S. Application Data**

continuation of application No. 16/662,957, filed on Oct. 24, 2019, now Pat. No. 11,053,948, which is a continuation of application No. 15/648,261, filed on Jul. 12, 2017, now Pat. No. 10,487,840, which is a continuation of application No. 15/480,285, filed on Apr. 5, 2017, now Pat. No. 9,714,663, which is a continuation of application No. 15/061,951, filed on Mar. 4, 2016, now Pat. No. 9,631,627, which is a continuation of application No. 13/365,223, filed on Feb. 2, 2012, now abandoned, which is a continuation-in-part of application No. 12/130,909, filed on May 30, 2008, now abandoned, which is a continuation of application No. 11/027,039, filed on Dec. 30, 2004, now Pat. No. 7,381,129.

(60) Provisional application No. 61/521,270, filed on Aug. 8, 2011, provisional application No. 60/553,720, filed on Mar. 15, 2004.

(51) **Int. Cl.**

- F04D 29/60* (2006.01)
- F24F 7/007* (2006.01)
- F04D 25/12* (2006.01)
- B23P 19/00* (2006.01)
- F04D 13/06* (2006.01)
- F04D 29/52* (2006.01)
- F21V 33/00* (2006.01)
- F04D 19/00* (2006.01)
- F04D 29/32* (2006.01)
- F04D 29/42* (2006.01)

(52) **U.S. Cl.**

CPC ..... *F04D 19/002* (2013.01); *F04D 25/12* (2013.01); *F04D 29/325* (2013.01); *F04D 29/329* (2013.01); *F04D 29/522* (2013.01); *F04D 29/542* (2013.01); *F04D 29/547* (2013.01); *F04D 29/601* (2013.01); *F21V 33/0096* (2013.01); *F24F 7/007* (2013.01); *F04D 29/4226* (2013.01); *F24F 2221/02* (2013.01); *F24F 2221/14* (2013.01)

(58) **Field of Classification Search**

CPC .. *F04D 29/325*; *F04D 29/4226*; *F04D 29/547*; *F04D 29/542*; *F04D 29/601*; *F04D 29/329*; *F04D 29/522*; *F24F 2221/02*; *F24F 2221/14*

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- 818,604 A 4/1906 Biedr
- 866,292 A 9/1907 Meston
- 917,206 A 4/1909 Watts
- 1,858,067 A 5/1932 Warren
- 1,877,347 A 9/1932 McCurdie
- 1,926,795 A 9/1933 Sassenberg
- 2,016,778 A 10/1935 Hall et al.
- 2,142,307 A 1/1939 De Mey et al.
- 2,144,035 A 1/1939 Smith, Jr.
- 2,154,313 A 4/1939 McMahan
- 2,189,008 A 2/1940 Kurth
- 2,189,502 A 2/1940 Johnston
- 2,232,573 A 2/1941 Teves
- 2,258,731 A 10/1941 Blumenthal
- D133,120 S 7/1942 Spear
- 2,300,574 A 11/1942 Jepertinger
- 2,359,021 A 9/1944 Campbell et al.
- 2,366,773 A 1/1945 Eklund et al.

- 2,371,821 A 3/1945 Havis
- D152,397 S 1/1949 Damond
- 2,513,463 A 7/1950 Eklund et al.
- 2,524,974 A 10/1950 Hickmott
- 2,615,620 A 10/1952 Goettl
- 2,632,375 A 3/1953 Stair et al.
- 2,658,719 A 11/1953 Johanson
- D174,230 S 3/1955 Lewis, II
- 2,710,337 A 6/1955 Moore, Jr.
- 2,814,433 A 11/1957 Brinen
- 2,830,523 A 4/1958 Vehige
- D187,699 S 4/1960 van Rijn
- 2,982,198 A 5/1961 Mohrman
- 3,012,494 A 12/1961 Drummond
- 3,036,509 A 5/1962 Babbitt
- 3,040,993 A 6/1962 Schultz
- 3,068,341 A 12/1962 Ortiz et al.
- 3,072,321 A 1/1963 King, Jr.
- D195,287 S 5/1963 Downing
- 3,099,949 A 8/1963 Davidson
- 3,165,294 A 1/1965 Anderson
- 3,188,007 A 6/1965 Myklebust
- 3,212,425 A 10/1965 Lindner et al.
- 3,246,699 A 4/1966 Jocz
- 3,300,123 A 1/1967 Freyholdt et al.
- 3,306,179 A 2/1967 Lambie et al.
- 3,320,869 A 5/1967 Schach
- 3,364,839 A 1/1968 Sweeney et al.
- 3,382,791 A 5/1968 Henry-Biabaud
- 3,386,368 A 6/1968 Fielding
- 3,413,905 A 12/1968 Johnson
- 3,524,399 A 8/1970 Bohanon
- 3,584,968 A 6/1971 Keith
- 3,601,184 A 8/1971 Hauville
- 3,690,244 A 9/1972 Kallel et al.
- 3,699,872 A 10/1972 Kruger
- 3,765,317 A 10/1973 Lowe
- 3,785,271 A 1/1974 Joy
- 3,827,342 A 8/1974 Hughes
- D232,831 S 9/1974 Vidmar, Jr.
- 3,835,759 A 9/1974 LLoyd
- D234,847 S 4/1975 Hoffman
- 3,876,331 A 4/1975 DenHerder et al.
- 3,927,300 A 12/1975 Wada et al.
- 3,932,054 A 1/1976 McKelvey
- 3,934,494 A 1/1976 Butler
- 3,967,927 A 7/1976 Patterson
- 3,973,479 A 8/1976 Whiteley
- 3,988,973 A 11/1976 Honmann
- 4,006,673 A 2/1977 Meyer et al.
- D246,467 S 11/1977 Kurata
- 4,064,427 A 12/1977 Hansen et al.
- 4,123,197 A 10/1978 Keem et al.
- D251,851 S 5/1979 Palm
- 4,152,973 A 5/1979 Peterson
- 4,162,779 A 7/1979 Van Steenhoven et al.
- 4,185,545 A 1/1980 Rusth et al.
- D255,488 S 6/1980 Kanarek
- 4,210,833 A 7/1980 Neveux
- D256,273 S 8/1980 Townsend et al.
- 4,234,916 A 11/1980 Goralnik
- D258,010 S 1/1981 Bowls et al.
- D258,526 S 3/1981 Nederman
- 4,261,255 A 4/1981 Anderson et al.
- 4,321,659 A 3/1982 Wheeler
- 4,344,112 A 8/1982 Brown
- D269,638 S 7/1983 Frye, Jr. et al.
- 4,391,570 A 7/1983 Stutzman
- 4,396,352 A 8/1983 Pearce
- D272,184 S 1/1984 Karpowicz
- D273,793 S 5/1984 Nachatelo
- D274,772 S 7/1984 Obland
- 4,473,000 A 9/1984 Perkins
- 4,512,242 A 4/1985 Bohanon, Sr.
- 4,515,538 A 5/1985 Shih
- 4,522,255 A 6/1985 Baker
- 4,524,679 A 6/1985 Lyons
- 4,546,420 A 10/1985 Wheeler et al.
- 4,548,548 A 10/1985 Gray, III

(56)

References Cited

U.S. PATENT DOCUMENTS

4,550,649 A	11/1985	Zambolin	D386,267 S	11/1997	Tickner
D283,054 S	3/1986	Altman	5,709,458 A	1/1998	Metz
4,630,182 A	12/1986	Moroi et al.	5,725,190 A	3/1998	Cuthbertson et al.
4,657,483 A	4/1987	Bede	5,725,356 A	3/1998	Carter
4,657,485 A	4/1987	Hartwig	5,782,438 A	7/1998	Hubben et al.
4,662,912 A	5/1987	Perkins	5,791,985 A	8/1998	Schiedegger et al.
4,678,410 A	7/1987	Kullen	5,822,186 A	10/1998	Bull
4,681,024 A	7/1987	Ivey	D404,617 S	1/1999	Mick et al.
D291,488 S	8/1987	Delmas	D407,696 S	4/1999	Shimazu
4,692,091 A	9/1987	Ritenour	5,918,972 A	7/1999	Van Belle
D293,029 S	12/1987	Shwisha	5,934,783 A	8/1999	Yoshikawa
4,714,230 A	12/1987	Huang	5,938,527 A	8/1999	Oshima et al.
4,715,784 A	12/1987	Mosiewicz	D414,550 S	9/1999	Bloom
4,716,818 A	1/1988	Brown	5,947,816 A	9/1999	Schiedegger et al.
4,730,551 A	3/1988	Peludat	5,967,891 A	10/1999	Riley et al.
4,750,863 A	6/1988	Scoggins	5,975,853 A	11/1999	Lackey
4,790,863 A	12/1988	Nobiraki et al.	5,984,252 A	11/1999	Bograng et al.
4,794,851 A	1/1989	Kurrle	5,997,253 A	12/1999	Fechan
4,796,343 A	1/1989	Wing	6,004,097 A	12/1999	Wark et al.
4,848,669 A	7/1989	George	6,068,385 A	5/2000	Hsieh
4,850,265 A	7/1989	Raisanen	D427,673 S	7/2000	Stout, Jr.
4,890,547 A	1/1990	Wagner et al.	6,095,671 A	8/2000	Hutain
4,895,065 A	1/1990	Lamparter	6,109,874 A	8/2000	Steiner
D308,416 S	6/1990	Brumbach	6,145,798 A	11/2000	Janisse et al.
4,930,987 A	6/1990	Stahl	6,149,513 A	11/2000	Lyu
4,971,143 A	11/1990	Hogan	6,155,782 A	12/2000	Hsu
4,973,016 A	11/1990	Hertenstein	6,168,517 B1	1/2001	Cook
D312,875 S	12/1990	Spock	6,176,680 B1	1/2001	Ringblom et al.
D314,619 S	2/1991	Beavers et al.	6,183,203 B1	2/2001	Grintz
5,000,081 A	3/1991	Gilmer	6,192,702 B1	2/2001	Shimogori
5,021,932 A	6/1991	Ivey	6,193,384 B1	2/2001	Stein
5,033,711 A	7/1991	Gregorich et al.	6,196,915 B1	3/2001	Schiedegger et al.
5,042,366 A	8/1991	Panetski et al.	D443,053 S	5/2001	Schaefer
5,060,901 A	10/1991	Lathrop et al.	6,319,304 B1	11/2001	Moredock
5,078,574 A	1/1992	Olsen	D453,960 S	2/2002	Shelby et al.
5,094,676 A	3/1992	Karbacher	6,352,473 B1	3/2002	Clark
D325,628 S	4/1992	Cho	6,357,714 B1	3/2002	Johnson
5,107,755 A	4/1992	Leban et al.	6,360,816 B1	3/2002	Wagner
5,121,675 A	6/1992	Muller et al.	6,361,428 B1	3/2002	Tosconi et al.
5,127,876 A	7/1992	Howe et al.	6,361,431 B1	3/2002	Kawano
D328,405 S	8/1992	Heiligenstein et al.	6,364,760 B1	4/2002	Rooney
5,152,606 A	10/1992	Borraccia et al.	D457,142 S	5/2002	Chang
5,156,568 A	10/1992	Ricci	D457,452 S	5/2002	Christiansen
5,191,618 A	3/1993	Hisey	D457,613 S	5/2002	Schaefer
D335,532 S	5/1993	Lopez	6,382,911 B1	5/2002	Beltowski
D337,157 S	7/1993	Ortiz	6,383,072 B2	5/2002	Schiedegger et al.
D340,765 S	10/1993	Joss et al.	6,384,494 B1	5/2002	Avidano et al.
5,251,461 A	10/1993	Fallows, III et al.	6,386,828 B1	5/2002	Davis et al.
D347,467 S	5/1994	Medvick	6,386,970 B1	5/2002	Vernier, II et al.
5,328,152 A	7/1994	Castle	6,386,972 B1	5/2002	Schiedegger et al.
5,358,443 A	10/1994	Mitchell et al.	6,435,964 B1	8/2002	Chang
5,399,119 A	3/1995	Birk et al.	6,451,080 B1	9/2002	Rocklitz et al.
5,423,660 A	6/1995	Sortor	6,458,028 B2	10/2002	Snyder
5,429,481 A	7/1995	Liu	6,458,628 B1	10/2002	Distefano et al.
5,439,349 A	8/1995	Kupferberg	6,484,524 B1	11/2002	Ulanov
5,439,352 A	8/1995	Line	D470,066 S	2/2003	Christiansen
5,443,625 A	8/1995	Schaffhausen	D470,731 S	2/2003	Hipgrave et al.
5,458,505 A	10/1995	Prager	6,551,185 B1	4/2003	Miyake et al.
5,462,484 A	10/1995	Jung et al.	6,575,011 B1	6/2003	Busby
5,466,120 A	11/1995	Takeuchi et al.	6,581,974 B1	6/2003	Ragner et al.
5,484,076 A	1/1996	Petrushka	6,582,291 B2	6/2003	Clark
5,511,942 A	4/1996	Meier	6,592,328 B1	7/2003	Cahill
5,513,953 A *	5/1996	Hansen ..... F24F 7/10 415/213.1	6,595,747 B2	7/2003	Bos
5,520,515 A	5/1996	Bailey et al.	D480,132 S	9/2003	Stout, Jr.
5,545,241 A	8/1996	Vanderauwera et al.	6,626,003 B1	9/2003	Kortüm et al.
5,547,343 A	8/1996	Jané et al.	6,626,636 B2	9/2003	Bohn
5,551,841 A	9/1996	Kamada	D481,101 S	10/2003	Boehrs et al.
5,561,952 A	10/1996	Damron	D481,127 S	10/2003	Hayamizu
5,569,019 A	10/1996	Katariya et al.	D481,159 S	10/2003	Walker
5,584,656 A	12/1996	Rose	6,648,752 B2	11/2003	Vernier, II et al.
5,595,068 A	1/1997	Amr	6,679,433 B2	1/2004	Gordon et al.
5,613,833 A	3/1997	Wolfe et al.	6,682,308 B1	1/2004	Fei et al.
5,658,196 A	8/1997	Swaim	6,700,266 B2	3/2004	Winkel et al.
5,664,872 A	9/1997	Spearman et al.	D489,967 S	5/2004	Funk
			6,761,531 B2	7/2004	Toye
			6,767,281 B2	7/2004	McKee
			6,783,578 B2	8/2004	Tillman, Jr.
			6,804,627 B1	10/2004	Marokhovsky et al.
			6,805,627 B2	10/2004	Marts et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,812,849 B1	11/2004	Ancel		D621,985 S	8/2010	Sanoner	
D500,773 S	1/2005	Colson et al.		D622,895 S	8/2010	Lyons	
D505,627 S	5/2005	Py et al.		7,774,999 B2	8/2010	McKee	
6,886,270 B2	5/2005	Gilmer		7,780,510 B2	8/2010	Polston	
6,916,240 B1	7/2005	Morton		7,785,064 B2	8/2010	Bartholmey et al.	
6,938,631 B2	9/2005	Gridley		D625,855 S	10/2010	Franklin	
6,941,698 B2	9/2005	Telles		D625,856 S	10/2010	Franklin	
6,951,081 B2	10/2005	Bonshor		7,849,644 B2	12/2010	Melesky	
6,966,830 B2	11/2005	Hurlstone et al.		D630,337 S	1/2011	Chia et al.	
6,974,381 B1	12/2005	Walker et al.		D630,536 S	1/2011	Pettit	
D514,688 S	2/2006	Avedon		D631,142 S	1/2011	Angell	
7,011,500 B2	3/2006	Matson		D631,148 S	1/2011	Benton et al.	
7,011,578 B1	3/2006	Core		D631,579 S	1/2011	Franklin	
7,044,849 B2	5/2006	Dippel		D631,580 S	1/2011	Franklin	
7,048,499 B2	5/2006	Mathson et al.		D631,581 S	1/2011	Franklin	
7,056,092 B2	6/2006	Stahl		7,901,278 B2	3/2011	O'Hagin	
7,056,368 B2	6/2006	Moredock et al.		7,930,858 B2	4/2011	Lajewski	
D525,725 S	7/2006	Foo		7,942,627 B2 *	5/2011	Jin	F04D 29/542 415/209.1
7,101,064 B2	9/2006	Ancel		D645,550 S	9/2011	Ferroni	
D532,229 S	11/2006	Hoernig et al.		D645,561 S	9/2011	Herrmann et al.	
7,152,425 B2	12/2006	Han et al.		D645,593 S	9/2011	Janssen	
7,166,023 B2	1/2007	Haigh et al.		8,052,386 B1	11/2011	Fitzpatrick et al.	
7,175,309 B2	2/2007	Craw et al.		D651,709 S	1/2012	Zeyfang	
7,185,504 B2	3/2007	Kasai et al.		D651,919 S	1/2012	Lai et al.	
7,201,110 B1	4/2007	Pawlak		D651,920 S	1/2012	Lai et al.	
7,201,650 B2	4/2007	Demerath et al.		D661,902 S	6/2012	Italiano	
7,214,035 B2	5/2007	Bussieres et al.		8,215,789 B2	7/2012	Howard	
7,246,997 B2	7/2007	Liu et al.		8,282,138 B2	10/2012	Steiner	
D552,485 S	10/2007	Grabiner et al.		8,297,945 B2	10/2012	Spaggiari	
7,287,738 B2	10/2007	Pitlor		D672,863 S	12/2012	Romero Carreras	
7,288,023 B2	10/2007	Leopold		D676,877 S	2/2013	Drenth et al.	
D557,791 S	12/2007	Cox		1,053,025 A1	2/2013	Goodwin	
7,311,492 B2	12/2007	Östberg		8,366,387 B2	2/2013	Reuter	
7,320,636 B2	1/2008	Seliger et al.		D678,791 S	3/2013	Ford	
7,331,764 B1	2/2008	Reynolds et al.		D681,184 S	4/2013	Romero Carreras	
D564,120 S	3/2008	Layne et al.		D684,307 S	6/2013	Teller	
D567,930 S	4/2008	Smith		8,459,846 B2	6/2013	Tsao	
D567,961 S	4/2008	Yajima		8,487,517 B2	7/2013	Fang et al.	
7,374,408 B2	5/2008	Savage et al.		8,529,324 B2	9/2013	Moredock et al.	
D570,981 S	6/2008	McClelland		8,535,128 B2	9/2013	Chwala	
7,381,129 B2 *	6/2008	Avedon	F04D 29/542 416/247 R	8,596,596 B2	12/2013	Naji et al.	
D578,390 S	10/2008	Green		8,616,842 B2	12/2013	Avedon	
D582,502 S	12/2008	Brittingham		D698,916 S	2/2014	Avedon	
D583,451 S	12/2008	Aloe et al.		8,641,375 B2	2/2014	Tian et al.	
D583,452 S	12/2008	Aloe et al.		D702,887 S	4/2014	Peiruccelli	
7,467,931 B2	12/2008	O'Toole		D703,302 S	4/2014	Ruck	
D584,786 S	1/2009	Brittingham		D703,579 S	4/2014	Kuster et al.	
7,473,074 B2	1/2009	Herbst et al.		D709,643 S	7/2014	Kohler et al.	
7,476,079 B2	1/2009	Bartlett		D710,485 S	8/2014	Nudo	
7,484,863 B1	2/2009	Aubrey		D710,490 S	8/2014	Shurtleff	
7,497,773 B1	3/2009	Schmidt		D711,843 S	8/2014	Yamazaki et al.	
D591,382 S	4/2009	Brittingham		D714,996 S	10/2014	Trotter et al.	
7,516,578 B2	4/2009	Bonshor		D715,904 S	10/2014	Tate et al.	
7,544,124 B2	6/2009	Polston		8,894,354 B2	11/2014	Hodgson et al.	
7,549,258 B2	6/2009	Lajewski		8,899,930 B2	12/2014	Innocenti et al.	
7,566,034 B2	7/2009	Bonshor		D721,645 S	1/2015	Brown	
D599,471 S	9/2009	Borovicka et al.		8,931,936 B1	1/2015	Tham et al.	
D600,396 S	9/2009	Luinstra		D722,486 S	2/2015	Wang	
7,607,935 B2	10/2009	Dahl		D724,199 S	3/2015	Bambot et al.	
D604,880 S	11/2009	Lovegrove		D725,053 S	3/2015	Kaneko et al.	
7,610,717 B2	11/2009	Lüken et al.		D725,055 S	3/2015	Yamazaki et al.	
7,610,726 B2	11/2009	Lajewski		8,967,983 B2	3/2015	Kampf	
D605,332 S	12/2009	Miranda		8,992,174 B2	3/2015	Chang	
7,645,188 B1	1/2010	Peerbolt		D730,185 S	5/2015	Blanco et al.	
7,651,390 B1	1/2010	Profeta et al.		9,028,085 B2	5/2015	Todd, Jr.	
D612,925 S	3/2010	Kameyama et al.		9,028,211 B2	5/2015	Todd, Jr.	
7,677,770 B2	3/2010	Mazzochette		D731,030 S	6/2015	Tyler	
7,677,964 B1	3/2010	Bucher et al.		D733,555 S	7/2015	Brady et al.	
7,708,625 B2	5/2010	Leseman et al.		D739,223 S	9/2015	Paik et al.	
7,717,674 B2	5/2010	Tsuji et al.		D739,515 S	9/2015	Johnson et al.	
D617,890 S	6/2010	Thomas		D739,832 S	9/2015	Yamazaki et al.	
D620,096 S	7/2010	Underwood		D740,973 S	10/2015	Gonzalez	
7,748,954 B2	7/2010	Eguchi et al.		9,151,295 B2	10/2015	Avedon	
7,752,814 B2	7/2010	Bonshor		D742,508 S	11/2015	Row et al.	
				D742,563 S	11/2015	Kasha	
				D743,521 S	11/2015	Jackson	
				D746,416 S	12/2015	Barlar	
				D746,971 S	1/2016	Avedon	

(56)

References Cited

U.S. PATENT DOCUMENTS

D747,453 S	1/2016	Stewart et al.	10,641,506 B2	5/2020	Avedon
D752,339 S	3/2016	Hoover	10,655,841 B2	5/2020	Avedon
D753,817 S	4/2016	Maguire et al.	D886,275 S	6/2020	Avedon
D753,818 S	4/2016	Maguire et al.	D887,541 S	6/2020	Avedon
D754,312 S	4/2016	Ellis	10,724,542 B2	7/2020	Avedon
D755,438 S	5/2016	Kimmet	D895,784 S	9/2020	Wang
D756,494 S	5/2016	Gledhill et al.	11,053,948 B2	7/2021	Avedon
D756,498 S	5/2016	Norman et al.	D926,963 S	8/2021	Avedon
9,335,061 B2	5/2016	Avedon	11,092,330 B2	8/2021	Avedon
D758,642 S	6/2016	Eguchi	11,105,341 B2	8/2021	Avedon
D760,384 S	6/2016	Niunoya et al.	11,221,153 B2	1/2022	Avedon
D761,419 S	7/2016	Fitzgerald et al.	11,236,766 B2	2/2022	Avedon
D766,098 S	9/2016	Seo	D953,517 S	5/2022	Belozerova et al.
D766,100 S	9/2016	Jung	11,365,743 B2	6/2022	Avedon
D768,844 S	10/2016	Koseoglu	11,421,710 B2	8/2022	Avedon
9,459,020 B2	10/2016	Avedon	2001/0049927 A1	12/2001	Toepel
D772,531 S	11/2016	Troia	2002/0045420 A1	4/2002	Taillon
D774,689 S	12/2016	Terumichi	2002/0131865 A1	9/2002	Larzelere et al.
D775,719 S	1/2017	Smith et al.	2002/0137454 A1	9/2002	Baker
D777,311 S	1/2017	Chen	2003/0026691 A1*	2/2003	Huang ..... F04D 29/703
D783,795 S	4/2017	Avedon			415/121.2
9,631,627 B2	4/2017	Avedon	2003/0092373 A1	5/2003	Kuo
D788,886 S	6/2017	Salzer	2003/0213883 A1	11/2003	Fu-Liang
D788,953 S	6/2017	Khan	2004/0004173 A1	1/2004	Johnson
9,696,026 B1	7/2017	Hardgrave	2004/0050077 A1	3/2004	Kasai et al.
9,702,576 B2	7/2017	Avedon	2004/0052641 A1	3/2004	Chen
9,714,663 B1	7/2017	Avedon	2004/0240214 A1	12/2004	Whitlow et al.
D794,198 S	8/2017	Mizumura et al.	2004/0253095 A1	12/2004	Sasaki et al.
D794,199 S	8/2017	Mizumura et al.	2005/0045793 A1	3/2005	Johnson et al.
D798,718 S	10/2017	Foster et al.	2005/0077446 A1	4/2005	Bacon et al.
D799,014 S	10/2017	Suarez et al.	2005/0092888 A1	5/2005	Gonce
D799,675 S	10/2017	Wong	2005/0159101 A1	7/2005	Hrdina et al.
D800,174 S	10/2017	Ghalsasi et al.	2005/0202776 A1	9/2005	Avedon
D801,510 S	10/2017	O'Connett et al.	2006/0087810 A1	4/2006	Rockenfeller
D801,545 S	10/2017	Wiesli et al.	2006/0146542 A1	7/2006	Sullivan
D803,381 S	11/2017	Kim et al.	2006/0172688 A1	8/2006	Johnson
D805,176 S	12/2017	Avedon	2006/0193139 A1	8/2006	Sun et al.
D818,185 S	5/2018	Wilson	2006/0276123 A1	12/2006	Sanagi et al.
9,970,457 B2	5/2018	Avedon	2006/0278766 A1	12/2006	Wang
D820,967 S	6/2018	Avedon	2006/0284435 A1	12/2006	Vitito
10,024,531 B2	7/2018	Avedon	2007/0213003 A1	9/2007	Railkar et al.
D824,716 S	8/2018	Elgamil et al.	2007/0231145 A1	10/2007	Jin
D825,090 S	8/2018	Richardson et al.	2007/0246579 A1	10/2007	Blateri
D831,484 S	10/2018	Jung et al.	2007/0297906 A1	12/2007	Wu
D835,265 S	12/2018	Inoue	2007/0297912 A1	12/2007	Reuter
D836,238 S	12/2018	Ericson, Jr. et al.	2008/0019836 A1	1/2008	Butz et al.
D838,379 S	1/2019	Trump	2008/0061200 A1	3/2008	Bouissiere
10,184,489 B2	1/2019	Avedon	2008/0188175 A1	8/2008	Wilkins
D840,009 S	2/2019	Suarez et al.	2008/0227381 A1	9/2008	Avedon
D841,452 S	2/2019	Conselvan	2009/0041580 A1	2/2009	Wichmann et al.
D844,126 S	3/2019	Sheng et al.	2009/0122516 A1	5/2009	Yang
D844,128 S	3/2019	Li	2009/0155080 A1	6/2009	Yu
10,221,861 B2	3/2019	Avedon	2009/0170421 A1	7/2009	Adrian et al.
D845,461 S	4/2019	Li	2009/0219727 A1	9/2009	Weaver
D845,462 S	4/2019	Li	2009/0262550 A1	10/2009	Inoue
D847,967 S	5/2019	Hernández et al.	2010/0009621 A1	1/2010	Hsieh
D848,295 S	5/2019	Johnson et al.	2010/0052495 A1	3/2010	Liu et al.
D850,727 S	6/2019	Petrucelli	2010/0075588 A1	3/2010	Haneline
D852,143 S	6/2019	Ku	2010/0111698 A1	5/2010	Wiedman et al.
D853,017 S	7/2019	Rioux et al.	2010/0176706 A1	7/2010	Fu et al.
D861,979 S	10/2019	Sibley	2010/0192611 A1	8/2010	Yamaguchi et al.
D862,795 S	10/2019	Caldas	2010/0202932 A1	8/2010	Danville
D865,223 S	10/2019	Spork et al.	2010/0232168 A1	9/2010	Hornig
D865,907 S	11/2019	Wagner	2010/0266400 A1	10/2010	Avedon
D868,254 S	11/2019	Lintula et al.	2010/0295436 A1	11/2010	Hornig et al.
10,487,840 B2	11/2019	Avedon	2010/0328881 A1	12/2010	Huang
10,487,852 B2	11/2019	Avedon	2010/0329885 A1	12/2010	Criner et al.
D869,275 S	12/2019	Taunk	2011/0037368 A1	2/2011	Huang
D870,778 S	12/2019	Johnson	2011/0057551 A1	3/2011	Lee et al.
D871,535 S	12/2019	Ferrer	2011/0057552 A1	3/2011	Weaver
D872,911 S	1/2020	Chen	2011/0080096 A1	4/2011	Dudik et al.
D877,917 S	3/2020	Schill	2011/0084586 A1	4/2011	Lain et al.
D880,098 S	3/2020	Harrison et al.	2011/0133622 A1	6/2011	Mo et al.
D881,374 S	4/2020	Schoettle	2011/0140588 A1	6/2011	Chen
D885,550 S	5/2020	Avedon	2011/0223016 A1	9/2011	Ediger et al.
			2011/0228967 A1	9/2011	Kulchy et al.
			2012/0060453 A1	3/2012	Holzmann et al.
			2012/0062095 A1	3/2012	Hornig
			2012/0194054 A1	8/2012	Johnston

(56)

References Cited

U.S. PATENT DOCUMENTS

2012/0195749	A1	8/2012	Avedon	
2013/0011254	A1	1/2013	Avedon	
2013/0023195	A1	1/2013	Avedon	
2013/0027950	A1	1/2013	Avedon	
2013/0111721	A1	5/2013	Mahfoudh et al.	
2013/0196588	A1	8/2013	Liao	
2014/0314560	A1	10/2014	Avedon	
2014/0348634	A1	11/2014	Bourrilhon et al.	
2015/0021013	A1	1/2015	Batarseh	
2015/0176834	A1	6/2015	Avedon	
2015/0176851	A1	6/2015	Avedon	
2015/0354578	A1	12/2015	Avedon	
2016/0107200	A1	4/2016	Al-Shafei et al.	
2016/0146222	A1	5/2016	Avedon	
2016/0186765	A1	6/2016	Avedon	
2016/0238029	A1	8/2016	Avedon	
2017/0370363	A1	12/2017	Avedon	
2018/0149380	A1	5/2018	Avedon	
2018/0335049	A1	11/2018	Gu et al.	
2019/0010961	A1	1/2019	Kumaou	
2019/0011121	A1	1/2019	Avedon	
2019/0285088	A1	9/2019	Avedon	
2020/0166053	A1	5/2020	Avedon	
2020/0217530	A1	7/2020	Avedon	
2020/0333027	A1	10/2020	Avedon	
2020/0378594	A1	12/2020	Avedon	
2021/0007449	A1	1/2021	Udagawa	
2021/0040960	A1*	2/2021	Shih .....	F04D 29/522
2021/0062827	A1	3/2021	Avedon	
2021/0277914	A1	9/2021	Lu et al.	
2021/0396248	A1	12/2021	Gao	
2022/0120469	A1	4/2022	Doat et al.	
2022/0220975	A1	7/2022	Avedon	

FR	0 715 101	11/1931
FR	2 784 423	4/2000
GB	190617978	5/1907
GB	0 792 369	3/1958
GB	0 824 390	11/1959
GB	0 981 188	1/1965
GB	1 251 880	11/1971
GB	2 344 619	6/2000
GB	2 468 504	9/2010
JP	55-032965	3/1980
JP	61-502267	10/1986
JP	01-067548	3/1989
JP	07-167097	7/1995
JP	07-253231	10/1995
JP	08-219939	8/1996
JP	11-132543	5/1999
JP	2001-193979	7/2001
JP	2002-349489	12/2002
JP	2006-350237	12/2006
JP	2010-181124	8/2010
KR	20-0176664	4/2000
KR	2003-0025428	3/2003
KR	10-1255739	4/2013
RU	2400254	C2 9/2010
TW	M337636	8/2008
WO	WO 01/034983	5/2001
WO	WO 03/040572	5/2003
WO	WO 2005/091896	10/2005
WO	WO 2006/078102	7/2006
WO	WO 2008/062319	5/2008
WO	WO 2010/046536	4/2010
WO	WO 2010/114702	10/2010
WO	WO 2011/067430	6/2011
WO	WO 2012/174155	12/2012
WO	WO 2012/174156	12/2012
WO	WO 2015/187856	12/2015
WO	WO 2016/081693	5/2016
WO	WO 2020/214729	10/2020

FOREIGN PATENT DOCUMENTS


CN	101592328	12/2009
CN	201560963	8/2010
DE	44 13 542	10/1995
DE	196 38 518	4/1998
DE	10 2008 044874	3/2010
EP	0 037 958	10/1981
EP	0 212 749	3/1987
EP	0 772 007	5/1997
EP	2 248 692	11/2010

OTHER PUBLICATIONS


Keeler Hardware, "OC Oval Cylinder Escutcheon", <https://www.keelerhardware.com.au/products/oc-oval-cylinder-escutcheon> as printed Nov. 13, 2017 in 3 pages.

"The New Airius Q50 EC", <https://web.archive.org/web/20150721185407/http://airius.com.au/technical/specification-sheets/the-new-airius-q50-ec/> as archived Jul. 21, 2015, pp. 2.


\* cited by examiner




**Fig. 1**



**Fig. 2**




**Fig. 3**




**Fig. 4**







**Fig. 5**




**Fig. 7**



**Fig. 6**



**Fig. 8**



**Fig. 9**




Fig. 10







Fig. 18




**Fig. 11**




**Fig. 11A**




**Fig. 12**




**Fig. 13**



**Fig. 14**




**Fig. 15**




**Fig. 16**






**Fig. 17**




**Fig. 19**






**FIG. 20**



**FIG. 21**






FIG. 23



## TEMPERATURE DESTRATIFICATION SYSTEMS

### CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. application Ser. No. 17/303,592, filed Jun. 2, 2021, incorporated in its entirety by reference herein, which is a continuation of U.S. application Ser. No. 16/662,957, filed Oct. 24, 2019, now U.S. Pat. No. 11,053,948, issued Jul. 6, 2021, incorporated in its entirety by reference herein, which is a continuation of U.S. application Ser. No. 15/648,261, filed Jul. 12, 2017, now U.S. Pat. No. 10,487,840, issued Nov. 26, 2019, incorporated in its entirety by reference herein, which is a continuation of U.S. application Ser. No. 15/480,285, filed Apr. 5, 2017, now U.S. Pat. No. 9,714,663, issued Jul. 25, 2017, incorporated in its entirety by reference herein, which is a continuation of U.S. application Ser. No. 15/061,951, filed Mar. 4, 2016, now U.S. Pat. No. 9,631,627, issued Apr. 25, 2017, incorporated in its entirety by reference herein, which is a continuation of U.S. application Ser. No. 13/365,223, filed Feb. 2, 2012, incorporated in its entirety by reference herein, which is a continuation-in-part of U.S. application Ser. No. 12/130,909, filed May 30, 2008, incorporated in its entirety by reference herein, which is a continuation of U.S. application Ser. No. 11/027,039, filed Dec. 30, 2004, now U.S. Pat. No. 7,381,129, issued Jun. 3, 2008, incorporated in its entirety by reference herein, which claims the benefit under 35 U.S.C. § 119(e) to U.S. Provisional Patent Application No. 60/553,720 filed Mar. 15, 2004, which is incorporated in its entirety by reference herein, and said U.S. application Ser. No. 13/365,223 also claims the benefit under 35 U.S.C. § 119(e) to U.S. Provisional Patent Application No. 61/521,270 filed Aug. 8, 2011, which is incorporated in its entirety by reference herein.

### BACKGROUND OF THE INVENTION

#### Field of the Invention

The present invention relates to heating, ventilating and air conditioning air spaces, and more particularly to systems, devices and methods for moving air in a columnar pattern with minimal lateral dispersion that are particularly suitable for penetrating air spaces and air temperature de-stratification.

#### Description of the Related Art

The rise of warmer air and the sinking of colder air creates significant variation in air temperatures between the ceiling and floor of buildings with conventional heating, ventilation and air conditioning systems. Such air temperature stratification is particularly problematic in large spaces with high ceilings such as warehouses, gymnasiums, offices, auditoriums, hangars, commercial buildings, and even residences with cathedral ceilings, and can significantly decrease heating and air conditioning costs. Further, both low and high ceiling rooms can have stagnant or dead air. For standard ceiling heights with duct outlets in the ceiling there is a sharp rise in ceiling temperatures when the heat comes on.

One proposed solution to air temperature stratification is a ceiling fan. Ceiling fans are relatively large rotary fans, with a plurality of blades, mounted near the ceiling. The blades of a ceiling fan have a flat or airfoil shape. The blades have a lift component that pushes air upwards or down-

wards, depending on the direction of rotation, and a drag component that pushes the air tangentially. The drag component causes tangential or centrifugal flow so that the air being pushed diverges or spreads out. Conventional ceiling fans are generally ineffective as an air de-stratification device in relatively high ceiling rooms because the air pushed by conventional ceiling fans is not maintained in a columnar pattern from the ceiling to the floor, and often disperses or diffuses well above the floor.

Another proposed solution to air temperature stratification is a fan connected to a vertical tube that extends substantially from the ceiling to the floor. The fan may be mounted near the ceiling, near the floor or in between. This type of device may push cooler air up from the floor to the ceiling or warmer air down from the ceiling to the floor. Such devices, when located away from the walls in an open space in a building, interfere with floorspace use and are not aesthetically pleasing. When confined to locations only along the walls of an open space, such devices may not effectively circulate air near the center of the open space. Examples of fans connected to vertical tubes are disclosed in U.S. Pat. No. 3,827,342 to Hughes, and U.S. Pat. No. 3,973,479 to Whiteley.

A device that provides a column of air that has little or no diffusion from the ceiling the floor, without a vertical tube, can effectively provide air de-stratification. U.S. Pat. Nos. 4,473,000 and 4,662,912 to Perkins disclose a device having a housing, with a rotating impeller having blades in the top of the housing and a plurality of interspersed small and large, vertically extending, radial stationary vanes spaced below the impeller in the housing. The device disclosed by Perkins is intended to direct the air in a more clearly defined pattern and reduce dispersion. Perkins, however, does not disclose the importance of a specific, relatively small gap between the impeller blades and the stationary vanes, and the device illustrated creates a vortex and turbulence due to a large gap and centrifugal air flow bouncing off the inner walls of the housing between the blades and vanes. Perkins also discloses a tapering vane section. The tapering vane section increases velocity of the exiting air stream.

A device with a rotary fan that minimizes the rotary component of the air flow while maximizing the axial air flow quantity and velocity can provide a column of air that flows from a high ceiling to a floor in a columnar pattern with minimal lateral dispersion that does not require a physical transporting tube. Such a device should reduce the energy loss by minimizing the rotary component of the air flow, and therefore minimizes turbulence. Such a device should minimize back pressure, since a pressure drop at the outlet of the device will cause expansion, velocity loss and lateral dispersion. The device should have minimum noise and low electric power requirements.

### SUMMARY OF THE INVENTION

A temperature destratification assembly can include an outer housing. The outer housing can have an inlet, an outlet, and an inner wall. The assembly can include an impeller positioned within the outer housing between the inlet and outlet of the outer housing. In some embodiments, the impeller has an impeller hub and a plurality of impeller blades extending radially outward from the impeller hub. The destratification assembly can include an impeller motor configured to rotate the impeller blades about an axis of rotation. In some embodiments, the destratification assembly includes a stator positioned within the outer housing between the impeller and the outlet of the outer housing. The

stator can include an upstream end and a downstream end. In some embodiments, the stator includes a plurality of vanes, every vane of the stator having an upstream edge at the upstream end of the stator, a downstream edge, a first surface extending from the upstream edge to the downstream edge of the vane, and a second surface opposite the first surface and extending from the upstream edge to the downstream edge of vane. In some embodiments, the downstream edge of one or more of the plurality of the vanes is at the outlet of the outer housing.

In some embodiments, the impeller hub is hollow.

In some embodiments, one or more of the plurality of the vanes extend further inward toward the axis of rotation than the impeller blades.

In some embodiments, two or more of the plurality of vanes are connected to each other at the downstream end of the plurality of vanes.

In some embodiments, a downstream edge of at least one of the plurality of vanes is positioned between the impeller and the outlet of the housing.

In some embodiments, the outer housing includes an outer surface, and wherein the outer surface of the outer housing is narrower at the outlet than at the inlet.

In some embodiments, an upstream portion of each vane is curved and a downstream portion of each vane is straight and parallel with the axis of rotation.

In some embodiments, the destratification assembly includes a plurality of stator flow passages extending from the upstream end of the stator toward the downstream end of the stator, wherein each of the stator flow passages is free from obstruction from vane leading edges.

According to some variants, a temperature destratification assembly can include a housing having an inlet, an outlet, and an inner surface extending from the inlet to the outlet. The assembly can include an impeller positioned within the housing between the inlet and the outlet. In some embodiments, the impeller includes an impeller hub and a plurality of impeller blades extending from the impeller hub toward the inner surface of the housing. Each impeller blade can have an upstream edge and a downstream edge. In some embodiments, the destratification assembly includes an impeller motor configured to rotate the impeller hub about an axis of rotation. The assembly can include a stator assembly positioned downstream of the impeller. In some embodiments, the stator assembly includes a plurality of vanes extending along a majority of a distance between the impeller and the outlet of the housing. Each of the plurality of vanes can have an upstream vane edge adjacent the downstream edge of an impeller blade, a downstream vane edge opposite the upstream vane edge, a first face extending from the upstream vane edge to the downstream vane edge, and a second face opposite the first face and extending from the upstream vane edge to the downstream vane edge. In some embodiments, each of the first and second faces of the plurality of vanes has an upstream portion and a downstream portion. In some embodiments, the downstream portions of each of the first and second faces are uninterrupted.

In some embodiments, the impeller hub is hollow.

In some embodiments, the plurality of vanes extend further inward toward the axis of rotation than the impeller blades.

In some embodiments, the plurality of vanes are connected to each other at the downstream edge of the plurality of vanes.

In some embodiments, the outer housing includes an outer surface. In some embodiments, the outer surface of the outer housing is narrower at the outlet than at the inlet.

In some embodiments, an upstream portion of each vane is curved and a downstream portion of each vane is straight and parallel with the axis of rotation.

According to some variants, a temperature destratification assembly can include an outer housing having an inlet, an outlet, and an inner wall. The destratification assembly can include an impeller positioned within the outer housing between the inlet and outlet of the outer housing, the impeller having a plurality of impeller blades. In some embodiments, the assembly includes an impeller motor configured to rotate the impeller blades about an axis of rotation. The assembly can include a stator positioned within the outer housing between the impeller and the outlet of the outer housing. In some embodiments, the stator has an upstream end, a downstream end, a stator hub, a plurality of stator vanes connected to the stator hub and extending radially outward therefrom, a plurality of inlets at the upstream end of the stator, and a plurality of outlets at the downstream end of the stator. In some embodiments, the stator includes at least as many inlets as outlets.

In some embodiments, the inner wall is a smooth uninterrupted surface.

In some embodiments, the stator comprises more inlets than outlets.

In some embodiments, the stator hub tapers toward the axis of rotation from an upstream end of the stator hub to a downstream end of the stator hub.

In some embodiments, the outer housing tapers inward toward the axis of rotation between the upstream end of the stator and the downstream end of the stator.

In some embodiments, the stator hub is cylindrical

An air moving device which has a housing with an air inlet and an air outlet spaced from the inlet. A rotary impeller with a plurality of blades is mounted in the housing at the air inlet end and produces air flow with an axial component and a rotary component. A plurality of spaced, longitudinally extending, radial air guide vanes in the housing downstream of the impeller are in close proximity to the impeller blades to minimize the rotary component and change the air flow to a laminar and axial flow in the housing that exits the outlet end in a columnar pattern with minimal lateral dispersion. A method of moving air includes producing an air flow through a housing, and directing the air flow through the housing in a laminar and axial flow and exits an outlet so as to produce a columnar pattern with minimal lateral dispersion. The method also includes directing warm air from near the ceiling toward the floor, allowing the heat from the warm air to be stored in the floor, articles on the floor and the earth under the floor. The method includes directing air in a generally horizontal direction to allow penetration of an air space in a container, trailer truck or a room to promote flushing of that air space and circulation thereof. The device and method are particularly suitable for high efficiency, low power usage, air temperature de-stratification, and to improve air quality and circulation.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Details of this invention are described in connection with the accompanying drawings that bear similar reference numerals in which:

FIG. 1 is a top perspective view of an air moving device embodying features of the present invention.

FIG. 2 is a side elevation view of the device of FIG. 1.

FIG. 3 is a bottom view of the device of FIG. 1.

FIG. 4 is an exploded perspective view of the device 5 of FIG. 1.

## 5

FIG. 5 is a sectional view taken along line 5-5 of FIG. 2.

FIG. 6 is a sectional view taken along line 6-6 of FIG. 2.

FIG. 7 is a sectional view taken along line 5-5 of FIG. 2, with straight upstream portions of the vanes.

FIG. 8 is a side elevation view of the device of FIG. 1 showing angular direction of the device.

FIG. 9 is an enlarged, partial exploded view of the hangar attachment of the device of FIG. 1.

FIG. 10 is a side view of a room with the device of FIG. 1 showing an air flow pattern with dashed lines and arrows.

FIG. 11 is a side elevation view, partially cut away, showing the device of FIG. 1 modified for attachment to a light can.

FIG. 11A is a sectional view taken along line 11A-11A of FIG. 11.

FIG. 12 is a side elevation view of the device of FIG. 1 with an intake grill.

FIG. 13 is a sectional view taken along line 6-6 of FIG. 2 of the device of FIG. 1 with a misting nozzle.

FIG. 14 is a side elevation view of the device of FIG. 1 in combination with a tube and second air moving device.

FIG. 15 is a bottom perspective view, partially cut away, showing the device of FIG. 1 mounted in a drop ceiling.

FIG. 15A is a top perspective view of FIG. 15.

FIG. 15B is a top perspective view of the fastening member shown in FIG. 15A.

FIG. 15C is a sectional view taken along FIG. 15C-15C of FIG. 15A.

FIG. 15D is a sectional view along line 15D-15D of FIG. 15A.

FIG. 16 is an enlarged view of a portion of FIG. 15.

FIG. 17 is a side elevation view, partially cut away, showing the device of FIG. 1 modified for attachment to a light socket and having a light bulb at the lower end.

FIG. 18 is a schematic view of an open sided tent with an air moving device in the top.

FIG. 19 is a schematic view of a shipping container with an air moving device at one lower end.

FIGS. 20-24 are schematic representations of a plurality of air moving devices used to create a cascading airflow.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring now to FIGS. 1 to 9, there is shown an air moving device 12 having an elongated outer housing 13, an electric rotary fan 14 in the housing for producing air flow in the housing and a plurality of longitudinally extending, outer radial vanes 15 and an inner housing hub 16 opposite the vanes in the housing downstream of the fan for directing air flow in the housing.

The housing 13 has a circular cross section, and an open first end 17 and an open second end 18 spaced from the first end 17. In the illustrated embodiment, a detachable, axially outwardly convex cowling 19 forms the first end 17 and provides an air inlet 21 with a diameter slightly smaller than the outer diameter of the cowling 19.

The housing 13 has a first section 25 extending from the cowling 19 to an interior shelf 26. A generally C shaped hanger 23 mounts at opposite ends 24 to opposite sides of the housing 13 at the upper end of the first section 25, for mounting the air moving device 12 to a support. The first section 25, when viewed from the side, has a curved, slightly radially outwardly convex shape that conforms to the curvature of the cowling 19. The shelf 26 extends radially inwardly to join with the upstream end of a second section 27. The second section 27 tapers inwardly and extends

## 6

axially from the shelf 26 to the second end 18 along a smooth curve that goes from radially outwardly convex near the shelf 26 to radially outwardly concave near the second end 18. The second end 18 forms an air outlet 28 that has a smaller diameter than the air inlet 21. A plurality of circumferentially spaced external fins 29 extend from the shelf 26 to the second section 27 to provide the appearance of a smooth curve from the air inlet 21 to the air outlet 28 when the housing 13 is viewed from the side.

The fan 14 includes an impeller 31 having a cylindrical, inner impeller hub 32, with an electric motor 34 therein, and a plurality of rigidly mounted, circumferentially spaced blades 33 extending radially from the impeller hub 32. In the illustrated embodiment the impeller 31 has three equally spaced blades 33 and rotates about an axis in a counter-clockwise direction when viewed from above. Each blade 33, in side view, extends from an upstream edge 35, downwardly and leftwardly to a downstream edge 36 with each blade 33 being slightly concave, in an airfoil or wing shape, downwardly to propel air rightwardly as shown by the arrow. Each blade 33 then inclines at a selected angle to the axis of rotation of the impeller. Each blade 33 shown extends axially and radially toward the outlet or second end 18 to direct air axially with a rotary component. If the motor 34 runs in the opposite direction, the incline of the blades 33 would be reversed. The fan 14 includes a stationary cylindrical mounting ring 38 that extends around the blades 33, with the impeller hub 32 being rotably mounted relative to the mounting ring 38. The mounting ring 38 has spaced, protruding upstream and downstream rims 40 and 41. The fan 14 mounts in the housing 13 between the cowling 19 and the shelf 26.

Each of the vanes 15 is identical and includes upstream portion 43 and a downstream portion 44. The upstream portion 43 is carried in a stator 46. The stator 46 has a cylindrical stator hub 47 with a diameter substantially equal to the diameter of the impeller hub 32.

The upstream portions 43 of the vanes 15 are mounted in a circumferentially spaced arrangement around the stator hub 47, and extend longitudinally along and radially from the stator hub 47. Each upstream portion 43 has an upstream end 48 and a downstream end 49. A support body 50 includes a cylindrical stator ring 52 that extends around the upstream portions 43 and connects to the outer ends of the upstream portions 43 of the vanes 15 near the upstream ends 48. The support body 50 also includes a protruding stator rim 53 that is substantially planar with the upstream ends 48 of the upstream portions 43 of the vanes 15, and that connects to the stator ring 52 and extends radially outwardly therefrom.

The housing 13 has, an inner surface and the inner housing hub 16 has an outer surface concentric with a spaced from the housing inner surface to define an air flow passage through the housing. The inner housing hub 16 includes the fan hub 32, stator hub portion 47 and downstream hub portion 57, each having an outer surface and arranged end to end along the center of the housing and opposite and spaced from the housing inner surface to define the air flow passage. In particular, these outer surfaces shown are cylindrical and substantially the same diameter for a substantial portion of the passage and as the housing 13 converges the downstream hub portion 57 converges to generally follow the curvature of the inside surface of the housing.

The stator 46 nests in and is separable from the housing 13 with the stator rim 53 between the shelf 26 of the housing 13 and the downstream rim 41 of the mounting ring 38 of the fan 14, and with a gap 55 having a selected size between the



downstream edge 36 of the blades 33 of the impeller 31 and the upstream ends 49 of the upstream portions 43 of the vanes 15. If the gap 55 is too large, turbulence will be generated in the air flow between the impeller 31 and the vanes 15, reducing the velocity of the air flow. If the gap 55 is too small, fluid shear stress will generate noise. The size of the gap 55 is generally selected as no greater than a maximum selected dimension to avoid turbulence and no less than a selected minimum dimension to avoid noise, and more particularly selected as small as possible without generating noise.

The selected size of the gap 55 is generally proportional to the diameter of the impeller 31 and may further be affected by the speed of the impeller 31. The following are examples: For an impeller 31 with a diameter of 6.00", at 1800 rpm, the maximum size of the gap 55 should be 1.25" and the minimum gap should be 0.2". For an impeller 31 with a diameter of 8.5", at 1400 rpm, the maximum size of the gap 55 should be 1.25", and the minimum gap should be 0.2" but could be 0.020 for lower rpm's as the size of the gap is rpm dependent. Generally, the maximum size of the gap 55 should be less than one half the diameter of the impeller 31.

In the illustrated embodiment, eight equally spaced upstream portions 43 of the vanes 15 are provided, and when viewed from the side, the upstream portions 43 of the vanes 15 extend straight upwardly from the downstream ends 49 and then curve leftwardly near the upstream ends 48. The upstream portion 43 of each curved vane portion is inclined at an angle opposite the incline of the blade 33 that extends axially and radially inward toward the outlet or second end 28 to assist in converting the rotary component of the air flow into laminar and axial flow in the housing.

Straight upstream portions 43A of the vanes 15 may also be used, as shown in FIG. 7, and other numbers of vanes 15 may be used. Further, if the motor 34 runs in the opposite direction, the incline of the curvature near the upstream ends 48 would be reversed.

The downstream portions 44 of the vanes 15 attach at an inner end to a downstream inner housing hub portion 57, are circumferentially spaced and extend radially outwardly from the housing hub portion 57 to the housing 13. The housing hub portion 57 and the downstream portions 44 of the vanes 15 extend axially from the stator 46 to or near the air outlet 28. The housing hub portion 57 has a circular cross section, has a diameter substantially equal to the diameter of the stator housing hub portion 47 at the upstream end adjacent to the stator housing hub portion 47, and tapers downstream to a point 58 near the air outlet 28.

This hub portion may be characterized as torpedo shaped. In the illustrated embodiment there are four downstream portions 44 of the vanes 15 circumferentially spaced at 90 degrees, with each downstream portion 44 being aligned with an upstream portion 43 of a vane 15. Other numbers of downstream portions 44 of the vanes 15 can be used.

The number of the blades 33 may be 2, 3, 4, 5, 6, 7 or 8. The number of the vanes 15 may be 2, 3, 4, 5, 6, 7 or 8. The number of vanes 15 should be different from the number of blades 33. If the number of vanes 15 and blades 33 are the same, added noise is generated due to harmonics.

The air moving device 12 discharges air at a high velocity in a generally axial flow having a columnar pattern with minimal lateral dispersion after exiting the air outlet 28. The cowling 19 extends along a curve toward the inside to reduce turbulence and noise for air flow entering the air inlet 21. The impeller hub 32, the stator hub 47 and the housing hub 57 form the inner housing hub 16. The taper of the housing

hub 57 generally follows the taper of the housing 13 so that the cross sectional area for air flow decreases about 10% to 35% through the air moving device 12 to avoid back pressure and at the same time increase air flow velocity. In the embodiment shown the air flow decreases about 22%.

The vanes 15 convert the rotary component of the air flow from the impeller 31 into laminar and axial air flow in the housing. The leftward curve of the upstream ends 48 of the upstream portions 43 of the vanes 15, in the illustrated embodiment, reduces the energy loss in the conversion of the rotary component of the air flow from the impeller 31 into laminar and axial air flow in the housing. The small gap 55 between the impeller 31 and vanes 15 prevents the generation of turbulence in the air flow in the gap 55. The taper of the housing 13 in combination with the taper of the housing hub 57 to the point 58 allows the air flow to exit the air outlet 28 in a continuous, uninterrupted columnar pattern with minimal dispersion, with no center hole or gap at a linear speed greater than would be imparted by a fan alone. The inside surface of the housing 13 is a substantially smooth uninterrupted surface to minimize turbulence and energy loss.

The hanger 23 is mounted to rotate and lock relative to the housing 13, so that when the hanger 23 is attached to an overhead support such as ceiling, the air flow from the air moving device 12 may be directed vertically or aimed at any selected angle from the vertical as shown in FIG. 8. As shown in FIGS. 1 and 9, the first section 25 of the housing 13 includes mounting tabs 91 on opposite sides on the upper edge of the first section 25. Each mounting tab 91 includes a round, outwardly directed mounting face 92, and a housing aperture 93 that extends inwardly through the center of the mounting tab 91. A pair of outwardly projecting housing ridges 94 extend radially on the mounting face 92 on opposite sides of the housing aperture 93.

Each end 24 of the hanger 23 has a round, inwardly facing hanger end face 96, similar in size to the mounting face 92 on the housing 13. A hanger end aperture 97 extends through the center of the hanger end face 96. A plurality of spaced, radially extending grooves 98, sized to receive the housing ridges 94, are provided on each hanger end face 96. Bolt 100 extends through the hanger end aperture 97 and threads into an internally threaded cylindrical insert 101, rigidly affixed in housing aperture 93. The angle of the housing 13 is chosen by selecting a pair of opposed grooves 97 on each hanger end 24 to receive the housing ridges 94. The pivotal arrangement enables the housing to move to a selected angle and is lockable at the selected angle to direct air flow at the selected angle.

FIG. 10 shows an air moving device 12 mounted to the ceiling 62 of a room 63 shown as being closed sided with opposed side walls. Warm air near the ceiling 62 is pulled into the air moving device 12. The warm air exits the air moving device 12 in a column 64 that extends to the floor 65. When the column 64 reaches the floor 65, the warm air from the ceiling pushes the colder air at the floor 65 outward towards the opposed side walls 66 and upward towards the ceiling 62. When the column 64 reaches the floor 65, the warm air from the ceiling will also transfer heat into the floor 65, so that heat is stored in the floor 65. The stored heat is released when the ceiling is cooler than the floor. The heat may also be stored in articles on the floor and earth under the floor. The air moving device 12 destratifies the air in a room 63 without requiring the imperforate physical tube of many prior known devices. The air moving device 12 destratifies the air in a room 63 with the warmer air from the ceiling 62 minimally dispersing before reaching the floor 65, unlike

many other prior known devices. The air moving device **12** will also remove dead air anywhere in the room. It is understood that the air moving device **12** may also be mounted horizontally in a container, trailer truck or room as is describe hereafter.

Referring to FIG. **11**, an air moving device **12** is fitted with an inlet grill **68** and an electric connector **69** for attachment to a light can **70** with a light bulb socket **71** at the upper end. The inlet grill **68** includes a plurality of circumferentially spaced grill fins **72** that attach to the first end **17** of the housing **13**. The grill fins **72** are separated by air intake slots **73**, and extend axially outwardly from the first end **17** and curve radially inwardly and are integral with a flat circular mounting plate **74** that is substantially parallel with the first end **17**. The electrical connector **69** has a tube **76** that is integral at one end with the center of the mounting plate **74** and extends axially therefrom, and a light bulb type, right hand thread externally threaded male end **77** attached to the other end of the shaft **78**. Grill **68**, plate **74** and tube **76** are shown as made of a one piece construction. Plate **74** has holes that received screws **83** or like fasteners to fasten plate **74** to ceiling **62**.

The shaft **78** telescopes in the tube **76**. The tube **76** has a pair of opposed keyways **76A** that receive keys **78A** on the shaft **78** which allow axial sliding movement of the shaft **78** in the tube **76**. A compression spring **75** fits in the tube and bears against the bottom of shaft **78** and top of plate **74**. Preferably the shaft **78** has a selected length relative to the length of the can **70** such that when the air moving device **12** is mounted in a can **70** in a ceiling **62**, the threaded male end **77** engages the socket **71** before the mounting plate **74** contacts the ceiling **62** and when the threaded male end **77** is screwed into the socket **71**, the mounting plate **74** bears against the ceiling **62**. The spring **75** is compressed between plate **74** and shaft **78**. Screws **83** fasten the plate to the ceiling **62**. Since the light can **70** may be open to air above the ceiling **62**, the mounting plate **74** is preferably sized to cover the open lower end of the can **70**, so that only air from below the ceiling **62** is drawn into the air moving device **12**. The air moving device **12** fitted with the inlet grill **68** and the electrical connector **69** can also be used with a ceiling light socket.

The air moving device **12** may include an intake grill **79** for preventing objects from entering the impeller **31**, as shown in FIG. **12**. The intake grill **79** shown has a substantially hemispherical shape, and includes a plurality of circumferentially spaced grill fins **80** separated by intake slots **81**. The grill fins **80** extend axially outwardly and curve radially inwardly from the first end **17** of the housing **13** to a central point **82** spaced from the first end **17**. Other shapes of intake grills are suitable for the present invention.

FIG. **13** shows an air moving device **12** with a misting nozzle **84**. The nozzle **84** extends through the point **58** of the housing hub **57** to spray water into the column of air exiting the air outlet **28** to cool the air through evaporation. The media exiting the nozzle **84** and being supplied through tube **85** can have other purposes such as a disinfectant or a fragrance or a blocking agent for distinctive needs. The nozzle **84** connects to a water line **85**, in the housing hub **59** that connects to a water source (not shown).

FIG. **14** shows an air moving system **86** for use in buildings with very high ceilings, including an air moving device **12**, an upwardly extending, tube **87** (shown cut away) connected at a lower end to the air inlet **21** of the air moving device **12**, and a truncated upper air moving device **88** having an air outlet **89** connected to the upper end of the tube **87**. The housing of device **88** is called truncated because it

may be shortened or cut off below the fins **29**. A conventional air moving device **12** may be used for device **88**. The tube **87** may be flexible and is preferably fire resistant. The air moving system **86** is mounted to a ceiling or like support with the air outlet **28** of the air moving device **12** spaced above the floor, preferably about 10 to 50 feet. The tube may be for example from 30 to 100 feet long.

The upper air moving device **88** at the top of the system **86** has a higher air moving flow capacity than the air moving device **12** at the bottom of the cascading system **86**. By way of example, and not as a limitation, the upper air moving device **88** may have a capacity of 800 cfm and the air moving device **12** may have a capacity of 550 cfm.

FIGS. **15**, **15A**, **15B**, **15C**, **15D** and **16** show the air moving device **12** mounted in an opening **103** in a ceiling **104**. A generally cylindrical can **105** mounts on and extends above the ceiling **104**, and has an open can bottom **106**, and a closed can top **107**. The can top **107** includes a semi-circular, downward opening, circumferentially extending channel **108**. A semi-circular fin **111** extends radially across the channel **108** to prevent swirling of the air before entering the air inlet **21**. Additional fins may be used. A grill and support assembly **125** mounts to the ceiling and extends and connects to the exterior of the housing of device **12**. A grill including spaced openings **110** between fins **109** to allow air to flow up from the room along the housing and past the cowling **19** into the inlet **21**. The grill and support assembly **125** includes an outer ring **120** fastened to the underside of the ceiling including the convexly curved grill fins **109** with air openings **110** between connected outer ring **120** and an inner ring **121**. Ring **121** has a spherical concave inner bearing surface **122**.

A ring **123** has a spherical convexly curved exterior bearing surface **124** is mounted on and affixed to the housing with bearing surfaces **122** and **124** mating in a frictional fit to support the housing to be at a vertical position or tilted at an angle to the vertical axis and be held by friction at the vertical axis or a selected angle relative to the vertical axis to direct air flow as required.

The can **105** has an outwardly extending bottom flange **140** that fits against the underside of the ceiling **104**. The can **105** preferably has four circumferentially spaced bottom openings **141** at 90 degree intervals that are rectangular in shape and extend up the can wall a short distance from the bottom flange **140**. A clamping member **142** preferably made as a molded plastic body has a main body portion **143** above the ceiling **104** outside the can wall and an end flange portion **144** that fits inside the can opening **142**. The main body portion **143** has a U-shaped outer wall portion **145** and an inner hub portion **146** having an aperture **147**. The clamping member **142** inserts into the opening **141** via the open end of the can. A bolt fastener **151** extends through a hole in the flange, through a hole in the ceiling and threads into the aperture **147** in the main body portion to clamp the can **105** to the ceiling **104**.

As shown in FIG. **15D** the grill and support assembly **125** is mounted to the ceiling **104** and can **105** by a bolt fastener **149** extending through an aperture in ring **120**, through the ceiling **104** and into a nut **150** in flange **140** in the can. Preferably there are four bolt fasteners **149** at 90 degree intervals midway between fasteners **151** above described. The ceiling **104** typically would be a plasterboard ceiling in which a suitable hole is cut. A variation of FIG. **15** would be to extend or form the peripheral of outer ring **120** into a flat panel having a dimension of 2 ft. by 2 ft. that would fit in and be held by a grid that holds a conventional ceiling panel.

## 11

Referring to FIG. 17, an air moving device is fitted with an inlet grill 113, a light bulb style threaded male end 114 for threading into a light bulb socket, and a light bulb socket 115. The inlet grill 113 includes a plurality of circumferentially spaced grill fins 116 that attach to the first end of the housing 13. The grill fins 116 are separated by air intake slots 117, and extend axially outwardly from the first end 17 and curve radially inwardly to a flat circular mounting plate 118 that is substantially parallel with and spaced axially from the first end 17. Threaded male end 114 is mounted on and extends upwardly from the mounting plate 118. The socket 115 is mounted inside the housing 13 in a downwardly opening fashion so that light from a bulb 119 threaded into the socket 115 is directed downwards.

Referring now to FIG. 18, there is shown a tent having an inclined top 132 extending down from an apex and connected at the lower end to a vertical side wall 131 and terminating above a floor 133 to provide a side opening 134 so that the tent is an open sided room. The air moving device 12 is mounted below the top apex and directs the air in the room downwardly in a columnar pattern to the floor and along the floor and then back with some air passing in and out the side openings 134 along the floor 133. For wide tents, the air will pass up before it reaches the side walls.

The air moving device and system herein described has relatively low electrical power requirement. A typical fan motor is 35 watts at 1600 rpm for an impeller of 8.5" that will effectively move the air from the ceiling to the floor in a room having a ceiling height of 30 ft. Another example is 75 watts with an impeller diameter 8.5" at 2300 rpm in a room having a ceiling height of 70 ft.

Referring now to FIG. 19, there is shown a shipping container 161 having an air moving device 12 disposed horizontally in the lower left end. The device 12 directs the air horizontally along the bottom wall or floor, up the opposite side wall and across the top wall to exit an outlet duct 162 above and spaced from the device 12 of the air moving device. The device 12 will penetrate the air and promote flushing and circulation of the air space. The device 12 may be mounted to direct the air generally horizontally or up or down at an angle to the true horizontal. This arrangement may be provided in other air spaces such as a trailer truck, room or the like.

It is understood that the stator 46 and housing 13 could be made as a single unit. It is also understood that the housing 13 may be made in two sections as for example a tubular section of a selected length may be added to the end of a truncated devices as shown in FIG. 14.

Further to the discussion above, and referring to FIGS. 20-25, in some embodiments a plurality of the air moving devices 12 described above can be used to create a cascading flow of air from one location to a second location. For example, with reference to FIG. 20, in some embodiments a plurality of air moving devices 12 can be positioned at or near the ceiling of a room or roof of a building. Alternatively or in addition, the air moving devices can be positioned within 4 feet of the floor, within 8 feet of a floor, within 12 feet of a floor or greater than 12 feet from the floor. The air moving devices 12 can be distanced apart from one another. The distances between the air moving devices 12 can vary. In some embodiments the distances can be equal between each air moving device 12. In some embodiments the distance between a first and second air moving device 12 can be different than the distance between the second and a third air moving device 12. In some embodiments the distance

## 12

between two air moving devices 12 can be approximately 5 feet, 10 feet, 15 feet, 20 feet, 25 feet, 30 feet, 35 feet, or any other desired distance.

The air moving devices 12 can be angled and/or positioned such that the air flow exiting a first air moving device 12 is directed generally towards a second air moving device 12 and/or the air flow exiting the second air moving device 12. In some embodiments the air flow exiting the first air moving device 12 and the air flow exiting the second air moving device 12 are directed generally in the same direction, such that when the air flow exiting the first air moving device 12 reaches the air flow exiting the second air moving device 12, the two air flows generally merge together.

Often times the air flow exiting an air moving device 12 will have a higher velocity nearest the air moving device 12 from which it left, as compared with the velocity of the air flow as it moves farther away from the air moving device 12. The farther away the air flow is from the air moving device 12, the more the air flow will slow down. Thus, with reference to FIG. 20, the air moving devices 12 can be arranged such that as the air flow of a first air moving device 12 is at least 80% of its initial velocity, at least 60% of its initial velocity, at least 40% of its initial velocity, at least 20% of its initial velocity, or at least 10% of its initial velocity before the airflow of the first air moving device 12 encounters and/or is accelerated into the higher velocity air flow created by a second air moving device 12. Desirably, the second air moving device accelerates the air to at least 120%, at least 140%, 160%, 200%, 300%, 400%, 500% of the velocity of the air flow when the air flow from the first air moving device encounters and/or is accelerated into the higher velocity air flow created by a second air moving device 12. In this manner, the second air moving device 12 acts to cascade the air from the first air moving device 12, and to continue to push it along with the air flow from the second air moving device 12. In some embodiments, at least a portion of the air flow from the first air moving device 12 also enters the second air moving device 12, and is directed back out the second air moving device 12 at a higher velocity. Thus, both the second air moving device 12, as well as its exiting air flow, can be used to propel the air flow from the first air moving device 12. With a plurality of air moving devices 12 working in concert, a cascading effect can be achieved, in which the air moving devices 12 work together to move air. This cascading effect can advantageously be used to create a continuous movement of air throughout long stretches of space. This continuous movement of air can help to ventilate, clean, cool, and/or prevent stale air pockets from building up over time.

While the air moving devices 12 can be used within buildings, they can also be used outdoors. For example, people are often required to stand in long lines at amusement parks or other locations. The long lines can extend partially within a building, and/or outside a building. Heat can build up over time, making people uncomfortable as they wait, as can pockets of stale air. Thus, a plurality of air moving devices 12 can be arranged and/or mounted outdoors as well, to help cool and/or remove pockets of stale air.

With reference to FIGS. 21-23, in some embodiments a plurality of air moving devices 12 can be arranged, for example, to move cool air from a first location into a second location. For example, cool air can be moved from a street level location to a subway or train station terminal. As illustrated in FIGS. 21-23, the air moving devices 12 can be spaced apart and angled such that a continuous airflow is created within the terminal. The continuous airflow can direct air down from street level towards the platform level

## 13

of the terminal (see FIGS. 21, 23), then generally parallel to a train or train track along the platform (see FIG. 23), and finally back up from the platform level to the street level again (see FIGS. 22, 23). The air flow devices 12 can work in concert to create the continuous airflow, helping to cool the subway or train station terminal, and/or to eliminate pockets of stale air that have built up within the terminal. This cascading movement of air can especially be useful at night, when the air at the street level is cool, and fresh. During night, when there are fewer people, and the trains are not running, the air moving devices 12 can be operated at high speeds to help quickly cool the terminal area, and then be run at lower speeds during the daytime when the people in the terminal area.

With reference to FIG. 24, in some embodiments a plurality of air moving devices 12 can also be arranged such that some of the air moving devices 12 are angled to direct air in a cascading manner as described above, whereas other air moving devices 12 are angled to direct air downwardly. This arrangement of air moving devices 12 can advantageously be used in commercial areas, such as grocery stores. For example, as illustrated in FIG. 24, air can be directed in through a roof unit 164. Once the air is inside the building (e.g. grocery store), the air moving devices 12 can pick up the air and move it in a cascading manner within the store to cool and/or eliminate pockets of stale air. Some of the air moving devices 12 can be angled so as to direct the air in a downward manner, cooling areas such as aisles or other portions of the store that may need to be cooled. This combination of cascading and downward cooling can help to keep the store as fresh, and comfortable, as possible.

Additionally, moving air laterally and in a cascading manner can advantageously be used where it is not possible to use ductwork to achieve the same purpose, or where ductwork would be too expensive or too large. For example, often the clearance within a commercial or manufacturing building's roof is not suitable for use of ductwork. The ductwork for such buildings can be costly, and can incorporate multiple pipes or other structures which accumulate losses. Ductwork is also often not available for areas in which people are waiting in line (e.g. waiting to get into rides as described above). In some large industrial buildings, manufacturing processes such as blow molding are used. These processes generate large amounts of heat (e.g. in the form of a heat plume) that need to be moved to other areas of the building to prevent electronics in the area (e.g. near the ceiling) from melting and/or otherwise being damaged. In these areas ductwork is also often not appropriate because the runs may be 500 feet or more. The ductwork would need to be very large, and the motors would need to be very large as well in order to move propel the air, resulting in high cost. Additionally, the ceilings of these buildings are often filled with conveyers and other objects that would make such large ductwork unfeasible. Thus, using a plurality of air moving devices 12, which cascade the air as described above, would be advantageous alternatives for ductwork in these and the other structures and setting described above.

Although the present invention has been described with a certain degree of particularity, it is understood that the present disclosure has been made by way of example and that changes in details of structure may be made without departing from the spirit thereof.

What is claimed is:

1. An air moving system comprising:

an air moving device comprising:

a housing having an air inlet and an air outlet,  
a fan disposed within the housing, and

## 14

a stator hub disposed within the housing and having a plurality of circumferentially spaced vanes;  
a can configured to be mounted above a ceiling, the can comprising an open can bottom and a closed can top defining a downward opening, circumferentially extending channel, the air moving device configured to be positioned at least partially within the can, wherein the air outlet extends at least partially out of the can; and

a grill configured to be mounted to the ceiling and coupled to an exterior surface of the housing of the air moving device, the grill comprising a plurality of spaced openings configured to allow air to flow up from the room and into the air inlet.

2. The air moving system of claim 1, wherein the plurality of spaced openings are positioned between fins.

3. The air moving system of claim 1, wherein the grill further comprises an outer ring fastened to the an underside of the ceiling.

4. The air moving system of claim 1, wherein the grill further comprises an inner ring configured to receive the air outlet portion of the air moving device.

5. The air moving system of claim 1, wherein the can further comprises an outwardly extending bottom flange that is configured to fit against an underside of the ceiling.

6. The air moving system of claim 1, wherein the can has a plurality of circumferentially spaced bottom openings that extend up a wall of the can.

7. The air moving system of claim 5, further comprising a plurality of clamping members corresponding to the plurality of circumferentially spaced bottom openings, the plurality of clamping members configured to be inserted into the plurality of circumferentially spaced bottom openings.

8. An air moving system comprising:

an air moving device having an air inlet and an air outlet;  
a can configured to be mounted above a ceiling, the can comprising an open can bottom and a closed can top, the air moving device configured to be positioned at least partially within the can, wherein the air outlet extends at least partially out of the can; and

a grill configured to be mounted to the ceiling and coupled to an exterior surface of the housing of the air moving device, the grill comprising a plurality of spaced openings configured to allow air to flow up from the room and into the air inlet.

9. The air moving system of claim 8, wherein the closed can top defines a downward opening, circumferentially extending channel.

10. The air moving system of claim 8, wherein the plurality of spaced openings are positioned between fins.

11. The air moving system of claim 8, wherein the grill further comprises an outer ring fastened to the an underside of the ceiling.

12. The air moving system of claim 8, wherein the grill further comprises an inner ring configured to receive the air outlet portion of the air moving device.

13. The air moving system of claim 8, wherein the can further comprises an outwardly extending bottom flange that is configured to fit against an underside of the ceiling.

14. The air moving system of claim 8, wherein the can has a plurality of circumferentially spaced bottom openings that extend up a wall of the can.

15. The air moving system of claim 14, further comprising a plurality of clamping members corresponding to the plurality of circumferentially spaced bottom openings, the

**15**

plurality of clamping members configured to be inserted into  
the plurality of circumferentially spaced bottom openings.

\* \* \* \* \*

**16**