

US011724370B2

(12) **United States Patent**
Zimmermann et al.

(10) **Patent No.:** **US 11,724,370 B2**
(45) **Date of Patent:** **Aug. 15, 2023**

(54) **LOCKABLE DRIVE SOCKET ADAPTER**
(71) Applicant: **MILWAUKEE ELECTRIC TOOL CORPORATION**, Brookfield, WI (US)
(72) Inventors: **Michael J. Zimmermann**, New Berlin, WI (US); **James J. Van Essen**, Hales Corners, WI (US)
(73) Assignee: **MILWAUKEE ELECTRIC TOOL CORPORATION**, Brookfield, WI (US)
(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **17/524,108**

(22) Filed: **Nov. 11, 2021**

(65) **Prior Publication Data**

US 2022/0063066 A1 Mar. 3, 2022

Related U.S. Application Data

(63) Continuation of application No. 16/505,900, filed on Jul. 9, 2019, now Pat. No. 11,179,831.

(60) Provisional application No. 62/696,373, filed on Jul. 11, 2018.

(51) **Int. Cl.**
B25B 23/00 (2006.01)
B25B 21/00 (2006.01)

(52) **U.S. Cl.**
CPC **B25B 23/0035** (2013.01); **B25B 21/007** (2013.01)

(58) **Field of Classification Search**
CPC **B25B 23/0035**; **B25B 23/0007**; **B25B 21/007**; **F16B 21/00**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,215,208	B1	4/2001	Kakizawa et al.	
6,386,789	B1	5/2002	Chausse et al.	
6,543,959	B1	4/2003	Jore	
6,813,614	B2	11/2004	Cordery	
7,195,247	B2	3/2007	Shu	
7,469,909	B2	12/2008	Strauch et al.	
9,067,266	B2	6/2015	Puzio et al.	
10,259,107	B2	4/2019	Wang	
2010/0054854	A1*	3/2010	Wang	B25B 15/001 403/322.2
2017/0014979	A1*	1/2017	Su	B25B 23/0021
2018/0178357	A1*	6/2018	Su	B25B 23/0021
2018/0200871	A1*	7/2018	Shyu	B25B 13/462
2018/0207775	A1*	7/2018	Huang	F16B 21/165

* cited by examiner


Primary Examiner — David B. Thomas

(74) *Attorney, Agent, or Firm* — Michael Best & Friedrich LLP

(57) **ABSTRACT**

A lockable adapter is configured to couple a drive socket to a tool. The lockable adapter includes a body defining a longitudinal axis. The body is configured to couple the lockable adapter to the tool. The lockable adapter includes a sleeve moveably coupled relative to the body along the longitudinal axis of the body between a first position and a second position. The sleeve is configured to interface with the drive socket to support the drive socket on the sleeve. The lockable adapter includes a collar moveable relative to the sleeve. The sleeve moves into the second position configured to lock the drive socket to the sleeve in response to inserting the drive socket onto the sleeve. The sleeve moves into the first position configured to allow removal of the drive socket from the sleeve in response to moving the collar relative to the sleeve.

20 Claims, 4 Drawing Sheets







FIG. 1






FIG. 3




FIG. 4

LOCKABLE DRIVE SOCKET ADAPTER

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 16/505,900 filed Jul. 9, 2019, now U.S. Pat. No. 11,179,831, which claims priority to U.S. Provisional Patent Application No. 62/696,373 filed Jul. 11, 2018, the entire contents of both of which are hereby incorporated by reference.

BACKGROUND

The present application relates to a drive socket adapter that selectively couples a drive socket or the like to a power tool.

SUMMARY

In one aspect, a lockable adapter is configured to couple a drive socket to a tool. The lockable adapter includes a body defining a longitudinal axis. The body is configured to couple the lockable adapter to the tool. The lockable adapter includes a sleeve moveably coupled relative to the body along the longitudinal axis of the body between a first position and a second position and a retaining member coupled to the sleeve. The retaining member is positionable in a retracted position when the sleeve is in the first position. The retaining member is positionable in an extended position when the sleeve is in the second position. The lockable adapter is configured to secure the drive socket relative to the sleeve when the retaining member is in the extended position. The lockable adapter is configured to allow removal of the drive socket from the sleeve when the retaining member is in the retracted position.

In another aspect, a lockable adapter is configured to couple a drive socket to a tool. The lockable adapter includes a body defining a longitudinal axis. The body is configured to couple the lockable adapter to the tool. The lockable adapter includes a sleeve moveably coupled relative to the body along the longitudinal axis of the body between a first position and a second position. The sleeve is configured to interface with the drive socket to support the drive socket on the sleeve. The lockable adapter includes a collar moveable relative to the sleeve. The sleeve moves into the second position configured to lock the drive socket to the sleeve in response to inserting the drive socket onto the sleeve. The sleeve moves into the first position configured to allow removal of the drive socket from the sleeve in response to moving the collar relative to the sleeve.

In yet another aspect, a method of operating a lockable adapter with the lockable adapter including a body selectively coupled to a tool, a sleeve moveable relative to the body, and a collar moveable relative to the sleeve includes inserting a drive socket onto the sleeve, moving the lockable adapter into a locked state in which the drive socket is secured to the sleeve in response to inserting the drive socket onto the sleeve, and moving the lockable adapter into an unlocked state in which the drive socket is allowed to be removed from the sleeve in response to moving the collar relative to the sleeve.

Other aspects of the invention will become apparent by consideration of the detailed description and accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a lockable drive socket adapter according to one embodiment of the invention, the lockable drive socket adapter coupled to a power tool.

FIG. 2 is an exploded view of the lockable drive socket adapter.

FIG. 3 is a cross-sectional view of the lockable drive socket adapter along line 3-3 of FIG. 1 when the lockable drive socket adapter is in a locked position.

FIG. 4 is a cross-sectional view of the lockable drive socket adapter along line 3-3 of FIG. 1 when the lockable drive socket adapter is in an unlocked position.

Before any embodiments of the invention are explained in detail, it is to be understood that the invention is not limited in its application to the details of construction and the arrangement of components set forth in the following description or illustrated in the following drawings. The invention is capable of other embodiments and of being practiced or of being carried out in various ways. Terms of degree, such as “substantially,” “about,” “approximately,” etc. are understood by those of ordinary skill to refer to reasonable ranges outside of the given value, for example, general tolerances associated with manufacturing, assembly, and use of the described embodiments.

DETAILED DESCRIPTION

FIG. 1 illustrates a lockable drive socket adapter 10 selectively coupled to a chuck 15 of a power tool 20. The illustrated power tool 20 is a power drill, but in other embodiments, the power tool 20 can be an impact drill or other rotary power tools. When the adapter 10 is coupled to the chuck 15, the power tool 20 is operable to move the adapter 10—and ultimately a drive socket 24 (FIG. 3) coupled to the adapter 10—about a rotational axis 25.

With reference to FIG. 2, the adapter 10 includes a shaft 30 having a longitudinal axis 35, a hexagonal drive portion or body 40 that engages the chuck 15 of the power tool 20, and a projection 45 extending from the body 40. In the illustrated embodiment, the body 40 includes an annular groove 50 adjacent an end 52 of the body 40 adapted to interface with the chuck 15 (e.g., a quick release chuck), allowing the adapter 10 to be quickly secured to or released from the chuck 15. In other embodiments, the groove 50 can be omitted. In some embodiments, at least a portion of the body 40 can be sized as a 1/4 inch hexagonal shank, a 7/16 inch hexagonal shank, and the like. The illustrated body 40 also includes a variable depth groove 55 (e.g., a stepped groove) having a first groove 60 with a first diameter D_1 (e.g., a first radial dimension; FIG. 3), a second groove 65 with a second diameter D_2 (e.g., a second radial dimension; FIG. 3), and a step 70 positioned between the first and second grooves 60, 65. The second groove 65 is positioned closer to the projection 45 than the first groove 60 in a direction along the longitudinal axis 35, and the first diameter D_1 is smaller than the second diameter D_2 . In other embodiments, the first and second grooves 60, 65 can be different sized apertures or detents on the shaft 30. In addition, the illustrated projection 45 of the shaft 30 is substantially cylindrical and includes a tip 75 having a step 78.

The illustrated adapter 10 also includes a sleeve 80 (e.g., a drive member) having a cavity 85 that receives a portion of the body 40 and the projection 45. With reference to FIG. 3, the cavity 85 includes a first portion 90 sized to receive the projection 45, a second portion 95 sized to receive a portion of the body 40, and a third portion 100 positioned

between the first and second portions **90**, **95**. In other embodiments, the sleeve **80** can include the first and second portions **90**, **95** and omit the third portion **100**. With reference back to FIG. **2**, inner walls of the sleeve **80** that form the second portion **95** are hexagonally shaped to match the hexagonal shape of the body **40**. As such, the sleeve **80** is inhibited from rotating relative to the shaft **30** about the longitudinal axis **35** when the body **40** is received within the second portion **95** of the cavity **85**.

With continued reference to FIG. **2**, the illustrated sleeve **80** also includes a drive protrusion **105** having a retaining aperture **110**, an annular groove **115**, and a pair of locking apertures **120** (only one aperture **120** is shown in FIG. **2**). In the illustrated embodiment, the drive protrusion **105** has a generally square cross-section such that the drive protrusion **105** may be referred to as a square drive protrusion. In some embodiments, the square drive protrusion **105** can be a $\frac{3}{8}$ inch square protrusion, a $\frac{1}{2}$ inch square protrusion, and the like. In the illustrated embodiment, the pair of locking apertures **120** are spaced 180 degrees relative to each other about the axis **35**. In other embodiments, the sleeve **80** can include one locking aperture **120** or more than two locking apertures **120**. Also, the illustrated annular groove **115** is positioned between the pair of locking apertures **120** and the square drive protrusion **105** in the direction along the longitudinal axis **35**. In other embodiments, the pair of locking apertures **120** can be positioned between the annular groove **115** and the square drive protrusion **105** in the direction along the longitudinal axis **35**.

With reference to FIGS. **2** and **3**, the illustrated adapter **10** further includes a collar **125** having a cavity **130** that receives portions of the sleeve **80** and the shaft **30**. The body **40** of the shaft **30** also extends through a rear collar aperture **140** of the collar **125**. In one embodiment, the collar aperture **140** can be hexagonally shaped to match the hexagonal shape of the shaft **30** so that the collar **125** is inhibited from rotating relative to the shaft **30** (and the sleeve **80**) about the longitudinal axis **35** and to inhibit dirt and debris from entering the cavity **130** between the shaft **30** and the collar **125**. The illustrated collar **125** includes a first annular groove **145** and a second annular groove **150** formed into an inner surface **155** of the collar **125**. In the illustrated embodiment, the grooves **145**, **150** extend 360 degrees around the inner surface **155**. In other embodiments, the grooves **145**, **150** can extend less than 360 degrees around the inner surface **155** (e.g., the grooves **145**, **150** can be discrete detents).

As best shown in FIGS. **3** and **4**, the collar **125** and the sleeve **80** are axially biased relative to each other along the longitudinal axis **35** by a first biasing member **160**. In the illustrated embodiment, the first biasing member **160** is a first coil spring. In other embodiments, the first biasing member **160** may include other types of spring elements. The sleeve **80** and the shaft **30** are axially biased relative to each other along the longitudinal axis **35** by a second biasing member **165**. In the illustrated embodiment, the second biasing member **165** is a second coil spring. In other embodiments, the second biasing member **165** may include other types of spring elements. In particular, the first biasing member **160** extends around the body **40** of the shaft **30** and contacts a bottom surface **170** of the collar **125** and a rear surface **175** of the sleeve **80** to bias the bottom surface **170** and the rear surface **175** away from each other. The second biasing member **165** extends around the projection **45** of the shaft **30** and contacts an inner wall **180** of the sleeve **80** and a front surface **185** of the body **40** to bias the inner wall **180** and the front surface **185** away from each other.

Locking members **190** are each received within one locking aperture **120** of the sleeve **80** and the variable depth groove **55** of the shaft **30** (FIGS. **3** and **4**). In the illustrated embodiment, the locking members **190** are ball bearings or locking spheres, but may alternatively be other types of suitable locking members. As discussed in more detail below, the locking members **190** can also be received within the first annular groove **145** of the collar **125** when the adapter **10** is in an unlocked state (FIG. **4**). Furthermore, a retaining member **195** is received within the retaining aperture **110** of the square drive protrusion **105**. In the illustrated embodiment, the retaining member **195** is a ball bearing or retaining sphere, but may alternatively be another type of suitable retaining member. The retaining aperture **110** is sized such that only a portion of the retaining member **195** can extend beyond a planar surface **196** (e.g., an outer surface) of the square drive protrusion **105** (as shown in FIG. **3**).

With continued reference to FIGS. **3** and **4**, a retaining ring **200** is axially fixed within the annular groove **115** of the sleeve **80**, but is axially moveable within the second annular groove **150** of the collar **125**. As such, the retaining ring **200** restricts axially movement of the collar **125** relative to the sleeve **80** by the retaining ring **200** abutting ends of the second annular groove **150**.

FIG. **3** illustrates a locked state of the adapter **10**. In the locked state, the drive socket **24** is secured to the square drive protrusion **105** to inhibit the drive socket **24** from being removed from the adapter **10**. In particular, the retaining member **195** is in contact with an outer surface **202** of the projection **45** for the shaft **30** to position the portion of the retaining member **195** beyond the planar surface **196** (FIG. **2**) of the square drive protrusion **105**. As such, the portion of the retaining member **195** is received within a groove **204** of the drive socket **24** to inhibit the drive socket **24** from sliding off and being removed from the square drive protrusion **105**. Also in the locked state, the sleeve **80** is axially locked relative to the shaft **30** to maintain the portion of the retaining member **195** above the planar surface **196** of the square drive protrusion **105**. Specifically, a portion of the inner surface **155** of the collar **125** engages the locking members **190** to locate the locking members **190** within the first groove **60** of the variable depth groove **55** (e.g., the locking members **190** are captured between the inner surface **155**, the corresponding locking aperture **120**, and the first groove **60**). Consequently, the sleeve **80** is axially locked relative to the shaft **30** as axial movement of the sleeve **80** (e.g., in a forward direction **205** away from the end **52** of the shaft **30**) is blocked by walls of the locking apertures **120** pushing (via the biasing force of the second biasing member **165**) the locking members **190** against the step **70**. As such, the second biasing member **165** is in a compressed configuration between the sleeve **80** and the shaft **30** when the adapter **10** is in the locked state. Furthermore in the locked state, the first biasing member **160** biases the collar **125** in a rearward direction opposite the forward direction **205** such that the retaining ring **200** engages a forward end of the second annular groove **150**.

To move the adapter **10** from the locked state (FIG. **3**) to the unlocked state (FIG. **4**), allowing the drive socket **24** to be removed from the adapter **10**, the collar **125** is axially moved relative to the shaft **30** in the forward direction **205**. This movement allows the first annular groove **145** of the collar **125** to align with the locking members **190**, creating enough clearance for the locking members **190** to move radially outward and away from the first groove **60** of the variable depth groove **55**. For example, the collar **125** is

5

moved into a position where the first groove **60**, the locking apertures **120**, and the first annular groove **145** radially align with each other. Thereafter, the sleeve **80** and the shaft **30** are axially unlocked relative to each other, allowing the biasing force of the second biasing member **165** to be released to push the sleeve **80** in the forward direction **205** relative to the shaft **30**. Consequently, the locking members **190** are pushed over the step **70** to be positioned within the second groove **65** and within the first annular groove **145** by the movement of the sleeve **80**. In addition, the retaining aperture **110** radially aligns with the tip **75** of the shaft **30**. This allows enough clearance for the retaining member **195** to partially move into the first cavity **90** of the sleeve **80**, leaving little to no portion of the retaining member **195** extending beyond the planar surface **196** of the square drive protrusion **105** (FIG. 4). Accordingly, the drive socket **24** can slide off and be removed from the square drive protrusion **105**.

To again couple the drive socket **24** to the adapter **10**, the adapter **10** is positioned within the unlocked state (FIG. 4) and the drive socket **24** is slid onto the square drive protrusion **105**. Eventually, a rear edge of the drive socket **24** comes into contact with a flange **210** of the sleeve **80**, causing the drive socket **24** to push the sleeve **80** in the rearward direction. Such movement of the sleeve **80** and the drive socket **24** also radially moves the retaining member **195** relative to the retaining aperture **110**. In particular, the movement of the sleeve **80** relative to the shaft **30** in the rearward direction causes the sleeve **80** to push the retaining member **195** against the step **78** of the shaft **30** for the retaining member **195** to ride up onto the outer surface **202** of the projection **45**. As such, the portion of the retaining member **195** extends beyond the outer surface **202** of the square drive protrusion **105** to be received within the groove **204** of the drive socket **24**, as illustrated in FIG. 3.

With continued movement of the sleeve **80** and the drive socket **24** in the rearward direction (against the biasing force of the second biasing member **165**), the sleeve **80** pushes the locking members **190** out of the second groove **65** and back toward the first groove **60**. The collar **125** also moves with the sleeve **80** in the rearward direction by the biasing force of the first biasing member **160** (e.g., a portion of the locking members **190** positioned within the first annular groove **145** maintains radial alignment of the locking apertures **120** and the first annular groove **145**). Eventually, the first annular groove **145**, the locking apertures **120**, and the first groove **60** of the shaft **30** come into radial alignment, allowing the locking members **190** to be received within the first groove **60**. To then relock the adapter **10** (FIG. 3), the sleeve **80** is further moved in the rearward direction by the drive socket **24** for an edge **215** (FIG. 4) of the first annular groove **145** to push the locking members **190** into the first groove **60**, allowing the inner surface **155** of the collar **125** to slide over the locking members **190** and position the adapter **10** in the locked state.

As such, the drive socket **24** can be coupled to the adapter **10** through single-handed operation (e.g., simply by pushing the drive socket **24** onto the drive protrusion **105**), without requiring a user to manually manipulate the sleeve **80** or the collar **125**. In other words, the drive socket **24** is automatically locked to the adapter **10** by simply inserting the drive socket **24** onto the adapter **10**. The adapter **10** remains biased in the locked state (FIG. 3) until the collar **125** is manually actuated to bias the sleeve **80** forward. The adapter **10** then remains biased in the unlocked state (FIG. 4) until the drive socket **24** is pushed onto the sleeve **80**. In other embodiments, the drive member **80** can be a socket that receives a

6

drive member (e.g., a screwdriver bit, etc.) to couple the drive member to the power tool **20** with the lockable adapter **10** actuated in a similar manner as described above to lock or unlock the drive member to the adapter **10**.

Although the invention has been described in detail with reference to certain preferred embodiments, variations and modifications exist within the scope and spirit of one or more independent aspects of the invention as described. Various features and advantages of the disclosure are set forth in the following claims.

The invention claimed is:

1. A lockable adapter configured to couple a drive socket to a tool, the lockable adapter comprising:

a body defining a longitudinal axis, the body configured to couple the lockable adapter to the tool;

a sleeve moveably coupled relative to the body along the longitudinal axis of the body between a first position and a second position;

a retaining member coupled to the sleeve, the retaining member positionable in a retracted position when the sleeve is in the first position, the retaining member positionable in an extended position when the sleeve is in the second position; and

a collar including a cavity that receives a portion of the sleeve and a portion of the body, wherein the collar is in a first position relative to the sleeve when the retaining member is in the retracted position, wherein the collar is in a second position relative to the sleeve when the retaining member is in the extended position, wherein the lockable adapter is configured to secure the drive socket relative to the sleeve when the retaining member is in the extended position, and wherein the lockable adapter is configured to allow removal of the drive socket from the sleeve when the retaining member is in the retracted position.

2. The lockable adapter of claim 1, wherein the sleeve includes a square drive protrusion, wherein a portion of the retaining member extends from the square drive protrusion when the retaining member is in the extended position, and wherein the square drive protrusion is configured to be received within the drive socket to secure the drive socket on the square drive protrusion when the retaining member is in the extended position.

3. The lockable adapter of claim 1, wherein the sleeve includes an aperture that receives a locking member to locate the locking member between the collar and the body, and wherein the body includes a variable depth groove that receives the locking member.

4. The locking adapter of claim 3, wherein the variable depth groove includes a first groove having a first radial dimension and a second groove having a second radial dimension different than the first radial dimension, wherein the locking member is received within the first groove when the sleeve is in the second position, and wherein the locking member is received within the second groove when the sleeve is in the first position.

5. The locking adapter of claim 4, wherein the first radial dimension is less than the second radial dimension.

6. The locking adapter of claim 1, wherein a biasing member is positioned between the collar and the sleeve to hold the sleeve in the second position.

7. The lockable adapter of claim 1, further comprising a biasing member positioned between the body and the sleeve, wherein the biasing member holds the sleeve in the first position.

8. A lockable adapter configured to couple a drive socket to a tool, the lockable adapter comprising:

7

a body defining a longitudinal axis, the body configured to couple the lockable adapter to the tool;

a sleeve moveably coupled relative to the body along the longitudinal axis of the body between a first position and a second position, the sleeve configured to interface with the drive socket to support the drive socket on the sleeve; and

a collar moveable relative to the sleeve, wherein the sleeve moves into the second position configured to lock the drive socket to the sleeve in response to inserting the drive socket onto the sleeve, and wherein the sleeve moves into the first position configured to allow removal of the drive socket from the sleeve in response to moving the collar relative to the sleeve.

9. The lockable adapter of claim 8, further comprising a first biasing member positioned between the collar and the sleeve, wherein the first biasing member holds the sleeve in the second position.

10. The lockable adapter of claim 9, further comprising a second biasing member positioned between the body and the sleeve, wherein the second biasing member holds the sleeve in the first position.

11. The lockable adapter of claim 8, wherein the sleeve includes an aperture that receives a locking member to locate the locking member between the collar and the body, and wherein the body includes a variable depth groove that receives the locking member.

12. The locking adapter of claim 11, wherein the variable depth groove includes a first groove having a first radial dimension and a second groove having a second radial dimension different than the first radial dimension, wherein the locking member is received within the first groove when the sleeve is in the second position, and wherein the locking member is received within the second groove when the sleeve is in the first position.

13. The locking adapter of claim 12, wherein the first radial dimension is less than the second radial dimension.

14. The lockable adapter of claim 8, wherein the sleeve includes a square drive protrusion configured to be received within the drive socket.

15. The lockable adapter of claim 14, further comprising a retaining member supported by the square drive protrusion, wherein a projection extending from the body engages the retaining member such that a portion of the retaining member protrudes beyond a surface of the square drive protrusion when the sleeve is in the second position.

8

16. A method of operating a lockable adapter, the lockable adapter including a body selectively coupled to a tool, a sleeve moveable relative to the body, and a collar moveable relative to the sleeve, the method comprising:

inserting a drive socket onto the sleeve;

moving the lockable adapter into a locked state in which the drive socket is secured to the sleeve in response to inserting the drive socket onto the sleeve; and

moving the lockable adapter into an unlocked state in which the drive socket is allowed to be removed from the sleeve in response to moving the collar relative to the sleeve.

17. The method of claim 16, wherein moving the lockable adapter into the locked state further includes moving the sleeve relative to the body toward the tool in response to inserting the drive socket onto a square drive protrusion of the sleeve.

18. The method of claim 16, wherein moving the lockable adapter into the unlocked state further includes moving the collar relative to the sleeve away from the tool.

19. The method of claim 18, further comprising biasing the sleeve away from the tool by a biasing member such that the lockable adapter is held in the unlocked position.

20. A lockable adapter configured to couple a drive socket to a tool, the lockable adapter comprising:

a body defining a longitudinal axis, the body configured to couple the lockable adapter to the tool;

a sleeve moveably coupled relative to the body along the longitudinal axis of the body between a first position and a second position;

a retaining member coupled to the sleeve, the retaining member positionable in a retracted position when the sleeve is in the first position, the retaining member positionable in an extended position when the sleeve is in the second position; and

a collar including a cavity that receives a portion of the sleeve and a portion of the body, wherein a biasing member is positioned between the collar and the sleeve to hold the sleeve in the second position,

wherein the lockable adapter is configured to secure the drive socket relative to the sleeve when the retaining member is in the extended position, and wherein the lockable adapter is configured to allow removal of the drive socket from the sleeve when the retaining member is in the retracted position.

* * * * *