



(12) **United States Patent**
Speight

(10) **Patent No.:** **US 11,729,747 B2**
(45) **Date of Patent:** ***Aug. 15, 2023**

(54) **SCHEDULING TRANSMISSIONS ON CHANNELS IN A WIRELESS NETWORK**

(71) Applicant: **Intellectual Ventures II LLC**,
Wilmington, DE (US)

(72) Inventor: **Timothy J. Speight**, Bristol (GB)

(73) Assignee: **Intellectual Ventures II LLC**,
Wilmington, DE (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **17/712,893**

(22) Filed: **Apr. 4, 2022**

(65) **Prior Publication Data**

US 2022/0232533 A1 Jul. 21, 2022

Related U.S. Application Data

(63) Continuation of application No. 17/181,417, filed on Feb. 22, 2021, now Pat. No. 11,297,605, which is a (Continued)

(51) **Int. Cl.**
H04W 72/04 (2009.01)
H04L 47/10 (2022.01)
(Continued)

(52) **U.S. Cl.**
CPC *H04W 72/04* (2013.01); *H04L 47/10* (2013.01); *H04L 47/2425* (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC H04W 72/04; H04L 47/10
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,274,625 A 12/1993 Derby et al.
5,566,175 A 10/1996 Davis

(Continued)

FOREIGN PATENT DOCUMENTS

EP 1 511 245 3/2005
WO 2002/098077 12/2002

(Continued)

OTHER PUBLICATIONS

“3rd Generation Partnership Project; Technical Specification Group Radio Access Network; UTRAN Overall Description (Release 7),” (Mar. 2006); 3GPP: Valbonne, France, TS 25.401 V7.0.0:1-48.

(Continued)


Primary Examiner — Zhiren Qin

(74) *Attorney, Agent, or Firm* — Volpe Koenig

(57) **ABSTRACT**

A user equipment (UE) is configured to receive, from a wireless network, information including a plurality of first values and queue limit information, wherein each of the plurality of first values is associated with at least one radio bearer. Further, the UE is configured to transmit a plurality of buffer occupancy indicators, wherein each buffer occupancy indicator is associated with at least one queue. The UE is further configured, in response to the transmitted plurality of buffer occupancy indicators, to receive, from the wireless network, an uplink resource allocation. The UE is determined, based on the received queue limit information, select a limited number of queues for providing data for transmission and to transmit the data based on the first value associated with the select queue of the selected limited number of queues in resources determined from the received uplink resource allocation.

20 Claims, 6 Drawing Sheets



Related U.S. Application Data

continuation of application No. 16/410,581, filed on May 13, 2019, now Pat. No. 10,932,232, which is a continuation of application No. 15/618,669, filed on Jun. 9, 2017, now Pat. No. 10,292,138, which is a continuation of application No. 15/131,250, filed on Apr. 18, 2016, now Pat. No. 9,681,466, which is a continuation of application No. 13/858,666, filed on Apr. 8, 2013, now Pat. No. 9,320,018, which is a continuation of application No. 13/212,843, filed on Aug. 18, 2011, now Pat. No. 8,428,026, which is a continuation of application No. 11/430,421, filed on May 8, 2006, now Pat. No. 8,005,041.

(51) **Int. Cl.**

H04L 47/2425 (2022.01)
H04L 47/30 (2022.01)
H04W 28/14 (2009.01)
H04W 8/04 (2009.01)
H04W 72/1268 (2023.01)
H04W 76/10 (2018.01)
H04W 8/24 (2009.01)
H04W 72/0453 (2023.01)

(52) **U.S. Cl.**

CPC *H04L 47/30* (2013.01); *H04W 8/04* (2013.01); *H04W 28/14* (2013.01); *H04W 72/1268* (2013.01); *H04W 8/24* (2013.01); *H04W 72/0453* (2013.01); *H04W 76/10* (2018.02)

(56)

References Cited

U.S. PATENT DOCUMENTS

5,742,592	A	4/1998	Scholefield et al.	
6,067,301	A	5/2000	Aatresh	
6,078,959	A	6/2000	Wright et al.	
6,157,614	A	12/2000	Pasternak et al.	
6,347,091	B1 *	2/2002	Wallentin	H04W 28/18 370/464
6,374,112	B1	4/2002	Widegren et al.	
6,661,777	B1	12/2003	Blanc et al.	
6,668,175	B1	12/2003	Almgren et al.	
6,690,646	B1 *	2/2004	Fichou	H04Q 11/0478 370/395.1
6,834,053	B1	12/2004	Stacey et al.	
6,845,100	B1	1/2005	Rinne	
6,850,540	B1 *	2/2005	Peisa	H04L 47/32 370/468
6,934,250	B1	8/2005	Kejriwal et al.	
7,127,250	B2	10/2006	Gallagher et al.	
7,142,548	B2	11/2006	Fong et al.	
7,292,552	B2	11/2007	Willenegger et al.	
7,372,842	B2	5/2008	Kim et al.	
7,394,765	B2	7/2008	Yi et al.	
7,512,065	B1	3/2009	Phadnis et al.	
7,551,637	B2	6/2009	Damnjanovic et al.	
7,555,010	B2	6/2009	Chun et al.	
7,623,869	B2	11/2009	Lee et al.	
7,630,338	B2	12/2009	Vesterinen et al.	
7,801,105	B2	9/2010	Larsson et al.	
7,807,970	B2	10/2010	Richard	
7,869,461	B2	1/2011	Lohr et al.	
7,912,471	B2	3/2011	Kodikara Patabandi et al.	
7,944,935	B2	5/2011	Bucknell et al.	
7,948,936	B2	5/2011	Lohr et al.	
8,175,039	B2	5/2012	Heo et al.	
9,320,018	B2	4/2016	Speight	
9,681,466	B2	6/2017	Speight	
10,292,138	B2	5/2019	Speight	
2003/0117964	A1	6/2003	Chen et al.	
2003/0123392	A1	7/2003	Ruutu et al.	

2003/0128665	A1	7/2003	Bernhard et al.	
2003/0147371	A1	8/2003	Choi et al.	
2003/0156578	A1	8/2003	Bergenlid et al.	
2003/0169746	A1	9/2003	Kitazawa et al.	
2004/0064467	A1	4/2004	Kola et al.	
2004/0071086	A1 *	4/2004	Haumont	H04Q 3/0091 370/328
2004/0090917	A1 *	5/2004	Ruutu	H04L 9/40 370/235
2004/0090974	A1	5/2004	Balakrishnan et al.	
2004/0114574	A1 *	6/2004	Zeira	H04L 1/0002 370/352
2004/0160914	A1	8/2004	Sarkar	
2004/0170179	A1	9/2004	Johansson et al.	
2004/0210619	A1	10/2004	Balachandran et al.	
2005/0020313	A1	1/2005	Chae et al.	
2005/0047416	A1	3/2005	Heo et al.	
2005/0052997	A1	3/2005	Montes Linares	
2005/0063392	A1	3/2005	Ofuji et al.	
2005/0111398	A1	5/2005	Wybenga et al.	
2005/0174965	A1	8/2005	Sarkkinen et al.	
2006/0018277	A1 *	1/2006	Petrovic	H04L 47/30 370/329
2006/0019671	A1	1/2006	Chemiakina et al.	
2006/0062171	A1	3/2006	Baiamonte et al.	
2006/0088058	A1 *	4/2006	Eckert	H04L 47/50 370/469
2006/0092972	A1	5/2006	Petrovic et al.	
2006/0187844	A1	8/2006	Chun et al.	
2006/0215612	A1	9/2006	Chemiakina et al.	
2006/0242319	A1	10/2006	Sang et al.	
2007/0115915	A1	5/2007	Sheng et al.	
2007/0121542	A1 *	5/2007	Lohr	H04L 47/50 370/395.21
2007/0133411	A1	6/2007	Bosch et al.	
2007/0258433	A1	11/2007	Speight	
2007/0275728	A1	11/2007	Lohr et al.	
2007/0297360	A1	12/2007	Joachim et al.	
2008/0212524	A1	9/2008	Niwano	
2008/0254804	A1	10/2008	Lohr et al.	
2010/0322075	A1	12/2010	Sindhu et al.	
2012/0033578	A1 *	2/2012	Anderson	H04W 52/20 370/252
2016/0135075	A1	5/2016	Wigren et al.	

FOREIGN PATENT DOCUMENTS

WO	2003/049320	6/2003
WO	2003/085903	10/2003
WO	2005/034542	4/2005
WO	2006/037492	4/2006

OTHER PUBLICATIONS

“3rd Generation Partnership Project; Technical Specification Group Services and System Agenda; General Packet Radio Service (GPRS); Service Description; Stage 2 (Release 7),” (Mar. 2006), 3GPP: Valbonne, France, TS 23.060 V7.0.0:1-212.
 3GPP TS 23.107 v6.1.0 (Mar. 2004) “Technical Specification Group Services and System Aspects; Quality of Service (QoS) concepts and Architecture,” filed in *Sprint Spectrum L.P. et al. v. Intellectual Ventures II LLC*, Case No. IPR2018-01765 (P.T.A.B), Exhibit 1009, filed Sep. 20, 2018; 41 pages.
 3GPP TS 25.990 v3.0.0 (Oct. 1999), filed in *Ericsson Inc. and Telefonaktiebolaget LAI Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01185 (P.T.A.B), Exhibit 1012, filed May 31, 2018; 20 pages.
 Chinese first Office Action (including translation) dated Apr. 2, 2001 from Chinese Patent Application No. 200780021662.5.
 Communication pursuant to Article 94(3) EPC from European Application No. 07 728 609.4-2412 dated Apr. 9, 2010.
 Communication pursuant to Article 94(3) EPC from European Application No. 07 728 609.4-2412 dated Jul. 31, 2009.
 CV of Anthony Acampora, filed in *Ericsson Inc. and Telefonaktiebolaget LM Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01289 (P.T.A.B), Exhibit 1002, filed Jun. 20, 2018; 52 pages.

(56)

References Cited

OTHER PUBLICATIONS

Declaration of Andrew Singer, Ph.D., filed in *Sprint Spectrum L.P. et al. v. Intellectual Ventures II LLC*, Case No. IPR2018-011765 (P.T.A.B), Exhibit 1003, filed Sep. 20, 2018; 118 pages.

Defendant Alcatel-Lucent USA, Inc.'s Answer and Affirmative Defense [33], filed by *Intellectual Ventures II, LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662, filed Dec. 7, 2017; 58 pages.

Defendants' Unopposed Motion for Leave to Amend Invalidity Contentions [153], filed *Intellectual Ventures II LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662, Jun. 28, 2018; 6 pages.

Design of Call Control Signaling in Wireless ATM Networks by Loukas et al. ("Loukas"), filed in *Ericsson Inc. and Telefonaktiebolaget LAI Ericsson v. Intellectual Ventures II LLC*. Case No. IPR2018-01185 (P.T.A.B), Exhibit 1008, filed May 31, 2016; 6 pages.

File History for the 9,681,466 Patent, filed in *Sprint Spectrum L.P. et al. v. Intellectual Ventures II LLC*, Case No. IPR2018-01765 (P.T.A.B), Exhibit 1002, filed Sep. 20, 2018; 161 pages.

Holma, H. ed. et al., (2001) WCDMA for UMTS, Wiley & Sons, ISBN-0471486876.

IEEE 100, The Authoritative Dictionary of IEEE Standards, 7th Ed., Standards Information Network, IEEE Press, The Institute of Electrical and Electronics Engineering, New York, NY, 2000, filed in *Ericsson Inc. and Telefonaktiebolaget LM Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01289 (P.T.A.B), Exhibit 2002, filed Sep. 5, 2018; 5 pages.

IV's Brief in Opposition to the T-Mobile and Sprint Defendants' Motion to Dismiss, filed in *Intellectual Ventures II LLC v. Sprint Spectrum L.P. et al.*, 2:17-cv-662, Dirt. 59 (E.D. Tex, Jan. 5, 2018), filed in *Sprint Spectrum L.P. et al. v. Intellectual Ventures II LLC*, Case No. IPR2018-01764 (P.T.A.B), Exhibit 1010, filed Sep. 20, 2018; 37 pages.

IV's Infringement Contentions, Exhibit G, filed in *Intellectual Ventures II LLC v. Sprint Spectrum L.P. et al.*, 2:17-cv-662. Dkt. 59 (E.D. Tex, Jan. 5, 2018), filed in *Sprint Spectrum L.P. et al. v. Intellectual Ventures II LLC*, Case No. IPR2018-01764 (P.T.A.B), Exhibit 1011, filed Sep. 20, 2018; 64 pages.

Korean Preliminary Office Action (translation) dated Sep. 20, 2010 from Korean Patent Application No. 10-2008-702945.

Moldy, M. et al. (1992) The GSM System for Mobile Communications, Bay Foreign Language Books, ISBN-2950701997.

The T-Mobile and Sprint Defendants' Motion to Dismiss [20], filed in *Intellectual Ventures II LLC v. T-Mobile USA, Inc. f/k/a MetroPCS Communications, Inc. et al.*, Case No. TXED-2-17-cv-00661, filed Dec. 7, 2017; 36 pages.

U.S. Appl. No. 60/792,012 to Vincent Park entitled "Method and Apparatus for Static Quality of Service" ("Park Provisional"), filed in *Sprint Spectrum L.P. et al. v. Intellectual Ventures II LLC*, Case No. IPR2018-01765 (P.T.A.B), Exhibit 1007, filed Sep. 20, 2018; 54 pages.

U.S. Appl. No. 60/792,012 to Vincent Park entitled "Method and Apparatus for Static Quality of Service" ("Park Provisional"), filed in *Sprint Spectrum L.P. et al. v. Intellectual Ventures II LLC*, Case No. IPR2018-01764 (P.T.A.B), Exhibit 1007, filed Sep. 20, 2018; 54 pages.

Updated Docket History, *Intellectual Ventures II LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662. filed Sep. 21, 2017; 11 pages.

Updated Docket History, *Intellectual Ventures II LLC v. T-Mobile UV, Inc. f/k/a MetroPCS Communications, Inc. et al.*, Case No. TXED-2-17-cv-00661, filed Sep. 21, 2017, dismissed Jun. 24, 2019; 5 pages.

UTRAN Overall Description, Release 7, 3rd Generation Partnership Project, Technical Specification Group Radio Access Network, 2006, filed in *Ericsson Inc. and Telefonaktiebolaget LM Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01185 (P.T.A.B), Exhibit 2004, filed Sep. 5, 2018; 48 pages.

Zhang, H. (Oct. 1995) "Service disciplines for guaranteed performance service in packet-switching networks," Proceedings of the IEEE, 83(10):1374-1396.

"3rd Generation Partnership Project; Technical Specification Group Radio Access Network; UTRAN Overall Description (Release 7)," (Mar. 2006); 3GPP: Valbonne, France, TS 25.401 V7.0.0:1-48, cited by other.

"An Introduction to Broadband Networks: LANs, MANs, ATM, BISDN, and Optical Networks for Integrated Multimedia Telecommunications," by Tony Acampora ("Acampora text"), filed in *Ericsson Inc. and Telefonaktiebolaget La'! Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01185 (P.T.A.B), Exhibit 1015, filed May 31, 2018; 51 pages.

"An Introduction to Broadband Networks: LANs, MANs, ATM, BISDN, and Optical Networks for integrated Multimedia Telecommunications," by Anthony S. Acampora ("Acampora text"), filed in *Ericsson Inc. and Telefonaktiebolaget LM Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01289 (P.T.A.B), Exhibit 1010, filed Jun. 20, 2018; 51 pages.

"3rd Generation Partnership Project; Technical Specification Group Services and System Agenda; General Packet Radio Service (GPRS); Service Description; Stage 2 (Release 7)," (Mar. 2006), 3GPP: Valbonne, France, TS 23.060 V7.0.0:1-212, cited by other.

3GPP TS 21.905 v6.0.0 (Sep. 2002), filed in *Ericsson Inc. and Telefonaktiebolaget LM Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01185 (P.T.A.B), Exhibit 1013, filed May 31, 2018; 51 pages.

3GPP TS 23.107 v6.1.0 (Mar. 2004) "Technical Specification Group Services and System Aspects; Quality of Service (QoS) concepts and Architecture," filed in *Sprint Spectrum L.P. et al. v. Intellectual Ventures II LLC*, Case No. IPR2018-01764 (P.T.A.B), Exhibit 1009, filed Sep. 20, 2018; 41 pages.

3GPP TS 23.107 v6.1.0 (Mar. 2004)—Technical Specification Group Services and System Aspects; Quality of Service (QoS) concepts and Architecture, filed in *Sprint Spectrum L.P. et al. v. Intellectual Ventures II LLC*, Case No. IPR2018-01765 (P.T.A.B), Exhibit 1009, filed Sep. 20, 2018; 41 pages.

3GPP TS 25.401 v7.0.0 (Mar. 2006), filed in *Ericsson Inc. and Telefonaktiebolaget LM Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01185 (P.T.A.B), Exhibit 1011, filed May 31, 2018; 48 pages.

3GPP TS 25.990 v3.0.0 (1999-10), filed in *Ericsson Inc. and Telefonaktiebolaget Lai Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01185 (P.T.A.B), Exhibit 1012, filed May 31, 2018; 20 pp.

American Honda Motor Co., Inc. v. Intellectual Ventures II LLC, Declaration of Stephen B. Wicker, Case No. IPR 2023-00020, U.S. Pat. No. 10,292,138 (Oct. 6, 2022).

American Honda Motor Co., Inc. v. Intellectual Ventures II LLC, Declaration of Stephen B. Wicker, Case No. IPR 2022-01521, U.S. Pat. No. 9,681,466 (Sep. 8, 2022).

American Honda Motor Co., Inc. v. Intellectual Ventures II LLC, Patent Owner's Preliminary Response, Case No. IPR 2022-01521, U.S. Pat. No. 9,681,466 (Dec. 28, 2022).

American Honda Motor Co., Inc. v. Intellectual Ventures II LLC, Petition for Inter Partes Review of U.S. Pat. No. 10,292,138, Case No. IPR 2023-00020 (Oct. 6, 2022).

American Honda Motor Co., Inc. v. Intellectual Ventures II LLC, Petition for Inter Partes Review of U.S. Pat. No. 9,681,466, Case No. IPR 2022-01521 (Sep. 9, 2022).

Chinese first Office Action (including translation) dated Apr. 2, 2001 from Chinese Patent Application No. 200780021662.5, cited by other.

Communication pursuant to Article 94(3) EPC from European Application No. 07 728 609.4-2412 dated Apr. 9, 2010, cited by other.

Communication pursuant to Article 94(3) EPC from European Application No. 07 728 609.4-2412 dated Jul. 31, 2009, cited by other.

Complaint [1], filed by Intellectual Ventures II, LLC, filed in *Intellectual Ventures II LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662, filed Sep. 21, 2017; 44 pages.

(56)

References Cited

OTHER PUBLICATIONS

Complaint [1], filed in *Intellectual Ventures II LLC v. T-Mobile USA, Inc. f/k/a MetroPCS Communications, Inc. et al.*, Case No. TXED-2-17-cv-00661, filed Sep. 21, 2017; 43 pages.

CV of Anthony Acampora, filed in *Ericsson Inc. and Telefonaktiebolaget LM Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01289 (P.T.A.B), Exhibit 1002, filed Jun. 20, 2018; 52 pages.

CV of Tony Acampora, filed in *Ericsson Inc. and Telefonaktiebolaget LAI Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01185 (P.T.A.B), Exhibit 1002, filed May 31, 2018; 52 pages.

Decision, filed in *Ericsson Inc. and Telefonaktiebolaget LM Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01185 (P.T.A.B), Paper 7, filed Dec. 3, 2018; 25 pages.

Declaration of Andrew Singer, Ph.D., filed in *Sprint Spectrum L.P. et al. v. Intellectual Ventures II LLC*, Case No. IPR2018-01765 (P.T.A.B), Exhibit 1003, filed Sep. 20, 2018; 118 pages.

Declaration of Andrew Singer, Ph.D., filed in *Sprint Spectrum L.P. et al. v. Intellectual Ventures II LLC*, Case No. IPR2018-01764 (P.T.A.B), Exhibit 1003, filed Sep. 20, 2018; 123 pages.

Defendant Alcatel-Lucent USA, Inc.'s Answer and Affirmative Defense [33], filed by Intellectual Ventures II, LLC, filed in *Intellectual Ventures II LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662, filed Dec. 7, 2017; 58 pages.

Defendants' Responsive Claim Construction Brief [194], filed in *Intellectual Ventures II LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662, filed Oct. 3, 2018; 36 pages.

Defendants' T-Mobile USA, Inc. and T-Mobile US, Inc. Notice of Joinder [27], filed in *Intellectual Ventures II LLC v. T-Mobile USA, Inc. f/k/a MetroPCS Communications, Inc. et al.*, Case No. TXED-2-17-CV-00661, filed Dec. 7, 2017; 2 pages.

Defendants' Unopposed Motion for Leave to Amend Invalidity Contentions [153], filed in *Intellectual Ventures II LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662, Jun. 28, 2018; 6 pages.

Design of Call Control signaling in Wireless ATM Networks by Loukas et al. ("Loukas"), filed in *Ericsson Inc. and Telefonaktiebolaget LAI Ericsson v. Intellectual Ventures II LLC*. Case No. IPR2018-01185 (P.T.A.B), Exhibit 1008, filed May 31, 2018; 6 pages.

Docket History, *Intellectual Ventures II LLC v. T-Mobile USA, Inc. f/k/a MetroPCS Communications, Inc. et al.*, Case No. TXED-2-17-cv-00661, filed Sep. 21, 2017; 3 pages.

Encyclopedia of Electronics (First Ed. 1985), filed in *Ericsson Inc. and Telefonaktiebolaget LM Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01289 (P.T.A.B), Exhibit 1013, filed Jun. 20, 2018; 4 pages.

Ericsson Inc. et al. v. Intellectual Ventures II LLC, Decision Denying Institution of Inter Partes Review, U.S. Pat. No. 9,682,466, Case No. 2018-01289 (Jan. 10, 2019).

Ericsson's Answer to IV's Complaint [201], filed in *Intellectual Ventures II LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662, filed Oct. 10, 2018; 62 pages.

Ericsson's Answer to IV's Complaint [202], filed in *Intellectual Ventures II LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662, filed Oct. 10, 2018; 56 pages.

Ericsson's Motion to Dismiss [22], filed in *Intellectual Ventures II LLC v. T-Mobile USA, Inc. f/k/a MetroPCS Communications, Inc. et al.*, Case No. TXED-2-17-cv-00661, filed Dec. 7, 2017; 15 pages.

Ericsson's Motion to Dismiss [28], filed in *Intellectual Ventures II LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662, filed Dec. 7, 2017; 15 pages.

Ericsson's Sur-Sur-reply [144], filed in *Intellectual Ventures II LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662, filed Jun. 11, 2018; 6 pages.

Exhibit A to P.R. 4-3 Joint Claim Construction and Prehearing Statement (filed in *Intellectual Ventures II LLC v. Sprint Spectrum L.P. et al.*, 2:17-cv-662, Mt 175-1 (E.D. Tex., Aug. 10, 2018)), filed in *Sprint Spectrum L.P. et al. v. Intellectual Ventures II LLC*, Case No. IPR2018-01764 (P.T.A.B), Exhibit 1014, filed Sep. 20, 2018; 9 pages.

Exhibit A to P.R. 4-3 Joint Claim Construction and Prehearing Statement, filed in *Intellectual Ventures II LLC v. Sprint Spectrum L.P. et al.*, 2:17-cv-662, Dkt. 175-1 (E.D. Tex., Aug. 10, 2018), filed in *Sprint Spectrum L.P. et al. v. Intellectual Ventures II LLC*, Case No. IPR2018-01765 (13 T A E3). Exhibit 1014, filed Sep. 20, 2018; 9 pages.

Expert Declaration of Anthony Acampora, filed in *Ericsson Inc. and Telefonaktiebolaget LM Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01289 (P.T.A.B), Exhibit 1003, filed Jun. 20, 2018; 99 pages.

Expert Declaration of Dr. Sylvia Hall-Ellis (exhibit previously filed as Exhibit 1014 in IPR2018-1185 with respect to U.S. Pat. 9,320,018), filed in *Ericsson Inc. and Telefonaktiebolaget LM Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01289 (P.T.A.B), Exhibit 1009, filed Jun. 20, 2018; 104 pages.

Expert Declaration of Dr. Sylvia Hall-Ellis, filed in *Ericsson Inc. and Telefonaktiebolaget LAI Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01185 (P.T.A.B), Exhibit 1014, filed May 31, 2018; 104 pages.

Expert Declaration of Tony Acampora, filed in *Ericsson Inc. and Telefonaktiebolaget LM Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01185 (P.T.A.B), Exhibit 1003, filed May 31, 2018; 100 pages.

File History for the '018 Patent, filed in *Sprint Spectrum L.P. et al. v. Intellectual Ventures II LLC*, Case No. IPR2018-01764 (P.T.A.B), Exhibit 1002, filed Sep. 20, 2018; 156 pages.

File History for the U.S. Pat. No. 9,681,466, filed in *Sprint Spectrum L.P. et al. v. Intellectual Ventures II LLC*, Case No. IPR2018-01765 (P.T.A.B), Exhibit 1002, filed Sep. 20, 2018; 161 pages.

File History for U.S. Appl. No. 11/718,492 to Joachim Lohr et al., entitled "HARQ Protocol Optimization for Packet Data Transmission," filed in *Sprint Spectrum L.P. et al. v. Intellectual Ventures II LLC*, Case No. IPR2018-01765 (P.T.A.B), Exhibit 1015, filed Sep. 20, 2018; 279 pages.

File History for U.S. Appl. No. 11/718,492 to Joachim Lohr et al., entitled "HARQ Protocol Optimization for Packet Data Transmission," filed in *Sprint Spectrum L.P. et al. v. Intellectual Ventures II LLC*, Case No. IPR2018-01764 (P.T.A.B), Exhibit 1015, filed Sep. 20, 2018; 279 pages.

File History' for U.S. Pat. No. 8,005,041, filed in *Sprint Spectrum L.P. et al. v. Intellectual Ventures II LLC*, Case No. IPR2018-01765 (P.T.A.B), Exhibit 1013, filed Sep. 20, 2018; 499 pages.

File History for U.S. Pat. No. 8,005,041, filed in *Sprint Spectrum L.P. et al. v. Intellectual Ventures II LLC*, Case No. IPR2018-01764 (P.T.A.B), Exhibit 1013, filed Sep. 20, 2018; 499 pages.

File History for U.S. Pat. No. 8,428,026, filed in *Sprint Spectrum L.P. et al. v. Intellectual Ventures II LLC*, Case No. IPR2018-01765 (P.T.A.B), Exhibit 1012, filed Sep. 20, 2018; 448 pages.

File History for U.S. Pat. No. 8,428,026, filed in *Sprint Spectrum L.P. et al. v. Intellectual Ventures II LLC*, Case No. IPR2018-01764 (P.T.A.B), Exhibit 1012, filed Sep. 20, 2018; 448 pages.

Final Rejection issued by USPTO, dated Nov. 30, 2009 for U.S. Appl. No. 11/430,421.

Holma, H. ed et al., (2001) WCDMA for UMTS, Wiley & Sons, ISBN-0471486876, cited by other.

IEEE 100, The Authoritative Dictionary of IEEE Standards, 7th Ed., Standards Information Network, IEEE Press, The Institute of Electrical and Electronics Engineering, New York, NY, 2000, filed in *Ericsson Inc. and Telefonaktiebolaget LM Ericsson v. Intellectual Ventures II LLC*, Case No. IPR.2018-01289 (P.T.A.B), Exhibit 2002, filed Oct. 19, 2018; 5 pages.

IEEE 100, The Authoritative Dictionary of IEEE Standards, 7th Ed., Standards Information Network, IEEE Press, The Institute of Electrical and Electronics Engineering, New York, NY, 2000, filed in *Ericsson Inc. and Telefonaktiebolaget LM Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01185 (P.T.A.B), Exhibit 2002, filed Sep. 5, 2018; 5 pages.

Improving Traffic Scheduling in Wireless ATM Networks by Nikos Passas et al. ("Passas-I"), filed in *Ericsson Inc. and Telefonaktiebolaget LM Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01185 (P.T.A.B), Exhibit 1004, filed May 31, 2018; 18 pages.

Improving Traffic Scheduling in Wireless ATM Networks by Nikos Passas et al. ("Passas-I"), filed in *Ericsson Inc. and Telefonaktiebolaget*

(56)

References Cited

OTHER PUBLICATIONS

LM Ericsson v. Intellectual Ventures II LLC, Case No. IPR2018-01289 (P.T.A.B). Exhibit 1004, filed Jun. 20, 2018; 18 pages.

Intellectual Ventures I LLC et al., v. General Motor Company et al., Memorandum in Support of Claim Construction Order, U.S. District Court for the Western District of Texas, Waco Division, 6:21-CV-1088-ADA (Dec. 1, 2022).

Intellectual Ventures I LLC et al., v. Honda Motor Company Ltd. et al., Complaint for Patent Infringement, U.S. District Court for the Northern District of Texas Dallas Division, No. 3:22-cv-761 (April 4, 2022).

Intellectual Ventures I LLC et al., v. Toyota Motor Corp. et al., Complaint for Patent Infringement, U.S. District Court, Eastern District of Texas, Marshall Division, No. 2:21-cv-389 (Oct. 19, 2021).

Intellectual Ventures I LLC et al., v. Toyota Motor Corp. et al., Plaintiffs' Disclosure of Preliminary Infringement Contentions, U.S. District Court, Eastern District of Texas, Marshall Division, No. 2:21-cv-389 (Mar. 2, 2022).

Intellectual Ventures II LLC v. Sprint Spectrum L.P. et al., Claim Construction Memorandum Opinion and Order, U.S. District Court, Eastern District of Texas, Marshall Division, No. 2:17-cv-662-JRG-RSP (Nov. 16, 2018).

Intellectual Ventures II LLC's Answer to Alcatel-Lucent USA, Inc.'s Counterclaims [54], filed in *Intellectual Ventures II LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662, filed Dec. 29, 2017; 7 pages.

IV's Brief in Opposition to the T-Mobile and Sprint Defendants' Motion to Dismiss, filed in *Intellectual Ventures II LLC v. Sprint Spectrum L.P. et al.*, 2:17-cv-662, Dirt. 59 (E.D. Tex., Jan. 5, 2018), filed in *Sprint Spectrum L.P. et al. v. Intellectual Ventures II LLC*, Case No. IPR2018-01765 (P.T.A.B), Exhibit 1010, filed Sep. 20, 2018; 37 pages.

IV's Brief in Opposition to the T-Mobile and Sprint Defendants' Motion to Dismiss, filed in *Intellectual Ventures II LLC v. Sprint Spectrum L.P. et al.*, 2:17-cv-662, (E.D. Tex., Jan. 5, 2018), filed in *Sprint Spectrum L.P. et al. v. Intellectual Ventures II LLC*, Case No. IPR2018-01764 (P.T.A.B), Exhibit 1010, filed Sep. 20, 2018; 37 pages.

IV's Infringement Contentions, Exhibit F, filed in *Ericsson Inc. and Telefonaktiebolaget LM Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01185 (P.T.A.B), Exhibit 1007, filed May 31, 2018; 47 pages.

IV's Infringement Contentions, Exhibit G, filed in *Ericsson Inc. and Telefonaktiebolaget LM Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01289 (P.T.A.B), Exhibit 1007, filed Jun. 20, 2018; 63 pages.

IV's Infringement Contentions, Exhibit G, filed in *Intellectual Ventures II LLC v. Sprint Spectrum L.P. et al.*, 2:17-cv-662. (E.D. Tex., Jan. 5, 2018), filed in *Sprint Spectrum L.P. et al. v. Intellectual Ventures II LLC*, Case No. IPR2018-01764 (P.T.A.B), Exhibit 1011, filed Sep. 20, 2018; 64 pages.

IV's infringement Contentions, Exhibit G, filed in *Sprint Spectrum L.P. et al. v. Intellectual Ventures II LLC*, Case No. IPR2018-01765 (P.T.A.B), Exhibit 1011, filed Sep. 20, 2018; 64 pages.

IV's Opposition to Defendants' Motion to Dismiss, filed in *Ericsson Inc. and Telefonaktiebolaget LM Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01185 (P.T.A.B), Exhibit 1010, filed May 31, 2018; 37 pages.

IV's Opposition to Defendants' Motion to Dismiss, filed in *Ericsson Inc. and Telefonaktiebolaget LM Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01289 (P.T.A.B), Exhibit 1008, filed Jun. 20, 2018; 37 pages.

Joint Motion for Leave to Amend P.R. 4-3 Joint Claim Construction and Prehearing Statement [176], filed in *Intellectual Ventures II LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662, filed Sep. 10, 2018; 7 pages.

Korean Preliminary Office Action (translation) dated Sep. 20, 2010 from Korean Patent Application No. 10-2008-702945, cited by other.

Korhonen, Introduction to 3G Mobile Communications, Artech House, 2nd edition (2003).

MAC Protocol and Traffic Scheduling for Wireless ATM Networks, by Nikos Passas et al. ("Passas-II"), filed in *Ericsson Inc. and Telefonaktiebolaget LAI Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01185 (P.T.A.B), Exhibit 1005, filed May 31, 2018; 20 pages.

MAC Protocol and Traffic Scheduling for Wireless ATM Networks, by Nikos Passas et al. ("Passas-II"), filed in *Ericsson Inc. and Telefonaktiebolaget LM Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01289 (P.T.A.B), Exhibit 1005, filed Jun. 20, 2018; 20 pages.

Manfredi et al.; A Channel Aware Scheduling Algorithm for HSPDA System, 2005 IEEE 16th International Symposium on Personal, Indoor, and Mobile Radio Communications: 2005.

Meeting the Challenge: Congestion and Flow Control Strategies for Broadband Information Transport by A.E. Eckberg, Jr. ("Eckberg"), filed in *Ericsson Inc. and Telefonaktiebolaget LM Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01185 (P.T.A.B), Exhibit 1006, filed May 31, 2018, 25 pages.

Meeting the Challenge: Congestion and Flow Control Strategies for Broadband Information Transport by A.E. Eckberg, Jr. ("Eckberg"), filed in *Ericsson Inc. and Telefonaktiebolaget LAI Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01289 (P.T.A.B), Exhibit 1006, filed Jun. 20, 2018; 25 pages.

Moldy, M. et al. (1992) The GSM System for Mobile Communications, Bay Foreign Language Books, ISBN-2950701997, cited by other.

Nokia of America Corporation's Answer and Affirmative Defense [118], filed in *Intellectual Ventures H LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662, filed Apr. 12, 2018; 57 pages.

Nokia of America Corporation's Answer and Affirmative Defenses [Null], filed in *Intellectual Ventures II LLC v. T-Mobile USA, Inc. f/k/a MetroPCS Communications, Inc. et al.*, Case No. TXED-2-17-cv-0066L filed Apr. 12, 2018; 57 pages.

Non-Final Rejection issued by USPTO, dated Apr. 30, 2015, for U.S. Appl. No. 13/858,666.

Non-Final Rejection issued by USPTO, dated Aug. 12, 2016, for U.S. Appl. No. 15/131,250.

Non-Final Rejection issued by USPTO, dated Aug. 13, 2010 for U.S. Appl. No. 11/430,421.

Non-Final Rejection issued by USPTO, dated Dec. 9, 2011 for U.S. Appl. No. 13/212,843.

Non-Final Rejection issued by USPTO, dated Feb. 6, 2009 for U.S. Appl. No. 11/430,421.

Non-Final Rejection issued by USPTO, dated Jan. 12, 2018, for U.S. Appl. No. 15/618,669.

Non-Final Rejection issued by USPTO, dated Jun. 26, 2009 for U.S. Appl. No. 11/430,421.

Non-Final Rejection, U.S. Appl. No. 16/410,581, dated Jun. 2, 2020.

Non-Final Rejection, U.S. Appl. No. 17/181,417, dated May 14, 2021.

Non-Final Rejection, U.S. Appl. No. 17/181,417, dated Sep. 13, 2021.

Notice of Allowance issued by USPTO, dated Apr. 11, 2011 for U.S. Appl. No. 11/430,421.

Notice of Allowance issued by USPTO, dated Dec. 11, 2015, for U.S. Appl. No. 13/858,666.

Notice of Allowance issued by USPTO, dated Feb. 14, 2017 for U.S. Appl. No. 15/131,250.

Notice of Allowance issued by USPTO, dated Feb. 6, 2013 for U.S. Appl. No. 13/212,843.

Notice of Allowance issued by USPTO, dated Sep. 11, 2018, for U.S. Appl. No. 15/618,669.

Notice of Allowance issued by USPTO, dated Sep. 21, 2012 for U.S. Appl. No. 13/212,843.

Notice of Allowance, U.S. Appl. No. 16/410,581, dated Nov. 4, 2020.

Notice of Allowance, U.S. Appl. No. 16/410,581, dated Dec. 23, 2020.

(56)

References Cited

OTHER PUBLICATIONS

Notice of Allowance, U.S. Appl. No. 17/181,417, dated Dec. 2, 2021.

Order [115], filed in *Intellectual Ventures II LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662, filed Apr. 2, 2018; 1 page.

Order [157], filed in *Intellectual Ventures II LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662, filed Jun. 29, 2018; 1 page.

Order [163], filed in *Intellectual Ventures II LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662, filed Jul. 10, 2018; 1 page.

Order and Opinion on Defendants Motion to Dismiss [189], filed in *Intellectual Ventures II LLC v. Sprint Spectrum LP (d/b/a Sprint PCS et al.)*, Case No. TXED-2-17-cv-00662, filed Sep. 24, 2018; 19 pages.

Order and Opinion on Defendants Motions to Dismiss [62], filed in *Intellectual Ventures II LLC v. T-Mobile USA, Inc. f/k/a MetroPCS Communications, Inc. et al.*, Case No. TXED-2-17-cv-00661, filed Sep. 24, 2018; 19 pages.

Order Denying Defendants' Motion to Dismiss [60], filed in *Intellectual Ventures II LLC v. T-Mobile USA, Inc. f/k/a MetroPCS Communications, Inc. et al.*, Case No. TXED-2-17-cv-00661, filed Sep. 18, 2018; 8 pages.

Order Denying Defendants Motions to Dismiss [183], filed in *Intellectual Ventures II LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662, filed Sep. 18, 2018; 8 pages.

Order Granting Joint Motion for Leave to Amend P.R. 4-3 [177], filed in *Intellectual Ventures II LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662, filed Sep. 12, 2018; 2 pages.

P.R. 4-3 Joint Claim Construction and Prehearing Statement [175], filed in *Intellectual Ventures II LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662, filed Aug. 10, 2018; 7 pages.

P.R. 4-5 Joint Claim Construction Chart [210], filed in *Intellectual Ventures II LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662, filed Oct. 17, 2018; 33 pages.

Passas et al., "Traffic Scheduling in Wireless ATM Networks," Communication Networks Laboratory, Dept. of Informatics, U. of Athens, IEEE 0-7803-4196-1, 1997, pp. 391-400, filed in *Ericsson Inc. and Telefonaktiebolaget LM Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01185 (P.T.A.B.), Exhibit 2001, filed Sep. 5, 2018; 10 pages.

Passas et al., "Traffic Scheduling in Wireless ATM Networks," Communication Networks Laboratory, Dept. of Informatics, U. of Athens, IEEE 0-7803-4196-1, 1997, pp. 391-400, filed in *Ericsson Inc. and Telefonaktiebolaget LM Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01289 (P.T.A.B.), Exhibit 2001, filed Oct. 19, 2018; 10 pages.

Patent Owner intellectual Ventures II LLC's Preliminary Response to Petition, filed in *Ericsson Inc. and Telefonaktiebolaget LM Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01289 (P.T.A.B.), Paper 6, filed Oct. 19, 2018; 35 pages.

Patent Owner Intellectual Ventures II LLC's Preliminary Response to Petition, filed in *Ericsson Inc. and Telefonaktiebolaget LAI Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01185 (P T A Pi') Paper 6, filed Sep. 5, 2018 -VI pages.

Patent Owner's Preliminary Response, IPR2018-01185, Paper 6 (Sep. 5, 2018), filed in *Sprint Spectrum L.P. et al. v. Intellectual Ventures II LLC*, Case No. IPR2018-01764 (P.T.A.B.), Exhibit 1016, filed Sep. 20, 2018; 43 pages.

Patent Owner's Preliminary Response, IPR2018-01185, Paper 6 (Sep. 5, 2018), filed in *Sprint Spectrum L.P. et al. v. Intellectual Ventures II LLC*, Case No. IPR2018-01765 (P.T.A.B.), Exhibit 1016, filed Sep. 20, 2018; 43 pages.

PCT Patent Application No. PCT/EP2007/054154; Notification of Transmittal of International Search Report and Written Opinion; dated Oct. 16, 2007.

Petition for Inter Partes Review, filed in *Ericsson Inc. and Telefonaktiebolaget LM Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01185 (P.T.A.B.), Paper 1, filed May 31, 2018; 77 pages.

Petition for Inter Partes Review, filed in *Sprint Spectrum L.P. et al. v. Intellectual Ventures II LLC*, Case No. IPR2018-01765 (P.T.A.B.), Paper 1, filed Sep. 20, 2018; 74 pages.

Petition for Inter Partes Review, filed in *Sprint Spectrum L.P. et al. v. Intellectual Ventures II LLC*, Case No. IPR2018-01764 (P.T.A.B.), Paper 1, filed Sep. 20, 2018; 74 pages.

Petition for Inter Partes Review, filed in *Ericsson Inc. and Telefonaktiebolaget LM Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01289 (P.T.A.B.), Paper 1, filed Jun. 20, 2018; 74 pages.

Plaintiff Intellectual Ventures II LLC's Answer to Nokia of America [120], filed in *Intellectual Ventures II LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662, filed Apr. 12, 2018; 7 pages.

Plaintiff Intellectual Ventures II LLC's Notice of Supplemental Authority [141], filed in *Intellectual Ventures II LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662, filed Jun. 5, 2018; 4 pages.

Plaintiff Intellectual Ventures II LLC's Opening Claim Construction Brief [180], filed in *Intellectual Ventures II LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662, filed Sep. 14, 2018 29 pages.

Plaintiff Intellectual Ventures II LLC's Response to the T-Mobile and Sprint Defendants' Notice of Supplemental Authority [160], filed in *Intellectual Ventures II LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662, filed Jul. 5, 2018; 4 pages.

Plaintiff Intellectual Ventures II LLC's Unopposed Motion for Leave to Amend Infringement Contentions [161], filed in *Intellectual Ventures II LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662, filed Jul. 9, 2018; 4 pages.

Plaintiff Intellectual Ventures' Opening Supplemental Brief [126], filed in *Intellectual Ventures II LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662, filed Apr. 24, 2018; 21 pages.

Plaintiff's Reply Claim Construction Brief [207], filed in *Intellectual Ventures II LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662, filed Oct. 15, 2018; 14 pages.

Smith et al., 3G Wireless Networks, The McGraw-Hill Companies, Inc. pp. 1-641 (2002).

Sprint Spectrum L.P. et al. v. Intellectual Ventures II LLC, Decision Denying Institution of Inter Partes Review, Case No. IPR 2018-01765, U.S. Pat. No. 9,681,466 (May 6, 2019).

Sprint's Sealed Answer, Affirmative Defenses, and Counterclaims [208], filed in *Intellectual Ventures II LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662, filed Oct. 17, 2018; 54 pages.

Tanenbaum, Computer Networks, 4th edition, Pearson Education, Inc., pp. 1-674 (2003).

Telephony's Dictionary, Second Edition, by Graham Langley ("Langley"), filed in *Ericsson Inc. and Telefonaktiebolaget Di Ericsson v. Intellectual Ventures II LLC*, Case No. IPR'2018-01185 (P.T.A.B.), Exhibit 1009, filed May 31, 2018; 5 pages.

The New Oxford Dictionary of English, Oxford University Press, Inc., New York, 2001, filed in *Ericsson Inc. and Telefonaktiebolaget LM Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01289 (P.T.A.B.) Exhibit 2003, filed Oct. 19, 2018; 5 pages.

The New Oxford Dictionary of English, Oxford University Press, Inc., New York. 2001. filed in *Ericsson Inc. and Telefonaktiebolaget LM Ericsson v. Intellectual Ventures II LLC*, Case No. IPR2018-01185 (P.T.A.B.), Exhibit 2003, filed Sep. 5, 2018; 5 pages.

The T-Mobile and Sprint Defendants' Motion to Dismiss [20], filed in *Intellectual Ventures II LLC v. T-Mobile USA, Inc. f/k/a MetroPCS Communications, Inc. et al.*, Case No. TXED-2-17-cv-00661, filed Dec. 7, 2017; 36 pages.

The T-Mobile and Sprint Defendants' Notice of Supplemental Authority [154], filed in *Intellectual Ventures II LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662, filed Jun. 29, 2018; 4 pages.

(56)

References Cited

OTHER PUBLICATIONS

The T-Mobile and Sprint Defendants' Response to IV's Notice of Supplemental Authority [143], filed in *Intellectual Ventures H LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662, Jun. 7, 2018; 5 pages.

The T-Mobile and Sprint Defendants' Response to Plaintiff Intellectual Ventures' Opening Supplemental Brief [134], filed in *Intellectual Ventures II LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-CV-00662, filed May 15, 2018; 22 pages.

The T-Mobile and Sprint Defendants' Sur-Reply to Plaintiff [139], filed in *Intellectual Ventures II LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662, filed May 29, 2018; 10 pages.

Third Generation Partnership Project, "Technical Specification Group Radio Access Network; Medium Access Control (MAC) protocol specification (Release 6)," 3GPP TS 25.321 V6.7.0 (Dec. 2005).

Third Generation Partnership Project, "Technical Specification Group Radio Access Network; Radio Interface Protocol Architecture (Release 6)," 3GPP TS 25.301 V7.0.0 (Mar. 2006).

Third Generation Partnership Project, "Technical Specification Group Radio Access Network; Physical channels and mapping of transport channels onto physical channels (FDD) (Release 7)," 3GPP TS 25.211 V7.0.0 (Mar. 2006).

Third Generation Partnership Project, "Technical Specification Group Radio Access Network; Radio Resource Control (RRC); Protocol Specification (Release 7)," 3GPP TS 25.331 V7.0.0 (Mar. 2006).

Third Generation Partnership Project, "Technical Specification Group Core Network; Mobile radio interface Layer 3 specification; Core network protocols; Stage 3 (Release 6)," 3GPP TS 24.008 V6.6.0 (Sep. 2004).

Third Generation Partnership Project, "Technical Specification Group Radio Access Network; Medium Access Control (MAC) protocol specification (Release 7)," 3GPP TS 25.321 V7.0.0 (Mar. 2006).

Third Generation Partnership Project, "Technical Specification Group Core Network; Mobile radio interface Layer 3 specification; Core network protocols; Stage 3 (Release 7)," 3GPP TS 24.008 V7.3.0 (March 2006).

T-Mobile and Sprint Defendants' Motion to Dismiss [26], filed in *Intellectual Ventures II LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662, filed Dec. 7, 2017; 36 pages.

T-Mobile USA, Inc., and T-Mobile US, Inc.'s [redacted] Answer and Counterclaims to IV's Complaint [209], filed in *Intellectual Ventures II LLC v. Sprint Spectrum LP d/b/a Sprint PCS et al.*, Case No. TXED-2-17-cv-00662, filed Oct. 17, 2018; 57 pages.

Toyota Motor Corp. et al. v. Intellectual Ventures II LLC, Decision Granting Institution of Inter Partes Review, Case No. IPR2022-00972, U.S. Pat. No. 9,681,466 (Dec. 7, 2022).

Toyota Motor Corp. et al. v. Intellectual Ventures II LLC, Declaration of Dr. Gary Lomp in Support of Patent Owner's Preliminary Response, Case No. IPR 2022-00972, U.S. Pat. No. 9,681,466 (Sep. 8, 2022).

Toyota Motor Corp. et al. v. Intellectual Ventures II LLC, Declaration of Dr. Gary Lomp in Support of Patent Owner's Preliminary Response, Case No. IPR 2022-01127, U.S. Pat. No. 10,292,138 (Oct. 6, 2022).

Toyota Motor Corp. et al. v. Intellectual Ventures II LLC, Declaration of Dr. Robert Akl, D.Sc., Case No. IPR 2022-00972, U.S. Pat. No. 9,681,466 (May 20, 2022).

Toyota Motor Corp. et al. v. Intellectual Ventures II LLC, Declaration of Dr. Robert Akl, D.Sc., Case No. IPR 2022-01127, U.S. Pat. No. 10,292,138 (Jun. 10, 2022).

Toyota Motor Corp. et al. v. Intellectual Ventures II LLC, Patent Owner's Pre-Institution Sur-Reply, Case No. IPR 2022-00972, U.S. Pat. No. 9,681,466 (Oct. 20, 2022).

Toyota Motor Corp. et al. v. Intellectual Ventures II LLC, Patent Owner's Preliminary Response, Case No. IPR 2022-01127, U.S. Pat. No. 10,292,138 (Oct. 6, 2022).

Toyota Motor Corp. et al. v. Intellectual Ventures II LLC, Patent Owner's Pre-Institution Sur-Reply, Case No. IPR 2022-01127, U.S. Pat. No. 10,292,138 (Nov. 30, 2022).

Toyota Motor Corp. et al. v. Intellectual Ventures II LLC, Patent Owner's Preliminary Response, Case No. IPR 2022-00972, U.S. Pat. No. 9,681,466 (Sep. 9, 2022).

Toyota Motor Corp. et al. v. Intellectual Ventures II LLC, Petitioner's Pre-Institution Reply, Case No. IPR 2022-00972, U.S. Pat. No. 9,681,466 (Oct. 11, 2022).

Toyota Motor Corp. et al. v. Intellectual Ventures II LLC, Petitioner's Pre-Institution Sur-Reply, Case No. IPR 2022-01127, U.S. Pat. No. 10,292,138 (Nov. 21, 2022).

Toyota Motor Corp. et al. v. Intellectual Ventures II LLC, Petition for Inter Partes Review of U.S. Pat. No. 10,292,138, Case No. IPR 2022-01127, (Jun. 10, 2022).

Toyota Motor Corp. et al. v. Intellectual Ventures II LLC, Petition for Inter Partes Review of U.S. Pat. No. 9,681,466, Case No. IPR 2022-00972 (May 20, 2022).

Toyota Motor Corp. et al. v. Intellectual Ventures II LLC, Petitioners' Request for Rehearing, Case No. IPR2022-01127, U.S. Pat. No. 10,292,138 (Feb. 2, 2023).

Ericsson Inc., et al v. Intellectual Ventures II LLC, IPR2018-01289, filed Jun. 20, 2018, Institution Denied.

Sprint Spectrum LP, et al v. Intellectual Ventures II LLC, IPR2018-01765, filed Sep. 20, 2018, Institution Denied.

Toyota Motor Corp. et al. v. Intellectual Ventures II LLC, IPR2022-00972, filed May 20, 2022, Pending.

American Honda Motor Co., Inc. v. Intellectual Ventures II PLC, IPR2022-01521, filed Sep. 9, 2022, Pending.

Toyota Motor Corp. et al. v. Intellectual Ventures II LLC, IPR2022-01127, filed Jun. 10, 2022, Pending.

American Honda Motor Co., Inc. v. Intellectual Ventures II LLC, IPR2023-00020, filed Oct. 6, 2022, Pending.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

SCHEDULING TRANSMISSIONS ON CHANNELS IN A WIRELESS NETWORK

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 17/181,417 filed Feb. 22, 2021, which will issue as U.S. Pat. No. 11,297,605 on Apr. 5, 2022, which is a continuation of U.S. patent application Ser. No. 16/410,581 filed May 13, 2019, which issued as U.S. Pat. No. 10,932,232 on Feb. 23, 2021, which is a continuation of U.S. patent application Ser. No. 15/618,669 filed Jun. 9, 2017, which issued as U.S. Pat. No. 10,292,138 on May 14, 2019, which is a continuation of U.S. patent application Ser. No. 15/131,250 filed Apr. 18, 2016, which issued as U.S. Pat. No. 9,681,466 on Jun. 13, 2017, which is a continuation of U.S. patent application Ser. No. 13/858,666 filed Apr. 8, 2013, which issued as U.S. Pat. No. 9,320,018 on Apr. 19, 2016, which is a continuation of U.S. patent application Ser. No. 13/212,843 filed Aug. 18, 2011, which issued as U.S. Pat. No. 8,428,026 on Apr. 23, 2013, which is a continuation of U.S. patent application Ser. No. 11/430,421 filed May 8, 2006, which issued as U.S. Pat. No. 8,005,041 on Aug. 23, 2011, the contents of which are all incorporated by reference herein as if fully set forth.

FIELD OF THE INVENTION

This invention relates to a mechanism to support Internet Protocol data flows within a wireless communication system. The invention is applicable to, but not limited to, gateway queuing algorithms in packet data transmissions, for example, for use in the universal mobile telecommunication standard.

BACKGROUND OF THE INVENTION

In a cellular communication system, a geographical region is divided into a number of cells, each of which is served by base stations, sometimes referred to as Node-Bs. The base stations are interconnected by a fixed network which can communicate data between the base stations. A mobile station, sometimes referred to as user equipment (UE) is served via a radio communication link from the base station of the cell within which the mobile station is situated.

A typical cellular communication system extends coverage over an entire country and comprises hundreds or even thousands of cells supporting thousands or even millions of mobile stations. Communication from a mobile station to a base station is known as the uplink, and communication from a base station to a mobile station is known as the downlink.

The fixed network interconnecting the base stations is operable to route data between any two base stations, thereby enabling a mobile station in a cell to communicate with a mobile station in any other cell. In addition, the fixed network comprises gateway functions for interconnecting to external networks such as the Internet or the Public Switched Telephone Network (PSTN), thereby allowing mobile stations to communicate with landline telephones and other communication terminals connected by a landline. Furthermore, the fixed network comprises much of the functionality required for managing a conventional cellular communication network including functionality for routing data, admission control, resource allocation, subscriber billing, mobile station authentication etc.

Currently, the most ubiquitous cellular communication system is the 2nd generation communication system known as the Global System for Mobile communication (GSM). GSM uses a technology known as Time Division Multiple Access (TDMA) wherein user separation is achieved by dividing frequency carriers into 8 discrete time slots, which individually can be allocated to a user. Further description of the GSM TDMA communication system can be found in 'The GSM System for Mobile Communications' by Michel Mouly and Marie Bernadette Pautet, Bay Foreign Language Books, 1992, ISBN 2950719007.

Currently, 3rd generation systems are being rolled out to further enhance the communication services provided to mobile users. The most widely adopted 3rd generation communication systems are based on Code Division Multiple Access (CDMA) technology. Both Frequency Division Duplex (FDD) and Time Division Duplex (TDD) techniques employ this CDMA technology. In CDMA systems, user separation is obtained by allocating different spreading and scrambling codes to different users on the same carrier frequency and in the same time intervals. In TDD, additional user separation is achieved by assigning different time slots to different users similarly to TDMA. However, in contrast to TDMA, TDD provides for the same carrier frequency to be used for both uplink and downlink transmissions. An example of a communication system using this principle is the Universal Mobile Telecommunication System (UMTS). Further description of CDMA and specifically of the Wideband CDMA (WCDMA) mode of UMTS can be found in 'WCDMA for UMTS', Harri Holma (editor), Antti Toskala (Editor), Wiley & Sons, 2001, ISBN 0471486876.

In a 3rd generation cellular communication system, the communication network comprises a core network and a Radio Access Network (RAN). The core network is operable to route data from one part of the RAN to another, as well as interfacing with other communication systems. In addition, it performs many of the operation and management functions of a cellular communication system, such as billing. The RAN is operable to support wireless user equipment over a radio link of the air interface. The RAN comprises the base stations, which in UMTS are known as Node Bs, as well as Radio Network Controllers (RNCs) which control the base stations and the communication over the air interface.

The RNC performs many of the control functions related to the air interface including radio resource management and routing of data to and from appropriate base stations. It further provides the interface between the RAN and the core network. An RNC and associated base stations are known as a Radio Network Subsystem (RNS).

3rd generation cellular communication systems have been specified to provide a large number of different services including efficient packet data services. For example, downlink packet data services are supported within the 3GPP release 5 specifications in the form of the High Speed Downlink Packet Access (HSDPA) service. A High Speed Uplink Packet Access (HSUPA) feature is also in the process of being standardised. This uplink packet access feature will adopt many of the features of HSDPA.

In accordance with the 3GPP specifications, the HSDPA service may be used in both Frequency Division Duplex (FDD) mode and Time Division Duplex (TDD) mode.

In HSDPA, transmission code resources are shared amongst users according to their traffic needs. The base station or "Node-B" is responsible for allocating and distributing the resources to the users, within a so-called scheduling task. Hence, for HSDPA, some scheduling is

performed by the RNC whereas other scheduling is performed by the base station. Specifically, the RNC allocates a set of resources to each base station, which the base station can use exclusively for high speed packet services. The RNC furthermore controls the flow of data to and from the base stations.

Therefore, most packet based systems contain schedulers that control when the individual data packets are transmitted, in order to share the available resource, whether time-slots in a time division multiple access (TDMA) communication system or power and codes in a code division multiple access (CDMA) communication system. An introduction to schedulers can be found in 'Service discipline for guaranteed performance service in packet-switching networks', authored by Hui Zhang, and published in the Proceedings of the IEEE, volume 83, no. 10, October 1995.

U.S. Pat. No. 6,845,100 describes use of two separate schedulers; a packet scheduler and a QoS scheduler. The packet scheduler allocates resources to users and then within this user's allocation the QoS scheduler prioritizes some packets over other depending upon the radio bearer they are assigned to.

Thus, there exists a need to provide an improved mechanism to differentiate between IP data flows.

SUMMARY OF THE INVENTION

In accordance with aspects of the present invention, there is provided a wireless communication system, an apparatus, and a method of operation therefor, as defined in the claims.

Accordingly, in one embodiment of the present invention there is provided an apparatus for use in allocating resource in a wireless communication system, the apparatus comprising mapping logic arranged to map one or more services to individual radio bearers of a plurality of radio bearers; reporting logic arranged to indicate buffer occupancy for the plurality of radio bearers; and prioritization logic arranged to prioritize the allocated resource across multiple wireless communication units on a radio bearer basis.

The provision of prioritization logic arranged to prioritize allocated resource across multiple wireless communication units enables prioritization of a particular service across users, so that for instance hyper text transport protocol (HTTP) traffic can be prioritized over file transfer protocol (FTP) traffic, whether the FTP traffic was associated with one user or a number of other users.

In one embodiment of the present invention, the apparatus comprises a database storing a plurality of service specifications, one per wireless communication unit, that define the mapping between data flow and respective radio bearers.

The provision of a database storing a plurality of service specifications provides a very wide range of mapping characteristics can be configured. Furthermore, different mappings can be achieved on a per tier or even per user basis.

In one embodiment of the present invention, the apparatus further comprises signal dividing logic operably coupled to mapping logic and arranged to split services into individual radio bearers from a single (PDP) context.

The provision of the signal dividing logic provides user equipment with the ability to no longer need to send a secondary packet data protocol (PDP) context request to begin a new service, thereby avoiding significant latency.

In one embodiment of the present invention, the wireless communication unit is user equipment arranged to allocate resource in an uplink communication path.

In one embodiment of the present invention, the apparatus is located in a radio access network (RAN) that comprises

prioritization logic arranged to allocate resource to a plurality of wireless communication units in a downlink communication path on a radio bearer basis.

In one embodiment of the present invention, a wireless communication unit of the plurality of wireless communication units comprises a signal processor arranged to identify buffer occupancy for individual radio bearers and a transmitter operably coupled to the signal processor and arranged to transmit a message to the radio access network.

The provision of a signal processor arranged to identify buffer occupancy for individual radio bearers (or services) advantageously enables any system to provide prioritization, whether within a users allocation or across users. In one embodiment of the present invention the message indicates separate buffer occupancy for each of the radio bearers.

The provision of a message that indicates separate buffer occupancy for each of the individual radio bearers provides effective prioritization, in that the allocator knows the buffer occupancy for each radio bearer (RB), in the UL direction. This supports signalling to enable the UE to report this volume.

In one embodiment of the present invention, the apparatus further comprises weighting logic operably coupled to the signal processor and the prioritization logic and arranged to provide a set of weight values for each service across a plurality of users such that the prioritization logic allocates bandwidth resource to individual radio bearers according to a set of weight values.

The provision of weighting logic operably coupled to the signal processor and the prioritization logic allows a proportion of the resource to be allocated to particular radio bearers (e.g. services). This is in contrast to the conventional prioritization scheme provided by 3GPP, which uses a simple absolute priority scheme.

In one embodiment of the present invention, the apparatus further comprises a transmitter transmitting the set of weight values to the wireless communication unit. This feature provides the advantage that the UE can then properly prioritize traffic whilst receiving a single physical allocation from the network and not have to use the simple absolute priority system defined in 3GPP.

In one embodiment of the present invention, the radio access network comprises a scheduler arranged to schedule prioritized allocated resource across multiple wireless communication units in response to the message.

In one embodiment of the present invention, the radio access network comprises a plurality of classifiers associated with the one or more services operably coupled to the mapping logic such that the mapping logic maps data packets onto respective radio bearers.

The provision of classifiers associated with the one or more services advantageously supports the filtering of services onto radio bearers.

In one embodiment of the present invention, there is provided an apparatus comprising a memory and a processor operably coupled to the memory. Program code is executable on the processor, where the program code is operable for mapping one or more services to individual radio bearers of a plurality of radio bearers; reporting buffer occupancy for the plurality of radio bearers; and prioritizing the allocated resource across multiple wireless communication units on a radio bearer basis.

In one embodiment of the present invention, a wireless communication system

comprises a radio access network facilitating communication to a plurality of wireless communication units. The wireless communication system comprises mapping logic

arranged to map one or more services to individual radio bearers of a plurality of radio bearers; reporting logic arranged to indicate buffer occupancy for the plurality of radio bearers; and prioritization logic arranged to prioritize the allocated resource across multiple wireless communication units on a radio bearer basis.

In one embodiment of the present invention, a method for limiting a number of services supported at an instant of time in a wireless communication system is described. The method comprises determining a normalised service weighting parameter of allocated resources; determining a number of resource allocation units allocated to each service; and determining whether the number of services that have resources allocated is greater than a threshold. The method further comprises limiting a number of resource allocation units allocated in response to the number of services that have resources allocated is greater than a threshold; recalculating a number of resource allocation units allocated to each service; and ordering services in an order of resource allocation units allocated to each service, and select a number from the ordered services. The method further comprises setting all services not selected to zero; determining whether the number of services that have resources allocated is greater than a threshold; and when said number of services that have resources allocated is greater than the threshold, repeating said steps of re-calculating, ordering, setting and determining.

In this manner, even when a large population of users exist, each with many services, the number of messages required to allocate the overall resource is limited to a manageable number. It is noteworthy that a single user with multiple services, each allocated resource, will only result in a single allocation message. However, by having large numbers of users with large numbers of services the chance of allocating a small amount of resource to many users is increased.

BRIEF DESCRIPTION OF THE DRAWINGS

Embodiments of the invention will be described, by way of example only, with reference to the accompanying drawings, in which

FIG. 1 illustrates a 3GPP cellular communication system capable of supporting embodiments of the present invention;

FIG. 2 illustrates a downlink operation to allow service prioritization across a plurality of users according to embodiments of the present invention;

FIG. 3 illustrates an example of a mechanism whereby UEs are mapped to radio bearers according to embodiments of the present invention;

FIG. 4 illustrates a tier-based weighted fair queuing system that can be utilised in embodiments of the present invention;

FIG. 5 illustrates a communication system comprising uplink scheduling, in accordance with some embodiments of the invention; and

FIG. 6 illustrates a method to limit a number of services/queues to be allocated radio bearers at a particular instant in time, in accordance with embodiments of the invention.

DETAILED DESCRIPTION OF EMBODIMENTS OF THE INVENTION

In summary, embodiments of the present invention describe an architecture for supporting IP flows with different quality of service within a wireless communications system. Embodiments of the present invention comprise a

database carrying service specifications, one per user equipment, which define the mapping between IP flows and radio bearers. At the user equipment, and within the Radio Access Network, classifiers use the specifications to map IP packets onto the appropriate radio bearers. A scheduler within the Radio Access Network is configured to allocate bandwidths to the different radio bearers, according to a set of weights values. Thus, in this manner, quality of service (QoS) differentiation between different services carried over IP over the wireless network is achieved.

RAN functionality already assumes that data associated with separate service definition specifications (e.g. port numbers) is placed on separate radio bearers. However, in embodiments of the present invention, the RAN functionality is configured to allow services to be prioritized across multiple users, in contrast to prior art techniques that only allow prioritization within a user's allocation.

Referring firstly to FIG. 1, a typical, standard UMTS Radio Access Network (UTRAN) system **100** is conveniently considered as comprising: terminal/user equipment domain **110**; a UMTS Terrestrial Radio Access Network domain **120**; and an infrastructure domain **130**.

In the terminal/user equipment domain **110**, terminal equipment (TE) **112** is connected to mobile equipment (ME) **114** via the wired or wireless R interface. The ME **114** is also connected to a user service identity module (USIM) **116**; the ME **114** and the USIM **116** together are considered as user equipment (UE) **118**. The UE may be for example a remote unit, a mobile station, a communication terminal, a personal digital assistant, a laptop computer, an embedded communication processor or any communication element communicating over the air interface of the cellular communication system.

The UE **118** communicates data with a Node-B (base station) **122** in the radio access network domain **120** via the wireless Uu interface. Within the radio access network domain **120**, the Node-B **122** communicates with a radio network controller (RNC) **124** via the Iub interface. The RNC **124** communicates with other RNCs (not shown) via the Iur interface.

The Node-B **122** and the RNC **124** together form the UTRAN **126**. The RNC **124** communicates with a serving GPRS service node (SGSN) **132** in the core network domain **130** via the Iu interface. Within the core network domain **130**, the SGSN **132** communicates with a gateway GPRS support node **134** via the Gn interface; the SGSN **132** and the GGSN **134** communicate with a home location register (HLR) server **136** via the Gr interface and the Gc interface respectively. The GGSN **134** communicates with public data network **138** via the Gi interface.

Thus, the elements RNC **124**, SGSN **132** and GGSN **134** are conventionally provided as discrete and separate units (on their own respective software/hardware platforms) divided across the radio access network domain **120** and the core network domain **130**, as shown FIG. 1.

The RNC **124** is the UTRAN element responsible for the control and allocation of resources for numerous Node-Bs **122**; typically 50 to 100 Node-Bs may be controlled by one RNC. The RNC also provides reliable delivery of user traffic over the air interfaces. RNCs communicate with each other (via the Iur interface).

The SGSN **132** is the UMTS Core Network element responsible for Session Control and interface to the HLR. The SGSN keeps track of the location of an individual UE and performs security functions and access control. The SGSN is a large centralised controller for many RNCs.

The GGSN **134** is the UMTS Core Network element responsible for concentrating and tunneling user data within the core packet network to the ultimate destination (e.g., internet service provider—ISP). Terminal equipment (TE) **112** is connected to mobile equipment (ME) **114** via the wired or wireless R interface. The ME **114** is also connected to a user service identity module (USIM) **116**; the ME **114** and the USIM **116** together are considered as user equipment (UE) **118**. The UE **118** communicates data with a Node-B (base station) **122** in the radio access network domain **120** via the wireless Uu interface. Within the radio access network domain **120**, the Node-B **122** communicates with a radio network controller (RNC) **124** via the Iub interface. The RNC **124** communicates with other RNCs (not shown) via the Iur interface. The Node-B **122** and the RNC **124** together form the UTRAN **126**. The RNC **124** communicates with a serving GPRS service node (SGSN) **132** in the core network domain **130** via the Iu interface. Within the core network domain **130**, the SGSN **132** communicates with a gateway GPRS support node **134** via the Gn interface; the SGSN **132** and the GGSN **134** communicate with a home location register (HLR) server **136** via the Gr interface and the Gc interface respectively. The GGSN **134** communicates with public data network **138** via the Gi interface.

Thus, the elements RNC **124**, SGSN **132** and GGSN **134** are conventionally provided as discrete and separate units (on their own respective software/hardware platforms) divided across the radio access network domain **120** and the core network domain **130**, as shown FIG. 1.

The RNC **124** is the UTRAN element responsible for the control and allocation of resources for numerous Node-Bs **122**; typically 50 to 100 Node-Bs may be controlled by one RNC. The RNC **124** also provides reliable delivery of user traffic over the air interfaces. RNCs communicate with each other (via the Iur interface).

The SGSN **132** is the UMTS Core Network element responsible for Session Control and interface to the HLR. The SGSN keeps track of the location of an individual UE and performs security functions and access control. The SGSN is a large centralised controller for many RNCs.

The GGSN **134** is the UMTS Core Network element responsible for concentrating and tunneling user data within the core packet network to the ultimate destination (e.g., internet service provider—ISP).

Such a UTRAN system and its operation are described more fully in the 3rd Generation Partnership Project technical specification documents 3GPP TS 25.401, 3GPP TS 23.060, and related documents, available from the 3GPP website at www.3gpp.org, and need not be described herein in more detail.

Within the RNC **124**, separate functional blocks exist that have been incorporated or adapted in accordance with embodiments of the present invention. In particular, as shown in FIG. 1, a Mapper **128** is responsible for mapping IP packets to separate RBs. The Mapper **128** is shown in greater detail in FIG. 2. A scheduler **129** is responsible for allocating a certain proportion of the radio resource to each of the RBs, which is described in further detail with respect to FIG. 3 and FIG. 4.

Additionally, in accordance with embodiments of the present invention, element manager logic **140** has been incorporated into the system, which is used to contain the database that defines the mapping characteristics for IP packets to RBs. The element manager logic **140** also contains the values of the queue weighting parameters, S_{tier} , as described in more detail later.

FIG. 2 illustrates a downlink operation according to one embodiment of the present invention that may allow service prioritization across a plurality of users. In this regard, processing logic **128** within the RNC comprises signal dividing logic **215**, which splits services **220**, **225**, **230** into separate radio bearers **235**, **240**, **245** from a single PDP context **205**. In one embodiment of the present invention, the services may be divided between separate radio bearers based on, say, port numbers.

Although eight services/radio bearers are illustrated in FIG. 2, it is envisaged that the inventive concept may be applied to any number of services/radio bearers. In this manner, for each user, the scheduler is now aware of the total amount of data present in buffers for each service.

FIG. 3 illustrates an example of a mechanism whereby a plurality of UEs is mapped to radio bearers according to embodiments of the present invention. In this example, a first UE **315**, a second UE **320** and a third UE **335** are illustrated, whereby the first UE **315** and second UE **320** use a first service level agreement (SLA-1) **305** and the third UE **335** uses a second (SLA-2) **345**. The first SLA-1 **305** and the second SLA-2 **345** employ a plurality of radio bearers that they organise packet data queues for.

In one embodiment of the present invention, it is envisaged that separate queues may be provided for the same services, but using different SLAs.

Referring now to FIG. 4, resource allocator logic associated with a single SLA is shown, i.e. FIG. 4 provides a more detailed version of element **305** in FIG. 3. Separate reports **410**, **430**, **460** for RBs '1' to '8' are provided and these are associated with separate services within an SLA.

In one embodiment of the present invention, within each queue there is a single indication of the volume of data for each user (for the associated radio bearer) **420**, **440**, **470** rather than the data itself. Within each queue a simple round robin allocation scheme may operate, whereby when the volume indication reaches the head of the queue a fixed volume of resource is allocated to the user. When the user has been granted this resource, the user is placed at the back of the queue (assuming there is still buffer occupancy left for this user given the resource that has been allocated).

The output from the respective queues provides individual indications of an allocation for each logical channel to the UTRAN side medium access layer (MAC). The outputs are combined in a scheduler **480** that provides a DL allocation that is sent to the respective UEs in a physical shared channel allocation message.

With reference to FIG. 4, the above scheme may be supported in a mechanism that provides 'tier-based, weighted fair queuing'. Briefly, in such a mechanism, each queue determines the weight value based on:

$$W'_{tier} = \frac{N_{tier} * S_{tier}}{\sum_{alltiers} (N_{tier} * S_{tier})} \quad [1]$$

Where:

N_{tier} is the number of separate users in the queue.

The overall volume of spare physical resource is then allocated to each queue in proportion to the W'_{tier} values. As mentioned previously, a simple round robin allocation policy may also apply within each queue.

Referring back to FIG. 3 a total of 16 queue weights (S_{tier}) are desired. These queue weights define the relative amount of the total resource that is allocated to each queue. Thus, the

bandwidth allocated to different radio bearers is shared according to the relative weights. In the implementation, these weights are set by the element manager. However, in one embodiment of the present invention, the weights may also be configured by RADIUS, in which case the service specification is interpreted by the radio resource manager (RRM) to configure appropriate resource allocation (RA) queues and RBs.

The structure of this architecture means that it is possible to provide QoS prioritization across multiple users. Hence, for example, in a scenario where there are two users, one may have hyper-text transfer protocol (HTTP) traffic and this may be mapped to RB1, and a second user may employ file transfer protocol (FTP) traffic, which may be mapped to RB2. The S_{tier} associated with RB1 ($S_{tier\ 1}$) is higher than that for RB2 ($S_{tier\ 2}$). Therefore, assuming the volume of data in the buffers for the 2 users is the same, then the ratio of the total resource allocated to RB1 may be defined as:

$$S_{tier\ 1}/(S_{tier\ 1}+S_{tier\ 2}) \quad [3]$$

Thus, the ratio of the total resource allocated to RB2 may be defined as:

$$S_{tier\ 2}/(S_{tier\ 1}+S_{tier\ 2}) \quad [4]$$

It is noteworthy that there is no restriction on the values associated with each queue weight value (S_{tier}). Therefore, in accordance with embodiments of the present invention, it may be possible to, say, set the relative weight for service 1 for SLA-2 to be higher than a number of services on SLA-1, which may nominally be a higher-priority SLA.

In accordance with one embodiment of the present invention, a mechanism to provide prioritization of services across multiple users in an uplink direction is described. In this regard, weight values are signaled to the UE. Again, as described above with respect to a downlink direction, it is assumed that logic exists that splits data onto a number of radio bearers dependent on the type of service. It is also assumed that the UE is able to signal to the network separate buffer occupancy for each queue associated with the various RBs.

If there are multiple QoS requirements within a single 3GPP PDP context, a single physical allocation of radio resources may be made to the UE. In this manner, a single PDP context implies a single CCTrCh. This single physical allocation of radio resources provided to a UE is shared amongst a number of services, in proportion to their respective QoS requirements, for example in proportion to the signalled weight values (S_{tier}).

The network knows separate buffer occupancies associated with each RB. Therefore, the logic required to operate the uplink case is largely unchanged compared with the aforementioned downlink case. However, as only a single physical allocation is signaled to the UE, all the physical allocations associated with each queue are summed together. In this regard, this mechanism is unlike the downlink case where direct control of which RB is allocated physical resources is implemented.

In the uplink case, as a single physical allocation is used, the scheduler logic in the network is mirrored with similar scheduler logic in the UE, which takes the single physical allocation and splits it between different RBs using the weight, S_{tier} , values. In addition, in order for the UE to know the value of the S_{tier} parameters that are also used at the network side, the uplink case supports signaling between the network and UE to communicate these values.

In one embodiment of the present invention, the signaling of the S_{tier} parameters will typically be sent to the UE when

it initially connects to the network (for example in the radio bearer setup message). If there are any modifications to the S_{tier} parameters then these may be typically signaled to the UE in dedicated control signaling (using, for example, a radio bearer reconfiguration message). However, it is also envisaged that S_{tier} parameters could also be signaled to the UE using other mechanisms, such as system information.

Referring now to FIG. 5, an overview of the communication between an UE 505 and the UTRAN 540 to support an uplink scenario is illustrated. In this regard, the UE 505 may receive a single PDP context 510 and split the single PDP context 510 into separate services on individual radio bearers in divider logic 515. The UE may then transmit a message 535 indicating separate buffer occupancy for each of the radio bearers to a UTRAN scheduler 545.

The separate services on individual radio bearers are input to a UE mirror scheduler 525. In one embodiment of the present invention, the UE mirror scheduler 525 receives a S_{tier} parameter 550 signalled 555 from the UTRAN 540 when the UE first connects to the UTRAN 540. The S_{tier} parameters 550 within the UTRAN 540 are also input to the UTRAN scheduler 545. The UTRAN scheduler 545 is adapted to provide a single allocation of a physical resource to the UE mirror scheduler 525 within message 560. The UE mirror scheduler 525 is then able to inform the UTRAN 540 in a message 535 on its use of the physical allocation, in order to transmit data in each radio bearer in proportion to the informed S_{tier} parameters 550.

Thus, within the UE 505, the S_{tier} values are known, together with the total allocation of resources for the UE 505. Clearly there is only a single SLA at the UE, and N_{tier} can be either a '0' or '1'. Thus, and advantageously, the overall resources allocated by the network are now split up based on the relative values of W_{tier} .

Furthermore, it is noteworthy that, the aforementioned structure allows the ability to prioritize QoS across users in the DL to be extended to the UL.

As each SLA is can now be split into multiple RBs it may be the case that very small proportions of the overall resources are allocated to each RB. This may create signaling problems, as the mechanism may result in a large number of individual users being allocated some resource at any one time and each user will require a separate allocation message. Therefore, in an enhanced embodiment of the present invention, a mechanism to implement additional functionality to limit a total number of queues served, e.g. to be allocated resource allocation units, is described. Thus, this algorithm limits a number queues that can be allocated resource at any one instance, for example to an operator-specified value. The algorithm may also ensure that the ratio of allocated resource is maintained, over the long term, to the ratios specified by the S_{tier} values.

It is noteworthy that this algorithm can be implemented in both the uplink and downlink.

Referring now to FIG. 6, an algorithm 600 employing embodiments of the present invention is illustrated. The algorithm describes one mechanism to limit a number of queues served at a single instant of time. The algorithm may be run when a number of active users (i.e. those users known to have a buffer occupancy greater than zero in any queue) is greater than a known fixed parameter, for example 'max_number_queues_served', as defined by the Element Manager (EM).

The process commences in step 605 by determining a normalised queue weighting parameter $W'q$ of the allocated resources:

11

$$W'_q = \frac{N_q * S_q}{\sum_{q=0}^{NB_q-1} (N_q * S_q)} \quad [6]$$

Where:

N_Q is the number of entries in queue Q (i.e. the number of UEs with data in queue q); and

NB_q is the number of queues configured at the Node-B.

The process then determines, as shown in step 610, the number of RAAU allocated to each queue, for example using:

$$RAAUq = \text{FreeRAAU} * W'_q \quad [7]$$

Where:

RAAU represents a quantum of physical resource (codes and timeslots); and FreeRAAU is a number of free RAAU that the resource allocator (RA) can share out.

The algorithm may then determine whether the number of queues that have resources allocated greater than the EM parameter-max_number_queues_served, as shown in step 615. If the number of queues that have resources allocated is greater than a threshold, for example the EM parameter max_number_queues_served, the process moves to step 620. If the number of queues that have resources allocated is not greater than the EM parameter max_number_queues_served then the process may operate as normal as described in the PCT publication WO 03/049320, by the same Applicant as the present invention.

Step 620 re-calculates RAAUq as follows:

$$RAAUq' = RAAUq + \text{running RAAU delta} \quad [8]$$

Where:

RAAUq is calculated in step 610, and

Running_RAAU_delta is the running difference between the number of RAAU that would be allocated without the limitation of the number of queues serviced and the number of RAAU allocated with the limitation.

Note that this algorithm is iterative and running_RAAU_delta is determined from the previous iteration of the algorithm. Hence, although no limitation has been applied in the first iteration, on the second iteration the limitation of the number of queues in the previous iteration has meant that there are some queues that did not receive the number of RAAU that were originally determined.

In step 625, the queues are then ordered in order of RAAUq', beginning with the highest queue. The first max_number_queues_served queues are then selected, as shown in step 628.

In all queues not selected in step 628, the Nq' value is set to zero, as shown in step 630. In all of the tiers that were selected in step 628, Nq' is set to Nq , as shown in step 635.

In step 640, Wq (now known as W''_q) may be re-calculated using the Nq' vector determined in step 635, for example using:

$$W''_q = \frac{N'_q * S_q}{\sum_{q=0}^{NB_q-1} (N'_q * S_q)} \quad [10]$$

12

The modified number of RAAU, allocated to each queue, may then be determined in step 645. For example, the modified number may be determined using:

$$RAAUq'' = \text{round}(\text{FreeRAAU} * W''_q) \quad [11]$$

where: round(. .) rounds to the nearest integer.

The sum of all RAAU allocated may then be determined in step 650. Here, if the sum of all RAAU allocated is greater than freeRAAU (which is possible following the rounding operation in step 645) then the RAAUq'' may be modified in step 655, as also described in the PCT publication WO 03/049320, by the same Applicant as the present invention.

It is possible that the volume of resource allocated to the queue may be less than that required given the cell edge state that the UE is in. For example, if the UE is in cell edge '2' then four RAAU will be needed as a minimum. Therefore, if the amount of RAAU allocated by RAAU tier'' is less than the minimum required RAAU, given the cell edge state for any q, then RAAUq'' may be set for one of the queues that has RAAUq'' less than the minimum to zero, as shown in step 660. Here, it is noteworthy that there may be multiple queues below the minimum.

In this scenario, any spare resources are allocated first to any other queues that are below the minimum, as shown in step 665. If there are still spare resources, then any spare resources are allocated in turn; one RAAU each to the queues that currently have RAAUq'' greater than zero.

The RAAUq'' value is then updated, as shown in step 670. The running difference, between the actually allocated RAAU (RAAUq'') and the originally determined allocated RAAU RAAUq, is then updated, as shown in step 675. For example, in this manner:

$$\text{running_RAAU_delta} = \text{running_RAAU_delta} - k \cdot (RAAUq - RAAUq'') \quad [12]$$

Thus, a mechanism is described whereby the number of queues to be allocated resources at any particular time may be limited.

In summary, the inventive concept of the present invention aims to provide at least one or more of the following features:

- (i) A method to provide prioritization of services across users in the DL;
- (ii) A method to provide prioritization of services across users in the UL. This requires that weight values are signalled to the UE;
- (iii) A method to limit the number of queues (i.e. services) to be allocated radio resources at any one time. This functionality is provided in the UL as well as the DL; and
- (iv) The inventive concept of the present invention enables prioritization of packet types across users, as there is a single allocation process for each packet type and each user. This is particularly beneficial for packet-based, best-effort services. For instance, if a wireless communication system comprises a plurality of users that are performing very large file transfer protocol (FTP) downloads, and another user is web browsing, it is possible to prioritize the web browsing user over the others.

It is noteworthy that U.S. Pat. No. 6,845,100 is significantly different from the inventive concept herein described, which proposes a mechanism that is able to prioritize packet types across users. In one embodiment, this is achieved through provision of a single allocation process for each packet type and each user. This is particularly beneficial for packet based best-effort services. For instance if a first number of users are performing very large file transfer protocol (FTP) downloads, and another user is web browsing, it is possible to prioritize the web browsing user amongst others, in employing the inventive concept herein

described, in contrast to the known prior art, such as U.S. Pat. No. 6,845,100, which will not allow this to happen.

In particular, it is envisaged that the aforementioned inventive concept can be applied by a semiconductor manufacturer to any signal processing integrated circuit (IC). It is further envisaged that, for example, a semiconductor manufacturer may employ the inventive concept in a design of a stand-alone device, or application-specific integrated circuit (ASIC) and/or any other sub-system element.

It will be appreciated that any suitable distribution of functionality between different functional units or logic elements, may be used without detracting from the inventive concept herein described. Hence, references to specific functional devices or elements are only to be seen as references to suitable means for providing the described functionality, rather than indicative of a strict logical or physical structure or organization.

Aspects of the invention may be implemented in any suitable form including hardware, software, firmware or any combination of these. Software and firmware may be stored on computer-readable media. The elements and components of an embodiment of the invention may be physically, functionally and logically implemented in any suitable way. Indeed, the functionality may be implemented in a single unit or IC, in a plurality of units or ICs or as part of other functional units.

Although the present invention has been described in connection with some embodiments, it is not intended to be limited to the specific form set forth herein. Rather, the scope of the present invention is limited only by the claims. Additionally, although a feature may appear to be described in connection with particular embodiments, one skilled in the art would recognize that various features of the described embodiments may be combined in accordance with the invention. Further, although embodiments of the present invention may be described, in some instances, using terminology from a particular protocol, those skilled in the art will recognize that such terms are also used in a generic sense herein, and that, unless otherwise specified, the present invention is not limited to systems implementing a particular protocol. In the claims, the term 'comprising' does not exclude the presence of other elements or steps.

Furthermore, although individual features may be included in different claims, these may possibly be advantageously combined, and the inclusion in different claims does not imply that a combination of features is not feasible and/or advantageous. Also, the inclusion of a feature in one category of claims does not imply a limitation to this category, but rather indicates that the feature is equally applicable to other claim categories, as appropriate.

Furthermore, the order of features in the claims does not imply any specific order in which the features must be performed and in particular the order of individual steps in a method claim does not imply that the steps must be performed in this order. Rather, the steps may be performed in any suitable order. In addition, singular references do not exclude a plurality. Thus, references to "a", "an", "first", "second" etc. do not preclude a plurality.

Thus, an improved wireless communication system, apparatus, integrated circuit, and a method of operation therefor have been described, wherein the aforementioned disadvantages with prior art arrangements have been substantially alleviated.

What is claimed is:

1. A user equipment (UE) comprising:
 - a transmitter;
 - a receiver;
 - a processor; and

wherein:

the receiver and the processor are configured to receive, from a wireless network, information including a plurality of first values and queue limit information, wherein each of the plurality of first values is associated with at least one radio bearer;

the transmitter and the processor are configured to transmit a plurality of buffer occupancy indicators, wherein each buffer occupancy indicator is associated with at least one queue, wherein each queue is associated with at least one radio bearer;

the receiver and the processor are further configured, in response to the transmitted plurality of buffer occupancy indicators, to receive, from the wireless network, an uplink resource allocation;

the processor is further configured to determine, based on the received queue limit information, a limited number of queues to select for providing data for transmission;

the processor is further configured to provide data for transmission from the selected limited number of queues, wherein data from each of the selected limited number of queues is limited based on the first value associated with the selected queue; and

the transmitter and the processor are further configured to transmit the data provided by the selected limited number of queues in resources determined from the received uplink resource allocation.

2. The user equipment of claim 1 wherein the processor further determines, from each of the selected limited number of queues, an amount of data to allocate from that queue based on the first value.

3. The user equipment of claim 2 wherein the amount of data to allocate from that queues is based on multiplying the first value with a second value.

4. The user equipment of claim 2 wherein the amount of data to allocate from that queue is subtracted from a third value prior to a subsequent allocation of data from that queue.

5. The user equipment of claim 1 wherein the data from each of the selected limited number of queues is further selected based on a priority of the queues.

6. The user equipment of claim 1 wherein after the data is selected from the selected queues based on the first values, data is further selected from the selected queues based on spare resources of the uplink resource allocation.

7. The user equipment of claim 1 wherein the processor is further configured to receive a radio bearer and split the radio bearer into a plurality of bearers for separate transmission.

8. A method performed by a user equipment (UE), the method comprising:

receiving information, from a wireless network, including a plurality of first values and queue limit information, wherein each of the plurality of first values is associated with at least one radio bearer;

transmitting a plurality of buffer occupancy indicators, wherein each buffer occupancy indicator is associated with at least one queue, wherein each queue is associated with at least one radio bearer;

receiving, from the wireless network, an uplink resource allocation, in response to the transmitted plurality of buffer occupancy indicators;

determining, based on the received queue limit information, a limited number of queues to select for providing data for transmission;

15

providing data for transmission from the selected limited number of queues, wherein data from each of the selected limited number of queues is limited based on the first value associated with the selected queue; and transmitting the data provided by the selected limited number of queues in resources determined from the received uplink resource allocation.

9. The method of claim **8** wherein an amount of data to allocate from that queue is based on multiplying the first value with a second value.

10. The method of claim **9** wherein the amount of data to allocate from that queues is based on multiplying the first value with a second value.

11. The method of claim **9** wherein the amount of data to allocate from that queue is subtracted from a third value prior to a subsequent allocation of data from that queue.

12. The method of claim **8** wherein the data from each of the selected limited number of queues is further selected based on a priority of the queues.

13. The method of claim **8** wherein after the data is selected from the selected queues based on the first values, data is further selected from the selected queues based on spare resources of the uplink resource allocation.

14. The method of claim **8** further comprising receiving a radio bearer and splitting the radio bearer into a plurality of bearers for separate transmission.

15. A base station (BS) comprising:

a transmitter;

a receiver;

a processor; and

wherein:

the transmitter and the processor configure to transmit information, to a user equipment (UE), information including a plurality of first values and queue limit

16

information, wherein each of the plurality of first values is associated with at least one radio bearer;

the receiver and the processor are configured to receive a plurality of buffer occupancy indicators, wherein each buffer occupancy indicator is associated with at least one queue, wherein each queue is associated with at least one radio bearer;

the transmitter and the processor are further configured, in response to the received plurality of buffer occupancy indicators, to transmit, to the UE, an uplink resource allocation; and

the receiver and the processor are further configured to receive data provided by limited number of queues in allocated uplink resources, based on the transmitted queue limit information and the transmitted first values wherein the limited number of queues is selected by the UE.

16. The BS of claim **15** wherein an amount of data received from each of the selected limited number of queues is limited based on the first values.

17. The BS of claim **16** wherein the amount of data to allocate from each queue is based on multiplying the respective first value with a second value.

18. The BS of claim **16** wherein the amount of data received from at least one of queue is iteratively allocated from that at least one queue.

19. The BS of claim **15** wherein the data received from each of the selected limited number of queues is further selected based on a priority of the queues.

20. The BS of claim **15** wherein the receiver and the processor are further configured to receive a plurality of split bearers, wherein the plurality of split bearers are split from a single radio bearer.

* * * * *