



US011733064B1

(12) **United States Patent**
Yedid et al.

(10) **Patent No.:** **US 11,733,064 B1**
(45) **Date of Patent:** **Aug. 22, 2023**

(54) **OPTICAL-PATH FOLDING-ELEMENT WITH AN EXTENDED TWO DEGREE OF FREEDOM ROTATION RANGE**

H04N 23/45 (2023.01); *H04N 23/57* (2023.01); *H04N 23/58* (2023.01); *H04N 23/69* (2023.01); *H04N 23/698* (2023.01); *H04N 23/55* (2023.01)

(71) Applicant: **Corephotonics Ltd.**, Tel Aviv (IL)

(58) **Field of Classification Search**
CPC combination set(s) only.
See application file for complete search history.

(72) Inventors: **Itay Yedid**, Tel Aviv (IL); **Ephraim Goldenberg**, Tel Aviv (IL); **Gil Bachar**, Tel Aviv (IL); **Gal Barak**, Tel Aviv (IL); **Yiftah Kowal**, Tel Aviv (IL)

(56) **References Cited**

(73) Assignee: **Corephotonics Ltd.**, Tel Aviv (IL)

U.S. PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

3,085,354 A 4/1963 Rasmussen et al.
3,584,513 A 6/1971 Gates
(Continued)

(21) Appl. No.: **18/299,727**

FOREIGN PATENT DOCUMENTS

(22) Filed: **Apr. 13, 2023**

CN 101276415 A 10/2008
CN 201514511 U 6/2010
(Continued)

Related U.S. Application Data

OTHER PUBLICATIONS

(63) Continuation of application No. 17/984,355, filed on Nov. 10, 2022, now Pat. No. 11,650,080, which is a
(Continued)

Statistical Modeling and Performance Characterization of a Real-Time Dual Camera Surveillance System, Greenhagen et al., Publisher: IEEE, 2000, 8 pages.

(51) **Int. Cl.**

(Continued)

G01D 5/14 (2006.01)
G01P 13/00 (2006.01)
G02B 7/18 (2021.01)
G02B 13/00 (2006.01)
H01F 7/02 (2006.01)
G02B 7/182 (2021.01)
G03B 17/17 (2021.01)
H04N 23/45 (2023.01)

Primary Examiner — Alvaro E Fortich
(74) *Attorney, Agent, or Firm* — Nathan & Associates;
Menachem Nathan

(Continued)


(52) **U.S. Cl.**

(57) **ABSTRACT**

CPC **G01D 5/145** (2013.01); **G01P 13/00** (2013.01); **G02B 7/18** (2013.01); **G02B 7/1827** (2013.01); **G02B 13/0065** (2013.01); **G03B 17/17** (2013.01); **H01F 7/02** (2013.01);

Actuators for rotating an optical-path-folding-element with two, first and second, degrees of freedom in an extended rotation range around two respective rotation axes, folded cameras including such actuators and dual-cameras including a folded camera as above together with an upright camera.

19 Claims, 26 Drawing Sheets



Related U.S. Application Data

continuation of application No. 17/829,722, filed on Jun. 1, 2022, now Pat. No. 11,506,513, which is a continuation of application No. 17/013,561, filed on Sep. 5, 2020, now Pat. No. 11,359,937, which is a continuation of application No. 16/615,310, filed as application No. PCT/IB2019/053315 on Apr. 22, 2019, now Pat. No. 11,268,829.

(60) Provisional application No. 62/661,158, filed on Apr. 23, 2018.

(51) **Int. Cl.**

H04N 23/57 (2023.01)
H04N 23/58 (2023.01)
H04N 23/69 (2023.01)
H04N 23/698 (2023.01)
H04N 23/55 (2023.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,941,001 A 3/1976 LaSarge
 4,199,785 A 4/1980 McCullough et al.
 4,792,822 A 12/1988 Akiyama et al.
 5,005,083 A 4/1991 Grage et al.
 5,032,917 A 7/1991 Aschwanden
 5,041,852 A 8/1991 Misawa et al.
 5,051,830 A 9/1991 von Hoessle
 5,099,263 A 3/1992 Matsumoto et al.
 5,248,971 A 9/1993 Mandl
 5,287,093 A 2/1994 Amano et al.
 5,331,465 A 7/1994 Miyano
 5,394,520 A 2/1995 Hall
 5,436,660 A 7/1995 Sakamoto
 5,444,478 A 8/1995 Lelong et al.
 5,459,520 A 10/1995 Sasaki
 5,502,537 A 3/1996 Utagawa
 5,657,402 A 8/1997 Bender et al.
 5,682,198 A 10/1997 Katayama et al.
 5,768,443 A 6/1998 Michael et al.
 5,892,855 A 4/1999 Kakinami et al.
 5,926,190 A 7/1999 Turkowski et al.
 5,940,641 A 8/1999 McIntyre et al.
 5,982,951 A 11/1999 Katayama et al.
 6,101,334 A 8/2000 Fantone
 6,128,416 A 10/2000 Oura
 6,148,120 A 11/2000 Sussman
 6,201,533 B1 3/2001 Rosenberg et al.
 6,208,765 B1 3/2001 Bergen
 6,211,668 B1 4/2001 Duesler et al.
 6,215,299 B1 4/2001 Reynolds et al.
 6,222,359 B1 4/2001 Duesler et al.
 6,268,611 B1 7/2001 Pettersson et al.
 6,549,215 B2 4/2003 Jouppi
 6,611,289 B1 8/2003 Yu et al.
 6,643,416 B1 11/2003 Daniels et al.
 6,650,368 B1 11/2003 Doron
 6,680,748 B1 1/2004 Monti
 6,714,665 B1 3/2004 Hanna et al.
 6,724,421 B1 4/2004 Glatt
 6,738,073 B2 5/2004 Park et al.
 6,741,250 B1 5/2004 Furlan et al.
 6,750,903 B1 6/2004 Miyatake et al.
 6,778,207 B1 8/2004 Lee et al.
 7,002,583 B2 2/2006 Rabb, III
 7,015,954 B1 3/2006 Foote et al.
 7,038,716 B2 5/2006 Klein et al.
 7,199,348 B2 4/2007 Olsen et al.
 7,206,136 B2 4/2007 Labaziewicz et al.
 7,248,294 B2 7/2007 Slatter
 7,256,944 B2 8/2007 Labaziewicz et al.
 7,305,180 B2 12/2007 Labaziewicz et al.
 7,339,621 B2 3/2008 Fortier

7,346,217 B1 3/2008 Gold, Jr.
 7,365,793 B2 4/2008 Cheatle et al.
 7,411,610 B2 8/2008 Doyle
 7,424,218 B2 9/2008 Baudisch et al.
 7,509,041 B2 3/2009 Hosono
 7,533,819 B2 5/2009 Barkan et al.
 7,619,683 B2 11/2009 Davis
 7,738,016 B2 6/2010 Toyofuku
 7,773,121 B1 8/2010 Huntsberger et al.
 7,809,256 B2 10/2010 Kuroda et al.
 7,880,776 B2 2/2011 LeGall et al.
 7,918,398 B2 4/2011 Li et al.
 7,964,835 B2 6/2011 Olsen et al.
 7,978,239 B2 7/2011 Deever et al.
 8,115,825 B2 2/2012 Culbert et al.
 8,149,327 B2 4/2012 Lin et al.
 8,154,610 B2 4/2012 Jo et al.
 8,238,695 B1 8/2012 Davey et al.
 8,274,552 B2 9/2012 Dahi et al.
 8,390,729 B2 3/2013 Long
 8,391,697 B2 3/2013 Cho et al.
 8,400,555 B1 3/2013 Georgiev et al.
 8,439,265 B2 5/2013 Ferren et al.
 8,446,484 B2 5/2013 Muukki et al.
 8,483,452 B2 7/2013 Ueda et al.
 8,514,491 B2 8/2013 Duparre
 8,547,389 B2 10/2013 Hoppe et al.
 8,553,106 B2 10/2013 Scarff
 8,587,691 B2 11/2013 Takane
 8,619,148 B1 12/2013 Watts et al.
 8,752,969 B1 6/2014 Kane et al.
 8,803,990 B2 8/2014 Smith
 8,896,655 B2 11/2014 Mauchly et al.
 8,976,255 B2 3/2015 Matsuoto et al.
 9,019,387 B2 4/2015 Nakano
 9,025,073 B2 5/2015 Attar et al.
 9,025,077 B2 5/2015 Attar et al.
 9,041,835 B2 5/2015 Honda
 9,137,447 B2 9/2015 Shibuno
 9,185,291 B1 11/2015 Shabtay et al.
 9,215,377 B2 12/2015 Sokeila et al.
 9,215,385 B2 12/2015 Luo
 9,270,875 B2 2/2016 Brisedoux et al.
 9,286,680 B1 3/2016 Jiang et al.
 9,344,626 B2 5/2016 Silverstein et al.
 9,360,671 B1 6/2016 Zhou
 9,369,621 B2 6/2016 Malone et al.
 9,413,930 B2 8/2016 Geerds
 9,413,984 B2 8/2016 Attar et al.
 9,420,180 B2 8/2016 Jin
 9,438,792 B2 9/2016 Nakada et al.
 9,485,432 B1 11/2016 Medasani et al.
 9,578,257 B2 2/2017 Attar et al.
 9,618,748 B2 4/2017 Munger et al.
 9,681,057 B2 6/2017 Attar et al.
 9,723,220 B2 8/2017 Sugie
 9,736,365 B2 8/2017 Laroia
 9,736,391 B2 8/2017 Du et al.
 9,768,310 B2 9/2017 Ahn et al.
 9,800,798 B2 10/2017 Ravirala et al.
 9,851,803 B2 12/2017 Fisher et al.
 9,894,287 B2 2/2018 Qian et al.
 9,900,522 B2 2/2018 Lu
 9,927,600 B2 3/2018 Goldenberg et al.
 2002/0005902 A1 1/2002 Yuen
 2002/0030163 A1 3/2002 Zhang
 2002/0054214 A1 5/2002 Yoshikawa
 2002/0063711 A1 5/2002 Park et al.
 2002/0075258 A1 6/2002 Park et al.
 2002/0122113 A1 9/2002 Foote
 2002/0167741 A1 11/2002 Koiwai et al.
 2003/0030729 A1 2/2003 Prentice et al.
 2003/0093805 A1 5/2003 Gin
 2003/0156751 A1 8/2003 Lee et al.
 2003/0160886 A1 8/2003 Misawa et al.
 2003/0202113 A1 10/2003 Yoshikawa
 2004/0008773 A1 1/2004 Itokawa
 2004/0012683 A1 1/2004 Yamasaki et al.
 2004/0017386 A1 1/2004 Liu et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2015/0110345 A1 4/2015 Weichselbaum
 2015/0124059 A1 5/2015 Georgiev et al.
 2015/0138381 A1 5/2015 Ahn
 2015/0145965 A1 5/2015 Livyatan et al.
 2015/0154776 A1 6/2015 Zhang et al.
 2015/0162048 A1 6/2015 Hirata et al.
 2015/0195458 A1 7/2015 Nakayama et al.
 2015/0198464 A1 7/2015 El Alami
 2015/0215516 A1 7/2015 Dolgin
 2015/0237280 A1 8/2015 Choi et al.
 2015/0242994 A1 8/2015 Shen
 2015/0244906 A1 8/2015 Wu et al.
 2015/0253543 A1 9/2015 Mercado
 2015/0253647 A1 9/2015 Mercado
 2015/0261299 A1 9/2015 Wajs
 2015/0271471 A1 9/2015 Hsieh et al.
 2015/0281678 A1 10/2015 Park et al.
 2015/0286033 A1 10/2015 Osborne
 2015/0296112 A1 10/2015 Park et al.
 2015/0316744 A1 11/2015 Chen
 2015/0334309 A1 11/2015 Peng et al.
 2016/0044247 A1* 2/2016 Shabtay H04N 23/45
 348/240.3
 2016/0044250 A1* 2/2016 Shabtay G02B 7/102
 348/240.3
 2016/0070088 A1 3/2016 Koguchi
 2016/0154066 A1 6/2016 Hioka et al.
 2016/0154202 A1 6/2016 Wippermann et al.
 2016/0154204 A1 6/2016 Lim et al.
 2016/0212358 A1 7/2016 Shikata
 2016/0212418 A1 7/2016 Demirdjian et al.
 2016/0238834 A1 8/2016 Erlich et al.
 2016/0241751 A1 8/2016 Park
 2016/0291295 A1 10/2016 Shabtay et al.
 2016/0295112 A1 10/2016 Georgiev et al.
 2016/0301840 A1 10/2016 Du et al.
 2016/0301868 A1 10/2016 Acharya et al.
 2016/0342095 A1 11/2016 Bieling et al.
 2016/0353008 A1 12/2016 Osborne
 2016/0353012 A1 12/2016 Kao et al.
 2016/0381289 A1 12/2016 Kim et al.
 2017/0001577 A1 1/2017 Seagraves et al.
 2017/0019616 A1 1/2017 Zhu et al.
 2017/0070731 A1 3/2017 Darling et al.
 2017/0094187 A1 3/2017 Sharma et al.
 2017/0124987 A1 5/2017 Kim et al.
 2017/0150061 A1 5/2017 Shabtay et al.
 2017/0187962 A1 6/2017 Lee et al.
 2017/0214846 A1 7/2017 Du et al.
 2017/0214866 A1 7/2017 Zhu et al.
 2017/0219749 A1 8/2017 Hou et al.
 2017/0242225 A1 8/2017 Fiske
 2017/0276954 A1 9/2017 Bajorins et al.
 2017/0289458 A1 10/2017 Song et al.
 2018/0013944 A1 1/2018 Evans, V et al.
 2018/0017844 A1 1/2018 Yu et al.
 2018/0024329 A1 1/2018 Goldenberg et al.
 2018/0059379 A1 3/2018 Chou
 2018/0109660 A1 4/2018 Yoon et al.
 2018/0109710 A1 4/2018 Lee et al.
 2018/0120674 A1 5/2018 Avivi et al.
 2018/0150973 A1 5/2018 Tang et al.
 2018/0176426 A1 6/2018 Wei et al.
 2018/0184010 A1 6/2018 Cohen et al.
 2018/0198897 A1 7/2018 Tang et al.
 2018/0241922 A1 8/2018 Baldwin et al.
 2018/0295292 A1 10/2018 Lee et al.
 2018/0300901 A1 10/2018 Wakai et al.
 2018/0329281 A1 11/2018 Ye
 2018/0368656 A1 12/2018 Austin et al.
 2019/0100156 A1 4/2019 Chung et al.
 2019/0121103 A1 4/2019 Bachar et al.
 2019/0121216 A1 4/2019 Shabtay et al.
 2019/0130822 A1 5/2019 Jung et al.
 2019/0213712 A1 7/2019 Lashdan et al.

2019/0215440 A1 7/2019 Rivard et al.
 2019/0222758 A1 7/2019 Goldenberg et al.
 2019/0228562 A1 7/2019 Song
 2019/0297238 A1 9/2019 Klosterman
 2020/0103726 A1 4/2020 Shabtay et al.
 2020/0104034 A1 4/2020 Lee et al.
 2020/0134848 A1 4/2020 El-Khamy et al.
 2020/0221026 A1 7/2020 Fridman et al.
 2020/0264403 A1 8/2020 Bachar et al.
 2020/0389580 A1 12/2020 Kodama et al.
 2021/0180989 A1 6/2021 Fukumura et al.
 2021/0333521 A9 10/2021 Yedid et al.
 2022/0252963 A1 8/2022 Shabtay et al.

FOREIGN PATENT DOCUMENTS

CN 102215373 A 10/2011
 CN 102739949 A 10/2012
 CN 102982518 A 3/2013
 CN 103024272 A 4/2013
 CN 203406908 U 1/2014
 CN 103841404 A 6/2014
 CN 205301703 U 6/2016
 CN 105827903 A 8/2016
 CN 105847662 A 8/2016
 CN 107608052 A 1/2018
 CN 107682489 A 2/2018
 CN 109729266 A 5/2019
 EP 1536633 A1 6/2005
 EP 1780567 A1 5/2007
 EP 2523450 A1 11/2012
 JP S59191146 A 10/1984
 JP 04211230 A 8/1992
 JP H07318864 A 12/1995
 JP 08271976 A 10/1996
 JP 2002010276 A 1/2002
 JP 2003298920 A 10/2003
 JP 2003304024 A 10/2003
 JP 2004056779 A 2/2004
 JP 2004133054 A 4/2004
 JP 2004245982 A 9/2004
 JP 2005099265 A 4/2005
 JP 2005122084 A 5/2005
 JP 2005321592 A 11/2005
 JP 2006237914 A 9/2006
 JP 2006238325 A 9/2006
 JP 2007228006 A 9/2007
 JP 2007306282 A 11/2007
 JP 2008076485 A 4/2008
 JP 2008271026 A 11/2008
 JP 2010204341 A 9/2010
 JP 2011055246 A 3/2011
 JP 2011085666 A 4/2011
 JP 2011138407 A 7/2011
 JP 2011203283 A 10/2011
 JP 2012132739 A 7/2012
 JP 2013101213 A 5/2013
 JP 2013106289 A 5/2013
 JP 2016105577 A 6/2016
 JP 2017146440 A 8/2017
 KR 20070005946 A 1/2007
 KR 20090058229 A 6/2009
 KR 20100008936 A 1/2010
 KR 20110080590 A 7/2011
 KR 20130104764 A 9/2013
 KR 1020130135805 A 11/2013
 KR 20140014787 A 2/2014
 KR 101428042 B1 8/2014
 KR 101477178 B1 12/2014
 KR 20140144126 A 12/2014
 KR 20150118012 A 10/2015
 KR 20170105236 A 9/2017
 KR 20180120894 A 11/2018
 KR 20130085116 A 6/2019
 WO 2000027131 A2 5/2000
 WO 2004084542 A1 9/2004
 WO 2006008805 A1 1/2006
 WO 2010122841 A1 10/2010
 WO 2014072818 A2 5/2014

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO WO-2016166730 A1 * 10/2016 G02B 13/0065
 WO WO-2016207754 A1 * 12/2016 G02B 27/0075
 WO 2017025822 A1 2/2017
 WO 2017037688 A1 3/2017
 WO 2018130898 A1 7/2018

OTHER PUBLICATIONS

A 3MPixel Multi-Aperture Image Sensor with 0.7 μ m Pixels in 0.11 μ m CMOS, Fife et al., Stanford University, 2008, 3 pages.

Dual camera intelligent sensor for high definition 360 degrees surveillance, Scotti et al., Publisher: IET, May 9, 2000, 8 pages.

Dual-sensor foveated imaging system, Hua et al., Publisher: Optical Society of America, Jan. 14, 2008, 11 pages.

Defocus Video Matting, McGuire et al., Publisher: ACM SIGGRAPH, Jul. 31, 2005, 11 pages.

Compact multi-aperture imaging with high angular resolution, Santacana et al., Publisher: Optical Society of America, 2015, 10 pages.

Multi-Aperture Photography, Green et al., Publisher: Mitsubishi Electric Research Laboratories, Inc., Jul. 2007, 10 pages.

Multispectral Bilateral Video Fusion, Bennett et al., Publisher: IEEE, May 2007, 10 pages.

Super-resolution imaging using a camera array, Santacana et al., Publisher: Optical Society of America, 2014, 6 pages.

Optical Splitting Trees for High-Precision Monocular Imaging, McGuire et al., Publisher: IEEE, 2007, 11 pages.

High Performance Imaging Using Large Camera Arrays, Wilburn et al., Publisher: Association for Computing Machinery, Inc., 2005, 12 pages.

Real-time Edge-Aware Image Processing with the Bilateral Grid, Chen et al., Publisher: ACM SIGGRAPH, 2007, 9 pages.

Superimposed multi-resolution imaging, Carles et al., Publisher: Optical Society of America, 2017, 13 pages.

Viewfinder Alignment, Adams et al., Publisher: EUROGRAPHICS, 2008, 10 pages.

Dual-Camera System for Multi-Level Activity Recognition, Bodor et al., Publisher: IEEE, Oct. 2014, 6 pages.

Engineered to the task: Why camera-phone cameras are different, Giles Humpston, Publisher: Solid State Technology, Jun. 2009, 3 pages.

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 1C






FIG. 2A






FIG. 3B




FIG. 3C




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 5A




FIG. 5B




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 7




FIG. 8




FIG. 9A




FIG. 9B




FIG. 10A




FIG. 10B




FIG. 11A




FIG. 11B




FIG. 11C




FIG. 11D




FIG. 11E




FIG. 11F




FIG. 11 - i




FIG. 11- ii




FIG. 11-iii




FIG. 11-iv




FIG. 11-v




FIG. 11-vi




FIG. 12A




FIG. 12B




FIG. 12C




FIG. 13




FIG. 14A




FIG. 14B




FIG. 14C




FIG. 15A




FIG. 15B




FIG. 15C




FIG. 15D




FIG. 15E

**OPTICAL-PATH FOLDING-ELEMENT WITH
AN EXTENDED TWO DEGREE OF
FREEDOM ROTATION RANGE**

CROSS-REFERENCE TO RELATED
APPLICATIONS

This is a continuation application from U.S. patent application Ser. No. 17/984,355 filed Nov. 10, 2022 (now allowed), which was a continuation application from U.S. patent application Ser. No. 17/829,722 filed Jun. 1, 2022 (now U.S. Pat. No. 11,506,513), which was a continuation application from U.S. patent application Ser. No. 17/013,561 filed Sep. 5, 2020 (now U.S. Pat. No. 11,359,937), which was a continuation application from U.S. patent application Ser. No. 16/615,310 filed Nov. 20, 2019 (now U.S. Pat. No. 11,268,829), which was a 371 application from international patent application PCT/IB2019/053315 filed Apr. 22, 2019, and is related to and hereby claims the priority benefit of commonly-owned and co-pending U.S. Provisional Patent Application No. 62/661,158 filed Apr. 23, 2018, which is incorporated herein by reference in its entirety.

FIELD

The subject matter disclosed herein relates in general to a folded-lens and to digital cameras with one or more folded lens.

BACKGROUND

In recent years, mobile devices such as cell-phones (and in particular smart-phones), tablets and laptops have become ubiquitous. Many of these devices include one or two compact cameras including, for example, a main rear-facing camera (i.e. a camera on the back face of the device, facing away from the user and often used for casual photography), and a secondary front-facing camera (i.e. a camera located on the front face of the device and often used for video conferencing).

Although relatively compact in nature, the design of most of these cameras is similar to the traditional structure of a digital still camera, i.e. it comprises a lens module (or a train of several optical elements) placed on top of an image sensor. The lens module refracts the incoming light rays and bends them to create an image of a scene on the sensor. The dimensions of these cameras are largely determined by the size of the sensor and by the height of the optics. These are usually tied together through the focal length (“f”) of the lens and its field of view (FOV)—a lens that has to image a certain FOV on a sensor of a certain size has a specific focal length. Keeping the FOV constant, the larger the sensor dimensions (e.g. in a X-Y plane), the larger the focal length and the optics height.

A “folded camera module” structure has been suggested to reduce the height of a compact camera. In the folded camera module structure, an optical path folding element (referred to hereinafter as “OPFE” that includes a reflection surface such as a prism or a mirror ;otherwise referred to herein collectively as a “reflecting element”) is added in order to tilt the light propagation direction from a first optical path (e.g. perpendicular to the smart-phone back surface) to a second optical path, (e.g. parallel to the smart-phone back surface). If the folded camera module is part of a dual-aperture camera, this provides a folded optical path through one lens module (e.g. a Tele lens). Such a camera is referred to herein as a “folded-lens dual-aperture

camera” or a “dual-aperture camera with a folded lens”. In some examples, the folded camera module may be included in a multi-aperture camera, e.g. together with two “non-folded” camera modules in a triple-aperture camera.

A folded-lens dual-aperture camera (or “dual-camera”) with an auto-focus (AF) mechanism is disclosed in Applicant’s US published patent application No. 20160044247.

SUMMARY

According to one aspect of the presently disclosed subject matter there is provided an actuator for rotating an OPFE in two degrees of freedom in an extended rotation range a first sub-assembly, a second sub-assembly and a stationary sub-assembly, the first sub-assembly configured to rotate the OPFE relative to the stationary sub-assembly in an extended rotation range around a yaw rotation axis and the second sub-assembly configured to rotate the OPFE relative to the first sub-assembly in an extended rotation range around a pitch rotation axis that is substantially perpendicular to the yaw rotation axis; a first sensor configured to sense rotation around the yaw rotation axis and a second sensor configured to sense rotation around the pitch rotation axis, the first and second sensors being fixed to the stationary sub-assembly, wherein at least one of the first sensor or the second sensor is a magnetic flux sensor; and a voice coil motor (VCM) comprising a magnet and a coil, wherein the magnet is fixedly attached to one of the first sub-assembly or the second sub-assembly, wherein the coil is fixedly attached to the stationary sub-assembly, wherein a driving current in the coil creates a force that is translated to a torque around a respective rotation axis, and wherein the second sensor is positioned such that sensing by the second sensor is decoupled from the rotation of the OPFE around the yaw rotation axis.

In addition to the above features, the actuator according to this aspect of the presently disclosed subject matter can optionally comprise one or more of features (i) to (xxv) listed below, in any technically possible combination or permutation:

- i. wherein the actuator is adapted to be installed and operable in a folded digital camera for rotating the OPFE within the camera,
- ii. wherein the actuator comprises a first actuation mechanism (including a first VCM) configured to rotate the first sub-assembly around the yaw rotation axis and a second actuation mechanism (including a second VCM) configured to rotate the second sub-assembly around the yaw rotation axis,
- iii. wherein the actuator comprises a first sensing mechanism that comprises the first sensor and a respective first magnet configured to sense the rotation around the yaw rotation axis and a second sensing mechanism that comprises the second sensor and a second magnet configured to sense the rotation around the pitch rotation axis,
- iv. wherein the yaw rotation axis passes through the second sensor to thereby decouple the second sensor from rotation around the yaw axis,
- v. wherein the yaw rotation axis passes through a center of the second sensor,
- vi. wherein the actuator further comprises a first curved ball-guided mechanism operative to enable the rotation around the pitch axis, and a second curved ball-guided mechanism operative to enable the rotation around the yaw axis,

- vii. wherein the actuator further comprises a curved ball-guided mechanism operative to enable the rotation around the yaw axis, the curved ball-guided mechanism is located on a side of the OPFE which is opposite to side facing an image sensor, 5
- viii. wherein the extended rotation range is equal to or greater than ± 5 degrees around the pitch and yaw rotation axes,
- ix. wherein the extended rotation range is equal to or greater than ± 10 degrees the pitch and yaw rotation axes, 10
- x. wherein the extended rotation range is between ± 15 -40 degrees around the pitch and yaw rotation axes,
- xi. wherein the extended rotation range around the pitch rotation axis is different from the extended rotation range around the second rotation axis, 15
- xii. wherein the at least one voice coil motor includes a pitch magnet and a coil dedicated for generating the rotation around the pitch rotation axis and wherein the pitch magnet is designed with a flat surface facing the coil, 20
- xiii. wherein the magnetic sensor is a magnetic flux sensor such as a Hall sensor.
- xiv. wherein the actuator comprises a sensing mechanism that includes the first sensor and a magnet (e.g. yaw sensing magnet), the magnet is shaped or formed such that a central part of the sensing magnet is further away from a projection line of motion of the first sensor, relative to an end of the sensing magnet, 25
- xv. wherein the actuator comprises a sensing magnet (e.g. yaw sensing magnet) shaped such that width of a cross section of the sensing magnet increases from a point substantially at its center towards each end of the magnet, thereby resulting in a variable distance between the first sensor and the magnet when relative movement occurs between the sensing magnet and the sensor, 30
- xvi. wherein the actuator further comprises a first magnet-yoke pair which pulls the first sub-assembly to the second sub-assembly in a radial direction relative to the pitch rotation axis and a second magnet-yoke pair which pulls the first sub-assembly to the stationary sub-assembly in a radial direction relative to the yaw rotation axis, 35
- xvii. wherein the first sub-assembly comprises a middle moving frame, the second sub-assembly comprises an OPFE holder, and the stationary sub-assembly comprises a base; wherein the first magnet-yoke pair pulls the OPFE holder to middle moving frame and the second magnet-yoke pair pulls the middle moving frame to the base, 40
- xviii. wherein the first sub-assembly comprises a middle moving frame and the second sub-assembly comprises an OPFE holder, and the stationary sub-assembly comprises a base; wherein rotation around the yaw rotation axis is generated by rotating the middle moving frame relative to the base and rotation around the pitch rotation axis is generated by rotating the OPFE holder relative to the middle moving frame., 45
- xix. wherein the actuator comprises a magnet characterized by a cut sphere shape and a coil characterized by a circular shape, the coil is symmetrically positioned around the cut sphere, 50
- xx. wherein the actuator comprises a single magnet that is used for creating an actuation force for rotation around the yaw rotation axis, creating a pre-load force in a magnet-yoke pair for holding together the first sub-

- assembly and the stationary sub-assembly, and sensing the rotation around the yaw rotation axis.
- xxi. wherein the actuator comprises only one magnetic flux sensor that is used for sensing rotation around the yaw rotation axis,
- xxii. wherein the single magnet is a polarization magnet characterized by continuous changes in direction of a magnetic field of the magnet along the magnet's length. wherein the first and second sensing mechanisms are decoupled from each other,
- xxiii. wherein the actuator is designed to be installed in a folded camera that comprises a lens module accommodating a plurality of lens elements along an optical axis; wherein the OPFE redirects light that enters the folded camera from a direction of a view section along a first optical path to a second optical path that passed along the optical axis,
- xxiv. wherein the actuator comprises a pitch magnet located at a side of the OPFE that is opposite to the side facing the view section,
- xxv. wherein the actuator comprises a yaw magnet located at a side of the OPFE that is opposite to the side facing the lens module,
- According to another aspect of the presently disclosed subject matter there is provided a folded camera comprising the actuator according to the previous aspect.
- In addition to the above features, the folded camera according to this aspect of the presently disclosed subject matter can optionally comprise one or more of features (i) to (xxv) listed above, in any technically possible combination or permutation.
- According to yet another aspect of the presently disclosed subject matter there is provided an actuator for rotating an OPFE with a first degree of freedom (DOF) around a first rotation axis and a second DOF around a second rotation axis, comprising:
- a first actuation mechanism for rotation in the first DOF;
 - a first sensing mechanism for sensing movement in the first DOF;
 - a second actuation mechanism for rotation in the second DOF; and
 - a second sensing mechanism for sensing movement in the second DOF;
- wherein first and second actuation mechanisms are configured to rotate the OPFE around the respective first or second rotation axis in an extended rotation range, and wherein in some examples the first and second actuation mechanism are voice coil motors and the second sensing mechanism comprises a sensor positioned such that rotation of the OPFE around the first rotation axis is decoupled from the second sensor.
- In addition to the above features, the camera according to this aspect of the presently disclosed subject matter can optionally comprise one or more of features (i) to (xxv) listed above, in any technically possible combination or permutation.
- According to another aspect of the presently disclosed subject matter there is provided a sensing mechanism for sensing rotation movement around a rotation axis, comprising a magnet and a magnetic sensor configured to detect a magnetic flux of the magnet and to determine a relative shift between the magnet and the magnetic sensor based on change in the detected magnetic flux, wherein the magnet is shaped such that a cross section of the magnet has a width that increases from a point substantially at a center of the magnet towards each end of the magnet, thereby increasing

5

a range of detectable change in the magnetic flux and increasing a corresponding detectable range of the relative shift between the magnet and the magnetic sensor.

In addition to the above features, the actuator according to this aspect of the presently disclosed subject matter can optionally comprise one or more of features (i) to (iv) listed below, in any technically possible combination or permutation:

- i. wherein the detectible range of relative shift between the magnet and the magnetic sensor is of more than 0.8 mm,
- ii. wherein the detectible range of relative shift between the magnet and the magnetic sensor is of more than 1.0 mm,
- iii. wherein the detectible range of relative shift between the magnet and the magnetic sensor is of more than 2.0 mm, and
- iv. wherein the magnetic sensor is a Hall bar sensor.

BRIEF DESCRIPTION OF THE DRAWINGS

Non-limiting examples of the presently disclosed subject matter are described below with reference to figures attached hereto that are listed following this paragraph. Identical structures, elements or parts that appear in more than one figure may be labeled with the same numeral in the figures in which they appear. The drawings and descriptions are meant to illuminate and clarify embodiments disclosed herein, and should not be considered limiting in any way.

FIG. 1A illustrates a folded camera with an optical path folding element (OPFE) with an extended 2 degrees-of-freedom (DOF) rotation range, according to some examples of the presently disclosed subject matter;

FIG. 1B shows the folded camera of FIG. 1A with an OPFE actuator, according to some examples of the presently disclosed subject matter;

FIG. 1C shows a dual-camera the includes a folded camera as in FIG. 1A together with an upright (non-folded) camera, according to some examples of the presently disclosed subject matter;

FIG. 2A shows an OPFE actuator of the folded camera of FIG. 1 in an isometric view, according to some examples of the presently disclosed subject matter;

FIG. 2B shows the actuator in FIG. 2A without a shield, according to some examples of the presently disclosed subject matter;

FIG. 3A shows a top actuated sub-assembly of the actuator of FIGS. 2A and 2B from one side, according to some examples of the presently disclosed subject matter;

FIG. 3B shows the top actuated sub-assembly of FIG. 3A from an opposite side, according to some examples of the presently disclosed subject matter;

FIG. 3C shows the top actuated sub-assembly of FIG. 3A in an exploded view, according to some examples of the presently disclosed subject matter;

FIG. 4A shows a bottom actuated sub-assembly of the actuator of FIGS. 2A and 2B from one side, according to some examples of the presently disclosed subject matter;

FIG. 4B shows the bottom actuated sub-assembly of FIG. 4A from an opposite side, according to some examples of the presently disclosed subject matter;

FIG. 4C shows the bottom actuated sub-assembly in an exploded view, according to some examples of the presently disclosed subject matter;

FIG. 5A shows the top and bottom actuated sub-assemblies installed together in an isometric view, according to some examples of the presently disclosed subject matter;

6

FIG. 5B shows the top and bottom actuated sub-assemblies installed together in a cut along a line A-B shown in FIG. 5A, according to some examples of the presently disclosed subject matter;

FIG. 6A shows a stationary sub-assembly of the actuator of FIGS. 2A and 2B from one side, according to some examples of the presently disclosed subject matter;

FIG. 6B shows the stationary sub-assembly of FIG. 6A from an opposite side, according to some examples of the presently disclosed subject matter;

FIG. 6C shows the stationary actuated sub-assembly in an exploded view, according to some examples of the presently disclosed subject matter;

FIG. 7 shows the actuator of FIG. 2B along a cut along line A-B shown in FIG. 2A, according to some examples of the presently disclosed subject matter;

FIG. 8 shows details of an electronic circuitry included in the stationary sub-assembly of FIGS. 6A-6C, according to some examples of the presently disclosed subject matter;

FIG. 9A shows a pitch actuation and sensing mechanism of the actuator in FIGS. 2A-2B in an isometric view, according to some examples of the presently disclosed subject matter;

FIG. 9B shows a side cut along a line A-B shown in FIG. 9A of the pitch actuation and sensing mechanism of FIG. 9A, according to some examples of the presently disclosed subject matter;

FIG. 10A shows a pitch actuation and sensing mechanism of the actuator in FIGS. 2A-2B in an isometric view, according to other examples of the presently disclosed subject matter;

FIG. 10B shows a side cut of the pitch actuation and sensing mechanism of FIG. 10A along a line A-B shown in FIG. 10A, according to some examples of the presently disclosed subject matter;

FIG. 11A shows a yaw sensing mechanism of the actuator in FIGS. 2A-2B, according to some examples of the presently disclosed subject matter;

FIG. 11B shows a yaw rotation range β , a distance R_{YAW} between a yaw Hall bar element and a yaw rotation axis, and a trajectory of a yaw sensing magnet of the yaw sensing mechanism of FIG. 11A in the Y-Z plane, according to some examples of the presently disclosed subject matter;

FIG. 11C shows one magnetic configuration for the yaw sensing magnet of FIG. 11B in a cut along a line A-B shown in FIG. 11A, according to some examples of the presently disclosed subject matter;

FIG. 11D shows another magnetic configuration for the yaw sensing magnet of FIG. 11B in a cut along a line A-B shown in FIG. 11A, according to some examples of the presently disclosed subject matter;

FIG. 11E shows yet another magnetic configuration for the yaw sensing magnet of FIG. 11B in a cut along a line A-B shown in FIG. 11A, according to some examples of the presently disclosed subject matter;

FIG. 11F shows the magnetic field as a function of rotation along a given trajectory for the cases presented in FIGS. 11C-E, according to some examples of the presently disclosed subject matter;

FIG. 11-i to FIG. 11-vi show various possible alternative examples of magnetic configuration for the yaw sensing magnet.

FIG. 12A shows a yaw magnetic actuation mechanism in an isometric view from one side, according to some examples of the presently disclosed subject matter

FIG. 12B shows the yaw magnetic actuation mechanism of FIG. 12A in an isometric view from another side, according to some examples of the presently disclosed subject matter;

FIG. 12C shows magnetic field directions in a Y-Z plane along a cut A-B in FIG. 12A, according to some examples of the presently disclosed subject matter;

FIG. 13 shows additional magnetic yoke positioned next to yaw magnet, according to some examples of the presently disclosed subject matter;

FIG. 14A is a schematic illustration of a stitched image generated from four Tele images, according to some examples of the presently disclosed subject matter;

FIG. 14B is a schematic illustration of a stitched image generated from six Tele images, according to some examples of the presently disclosed subject matter;

FIG. 14C is a schematic illustration of a stitched image generated from nine Tele images, according to some examples of the presently disclosed subject matter;

FIG. 15A is a cross section of top actuated sub-assembly and bottom actuated sub-assembly installed together along a cut along line A-B shown in FIG. 15B, according to other examples of the presently disclosed subject matter;

FIG. 15B is an isometric view of top actuated sub-assembly and bottom actuated sub-assembly installed together of the example shown in FIG. 15A, according to other examples of the presently disclosed subject matter;

FIG. 15C is an isometric view of top actuated sub-assembly and bottom actuated sub-assembly installed together, showing an external yoke, according to other examples of the presently disclosed subject matter;

FIG. 15D is a schematic illustration of a single polarization magnet, according to some examples of the presently disclosed subject matter; and

FIG. 15E is a schematic illustration of the magnetic field lines directions in a Y-Z plane of the single polarization magnet illustrated in FIG. 15D, according to some examples of the presently disclosed subject matter.

DETAILED DESCRIPTION

For the sake of clarity, the term “substantially” is used herein to imply the possibility of variations in values within an acceptable range as would be known to a person skilled in the art. According to one example, the term “substantially” used herein should be interpreted to imply possible variation of up to 10% over or under any specified value. According to another example, the term “substantially” used herein should be interpreted to imply possible variation of up to 5% over or under any specified value. According to a further example, the term “substantially” used herein should be interpreted to imply possible variation of up to 2.5% over or under any specified value. For example, the phrase substantially perpendicular should be interpreted to include possible variations from exactly 90°.

FIG. 1A illustrates a folded camera 100 with a 2 degrees-of-freedom (DOF) optical path folding element (OPFE) with an extended rotation range, according to an example of the presently disclosed subject matter. An orthogonal X-Y-Z coordinate (“axis”) system shown applies also to all following drawings. This coordinate system is exemplary only and should not be construed as limiting. In some examples, the term “extended rotation range” used herein is used to describe a rotation range larger than the 2-3 degrees necessary for another application, for example optical image stabilization (OIS). In an example, an extended rotation range may be a range equal to or greater than ± 5 degrees in

each DOF relative to an OPFE zero state (as defined below). According to another example, an extended rotation range may be a range equal to or greater than ± 10 degrees in each DOF relative to an OPFE zero state (as defined below).

According to yet another example, an extended rotation range may be a range between ± 15 -40 degrees in each DOF relative to an OPFE zero state (as defined below). The extended rotation range may or may not be equal in the two DOF. In an example, the extended rotation range may be twice or more in the yaw DOF than in the pitch DOF, because the optical effect (shift of image on the image sensor) of pitch rotation is double the optical effect of yaw rotation.

Camera 100 includes a lens assembly or lens module (or simply “lens”) 102, an OPFE 104 and an image sensor 106. In general lens module 102 comprises a plurality of lens elements positioned along an optical axis, for example between 3 to 7 lens elements. In some examples, lens 102 has a fixed focal length “f”. In other examples, lens 102 has a variable focal length (zoom lens). In some examples, lens 102 may be a lens designed for folded cameras described for example in co-owned U.S. Pat. No. 9,392,188. OPFE 104 has a reflection surface (e.g. it may be a mirror or a prism).

OPFE 104 folds light from a first optical path 108 to a second optical path 110. First optical path 108 extends from the direction of a view section 114 (facing an object or scene) towards OPFE 104 and is substantially parallel to the X axis (in the exemplary coordinate system). Second optical path 110 extends from OPFE 104 towards image sensor 106 and is substantially parallel to the Z axis (in the exemplary coordinate system).

View section 114 may include, for example, one or more objects, a scene and/or a panoramic view, etc. According to the illustrated example, axis 110 is aligned with the optical axis of lens 102, and therefore is also referred to herein as “lens optical axis”. Image sensor 106 may be aligned with a plane substantially perpendicular to axis 110 (a plane that includes the X and Y axes). Image sensor 106 may output an output image. The output image may be processed by an image signal processor (ISP-not shown), the processing including for example, demosaicing, white balance, lens shading correction, bad pixel correction and other processes that may be carried out by an ISP. In some embodiments, the ISP (or some functionalities of the ISP) may be part of image sensor 106.

It is noted that while the OPFE and some of the parts described below may be configured to rotate in two DOF, all the figures, the description and the directions therein show the OPFE in a “zero” state (without rotation) unless otherwise mentioned.

For the sake of clarity of the description and by way of a non-limiting example only, it is defined that at zero state the first optical path 108 extending from the direction of view section 114 towards the OPFE 104 is perpendicular to a zero plane. The term “zero plane” as used herein refers to an imaginary plane on which an actuator 202 described below is positioned and is parallel to the lens optical axis. For example, in a mobile phone, the zero plane is a plane parallel to the screen of the phone.

Furthermore, in zero state the reflecting surface of the OPFE is positioned such that light along the first optical path 108 is redirected to a second optical path 108 that coincides with lens optical axis 110. Notably, the above definition is assumed to be true for the center of the field of view (FOV).

Yaw rotation can be defined as rotation around an axis substantially parallel to the first optical path in zero state.

Pitch rotation can be defined as rotation around an axis substantially perpendicular to the yaw rotation axis and the lens optical axis.

In some examples, camera **100** may further include a focus or autofocus (AF) mechanism (not shown), allowing to move (or “shift” or “actuate”) lens **102** along axis **110**. The AF mechanism may be configured to adjust the focus of the camera on view section **114**. Adjusting the focus on view section **114** may bring into focus one or more objects and/or take out of focus one or more objects that may be part of view section **114**, depending on their distance from OPFE **104**. For simplicity, the description continues with reference only to AF mechanisms, with the understanding that it also covers regular (manual) focus.

An AF mechanism may comprise an AF actuation mechanism. The AF actuation mechanism may comprise a motor that may impart motion such as a voice coil motor (VCM), a stepper motor, a shape memory alloy (SMA) actuator and/or other types of motors. An AF actuation mechanism that comprises a VCM may be referred to as a “VCM actuator”. Such actuation mechanisms are known in the art and disclosed for example in Applicant’s co-owned international patent applications PCT/IB2015/056004 and PCT/IB2016/055308. In some embodiments, camera **100** may include an optical image stabilization (OIS) actuation mechanism (not shown) in addition to, or instead of, the AF actuation mechanism. In some embodiments, OIS may be achieved by shifting lens **102** and/or image sensor **106** in one or more directions in the X-Y plane, compensating for tilt of camera **100** around the Z and Y directions. A three-degrees of freedom (3-DOF) OIS and focus actuation mechanism (which performs two movements for OIS and one for AF) may be of VCM type and known in the art, for example as disclosed in international patent application PCT/US2013/076753 and in U.S. patent application Ser. No. 2014/0327965. In other embodiments, OIS may be achieved by shifting the lens in one direction (i.e. the Y direction), perpendicular to both the first and second optical paths, compensating for tilt of camera **100** around the Z direction (lens optical axis). In this case, a second OIS operation, compensating for tilt of camera **100** around the Z direction may be done by tilting the OPFE around the Y axis, as demonstrated below. More information on auto-focus and OIS in a compact folded camera may be found in Applicant’s co-owned international patent applications PCT/IB2016/052143, PCT/IB2016/052179 and PCT/IB2016/053335.

Camera **100** is designed with a capability to rotate OPFE **104** with at least two DOF (2-DOF) in an extended rotation range. Rotation can be done for example using OPFE actuator **120**, seen in FIG. **1B**. Two-DOF rotation may be used to describe rotation of the prism around two axes (each axis being a DOF); in camera **100**, the degrees of freedom are a yaw rotation **132** around yaw rotation axis **122** which is parallel to first optical path **108** (X axis) when in zero state as defined above, and a pitch rotation **134** around a pitch rotation axis **124** which is parallel to the Y axis. In camera **100**, yaw rotation axis **122** and pitch rotation axis **124** may intersect, which may reduce coupling between a pitch sensing mechanism and yaw rotation, as described below with reference to FIG. **9**. In camera **100**, lens optical axis **110** intersects the intersection point of yaw rotation axis **122** and pitch rotation axis **124**. In other embodiments, this may not be the case.

As shown in FIG. **1C**, camera **100** may be a part of a dual-camera **180**. Dual-camera **180** comprises camera **100** and an upright camera **190**. Upright camera **190** includes a

lens **192** and an image sensor **194**. Upright camera **190** may further include other parts such as a shield, a focus or AF mechanism, and/or an OIS mechanism (all of which are not shown), as known in the art. Cameras **100** and **190** may share some or all of respective fields of view (FOV_S). According to some examples, camera **190** may have a wider FOV than camera **100**. In such an example, camera **100** will be referred as a “Tele camera”, while camera **190** will be referred as a “Wide camera”. In such an example, a scanning mechanism of camera **100** may be used to cover some or all of the FOV of camera **190**, as explained in the description below of FIGS. **14A-14C**. In other examples, camera **100** may be a part of a multiple aperture camera (multi-camera) comprising more than two cameras, e.g. comprising two or more additional upright and/or two or more additional folded cameras. Notably, while characterized by extended rotation ranges, camera **100** and actuator **120** may also be capable of performing small range (1-2 degree) actuations with high accuracy, which enable OIS around any position in the extended rotation range.

FIGS. **2A-B** show OPFE actuator **120** with more details according to some non-limiting examples of the presently disclosed subject matter. FIG. **2A** shows OPFE actuator **120** in an isometric view. OPFE actuator **120** may be covered by a shield **202** with an opening **204** through which light can enter into OPFE **104** and an opening **206** through which light can exit from OPFE **104**. FIG. **2B** shows actuator **120** without shield **202**. Actuator **120** further includes a bottom actuated sub-assembly **220** (also referred to herein as “yaw sub-assembly” or “first sub-assembly”), a top actuated sub-assembly **210** (also referred to herein as “pitch sub-assembly” or “second sub-assembly”), and a stationary sub-assembly **230**. Top actuated sub-assembly **210** may be operable to be rotated, and thus rotate OPFE **104**, around the pitch rotation axis (parallel to the Y axis) relative to bottom actuated sub-assembly **220** (pitch rotation **134**), as described below. Bottom actuated sub-assembly **220** may be operable to be rotated, and thus rotate OPFE **104**, around the yaw rotation axis (parallel to the X axis) relative to stationary sub-assembly **230** (yaw rotation **132**), as described below.

As described in more detail below, according to one example, the bottom (yaw) actuated sub-assembly **220** rotates relative to a stationary sub-assembly and the top (pitch) actuated sub-assembly **210** rotates relative to the bottom sub-assembly, thus the bottom sub-assembly acts as a master and the top sub-assembly acts as a slave. Applicant has found that this design, with the bottom actuated sub-assembly used for yaw rotation and the top actuated sub-assembly used for pitch rotation, and with the bottom actuated sub-assembly serving as a master and the top actuated sub-assembly serving as a slave, enables to maintain a lower overall height of the actuator and thus to mitigate a penalty on the folded camera height.

FIGS. **3A-C** show top (pitch) actuated sub-assembly **210** with more details in an isometric view from one side (FIG. **3A**), an isometric view from another side (FIG. **3B**), and an exploded view (FIG. **3C**), according to some non-limiting examples of the presently disclosed subject matter. Top actuated sub-assembly **210** includes an OPFE holder (or carrier) **302** that can be made, for example, by a plastic mold that fits the shape of OPFE **104**. Top actuated sub-assembly **210** further includes a permanent (fixed) pitch magnet **304**. Pitch magnet **304**, as well as all other magnets in this application, can be for example a permanent magnet, made from a neodymium alloy (e.g. Nd₂Fe₁₄B) or a samarium-cobalt alloy (e.g. SmCo₅), and can be made by sintering. According to one example, pitch magnet **304** is fixedly

attached (e.g. glued) to OPFE carrier **302** from below (negative X direction in FIG. 3A). Hereinafter, the term “below” used with reference to the position of OPFE **104** refers to a side of the OPFE opposite to the side facing the view section (in the negative X direction relative to the view). Details of pitch magnet **304** and its operation are given below. In some examples, OPFE carrier **302** includes (e.g. is molded with) two pins **308**.

Sub-assembly **210** may further include two ferromagnetic yokes **306**. Ferromagnetic yokes **306** may be attached (e.g. glued) to OPFE holder **302** on pins **308**. Ferromagnetic yokes **306** may be made of a ferromagnetic material (e.g. iron) and have an arced (curved) shape with a center on pitch rotation axis **124**. Ferromagnetic yokes **306** are pulled by pitch-pull magnets **408** (see FIGS. 4A, 4C) to attach top actuated sub-assembly **210** to bottom actuated sub-assembly **220** as described below with reference to FIGS. 5A-5C. OPFE holder **302** may further include (e.g. is molded with) two parallel arc-shaped (curved) grooves **310a** and **310b** (FIG. 3B) positioned at two opposite sides of OPFE holder **302**, each arc-shaped groove having an angle $\alpha' > \alpha$, where angle α is a desired pitch stroke, as defined by optical needs. Angle α' is shown in FIG. 5B. Arc-shaped grooves **310a** and **310b** have a center of curvature on pitch rotation axis **124** (see FIGS. 3A, 5A, 5B). OPFE holder **302** further includes (e.g. is molded with) two stoppers **312** (FIG. 3A) positioned at two opposite sides of OPFE holder **302**. Stoppers **312** are used to stop OPFE **104** in a required position.

FIGS. 4A-C show bottom (yaw) actuated sub-assembly **220** with more details in an isometric view from one side (FIG. 4A), an isometric view from another side (FIG. 4B), and an exploded view (FIG. 4C). Bottom actuated sub-assembly **220** includes a middle moving frame **402** which can be made, for example, by a plastic mold. Bottom actuated sub-assembly **220** further included four permanent (fixed) magnets: a yaw actuation magnet **404**, a yaw sensing magnet **406**, and two pitch-pull magnets **408**. All magnets are fixedly attached (e.g. glued) to middle moving frame **402**. Notably, yaw magnet **404** is located on a side of the OPFE that is opposite to the side facing lens module **102** in camera **100**. Details of all magnets and their operation are given below.

Bottom actuated sub-assembly **220** further includes two stoppers **410**, made for example from a non-magnetic metal. Stoppers **410** are fixedly attached (e.g. glued) to middle moving frame **402**. Stoppers **410** help to prevent top actuated sub-assembly **210** from detaching from bottom actuated sub-assembly **220** in case of a strong external impact or drop, as described in more detail below. Middle moving frame **402** includes (i.e. is molded with) two parallel arc-shaped (curved) grooves **412** (FIG. 4A) positioned at two opposite sides of middle moving frame **402**, each arc-shaped groove having an angle $\alpha'' > \alpha$. Angle α'' is shown in FIG. 5B. Arc-shaped grooves **412** have a center of curvature on yaw rotation axis **122** (FIG. 5B) in common with arc shaped grooves **310**. Middle moving frame **402** further includes (e.g. is molded with) two parallel arc-shaped (or “curved”) grooves **414** (FIG. 4B) positioned at a back side of middle moving frame **402** (negative Z axis), each arc-shaped groove having an angle $\beta' > \beta$, where angle β is a required yaw stroke, as defined by optical needs. Angle β' is shown in FIG. 7. Arc-shaped grooves **414** have a center of curvature on yaw rotation axis **122** (FIG. 7).

FIGS. 5A-B show top actuated sub-assembly **210** and bottom actuated sub-assembly **220** installed together. FIG. 5A shows an isometric view and FIG. 5B shows a cut along line A-B in FIG. 5A. The figures also show various elements

described above. FIG. 5B shows actuator **120** with three balls **512a**, **514a** and **516a** positioned in the space between grooves **310a** and **412a**, and three balls **512b**, **514b** and **516b** positioned in the space between grooves **310b** and **412b**. FIG. 5B shows only balls **512b**, **514b** and **516b** and grooves **310b** and **412b**, while balls **512a**, **514a** and **516a** and grooves **310a** and **412a** are not seen (being in the unseen back side of the drawing), with understanding of them being symmetric along plane Z-Y. The number of balls (here 3) shown in the drawing is for the sake of example only and should not be construed as limiting. In other embodiments, an actuator such as actuator **120** may have more or fewer of three balls (e.g. 2-7 balls) in the space between adjacent grooves. The balls may be made of Alumina, another ceramic material, metal, plastic or other suitable materials. The balls may have for example a diameter in the range of 0.3-1 mm. In actuator **120**, grooves **310a**, **301b**, **412a**, **412b** and balls **512a**, **512b**, **514a**, **514b**, **516a** and **516b** form a curved ball-guided mechanism **560** operative to impart a rotation or tilt movement to an optical element (e.g. OPFE **104**) upon actuation by the VCM actuator (see below). More details on ball-guided mechanisms in actuators may be found in co-owned international patent applications PCT/IB2017/052383 and PCT/IB2017/054088.

In some embodiments, balls having different sizes (e.g. two different ball sizes) may be used to provide smoother motion. The balls can be divided into a large diameter (LD) group and a small diameter (SD) group. The balls in each group may have the same diameter. LD balls may have for example a 0.1-0.3 mm larger diameter than SD balls. A SD ball may be positioned between two LD balls to maintain the rolling ability of the mechanism. For example, balls **512b** and **516b** may be LD balls and ball **514b** may be a SD ball (and similarly for balls **512a-516a**). As described above, two metallic ferromagnetic yokes **306** that may be fixedly attached to OPFE holder **302** face two pitch-pull magnets **408** that may be attached to middle frame **402**. Ferromagnetic yokes **306** may pull magnets **408** (and thus pull top actuated sub-assembly **210** to bottom actuated sub assembly **220**) by magnetic force and hold a curved ball-guided mechanism **560** from coming apart. The magnetic force (e.g. acting between yoke **306** and magnets **408**) that is used for preventing two parts of a moving mechanism to be detached is referred to herein as “pre-load force”. A pitch-pull magnet **408** and its respective yoke **306** may be referred to as “first magnet-yoke pair”. Ferromagnetic yokes **306** and pitch-pull magnets **408** both have arc shapes, with a center on pitch rotation axis **124**. The magnetic direction of pitch-pull magnets **408** is along pitch rotation axis **124**, e.g. with a north pole toward OPFE **104** and a south pole away from OPFE **104**. Due to the geometric and magnetic design presented, the magnetic force (pre-load force) between ferromagnetic yokes **306** and pitch-pull magnets **408** is kept substantially in a radial direction **520** with a center on pitch rotation axis **124**, and negligible tangent force, at all rotation positions, as can be seen in FIG. 5A.

Balls **512a-516a** and **512b-516b** prevent top actuated sub-assembly **210** from touching bottom actuated sub-assembly **220**. Top actuated sub-assembly **210** is thus confined with a constant distance from bottom actuated sub-assembly **220**. Curved ball-guided mechanism **560** further confines top actuated sub-assembly **210** along pitch rotation axis **124**. Top actuated sub-assembly **210** can only move along the path defined by curved ball-guided mechanism **560**, namely in a pitch rotation **134** around pitch rotation axis **124**.

FIGS. 6A-C show stationary sub-assembly **230** with more details, in an isometric view from one side (FIG. 6A), an

isometric view from another side (FIG. 6B) and an exploded view (FIG. 6C). Stationary sub-assembly 230 includes a base 602 that can be made, for example, by plastic mold. Stationary sub-assembly 230 further includes electronic circuitry 608 attached to base 602, shown in FIG. 6C. Details of electronic circuitry 608 are given below with reference to FIG. 8. Stationary sub-assembly 230 further includes a ferromagnetic yoke 606. Ferromagnetic yoke 606 is made by ferromagnetic material (e.g. iron) and is pulled by yaw actuation magnet 404 (see FIGS. 6B and 7C) to attach bottom actuated sub-assembly 220 to stationary sub-assembly 230 as described in more detail below. Ferromagnetic yoke 606 and yaw actuation magnet 404 may be referred to as "second magnet-yoke pair".

Stationary actuated sub-assembly 230 further include a stopper 610. Stopper 610 is made for example from a non-magnetic metal. Stopper 610 is attached (e.g. glued) to base 602. Stopper 610 helps to prevent bottom actuated sub-assembly 220 from detaching from base 602 in case of a strong external impact or drop, as described in more detail below. In some examples, base 602 includes (i.e. is molded with) two parallel arc-shaped (curved) grooves 612a-d (FIG. 6A), each arc-shaped groove having an angle $\beta'' > \beta$, where angle β is a required tilt stroke, as defined by optical needs. Angle β'' is shown in FIG. 7. Arc-shaped grooves 612a-d may further include a center of curvature on yaw rotation axis 122 (FIGS. 2C, 6A and 7), in common with arc-shaped grooves 414a-b.

FIG. 7 shows actuator 120 without the shield along a cut along line A-B seen in FIG. 2A. Grooves 612a-d are shown to share a center with grooves 414a-b on yaw rotation axis 122 (612c and 612d, which are shown in FIGS. 6B and 6C are hidden in FIG. 7). Angles β' and β'' are demonstrated. Grooves 612a-b are adjacent to groove 414a while grooves 612c-d are adjacent to groove 414b. Four balls 712 (two are shown in FIG. 7) are positioned between adjacent groove pairs 612a and 414a, 612b and 414a, 612c and 414b, and 612d and 414b, one ball between each adjacent groove pair. In other embodiments, actuator 120 may have more than one ball pair in each adjacent groove pair, e.g. in the range of 1-4 balls. The considerations for size and materials of all balls are similar to those described above. Grooves 414a-b, 612a-d and balls 712 form a second curved ball-guided mechanism 760 of actuator 120. As shown in FIG. 6 and FIG. 7, the second curved ball-guided mechanism is situated such that the grooves 612 for rotating around the yaw axis are located behind OPFE 104 i.e. in the positive direction along the Z axis relative to OPFE 104 (a side opposite to the side facing the lens module).

As described above, ferromagnetic yoke 606 is fixedly attached to base 602 facing magnet 404 (illustrated for example in FIG. 4a and FIG. 4c). Ferromagnetic yoke 606 pulls magnet 404 (and thus pulls bottom actuated sub-assembly 220) to stationary sub-assembly 230 by magnetic force 702 (pre-load force) and thus holds curved ball-guided mechanisms 760 from coming apart. The direction of magnetic force 702 is marked in FIG. 7 as the Z direction. Balls 712 prevent bottom actuated sub-assembly 220 from touching stationary sub-assembly 230. Bottom actuated sub-assembly 220 is thus confined with a constant distance from stationary sub-assembly 230. Second curved ball-guided mechanism 760 further confines bottom actuated sub-assembly 220 along the Y-axis. Bottom actuated sub-assembly 220 can only move along the path defined by the curved ball-guided mechanism 760, namely in a yaw rotation around yaw rotation axis 122.

The curved ball-guided mechanisms 560 and 760 disclosed herein provides flexibility when defining the pitch and yaw rotation axes respectively, as the curve can be adapted to the required rotation axis. Furthermore, curved ball-guided mechanisms 560 and 760 enable to execute movement of the top actuated sub-assembly and the bottom actuated sub-assembly by rolling over the balls confined within the grooves (rails) along the path prescribed by the grooves, and thus help to reduce or eliminate friction that may otherwise exist during movement between the balls and the moving parts.

FIG. 8 shows electronic circuitry 608 with more details, according to some examples of the presently disclosed subject matter. Electronic circuitry 608 includes a printed circuit board (PCB) 802 and may include processing circuitry. PCB 802 allows sending input and output currents to coils 806 and 804 and to Hall bar elements 808 and 810 (described below), the currents carrying both power and electronic signals needed for operation. PCB 802 may be connected electronically to host camera (camera 100 or similar cameras) or host device (e.g. phone, computer, not shown) e.g. by wires (not shown). PCB 802 may be a flexible PCB (FPCB) or a rigid flex PCB (RFPCB) and may have several layers (e.g. 2-6) as known in the art. Electronic circuitry 608 further includes three coils, a pitch coil 804 and two yaw coils 806. Electronic circuitry 608 further includes two Hall bar sensing elements, a pitch Hall bar element 808 and a yaw Hall bar element 810. Coils 804 and 806 and Hall bar elements 808 and 810 are all connected (e.g. soldered) to PCB 802. In actuator 120, pitch coil 804 and pitch Hall bar element 808 are positioned below pitch magnet 304. Notably, some of the components mentioned as part of the electronic circuitry are also considered as part of an actuation and sensing mechanism.

Notably, yaw rotation axis 122 is positioned as closely as possible to the pitch sensor (e.g. Hall bar element 808). According to one example, yaw rotation axis 122 passes through pitch sensor 808, in order to decouple the sensing of the pitch sensor from the rotation around the yaw axis. When decoupled, the influence on the sensing of the pitch sensor by rotation around the yaw axis is reduced or eliminated. More specifically, according to one example, yaw rotation axis 122 passes through the center of pitch sensor 808. By positioning the yaw rotation axis so it passes through the center of the pitch sensor, the influence of yaw rotation on the sensing of pitch sensor can be completely eliminated. In addition, in some designs, yaw rotation axis 122 may optionally pass through the center of pitch coil 804.

FIGS. 9A-B show an example of a pitch actuation and sensing mechanism (PAASM) 900 that includes pitch magnet 304, pitch coil 804 and pitch Hall bar element 808. PAASM 900 may be included in actuator 120. In some embodiments, PAASM 900 may be used only for actuation (acting as an actuation mechanism for one DOF). FIG. 9A shows PAASM 900 in an isometric view and FIG. 9B shows a side cut of pitch magnet 304 along a line A-B. According to one example, pitch magnet 304 may be symmetric along a plane that includes pitch rotation axis 124 and first optical axis 108. In an example, pitch magnet 304 may be fabricated (e.g. sintered) such that it has a changing magnetic field direction along its mechanical symmetry plane, e.g. a north magnetic field facing the positive X direction on the left side and a north magnetic field facing the negative X direction on the right side. Pitch magnet 304 may have a length R_{PITCH} of a few millimeters (for example 2-6 mm) in parallel to pitch rotation axis 124 and substantially longer than pitch coil 804, such that its magnetic field on most lines parallel

to pitch rotation axis **124** may be considered constant. Upon driving a current in pitch coil **804**, a Lorentz force is created on pitch magnet **304**; a current in a clockwise direction will create force in the positive Z direction (along the Z axis), while a current in counter clockwise direction will create a force in the negative Z direction. Any force on pitch magnet **304** is translated to torque around pitch rotation axis **124**, and thus top actuated subassembly **210** will rotate relative to bottom actuated sub-assembly **220**.

Pitch Hall bar element (sensor) **808**, which is positioned inside pitch coil **804**, can sense the intensity and direction of the magnetic field of pitch magnet **304** radially directed away from pitch rotation axis **124**. In other words, for any pitch orientation of top actuated sub-assembly **210**, pitch Hall bar measures the intensity of the magnetic field directed in the X direction only. Since yaw rotation axis **122** passes through pitch Hall bar element **808**, the effect of the yaw rotation of bottom actuated sub-assembly **220** on the magnetic field in the X direction applied by pitch magnet **304** is reduced (e.g. eliminated) and thus any change on the measurement of pitch Hall bar element **808** is reduced (e.g. eliminated) as well. By positioning the Hall bar element **808** such that the yaw rotation axis **122** passes through its center, the effect of the yaw rotation of bottom actuated sub-assembly **220** on the magnetic field in the X direction applied by pitch magnet **304** is reduced (e.g. minimized) and thus any change on the measurement of pitch Hall bar element **808** is mitigated. Pitch Hall bar element **808** can thus measure the respective pitch rotation of top actuated sub-assembly **210** while being unaffected by the yaw rotation of bottom actuated sub-assembly.

FIGS. **10A-B** show another exemplary embodiment of a PAASM numbered **1000**, similar to PAASM **900**. PAASM **1000** may be included in actuator **120**, to replace PAASM **900**. According to one example, a pitch magnet **1004** replaces pitch magnet **304**. Pitch magnet **1004** is a cut of a sphere with its center positioned substantially on the intersection point of yaw rotation axis **122** and pitch rotation axis **124**. According to one example, a pitch coil **1006** that replaces pitch coil **804** has a circular shape with a center substantially on yaw rotation axis **122** (in some examples the yaw rotation axis passes exactly through the center of the coil). Pitch coil **1006** may be made (fabricated) with similar considerations presented above for pitch coil **804**. Due to the symmetry of the pitch magnet around yaw rotation axis **122**, any yaw rotation will not influence the magnetic field of the pitch coil and thus will not change the force applied by pitch coil **1006** on pitch magnet **1004**. Having a constant force for various yaw positions may facilitate and simplify pitch position control (close loop control or open loop control). As mentioned above, yaw rotation axis passes through sensor **808** to thereby reduce the effect of yaw rotation of bottom actuated sub-assembly **220** on the magnetic field in the X direction applied by pitch magnet **1004**.

FIG. **11A** shows a yaw sensing mechanism numbered **1100**. Yaw sensing mechanism **1100** includes yaw sensing magnet **406** and yaw Hall bar element **810**. Yaw Hall bar element **810** can measure the intensity and direction of the magnetic field of yaw sensing magnet **406** directed along yaw rotation axis **122**. In other words, Hall bar element **810** measures the intensity of magnetic field directed in the X direction only.

FIG. **11B** shows a yaw rotation range β a distance R_{YAW} between yaw Hall bar element **810** and yaw rotation axis **122**, and a trajectory **1108** of yaw sensing magnet **406** in the Y-Z plane. In some examples, yaw rotation range β is more than 10 degrees. The distance R_{YAW} is e.g. in the range of 2-5

mm. As an example, a case in which $\beta=40^\circ$ (meaning $\pm 20^\circ$ from the "zero" position) and $R_{YAW}=2.75$ mm is analyzed in FIGS. **11C-F** below. As bottom actuated sub-assembly **220** is yaw-rotated, trajectory **1108** is in the Y-Z plane. Trajectory **1108** has an arc projection in the Y-Z plane (FIG. **11B**) with length $\beta \times R_{YAW}$, where β is calculated in radians. Trajectory **1108** has a line shape projection on the X-Y plane (FIGS. **11C-E**) with length $2 \times R_{YAW} \times \cos(\beta)$.

Yaw sensing magnet **406** is designed such that it has dimensions along Z-Y directions and such that it covers trajectory **1108** from the top view (Y-Z plane). Yaw sensing magnet **406** can have different configurations.

FIGS. **11C-E** show three different examples of magnetic configurations for yaw sensing magnet **406** in a cross section along X-Y plane of yaw sensing mechanism **1100**. In the configuration of FIG. **11C**, yaw sensing magnet **406** has a rectangular cross section and the magnetic field of yaw sensing magnet **406** changes direction in the middle, e.g. the north magnetic field facing the positive X direction on the left side and the north magnetic field facing the negative X direction on the right side. In the configuration of FIG. **11D**, yaw sensing magnet **406** has a rectangular cross section, and the magnetic field of yaw sensing magnet **406** is directed in the Y direction.

In the configuration shown in FIG. **11E**, yaw sensing magnet **406** is characterized, along the Y direction, by a thinner cross section (the Y-X plane) in the middle and a thicker cross section on the sides. The varying width results in a varying distance between the sensor and the magnet positioned near the magnet (the sensor is located towards the negative X direction relative to the magnet) and thus a varying magnetic field along a projection of trajectory **1108** (line **1114**) on the Y-X plane. In some examples, the variation around the magnetic field is symmetrical around its center such that the thickness of the cross section of the magnet increases from a point substantially at its center towards each end of the magnet. Various examples of magnets constructed according to this principle are illustrated in FIGS. **11-i** to **11-vi**.

In addition, in some examples of the configuration of FIG. **11E** (or any one of FIGS. **11-i** to **11-vi**), the magnetic field of yaw sensing magnet **406** changes direction in the middle, e.g. the north magnetic field faces the positive X direction on the left side and the north magnetic field faces the negative X direction on the right side. This results in zero magnetic field in the X direction in yaw hall bar element **810** facing the center of magnet **406** (along the center line).

FIG. **11F** shows the magnetic field as a function of rotation along trajectory **1108**, for the 3 cases presented in FIGS. **11C-E**. The projection of trajectory **1108** on plane X-Y (representing a lateral shift component of the magnet shift relative to the sensor) is shown by line **1110** in FIG. **11C**, line **1112** in FIG. **11D** and line **1114** in FIG. **11E**. For line **1110**, the maximal magnetic field change along ± 20 degrees trajectory is ± 0.28 Tesla. However, most of the magnetic field change is obtained in a ± 7 degrees trajectory and the magnetic field gradient at higher yaw angles is lower than at lower yaw angles. This limits the ability to sense changes with high accuracy in high yaw angles. For projection line **1112**, the magnetic field gradient is more uniform along the trajectory of ± 20 , comparing to projection line **1110**. However, the magnetic field total change is limited to under ± 0.08 Tesla. For projection line **1114** the magnetic field gradient is more uniform than for both lines **1110** and **1112**, and the total magnetic field change is ± 0.25 Tesla, which can give high accuracy for position measurements. Thus, the magnetic configuration presented

in FIG. 11E is superior for position sensing at large strokes, relative to the distance between the Hall bar and the corresponding magnet (e.g. in 1-4 mm range) using changes in magnetic field. Thus, by shaping the magnet with a variable thickness as shown in FIGS. 11E and 11-i to 11-vi, the range of detectable change in magnetic flux is increased. Accordingly, the corresponding detectable range of relative (lateral) shift of the magnet and sensor is increased as well.

FIG. 12A-C shows a yaw magnetic actuation mechanism numbered 1200. This actuation mechanism is for a second DOF. FIG. 12A show isometric view from one side, FIG. 12B shows isometric view from another side. Yaw magnetic actuation mechanism 1200 include yaw actuation magnet 404, yaw coils 806 and ferromagnetic yoke 606. FIG. 12C shows the magnetic field directions is Y-Z plane, along a cut A-B in FIG. 12A. Yaw actuation magnet 404 may be sintered such that its magnetic field is pointed toward negative Z direction. Each of coils 806 has one part (1202, 1204) which is positioned in close proximity to yaw actuation magnet 404 (e.g. distance of 100-300 μm), and one part (1206, 1208) which is further apart from yaw magnet 404. Coils 806 may be connected in serial, such that the current in the two coil is equal. When current in 1202 is in the positive X direction the current in 1204 is also in the positive X direction, and the current in parts 1206 and 1208 is in the negative X direction. Upon driving a current in Yaw coils 806, a Lorentz force is created on the yaw magnet 404, according to $d\vec{F} = Id\vec{l} \times \vec{B}$. The direction of the magnetic field is demonstrated in FIG. 12C. The Lorentz force is translated into torque around yaw rotation axis 122.

In some examples, an additional magnetic yoke 1302 may be located next to yaw magnet 404. This yoke may increase the intensity of the magnetic field in coils 806 and increase the torque created by yaw magnetic actuation mechanism 1200. FIG. 13 shows this case.

In some examples, rotation of the reflecting element around one or two axes moves the position of the camera FOV, wherein in each position a different portion of a scene is captured in an image having the resolution of the digital camera. In this way a plurality of images of adjacent camera FOV_S (e.g. partially overlapping FOV_S) are captured and stitched together to form a stitched (also referred to as “composite”) image having an overall image area of an FOV greater than digital camera FOV.

In some examples the digital camera can be a folded Tele camera configured to provide a Tele image with a Tele image resolution, the folded Tele camera comprising a Tele image sensor and its Tele lens assembly is characterized with a Tele field of view (FOV_T).

According to some examples, the folded Tele camera is integrated in a multiple aperture digital camera that comprises at least one additional upright Wide camera configured to provide a Wide image with a Wide image resolution, being smaller than the Tele image resolution, the Wide camera comprising a Wide image sensor and a Wide lens module with a Wide field of view (FOV_W); wherein FOV_T is smaller than FOV_W, wherein rotation of the OPFE moves FOV_T relative to FOV_W, for example as shown in of co-owned international patent applications PCT/IB2016/056060 and PCT/IB2016/057366.

The description of these PCT applications includes a Tele camera with an adjustable Tele field of view. As described in PCT/IB2016/056060 and PCT/IB2016/057366, rotation of the reflecting element around one or two axes moves the position of Tele FOV (FOV_T) relative to the Wide FOV (FOV_W), wherein in each position a different portion a scene

(within FOV_W) is captured in a “Tele image” with higher resolution. According to some examples, disclosed in PCT/IB2016/056060 and PCT/IB2016/057366, a plurality of Tele images of adjacent non-overlapping (or partially overlapping) Tele FOV_S are captured and stitched together to form a stitched (also referred to as “composite”) Tele image having an overall image area of an FOV greater than FOV_T. According to some examples, the stitched Tele image is fused with the Wide image generated by the Wide camera.

Digital camera 100 can further comprise or be otherwise operatively connected to a computer processing circuitry (comprising one or more computer processing devices), which is configured to control the operation of the digital camera (e.g. camera CPU). The processing circuitry, can comprise for example a controller operatively connected to the actuator of the rotating OPFE configured to control its operation.

The processing circuitry can be responsive to a command requesting an image with a certain zoom factor and control the operation of the digital camera for providing images having the requested zoom. As mentioned in applications PCT/IB2016/056060 and PCT/IB2016/057366, in some examples a user interface (executed for example by the processing circuitry) can be configured to allow input of user command being indicative of a requested zoom factor. The processing circuitry can be configured to process the command and provide appropriate instructions to the digital camera for capturing images having the requested zoom.

In some cases, if the requested zoom factor is a value between the FOV_W of a wide camera and FOV_T of a tele camera, the processing circuitry can be configured to cause the actuator of the reflecting element to move the reflecting element (by providing instruction to the controller of the actuator) such that a partial area of the scene corresponding to the requested zoom factor is scanned and a plurality of partially overlapping or non-overlapping Tele images, each having a Tele resolution and covering a portion of the partial area, are captured. The processing circuitry can be further configured to stitch the plurality of captured imaged together in order to form a stitched image (composite image) having Tele resolution and an FOV greater than the FOV_T of the digital camera. Optionally the stitched image can then be fused with the Wide image.

FIG. 14A is a schematic illustration of an example of a stitched image 1400 generated by scanning, capturing and stitching together four Tele images with FOV_T, compared to the FOV_W of a Wide camera, as in the example of FIG. 1C, where camera 190 represents a Wide FOV camera with a FOV_W coupled to folded Tele camera 100 with a FOV_T. In FIG. 14A, 1402 denotes FOV_W, 1404 denotes FOV_T at the center of FOV_W and 1406 indicates the size of the requested zoom factor. In the illustrated example, four partially overlapping Tele images 1408 are captured.

Notably, the overall area of captured Tele images 1408 is greater than the area of the zoom image 1406 in the requested zoom. The central part of the captured Tele images is extracted (e.g. by the computer processing circuitry as part of the generation of the stitched image) for generating stitched image 1400. This helps to reduce the effect of image artefacts resulting from transition from an image area covered by one image to an image area covered by a different image.

FIG. 14B is a schematic illustration of an example of a stitched image 1400' generated by capturing and stitching together six Tele images. FIG. 14C is a schematic illustration of an example of a stitched image 1400'' generated by capturing and stitching together nine Tele images. The same

principles described with reference to FIG. 14A apply to FIGS. 14B and 14C. Notably, the output image resulting from the stitching can have a different width to height ratio than the single image proportion. For example, as illustrated in FIG. 14B, a single image can have a 3:4 ratio and the output stitched image can have a 9:16 ratio.

It is noted that image stitching per se is well known in the art and therefore it is not explained further in detail.

An alternative design of the top and bottom actuated sub-assemblies described above is now described with reference to FIGS. 15A-15E. Notably, as would be apparent to any person skilled in the art, unless stated otherwise, some of the details described above with reference to the previous figures can also be applied to the example described with reference to FIGS. 15A-15E.

According to this design, a single magnet 1510 serves for three purposes: 1) as a pre-load magnet in magnet-yoke pair, dedicated for fastening the bottom actuated sub-assembly to the stationary sub-assembly; 2) as a yaw actuation magnet dedicated for generating yaw movement of bottom actuated sub-assembly; and 3) as a yaw sensing magnet for sensing yaw movement.

FIG. 15A shows a magnet 1506 and a yoke (e.g. a ferromagnetic plate such as iron) 1504, where the magnet and yoke are pulled together by pre-load force (indicated by black double head arrow) and thus fasten top actuated sub-assembly 210 to bottom actuated sub-assembly 220. In some examples, magnet 1506 and yoke 1504 are positioned substantially at the center (relative to the Y axis direction) of the top actuated sub-assembly. Pitch rotation axis relative to the bottom actuated sub-assembly is demonstrated by the circular arrow 1508.

FIG. 15B shows top and bottom actuated sub-assemblies in isometric view. FIG. 15B illustrates magnet 1510 located at the internal part of bottom actuated sub-assembly, sensor 1512 and a coil 1514, which is located at the back of bottom actuated sub-assembly (in the positive Z direction relative to magnet 1510). According to one example, a single coil can be used for actuation.

As shown in FIG. 15C, yoke 1516, is fastened to the stationary sub-assembly. Magnet 1510 and yoke 1516 are attracted by pre-load force to thereby fasten bottom actuated sub-assembly 220 to stationary sub-assembly 230. Coil 1514 is positioned in close proximity to yaw actuation magnet 1510 (e.g. distance of 100-300 μm). When current is applied in coil 1514, a Lorentz force is created on yaw magnet 1510 according to $d\vec{F} = Id\vec{T} \times \vec{B}$, where the Lorentz force is translated into torque around yaw rotation axis 122 (not shown) as explained above.

Magnet 1510 moves along the yaw direction as part of the bottom actuated sub-assembly. In addition of being more compact, this type of yaw actuation mechanism also provides better efficiency, as it does not generate force in the opposite direction to the desired yaw movement.

As explained above, in some examples top actuated sub-assembly 210 includes an OPFE holder (or carrier) 302 and bottom actuated sub-assembly includes a middle moving frame 402. According to an example, yoke 1504 is attached (e.g. glued) to the holder and the first magnet-yoke pair (1506-1504) pulls the OPFE holder to the middle moving frame. Alternatively, the position of the magnet and yoke can be switched. The stationary sub-assembly includes a base and the yoke is attached to the base in a manner that the second magnet-yoke pair (1510-1516) pulls the middle moving frame to the base. Also, in an example coil 1514 and sensor 1512 are fixed (e.g. glued) to the base.

According to some examples of the presently disclosed subject matter yaw magnet 1510, which also serves as yaw sensing magnet, is made to have an increased detection range. To this end, magnet 1510 is made to have a single magnetic polarization direction as indicated by the back arrow extending from the south pole to the north pole of magnet 1510 shown in FIG. 15D. The directions of the magnetic field lines are indicated by arrows a-e in FIG. 15D and in more detail in FIG. 15E, which is a top view of magnet 1510. As indicated by arrows a-e, as a result of the single magnetic polarization direction of magnet 1510, the angle of the magnetic field relative to the magnet surface changes continuously along the length of magnet. The illustration shows the angle changing from being substantially perpendicular in the positive direction at one end, to being in a parallel direction at the magnet center and to being substantially perpendicular in the negative direction at the other one. Since the relative changes (e.g. of magnetic flux) are detectable at each of the points where change in the direction of the magnetic field occurs, yaw movement of the magnet relative to sensor 1512 can be detected over an increased range. The increased detection range of the yaw magnet as disclosed herein enables to use the same magnet for both actuation and sensing, eliminating the need for two separate magnets.

Note that unless stated otherwise terms such as “first” and “second” as used herein are not meant to imply a particular order but are only meant to distinguish between two elements or actions in the sense of “one” and “another”.

While this disclosure has been described in terms of certain embodiments and generally associated methods, alterations and permutations of the embodiments and methods will be apparent to those skilled in the art. The disclosure is to be understood as not limited by the specific embodiments described herein, but only by the scope of the appended claims.

All references mentioned in this specification are herein incorporated in their entirety by reference into the specification, to the same extent as if each individual reference was specifically and individually indicated to be incorporated herein by reference. In addition, citation or identification of any reference in this application shall not be construed as an admission that such reference is available as prior art to the present application.

What is claimed is:

1. An actuator for rotating an optical path folding element (OPFE), comprising:

- a first sub-assembly;
- a second sub-assembly; and
- a stationary sub-assembly,

wherein the first sub-assembly is configured to rotate the OPFE relative to the stationary sub-assembly in an extended rotation range around a yaw rotation axis,

wherein the second sub-assembly is configured to rotate the OPFE relative to the first sub-assembly in an extended rotation range around a pitch rotation axis that is substantially perpendicular to the yaw rotation axis, wherein a respective rotation of the OPFE is used for performing optical image stabilization (OIS),

and wherein the actuator is included in a folded camera.

2. The actuator of claim 1, further comprising a voice coil motor (VCM) comprising a magnet and a coil, wherein a driving current in the coil creates a force that is translated to a torque around a respective rotation axis.

3. The actuator of claim 2, further comprising a first sensor configured to sense the rotation around the yaw rotation axis and a second sensor configured to sense the

21

rotation around the pitch rotation axis, the first and second sensors being fixed to the stationary sub-assembly, wherein at least one of the first sensor or the second sensor is a magnetic flux sensor.

4. The actuator of claim 2, wherein the magnet is fixedly attached to one of the first sub-assembly or the second sub-assembly, and wherein the coil is fixedly attached to the stationary sub-assembly.

5. The actuator of claim 3, wherein the second sensor is positioned such that sensing by the second sensor is decoupled from the rotation of the OPFE around the yaw rotation axis.

6. The actuator of claim 1, wherein the OIS compensates for tilt of the folded camera around two directions.

7. The actuator of claim 1, wherein the rotation of the OPFE for performing OIS enables performing OIS around any position in the extended rotation range.

8. The actuator of claim 1, wherein the folded camera comprises a lens and an image sensor, and wherein the lens or the image sensor are moved for OIS in addition to the rotation of the OPFE for performing OIS.

9. The actuator of claim 1, wherein the folded camera comprises a lens and an image sensor, and wherein the lens is moved for focusing.

10. The actuator of claim 1, wherein the extended rotation range is equal to or greater than ± 2 degrees around each of the pitch and yaw rotation axes.

22

11. The actuator of claim 1, wherein the extended rotation range is equal to or greater than ± 3 degrees around each of the pitch and yaw rotation axes.

12. The actuator of claim 1, wherein the extended rotation range is equal to or greater than ± 4 degrees around each of the pitch and yaw rotation axes.

13. The actuator of claim 1, wherein the extended rotation range is equal to or greater than ± 5 degrees around each of the pitch and yaw rotation axes.

14. The actuator of claim 1, wherein the extended rotation range is equal to or greater than ± 10 degrees around each of the pitch and yaw rotation axes.

15. The actuator of claim 1, wherein the extended rotation range is between ± 15 -40 degrees around each of the pitch and yaw rotation axes.

16. The actuator of claim 1, wherein the folded camera is included in a mobile device.

17. The actuator of claim 16, wherein the mobile device also includes a second camera that has a field of view (FOV) greater than a FOV of the folded camera.

18. The actuator of claim 16, wherein the mobile device is a smartphone.

19. The actuator of claim 16, wherein the mobile device is a tablet.

* * * * *