

US011735040B2

(12) **United States Patent**  
**Houssami**

(10) **Patent No.:** **US 11,735,040 B2**  
(45) **Date of Patent:** **\*Aug. 22, 2023**

(54) **PACE DELINEATION JIBE IOTA**

*G08G 1/08* (2013.01); *G08G 1/164* (2013.01);  
*G08G 1/166* (2013.01); *H04W 84/00*  
(2013.01)

(71) Applicant: **Rami B. Houssami**, Herndon, VA (US)

(72) Inventor: **Rami B. Houssami**, Herndon, VA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(58) **Field of Classification Search**

CPC .... *G08G 1/0145*; *G08G 1/0112*; *G08G 1/052*;  
*G08G 1/08*; *G08G 1/164*; *G08G 1/166*;  
*B60W 30/00*; *H04W 84/00*; *G05D 1/021*  
See application file for complete search history.

(21) Appl. No.: **17/373,077**

(22) Filed: **Jul. 12, 2021**

(65) **Prior Publication Data**

US 2022/0005347 A1 Jan. 6, 2022

**Related U.S. Application Data**

(63) Continuation of application No. 16/866,340, filed on May 4, 2020, now Pat. No. 11,062,596, which is a continuation of application No. 15/497,124, filed on Apr. 25, 2017, now Pat. No. 10,643,464.

(60) Provisional application No. 62/326,833, filed on Apr. 25, 2016.

(51) **Int. Cl.**

*G08G 1/00* (2006.01)  
*G08G 1/01* (2006.01)  
*G08G 1/16* (2006.01)  
*G08G 1/08* (2006.01)  
*G05D 1/02* (2020.01)  
*B60W 30/00* (2006.01)  
*H04W 84/00* (2009.01)  
*G08G 1/052* (2006.01)

(52) **U.S. Cl.**

CPC ..... *G08G 1/0145* (2013.01); *B60W 30/00*  
(2013.01); *G05D 1/021* (2013.01); *G08G*  
*1/0112* (2013.01); *G08G 1/052* (2013.01);

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,788,232 A \* 1/1974 Schneider ..... B61B 13/00  
104/28  
6,587,781 B2 \* 7/2003 Feldman ..... H04W 12/02  
340/909  
7,075,427 B1 \* 7/2006 Pace ..... B61L 23/06  
246/126  
8,571,743 B1 \* 10/2013 Cullinane ..... G08G 1/166  
701/23  
9,704,047 B2 \* 7/2017 Shima ..... G06V 20/00  
9,841,287 B1 \* 12/2017 Hayward ..... G05D 1/0223

(Continued)



*Primary Examiner* — Ojiako K Nwugo

(74) *Attorney, Agent, or Firm* — Fish & Richardson P.C.

(57) **ABSTRACT**

With the aim of contributing to the optimization of commuting systems, roadways, and other motion systems, Pace Delineation jibe iota (PD) addresses the issue of crossing paths of travel. PD is the process of gathering and analyzing velocities, positions, and other parameters and properties of traversing units to determine the velocities of each such that they do not arrive at the intersections at the same time. Such coordination can help avoid the stoppage of vehicles at an intersection, and collisions obviously. The process also accommodates an overtaking condition which may be used to prioritize emergency responders or other traversals.

**16 Claims, 6 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

2002/0026278	A1 *	2/2002	Feldman	.....	G08G 1/0104	2013/0014683	A1 *	1/2013	Hoyt	.....	B63H 9/061
					701/414						114/102.13
2004/0039504	A1 *	2/2004	Coffee	.....	B28C 5/422	2013/0116865	A1 *	5/2013	Cooper	.....	B61L 27/16
					701/482						701/20
2006/0007039	A1 *	1/2006	Duvall	.....	G01S 5/0072	2013/0117054	A1 *	5/2013	Cooper	.....	G06Q 10/083
					342/357.55						705/7.12
2006/0181433	A1 *	8/2006	Wolterman	.....	G08G 1/164	2013/0194423	A1 *	8/2013	Baines	.....	B61L 23/00
					340/905						348/148
2008/0128563	A1 *	6/2008	Kumar	.....	B61L 3/127	2014/0361126	A1 *	12/2014	Steffen	.....	B61L 29/32
					246/187 A						246/473.1
2009/0005929	A1 *	1/2009	Nakao	.....	B60T 7/22	2015/0232097	A1 *	8/2015	Luther	.....	B60W 30/188
					701/33.4						701/1
2009/0063030	A1 *	3/2009	Howarter	.....	G08G 1/096783	2016/0155329	A1 *	6/2016	Goto	.....	G08G 1/096716
					701/117						340/903
2011/0123961	A1 *	5/2011	Staplin	.....	G09B 9/052	2016/0176399	A1 *	6/2016	Takagi	.....	B60W 30/16
					434/64						701/301
						2016/0231746	A1 *	8/2016	Hazelton	.....	G05D 1/0274
						2016/0341555	A1 *	11/2016	Laur	.....	G08G 1/164
						2017/0217276	A1 *	8/2017	Banvair	.....	B60G 17/0195

\* cited by examiner




Fig 1.1




Fig 1.0




Fig 1.3




Fig 1.2




Fig 2.0




Fig 3.0




Fig 3.1




Fig 4.0




Fig 5.0



## 1

## PACE DELINEATION JIBE IOTA

## CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. application Ser. No. 16/866,340, filed May 4, 2020, which is a continuation of U.S. patent application Ser. No. 15/497,124, filed Apr. 25, 2017 and issuing as U.S. Pat. No. 10,643,464, which claims the benefit of U.S. Provisional Application No. 62/326,833, filed Apr. 25, 2016. The contents of the prior applications are incorporated herein by reference.

## BACKGROUND

The process herein described coordinates the velocities of traversing units across a demarcated zone where paths of different units intersect such that collision and stoppage of the traversing units are avoided.

## BRIEF SUMMARY

Pace Delineation jibe iota (PD) is a process for jibing the velocities of traversing units, such as autonomous vehicles, through an intersection as to avoid collision and stoppage. With the increasing utility of autonomous vehicles, the capability to efficiently and safely cross intersections with the least complications would likely enhance that utility. Such a method can be accomplished using different types of communications protocols and straightforward computations and formulas. By utilizing communication channels between a central controller or temporary host, and the Traversing Units (TU's), and/or sufficiently equipped infrastructure, along with the sharing of data pertinent to compartmentalizing the crossing of the Demarcated Zone (DZ), the PD process can be a robust and effective way to increase the efficiency of intersection traversal, and easily accommodate the prioritization of emergency vehicles, responders, and others. Usage can range from aiding automated logistics systems to applications in Infrastructure as a Platform (TAP), Vehicular communication systems, vehicle ad hoc networks (VANETs).

## BRIEF DESCRIPTION

PD is accomplished by using defined distances, velocities of the TU's intended path to calculate the time required to traverse the DZ in its entirety, then deriving an adjusted velocity for each TU such that the time within the DZ is distinguished and does not coincide with any other TU's or its margins. The calculations require distance parameters which are provided by PD-components that may be embodied by appropriately configured vehicle-to-infrastructure (V2I), vehicle-to-vehicle (V2V) communications, vehicle-to-everything (V2X), VANETs, and other proximity or remote communication protocols

The PD process distinguishes the crossing times by coordinating the velocities of the TU's such that they do not cross the DZ at the same time. The calculations may also account for universal margins defined by the a PD implementing system, such as safety margins added between each TU, or a TU's own margins which may simply take the form of length parameters and accommodate for protruding and non-permanent objects.

## BRIEF DESCRIPTION OF THE FIGURES

FIG. 1.0 is a wireframe of a four-way intersection with an ideal PDC layout embedded as infrastructure components;

## 2

FIG. 1.1 is a wireframe of a three-way intersection with an idea PDC layout embedded as infrastructure components;

FIG. 1.2 is a wireframe of a four-way intersection displaying a pathway through the RZ & DZ, and highlighting the distance variables used in PD iterations;

FIG. 1.3 is a wireframe of a three-way intersection displaying a pathway through the RZ & DZ, and highlighting the distance variables used in PD iterations;

FIG. 2.0 is flow chart displaying an ideal procession of a PD iteration for sequential jibing, i.e. delineation in the order of checkin;

FIG. 3.0 a visualization of the data stored by a counting element (DZ counter) with three time ranges of occupancy;

FIG. 3.1 is a visualization of the data stored by a counting element (DZ counter) with three time slots of occupancy, and highlighting the range of vacancy and availability for traversal;

FIG. 4.0 illustrates the presence of virtual margins around traversing units; and

FIG. 5.0 is a flow chart displaying an ideal procession of a PD iteration including a priority condition

## DETAILED DESCRIPTION

The pace delineation process described herein addresses the problem of intersecting paths between objects in motion, such as autonomous vehicles on roadways or logistic transport units in a warehouse. It is with this description, the pace delineation jibe iota is disclosed within its most basic form, yet of such form that the scope of the invention and implementation will be fully conveyed to anyone skilled in the art.

Pace delineation is accomplished through a series of steps collecting, sending and receiving data transmissions, all of which may involve signal communications, computation, and condition validations executed by a software platforms that may reside on vehicles, infrastructure, or ad hoc networks. Data sources may come from GPS, near field, wifi, 5 g, V2X (Vehicle to everything), vehicle ad hoc networks (VANETs), and other vehicular communication systems or protocols. A PDC is a conceptual point but also take a physical form as sensor, RFID reader, 5 g signal communications device, or other electronic component that may relay the arrival of a TU at the point defining the distances used to calculate the adjusted velocities.

Pace Delineation (PD)	The process herein described
Traversing Unit (TU)	A unit intended to pass through the demarcated zone
Demarcated Zone (DZ)	An area demarcated as the area TU's avoid being inside at the same time. The area where the travel paths of different TU's intersect.
PD Component (PDC)	A source representing and/or transmitting TU information used in the PD process. PDC outputs, whether from a sensor integrated within infrastructure, or stemming from accurate GPS coordinates, virtual V2V platforms, are primarily used to mark the location of a TU, its distance to the DZ, and the distance till it exits the DZ. The three PDC's types are a, b, and c, (figure 2) which mark a TUs full trajectory through a regulated zone. The distances between these points may be predetermined or derived on an ad hoc basis.
Regulated Zone (RZ)	The area consisting of the PDC layout and the travel paths of TU's, including the DZ.
Central Unit (CU)	The unit(s)/module that receives and facilitates the computation of pertinent variables, as well as the communication of computed outputs, such

-continued

	as adjusted velocities. The CU may either consist of, or leverage DZ-occupancy time values from a time counting mechanism.
Adjusted Velocity	The velocity calculated by the CU such that a TU does not enter the DZ while its occupied.
DZ counter	a mechanism that continuously stores and refreshes, and makes available the times a DZ is occupied. It may contain one sum of time a DZ will be reserved for preceding TU's at that instance in time, or an series of time slots represented by ranges of times when the DZ will be occupied or unoccupied which will include unoccupied times in-between occupied times. A dynamic log of time slots.
Occupied DZ	the state of the DZ when a TU or its margins, plus any universal margins if any, reside inside the DZ, or a DZ that has a TU(s) entering earlier than that of a later TU.
target _c	a TU's intended destination in terms of PDCs. The exit point of the DZ.
approbated velocity	signal output by the CU when the adjusted velocity equals the initial velocity ( $V^* = V_i$ ). This term is conceptual signifying if an initial velocity $V_i$ does not require adjustment to traverse the DZ safely
priority ranking	a property of a TU that PD uses to prioritize its traversal through the DZ, where a high priority ranking for TUs, such as emergency vehicles or law enforcement, will validate the derivation of traversing times earlier than other TU's.
lead condition	the condition that specifies a TU does not have any preceding TUs, and hence its $V^*$ is calculated without the t.c ( $\Sigma t.c$ ) of a preceding TU. This condition may not be maintained throughout the traversal.
overtake	results when the CU determines a traversal time slot ahead of another TU, regardless of the order of arrival.
checkin; checks in	a TU begins interacting with the regulated zone, conditionality's, initial velocity, target_c, priority ranking, and other parameters are captured at this step in the delineation process.
checkout; checks out	a TU, and the defined length margins fully exit clearing the DZ. Its relative time to clear (t.c) the DZ reaches zero. A signal useful to serve in the validation or evaluation of the state of the DZ.

To facilitate the description of the PD process, below are two tables of key terms and variables used for this application.

disAB	Distance from PDC_a to PDC_b, the area where a TU adjusts its speed
disBC	distance of the TU's target path from PDC_b to PDC_c, the area within the DZ
disAC	the total distance a TU travels within the regulated zone
disUm	The total physical length of each TU plus any additional virtual margins uniquely defined for each TU. disUm is considered from the point that would first enter the DZ (some distance in front of the TU: disU_front) to the last point that exits the DZ (some distance behind the TU: disU_ear) Allowing for margins around the TU's physical dimensions allows to accommodate for protruding, non-permanent objects, changes to the vehicles dimensions, and safety. The front and rear variations are denoted on the left, and refer to the distance in-front of the physical dimensions,
disTU_front	
disTU_rear	
$\mu$	a global margin that may be added to all TU disUm's and hence affect respective target velocity calculations. $\mu$ 's may be universally applied to all TUs, or premised on conditions, such as vehicle type, traffic density, whether conditions, and so on.

-continued

$V_i$	initial velocity of the TU as it enters the RZ at PDC_a
$V^*$	adjusted velocity, calculated by the CU and relayed back to the TU
dis. $\Delta s$	the distance covered by a TU between the previous velocity and its adjusted velocity.
t.c	the time a TU clears the DZ such that its disUm and any appended $\mu$ is completely outside the DZ.
t. $\Delta s$	time passed or will pass between a TU's previously relayed velocity and its current velocity amid continuous adjustment
10 t.ci	a TU's time to clear the DZ based on its initial velocity ( $V_i$ ), before adjustment
t.b	a TU's time to reach the DZ, i.e. time to reach PDC_b
$\Sigma t.c$	the t.c of the last preceding TU at a moment of query. This is not to be understood as the sum of each distinct TU's t.c's but the t.c. of the last TU as this itself accounts for the t.c's of all TU's preceding it; a value that increases as TU's checkin yet is always counting down as units traverse.

20 A PDC providing the position of a TU from entry to exit of an RZ, is important to signify the distances used to compute target velocities for TU's. Such sources may come from GPS, near field, wifi, 5 g, V2X (Vehicle to everything), vehicle ad hoc networks (VANETs), and other vehicular communication systems or protocols. A PDC is a conceptual point but also take a physical form as sensor, RFID readers, 25 5 g signal communications device, or other electronic components that may relay the arrival of a TU at the point defining the distances used to calculate the adjusted velocities. The layout provided in FIGS. 1.0 and 1.1 show a four-way and three-way intersection shows the conceptual layout of a PDC components a, b, and c where component 'a' is the entry point into the RZ. 'b' is the entry point into the DZ, and 'c' is the exit or check out area. As stated in the definitions table, PDC may be embodied by virtual plat- 30 forms, ad hoc networks, so long as they convey the arrival of a vehicle, and represent the disAB, and disBC in some machine readable and transmittable form.

In FIGS. 1.0 and 1.1, objects 10 and 11 represent PDC 40 embodiments as infrastructure components where 10 represents point PDC 'a' and 11 represents both PDC 'b' and 'c', to keep the diagram free from clutter. It is granted the same effects of this PDC layout as infrastructure may be extrapolated through virtual platforms, GPS coordinates, and other PDC data sources. Intuitively, one may note that the disAB 45 is the very distance between PDC 'a' and PDC 'b', as shown in FIGS. 1.2 and 1.3 item number 12; and the same conclusion may be made about the disBC being the distance between PDC 'b' and 'c'.

A TU checks in at PDC 'a', and has the distance of disAB to adjust its velocity to the target velocity before reaching point 'b' which marks the beginning of the DZ. As TU's check in at PDC 'a', a DZ timing element will receive updated expected clearing times. The clearing times will be 55 derived with respect to the velocities being approbated in PD. For the purpose of this disclosure, we will assume that check in occurs as the physical TU passes PDC 'a' triggering the check in. This results in the subtraction of two terms in the velocity derivations later (disU\_front &  $\mu$ ) because these 60 distances will already be inside the RZ upon check in, and PD delineates such that these virtual margins do not intersect and are treated as part of TU's dimensions.

It is worth noting the PDC layout may be rearranged, not only tailored to each intersection, but different PDC layouts 65 may occupy the same intersection to avoid having two vehicles traveling straight across the DZ yet not intersecting needing to adjust velocities. With different arrangements,

## 5

pace delineation can be further customized, this herein provides simply the fundamental principles and functions of delineating velocities.

With an adequate PDC layout, attention is now placed on the role of the central unit (CU), and idealized electronic component that leverages the communications of TU properties, the DZ counter element, and acquired or predetermined distance parameters of the PDC layout, and facilitates the computation and transmittal of a target velocity for TU's.

The CU does not have to itself be a central or contiguous component, but should in aggregate perform the operations herein described. The role of CU may be embodied in distributed software, and in temporary manifestations, such as in the case of VANETs.

The CU's operations account for the parameters described such as  $disUm$  for TU's,  $\mu$ 's, the distance till its target\_c, priority rankings, among others. These parameters are involved in the CU iteration. The flow chart in FIG. 2.0 shows the PD process at a high level for sequential jibing, the delineation of TU velocities preserving the order in which TU's checked in. In 100 the TU checks through one of the manifestations of PDC 'a', and the TU parameters described are captured via one of the communication channels described above. In 200 the CU initiates its iteration. In general, and from the perspective of the TU, one of the primary conditions is whether the  $t.ci$  (the time to clear to the DZ given the TUs initial velocity) is less than the current  $\Sigma t.c$  ( $t.c$  of the most recently traversing TU) captured in decision node 300. The implication here is that the TU with shorter (or earlier)  $t.c$  is that it will arrive at the DZ before preceding TU's, and out of order.

for TU's that do not meet this condition, the operation at 400, the CU approbates the  $V_i$  which may find similar manifestations as in the CU still calculates the TU's  $V^*$  and concludes with the same velocity. Such a signal may even be interpreted by the TU to accelerate up until its  $t.c$  is as close as the virtual margins allow as to seal the gaps in the DZ counter's time logs. For TU's meeting the condition, and thus will be arriving at the DZ out of order given their  $V_i$ , the CU computes the target velocity  $V^*$  for the respective TU at 500. The computation is:

$$V^* = \frac{disAB_{TU} - dc \cdot \Delta s_{TU} - disTU_{front}}{\Sigma t \cdot c \pm t \cdot \Delta s_{TU}}$$

The term  $disTU_{front}$  is subtracted if PDC 'a' is triggered by the physical TU at the beginning of point 'a' for checkin, because with this configuration, the TU checks in and its virtual margins in front are already inside the RZ. This assumes virtual margins are of reasonable length and do not exceed  $disAB$ . If a universal margin was applied, the  $\mu_{front}$  would also be subtracted in the numerator. The CU then outputs  $V^*$  to the respective CU at 600 and the iteration resets with 700. It is assumed with this calculation that the  $dc \cdot \Delta s_{TU}$  and the term  $t \cdot \Delta s_{TU}$  is provided by the TU, motion capture system, GPS, or other sensor system external to the PD process. The terms are provided here though they are dependent on the adjusted velocity from a pervious iteration. As a TU's  $V^*$  is calculated for the first time, this term is null/zero as there is no change toward a an adjusted velocity.

$$V^*_{TU2} = \frac{disAB_{TU2} - dc \cdot \Delta s_{TU2} - disTU2_{front} - \mu_{front}}{\Sigma t \cdot c \pm t \cdot \Delta s_{TU2}}$$

## 6

At 800 the process resembles the first iteration, with only the conceptual difference that the velocities captured are not at this point the initial velocities. Step 900 proceeds with the next iteration similar to 200. When  $V^*$  is calculated again in subsequent iterations  $dc \cdot \Delta s_{TU}$  and  $t \cdot \Delta s_{TU}$  can be used. Any TU's checking in while other TU's are already traversing will receive a  $V^*$  calculated with respect to the  $\Sigma t.c$  of the last TU in sequence. For example if TU2 checks in while TU1 is traversing, the  $V^*$  for TU2 is calculated using the formula:

$$V^*_{TU2} = \frac{disAB_{TU2} - dc \cdot \Delta s_{TU2} - disTU2_{front}}{\Sigma t \cdot c \pm t \cdot \Delta s_{TU2}}$$

where  $\Sigma t.c = t.c_{TU1}$

The preceding process make use of a mechanism fundamental to PD, and crucial to its execution, which is the DZ counter element. The DZ counter element may take form in electronic memory, local hardware flash or distributed systems, among other electronic storage solutions, and serves as a log of time ranges that represent the time a DZ is occupied. As with the other descriptions, herein is an idealized DZ counter for one DZ however an individual skilled in the art may apply this time ledger technique to multiple DZ's under one DZ counter, or multiple DZ counters to one DZ for various PD configurations.

The DZ counter is configured to receive time values that represent the times an area will be occupied by a traversing unit. These values may be stored as an array, indexed table, dictionary, data frame, or various other data formats. The time values for an occupied DZ will inherently go up as TU's check in, and count down as units traverse the DZ. A visualization of DZ counter values could look like is provided in FIGS. 3.0 and 3.1.

In FIG. 3.0, 21 is a timeline starting from  $t$  and extending to the right at some interval  $x$ . 20 represent the times a DZ will be unavailable for traversal, meaning any  $V^*$  calculations must not use the times beneath a 20 block. These blocks do include virtual margins  $disUm$  as well as any  $\mu$ 's imposed by the CU. FIG. 4.0 illustrates the extension of a virtual margins from, and affixed to, a TU; where 40 is a TU and 41 is the direction and magnitude of travel, and 42 is the virtual margin  $disUm$ . Any  $\mu$  imposed herein will be added to the the 42's which directly affect the  $V^*$ 's.

In sequential delineation, sequencing traversal by order of checkin, if a TU checks into a DZ with the DZ counters time log shown in FIG. 3.0, the time used to calculate  $V^*_{TUx}$  would be greater than  $t+5x$ .

In optimized delineation, where  $V^*$ 's are calculated to maximize traversal rates regardless of checkin order, we can find that a CU may sort out these time gaps by using a TU's  $V_i$ , to determine initial arrival time to the DZ, and its  $t.c.i$ . This range can be paired with the gaps in occupied time ranges existing in the DZ counters time log where the gaps represent availability of the DZ. Pairing the respective TU's initial traversal time range (given its  $V_i$ ) with available time range to traverse may be done by computing the differences between all TU's  $t.c$  and the next TU's arrival time which represents a duration of vacancy in the DZ. The difference between traversing TU's  $t.c$  and the next TU's arrival time may be paired with the initial traversal time range of a TU by searching the times of vacancy that are greater than the TU's traversal duration. The pairing of traversal durations with gaps between other traversals is best illustrated in FIG. 3.1 where 22 is the difference between two traversing units

exit and entry times.  $V^*$  may be calculated to minimize the change of velocity by running the computation on prospect time slots and determine which would require the least change from  $t_{c,i}$  or  $V_i$ .

Two functions described above require one more flow chart depicting a PD iteration accounting for priority rankings and optimized delineation. The flow chart of FIG. 5.0 starts off with an PD initiation at **1000** and checked in TU parameters are gathered, including priority ranking, at **1100**. With this iteration, the condition at **1200** validates potential priority rankings. Any  $V^*$  being calculate for TU's meeting this condition can assume the lead condition shown in **1300** such that their  $t_{c,i}$  virtually remains un changed or even decreases in duration as all subsequent TU's  $V^*$  are derived from  $t_{c,s}$  of preceding vehicles. If a priority vehicles  $V^*$  is calculated with the lead condition, subsequent TU's  $V^*$  will reflect this change. Any TU with the lead condition at that point is likely to become the second TU at **1500**. However at **1400** through the optimized delineation, the original leading TU may be better off jibing with a slot based on the logic in paragraph 18 above.

PD sequence of occurrence highlights: The following describes PD process's, conditionality's, and sequence of occurrence.

A PD iteration is run; time in between iterations may vary, with an ideal implementation utilizing short time intervals between iterations; the number of TU's already checked in may vary, from zero or greater.

TU's check in and are sequenced in order of entering and interacting with the Regulated Zone.

Conditions determining computations: lead condition, an ideal implementation of PD would check for any priority ranking.

If no preceding TU's ( $\sum t_{c,i}=0$ ) or if  $t_{c,i}$  of the TU  $> \sum t_{c,i}$ , i.e. the TU's  $V_i$  means TU reaches the DZ after the duration of the DZ's  $t_{c,i}$  ( $\sum t_{c,i}$ ) then  $V_i$  may remain as  $V^*$ , where  $V_i$  is an approbated velocity.

overtake condition: if  $t_{c,i}$  is well earlier than TU's ahead sequentially, quicker TU may overtake a sequence number; this condition may also be met by emergency vehicles such as ambulances, fire & rescue, and law enforcement even when their initial time to clear is not earlier than proceeding TU's, earlier sequence numbers may be granted to such prioritized TU's.

sequenced condition: DZ is occupied at time of checkin CU receives TU's  $V_i$ , target  $t_{c,i}$ , margin dimensions ( $disUm$ ), speeds rate of change

CU computes and relays  $V^*$ 's to all checked in TU's, this jibe of the regulated zone is iterative and can be run continuously, with multiple iterations throughout a TU's traversal through the regulated zone.

CU calculates the adjusted velocity  $V^*$  and relays the value(s) to the relative TU(s)

$V^*$  calculation: a TU's  $V^*=(disAB-dc.\Delta s-disUm-\mu)\div(\sum t_{c,i}\pm t.\Delta s)$

\* $\sum t_{c,i}$ =the  $t_{c,i}$  of the preceding TU—time since original  $t_{c,i}$  was calculated

the TU's  $t_{c,i}$  with no preceding TU's or TU's whose  $V_i$  does not bring the TU into the an occupied DZ:  $t_{c,i}=(disAC+disUm_{rear}+\mu_{rear})\div(V_i)$

When a TU checks out, the proceeding TU's  $V^*$  calculations assume the free-form due to the now meeting the lead condition.

The following embodiments demonstrate different scenarios handled by Pace Delineation to aid in the conceptualization of the process; these scenarios now assume TU

checkins when a virtual margin reaches PDC 'a'. Each variable below is followed by an underscore and sequence identifier.

i.e., Variable source:

5  $disUm\_TU1$ front-to-back=the distance of TU1's margins (the first lead TU)

$V^*\_TU2$ =the adjusted velocity for TU2 (the second sequenced TU)

Scenario 1—one TU, no preceding TU's, i.e.

10 TU1 checks in—meets lead condition

CU computes free-form:

$t_{c,i}\_TU1=(disAC\_TU1+disUm\_TU1\text{front-to-back}+\mu)\div(V_i\_TU1)$

15  $V^*\_TU1=(disAB\_TU1-dc.\Delta s\_TU1+disUm\_TU1\text{front})\div(t_{c,i}\_TU1\pm t.\Delta s\_TU1)$

CU computes/delineates  $V^*$  till TU1 checks out

Scenario 2—two TU's,

TU1 checks in—meets lead condition

20 CU computes:  $t_{c,i}\_TU1=(disAC\_TU1+disUm\_TU1\text{front-to-back}+\mu)\div(V_i\_TU1)$   $V^*\_TU1=(disAB\_TU1-dc.\Delta s\_TU1+disUm\_TU1\text{front})\div(t_{c,i}\_TU1\pm t.\Delta s\_TU1)$

TU2 checks in—meets sequenced condition

CU computes:  $V^*\_TU2=(disAB\_TU2-dc.\Delta s\_TU2+disUm\_TU2\text{front})\div(\sum t_{c,i}\_TU1\pm t.\Delta s\_TU2)$

CU delineates  $V^*$ 's till TU's check out

Scenario 3—four TU's,

TU1 checks in—meets lead condition

30 CU computes:  $t_{c,i}\_TU1=(disAC\_TU1+disUm\_TU1\text{front-to-back}+\mu)\div(V_i\_TU1)$   $V^*\_TU1=(disAB\_TU1-dc.\Delta s\_TU1+disUm\_TU1\text{front})\div(t_{c,i}\_TU1\pm t.\Delta s\_TU1)$

TU2 checks in—sequenced condition

CU computes:  $V^*\_TU2=(disAB\_TU2-dc.\Delta s\_TU2+disUm\_TU2\text{front})\div(\sum t_{c,i}\_TU1\pm t.\Delta s\_TU2)$

35  $t_{c,i}\_TU2=(disAC\_TU2-dc.\Delta s\_TU2+disUm\_TU\text{front-to-back}+\mu)\div V^*\_TU2$

TU3 checks in—meets sequenced condition

40 CU computes:  $V^*\_TU3=(disAB\_TU3-dc.\Delta s\_TU3+disUm\_TU3\text{front}+\mu)\div(\sum t_{c,i}\_TU2\pm t.\Delta s\_TU3)$

$t_{c,i}\_TU3=(disAC\_TU3-dc.\Delta s\_TU3+disUm\_TU3\text{front-to-back}+\mu)\div V^*\_TU3$

TU4 checks in—meets sequenced condition

45 CU computes:  $V^*\_TU4=(disAB\_TU4-dc.\Delta s\_TU4+disUm\_TU4\text{front}+\mu)\div(\sum t_{c,i}\_TU3\pm t.\Delta s\_TU4)$

$t_{c,i}\_TU4=(disAC\_TU4-dc.\Delta s\_TU4+disUm\_TU4\text{front-to-back}+\mu)\div V^*\_TU4$

CU delineates  $V^*$ 's till all TU's check out

Scenario 4—overtake condition—

TU1 checks in—meets lead condition

CU computes:  $t_{c,i}\_TU1=(disAC\_TU1+disUm\_TU1\text{front-to-back}+\mu)\div(V_i\_TU1)$   $V^*\_TU1=(disAB\_TU1-dc.\Delta s\_TU1+disUm\_TU1\text{front})\div(t_{c,i}\_TU1\pm t.\Delta s\_TU1)$

TUambulance (TUamb) checks in—meets overtake condition

TUamb prioritized in next iteration,  $V^*\_TUamb$  calculated under lead condition CU computes:

$t_{c,i}\_TUamb=(disAC\_TUamb+disUm\_TUamb\text{front-to-back}+\mu)\div(V_i\_TUamb)$

$V^*\_TUamb=(disAB\_TUamb-dc.\Delta s\_TUamb+disUm\_TUamb\text{front}+\mu)\div(t_{c,i}\_TUamb\pm t.\Delta s\_TUamb)$

TU<sub>1</sub> now meets sequenced condition

$V^*\_TU1=(disAB\_TU1-dc.\Delta s\_T1+disUm\_TU1\text{front}+\mu)\div(\sum t_{c,i}\_TUamb\pm t.\Delta s\_TU1)$

65  $t_{c,i}\_TU1=(disAB\_TU1-dc.\Delta s\_TU1+disUm\_TU1+\mu)\div(V^*\_TU1)$

CU delineates  $V^*$ 's till TU's check out

What is claimed:

1. A system comprising:
  - a plurality of first pace delineation components arranged according to a first layout, the first pace delineation components being configured to obtain data indicative of a check in of a first traversing unit at a first regulated zone associated with a particular intersecting path;
  - a plurality of second pace delineation components arranged according to a second layout, the second pace delineation components being configured to obtain data indicative of a check in of a second traversing unit at a second regulated zone associated with the particular intersecting path; and
  - a processor configured to:
    - obtain the data indicative of the check in and a virtual margin of the first traversing unit from one of the first pace delineation components and the data indicative of the check in and a virtual margin of the second traversing unit from one of the second pace delineation components;
    - determine a first target velocity for the first traversing unit based on the data indicative of the check in and a virtual margin of the first traversing unit and the data indicative of the check in and a virtual margin of the second traversing unit; and
    - transmit, to the first traversing unit, data indicative of the first target velocity of the first traversing unit to enable the first traversing unit to travel according to the first target velocity through a demarcated zone.
2. The system of claim 1, wherein the first target velocity is the same as a first velocity of the first traversing unit.
3. The system of claim 1, wherein the first target velocity is greater than a first velocity of the first traversing unit.
4. The system of claim 1, wherein the first target velocity is greater than a first velocity by an amount that the first traversing unit has a time to clear the demarcated zone that is less than or equal to a time to clear of the second traversing unit based on the data indicative of the check in and the virtual margin of the first traversing unit and the data indicative of the check in and the virtual margin of the second traversing unit.
5. The system of claim 1, wherein:
  - the virtual margin of the first traversing unit is a universal margin or a margin assigned to the first traversing unit; and
  - the virtual margin of the second traversing unit is a universal margin or a margin assigned to the second traversing unit.
6. The system of claim 5, wherein:
  - the universal margin is a safety margin added between two or more traversing units;
  - the margin assigned to the first traversing unit is determined based on length parameters of the first traversing unit and is configured to accommodate for protruding and non-permanent objects; and
  - the margin assigned to the second traversing unit is determined based on length parameters of the second traversing unit and is configured to accommodate for protruding and non-permanent objects.
7. The system of claim 1, wherein:
  - the virtual margin of the first traversing unit is zero; or
  - the virtual margin of the second traversing unit is zero.
8. The system of claim 1, wherein the processor is configured to transmit, to the second traversing unit, data indicative of a second target velocity to enable the second

- traversing unit to travel according to the second target velocity through the demarcated zone; and
  - wherein the first target velocity and the second target velocity are configured to allow for a temporal spacing or a physical spacing between the first traversing unit and the second traversing unit within the demarcated zone.
- 9. The system of claim 8, wherein the temporal spacing allows for spacing between an entry time of the first traversing unit and an exit time of the second traversing unit.
- 10. The system of claim 1, wherein each of the first pace delineation components and the second pace delineation components comprises one of a sensor, RFID reader, or 5G signal communications device.
- 11. The system of claim 1, wherein the processor is configured to:
  - transmit, to the second traversing unit, data indicative of a second target velocity to enable the second traversing unit to travel according to the second target velocity through the demarcated zone; and
  - wherein the first target velocity and the second target velocity are configured to minimize a time during which the demarcated zone is vacant of traversing units.
- 12. The system of claim 1, wherein the processor is configured to:
  - obtain priority rankings of the first traversing unit and the second traversing unit; and
  - transmit, to the second traversing unit, data indicative of a second target velocity determined according to the priority rankings to enable the second traversing unit to travel according to the second target velocity through the demarcated zone, wherein the first target velocity is different from the second target velocity.
- 13. The system of claim 1, wherein the plurality of first pace delineation components and the plurality of second pace delineation components are rearrangeable.
- 14. The system of claim 1, wherein the first regulated zone, the second regulated zone, and the demarcated zone have variable size and shape.
- 15. The system of claim 1, wherein
  - at least one of the first pace delineation components is configured to:
    - provide data indicative of a particular velocity of the first traversing unit, a priority ranking of the first traversing unit, a distance to an entry point of the demarcated zone, and a distance to an exit point of the demarcated zone; and
    - receive data from one or more motion capture systems; and
  - at least one of the second pace delineation components is configured to:
    - provide data indicative of a particular velocity of the second traversing unit, a priority ranking of the second traversing unit, a distance to an entry point of the demarcated zone, and a distance to an exit point of the demarcated zone; and
    - receive data from the one or more motion capture systems.
- 16. The system of claim 15, wherein:
  - the processor is configured to obtain the data through communication channels between one or more of a central controller, a temporary host, one or more traversing units, and equipped infrastructure.