

US011767073B2

(12) **United States Patent**
Staples

(10) **Patent No.:** **US 11,767,073 B2**
(45) **Date of Patent:** **Sep. 26, 2023**

(54) **BICYCLE DROPPER SEAT POST ASSEMBLY WITH A LOCKING SPRING CARTRIDGE**

FOREIGN PATENT DOCUMENTS

(71) Applicant: **D3 Innovation Inc.**, Squamish (CA)

EP 2657113 10/2013
EP 3196107 7/2017

(Continued)

(72) Inventor: **Jonathan Staples**, Garibaldi Highlands (CA)

OTHER PUBLICATIONS

(73) Assignee: **D3 Innovation Inc.**, Squamish (CA)

Mad Suspension Manic Drop Post, information found online at https://www.xfusionshox.com/products_detail/44.htm 2020.

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 90 days.

(Continued)

(21) Appl. No.: **17/495,925**

Primary Examiner — Milton Nelson, Jr.

(22) Filed: **Oct. 7, 2021**

(74) *Attorney, Agent, or Firm* — Marks & Clerk; Kevin Shipley

(65) **Prior Publication Data**

US 2022/0111919 A1 Apr. 14, 2022

Related U.S. Application Data

(60) Provisional application No. 63/089,738, filed on Oct. 9, 2020.

(51) **Int. Cl.**
B62J 1/08 (2006.01)

(52) **U.S. Cl.**
CPC **B62J 1/08** (2013.01); **B62J 2001/085** (2013.01)

(58) **Field of Classification Search**
CPC B62J 1/08; B62J 2001/085; B62J 1/00
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS


3,730,019 A 5/1973 Ballard
4,354,398 A 10/1982 Porter
4,421,357 A 12/1983 Shimano

(Continued)

(57) **ABSTRACT**

A dropper post assembly for supporting a bicycle seat may include an outer tube extending along a post axis and an inner tube configured to be axially slidable within the outer tube by a travel distance that is at least 200 mm between a retracted and an extended position. The inner tube may have an outer diameter that is between 25.5 mm and 30 mm, and when the inner tube is in the extended position a moment of inertia (Ix) taken adjacent the seat collar is at least 11,000 mm⁴. A spring cartridge may have an unlocked configuration in which the spring cartridge exerts an extension force (FE) on the inner tube that biases the inner tube toward the extended position, and a locked configuration in which the spring cartridge is operable to generate a degassing force (FD) of between about 90 lbs and about 140 lbs to resist movement of the inner tube toward the retracted configuration. An actuator may be operable to change the spring cartridge between the locked configuration and the unlocked configuration.

18 Claims, 8 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

4,807,856 A 2/1989 Teckenbrock
 4,916,968 A 4/1990 Kabaya
 4,995,753 A 2/1991 Shook
 5,226,624 A 7/1993 Kingsbery
 5,244,301 A 9/1993 Kurke et al.
 5,466,042 A 11/1995 Herman
 5,649,738 A 7/1997 Thomson
 5,664,829 A 9/1997 Thomson
 5,722,718 A 3/1998 Still et al.
 5,829,733 A 11/1998 Becker
 5,857,657 A 1/1999 Yamamoto
 5,881,988 A 3/1999 Liu
 5,899,530 A 5/1999 Tedesco
 5,909,890 A 6/1999 Sachs
 5,979,978 A 11/1999 Olsen et al.
 6,220,582 B1 4/2001 Wandschneider
 6,276,756 B1 8/2001 Cho
 7,007,587 B2 3/2006 Zanden
 7,059,592 B2 6/2006 Huh
 7,083,180 B2 8/2006 Tumer
 7,231,866 B2 6/2007 Seong
 7,721,640 B2 5/2010 Lee
 7,845,602 B1 12/2010 Young
 8,079,772 B1 12/2011 Brennan et al.
 8,167,373 B2 5/2012 Allison
 8,177,251 B2 5/2012 Shirai
 8,191,964 B2 6/2012 Hsu
 8,308,124 B2 11/2012 Hsu
 8,550,551 B2 10/2013 Shirai
 8,814,109 B2 8/2014 Laird et al.
 8,926,216 B2 1/2015 McAndrews
 9,073,592 B2 7/2015 Hsu
 9,688,331 B1 6/2017 Shirai
 9,878,753 B2 1/2018 Tsai
 9,969,448 B1 5/2018 Chen
 10,549,803 B2 2/2020 Shipman et al.
 10,787,215 B1 9/2020 Staples
 10,974,781 B2 4/2021 Staples
 11,180,212 B2 11/2021 Shirai
 11,447,201 B2 9/2022 Coaplen et al.
 2002/0185581 A1 12/2002 Trask
 2004/0065238 A1 4/2004 Chen
 2005/0067863 A1 3/2005 Roizen
 2006/0066074 A1 3/2006 Turner
 2006/0152045 A1 7/2006 Okajima et al.
 2007/0046081 A1 3/2007 Shook
 2007/0063554 A1 3/2007 Liao
 2007/0286671 A1 12/2007 Meggiolan
 2009/0066124 A1 3/2009 Pirovano
 2010/0052377 A1 3/2010 Hsu et al.
 2011/0097139 A1 4/2011 Hsu
 2011/0291446 A1 12/2011 Bourgeois
 2012/0098175 A1 4/2012 Wu
 2012/0181824 A1 7/2012 Hsu et al.
 2013/0269655 A1 10/2013 Yamazaki
 2014/0239682 A1 8/2014 Tisue
 2014/0305253 A1 10/2014 Tseng
 2015/0145294 A1 5/2015 Kench, III
 2015/0191208 A1 7/2015 Hsu
 2015/0232142 A1* 8/2015 Shirai B62K 19/36
 403/104
 2015/0232158 A1 8/2015 Bouse et al.
 2017/0166275 A1 6/2017 McPherson et al.
 2017/0225731 A1 8/2017 Hsu
 2018/0015976 A1 1/2018 Hermansen et al.
 2018/0057087 A1 3/2018 Jhou et al.

2018/0127041 A1 5/2018 Tsai
 2019/0263464 A1 8/2019 Staples
 2019/0283827 A1 9/2019 Shipman et al.
 2019/0300088 A1 10/2019 Jordan
 2019/0301497 A1 10/2019 Jordan
 2020/0023918 A1 1/2020 Shirai
 2020/0070913 A1 3/2020 Staples
 2020/0140029 A1 5/2020 Shipman et al.
 2021/0214031 A1 7/2021 Liao
 2022/0111919 A1 4/2022 Staples
 2022/0153371 A1 5/2022 Tung

FOREIGN PATENT DOCUMENTS

TW I562922 12/2016
 TW 201730032 9/2017
 TW 201801969 1/2018
 TW M562805 7/2018
 WO WO2016029301 3/2016

OTHER PUBLICATIONS

Fox Transfer Hydraulic Infinite Adjust Seat Post, information found online at <https://www.ridefox.com/family.php?m=bike&family=seatpost> 2020.
 KS Suspension LEV Intergra dropper post, information found online at <https://www.kssuspension.com/product/lev-integra/> 2020.
 9point8 The Fall Line dropper post, information found online at https://www.9point8.ca/index.php?route=product/product&path=42&product_id=213 2020.
 Contact SL Switch Seatpost. Online at <<https://www.giant-bicycles.com/ca/contact-sl-switch-seatpost>> 2019.
 Crankbrothers Kronolog Adjustable Seat Post. Online at <<https://www.pinkbike.com/news/Crankbrother-Kronolog-Adjustable-Seat-Post.html>> 2019.
 RASE Components, LLC Launches the Mamba Rapid Adjust Seatpost. Online at <https://www.pinkbike.com/news/rase-mamba-rapid-adjust-post-2008.html> 2019.
 Third party prior art submission made to German patent office dated Feb. 9, 2022 regarding related German application No. 10 2020 109 014.5, including copies of references i) TW I562922, ii).
 Notice of third party opinion art submission made to TW IPO dated Sep. 1, 2021 in related ROC (Taiwan) Pat. Appln. No. 109111138.
 Translation of Office action dated Mar. 3, 2022 in related ROC (Taiwan) Pat. Appln. No. 109111138.
 Translation of Office action dated Nov. 17, 2021 in related ROC (Taiwan) Pat. Appln. No. 109111138.
 Third Party Submission of Prior Art dated Jan. 28, 2022 in related Canadian application No. 3,077,761.
 A webpage entitled "Model: 2017 LEV/LEV 272" showing product specifications and figures of a bicycle seat tube provided by Kind Shock Hi-Tech Co., Ltd. and downloadable from the Wayback Machine at <https://web.archive.org/web/20170610095807/kssuspension.com/wp-content/uploads/2016/12/2017-Lev-drawing.pdf>, available at least as early as Jun. 10, 2017.
 A webpage entitled "Model: LEV 272" showing an exploded view of a bicycle seat tube provided by Kind Shock Hi-Tech Co., Ltd. and downloadable from the Wayback Machine at <https://web.archive.org/web/20170629100108/http://kssuspension.com/wp-content/uploads/2015/12/LEV-272.PDF>, available at least as early as Jun. 10, 2017.
 2018 LEV dropper post drawings from Kind Shock Hi-Tech Co., dated Jan. 4, 2018.

* cited by examiner




FIG 1.




FIG 2.




FIG 3.




FIG. 4.




FIG. 5.




FIG 6.






FIG 7.






FIG 10.




FIG 11.





FIG 14.




FIG 15.

BICYCLE DROPPER SEAT POST ASSEMBLY WITH A LOCKING SPRING CARTRIDGE

CROSS-REFERENCE TO RELATED APPLICATION

The present application claims the benefit under 35 U.S.C. § 119(e) of U.S. provisional patent application No. 63/089,738 filed on Oct. 9, 2020, the entirety of which is hereby incorporated by reference.

TECHNICAL FIELD

The present invention relates to a locking spring cartridge used to control the height of a dropper seat post on a bicycle, and a dropper post assembly including the same.

INTRODUCTION

U.S. Pat. No. 5,881,988 discloses a seat assembly includes a seat tube in which a seat post is movably received therein which has a clamping member with a seat disposed thereto. The seat post has two plain portions defined diametrically opposite in an outer periphery thereof and the seat tube has two wedge-shaped recesses defined diametrically opposite in an inner periphery thereof so as to receive two wedge-shaped blocks therein. The seat post extends through a nut member which is threadedly mounted to the seat tube.

U.S. Patent Publication No. 2020/070913 discloses a bicycle seat post assembly in which the travel distance of the seat post can be adjusted. The seat post assembly includes an outer tube that is configured to telescopically receive an inner tube. The inner tube is axially slidable relative to the outer tube between a retracted position and an extended position, the extended position being determined by an extension assembly in which an inner contact member engages an outer contact member, thereby setting the upper limit of axial extension of the inner tube. The extension of the inner tube can be limited to an intermediate position that lies between the retracted and extended positions by an insertable shim that is positionable between the inner and outer contact members.

Taiwan patent publication no. TW201801969A discloses a casing gap filling structure for a bicycle seat tube, which comprises a casing set having an outer tube and an inner tube which are sleeved onto each other and move linearly; a rotation constraining set which is arranged between the inner tube and the outer tube and provided with a first constraining groove arranged on the inner diameter edge of the outer tube and a second constraining groove arranged on an outer diameter edge of the inner tube, the first and second constraining grooves forms a constraining space together, and at least one metal constraining member made of a metal material is accommodated in the constraining space and capable of conducting synchronous linear displacement with the inner tube; a gap filler set is disposed in the constraining space and provided with at least one plastic constraining member made of a plastic material, the gap filler set and the metal constraining member respectively overlapping with each other in the constraining space along the axial direction of the inner and outer tubes, and the plastic constraining member is able to effectively fill the constraining space so as to eliminate the gaps among the plastic constraining member and the first and second constraining grooves; in this way, the rotation constraining set and the gap filler set are used to achieve the dual function of constraining the rotation and eliminating the gaps between the inner tube and the outer

tube at the same time. The manufacturing cost of the filling structure is low because the overall components are simple and easy to be assembled quickly. Further, the gaps among the components generated by the fit tolerance and the manufacturing tolerance are reduced with no requirement of tight rotation actions, the automatic filling function is thus achieved and compatible with the lifting seat tube and the suspension seat tube.

U.S. Pat. No. 10,974,781 discloses a bicycle seat post assembly in which the travel distance of the seat post can be adjusted. The seat post assembly includes an outer tube that is configured to telescopically receive an inner tube. The inner tube is axially slidable relative to the outer tube between a retracted position and an extension position, the extension position being determined by an extension assembly in which a slider engages an upper retainer surface, thereby setting the upper limit of axial extension of the inner tube. The extension of the inner tube can be limited to an intermediary extension position that lies between the retracted and extension positions by an insertable extension stopper that is positionable under the upper retainer surface.

Taiwan utility model publication no. TWM517710U discloses a bicycle gas hydraulic seat tube assembly related to bicycles, especially a bicycle hydraulic pressure seat tube assembly. The common gas-oil seat tube adopts the gas compressible characteristic to match the flow of hydraulic oil in the space, so that the relative position change between the seat tube and the seat post is achieved, thereby achieving the effect of adjusting the height of the seat cushion. For example, as disclosed in the Republic of China Announcement No. M332057, the upper and lower displacements of the valve stem are used to switch the flow state of the adjustment flow path, so that the seat tube can achieve the effect of adjusting the height. However, in the aforementioned patent case, the inner and outer spaces for storing the hydraulic oil are disposed between the relatively exposed seat tube and the adjustment seat, and are not located in the relatively closed riser. The risk of leakage is therefore necessary for structural improvements. The main purpose of this creation is to provide a bicycle gas pressure seat tube assembly that reduces the risk of oil and gas leakage.

SUMMARY

Dropper seat posts are telescopic posts that allow the rider to change the height of their seat without having to stop and adjust a mechanically tightened seat post collar. It can be generally advantageous to lower the bicycle seat as far as possible when riding through technical terrain to allow the rider to change body position or bend their knees deeply without contacting the seat.

Some known dropper post locking spring cartridges are configured with two or more chambers containing liquid (i.e. hydraulic oil), gas (i.e. air) or a combination thereof. There is typically an internal piston valve controlled by an actuator/remote and an actuation rod translatable between an open and a closed position. When the piston valve is closed and a rider sits on a seat attached to the top of the post, the chamber containing, by design, only oil is placed in compression thereby allowing the post to be loaded without retracting.

In this configuration, when the piston valve is opened the piston travels into the oil only chamber. Because the oil in the oil only chamber is substantially incompressible it is typically more difficult to open the valve while the upper tube is being urged toward the retracted position. This causes the rider to have to exert more force on the actuator/remote

than may be comfortable, and/or that may put unwanted loads on the actuator system, in order to overcome this resistance and open the valve.

In this configuration, if the rider sits down on the seat too fast/hard while the piston valve is locked (closed), for example if a rider were to have one or both feet slip off the pedals and fall onto the seat with substantially all of their body weight, the seat post would generally not retract and therefore the seat would not move/lower to absorb and the rider could be injured by the seat and/or cause damage to the dropper post or seat.

Also, in this configuration air can sometimes enter the oil only chamber unintentionally. Once there, the presence of the relatively compressible air/gas within the chamber that is intended to contain only oil/liquid may allow the post to compress slightly under a relatively low force while the piston valve is, and remains, locked. This relatively-low force sponginess is seen by consumers as being generally undesirable and as an indicator of a low-quality design. Correcting and a generally expensive and/or complicated rebuild is required fix the problem.

Accordingly, there remains for a dropper post, including a suitable spring cartridge device, in which the actuation force of the spring cartridge device is not materially affected by the instantaneous load that is being applied to the seat (e.g. can operate in substantially the same way when the seat is loaded or unloaded), and where, when the piston valve is closed, the upper tube remains sufficiently rigid to resist loading of the seat up to a pre-determined, overload force above which the post can compress slightly, in accordance with its cushion quotient, to help protect the post from damage and/or the rider from injury.

The foregoing examples of the related art and limitations related thereto are intended to be illustrative and not exclusive. Other limitations of the related art will become apparent to those of skill in the art upon a reading of the specification and a study of the drawings.

The following embodiments and aspects thereof are described and illustrated in conjunction with systems, tools, and methods which are meant to be exemplary and illustrative, not limiting in scope. In various embodiments, one or more of the above-described problems have been reduced or eliminated, while other embodiments are directed to other improvements.

One aspect of the embodiments described herein provides a dropper post assembly for supporting a bicycle seat, the dropper post assembly comprising an outer tube extending along a post axis between a lower end and an upper end; an inner tube telescopically receivable in the outer tube and extending between an upper end that is connectable to a bicycle seat and a lower end that is disposed within the outer tube, the inner tube being axially slidable within the outer tube between a retracted position in which the lower end of the inner tube is proximate the lower end of the outer tube and an extended position in which the lower end of the inner tube is axially spaced from the lower end of the outer tube.

One aspect of the embodiments described herein provides a dropper post assembly where the inner tube has an outer diameter that is greater than about 25.5 mm

One aspect of the embodiments described herein provides a dropper post assembly where the moment of inertia of the inner tube taken in a plane adjacent the upper end of the outer tube and orthogonal to the post axis that is greater than $11,000 \text{ mm}^4$

One aspect of the embodiments described herein provides a dropper post assembly with a locking spring cartridge comprising an axially extending cylinder a piston disposed

within the cylinder, a first chamber containing oil only on a lower side of the piston, a second chamber containing a combination of oil and gas on an opposing, upper side of the piston; and a valve that is configurable in an open position in which fluid communication is established between the first chamber and second chamber and a closed position in which the first chamber is fluidly isolated from the second chamber; the cartridge configured so that moving the inner tube toward the retracted position expands the first chamber

One aspect of the embodiments described herein provides a dropper post assembly with an extension force used to extend the post when unweighted and an extension force multiplier that defines the degassing point of the hydraulic fluid in tension and wherein the assembly is configured so that the force multiplier is between about 3 and about 6.

One aspect of the embodiments described herein provides a dropper post assembly with a moment of inertia of the inner tube taken in a plane adjacent the upper end of the outer tube and orthogonal to the post axis and an extension force multiplier that defines the degassing point of the hydraulic fluid in tension and wherein the assembly defines a cushion quotient. The cushion quotient defined by the moment of inertia in mm^4 divided by the extension force multiplier and is greater than about 2700 mm^4 .

In accordance with one broad aspect of the teachings herein, a dropper post assembly for supporting a bicycle seat can include an outer tube extending along a post axis between a lower end and an upper end comprising a seat collar. An inner tube may have an upper end that is connectable to a bicycle seat and a lower end that is axially spaced from the upper end and is disposed within the outer tube, and may be configured to be axially slidable within the outer tube by a travel distance that is at least 200 mm between a retracted position in which the lower end of the inner tube is proximate the lower end of the outer tube and an extended position in which the lower end of the inner tube is axially spaced from the lower end of the outer tube. The inner tube may have an outer diameter that is between 25.5 mm and 30 mm, and when the inner tube is in the extended position a moment of inertia (I_x) taken in a plane that is orthogonal to the post axis, and adjacent the seat collar is at least $11,000 \text{ mm}^4$. A spring cartridge may include an axially extending cylinder disposed within the upper tube and a piston movably received within the cylinder. The spring cartridge may have an unlocked configuration in which the spring cartridge exerts an extension force (F_E) on the inner tube that biases the inner tube toward the extended position, and a locked configuration in which the spring cartridge is operable to generate a degassing force (F_D) of between about 90 lbs and about 140 lbs to resist movement of the inner tube toward the retracted configuration. An actuator may have a body disposed at the lower end of the outer tube and may be operable to change the spring cartridge between the locked configuration and the unlocked configuration.

The degassing force divided by the extension force defines a force multiplier M_F ($M_F = F_D / F_E$), and dividing the moment of inertia by the force multiplier defines a cushion quotient Q_C ($Q_C = I_x / M_F$), and the cushion quotient may be at least 2400 mm^4 .

The force multiplier may be between about 3 and 6.

The force multiplier may be between 4 and 5.

The cushion quotient may be at least 2600 mm^4 .

The degassing force may be equal to or less than 100 lbs, and the extension force may be between about 15 lbs and about 35 lbs.

The cylinder may include an inward facing sliding surface and the piston may slidably seal against the sliding surface

5

thereby dividing the cylinder to provide a first chamber containing a liquid and disposed on a lower side of the piston, and a second chamber and disposed on an opposing, upper side of the piston, whereby moving the inner tube toward the retracted position expands the first chamber.

The second chamber may contain a combination of the liquid and a gas at an operating pressure that is between about 200 psi and about 300 psi.

The spring cartridge may include a cartridge rod extending from the piston through the first chamber, and a valve that is configurable in an open position in which fluid communication is established between the first chamber and second chamber and the cartridge is in the unlocked configuration, and a closed position in which the first chamber is fluidly isolated from the second chamber and the cartridge is in the locked configuration. An actuation rod may extend from the body of the actuator and through the cartridge rod to the valve and operable to selectably open and close the valve.

The sliding surface defines a sliding surface diameter (D_S) may be between about 18 mm and about 25 mm and the cartridge rod may have a cartridge rod diameter (D_R). A ratio of the sliding surface diameter to the cartridge rod diameter ($D_S:D_R$) may be between about 1.8 and about 4.17.

The degassing force divided by the extension force defines a force multiplier MF ($MF=FD/FE$) and wherein the force multiplier may be within about 10% of 3.72 (D_S/D_R)–5.59.

The cartridge rod diameter may be between about 7 mm and about 9 mm.

The valve may include a valve body formed in the piston and a plunger that seals against the valve body when the valve is in the closed position and that is translatable relative to the valve body and into the second chamber to change the valve to the open position. A plunging force required to translate the plunger relative to the valve body may be substantially constant regardless of the axial position or loading of the inner tube.

The plunging force required when the inner tube is subjected to an axial load may be within about 10% of the plunging force required to translate the plunger relative to the valve body is when the inner tube is unloaded.

The cylinder may be integrally formed with the inner tube, whereby the inner tube comprises the sliding surface.

The cylinder may include an outer cartridge tube that is disposed within and is connected to translate with the upper tube.

The moment of inertia may be greater than 13,000 mm⁴.

The inner tube may have an inner diameter that is less than 82.5% of the outer diameter.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a side view of one example of a dropper post in a retracted position;

FIG. 2 is a side view of the dropper post of FIG. 1 in an extended position;

FIG. 3 is a partially exploded view of the dropper post of FIG. 1;

FIG. 4 is a cross-sectional view of the dropper post of FIG. 2, taken along line 4-4;

FIG. 5 is an enlarged view of a portion of the cross-sectional view of FIG. 4;

FIG. 6 is a cross-sectional view of another example of a dropper post;

FIG. 7 is an enlarged view of a portion of the cross-sectional view of FIG. 6;

6

FIGS. 8 and 9 are enlarged views of another portion of the cross-sectional view of FIG. 6;

FIGS. 10-13 are additional cross-sectional views of dropper post of FIG. 6; and

FIG. 14 is a cross-sectional view of a portion of the dropper post of FIG. 12, taken along Plane A;

FIG. 15 is a graph showing M_F vs (D_S/D_R).

DESCRIPTION

Various apparatuses or processes will be described below to provide an example of an embodiment of each claimed invention. No embodiment described below limits any claimed invention and any claimed invention may cover processes or apparatuses that differ from those described below. The claimed inventions are not limited to apparatuses or processes having all of the features of any one apparatus or process described below or to features common to multiple or all of the apparatuses described below. It is possible that an apparatus or process described below is not an embodiment of any claimed invention. Any invention disclosed in an apparatus or process described below that is not claimed in this document may be the subject matter of another protective instrument, for example, a continuing patent application, and the applicants, inventors or owners do not intend to abandon, disclaim, or dedicate to the public any such invention by its disclosure in this document.

Bicycle dropper seatposts allow a rider to change the height of their seat while riding without having to stop and adjust a mechanically tightened seat post collar. Dropper seat posts are available in different sizes, having different lengths of travel and different minimum and maximum seat heights. The dropper posts can include a lower or outer tube that can be connected to a bicycle, and an upper or inner tube that is telescopically slidable relative to the outer tube. A bicycle seat is connectable to the upper end of the inner tube, using a suitable clamping mechanism, and the lower end of the inner tube is usually nested within the outer tube. The inner tube is movable, relative to the outer tube, between a retracted position (in which the seat is relatively closer to the bicycle and most of the inner tube is received within the outer tube) and at least one extended position (in which the seat is relatively farther from the bicycle and a significant portion of the inner tube is exposed and extended outside the outer tube).

To help facilitate the desired extension and retraction of the inner tube, dropper seatposts can also include a biasing and locking mechanism that can be used to urge/bias the inner tube toward at least one of the retracted or extended positions, and can also help secure the inner tube in place—such as in its extended position—if the rider wishes to keep the seat at a given height/position. Preferably, the biasing and locking mechanism can be arranged to bias the inner tube (and seat mounted thereon) to its extended position, and then maintain the inner tube in this position until the rider chooses to have the inner tube retracted. In the embodiments described below, the biasing and locking mechanism includes a locking spring cartridge.

Preferably, the dropper seatposts also include some type of actuator mechanism that a rider can use to actuate/trigger the biasing and locking mechanism, so as to allow the rider to selectably alter the seat height. For example, the dropper seat post can include an actuator assembly that is used to trigger and/or selectable lock and unlock the locking spring cartridge. The locking spring cartridge, as described herein, can be configured so that it remains fixed/lock when not engage by the actuator assembly, and will stay in either its

extended or retracted configuration. The locking spring cartridge is preferably biased toward its extended configuration, whereby if the locking spring cartridge is retracted and is then unlocked by the rider via the actuator, the locking spring cartridge can apply a biasing, extension force that urges the inner tube (and seat) toward its extended position—thereby raising the seat. With the actuator disengaged, the locking spring cartridge is considered locked and will resist movement/retraction of the inner tube. That is, the locking spring cartridge force will resist the axial/vertical loads on the inner tube while in use to help keep the seat at the desired height, but the resistance of the locking spring cartridge may be overcome if a sufficiently large axial/vertical force is applied. Allowing the locking spring cartridge to yield in response to an overload situation (e.g. when the applied force passes a predetermined load threshold), while remaining sufficiently rigid when subjected to loads below the predetermined load/yield threshold may be advantageous because it can allow the post to support the weight of the rider when in use (in a manner that is perceived to be stable by the rider), while allowing the post to yield when overloaded to avoid damaging or bending portions of the post or injuring the rider. Having a cushion quotient, Q_C , that is sufficiently high can help achieve this desired performance.

When a rider wishes to lower the seat height, the actuator is engaged and the rider can apply a downward force on the seat (typically using their body weight) that is sufficient to overcome the biasing force of the locking spring cartridge so that the inner tube can be retracted into the outer tube. Once retracted, the actuator is disengaged, thereby locking the locking spring cartridge and keeping the inner tube in its retracted position. In this arrangement, the biasing force of the locking spring cartridge when unlocked is preferably set relatively low so that the inner tube can be retracted using the body weight of the rider (and of riders of potentially different sizes and weights), whereas the force required to cause movement of the locking spring cartridge when it is locked is relatively higher, but below the predetermined threshold.

To make things convenient for the rider, the triggering mechanism/remote for the actuator assembly can be provided at another location on the bicycle, such as on the handlebars, and can be operatively connected to a the actuator assembly by a remote connector (such as a wire, cable, chain, level, pneumatic or hydraulic link or the like). Because such remotes are usually connected to the actuator assembly in a mechanical/fluid power manner that transmits forces back to the user, it is preferable that the force required to engage the actuator assembly remains in a range that is feasible/comfortable for the rider to apply using the remote, and more preferably the force required to engage the actuator assembly remains relatively constant whether the inner tube is extended or retracted. This may help provide a more consistent tactile experience for the rider.

The inventor has determined that the extension force, overload yield force and other parameters of the dropper post can be configured by modifying aspects of the locking spring cartridge design, such that a new dropper post has been created in which the actuation force of the spring cartridge device is not materially affected by the instantaneous load that is being applied to the seat (e.g. can operate in substantially the same way when the seat is loaded or unloaded), and/or where, when the spring cartridge is locked (e.g. the piston valve is closed), the upper tube can remain sufficiently rigid to resist loading of the seat up to a pre-determined, overload force above which the post can

compress slightly to help protect the post from damage and/or the rider from injury. Examples of suitable locking spring cartridges that can be used in such dropper posts are described herein.

FIGS. 1-5 illustrate one example of a dropper seat post **100** includes an inner tube **110**, seat clamps **150** (for connecting to a bicycle seat—not shown), an outer tube **120**, a seat collar **130**, an actuator assembly **140**, including actuator mechanism **170**, and a locking spring cartridge **160**. In this arrangement, both the inner tube **110** and outer tube **120** are elongate, tubular members that extend along a post axis **102**. While the post axis **102** is shown as generally vertical in FIGS. 1 and 2, when the dropper post **100** is in installed on a bicycle the post axis may be inclined and need not be vertical.

In this example, the inner tube **110** is configured to slide telescopically within the outer tube **120** between a retracted position (FIG. 1) and an extended position (FIGS. 2 and 4, for example). The inner tube **110** includes a lower end **112** that is sized to fit within the outer tube **120** and that is intended to be retained within the outer tube **120** in both of the seat post's **100** retracted (FIG. 1) and extended configurations (FIG. 2). The inner tube **110** also has sidewall with an inner wall surface **111**, and defines an inner tube outer diameter (D_{TO}) **113** and inner tube inner diameter (D_{TI}) **114**. While the term inner tube diameter is used for convenience in this description, it is possible in some examples that the inner wall does not have a circular cross-sectional shape, and may have an oval shape, rectangular shape or other suitable shape, even if the outer shape is circular or substantially circular. As described herein, the interior of the upper tube is preferably sized to accommodate the associated spring cartridge (as described herein) and can influence the formula that is used to calculate its movement of inertia (as described herein), but the values for the moment of inertia can be compared for different shapes. Therefore, references to inner diameters can be understood to mean inner width and/or other relevant interior measurement that is useful for calculating the moment of inertia for a given shape. The term diameter is not intended to limit the present teachings to only be applicable to posts with a circular interior shape.

Referring to FIGS. 3-5, one example of a locking spring cartridge **160** that is suitable for use with the dropper posts described herein includes a cartridge outer tube **161** that has a sidewall with an inner surface that can be engaged by portions of the cartridge and can form part of the boundary of internal cartridge chambers and/or may be part of the sealing structures. In this example, the inner surface of the cartridge outer tube **161** can be referred to as an inner sliding surface **191** that defines a sliding surface diameter **191a**. The cartridge outer tube **161** is preferably connectable to the inner tube **110** in a manner that is sufficiently strong enough to carry the forces described herein, and that allows the inner tube **110** to move with the cartridge outer tube **161**. In the illustrated example, the cartridge outer tube **161** includes upper connection portion **162** for attaching cartridge **160** to upper tube **110**, but other fasteners could be used. In addition to the cartridge outer tube **161**, the locking spring cartridge **160** also includes a cartridge rod **163**, a locking groove **165** and actuation rod **164**. Fixedly attached to sliding surface **191** are upper seal head **192** and lower seal head **193**, which together help seal in the interior of the cartridge outer tube **161** and substantially fluidly isolate the interior of the cartridge outer tube **161** from the surrounding environment (at least with a sufficient degree of sealing/isolation to facilitate the operation of the locking spring cartridge **160** as described herein).

Within the interior of the cartridge outer tube **161** a piston assembly is provided to separate the interior of the cartridge outer tube **161** into two different chambers, and to help facilitate the translation of the cartridge outer tube **161** as described. The piston assembly can be of any suitable configuration that can operate as described herein. A valve mechanism is also preferably provided that can selectably allow fluid communication between the chambers on opposite sides of the piston assembly, as this can be used to lock and unlock the locking spring cartridge **160**. The valve, and related fluid flow path regions, can be of any suitable configuration. To help reduce the overall size of the locking spring cartridge **160**, it may be preferable to integrate a suitable valve mechanism within the piston assembly, as is shown in the present example that includes a piston valve **194** attached to the upper end **163a** of a cartridge rod **163** that can extend from the piston valve **194** to the actuator assembly **140**. The piston valve **194** is sized to generally fill the cartridge outer tube **164**, is positioned axially between the upper and lower cartridge seal heads **192** and **193**, and has a sealing portion that is positioned opposite and configured to seal against the sliding surface **191** and includes a body-sliding-surface o-ring **198** (or other suitable translatable sealing member). The piston valve **194**, in this example, also includes a valve body **195**, a plunger **196** that can move relative to the valve body **195**, a body-piston o-ring **197**, and valve cap **199**. In this embodiment the valve cap **199** defines a valve cap channel **199a** and the valve body **195** defines a corresponding valve body channel **195a** and a valve inner pathway **195b**. The plunger **196** includes a seal surface **196a**, that can seal against the valve body **195** (e.g. against o-ring **197** in this example) to inhibit fluid flow through the piston valve, and neck portion **196b**.

In this arrangement, the piston **194** divides the interior of the cartridge outer tube **161** into two operating chambers that can be fluidly isolated from each other while the locking spring cartridge **160** is in use to selectably lock and unlock the locking spring cartridge **160**. For example, when the operating chambers are fluidly isolated from each other the locking spring cartridge **160** can be considered to be in a locked configuration, and will resist movement of the cartridge outer tube **161** and seat post inner tube **110**. In contrast, when the operating chambers are fluidly connected, such as by activating the piston valve **194** and allowing fluid (liquid) to pass through the piston **194** and flow between the operating chambers, the locking spring cartridge **160** can be considered to be in an unlocked configuration, and will facilitate the relative movement of the cartridge outer tube **161** and seat post inner tube **110** relative to the outer tube **120**. As described herein, when the locking spring cartridge **160** is in use, and the piston valve **194** is opened, the cartridge outer tube **161** can translate relative to the piston **194** to allow the seat post inner tube **110** to translate relative to the outer tube **120**.

Referring to FIGS. **4** and **5**, in this example one, or a first, of the operating chambers is chamber **181**, which is located axially between the piston valve **194** and the lower seal head **193** and is laterally bounded the sliding surface **191**. Preferably, the lower chamber **181** is configured to contain only, or at least substantially only liquid, such as the oil described herein, rather than a mixture of liquid and gas or other material and can also be referred to as a liquid chamber. When the locking spring cartridge **160** is in use within the seat post **100** in the orientation illustrated these Figures (which is also the orientation of the locking spring cartridge **160** when it is in use on a bicycle) the chamber **181** can be referred to as a lower chamber **181**, but it is understood that

the term lower is used for convenience and is not intended to limit the orientation of the locking spring cartridge **160** when in use.

In the present example, the other, or second, operating chamber is chamber **182** which is located axially between the piston valve **194** and the upper seal head **192** and is also laterally bounded by the sliding surface **191**. Because of its relative location within the locking spring cartridge **160** as illustrated, the second chamber **182** can be referred to as an upper chamber **182**, but it is understood that the term lower is used for convenience and is not intended to limit the orientation of the locking spring cartridge **160** when in use. In contrast to lower chamber **181**, the upper chamber **182** is preferably configured to contain a mixture of oil (or other suitable liquid) and pressurized air (or other suitable gas), instead of containing only oil/liquid, and can be referred to as a gas/liquid chamber.

Under the intended operating conditions of the locking spring cartridge **160** the oil and air (or other liquid and gas) in the gas/liquid chamber **182** will tend to separate from each other due the differences in their densities and mechanical properties, such that an air/oil interface or boundary **183** is defined between piston valve **194** and upper seal head **192** within chamber **182**. In this arrangement, the gas/liquid chamber **182** will have a lower layer or region containing oil occupying the space located axially between the boundary **183** and the piston valve **194**, and an upper layer or region that is above the oil layer and boundary **183** and is located axially between the boundary **183** and the upper seal head **192**. When the piston valve **194** is actuated and its valve is open, fluid communication between the liquid layer within chamber **182** and the liquid within the lower chamber **181** is established.

While illustrated as separate members in this example of dropper seat post **100**, the cartridge outer tube **161** and upper tube **110** may alternatively be integrally formed with each other and as is shown in another example of a dropper seat post **200**. The seat post **200** is analogous to seat post **100** and like features are illustrated using like reference characters indexed by **100**. As described further herein, seat post **200** can operate in substantially the same manner as seat post **100**, but may have some slightly different components and configurations as a result of the integral formation of the cartridge outer tube **161** and upper tube **110** that do not materially alter how the posts **100** and **200** operate. For example, if the cartridge outer tube **161** and upper tube **110** are of integral, one-piece construction as shown in this second example then features such as the upper connection portion **162**, that is used to connect the separate cartridge outer tube **161** to the upper tube **110** in the previous example, is not needed. Similar functioning components on dropper post **100** will now be described using characters indexed by **100** (i.e. **163** is now **263**).

FIGS. **6-7** illustrate an example of a dropper seat post **200** that embodies another preferred embodiment of the teachings described herein. In this example, the seat post **200** includes an inner tube **210**, seat clamps **250**, outer tube **220**, seat collar **230**, actuator assembly **240**, including actuator mechanism **270**. The inner tube **210** further includes lower end **212**, inner wall surface **211**, inner tube outer diameter (DTO) **213** and inner tube inner diameter (DTI) **214**.

In contrast to the seat post **100**, in this example the inner tube **210** and outer cartridge tube **261** are integrally formed together (i.e. are of integral, one-piece construction) so that the inner tube **210** forms a part of locking spring cartridge **260**. This example of the locking spring cartridge **260** further includes an inner sliding surface **291** that defines a

respective sliding surface diameter **291a** (which is the same as tube inner diameter **214** in the case of dropper post **200**), cartridge rod **263** defining a cartridge rod diameter **263b**, locking groove **265** and actuation rod **264**. Fixedly attached to sliding surface **291** are upper seal head **292** and lower seal head **293**. While fixed during the operation of the locking spring cartridge **260** to help contain the liquid and gas within the cartridge tube **261**, the upper and lower seal heads **292** and **293** (and analogous seals **192** and **193**) can be removed for maintenance, assembly of the mechanism and for any other reason while the seat post **200** (or **100**) is not in use.

In this example, the piston valve **294** is attached to the upper end **263a** of cartridge rod **263** and is positioned so that it can seal against and slide relative to the sliding surface **291**, and is located axially between the upper and lower cartridge seal heads **292** and **293**. In this example, the sliding surface **291** is an inner surface of the inner tube **210**.

Piston valve **294** further contains a valve body **295**, a plunger **296**, a body-piston o-ring **297**, body-sliding-surface o-ring **298** (or other suitable sealing member) and valve cap **299**. In this example, the valve (including the valve body **295**, plunger **296** and related sealing members, etc.) are included as part of the piston that separates the chambers **281** and **282**, which can help reduce the overall size of the dropper post **200**. Alternatively, a different type of valve and liquid flow path may be provided that does not necessarily require the flow path to extend through the piston as illustrated.

Valve cap **299** defines a valve cap channel **299a** and valve body **295** defines a valve body channel **295a** and a valve inner pathway **295b**. Plunger **296** further defines seal surface **296a** and neck **296b**. Lower chamber **281** located within sliding surface **291** and between piston valve **294** and lower seal head **293** contains only oil (or other suitable liquid). Upper chamber **282** that is bounded by the sliding surface **291** and located axially between piston valve **294** and upper seal head **292** preferably contains a mixture of oil (or other suitable liquid) and pressurized air (or other suitable gas). When dropper post **200** is in a substantially upright position (as illustrated in FIGS. 6 and 7), the oil and air in chamber **282** will tend to separate from each other, with the oil occupying the lower portion of the space adjacent piston valve **294** and the relatively less dense air occupying the upper portion of the chamber **282** space adjacent the upper seal head **292**. An air/oil boundary **283** is therefore defined between piston valve **294** and upper seal head **292** within chamber **282**.

FIGS. 8-9 show the actuator **240**, and lockable spring cartridge **260** in use. While the operation of the actuator and cartridge is described with reference to the actuator **240**, and lockable spring cartridge **260**, actuator **140** and lockable spring cartridge **160** have substantially the same features and are operable in an analogous manner (regardless of whether the cartridge outer tube is a separate member or is integrally formed with the dropper post inner tube). Further, while a given actuator **240** is described for convenience, other suitable actuators may be used provided that they can selectively trigger the piston valve **294** (or **194**) to enable the locking and unlocking of the spring cartridge.

In the illustrated examples, actuator **240** includes a body **243**, a cartridge rod receiving portion **247** for attaching cartridge rod **263** to body **243**, an inner tube stop surface **246** and an actuation mechanism **270** to push actuation rod **264**. Upper tube stop surface **246** may exist on body **243** or as illustrated may be the upper surface of cushioning member **244**.

Cartridge rod **263** can be attached to rod receiving portion **247** of actuator body **243** in any suitable manner. In the illustrated example bolts **245a** and **245b** are provided and interact with locking groove **265** to securely connect the cartridge rod **263** to the actuator body **243**. Alternatively, other suitable methods such as threaded engagement, a press-fit, a deformation fit or the like could be used.

Actuator body **243** of actuator **240** can be attached to lower tube **220** using any suitable techniques or fasteners, and preferably may be removably connected to allow access to the interior of the lower tube **220**. In the illustrated example, body **243** uses circlip **241** that engages with groove **221** of lower tube **220**. Other suitable methods such as threads, a press-fit, a deformation fit or the like could be used.

To operate the piston valve **294**, the actuator **240** can also include a suitable actuator mechanism **270**, which in this example includes a lower arm **271** that has a dynamic cable stop surface **277**. An upper arm **272** is linked to the lower arm **271** and includes an actuation rod contact surface **278** that is configured to engage the lower end of the actuation rod **264**. Pivot pins **273** and **274** are used to connect the lower and upper arms **271** and **272** to each other and to the body **243** and to facilitate the desired pivoting of the arms **271** and **272** when the actuator **240** is in use. An alignment pin **275** is used to help guide the movement of the upper arm **272**, and preferably to limit movement of the upper arm **272** to a substantially axial translation as the pin **275** is captive, and slides within a corresponding slot in the upper arm **272**.

In this example, the actuator mechanism **270** uses a cable and housing arrangement (not shown—but that can be connected to a suitable remote trigger unit) to lower the distance between static cable stop surface **242** of body **243** and dynamic cable stop surface **277** of lower arm **271** when tension is applied to the cable (i.e. to pull the cable stop surface **277** downwardly as illustrated in FIG. 8). Lowering the distance between cable stops **277** and **242** pivots lower arm **271** about pin **273** thereby pushing upper arm **272** upward while it pivots about pin **274**. Upper arm **272** is aligned to body **243** by alignment pin **275**.

When the lower arm **271** is pivoted in this manner in response to tension being applied on the actuating cable, the upper arm **272** moves upwardly and the actuation rod contact surface **278** pushes actuation rod **264** upward (as illustrated). Axial movement of the actuation rod **264** then causes a corresponding axial movement of the translating plunger **296** (upwardly as illustrated) thereby 'opening' the piston valve **294**. FIG. 8 shows actuator assembly **240** in a relaxed (closed) position. FIG. 9 shows actuator mechanism **240** in an actuated (open) position. Because plunger **296** translates into the upper chamber **282** containing gas and oil, the gas can compress as the plunger **296** moves into the upper chamber **282** therefore the force required to move plunger **296** is less than it would be if attempting to translate into chamber that contained oil/liquid. This arrangement can help facilitate the actuating of the piston valve **294**, via the translation of plunger **296**, with a substantially constant amount of force being required regardless of the axial position and/or relative loading of the inner tube **210** (or **110**), e.g. where a plunging force required to translate the plunger **296** when the inner tube **210** is subjected to an axial load is within about 20%, and preferably within about 10% or 5% of the force required to translate the plunger **296** when the inner tube **210** is loaded (whether measured as tension on

the cable, axial force acting on the actuator rod **264**, feedback experienced by a rider at the remote triggering unit, or the like).

Once actuated (opened) plunger **296** translates upward and seal surface **296a** of plunger **296** unseats from o-ring **297** and the neck **296b** is sufficiently smaller in diameter that it does not seal against o-ring **297**. In this example, when the plunger **296** is translated in this way a fluid flow path (including channel **299a**, pathway **295b** and channel **295a**) is established within the piston valve **294** and between the chambers **281** and **282**, and they are in fluid communication with each other fluidly communicate. That is, oil from chamber **282** can travel through channel **299a**, pathway **295b** and channel **295a** into chamber **281**, and vice versa. As such when the piston valve **294** is actuated (open) relative axial movement is possible between cartridge rod **263** and inner tube **210**. Relative axial movement between upper tube **210** and lower tube **220** is therefore also possible.

When cartridge **260** is actuated (opened), and inner tube **210** is urged towards its retracted position, it can reach a lower limit in outer tube **220** when upper tube lower surface **212** contacts upper tube stop surface **246**. The travel or drop length of the post is then defined, in this example, by the distance **248** between lower end **212** of the inner tube **210** when it is in its extended position (FIG. **8**) and the upper tube stop **246**. The drop length is preferably long enough to allow the seat to be in a comfortable riding position when the dropper post is extended, and to be sufficiently lowered so as to not substantially interfere with the rider when the dropper post is retracted. In some examples, the drop length **248** can be at least 190 mm, 195 mm, 200 mm, 205 mm, 210 mm, 215 mm, 220 mm, 225 mm, 230 mm, 235 mm, 240 mm, 245 mm or more, and preferably may be between about 190 mm and about 230 mm, or between about 200 mm and about 225 mm.

If valve **294** remains open and the force urging tube **210** towards its retracted position ceases (e.g. if the rider is not sitting on the seat or otherwise pushing to try and retract the inner tube **210**), then the locking spring cartridge **260** in this example will bias the inner tube **210** to extend with an extension force F_E . In the illustrated configuration, the extension force F_E is defined by the product of the air pressure P in chamber **182** and the cross-sectional area of rod diameter (D_R) **263b** as shown in the following equation.

$$F_E = P \times \pi \left(\frac{D_R}{2} \right)^2$$

The inventor has determined that configuring the air within the second chamber **282** to be at a predetermined, operating pressure, can help dictate the magnitude of the extension force F_E for a given spring cartridge geometry, which can in turn help determine the perceived stiffness of the dropper post and the yield force as described herein. The operating pressure can be varied based on the specific geometry of a given dropper post to help obtain the desired performance, but in the illustrated example can be about 300 psi, and in other examples may be equal or less than 300 psi, such as between 200 psi and 300 psi, and preferably between about 250 psi and about 300 psi. In other examples, the operating pressure and relevant diameters (e.g. **291a/214** and **263b**) can be selected for a given arrangement so that the extension force F_E and other relevant forces and ratios described herein fall within the desired ranges.

One example of a suitable operating pressure P for the gas within chamber **282** that can be used for exemplary description purposes is an operating pressure of about 300 psi, and one example of a suitable D_R would be 8 mm (0.315") Therefore the F_E calculation would be as follows:

$$F_E = 300 \times \pi \left(\frac{0.315}{2} \right)^2$$

$$F_E = 23.37 \text{ lbs}$$

The inventor has discovered that the extension force F_E under these conditions is sufficient to overcome the anticipated friction between inner tube **210** and outer tube **220** while the inner tube **210** is moved toward its extended position, but is also low enough to allow the rider's body weight to overcome in order to urge inner tube **210** toward a retracted position while piston valve **294** is open. Preferably, the inventor has determined that the extension force F_E should be between about 15 and 35 lbs and preferably may be between about 20 and 25 lbs. As noted herein, the parameters of any given spring cartridge can be selected so that the resulting extension force F_E is within this desired range.

Referring also to FIGS. **10** and **11**, the dropper post **200** is shown with its piston valve **294** in its open configuration, as it would be when a rider has triggered the actuator **240**. With the dropper post **200** in this configuration, if the rider wishes to move the inner tube **210** to its retracted position (FIG. **11**) the axial force applied to the inner tube **210** must exceed the extension force F_E (and any friction forces and losses, which are considered to be negligible as compared to the main extension force). Once extension force F_E threshold has been exceeded the inner tube **210** will proceed to translate towards a retracted position while oil is transferred from upper chamber **282** to lower chamber **281**. FIG. **11** shows dropper post **200** in a fully retracted position.

FIGS. **12** and **13** show actuation mechanism **270** in its relaxed (closed) position and with the piston valve **294** in its closed position. In this arrangement, the fluid path between the upper chamber **282** and the lower chamber **281** is interrupted and the spring cartridge **260** can be considered to be locked. When in this state, a force used to urge inner tube **210** towards a retracted position will place the oil in lower chamber **281** in tension, as moving the inner tube **210** downwardly relative to the piston valve **294** would lead to an to increase the volume of lower chamber **281**, which would tend to lower the pressure acting on the liquid within the chamber **281**. The generally incompressible nature of the liquid in the lower chamber **281** will tend to resist such movement while the piston valve **294** is closed. The combination of the liquid and gas in the upper chamber **282** may also tend to resist such relative movement of the piston valve **294** into the upper chamber **282** and compression of the interior of the upper chamber **282**. However, because the gas in the upper chamber **282** is relatively compressible, the resistance to the movement of the piston valve **294** provided by the upper chamber **282** may be less than the resistance provided by the lower chamber **281**.

In this arrangement (e.g. while the piston valve is closed and the spring cartridge is locked) the inner tube **210** will remain substantially, axially fixed relative to outer tube **220** (and piston valve **294**) until a sufficient force is applied to overcome the tensile, resistive force that is generated by the oil under tension in lower chamber **281**. That is, the spring cartridge will provide a resistive force that opposes axial

movement of the inner tube when the spring cartridge is locked, and in particular a resistive force that will oppose the retraction of the inner tube **210** (e.g. will oppose movement of the inner tube **210** toward the retracted position). If a sufficiently large force is applied to the inner tube **210** that the magnitude of the applied force exceeds the resistive force of the cartridge, then relative motion between the piston **294** and the cylinder can occur, which will then result in an expansion of the volume of the chamber **281** which in turn lowers the vapour pressure within the chamber **281** and can pull dissolved gas(es) out of solution from the oil within chamber **281**. This resistance force that opposes axial movement of the inner tube when the spring cartridge is locked can be referred to as a degassing force (F_D), and a force that exceeds the degassing force can be referred to as an overload force. The inventor has determined that the degassing force should preferably be between about 80 and 160 lbs and preferably between about 90 lbs and 140 lbs or between 90 and 120 lbs, and more preferably is less than 100 lbs, and is between 90 and 100 lbs. This range of forces has been found to offer a satisfactory rider experience and seat feel, while also allowing the seat post to yield when subjected to the overload forces as described herein. The inventor has also determined that this degassing force (F_D) can be a function of the geometry of the spring cartridge **260** and can be expressed as a force multiplier (M_F) of extension force (F_E) of a given cartridge, according to the relation below:

$$F_D = M_F \times F_E$$

To obtain a desired balance of extension and degassing forces in a commercial dropper post, the inventor has determined that the desired force multiplier M_F value may be between 3 and 6 and may preferably be between 4 and 5.

Using these novel parameters, if, in one example, a low-end of extension force F_E range may be about 15 lbs, which if multiplied by an M_F of 6 could result in a force F_D of about 90 lbs. If the cartridge is designed so that the extension force F_E is toward the higher end of preferred range and is about 35 lbs, which if multiplied by an M_F of 3 this would result in a degassing force F_D of about 105 lbs.

When developing the present inventions, the inventor further determined that the force multiplier (M_F) is also proportional to the quotient of sliding surface diameter (D_S) **291a** of the spring cartridge upper tube **261** and rod diameter (D_R) **263b**. That is:

$$M_F \propto \left(\frac{D_S}{D_R} \right)$$

Preferably, when constructing dropper posts in accordance with the present teachings, the sliding surface diameter D_S may be between about 18 and 25 mm and preferably between about 20 and about 23 mm, as this may help provide a dropper post of a reasonable size that may fit many standard bicycles. The inventor has determined that acceptable rod diameters D_R , e.g. that provide a suitable level of strength while still fitting into the other size limitations and area ratios that are used to provide the desired performance of the dropper posts described herein, may optionally be between about 6 and 10 mm and preferably between about 7 mm and about 9 mm.

As one of the factors that can be balanced in a given dropper post embodiment, the ratios of sliding surface diameter D_S to rod diameter D_R may therefore be between about 1.8 (18 divided by 10 or 18/10) and 4.17 (25 divided

by 6 or 25/6), between about 2.22 (20 divided by 9 or 20/9) and about 3.29 (23 divided by 7 or 27/3) and preferably about 2.625 (21 divided by 8).

Based on one known experimental data set that was obtained from a publication entitled *Lockable Gas Springs "Gas Top"* produced in 2021 by Vapsint® Gas Springs and Dampers, and available at https://www.vapsint.com/wp-content/upload/2015/06/gas_top_vapsint.pdf, the force multiplier (M_F) versus the quotient of sliding surface diameter (D_S) **291a** and rod diameter (D_R) **263b** can be expressed via as graph of M_F vs (D_S/D_R) as shown in FIG. **15**.

One way of determining the force multiplier M_F can be further defined based a line of best fit from the graph in FIG. **15** as:

$$M_F = 3.72 \left(\frac{D_S}{D_R} \right) - 5.59$$

While fitting different lines of best fit may produce slightly different slope and y-intercept values, the inventor has determined that the preferred spring cartridge performance can be obtained using values that are not materially different than those provided herein. That is, the M_F for a given example may be within about 10% of the value of the line of best fit equation.

One exemplary calculation for force multiplier M_F using this experimental line of best fit and a ratio of sliding surface diameter D_S to rod diameter D_R of 2.625 (from above) is:

$$M_F = 3.72(2.625) - 5.59$$

$$M_F = 9.77 - 5.59$$

$$M_F = 4.18$$

While allowing for some variation in the constants in this example equation, the M_F that is within about 10% of this calculated value may be between about 3.76 and about 4.6. Given these exemplary ratios above of sliding surface diameter D_S to rod diameter D_R , force multiplier M_F may be calculated as being between about 1.11 ($D_S/D_R=1.8$) and 9.91 ($D_S/D_R=4.17$), between about 2.67 ($D_S/D_R=2.22$) and about 6.65 ($D_S/D_R=3.29$) and preferably about 4.18 ($D_S/D_R=2.625$). Based on this, the preferred force multipliers M_F may be between 3 and 6 and may preferably be between 4 and 5.

In these illustrated examples, if, while the piston valve **294** is closed and the spring cartridge is considered to be locked, inner tube **210** is urged towards its retracted position with a force that less than degassing Force F_D , inner tube **210** will remain axially fixed with outer tube **220**. This can help facilitate the desired rider experience and the desired feeling of solidity and stability of the dropper post. However, when the force urging the inner tube **210** toward its retracted position exceeds the degassing force F_D (and any associated losses, friction forces and the like), dissolved air is pulled out of solution within lower chamber **281**. Small air bubbles **285** form in lower chamber **281** and this can allow a relatively small amount of relative axial movement of the inner tube **210** relative to the piston valve **294**, shown as the overload cushion distance **284** (as shown in FIGS. **12** and **13**). Preferably, the overload cushion distance **284** is less than the expected drop length **248** of the dropper post **200**, and more preferably may be at least, and optionally can be between about 1 mm and 40 mm or between 10 mm and about 30 mm, and can be between about 0% and about 20% of the travel length **248**, and preferably can be between about

5% and about 15% of the travel length **248** to help provide a desired deflection or cushioning. This axial movement **284** therefore acts as a cushion if a rider overloads the post, such as while when riding or during a crash. Once the force urging inner tube **210** toward the retracted position drops back below the degassing force F_D , the air bubbles **285** can go back into solution and the inner tube **210** returns to its original height (FIG. 12).

FIG. 12 further shows the location of a plane A, illustrated when the inner tube **210** of dropper post **200** is in its extended position. The plane A in this arrangement is at a location that is located along the length of the inner tube **210** and is adjacent the upper end of outer tube **220** and seat collar **230**. The moment of inertia at plane A relates to the strength of inner tube **210** for a given material and load. This location, adjacent the seat collar **230** is a location where the inner tube **210** may be subjected to relatively high bending loads, as the portions of the inner tube **210** that are below the seat collar **230** are nested in and supported by the outer tube **220**, while portions of the inner tube **210** that are exposed above the seat collar **230** are not supported in the same manner. Providing an inner tube **210** that is sufficiently strong at this location can help resist bending of the inner tube **210** when in use and extended.

In addition to conforming with the multiple geometric parameters described herein to provide the desired spring cartridge parameters, the moment of Inertia I_x for inner tube **210** at Plane A is defined by tube outer diameter D_{TO} and tube inner diameter D_{TI} as follows:

$$I_x = \frac{\pi(D_{TO}^4 - D_{TI}^4)}{64}$$

To help the dropper post **200** fit with standard bicycle tubes, the inner tube outer diameter D_{TO} may be 25.5-30 mm and preferably is about 26-28 mm. The ratio of tube inner diameter D_{TI} to tube outer diameter D_{TO} may preferably be less than about 82.5% and preferable less than about 80%.

For example, the moment of inertia I_x for one preferred embodiment would have a diameter D_{TO} of about 26 mm and a diameter D_{TI} of about 20.8 mm (80% of diameter D_{TO}). The resulting moment of inertia calculation would be as follows:

$$I_x = \frac{\pi(26^4 - 20.8^4)}{64}$$

$$I_x = \frac{\pi(269,798.6)}{64}$$

$$I_x = \pi(4415.6)$$

$$I_x = 13,243.7 \text{ mm}^4$$

Similarly, the inventor has discovered that the moment of inertia I_x for the preferred ranges of tube outer diameters

DTO and tube inner diameters DTI described herein may be between about 11,140 mm⁴ (DTO=25.5, DTI=21.0 (82.5% of diameter DTO)) and about 23,474 mm⁴ (DTO=30, DTI=24.0 (80% of diameter DTO)).

FIG. 14 shows the cross section of inner tube **210** taken at Plane A of the illustrated embodiment and includes an inner tube outer diameter (DTO) **213** and inner tube inner diameter (DTI) **214** as two co-axial diameters. While in these examples the tubes **210** and **220** are shown as being circular in cross-sectional shape, other shapes and be used including ovular, non-coaxial circles or various sided polygons and the moment of inertia calculation would change to another known formula, but analogous ratios could be utilized.

Using the preferred geometries of the tubes **110** and **210** that can help provide the desired areas and forces described herein, the inventor has discovered that the moment of inertia at plane A for such designs may be greater than about 11,000 mm⁴, and in some more preferred examples can be greater than about 13,000 mm⁴. Similarly, the tube outer diameter D_{TO} may be 25.5-30 mm and preferably 26-28 mm, and therefore the ratio of tube inner D_{TI} diameter to tube outer diameter D_{TO} may be less than about 82.5% and preferable less than about 80%, and the ratio of I_x of inner tube **210** (in mm⁴) at plane A to the force multiplier M_F (I_x/M_F) may define a ratio described herein as the cushion quotient Q_C , and the inventor has determined that preferred examples of the dropper posts described herein can have a cushion quotient that is equal to or greater than about 2400 mm⁴, 2500 mm⁴, 2600 mm⁴, 2700 mm⁴ or more. The table below shows moment of inertia, force multiplier and cushion quotient values for two examples dropper posts considered by the inventor.

Post	D_{TI} (mm)	D_{TO} (mm)	D_S (mm)	D_R (mm)	D_S/D_R	M_F	Operating pressure (psi)	F_E (lbs)	F_D (lbs)	I_x at Plane A (mm ⁴)	Cushion Quotient I_x/M_F (mm ⁴)
1	26	20.8	20.8	8	2.6	4.082	300	23.37	95.41	13243.70	3244.41
2	28	24	24	8	3	5.57	300	23.37	130.19	13885.83	2492.96

While this invention has been described with reference to illustrative embodiments and examples, the description is not intended to be construed in a limiting sense. Thus, various modifications of the illustrative embodiments, as well as other embodiments of the invention, will be apparent to persons skilled in the art upon reference to this description. It is therefore contemplated that the appended claims will cover any such modifications or embodiments.

All publications, patents and patent applications referred to herein are incorporated by reference in their entirety to the same extent as if each individual publication, patent, or patent application was specifically and individually indicated to be incorporated by reference in its entirety.

I claim:

1. A dropper post assembly for supporting a bicycle seat, the dropper post assembly comprising:

- an outer tube extending along a post axis between a lower end and an upper end comprising a seat collar;
- an inner tube having an upper end that is connectable to a bicycle seat and a lower end that is axially spaced from the upper end and is disposed within the outer tube, and configured to be axially slidable within the

- outer tube by a travel distance that is at least 200 mm between a retracted position in which the lower end of the inner tube is proximate the lower end of the outer tube and an extended position in which the lower end of the inner tube is axially spaced from the lower end of the outer tube, the inner tube has an outer diameter that is between 25.5 mm and 30 mm, and when the inner tube is in the extended position a moment of inertia (I_x) taken in a plane that is orthogonal to the post axis, and adjacent the seat collar is at least 11,000 mm⁴;
- c) a spring cartridge comprising an axially extending cylinder disposed within the inner tube, a piston movably received within the cylinder, the spring cartridge having an unlocked configuration in which the spring cartridge exerts an extension force (F_E) on the inner tube that biases the inner tube toward the extended position, and a locked configuration in which the spring cartridge is operable to generate a degassing force (F_D) of between about 90 lbs and about 140 lbs to resist movement of the inner tube toward the retracted configuration; and
- d) an actuator having a body disposed at the lower end of the outer tube and operable to change the spring cartridge between the locked configuration and the unlocked configuration.
2. The dropper post assembly of claim 1, wherein the degassing force divided by the extension force defines a force multiplier M_F ($M_F=F_D/F_E$), and dividing the moment of inertia by the force multiplier defines a cushion quotient Q_C ($Q_C=I_x/M_F$), and wherein the cushion quotient is at least 2400 mm⁴.
3. The dropper post assembly of claim 2, wherein the force multiplier is between about 3 and 6.
4. The dropper post assembly of claim 3, wherein the force multiplier is between 4 and 5.
5. The dropper post assembly of claim 2, wherein the cushion quotient is at least 2600 mm⁴.
6. The dropper post assembly of claim 1, wherein the degassing force is equal to or less than 100 lbs, and the extension force is between about 15 lbs and about 35 lbs.
7. The dropper post assembly of claim 1, wherein the cylinder comprises an inward facing sliding surface and the piston slidably seals against the sliding surface thereby dividing the cylinder to provide a first chamber containing a liquid and disposed on a lower side of the piston, and a second chamber and disposed on an opposing, upper side of the piston, whereby moving the inner tube toward the retracted position expands the first chamber.
8. The dropper post assembly of claim 7, wherein the second chamber contains a combination of the liquid and a gas at an operating pressure that is between about 200 psi and about 300 psi.
9. The dropper post assembly of claim 7, wherein the spring cartridge comprises a cartridge rod extending from

the piston through the first chamber, and a valve that is configurable in an open position in which fluid communication is established between the first chamber and second chamber and the cartridge is in the unlocked configuration, and a closed position in which the first chamber is fluidly isolated from the second chamber and the cartridge is in the locked configuration, and further comprising an actuation rod extending from the body of the actuator and through the cartridge rod to the valve and operable to selectably open and close the valve.

10. The dropper post assembly of claim 9, wherein the sliding surface defines a sliding surface diameter (D_S) that is between about 18 mm and about 25 mm and the cartridge rod has a cartridge rod diameter (D_R), and wherein a ratio of the sliding surface diameter to the cartridge rod diameter ($D_S:D_R$) is between about 1.8 and about 4.17.

11. The dropper post assembly of claim 9, wherein the degassing force divided by the extension force defines a force multiplier M_F ($M_F=F_D/F_E$) and wherein the force multiplier is within about 10% of

$$3.72\left(\frac{D_S}{D_R}\right) - 5.59.$$

12. The dropper post assembly of claim 9, wherein the cartridge rod diameter is between about 7 mm and about 9 mm.

13. The dropper post assembly of claim 9, wherein the valve comprises a valve body formed in the piston and a plunger that seals against the valve body when the valve is in the closed position and that is translatable relative to the valve body and into the second chamber to change the valve to the open position, whereby a plunging force required to translate the plunger relative to the valve body is substantially constant regardless of the axial position or loading of the inner tube.

14. The dropper post assembly of claim 13, wherein the plunging force required when the inner tube is subjected to an axial load is within about 10% of the plunging force required to translate the plunger relative to the valve body when the inner tube is unloaded.

15. The dropper post assembly of claim 7, wherein the cylinder is integrally formed with the inner tube, whereby the inner tube comprises the sliding surface.

16. The dropper post assembly of claim 1, wherein the cylinder comprises an outer cartridge tube that is disposed within and is connected to translate with the inner tube.

17. The dropper post assembly of claim 1, wherein the moment of inertia is greater than 13,000 mm⁴.

18. The dropper post assembly of claim 1, wherein the inner tube comprises an inner diameter that is less than 82.5% of the outer diameter.

* * * * *