

US011769373B2

(12) **United States Patent**
Casey et al.

(10) **Patent No.:** **US 11,769,373 B2**
(45) **Date of Patent:** ***Sep. 26, 2023**

(54) **SYSTEMS AND METHODS FOR PROVIDING A MULTI-GAME BINGO GAME**

(71) Applicant: **Aristocrat Technologies, Inc.**, Las Vegas, NV (US)

(72) Inventors: **Michael Casey**, Reno, NV (US); **Eric Telaak**, Spring Hill, TN (US)

(73) Assignee: **Aristocrat Technologies, Inc.**, Las Vegas, NV (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 63 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **17/549,361**

(22) Filed: **Dec. 13, 2021**

(65) **Prior Publication Data**

US 2022/0101691 A1 Mar. 31, 2022

Related U.S. Application Data

(63) Continuation of application No. 16/852,014, filed on Apr. 17, 2020, now Pat. No. 11,210,905.

(60) Provisional application No. 62/862,601, filed on Jun. 17, 2019.

(51) **Int. Cl.**
G07F 17/32 (2006.01)

(52) **U.S. Cl.**
CPC **G07F 17/3267** (2013.01); **G07F 17/3211** (2013.01); **G07F 17/3286** (2013.01)

(58) **Field of Classification Search**

None
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

9,147,307 B2	9/2015	Meyer	
10,445,974 B2	10/2019	Watkins	
10,810,840 B2 *	10/2020	Casey G07F 17/3262
2004/0152503 A1	8/2004	Lind	
2004/0152508 A1	8/2004	Lind	
2005/0096119 A1	5/2005	Lind	

(Continued)

FOREIGN PATENT DOCUMENTS

CA 2783272 C 3/2019

OTHER PUBLICATIONS

Office Action dated Apr. 26, 2021 for U.S. Appl. No. 16/852,014 (pp. 1-7).

(Continued)


Primary Examiner — Ronald Laneau

(74) *Attorney, Agent, or Firm* — Armstrong Teasdale LLP

(57) **ABSTRACT**

A gaming machine includes a processor configured to execute instructions, which when executed, cause the processor to at least control a display device to display a first subgame and a second subgame during a multi-game bingo game, evaluate a first bingo card to determine a first outcome for the first subgame, and evaluate a second bingo card to determine a second outcome for the second subgame. The instructions also cause the processor to control the display device to display the first outcome for the first subgame and the second outcome for the second subgame, and evaluate a game ending win (GEW) bingo card to determine whether a game ending win has been achieved by a player of the electronic gaming machine, where the GEW bingo card is different from the first bingo card and the second bingo card.

20 Claims, 7 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0101370 A1 5/2005 Lind
2005/0119042 A1* 6/2005 Chamberlain G07F 17/3267
463/19
2005/0164771 A1 7/2005 Lind
2005/0164772 A1 7/2005 Lind
2005/0255906 A1 11/2005 Lind
2006/0040727 A1 2/2006 Lind
2006/0135245 A1* 6/2006 Hedrick G07F 17/3202
463/19
2006/0211496 A1 9/2006 Manz
2008/0153568 A1 6/2008 Lind
2009/0156296 A1 6/2009 Manz
2010/0210340 A1 8/2010 Lind
2012/0028696 A1 2/2012 Gail
2012/0202575 A1 8/2012 Matsuno
2012/0315975 A1 12/2012 Lind
2013/0316785 A1 11/2013 Lind
2014/0221071 A1 8/2014 Calio
2015/0018067 A1 1/2015 Cuddy
2016/0307410 A1 10/2016 Cannon
2017/0004672 A1 1/2017 Coleman
2017/0113127 A1* 4/2017 Hoover G07F 17/3272
2019/0102972 A1 4/2019 Watkins
2020/0013257 A1 1/2020 Watkins
2021/0082241 A1* 3/2021 Marsh G07F 17/3213
2022/0005309 A1* 1/2022 Welch A63F 3/0645

OTHER PUBLICATIONS

Office Action (Notice of Allowance and Fees Due (PTOL-85)) dated Aug. 30, 2021 for U.S. Appl. No. 16/852,014 (pp. 1-5).

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG.4





FIG. 5






FIG. 7

SYSTEMS AND METHODS FOR PROVIDING A MULTI-GAME BINGO GAME

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation of and claims priority to U.S. patent application Ser. No. 16/852,014, filed Apr. 17, 2020, which claims the benefit of and priority to U.S. Provisional Patent Application No. 62/862,601, filed Jun. 17, 2019, which are hereby incorporated by reference in their entireties.

TECHNICAL FIELD

The field of disclosure relates generally to electronic gaming, and more particularly, to systems and methods for Class II electronic gaming, in which a multi-game bingo game is provided.

BACKGROUND

Electronic gaming machines (“EGMs”) or gaming devices provide a variety of wagering games such as slot games, video poker games, video blackjack games, roulette games, video bingo games, keno games and other types of games that are frequently offered at casinos and other locations. Play on EGMs typically involves a player establishing a credit balance by inputting money, or another form of monetary credit, and placing a monetary wager (from the credit balance) on one or more outcomes of an instance (or single play) of a primary or base game. In some cases, a player may qualify for a special mode of the base game, a secondary game, or a bonus round of the base game by attaining a certain winning combination or triggering event in, or related to, the base game, or after the player is randomly awarded the special mode, secondary game, or bonus round. In the special mode, secondary game, or bonus round, the player is given an opportunity to win extra game credits, game tokens or other forms of payout. In the case of “game credits” that are awarded during play, the game credits are typically added to a credit meter total on the EGM and can be provided to the player upon completion of a gaming session or when the player wants to “cash out.”

“Slot” type games are often displayed to the player in the form of various symbols arrayed in a row-by-column grid or matrix. Specific matching combinations of symbols along predetermined paths (or paylines) through the matrix indicate the outcome of the game. The display typically highlights winning combinations/outcomes for ready identification by the player. Matching combinations and their corresponding awards are usually shown in a “pay-table” which is available to the player for reference. Often, the player may vary his/her wager to include differing numbers of paylines and/or the amount bet on each line. By varying the wager, the player may sometimes alter the frequency or number of winning combinations, frequency or number of secondary games, and/or the amount awarded.

Typical games use a random number generator (RNG) to randomly determine the outcome of each game. The game is designed to return a certain percentage of the amount wagered back to the player over the course of many plays or instances of the game, which is generally referred to as return to player (RTP). The RTP and randomness of the RNG ensure the fairness of the games and are highly regulated. Upon initiation of play, the RNG randomly determines a game outcome and symbols are then selected which

correspond to that outcome. Notably, some games may include an element of skill on the part of the player and are therefore not entirely random.

SUMMARY

In one aspect, an electronic gaming machine is provided. The gaming machine includes a display device, a memory device, and a processor configured to execute instructions, which when executed, cause the processor to at least control the display device to display, at least, a first subgame and a second subgame during a multi-game bingo game; evaluate a first bingo card to determine a first outcome for the first subgame; evaluate a second bingo card to determine a second outcome for the second subgame; control the display device to display the first outcome for the first subgame and the second outcome for the second subgame; and evaluate a game ending win (GEW) bingo card to determine whether a game ending win has been achieved by a player of the electronic gaming machine, the GEW bingo card being different from the first bingo card and the second bingo card.

In another aspect, an electronic gaming system for providing a multi-game bingo game is provided. The electronic gaming system includes a server configured to generate a bingo number listing and an electronic gaming machine communicatively coupled to the server. The electronic gaming machine includes a display device, a memory device, and a processor configured to execute instructions stored in the memory device, which when executed, cause the processor to at least: control the display device to display, at least, a first subgame and a second subgame; receive, from the server, at least a portion of the bingo number listing; evaluate a first bingo card against the portion of the bingo number listing to determine a first outcome for the first subgame; evaluate a second bingo card against the portion of the bingo number listing to determine a second outcome for the second subgame; control the display device to display the first outcome for the first subgame and the second outcome for the second subgame; and evaluate a plurality of game ending win (GEW) bingo cards against the portion of the bingo number listing to determine whether a game ending win has been achieved by at least one player of the bingo game.

In yet another aspect, a computer-implemented method for providing a multi-game bingo game is provided. The computer-implemented method includes controlling, by a processor of an electronic gaming machine, a display device of the electronic gaming machine to display, at least, a first subgame and a second subgame during the bingo game; evaluating, by the processor, a first bingo card to determine a first outcome for the first subgame; evaluating, by the processor, a second bingo card to determine a second outcome for the second subgame; and controlling, by the processor, the display device to display the first outcome for the first subgame and the second outcome for the second subgame.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is exemplary diagram showing several EGMs networked with various gaming related servers;

FIG. 2 is a block diagram showing various functional elements of an exemplary EGM;

FIG. 3 is a screenshot of an example Class II bingo game being displayed on an EGM as shown in FIG. 2;

FIG. 4 is a flowchart illustrating a process for providing a Class II multi-game bingo game, in which each of a plurality of bingo cards are evaluated for interim wins;

FIG. 5 is a screenshot of the example Class II multi-game bingo game described with reference to FIG. 4;

FIG. 6 is another example of a Class II bingo game being displayed in the EGM of FIG. 2; and

FIG. 7 is a screenshot of yet another example of a Class II bingo game being displayed in the EGM of FIG. 2.

DETAILED DESCRIPTION

Systems and methods for providing a multi-game bingo game are described herein. In various embodiments, a plurality of player selectable subgames are provided and displayed during the multi-game bingo game. In one example, four subgames are shown in four quadrants of a display screen. An outcome of each subgame may be determined based upon a respective (independent) bingo game outcome. For example, if four subgames are provided, four subgame bingo cards may be independently evaluated to generate four subgame outcomes, each of which may be displayed in one of the four quadrants.

Moreover, the multi-game bingo game may use a single bingo number listing (e.g., a ball call) to determine the outcome of the different subgames. For example, in the example in which four subgames are shown in four quadrants of the display screen, a bingo card may be selected for each of the four subgames. A single bingo number listing may then be generated and the independent bingo game outcomes may be determined by comparing each of the four bingo cards with the single bingo number listing. For example, in some such embodiments, a bingo server generates the single bingo number listing that is used to determine the outcome of each of the subgames. As a result, in such embodiments, the bingo server does not need to generate distinct bingo number listings for each subgame of the multi-game bingo game, thereby preserving memory and processing resources of bingo server.

In addition, the subgame outcomes may be associated with or mapped to any of a variety of game presentations, such as any Class III slot game presentation. In at least one embodiment, each subgame outcome is mapped from a bingo outcome to a reel game presentation. Each player participating in the multi-game bingo game may also be provided a game ending win bingo card, which may be associated, as described herein, with a nominal award value, and which may be used to determine a beginning and ending of each round of bingo, where each player may place many wagers for many subgame outcomes, during a single round of bingo. In some embodiments, a condition other than a GEW may be used to satisfy a requirement that a game of bingo be played by multiple players (in which case, players may or may not be provided GEW bingo cards).

FIG. 1 illustrates several different models of EGMs which may be networked to various gaming related servers. Shown is a system 100 in a gaming environment including one or more server computers 102 (e.g., slot servers of a casino) that are in communication, via a communications network, with one or more gaming devices 104A-104X (EGMs, slots, video poker, bingo machines, etc.) that can implement one or more aspects of the present disclosure. The gaming devices 104A-104X may alternatively be portable and/or remote gaming devices such as, but not limited to, a smart phone, a tablet, a laptop, or a game console. Gaming devices 104A-104X utilize specialized software and/or hardware to form non-generic, particular machines or apparatuses that

comply with regulatory requirements regarding devices used for wagering or games of chance that provide monetary awards.

Communication between the gaming devices 104A-104X and the server computers 102, and among the gaming devices 104A-104X, may be direct or indirect using one or more communication protocols. As an example, gaming devices 104A-104X and the server computers 102 can communicate over one or more communication networks, such as over the Internet through a website maintained by a computer on a remote server or over an online data network including commercial online service providers, Internet service providers, private networks (e.g., local area networks and enterprise networks), and the like (e.g., wide area networks). The communication networks could allow gaming devices 104A-104X to communicate with one another and/or the server computers 102 using a variety of communication-based technologies, such as radio frequency (RF) (e.g., wireless fidelity (WiFi®) and Bluetooth®), cable TV, satellite links and the like.

In some embodiments, server computers 102 may not be necessary and/or preferred. For example, in one or more embodiments, a stand-alone gaming device such as gaming device 104A, gaming device 104B or any of the other gaming devices 104C-104X can implement one or more aspects of the present disclosure. However, it is typical to find multiple EGMs connected to networks implemented with one or more of the different server computers 102 described herein.

The server computers 102 may include a central determination gaming system server 106, a ticket-in-ticket-out (TITO) system server 108, a player tracking system server 110, a progressive system server 112, and/or a casino management system server 114. Gaming devices 104A-104X may include features to enable operation of any or all servers for use by the player and/or operator (e.g., the casino, resort, gaming establishment, tavern, pub, etc.). For example, game outcomes may be generated on a central determination gaming system server 106 and then transmitted over the network to any of a group of remote terminals or remote gaming devices 104A-104X that utilize the game outcomes and display the results to the players.

Gaming device 104A is often of a cabinet construction which may be aligned in rows or banks of similar devices for placement and operation on a casino floor. The gaming device 104A often includes a main door which provides access to the interior of the cabinet. Gaming device 104A typically includes a button area or button deck 120 accessible by a player that is configured with input switches or buttons 122, an access channel for a bill validator 124, and/or an access channel for a ticket-out printer 126.

In FIG. 1, gaming device 104A is shown as a Reelm XL™ model gaming device manufactured by Aristocrat® Technologies, Inc. As shown, gaming device 104A is a reel machine having a gaming display area 118 comprising a number (typically 3 or 5) of mechanical reels 130 with various symbols displayed on them. The reels 130 are independently spun and stopped to show a set of symbols within the gaming display area 118 which may be used to determine an outcome to the game.

In many configurations, the gaming device 104A may have a main display 128 (e.g., video display monitor) mounted to, or above, the gaming display area 118. The main display 128 can be a high-resolution LCD, plasma, LED, or OLED panel which may be flat or curved as shown, a cathode ray tube, or other conventional electronically controlled video monitor.

In some embodiments, the bill validator **124** may also function as a “ticket-in” reader that allows the player to use a casino issued credit ticket to load credits onto the gaming device **104A** (e.g., in a cashless ticket (“TITO”) system). In such cashless embodiments, the gaming device **104A** may also include a “ticket-out” printer **126** for outputting a credit ticket when a “cash out” button is pressed. Cashless TITO systems are used to generate and track unique bar-codes or other indicators printed on tickets to allow players to avoid the use of bills and coins by loading credits using a ticket reader and cashing out credits using a ticket-out printer **126** on the gaming device **104A**. The gaming device **104A** can have hardware meters for purposes including ensuring regulatory compliance and monitoring the player credit balance. In addition, there can be additional meters that record the total amount of money wagered on the gaming device, total amount of money deposited, total amount of money withdrawn, total amount of winnings on gaming device **104A**.

In some embodiments, a player tracking card reader **144**, a transceiver for wireless communication with a mobile device (e.g., a player’s smartphone), a keypad **146**, and/or an illuminated display **148** for reading, receiving, entering, and/or displaying player tracking information is provided in EGM **104A**. In such embodiments, a game controller within the gaming device **104A** can communicate with the player tracking system server **110** to send and receive player tracking information.

Gaming device **104A** may also include a bonus topper wheel **134**. When bonus play is triggered (e.g., by a player achieving a particular outcome or set of outcomes in the primary game), bonus topper wheel **134** is operative to spin and stop with indicator arrow **136** indicating the outcome of the bonus game. Bonus topper wheel **134** is typically used to play a bonus game, but it could also be incorporated into play of the base or primary game.

A candle **138** may be mounted on the top of gaming device **104A** and may be activated by a player (e.g., using a switch or one of buttons **122**) to indicate to operations staff that gaming device **104A** has experienced a malfunction or the player requires service. The candle **138** is also often used to indicate a jackpot has been won and to alert staff that a hand payout of an award may be needed.

There may also be one or more information panels **152** which may be a back-lit, silkscreened glass panel with lettering to indicate general game information including, for example, a game denomination (e.g., \$0.25 or \$1), pay lines, pay tables, and/or various game related graphics. In some embodiments, the information panel(s) **152** may be implemented as an additional video display.

Gaming devices **104A** have traditionally also included a handle **132** typically mounted to the side of main cabinet **116** which may be used to initiate game play.

Many or all the above described components can be controlled by circuitry (e.g., a game controller) housed inside the main cabinet **116** of the gaming device **104A**, the details of which are shown in FIG. 2.

An alternative example gaming device **104B** illustrated in FIG. 1 is the Arc™ model gaming device manufactured by Aristocrat® Technologies, Inc. Note that where possible, reference numerals identifying similar features of the gaming device **104A** embodiment are also identified in the gaming device **104B** embodiment using the same reference numbers. Gaming device **104B** does not include physical reels and instead shows game play functions on main display **128**. An optional topper screen **140** may be used as a secondary game display for bonus play, to show game features or attraction activities while a game is not in play,

or any other information or media desired by the game designer or operator. In some embodiments, topper screen **140** may also or alternatively be used to display progressive jackpot prizes available to a player during play of gaming device **104B**.

Example gaming device **104B** includes a main cabinet **116** including a main door which opens to provide access to the interior of the gaming device **104B**. The main or service door is typically used by service personnel to refill the ticket-out printer **126** and collect bills and tickets inserted into the bill validator **124**. The main or service door may also be accessed to reset the machine, verify and/or upgrade the software, and for general maintenance operations.

Another example gaming device **104C** shown is the Helix™ model gaming device manufactured by Aristocrat® Technologies, Inc. Gaming device **104C** includes a main display **128A** that is in a landscape orientation. Although not illustrated by the front view provided, the landscape display **128A** may have a curvature radius from top to bottom, or alternatively from side to side. In some embodiments, display **128A** is a flat panel display. Main display **128A** is typically used for primary game play while secondary display **128B** is typically used for bonus game play, to show game features or attraction activities while the game is not in play or any other information or media desired by the game designer or operator. In some embodiments, example gaming device **104C** may also include speakers **142** to output various audio such as game sound, background music, etc.

Many different types of games, including mechanical slot games, video slot games, video poker, video black jack, video pachinko, keno, bingo, and lottery, may be provided with or implemented within the depicted gaming devices **104A-104C** and other similar gaming devices. Each gaming device may also be operable to provide many different games. Games may be differentiated according to themes, sounds, graphics, type of game (e.g., slot game vs. card game vs. game with aspects of skill), denomination, number of paylines, maximum jackpot, progressive or non-progressive, bonus games, and may be deployed for operation in Class 2 or Class 3, etc.

FIG. 2 is a block diagram depicting exemplary internal electronic components of a gaming device **200** connected to various external systems. All or parts of the example gaming device **200** shown could be used to implement any one of the example gaming devices **104A-X** depicted in FIG. 1. As shown in FIG. 2, gaming device **200** includes a topper display **216** or another form of a top box (e.g., a topper wheel, a topper screen, etc.) that sits above cabinet **218**. Cabinet **218** or topper display **216** may also house a number of other components which may be used to add features to a game being played on gaming device **200**, including speakers **220**, a ticket printer **222** which prints bar-coded tickets or other media or mechanisms for storing or indicating a player’s credit value, a ticket reader **224** which reads bar-coded tickets or other media or mechanisms for storing or indicating a player’s credit value, and a player tracking interface **232**. Player tracking interface **232** may include a keypad **226** for entering information, a player tracking display **228** for displaying information (e.g., an illuminated or video display), a card reader **230** for receiving data and/or communicating information to and from media or a device such as a smart phone enabling player tracking. FIG. 2 also depicts utilizing a ticket printer **222** to print tickets for a TITO system server **108**. Gaming device **200** may further include a bill validator **234**, player-input buttons **236** for player input, cabinet security sensors **238** to detect unau-

thorized opening of the cabinet **218**, a primary game display **240**, and a secondary game display **242**, each coupled to and operable under the control of game controller **202**.

The games available for play on the gaming device **200** are controlled by a game controller **202** that includes one or more processors **204**. Processor **204** represents a general-purpose processor, a specialized processor intended to perform certain functional tasks, or a combination thereof. As an example, processor **204** can be a central processing unit (CPU) that has one or more multi-core processing units and memory mediums (e.g., cache memory) that function as buffers and/or temporary storage for data. Alternatively, processor **204** can be a specialized processor, such as an application specific integrated circuit (ASIC), graphics processing unit (GPU), field-programmable gate array (FPGA), digital signal processor (DSP), or another type of hardware accelerator. In another example, processor **204** is a system on chip (SoC) that combines and integrates one or more general-purpose processors and/or one or more specialized processors. Although FIG. 2 illustrates that game controller **202** includes a single processor **204**, game controller **202** is not limited to this representation and instead can include multiple processors **204** (e.g., two or more processors).

FIG. 2 illustrates that processor **204** is operatively coupled to memory **208**. Memory **208** is defined herein as including volatile and nonvolatile memory and other types of non-transitory data storage components. Volatile memory is memory that do not retain data values upon loss of power. Nonvolatile memory is memory that do retain data upon a loss of power. Examples of memory **208** include random access memory (RAM), read-only memory (ROM), hard disk drives, solid-state drives, USB flash drives, memory cards accessed via a memory card reader, floppy disks accessed via an associated floppy disk drive, optical discs accessed via an optical disc drive, magnetic tapes accessed via an appropriate tape drive, and/or other memory components, or a combination of any two or more of these memory components. In addition, examples of RAM include static random access memory (SRAM), dynamic random access memory (DRAM), magnetic random access memory (MRAM), and other such devices. Examples of ROM include a programmable read-only memory (PROM), an erasable programmable read-only memory (EPROM), an electrically erasable programmable read-only memory (EEPROM), or other like memory device. Even though FIG. 2 illustrates that game controller **202** includes a single memory **208**, game controller **202** could include multiple memories **208** for storing program instructions and/or data.

Memory **208** can store one or more game programs **206** that provide program instructions and/or data for carrying out various embodiments (e.g., game mechanics) described herein. Stated another way, game program **206** represents an executable program stored in any portion or component of memory **208**. In one or more embodiments, game program **206** is embodied in the form of source code that includes human-readable statements written in a programming language or machine code that contains numerical instructions recognizable by a suitable execution system, such as a processor **204** in a game controller or other system. Examples of executable programs include: (1) a compiled program that can be translated into machine code in a format that can be loaded into a random access portion of memory **208** and run by processor **204**; (2) source code that may be expressed in proper format such as object code that is capable of being loaded into a random access portion of memory **208** and executed by processor **204**; and (3) source code that may be interpreted by another executable program

to generate instructions in a random access portion of memory **208** to be executed by processor **204**.

Alternatively, game programs **206** can be setup to generate one or more game instances based on instructions and/or data that gaming device **200** exchange with one or more remote gaming devices, such as a central determination gaming system server **106** (not shown in FIG. 2 but shown in FIG. 1). For purpose of this disclosure, the term “game instance” refers to a play or a round of a game that gaming device **200** presents (e.g., via a user interface (UI)) to a player. The game instance is communicated to gaming device **200** via the network **214** and then displayed on gaming device **200**. For example, gaming device **200** may execute game program **206** as video streaming software that allows the game to be displayed on gaming device **200**. When a game is stored on gaming device **200**, it may be loaded from memory **208** (e.g., from a read only memory (ROM)) or from the central determination gaming system server **106** to memory **208**.

Gaming devices, such as gaming device **200**, are highly regulated to ensure fairness and, in many cases, gaming device **200** is operable to award monetary awards (e.g., typically dispensed in the form of a redeemable voucher). Therefore, to satisfy security and regulatory requirements in a gaming environment, hardware and software architectures are implemented in gaming devices **200** that differ significantly from those of general-purpose computers. Adapting general purpose computers to function as gaming devices **200** is not simple or straightforward because of: (1) the regulatory requirements for gaming devices **200**, (2) the harsh environment in which gaming devices **200** operate, (3) security requirements, (4) fault tolerance requirements, and (5) the requirement for additional special purpose componentry enabling functionality of an EGM. These differences require substantial engineering effort with respect to game design implementation, game mechanics, hardware components, and software.

One regulatory requirement for games running on gaming device **200** generally involves complying with a certain level of randomness. Typically, gaming jurisdictions mandate that gaming devices **200** satisfy a minimum level of randomness without specifying how a gaming device **200** should achieve this level of randomness. To comply, FIG. 2 illustrates that gaming device **200** includes an RNG **212** that utilizes hardware and/or software to generate RNG outcomes that lack any pattern. The RNG operations are often specialized and non-generic in order to comply with regulatory and gaming requirements. For example, in a reel game, game program **206** can initiate multiple RNG calls to RNG **212** to generate RNG outcomes, where each RNG call and RNG outcome corresponds to an outcome for a reel. In another example, gaming device **200** can be a Class II gaming device where RNG **212** generates RNG outcomes for creating Bingo cards. In one or more embodiments, RNG **212** could be one of a set of RNGs operating on gaming device **200**. More generally, an output of the RNG **212** can be the basis on which game outcomes are determined by the game controller **202**. Game developers could vary the degree of true randomness for each RNG (e.g., pseudorandom) and utilize specific RNGs depending on game requirements. The output of the RNG **212** can include a random number or pseudorandom number (either is generally referred to as a “random number”).

Another regulatory requirement for running games on gaming device **200** includes ensuring a certain level of RTP. Similar to the randomness requirement discussed above, numerous gaming jurisdictions also mandate that gaming

device **200** provides a minimum level of RTP (e.g., RTP of at least 75%). A game can use one or more lookup tables (also called weighted tables) as part of a technical solution that satisfies regulatory requirements for randomness and RTP. In particular, a lookup table can integrate game features (e.g., trigger events for special modes or bonus games; newly introduced game elements such as extra reels, new symbols, or new cards; stop positions for dynamic game elements such as spinning reels, spinning wheels, or shifting reels; or card selections from a deck) with random numbers generated by one or more RNGs, so as to achieve a given level of volatility for a target level of RTP. (In general, volatility refers to the frequency or probability of an event such as a special mode, payout, etc. For example, for a target level of RTP, a higher-volatility game may have a lower payout most of the time with an occasional bonus having a very high payout, while a lower-volatility game has a steadier payout with more frequent bonuses of smaller amounts.) Configuring a lookup table can involve engineering decisions with respect to how RNG outcomes are mapped to game outcomes for a given game feature, while still satisfying regulatory requirements for RTP. Configuring a lookup table can also involve engineering decisions about whether different game features are combined in a given entry of the lookup table or split between different entries (for the respective game features), while still satisfying regulatory requirements for RTP and allowing for varying levels of game volatility.

FIG. 2 illustrates that gaming device **200** includes an RNG conversion engine **210** that translates the RNG outcome from RNG **212** to a game outcome presented to a player. To meet a designated RTP, a game developer can setup the RNG conversion engine **210** to utilize one or more lookup tables to translate the RNG outcome to a symbol element, stop position on a reel strip layout, and/or randomly chosen aspect of a game feature. As an example, the lookup tables can regulate a prize payout amount for each RNG outcome and how often the gaming device **200** pays out the prize payout amounts. The RNG conversion engine **210** could utilize one lookup table to map the RNG outcome to a game outcome displayed to a player and a second lookup table as a pay table for determining the prize payout amount for each game outcome. The mapping between the RNG outcome to the game outcome controls the frequency in hitting certain prize payout amounts.

FIG. 2 also depicts that gaming device **200** is connected over network **214** to player tracking system server **110**. Player tracking system server **110** may be, for example, an OASIS® system manufactured by Aristocrat® Technologies, Inc. Player tracking system server **110** is used to track play (e.g. amount wagered, games played, time of play and/or other quantitative or qualitative measures) for individual players so that an operator may reward players in a loyalty program. The player may use the player tracking interface **232** to access his/her account information, activate free play, and/or request various information. Player tracking or loyalty programs seek to reward players for their play and help build brand loyalty to the gaming establishment. The rewards typically correspond to the player's level of patronage (e.g., to the player's playing frequency and/or total amount of game plays at a given casino). Player tracking rewards may be complimentary and/or discounted meals, lodging, entertainment and/or additional play. Player tracking information may be combined with other information that is now readily obtainable by a casino management system.

When a player wishes to play the gaming device **200**, he/she can insert cash or a ticket voucher through a coin acceptor (not shown) or bill validator **234** to establish a credit balance on the game device. The credit balance is used by the player to place wagers on instances of the game and to receive credit awards based on the outcome of winning instances. The credit balance is decreased by the amount of each wager and increased upon a win. The player can add additional credits to the balance at any time. The player may also optionally insert a loyalty club card into the card reader **230**. During the game, the player views with one or more UIs, the game outcome on one or more of the primary game display **240** and secondary game display **242**. Other game and prize information may also be displayed.

For each game instance, a player may make selections, which may affect play of the game. For example, the player may vary the total amount wagered by selecting the amount bet per line and the number of lines played. In many games, the player is asked to initiate or select options during course of game play (such as spinning a wheel to begin a bonus round or select various items during a feature game). The player may make these selections using the player-input buttons **236**, the primary game display **240** which may be a touch screen, or using some other device which enables a player to input information into the gaming device **200**.

During certain game events, the gaming device **200** may display visual and auditory effects that can be perceived by the player. These effects add to the excitement of a game, which makes a player more likely to enjoy the playing experience. Auditory effects include various sounds that are projected by the speakers **220**. Visual effects include flashing lights, strobing lights or other patterns displayed from lights on the gaming device **200** or from lights behind the information panel **152** (FIG. 1).

When the player is done, he/she cashes out the credit balance (typically by pressing a cash out button to receive a ticket from the ticket printer **222**). The ticket may be "cashed-in" for money or inserted into another machine to establish a credit balance for play.

Although FIGS. 1 and 2 illustrates specific embodiments of a gaming device (e.g., gaming devices **104A-104X** and **200**), the disclosure is not limited to those embodiments shown in FIGS. 1 and 2. For example, not all gaming devices suitable for implementing embodiments of the present disclosure necessarily include top wheels, top boxes, information panels, cashless ticket systems, and/or player tracking systems. Further, some suitable gaming devices have only a single game display that includes only a mechanical set of reels and/or a video display, while others are designed for bar counters or tabletops and have displays that face upwards. Additionally, or alternatively, gaming devices **104A-104X** and **200** can include credit transceivers that wirelessly communicate (e.g., Bluetooth or other near-field communication technology) with one or more mobile devices to perform credit transactions. As an example, bill validator **234** could contain or be coupled to the credit transceiver that output credits from and/or load credits onto the gaming device **104A** by communicating with a player's smartphone (e.g., a digital wallet interface). Gaming devices **104A-104X** and **200** may also include other processors that are not separately shown. Using FIG. 2 as an example, gaming device **200** could include display controllers (not shown in FIG. 2) configured to receive video input signals or instructions to display images on game displays **240** and **242**. Alternatively, such display controllers may be inte-

11

grated into the game controller 202. The use and discussion of FIGS. 1 and 2 are examples to facilitate ease of description and explanation.

FIG. 3 depicts an example of a Class II bingo game being displayed in the primary game display 240 and secondary game display 242 of the EGM 200 of FIG. 2. In the example of FIG. 3, a plurality of reels 301, 303, and 305 are displayed within the primary game display 240. While only three reels 301, 303, 305 are shown in the example of FIG. 3, in some examples, more or fewer reels may be used. In some examples, the reels 301, 303, and/or 305 may be implemented as mechanical reels. As shown, each reel 301, 303, 305 has a plurality of symbol display positions for presenting symbols (and/or symbol combinations) which may be associated with winning and/or losing reel game outcomes and/or awards.

In the example of FIG. 3, a bingo card 304 and a bingo number listing 306 are displayed in the secondary game display 242. As shown, the bingo card 304 comprises a matrix of bingo cells 302 (e.g., squares). In some examples, the matrix may be a 5x5 matrix of 25 total cells. In some examples, the bingo card 304 may have a matrix of a different size (e.g., 3x3, 4x4, 4x5, 4x6, 6x6, 7x7, 3x8, 10x10, etc.). In some examples, the matrix may be larger or smaller. In the example of FIG. 3, each cell 302 in the matrix of the bingo card 304 includes a number that is not repeated in any other cell of the bingo card 304.

In the example of FIG. 3, the secondary game display 242 further displays a credit meter 308 showing an amount of money and/or credits (e.g. credit balance) held by a player of the EGM 200. In the example of FIG. 3, the credit balance 308 shows \$1000. The secondary display 242 additionally shows a wager meter 310 adjacent to the credit meter 308, under "BET." In the example of FIG. 3, the amount wagered is 10 credits (e.g., \$0.10). The amount wagered (e.g., via the user interface) may be deducted from the credit meter 308. The secondary game display 242 additionally displays a win meter 312 and a total win meter 314. In the example of FIG. 3, the win meter 312 is 500, indicating that the simulated combination of symbols in reels 301, 303, 305 is associated with a 500 award (which is equal to the award associated with the bingo game outcome). As shown, the total win meter 314 is also 500, indicating that the cumulative total of awards received comprises just that one 500 credit award. In the example of FIG. 3, the secondary game display 242 further displays reel win information 316. The reel win information 316 includes win line information 318 and award information 320. The win line information 318 indicates which win line in the reels 301, 303, 305 contains symbols comprising a winning reel game outcome. The award information 320 indicates an associated award amount for that winning reel game outcome.

In some examples, the bingo game may be a networked game that involves two or more networked EGMs 200, such as EGMs 104A-104X. For example, many electronic bingo games are required, by state gaming regulations, to include at least two players. In other words, as a result of jurisdictional requirements, many Class II games are required (e.g., by law) to include greater than a single player. As a result, in these circumstances, a bingo game can only occur if two or more players have placed wagers and received a bingo card. As described in additional detail herein, a ball call is initiated once at least two players have joined an electronic bingo game (e.g., a networked electronic bingo game), and each player's bingo card (or cards) are compared to the same ball call (e.g., bingo number listing 306), even where the

12

players are physically separated, such as in different parts of a casino or even in different casinos.

The bingo server 107 may manage (and/or host) the bingo game, such as by generating the bingo card 304 and/or bingo number listing 306. In some examples, the bingo card 304 (and/or information on which the bingo card 304 is based), and/or the bingo number listing 306 may be generated using an RNG. In some examples, the bingo card 304 may be randomly selected from a set of bingo cards or a player may select their own bingo card 304 (e.g., via the user interface), such as from a set of randomly generated bingo cards, for example. In certain embodiments, the bingo number listing 306 is a sequential listing of 80 numbers, selected randomly without replacement, from a pool of numbers. The bingo server 107 may generate this list at one go, or may generate a portion of this list (such as 40 numbers) first, and then sequentially generate one number after every n seconds. In certain embodiments, the bingo server may generate the list at once, and then transmit a portion (such as the first 40 numbers) to the various EGMs 200 and then transmit one number every n seconds, until a game end win occurs. At that point, the bingo game is complete, and a new bingo number listing is generated by the bingo server 107.

In operation, a player and/or EGM 200 may be provided with the bingo card 304, such as by bingo server 107. For example, a player may be provided a new bingo card 304 each time a "Spin" or "Play" button is pressed by the player (e.g., via user interface), provided the player has made a wager. In some examples, more than one bingo card 304 may be generated in response to wager. The bingo number listing 306 (e.g., "ball call") may be randomly generated, such as by bingo server 107. The bingo card 304 may be compared to the current bingo number listing 306, and numbered cells 302 on the bingo card 304 that match numbers in the bingo number listing 306 may be marked or "daubed" on the bingo card 304. Finally, the marked or daubed bingo card 304 may be evaluated against a paytable of winning bingo patterns.

The bingo number listing 306 may be continually generated until a maximum amount of numbers are listed (e.g., seventy-five numbers listed) or until a game-ending pattern is awarded to a player participating in the bingo game. A typical game-ending pattern may be a bingo card blackout pattern, in which each of the numbers of a bingo card match a number displayed in the bingo number listing 306. Other game-ending patterns are also possible. When the game-ending pattern is awarded, the bingo number listing 306 is reset, and the process repeats. In some examples, a single play of the bingo game includes a wager, a bingo card, a bingo number listing 306, a matching of the numbers called with those on a bingo card 304, a determination of a bingo game outcome, and a presentation of an associated award, if any.

A bingo game outcome may be determined by comparing one or more patterns of marked (and/or "daubed") cells of the bingo card 304 with the paytable of winning bingo patterns. If the bingo card 304 does not include a pattern that matches a pattern in the paytable of winning patterns, then a losing bingo outcome is determined, and no award may be provided to the player. If the bingo card 304 does include a pattern that matches a pattern in the paytable of winning patterns, then a winning bingo outcome is determined, and an award may be provided to the player.

Different winning patterns may be associated with different awards. The award for a winning main bingo game outcome may be based on an amount wagered, an associated main bingo game paytable, an associated set of rules for the

main bingo game, a probability (and/or likelihood) of achieving a particular bingo pattern/combination, an amount of bingo numbers needed to achieve the particular bingo pattern/combination, and/or other considerations. In some examples, the player may be awarded for multiple patterns (e.g. all winning patterns) that are matched when the bingo card **304** is evaluated against the paytable of winning patterns. In some examples, the player may be awarded for only the highest priority pattern (e.g. the highest paying winning pattern) that is matched. In some examples, during play of a Class II game, a player is provided or selects a single bingo card **304** for multiple plays of the bingo game, with a new bingo number listing **306** generated for each play of the bingo game. Other methods of play of a Class II bingo game are also possible and are within the scope of this disclosure.

The bingo game outcome may be presented to the player via a spinning reel game simulation. In the example of FIG. **3**, the spinning reel game is simulated via the plurality of reels **301**, **303** and **305** in the primary game display **240**. For each play of the bingo game, the bingo game outcome is presented as a reel spin outcome in the reel game. In some examples, the spinning reel game simulation may operate by spinning each reel **301**, **303**, **305** and then stopping each reel **301**, **303**, **305** in a particular position to obtain a matrix of symbols. One or more combinations of symbols in the matrix of symbols may be associated with a reel game outcome that is equal to the main bingo game outcome. For example, a winning bingo game outcome may be displayed as a winning combination of reels **301**, **303** and **305**. Similarly, a losing bingo game outcome may be displayed as a losing combination of reels **301**, **303** and **305**. Different outcomes of the bingo game may be displayed as different outcomes in the spinning reel game. Thus, the bingo game outcome is presented to the player as a particular reel spin outcome of reels **301**, **303** and **305**.

FIG. **4** is a flowchart illustrating a process **400** for providing a Class II multi-game bingo game **500**. FIG. **5** is a screenshot of the example Class II multi-game bingo game **500** (described with reference to FIG. **4**). FIG. **4** and FIG. **5** are discussed together below.

Accordingly, in the example embodiment shown in FIG. **5**, bingo game **500** includes one or more player selectable subgames. For example, bingo game **500** may include, as shown, a first subgame **502**, a second subgame **504**, a third subgame **506**, and a fourth subgame **508**. Each subgame **502-508** may be displayed in a quadrant of a display device, such as, in this example, primary game display **240**. For instance, first subgame **502** may be displayed in a first quadrant **510**, second subgame **504** may be displayed in a second quadrant **512**, third subgame **506** may be displayed in a third quadrant **514**, and fourth subgame **508** may be displayed in a fourth quadrant **516**.

Each subgame **502-508** may be associated with a desired game presentation. More particularly, as described in detail herein, an outcome of each subgame **502-508** may be based upon a bingo game outcome. However, each bingo game outcome may be presented in a variety of ways. Specifically, a game presentation (or “façade”) may be adjusted or changed for each subgame **502-508** as desired. In the example embodiment, a presentation of each subgame **502-508** is a reel game presentation. However, it will be appreciated that any desired presentation may be used. For instance, any Class III “Las Vegas style” or “slot game” presentation may be used, including, as shown, any reel game presentation.

As a result, at least one specific improvement to the technical field of Class II wagering games is that players who wish to play Class III “Las Vegas style” games may be provided access to the desired game presentation, even in gaming jurisdictions (e.g., Amer-Indian gaming jurisdictions) limited to Class II gaming. Further, although many implementations may map bingo game outcomes to Class III game presentations, as described above, in at least some embodiments, one or more subgames **502-508** may include a traditional Class II presentation. Specifically, in at least some embodiments, one or more subgames **502-508** may present a bingo card or another bingo game presentation.

Accordingly, in at least some embodiments, each subgame **502-508** may include one or more reels. In the example embodiment, each subgame **502-508** includes five reels. However, it will be appreciated that any suitable number of reels may be included in each subgame **502-508**. It will also be appreciated that the number of reels may differ from subgame to subgame. To illustrate, first subgame **502** may, in at least one embodiment, include a single reel, while fourth subgame **508** may, in at least one embodiment, include ten or more reels. Again, although each subgame **502-508** includes reels in the illustrated example, it will be appreciated that any suitable game, such as any suitable game typically played on a Class III slot machine (or “slot game”) may be implemented.

Thus, bingo game **500** may include a plurality of player selectable subgames **502-508**, each of which may be associated with a distinct bingo game outcome. In particular, a plurality of bingo game outcomes may be determined from a plurality of subgame bingo cards and mapped to or otherwise provided in association with each subgame **502-508** presentation. For example, in a four subgame **502-508** implementation, each player of bingo game **500** may be provided up to four subgame bingo cards, one per selected subgame **502-508**, each time the player places a wager. In alternative embodiments, bingo game **500** may include any number of subgames **502-508** that enables bingo game **500** to function as described herein. For example, and without limitation, as discussed below with respect to FIG. **6**, in some alternative embodiments, bingo game **500** includes two subgames each associated with a subgame bingo card. In further alternative embodiments, bingo game **500** includes eight or more subgames each associated with a bingo subgame card.

Each player of bingo game **500** may also be provided a gaming ending win (GEW) bingo card (not shown), which may be used to determine whether to conclude a current round of bingo game **500**, where a bingo round may conclude by removing or purging an existing bingo number listing **306** and generating a new bingo number listing **306**. As a result, the subgame bingo cards provided each time the player places a wager may be regarded as “interim” or “non-game-ending” bingo cards, in that a game outcome of each subgame **502-508** may be determined using each of the subgame bingo cards during generation of bingo number listing **306** and prior to any player achieving a game ending win. In addition, a player of bingo game **500** may be provided many interim bingo cards in association with many plays of one or more selected subgames **502-508** during a single round of bingo game **500** (i.e., prior to a game ending win being achieved by at least one player). In some embodiments, a condition other than a GEW may be used to determine whether to conclude a current round of bingo game **500**, in which case, players may or may not be provided GEW bingo cards.

In the example embodiment, a server, such as bingo server 107, may generate bingo number listing 306 (step 402). In the parlance of bingo games, bingo number listing 306 may also be referred to as a “ball call.” In some embodiments, bingo number listing 306 may be provided on a display screen of button deck 120. In other embodiments, bingo number listing 306 is provided on a display of EGM 104A-104X, such as any of topper display 216, secondary game display 242, and/or primary game display 240. Similarly, in some embodiments, bingo number listing 306 may be provided on display 228 of player tracking interface 232. More generally, bingo number listing 306 may be displayed in any suitable location and/or on any suitable display screen.

In certain embodiments, bingo server 107 does not generate a bingo number listing 306 until a valid bingo game has been established. This may require at least 2 players to play the bingo game. Since the present disclosure includes multiple simultaneous played bingo games from a single EGM against a single bingo ball call, by initially two or more games in accordance with the present disclosure, the requirement of a bingo game may be satisfied by a single player. Further, in some embodiments, bingo number listing 306 may be continuously generated, even, for example, where a player has not placed a wager or has yet to place a wager. In other words, bingo server 107 may generate one ball call after another, irrespective of whether any player is currently participating in bingo game 500. In some embodiments, bingo number listing 306 may be displayed in response to a player placing a wager (step 404). Thus, in some cases, bingo server 107 may continuously generate bingo number listing 306, but bingo number listing 306 may only be displayed in response to a player wager. As described herein, the first forty numbers or “balls” of bingo number listing 306 may be substantially simultaneously displayed, and the next thirty-five numbers of balls selected and/or displayed, one at a time, in short intervals (e.g., one or two seconds) until bingo number listing reaches seventy-five total balls called.

If, during display of bingo number listing 306, a game ending win (GEW) is achieved by any player participating in bingo game 500, bingo server 107 may begin generation of bingo number listing 306 anew, removing previously selected balls from being displayed and starting over with a new bingo number listing 306. Similarly, if bingo server 107 reaches the end of bingo number listing 306 generation (e.g., if all seventy-five balls are called) and no player has achieved a GEW, bingo server 107 may also begin a new generation of bingo number listing 306. As described herein, a GEW may be determined by evaluating the GEW bingo card of each player for a GEW bingo pattern, such as a “blackout” or “all spots” pattern. If any player achieves such a pattern, a new bingo number listing 306 and/or new subgame bingo cards may be provided to each player of bingo game 500.

Accordingly, to initiate bingo game 500, a player of an EGM 104A-104X may place a wager (e.g., using a “Spin” or “Play” button, as described herein) and/or select one or more subgames 502-508 to play. To select a subgame 502-508, a player may tap or touch the subgame 502-508 if subgames 502-508 are displayed on a touchscreen or touch-sensitive display. In some cases, a player may use one or more mechanical pushbuttons of button deck 120 to select one or more subgames 508-508.

In some embodiments, a player may not be provided an option to select from subgames 502-508. Rather, in some embodiments, all subgames 502-508 may be automatically selected for participation each time a player places a wager.

However, in the example embodiment, a player may select any of subgames 502-508 to play. The player may not, in addition, need to provide a distinct or additional wager for each subgame 502-508 selected. Rather, a single wager may selection of any number of subgames 502-508. In another embodiment, however, a player may provide an independent wager for each subgame 502-508 and/or specify a percentage or portion of a single wager to allocate to each subgame 502-508.

In response to a player placing a wager, a first subgame bingo card 518 may be evaluated against bingo number listing 306 to determine a first bingo subgame outcome (step 406). Likewise, depending upon subgames 502-508 selected by the player, a second subgame bingo card 520, a third subgame bingo card 522, and a fourth subgame bingo card 524 may be evaluated against bingo number listing 306 to determine a second bingo subgame outcome, a third bingo subgame outcome, and/or a fourth bingo subgame outcome, respectively (steps 408, 410, and 412). In certain embodiments, the evaluation of the bingo cards 518-524 against the bingo number listing 306 may depend on a time when the wager button is pressed by the player. In other words, at the moment the wager button is pressed, the bingo number listing may not be complete (not all 80 numbers may have been determined). For example, if only 2 players are engaged in playing the bingo game, once the second player places a wager (assuming the first player has placed a wager already), the bingo game begins and a portion of the bingo number listing (first 40) may be determined. The bingo cards of the two players will be evaluated against the portion of the bingo number listing as it existed when the wagers were placed, and if the wager was placed before the bingo number listing was generated, then the portion (first 40) is used to determine the outcome. After the portion is generated, a number may be determined every n seconds (say 1 second) to add to the bingo game listing. After 5 seconds have elapsed and a total of 45 numbers of the bingo number listing have been determined, a third player may place a wager. The third player’s outcome may be determined based on the bingo number listing at that point, which now includes the 45 numbers. In certain embodiments, the four subgame bingo cards may be evaluated against a portion of the bingo number listing which is substantially the same of the four bingo cards. If a player wanted to play four games simultaneously prior to the present disclosure, they would have to wager on four successive bingo games, each having variances in the bingo number listing, due to the different times at which each of the successive four bingo games were initiated. Therefore, another improvement provided with the present disclosure is the ability to wager multiple games against a same portion of a bingo number listing.

In addition, a GEW bingo card (not shown) may also be evaluated to determine whether a game ending win has occurred (step 414). As described herein, if at least one player of bingo game 500 has achieved a game ending win, the player may be provided a game ending win award (steps 414 and 416). In some embodiments, the game ending win award is a nominal award (e.g., one penny), because GEW bingo cards may be primarily used for determining when to generate a new bingo number listing 306 and ensuring compliance with one or more Class II regulatory or jurisdictional requirements.

Accordingly, in response to any player of bingo game 500 achieving a game ending win, bingo server 107 may begin generation of a new bingo number listing 306. In addition, each player participating in bingo game 500 may be provided one or more new subgame bingo cards 518-522 for

evaluation against the new bingo number listing **306**, such as, for example, in based upon a wager of each player and player selection of one or more subgames **502-508**.

In various embodiments, the evaluation of subgame bingo cards **502-508** may take place on a player's EGM **104A-104X** and/or on bingo server **107**. For example, if bingo card evaluation takes place on a player's EGM **104A-104X**, bingo server **107** may periodically provide a group of bingo cards to each player's EGM **104A-104X**. These bingo cards may include subgame bingo cards **518-524** and GEW bingo cards, although there may, in at least some embodiments, be no distinction between subgame and GEW bingo cards themselves other than that subgame bingo cards **518-524** are used to evaluate subgame outcomes, and GEW bingo cards are used to determine whether a game ending win has occurred. Each time a player places a wager and selects one or more subgames **502-508**, the player's EGM **104A-104X** may (randomly or in list order) select one or more bingo cards from the group of bingo cards stored on the player's EGM **104A-104X** for comparison to bingo number listing **306**.

Similarly, where the bingo card evaluation is performed by bingo server **107**, it may be unnecessary to periodically provide a group of bingo cards to each player's EGM **104A-104X**, because bingo server **107** may select subgame bingo cards **518-524** and GEW bingo cards for each player participating in bingo game **500**. In this (server based) embodiment, one specific improvement to the technical field of Class II wagering is EGM **104A-104X** memory and processing resources may be preserved for other operations, as bingo server **107** (equipped with greater memory and processing resources) may perform the bulk of the storage and processing operations. EGM security may also be improved, as game data (i.e., bingo cards) may not be stored locally on any EGM, thereby removing the bingo cards used during bingo game **500** from the risk of local hacking and/or other tampering efforts occurring on a casino floor.

In either case, each bingo subgame outcome (or interim bingo game outcome) may be mapped to a presentation of a respective subgame. In the example embodiment, the first bingo subgame game outcome is mapped to a reel outcome or reel presentation of first subgame **502**. Likewise, the second bingo subgame outcome is mapped to a reel outcome or reel presentation of second subgame **504**, the third bingo subgame outcome is mapped to a reel outcome or reel presentation of third subgame **506**, and the fourth bingo subgame outcome is mapped to a reel outcome or reel presentation of fourth subgame **508**.

Furthermore, one of bingo server **107** and EGM **104A-104X** may store the selected bingo cards for a multi-game bingo game in a game history log of the memory of either the player's EGM **104A-104X** or the bingo server **107**. In particular, at least some gaming jurisdictions require that game outcomes be logged for an amount of time after game play has occurred so that, for example, the gameplay outcomes may be verified at a later time. In the example embodiment of FIG. **5**, after EGM **104A-104X** selects cards **518-524**, EGM **104A-104X** associated cards **518-524** together as corresponding to a single multi-game bingo game in the game history log of the memory of EGM **104A-104X**. Thus, each multi-game bingo game log entry in the game history log of EGM **104A-104X** may include multiple linked bingo cards (e.g., cards **518-524**) to identify each of the cards that were selected in a single multi-game bingo game. In alternative embodiments, the cards **518-524** are each linked and logged on a game history log of bingo server **107**.

More generally, although not central to an understanding of the present disclosure, a bingo game outcome may be mapped to a reel presentation using a lookup table that correlates one or more bingo game outcomes (e.g., all possible bingo game outcomes) in a one-to-one, one-to-many, many-to-one, or many-to-many relationship to one or more reel outcomes or reel stopping positions. A variety of standard mapping algorithms are known in the art and are not described in additional detail herein.

Each subgame bingo card **518-524** provided to a player may also be shown or displayed for the player to view. In the example embodiment, subgame bingo cards **518-524** are shown on a display of button deck **120** under bingo number listing **306**. In addition, a portion of button deck **120** may be divided into quadrants matching or visibly associated with quadrants **510-516** of primary game display **240**. As a result, the subgame bingo cards **518-524** used during bingo game **500** may be displayed in a quadrant to intuitively and visibly correspond to a respective quadrant of a subgame **502-508**.

In the example of FIG. **5**, button deck **120** includes a first quadrant **526** (visibly associated with first quadrant **510** and/or first subgame **502**), a second quadrant **528** (visibly associated with second quadrant **512** and/or second subgame **504**), a third quadrant **530** (visibly associated with third quadrant **514** and/or third subgame **506**), and a fourth quadrant **532** (visibly associated with fourth quadrant **516** and/or fourth subgame **508**). One specific improvement associated with this method of organizing and displaying subgame bingo cards is that a player may easily and intuitively grasp a correspondence between one or more selected subgames **502-508** and one or more displayed subgame bingo cards **518-524**.

Bingo server **107** and/or each EGM **104A-104X** may, in addition, determine a subgame award to provide to a player based upon each respective bingo subgame outcome. For example, each bingo subgame outcome may be mapped to a reel outcome or reel presentation, which may, in turn, be mapped (e.g., in a paytable) to a subgame award. In another embodiment, each bingo subgame outcome may be mapped by a lookup table to a respective reel presentation, and by a separate paytable, to a subgame award. In either case, a player's credit balance may be increased by a value of each subgame award at the conclusion of each subgame evaluation and/or reel presentation.

One advantage (and specific improvement to the technical field of bingo games) of providing a plurality of subgame bingo cards **518-524** in association with a plurality of subgames **502-508** is that a variability or variety of game outcomes may be increased by conducting independent (random) bingo subgame determinations for each subgame **502-508** of the multi-game bingo game **500**. For example, if a single subgame bingo card were used and its outcome mapped to each subgame **502-508**, the number of available reel presentations across each of the twenty reels (i.e., five reels each over four subgames **502-508** for a total of twenty reels) would be much less than the number of outcomes available as a result of the presently described manner of subgame outcome determination. Stated another way, mapping a single subgame bingo card to a plurality of subgame **502-508** reel presentations would result in a game that players might become quickly accustomed to our bored with, in that the total number of available outcomes and/or subgame presentations would be much less (and therefore more predictable or simply "stale" from a player perspective) than the number of outcomes and/or subgame presentations available by way of the presently described method. For example, a multi-game bingo game that included four

subgames (e.g., **502-508**), the outcomes of which are determined by a single bingo card, results in fewer potential game outcomes to display to the user, as a single win generated by the bingo card can only be mapped to the outcomes of the four separate subgames **502-508** in a relatively low number of award outcomes. To illustrate further, in at least one hypothetical example, if each bingo game (of the four example bingo games) has 1000 award outcomes, then, before removing overlapping sums of awards, there may be approximately 1 trillion award outcomes. However, if only combined outcomes were awarded, then the same amount of Class II data may only support about 4000 award outcomes.

An additional specific improvement of the present disclosure is that a multi-game bingo game **500** may be provided in which a single bingo number listing **306** (e.g., a ball call) may be generated and used to determine the outcome of a plurality of different subgames on a single EGM **104A-104X**. For example, in some embodiments of the present disclosure, the bingo number listing **306** is generated by bingo server **107** and transmitted to a player's EGM **104A-104X**. After a player initiates a game, the player's EGM **104A-104X** may (randomly or in list order) select one or more bingo cards from a group of bingo cards stored on the player's EGM **104A-104X** for comparison to the single bingo number listing **306**. For example, in the embodiment shown in FIG. 5, bingo server **107** transmits bingo number listing **306** and the player's EGM **104A-104X** selects five bingo cards. In particular of the five selected bingo cards, four (e.g., **518-524**) are each linked to one of the subgames **502-508** and a fifth bingo card (not shown) is designated as a "game end win" card. Each of the four bingo cards **518-524** are each compared to the bingo number listing **306** to determine the outcome of each respective subgame **502-508**. Thus, in such embodiments, the single bingo number listing **306** generated by the bingo server **107** is used to determine the outcome of each subgame **502-508**. As a result, the bingo server **107** does not need to generate distinct bingo number listings **306** for each subgame of the multi-game bingo game **500**, thereby preserving memory and processing resources of bingo server **107**.

As described briefly above, another specific improvement of the present disclosure is that a multi-game bingo game **500** may be provided in compliance with Class II regulatory requirements by using a GEW bingo card that delivers only a nominal game award (e.g., one penny). More particularly, one advantage of supplying a GEW bingo card associated with a nominal award value is that the GEW bingo card may be used to control beginning and ending of a round of bingo (e.g., when bingo number listing **306** is re-generated) without substantially (if at all) affecting return to player (RTP) of bingo game **500**, while an outcome of each subgame **502-508** may be controlled or determined individually for each player based solely upon a respective subgame bingo card **518-524** provided to the player in response to each player wager and subgame selection. Another advantage of the present disclosure is that, by having a single GEW per multigame play, the situation where a player could potentially be determined to be playing bingo against themselves may be avoided (where this situation may potentially raise a regulatory concerns).

FIG. 6 depicts another example of a Class II bingo game being displayed in the primary game display **240** and secondary game display **242** of the EGM **200** of FIG. 2. In the example of FIG. 6, a plurality of reels **601, 603, and 605** are displayed within the primary game display **240**. While only three reels **601, 603, 605** are shown in the example of FIG. 6, in some examples, more or fewer reels may be used.

In some examples, the reels **601, 603, and/or 607** may be implemented as mechanical reels. As shown, each reel **601, 603, 605** has a plurality of symbol display positions for presenting symbols (and/or symbol combinations) which may be associated with winning and/or losing reel game outcomes and/or awards. The Class II bingo game of FIG. 6 is substantially similar to the Class II bingo game described above with respect to FIG. 3, except as described below.

In the example of FIG. 6, a "Game 1" bingo card **604** and a bingo number listing **606** are displayed in the secondary game display **242**. As shown, the "Game 1" bingo card **604** comprises a matrix of bingo cells (e.g., squares). In some examples, the matrix may be a 5x5 matrix of 25 total cells. In some examples, the "Game 1" bingo card **604** may have a matrix of a different size (e.g., 3x3, 4x4, 4x5, 4x6, 6x6, 7x7, 3x8, 10x10, etc.). In some examples, the matrix may be larger or smaller. In the example of FIG. 3, each cell in the matrix of the "Game 1" bingo card **604** includes a number that is not repeated in any other cell of the "Game 1" bingo card **604**. In the example of FIG. 6, a "Game 2" bingo card **607** and a "Game End Win" bingo card **609** are also displayed in the secondary game display **542**. "Game 2" bingo card **607** and a "Game End Win" bingo card **609** are substantially similar (e.g., include a similarly sized matrix) as "Game 1" bingo card but include different numbers.

In the example of FIG. 6, the secondary game display **242** further displays a credit meter **608** showing an amount of money and/or credits (e.g. credit balance) held by a player of the EGM **200**. In the example of FIG. 6, the credit balance **608** shows \$1000. The secondary display **242** additionally shows a wager meter **610** adjacent to the credit meter **608**, under "BET." In the example of FIG. 6, the amount wagered is 10 credits (e.g., \$0.10). The amount wagered (e.g., via the user interface) may be deducted from the credit meter **608**. The secondary game display **242** additionally displays a win meter **612** and a total win meter **614**. In the example of FIG. 6, the win meter **612** is 500, indicating that the simulated combination of symbols in reels **601, 603, 605** is associated with a 500 award (which is equal to the award associated with the bingo game outcome). As shown, the total win meter **614** is also 500, indicating that the cumulative total of awards received comprises just that one 500 credit award. In the example of FIG. 6, the secondary game display **242** further displays reel win information **616**. The reel win information **616** includes win line information **618** and award information **620**. The win line information **618** indicates which win line in the reels **601, 603, 605** contains symbols comprising a winning reel game outcome. The award information **620** indicates an associated award amount for that winning reel game outcome.

The bingo server **107** may manage (and/or host) the bingo game, such as by generating the "Game 1" bingo card **604**, the "Game 2" bingo card **607**, the "Game End Win" bingo card **609**, and/or bingo number listing **606**. In some examples, the bingo cards **604, 607, 609** (and/or information on which the bingo cards **604, 607, 609** are based), and/or the bingo number listing **606** may be generated using an RNG. In some examples, the bingo cards **604, 607, 609** may be randomly selected from a set of bingo cards or a player may select their own bingo cards **604, 607, 609** (e.g., via the user interface), such as from a set of randomly generated bingo cards, for example. In certain embodiments, the bingo cards may be selected from a set of bingo cards that are stored on EGM **200**. Once a threshold number of bingo cards of the set are used for gameplay, a new set may be requested by the EGM **200** from the bingo server **107**.

In operation, a player and/or EGM 200 may be provided with the bingo cards 604, 607, 609, such as by bingo server 107. For example, a player may be provided a new bingo cards 604, 607, 609 each time a “Spin” or “Play” button is pressed by the player (e.g., via user interface), provided the player has made a wager. The bingo number listing 606 (e.g., “ball call”) may be randomly generated, such as by bingo server 107. The bingo cards 604, 607, 609 may each be compared to the current bingo number listing 606, and numbered cells on the bingo cards 604, 607, 609 that match numbers in the bingo number listing 606 may be marked or “daubed” on the bingo cards 604, 607, 609. Finally, the marked or daubed bingo cards 604, 607, 609 may be evaluated against a payable of winning bingo patterns.

A bingo game outcome may be determined by comparing one or more patterns of marked (and/or “daubed”) cells of the bingo cards 604, 607, 609 with the payable of winning bingo patterns. If each of the bingo cards 604, 607, 609 do not include a pattern that matches a pattern in the payable of winning patterns, then a losing bingo outcome is determined for each of the bingo cards 604, 607, 609, and no award may be provided to the player. If one of the bingo cards 604, 607, 609 does include a pattern that matches a pattern in the payable of winning patterns, then a winning bingo outcome is determined for the respective bingo card 604, 607, 609, and an award may be provided to the player.

The bingo game outcomes may be presented to the player via different game simulations. In the example of FIG. 6, a spinning reel game simulation is used to present the outcome of a first bingo game based on the “Game 1” bingo card 604 by spinning the plurality of reels 601, 603 and 605 in the primary game display 240. For each play of the bingo game, the first bingo game outcome is presented as a reel spin outcome in the reel game. In some examples, the spinning reel game simulation may operate by spinning each reel 601, 603, 605 and then stopping each reel 601, 603, 605 in a particular position to obtain a matrix of symbols. One or more combinations of symbols in the matrix of symbols may be associated with a reel game outcome that is equal to the main bingo game outcome. For example, a winning bingo game outcome for the first bingo game may be displayed as a winning combination of reels 601, 603 and 605. Similarly, a losing bingo game outcome may be displayed as a losing combination of reels 601, 603 and 605. Different outcomes of the bingo game may be displayed as different outcomes in the spinning reel game. Thus, the first bingo game outcome is presented to the player as a particular reel spin outcome of reels 601, 603 and 605.

In the example of FIG. 6, a side game simulation is used to present the outcome of a second bingo game based on the “Game 2” bingo card 607 in the secondary gaming display 242. In particular, secondary game display 542 includes a side game display area 611 to display the outcome of the second bingo game. In the example of FIG. 6, the results of the side game are determined by comparing the “Game 2” bingo card 607 to the bingo number listing 606. More specifically, in the example of FIG. 6, the side game displayed is a card draw game, in which three cards are presented in the side display area. Two cards of the cards are revealed with a message indicating that a win is indicated by a third card being revealed to be in-between the two previously revealed card. In such embodiments, the “Game 2” bingo card 607 is compared to the bingo number listing 606 to determine whether a win has occurred. If the “Game 2” bingo card 607 is determined to contain a win based on the comparison with the bingo number listing 606, the EGM 104A-104X controls the display to reveal a third card (e.g.,

a Jack as shown in FIG. 6) that is in-between the two covered cards. If the “Game 2” bingo card 607 is determined to not contain a win based on the comparison with the bingo number listing 606 the EGM 104A-104X controls the display to reveal a third card that is not between the two covered cards. In particular, in the example embodiment of FIG. 6, the three cards are revealed on the display only after EGM 104A-104X determines whether the “Game 2” bingo card 607 contains a win. In alternative embodiments, the side game simulation may include any simulation that is capable of conveying a bingo game outcome. In various embodiments, the display of the side game is not tied to the display of the primary game. In other words, both games can be played concurrently, and their outcomes do not affect either game. Additionally, since each game uses their own bingo card, each game may start and end at different time points.

FIG. 7 is a screenshot of yet another example Class II multi-game bingo game 700. In the example embodiment shown in FIG. 7, bingo game 700 includes one or more player selectable subgames. For example, bingo game 700 may include, as shown, a first subgame 702, a second subgame 704, a third subgame 706, and a fourth subgame 708. In the example embodiment, bingo game outcomes for each of the subgames 702-708 may be determined from a corresponding plurality of subgame bingo cards and mapped to or otherwise provided in association with each subgame 702-708 presentation. For example, in the four subgame 702-708 implementation, each player of bingo game 700 may be provided up to five bingo cards, including one subgame bingo card for each selected subgame 702-708, and a game ending win bingo card 725 each time the player places a wager. Accordingly, the Class II bingo game 700 of FIG. 7 is substantially similar to the Class II bingo game 500 described above with respect to FIGS. 4 and 5, except as described below.

In the example embodiment, button deck 120 includes a button deck display screen 701 having a card display region 703 and an interface region 705. More specifically, in the example embodiment, button deck display screen 701 includes a user interface such as, but not limited to, a touch screen or touch-sensitive display interface spanning at least a portion of button deck display screen 701. In the example embodiment, button deck display screen 701 is configured to display GEW card 725 and each of the bingo cards corresponding to each of the subgames 702-708 in the card display region 703 of button deck display screen 701. More specifically, in the example embodiment, the button deck display 701 displays the GEW card 725 and one of the subgame bingo cards below the GEW card 725. During gameplay, button deck display 701 may cycle the displayed bingo card that is associated with one of the subgames 702-708, while maintaining the display of the GEW card 725. For example, as shown in FIG. 7, the Game 1 bingo card 718, corresponding to the first subgame 702 is displayed below the GEW card 725. In some embodiments, button deck display 701 may cycle through the displayed subgame bingo card by replacing the Game 1 bingo card 718 with each of the remaining bingo cards (not shown) corresponding to the second, third, and fourth subgames 704-708, sequentially, such that all subgame cards are displayed to the player during and/or at the end of the game. In other embodiments, button deck display 701 may also cycle the GEW card 725 in addition to and/or instead of the first subgame card 718. One specific improvement associated with this method of organizing and displaying subgame bingo cards is that a player may intuitively view each of the

subgame bingo cards while preserving area of the button deck display 701 to display other information/player selectable options by cycling each of the subgame bingo cards 718.

Additionally, in some embodiments, button deck display 701 displays each subgame bingo card substantially simultaneously with the display of the game outcome of each of subgames 702-708 on primary display 240. For example, in some such embodiments, button deck display 701 displays first subgame bingo card 718 below GEW card 725 at the same time as primary display 240 displays an outcome of the first subgame 702 (e.g., by stopping spinning reels in first subgame 702). After the first subgame 702 outcome has been displayed, primary display 240 may then display an outcome for second subgame 704 and button deck display 701 may simultaneously replace the first subgame bingo card 718 with a second subgame bingo card (not shown) corresponding to the second subgame 707. In further embodiments, button deck display 701 may display any of subgame bingo cards and GEW card 725 based on suitable criteria. For example, and without limitation, in some embodiments, button deck display 701 may display subgame bingo cards in response to a player selection made using the touch interface of button deck display screen 701.

In the example embodiment, the bingo number listing 306 and a plurality of player selectable options 727 are displayed in the interface region 705 of the button deck display 701. The player selectable options 727 are selectable by a player to control at least one of a wager, subgame selection, credit withdrawal, and/or a service request. In alternative embodiments, player selectable options 727 may include any suitable player selectable options. In further alternative embodiments any one of bingo number listing 306, bingo cards 718-725, and player selectable options 727 may be displayed in any suitable location on button deck display screen 701 and/or on any suitable display screen.

Systems and methods for providing a multi-game bingo game are thus provided. In various embodiments, a plurality of player selectable subgames are provided and displayed during the multi-game bingo game, such as, for example, in different sections or areas of a game display. An outcome of each subgame may be determined based upon an independent bingo game outcome. For example, if four subgames are provided, four subgame bingo cards may be evaluated to generate four subgame outcomes. In addition, the subgame outcomes may be associated with or mapped to any of a variety of game presentations, such as any Class III slot game presentation. In at least one embodiment, each subgame outcome is mapped from a bingo outcome to a reel game presentation. Each player participating in the bingo game may also be provided a game ending win bingo card, which may be associated, as described herein, with a nominal award value, and which may be used to determine a beginning and ending of each round of bingo, where each player may place many wagers for many subgame outcomes, during a single round of bingo.

While the invention has been described with respect to the figures, it will be appreciated that many modifications and changes may be made by those skilled in the art without departing from the spirit of the invention. Any variation and derivation from the above description and figures are included in the scope of the present invention as defined by the claims.

What is claimed is:

1. An electronic gaming system comprising:
 - a display device;
 - a memory device; and

a processor configured to execute instructions stored in the memory device, wherein the instructions, when executed, cause the processor to:

- control display of a first game in a first display area of the display device during a multi-game bingo game;
- control display of a second game in a second display area of the display device during the multi-game bingo game, the multi-game bingo game comprising the first game and the second game;
- determine a first outcome for the first game based upon an evaluation of a first bingo card associated with the first display area;
- determine a second outcome for the second game based upon an evaluation of a second bingo card associated with the second display area;
- control the display device to display a simulation communicating the first outcome for the first game associated with the first display area and the second outcome for the second game associated with the second display area; and
- determine whether a game ending win (GEW) has been achieved based upon an evaluation of a GEW bingo card.

2. The electronic gaming system of claim 1, wherein the instructions, when executed, further cause the processor to control the display device to display the simulation, wherein the simulation comprises a first simulation corresponding to the first outcome and a second simulation corresponding to the second outcome.

3. The electronic gaming system of claim 2, wherein the instructions, when executed, further cause the processor to control the display device to display the second simulation in the second display area, the second display area comprising a side game display area.

4. The electronic gaming system of claim 2, wherein the instructions, when executed, further cause the processor to control the display device to display the second simulation in response to determining that the second outcome comprises a winning outcome.

5. The electronic gaming system of claim 1, further comprising a user interface, wherein the user interface comprises a touch screen for receiving player input, the touch screen spanning at least a portion of the user interface.

6. The electronic gaming system of claim 5, wherein the instructions, when executed, further cause the processor to control the user interface to display the first bingo card and the second bingo card by cycling display of the first bingo card and the second bingo card.

7. The electronic gaming system of claim 5, wherein the instructions, when executed, further cause the processor to control the user interface to display at least one player selectable option, the at least one player selectable option selectable by a player to control at least one of a wager, a game selection, a credit withdrawal, or a service request.

8. An electronic gaming system for providing a bingo game, the electronic gaming system comprising:

- a server configured to generate a bingo number listing; and
- an electronic gaming machine communicatively coupled to the server, the electronic gaming machine comprising a display device, a user interface, a memory device, and a processor configured to execute instructions stored in the memory device, which, when executed, cause the processor to:
 - control display of a first game in a first display area of the display device;

25

control display of a second game in a second display area of the display device;
 receive, from the server, at least a portion of the bingo number listing;
 control display of at least a portion of the portion of the bingo number listing and at least one player selectable option on the user interface;
 determine a first outcome for the first game based upon an evaluation of a first bingo card against the portion of the bingo number listing;
 determine a second outcome for the second game based upon an evaluation of a second bingo card against the portion of the bingo number listing; and
 control the display device to display a simulation communicating the first outcome for the first game associated with the first display area and the second outcome for the second game associated with the second display area.

9. The electronic gaming system of claim 8, wherein the instructions, when executed, further cause the processor to determine whether a game ending win (GEW) has been achieved by at least one player of the bingo game based upon an evaluation of at least one GEW bingo card.

10. The electronic gaming system of claim 8, wherein the instructions, when executed, further cause the processor to control the display device to display the simulation, wherein the simulation comprises a first simulation corresponding to the first outcome and a second simulation corresponding to the second outcome.

11. The electronic gaming system of claim 10, wherein the instructions, when executed, further cause the processor to control the display device to display the second simulation in the second display area, the second display area comprising a side game display area.

12. The electronic gaming system of claim 10, wherein the instructions, when executed, further cause the processor to control the display device to display the second simulation in response to determining that the second outcome comprises a winning outcome.

13. The electronic gaming system of claim 8, wherein the instructions, when executed, further cause the processor to control the user interface to display the first bingo card and the second bingo card by cycling display of the first bingo card and the second bingo card.

14. The electronic gaming system of claim 8, wherein the instructions, when executed, further cause the processor to control the user interface to display the at least one player selectable option, the at least one player selectable option selectable by a player to control at least one of a wager, a game selection, a credit withdrawal, or a service request.

26

15. A computer-implemented method for providing a bingo game, the computer-implemented method comprising:
 controlling, by a processor of an electronic gaming system, display of a first game in a first display area of a display device of the electronic gaming system during a bingo game;
 controlling, by the processor, display of a second game in a second display area of the display device during the bingo game;
 determining, by the processor, a first outcome for the first game based upon an evaluation of a first bingo card associated with the first display area;
 determining, by the processor, a second outcome for the second game based upon an evaluation of a second bingo card associated with the second display area; and
 controlling, by the processor, the display device to display a simulation communicating the first outcome for the first game associated with the first display area and the second outcome for the second game associated with the second display area.

16. The computer-implemented method of claim 15, further comprising determining, by the processor, whether a game ending win (GEW) has been achieved based upon an evaluation of a GEW bingo card.

17. The computer-implemented method of claim 15, further comprising controlling, by the processor, the display device to display the simulation, wherein the simulation comprises a first simulation corresponding to the first outcome and a second simulation corresponding to the second outcome.

18. The computer-implemented method of claim 17, further comprising controlling, by the processor, the display device to display the second simulation in the second display area, the second display area comprising a side game display area.

19. The computer-implemented method of claim 17, wherein the electronic gaming system further comprises a user interface, the method further comprising controlling, by the processor, the user interface to display the first bingo card and the second bingo card by cycling display of the first bingo card and the second bingo card.

20. The computer-implemented method of claim 19, further comprising controlling the user interface to display at least one player selectable option, the at least one player selectable option selectable by a player to control at least one of a wager, a game selection, a credit withdrawal, or a service request.

* * * * *