



US011782488B2

(12) **United States Patent**
Cooper et al.

(10) **Patent No.:** **US 11,782,488 B2**
(45) **Date of Patent:** **Oct. 10, 2023**

(54) **METHODS AND APPARATUS TO OPERATE CLOSED-LID PORTABLE COMPUTERS**

(71) Applicant: **Intel Corporation**, Santa Clara, CA (US)

(72) Inventors: **Barnes Cooper**, Hillsboro, OR (US); **Aleksander Magi**, Portland, OR (US); **Arvind Kumar**, Beaverton, OR (US); **Giuseppe Raffa**, Portland, OR (US); **Wendy March**, Portland, OR (US); **Marko Bartscherer**, Chula Vista, CA (US); **Irina Lazutkina**, Hillsboro, OR (US); **Duck Young Kong**, Beaverton, OR (US); **Meng Shi**, Hillsboro, OR (US); **Vivek Paranjape**, Hillsboro, OR (US); **Vinod Gomathi Nayagam**, San Jose, CA (US); **Glen J. Anderson**, Beaverton, OR (US)

(73) Assignee: **INTEL CORPORATION**, Santa Clara, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **17/856,587**

(22) Filed: **Jul. 1, 2022**

(65) **Prior Publication Data**
US 2022/0334620 A1 Oct. 20, 2022

Related U.S. Application Data

(63) Continuation of application No. 16/421,217, filed on May 23, 2019, now Pat. No. 11,379,016.

(51) **Int. Cl.**
G06F 1/16 (2006.01)
G06F 3/16 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **G06F 1/1686** (2013.01); **G06F 1/165** (2013.01); **G06F 1/1618** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC G06F 1/1686; G06F 1/1618; G06F 1/165; G06F 1/1681; G06F 1/1692
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D324,036 S 2/1992 Wakasa
5,173,940 A 12/1992 Lantz et al.
(Continued)

FOREIGN PATENT DOCUMENTS

CN 102197349 9/2011
CN 107077184 8/2017
(Continued)

OTHER PUBLICATIONS

“Dell’s New Latitude 7400 2-in-1 Can Detect Your Presence and Automatically Wake the System,” MSPowerUser, Jan. 4, 2019, available at <https://mspoweruser.com/dells-new-latitude-7400-2-in-1-can-detect-your-presence-and-automatically-wake-the-system/> (20 pages).


(Continued)

Primary Examiner — Abbas I Abdulsalam
(74) *Attorney, Agent, or Firm* — Hanley, Flight & Zimmerman, LLC

(57) **ABSTRACT**

Methods and apparatus to operate closed-lid portable computers are disclosed. An example portable compute device includes: a microphone; a speaker; a first camera to face a first direction; and a second camera to face a second direction, the second direction opposite the first direction. The compute device further includes communications circuitry; a first display; a second display separate from the first

(Continued)



display; and a hinge to enable the first display to rotate relative to the second display between an open position and a closed position. At least a portion of the second display is capable of being visible when the first display is rotated about the hinge to the closed position. The portion of the second display is multiple times longer in a third direction than in a fourth direction perpendicular to the third direction, the third direction extending parallel to an axis of rotation of the hinge.

24 Claims, 18 Drawing Sheets

- (51) **Int. Cl.**
G06F 21/32 (2013.01)
G06F 9/54 (2006.01)
G06V 40/16 (2022.01)
- (52) **U.S. Cl.**
 CPC *G06F 1/1681* (2013.01); *G06F 1/1692* (2013.01); *G06F 3/167* (2013.01); *G06F 9/542* (2013.01); *G06F 21/32* (2013.01); *G06V 40/172* (2022.01); *G06F 2221/2149* (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

D359,275 S 6/1995 Yamazaki
 D376,791 S 12/1996 Schreiner
 D388,774 S 1/1998 Guintoli
 D389,129 S 1/1998 Guintoli
 D433,024 S 10/2000 Oross
 D434,773 S 12/2000 Suzuki
 D444,462 S 7/2001 Tsuji
 D449,307 S 10/2001 Amano
 D453,508 S 2/2002 Shibata
 D454,126 S 3/2002 Bliven et al.
 D462,967 S 9/2002 Suzuki
 D478,089 S 8/2003 Yokota
 D480,089 S 9/2003 Skinner et al.
 6,657,647 B1 12/2003 Bright
 6,760,649 B2 7/2004 Cohen
 D494,161 S 8/2004 Sawaguchi
 D504,129 S 4/2005 Loew et al.
 D517,542 S 3/2006 Lee et al.
 D518,042 S 3/2006 Kanayama
 D534,531 S 1/2007 Ogasawara
 7,386,799 B1 6/2008 Clanton et al.
 D577,013 S 9/2008 Harris
 D591,737 S 5/2009 Morooka
 7,559,034 B1 7/2009 Paperny et al.
 D607,449 S 1/2010 Morisawa
 D608,380 S 1/2010 Nagase et al.
 D611,043 S 3/2010 Andre et al.
 D611,045 S 3/2010 Andre et al.
 D612,830 S 3/2010 Kim et al.
 D614,180 S 4/2010 Gou
 D616,433 S 5/2010 Morishita et al.
 7,725,547 B2 5/2010 Albertson et al.
 D616,882 S 6/2010 Denhez
 D631,039 S 1/2011 Sakai et al.
 7,971,156 B2 6/2011 Albertson et al.
 D645,857 S 9/2011 Cho et al.
 8,139,032 B2 3/2012 Su et al.
 D659,134 S 5/2012 Ahn et al.
 D672,765 S 12/2012 Masui
 D673,558 S 1/2013 Cruz et al.
 D674,382 S 1/2013 Andre et al.
 D684,570 S 6/2013 Akana et al.
 D687,831 S 8/2013 Kim
 8,566,696 B1 10/2013 Hamon et al.
 D692,875 S 11/2013 Lawrence

8,581,974 B2 11/2013 Lin et al.
 D698,348 S 1/2014 Ilchan et al.
 D704,185 S 5/2014 Bowers et al.
 8,717,318 B2 5/2014 Anderson et al.
 D706,767 S 6/2014 Kawai et al.
 D706,768 S 6/2014 Kawai
 D706,769 S 6/2014 Kawai et al.
 D706,772 S 6/2014 Koyama et al.
 D708,178 S 7/2014 Honda et al.
 D708,179 S 7/2014 Andre et al.
 D709,491 S 7/2014 Kurimoto et al.
 8,812,831 B2 8/2014 Cheng et al.
 D712,971 S 9/2014 Huang
 D715,793 S 10/2014 Tsao et al.
 D716,795 S 11/2014 Huang et al.
 D718,818 S 12/2014 Sumii et al.
 D720,712 S 1/2015 Park et al.
 8,954,884 B1 2/2015 Barger
 D724,576 S 3/2015 Wolff et al.
 8,994,847 B2 3/2015 Chen et al.
 D727,314 S 4/2015 Fukuoka
 D729,227 S 5/2015 Fukuoka
 D729,228 S 5/2015 Kawai
 D729,229 S 5/2015 Kurimoto et al.
 D729,791 S 5/2015 Adamson et al.
 D729,792 S 5/2015 Kurimoto et al.
 D731,475 S 6/2015 Mehandjiysky et al.
 D739,398 S 9/2015 Adamson et al.
 D739,399 S 9/2015 Adamson et al.
 D739,400 S 9/2015 Adamson et al.
 D740,278 S 10/2015 Bowers et al.
 D741,318 S 10/2015 Oakley
 D746,809 S 1/2016 Takada et al.
 9,268,434 B2 2/2016 Sultenfuss
 D751,062 S 3/2016 Chang
 9,311,909 B2 4/2016 Giaimo, III et al.
 9,436,241 B2 9/2016 Tang et al.
 D769,251 S 10/2016 Chen
 D771,684 S 11/2016 Kim
 D780,173 S 2/2017 Matsuoka
 9,575,559 B2 2/2017 Andryscio
 D780,760 S 3/2017 Ironmonger et al.
 D788,767 S 6/2017 Magi
 D794,027 S 8/2017 Ironmonger et al.
 9,721,383 B1 8/2017 Horowitz et al.
 9,740,290 B2 8/2017 Rosenberg et al.
 9,766,700 B2 9/2017 Lyons et al.
 9,785,234 B2 10/2017 Horesh
 D801,945 S 11/2017 Cho et al.
 D803,946 S 11/2017 Matsuda
 9,846,471 B1 12/2017 Arora
 D810,069 S 2/2018 Hishiki
 D810,071 S 2/2018 Hishiki
 D813,235 S 3/2018 Rosenberg et al.
 D814,469 S 4/2018 Rundberg
 D816,083 S 4/2018 Wu
 9,936,195 B2 4/2018 Horesh
 9,996,638 B1 6/2018 Holz et al.
 D823,850 S 7/2018 Lim et al.
 10,027,662 B1 7/2018 Mutagi et al.
 D825,435 S 8/2018 Yu
 10,101,817 B2 10/2018 Hsin et al.
 10,234,928 B2 3/2019 Chen
 10,254,178 B2 4/2019 Carbone et al.
 10,262,599 B2 4/2019 Lang et al.
 10,304,209 B2 5/2019 Alonso
 10,415,286 B1 9/2019 Porcella et al.
 D867,460 S 11/2019 Yan et al.
 D873,835 S 1/2020 Chan
 10,551,888 B1 2/2020 North et al.
 D878,475 S 3/2020 Jetter
 D879,777 S 3/2020 Cho
 10,620,457 B2 4/2020 Ain-Kedem
 10,620,786 B2 4/2020 Veeramani et al.
 D886,112 S 6/2020 Yeh et al.
 10,725,510 B2 7/2020 Ho et al.
 10,740,912 B2 8/2020 Ren et al.
 10,768,724 B1 9/2020 Han
 10,819,920 B1 10/2020 Hamlin et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

10,884,479 B2	1/2021	Chen		2014/0191995 A1	7/2014	Karpin et al.
D914,021 S	3/2021	Magi et al.		2014/0201690 A1	7/2014	Holz et al.
11,153,472 B2	10/2021	Konicek		2014/0208260 A1	7/2014	Kawahara et al.
11,194,398 B2	12/2021	Bernhart		2014/0258942 A1	9/2014	Kutliroff et al.
11,360,528 B2	6/2022	Mishra et al.		2014/0267021 A1	9/2014	Lee et al.
11,379,016 B2	7/2022	Cooper et al.		2014/0281918 A1	9/2014	Wei et al.
11,543,873 B2	1/2023	Sengupta et al.		2014/0313120 A1	10/2014	Kamhi
2002/0089190 A1	7/2002	Wang et al.		2014/0361977 A1	12/2014	Stafford et al.
2002/0091738 A1	7/2002	Rohrbaugh et al.		2014/0372511 A1	12/2014	Kapadia et al.
2003/0043174 A1	3/2003	Hinckley et al.		2014/0380075 A1	12/2014	Pulapaka et al.
2003/0174149 A1	9/2003	Fujisaki et al.		2015/0009238 A1	1/2015	Kudalkar
2004/0158739 A1	8/2004	Wakai et al.		2015/0015688 A1	1/2015	Yang
2004/0175020 A1	9/2004	Bradski et al.		2015/0042572 A1	2/2015	Lombardi et al.
2004/0252101 A1	12/2004	Wilk		2015/0058649 A1	2/2015	Song et al.
2005/0071698 A1	3/2005	Kangas		2015/0100884 A1	4/2015	Ryu et al.
2006/0146030 A1	7/2006	Kim		2015/0121193 A1	4/2015	Beveridge et al.
2006/0192775 A1	8/2006	Nicholson et al.		2015/0121287 A1	4/2015	Fermon
2007/0228138 A1*	10/2007	Huang	H04N 1/00241 235/375	2015/0177843 A1	6/2015	Kwon
2008/0046425 A1	2/2008	Perski		2015/0185909 A1	7/2015	Gecnuk
2008/0112571 A1	5/2008	Bradicich et al.		2015/0193395 A1	7/2015	Nicolaou et al.
2008/0158144 A1	7/2008	Schobben et al.		2015/0220149 A1	8/2015	Plagemann et al.
2008/0301300 A1	12/2008	Toub		2015/0220150 A1	8/2015	Plagemann et al.
2009/0092293 A1	4/2009	Lin		2015/0248167 A1	9/2015	Turbell et al.
2009/0165125 A1	6/2009	Brown et al.		2015/0264572 A1	9/2015	Turgeman
2010/0039376 A1	2/2010	Wang		2015/0360567 A1	12/2015	Sannomiya et al.
2010/0079508 A1	4/2010	Hodge et al.		2015/0363070 A1	12/2015	Katz
2010/0281432 A1	11/2010	Geisner et al.		2016/0034019 A1	2/2016	Seo et al.
2011/0055752 A1	3/2011	Rubinstein et al.		2016/0062584 A1	3/2016	Cohen et al.
2011/0154266 A1	6/2011	Friend et al.		2016/0087981 A1	3/2016	Dorresteyn
2011/0175932 A1	7/2011	Yu et al.		2016/0109961 A1	4/2016	Parshionikar
2011/0298702 A1	8/2011	Sakata et al.		2016/0116960 A1	4/2016	Kwak et al.
2011/0248918 A1	10/2011	Yoo et al.		2016/0091938 A1	5/2016	Edwards et al.
2011/0252339 A1	10/2011	Lemonik et al.		2016/0132099 A1	5/2016	Grabau et al.
2011/0273546 A1	11/2011	Lin et al.		2016/0170617 A1	6/2016	Shi et al.
2011/0296163 A1	12/2011	Abernethy et al.		2016/0179767 A1	6/2016	Mavinakuli et al.
2011/0298967 A1	12/2011	Clavin et al.		2016/0180762 A1	6/2016	Bathiche et al.
2012/0032894 A1	2/2012	Parivar et al.		2016/0187994 A1	6/2016	La et al.
2012/0054670 A1	3/2012	Rainisto		2016/0202750 A1	7/2016	Pulapaka et al.
2012/0062470 A1	3/2012	Chang		2016/0212317 A1	7/2016	Alameh et al.
2012/0123680 A1	5/2012	Wipplinger et al.		2016/0232701 A1	8/2016	Drozdyuk
2012/0171656 A1*	7/2012	Shen	G06F 1/169 345/173	2016/0259467 A1	9/2016	Nayyar et al.
2012/0172085 A1	7/2012	Vuppu et al.		2016/0297362 A1	10/2016	Tijerina et al.
2012/0249429 A1	10/2012	Anderson et al.		2016/0370860 A1	12/2016	Bychkov et al.
2012/0300061 A1	11/2012	Osman et al.		2017/0010654 A1	1/2017	Chen
2012/0319997 A1	12/2012	Majumder		2017/0018234 A1	1/2017	Na et al.
2013/0007096 A1	1/2013	Pahlavan et al.		2017/0034146 A1	2/2017	Sugya
2013/0007590 A1	1/2013	Rivera et al.		2017/0039170 A1	2/2017	Tunali et al.
2013/0021265 A1	1/2013	Selim		2017/0075479 A1	3/2017	Tsukamoto
2013/0021750 A1	1/2013	Senatori		2017/0085790 A1	3/2017	Bohn
2013/0120460 A1	5/2013	Adams et al.		2017/0090585 A1	3/2017	Bernhart
2013/0321265 A1	5/2013	Bychkov et al.		2017/0147879 A1	5/2017	Alameh et al.
2013/0321271 A1	5/2013	Bychkov et al.		2017/0201254 A1	7/2017	Hanssen et al.
2013/0158999 A1	6/2013	Maruta et al.		2017/0219240 A1	8/2017	Cassini et al.
2013/0173946 A1	7/2013	Rotem et al.		2017/0269725 A1	9/2017	Kang
2013/0174016 A1	7/2013	Glazer et al.		2017/0321856 A1	9/2017	Keates
2013/0185633 A1	7/2013	Bunker et al.		2018/0039410 A1	2/2018	Kim et al.
2013/0207895 A1	8/2013	Lee et al.		2018/0039990 A1	2/2018	Lindemann
2013/0212462 A1	8/2013	Athas et al.		2018/0136719 A1	5/2018	Chen
2013/0222329 A1	8/2013	Larsby et al.		2018/0157815 A1	6/2018	Salama et al.
2013/0283213 A1	10/2013	Guendelman et al.		2018/0164942 A1	6/2018	Huffman et al.
2013/0289792 A1	10/2013	Cheng et al.		2018/0166076 A1	6/2018	Higuchi et al.
2013/0332760 A1	12/2013	Reece et al.		2018/0188774 A1	7/2018	Ent et al.
2014/0006830 A1	1/2014	Kamhi et al.		2018/0188803 A1	7/2018	Sharma et al.
2014/0028548 A1	1/2014	Bychkov et al.		2018/0189547 A1	7/2018	Daniels et al.
2014/0050360 A1	2/2014	Lin et al.		2018/0224871 A1	8/2018	Sahu et al.
2014/0085451 A1	3/2014	Kamimura et al.		2018/0321731 A1	11/2018	Alfano et al.
2014/0089865 A1	3/2014	Gay et al.		2018/0373292 A1	12/2018	Perelli
2014/0129937 A1	5/2014	Jarvinen et al.		2019/0004764 A1	1/2019	Son et al.
2014/0132508 A1	5/2014	Hodge et al.		2019/0034609 A1	1/2019	Yang et al.
2014/0132514 A1	5/2014	Kuzara et al.		2019/0079572 A1	3/2019	Yamamoto
2014/0139456 A1	5/2014	Wigdor et al.		2019/0129473 A1	5/2019	Hu et al.
2014/0149935 A1	5/2014	Johnson et al.		2019/0147875 A1	5/2019	Stemmer et al.
2014/0189579 A1	7/2014	Rimon et al.		2019/0155364 A1	5/2019	Chen
				2019/0174419 A1	6/2019	Schillings et al.
				2019/0236390 A1	8/2019	Guo et al.
				2019/0239384 A1	8/2019	North et al.
				2019/0250691 A1	8/2019	Lee et al.
				2019/0258785 A1	8/2019	Alameh et al.
				2019/0265831 A1	8/2019	Sinnott et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2019/0278339	A1	9/2019	Cooper et al.
2019/0361501	A1	11/2019	Park et al.
2019/0371326	A1	12/2019	Bocklet et al.
2019/0371342	A1	12/2019	Tukka et al.
2020/0012331	A1	1/2020	De Cesare et al.
2020/0026342	A1	1/2020	Sengupta et al.
2020/0033920	A1	1/2020	Nielsen et al.
2020/0134151	A1	1/2020	Magi et al.
2020/0092817	A1	3/2020	Bai
2020/0125158	A1	4/2020	Giusti et al.
2020/0125179	A1	4/2020	Okuley
2020/0133358	A1	4/2020	Mishra et al.
2020/0133374	A1	4/2020	Sinha et al.
2020/0175944	A1	6/2020	Sun et al.
2020/0213501	A1	7/2020	Sohn
2020/0259638	A1	8/2020	Carmignani et al.
2020/0348745	A1	11/2020	Hamlin et al.
2021/0025976	A1	1/2021	Chandel et al.
2021/0096237	A1	4/2021	Patole et al.
2021/0109585	A1	4/2021	Fleming et al.
2021/0240254	A1	8/2021	Hamlin et al.
2021/0318743	A1	10/2021	Partiwala et al.
2022/0147142	A1	5/2022	Bui et al.
2022/0350385	A1	11/2022	Mishra et al.

FOREIGN PATENT DOCUMENTS

CN	112558056	3/2021
EP	2518586	10/2012
EP	3285133	1/2019
JP	10-240389	A 9/1998
JP	2001255854	A 9/2001
JP	2002071833	A 3/2002
JP	2005221907	A 8/2005
KR	20150022673	3/2015
KR	20180029370	3/2018
WO	2010071631	6/2010
WO	2014131188	9/2014
WO	2014186294	11/2014
WO	2014205227	12/2014
WO	2015026203	2/2016
WO	2020191643	1/2020
WO	2021258395	12/2021
WO	2022139895	6/2022

OTHER PUBLICATIONS

Brian Reads, "Microsoft Windows Vista SideShow—In-Depth (pics)", Notebook Review, available at www.notebookreview.com/news/microsoft-windows-vista-sideshow-in-depth-pics/ (retrieved May 6, 2019), Jan. 11, 2006, 7 pages.

Chethan, "Proximity Sensing with CapSense," Cypress AN92239, 2016, 62 pages.

Cravotta, Nicholas, "Optimizing Proximity Sensing for Consumer Electronics Applications," Digi-Key Electronics, Apr. 26, 2012, 9 pages.

Cutress, "Asus ZenBook Pro 15(UX580): A 5.5-inch Screen in the Touchpad", retrieved from <https://www.anandtech.com/show/12880/asus-zenbook-pro-15-ux580-a-55inch-screen-in-the-touchpad>, Jun. 5, 2018, 5 pages.

European Patent Office, "Communication pursuant to Article 94(3) EPC," issued in connection with European Patent Application No. 20164273.3, dated Sep. 28, 2021 9 pages.

European Patent Office, "Extended European Search Report" issued in connection with European Patent Application No. 20194494.9, dated Feb. 17, 2021, 62 pages.

European Patent Office, "Extended European Search Report," issued in connection with European Patent Application No. 19921860.3, dated Oct. 10, 2022, 8 pages.

European Patent Office, "Extended European Search Report," issued in connection with European Patent Application No. 20164273.3, dated Oct. 9, 2020, 14 pages.

European Patent Office, "Extended European Search Report," issued in connection with European Patent Application No. 20197335.1, dated Jul. 16, 2021, 11 pages.

European Patent Office, "Extended European Search Report," issued in connection with European Patent Application No. 20197337.7, dated Mar. 9, 2021, 11 pages.

European Patent Office, "Rule 62a(1) Communication," issued in connection with European Patent Application No. 20197335.1, dated Mar. 17, 2021, 2 pages.

European Patent Office, "Extended Search Report," issued in connection with European Patent Application No. 20181123.9, dated Dec. 4, 2020, 11 pages.

Gajitz, "Open Sesame! Gesture-Controlled Motorized Laptop Lid", available at <https://gajitz.com/open-sesame-gesture-controlled-motorized-laptop-lid/> (retrieved May 6, 2019), Sep. 2012, 3 pages. Indiegogo, "Cosmo Communicator", available at <https://www.indiegogo.com/projects/cosmo-communicator#/> (retrieved May 6, 2019), 2018, 18 pages.

International Searching Authority, "International Preliminary Report on Patentability," issued in connection with application No. PCT/CN2019/079790, dated Sep. 28, 2021, 5 pages.

International Searching Authority, "International Preliminary Report on Patentability," issued in connection with PCT/US2016/048953, dated Mar. 27, 2018, 10 pages.

International Searching Authority, "International Search Report", issued in connection with PCT. Application No. PCT/US2021/049649, dated Jan. 14, 2022, 5 pages.

International Searching Authority, "International Search Report," issued in connection with PCT Application No. PCT/US2016/048953, dated Nov. 23, 2016.

International Searching Authority, "Invitation to Pay Additional Fees," issued in connection with PCT/US2021/049649, dated Nov. 26, 2021, 7 pages.

International Searching Authority, "Search Report and Written Opinion," issued in connection with PCT Application No. PCT/CN2020/098326, dated Mar. 29, 2021, 9 pages.

International Searching Authority, "Search Report," issued in connection with application No. PCT/CN2019/079790, dated Jan. 3, 2020, 4 pages.

International Searching Authority, "Written Opinion of the International Searching Authority," issued in connection with PCT Application No. PCT/US2016/048953, issued on Nov. 23, 2016.

International Searching Authority, "Written Opinion", issued in connection with PCT, Application No. PCT/US2021/049649, dated Jan. 14, 2022, 9 pages.

International Searching Authority, "Written Opinion," issued in connection with application No. PCT/CN2019/079790, dated Jan. 3, 2020, 4 pages.

Jack Purcher, "Google Patents a Motorized Pixelbook Lid that Opens and Closes with a Simple Touch & Auto-Aligns the Display to the user's Face", Patently Mobile, available at <https://www.patentlymobile.com/2017/11/google-patents-a-motorized-pixelbook-lid-that-opens-and-closes-with-a-simple-touch-auto-aligns-the-display-to-the-users-fa.html> (retrieved May 6, 2019), Nov. 25, 2017, 6 pages.

Kul Bushan, "CES 2019_ Dell's new laptop can sense your presence and wake itself" Hindustan Times, available at <https://www.hindustantimes.com/tech/ces-2019-dell-latitude-7400-2-in-1-laptop-launched-price-specifications-features/story-CiRoU1GoHHsHq3K3qtPZWJ.html> (retrieved May 6, 2019), Jan. 5, 2019, 8 pages.

Monica Chin, "Alexa on Windows 10 Hands-On: Useful, with 1 Big Catch", Laptop Magazine, available at <https://www.laptopmag.com/articles/alex-windows-10-hands-on> (retrieved May 6, 2019), Nov. 14, 2018, 6 pages.

Notebook Review, "CES 2007: Vista SideShow in HP, Fujitsu, LG and Asus Notebooks," Notebook Review, available at www.notebookreview.com/news/ces-2007-vista-sideshow-in-hp-fujitsu-lg-and-asus-notebooks/ (retrieved May 6, 2019), Jan. 8, 2007, 8 pages.

NVIDIA "PDK User's Guide: Preface Personal Media Device," Manual, published Sep. 4, 2007, 39 pages.

(56)

References Cited

OTHER PUBLICATIONS

NVIDIA, "NVIDIA and ASUS Deliver World's First Notebook with Windows Sideshow Secondary Display," Press Release, available at https://www.nvidia.com/object/IO_38772.html (retrieved May 6, 2019), Jan. 8, 2007, 5 pages.

NVIDIA, "NVIDIA® Preface™ Platform Enables Windows Vista On The Go," Press Release, available at https://www.nvidia.com/object/IO_38775.html (retrieved May 6, 2019), Jan. 8, 2007, 5 pages.

United States Patent and Trademark Office, "Non-Final Office Action," issued in connection with U.S. Appl. No. 16/421,217, dated Oct. 27, 2021, 29 pages.

United States Patent and Trademark Office, "Advisory Action" issued in connection with U.S. Appl. No. 14/866,894, dated Aug. 17, 2020, 3 pages.

United States Patent and Trademark Office, "Advisory Action" issued in connection with U.S. Appl. No. 14/866,894, dated Nov. 5, 2019, 6 pages.

United States Patent and Trademark Office, "Corrected Notice of Allowability" issued in connection with U.S. Appl. No. 16/586,225, dated Mar. 16, 2022, 3 pages.

United States Patent and Trademark Office, "Corrected Notice of Allowability," issued in connection with U.S. Appl. No. 16/586,225, dated Dec. 16, 2021, 3 pages.

United States Patent and Trademark Office, "Corrected Notice of Allowability," issued in connection with U.S. Appl. No. 16/586,225, dated May 18, 2022, 3 pages.

United States Patent and Trademark Office, "Corrected Notice of Allowability," issued in connection with U.S. Appl. No. 16/586,225, dated Sep. 19, 2022, 2 pages.

United States Patent and Trademark Office, "Final Office Action" issued in connection with U.S. Appl. No. 14/866,894, dated Jul. 29, 2019, 27 pages.

United States Patent and Trademark Office, "Final Office Action" issued in connection with U.S. Appl. No. 14/866,894, dated Jun. 23, 2020, 33 pages.

United States Patent and Trademark Office, "Final Office Action," issued in connection with U.S. Appl. No. 14/866,894, dated May 11, 2021, 17 pages.

United States Patent and Trademark Office, "Final Office Action," issued in connection with U.S. Appl. No. 16/725,467, dated Aug. 18, 2022, 29 pages.

United States Patent and Trademark Office, "Final Office Action," issued in connection with U.S. Appl. No. 16/728,774, dated Sep. 22, 2021, 20 pages.

United States Patent and Trademark Office, "Final Office Action," issued in connection with U.S. Appl. No. 16/728,899, dated Jun. 24, 2022, 10 pages.

United States Patent and Trademark Office, "Non Final Office Action" issued in connection with U.S. Appl. No. 14/866,894, dated Feb. 21, 2020, 30 pages.

United States Patent and Trademark Office, "Non Final Office Action" issued in connection with U.S. Appl. No. 14/866,894, dated Oct. 8, 2020, 40 pages.

United States Patent and Trademark Office, "Non-Final Office Action" issued in connection with U.S. Appl. No. 14/866,894, dated Dec. 14, 2018, 24 pages.

United States Patent and Trademark Office, "Non-Final Office Action" issued in connection with U.S. Appl. No. 16/728,899, dated Dec. 8, 2021, 9 pages.

United States Patent and Trademark Office, "Non-Final Office Action" issued in connection with U.S. Appl. No. 16/728,899, dated Oct. 20, 2022, 9 pages.

United States Patent and Trademark Office, "Non-Final Office Action," issued in connection with U.S. Appl. No. 16/586,225, dated Jun. 15, 2021, 28 pages.

United States Patent and Trademark Office, "Non-Final Office Action," issued in connection with U.S. Appl. No. 16/725,467, dated Apr. 7, 2022, 19 pages.

United States Patent and Trademark Office, "Non-Final Office Action," issued in connection with U.S. Appl. No. 16/728,774, dated May 3, 2021, 12 pages.

United States Patent and Trademark Office, "Non-Final Office Action," issued in connection with U.S. Appl. No. 17/434,603, dated Jul. 5, 2022, 15 pages.

United States Patent and Trademark Office, "Notice of Allowance and Fee(s) Due" issued in connection with U.S. Appl. No. 16/421,217, dated Mar. 9, 2022, 6 pages.

United States Patent and Trademark Office, "Notice of Allowance and Fee(s) Due," issued in connection with U.S. Appl. No. 14/866,894, dated Jul. 30, 2021, 8 pages.

United States Patent and Trademark Office, "Notice of Allowance and Fee(s) Due," issued in connection with U.S. Appl. No. 16/586,225, dated Apr. 29, 2022, 6 pages.

United States Patent and Trademark Office, "Notice of Allowance and Fee(s) Due," issued in connection with U.S. Appl. No. 16/586,225, dated Aug. 31, 2022, 5 pages.

United States Patent and Trademark Office, "Notice of Allowance and Fee(s) Due," issued in connection with U.S. Appl. No. 16/728,774, dated Feb. 2, 2022, 9 pages.

United States Patent and Trademark Office, "Notice of Allowance," issued in connection with U.S. Appl. No. 29/673,785, dated Nov. 16, 2020, 8 pages.

United States Patent and Trademark Office, "Notice of Allowance," issued in connection with U.S. Appl. No. 16/586,225, dated Dec. 8, 2021, 6 pages.

United States Patent and Trademark Office, "Requirement for Restriction," issued in connection with U.S. Appl. No. 29/673,785, dated Aug. 27, 2020, 4 pages.

United States Patent and Trademark Office, "Notice of Allowability" issued in connection with U.S. Appl. No. 16/421,217, dated Mar. 24, 2022, 3 pages.

European Patent Office, "Communication pursuant to Article 94(3) EPC," issued in connection with European Patent Application No. 20194494.9, dated Jan. 24, 2023, 6 pages.

International Searching Authority, "International Search Report," issued in connection with PCT Application No. PCT/CN2022/084726, dated Jan. 4, 2023, 4 pages.

International Searching Authority, "Written Opinion," issued in connection with PCT Application No. PCT/CN2022/084726, dated Jan. 4, 2023, 4 pages.

United States Patent and Trademark Office, "Advisory Action," issued in connection with U.S. Appl. No. 16/725,467, dated Jan. 4, 2023, 4 pages.

United States Patent and Trademark Office, "Non-Final Office Action," issued in connection with U.S. Appl. No. 17/129,465, dated Jan. 5, 2023, 12 pages.

European Patent Office, "Extended European Search Report," issued in connection with European Patent Application No. 23154752.2, dated May 4, 2023, 14 pages.

The Netherlands Patent Office, "Office Action," issued in connection with Netherlands Patent Application No. 2029823, dated Mar. 15, 2023, 14 pages (Written Opinion Provided in English).

United States Patent and Trademark Office, "Notice of Allowance and Fee(s) Due," issued in connection with U.S. Appl. No. 16/728,899, dated Apr. 3, 2023, 10 pages.

Japanese Patent Office, "Notice of Reasons for Rejection," issued in connection with Japanese Patent Application No. 2021-538701, dated Feb. 21, 2023, 7 pages (English translation included).

European Patent Office, "Communication pursuant to Article 71(3) EPC," issued in connection with European Patent Application No. 20164273.3, dated Dec. 23, 2022, 78 pages.

United States Patent and Trademark Office, "Final Office Action," issued in connection with U.S. Appl. No. 17/434,603, dated Feb. 8, 2023, 17 pages.

United States Patent and Trademark Office, "Notice of Allowance and Fee(s) Due," issued in connection with U.S. Appl. No. 18/160,419, dated Aug. 23, 2023, 11 pages.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12A




FIG. 12B




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19

METHODS AND APPARATUS TO OPERATE CLOSED-LID PORTABLE COMPUTERS

RELATED APPLICATION(S)

This patent arises from a continuation of U.S. patent application Ser. No. 16/421,217, which was filed on May 23, 2019. U.S. patent application Ser. No. 16/421,217 is incorporated herein by reference in its entirety. Priority to U.S. patent application Ser. No. 16/421,217 is claimed.

FIELD OF THE DISCLOSURE

This disclosure relates generally to computing, and, more particularly, to methods and apparatus to operate closed-lid portable computers.

BACKGROUND

Housings for laptop computers typically include a base portion that is rotationally coupled to a lid portion. The base portion of a laptop usually includes a keyboard that faces a display screen in the lid portion when the lid is closed against the base portion. Typically, laptop computers either shut down or go to an idle state when the lid is closed.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates an example portable computer constructed in accordance with teachings disclosed herein.

FIG. 2 illustrates the example portable computer of FIG. 1 with the lid in a closed position.

FIGS. 3 and 4 illustrate example secondary user interfaces rendered on the example secondary display of the example portable computer of FIGS. 1 and 2.

FIG. 5 is a block diagram illustrating an example implementation of the example portable computers of FIGS. 1 and 2.

FIGS. 6-11 illustrate example secondary user interfaces that may be rendered on the example secondary display as a user interacts with the example portable computer of FIGS. 1, 2, and/or 5.

FIGS. 12A, 12B, and 13-18 are flowcharts representative of example machine readable instructions which may be executed to implement the example portable computer of FIGS. 1, 2, and/or 5.

FIG. 19 is a block diagram of an example processing platform structured to execute the instructions of FIGS. 12A, 12B, and 13-18 to implement example portable computer of FIGS. 1, 2, and/or 5.

The figures are not to scale. In general, the same reference numbers will be used throughout the drawing(s) and accompanying written description to refer to the same or like parts.

Descriptors “first,” “second,” “third,” etc. are used herein when identifying multiple elements or components which may be referred to separately. Unless otherwise specified or understood based on their context of use, such descriptors are not intended to impute any meaning of priority, physical order or arrangement in a list, or ordering in time but are merely used as labels for referring to multiple elements or components separately for ease of understanding the disclosed examples. In some examples, the descriptor “first” may be used to refer to an element in the detailed description, while the same element may be referred to in a claim with a different descriptor such as “second” or “third.” In

such instances, it should be understood that such descriptors are used merely for ease of referencing multiple elements or components.

DETAILED DESCRIPTION

Many laptops and other similar portable computers today can provide virtually the same functionality as a desktop computer with the added feature of being easily carried by a user. The portability of a laptop and other clamshell devices is at least partially achieved in the design of the device housing that collapses on itself to reduce its size while protecting and/or concealing the display screen, keyboard, touchpad, and/or other components. More particular, the lid of such a portable computing device typically contains a display screen that folds down or closes upon a base of the housing. The base typically contains a keyboard (a physical keyboard or a virtual (e-ink or touch screen) keyboard), a touchpad, and/or the processor and/or other logic circuits to enable operation of the device. Some portable computing devices include a foldable display screen that extends across both the base and lid (with the keyboard and/or touchpad functionality integrated into the foldable display). While closing the lid of a clamshell device (e.g., a laptop) improves portability while protecting the user interface components of the device, many such devices do not provide any functionality while the lid is closed.

Example portable computers disclosed herein operate while the lid is closed to provide functionality previously only available when the computers are opened and turned on. Some examples portable computers disclosed herein operate in a low power or idle state when the lid is closed to conserve power. However, in some examples, the portable computer includes one or more sensors that remain active or turned on when the portable computer is in the lower power state with the lid closed. The sensors enable the portable computer to determine the context of the environment in which the portable computer is located to initiate appropriate actions that are responsive to the environment. For example, a human presence sensor on the portable computer may detect a person is approaching the closed computer. Upon detection of the person, the computer may initiate a user recognition process to identify or authenticate the person as an authorized user of the computer. If the person is recognized as an authorized user, the computer may wake up and automatically login the user so the user can immediately begin using the computer as soon as the lid is opened. In some examples, users may additionally or alternatively be authenticated based on voice recognition and/or in any other suitable manner. Further, in some examples, the computer may automatically open and/or initiate a particular application in response to detecting an indication of the user intended to access content associated with the particular application. Thus, examples disclosed herein enhance the user experience by enabling a portable computer to determine the context of its environment and to respond accordingly to provide a more seamless experience as a user seeks to open a closed portable computer (e.g., which may be in a sleep state) to begin using the device.

Further, in some examples, the portable computer may include a secondary display that is visible when the computer is closed (e.g., when a primary or main display is not visible). In some such examples, the secondary display may provide a graphical user interface containing user specific information that the user can access and/or interact without having to open the computer. In some examples, the active operation of the secondary display is associated with an

intermediate power state that consumes more power than when the computer is in an idle or sleep state but less power than when the computer is open with full functionality provided via the primary display. In some examples, power consumption is reduced relative to the full power state by implementing operations associated with the secondary display via a secondary, low power processor that is separate from a main processor used when the computer is fully turned on. In some examples, interactions with the secondary display may trigger the operation of functionality associated with the primary display to provide users with a seamless experience as they initially interact with the computer with a closed lid (via the secondary display) and then transition to a full power state with the lid opened. Similarly, in some examples, functionality provided via the primary display may continue to be available via the secondary display event after the computer is closed so that the primary display is no longer turned on.

FIG. 1 illustrates an example portable computer 100 constructed in accordance with teachings disclosed herein. In this example, the portable computer 100 is a laptop. In other examples, the portable computer 100 may correspond to different types of clamshell computing devices. The example portable computer 100 includes a housing 102 that includes a base 104 and a top or lid 106. As shown in the illustrated example, the base 104 of the portable computer includes a keyboard 108 and a touchpad 110. The lid 106 includes a primary display screen 114 (or primary display for short). In the illustrated example, the base 104 and the lid 106 are connected via a hinge 112 to enable the lid 106 to rotate relative to the base 104 between an open position (as shown in FIG. 1), and a closed position (as shown in FIG. 2). In some examples, the hinge 112 is constructed to open automatically without a user having to manually move the lid 106 from the closed position to the open position. Additionally or alternatively, in some examples, the hinge 112 is constructed to close automatically without a user having to manually move the lid 106 to the closed position.

For purposes of explanation, the primary display 114 in the lid 106 of the example portable computer 100 is referred to herein as a primary display to distinguish the primary display 114 from a secondary display screen 116 (or secondary display for short) that is also included on the portable computer 100. In this example, the secondary display 116 is an extension of the touchpad 110 that extends along a front edge 118 of the base 104 distal to the hinge 112. In the illustrated example, the secondary display 116 is positioned so as to be visible even when the lid 106 is closed as shown in FIG. 2. As used herein, reference to the portable computer 100 being closed and the lid 106 being closed are intended to convey the same thing, which is that the lid 106 is rotated about the hinge 112 to position a distal edge 120 of the lid 106 (top edge as viewed in FIG. 1) adjacent a distal edge of the base 104 (e.g., the front edge as viewed in FIG. 1) with the primary display 114 facing the base 104 in a generally parallel and/or face-to-face arrangement (although space between the base and the display is present in some examples). In some examples, the lid 106 is substantially parallel to the base 104 when in the closed position.

Although the secondary display 116 is shown as an extension of the touchpad 110, in other examples, the secondary display 116 may be separate from the touchpad 110. Additionally or alternatively, the secondary display may be located in a position different than what is shown in FIGS. 1 and 2. For example, the secondary display 116 may be positioned at a different location on the edge of the housing 102. In some examples, the secondary display 116 may be

positioned on the lid 106 (e.g., along the distal edge 120). In some examples, the secondary display 116 is located in a position that is visible to a user facing the front of the portable computer 100 regardless of whether the portable computer 100 is opened or closed.

As shown in FIGS. 1 and 2, the example portable computer 100 includes a user facing camera 122 positioned on an inside surface of the lid 106 so as to face in a same direction as the primary display 114. Additionally, the example portable computer 100 includes a world facing camera 124 positioned on an outside surface of the lid 106 so as to face in the opposite direction to the primary display 114. In some examples, the user facing camera 122 and the world facing camera 124 are positioned at correspond locations on opposite sides of the lid 106. In some examples, the user facing camera 122 and the world facing camera 124 include panamorphic lenses to enable the capture of ultra wide-angle images (e.g., panoramic or hemispherical images). In some examples, the panamorphic lenses have a field of view of at least 180 degrees as measured within a plane extending substantially perpendicular to the lid 106 with a 360 degree rotational view as measured in a plane substantially parallel to the lid 106. As a result, when the lid 106 is open and both cameras 122, 124 are turned on, it is possible to capture a 360 degree image of the surrounding environment in all directions (e.g., on both sides of the lid 106). Further, when the portable computer 100 is resting on a substantially flat surface with the lid 106 closed, the world facing camera 124 may be able to capture a 360 degree image of the surrounding environment (at least for areas above a plane defined by the outer surface of the lid 106). Accordingly, in some examples, the world facing camera 124 is able to monitor the environment surrounding the portable computer 100 when closed to determine a context that can be used as the basis to perform particular operations. In some examples, the portable computer 100 implements facial recognition procedures to uniquely identify a person detected in the vicinity of the computer to confirm or authenticate the person as an authorized user of the computer. In some such examples, once a user is authenticated in this manner, the computer may log the user into the computer and/or perform other suitable actions based on the authentication. Thus, users may be authenticated and logged into their computers before they have lifted the lid to their portable computers to begin using the devices (i.e., they may be authenticated while the lid is closed).

In some examples, the portable computer 100 includes light indicators 126 (e.g., LEDs) that turn on to indicate when a corresponding one of the cameras 122, 124 is on and capturing image data. As shown in the illustrated example, there are two light indicators 126 adjacent each of the cameras 122, 124 to indicate the active status of both cameras 122, 124. In other examples, only a single light indicator 126 is positioned adjacent each camera 122, 124 to indicate the status of the adjacent camera. In some examples, the light indicators 126 are positioned at a different location relative to the cameras 122, 124 (e.g., on the base 104 of the portable computer 100). In some examples, the light indicators 126 are omitted.

In some examples, the portable computer includes other sensors that may be used to monitor aspects of the environment surrounding the portable computer 100 while the computer is closed (or open). For instance, in some examples, the portable computer 100 may include one or more human presence sensors 128 (e.g., a motion sensor) to detect the presence of a person in the vicinity of the portable computer 100. In some examples, activation of the world

facing camera **124** when the portable computer **100** is closed is triggered by the human presence sensor **128** detecting a person (or at least some movement that may be caused by a person). Whether a person caused the movement (and whether the person is recognizable as an authorized user) can be verified based on image analysis of data captured by the camera **124**). Thus, in some examples, the world facing camera **124** is not always on when the computer is in a low powered idle state unless triggered by the human presence sensor **128**, thereby reducing power consumption in the low powered state. In other examples, the world facing camera **124** may always be turned on (unless configured by the user to be off). In some examples, the one or more human presence sensors **128** may be positioned to detect movement (e.g., people) in all direction. In other examples, the one or more human presence sensors **128** may be limited to monitoring an area in front of the portable computer **100** so as to avoid false positives triggering the world facing camera **124** (or other functionality) when detecting movement behind the portable computer **100**.

In the illustrated example, the portable computer **100** includes one or more microphones **130** to detect sounds in the environment surrounding the portable computer **100**. In some examples, different microphones **130** are located adjacent each of the cameras **122**, **124** on either side of the lid to enable audio monitoring whether the lid **106** is opened or closed. Additionally or alternatively, one or more microphones **130** may be placed at different locations (e.g., the front edge **118** of the base **104**) to capture sounds regardless of the position of the lid **106**. In some examples, the audio data captured by the microphones may be used as a separate technique to authenticate and log a user into a portable computer **100** while the computer is closed. More particularly, in some examples, the portable computer **100** may use voice recognition procedures to recognize a particular voice command stated by a nearby user. In some examples, the microphones **130** may be triggered by the human presence sensor **128**. In other examples, the microphones **130** may operate independent of the human presence sensor **128** to capture voice commands of people that are beyond the reliable range of the human presence sensor **128**.

The example computer includes one or more speakers **132** to provide audible outputs to a user. In some examples, the speakers **132** are positioned on an exterior surface of the portable computer **100** (e.g., the front edge **118** of the base **104**) so that sound produced by the speakers can be heard by users regardless of whether the lid **106** is opened or closed. In some examples, the portable computer **100** may include additional (e.g., larger) speakers that are covered by the lid **106** when the computer **100** is closed. Such speakers may only be operational when the portable computer **100** is open.

As mentioned above, the example portable computer **100** includes a secondary display **116** that is visible when the lid **106** is closed. In some examples, the secondary display **116** is capable of rendering graphical user interface content that changes based on the circumstances detected by the computer sensors and/or based on user inputs. For instance, the content rendered via the secondary display **116** may depend on whether a user is logged in to the portable computer **100**. In some examples, the content rendered via the secondary display **116** may depend on how close the user is to the portable computer **100** and/or the position and/or orientation of the person relative to the portable computer **100**. In some examples, the content rendered via the secondary display **116** may depend on the setting in which the portable computer **100** is located (e.g., at home, at work, in a public area, etc.).

In the illustrated example, the secondary display **116** includes a rendering of a power icon **134** and a battery power icon **136**. In the illustrated example, the secondary display **116** is touch sensitive so that a user may interact with the display. In some examples, the touch sensor for the secondary display **116** is the same as the touch sensor for the touchpad **110**. In other examples, user inputs detected by secondary display **116** may be accomplished independent of the sensor system of the touchpad **110**.

In some examples, the icons and/or other content rendered via the secondary display **116** are associated with particular operations that are invoked when the associated icons and/or content is touched by a user. For example, a user may touch the power icon **134** to turn on or off the secondary display **116**. Additionally or alternatively, touching the power icon **134** may turn off the entire portable computer **100**. In some examples, interactions of a user with the icons and/or other content on the secondary display may result in different actions by the portable computer **100** depending on the context in which a user interacts with the secondary display **116**. For instance, in some examples, a user selecting a particular icon rendered on the secondary display **116** may perform one function when the portable computer **100** is closed and a different function when the portable computer **100** is opened and in a full power state. In some examples, user interactions with the secondary display **116** may affect content that is rendered via the primary display **114**. Similarly, user interactions with the primary display **114** (and/or the associated keyboard **108** or touchpad **110**) may affect content that is (and/or will be) rendered via the secondary display **116**. Further, in some examples, content rendered via either the primary display **114** and/or the secondary display **116** may be controlled using voice commands without a user physically touching the secondary display **116** or any other component of the portable computer **100**.

In some examples, the content rendered via the secondary display and/or functionality associated with such content (e.g., when selected by a user) may depend on whether the user has been authenticated and/or logged into the computer. As mentioned above, in some examples, a user may be logged in automatically based on facial and/or voice recognition. In some examples, when a user has not been authenticated or logged in, the secondary display **116** renders a generic secondary user interface **300** (e.g., displaying the time, date, and power icon **134**) as shown in the illustrated example of FIG. 3. By contrast, when a user has been authenticated, a personalized secondary user interface **400** (e.g., displaying a user specific message **402** and/or other personalized information including one or more other icons) may be rendered via the secondary display as shown in the illustrated example of FIG. 4. As used herein, the term “secondary user interface” refers to rendered content and associated user-interactive functionality provided via the secondary display **116** to distinguish such from a “primary user interface” that corresponds to rendered content and associated user-interactive functionality provided via the primary display **114**.

As shown in the illustrated examples of FIGS. 3 and 4, both the generic and personalized secondary user interfaces **300**, **400** include the power icon **134** and the battery power icon **136**. However, in some examples, only an authorized user may be able to turn off the secondary display **116** by selecting the power icon. By contrast, if an unauthorized (e.g., unauthenticated) user selects the power icon **134**, the secondary display **116** may prompt the user to provide authentication information (e.g., request the user hold still while the world facing camera **124** captures an image for

facial recognition purposes, request the user to repeat a statement used for voice recognition, etc.).

Both the generic and personalized secondary user interfaces **300**, **400** of FIGS. **3** and **4** also include a camera icon **302** and a microphone icon **304**. In some examples, the camera icon **302** indicates when the world facing camera **124** and/or the user facing camera **122** is turned on to capture image data. Similarly, the microphone icon **304** indicates whether the one or more microphones **130** are turned on to capture audio data. In some examples, a user may select the camera icon **302** and/or the microphone icon **304** to toggle the corresponding camera or microphone on or off (e.g., to mute the microphone). In some such examples, the appearance of the icons **302**, **304** may change in appearance (e.g., color, brightness, etc.) to indicate when the associated microphone or camera is turned on or turned off. However, in some examples, only when the user has been authenticated and logged in is this toggling functionality enabled.

The main middle section of the secondary display **116** includes generic information **306** (e.g., time and date) when the generic secondary user interface **300** is rendered as shown in FIG. **3**. By contrast, as shown in the illustrated example of FIG. **4**, where a user has been authenticated and logged into the system, the personalized secondary user interface **400** includes personalized information **402** such as, for example, an identification or greeting of the user (e.g., with the user's name), and notifications about any pertinent information such as new emails, upcoming calendar appointments, etc. Further, in some examples, the secondary display **116** may render additional icons that the user can select to obtain more information and/or implement other actions. For instance, in the illustrated example of FIG. **4**, the personalized secondary user interface **400** includes a calendar icon **404** to enable users to access their calendars, an email icon **406** to enable users to access their emails, and a music player icon **408** to enable users to access their music. There may be any other number of icons or other content provided to the user via the secondary display **116**. In some examples, when the user selects on a particular icon associated with user-specific information, the user-specific information may be displayed via the secondary display **116**. Additionally or alternatively, selecting such information (e.g., by touching the relevant content via the secondary display **116** or via a voice command) may trigger the portable computer **100** to wake up so that the user-specific information is automatically rendered via the primary display **114** once the portable computer **100** is opened. Further, in some examples, selecting such information may trigger to automatically open and begin rendering the relevant content via the primary display **114**.

FIG. **5** is a block diagram illustrating an example implementation of the portable computer **100** of FIGS. **1** and **2**. In this example, the portable computer **100** includes one or more example sensor(s) **502**, one or more example communications interface(s) **504**, an example camera input analyzer **506**, an example audio input analyzer **508**, an example touch-based input analyzer **510**, an example login controller **512**, an example push notification controller **514**, an example primary display controller **516**, an example secondary display controller **518**, an example lid controller **520**, an example system controller **522**, and one or more example database(s) **524**.

The example sensor(s) **502** include any sensors that may be implemented to monitor or detect the circumstances or context of an environment surrounding the portable computer **100** and/or alternatively to detect or enable interactions with the portable computer **100** by a user. Thus, for example,

the sensor(s) **502** include a touch sensor associated with the secondary display **116** (which may be the same as or different than a touch sensor associated with the touchpad **110**) to detect a user's interactions with the secondary display **116**. The example sensor(s) **502** include the example user facing camera **122** and the example world facing camera **124** to capture images of the user and/or the surrounding environment. The example sensor(s) **502** include the one or more example microphones **130** to capture audio (e.g., voice commands) from a user within audible range of the portable computer **100**. The example sensor(s) **502** include the example human presence sensor **128** (e.g., a motion sensor) to detect motion in the vicinity of the portable computer **100** that may be indicative of a nearby person. The example sensor(s) **502** may include any other suitable sensor devices that collect relevant sensor data that may be used by the portable computer **100** to determine a current context. For example, the sensor(s) **502** may include an accelerometer, a gyroscope, and/or a magnetometer to determine motion, position, and/or orientation of the portable computer **100**. As another example, the sensor(s) **502** may include a fingerprint scanner to authenticate users based on their fingerprints. In some examples, one or more of the sensor(s) **502** may be powered on to collect sensor data while the portable computer **100** is closed and/or otherwise in a low power or idle state.

The example portable computer **100** of FIG. **5** includes one or more communication interface(s) **504** to enable the computer to communicate with other devices in a wired or wireless manner. For instance, in some examples, the communication interface(s) **504** includes an Ethernet jack to enable the portable computer **100** to be physically wired to a network. Additionally or alternatively, the communications interface(s) **504** may include wireless communications circuitry to communicate with other devices wireless (e.g., via Wi-Fi, Bluetooth, and/or a mobile telephone network). In some examples, the portable computer **100** may be connected to a cloud network (e.g., the Internet) via the communications interface to transmit data to and/or retrieve data from remote servers that may be used by the portable computer **100**. In some examples, the communications interface **504** may receive push notifications from remote servers and/or other devices that are subsequently processed and/or initiate particular actions. For example, push notifications may correspond to the receipt of new email messages, incoming conference calls, a request from a nearby device to connect with the computer to share a file or other document, a file or other document shared by a nearby device designated as a trusted device for file sharing purposes, etc. In some examples, one or more of the communication interface(s) **504** may be powered on to send or receive data while the portable computer **100** is closed and in a low power and/or intermediate power state that consumes less power than when the computer is opened and fully active (e.g., with the primary display **114** turned on to render content for a user).

The example camera input analyzer **506** of the illustrated example of FIG. **5** processes and/or analyzes image data captured by the user facing camera **122** and/or the world facing camera **124**. In some examples, the camera input analyzer **506** is implemented to authenticate a user of the portable computer **100** based on a facial recognition analysis of an image of the user's face. In some examples, this facial recognition analysis may be performed while the portable computer **100** is closed so that a user may be authenticated and logged into the portable computer **100** before the user opens (or even touches) the portable computer **100**. In some

examples, the camera input analyzer **506** may transmit image data to a remote server (e.g., via the communications interface **504**) to perform the facial recognition. In other examples, the facial recognition may be performed locally on the portable computer **100** by comparing image data to reference user authentication data (e.g., reference images of authorized users) stored in the database(s) **524**. In some examples, the camera input analyzer **506** may implement other actions on the portable computer **100** based on an analysis of image data captured by one of the cameras **122**, **124**. For example, the camera input analyzer **506** may determine the context in which the computer is located (e.g., public versus private setting) to determine whether to display private information to the authenticated user. In other examples, the camera input analyzer **506** may monitor movement of the user for particular gestures (e.g., hand motions) intended to control operation of the portable computer **100**.

The example audio input analyzer **508** of the illustrated example of FIG. **5** processes and/or analyzes audio data captured by the microphones **130** on the portable computer **100**. In some examples, the audio input analyzer **508** is implemented to authenticate a user of the portable computer **100** based on a voice recognition analysis of captured audio corresponding to the voice of a user. In some examples, this voice recognition analysis may be performed while the portable computer **100** is closed so that a user may be authenticated and logged into the portable computer **100** before the user opens (or even touches) the portable computer **100**. In some examples, the audio input analyzer **508** may transmit audio data to a remote server (e.g., via the communications interface **504**) to perform the voice recognition. In other examples, the voice recognition may be performed locally on the portable computer **100** by comparing image data to reference user authentication data (e.g., reference images of authorized users) stored in the database(s) **524**. In some examples, the audio input analyzer **508** may analyze audio input to detect voice commands from a user to enable the user to interact and/or control the portable computer **100** without touching the device. As with the voice recognition, such voice detection may be implemented locally on the computer or accomplished via a remote server. In some examples, the audio input analyzer **508** may determine whether a detected voice command is to be implemented based on whether or not the person providing the command is an authorized user (e.g., authenticated based on voice recognition).

The example touch-based input analyzer **510** of the illustrated example of FIG. **5** processes and/or analyzes touch-based data captured by a touch sensor associated with the touchpad **110** and/or the secondary display **116**. Inasmuch as the secondary display **116** is visible and available for user interaction when the computer lid **106** is closed, the touch-based input analyzer **510** may be powered and operating while the portable computer **100** is closed. In some examples, the touch-based input analyzer **510** is always powered when the portable computer **100** is turned on, even when the computer is in a low power or sleep state. In other examples, the touch-based input analyzer **510** may be activated in response to detection of a person in the vicinity of the portable computer **100** by the human presence sensor **128**. In other examples, the touch-based input analyzer **510** is activated only after a user has been authenticated (e.g., via facial recognition and/or voice recognition).

The example login controller **512** of the illustrated example of FIG. **5**, determines when and whether to login or logout a user on the portable computer **100**. In some

examples, the login controller **512** determines to login a user after the user has been authenticated visually by the camera input analyzer **506** and/or audibly by the audio input analyzer **508**. In some examples, if not of the sensor(s) **502** detect any activity for a threshold period of time, the login controller **512** may automatically logout a user current logged in to the portable computer **100**. In some examples, the login controller **512** may be powered or turned on while the portable computer **100** is still closed to enable a user to login to the portable computer **100** without having to open the portable computer **100** and wait for the device to boot up.

The example push notification controller **514** of the illustrated example of FIG. **5** analyzes and/or controls responses to push notifications received from remote sources via the communications interface. For instance, in some examples, the push notification controller **514** causes an audio, visual, and/or haptic signal to be generated to alert a user of an incoming notification. In some examples, whether such a notification is generated and/or the nature of the notification (e.g., the amount of detail included with the notification) may depend on whether a user is logged in as determined by the login controller **512**. Further, in some examples, the push notification controller **514** may generate and/or determine different options a user may select to respond to an incoming notification. For instance, one option may be for a user to dismiss the notification and respond later, a second option may be for a user to provide a quick reply (e.g., a short preset text message), and a third option may be for the user to provide a detailed response (e.g., immediately answer an incoming conference call, begin drafting a reply email, etc.). In some examples, the push notification controller **514** may be powered or turned on while the portable computer **100** is still closed to enable a user to respond to incoming push notifications while the computer is closed (e.g., via the secondary display **116**).

In the illustrated example of FIG. **5**, the primary display controller **516** serves to control the operation of the primary display **114** and to facilitate the rendering of content (e.g., primary user interfaces) via the primary display. The example secondary display controller **518** of FIG. **5** serves to control the operation of the secondary display **116** and to facilitate the rendering of content (e.g., secondary user interfaces) via the secondary display. In some examples, the primary display controller **516** and the secondary display controller **518** update the rendering of content on the respective displays **114**, **116** based on outputs of one or more of the example sensor(s) **502**, the example communications interface(s) **504**, the example camera input analyzer **506**, the example audio input analyzer **508**, the example touch-based input analyzer **510**, the example login controller **512**, and/or the example push notification controller **514**. In some examples, the nature of content rendered by the primary display controller **516** and the secondary display controller **518** depends on whether there is an authorized or authenticated user logged into the portable computer **100**.

Further, in some examples, content accessed and/or interacted with by a user on one of the displays **114**, **116** may affect content rendered via the other display. For instance, in some examples, when a user launches an application having a primary user interface to be rendered via the primary display **114**, the secondary display controller **518** may automatically launch a corresponding secondary user interface associated with the application to be rendered via the secondary display **116**. As a specific example, a user may launch a media player via the primary display **114**, which may cause the secondary display controller **518** to render a secondary user interface via the secondary display **116** that

11

contains control options (e.g., play, pause, skip, backward, forward, volume controls, etc.) that enable a user to control the playback of media (e.g., videos, music, etc.) shown in an application user interface rendered on the primary display 114.

In the above examples, user interactions with the primary display 114 (and the associated primary display controller 516) result in changes to the secondary display 116 based on operations of the secondary display controller 518. Similarly, user interactions with the secondary display 116 (and the associated secondary display controller 518) may cause the primary display controller 516 to implement operations affecting content rendered via the primary display 114. As a specific example, the secondary display controller 518 may render the email icon 406 shown in FIG. 4 when the user has new emails to read. If the user selects the email icon 406 (either by touching the icon or through a voice command), the secondary display controller 518 may render basic details about the new emails (e.g., sender name, subject line, etc.). If the user selects a particular email listed on the secondary display 116, the primary display controller 516 may initiate or render a primary user interface for an email application via the primary display 114 for the user to view the entire email and/or to reply as appropriate.

As described above, while the primary display 114 is not visible when the lid 106 of the portable computer 100 is closed, the secondary display 116 remains visible. Accordingly, in some examples, the secondary display controller 518 remains powered and/or in operation while the computer is closed. By contrast, in some examples, the primary display controller 516 is powered and/or in operation only when the lid 106 is opened. However, in some examples, the primary display controller 516 may be turned on or activated before the lid 106 is opened based on an indication of intent of the user to open the lid 106 to begin accessing content using the primary display 114. For instance, assume that the portable computer 100 is closed in the above example when the user selects a particular email via the secondary display 116 to view in further detail. In some such examples, the secondary display controller 518 may communicate the intent of the user to view the email via the primary display while the portable computer 100 is still closed, thereby causing the secondary display controller 518 to activate and turn on the primary display 114 to render the email within a primary user interface associated with a corresponding email application. Thus, although the primary display controller 516 may be turned on while the computer is closed, in some examples, activation of the primary display controller 516 corresponds with activation of the computer to a full power (awake) state.

As outlined above, operation of the primary display controller 516 is associated with the portable computer 100 being in a full power state. By contrast, the secondary display controller 518 may operate in a lower power state (e.g., idle/sleep state and/or an intermediate power state). In some examples, to improve (e.g., optimize) the power consumption of the portable computer 100 in the different power states, the primary display controller 516 and the secondary display controller 518 may be implemented on different processors including a main processor for use when the portable computer 100 is in a full power state and a second low power processor for use when the computer is in a lower power state. In some such examples, certain aspects of functionalities of the other components of the portable computer 100 shown in FIG. 5 may be implemented by the main processor while other aspects or functionalities are implemented by the low power processor.

12

The example lid controller 520 of the illustrated example controls and/or monitors the positional relationship of the lid 106 and the base 104 of the portable computer 100 about the hinge 112. More particularly, in some examples, the lid controller 520 determines when the portable computer 100 is closed and when the computer is closed. In some examples, opening and closing the portable computer 100 may trigger a transition of the portable computer 100 between different power states, which may affect the type of content that is rendered via the displays 114, 116 and/or what displays 114, 116 are used to display content. Further, in some examples, the lid controller 520 is able to control the hinge 112 to automatically open the lid 106 without a person manually moving the lid 106 open. Additionally or alternatively, in some examples, the lid controller 520 is able to control the hinge 112 to automatically close the lid 106 without a person manually moving the lid 106 closed. In some examples, the automatic opening and/or closing of the lid 106 is performed in response to user inputs (e.g., via a voice command, via a touch-based user selection on the secondary display 116, etc.). In some examples, the hinge 112 is associated with a spring to automatically open and/or close the lid 106 in response to the lid controller 520 releasing a latch securing the lid 106 in closed or open position. In other examples, the hinge 112 is associated with a motor to automatically open and/or close the lid 106.

The example system controller 522 of the illustrated example of FIG. 5 serves to oversee, control and/or facilitate interactions between different ones of the components of the portable computer 100 shown in FIG. 5 and/or other components of the portable computer 100 not represented in the illustrated example.

As mentioned above, the example database(s) 524 may store user authentication data to enable the camera input analyzer 506 to recognize a person captured in an image as an authorized user and/or to enable the audio input analyzer 508 to recognize a person as an authorized user based on the voice of the user. Further, in some examples, the database(s) 524 include a database of voice commands that may be identified by the audio input analyzer 508 (regardless of whether the voice is recognized as corresponding to a unique individual) to enable voice detection of commands locally on the portable computer 100 without the need for transmitting audio data to or otherwise communicating with a remote server. Further, in some examples, the database(s) 524 store user preferences pertaining to the operation of the secondary display 116 and/or the content rendered via the display 116 both when no authorized user has been recognized and when an authorized user has been recognized.

While an example manner of implementing the example portable computer 100 of FIGS. 1 and 2 is illustrated in FIG. 5, one or more of the elements, processes and/or devices illustrated in FIG. 5 may be combined, divided, re-arranged, omitted, eliminated and/or implemented in any other way. Further, the example sensor(s) 502, the example communications interface(s) 504, the example camera input analyzer 506, the example audio input analyzer 508, the example touch-based input analyzer 510, the example login controller 512, the example push notification controller 514, the example primary display controller 516, the example secondary display controller 518, the example lid controller 520, the example system controller 522, the example database(s) 524 and/or, more generally, the example portable computer 100 of FIG. 5 may be implemented by hardware, software, firmware and/or any combination of hardware, software and/or firmware. Thus, for example, any of the example sensor(s) 502, the example communications inter-

face(s) 504, the example camera input analyzer 506, the example audio input analyzer 508, the example touch-based input analyzer 510, the example login controller 512, the example push notification controller 514, the example primary display controller 516, the example secondary display controller 518, the example lid controller 520, the example system controller 522, the example database(s) 524 and/or, more generally, the example portable computer 100 could be implemented by one or more analog or digital circuit(s), logic circuits, programmable processor(s), programmable controller(s), graphics processing unit(s) (GPU(s)), digital signal processor(s) (DSP(s)), application specific integrated circuit(s) (ASIC(s)), programmable logic device(s) (PLD(s)) and/or field programmable logic device(s) (FPLD(s)). When reading any of the apparatus or system claims of this patent to cover a purely software and/or firmware implementation, at least one of the example sensor(s) 502, the example communications interface(s) 504, the example camera input analyzer 506, the example audio input analyzer 508, the example touch-based input analyzer 510, the example login controller 512, the example push notification controller 514, the example primary display controller 516, the example secondary display controller 518, the example lid controller 520, the example system controller 522, and/or the example database(s) 524 is/are hereby expressly defined to include a non-transitory computer readable storage device or storage disk such as a memory, a digital versatile disk (DVD), a compact disk (CD), a Blu-ray disk, etc. including the software and/or firmware. Further still, the example portable computer 100 of FIGS. 1 and 2 may include one or more elements, processes and/or devices in addition to, or instead of, those illustrated in FIG. 5, and/or may include more than one of any or all of the illustrated elements, processes and devices. As used herein, the phrase “in communication,” including variations thereof, encompasses direct communication and/or indirect communication through one or more intermediary components, and does not require direct physical (e.g., wired) communication and/or constant communication, but rather additionally includes selective communication at periodic intervals, scheduled intervals, aperiodic intervals, and/or one-time events.

FIGS. 6-11 illustrate example secondary user interfaces rendered on the secondary display 116 as a user interacts with the example portable computer 100 in different ways. In particular, FIG. 6 illustrates different secondary user interfaces rendered via the secondary display 116 at different stages 602, 604, 606, 608, 610 in time during a wakeup sequence for the secondary display 116. In the illustrated example, the portable computer 100 begins in a lower power idle state with the lid 106 closed and the secondary display 116 in an idle or sleep state. As such, at the initial stage 602 in the sequence, the secondary display 116 does not include any content rendered thereon. In this low power idle state of the portable computer 100, the human presence sensor 128 is monitoring for people in the vicinity of the portable computer 100. Once the human presence sensor 128 detects a person, the sequence advances to the second stage 604 where the secondary display 116 is activated. Further, in this example, the world facing camera 124 is activated to capture an image of the detected person for authentication purposes (e.g., based on facial recognition). In some examples, the secondary display 116 displays an indication that the camera 124 is capturing an image and/or analyzing the captured image. In some examples, the indication may correspond to changing an appearance of the camera icon 302 and/or including an additional icon and/or animation 612 in the central region of the secondary display 116. The icon and/or

animation 612 may convey to a user the time period during which the user may choose to hold still facing the camera to facilitate the user recognition. The camera input analyzer 506 then determines whether the detected person can be recognized as an authorized user. If not, the process moves to the third stage 606 where a generic secondary user interface is provided (e.g., similar to the secondary user interface 300 discussed above in connection with FIG. 3). If the person is recognized, the process advances to the fourth stage 608 where the secondary display controller 518 causes the secondary display 116 to render an acknowledgement (e.g., a greeting 614 identifying the user by name) that the user was recognized. In some examples, the system controller 522 may additionally cause speakers 132 to provide an audible greeting and/or other audible notification indicating the user has been recognized and logged into the portable computer 100 as an authorized user. Thereafter, at the fifth stage 610, the secondary display 116 renders a personalized home screen containing personalized information and/or icons that enable the user to access personalized information. In some examples, the personalized home screen may be similar to the secondary user interface 400 discussed above in connection with FIG. 4.

FIG. 7 illustrates different secondary user interfaces rendered via the secondary display 116 at different stages 702, 704, 706, 708, 710 in time associated with responding to a voice command from a user. As with FIG. 6, all of the stages 702, 704, 706, 708, 710 in FIG. 7 occur with the lid 106 of the portable computer 100 closed. Further, all of the stages 702, 704, 706, 708, 710 in FIG. 7 may be performed while the portable computer 100 is in a lower power state (e.g., less than in a full power state). In this example, the first stage 702 corresponds to the secondary display 116 rendering the personalized home screen indicating that a user has already been recognized and logged into the system. In some examples, a voice command may be used to authenticate a user in a similar manner to the process flow for capturing and analyzing image data discussed above in connection with FIG. 6. In this example, the microphone 130 is monitoring for a voice assistant trigger word, which, in this example is “computer.” Thus, as the user speaks the trigger word, a voice assistant (e.g., associated with the audio input analyzer 508) is activated to monitor and detect the rest of the user’s voice command. In some examples, the secondary display 116 displays an indication that the voice assistant (audio input analyzer 508) is listening for a voice command and/or analyzing audio associated with the command. In some examples, the indication may correspond to changing an appearance of the microphone icon 304 and/or including an additional icon and/or animation 712 in the central region of the secondary display 116. In some examples, the icon and/or animation 712 of FIG. 7 may be the same as the icon and/or animation 612 associated with the camera input analyzer 506 capturing and/or analyzing image data as discussed above in FIG. 6.

In this example, the voice command is “Computer, when is my next meeting?” In some examples, the audio input analyzer 508 may perform voice recognition on the voice command to confirm that the voice comes from the authorized user before proceeding. In other examples, the process may proceed without user authentication inasmuch as the user has already been authenticated and logged into the portable computer 100. Assuming the user was recognized and/or the recognition was not performed, the process advances to the third stage 706 where the secondary display 116 provides confirmation that the voice command was detected by, for example, showing the voice command as

15

text on the display. Additionally or alternatively, the voice command may be repeated back to the user via the speakers 132. The audio input analyzer 508 in conjunction with the system controller 522 may determine the intent of the voice command and retrieve the relevant information from the user's calendar that is responsive to the user's request. The relevant information is then provided via the secondary display 116 (and/or via the speakers 132) at the fourth stage 708. After a threshold period of time, the secondary user interface rendered on the secondary display 116 may revert to the previous view prior to detecting the voice command at the fifth stage 710. In this example, the previous view corresponds to the personalized home screen shown at the first stage 702 in the process.

FIG. 8 illustrates different secondary user interfaces rendered via the secondary display 116 at different stages 802, 804, 806, 808, 810, 812 in time associated with responding to a voice command from a user. As with FIGS. 6 and 7, all of the stages 802, 804, 806, 808, 810, 812 in FIG. 8 occur with the lid 106 of the portable computer 100 closed. Further, all of the stages 802, 804, 806, 808, 810, 812 in FIG. 8 may be performed while the portable computer 100 is in a lower power state (e.g., less than in a full power state). In some examples, rather than the audio input analyzer 508 always monitoring for a voice assistant trigger word, a user may provide a touch-based input to activate or trigger the voice assistant system associated with the audio input analyzer 508 as demonstrated in the illustrated example of FIG. 8. Specifically, the first stage 802 corresponds to the secondary display 116 rendering the personalized home screen. While at this stage, the user may select (e.g., by touching) the microphone icon 304 on the secondary display to indicate the intent to provide a voice command to the system. By touching the microphone icon 304, the user activates the voice assistant such that, at the second stage 804, the secondary display 116 displays an indication that the voice assistant (audio input analyzer 508) is listening for a voice command and/or analyzing audio associated with the command as discussed above in connection with the second stage 704 of FIG. 7. With the indication on the secondary display 116, the user knows to proceed to speaking a voice command, which, in this example, is "Computer, show me my calendar?" At the third stage 806, the secondary display 116 renders an acknowledgement that the voice command was detected. Thereafter, at a fourth stage 808, the secondary display 116 is updated to render a secondary user interface associated with the calendar application on the portable computer 100. In some examples, the user may interact with the calendar by touching the secondary display 116. Thus, for example, the user may slide the calendar display into the future to see future appointments as shown at the fifth stage 810 in the illustrated example. Either after a threshold period of time without user activity or in response to a user request (e.g., selecting the home screen icon 814), the secondary display 116 may again revert to the home screen at the sixth stage 812. Although the procedures of FIGS. 6 and 7 are described in the context of user interactions based on voice commands, in other examples, the user may control the secondary user interface exclusively through touch. For example, rather than requesting to view the calendar using speech, a user may simply select the calendar icon 816 on the home screen to bring up the secondary user interface associated with the calendar.

FIG. 9 illustrates different secondary user interfaces rendered via the secondary display 116 at different stages 902, 904, 906, 908, 910 in time associated with providing a push notification to an authorized user of the portable computer

16

100. As with FIGS. 6-8, all of the stages 902, 904, 906, 908, 910 in FIG. 9 occur with the lid 106 of the portable computer 100 closed. Further, all of the stages 902, 904, 906, 908, 910 in FIG. 9 may be performed while the portable computer 100 is in a lower power state (e.g., less than in a full power state). In this example, the first stage 902 corresponds to the secondary display 116 rendering the personalized home screen indicating that a user has already been recognized and logged into the system. Thereafter, the calendar application running on the portable computer 100 may generate a push notification to provide a reminder that it is almost time for an upcoming meeting or other scheduled appointment. Accordingly, at the second stage 904, the secondary display 116 is automatically updated with a reminder notification 912. In this example, the reminder notification 912 includes an indication of the location (e.g., room JF3-201) and a document icon 914 indicating there is a document associated with the meeting. In some examples, the system controller 522 may generate an audible and/or haptic signal to alert the user of the reminder.

Continuing in time in the illustrated example, the calendar app may receive a push notification from the organizer of the meeting that there has been a room change. Accordingly, at the third stage 906 of the illustrated example, the secondary display includes an alert icon 916. In this example, when the user selects the alert icon 916, details of the room change are rendered via the secondary display 116 at the fourth stage 908. In some examples, the secondary user interface at the fourth stage includes response options associated with the push notifications. In this example, the options include the user accepting or acknowledging the room change, rejecting or dismissing the room change, or replying to the room change (e.g., to propose an alternate room). In this example, the user accepts the room change such that, at the fifth stage 910, the calendar is updated with the new room number. In some examples, the calendar may be automatically updated with the new room number without the user having to accept the change.

FIG. 10 illustrates different secondary user interfaces rendered via the secondary display 116 at different stages 1002, 1004, 1006, 1008, 1010, 1012, 1014 in time associated with providing and responding to a push notification corresponding to an incoming conference call. In this example, the first stage 1002 corresponds to the secondary display 116 rendering the personalized home screen while the lid 106 of the portable computer 100 is closed. When an incoming call is received, a secondary user interface associated with the conference calling application on the portable computer 100 is rendered via the secondary display 116 at the second stage 1004. In some examples, an audible alert may be generated via the speakers 132. As shown in the illustrated example, the secondary user interface rendered at the second stage 1004 includes an identification of the caller and different response options for the user that include accepting or answering the call, dismissing or hanging up the call, or providing a quick reply. In some examples, the quick reply may be short text message to the caller selected from a list of preconfigured text replies. In this example, the user accepts the call and the secondary user interface is updated to provide control options and/or additional detail about the ongoing call as shown at the third stage 1006 of the illustrated example. In some examples, the call automatically activates the microphone so that the user can speak on the call, which is indicated by a microphone icon 1016 within the control options for the ongoing conference call. In some examples, if the user selects the microphone icon 1016, the user mutes the microphone. Muting the micro-

17

phone may be indicated by a change in the microphone icon **1016** as shown at the fourth stage **1008** in FIG. **10**.

In some examples, the control options may also include a video icon **1018** that may be selected by the user to activate the world facing camera **124** to transmit video on the call. In some examples, the video icon may be provided as an option only when the portable computer **100** is open. In the illustrated example, the user opens the portable computer **100** between the fourth and fifth stages **1008**, **1010**. Once the portable computer **100** is opened, a 360 degree video icon **1020** may be provided via the secondary user interface. In some examples, the 360 degree video icon may be included alongside the standard video icon **1018** or in place of it. In some examples, the standard video icon **1018** activates the camera that is facing the user. That is, if the portable computer **100** is closed, selecting the standard video icon **1018** may activate the world facing camera **124**. However, when the portable computer **100** is open, selecting the standard video camera **1018** may activate the user facing camera **122**. By contrast, selecting the 360 degree video icon **1020** activates both the user facing camera **122** and the world facing camera **124** to capture a 360 degree view of the area surrounding the portable computer **100**. The sixth stage **1012** in the illustrated occurs after the user has unmuted the microphone and selected the 360 degree video icon **1020**. In some examples, a primary user interface associated with the conference calling application is rendered via the primary display **114** in response to the user selecting the video option so that the user is able to view the video stream on the primary display **114**. In some examples, the primary user interface may be rendered automatically on the primary display **114** in response to the lid **106** of the portable computer **100** being opened regardless of whether the user selects one of the video options. In some examples, one or both of the video options may be provided on the secondary display **116** while the computer is closed and, if selected, cause the primary display to turn on to render the primary user interface associated with the conference calling application even before the display is open. In this manner, the video conference call will be ready and going as soon as the user opens the portable computer **100**.

The seventh stage **1014** in the illustrated example corresponds to after the conference all has ended. In this example, although the portable computer **100** is now opened, the secondary display still reverts to the view prior to the conference call. In this example, the previous view corresponds to the personalized home screen of the user as in the first stage **1002**,

FIG. **11** illustrates different secondary user interfaces rendered via the secondary display **116** at different stages **1102**, **1104**, **1106**, **1108**, **1110**, **1112**, **1114** in time associated with user interactions between both the primary and secondary displays **114**, **116**. In this example, the first stage **1102** corresponds to the secondary display **116** rendering the personalized home screen while the lid **106** of the portable computer **100** is opened so that the user may be interacting with the primary display **114**. More particular, the example proceeds with the user launching a music player application via the primary display to begin playing music. At the second stage **1104**, the secondary display **116** is updated to identify the song that is playing and to provide control options for the user to control the music via the secondary display. In some examples, if the user does not interact with the secondary display within a threshold period of time, the secondary display will revert to the personalized home screen as shown at the third stage **1106**. The user may still activate the music player controls on the secondary display

18

116 by selecting the music player icon **408**. Once the icon **408** is selected, a full secondary user interface associated with the music player may be rendered via the secondary display **116** as shown at the fourth stage **1108** in the illustrated example. In some examples, the full secondary user interface for the music player application may automatically be launched on the secondary display **116** in response to the user launching the application via the primary display **114**. In some examples, that the music player application is active on the secondary display **116** is indicated by a change to the music player icon **408** as shown in the illustrated example.

While the music is still playing, the user may close the portable computer **100**. In some examples, the music player application may continue to be executed in connection with the secondary display **116**. In some examples, closing the computer lid **106** may cause the current song being played to pause. However, the secondary display may provide an option in the controls to enable the user to have the song continue playing where it was paused as shown at the fifth stage **1110** in FIG. **11**. The playback of the song when the lid **106** is closed may be from the speakers **132** on the front of the portable computer **100** if the user was using speakers before closing the portable computer **100**. If the user was playing the music via headphones (e.g., via a Bluetooth or wired connection), the song would continue to play the music via the headphones after the lid **106** is closed and the user selects the option to continue playing the song. In some examples, the song may automatically continue to play after the user closes the computer lid **106** without waiting for the user to indicate the song should continue to be played. The sixth stage **1112** in the illustrated example represents the song being played (with the option to again pause the song) while the portable computer **100** is closed. The user may desire to access other information and/or functionality on the computer via the secondary display while the music continues to play. To do so, the user may select the home screen icon **814** on the secondary display to return to the personalized home screen as shown in the seventh stage **1114** of FIG. **11**. In this example, even though the secondary user interface associated with the music player is no longer being rendered via the secondary display **116**, the music continues to play. In some examples, the active music player continues to be indicated on the secondary display **116** based on the changed appearance of the music player icon **408**. If the user wishes to change songs or otherwise again control the music, the user may again select the music player icon **408** to reopen the associated secondary user interface.

Flowcharts representative of example hardware logic, machine readable instructions, hardware implemented state machines, and/or any combination thereof for implementing the portable computer **100** of FIGS. **1** and **2** is shown in FIGS. **12A**, **12B**, and **13-18**. The machine readable instructions may be one or more executable programs or portion(s) of an executable program for execution by a computer processor such as the processors **1910**, **1912** shown in the example processor platform **1900** discussed below in connection with FIG. **19**. The program may be embodied in software stored on a non-transitory computer readable storage medium such as a CD-ROM, a floppy disk, a hard drive, a DVD, a Blu-ray disk, or a memory associated with the processors **1910**, **1912**, but the entire program and/or parts thereof could alternatively be executed by a device other than the processors **1910**, **1912** and/or embodied in firmware or dedicated hardware. Further, although the example program is described with reference to the flowcharts illustrated in FIGS. **12A**, **12B**, and **13-18**, many other methods of

implementing the example portable computer **100** may alternatively be used. For example, the order of execution of the blocks may be changed, and/or some of the blocks described may be changed, eliminated, or combined. Additionally or alternatively, any or all of the blocks may be implemented by one or more hardware circuits (e.g., discrete and/or integrated analog and/or digital circuitry, an FPGA, an ASIC, a comparator, an operational-amplifier (op-amp), a logic circuit, etc.) structured to perform the corresponding operation without executing software or firmware.

The machine readable instructions described herein may be stored in one or more of a compressed format, an encrypted format, a fragmented format, a packaged format, etc. Machine readable instructions as described herein may be stored as data (e.g., portions of instructions, code, representations of code, etc.) that may be utilized to create, manufacture, and/or produce machine executable instructions. For example, the machine readable instructions may be fragmented and stored on one or more storage devices and/or computing devices (e.g., servers). The machine readable instructions may require one or more of installation, modification, adaptation, updating, combining, supplementing, configuring, decryption, decompression, unpacking, distribution, reassignment, etc. in order to make them directly readable and/or executable by a computing device and/or other machine. For example, the machine readable instructions may be stored in multiple parts, which are individually compressed, encrypted, and stored on separate computing devices, wherein the parts when decrypted, decompressed, and combined form a set of executable instructions that implement a program such as that described herein. In another example, the machine readable instructions may be stored in a state in which they may be read by a computer, but require addition of a library (e.g., a dynamic link library (DLL)), a software development kit (SDK), an application programming interface (API), etc. in order to execute the instructions on a particular computing device or other device. In another example, the machine readable instructions may need to be configured (e.g., settings stored, data input, network addresses recorded, etc.) before the machine readable instructions and/or the corresponding program(s) can be executed in whole or in part. Thus, the disclosed machine readable instructions and/or corresponding program(s) are intended to encompass such machine readable instructions and/or program(s) regardless of the particular format or state of the machine readable instructions and/or program(s) when stored or otherwise at rest or in transit.

As mentioned above, the example processes of FIGS. **12A**, **12B**, and **13-18** may be implemented using executable instructions (e.g., computer and/or machine readable instructions) stored on a non-transitory computer and/or machine readable medium such as a hard disk drive, a flash memory, a read-only memory, a compact disk, a digital versatile disk, a cache, a random-access memory and/or any other storage device or storage disk in which information is stored for any duration (e.g., for extended time periods, permanently, for brief instances, for temporarily buffering, and/or for caching of the information). As used herein, the term non-transitory computer readable medium is expressly defined to include any type of computer readable storage device and/or storage disk and to exclude propagating signals and to exclude transmission media.

“Including” and “comprising” (and all forms and tenses thereof) are used herein to be open ended terms. Thus, whenever a claim employs any form of “include” or “comprise” (e.g., comprises, includes, comprising, including,

having, etc.) as a preamble or within a claim recitation of any kind, it is to be understood that additional elements, terms, etc. may be present without falling outside the scope of the corresponding claim or recitation. As used herein, when the phrase “at least” is used as the transition term in, for example, a preamble of a claim, it is open-ended in the same manner as the term “comprising” and “including” are open ended. The term “and/or” when used, for example, in a form such as A, B, and/or C refers to any combination or subset of A, B, C such as (1) A alone, (2) B alone, (3) C alone, (4) A with B, (5) A with C, (6) B with C, and (7) A with B and with C. As used herein in the context of describing structures, components, items, objects and/or things, the phrase “at least one of A and B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, and (3) at least one A and at least one B. Similarly, as used herein in the context of describing structures, components, items, objects and/or things, the phrase “at least one of A or B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, and (3) at least one A and at least one B. As used herein in the context of describing the performance or execution of processes, instructions, actions, activities and/or steps, the phrase “at least one of A and B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, and (3) at least one A and at least one B. Similarly, as used herein in the context of describing the performance or execution of processes, instructions, actions, activities and/or steps, the phrase “at least one of A or B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, and (3) at least one A and at least one B.

The program of FIGS. **12A** and **12B** begins at block **1202**, the example login controller **512** determines whether an authorized user has already been recognized and logged into the portable computer **100**. If so, control advances to block **1204** where the example login controller **512** determines whether a threshold period of time has elapsed without activity on the portable computer **100**. If so, control advances to block **1206** where the example login controller **512** logs out the user. At block **1208**, the example secondary display controller **518** turns off the secondary display **116**. That is, the portable computer **100** is placed in a low power sleep mode. In some such examples, nearly all functionality of the computer is put to sleep except for the human presence sensor **128**, which may continue to monitor for the presence of a person (e.g., the user approaching the portable computer **100**). Additionally or alternatively, in some examples, the microphone **130** and the example audio input analyzer **508** may continue to monitor for a voice assistant trigger that may cause the portable computer **100** to again wake up into a higher power state. After turning off the secondary display **116** at block **1208**, control advances to block **1210**. Returning to block **1202**, if the example login controller **512** determines that an authorized user has not been recognized and logged in (e.g., since being logged out at block **1206** in a previous iteration of the process), control advances directly to block **1210**.

At block **1210**, the human presence sensor **128** determines whether a person near the portable computer **100** has been detected. If so, control advances to block **1212** to attempt to authenticate or recognize the person using a camera (e.g., either the world facing camera **124** if the portable computer **100** is closed or the user facing camera **122** if the portable computer **100** is open). Further detail regarding the implementation of block **1212** is provided below in connection with FIG. **13**. Thereafter, at block **1214**, the example login

controller **512** determines whether the person was recognized as an authorized user. If so, control advances to block **1222**. If not, control advances to block **1216**. Returning to block **1210**, if the human presence sensor **128** does not detect a person near the portable computer **100**, control advances directly to block **1216**.

At block **1216**, the example system controller **522** determines whether to monitor audio for voice-based user authentication. In some examples, the monitoring of audio is done in parallel with the human presence detection of blocks **1210** and **1212** rather than occur after no person has been recognized as represented in the flowchart of FIG. **12A**. If the example system controller **522** determines to monitor audio for voice-based user authentication, control advances to block **1218** to attempt to authenticate or recognize a person based on their voice. Further detail regarding the implementation of block **1218** is provided below in connection with FIG. **14**. Thereafter, control advances to block **1220** where the example login controller **512** determines whether the person was recognized as an authorized user. If so, control advances to block **1222**. If it is determined that a person was not recognized at block **1220** (and that no person was recognized at block **1212**), then there is no person recognized as an authorized user. In such situations control advances to block **1238** on FIG. **12B**. Likewise, if the example system controller **522** determines at block **1216** not to monitor audio for voice-based user authentication, control advances directly to block **1238**.

At block **1222**, the example login controller **512** automatically logs in the person recognized at block **1214** or block **1218** as an authorized user. Thereafter, at block **1224**, the example secondary display controller **518** renders a personalized message confirming the identification of the person as an authorized user via the secondary display **116**. In some examples, the message may include a greeting that uses the name of the person. In some examples, the greeting may be audible in addition to what is rendered via the secondary display **116**. At block **1226**, the example secondary display controller **518** renders personalized user information via the secondary display **116**. In some examples, the personalized user information may be represented in a personalized home screen (e.g., the personalized secondary user interface **400** of FIG. **4**). In examples, where the user was previously logged in and has already interacted with the secondary display **116**, the personalized information may correspond to a secondary user interface associated with a particular application running on the portable computer **100** (e.g., any of the various personalized secondary user interfaces described in connection with FIGS. **6-11**). In some examples, a user may be previously logged in if control came from block **1204**. That is, returning to block **1204**, if the example login controller **512** determines that a threshold period of time has not elapsed without activity on the portable computer **100** (after an authorized user has already been recognized and logged in), control advances directly to block **1226**.

At block **1228** (top of FIG. **12B**), the example audio input analyzer **508** determines whether to detect a voice command. In some examples, this determination is made based on the audio input analyzer **508** detecting a voice assistant trigger word spoken by a person within audible range of the microphones **130** of the portable computer **100**. In some examples, this trigger word may be the same voice command associated with the initial voice recognition performed at block **1218**. In other examples, this voice command may occur after the user has already been recognized and logged in. If the example audio input analyzer **508** determines to

detect a voice command, control advances to block **1230** where the example audio input analyzer **508** determines whether the detected voice is recognized as corresponding to an authorized user. If so, control advances to block **1232** to implement actions to provide a response to the voice command. Further detail regarding the implementation of block **1232** is provided below in connection with FIG. **15**. Thereafter, control advances to block **1234**. In some examples, block **1230** may be omitted with control advances directly to block **1232** where the voice is automatically assumed to correspond to the authorized user based on the user having already been recognized and logged into the portable computer **100**. Additionally or alternatively, in some examples block **1230** may be omitted with control advancing directly to block **1232** when the voice command does not involve the access or retrieval of personal information associated with the user (e.g., a voice command stating, "Computer, what is the weather today?"). Returning to block **1228**, if the example audio input analyzer **508** determines not to detect a voice command (e.g., no voice assistant trigger word has been detected), control advances directly to block **1234**.

At block **1234**, the example communications interface(s) **504** determine whether a push notification has been received. In some examples, push notifications are received in connection with applications running on the computer. Additionally or alternatively, push notifications may be received from separate devices communicatively coupled to the computer (e.g., a remote server connected via the Internet or a local trusted device connected via Bluetooth or Wi-Fi). For example, a push notification may include a reminder regarding an upcoming appointment and/or a change in the appointment details associated with a calendar application of the user (as discussed in connection with FIG. **9**), an incoming call on a conference calling application (as discussed in connection with FIG. **10**), or any other type of push notification (e.g., a new email message, new posts on social media, etc.). If the example communications interface(s) **504** determine that push notification has been received at block **1234**, control advances to block **1236** to implement actions enabling the user to respond to the push notification. Further detail regarding the implementation of block **1236** is provided below in connection with FIG. **16**. Thereafter, control advances to block **1238**. Returning to block **1234**, if the example communications interface(s) **504** determine that no push notification has been received, control advances directly to block **1238**.

At block **1238**, the example lid controller **520** determines whether the computer lid has been opened. If so, control advances to block **1240** to implement actions enabling interaction between the primary display **114** and the secondary display **116**. Further detail regarding the implementation of block **1240** is provided below in connection with FIG. **17**. Thereafter, control advances to block **1242**, where the example login controller **512** determines whether the authorized user is recognized and logged in. If so, control advances to block **1244**. Returning to block **1238**, if the example lid controller **520** determines that the computer lid has not been opened, control advances directly to block **1244**.

At block **1244**, the example touch-based input analyzer **510** determines whether a touch-based user input on the secondary display **116** has been detected. If so, control advances to block **1246** where the example touch-based input analyzer **510** implements actions corresponding to the touch-based user input. Touch-based user inputs may occur at any point during the process of FIGS. **12A** and **12B**. Thus, the touch-based inputs may be associated with a user pro-

viding a voice command and/or the user responding to feedback provided in response to a voice command. Similarly, touch-based user inputs may be implemented in connection with a user responding to push notifications. Touch-based user inputs on the secondary display 116 may also be used to control applications rendered on the primary display (e.g., when the lid 106 of the portable computer 100 is open). Further, touch-based user inputs on the secondary display 116 may be used at other times whenever the user desires to access and/or interact with information and/or other content directly via the secondary display 116. As a specific example, the touch-based inputs may enable a user to perform the reverse operations to receiving push notifications. That is, rather than answer a conference call, in some examples, a user may be able to initiate a conference call with someone else based on user interactions with the secondary display 116. As another example, a user may be able to use touch-based inputs on the secondary display 116 to locate and identify a particular document or file stored on the portable computer 100 to share with a separate device. In some examples, after selecting the particular document or file, the user may request (via the secondary display 116) the portable computer 100 to identify any nearby devices (e.g., within wireless communication range) to which the document or file may be sent. In some such examples, the user may select (via the secondary display 116) one or more of the identified device and cause the portable computer 100 share the file with such devices. In some such examples, the portable computer 100 may first transmit a request to the devices and wait for an acknowledgement before establishing a connecting and transferring the data. In some examples, any operations capable using touch-based inputs may also be performed using corresponding voice commands. After implementing actions corresponding to the touch-based user input at block 1246, control advances to block 1250. Returning to block 1244, if the example touch-based input analyzer 510 has not detected a touch-based user input, control advances directly to block 1250.

Returning to block 1242, if no authorized user has been recognized and logged in, control advances to block 1248 where the example secondary display controller 518 renders generic information via the secondary display. In some examples, the generic information corresponds to the generic secondary user interface described above in connection with FIG. 3. Thereafter, control advances to block 1250 to determine whether to continue the process. If so, control returns to block 1202. Otherwise, the example process of FIGS. 12A and 12B ends.

FIG. 13 provides further detail regarding the implementation of block 1212 of FIG. 12A to attempt to authenticate or recognize a person using a camera. The example process of FIG. 13 begins at block 1302 where the example camera input analyzer 506 determines whether the relevant camera is turned on. In some examples, which camera is the relevant camera depends on whether the portable computer 100 is opened or closed (as determined by the example lid controller 520). If the portable computer 100 is closed, the relevant camera corresponds to the world facing camera 124. If the portable computer 100 is open, the relevant camera corresponds to the user facing camera 122. In some examples, both cameras 122, 124 may be considered when the portable computer 100 is open. If the example camera input analyzer 506 determines that the relevant camera is not turned on, control advances to block 1304 where the example system controller 522 activates the relevant camera. At block 1306, the example system controller 522 turns on the light indicator 126 to indicate relevant camera is on.

At block 1308, the example secondary display controller 518 renders the camera icon 302 via the secondary display 116. Thereafter, control advances to block 1310. Returning to block 1302, if the example camera input analyzer 506 determines the relevant camera is already turned on, control advances directly to block 1310.

At block 1310, the relevant camera captures an image of the person. At block 1312, the example camera input analyzer 506 analyzes the captured image relative to image data associated with authorized user(s) of the portable computer 100. At block 1314, the example secondary display controller 518 renders a graphic (e.g., the icon and/or animation 612 shown in FIG. 6) via the secondary display indicating the image is being captured and/or analyzed. At block 1316, the example camera input analyzer 506 determines whether to turn off the camera. If so, control advances to block 1318 where the example system controller 522 deactivates the camera. Thereafter, the process of FIG. 13 ends and returns to complete the process of FIGS. 12A and 12B. If the example camera input analyzer 506 determines not to turn off the camera, the example process immediately ends and returns to complete the process of FIGS. 12A and 12B.

FIG. 14 provides further detail regarding the implementation of block 1218 of FIG. 12A to attempt to authenticate or recognize a person using their voice. The example process of FIG. 14 begins at block 1402 where the example audio input analyzer 508 determines whether the microphone 130 is turned on. If not, control advances to block 1404 where the example system controller 522 activates the microphone 130. At block 1406, the example secondary display controller 518 renders the microphone icon 304 via the secondary display 116. Thereafter, control advances to block 1408. Returning to block 1402, if the example audio input analyzer 508 determines the microphone 130 is already turned on, control advances directly to block 1408.

At block 1408, the example audio input analyzer 508 determines whether a voice assistant trigger word has been detected. If so, control advances to block 1410 where the example secondary display controller 518 renders a graphic (e.g., the icon and/or animation 712 of FIG. 7) via the secondary display 116 indicating the system is monitoring for a voice command. At block 1412, the example audio input analyzer 508 determines whether a voice command has been detected. If so, control advances to block 1414 where the example secondary display controller 518 renders a graphic on the secondary display acknowledging the voice command. In some examples, the acknowledgement graphic is a text-based reproduction of the voice command as described in the connection with the illustrated examples of FIGS. 7 and 8. At block 1416, the example audio input analyzer 508 analyzes the voice command relative to voice data associated with authorized user(s) of the portable computer 100. Thereafter, control advances to block 1418. If no voice assistant word was detected (block 1408) or no voice command was detected (block 1412), control advances directly to block 1418.

At block 1418, the example audio input analyzer 508 determines whether to turn off the microphone 130. If so, control advances to block 1420 where the example system controller 522 deactivates the microphone 130. Thereafter, the process of FIG. 14 ends and returns to continue the process of FIGS. 12A and 12B. If the example audio input analyzer 508 determines not to turn off the microphone 130, the example process immediately ends and returns to continue the process of FIGS. 12A and 12B.

FIG. 15 provides further detail regarding the implementation of block 1232 of FIG. 12B to implement actions to

provide a response to the voice command. As described above in connection with FIG. 12B, this process begins after a voice command has already been detected (block 1228 of FIG. 12B). Accordingly, the example process of FIG. 15 begins at block 1502 where the example secondary display controller 518 renders a graphic via the secondary display acknowledging the voice command. In some examples, the acknowledgement graphic is a text-based reproduction of the voice command as described in the connection with the illustrated examples of FIGS. 7 and 8. At block 1504, the example system controller 522 retrieves information needed to respond to the voice command. In some examples, the information may be retrieved from the example database(s) 524. In some examples, the information is retrieved from an application running on the portable computer 100. In some examples, the information may be retrieved from a remote server via the communications interface(s) 504.

At block 1506, the example secondary display controller 518 determines whether to render a response to voice command via the secondary display 116. If so, control advances to block 1508 where the example secondary display controller 518 renders the response via the secondary display 116. In some examples, the response may be rendered as text on the secondary display 116 (e.g., as described in the illustrated example of FIG. 7). In some examples, the response may include rendering a secondary user interface associated with an application running on the computer (e.g., the calendar application as described in the illustrated example of FIG. 8). Thereafter, control advances to block 1510. Returning to block 1506, if the example secondary display controller 518 determines not to render a response to voice command via the secondary display 116, control advances directly to block 1510.

At block 1510, the example system controller 522 determines whether to provide a response to the voice command via the speakers 132. If so, control advances to block 1512 where the example system controller 522 generates a response via the speakers. Thereafter, control advances to block 1514. Returning to block 1510, if the example system controller 522 determines not to provide a response to the voice command via the speakers 132, control advances directly to block 1514.

At block 1514, the example system controller 522 determines whether to render content via the primary display 114 as part of the response. If so, control advances to block 1516 where the example primary display controller 516 turns on the primary display 114 if it is not already on. The primary display 114 may not be on if the lid 106 of the portable computer 100 is closed at the time the voice command is detected. At block 1518, the example primary display controller 516 renders a primary user interface associated with an application responsive to the voice command. As a specific example, if the user provides a voice command to initiate a 360 degree video conference call, the example primary display controller 516 may render a primary user interface associated with the conference calling application via the primary display 114, where the user interface includes a 360 video stream of the surrounding environment of the portable computer 100 as captured by the world and user facing cameras 122, 124. At block 1520, the example lid controller 520 automatically opens the computer lid if not already open. In some examples, the hinge 112 may not be constructed to automatically open the lid 106 of the portable computer 100. In such examples, block 1520 may be omitted. In some such examples, the secondary display 116 may provide a prompt directing the user to open the lid 106 to be able to see the content rendered via the primary display 114.

Thereafter, control advances to block 1522. Returning to block 1514, if the example system controller 522 determines not to render content via the primary display 114 as part of the response, control advances directly to block 1522.

At block 1522, the example secondary display controller 518 determines whether to return the secondary display 116 to a previous screen. In some examples, the example secondary display controller 518 may determine to do so based on a threshold period of time elapsing without the user taking any action following the rendering of the response to the voice command. In other examples, the determination may be made based on the user providing input that the response to the voice command is no longer needed. If the example secondary display controller 518 determines to return the secondary display 116 to a previous screen, control advances to block 1524 where the example secondary display controller 518 renders the primary user interface previously rendered on the secondary display prior to the voice command. Thereafter, the example process ends and returns to continue the process of FIGS. 12A and 12B. If the example secondary display controller 518 determines not to return the secondary display 116 to a previous screen, the example process of FIG. 15 immediately ends and returns to continue the process of FIGS. 12A and 12B.

FIG. 16 provides further detail regarding the implementation of block 1236 of FIG. 12B to implement actions enabling the user to respond to a push notification. As described above in connection with FIG. 12B, this process begins after having received a push notification (as determined at block 1234 of FIG. 12B). Accordingly, the example process of FIG. 16 begins at block 1602 where the example push notification controller 514 determines whether to generate an audio and/or haptic signal to indicate the receipt of the push notification. If so, control advances to block 1604 where the example system controller 522 generates the audio and/or haptic signal. Thereafter, control advances to block 1606. If the example push notification controller 514 determines not to generate an audio and/or haptic signal, control advances directly to block 1606.

At block 1606, the example secondary display controller 518 renders a graphic indicative of the push notification with an option for the user to dismiss the notification or to take further action. The nature of the further action and/or the associated graphic may depend on the nature of the push notification. In some examples, the further action may involve reviewing more detailed information about the notification. In some examples, the further action may involve the user responding to the notification either by acknowledging and/or accepting the notification or providing a more detailed response. In some examples, the option to dismiss the notification may be presented as an explicit option (e.g., as a button or icon) the user is to select. In other examples, the user may dismiss the notification by not taking any further action regarding the notification within a threshold period of time. As a specific example, a push notification may correspond to an incoming conference call. The options for further action to be taken by the user may include accepting or answering, dismissing the call (e.g., by selecting the hang up icon or by not answering within a threshold period of time), or sending a quick reply (e.g., a text message stating the user cannot take the call at the moment).

At block 1608, the example system controller 522 activates the microphone 130 if not already turned on to detect user voice commands. In this manner, the user may specify the further action the user intends to take using a voice command without having to physically touch the secondary display 116. At block 1610, the example push notification

controller **514** determines whether the user selects an option to take further action or to dismiss the notification. If the example push notification controller **514** determines that further action was taken, control advances to block **1612** where the example push notification controller **514** determines whether the user selected a quick response or a detailed response. In the context of an incoming conference call, a quick response may include a text message to the caller whereas a more detailed response includes answering the call. In other contexts, for example, a push notification indicating a new email message has been received, a quick reply may be to acknowledge receipt of the email whereas a more detailed response includes drafting a reply email. If the user selected a quick response, control advances to block **1614**, where the example secondary display controller **518** renders options for the quick response via the secondary display **116**. That is, in some examples, after the user has indicated an intent to provide a quick response there may be multiple options for the quick response. As a specific example, if the user cannot answer an incoming conference call, the user may select an option to send a quick text message. Upon selecting this option, multiple preset text messages may be provided to the user to select to send to the caller. In some examples, there may not be multiple options for the quick response such that block **1614** may be omitted. For instance, in some examples, the push notification may be a request from a separate device to share a document or other file with the portable computer **100**. In other examples, where the separate device is a trusted device, the push notification may indicate the separate device is transmitting the file or document to the portable computer **100**. In such examples, the only option for response by the user may be either to dismiss or deny the request/transmission or to select a quick reply corresponding to accepting the request.

At block **1616**, the example system controller **522** implements the quick response based on the user input. How the system controller **522** implements the quick response may depend on the nature of the notification and the quick response selected by the user. For example, in the context of a quick text-message reply to an incoming conference call, the system controller **522** may transmit the selected text message (e.g., via the communications interface(s) **504**) to the caller. In examples where the push notification indicates a trusted device is transmitting a document or other file, the quick response involves the portable computer **100** storing the shared document. In some examples, where the separate device has been previously established as a trusted device, the portable computer **100** may automatically receive and store the shared document and the quick response is merely to acknowledge receipt of the document. Where the push notification corresponds to a request to share the document or file, the system controller **522** may establish a connection with the separate device to then receive the document or file following the user's quick response to accept the request. After implementing the quick response at block **1616**, control advances to block **1628**. Returning to block **1612**, if the example push notification controller **514** determines the user selected a detailed response, control advances to block **1618**. In some examples, a quick response may not be an option such that control automatically advances from block **1610** to block **1618** when the user takes further action.

At block **1618**, the example system controller **522** determines whether the further action involves rendering content via the primary display **114** as part of the response. If so, control advances to block **1620** where the example primary display controller **516** turns on the primary display **114** if it is not already on. The primary display **114** may not be on if

the lid **106** of the portable computer **100** is closed at the time the push notification is received. At block **1622**, the example primary display controller **516** renders a primary user interface associated with an application that enables the further action of the user. As a specific example, if the user indicates the intent to response to an incoming call with a 360 degree video, the example primary display controller **516** may render a primary user interface associated with the conference calling application via the primary display **114**, where the user interface includes a 360 video stream of the surrounding environment of the portable computer **100** as captured by the world and user facing cameras **122**, **124**. As another example, if the push notification corresponds to a new email and the user indicates the intent to draft a reply email, the example primary display controller **516** may render a primary user interface associated with an email application via the primary display **114**. At block **1624**, the example lid controller **520** automatically opens the computer lid if not already open. In some examples, the hinge **112** may not be constructed to automatically open the lid **106** of the portable computer **100**. In such examples, block **1624** may be omitted. In some such examples, the secondary display **116** may provide a prompt directing the user to open the lid **106** to be able to see the content rendered via the primary display **114**. Thereafter, control advances to block **1626**. Returning to block **1618**, if the example system controller **522** determines the further action does not to rendering content via the primary display **114**, control advances directly to block **1626**.

At block **1626**, the example secondary display controller **518** renders a secondary user interface via the secondary display to enable the user to take the further action. In some examples, the content rendered via the secondary display **116** may be done in conjunction with what is rendered via the primary display **114**. For instance, in some examples, while a video stream for a video conference call may be rendered via the primary display **114**, controls for the call may be rendered via the secondary display **116**. In some examples, when the primary display **114** is used by the user in taking further action to respond to the push notification, no content relevant to the push notification is rendered via the secondary display **116** such that block **1626** may be omitted. Thereafter, control advances to block **1628**. Returning to block **1610**, if the example push notification controller **514** determines that the user selects to dismiss the notification, control advances directly to block **1628**.

At block **1622**, the example secondary display controller **518** determines whether to return the secondary display **116** to a previous screen. If so, control advances to block **1628** where the example secondary display controller **518** renders the secondary user interface previously rendered on the secondary display prior to the voice command. Thereafter, the example process ends and returns to continue the process of FIGS. **12A** and **12B**. If the example secondary display controller **518** determines not to return the secondary display **116** to a previous screen, the example process of FIG. **16** immediately ends and returns to continue the process of FIGS. **12A** and **12B**.

FIG. **17** provides further detail regarding the implementation of block **1240** of FIG. **12B** to implement actions enabling interaction between the primary display **114** and the secondary display **116**. As described above in connection with FIG. **12B**, this process begins after having determined that this computer lid **106** is opened. Further, as described above, block **1240** may be implemented in the context of an authorized user being logged into the portable computer **100** (e.g., when control comes from block **1234** or block **1236**)

or in the context of no authorized user being logged into the portable computer 100 (e.g., when control comes from block 1216 or block 1220). Accordingly, the example process of FIG. 17 begins at block 1702 where the example login controller 512 determines whether an authorized user has been recognized and logged into the portable computer 100. If so, control advances to block 1710. Otherwise, control advances to block 1704 where the example login controller 512 (in conjunction with the primary display controller 516) request the user to log in via the primary display 114. At block 1706, the example login controller 512 determines whether the login credentials are received. If not, the example process of FIG. 17 ends and returns to continue the process of FIGS. 12A and 12B. If so, control advances to block 1708 where the example login controller 512 logs in the authorized user.

At block 1710, the example primary display controller 516 renders personalized content via the primary display 114 associated with the authorized user. At block 1712, the example lid controller 520 determines whether the computer lid 106 was opened based on a response to an active application associated with content rendered via the secondary display 116. As an example, a user may have indicated an intent via the secondary display 116 to initiate a 360 degree video conference call (that involves use of the primary display 114) before opening the lid 106 of the portable computer 100 as discussed in the illustrated example of FIG. 10. As another example, the user may have indicated an intent via the secondary display 116 to draft a reply (on the primary display 114) to a new email message before opening the lid 106. If the example lid controller 520 determines that the computer lid 106 was opened based on a response to an active application associated with content rendered via the secondary display 116, control advances to block 1714 where the example primary display controller 516 renders a primary user interface for the active application on the primary display 114. Thereafter, control advances to block 1716. Returning to block 1712, if the example lid controller 520 determines that the computer lid 106 was not opened based on a response to an active application associated with content rendered via the secondary display 116, control advances directly to block 1716.

At block 1716, the example system controller 522 determines whether there is a secondary user interface associated with the active application. If so, control advances to block 1718 where the example secondary display controller 518 renders the secondary user interface associated with the active application via the secondary display 116. Thereafter, control advances to block 1724. If the example system controller 522 determines there is not a secondary user interface associated with the active application (or there is currently no active application), control advances to block 1720 where the example secondary display controller 518 determines whether to turn off the secondary display 116. If so, control advances to block 1722 where the example secondary display controller 518 turns off the secondary display 116. Thereafter, control advances to block 1724. If the example secondary display controller 518 determines not to turn off the secondary display 116 at block 1720, control advances directly to block 1724.

At block 1724, the example system controller 522 determines whether the user has activated a new application. In some examples, the new application may be launched or activated by the user interacting with either the primary display 114 or the secondary display 116. If a new application was activated, control advances to block 1726 where the example primary display controller 516 renders a primary

user interface for the active application on the primary display 114. If, at block 1724, the example system controller 522 determines the user has not activated a new application control advances to block 1728 where the example lid controller 520 determines whether the computer lid has been closed. If the lid has not closed, the example process of FIG. 17 ends and returns to continue the process of FIGS. 12A and 12B. If the lid has closed, control advances to block 1730.

At block 1730, the example system controller 522 determines whether the active application associated with the current rendering on the secondary display 116 includes closed-lid functionality. Example applications associated with closed-lid functionality include the conference calling application described above in connection with FIG. 10 and the music player application described above in connection with FIG. 11. If the active application is associated with closed-lid functionality, control advances to block 1732 where the example system controller 522 continues implementing the active application with the lid 106 closed. At block 1734, the example secondary display controller 518 continues to render the secondary user interface associated with the active application via the secondary display 116. Thereafter, the example process of FIG. 17 ends and returns to continue the process of FIGS. 12A and 12B. Returning to block 1730, if the example system controller 522 determines that the active application associated with the current rendering on the secondary display 116 does not include closed-lid functionality, control advances to block 1736 where the example primary display controller 516 renders a personalized home screen via the secondary display 116. Thereafter, the example process of FIG. 17 ends and returns to continue the process of FIGS. 12A and 12B.

As mentioned above, in some examples, the portable computer 100 includes a hinge 112 that enables the lid 106 to be automatically opened and/or closed without a user manually moving the lid 106. In some examples, the computer lid 106 may automatically open in response to user interactions with the secondary display 116 (either through a voice command or a physical touch). There may be other circumstances in which a user may indicate an intent to access content via the primary display 114 while the portable computer 100 is closed to trigger the portable computer 100 to automatically open. In one example, the user may tap on the portable computer 100 while closed with a unique tapping sequence corresponding to an accelerometer-based password that causes the user to be authenticated and logged in to the portable computer 100 and further caused the lid 106 to automatically open. Additionally or alternatively, the lid 106 may automatically open in response to the camera input analyzer 506 recognizing the user.

In other examples, triggering the portable computer 100 to automatically open from a closed position may and render relevant content via the primary display 114 may be based on interactions associated with a separate device. For example, the user may be viewing content via a portable device (e.g., a smartphone) and then tap the closed portable computer 100 with the portable device to cause the portable computer 100 to open and begin rendering the content rendered via the portable device. As another example, a user may virtually (e.g., through a physical gesture of the user's hand) pick up an object (e.g., a document, an image, etc.) rendered on a portable device and virtually drop it on to a closed portable computer 100 to cause the portable computer 100 to open up and provide the moved object via the primary display 114. In such examples, the physical gesture of the user's hand may be detected by analyzing images captured

by the world facing camera **124** on the portable computer **100**. In some examples, the separate portable device, which may already be communicatively coupled to the portable computer **100** (e.g., via a Bluetooth pairing) may transmit a signal to the portable computer **100** to cause the world facing camera **124** to turn on to detect the gesture based on the portable device first detecting the user's gesture to virtually pick up the object. In some examples, the gesture, tapping of devices, and/or other actions by the user may trigger the portable device and the portable computer **100** to communicatively connect so that the content from the portable device may be shared with the portable computer **100** for rendering via the primary display **114** once the lid **106** is opened.

In some examples, the lid **106** may begin to open when the user did not intend to open the portable computer **100**. In some examples, the user may provide an additional command (via voice, touch, or gesture) to reverse the operation. In some such examples, the lid **106** may automatically reverse its direction and return to the closed position.

FIG. **18** illustrates an example process flow to automatically open the lid **106** of the portable computer **100** based on an indication of intent of an authenticated user to access content via the primary display **114**. The example process begins with the computer lid **106** closed. At block **1802**, one or more of the example camera input analyzer **506**, the example audio input analyzer **508**, the touch-based input analyzer detects an indication of user intent to access content via the primary display **114**. At block **1804**, the example system controller **522** determines whether to obtain verification of the user intent. In some examples, verification may be obtained to avoid false positives in detecting an intent to open the lid based on a single sensor or single associated user input. If the example system controller **522** determines to obtain verification, control advances to block **1806** where the example system controller **522** determines whether verification was received? If so, control advances to block **1808** where the example login controller **512** determines whether the user is an authorized user. If so, control advances to block **1810**, where the example lid controller **520** automatically opens the computer lid **106**. At block **1812**, the example primary display controller **516** renders personalized content (e.g., a home screen) on the primary display **114**.

At block **1814**, the example system controller **522** determines whether particular content to be accessed by the user is identifiable. Particular content may be identifiable if the content is being shared from a separate electronic device (e.g., a smartphone in communication with the portable computer **100**) or identified based on user interactions with the secondary display **116**. Particular content may not be identified where the user had merely indicated an intent to open the portable computer **100** without reference to how the user intends to use the portable computer **100** thereafter. If particular content to be accessed by the user is identifiable, control advances to block **1816** where the example system controller **522** retrieves the particular content. The way in which the content is retrieved may depend on the nature of the content and the way in which the user indicated an intent to access the content. For instance, in some examples, the content may be stored on the portable computer **100** and is identified by the user based on a touch-based selection of the content via the secondary display **116**. In such examples, the example system controller **522** may retrieve the content from the memory of the portable computer **100**. In another example, the particular content may be transferred (e.g., retrieved) from a separate device (e.g., the user's smart-

phone) that is local to and communicatively coupled to the portable computer **100**. In other examples, the desired content may be requested based on a voice command that involve the portable computer **100** launching a web browser that retrieves the particular content by accessing a remote server. At block **1818**, the example system controller **522** initiates an application to enable the rendering of the particular content via the primary display **114**.

Thereafter, control advances to block **1820**. If no indication of user intent is detected at block **1802**, no verification is received at block **1806**, the user is not authorized at block **1808**, or there is no particular content that is identifiable at block **1814**, control advances directly to block **1820**. At block **1820**, the example system controller **522** determines whether to continue the process. If so, control returns to block **1802**. Otherwise, the example process of FIG. **18** ends.

FIG. **19** is a block diagram of an example processor platform **1900** structured to execute the instructions of FIGS. **12A**, **12B**, and **13-18** to implement the example portable computer **100** of FIGS. **1**, **2**, and/or **5**. The processor platform **1900** of the illustrated example includes a first processor **1910** and a second processor **1912**. The processors **1910**, **1912** of the illustrated example are hardware. For example, the processors **1910**, **1912** can be implemented by one or more integrated circuits, logic circuits, microprocessors, GPUs, DSPs, or controllers from any desired family or manufacturer. The hardware processors may be a semiconductor based (e.g., silicon based) device. The separate processors enable the functions of the portable computer **100** to be performed when the lid **106** is closed with less power (e.g., using the second processor **1912**) than when the portable computer **100** is opened and operating in a full power mode (e.g., using the first processor **1910**). In some such examples, the processor platform **1900** includes a first power supply **1906** to provide power to the first processor **1910** and other components when the system is operating in a full power mode and a second power supply **1908** to provide power to the second processor **1912** and other components when the system is operating in a low power mode. In the illustrated example of FIG. **19**, the first processor **1910** implements the example camera input analyzer **506**, the example audio input analyzer **508**, the example touch-based input analyzer **510**, the example login controller **512**, the example push notification controller **514**, the example primary display controller **516**, the example lid controller **520**, and the example system controller **522**. Further, in the illustrated example, the second processor **1912** implements the example secondary display controller **518**, and the example system controller **522**. The example system controller **522** is described as being implemented by both processors **1910** because the functionality of the system controller **522** is shared across both processors. In some examples, different functions of the system controller **522** may be implemented exclusive on one of the processors **1910**, **1912**. In other examples, functionality of the system controller **522** may be redundantly implemented on both processors **1910**, **1912**. Although not represented in the illustrated example, one or more of the example camera input analyzer **506**, the example audio input analyzer **508**, the example touch-based input analyzer **510**, the example login controller **512**, the example push notification controller **514**, the example primary display controller **516**, and/or the example lid controller **520** may be implemented in whole or in part by the second processor **1912** instead of or in addition to the first processor **1910**. In some examples, the second processor **1912** may be omitted and the first processor **1910**

may implement each of the example camera input analyzer **506**, the example audio input analyzer **508**, the example touch-based input analyzer **510**, the example login controller **512**, the example push notification controller **514**, the example primary display controller **516**, the example secondary display controller **518**, the example lid controller **520**, and the example system controller **522**.

The processor **1910** of the illustrated example includes a local memory **1911** (e.g., a cache) and the processor **1912** of the illustrated example includes a local memory **1913** (e.g., a cache). The processors **1910**, **1912** of the illustrated example are in communication with a main memory including a volatile memory **1914** and a non-volatile memory **1916** via a bus **1918**. The volatile memory **1914** may be implemented by Synchronous Dynamic Random Access Memory (SDRAM), Dynamic Random Access Memory (DRAM), RAMBUS® Dynamic Random Access Memory (RDRAM®) and/or any other type of random access memory device. The non-volatile memory **1916** may be implemented by flash memory and/or any other desired type of memory device. Access to the main memory **1914**, **1916** is controlled by a memory controller.

The processor platform **1900** of the illustrated example also includes an interface circuit **1920**. The interface circuit **1920** may be implemented by any type of interface standard, such as an Ethernet interface, a universal serial bus (USB), a Bluetooth® interface, a near field communication (NFC) interface, and/or a PCI express interface. In this example, the interface circuit **1920** implements the example communication interface(s) **504**.

In the illustrated example, one or more input devices **1922** are connected to the interface circuit **1920**. The input device(s) **1922** permit(s) a user to enter data and/or commands into the processor **1910**. The input device(s) can be implemented by, for example, an audio sensor, a microphone, a camera (still or video), a keyboard, a button, a mouse, a touchscreen, a track-pad, a trackball, isopoint and/or a voice recognition system.

One or more output devices **1924** are also connected to the interface circuit **1920** of the illustrated example. The output devices **1924** can be implemented, for example, by display devices (e.g., a light emitting diode (LED), an organic light emitting diode (OLED), a liquid crystal display (LCD), a cathode ray tube display (CRT), an in-place switching (IPS) display, a touchscreen, etc.), a tactile output device, a printer and/or speaker. The interface circuit **1920** of the illustrated example, thus, typically includes a graphics driver card, a graphics driver chip and/or a graphics driver processor.

The interface circuit **1920** of the illustrated example also includes a communication device such as a transmitter, a receiver, a transceiver, a modem, a residential gateway, a wireless access point, and/or a network interface to facilitate exchange of data with external machines (e.g., computing devices of any kind) via a network **1926**. The communication can be via, for example, an Ethernet connection, a digital subscriber line (DSL) connection, a telephone line connection, a coaxial cable system, a satellite system, a line-of-site wireless system, a cellular telephone system, etc.

The processor platform **1900** of the illustrated example also includes one or more mass storage devices **1928** for storing software and/or data. Examples of such mass storage devices **1928** include floppy disk drives, hard drive disks, compact disk drives, Blu-ray disk drives, redundant array of independent disks (RAID) systems, and digital versatile disk (DVD) drives. In this example, the mass storage devices **1928** includes the example database(s) **524**.

The machine executable instructions **1932** of FIGS. **12A**, **12B**, and **13-18** may be stored in the mass storage device **1928**, in the volatile memory **1914**, in the non-volatile memory **1916**, and/or on a removable non-transitory computer readable storage medium such as a CD or DVD.

From the foregoing, it will be appreciated that example methods, apparatus and articles of manufacture have been disclosed that enable a user to interact with and/or operate a portable computer while the lid is closed and the computer is in a lower power state than when the computer is opened and operating in a full power mode. This is achieved in part by a low power secondary display that is visible to the user when the computer lid is closed. Examples disclosed herein enable a user to be recognized and/or authenticated to be logged into the computer before the user has opened the lid to provide a more seamless user experience with the computer. Further, in some examples, the computer may automatically open from a closed position without the user having to manually lift the lid to further assist a user in being able to quickly open and access content via a primary display. Disclosed methods, apparatus and articles of manufacture are accordingly directed to one or more improvement(s) in the functioning of a computer.

Example methods, apparatus, systems, and articles of manufacture to operate closed-lid portable computers are disclosed herein. Further examples and combinations thereof include the following:

Example 1 includes an apparatus, comprising a camera input analyzer to analyze image data captured by a world facing camera on a portable computer when a lid of the portable computer is in a closed position, the world facing camera on a first side of the lid, the portable computer including a primary display on a second side of the lid opposite the first side, and a secondary display controller to render content via a secondary display of the portable computer in response to the analysis of the image data, the secondary display controller to render the content on the secondary display while the lid of the portable computer is in the closed position and the primary display is turned off.

Example 2 includes the apparatus of example 1, wherein the secondary display is disposed in a base of the portable computer, the lid rotatable relative to the base about a hinge connecting the lid to the base.

Example 3 includes the apparatus of example 2, wherein the hinge is to automatically open the lid in response to the analysis of the image data authenticating a user.

Example 4 includes the apparatus of any one of examples 1-3, wherein the camera input analyzer is to perform facial recognition analysis on the image data to identify a person captured by the world facing camera, and further including a login controller to login the person in response to the camera input analyzer recognizing the person as an authorized user of the portable computer, the login controller to login the person before the lid is moved from the closed position.

Example 5 includes the apparatus of example 4, wherein the content rendered via the secondary display includes personalized information corresponding to the authorized user.

Example 6 includes the apparatus of example 4, wherein the content rendered via the secondary display includes generic information when the camera input analyzer is unable to recognize the person.

Example 7 includes the apparatus of any one of examples 1-6, further including a human presence sensor to detect a

presence of a person nearby the portable computer, the human presence sensor to trigger activation of the world facing camera.

Example 8 includes the apparatus of any one of examples 1-7, wherein the content is first content, and further including an audio input analyzer to analyze a voice command spoken when the lid is in the closed position, a microphone on the portable computer to capture the voice command when the lid is in the closed position and the voice command is spoken by a person within audible range of the microphone, the secondary display controller to render second content via the secondary display in response to the analysis of the voice command.

Example 9 includes the apparatus of example 8, wherein the audio input analyzer is to perform voice recognition analysis of the voice command without communicating with a remote server.

Example 10 includes the apparatus of example 9, wherein the second content rendered via the secondary display includes personalized information corresponding to the person when the audio input analyzer recognizes the voice command as corresponding to a voice of an authorized user of the portable computer.

Example 11 includes the apparatus of any one of examples 8-10, further including a system controller to determine whether third content is to be rendered via the primary display as part of a response to the voice command, and a primary display controller to activate the primary display while the lid is still closed and render the third content via the primary display.

Example 12 includes the apparatus of example 11, further including a lid controller to automatically move the lid to an open position in response to the voice command.

Example 13 includes the apparatus of any one of examples 1-12, wherein the world facing camera has a field of view of at least 180 degrees.

Example 14 includes the apparatus of example 13, wherein the image data is first image data, the camera input analyzer to combine the first image data with second image data to form a 360 degree image of an environment surrounding the portable computer, the second image data captured by a user facing camera on the portable computer, the user facing camera on the second side of the lid, the user facing camera having a field of view of at least 180 degrees.

Example 15 includes the apparatus of any one of examples 1-14, further including a communications interface to receive a push notification from a device separate from the portable computer while the lid is in the closed position, the secondary display to render a graphic while the lid is in the closed position, the graphic including an option for a user to respond to the push notification.

Example 16 includes the apparatus of example 15, wherein the push notification corresponds to the device sharing data with the portable computer.

Example 17 includes the apparatus of any one of examples 1-16, further including a touch-based input analyzer to analyze user interactions with the secondary display detected by a touch sensor associated with the secondary display.

Example 18 includes the apparatus of example 17, wherein the touch sensor is associated with a touchpad disposed on a base of the portable computer, the secondary display corresponding to an extension of the touchpad, the secondary display to extend along a front edge of the base to be visible when the lid is in the closed position.

Example 19 includes the apparatus of any one of examples 1-18, further including a primary display control-

ler to render a primary user interface via the primary display when the lid is open and the primary display is powered, the primary user interface associated with an application running on the portable computer, the secondary display to render a secondary user interface associated with the application via the secondary display.

Example 20 includes the apparatus of example 19, wherein the secondary user interface includes controls to enable a user to operate the application, the primary display controller to update the primary user interface based on user interactions with the controls in the secondary user interface.

Example 21 includes the apparatus of example 20, wherein the secondary display controller is to continue to render the secondary user interface via the secondary display after the lid is returned to the closed position and the primary display is turned off, the controls in the secondary user interface to enable the user to continue to operate the application when the lid is in the closed position.

Example 22 includes the apparatus of any one of examples 19-21, wherein the primary display controller is implemented with a first processor and the secondary display controller is implemented with a second processor.

Example 23 includes the apparatus of example 22, wherein the second processor consumes less power than the first processor.

Example 24 includes a non-transitory computer readable medium comprising instructions that, when executed, cause a portable computer to at least analyze image data captured by a world facing camera on the portable computer when a lid of the portable computer is in a closed position, the world facing camera on a first side of the lid, the portable computer including a primary display on a second side of the lid opposite the first side, and render content via a secondary display of the portable computer in response to the analysis of the image data, the portable computer to render the content on the secondary display while the lid of the portable computer is in the closed position and the primary display is turned off.

Example 25 includes the non-transitory computer readable medium of example 24, wherein the instructions further cause the portable computer to perform facial recognition analysis on the image data to identify a person captured by the world facing camera, and login the person in response to recognition of the person as an authorized user of the portable computer before the lid is moved from the closed position.

Example 26 includes the non-transitory computer readable medium of example 25, wherein the content rendered via the secondary display includes personalized information corresponding to the authorized user.

Example 27 includes the non-transitory computer readable medium of example 25, wherein the content rendered via the secondary display includes generic information when the person is not recognized.

Example 28 includes the non-transitory computer readable medium of any one of examples 24-27, wherein the instructions further cause the portable computer to detect a presence of a person nearby the portable computer, and trigger activation of the world facing camera.

Example 29 includes the non-transitory computer readable medium of any one of examples 24-28, wherein the content is first content, the instructions to further cause the portable computer to analyze a voice command when the lid is in the closed position, a microphone on the portable computer to capture the voice command when the lid is in the closed position and the voice command is spoken by a person within audible range of the microphone on the

portable computer, and render second content via the secondary display in response to the analysis of the voice command.

Example 30 includes the non-transitory computer readable medium of example 29, wherein the instructions further cause the portable computer to perform voice recognition analysis of the voice command without communicating with a remote server.

Example 31 includes the non-transitory computer readable medium of example 30, wherein the second content rendered via the secondary display includes personalized information corresponding to the person when the voice command is recognized as corresponding to a voice of an authorized user of the portable computer.

Example 32 includes the non-transitory computer readable medium of any one of examples 29-31, wherein the instructions further cause the portable computer to determine whether third content is to be rendered via the primary display as part of a response to the voice command, activate the primary display while the lid is still closed, and render the third content via the primary display.

Example 33 includes the non-transitory computer readable medium of example 32, wherein the instructions further cause the portable computer to automatically move the lid to an open position in response to the voice command.

Example 34 includes the non-transitory computer readable medium of any one of examples 24-33, wherein the image data is first image data, the instructions to further cause the portable computer to combine the first image data with second image data to form a 360 degree image of an environment surrounding the portable computer, the second image data captured by a user facing camera on the portable computer, the user facing camera on the second side of the lid, each of the world facing camera and the user facing camera having a field of view of at least 180 degrees respectively.

Example 35 includes the non-transitory computer readable medium of any one of examples 24-34, wherein the instructions further cause the portable computer to render a graphic while the lid is in the closed position in response to receipt of a push notification from a device separate from the portable computer, the graphic including an option for a user to respond to the push notification.

Example 36 includes the non-transitory computer readable medium of example 35, wherein the push notification corresponds to the device sharing data with the portable computer.

Example 37 includes the non-transitory computer readable medium of any one of examples 24-36, wherein the instructions further cause the portable computer to analyze user interactions with the secondary display detected by a touch sensor associated with the secondary display.

Example 38 includes the non-transitory computer readable medium of any one of examples 24-37, wherein the instructions further cause the portable computer to render a primary user interface via the primary display when the lid is open and the primary display is powered, the primary user interface associated with an application running on the portable computer, and render a secondary user interface associated with the application via the secondary display.

Example 39 includes the non-transitory computer readable medium of example 38, wherein the secondary user interface includes controls to enable a user to operate the application, the instructions to further cause the portable computer to update the primary user interface based on user interactions with the controls in the secondary user interface.

Example 40 includes the non-transitory computer readable medium of example 39, wherein the instructions further cause the portable computer to continue to render the secondary user interface via the secondary display after the lid is returned to the closed position and the primary display is turned off, the controls in the secondary user interface to enable the user to continue to operate the application when the lid is in the closed position.

Example 41 includes a method comprising analyzing, by executed an instruction with at least one processor, image data captured by a world facing camera on a portable computer when a lid of the portable computer is in a closed position, the world facing camera on a first side of the lid, the portable computer including a primary display on a second side of the lid opposite the first side, and rendering, by executed an instruction with the at least one processor, content via a secondary display of the portable computer in response to the analysis of the image data, the portable computer to render the content on the secondary display while the lid of the portable computer is in the closed position and the primary display is turned off.

Example 42 includes the method of example 41, further including performing facial recognition analysis on the image data to identify a person captured by the world facing camera, and logging in the person in response to recognition of the person as an authorized user of the portable computer before the lid is moved from the closed position.

Example 43 includes the method of example 42, further including rendering the content via the secondary display to include personalized information corresponding to the authorized user.

Example 44 includes the method of example 42, further including rendering the content via the secondary display to include generic information when the person is not recognized.

Example 45 includes the method of any one of examples 41-44, further including detecting a presence of a person nearby the portable computer, and triggering activation of the world facing camera.

Example 46 includes the method of any one of examples 41-45, wherein the content is first content, the method further including analyzing a voice command when the lid is in the closed position, a microphone on the portable computer to capture the voice command when the lid is in the closed position and the voice command spoken by a person within audible range of the microphone on the portable computer, and rendering second content via the secondary display in response to the analysis of the voice command.

Example 47 includes the method of example 46, further including performing voice recognition analysis of the voice command without communicating with a remote server, the second content rendered via the secondary display includes personalized information corresponding to the person when the voice command is recognized as corresponding to a voice of an authorized user of the portable computer.

Example 48 includes the method of any one of examples 46 or 47, further including determining whether third content is to be rendered via the primary display as part of a response to the voice command, activating the primary display while the lid is still closed, and rendering the third content via the primary display.

Example 49 includes the method of example 48, further including automatically moving the lid to an open position in response to the voice command.

Example 50 includes the method of any one of examples 41-49, wherein the image data is first image data, the method

further including combining the first image data with second image data to form a 360 degree image of an environment surrounding the portable computer, the second image data captured by a user facing camera on the portable computer, the user facing camera on the second side of the lid, the world facing camera having a field of view of at least 180 degrees and the user facing camera having a field of view of at least 180 degrees.

Example 51 includes the method of any one of examples 41-50, further including rendering a graphic while the lid is in the closed position in response to receipt of a push notification from a device separate from the portable computer, the graphic including an option for a user to respond to the push notification.

Example 52 includes the method of example 51, wherein the push notification corresponds to the device sharing data with the portable computer.

Example 53 includes the method of any one of examples 41-52, further including analyzing user interactions with the secondary display detected by a touch sensor associated with the secondary display.

Example 54 includes the method of any one of examples 41-53, further including rendering a primary user interface via the primary display when the lid is open and the primary display is powered, the primary user interface associated with an application running on the portable computer, and rendering a secondary user interface associated with the application via the secondary display.

Example 55 includes the method of example 54, wherein the secondary user interface includes controls to enable a user to operate the application, the method further including updating the primary user interface based on user interactions with the controls in the secondary user interface.

Example 56 includes the method of example 55, further including continuing to render the secondary user interface via the secondary display after the lid is returned to the closed position and the primary display is turned off, the controls in the secondary user interface to enable the user to continue to operate the application when the lid is in the closed position.

Example 57 includes the method of any one of examples 54-56, wherein the at least one processor includes a first processor to control rendering of content via the primary display and a second processor to control rendering of content via the secondary display.

Example 58 includes the method of example 57, wherein the second processor consumes less power than the first processor.

Example 59 includes a portable computer, comprising a base, a lid, a hinge to rotatably couple the lid to the base to enable movement of the lid between a closed position and an open position, a primary display on a first side of the lid, a world facing camera on a second side of the lid opposite the first side, the world facing camera to capture image data at least when the lid is in the closed position, and at least one processor to initiate an operation on the portable computer in response to analysis of the image data, the at least one processor to initiate the operation while the lid is closed.

Example 60 includes the portable computer of example 59, wherein the operation includes logging the user into the portable computer when the analysis of the image data results in recognition of a user.

Example 61 includes the portable computer of example 59, wherein the operation includes automatically moving the lid to the open position when the analysis of the image data results in recognition of a user.

Example 62 includes the portable computer of any one of examples 59-61, further including a human presence sensor to trigger activation of the world facing camera in response to detecting a presence of a user.

Example 63 includes the portable computer of any one of examples 59-62, wherein the world facing camera is a panamorphic camera having a field of view of at least 180 degrees.

Example 64 includes the portable computer of example 63, further including a user facing camera on the first side of the lid, the user facing camera being a second panamorphic to enable the capture of a 360 degree field of view when using both the world facing camera and the user facing camera.

Example 65 includes the portable computer of any one of examples 59-64, further including a microphone to capture audio data corresponding to a voice command of a user, the at least one processor to recognize the user based on the voice command without communicating with a remote server.

Example 66 includes the portable computer of example 65, further including at least one of a spring or a motor associated with the hinge to automatically move the lid to the open position in response to the voice command.

Example 67 includes the portable computer of any one of examples 59-66, further including a secondary display on the base, the secondary display visible to a user when the lid is in the closed position, the secondary display including a touch sensitive surface to enable user interactions with the secondary display via touch.

Example 68 includes the portable computer of example 67, wherein the operation includes rendering content via the secondary display on the portable computer.

Example 69 includes the portable computer of example 68, wherein the content rendered via the secondary display includes user specific information associated with the user.

Example 70 includes the portable computer of example 68, wherein the at least one processor is to render generic information via the secondary display when the at least one processor does not recognize the user.

Example 71 includes the portable computer of any one of examples 67-70, further including a touchpad disposed on the base to face the primary display when the lid is in the closed position, the secondary display corresponding to an extension of the touchpad extending along a front edge of the base.

Example 72 includes the portable computer of any one of examples 67-71, wherein the secondary display is to render content associated with an application running on the portable computer while the primary display is turned off.

Example 73 includes the portable computer of any one of examples 67-72, wherein the at least one processor is to activate the primary display in response to user interactions with the secondary display while the lid is in the closed position.

Example 74 includes the portable computer of any one of examples 67-73, wherein the at least one processor is to render a primary user interface via the primary display when the lid is open, the primary user interface associated with an application executed by the at least one processor, the secondary display to render a secondary user interface associated with the application via the secondary display.

Example 75 includes the portable computer of example 74, wherein the secondary user interface includes user controls for the application.

Example 76 includes the portable computer of example 75, wherein the at least one processor is to continue to render

the secondary user interface via the secondary display after the lid is returned to the closed position and the primary display is turned off, the user controls in the secondary user interface to enable the user to continue to control the application when the lid is in the closed position.

Example 77 includes the portable computer of any one of examples 74-76, wherein the at least one processor includes a first processor to control rendering of content via the primary display and a second processor to control rendering of content via the secondary display.

Example 78 includes the portable computer of any one of examples 74-77, further including a communications interface to enable wireless communications with a separate device in communication range of the portable computer, the secondary display to render a graphic while the lid is in the closed position, the graphic indicating an option to transfer data between the portable computer and the separate device, the communications interface to transfer the data between the portable computer and the separate device in response to the user selecting the graphic on the secondary display while the lid is in the closed position.

Example 79 includes an apparatus, comprising an audio input analyzer to analyze a voice command captured by a microphone on a portable computer, the voice command spoken by a person within audible range of the microphone when a lid of the portable computer is in a closed position, the portable computer including a primary display that is concealed when the lid is in the closed position, and a secondary display controller to render content via a secondary display of the portable computer in response to the analysis of the voice command, the secondary display controller to render the content on the secondary display while the lid of the portable computer is in the closed position and the primary display is turned off.

Example 80 includes the apparatus of example 79, wherein the secondary display is disposed in a base of the portable computer, the lid rotatable relative to the base about a hinge connecting the lid to the base.

Example 81 includes the apparatus of example 80, further including a lid controller to automatically open the lid in response to the analysis of the voice command recognizing the person as an authorized user of the portable computer.

Example 82 includes the apparatus of any one of examples 79-81, wherein the audio input analyzer is to perform voice recognition analysis of the voice command without communicating with a remote server.

Example 83 includes the apparatus of example 82, wherein the content rendered via the secondary display includes personalized information corresponding to the person when the audio input analyzer recognizes the voice command as corresponding to a voice of an authorized user of the portable computer.

Example 84 includes the apparatus of any one of examples 79-83, further including a login controller to login the person in response to the audio input analyzer recognizing the person as an authorized user of the portable computer, the login controller to login the person before the lid is moved from the closed position.

Example 85 includes the apparatus of any one of examples 79-84, further including a camera input analyzer to analyze image data captured by a world facing camera on the portable computer when the lid is in the closed position, the world facing camera on a first side of the lid, the primary display on a second side of the lid opposite the first side.

Example 86 includes the apparatus of example 85, further including a human presence sensor to detect a presence of a

person nearby the portable computer, the human presence sensor to trigger activation of the world facing camera.

Example 87 includes the apparatus of any one of examples 79-86, wherein the content is first content, and further including a system controller to determine whether second content is to be rendered via the primary display as part of a response to the voice command, and a primary display controller to activate the primary display while the lid is still closed and render the second content via the primary display.

Example 88 includes the apparatus of example 87, further including a lid controller to automatically move the lid to an open position in response to the voice command.

Example 89 includes the apparatus of any one of examples 79-88, further including a communications interface to receive a push notification from a device separate from the portable computer while the lid is in the closed position, the secondary display controller to render a graphic on the secondary display while the lid is in the closed position, the graphic including an option for a user to respond to the push notification.

Example 90 includes the apparatus of example 89, wherein the push notification corresponds to the device sharing data with the portable computer.

Example 91 includes the apparatus of any one of examples 79-90, further including a touch-based input analyzer to analyze user interactions with the secondary display detected by a touch sensor associated with the secondary display.

Example 92 includes the apparatus of example 91, wherein the touch sensor is associated with a touchpad disposed on a base of the portable computer, the secondary display corresponding to an extension of the touchpad, the secondary display to extend along a front edge of the base to be visible when the lid is in the closed position.

Example 93 includes the apparatus of any one of examples 79-92, further including a primary display controller to render a primary user interface via the primary display when the lid is open and the primary display is powered, the primary user interface associated with an application running on the portable computer, the secondary display to render a secondary user interface associated with the application via the secondary display.

Example 94 includes the apparatus of example 93, wherein the secondary user interface includes controls to enable a user to operate the application, the primary display controller to update the primary user interface based on user interactions with the controls in the secondary user interface.

Example 95 includes the apparatus of example 94, wherein the secondary display controller is to continue to render the secondary user interface via the secondary display after the lid is returned to the closed position and the primary display is turned off, the controls in the secondary user interface to enable the user to continue to operate the application when the lid is in the closed position.

Example 96 includes the apparatus of any one of examples 93-95, wherein the primary display controller is implemented with a first processor and the secondary display controller is implemented with a second processor.

Example 97 includes the apparatus of example 96, wherein the second processor consumes less power than the first processor.

Although certain example methods, apparatus and articles of manufacture have been disclosed herein, the scope of coverage of this patent is not limited thereto. On the con-

trary, this patent covers all methods, apparatus and articles of manufacture fairly falling within the scope of the claims of this patent.

What is claimed is:

1. A portable compute device comprising:
 - a microphone;
 - a speaker;
 - a first camera to face a first direction;
 - a second camera to face a second direction, the second direction opposite the first direction;
 - communications circuitry;
 - a first display;
 - a second display separate from the first display;
 - a hinge to enable the first display to rotate relative to the second display between an open position and a closed position, at least a portion of the second display capable of being visible when the first display is rotated about the hinge to the closed position, the portion of the second display to be multiple times longer in a third direction than in a fourth direction perpendicular to the third direction, the third direction extending parallel to an axis of rotation of the hinge;
 - memory; and
 - processor circuitry.
2. The portable compute device of claim 1, further including instructions, the processor circuitry to execute the instructions to cause display of information on the portion of the second display when the first display is in the closed position, the information to indicate a time of day.
3. The portable compute device of claim 2, wherein the information is first information and the processor circuitry is to cause display of second information on the portion of the second display when the first display is in the closed position, the second information different than the first information.
4. The portable compute device of claim 3, wherein the second information indicates a battery level associated with the compute device.
5. The portable compute device of claim 3, wherein the second information indicates an incoming call.
6. The portable compute device of claim 3, wherein the communication circuitry is to receive a push notification from a second device while the first display is in the closed position, the second device separate from the compute device, the processor circuitry to cause the display of the second information in response to the receipt of the push notification, the second information to indicate the receipt of the push notification.
7. The portable compute device of claim 3, wherein the portion of the second display is an extension of a touch sensitive surface, the touch sensitive surface to face toward and be at least partially covered by the first display when the first display is in the closed position.
8. The portable compute device of claim 7, wherein the portion of the second display is to extend away from the touch sensitive surface in a direction that is nonplanar to the touch sensitive surface.
9. A foldable compute device comprising:
 - a microphone;
 - a speaker;
 - a first camera on a first side of a housing;
 - a second camera on a second side of the housing, the second side opposite the first side;
 - communications circuitry;
 - a display screen;
 - a touch display separate from the display screen;

a hinge to enable the compute device to be folded about an axis of rotation into different positions, a first position corresponding to an open position and second position corresponding to a closed position, at least a portion of the touch display visible while the compute device is in the closed position, the portion of the touch display to be multiple times longer in a first direction than in a second direction perpendicular to the first direction, the first direction extending parallel to the axis of rotation;

memory; and

processor circuitry.

10. The foldable compute device of claim 9, further including instructions, the processor circuitry to execute the instructions to cause presentation of information on the portion of the touch display with the compute device in the closed position, the information to indicate a time of day.

11. The foldable compute device of claim 10, wherein the information is first information and the processor circuitry is to cause presentation of second information on the portion of the touch display with the compute device in the closed position, the second information different than the first information.

12. The foldable compute device of claim 11, wherein the second information indicates a battery level associated with the compute device.

13. The foldable compute device of claim 11, wherein the second information indicates an incoming call.

14. The foldable compute device of claim 11, wherein the communication circuitry is to receive a push notification from a second device with the compute device in the closed position, the second device separate from the compute device, the processor circuitry to cause the presentation of the second information in response to the receipt of the push notification, the second information to indicate the receipt of the push notification.

15. The foldable compute device of claim 11, wherein the touch display includes a touch pad and a display area, the display area is an extension of the touch pad, the portion of the touch display corresponds to the display area, the touch pad to face toward and be at least partially covered by the display screen with the compute device in the closed position.

16. The foldable compute device of claim 15, wherein the display area of the touch display is to extend away from the touch pad in a direction that is nonplanar to the touch pad.

17. An apparatus comprising:

- a housing including different first and second parts;
- means for sensing audio;
- means for generating audio;
- first means for capturing an image;
- second means for capturing an image, both the first and second image capturing means to be on opposite sides of one of the first part of the housing or the second part of the housing;
- means for communicating;
- first means for displaying information, the first displaying means carried by the first part of the housing;
- second means for displaying information, the second displaying means carried by the second part of the housing;
- a hinge for rotatably coupling the first part of the housing to the second part of the housing to enable the apparatus to be adjusted between an open position and a closed position, the first and second parts of the housing to extend alongside one another while the apparatus is in the closed position, the first and second parts of the

45

housing to extend away from one another while the apparatus is in the open position, at least a portion of the second displaying means to remain visible while the apparatus is adjusted to the closed position, the portion of the second displaying means to be multiple times longer in a first direction than in a second direction perpendicular to the first direction, the first direction extending parallel to an axis of rotation of the hinge; means for storing data; and means for processing.

18. The apparatus of claim 17, further including instructions, the processing means to execute the instructions to cause information to be rendered on the portion of the second displaying means while the apparatus is adjusted to the closed position, the information to indicate a time of day.

19. The apparatus of claim 18, wherein the information is first information and the processing means is to cause second information to be rendered on the portion of the second displaying means while the apparatus is in the closed position, the second information different than the first information.

46

20. The apparatus of claim 19, wherein the second information indicates a charge level.

21. The apparatus of claim 19, wherein the second information indicates an incoming call.

22. The apparatus of claim 19, wherein the communicating means is to receive a push notification from a device while the apparatus is in the closed position, the device separate from the apparatus, the processing means to cause the second information to be rendered in response to the receipt of the push notification, the second information to indicate the receipt of the push notification.

23. The apparatus of claim 19, wherein the portion of the second displaying means is an extension of a means for sensing touch, the touch sensing means to face toward and be at least partially covered by the first displaying means while the apparatus is adjusted to the closed position.

24. The apparatus of claim 23, wherein the portion of the second displaying means is to extend away from the touch sensing means in a direction that is nonplanar to the touch sensing means.

* * * * *