



US011784692B1

(12) **United States Patent**
Chu et al.

(10) **Patent No.:** **US 11,784,692 B1**
(45) **Date of Patent:** ***Oct. 10, 2023**

(54) **EXPLICIT MULTIUSER BEAMFORMING TRAINING IN A WIRELESS LOCAL AREA NETWORK**

(71) Applicant: **Marvell Asia Pte Ltd**, Singapore (SG)

(72) Inventors: **Liwen Chu**, San Ramon, CA (US); **Yakun Sun**, San Jose, CA (US); **Rui Cao**, Sunnyvale, CA (US); **Hongyuan Zhang**, Fremont, CA (US); **Hui-Ling Lou**, Sunnyvale, CA (US)

(73) Assignee: **Marvell Asia Pte Ltd**, Singapore (SG)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **17/883,308**

(22) Filed: **Aug. 8, 2022**

Related U.S. Application Data

(63) Continuation of application No. 16/985,870, filed on Aug. 5, 2020, now Pat. No. 11,411,627, which is a (Continued)

(51) **Int. Cl.**
H04B 7/06 (2006.01)
H04L 5/00 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **H04B 7/0617** (2013.01); **H04L 1/1614** (2013.01); **H04L 5/0055** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC . H04B 7/0617; H04B 7/0452; H04L 27/2601; H04L 1/1614; H04W 84/12
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,599,332 B2 10/2009 Zelst et al.
7,742,390 B2 6/2010 Mujtaba

(Continued)

FOREIGN PATENT DOCUMENTS

CN 101578805 A 11/2009
CN 102013959 A 4/2011

OTHER PUBLICATIONS

Ansari et al., "Unified MIMO Pre-Coding Based on Givens Rotation, The Institute of Electrical and Electronics Engineers, doc. No. IEEE C802.16e-04/516r2," pp. 1-13, (Jan. 11, 2005).


(Continued)

Primary Examiner — Jael M Ulysse

(57) **ABSTRACT**

A first communication device transmits a null data packet (NDP) to a second communication device as part of a multi-user beamforming training transmission sequence and receives a first packet from the second communication device responsive to transmitting the NDP. The first packet includes an aggregate media access control protocol data unit (A-MPDU) having a plurality of fragments of beamforming training information that was generated by the second communication device based on the NDP. The first communication device determines that one or more of the fragments were not correctly received by the first communication device and generates a bitmap to indicate a set of at least one fragment that is to be retransmitted by the second communication device. The first communication device transmits a second packet having the bitmap to the second communication device to prompt the second communication device to retransmit the set of at least one fragment.

15 Claims, 12 Drawing Sheets



Related U.S. Application Data

continuation of application No. 15/350,985, filed on Nov. 14, 2016, now Pat. No. 10,742,285.

(60) Provisional application No. 62/255,018, filed on Nov. 13, 2015.

(51) **Int. Cl.**

H04L 25/02 (2006.01)
H04L 1/1607 (2023.01)
H04W 84/12 (2009.01)
H04B 7/0452 (2017.01)
H04L 27/26 (2006.01)

(52) **U.S. Cl.**

CPC *H04L 25/0202* (2013.01); *H04B 7/0452* (2013.01); *H04L 27/2601* (2013.01); *H04W 84/12* (2013.01)

(56)

References Cited

U.S. PATENT DOCUMENTS

8,155,138	B2	4/2012	van Nee	
8,270,909	B2	9/2012	Zhang et al.	
8,289,869	B2	10/2012	Sawai	
8,526,351	B2	9/2013	Fischer et al.	
8,619,907	B2	12/2013	Mujtaba et al.	
8,724,720	B2	5/2014	Srinivasa et al.	
9,166,660	B2	10/2015	Chu et al.	
9,197,298	B2	11/2015	Kim et al.	
9,351,297	B2	5/2016	Aboul-Magd et al.	
10,742,285	B1 *	8/2020	Chu	H04B 7/0695
11,411,627	B1 *	8/2022	Chu	H04L 5/0055
2005/0181799	A1	8/2005	Laroia	
2006/0203891	A1	9/2006	Sampath	
2006/0285483	A1	12/2006	Khan	
2007/0230373	A1	10/2007	Li et al.	
2007/0298742	A1	12/2007	Ketchum et al.	
2009/0196163	A1	8/2009	Du	
2009/0225697	A1	9/2009	Solomon	
2010/0220614	A1	9/2010	Seong et al.	
2011/0002219	A1	1/2011	Kim et al.	
2011/0128947	A1	6/2011	Liu et al.	
2011/0199946	A1	8/2011	Breit et al.	
2011/0222472	A1	9/2011	Breit et al.	
2011/0243262	A1	10/2011	Ratasuk et al.	
2011/0261708	A1	10/2011	Grandhi	
2012/0026909	A1	2/2012	Seok	
2012/0033592	A1	2/2012	Kim et al.	
2012/0033614	A1	2/2012	Sampath et al.	
2012/0039196	A1	2/2012	Zhang	
2012/0051246	A1	3/2012	Zhang et al.	
2012/0051287	A1	3/2012	Merlin et al.	
2012/0140753	A1	6/2012	Lee et al.	
2012/0176921	A1	7/2012	Abraham et al.	
2012/0177018	A1	7/2012	Abraham et al.	
2012/0218981	A1	8/2012	Lee et al.	
2012/0250618	A1	10/2012	Abraham et al.	
2012/0328034	A1	12/2012	Nabar et al.	
2013/0044743	A1	2/2013	Zhang et al.	
2013/0058239	A1	3/2013	Wang et al.	
2013/0094488	A1	4/2013	Choi et al.	
2013/0188567	A1	7/2013	Wang	
2013/0223427	A1 *	8/2013	Sohn	H04L 5/0048 370/338
2013/0229996	A1	9/2013	Wang et al.	
2013/0286959	A1	10/2013	Lou et al.	
2014/0044069	A1 *	2/2014	Bao	H04B 7/0689 370/329
2014/0093005	A1	4/2014	Xia et al.	
2014/0160964	A1	6/2014	Trainin	
2014/0192914	A1	7/2014	Liu et al.	
2014/0254351	A1	9/2014	Newman et al.	
2014/0269358	A1 *	9/2014	Gao	H04L 43/0888 370/252

2014/0294019	A1	10/2014	Quan et al.	
2014/0307612	A1	10/2014	Vermani et al.	
2014/0328242	A1	11/2014	Tong et al.	
2014/0334420	A1	11/2014	You	
2015/0063128	A1	3/2015	Garikipati et al.	
2015/0110046	A1	4/2015	Merlin et al.	
2015/0124689	A1	5/2015	Merlin et al.	
2015/0131517	A1	5/2015	Chu et al.	
2015/0139091	A1	5/2015	Azizi et al.	
2015/0222346	A1	8/2015	Garrett et al.	
2015/0236770	A1	8/2015	Garrett et al.	
2015/0288501	A1 *	10/2015	Kwon	H04L 5/0007 370/329
2015/0289147	A1	10/2015	Lou et al.	
2015/0304007	A1	10/2015	Chu et al.	
2015/0319747	A1	11/2015	Chu et al.	
2015/0319782	A1	11/2015	Chu et al.	
2015/0333812	A1 *	11/2015	Breit	H04L 25/03343 370/329
2016/0014804	A1	1/2016	Merlin et al.	
2016/0037330	A1	2/2016	Ponnuswamy	
2016/0043781	A1	2/2016	Cho et al.	
2016/0072564	A1	3/2016	Li et al.	
2016/0073387	A1	3/2016	Yang et al.	
2016/0081075	A1	3/2016	Kim et al.	
2016/0100396	A1	4/2016	Seok	
2016/0100408	A1	4/2016	Hedayat	
2016/0142122	A1 *	5/2016	Merlin	H04B 7/0626 375/267
2016/0150505	A1	5/2016	Hedayat	
2016/0165574	A1	6/2016	Chu et al.	
2016/0165589	A1	6/2016	Chu et al.	
2016/0165607	A1 *	6/2016	Hedayat	H04W 24/00 370/338
2016/0197655	A1 *	7/2016	Lee	H04W 48/00 370/338
2016/0255606	A1	9/2016	Chu et al.	
2016/0261327	A1	9/2016	Merlin et al.	
2016/0262050	A1 *	9/2016	Merlin	H04L 1/0026
2016/0295581	A1	10/2016	Ghosh et al.	
2016/0295629	A1	10/2016	Gubeskys et al.	
2016/0316424	A1 *	10/2016	Jia	H04W 48/18
2016/0323879	A1	11/2016	Ghosh et al.	
2016/0338059	A1 *	11/2016	Huang	H04W 72/02
2017/0005708	A1 *	1/2017	Bhat	H04B 7/063
2017/0141828	A1	5/2017	Tosato et al.	
2017/0171878	A1 *	6/2017	Chun	H04W 72/0453
2017/0188390	A1	6/2017	Adachi et al.	
2017/0202026	A1	7/2017	Ahn et al.	
2017/0272138	A1 *	9/2017	Chun	H04L 1/0031
2017/0279864	A1 *	9/2017	Chun	H04L 1/1685
2017/0288748	A1 *	10/2017	Lou	H04B 7/0452
2017/0289911	A1	10/2017	Kim et al.	
2017/0338919	A1	11/2017	Lim et al.	
2018/0220443	A1	8/2018	Kim et al.	
2018/0359761	A1 *	12/2018	Chun	H04W 72/21

OTHER PUBLICATIONS

Chen, "Home Network Basis: Transmission Environments and Wired/Wireless Protocols," Prentice Hall, pp. 1-26 (Jul. 2006).

Chun et al., "Legacy Support on HEW frame structure," doc: IEEE 11-13/1057r0, *The Institute of Electrical and Electronics Engineers, Inc.*, pp. 1-8 (Sep. 2013).

Hiertz et al., "The IEEE 802.11 Universe," *IEEE Communications Magazine*, pp. 62-70, (Jan. 2010).

IEEE P802.11 ax™/D0.1, "Draft Standard for Information technology—Telecommunications and information exchange between systems Local and metropolitan area networks—Specific Requirements, Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications, Amendment 6: Enhancements for high efficiency in frequency bands between 1 GHz and 6 GHz," *IEEE Computer Society*, 221 pages (Mar. 2016).

IEEE P802.11ax™/D0.4, "Draft Standard for Information technology—Telecommunications and information exchange between systems Local and metropolitan area networks—Specific Requirements, Part

(56)

References Cited

OTHER PUBLICATIONS

11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications, Amendment 6: Enhancements for High Efficiency WLAN,” IEEE Computer Society, 317 pages (Aug. 2016).

IEEE P802.11ax™/D0.5, “Draft Standard for Information technology—Telecommunications and information exchange between systems—Local and metropolitan area networks—Specific Requirements, Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications, Amendment 6: Enhancements for High Efficiency WLAN (#1121),” IEEE Computer Society, 376 pages (Sep. 2016).

IEEE Std 802.11ac/D2.0 “Draft Standard for Information Technology—Telecommunications and information exchange between systems—Local and metropolitan area networks—Specific requirements, Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) specifications: Amendment 4: Enhancements for Very High Throughput for Operation in Bands below 6 GHz,” *The Institute of Electrical and Electronics Engineers, Inc.*, pp. 1-359 (Jan. 2012).

IEEE Std 802.11ac/D2.1 “Draft Standard for Information Technology—Telecommunications and information exchange between systems—Local and metropolitan area networks—Specific requirements, Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) specifications: Amendment 4: Enhancements for Very High Throughput for Operation in Bands below 6 GHz,” *The Institute of Electrical and Electronics Engineers, Inc.*, pp. 1-363 (Mar. 2012).

IEEE Std 802.11ac/D3.0 “Draft Standard for Information Technology—Telecommunications and information exchange between systems—Local and metropolitan area networks—Specific requirements, Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) specifications: Amendment 4: Enhancements for Very High Throughput for Operation in Bands below 6 GHz,” *The Institute of Electrical and Electronics Engineers, Inc.*, pp. 1-385 (Jun. 2012).

IEEE Std 802.11ac/D4.0 “Draft Standard for Information Technology—Telecommunications and information exchange between systems—Local and metropolitan area networks—Specific requirements, Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) specifications: Amendment 4: Enhancements for Very High Throughput for Operation in Bands below 6 GHz,” *The Institute of Electrical and Electronics Engineers, Inc.*, pp. 1-408 (Oct. 2012).

IEEE Std 802.11ac/D5.0 “Draft Standard for Information Technology—Telecommunications and information exchange between systems—Local and metropolitan area networks—Specific requirements, Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) specifications: Amendment 4: Enhancements for Very High Throughput for Operation in Bands below 6 GHz,” *The Institute of Electrical and Electronics Engineers, Inc.*, pp. 1-440 (Jan. 2013).

IEEE Std 802.11ac/D6.0 “Draft Standard for Information Technology—Telecommunications and information exchange between systems—Local and metropolitan area networks—Specific requirements, Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) specifications: Amendment 4: Enhancements for Very High Throughput for Operation in Bands below 6 GHz,” *The Institute of Electrical and Electronics Engineers, Inc.*, pp. 1-446 (Jul. 2013).

IEEE Std 802.11ac/D7.0 “Draft Standard for Information Technology—Telecommunications and information exchange between systems—Local and metropolitan area networks—Specific requirements, Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) specifications: Amendment 4: Enhancements for Very High Throughput for Operation in Bands below 6 GHz,” *The Institute of Electrical and Electronics Engineers, Inc.*, pp. 1-456 (Sep. 2013).

IEEE Std 802.11™ 2012 (Revision of IEEE Std 802.11-2007) IEEE Standard for Information technology—Telecommunications and information exchange between systems—Local and metropolitan area networks—Specific requirements Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) specifications, *The Institute of Electrical and Electronics Engineers, Inc.*, pp. 1-2695 (Mar. 29, 2012).

IEEE Std 802.16™-2012 (Revision of IEEE Std. 802.16-2009), IEEE Standard for Air Interface for Broadband Wireless Access Systems: Part 1—Beginning through Section 7, IEEE Computer Society and the IEEE Microwave Theory and Techniques Society, *The Institute of Electrical and Electronics Engineers, Inc.*, 2558 pages (Aug. 17, 2012).

International Standard, ISO/IEC 8802-11, ANSI/IEEE Std 802.11, “Information technology—Telecommunications and information exchange between systems—local and metropolitan area networks—specific requirements” Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) specifications, *The Institute of Electrical and Electronics Engineers, Inc.*, pp. 1-512 (1999).

Love et al., “An Overview of Limited Feedback in Wireless Communication Systems,” *IEEE J. on Selected Areas in Communications*, vol. 26, No. 8, pp. 1341-1365 (Oct. 2008).

Merlin et al., “Trigger Frame Format,” IEEE Draft, doc. IEEE 802.11-15/0877r1, vol. 802.11ax, No. 1, 16 pages (Jul. 13, 2015).

Mujtaba, “IEEE P802.11—Wireless LANs, TGN Sync Proposal Technical Specification,” *The Institute of Electrical and Electronics Engineers, Inc.*, doc.: IEEE 802.11-04/0889r6, pp. 1-131 (May 2005).

Perahia et al., “Gigabit Wireless LANs: an overview of IEEE 802.11ac and 802.11ad,” *ACM SIGMOBILE Mobile Computing and Communications Review*, vol. 15, No. 3, pp. 23-33 (Jul. 2011).

Seok et al., “HEW PPDU Format for Supporting MIMO-OFDMA,” IEEE 802.11-14/1210r0, 16 pages, (Sep. 14, 2014).

Stacey et al., “IEEE P802.11, Wireless LANs, Proposed TGac Draft Amendment,” *Institute of Electrical and Electronics Engineers*, doc. No. IEEE 802.11-10/1361r3 pp. 1-154 (Jan. 2011).

Stacey et al., “Specification Framework for TGac,” document No. IEEE 802.11-09/0992r20, *Institute for Electrical and Electronics Engineers*, pp. 1-49, (Jan. 18, 2011).


Tandai et al., “An Efficient Uplink Multiuser MIMO Protocol in IEEE 802.11 WLANs,” *IEEE 20th International Symposium on Personal, Indoor and Mobile Radio Communications (PIMRC 2009)*, pp. 1153-1157 (Sep. 13, 2009).

Van Nee et al. “The 802.11n MIMO-OFDM Standard for Wireless LAN and Beyond,” *Wireless Personal Communications*, vol. 37, pp. 445-453 (Jun. 2006).

Zhang et al., “Beamforming Feedback for Single Stream,” *The Institute of Electrical and Electronics Engineers*, doc. No. IEEE 802.11-12/1312r0, pp. 1-22 (Nov. 12, 2012).

* cited by examiner

FIG. 1






FIG. 2




FIG. 3




FIG. 4

500




FIG. 5




FIG. 6

700





FIG. 7

800




Some fragments are missing and STA3 and STA4

All fragments are retransmitted to STA2

FIG. 8

900



Some fragments are missing

Missing fragments are retransmitted to STA2 and STA3

FIG. 9




FIG. 10





FIG. 11

**FIG. 12**

1

EXPLICIT MULTIUSER BEAMFORMING TRAINING IN A WIRELESS LOCAL AREA NETWORK

CROSS-REFERENCE TO RELATED APPLICATIONS

The present application is a continuation of U.S. patent application Ser. No. 16/985,870 (now U.S. Pat. No. 11,411,627), entitled "Explicit Multiuser Beamforming Training in a Wireless Local Area Network," filed on Aug. 5, 2020, which is a continuation of U.S. patent application Ser. No. 15/350,985 (now U.S. Pat. No. 10,742,285), entitled "Explicit Multiuser Beamforming Training in a Wireless Local Area Network," filed on Nov. 14, 2016, which claims the benefit of U.S. Provisional Patent Application No. 62/255,018, entitled "Explicit UL MU MIMO Beamforming" filed on Nov. 13, 2015. All of the applications listed above are incorporated herein by reference in their entireties.

FIELD OF THE DISCLOSURE

The present disclosure relates generally to communication networks and, more particularly, to beamforming training in wireless local area networks.

BACKGROUND

Wireless local area networks (WLANs) have evolved rapidly over the past decade. Development of WLAN standards such as the Institute for Electrical and Electronics Engineers (IEEE) 802.11a, 802.11b, 802.11g, 802.11n, and 802.11ac Standards has improved single-user peak data throughput. For example, the IEEE 802.11b Standard specifies a single-user peak throughput of 11 megabits per second (Mbps), the IEEE 802.11a and 802.11g Standards specify a single-user peak throughput of 54 Mbps, the IEEE 802.11n Standard specifies a single-user peak throughput of 600 Mbps, and the IEEE 802.11ac Standard specifies a single-user peak throughput in the gigabits per second (Gbps) range. Future standards promise to provide even greater throughputs, such as throughputs in the tens of Gbps range.

SUMMARY

In an embodiment, a method for beamforming training in a wireless communication network includes: transmitting, by a first communication device, a null data packet (NDP) to a second communication device as part of a multi-user beamforming training transmission sequence, wherein the NDP i) includes a set of one or more training signals that allow the second communication device to estimate a communication channel from the first communication device to the second communication device, and ii) omits a data portion; receiving, at the first communication device, a first packet from the second communication device responsive to transmitting the NDP, the first packet including an aggregate media access control protocol data unit (A-MPDU), the A-MPDU having a plurality of fragments of beamforming training information that was generated by the second communication device based on the set of one or more training signals included in the NDP, wherein an entirety of the beamforming training information generated by the second communication device in response to the NDP is included in the plurality of fragments, and wherein no single fragment among the plurality of fragments includes the entirety of the beamforming training information; determining, at the first

2

communication device, that one or more of the fragments in the plurality of fragments were not correctly received by the first communication device; in response to determining that one or more of the fragments in the plurality of fragments were not correctly received by the first communication device, generating, by the first communication device, a bitmap to indicate a set of at least one fragment of the plurality of fragments that is to be retransmitted by the second communication device, wherein bits of the bitmap correspond to respective fragments in the plurality of fragments; and transmitting, by the first communication device, a second packet having the bitmap to the second communication device to prompt the second communication device to retransmit the set of at least one fragment of the plurality of fragments.

In another embodiment, a first wireless communication device comprises a wireless network interface device having one or more integrated circuit (IC) devices configured to: control the wireless network interface device to transmit a null data packet (NDP) to a second wireless communication device as part of a multi-user beamforming training transmission sequence, wherein the NDP i) includes a set of one or more training signals that allow the second wireless communication device to estimate a communication channel from the first communication device to the second wireless communication device, and ii) omits a data portion; receive an aggregate media access control protocol data unit (A-MPDU) that was transmitted within a first packet by the second wireless communication device, the A-MPDU having a plurality of fragments of beamforming training information that was generated by the second wireless communication device based on the set of one or more training signals included in the NDP, wherein an entirety of the beamforming training information generated by the second wireless communication device in response to the NDP is included in the plurality of fragments, and wherein no single fragment among the plurality of fragments includes the entirety of the beamforming training information; determine that one or more of the fragments in the plurality of fragments were not correctly received by the first communication device; in response to determining that one or more of the fragments in the plurality of fragments were not correctly received by the first communication device, generate a bitmap to indicate a set of at least one fragment of the plurality of fragments that is to be retransmitted by the second wireless communication device, wherein bits of the bitmap correspond to respective fragments in the plurality of fragments; and control the wireless network interface device to transmit a second packet having the bitmap to the second wireless communication device to prompt the second wireless communication device to retransmit the set of at least one fragment of the plurality of fragments.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of an example wireless local area network (WLAN), according to an embodiment.

FIG. 2 is a diagram of an example transmission sequence in a WLAN, according to an embodiment;

FIG. 3 is a block diagram of a control frame for announcing beamforming training, according to an embodiment;

FIG. 4 is a block diagram of an information field included in the control frame of FIG. 3, according to an embodiment;

FIG. 5 is a block diagram of a trigger frame of beamforming trigger type, according to an embodiment;

FIG. 6 is a block diagram of a common information field included in the trigger frame of FIG. 5, according to an embodiment;

FIG. 7 is a block diagram of a per-user information field included in the trigger frame of FIG. 5, according to an embodiment;

FIG. 8 is a diagram of an example transmission sequence in a WLAN, according to an embodiment;

FIG. 9 is a diagram of an example transmission sequence in a WLAN, according to an embodiment;

FIG. 10 is a block diagram of an action block acknowledgement frame, according to an embodiment;

FIG. 11 is a block diagram of a block acknowledgement control field included in the action block acknowledgment frame of FIG. 10, according to an embodiment; and

FIG. 12 is a flow diagram of an example method for beamforming training in a WLAN, according to an embodiment.

DETAILED DESCRIPTION

In embodiments described below, a wireless network device such as an access point (AP) of a wireless local area network (WLAN) simultaneously communicates with multiple client devices such as client stations (STAs). In an embodiment, the AP and the client stations support single user and multi-user uplink transmissions in the direction from the client stations to the AP. In single user transmission, in an embodiment, a single client station transmits data to the AP at a given time. In multi-user transmission, multiple client stations simultaneously transmit data to the AP, in various embodiments. For example, multiple client stations simultaneously transmit data to the AP by transmitting the data using respective different frequency portions or sub-channels of an orthogonal frequency division multiple access (OFDMA) transmission and/or using respective different spatial streams of a multi-user multiple input multiple output (MU-MIMO) transmission, in various embodiments.

In some embodiments, client stations that are equipped with multiple antennas are configured to utilize the multiple antennas to beamform or steer transmissions to the AP. Beamforming is used by such client stations to beamform single-user uplink transmissions and/or to beamform multi-user uplink transmissions to the AP, in various embodiments. Generally speaking, uplink beamforming involves obtaining a description of a communication channel from a client station to the AP, and determining, based on the description of the communication channel, determining, based on the channel description, beamforming coefficients (e.g., a steering matrix) to be applied to subsequent transmissions from the client station to the AP. To obtain characteristics of the communication channel from a client station to the AP, in explicit beamforming, the client station transmits a beamforming training packet, such as a sounding packet, to the AP. The AP receives the beamforming training packet from the client station and, based on training signals included in the beamforming training packet, develops a channel description, such as an estimate of the channel response of the communication channel from the client station to the AP. The AP then feeds back the channel description or beamforming coefficients determined based on the channel description, in some form, to the client station. The client station utilizes this information fed back from the AP to beamform or steer subsequent transmissions from the client station to the AP.

To efficiently obtain characteristics of respective communication channels from multiple client stations to the AP, in

an embodiment, the AP and the multiple client stations perform a beamforming procedure in which the multiple client stations simultaneously transmit beamforming training packets to the AP, for example using OFDMA and or MU-MIMO transmission to the AP. The AP determines, based on the beamforming training packets, respective beamforming feedback information for the multiple client stations. The AP then transmits the respective beamforming information to the client stations, for example by including the beamforming feedback information in a multi-user (e.g., OFDMA and/or MU MIMO) downlink transmission from the AP to the client stations. Performing uplink beamforming training simultaneously with multiple client stations results in a reduced system overhead associated with uplink beamforming training as compared to systems in which uplink beamforming training is performed sequentially with respective ones of the multiple client stations, in at least some embodiments.

FIG. 1 is a block diagram of an example wireless local area network (WLAN) 10, according to an embodiment. An AP 14 includes a host processor 15 coupled to a network interface 16. In an embodiment, the network interface 16 includes one or more integrate circuits (ICs) configured to operate as discussed below. The network interface 16 includes a medium access control (MAC) processor 18 and a physical layer (PHY) processor 20. The PHY processor 20 includes a plurality of transceivers 21, and the transceivers 21 are coupled to a plurality of antennas 24. Although three transceivers 21 and three antennas 24 are illustrated in FIG. 1, the AP 14 includes other suitable numbers (e.g., 1, 2, 4, 5, etc.) of transceivers 21 and antennas 24 in other embodiments. In some embodiments, the AP 14 includes a higher number of antennas 24 than transceivers 21, and antenna switching techniques are utilized. In an embodiment, the MAC processor 18 is implemented on at least a first IC, and the PHY processor 20 is implemented on at least a second IC. In an embodiment, at least a portion of the MAC processor 18 and at least a portion of the PHY processor 20 are implemented on a single IC.

In various embodiments, the MAC processor 18 and the PHY processor 20 are configured to operate according to a first communication protocol (e.g., a High Efficiency, HE, or 802.11ax communication protocol). In some embodiments, the MAC processor 18 and the PHY processor 20 are also configured to operate according to a second communication protocol (e.g., according to the IEEE 802.11ac Standard). In yet another embodiment, the MAC processor 18 and the PHY processor 20 are additionally configured to operate according to the second communication protocol, a third communication protocol, and/or a fourth communication protocol (e.g., according to the IEEE 802.11a Standard and/or the IEEE 802.11n Standard).

The WLAN 10 includes a plurality of client stations 25. Although four client stations 25 are illustrated in FIG. 1, the WLAN 10 includes other suitable numbers (e.g., 1, 2, 3, 5, 6, etc.) of client stations 25 in various scenarios and embodiments. At least one of the client stations 25 (e.g., client station 25-1) is configured to operate at least according to the first communication protocol. In some embodiments, at least one of the client stations 25 is not configured to operate according to the first communication protocol but is configured to operate according to at least one of the second communication protocol, the third communication protocol, and/or the fourth communication protocol (referred to herein as a “legacy client station”).

The client station 25-1 includes a host processor 26 coupled to a network interface 27. In an embodiment, the

network interface **27** includes one or more ICs configured to operate as discussed below. The network interface **27** includes a MAC processor **28** and a PHY processor **29**. The PHY processor **29** includes a plurality of transceivers **30**, and the transceivers **30** are coupled to a plurality of antennas **34**. Although three transceivers **30** and three antennas **34** are illustrated in FIG. **1**, the client station **25-1** includes other suitable numbers (e.g., 1, 2, 4, 5, etc.) of transceivers **30** and antennas **34** in other embodiments. In some embodiments, the client station **25-1** includes a higher number of antennas **34** than transceivers **30**, and antenna switching techniques are utilized. In an embodiment, the MAC processor **28** is implemented on at least a first IC, and the PHY processor **29** is implemented on at least a second IC. In an embodiment, at least a portion of the MAC processor **28** and at least a portion of the PHY processor **29** are implemented on a single IC.

According to an embodiment, the client station **25-4** is a legacy client station, i.e., the client station **25-4** is not enabled to receive and fully decode a data unit that is transmitted by the AP **14** or another client station **25** according to the first communication protocol. Similarly, according to an embodiment, the legacy client station **25-4** is not enabled to transmit data units according to the first communication protocol. On the other hand, the legacy client station **25-4** is enabled to receive and fully decode and transmit data units according to the second communication protocol, the third communication protocol, and/or the fourth communication protocol.

In an embodiment, one or both of the client stations **25-2** and **25-3**, has a structure that is the same as or similar to the client station **25-1**. In an embodiment, the client station **25-4** has a structure similar to the client station **25-1**. In these embodiments, the client stations **25** structured the same as or similar to the client station **25-1** have the same or a different number of transceivers and antennas. For example, the client station **25-2** has only two transceivers and two antennas (not shown), according to an embodiment.

In various embodiments, the MAC processor **18** and the PHY processor **20** of the AP **14** are configured to generate data units conforming to the first communication protocol and having formats described herein. In an embodiment, the MAC processor **18** is configured to implement MAC layer functions, including MAC layer functions of the first communication protocol. In an embodiment, the PHY processor **20** is configured to implement PHY functions, including PHY functions of the first communication protocol. For example, in an embodiment, the MAC processor **18** is configured to generate MAC layer data units such as MPDUs, MAC control frames, etc., and provide the MAC layer data units to the PHY processor **20**. In an embodiment, the PHY processor **20** is configured to receive MAC layer data units from the MAC processor **18** and encapsulate the MAC layer data units to generate PHY data units such as PHY protocol data units (PPDUs) for transmission via the antennas **24**. Similarly, in an embodiment, the PHY processor **20** is configured to receive PHY data units that were received via the antennas **24**, and extract MAC layer data units encapsulated within the PHY data units. In an embodiment, the PHY processor **20** provides the extracted MAC layer data units to the MAC processor **18**, which processes the MAC layer data units.

The transceiver(s) **21** is/are configured to transmit the generated data units via the antenna(s) **24**. Similarly, the transceiver(s) **21** is/are configured to receive data units via the antenna(s) **24**. The MAC processor **18** and the PHY processor **20** of the AP **14** are configured to process received

data units conforming to the first communication protocol and having formats described hereinafter and to determine that such data units conform to the first communication protocol, according to various embodiments.

In various embodiments, the MAC processor **28** and the PHY processor **29** of the client station **25-1** are configured to generate data units conforming to the first communication protocol and having formats described herein. In an embodiment, the MAC processor **28** is configured to implement MAC layer functions, including MAC layer functions of the first communication protocol. In an embodiment, the PHY processor **29** is configured to implement PHY functions, including PHY functions of the first communication protocol. For example, in an embodiment, the MAC processor **28** is configured to generate MAC layer data units such as MPDUs, MAC control frames, etc., and provide the MAC layer data units to the PHY processor **29**. In an embodiment, the PHY processor **29** is configured to receive MAC layer data units from the MAC processor **28** and encapsulate the MAC layer data units to generate PHY data units such as PPDUs for transmission via the antennas **34**. Similarly, in an embodiment, the PHY processor **29** is configured to receive PHY data units that were received via the antennas **34**, and extract MAC layer data units encapsulated within the PHY data units. In an embodiment, the PHY processor **29** provides the extracted MAC layer data units to the MAC processor **28**, which processes the MAC layer data units.

The transceiver(s) **30** is/are configured to transmit the generated data units via the antenna(s) **34**. Similarly, the transceiver(s) **30** is/are configured to receive data units via the antenna(s) **34**. The MAC processor **28** and the PHY processor **29** of the client station **25-1** are configured to process received data units conforming to the first communication protocol and having formats described hereinafter and to determine that such data units conform to the first communication protocol, according to various embodiments.

FIG. **2** is a diagram of an example transmission sequence **200** in a WLAN, such as the WLAN **10** of FIG. **1**, according to an embodiment, in which an AP, such as the AP **14**, performs beamforming training with multiple client stations, such as multiple ones of the client stations **25**. In the example embodiment of FIG. **2**, the AP performs beamforming training simultaneously with four client stations (STA**1**, STA**2**, STA**3**, and STA**4**). In other embodiments, the AP performs beamforming training simultaneously with a different number (2, 3, 5, 6, 7, 8, 8, 10, etc.) of client stations.

With continued reference to FIG. **2**, the AP generates and transmits an announcement data unit **202**. The announcement data unit **202** is a downlink (DL) data unit because the announcement data unit **202** is transmitted in the downlink direction from the AP to client stations, in an embodiment. In an embodiment, the announcement data unit **202** is a null data packet announcement (NDPA) data unit that omits a data portion. In another embodiment, the announcement data unit **202** includes a data portion. The announcement data unit **202** includes a control frame, such as a UL beamforming announcement control frame defined by the first communication protocol for initiation of uplink beamforming training, in an embodiment. In another embodiment, the announcement data unit **202** includes a trigger frame of beamforming announcement trigger type. In other embodiments, the announcement data unit **202** includes a beamforming announcement frame that conforms to another suitable format.

In an embodiment, the announcement data unit **202** is a duplicate data unit that is duplicated in each of a plurality of

sub-bands of a bandwidth in which the beamforming training is being performed. Thus, for example, in an embodiment in which the beamforming training is being performed in a 40 MHz-wide communication channel, the announcement data unit **202** is duplicated in each of two 20 MHz-wide subchannels of the 40 MHz-wide communication channel. As another example, in an embodiment in which the beamforming training is being performed in an 80 MHz-wide communication channel, the announcement data unit **202** is duplicated in each of four 20 MHz-wide subchannels of the 80 MHz-wide communication channel. In other embodiments, the announcement data unit **202** is duplicated in another suitable number of subchannels of the communication channel in which the beamforming training is being performed. Alternatively, the announcement data unit **202** is not a duplicate frame but rather occupies the entire bandwidth in which the beamforming training is being performed.

In an embodiment, the announcement data unit **202** identifies multiple client stations that are intended participants of a beamforming training procedure being announced by the announcement data unit **202**. For example, the announcement data unit **202** includes a respective identifier, such as an association identifier (AID) or a partial AID (PAID), associated with each of the client stations **STA1**, **STA2**, **STA3**, and **STA4** that is an intended participant of the beamforming training procedure being announced by the announcement data unit **202**, in an embodiment. Additionally, the announcement data unit **202** indicates respective resources to be used by identified the client stations **STA1**, **STA2**, **STA3**, and **STA4** during the beamforming procedure, such as resources to be used for uplink transmission of training packets by the client stations to the AP and/or resources for receiving beamforming training feedback from the AP, in an embodiment. For example, the announcement data unit **202** indicates respective resources (e.g., frequency portions and/or spatial streams) to be used by the identified client stations **STA1**, **STA2**, **STA3**, and **STA4** for uplink transmission of training packets by the client stations to the AP and/or resources for receiving beamforming training feedback from the AP, in an embodiment.

In response to receiving the announcement data unit **202**, each of the client stations **STA1**, **STA2**, **STA3**, and **STA4** identified by the announcement data unit **202** transmits a respective beamforming training data unit **204** to the AP. In an embodiment, the client stations transmit the respective beamforming training data units **204** to the AP simultaneously as parts of an uplink multi-user transmission **206** to the AP. In an embodiment, the client stations **STA1**, **STA2**, **STA3**, and **STA4** transmit the respective beamforming training data units **204** to the AP simultaneously using respective spatial streams and/or respective frequency portions indicated in the announcement data unit **202** received from the AP. Each of the beamforming training data units **204** includes one or more training signals, such as one or more training fields (e.g., long training fields (LTFs)), that allow the AP to estimate the communication channel from the corresponding client station to the AP, in an embodiment. Each beamforming training data unit **204** is an NDP that omits a data portion, in an embodiment. In another embodiment, one or more of the beamforming training data unit **204** includes a data portion.

In an embodiment, the client stations **STA1**, **STA2**, **STA3**, and **STA4** initiate transmission of their respective beamforming training data units **204** upon expiration of a predetermined time interval after receiving the end of the announcement data unit **202**. In an embodiment, the prede-

termined time interval is a time interval corresponding to a short inter-frame space (SIFS) defined by the first communication protocol (e.g., IEEE 802.11ax) and/or by a legacy communication protocol (e.g., the IEEE 802.11n/ac). In another embodiment, the predetermined time interval is a suitable time interval different from SIFS time interval.

The AP receives the beamforming training data units **204**, and determines, based on the beamforming training data units **204**, respective channel estimates for the communication channels from the client stations **STA1**, **STA2**, **STA3**, and **STA4** to the AP. Based on the determined channel estimates, the AP generates respective beamforming feedback data units **206** to be transmitted to the client stations **STA1**, **STA2**, **STA3**, and **STA4**. In an embodiment, beamforming feedback information for a client station **STA1**, **STA2**, **STA3**, and **STA4** is generated differently depending on whether the client station will use the beamforming feedback for single user transmission to the AP (SU feedback) or will use the beamforming feedback for multi-user uplink transmission to the AP (MU feedback). In an embodiment, for example, if the client station will use the beamforming feedback for beamforming uplink SU transmission, then the AP generates the beamforming feedback information for the client station based on the channel estimate determined for the client station itself without taking into account channel estimates determined for other ones of the client stations, in an embodiment. On the other hand, if the client station will use the beamforming feedback for beamforming uplink MU transmission, then the AP generates the beamforming feedback information for the client station based on the channel estimate determined for the client station itself and channel estimates determined for other ones of the client stations, in an embodiment.

Each respective data unit **206** includes beamforming feedback information for a corresponding client station **STA1**, **STA2**, **STA3**, **STA4**, such as the channel estimate obtained for the client station **STA1**, **STA2**, **STA3**, **STA4**, steering matrix coefficients (in uncompressed or compressed form) generated based on the channel estimate obtained for the client station **STA1**, **STA2**, **STA3**, **STA4**, etc. In an embodiment, the AP transmits the respective beamforming feedback data unit **206** to the client stations **STA1**, **STA2**, **STA3**, **STA4** as parts of a downlink multi-user data unit **208** to the client stations **STA1**, **STA2**, **STA3**, **STA4**. The downlink multi-user data unit **208** includes the respective beamforming feedback data unit **206** in respective frequency portions and/or respective spatial streams allocated for downlink multi-user transmission to the client stations **STA1**, **STA2**, **STA3**, and **STA4**, in various embodiments.

In an embodiment, the AP initiates transmission beamforming feedback data unit **208** upon expiration of a predetermined time interval after receiving the end of the beamforming training data units **204**. In an embodiment, the predetermined time interval is a time interval corresponding to an inter-frame space (IFS) defined by the first communication protocol (e.g., IEEE 802.11ax) and/or by a legacy communication protocol (e.g., the IEEE 802.11n/ac). In another embodiment, the predetermined time interval is a suitable time interval different from IFS time interval.

Upon successful receiving their respective beamforming feedback data units **206** from the AP, the client stations **STA1**, **STA2**, **STA3**, **STA4** transmit respective acknowledgement data units **210** to the AP. In an embodiment, the client stations **STA1**, **STA2**, **STA3**, **STA4** transmit their respective acknowledgement data units **210** simultaneously as parts of an OFDMA and/or MU-MIMO transmission **212** to the AP. In an embodiment, transmission of the acknowl-

edgement data units **210** is triggered by the beamforming feedback data unit **208**. In an embodiment, respective resources (e.g., frequency portions and/or spatial streams) to be used by the client stations **STA1**, **STA2**, **STA3**, and **STA4** for transition of the acknowledgement data units **210** are indicated to the client stations **STA1**, **STA2**, **STA3**, and **STA4** in the downlink data unit **208**, such as in one or more physical layer (PHY) signal fields of the downlink data unit **208**, in a trigger frame included in the data unit **208**, in an HE control field of a MAC header of the data unit **208**, and/or in another suitable portion of the data unit **208**. In some embodiments, the client stations **STA1**, **STA2**, **STA3**, and **STA4** use same respective resources (e.g., frequency portions and/or spatial streams) as the resources that were used to transmit the respective feedback data units **206** to the client stations **STA1**, **STA2**, **STA3**, and **STA4**. Indications of resources are omitted from the data unit **208**, in such embodiments. In some embodiments, transmission parameters (e.g., transmit power, acknowledgement type, data unit length, etc.) to be used by the client stations **STA1**, **STA2**, **STA3**, and **STA4** for transition of the acknowledgement data units are indicated in the downlink data unit **208**, such as in one or more physical layer (PHY) signal fields of the downlink data unit **208**.

In the embodiment of FIG. 2, respective data units **206** are transmitted to the client stations **STA1**, **STA2**, **STA3**, and **STA4** using a single downlink multi-user data unit **208** to the client stations **STA1**, **STA2**, **STA3**, and **STA4**. In another embodiment, however, the downlink multi-user **208** includes respective data units **206** for some by not all of the client stations **STA1**, **STA2**, **STA3**, and **STA4**. In an embodiment in which the data unit **208** includes respective data units **206** for some by not all of the client stations **STA1**, **STA2**, **STA3**, and **STA4**, more resources (e.g., larger frequency portions and/or greater numbers of spatial streams) are used for transmission of feedback to the other ones of the client stations. In an embodiment, one or more beamforming feedback data units **206** that are not included in the data unit **208** are subsequently transmitted by the AP using one or more additional downlink transmissions to the corresponding client stations from the AP. As just an example, the AP includes the data unit **206-1** for the client station **STA 1** and the data unit **206-1** for the client station **206-2** in the data unit **208**, and omits the data unit the data unit **206-3** for the client station **STA3** and the data unit **206-4** for the client station **206-4** from the data unit **208**, in an embodiment. The AP transmits the data unit **206-3** and the data unit **206-4** to the client stations **STA3**, **STA4** using an additional multi-user downlink data unit transmitted upon expiration of a predetermined time interval such as SIFS after the end of reception of the ACK data unit **210**, in an embodiment. The client stations **STA3**, **STA4** then transmit acknowledgement data units to the AP to acknowledge receipt of their data units **206**, in an embodiment.

Although the transmission sequence **200** is described with respect to beamforming training simultaneously performed with multiple client stations, a similar transmission sequence is used in beamforming training performed between an AP and only one client station, in an embodiment. For example, the announcement data unit **202** transmitted by the AP indicates only one client station as an intended participant in a beamforming training procedure, in an embodiment. In response to receiving the announcement data unit **202**, the one client station that is identified by the announcement data unit **202** transmits a beamforming training data unit **204** to the AP, in this embodiment. The AP generates and transmits one feedback data unit **206** for the one client station and

transmits the feedback data unit **206** in a single user downlink transmission to the client station, in an embodiment. Upon receiving the data unit **206**, the client station transmits an acknowledgement data unit to the AP, in an embodiment.

FIG. 3 is a block diagram of a control frame (e.g., HE control field) **300**, such as an uplink beamforming training NDP announcement control frame defined by the first communication protocol, according to an embodiment. In an embodiment, the control frame **300** is included in the announcement data unit **202** of the transmission sequence **200** of FIG. 2. For ease of explanation, the control frame **300** is described with respect to the announcement data unit **202** of the transmission sequence **200** of FIG. 2. However, the control frame **300** is included in an announcement data unit different from the announcement data unit **202** of FIG. 2 and/or is used in a transmission sequence different from the transmission sequence **200** of FIG. 2, in some embodiments. The control frame **300** includes a plurality of fields, including a frame control field **302**, a duration/ID field **304**, a first address field (e.g., a receiver address (RA) field) **306**, a second address field (e.g., a transmitter address (TA) field) **308**, a sounding dialog token field **310**, a plurality of station (STA) information fields (also referred to herein as “per-user information fields”) **312**, and a frame check sequence **316**. The number of octets allocated to each of the fields of the control frame **300**, according to an example embodiment, is indicated in FIG. 3 above the corresponding field. Other suitable numbers of octets (or bits) are allocated to at least some of the fields of the control frame **300**, in other embodiments.

In an embodiment, the first address field (RA field) **306** includes a broadcast MAC address to indicate that the control frame **300** is a broadcast control frame intended for multiple client stations (e.g., all of the client stations **25** of the WLAN **10**), in an embodiment. The second address field (TA field) **308** includes the address of the AP, in an embodiment. The sounding dialog token field **310** includes a sounding token value, in an embodiment. The STA information fields **312** identify client stations that are intended participants of the beamforming training being announced by the control frame **300**, and provide resource allocations and other beamforming training control information to the identified client stations, in an embodiment.

FIG. 4 is a block diagram of an STA information field **400**, according to an embodiment. In an embodiment, the STA information field **400** corresponds to each of STA information fields **312** of FIG. 3. The STA information field **400** includes a plurality of subfields **402**, including an AID subfield **402-1**, a transmit (Tx) power subfield **402-2**, a feedback type subfield **402-3**, a start stream subfield **402-4**, a number of space time streams (Nsts) subfield **402-5**, and a resource unit (RU) allocation subfield **402-6**. The number of bits allocated to the subfields **402**, according to an example embodiment, is indicated in FIG. 4 above the corresponding subfield **402**. Other suitable numbers or bits are allocated to at least some of the subfields **402**, in other embodiments.

In an embodiment, the AID subfield **402** includes an identifier of a client station, such as a full association identifier (AID) of the client station, or a partial association identifier (PAID) of the client station. The Tx power subfield **402-2** indicates a power level at which a beamforming packet is to be transmitted by the client station identified by the AID subfield **402-1**, in an embodiment. The feedback type subfield **402-3** indicates a type of feedback that will be provided to the client station identified by the AID subfield **402-1**, in an embodiment. For example, the feedback type

field **402-3** indicates whether SU feedback for use in single user uplink transmission or MU feedback for use in multi-user uplink transmission will be provided, in an embodiment. In an embodiment, the feedback type subfield **402-3** is omitted from the STA information field **400**. For example, a feedback type indication is instead included in the BF feedback data unit **208**, in an embodiment.

With continued reference to FIG. 4, the start stream subfield **402-4** and the Nsts subfield **402-5** indicate a number of a first spatial stream and a number of the spatial streams, respectively, allocated to the client station identified by the AID subfield **402-1** for transmission of a beamforming training packet by the client station. Thus, the start stream subfield **402-4** and the Nsts subfield **402-5** collectively indicate to the client station identified by the AID subfield **402-1** the spatial streams that the client station should use to transmit a beamforming training packet to the AP, in an embodiment. The RU allocation subfield **402-6** indicates a subchannel (e.g., one or more resource units) allocated for transmission of a beamforming training packet by the identified by the AID subfield **402-1**, in an embodiment. For example, the RU allocation subfield **402-6** indicates a start of a subchannel and a bandwidth of the subchannel allocated for transmission of a beamforming training packet by the client station identified by the AID subfield **402-1**, in an embodiment.

In some embodiments, the RU allocation subfield **402-6** is omitted from STA information field **400** or is reserved in the STA information field **400**. For example, the RU allocation subfield **402-6** is omitted or reserved in an embodiment in which respective beamforming training packets being triggered by the control frame **300** are to be transmitted using MU-MIMO transmission over entire channel bandwidth, such as the data unit entire bandwidth indicated by a bandwidth indication in a PHY preamble (e.g., in an HE SIG field) of the data unit that includes the control frame **300**. Similarly, in an embodiment, the start stream subfield **402-4** and the Nsts subfield **402-5** are omitted from the STA information field **400** or are reserved in the STA information field **400**. For example, the start stream subfield **402-4** and the Nsts subfield **402-5** are omitted or reserved if the subchannel indicated by the RU allocation subfield **402-6** is allocated for transmission of a beamforming training packet by only one client station (i.e., the client station identified by the AID subfield **402-1**).

FIG. 5 is a block diagram of a trigger frame **500** of beamforming trigger type, according to an embodiment. In an embodiment, the trigger frame **500** is included in the announcement data unit **202** of the transmission sequence **200** of FIG. 2. For ease of explanation, the trigger frame **500** is described with respect to the announcement data unit **202** of the transmission sequence **200** of FIG. 2. However, the trigger frame **500** is included in an announcement data unit different from the announcement data unit **202** of FIG. 2 and/or is used in a transmission sequence different from the transmission sequence **200** of FIG. 2, in some embodiments. The trigger frame **500** includes a plurality of fields, including a frame control field **502**, a duration/ID field **504**, a first address field (e.g., a receiver address (RA) field) **506**, a second address field (e.g., a transmitter address (TA) field) **508**, a common information field **510**, a plurality of station (STA) information fields **512**, and a frame check sequence **516**. The number of octets allocated to each of the fields of the trigger frame **500**, according to an example embodiment, is indicated in FIG. 5 above the corresponding field. Other

suitable numbers of octets (or bits) are allocated to at least some of the fields of the trigger frame **500**, in other embodiments.

In an embodiment, the first address field **506** and the second address field **508** are generally the same as or similar to the duration field **304**, the duration field **306**, the first address field **306** and the second address field **308**, respectively, described above with respect to FIG. 3. The common information field **510** and the STA information fields **512** generally identify the client stations that are intended participants in the beamforming training being triggered by the trigger frame **500** and provide resource allocations and other beamforming training control information to the identified client stations, in an embodiment, where the common field **510** includes information that is common to the identified client stations, and the STA information fields **512** include user-specific information for respective ones of the identified client stations.

FIG. 6 is a block diagram of a common information field **600** of a trigger frame included in an announcement data unit, according to an embodiment. In an embodiment, the common information field **600** corresponds to the common information field **510** of the trigger frame **500** of FIG. 5. For ease of explanation the common information field **600** is described with respect to the trigger frame **500** of FIG. 5. In another embodiment, however, the common information field **600** is included in trigger frame different from the trigger frame **500**. The common information field **600** includes a plurality of subfields **602**, including a trigger type subfield **602-1**, a bandwidth subfield **602-2**, a UL PPDU length subfield **602-3**, a guard interval (GI) mode subfield **602-4**, an LTF type subfield **602-5**, and LTF number subfield **602-6**, and a sounding dialog token subfield **602-7**. The number of bits allocated to the subfields **602**, according to an example embodiment, is indicated in FIG. 6 above the corresponding subfield **602**. Other suitable numbers or bits are allocated to at least some of the subfields **602**, in other embodiments.

In an embodiment, the trigger type subfield **602-1** is set to indicate that the trigger frame **500** is of an UL NDP trigger type. The bandwidth subfield **602-2** is set to indicate NDP packet bandwidth being triggered by the trigger frame **500**. The sounding dialog token subfield **602-7** indicates a sounding token value, in an embodiment. One or more of the remaining subfields (i.e., the UL PPDU length subfield **602-3**, the GI mode subfield **602-4**, the LTF type subfield **602-5**, and the LTF number subfield **602-6**) are not needed, particularly in embodiments in which a beamforming training packet (or packets) being triggered by the trigger frame **500** is a non-data packet. Accordingly, one or more of the remaining subfields (i.e., the UL PPDU length subfield **602-3**, the GI mode subfield **602-4**, the LTF type subfield **602-5**, and the LTF number subfield **602-6**) are reserved subfields that do not include indications specific to the beamforming training packet (or packets) being triggered by the trigger frame **500**, in an embodiment.

FIG. 7 is a block diagram of a per-user information field **700** of a trigger frame included in a beamforming training announcement data unit, according to an embodiment. In an embodiment, the per-user information field **700** corresponds to each of the per-user information fields **512** of the trigger frame **500** of FIG. 5. For ease of explanation the common information field **600** is described with respect to the trigger frame **500** of FIG. 5. In another embodiment, however, the per-user information field **700** is included in a trigger frame different from the trigger frame **500**. The per-user information field **700** includes a plurality of subfields **702**, including

a RU allocation subfield **702-1**, a SU/MU MIMO subfield **702-2**, an AID subfield **702-3**, a Tx power subfield **702-4**, a modulation and coding scheme (MCS), a low density parity check (LDPC) subfield **702-6**, a space block coding subfield **702-7**, a start stream subfield **702-8**, an Nsts subfield **702-9**, a transmit beamforming (TxBF) subfield **702-10**, a traffic class (TC) subfield **702-11**, and a feedback type subfield **702-12**.

In an embodiment, the AID subfield **702-3** identifies a client station that is an intended participant in the beamforming training procedure being triggered by the trigger frame **500**, in an embodiment. For example, the AID subfield **702-3** includes an identifier, such as a full association identifier (AID) or a partial association identifier (PAID), of a client station that is an intended participant in the beamforming training procedure, in an embodiment. The RU allocation subfield **702-1** indicates a subchannel (e.g., one or more resource units) allocated for transmission of a beamforming training packet by the AID subfield **702-3**, in an embodiment. For example, the RU allocation subfield **702-1** indicates a start of a subchannel and a bandwidth of the subchannel allocated for transmission of a beamforming training packet by the client station identified by the AID subfield **702-3**, in an embodiment. The Tx power subfield **702-4** indicates a power level at which a beamforming packet is to be transmitted by the client station identified by the AID subfield **702-3**, in an embodiment. The start stream subfield **702-8** and the Nsts subfield **702-9** indicate a number of a first spatial stream and a number of the spatial streams, respectively, allocated for transmission of a beamforming training packet the client station identified by the AID subfield **702-3**. Thus, the start stream subfield **702-8** and the Nsts subfield **702-9** collectively indicate the particular spatial streams that to the client station identified by the AID subfield **702-3** should use to transmit a beamforming training packet, in an embodiment. The feedback type subfield **702-12** indicates a type of feedback that will be provided to the client station identified by the AID subfield **702-3**, in an embodiment. For example, the feedback type field **702-12** indicates whether SU feedback for use in single user uplink transmission or MU feedback for use in multi-user uplink transmission will be provided, in an embodiment. In an embodiment, the feedback type subfield **702-12** is omitted from the per-user information field **700**. For example, a feedback type indication is instead included in the BF feedback data unit **208**, in an embodiment.

With continued reference to FIG. 7, one or more of the remaining subfields **702** (e.g., the SU/MU MIMO subfield **702-2**, the MCS subfield **702-5**, the LDPC subfield **702-6**, the STBC subfield **702-7**, the transmit beamforming (TxBF) subfield **702-10**, and/or the TC subfield **702-11**), that may generally be used in trigger frames of types other than UL beamforming training trigger type, may not be needed in the trigger frame **500** of UL beamforming training trigger type, such as in embodiments in which a beamforming training packet (or packets) being triggered by the trigger frame **500** is a null data packet. Accordingly, one or more of these remaining subfields **702** in the trigger frame **500** are reserved subfields, in an embodiment.

In some embodiments, the RU allocation subfield **702-1** is omitted from the per-user information field **700** or is reserved in the per-user information field **700**. For example, the RU allocation subfield **702-1** is omitted or reserved in an embodiment in which respective beamforming training packets being triggered by the trigger frame **500** are to be transmitted using MU-MIMO transmission over entire channel bandwidth, such as the data unit entire bandwidth

indicated by a bandwidth indication in a PHY preamble (e.g., in an HE SIG field) of the data unit that includes the trigger frame **500**. Similarly, in an embodiment, the start stream subfield **702-8** and the Nsts subfield **702-9** are omitted from the per-user information field **700** or are reserved in the per-user information field **700**. For example, the start stream subfield **702-8** and the Nsts subfield **702-9** are omitted or reserved if the subchannel indicated by the RU allocation subfield **702-1** is allocated for transmission of a beamforming training packet by only one client station (i.e., the client station identified by the AID subfield **702-3**).

FIG. 8 is a diagram of an example transmission sequence **800** in a WLAN, such as the WLAN **10** of FIG. 1, according to an embodiment, in which an AP, such as the AP **14**, performs beamforming training with multiple client stations, such as multiple ones of the client stations **25**. The transmission sequence **800** is generally similar to the transmission sequence **200** of FIG. 2. Transmission sequence **800** includes transmission of the announcement data unit **202** from the AP to the multiple client stations STA1, STA2, STA3, STA4, and transmission of the beamforming training data units **204** from the multiple client stations STA1, STA2, STA3, STA4 to the AP, in an embodiment. The AP generates, based on the beamforming data units **204**, beamforming feedback information for the client stations STA1, STA2, STA3, STA4. The AP generates respective beamforming feedback data units **806** to include respective feedback information generated for the client stations. The beamforming feedback data units **806** are generally similar to the beamforming feedback data unit **206** of FIG. 2. In an embodiment, if amount of beamforming feedback information generated for a client station cannot be transmitted in a single data unit (e.g., single MPDU) to the client station because a size of the single data unit would exceed a maximum MPDU length restriction of the client station, then the AP fragments the beamforming feedback information for the client station, and generates an aggregated MPDU (A-MPDU) **806** to be transmitted to the client station to include the fragments of the beamforming feedback information for the client station. For example, in the embodiment of FIG. 8, each of beamforming feedback data unit **806** is an A-MPDU that includes fragmented feedback information. In another embodiment, one or more of the beamforming feedback data units **806** are MPDUs, and other one or more of the beamforming feedback data units **806** are A-MPDUs. For example, the beamforming feedback data units **806-1** for the client station STA1 is an MPDU, while the remaining ones of the beamforming feedback data units **806-2**, **806-3**, and **806-4** are A-MPDUs, in an embodiment. The AP generates a multi-user (e.g., OFDMA and/or MU-MIMO) beamforming feedback data unit **808** that includes the respective beamforming feedback data unit **806**, and transmits the multi-user beamforming data unit **808** to the client stations, in an embodiment. Upon receiving its beamforming feedback data units **806**, each client station determines whether all fragments in the beamforming feedback data units **806** were correctly received by the client station, in an embodiment. Based on the determination, each client station generates either an Ack data unit **810** to positively acknowledge receipt of the data unit **806** or a negative acknowledgement (NAK) data unit **812** to negatively acknowledge receipt of the data unit **806**, in an embodiment. More specifically, if all of the fragments in the beamforming feedback data unit **806** were correctly received at the client station, then the client station generates and transmits an Ack data unit **810** to positively acknowledge receipt of the beamforming feedback data unit **806**, in an

embodiment. On the other hand, if one or more of the fragments in the beamforming feedback data unit **806** were not correctly received at the client station, then the client station generates and transmits a negative acknowledgement (NAK) data unit **812** to indicate to the AP that there was an error in at least one of the fragments in the beamforming feedback data unit **806**, in an embodiment. For example, in the embodiment of FIG. **8**, the client station STA2 generates and transmits a NAK data unit **812-2** to indicate to the AP that there was an error in at least one of the fragments in the beamforming feedback data unit **806-2**, and the client station STA3 generates and transmits a NAK data unit **812-3** to indicate to the AP that there was an error in at least one of the fragments in the beamforming feedback data unit **806-3**. Each NAK data unit **812** includes a NAK control frame defined by the first communication protocol, in an embodiment. Each NAK data unit **812** includes another suitable frame, such as a quality of service (QoS) Null frame, in another embodiment.

The client stations transmit the generated Ack data units **810** or NAK data units **812** to the AP simultaneously as parts of a multi-user (e.g., OFDMA and/or MU-MIMO) transmission **814** to the AP, in an embodiment. In an embodiment, in response to receiving a NAK data unit **812** from a client station, the AP re-transmits all of the fragments that were included in the corresponding data unit **806** to the client station. Thus, for example, in response to receiving the NAK data unit **812-2** from STA2, the AP generates a beamforming feedback data unit **816-1** to include all fragments that were included in the data unit **806-2**. Similarly, in response to receiving the NAK data unit **812-3** from STA3, the AP generates a beamforming feedback data unit **816-2** to include all fragments that were included in the data unit **806-3**. In response to correctly receiving the beamforming feedback data units **816**, the client stations STA2, STA3 generate acknowledgement data units **820** and transmit the acknowledgement data units **820** to the AP as parts of a multi-user (e.g., OFDMA and/or MU-MIMO) transmission **822** to the AP, in an embodiment.

FIG. **9** is a diagram of an example transmission sequence **900** in a WLAN, such as the WLAN **10** of FIG. **1**, according to an embodiment, in which an AP, such as the AP **14**, performs beamforming training with multiple client stations, such as multiple ones of the client stations **25**. The transmission sequence **900** is similar to the transmission sequence **800** of FIG. **8**, except that in the transmission sequence **900**, rather than using Ack data units **810** or NAK data units **812** to positively or negatively acknowledge receipt of beamforming feedback data units **806**, client stations use action block acknowledgement (Action BA) data units **910** to indicate whether or not respective fragments in the beamforming feedback data units **806** were correctly received by the client stations. An action BA data unit **910** includes an action BA frame defined by the first communication protocol for acknowledging receipt of multiple fragments (MPDUs) in an action data unit such as a beamforming feedback A-MPDU **806**, in an embodiment. In an embodiment, an action BA data unit **910** includes a bitmap, with each bit of the bitmap set to indicate whether or not a particular fragment of the corresponding beamforming training data unit **806** was correctly received by the corresponding client station. In response to receiving an action BA data unit **910** that indicates that one or more particular fragments were not correctly received by a client station, the AP re-transmits only the particular fragments to the client station, in an embodiment.

With continued reference to FIG. **8**, in an embodiment, a beamforming feedback A-MPDU **806** includes a beamforming feedback action frame that is defined, by the first communication protocol, to include a sequence of a predetermined maximum number of fragments (MPDUs). For example, an BF feedback A-MPDU **806** includes a beamforming feedback action frame defined by the first communication protocol to have at most eight fragments, with a starting sequence number of zero (0) of the first fragment and a highest sequence number of (7) of the last fragment. In an embodiment, because the action BA data unit **910** acknowledges receipt of fragments in an action frame that has at most eight fragments, with a starting sequence number of zero (0) of the first fragment, the BA data unit **910** omits a starting sequence number indication that may be included in a non-action block acknowledgement frame defined by the first communication protocol and/or a legacy communication protocol. Additionally, the bitmap included in the BA **910** is of a set size corresponding to the predetermined maximum number of fragments in the BF feedback A-MPDU **806**, in an embodiment. Thus, for example, continuing with the above example with a maximum number of eight fragments, the bitmap included in the BA data unit **910** includes exactly, or at most, eight bits, in an embodiment.

The client stations transmit the generated action BA data units **910** to the AP simultaneously as parts of a multi-user (e.g., OFDMA and/or MU-MIMO) transmission **914** to the AP, in an embodiment. In the embodiment of FIG. **9**, the action BA data unit **910-2** transmitted by the client station STA2 indicates that one or more particular fragments in the data unit **806-2** were not correctly received by the client station STA2, and the action BA data unit **910-3** transmitted by the client station STA3 indicates that one or more particular fragments in the data unit **806-3** were not correctly received by the client station STA3. In response to receiving the action BA **910-2** in acknowledgement data unit **914**, the AP generates a beamforming feedback data unit **916-1** to include the particular fragments in the beamforming data unit **806-2** that were not correctly received by the client station STA2 and to omit the fragments that were correctly received by the client station STA2, in an embodiment. Similarly, in response to receiving the action BA data unit **910-3** in acknowledgement data unit **914**, the AP generates a beamforming feedback data unit **916-2** to include the particular fragments in the beamforming data unit **806-3** that were not correctly received by the client station STA3 and to omit the fragments that were correctly received by the client station STA3, in an embodiment. The AP generates and transmits a multi-user (e.g., OFDMA and/or MU-MIMO) beamforming feedback data unit **918** and transmits the beamforming feedback data unit **918** to the client stations STA2, STA3, in an embodiment. In response to receiving the beamforming feedback data units **916**, the client stations STA2, STA3 generate action BA data units **920** and transmit action BA data units **920** to the AP as parts of a multi-user (e.g., OFDMA and/or MU-MIMO) **922** to the AP, in an embodiment.

FIG. **10** is a block diagram of an action BA frame **1000**, according to an embodiment. In an embodiment, an action BA frame **1000** is included in each of the action BA data units **910** of the transmission sequence **900** of FIG. **9**. In other embodiment, the action BA frame **1000** is included in an acknowledgement data unit different from the action BA data units **910**. The action BA frame **1000** includes a plurality of fields, including a frame control field **1002**, a duration field **1004**, a first address field (e.g., a receiver address (RA) field) **1006**, a second address field (e.g., a

transmitter address (TA) field) **1008**, a BA control field **1010**, a BA information and a frame check sequence **316**. The number of octets allocated to each of the fields of the control frame **1000**, according to an example embodiment, is indicated in FIG. **9** above the corresponding field. Other suitable numbers of octets (or bits) are allocated to at least some of the fields of the control frame **1000**, in other embodiments.

The BA information field **1012** includes a bitmap, with each bit of the bitmap corresponding to a particular fragment (MPDU) of a BA feedback A-MPDU **806** being acknowledged, in an embodiment. Thus, for example, in an embodiment in which the BA feedback A-MPDU includes a maximum number of eight fragments (MPDUs), the BA information field **1012** includes a bitmap having eight bits. Further, the BA information field **1012** omits a starting sequence number indication, in an embodiment. In an embodiment, the BA information field **1012** is an eight bit (one byte) field. In another embodiment, the information field **1012** includes a number of bits different from eight bits.

FIG. **11** is a block diagram of a BA control field **1100**, according to an embodiment. In an embodiment, the BA control field **1100** corresponds to the BA control field **1010** of the action BA frame **1000** of FIG. **10**. In another embodiment, the BA control field **1100** is included in an acknowledgement frame different from the action BA frame **1000** of FIG. **10**. The BA control field **1100** includes a plurality of subfields **1102**, including a BA Ack policy subfield **1102-1**, a multi-TID subfield **1102-2**, a compressed bitmap subfield **1102-3**, a GCR subfield **1102-4**, an action BA subfield **1102-5**, a reserved subfield **1102-6**, and a TID information subfield **1102-7**.

FIG. **12** is a flow diagram of an example method **1200** for beamforming training in a wireless communication network, according to an embodiment. In some embodiments, the method **1200** is implemented by the AP **14** (FIG. **1**). For example, in some embodiments, the network interface device **16** (e.g., the PHY processor **20** and/or the MAC processor **18**) is configured to implement the method **1200**. In other embodiments, another suitable network interface device is configured to implement the method **1200**.

At block **1202**, respective beamforming training data units are received from multiple communication devices. In an embodiment, the beamforming training data units **204** of FIG. **2** are received. In another embodiment, other suitable beamforming training data units are received. In an embodiment, the beamforming training data units are simultaneously transmitted by the multiple communication devices, for example using respective frequency portions and/or spatial streams allocated to the multiple communication devices.

At block **1204**, respective beamforming feedback data units are generated based on the respective beamforming training packets received at block **1204**. In an embodiment, the beamforming feedback data units **206** of FIG. **2** are generated. In another embodiment, the beamforming feedback data units **806** of FIG. **8** are generated. In other embodiments, other suitable beamforming feedback data units are generated.

At block **1206**, the respective beamforming feedback data units that are generated at block **1204** are transmitted to the multiple communication devices.

At least some of the various blocks, operations, and techniques described above may be implemented utilizing hardware, a processor executing firmware instructions, a processor executing software instructions, or any combination thereof. When implemented utilizing a processor

executing software or firmware instructions, the software or firmware instructions may be stored in any computer readable memory such as on a magnetic disk, an optical disk, or other storage medium, in a RAM or ROM or flash memory, processor, hard disk drive, optical disk drive, tape drive, etc. The software or firmware instructions may include machine readable instructions that, when executed by one or more processors, cause the one or more processors to perform various acts.

When implemented in hardware, the hardware may comprise one or more of discrete components, an integrated circuit, an application-specific integrated circuit (ASIC), a programmable logic device (PLD), etc.

While the present invention has been described with reference to specific examples, which are intended to be illustrative only and not to be limiting of the invention, changes, additions and/or deletions may be made to the disclosed embodiments without departing from the scope of the invention.

What is claimed is:

1. A method for beamforming training in a wireless communication network, the method comprising:

transmitting, by a first communication device, a null data packet (NDP) to a second communication device as part of a multi-user beamforming training transmission sequence, wherein the NDP i) includes a set of one or more training signals that allow the second communication device to estimate a communication channel from the first communication device to the second communication device, and ii) omits a data portion;

receiving, at the first communication device, a first packet from the second communication device responsive to transmitting the NDP, the first packet including an aggregate media access control protocol data unit (A-MPDU), the A-MPDU having a plurality of fragments of beamforming training information that was generated by the second communication device based on the set of one or more training signals included in the NDP, wherein an entirety of the beamforming training information generated by the second communication device in response to the NDP is included in the plurality of fragments, and wherein no single fragment among the plurality of fragments includes the entirety of the beamforming training information;

determining, at the first communication device, that one or more of the fragments in the plurality of fragments were not correctly received by the first communication device;

in response to determining that one or more of the fragments in the plurality of fragments were not correctly received by the first communication device, generating, by the first communication device, a bitmap to indicate a set of at least one fragment of the plurality of fragments that is to be retransmitted by the second communication device, wherein bits of the bitmap correspond to respective fragments in the plurality of fragments; and

transmitting, by the first communication device, a second packet having the bitmap to the second communication device to prompt the second communication device to retransmit the set of at least one fragment of the plurality of fragments.

2. The method of claim **1**, wherein generating the bitmap comprises:

generating a first set of one or more bits in the bitmap that correspond to one or more first fragments that are to be retransmitted to have a first value;

19

generating a second set of one or more bits in the bitmap that correspond to one or more second fragments that are not to be retransmitted to have a second value.

3. The method of claim 1, further comprising:

generating, at the first communication device, a block acknowledgement data unit to include the bitmap; and generating the second packet to include the block acknowledgement data unit.

4. The method of claim 1, further comprising:

transmitting, by the first communication device to the second communication device, a transmission that is beamformed by the first communication device based on the beamforming training information in the A-MPDU received from the second communication device.

5. The method of claim 4, wherein the transmission to the second communication device utilizes one or both of orthogonal frequency division multiple access (OFDMA) or multiple input multiple output (MU-MIMO).

6. A first wireless communication device, comprising:

a wireless network interface device having one or more integrated circuit (IC) devices configured to:

control the wireless network interface device to transmit a null data packet (NDP) to a second wireless communication device as part of a multi-user beamforming training transmission sequence, wherein the NDP i) includes a set of one or more training signals that allow the second wireless communication device to estimate a communication channel from the first communication device to the second wireless communication device, and ii) omits a data portion,

receive an aggregate media access control protocol data unit (A-MPDU) that was transmitted within a first packet by the second wireless communication device, the A-MPDU having a plurality of fragments of beamforming training information that was generated by the second wireless communication device based on the set of one or more training signals included in the NDP, wherein an entirety of the beamforming training information generated by the second wireless communication device in response to the NDP is included in the plurality of fragments, and wherein no single fragment among the plurality of fragments includes the entirety of the beamforming training information,

determine that one or more of the fragments in the plurality of fragments were not correctly received by the first communication device,

in response to determining that one or more of the fragments in the plurality of fragments were not correctly received by the first communication device, generate a bitmap to indicate a set of at least one fragment of the plurality of fragments that is to be retransmitted by the second wireless communication device, wherein bits of the bitmap correspond to respective fragments in the plurality of fragments, and

20

control the wireless network interface device to transmit a second packet having the bitmap to the second wireless communication device to prompt the second wireless communication device to retransmit the set of at least one fragment of the plurality of fragments.

7. The first wireless communication device of claim 6, wherein the one or more IC devices are configured to:

generate a first set of one or more bits in the bitmap that correspond to one or more first fragments that are to be retransmitted to have a first value;

generate a second set of one or more bits in the bitmap that correspond to one or more second fragments that are not to be retransmitted to have a second value.

8. The first wireless communication device of claim 6, wherein the one or more IC devices are configured to:

generate a block acknowledgement data unit to include the bitmap; and

generate the second packet to include the block acknowledgement data unit.

9. The first wireless communication device of claim 6, wherein the one or more IC devices are configured to:

control the wireless network interface device to transmit, to the second wireless communication device, a transmission that is beamformed by the first communication device based on the beamforming training information in the A-MPDU received from the second wireless communication device.

10. The first wireless communication device of claim 9, wherein the one or more IC devices are configured to:

utilizes one or both of orthogonal frequency division multiple access (OFDMA) or multiple input multiple output (MU-MIMO) in connection with the transmission to the second wireless communication device.

11. The first communication device of claim 6, wherein the wireless network interface device further comprises one or more transceivers implemented using the one or more IC devices.

12. The first communication device of claim 11, further comprising:

one or more antennas coupled to the one or more transceivers.

13. The first communication device of claim 11, wherein the wireless network interface device further comprises:

a media access control (MAC) processor implemented using the one or more IC devices; and

a physical layer (PHY) processor implemented using the one or more IC devices, the PHY processor being communicatively coupled to the MAC processor.

14. The first communication device of claim 13, wherein the one or more transceivers are included in the PHY processor.

15. The first communication device of claim 6, further comprising:

a host processor communicatively coupled to the wireless network interface device.

* * * * *