



US011787507B2

(12) **United States Patent**
Ho

(10) **Patent No.:** **US 11,787,507 B2**
(45) **Date of Patent:** **Oct. 17, 2023**

(54) **SYSTEM FOR A BICYCLE**

(71) Applicant: **SRAM, LLC**, Chicago, IL (US)
(72) Inventor: **Alexander Kon-I Ho**, Chicago, IL (US)
(73) Assignee: **SRAM, LLC**, Chicago, IL (US)
(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 59 days.

(21) Appl. No.: **17/333,479**

(22) Filed: **May 28, 2021**

(65) **Prior Publication Data**
US 2021/0284284 A1 Sep. 16, 2021

Related U.S. Application Data
(63) Continuation of application No. 16/268,026, filed on Feb. 5, 2019, now Pat. No. 11,021,214.

(51) **Int. Cl.**
B62M 25/08 (2006.01)
B62L 3/02 (2006.01)
B62K 23/06 (2006.01)
H04W 76/14 (2018.01)
H04W 8/00 (2009.01)
B62J 1/08 (2006.01)

(52) **U.S. Cl.**
CPC **B62M 25/08** (2013.01); **B62J 1/08** (2013.01); **B62K 23/06** (2013.01); **B62L 3/02** (2013.01); **H04W 8/005** (2013.01); **H04W 76/14** (2018.02); **B62J 2001/085** (2013.01)

(58) **Field of Classification Search**
CPC B62M 25/08; B62M 9/122; B62M 9/132; B62J 1/08; B62J 2001/085; B62J 45/00; B62K 23/06; B62L 3/02; H04W 8/005; H04W 76/14

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

8,655,548	B2	2/2014	Ichida et al.	
9,229,712	B2	1/2016	Takamoto et al.	
9,491,788	B1 *	11/2016	Kasai	H04W 4/80
2016/0152302	A1 *	6/2016	Nishino	B62M 25/08 701/2
2016/0257370	A1	9/2016	Hashimoto et al.	
2017/0008465	A1 *	1/2017	Kasai	B62M 9/122
2017/0029057	A1 *	2/2017	Kato	B62J 6/16
2017/0043828	A1 *	2/2017	Mohamed	E05B 45/06

(Continued)

FOREIGN PATENT DOCUMENTS

CN	1524762	9/2004
CN	103723238	4/2014
CN	106256678	12/2016


(Continued)

Primary Examiner — Mary Cheung

(57) **ABSTRACT**

A bicycle system includes controller devices. Each controller device includes at least one respective input element configured to receive input from a user. The system includes operation-enacting devices. Each operation-enacting device is configured to enact at least one respective operation on the bicycle. The system includes a network coordinator device configured to (i) establish a wireless network for communications between the network coordinator device, the controller devices, and the operation-enacting devices, and (ii) reset the controller devices and operation-enacting device before pairing the controller devices and operation-enacting devices to the wireless network.

15 Claims, 15 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2019/0002053 A1 1/2019 Kakinoki
2019/0246437 A1* 8/2019 Chuang H04W 76/11

FOREIGN PATENT DOCUMENTS

CN	106394801	2/2017	
CN	106467159	3/2017	
CN	107600250	1/2018	
CN	108284912	7/2018	
CN	207985025 U *	10/2018	
EP	2719616	4/2014	
KR	2020078035 A *	7/2020 G06F 13/14
TW	201138374	11/2011	

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 1E




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 3




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 5




FIG. 6




FIG. 7

1

SYSTEM FOR A BICYCLE

This application is a continuation of U.S. patent application Ser. No. 16/268,026, filed Feb. 5, 2019, the contents of which are herein incorporated in their entirety.

BACKGROUND

A bicycle includes various components that allow a user to control the operation of the bicycle. For instance, the bicycle may include a drivetrain where one or more gears can be selectably engaged with a drive chain to modify pedaling cadence and resistance. Correspondingly, the bicycle may include controller devices that receive input from the user to cause the drive chain to engage different gears.

SUMMARY

According to aspects of the present disclosure, embodiments provide systems, devices and methods for controlling components on a bicycle. According to an example embodiment, a system for a bicycle includes a plurality of controller devices, wherein each controller device includes at least one respective input element configured to receive input from a user and transmits a signal indicating input received by the at least one respective input element. The system includes a plurality of operation-enacting devices, wherein each operation-enacting device is configured to enact at least one respective operation on the bicycle in response to receiving the signal transmitted from the controller device. The system includes a network coordinator device configured to (i) establish a pairing session to pair the network coordinator, the controller devices and the operation-enacting devices to a wireless network that enables communications between the network coordinator device, the controller devices, and the operation-enacting devices, and (ii) reset the controller devices and operation-enacting device before pairing the controller devices and operation-enacting devices to the wireless network.

According to another example embodiment, a network coordinator device for a bicycle includes a first communication interface configured to communicate wirelessly with a plurality of controller devices and a plurality of operation-enacting devices. Each controller device includes at least one respective input element configured to receive input from a user and transmit a signal indicating input received by the at least one respective input element, and each operation-enacting device is configured to enact at least one respective operation on the bicycle in response to receiving the signal transmitted from the controller device. The network coordinator device includes one or more processors configured to execute program instructions stored on computer-readable media, which when executed cause the one or more processors to: (i) establish, via the first communication interface, a pairing session that allows the controller devices and the operation-enacting devices to be paired to a wireless network, and (ii) reset the controller devices and operation-enacting device before pairing the controller devices and operation-enacting devices to the wireless network.

BRIEF DESCRIPTION OF DRAWINGS

FIG. 1A illustrates a right-side view of an example road bicycle that can implement aspects of the present disclosure.

2

FIG. 1B illustrates a schematic diagram of a handlebar assembly of the example road bicycle shown in FIG. 1A and other components coupled to the handlebar assembly.

FIG. 1C illustrates a side view of a front derailleur of the example road bicycle shown in FIG. 1A.

FIG. 1D illustrates a side view of a rear derailleur of the example road bicycle shown in FIG. 1A.

FIG. 1E illustrates a side view of a right controller device of the example road bicycle shown in FIG. 1A coupled to a right drop bar.

FIG. 2A illustrates a right-side view of an example mountain bicycle that can implement aspects of the present disclosure.

FIG. 2B illustrates a schematic diagram of a handlebar assembly of the example mountain bicycle shown in FIG. 2A and other components coupled to the handlebar assembly.

FIG. 2C illustrates a side view of a seat post assembly, with a saddle installed thereon, of the example mountain bicycle shown in FIG. 2A.

FIG. 3 illustrates an example system for controlling different combinations of operation-enacting devices on a bicycle, according to aspects of the present disclosure.

FIG. 4A illustrates an example scenario where operation-enacting devices respond to signals from controller devices according to a first set of assignments, according to aspects of the present disclosure.

FIG. 4B illustrates an example scenario where operation-enacting devices respond to signals from controller devices according to a second set of assignments, according to aspects of the present disclosure.

FIG. 4C illustrates an example scenario where operation-enacting devices respond to signals from controller devices according to a third set of assignments, according to aspects of the present disclosure.

FIG. 5 illustrates a flow chart of an embodiment for a method of establishing a wireless network between controller devices and operation-enacting devices of a bicycle.

FIG. 6 illustrates a flow chart of an embodiment for a method of method for controlling operation-enacting devices of a bicycle.

FIG. 7 illustrates a flow chart of an embodiment for a method of modifying the default or current set of assignments of a bicycle.

Other aspects and advantages of the embodiments disclosed herein will become apparent upon consideration of the following detailed description, wherein similar or identical structures have similar reference numerals. Various embodiments of the invention will be described herein with reference to the drawings. It will be understood that the drawings and the description set out herein are provided for illustration only and do not limit the invention as defined by the claims appended hereto and any and all their equivalents.

DETAILED DESCRIPTION

According to aspects of the present disclosure, embodiments provide systems, devices and methods for controlling components on a bicycle. The embodiments employ a plurality of controller devices that receive input from a user to control operation-enacting devices on the bicycle. Operation-enacting devices generally include at least one movable component configured to modify an operative state of the bicycle. The controller devices and the operation-enacting devices are paired to a wireless network. When a particular controller device receives an input from the user, the particular controller device sends a corresponding signal to the

operation-enacting devices paired to the network. Embodiments employ a set of assignments to determine which, if any, of the operation-enacting devices responds to the signal from the particular controller device. Advantageously, the set of assignments can be modified by the user according to the user's preferences. In other words, the embodiments provide a reconfigurable control system for the components of the bicycle.

Although the ability to reconfigure the control system may be a desirable feature, there may be concern over whether unknown devices can access and make unwanted modifications to the control system over the wireless network. The embodiments, however, can secure the control system against such access by unknown devices. According to one approach, the embodiments initiate a pairing session that allows the user to select controller devices and operation-enacting devices for the wireless network. Once the pairing session is complete, the roster of devices paired to the network is fixed and unchangeable, even though the assignments between the controller devices and the operation-enacting devices already on the network can still be changed by the user. As such, unknown devices cannot join the wireless network and interfere with the control system. According to another approach, the embodiments may not allow duplicate device types to be paired to the wireless network, so that an unknown device cannot imitate another device type that has already been selected for pairing. According to yet another approach, the embodiments may only permit each operation enacted by an operation-enacting device to occur in response to the signals from a single assigned controller device or a single assigned particular combination of controller devices, thereby reducing the likelihood of an unwanted response by an operation-enacting device to a signal from an unknown device. Moreover, the embodiments may employ a proprietary network protocol to enhance security by limiting access to the wireless network to devices that can operate under the protocol.

FIG. 1A illustrates a right side view of an example road bicycle 100. The bicycle 100 includes a frame 102, a front wheel 104, a rear wheel 106, and a drivetrain 108. The front wheel 104 and the rear wheel 106 are rotatably coupled to the frame 102. The bicycle includes a front brake 110 for braking the front wheel 104 and a rear brake 112 for braking the rear wheel 106. To allow a user to steer the bicycle 100, the bicycle 100 includes a handlebar assembly 114 attached to the frame 102.

FIG. 1B illustrates a schematic diagram depicting the handlebar assembly 114 and other components coupled to the handlebar assembly 114. As shown in FIGS. 1A and/or 1B, the handlebar assembly 114 includes a right drop bar 114a and a left drop bar 114b to accommodate the left and right hands of the user, respectively. Additionally, the bicycle 100 includes a first or right controller device 120 coupled to the right drop bar 114a. The first controller device 120 includes a first or right brake lever 116 to allow the user to operate the rear brake 112. Correspondingly, the bicycle 100 includes a second or left controller device 122 coupled to the left drop bar 114b. The second controller device 122 includes a second or left brake lever 118 to allow the user to operate the front brake 110.

As shown in FIGS. 1A, 1C and 1D, the drivetrain 108 includes a drive chain 108a, a front crank 108b, front chainrings 108c, a front gear changer such as an electromechanical front derailleur 108d, rear sprockets 108e, and a rear gear changer such as an electromechanical rear derailleur 108f. The front chainrings 108c are coupled to the front crank 108b. The diameters and number of teeth on the front

sprockets 108e may differ from each other. The rear sprockets 108e are coaxially mounted to the rear wheel 106. The diameters and the numbers of teeth on the rear sprockets 108e may gradually decrease from left to right. Alternatively, the diameters and the numbers of teeth on the rear sprockets 108e may gradually decrease from right to left. The chain 108a engages a selected chainring 108c and a selected sprocket 108e.

To drive the bicycle 100, the user can pedal to rotate the front crank 108b relative to the frame 102. Rotation of the front crank 108b causes the selected chainring 108c to rotate and the chain 108a to move through the drivetrain 108. Movement of the chain 108a causes corresponding rotation of the selected sprocket 108e and thus the rear wheel 106. Rotation of the rear wheel 106 against the ground may propel the bicycle 100 in a forward direction. The front and/or forward orientation and movement of the bicycle 100 is indicated by the direction of arrow "A." Further, other terms relating to direction may be used herein. For example, the "inboard" and "outboard," and "left" and "right" may be used. The terms "right" and "left," and "inboard" and "outboard" describe a position between parts or items and a vertical plane substantially bisecting the bicycle or a direction toward or away from the vertical plane substantially bisecting the bicycle. Moreover, terms such as "front" and "rear" referred to bicycle mechanisms conventionally mounted to the bicycle and with the bicycle oriented in the forward direction.

The selected chainring 108c and the selected sprocket 108e, in combination, determine a gear ratio for driving the bicycle 100. Operation of the front derailleur 108d allows the user to change the selected chainring 108c engaged by the chain 108a. In particular, the front derailleur 108d can be actuated to shift the chain 108a left or right from one chainring 108c to the other. The front derailleur 108d is shown as a wireless electrically-actuated front derailleur mounted to the frame 102. The front derailleur 108d may include a base member 108g mounted to the bicycle frame 102 and a chain guide assembly 108h or cage movably connected to the base member 108g by a front linkage 108i in the form of a parallelogram. A front power supply 108j, in this embodiment a removable battery, may be mounted on the front derailleur 108d. The front power supply 108j may supply power to a front motor unit 108k. The front motor unit 108k is configured to supply torque to the components of the front derailleur 108d to move the chain guide assembly 108h relative to the front base member 108g such that the front derailleur 108d may shift the chain 108a between the front sprockets 108c.

Meanwhile, operation of the rear derailleur 108f allows the user to change the selected sprocket 108e engaged by the chain 108a. In particular, the rear derailleur 108f can be actuated to shift the chain 108a left or right from one sprocket 108e to another. The rear derailleur 108f is shown as a wireless electrically-actuated rear derailleur mounted to the frame 102. The rear derailleur may include a base member 1081 (e.g., a b-knuckle) that is mounted to the bicycle frame 102. A linkage 108m may include two links 108n that are pivotally connected to the base member 1081. A movable member 108o (e.g., a p-knuckle) may be connected to the linkage 108m. A chain guide assembly 108q or cage may be configured to engage and maintain tension in the chain 108a and may be pivotally connected to a part of the movable member 108o.

A motor unit 108r and rear power supply 108s, in this embodiment a removable battery, are disposed on the rear derailleur 108f. The battery 108s supplies power to the

5

motor unit **108r**. In this embodiment, the motor unit **108r** is disposed in the movable member **1080**. Alternatively, the motor unit **108r** may be disposed in one of the links **108n** or in the base member **1081**. The motor unit **108r** may include a motor and a gear transmission. The motor unit **108r** may be coupled with the linkage **108m** to laterally move the cage **108q** and thus shift the chain **108a** among the rear sprockets **108e**.

Looking to FIGS. 1A, 1B and 1E, to allow the user to operate the front derailleur **108d** or the rear derailleur **108f**, the first and second controller devices **120**, **122** include first and second electrical switches **120c**, **122c**, that are actuated by first and second input elements, in this embodiment first and second shift levers **120a**, **122a**, respectively. The first shift lever **120a** is configured to receive a right input from the right hand of the user and actuate the first electrical switch **120c**. The second shift lever **122a** configured to receive a left input from the left hand of the user and actuate the second electrical switch **122c**. The first shift lever **120a** may be positioned behind to the first brake lever **116**, while the second shift lever **122a** may be positioned behind to the second brake lever **118**.

To provide the right input to the first shift lever **120a**, the user can manually apply pressure on the right side of the first shift lever **120a**. In response, the first shift lever **120a** may pivot about a first shift lever axis **L1** from an initial rest position to a shift actuation position. The first shift lever **120a** may be biased with a spring or the like so that when the manual pressure is no longer applied by the user, the first shift lever **120a** returns to the initial rest position. Similarly, to provide the left input to the second shift lever **122a**, the user can manually apply pressure on the left side of the second shift lever **122a**. In response, the second shift lever **122a** may pivot about a second shift lever axis **L2** (not shown) from an initial rest position to a shift actuation position. The second shift lever **122a** may be biased with a spring or the like so that when the manual pressure is no longer applied by the user, the second shift lever **122a** returns to the left starting position.

The first and second controller devices **120**, **122** include first and second controller processors **120e**, **122e**, which electronically process the manual input received by the first shift lever **120a** and the second shift lever **122a**, respectively. In particular, the right input triggers a first controller communication interface **120d** to wirelessly send a first shift signal **120b**, and left input triggers a second controller communication interface **122d** to wirelessly send a second shift signal **122b**. Correspondingly, the front derailleur **108d** and the rear derailleur **108f** include communication interfaces and processors that are configured to receive and electronically process the first shift signal **120b** and/or the second shift signal **122b** to determine a designated response.

In a first scenario, the user provides the right input via the first shift lever **120a** but does not provide the left input via the second shift lever **122a**. In response, the first controller device **120** sends the first shift signal **120b**, while the left controller device **122** sends no signal. When the rear derailleur **108f** receives the first shift signal **120b** with no second shift signal **122b**, the rear derailleur **108f** shifts the chain **108a** to engage the next smaller sprocket **108e** to the right or performs a downshift. Meanwhile, when the front derailleur **108d** receives the first shift signal **120b** with no second shift signal **122b**, the front derailleur **108d** remains idle.

In a second scenario, the user provides the left input via the second shift lever **122a** but does not provide the right input via the right shift lever **120a**. In response, the second controller device **122** sends the second shift signal **122b**,

6

while the first controller device **120** sends no signal. When the rear derailleur **108f** receives the second shift signal **122b** with no first shift signal **120b**, the rear derailleur **108f** shifts the chain **108a** to engage the next larger sprocket **108e** to the left or performs an upshift. Meanwhile, when the front derailleur **108d** receives the second shift signal **122b** with no first shift signal **120b**, the front derailleur **108d** remains idle.

In a third scenario, the user simultaneously provides the right input via the first shift lever **120a** and the left input via the second shift lever **122a**. In response, the first controller device **120** sends the first shift signal **120b**, and the second controller device **122** sends the second shift signal **122b**. When the rear derailleur **108f** receives the first shift signal **120b** and the second shift signal **122b** simultaneously or within a certain time period, the rear derailleur **108f** remains idle. Meanwhile, when the front derailleur **108d** receives the first shift signal **120b** and the second shift signal **122b** simultaneously or within a certain time period, the front derailleur **108d** shifts the chain **108a** left or right to engage a different chainring **108c**. In some cases, the drivetrain **108** includes only two chainrings **108c**, so the simultaneous right input and left input causes the chain **108a** to alternate between the two chainrings **108c**.

In some embodiments, the user can manually apply pressure to the first shift lever **120a** and/or the second shift lever **122a** for varying amounts of time. For instance, without applying pressure to the second shift lever **122a**, the user may apply continuous pressure to keep the first shift lever **120a** in the left final position for a period that exceeds a threshold amount of time, e.g., approximately one second. In response, the first controller device **120** sends the first shift signal **120b** for a corresponding amount of time, i.e., until the user releases the pressure on the first shift lever **120a**. When the rear derailleur **108f** receives the first shift signal **120b**, the rear derailleur **108f** determines that the first shift signal **120b** exceeds a threshold amount of time. In response, rather than merely shifting the chain **108a** to engage the next sprocket **108e** to the right, the rear derailleur **108f** shifts the chain **108a** repeatedly over multiple sprockets **108e** to the right until the user releases the pressure on the first shift lever **120a** and the first shift signal **120b** ceases, or until the chain **108a** reaches the right-most sprocket **108e**. Alternatively, to shift the chain **108a** repeatedly over multiple sprockets **108e** to the left, the user may apply continuous pressure to the left shift lever **122a** for a period that exceeds the threshold amount of time.

As shown in FIGS. 1A-B, the first controller device **120** and the second controller device **122** employ the first shift lever **120a** and the second shift lever **122a** as respective input elements to generate corresponding wireless shift signals **120b**, **122b** to actuate the front derailleur **108d** and the rear derailleur **108f**. Alternative embodiments, however, may include controller devices with different configurations to control a front derailleur and/or a rear derailleur. For instance, a bicycle may include aerobars with pushbuttons instead of drop bars with shift levers, where the pushbuttons act as input elements that can be pressed by the user to generate wireless signals which can be received and processed by the front derailleur and the rear derailleur. Also, while some controller devices may be coupled to handlebar assemblies, other controller devices may be coupled to other areas of a bicycle, such as locations throughout the frame. Furthermore, other types of controller devices are contemplated. For instance, a unified shifter device may be employed, where the user can press one or more pushbuttons on a mounted box to send signals that control the front

derailleur and/or the rear derailleur. Alternatively, a pedal sensor may be employed to receive input from the user via the user's pedaling action and the front derailleur and/or the rear derailleur may respond to a signal from the pedal sensor, e.g., select gears to maintain a desired cadence or pedal resistance.

While the example bicycle **100** shown in FIGS. 1A-B is a road bicycle, aspects of the present disclosure may be implemented with bicycles of any type. For instance, FIG. 2A illustrates a right side view of an example mountain bicycle **200**. The bicycle **200** includes a frame **202**, a front wheel **204**, a rear wheel **206**, a drivetrain **208**, front disk brakes **210**, and rear disk brakes **212**. The drivetrain **208** includes a chain **208a**, a front crank **208b**, a front chainring **208c**, rear sprockets **208e**, and a rear derailleur **208f**, which operate in a manner similar to the corresponding components of the drivetrain **108** above.

In contrast to the bicycle **100**, the bicycle **200** includes other operating-enacting devices such as a height-adjustable seat post assembly **226** and front and rear suspension systems **230**, **232**. In FIGS. 2A and 2C, the seat post assembly is shown as a wireless, electrically-actuated seat post assembly **226** that allows the position of a seat **228** to be dynamically adjusted. For instance, the adjustable seat post **226** may include an operable valve (not shown) that allows the seat **228** to be dropped to a lower height during a ride to change the position of the user relative to the frame **202** and achieve better handling. The seat post assembly **226** includes a first or lower tube **226a** and a second or upper tube **226b**. The two tubes **226a**, **226b** are movable relative to each other to establish a height of the seat **228** relative to the frame **202**. A head **226c** is fixed to a top of the second tube **226b**. A seat post motor unit **226d** is mounted to the head **226c** and a power supply **226e**, in this embodiment a removable battery, is attached to the motor unit **226d**. The motor unit **226d** may include a motor and a gear transmission. The seat post power supply **226e** may supply power to the seat post motor unit **226d**. The seat post motor unit **226d** is configured to supply torque to the components of the seat post assembly **226** to open and close the operable valve.

The front suspension system is shown as a wireless, electrically-actuated front suspension system **230** that allows the suspension characteristics at the front wheel **204** to be dynamically adjusted. Furthermore, the rear suspension system is shown as a wireless, electrically-actuated rear suspension system **232** that allows the suspension characteristics at the rear wheel **206** to be dynamically adjusted. The front and rear suspension systems **230**, **232** may further include power supplies such as batteries that supply power to front and rear suspension motor units, respectively. The motor units may be configured to supply torque to the components of the suspension systems to open and close one or more valves to change various suspension characteristics.

Looking to FIGS. 2A and 2B, the bicycle **200** includes a first or right controller device **220** and a second or left controller device **222**. The first and second controller device includes first and second electrical switches **220c**, **222c** that are actuated by first and second input elements, in this embodiment, first and second shift levers **220a**, **222a**, respectively. The handlebar assembly **214** includes a flat bar or a riser bar instead of drop bars. As such, the first controller device **220** is coupled to a right side of the flat or riser bar, and the second controller device **222** is coupled to a left side of the flat or riser bar. Additionally, the bicycle **200** may include a seat post controller device **234** and front and rear suspension controller devices **236**, **238** coupled to the handlebar assembly **214**.

The user can operate the first shift lever **220a** and/or the second shift lever **222a** as described above to generate a first shift signal **220b** and/or a second shift signal **222b**, respectively. Similar to the bicycle **100**, the first shift signal **220b** and/or the second shift signal **222b** can be employed to control the rear derailleur **208f**. To allow the user to adjust the height of the seat post assembly **226**, the seat post controller device **234** includes a seat post electrical switch **234c** that is actuated by a seat post input element **234c** such as a lever or button.

To allow the user to adjust the characteristics of the front and rear suspension systems **230**, **232**, the front and rear suspension controller devices **236**, **238** include front and rear suspension electrical switches **236c**, **238c** that are actuated by suspension input elements **236a**, **238a** such as levers or buttons. Alternatively, the adjustable seat post assembly **226**, the adjustable front suspension system **230**, and the adjustable rear suspension system **232** may also be configured to receive the first shift signal **220b** and/or the second shift signal **222b**, so that these devices can also be controlled by operation of the first shift lever **220a** and/or the second shift lever **222a**.

The seat post and front and rear suspension controller devices **234**, **236**, **238** include processors **234e**, **236e**, **238e**, respectively, which electronically process the manual input received by the seat post and front and rear suspension input elements **234a**, **236a**, **238a**, respectively. The seat post input triggers a seat post controller communication interface **234d** to wirelessly send a seat post signal **234b**. The front and rear suspension inputs trigger front and rear controller communication interfaces **236d**, **238d** to wirelessly send front and rear suspension signals **236b**, **238b**. Correspondingly, the seat post assembly **226** includes a communication interface and a processor that is configured to receive and electrically process the seat post signal **234b** to determine a designated response. The front and rear suspensions include communication interfaces and processors that are configured to receive and electronically process the front and rear suspension signals, respectively, to determine a designated response.

FIGS. 1A-E and 2A-C illustrate how various controller devices can be employed to wirelessly communicate control signals to different combinations of operation-enacting devices. The signals from the controller devices may be communicated wirelessly using any technique, protocol, or standard. For instance, Institute of Electrical and Electronics Engineers ("IEEE") 802.11 standards, IEEE 802.15.1 or BLUETOOTH® standards, and/or ANT™ or ANT+™ standards may be used. In some embodiments, however, control signals may be communicated wirelessly over a proprietary protocol, such as one that operates on top of the physical layer of the IEEE 802.15.4 wireless protocol. Advantageously, the use of a proprietary protocol can enhance security by limiting access to the wireless network to devices specifically configured to communicate under the proprietary protocol. This may thereby reduce the likelihood of unwanted interference from other wireless devices. The bicycle **100** includes a network coordinator device **124** that may be configured to establish and manage the wireless communications between the various devices as described in further detail below. Similarly, the bicycle **200** includes a network coordinator device **224**. Alternatively, one of the controller devices or the operation-enacting devices on the bicycle may be the network coordinator.

FIG. 3 illustrates an example system **300** for controlling different combinations of operation-enacting devices on a bicycle. The system **300** includes a plurality of controller

devices **302**. Each controller device **302** includes at least one respective input element **302a** configured to receive input from a user. For instance, as described above, the controller devices **302** may include a right controller device and a left controller device coupled to a handlebar assembly, where respective shifter levers act as input elements **302a**. In general, input elements **302a** may include any variety of shifter, pushbutton, clicker, switch, other toggled device, sensor (e.g., peddling sensor, etc.), or the like. A single controller device **302** may also include more than one input element **302a**, (e.g., two shifter levers, a plurality of push-buttons, etc.).

The system **300** also includes a plurality of operation-enacting devices **304**, where each operation-enacting device **304** is configured to enact at least one respective operation on the bicycle. For instance, the operation-enacting devices **304** may include a front derailleur, a rear derailleur, a height-adjustable seat post assembly, a front suspension system, and/or a rear suspension system as described above. Each operation-enacting device **304** may include at least one movable component **311** configured to modify an operative state of the bicycle. In some cases, an operation-enacting device **304** may act on more than one component of the bicycle in a single operation. In other cases, a single operation may include more than one act on one or more components of the bicycle. In yet other cases, the operation may include a physical action and a wireless action, where the wireless action sends wireless signals to cause further action by other cooperative device(s).

The system **300** also includes a network coordinator device **306**. The network coordinator device **306** includes a first communication interface **306a** configured to communicate wirelessly with the controller devices **302** and the operation-enacting devices **304**. Using the first communication interface **306a**, the network coordinator device **306** can establish a wireless network **308** that enables communications between the network coordinator device **306**, the controller devices **302**, and the operation-enacting devices **304**. Correspondingly, each controller device **302** includes a communication interface **302c** and each operation-enacting device **304** includes a communication interface **304a** for communicating with other devices, i.e., receiving and transmitting data/signals, on the wireless network **308**. Although the network coordinator device **306** may appear in FIG. 3 as a separate device, the features of a network coordinator device **306** in alternative embodiments may be provided by one or more of the other controller devices **302** and/or operation-enacting devices **304** such as a rear derailleur.

FIG. 5 illustrates a method for establishing a wireless network between a network coordinator device, controller devices and operation-enacting devices and establishing a set of default assignments that determine how the operating-enacting devices enact the operations in response to the signals received from the controller devices. The acts of the method presented below are intended to be illustrative. In some embodiment, the method may be accomplished with one or more additional acts not described, and/or without one or more of the acts discussed. Additionally, the order in which the acts of the method are illustrated in FIG. 5 and described below is not intended to be limiting.

In some embodiments, the method may be implemented in one or more processing device (e.g. digital processor, an analog processor, a digital circuit designed to process information, an analog-circuit designed to process information, a state machine, and/or other mechanisms for electronically processing information). The one or more processing devices include one or more devices executing some or all

the acts of the method in response to instructions stored electronically on an electronic storage medium. The one or more processing devices configured through hardware, firmware, and/or software to be specifically designed for execution of one or more of the acts of the method.

The network coordinator device **306** is configured to initiate a new pairing session to pair the controller devices **302**, and the operation-enacting devices **304** to the wireless network **308**. In act **502**, the user selects the network coordinator device **306** from among the controller devices **302** and operation-enacting devices **304** by operating a pairing input element **306c** such as a pushbutton, switch, or the like that prompts the selected network coordinator device **306** to initiate a new pairing session. While in the pairing mode, in act **504**, the network coordinator device **306** scans for pairing signals from other devices. When the new pairing session is active, the user can selectively pair a controller device **302** or an operation-enacting device **304** to the wireless network **308** by operating a corresponding pairing input element **302d**, **304b** such as a pushbutton, switch, or the like on the given device to be placed into pairing mode. While in pairing mode, in act **506**, the selected device transmits a pairing signal to the network coordinator device **306** in response to operation of the pairing input element **302d**, **304b** of the selected device. In act **508**, the pairing signal allows the network coordinator device **306** to recognize the given device and permit the given device to join the wireless network **308**. If a proprietary network protocol is employed for the wireless network **308**, only devices configured to communicate according to the proprietary network protocol can be recognized by the network coordinator device **306** and paired.

In some embodiments, in act **506**, the pairing signal from a given device provides a respective device type identification, and the network coordinator device **306** only pairs devices having different respective device type identifications in act **510**. For instance, the pairing signal may identify a given device to be a rear derailleur. By limiting the pairings to devices with different respective device type identifications, the system **300** will not include more than one rear derailleur. As such, an unknown device cannot imitate another device type that has already been selected for pairing.

In act **512**, the user can manually end the pairing session, e.g., by operating the pairing input element **306c** on the network coordinator device **306**. Alternatively, the network coordinator device **306** may automatically end the pairing session after a set time period has elapsed.

In act **514**, a roster **310** is defined by the controller devices **302** and the operation-enacting devices **304** that have been paired to the wireless network **308** at the end of the pairing session. To enhance the integrity of the system **300**, no other devices can be paired to the wireless network **308** after the pairing session has ended. By fixing the roster **310**, the system **300** only includes the devices **302**, **304** selected by the user. This blocks unauthorized devices from joining the wireless network **308** and maliciously or accidentally interfering with the operation of the devices **302**, **304** actually selected by the user.

In act **516**, when the pairing session ends, the network coordinator device **306** is configured to transmit, to the operation-enacting devices **304**, the roster **310** identifying the controller devices **302** and the operation-enacting devices **304** paired to the wireless network **308**. In act **518**, the operation-enacting devices **304** are configured to determine, based on the roster **310** received from the network

coordinator device **306**, how to enact operations in response to the signals **302b** received from the controller devices **302**.

If desired, a new pairing session can be initiated with the network coordinator device **306** to reset the roster **310** and to pair a different set of devices **302, 304**. Upon the end of the new pairing session, this different set of devices defines a new roster **310**. The new pairing session unpairs and resets all devices that may have been added to the wireless network **308** in a previous pairing session. In general, paired devices **302, 304** cannot be removed from the roster **310** and new devices cannot be added to the roster **310** until a new pairing session is initiated. A device paired to the wireless network **308** can be paired into another wireless network (e.g., on another bicycle system), but that device cannot rejoin the prior wireless network **308** because it is reset when paired to the other wireless network.

The controller devices **302** are configured to transmit, to the operation-enacting devices **304**, signals **302b** indicating input received by the input elements **302a** of the controller devices **302**. For instance, the first controller device **120** and the second controller device **122** may wirelessly transmit a first shift signal **120b** and a second shift signal **120a** as described above to indicate input received by the first shift lever **120a** and the second shift lever **122a**, respectively.

The operation-enacting devices **304** are configured to process a default set of assignments **312** based on the roster **310** to determine how the operation-enacting devices **304** enact the operations responsive to the signals **302b**. The default set of assignments **312** can be transmitted to the each operation-enacting device **304** by the network coordinator device **306**, and/or stored locally on each operation-enacting device **304**.

For example, after a pairing session is completed, the roster **310** may include a right controller device with a right shift lever, a left controller device with a left shift lever, a front derailleur, and a rear derailleur. The default set of assignments **312** controlling the operation of the operation-enacting devices **304** is determined according to the particular set of devices in the roster **310**. For instance, the default set of assignments **312** may provide that with the example roster **310** above: (i) the rear derailleur shifts the chain to a sprocket on the left in response to signals from the left controller device (with no signals from the right controller device); (ii) the rear derailleur shifts the chain to a sprocket on the right in response to signals from the right controller device (with no signals from the left controller device); and (iii) the front derailleur shifts the chain to an alternate chainring in response to simultaneous signals from the right controller device and the left controller device. If the roster **310** includes a different set of devices, the default set of assignments **312** may be different. For example, if the roster **310** includes a height-adjustable seat post assembly and does not include a front derailleur, the seat post assembly lowers the seat in response to the simultaneous signals from the right and left controller devices.

A paired device is considered to remain in the wireless network **308** and the roster **310** does not change even if the paired device becomes inactive or unavailable (e.g., if it loses power or is re-paired to another wireless network).

Each operation enacted by the corresponding operation-enacting device **304** occurs only in response to the signals **302b** from a single assigned controller device **302** or a single assigned combination of controller devices **302** as described below. For instance, an operation may involve shifting the chain to a sprocket on the left or inboard with the rear derailleur and such operation only occurs in response to signals from the left controller device. Advantageously, this

reduces the likelihood of an unwanted response by an operation-enacting device **304** to a signal from an unknown device.

When a combination of more than one controller device is employed to produce simultaneous signals, e.g., simultaneous signals from the right controller device and the left controller device, the combination of controller devices may be considered to be a single virtual controller device. Thus, an operation may involve the front derailleur shifting the chain to an alternate chainring, and such operation only occurs in response to signals from the single virtual controller device defined by the combination of the right controller device and the left controller device. Alternatively, a single virtual device may be provided by simultaneous signals from two or more inputs on a single device, e.g., simultaneous presses of pushbuttons on a single unified shifter device.

FIG. 6 illustrates a method for controlling the operation-enacting devices. Once the roster **310** is established and the default set of assignments **312** is determined according to the roster **310**, in act **602**, each operation-enacting device **304** can receive, via the wireless network **308**, the signals **302b** from the controller devices **302**. In act **604**, each operation-enacting device **304** can identify the one or more signals **302b** from an assigned controller device **302** or from an assigned combination of controller devices. In act **606**, each operation-enacting device enacts the operation in response to the one or more signals **302b** from the assigned controller device **302** or assigned combination of controller devices **302**.

Although the default set of assignments **312** may provide an effective approach for determining how the operation-enacting devices **304** should respond to the signals **302b** from the controller devices **302**, the user may prefer to use a modified set of assignments **312'**. For instance, the modified set of assignments **312'** may provide that with the example roster **310** above: (i) the rear derailleur shift the chain to the sprocket on the left in response to signals from the right controller device that do not exceed a threshold amount of time (without signals from the left controller device); (ii) the rear derailleur shift the chain to the sprocket on the right in response to signals from the right controller device that meet or exceed the threshold amount of time (without signals from the left controller device); and (iii) the front derailleur shift the chain to an alternate chainring in response to signals from the left controller device.

In some cases, the user may provide a modified set of assignments **312'** where an operation-enacting device **304** does not respond to signals **302b** from any controller device **302**. For instance, with the example roster **310** above, the modified set of assignments **312'** may alternatively provide that: (i) the rear derailleur shifts the chain to a sprocket on the left in response to signals from the left controller device (with no signals from the right controller device); (ii) the rear derailleur shifts the chain to a sprocket on the right in response to signals from the right controller device (with no signals from the left controller device); and (iii) the front derailleur remains idle regardless of what signals are transmitted by the left controller device and/or the right controller device. In general, not every operation by an operation-enacting device **304** must be assigned to an input received by a controller device **302**.

Accordingly, aspects of the present disclosure allow the assignments between the controller devices **302** and the operation-enacting devices **304** to be modified to reconfigure the system **300**. As shown further in FIG. 3, the network coordinator device **306** may include a second wired and/or

wireless communication interface **306b** configured to receive the modified set of assignments **312'**, where the modified set of assignments **312'** causes at least one operation enacted by an operation-enacting device **304** to occur in response to the signals **302b** from a different controller device **302**. The second communication interface **306b** may employ a different protocol than the first communication interface **306a**, particularly if the first communication interface **306a** employs a proprietary protocol.

FIG. 7 illustrates a method of modifying the default or current set of assignments. In act **702**, the network coordinator device **306** receives a modified set of assignments **312'**. In act **704**, the network coordinator device **306** is configured to transmit, via the wireless network **308**, the modified set of assignments **312'** to the operation-enacting devices **304**. Correspondingly, in act **706**, the operation-enacting devices **304** are configured to replace the default or current set of assignments **312** with the modified set of assignments **312'**. In act **708**, the operation-enacting devices **304** are configured to determine how the operation-enacting devices **304** enact operations in response to the signals **302b** according to the modified set of assignments **312'**. If desired, the user can modify the set of assignments again in a similar manner.

According to some embodiments, the second communication interface **306b** is configured to wirelessly couple the network coordinator device **306** to an external computing device **314**, such as a smart phone, computing tablet, laptop, personal computer, or the like. The external computing device **314** may include an application **316**, such as a mobile application or other computer software. The application **316** is configured to receive the modified set of assignments **312'** from a user and to transmit the modified set of assignments **312'** to the network coordinator device **306**.

FIGS. 4A-C illustrate example scenarios **400a-c** that further demonstrate how a modified set of assignments may be implemented in the system **300**. The controller devices **302** paired to the wireless network **308** include a first controller device **402** and a second controller device **403**. The first controller device **402** includes a first input element **402a** configured to receive a first input from the user, where the first input modifies a state of the first input element **402a**. The second controller device **403** includes a second input element **403a** configured to receive a second input from the user, where the second input modifies a state of the second input element **403a**. For instance, the first input element **402a** may be a right shift lever and the second input element **403a** may be a left shift lever. The user can engage either shift lever so that the state of the shift lever can be modified to any of the following: (i) an active state when engaged by the user for less than a threshold amount of time, (ii) an inactive state when not engaged by the user, or (iii) an update state when continuously engaged by the user for at least the threshold amount of time. The signals **302b** from the controller devices **302** include a first signal **402b** from the first controller device **402** and a second signal **403b** from the second controller device **403**, where the first signal **402b** indicates the modified state of the first input element **402a** and the second signal **403b** indicates the modified state of the second input element **403a**. The signals **302b** from a particular controller device **302** may include a device type identification for the particular controller device **302**, an input identifier for the input element **302a** on the particular controller device **302** (in case there is more than one input element **302a**), and information on the modified state for the input element **302a**.

The operation-enacting devices **304** include a first operation-enacting device **404** and a second operation-enacting

device **405**. For instance, the first operation-enacting device **404** may be a front suspension system and the second operation-enacting device **405** may be a rear suspension system. According to a first set of assignments **412** shown in FIG. 4A, the first operation-enacting device **404** is configured to (i) identify the first signal **402b** among the signals **302b** received from the controller devices **302**, (ii) identify the modified state of the first input element **402a**, and (iii) enact a first operation on the bicycle in response to the modified state of the first input element **402a**.

As shown in FIG. 4B, the network coordinator device **306** is configured to (i) receive a second set of assignments **412'**, and (ii) transmit the second set of assignments **412'** to the first operation-enacting device **404** via the wireless network **308**. The first operation-enacting device **404** is configured to receive the second signal **403b** from the second controller device **403** via the wireless network **308**. Responsive to receiving the second set of assignments **412'**, the first operation-enacting device **404** is modified to: (i) identify the modified state of the second input element **403a**, (ii) enact the first operation on the bicycle in response to the modified state of the second input element **403a**, and (iii) remain idle in response to the first signal from the first controller device **402**.

As shown in FIG. 4C, the network coordinator device is configured to (i) receive a third set of assignments **412''**, and (ii) transmit the third set of assignments **412''** to the operation-enacting devices **304** via the wireless network **308**. The second operation-enacting device **405** is configured to receive the first signal **402b** from the first controller device **402** via the wireless network **308**. Responsive to receiving the third set of assignments **412''**, (i) the second operation-enacting device **405** is configured to identify the modified state of the first input element **402a** and to enact a second operation on the bicycle in response to the modified state of the first input element **402a**, and (ii) the first operation-enacting device **404** is modified to remain idle in response to the first signal from the first controller device.

Accordingly, the embodiments described above provide a reconfigurable control system for the components of the bicycle. Despite this desirable feature, the embodiments can secure the control system against such access by unknown devices. In particular, the embodiments initiate a pairing session that allows the user to select controller devices and operation-enacting devices for the wireless network. Once the pairing session is complete, the roster of devices paired to the network is fixed and unchangeable, even though the assignments between the controller devices and the operation-enacting devices already on the network can still be changed by the user. As such, unknown devices cannot join the wireless network and interfere with the control system. Additionally, the embodiments do not allow duplicate device types to be paired to the wireless network, so that an unknown device cannot imitate another device that has been selected to be paired by user. Further, the embodiments only permit each operation enacted by an operation-enacting device to occur in response to the signals from a single assigned controller device or a single assigned combination of controller devices thereby reducing the likelihood of an unwanted response by an operation-enacting device to a signal from an unknown device. Moreover, the embodiments may employ a proprietary network protocol to enhance security by limiting access to the wireless network to devices that can operate under the protocol.

Aspects of the embodiments engage in computer processing, for instance, to receive and transmit wireless signals and to determine how to respond to such signals. For example,

the network coordinator device 306 may include one or more processors 306d configured to execute program instructions stored on computer-readable media 306e, which when executed cause the one or more processors 306d to: (i) establish, via the first communication interface 306c, a pairing session that allows the controller devices 302 and the operation-enacting devices 304 to be paired to a wireless network 308, and (ii) transmit to the operation-enacting devices 304, via the first communication interface 306c, a roster 310 identifying the controller devices 302 and the operation-enacting devices 304 paired to the wireless network 308.

For another example, an operation-enacting device 304 may include one or more processors 304c configured to execute program instructions stored on computer-readable media 304d, the program instructions causing the one or more processors 306d to process the default set of assignments 312 based on the roster 310, where the default set of assignments 312 indicates which of the controller devices 302 is selected to cause the operation-enacting device 304 to respond by modifying the operative state of the bicycle. Additionally, the one or more processors 304c of the operation-enacting devices 304 receives, via the communication interface 304a, a modified set of assignments 312' from the network coordinator device 306, where the modified set of assignments 312' causes the operation-enacting device 304 to modify the operative state of the bicycle in response to the signals 302b from a different one of the controller devices, and the program instructions cause the one or more processors 304c to replace the default or current set of assignments 312 with the modified set of assignments 312'.

The one or more processors 302e, 304c, 306d employed by the embodiments may include a general processor, digital signal processor, an application specific integrated circuit (ASIC), field programmable gate array (FPGA), analog circuit, digital circuit, combinations thereof, or other now known or later developed processor. The processor may be a single device or combinations of devices, such as through shared or parallel processing.

Aspects of the embodiments may also employ computer memory. Such memory may be a volatile memory or a non-volatile memory. The memory may include one or more of a read only memory (ROM), random access memory (RAM), a flash memory, an electronic erasable program read only memory (EEPROM), or other type of memory. The memory may be removable from the corresponding device, such as a secure digital (SD) memory card. Computer memory includes any one or more of a computer-readable medium and other equivalents and successor media, in which data or instructions may be stored. In general, a computer-readable medium includes any medium that is capable of storing, encoding or carrying a set of instructions for execution by a processor or that cause a computer system to perform any one or more of the methods or operations disclosed herein.

To power wireless communications and computer processing, embodiments employ power supplies, which may be stored internal to the operating device, or stored external to the operating device. The power supply may include a combination of multiple batteries or other power providing devices. Specially fitted or configured battery types, or standard battery types such as CR 2012, CR 2016, and/or CR 2032 may be used. In some embodiments, the devices in a system are all individually powered, e.g. by a dedicated battery.

As described above, the embodiments employ communication interfaces. Such communication interfaces are con-

figured to send data such as control signals and/or commands to bicycle components. In particular, the communication interface provides for wireless communications in any now known or later developed format. Although the present specification describes components and functions that may be implemented in particular embodiments with reference to particular standards and protocols, the invention is not limited to such standards and protocols. For example, standards for Internet and other packet switched network transmission (e.g., TCP/IP, UDP/IP, HTML, HTTP, HTTPS) represent examples of the state of the art. Such standards are periodically superseded by faster or more efficient equivalents having essentially the same functions. Accordingly, replacement standards and protocols having the same or similar functions as those disclosed herein are considered equivalents thereof.

It is understood that the illustration or other representation of devices, such as the network coordinator devices, the controller devices, and the operation-enacting devices, include (even if not expressly labeled) any combination of processor(s), memory device(s) (e.g., computer-readable media storing program instructions for execution by processor(s)), communication interface(s), and power supply necessary to achieve the disclosed features.

The illustrations of the embodiments described herein are intended to provide a general understanding of the structure of the various embodiments. The illustrations are not intended to serve as a complete description of all of the elements and features of apparatus and systems that utilize the structures or methods described herein. Many other embodiments may be apparent to those of skill in the art upon reviewing the disclosure. Other embodiments may be utilized and derived from the disclosure, such that structural and logical substitutions and changes may be made without departing from the scope of the disclosure. Additionally, the illustrations are merely representational and may not be drawn to scale. Certain proportions within the illustrations may be exaggerated, while other proportions may be minimized. Accordingly, the disclosure and the figures are to be regarded as illustrative rather than restrictive.

While this specification contains many specifics, these should not be construed as limitations on the scope of the invention or of what may be claimed, but rather as descriptions of features specific to particular embodiments of the invention. Certain features that are described in this specification in the context of separate embodiments can also be implemented in combination in a single embodiment. Conversely, various features that are described in the context of a single embodiment can also be implemented in multiple embodiments separately or in any suitable sub-combination. Moreover, although features may be described above as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination can in some cases be excised from the combination, and the claimed combination may be directed to a sub-combination or variation of a sub-combination.

Although some of the acts and/or functions described in this disclosure have been described as being performed by a particular entity, the acts and/or functions can be performed by any entity, such as those entities described in this disclosure. Further, although the acts and/or functions have been recited in a particular order, the acts and/or functions need not be performed in the order recited. However, in some instances, it can be desired to perform the acts and/or functions in the order recited. Further, each of the acts and/or functions can be performed responsive to one or more of the other acts and/or functions. Also, not all of the acts and/or

functions need to be performed to achieve one or more of the benefits provided by this disclosure, and therefore not all of the acts and/or functions are required

In certain circumstances, multitasking and parallel processing may be advantageous. Moreover, the separation of various system components in the embodiments described above should not be understood as requiring such separation in all embodiments, and it should be understood that any described program components and systems can generally be integrated together in a single software product or packaged into multiple software products.

It is intended that the foregoing detailed description be regarded as illustrative rather than limiting and that it is understood that the following claims including all equivalents are intended to define the scope of the invention. The claims should not be read as limited to the described order or elements unless stated to that effect. Therefore, all embodiments that come within the scope and spirit of the following claims and equivalents thereto are claimed as the invention.

What is claimed is:

1. A system for a bicycle, comprising:
 - a plurality of controller devices, wherein each controller device includes at least one respective input element configured to receive input from a user, and transmits a signal indicating input received by the at least one respective input element of the controller device;
 - a plurality of operation-enacting devices, wherein each operation-enacting device is configured to enact at least one respective operation on the bicycle in response to receiving the signal transmitted from the controller device; and
 - a network coordinator device configured to (i) establish a pairing session to pair the network coordinator device, the controller devices, and the operation-enacting devices to a wireless network that enables communication between the network coordinator device, the controller devices and the operation-enacting devices, and (ii) reset the controller devices and operation-enacting device before pairing the controller devices and operation-enacting devices to the wireless network.
2. The system of claim 1, wherein the network coordinator device is configured to transmit to the operation-enacting devices, via the wireless network, a roster identifying the controller devices and the operation-enacting devices paired to the wireless network.
3. The system of claim 2, wherein the operation-enacting devices are configured to determine, based on the roster received from the network coordinator device, how to enact the operations responsive to the signals received from the controller devices.
4. The system of claim 2, wherein the network coordinator device is configured to not add additional controller devices or additional operation-enacting devices to the roster after the pairing session has ended.
5. The system of claim 2, wherein the network coordinator device is configured to not change the roster when a paired controller device or a paired operation-enacting device is paired to another wireless network.
6. The system of claim 2, wherein the network coordinator device is configured to (i) establish a new pairing session to reset the roster and enable communications between the network coordinator and a different set of controller devices and operation-enacting devices via a new wireless network, and (ii) transmit to the operation-enacting devices, via the new wireless network, a new roster identifying the different

set of controller devices and operation-enacting devices paired to the new wireless network.

7. The system of claim 1, wherein each of the operation-enacting devices comprises at least one movable component including at least one of: (i) a front derailleur configured to modify a position of a bicycle chain relative to a set of front gears, (ii) a rear derailleur configured to modify a position of the bicycle chain relative to a set of rear gears, or (iii) a seat post assembly configured to modify a position of a seat relative to a frame of the bicycle.

8. The system of claim 1, wherein the network coordinator is a rear derailleur.

9. A network coordinator device for a bicycle, comprising: a first communication interface configured to communicate wirelessly with a plurality of controller devices and a plurality of operation-enacting devices, each controller device including at least one respective input element configured to receive input from a user and transmit a signal indicating input received by the at least one respective input element, and each operation-enacting device being configured to enact at least one respective operation on the bicycle in response to receiving the signal transmitted from the controller device; and

one or more processors configured to execute program instructions stored on computer-readable media, which when executed cause the one or more processors to: establish, via the first communication interface, a pairing session that allows the controller devices and the operation-enacting devices to be paired to a wireless network, and reset, via the first communication interface, the controller devices and operation-enacting device before pairing the controller devices and operation-enacting devices to the wireless network.

10. The network coordinator device of claim 9, wherein the one or more processes are configured to transmit to the operation-enacting devices, via the first communication interface, a roster identifying the controller devices and the operation-enacting devices paired to the wireless network, wherein the wireless network allows the controller devices to transmit, to the operation-enacting devices, the signals indicating input received by the input elements of the controller devices and causing the operation-enacting devices to enact the operations based on the roster.

11. The network coordinator device of claim 10, wherein the one or more processes are configured to (i) establish a new pairing session to reset the roster and enable communications between the network coordinator and a different set of controller devices and operation-enacting devices via a new wireless network, and (ii) transmit to the operation-enacting devices, via the new wireless network, a new roster identifying the different set of controller devices and operation-enacting devices paired to the new wireless network.

12. The network coordinator device of claim 10, wherein the one or more processes are configured to not add additional controller devices or additional operation-enacting devices to the roster after the pairing session has ended.

13. The network coordinator device of claim 10, wherein the one or more processes are configured to not change the roster when a paired controller device or a paired operation-enacting device is paired to another wireless network.

14. The network coordinator device of claim 9, wherein each of the operation-enacting devices comprises at least one movable component including at least one of: (i) a front derailleur configured to modify a position of a bicycle chain relative to a set of front gears, (ii) a rear derailleur configured

to modify a position of the bicycle chain relative to a set of rear gears, or (iii) a seat post assembly configured to modify a position of a seat relative to a frame of the bicycle.

15. The network coordinator device of claim 9, wherein the network coordinator device is a rear derailleur.

5

* * * * *